

# CrystalICL: Enabling In-Context Learning for Crystal Generation

Anonymous ACL submission

## Abstract

Designing crystal materials with desired physicochemical properties remains a fundamental challenge in materials science. While large language models (LLMs) have demonstrated strong in-context learning (ICL) capabilities, existing LLM-based crystal generation approaches are limited to zero-shot scenarios and are unable to benefit from few-shot scenarios. In contrast, human experts typically design new materials by modifying relevant known structures which aligns closely with the few-shot ICL paradigm. Motivated by this, we propose CrystalICL, a novel model designed for few-shot crystal generation. Specifically, we introduce a space-group based crystal tokenization method, which effectively reduces the complexity of modeling crystal symmetry in LLMs. We further introduce a condition-structure aware hybrid instruction tuning framework and a multi-task instruction tuning strategy, enabling the model to better exploit ICL by capturing structure–property relationships from limited data. Extensive experiments on four crystal generation benchmarks demonstrate the superiority of CrystalICL over the leading baseline methods on conditional and unconditional generation tasks.

## 1 Introduction

The design and discovery of crystal materials with specific physicochemical properties have remained a long-standing issue in the field of materials design. The development of novel crystal materials plays a crucial role in advancing technologies such as batteries, semiconductors, and catalysis (Butler et al., 2018; Desiraju, 2002). While traditional methods based on Density Functional Theory (DFT) (Kohn and Sham, 1965) have proven effective, they are often computationally expensive and time-consuming. In contrast, deep learning techniques (Xie et al., 2022; Jiao et al., 2023, 2024; Antunes et al., 2024; Gruver et al., 2024) have




Figure 1: The conditional crystal generation performance of GPT-3.5 Turbo and CrystalLLM on P5.

emerged as a powerful alternative, enabling the efficient prediction of potentially stable crystal material structures and significantly accelerating the discovery process.

In recent years, the successful adaptation of LLMs in drug discovery (Zheng et al., 2024) and protein structure prediction (Lin et al., 2023) has inspired growing interest in leveraging pretrained LLMs for crystal generation tasks. Among these efforts, CrystalLLM (Gruver et al., 2024), which is fine-tuned on Llama-2 (Touvron et al., 2023), has demonstrated competitive performance in crystal generation. However, it does not fully inherit the in-context learning (ICL) capabilities of LLMs. These capabilities are essential for emulating the expert-driven workflow in material discovery.

Specifically, human experts typically begin with a small set of known materials that share similar properties and modify their composition or structure to achieve new design objectives. This process closely mirrors the few-shot in-context learning paradigm, where models generate new structures by referencing a limited number of relevant examples. To verify this limitation, we compare GPT-3.5 Turbo and CrystalLLM on the P5 (Castelli et al., 2012) dataset under 0-shot and 3-shot prompts. As shown in Fig. 1, GPT-3.5 struggles in the 0-shot setting but improves markedly with 3-shot prompts, demonstrating strong ICL behavior. In contrast, CrystalLLM performs worse in the 3-shot setting than in 0-shot setting, indicating its limited ability to benefit from in-context examples.

Motivated by these limitations, we aim to bridge the gap in applying ICL to crystal generation by proposing CrystalICL—the first crystal generation model explicitly designed to inherit and leverage the ICL-driven generalization capabilities of LLMs. To this end, we first introduce **Space-group based Crystal Tokenization** (SGS), a novel method that transforms 3D crystal structures into 1D text. Compared with traditional XYZ-format crystal structure text (Flam-Shepherd and Aspuru-Guzik, 2023), SGS significantly improves LLMs’ ability to capture and model crystal symmetry. Next, we present the **Condition-Structure Aware Hybrid Crystal Instruction Tuning** framework, which incorporates three selection strategies to identify the most relevant crystal examples for downstream tasks. This framework effectively improves the model’s few-shot generation capability by allowing it to take advantage of informative contextual examples. Finally, to explicitly guide the model in learning the correspondence between crystal structures and their properties, we introduce the **Multi-Task Crystal Instruction Tuning** strategy. This approach integrates crystal property prediction instructions into the fine-tuning process, further enhancing the model’s ability to capture structure-property relationships and improving performance in crystal generation tasks. Our main **contributions** are summarized as follows:

- ★ We explore the underutilized in-context learning (ICL) capability of LLMs for crystal generation and introduce CrystalICL, the first approach to leverage LLMs’ few-shot reasoning abilities for material design, enabling efficient and adaptable crystal generation.
- ★ To achieve this, we propose a tailored crystal tokenization strategy and structure-aware instruction tuning mechanisms, incorporating template-based and multitask learning to collectively enhance CrystalICL’s ICL reasoning capabilities.
- ★ Experimental results on four publicly available datasets across diverse domains and scales demonstrate the effectiveness of CrystalICL in both zero-shot and few-shot learning scenarios.

## 2 Preliminary

### 2.1 Crystal Generation

The crystal structure is characterized by the geometry of the arrangement of particles within the unit cells. A unit cell is defined as the smallest repeating unit that preserves the full symmetry of the crystal

structure. Given a unit cell containing  $N$  atoms, it can be described by the triplet  $\mathcal{M} = (\mathbf{A}, \mathbf{X}, \mathbf{L})$ , where  $\mathbf{A} = [\mathbf{a}_1, \mathbf{a}_2, \dots, \mathbf{a}_N]^T \in \mathbb{R}^{N \times K}$  represents a list of atomic types in one-hot encoding format ( $K$  is the number of possible atomic types),  $\mathbf{X} = [\mathbf{x}_1, \mathbf{x}_2, \dots, \mathbf{x}_N]^T \in \mathbb{R}^{N \times 3}$  contains the Cartesian coordinates of the atoms, and  $\mathbf{L} = [\mathbf{l}_1, \mathbf{l}_2, \mathbf{l}_3]^T \in \mathbb{R}^{3 \times 3}$  is the lattice matrix that describes the periodicity of the crystal. The infinite periodic crystal structure is represented as follows:

$$\{(\mathbf{a}'_i, \mathbf{x}'_i) | \mathbf{a}'_i = \mathbf{a}_i, \mathbf{x}'_i = \mathbf{x}_i + \mathbf{kL}, \forall \mathbf{k} \in \mathbb{Z}^{1 \times 3}\}, \quad (1)$$

where the elements of the integer vector  $\mathbf{k}$  represent integral 3D translations along their corresponding lattice directions in  $\mathbf{L}$ .

In order to reflect the periodicity of the crystal structure, it is convenient to use the lattice vectors  $(\mathbf{l}_1, \mathbf{l}_2, \mathbf{l}_3)$  to replace the standard orthogonal Cartesian basis. In this case, the Cartesian coordinates  $\mathbf{x} = \sum_{i=1}^3 f_i \mathbf{l}_i$  can be replaced by the fractional coordinate vector  $\mathbf{f} = [f_1, f_2, f_3] \in [0, 1)^3$ . In this work, we adopt the fractional coordinate system and describe the crystal as  $\mathcal{M} = (\mathbf{A}, \mathbf{F}, \mathbf{L})$ , where the matrix  $\mathbf{F} \in [0, 1)^{N \times 3}$  contains the fractional coordinates of all atoms in the unit cell. This work focuses on two primary tasks:

**Conditional Crystal Generation:** Given a dataset  $\{(\mathcal{M}_j, s_j)\}_{j=1}^n$ , where  $s_j$  denotes a specific property of  $\mathcal{M}_j$ , our goal is to develop a conditional generative model  $p_\theta(\cdot | s)$  that generates 3D crystal structures with the specified property  $s$ .

**Unconditional Crystal Generation:** Given a dataset  $\{\mathcal{M}_j\}_{j=1}^n$ , our goal is to develop an unconditional generative model  $p_\theta(\cdot)$  that can generate a collection of crystals with a distribution similar to the training set.

### 2.2 Crystal Instruction Tuning

Given a set of  $n$  crystal materials  $D = \{(\mathcal{M}_j, s_j)\}_{j=1}^n$ , the goal of crystal instruction tuning is to fine-tune the LLM  $f_\theta$  by fitting the training instruction set  $S_D$  constructed from  $D$  as a collection of (input, output) pairs. The fine-tuned model is then expected to generate crystals with specific properties  $s$  (conditional generation) and generate new crystal structures similar to those in the training set (unconditional generation).

## 3 Method

In this section, we introduce the proposed CrystalICL, as illustrated in Fig. 2. First, we discuss




Figure 2: The illustration of our proposed CrystalICL. CrystalICL begins by using a space-group based crystal tokenization method to transform 3D crystal structures into a text format suitable for input into LLMs. Secondly, CrystalICL constructs a condition-structure aware hybrid crystal instruction set, which includes both zero-shot and few-shot instructions. The few-shot instructions combine various example selection strategies, which query the K most relevant demonstrations for prompt design tailored to crystal generation tasks. Finally, CrystalICL incorporates a crystal property prediction instruction set, which combines with the crystal generation instruction set to form a multi-task crystal instruction set.




Figure 3: Comparison of three methods (CIF, XYZ, SGS(ours)) for converting crystal structures to text.

a space-group based crystal tokenization method designed to reduce the complexity of modeling crystal symmetry within LLMs (in Sec. 3.1). Next, we elaborate on a condition-structure aware hybrid crystal instruction tuning framework, which effectively enhances the ICL capabilities of LLMs for crystal generation tasks (in Sec. 3.2). Finally, we introduced a multi-task crystal instruction tuning strategy, which strengthens the model’s ability to capture the relationship between crystal structures and their properties (in Sec. 3.3).

### 3.1 Space-group based Crystal Tokenization

To address the challenge of converting complex unit cell structures into text formats suitable for language models, we propose a novel space-group based crystal tokenization method (SGS) that reduces the complexity of crystal symmetry modeling for LLMs. Existing formats, such as CIF (Hall

et al., 1991) and XYZ (Flam-Shepherd and Aspuru-Guzik, 2023), exhibit notable limitations: CIF files, as highly formatted documents, include complex structures and a large number of specialized tokens thereby increasing the complexity of fine-tuning LLMs. Meanwhile, the XYZ format represents the fractional coordinates of all atoms within the unit cell, requiring the model to implicitly learn intricate symmetry relationships among atomic positions without structural guidance. Therefore, these limitations exacerbate the difficulty of crystal generation tasks and hinder model performance.

Our method simplifies the crystal structure text by leveraging the concept of Wyckoff positions (LIPSON, 1949) in crystallography. A Wyckoff position is defined as a set of points whose site symmetry groups are all conjugate subgroups of one another. The space group uniquely determines the types of Wyckoff positions present in a crystal. Therefore, given the space group, atoms of the same element occupying the same Wyckoff position can be represented by a single atom. This decomposes the task of predicting the fractional 3D coordinates of all atoms in the unit cell into two components: modeling the correspondence between the space group and Wyckoff positions, and predicting the Wyckoff positions of atoms within the unit cell.

Specifically, our space-group based crystal structure text consists of three components: the space group symbol, the lattice parameters, and the element symbols and fractional coordinates for atoms

at each Wyckoff position. An example of crystal string formatting is shown in Fig. 3. By replacing multiple atoms sharing the same Wyckoff position with a single representative atom, our method reduces the number of atomic coordinates that need to be generated and eliminates the need to enforce strict symmetry constraints during the atomic coordinate generation process, thereby lowering the difficulty of modeling crystallographic symmetry. This transformation simplifies the modeling of crystal symmetry, enabling LLMs to focus on key structural features, thereby reducing the complexity of the generation task and improving generation performance.

### 3.2 Condition-Structure Aware Hybrid Crystal Instruction Tuning

Following the crystal tokenization process, the subsequent step is to construct an instruction tuning set  $S_D$  for the crystal generation tasks. The tuning set consists of two components: the zero-shot instruction tuning set  $S_{D_z}$  and the few-shot instruction tuning set  $S_{D_f}$ . In accordance with the standard protocol for instruction fine-tuning (Gruver et al., 2024; Zhang et al., 2023), the zero-shot crystal generation instruction set  $S_{D_z}$  can be constructed from the given dataset  $D$  using the following prompt template  $T_z = \{Q, R\}$ , where  $Q$  represents the query and  $R$  denotes the response, providing the necessary contextual information for the task.:

```
### Instruction: Below is a description
→ of a bulk material. [Condition
→ Description]. Generate the space
→ group symbol, a description of the
→ lengths and angles of the lattice
→ vectors and then the element type
→ and coordinates for each atom within
→ the lattice:
### Response: [Crystal String].
```

We have shown how instruction fine-tuning can guide LLMs in zero-shot crystal generation tasks. However, the lack of contextual learning in zero-shot settings prevents the model from fully leveraging its powerful ICL capabilities, thus limiting its potential in crystal generation. To address this limitation, we propose a few-shot instruction design method that incorporates crystal structures from the target generation domain into the prompt. The key idea is to use a small set of target-domain crystal structures as demonstrations to guide the model

in generating similar crystal structures, thereby enhancing its conditional generation capabilities.

To achieve this, given a set of crystal properties  $S = \{s_1, s_2, \dots, s_n\}$  serving as generation conditions, we explore three different strategies for selecting  $K$  representative crystals:

**Condition-based selection.** The first strategy filters the dataset based on the specified properties, ensuring that the selected crystals meet the given generation conditions  $S$ . For chemical formula, anonymized representations (e.g., expressing  $\text{CaTiO}_3$  as  $\text{ABC}_3$ ) are used to generalize composition-based filtering. For discrete properties such as space group, crystals are selected by exact property matching. For continuous properties like band gap, we rank the crystals in ascending order of the absolute difference between their property values and the target condition, selecting those closest to the desired value.

**Structure-based selection.** In contrast, this strategy does not rely on explicit property constraints but instead retrieves structurally similar crystals from the dataset. A crystal is randomly chosen as an anchor crystal, and the CrystalNN fingerprint (Zimmermann and Jain, 2020) is computed for all other crystals. The top  $K - 1$  crystals with the smallest euclidean distance to the anchor crystal are then selected, ensuring that structurally similar  $K$  crystals serve as few-shot examples.

**Condition-Structure based selection.** To balance property consistency and structural similarity, this strategy combines the strengths of both approaches. We first filter the dataset to obtain crystals that meet the specified conditions and randomly select a crystal as anchor. Then, we retrieve the  $K - 1$  crystals with the highest structural similarity to the anchor based on euclidean distance in the CrystalNN fingerprint space. The final few-shot example set consists of the anchor crystal and its  $K - 1$  nearest neighbors, facilitating both property-conditioned and structure-aware generation.

By integrating the above three selection strategies, we construct the few-shot example set and extend the zero-shot instruction template to obtain the few-shot template  $T_f$ :

```
### Instruction: Below is three
→ description of bulk materials.
### First Example:
### [Condition Description-1]
### [Crys Str-1]
### ...
```

### [Condition Description]. Based on  
 → the three examples provided,  
 → generate the space group symbol, a  
 → description of the lengths and  
 → angles of the lattice vectors, along  
 → with the element type and  
 → coordinates for each atom within the  
 → lattice:  
 ### Response: [Crystal String].

Given the constructed condition-structure aware instruction template  $T_f$ , the few-shot crystal generation instruction set  $S_{D_f}$  can be generated by applying  $T_f$  to each sample in  $D$ . The fine-tuning instruction set  $S_D$  is obtained by combining the zero-shot instruction set  $S_{D_z}$  with the few-shot instruction set  $S_{D_f}$ . The pre-trained LLM can then be fine-tuned by optimizing the following training loss:

$$\mathcal{L}(\theta) = \sum_{(Q_i, R_i) \in S_D} -\log f_{\theta}(R_i|Q_i), \quad (2)$$

where  $f_{\theta}$  represents the pre-trained LLM parameterized by  $\theta$ . In practice,  $f_{\theta}$  is initialized using Llama2-7b-chat, and LoRA (Hu et al., 2022) is employed to accelerate the training process. Further details can be found in Appendix E.

### 3.3 Multi-Task Crystal Instruction Tuning: Property Prediction Auxiliary Task

In the previous section, we introduce a condition-structure aware hybrid crystal instruction tuning framework that enhances ICL ability by integrating hybrid example selection methods. However, the model still lacks explicit supervision for learning the intrinsic mapping between crystal structures and their physicochemical properties, which is critical for generating accurate and meaningful crystals. To address this limitation, we propose a multi-task crystal instruction tuning strategy that incorporates the property prediction auxiliary task. In addition to the primary crystal generation task, this auxiliary task trains the model to predict key crystal properties based on the crystal structure text. We define the property prediction template  $T_p$  as follows:

### Instruction: Below is a partial  
 → description of a bulk material where  
 → the [Property] has been replaced  
 → with the string "[MASK]":  
 ### The [Property] is [MASK].  
 ### [Crys Str]

### Generate the [Property] that could  
 → replace [MASK] in the bulk material:  
 ### Response: [Property Value].

By jointly optimizing both crystal generation and property prediction tasks, the model learns to internalize structural patterns and their corresponding physical attributes, improving both generation accuracy and property consistency.

## 4 Experiment

In our experiments, we aim to address five key research questions: **RQ1**: Can CrystalICL effectively inherit the ICL capabilities of LLMs and leverage limited examples in the prompt to improve performance in the conditional crystal generation task? **RQ2**: Can CrystalICL effectively utilize its ICL capabilities to achieve cross-domain conditional generation? **RQ3**: How does CrystalICL perform in the unconditional crystal generation task compared to existing baselines? **RQ4**: How do different types of instructions in the tuning set affect CrystalICL’s ICL ability? **RQ5**: How do different example selection strategies during inference affect the performance of CrystalICL?

### 4.1 Experimental Setup

**Datasets.** We evaluate the conditional generation task on four crystal generation datasets: MP20 (Jain et al., 2013), MP30 (Gruver et al., 2024), P5 (Castelli et al., 2012), and C24 (Pickard, 2020). For the unconditional generation task, following the previous work (Xie et al., 2022; Jiao et al., 2023), we evaluate on MP20, P5, and C24. Detailed dataset information is provided in Appendix B. For the conditional generation task, we employ the Success Rate as the evaluation metric. For the unconditional generation task, we evaluate performance across three key aspects: Validity, Coverage and Property Distribution. Further details can be found in Appendix C.

**Baselines.** For the conditional crystal generation task, we use CrystalLLM (Gruver et al., 2024) as the baseline model. For the unconditional crystal generation task, we select CDVAE (Xie et al., 2022), DiffCSP (Jiao et al., 2023), and CrystalLLM as the baseline models.

### 4.2 Conditional Generation Evaluation

To address RQ1, we conduct evaluations of conditional generation task across four datasets. Specifically, we select the properties of crystals from the

| Dataset | Method                  | Success Rate   |        |               |        |                  |        |               |        |
|---------|-------------------------|----------------|--------|---------------|--------|------------------|--------|---------------|--------|
|         |                         | Pretty Formula |        | Space Group   |        | Formation Energy |        | Band Gap      |        |
|         |                         | Mean           | Std.   | Mean          | Std.   | Mean             | Std.   | Mean          | Std.   |
| MP20    | CrystalLLM (XYZ)        | 0.9394         | 0.0099 | 0.0640        | 0.0078 | 0.8475           | 0.0169 | 0.6637        | 0.0129 |
|         | CrystalICL (XYZ) 0-Shot | 0.9578         | 0.0067 | 0.0868        | 0.0098 | 0.8751           | 0.0048 | 0.6655        | 0.0233 |
|         | CrystalICL (XYZ) 3-Shot | <b>0.9906</b>  | 0.0050 | <b>0.0886</b> | 0.0151 | <b>0.9125</b>    | 0.0072 | <b>0.7087</b> | 0.0165 |
|         | CrystalLLM (SGS)        | 0.4513         | 0.0218 | 0.8726        | 0.0097 | 0.7984           | 0.0144 | 0.6373        | 0.0159 |
|         | CrystalICL (SGS) 0-Shot | 0.7218         | 0.0135 | 0.9881        | 0.0050 | 0.9049           | 0.0170 | 0.7023        | 0.0146 |
|         | CrystalICL (SGS) 3-Shot | <b>0.8868</b>  | 0.0077 | <b>0.9908</b> | 0.0033 | <b>0.9392</b>    | 0.0094 | <b>0.7453</b> | 0.0263 |
| MP30    | CrystalLLM (XYZ)        | 0.9699         | 0.0019 | 0.0799        | 0.0087 | 0.8297           | 0.0091 | 0.6732        | 0.0211 |
|         | CrystalICL (XYZ) 0-Shot | 0.9536         | 0.0066 | 0.0926        | 0.0158 | 0.8485           | 0.0093 | 0.6767        | 0.0273 |
|         | CrystalICL (XYZ) 3-Shot | <b>0.9922</b>  | 0.0028 | <b>0.1083</b> | 0.0089 | <b>0.9461</b>    | 0.0056 | <b>0.7454</b> | 0.0139 |
|         | CrystalLLM (SGS)        | 0.5008         | 0.0253 | 0.9006        | 0.0098 | 0.8030           | 0.0177 | 0.6687        | 0.0220 |
|         | CrystalICL (SGS) 0-Shot | 0.7162         | 0.0118 | 0.9827        | 0.0052 | 0.8642           | 0.0143 | 0.6782        | 0.0053 |
|         | CrystalICL (SGS) 3-Shot | <b>0.9641</b>  | 0.0075 | <b>0.9956</b> | 0.0028 | <b>0.9789</b>    | 0.0043 | <b>0.7943</b> | 0.0098 |

Table 1: The conditional sample performance on MP20 and MP30.




Figure 4: The conditional sample performance on P5 and C24.

test set as generation conditions, and use examples from the training set as demonstrations in the few-shot prompt. Further details can be found in Appendix C. Each fine-tuned model is evaluated through five iterations of 1,000-sample testing, and Tab. 1 and Fig. 4 summarize the mean performance metrics along with their standard deviation across these iterations. Based on the experimental results, we summarize two key conclusions:

**CrystalICL is effective and reliable.** As shown in Tab. 1 and Fig. 4, CrystalICL exhibits superior performance in conditional crystal generation task across various crystal structure text formats and datasets of different domains and scales. In contrast to CrystalLLM, which experiences a significant performance drop in zero-shot scenarios for chemical formula generation using SGS-format crystal structure text, our CrystalICL shows a smaller decline, demonstrating its robustness across different formats of crystal structure text. Furthermore, CrystalICL shows a marked improvement in performance in few-shot scenarios compared to zero-shot scenarios, effectively validating its successful inheritance of the ICL capabilities of LLMs.

**SGS proves to be an effective method for crystal tokenization.** The results indicate that, compared to XYZ-format crystal structure text, SGS significantly enhances LLMs’ ability to generate

crystals conditioned on the space group, while performance for chemical-formula based tasks is slightly reduced. This highlights the effectiveness of our space-group based crystal tokenization method in simplifying the complexity of modeling crystal symmetry. Furthermore, on both the MP20 and MP30 datasets, the SGS-based approach outperforms in crystal physicochemical property conditioned generation tasks, demonstrating the importance of crystal symmetry in modeling the relationship between crystal structures and their properties. Additionally, the use of XYZ-format crystal structure text results in notably poor performance in space-group conditioned generation across multiple datasets, supporting our view raised in Sec. 3.1 that including the 3D coordinates of all atoms in the crystal structure text exacerbates the challenge of modeling crystal symmetry in LLMs.

### 4.3 Cross-domain Conditional Generation Evaluation

To address RQ2, we design a cross-domain conditional generation scenario for evaluation. The model is trained on the MP20 dataset, while testing is conducted on randomly selected crystals from the test sets of P5 and C24, using their properties as generation conditions.

**With the use of SGS, CrystalICL effectively leverages its ICL capabilities to achieve cross-domain conditional generation.** As shown in Fig. 5, the performance of the cross-domain conditional generation task experiences a significant decline when compared to the domain-specific conditional generation task shown in Fig. 4. This is primarily due to the considerable differences between the MP20, P5, and C24 datasets. Specifically, all crystals in the P5 dataset share the same chem-




Figure 5: The cross-domain conditional generation performance on P5 and C24.

ical formula  $ABX_3$ , and only four space groups are involved. In the C24 dataset, all crystals consist solely of carbon atoms. Moreover, most of the crystals in P5 and C24 do not exist in reality, making it challenging to transfer knowledge from the MP20 dataset to these datasets. However, it is encouraging to observe that when using SGS-format crystal structure text, CrystalICL demonstrates remarkable cross-domain performance in space-group conditioned generation, with almost no performance degradation compared to domain-specific conditional generation task. Additionally, when compared to CrystallLLM, CrystalICL exhibits a smaller performance decline in the chemical-formula conditioned generation task, showcasing its stronger generalization ability.

#### 4.4 Unconditional Generation Evaluation

To answer RQ3, we use the unconditional generation prompt to sample 10,000 structures from each fine-tuned model and attempt to parse them into CIF files based on the generated samples. If a sampled string cannot be parsed as a valid CIF, the sample is rejected and re-sampled.

**CrystalICL demonstrates a superior ability to capture the relationship between crystal structures and their properties.** As shown in Tab. 2, we evaluate the performance of unconditional crystal generation task across multiple datasets. The results indicate that, compared to CrystallLLM, CrystalICL generates crystal structures whose property distributions exhibit a much closer alignment with those in the training sets across all three datasets. This demonstrates the effectiveness of CrystalICL in learning both crystal structure and property distributions. It also validates the impact of incorporating few-shot crystal generation instructions into the instruction tuning set for modeling crystal distributions. Additionally, SGS-format crystal structure text reduce the distributional differences in density and formation energy across all three datasets, demonstrating the effectiveness of SGS in model-

| Dataset          | Method           | Validity Check $\uparrow$ |            |        | Coverage $\uparrow$ |           | Property Distribution $\downarrow$ |            |                 |
|------------------|------------------|---------------------------|------------|--------|---------------------|-----------|------------------------------------|------------|-----------------|
|                  |                  | Composition               | Structural | Valid  | Recall              | Precision | $wdist(\mu)$                       | $wdist(E)$ | $wdist(N_{II})$ |
| MP20             | CDVAE            | 0.8514                    | 0.9999     | 0.8514 | 0.9896              | 0.9946    | 0.6445                             | 0.2617     | 1.1567          |
|                  | DiffCSP          | 0.8182                    | 0.9983     | 0.8172 | 0.9957              | 0.9967    | 0.1907                             | 0.1394     | 0.5703          |
|                  | CrystallLLM(XYZ) | 0.9019                    | 0.9630     | 0.8697 | 0.9839              | 0.9931    | 1.3315                             | 0.4503     | 0.1811          |
|                  | CrystallICL(XYZ) | 0.8922                    | 0.9792     | 0.8747 | 0.9840              | 0.9949    | 1.2175                             | 0.3818     | 0.1756          |
|                  | CrystallLLM(SGS) | 0.8433                    | 0.9570     | 0.8144 | 0.9944              | 0.9847    | 0.8356                             | 0.3544     | 0.1743          |
| CrystallICL(SGS) | 0.8655           | 0.9859                    | 0.8555     | 0.9949 | 0.9926              | 0.6039    | 0.2568                             | 0.1359     |                 |
| P5               | CDVAE            | 0.9841                    | 1.0000     | 0.9841 | 0.9897              | 0.9852    | 0.0664                             | 0.0474     | 0.1350          |
|                  | DiffCSP          | 0.9848                    | 0.9999     | 0.9845 | 0.9947              | 0.9820    | 0.0462                             | 0.0532     | 0.0301          |
|                  | CrystallLLM(XYZ) | 0.9896                    | 1.0000     | 0.9896 | 0.9915              | 0.9856    | 0.1755                             | 0.0448     | 0.0196          |
|                  | CrystallICL(XYZ) | 0.9940                    | 1.0000     | 0.9940 | 0.9905              | 0.9898    | 0.2269                             | 0.0284     | 0.0200          |
|                  | CrystallLLM(SGS) | 0.9895                    | 1.0000     | 0.9895 | 0.9918              | 0.9880    | 0.1443                             | 0.0155     | 0.0333          |
| CrystallICL(SGS) | 0.9916           | 1.0000                    | 0.9916     | 0.9908 | 0.9872              | 0.1692    | 0.0089                             | 0.0644     |                 |
| C24              | CDVAE            | 1.0000                    | 1.0000     | 1.0000 | 0.9990              | 0.8416    | 0.1497                             | 0.2206     | -               |
|                  | DiffCSP          | 1.0000                    | 1.0000     | 1.0000 | 0.9990              | 0.9642    | 0.0548                             | 0.0415     | -               |
|                  | CrystallLLM(XYZ) | 1.0000                    | 0.8893     | 0.8893 | 0.2182              | 0.0005    | 0.0691                             | 30.8053    | -               |
|                  | CrystallICL(XYZ) | 1.0000                    | 0.9282     | 0.9282 | 0.5458              | 0.0052    | 0.0395                             | 29.4212    | -               |
|                  | CrystallLLM(SGS) | 1.0000                    | 0.9574     | 0.9574 | 0.9916              | 0.7965    | 0.0707                             | 3.0564     | -               |
| CrystallICL(SGS) | 1.0000           | 0.9669                    | 0.9669     | 0.9921 | 0.8928              | 0.0593    | 1.3061                             | -          |                 |

Table 2: The unconditional sample performance.

ing the relationship between crystal structures and properties. Particularly, for the C24 dataset, which consists entirely of carbon-based materials, SGS significantly alleviates the difficulty for LLMs in modeling crystal structure distributions, leading to a substantial improvement in precision and recall on this dataset.

#### 4.5 Effect of Instruction Types in the Tuning Set

To investigate RQ4, we conduct an ablation study to analyze how different instruction types affect conditional crystal generation performance. Specifically, to better align with real-world ICL scenarios, we train on the MP20 and select demonstrations from the MP30 (an extension of MP20), examining the influence of various instruction types on performance during the training process, with the results presented in Tab. 3. In this study, C, F, and CF correspond to the three demonstration selection strategies introduced in Sec. 3.2, Rand represents the random selection strategy, and noAux refers to the removal of the property prediction auxiliary instruction set described in Sec. 3.3.

**Hybrid instruction tuning effectively enhances the capabilities of CrystalICL across various scenarios.** Experimental results indicate that variants using a single example selection strategy during fine-tuning, such as F, CF, and C, show poorer performance in zero-shot scenarios. However, in the few-shot setting, the performance remains consistent with that in the zero-shot scenario, demonstrating that randomly example selection strategy leads to failing to derive task-relevant information from the demonstrations, thus losing ICL capability. Additionally, removing the property prediction instructions from the tuning set results in a decline in zero-shot performance, highlighting the importance of explicitly designing instructions to guide the model in learning the relationship between crystal structures and their properties.

| Scenario | Method     | Success Rate   |        |             |        |                  |        |          |        |
|----------|------------|----------------|--------|-------------|--------|------------------|--------|----------|--------|
|          |            | Pretty Formula |        | Space Group |        | Formation Energy |        | Band Gap |        |
|          |            | Mean           | Std.   | Mean        | Std.   | Mean             | Std.   | Mean     | Std.   |
| 0-Shot   | Rand       | 0.7364         | 0.0135 | 0.9916      | 0.0026 | 0.9082           | 0.0147 | 0.7006   | 0.0247 |
|          | F          | 0.2966         | 0.0039 | 0.6446      | 0.0169 | 0.8039           | 0.0170 | 0.6239   | 0.0149 |
|          | CF         | 0.6854         | 0.0081 | 0.9850      | 0.0039 | 0.8836           | 0.0186 | 0.7077   | 0.0126 |
|          | C          | 0.6620         | 0.0180 | 0.9788      | 0.0035 | 0.8917           | 0.0082 | 0.6941   | 0.0213 |
|          | noAux      | 0.4167         | 0.0227 | 0.3740      | 0.0178 | 0.8370           | 0.0047 | 0.6742   | 0.0156 |
|          | CrystalICL | 0.7390         | 0.0313 | 0.9904      | 0.0040 | 0.9104           | 0.0084 | 0.7017   | 0.0218 |
| 3-Shot   | Rand       | 0.7430         | 0.0140 | 0.9883      | 0.0023 | 0.9083           | 0.0103 | 0.6982   | 0.0180 |
|          | F          | 0.5425         | 0.0146 | 0.8436      | 0.0154 | 0.8144           | 0.0105 | 0.6473   | 0.0145 |
|          | CF         | 0.4878         | 0.0062 | 0.3681      | 0.0202 | 0.8528           | 0.0115 | 0.6991   | 0.0156 |
|          | C          | 0.9340         | 0.0075 | 0.9954      | 0.0016 | 0.9669           | 0.0073 | 0.7789   | 0.0214 |
|          | noAux      | 0.9347         | 0.0078 | 0.9959      | 0.0010 | 0.9647           | 0.0090 | 0.7765   | 0.0253 |
|          | CrystalICL | 0.9214         | 0.0104 | 0.9948      | 0.0033 | 0.9685           | 0.0087 | 0.7687   | 0.0146 |

Table 3: Impact of different instruction types in the 3-Shot Setting.

| Method | Success Rate   |        |             |        |                  |        |          |        |
|--------|----------------|--------|-------------|--------|------------------|--------|----------|--------|
|        | Pretty Formula |        | Space Group |        | Formation Energy |        | Band Gap |        |
|        | Mean           | Std.   | Mean        | Std.   | Mean             | Std.   | Mean     | Std.   |
| FR     | 0.7284         | 0.0131 | 0.9807      | 0.0041 | 0.9064           | 0.0079 | 0.6957   | 0.0173 |
| F      | 0.7273         | 0.0116 | 0.9846      | 0.0014 | 0.9020           | 0.0061 | 0.6981   | 0.0246 |
| R      | 0.7441         | 0.0147 | 0.9871      | 0.0046 | 0.9107           | 0.0094 | 0.7120   | 0.0167 |
| CFR    | 0.8417         | 0.0057 | 0.9925      | 0.0041 | 0.9457           | 0.0047 | 0.7237   | 0.0124 |
| CF     | 0.8445         | 0.0106 | 0.9931      | 0.0026 | 0.9346           | 0.0061 | 0.7327   | 0.0036 |
| CR     | 0.9024         | 0.0046 | 0.9950      | 0.0028 | 0.9532           | 0.0084 | 0.7655   | 0.0111 |
| C      | 0.9214         | 0.0104 | 0.9948      | 0.0033 | 0.9685           | 0.0087 | 0.7687   | 0.0146 |

Table 4: Impact of different example selection strategies in the 3-Shot Setting.

#### 4.6 Effect of Example Selection Strategies During Inference

To answer RQ5, we conduct experiments to evaluate the impact of different example selection strategies and the number of examples. The experimental setup follows the same configuration as described in Sec. 4.5. The results of these strategies under the 3-shot setting are presented in Tab. 4. Specifically, C, F, and CF correspond to the three example selection strategies introduced in Sec. 3.2, while R refers to the random selection of examples or the shuffling of the selected examples order. Based on the experimental results in Tab. 4 and Tab. 5, we summarize two conclusive findings as follows:

**Providing appropriate demonstrations is crucial for crystal generation.** The results in Tab. 4 demonstrate that shuffling the order of examples reduces the success rate of conditional generation, confirming the effectiveness of using generation conditions and CrystalINN fingerprints as criteria for example selection. Moreover, the condition-based prompt construction strategy achieves the best performance, highlighting the importance of providing similar examples in conditional crystal generation task.

**The number of demonstrations has an insignificant impact on crystal generation task.** Tab. 5 presents the influence of the number of examples on conditional generation performance, evaluating both random selection and condition-based selection strategies for prompt construction. The results indicate that the number of examples selected during generation has no significant impact

| Method  | Success Rate   |        |             |        |                  |        |          |        |
|---------|----------------|--------|-------------|--------|------------------|--------|----------|--------|
|         | Pretty Formula |        | Space Group |        | Formation Energy |        | Band Gap |        |
|         | Mean           | Std.   | Mean        | Std.   | Mean             | Std.   | Mean     | Std.   |
| 1Shot-R | 0.7360         | 0.0177 | 0.9866      | 0.0041 | 0.9026           | 0.0066 | 0.7070   | 0.0160 |
| 2Shot-R | 0.7310         | 0.0084 | 0.9865      | 0.0066 | 0.9072           | 0.0054 | 0.7023   | 0.0120 |
| 3Shot-R | 0.7441         | 0.0147 | 0.9871      | 0.0046 | 0.9107           | 0.0094 | 0.7120   | 0.0167 |
| 1Shot-C | 0.9376         | 0.0039 | 0.9946      | 0.0024 | 0.9731           | 0.0045 | 0.8009   | 0.0235 |
| 2Shot-C | 0.9410         | 0.0119 | 0.9954      | 0.0020 | 0.9683           | 0.0036 | 0.7777   | 0.0068 |
| 3Shot-C | 0.9214         | 0.0104 | 0.9948      | 0.0033 | 0.9685           | 0.0087 | 0.7687   | 0.0146 |

Table 5: Impact of different shot numbers.

on the model’s cross-domain conditional generation capability.

## 5 Related work

### 5.1 Equivariant Diffusion model-based Crystal Generation Methods

Periodicity and symmetry are fundamental characteristics of crystals, which have a decisive impact on their physical properties. Therefore, ensuring the SE(3) equivariance of the crystal generation process is crucial for crystal generation task (Han et al., 2024). To address this challenge, equivariant diffusion models (Xie et al., 2022; Jiao et al., 2023, 2024) have emerged as a leading method for generating stable crystal materials in recent years, owing to their ability to harness the physical symmetries inherent in periodic material structures.

### 5.2 Language model-based Crystal Generation Methods

In recent years, LLMs trained on large-scale unsupervised corpora have demonstrated unprecedented powerful capabilities across various tasks, which has stimulated researchers’ interest in the potential of language models in learning effective "world models" for crystal chemistry. Several studies (Antunes et al., 2024; Gruver et al., 2024) have begun to explore the capabilities of language models in the field of crystal generation.

## 6 Conclusion

In this work, we propose CrystalICL, a crystal generation model designed to effectively inherit the in-context learning (ICL) generalization ability of LLMs. CrystalICL leverages the Wyckoff position to simplify the modeling of crystal symmetry and constructs an instruction fine-tuning set that harnesses the ICL capabilities of LLMs for crystal generation tasks. Extensive experiments on four crystal generation benchmarks demonstrate the ICL capabilities of CrystalICL on conditional and unconditional generation tasks across domains.

## 7 Limitations

The limitations of our work are as follows:

- In this study, we have demonstrated that CrystalICL effectively inherits the ICL capabilities of LLMs for crystal generation tasks. However, future research may explore how to extend the ICL capabilities of LLMs to other crystal-related tasks, such as crystal property prediction, and work towards the development of a unified large model for crystal research.
- Our proposed space-group based crystal tokenization method reveals a trade-off between chemical formula and space group conditional generation tasks. Further exploration of crystal structure text that are more suitable for LLMs may prove to be a promising research direction.
- Additionally, while LLM-based crystal generation methods show potential in crystal generation tasks, their ability to model crystal symmetry may be limited by the current capacity of LLMs to process numerical coordinates effectively. Therefore, future studies should delve deeper into enhancing the capability of LLMs in processing numerical information, which could significantly improve their performance in crystal generation tasks.

## References

- Luis M Antunes, Keith T Butler, and Ricardo Grau-Crespo. 2024. Crystal structure generation with autoregressive large language modeling. *Nature Communications*, 15(1):1–16.
- Kohei Shinohara Atsushi Togo and Isao Tanaka. 2024. *Spglib: a software library for crystal symmetry search*. *Sci. Technol. Adv. Mater., Meth.*, 4(1):2384822–2384836.
- Keith T Butler, Daniel W Davies, Hugh Cartwright, Olexandr Isayev, and Aron Walsh. 2018. Machine learning for molecular and materials science. *Nature*, 559(7715):547–555.
- Ivano E Castelli, David D Landis, Kristian S Thygesen, Søren Dahl, Ib Chorkendorff, Thomas F Jaramillo, and Karsten W Jacobsen. 2012. New cubic perovskites for one-and two-photon water splitting using the computational materials repository. *Energy & Environmental Science*, 5(10):9034–9043.
- Chi Chen, Weike Ye, Yunxing Zuo, Chen Zheng, and Shyue Ping Ong. 2019. Graph networks as a universal machine learning framework for molecules and crystals. *Chemistry of Materials*, 31(9):3564–3572.
- Kishalay Das, Subhojyoti Khastagir, Pawan Goyal, Seung-Cheol Lee, Satadeep Bhattacharjee, and Niloy Ganguly. 2025. *Periodic materials generation using text guided joint diffusion model*. In *The Thirteenth International Conference on Learning Representations, ICLR*. OpenReview.net.
- Gautam R Desiraju. 2002. Cryptic crystallography. *Nature materials*, 1(2):77–79.
- Daniel Flam-Shepherd and Alán Aspuru-Guzik. 2023. *Language models can generate molecules, materials, and protein binding sites directly in three dimensions as xyz, cif, and PDB files*. *CoRR*, abs/2305.05708.
- Nate Gruver, Anuroop Sriram, Andrea Madotto, Andrew Gordon Wilson, C. Lawrence Zitnick, and Zachary W. Ulissi. 2024. Fine-tuned language models generate stable inorganic materials as text. In *The Twelfth International Conference on Learning Representations, ICLR 2024, Vienna, Austria, May 7-11, 2024*. OpenReview.net.
- Sydney R Hall, Frank H Allen, and I David Brown. 1991. The crystallographic information file (cif): a new standard archive file for crystallography. *Foundations of Crystallography*, 47(6):655–685.
- Jiaqi Han, Jiacheng Cen, Liming Wu, Zongzhao Li, Xiangzhe Kong, Rui Jiao, Ziyang Yu, Tingyang Xu, Fandi Wu, Ziheng Wang, Hongteng Xu, Zhewei Wei, Yang Liu, Yu Rong, and Wenbing Huang. 2024. *A survey of geometric graph neural networks: Data structures, models and applications*. *CoRR*, abs/2403.00485.
- Edward J. Hu, Yelong Shen, Phillip Wallis, Zeyuan Allen-Zhu, Yuanzhi Li, Shean Wang, Lu Wang, and Weizhu Chen. 2022. *Lora: Low-rank adaptation of large language models*. In *The Tenth International Conference on Learning Representations, ICLR 2022, Virtual Event, April 25-29, 2022*. OpenReview.net.
- Anubhav Jain, Shyue Ping Ong, Geoffroy Hautier, Wei Chen, William Davidson Richards, Stephen Dacek, Shreyas Cholia, Dan Gunter, David Skinner, Gerbrand Ceder, et al. 2013. Commentary: The materials project: A materials genome approach to accelerating materials innovation. *APL materials*, 1(1).
- Rui Jiao, Wenbing Huang, Peijia Lin, Jiaqi Han, Pin Chen, Yutong Lu, and Yang Liu. 2023. Crystal structure prediction by joint equivariant diffusion. In *Advances in Neural Information Processing Systems 36: Annual Conference on Neural Information Processing Systems 2023, NeurIPS 2023, New Orleans, LA, USA, December 10 - 16, 2023*.
- Rui Jiao, Wenbing Huang, Yu Liu, Deli Zhao, and Yang Liu. 2024. Space group constrained crystal generation. In *The Twelfth International Conference on*

|     |  |  |  |  |
|-----|--|--|--|--|
| 703 | <i>Learning Representations, ICLR 2024, Vienna, Austria, May 7-11, 2024.</i> OpenReview.net.   |  |  |  |
| 704 |  |  |  |  |
| 705 | Walter Kohn and Lu Jeu Sham. 1965. Self-consistent equations including exchange and correlation effects. <i>Physical review</i> , 140(4A):A1133.   |  |  |  |
| 706 |  |  |  |  |
| 707 |  |  |  |  |
| 708 | Zeming Lin, Halil Akin, Roshan Rao, Brian Hie, Zhongkai Zhu, Wenting Lu, Nikita Smetanin, Robert Verkuil, Ori Kabeli, Yaniv Shmueli, et al. 2023. Evolutionary-scale prediction of atomic-level protein structure with a language model. <i>Science</i> , 379(6637):1123–1130.   |  |  |  |
| 709 |  |  |  |  |
| 710 |  |  |  |  |
| 711 |  |  |  |  |
| 712 |  |  |  |  |
| 713 |  |  |  |  |
| 714 | H. LIPSON. 1949. <a href="#">Crystal structures.</a> <i>Nature</i> , 163(4147):622–622.  |  |  |  |
| 715 |  |  |  |  |
| 716 | Shyue Ping Ong, William Davidson Richards, Anubhav Jain, Geoffroy Hautier, Michael Kocher, Shreyas Cholia, Dan Gunter, Vincent L. Chevrier, Kristin A. Persson, and Gerbrand Ceder. 2013. <a href="#">Python materials genomics (pymatgen): A robust, open-source python library for materials analysis.</a> <i>Computational Materials Science</i> , 68:314–319.  |  |  |  |
| 717 |  |  |  |  |
| 718 |  |  |  |  |
| 719 |  |  |  |  |
| 720 |  |  |  |  |
| 721 |  |  |  |  |
| 722 |  |  |  |  |
| 723 | Chris J Pickard. 2020. Airss data for carbon at 10gpa and the c+ n+ h+ o system at 1gpa. ( <i>No Title</i> ).  |  |  |  |
| 724 |  |  |  |  |
| 725 | Izumi Takahara, Kiyou Shibata, and Teruyasu Mizoguchi. 2024. <a href="#">Generative inverse design of crystal structures via diffusion models with transformers.</a> <i>CoRR</i> , abs/2406.09263.   |  |  |  |
| 726 |  |  |  |  |
| 727 |  |  |  |  |
| 728 |  |  |  |  |
| 729 | Hugo Touvron, Louis Martin, Kevin Stone, Peter Albert, Amjad Almahairi, Yasmine Babaei, Nikolay Bashlykov, Soumya Batra, Prajwal Bhargava, Shruti Bhosale, Dan Bikel, Lukas Blecher, Cristian Canton-Ferrer, Moya Chen, Guillem Cucurull, David Esiobu, Jude Fernandes, Jeremy Fu, Wenyin Fu, Brian Fuller, Cynthia Gao, Vedanuj Goswami, Naman Goyal, Anthony Hartshorn, Saghar Hosseini, Rui Hou, Hakan Inan, Marcin Kardas, Viktor Kerkez, Madian Khabsa, Isabel Kloumann, Artem Korenev, Punit Singh Koura, Marie-Anne Lachaux, Thibaut Lavril, Jenya Lee, Diana Liskovich, Yinghai Lu, Yuning Mao, Xavier Martinet, Todor Mihaylov, Pushkar Mishra, Igor Molybog, Yixin Nie, Andrew Poulton, Jeremy Reizenstein, Rashi Rungta, Kalyan Saladi, Alan Schelten, Ruan Silva, Eric Michael Smith, Ranjan Subramanian, Xiaoqing Ellen Tan, Binh Tang, Ross Taylor, Adina Williams, Jian Xiang Kuan, Puxin Xu, Zheng Yan, Iliyan Zarov, Yuchen Zhang, Angela Fan, Melanie Kambadur, Sharan Narang, Aurélien Rodriguez, Robert Stojnic, Sergey Edunov, and Thomas Scialom. 2023. <a href="#">Llama 2: Open foundation and fine-tuned chat models.</a> <i>CoRR</i> , abs/2307.09288. |  |  |  |
| 730 |  |  |  |  |
| 731 |  |  |  |  |
| 732 |  |  |  |  |
| 733 |  |  |  |  |
| 734 |  |  |  |  |
| 735 |  |  |  |  |
| 736 |  |  |  |  |
| 737 |  |  |  |  |
| 738 |  |  |  |  |
| 739 |  |  |  |  |
| 740 |  |  |  |  |
| 741 |  |  |  |  |
| 742 |  |  |  |  |
| 743 |  |  |  |  |
| 744 |  |  |  |  |
| 745 |  |  |  |  |
| 746 |  |  |  |  |
| 747 |  |  |  |  |
| 748 |  |  |  |  |
| 749 |  |  |  |  |
| 750 |  |  |  |  |
| 751 |  |  |  |  |
| 752 | Logan Ward, Ankit Agrawal, Alok Choudhary, and Christopher Wolverton. 2016. A general-purpose machine learning framework for predicting properties of inorganic materials. <i>npj Computational Materials</i> , 2(1):1–7.  |  |  |  |
| 753 |  |  |  |  |
| 754 |  |  |  |  |
| 755 |  |  |  |  |
| 756 |  |  |  |  |
| 757 | Tian Xie, Xiang Fu, Octavian-Eugen Ganea, Regina Barzilay, and Tommi S. Jaakkola. 2022. Crystal diffusion variational autoencoder for periodic material  |  |  |  |
| 758 |  |  |  |  |
| 759 |  |  |  |  |
|     |  | generation. In <i>The Tenth International Conference on Learning Representations, ICLR 2022, Virtual Event, April 25-29, 2022.</i> OpenReview.net.   |  | 760<br>761<br>762                      |
|     |  | Weitong Zhang, Xiaoyun Wang, Weili Nie, Joe Eaton, Brad Rees, and Quanquan Gu. 2023. Moleculgpt: Instruction following large language models for molecular property prediction. In <i>NeurIPS 2023 Workshop on New Frontiers of AI for Drug Discovery and Development.</i> |  | 763<br>764<br>765<br>766<br>767<br>768 |
|     |  | Yizhen Zheng, Huan Yee Koh, Maddie Yang, Li Li, Lauren T. May, Geoffrey I. Webb, Shirui Pan, and George Church. 2024. <a href="#">Large language models in drug discovery and development: From disease mechanisms to clinical trials.</a> <i>CoRR</i> , abs/2409.04481.   |  | 769<br>770<br>771<br>772<br>773        |
|     |  | Nils ER Zimmermann and Anubhav Jain. 2020. Local structure order parameters and site fingerprints for quantification of coordination environment and crystal structure similarity. <i>RSC advances</i> , 10(10):6063–6081.   |  | 774<br>775<br>776<br>777<br>778        |
|     |  | <b>A Failure Example</b>   |  | 779                                    |
|     |  | The following is an example of a failed 0-shot generation by GPT-3.5 Turbo:  |  | 780<br>781                             |
|     |  | ### Instruction:   |  |  |
|     |  | ### Example:   |  |  |
|     |  | ### a b c  |  |  |
|     |  | ### alpha beta gamma   |  |  |
|     |  | ### atom   |  |  |
|     |  | ### x y z  |  |  |
|     |  | ### atom   |  |  |
|     |  | ### x y z  |  |  |
|     |  | ### Below is a description of a bulk   |  |  |
|     |  | → material. The chemical formula is  |  |  |
|     |  | → SnReN3. The spacegroup number is 221.  |  |  |
|     |  | → Generate a description of the  |  |  |
|     |  | → lengths and angles of the lattice  |  |  |
|     |  | → vectors and then the element type  |  |  |
|     |  | → and coordinates for each atom within   |  |  |
|     |  | → the lattice. The answer should   |  |  |
|     |  | → contain only the element symbol and  |  |  |
|     |  | → the number, and should be formatted  |  |  |
|     |  | → as given in the example:   |  |  |
|     |  | ### Response:  |  |  |
|     |  | ### Description of lattice vectors:  |  |  |
|     |  | ### a = 5.67 Å   |  |  |
|     |  | ### b = 5.67 Å   |  |  |
|     |  | ### c = 5.67 Å   |  |  |
|     |  | ### alpha = 90°  |  |  |
|     |  | ### beta = 90°   |  |  |
|     |  | ### gamma = 90°  |  |  |
|     |  | ###  |  |  |
|     |  | ### Element type and coordinates:  |  |  |

```
### Sn 0.00 0.00 0.00
### Re 0.50 0.50 0.50
### N 0.25 0.25 0.25
### N 0.75 0.75 0.75
### N 0.00 0.50 0.00
### N 0.50 0.00 0.50
```

From the above failed example, it is evident that despite providing example structures in the prompt and specifying that the response should contain only element symbols and numbers, the output generated by GPT-3.5 Turbo still included special symbols such as '=', 'Å', and '°', as well as the English phrase "Description of lattice vectors:". This illustrates that a general pretrained large language model, without fine-tuning, struggles to adhere to the instructions and generate the desired crystal structure text.

## B Details of Datasets

We selected four datasets with diverse domains and scales to comprehensively evaluate the model's performance. We apply the standard split as used in previous work (Xie et al., 2022; Gruver et al., 2024) for all of our experiments.

The MP20 dataset is derived from the Materials Project (Jain et al., 2013) and contains 45,231 materials with varying structural and compositional characteristics, covering 89 elements and unit cells ranging from 1 to 20 atoms. Following the previous work (Xie et al., 2022), we only select structures with formation energy smaller than 2 eV/atom and energy above the hull smaller than 0.08 eV/atom. All materials in MP20 have been relaxed using density functional theory (DFT). The dataset analysis indicates that most materials exhibit thermodynamic stability and have been successfully synthesized in experiments.

The MP30 dataset (Gruver et al., 2024) is also derived from the Materials Project and comprises 127,609 crystal structures. The dataset spans a wide range of materials, with unit cells containing 1 to 30 atoms. Compared to MP20, MP30 includes a more extensive collection of structures, capturing a broader diversity of compositions. All crystal structures in MP30 have been relaxed using DFT to ensure reliable structural and energetic information, facilitating its application in crystal generation and property prediction tasks.

The Perov-5 (P5) dataset (Castelli et al., 2012) consists of 18,928 perovskite materials that share

the same structure but differ in chemical composition. It includes 56 elements, with each unit cell containing 5 atoms. Perovskite materials typically follow the general chemical formula  $ABX_3$ , where, in an ideal cubic structure, the A atoms occupy the corner positions, the B atoms are located at the body center, and the X atoms are positioned at the face centers. Due to their wide range of applications, perovskites have attracted significant attention in photovoltaics, catalysis, and electronics. All structures in P5 have been relaxed using DFT. The resulting relaxed structures can deviate significantly from the ideal perovskite structures. Additionally, a significant portion of these materials are not thermodynamically stable, meaning they are prone to decomposition into more stable phases and are thus challenging to synthesize experimentally.

The Carbon-24 (C24) dataset comprises carbon structures generated through the ab initio random structure search (AIRSS) (Pickard, 2020) method under a pressure of 10 GPa. While all materials in this dataset are composed exclusively of carbon, they exhibit considerable structural diversity. The dataset includes materials with unit cells containing between 6 and 24 atoms. Consistent with previous work (Xie et al., 2022), we retain only the 10% of structures with the lowest energy per atom from the original dataset to create C24. All 10,153 structures in C24 have been optimized using DFT. The most stable structure under 10 GPa is diamond, whereas most remaining structures are thermodynamically unstable, although some may be kinetically stable. However, the majority of these structures are unlikely to be experimentally synthesizable.

## C Evaluation Metrics

For the evaluation of conditional crystal generation, we follow previous studies (Takahara et al., 2024; Das et al., 2025) and adopt the success rate as the primary evaluation metric. On the MP30 dataset, we focus on the conditional generation on chemical formula, space group, formation energy, and band gap, as these properties can be easily validated or approximated. On the P5 and C24 datasets, we restrict the conditional constraints to chemical formula and space group due to limitations in the available data. Chemical formula validation is performed by directly counting the atomic composition in the generated structures. Space group is determined using the SpacegroupAnalyzer module

875 from the pymatgen (Ong et al., 2013) library. For-  
876 mation energy and band gap are estimated using  
877 MEGNet (Chen et al., 2019) models trained on the  
878 Materials Project (Jain et al., 2013) dataset. Specif-  
879 ically, for formation energy, a generated sample is  
880 considered successful if its formation energy shares  
881 the same sign as the input condition (Das et al.,  
882 2025). For band gap, a sample is deemed valid  
883 if the absolute difference between the generated  
884 value and the input condition is less than 0.5 eV.  
885 For the P5 and C24 datasets, since many materials  
886 in these datasets are derived from DFT calculations  
887 and do not exist in reality, their physicochemical  
888 properties may not be accurately estimated. There-  
889 fore, the evaluation for these datasets is limited to  
890 chemical formula and space group.

891 For the unconditional generation task, we fol-  
892 low prior work (Xie et al., 2022; Jiao et al., 2023)  
893 and evaluate performance across three key aspects:  
894 validity metrics, coverage metrics, and property  
895 distribution metrics. Validity metrics are catego-  
896 rized into structural validity and compositional va-  
897 lidity. Structural validity is determined based on  
898 non-overlapping atomic radii, where overlap is de-  
899 fined as the distance between two atoms being less  
900 than half the sum of their radii. Compositional va-  
901 lidity ensures that the generated structure has a net  
902 neutral charge, as only charge-neutral structures  
903 are considered valid. Coverage metrics include  
904 recall and precision, which are computed based  
905 on CrystalNN fingerprints (Zimmermann and Jain,  
906 2020) and normalized Magpie fingerprints (Ward  
907 et al., 2016). Recall measures how many ground-  
908 truth materials are correctly predicted, while preci-  
909 sion assesses the quality of the generated materials.  
910 Property distribution metrics are evaluated using  
911 the Wasserstein distance for three key properties:  
912 density  $\rho$ , formation energy per atom  $E$ , and the  
913 number of distinct element types  $N_{el}$  within the  
914 unit cell. These metrics provide a comprehensive  
915 assessment of how well the generated crystal struc-  
916 tures align with real-world material distributions.

## 917 D Baseline

918 CrystalLLM (Gruber et al., 2024) finetunes Llama-  
919 2 on crystal structure texts in XYZ format, explor-  
920 ing both unconditional and conditional crystal gen-  
921 eration tasks in zero-shot settings, thus highlighting  
922 the potential of LLMs in crystal generation. CD-  
923 VAE (Xie et al., 2022) proposes a VAE framework  
924 that first predicts the invariant lattice parameters

925 and then generates the atom types and coordinates  
926 via a score-based decoder. DiffCSP (Jiao et al.,  
927 2023) jointly generates the lattices and atom coord-  
928 inates.

## E Training Hyperparameters

929 To efficiently fine-tune Llama2-7b-chat, this study  
930 employs the LoRA technique with a rank of 8, an  
931 alpha value of 32, and a dropout rate of  $5e-2$ . The  
932 learning rate follows a cosine annealing schedule  
933 with an initial value of  $5e-4$ . During training, dif-  
934 ferent batch sizes and epochs are used based on  
935 the dataset characteristics. For the MP20 and C24  
936 datasets, a batch size of 1 is used with 10 training  
937 epochs. Due to the larger scale and extended train-  
938 ing time required for the MP30 dataset, the batch  
939 size remains set to 1, while the number of training  
940 epochs is limited to 3. For the P5 dataset, where  
941 all crystal structures contain only five atoms per  
942 unit cell, a batch size of 4 is used with 10 train-  
943 ing epochs to accelerate training. In the inference  
944 stage, batch sizes are adjusted based on the specific  
945 generation task. The batch size is set to 6 for cross-  
946 domain conditional generation, 8 for conditional  
947 generation, and 32 for unconditional generation.  
948 Additionally, both the top-p sampling parameter  
949 and the temperature are set to 0.9. All training  
950 and inference processes are conducted on a single  
951 Nvidia L40 48G GPU. 952

## F Computational Cost of SGS Preprocessing

953 To address concerns regarding the potential com-  
954 putational overhead introduced by the use of space-  
955 group based tokenization (SGS), we provide de-  
956 tailed runtime statistics for the conversion of CIF  
957 files to SGS format across various crystal datasets.  
958 959

960 The SGS preprocessing involves the identifica-  
961 tion of space groups and Wyckoff positions for each  
962 crystal structure. This step is executed as a one-  
963 time offline transformation using pymatgen (Ong  
964 et al., 2013) and spglib (Atsushi Togo and Tanaka,  
965 2024), accelerated by 32-process parallelization via  
966 the pandarallel library. 967

968 Table 6 reports the wall-clock times for convert-  
969 ing commonly used datasets on a server equipped  
970 with  $4 \times$  Intel(R) Xeon(R) Gold 5120 CPUs @  
971 2.20GHz. As shown, SGS preprocessing is com-  
972 putationally efficient even for large-scale datasets.  
973 For example, the MP30 dataset, which includes  
974 over 140k crystals, can be converted in under 8

| Dataset | Dataset Size | Conversion Time (s) |
|---------|--------------|---------------------|
| MP20    | 43k          | 142.57              |
| MP30    | 144k         | 442.73              |
| P5      | 19k          | 20.94               |
| C24     | 10k          | 12.93               |

Table 6: Preprocessing time for CIF-to-SGS conversion using 32-process parallelism.

minutes. For smaller datasets, the conversion typically completes within seconds. Therefore, the computation of Wyckoff positions introduces minimal overhead and does not pose a bottleneck for practical usage.

## G Details of Instructions

Our instruction fine-tuning dataset consists of two components: the instruction section and the response section. The instruction section provides a description of the task, specifies the required output format, and may include optional few-shot examples. Depending on the specific fine-tuning task, the output can be either a textual representation of the crystal structure or a specific crystal property value. Below are examples illustrating different tasks from the four instruction fine-tuning datasets.

The following is an example of a 0-shot conditional generation instruction based on the MP20 dataset:

```
### Instruction: Below is a description
→ of a bulk material. The chemical
→ formula is LiCuCO3. The energy above
→ the convex hull is 0.0469. The
→ spacegroup number is 67. The
→ formation energy per atom is -1.681.
→ The band gap is 1.7254. Generate the
→ space group symbol, a description of
→ the lengths and angles of the
→ lattice vectors and then the element
→ type and coordinates for each atom
→ within the lattice:
### Response:
### Cmme
### 5.3 6.3 8.8
### 90 90 90
### Li
### 0.00 0.25 0.64
### Cu
### 0.25 0.25 0.00
### C
```

```
### 0.00 0.25 0.28
### 0
### 0.22 0.25 0.21
### 0
### 0.00 0.25 0.43
```

The following is an example of a 3-shot conditional generation instruction from the P5 dataset:

```
### Below is three description of bulk
→ materials.
### First Example:
### The chemical formula is BeBaO2F. The
→ spacegroup number is 123.
### P4/mmm
### 4.9 4.9 4.9
### 90 90 90
### Ba
### 0.50 0.50 0.50
### Be
### 0.00 0.00 0.00
### O
### 0.00 0.50 0.50
### F
### 0.50 0.50 0.00
### Second Example:
### The chemical formula is ZrMoO2N. The
→ spacegroup number is 123.
### P4/mmm
### 4.0 4.0 4.0
### 90 90 90
### Zr
### 0.00 0.00 0.00
### Mo
### 0.50 0.50 0.50
### N
### 0.50 0.50 0.00
### O
### 0.00 0.50 0.50
### Third Example:
### The chemical formula is NiNaO2F. The
→ spacegroup number is 123.
### P4/mmm
### 4.2 4.2 4.2
### 90 90 90
### Na
### 0.50 0.50 0.50
### Ni
### 0.00 0.00 0.00
### O
### 0.00 0.50 0.50
### F
### 0.50 0.50 0.00
```

993

994

```

### The chemical formula is MgAgO2F. The
↳ spacegroup number is 123. Based on
↳ the three examples provided,
↳ generate the space group symbol, a
↳ description of the lengths and
↳ angles of the lattice vectors, along
↳ with the element type and
↳ coordinates for each atom within the
↳ lattice:
### Response:
### P4/mmm
### 4.2 4.2 4.2
### 90 90 90
### Mg
### 0.00 0.00 0.00
### Ag
### 0.50 0.50 0.50
### O
### 0.00 0.50 0.50
### F
### 0.50 0.50 0.00

```

The following is an example of an unconditional generation instruction from the C24 dataset:

```

### Instruction: Below is a description
↳ of a bulk material. Generate the
↳ space group symbol, a description of
↳ the lengths and angles of the
↳ lattice vectors and then the element
↳ type and coordinates for each atom
↳ within the lattice:
### Response:
### Amm2
### 4.0 2.5 11.9
### 90 90 90
### C
### 0.19 0.00 0.67
### C
### 0.29 0.00 0.98
### C
### 0.30 0.00 0.23
### C
### 0.31 0.00 0.55
### C
### 0.00 0.00 0.32
### C
### 0.00 0.00 0.90

```

The following is an example of a crystal property prediction instruction from the MP30 dataset:

```

### Instruction: Below is a partial
↳ description of a bulk material where
↳ the energy above the convex hull has
↳ been replaced with the string
↳ "[MASK]":
### The energy above the convex hull is
↳ [MASK].
### P4/mmm
### 4.0 4.0 10.1
### 90 90 90
### Rb
### 0.00 0.00 0.50
### Zn
### 0.00 0.50 0.16
### P
### 0.50 0.50 0.28
### P
### 0.00 0.00 0.00
### Generate the energy above the convex
↳ hull that could replace [MASK] in
↳ the bulk material:
### Response: 0.0

```

## H Evaluation on Physical and Chemical Realism

To more comprehensively evaluate the physical and chemical realism of generated crystal structures, we supplement the success rate metric with three additional evaluation criteria: atomic overlap, symmetry adherence, and energy-based feasibility check. Atomic overlap reflects the extent to which generated atoms are placed unrealistically close to one another, indicating physical invalidity of the resulting structure. Symmetry adherence measures how well the generated structure conforms to the intended space group, reflecting consistency with the specified generation condition. Energy-based feasibility check evaluates whether the generated crystal exhibits a negative formation energy, which is a necessary condition for thermodynamic stability.

| Method                 | Atomic Overlap ↓ |        | Symmetry Adherence ↑ |        | energy-based feasibility check ↑ |        |
|------------------------|------------------|--------|----------------------|--------|----------------------------------|--------|
|                        | Mean             | Std.   | Mean                 | Std.   | Mean                             | Std.   |
| CrystalLLM (XYZ)       | 0.0974           | 0.0100 | 0.2562               | 0.0090 | 0.8179                           | 0.0205 |
| CrystalCL (XYZ) 0-Shot | 0.0840           | 0.0087 | 0.3102               | 0.0213 | 0.8411                           | 0.0049 |
| CrystalCL (XYZ) 3-Shot | <b>0.0731</b>    | 0.0052 | <b>0.3492</b>        | 0.0188 | <b>0.8795</b>                    | 0.0091 |
| CrystalLLM (SGS)       | 0.0868           | 0.0067 | 0.8290               | 0.0091 | 0.7753                           | 0.0161 |
| CrystalCL (SGS) 0-Shot | 0.0390           | 0.0037 | 0.9600               | 0.0028 | 0.8776                           | 0.0170 |
| CrystalCL (SGS) 3-Shot | <b>0.0290</b>    | 0.0058 | <b>0.9666</b>        | 0.0054 | <b>0.9151</b>                    | 0.0124 |

Table 7: Evaluation of physical and chemical realism on MP20.

To assess physical and chemical realism, we apply these metrics in a conditional generation task

995  
996

999  
1000

1001  
1002  
1003  
1004  
1005  
1006  
1007  
1008  
1009  
1010  
1011  
1012  
1013  
1014  
1015  
1016

997  
998

1017  
1018

1019 on the MP20 dataset. As shown in Table 7, our  
1020 method consistently achieves stronger performance  
1021 across all three metrics. In the few-shot SGS set-  
1022 ting, the model generates structures with notably  
1023 reduced atomic overlap and a symmetry adherence  
1024 success rate exceeding 96%. Furthermore, over  
1025 91.5% of the generated crystals exhibit negative for-  
1026 mation energy. These results demonstrate that the  
1027 proposed SGS representation and instruction tun-  
1028 ing strategies significantly improve the structural  
1029 validity and physical plausibility of the outputs.

## 1030 I License

1031 Llama-2 (Touvron et al., 2023) is distributed under  
1032 the *LLaMA 2 Community License Agreement* by  
1033 Meta. The MEGNet model (Chen et al., 2019) is  
1034 released under the *BSD-3-Clause license*. The py-  
1035 matgen (Ong et al., 2013) is released under the *MIT*  
1036 *license*. The Materials Project (Jain et al., 2013)  
1037 dataset, the P5 (Castelli et al., 2012) dataset and  
1038 the C24 (Pickard, 2020) dataset are released under  
1039 the *Creative Commons Attribution 4.0 license*. All  
1040 resources are used solely for academic research, in  
1041 accordance with their licensing terms.