

# Afrispeech Semantics: Evaluating Audio–Semantic Reasoning in Spoken Language Models Across Domains and Accents

Anonymous ACL submission

## Abstract

Audio language models (ALMs) are increasingly used for speech-based understanding; yet, their ability to perform semantic reasoning beyond transcription, Text-to-Audio Retrieval, Captioning, and Question-Answering accuracy remains insufficiently benchmarked. In particular, the effects of accent variation, domain shift, and semantic over-inference on audio reasoning are poorly understood. We evaluate audio language models across five semantic and paralinguistic reasoning tasks: entailment, consistency, plausibility, accent drift, and accent restraint. Collectively, these tasks assess a model’s ability to reason over spoken audio as the primary evidence source, including whether a textual hypothesis can be inferred, contradicted, or left undetermined by the audio, whether statements align or conflict with spoken content, whether claims are plausible given the discourse, and whether model predictions remain stable or appropriately constrained across accent variation. These findings highlight critical limitations in current audio reasoning evaluations and hope to provide guidance for more robust and equitable ALM design and assessment.

## 1 Introduction

Recent multimodal models, commonly referred to as audio language models (ALMs), are trained on large collections of audio–text pairs using either contrastive learning (Elizalde et al., 2023) or next-token prediction objectives (Chu et al., 2024; Tang et al., 2023; Goel et al., 2025; KimiTeam et al., 2025). Once trained, ALMs can be prompted to perform a wide range of tasks grounded in audio, including captioning, retrieval, and question answering, and have demonstrated strong performance across many established benchmarks (Sakshi et al., 2024; Wang et al., 2024).

Despite these advances, most existing evaluations primarily focus on surface-level correctness

rather than semantic reasoning grounded in the audio signal (Wang et al., 2024; Yang et al., 2025). In open-ended settings, ALMs are often rewarded for producing plausible responses, even when those responses rely on contextual assumptions or linguistic priors rather than evidence present in the audio (Chiang et al., 2025). This limitation becomes particularly problematic for interactive and reasoning-oriented applications, where models are expected to infer what can—and cannot—be concluded from what is heard (Sanni et al., 2025).

To address this gap, prior work introduced audio entailment as a focused task for evaluating deductive reasoning in audio language models (Deshmukh et al.), framing the problem as determining whether a textual hypothesis is entailed, contradicted, or unsupported by an audio premise. While this formulation provides a principled starting point, it captures only a narrow slice of the reasoning challenges faced by ALMs. Existing benchmarks are limited in domain diversity and do not explicitly test failure modes such as semantic over-inference, robustness to unfamiliar named entities, or sensitivity to accent and pronunciation variation (Shi et al., 2024; Wang et al., 2024; Sakshi et al., 2024).

In this work, we expand the evaluation of audio reasoning beyond a single entailment task or deductive reasoning task. We introduce a unified semantic reasoning framework comprising several domain-diverse speech datasets, each paired with task formulations tailored to the semantic properties of the domain.

Using this framework, we benchmark state-of-the-art contrastive and next-token prediction audio language models under a controlled inference protocol. Our results reveal consistent patterns of over-entailment, domain-specific reasoning failures, and accent-conditioned semantic drift, even when transcription quality is high. These findings suggest that current benchmarks substantially underesti-




Figure 1: Overview of Afrispeech Semantics.

mate reasoning errors in audio language models, underscoring the need for more comprehensive, domain-aware evaluation of semantic reasoning from audio.

In this work, we study logical and semantic reasoning for ALMs. Our contributions are as follows:

- We introduce four African-accented domain-diverse datasets that include linguistically diverse and accented audio, enabling the study of semantic reasoning beyond standard speech conditions.
- We propose multiple task formulations designed to test whether models preserve meaning under pronunciation variation rather than relying on contextual priors.
- Hypotheses are generated using LLaMA model and systematically verified and corrected by human annotators, ensuring semantic validity and grounding in the audio evidence, including accented and unfamiliar speech patterns.
- We benchmark both contrastive and next-token prediction audio language models under a unified inference protocol, revealing consistent over-entailment and accent-sensitive reasoning failures that are not captured by existing benchmarks.

## 2 Related works

Audio–language models combine acoustic perception with language modeling to support a broad range of audio understanding tasks (Ghosh et al., 2025, 2024). Early approaches focused primarily

on contrastive learning to align audio and text embeddings, enabling strong performance on retrieval and classification tasks (Elizalde et al., 2023). More recent work has explored next-token prediction frameworks that treat audio understanding as a conditional text generation problem, allowing models to perform open-ended tasks such as captioning, dialogue, and question answering (Deshmukh et al., 2023). These advances have substantially expanded the functional scope of ALMs; however, evaluation has largely emphasized task completion or linguistic plausibility rather than the semantic validity of the inferred conclusions (Peng et al., 2025).

As ALMs have become more capable of generating free-form responses, concerns have emerged regarding their reliance on contextual priors and language statistics rather than evidence grounded in the audio signal (Sakshi et al., 2024). Existing audio question answering and captioning benchmarks often permit multiple acceptable outputs, making it difficult to distinguish between correct inference and plausible hallucination (Chu et al., 2023). As a result, models may appear to perform well despite systematically over-interpreting or misattributing audio events (Shi et al., 2024; Kubis et al., 2025). These limitations have motivated interest in more principled evaluation frameworks that explicitly test reasoning behavior rather than surface-level alignment (Kubis et al., 2025).

Audio entailment was introduced as a structured task to evaluate deductive reasoning in audio–language models by determining whether a textual hypothesis is entailed, contradicted, or unsupported by an audio premise (Deshmukh et al.). By framing audio understanding as a three-way inference problem, this work provided an important step toward disentangling reasoning from generation quality and revealed significant reasoning deficiencies in state-of-the-art models. However, the focus of audio entailment is intentionally narrow: it evaluates a single reasoning formulation over a limited set of domains and does not explicitly probe how reasoning failures vary across domain types, semantic phenomena, or speech characteristics such as accent variation.

Related work in vision–language and text-based inference has shown that single-task benchmarks can underestimate reasoning errors and mask systematic failure modes (Sarkar et al., 2025; Cardoso et al.). Multi-task and domain-aware evaluation has proven essential for uncovering issues such as over-generalization, reliance on world knowledge,

Task	Reasoning	Complexity
Entailment	Deductive semantic	■■■■■
Consistency	Logical compatibility	■■■
Plausibility	Pragmatic semantic	■■■
Accent Drift	Robustness	■■■
Accent Restraint	Causal restraint	■■■■■

Table 1: Task taxonomy by reasoning type and the complexity of each reasoning type.

Dataset	Hours (h)	Accent Coverage
AfriSpeech-200 <sup>1</sup>	200	13
AfriSpeech-General <sup>2</sup>	2.07	8
Afri-Names <sup>3</sup>	8.92	12
Afrispeech - Medical <sup>4</sup>	4.20	6

Table 2: Overview of the four speech corpora used in this work. Durations are measured after pruning unusable segments. Detailed statistics and split methodology are provided in Appendix A.

and sensitivity to spurious correlations (Olatunji et al., 2023; Ogundepo et al., 2023). In the audio domain, however, comparable multi-task semantic reasoning evaluations remain underdeveloped. Prior benchmarks do not systematically test semantic restraint, robustness to unfamiliar named entities, or accent-conditioned meaning drift phenomena that are especially relevant for spoken language understanding in diverse, real-world settings (Wang et al., 2025; Sakshi et al., 2024).

### 3 Semantic Reasoning Tasks for Audio Language Models

#### 3.1 Problem Setup and Notation

We study semantic reasoning in audio language models through tasks that require models to draw conclusions from spoken audio. Each task is formulated as a relationship between an audio recording and a textual hypothesis, as illustrated in fig. 1. Let  $a$  denote an audio recording serving as the *premise*, and let  $h$  denote a natural language *hypothesis*. Given a pair  $(a, h)$ , the model predicts the semantic relationship between the hypothesis and the content expressed in the audio. An overview of the reasoning types associated with each task is provided in Table 1.

<sup>1</sup><https://huggingface.co/datasets/intronhealth/afri-speech-200>

<sup>2</sup><https://huggingface.co/datasets/intronhealth/afri-speech-dialog>

<sup>3</sup><https://huggingface.co/datasets/intronhealth/afri-names>

<sup>4</sup><https://huggingface.co/datasets/intronhealth/med-convo-nig>

Following prior work on audio entailment (Deshmukh et al.), we restrict inference to information supported by the audio signal itself. Models are not permitted to assume unstated facts or rely on external world knowledge beyond what can be reasonably inferred from the spoken content.

#### 3.2 Audio Entailment

We adopt audio entailment as the core semantic reasoning task. The objective is to determine whether a hypothesis is supported, contradicted, or left undetermined by an audio premise. Specifically, each  $(a, h)$  pair is assigned one of three labels:

- **Entailment (E):** The audio provides sufficient evidence to support the hypothesis.
- **Neutral (N):** The audio does not provide enough information to determine the truth of the hypothesis.
- **Contradiction (C):** The audio provides sufficient evidence to refute the hypothesis.

Formally, the task is defined as

$$f(a, h) \rightarrow y, \quad y \in \{E, N, C\}.$$

This task evaluates deductive semantic reasoning grounded in spoken language. Unlike text-based entailment, audio entailment requires models to reason over acoustic realizations of meaning, including speaker variation and prosodic cues, while maintaining strict evidence-based inference.

#### 3.3 Plausibility and Consistency

Beyond entailment, models may conflate semantic compatibility with evidential support. We therefore introduce plausibility and consistency tasks that further probe the boundaries of inference.

In the **plausibility** task, hypotheses are constructed to be reasonable given commonsense knowledge or discourse context, but are neither stated nor implied by the audio. The task assesses whether models incorrectly accept such hypotheses based solely on plausibility.

In the **consistency** task, hypotheses are either semantically compatible or incompatible with the spoken content. Unlike entailment, this task does not admit a neutral option; instead, it focuses on detecting agreement or contradiction with the audio premise. Together, these tasks assess whether models rely on semantic evidence rather than commonsense priors when making judgments.

239	<b>3.4 Accent-Conditioned Semantic Drift and</b>	<b>4.2 Hypothesis Generation</b>	287
240	<b>Accent Restraint</b>		
241	Spoken language varies substantially across speak-	For every audio premise we create a small set of	288
242	ers and accents. To evaluate robustness under such	hypotheses that probe different semantic relation-	289
243	variation, we introduce tasks that examine accent-	ships: whether a statement is entailed by the audio,	290
244	conditioned semantic drift. In this setting, audio	contradicted by it, merely plausible under common	291
245	recordings differ in accent or pronunciation while	sense, or tests for accent-induced drift. To scale	292
246	preserving equivalent semantic content, and hy-	this process, we first use an LLM to propose candi-	293
247	potheses remain unchanged. The task assesses	date hypotheses under carefully crafted prompts	294
248	whether accent variation systematically alters se-	that forbid unsupported negation and extraneous	295
249	semantic predictions.	world knowledge. These prompts are reproduced	296
250	We further introduce an accent restraint task to	verbatim in appendix I. Crucially, the LLM propos-	297
251	test whether models appropriately suppress accent-	als are only a starting point.	298
252	based cues when accent is semantically irrelevant.		
253	Here, accent functions as a nuisance variable, and	<b>4.3 Human Verification and Correction</b>	299
254	correct behavior requires invariant semantic judg-	After automatic generation, each candidate hypoth-	300
255	ments across accented realizations.	esis is vetted by trained human annotators. Anno-	301
256		tators listen to the audio in full and judge whether	302
257	<b>4 Dataset Construction and Annotation</b>	the proposed statement is entailed, contradicted,	303
258		or unsupported by the recording. If a hypothesis	304
259	In this section we describe how we curated and	contains hallucinated details or ambiguous phras-	305
260	annotated the data used throughout our evaluation.	ing, annotators edit or replace it to ensure that the	306
261	Rather than treating this step as a minor implemen-	final set of hypotheses is both semantically precise	307
262	tation detail, we view careful dataset construction	and audibly grounded. This manual verification	308
263	as central to any fair benchmark. Our goal was to	is particularly critical when dealing with accented	309
264	build a suite of tasks that capture real-world varia-	speech or rare proper names, where large language	310
265	tion in both content and pronunciation, while ensur-	models often introduce subtle semantic drift. Our	311
266	ing that every hypothesis is grounded in the acous-	annotation protocol—including guidelines, qual-	312
267	tic evidence. Table 2 gives a high-level overview	ity control procedures and examples—is described	313
268	of the four underlying corpora. A more detailed	in appendix B. By combining LLM-assisted gen-	314
269	description of the speaker demographics, transcript	eration with human oversight we strike a balance	315
270	quality and split methodology can be found in ap-	between scalability and data integrity.	316
271	pendix A. We provide qualitative examples of these		
272	tasks in Figure 2.	<b>5 Experimental Setup</b>	317
273			
274	<b>4.1 Audio Premises</b>	This section describes the models, inference pro-	318
275		cedures, and evaluation procedures used to assess	319
276	Each dataset is built around a collection of audio	semantic reasoning in audio language models. Our	320
277	premises $a$ paired with one or more textual hypothe-	setup is designed to enable fair comparison across	321
278	ses. The corpora span distinct domains including	model families while isolating reasoning behavior	322
279	conversational telephone speech, read speech fo-	from transcription or generation quality.	323
280	cused on named entities, and clinical dialogues to		
281	elicit a variety of reasoning behaviours. Import-	<b>5.1 Audio Language Models</b>	324
282	antly, the recordings cover a wide range of African		
283	accents and dialects, meaning models must con-	We evaluate two broad classes of audio language	325
284	tend with both linguistic and paralinguistic varia-	models (ALMs): <i>contrastive</i> models and <i>next-token</i>	326
285	tion rather than idealised laboratory speech. We se-	<i>prediction</i> models. Contrastive ALMs learn joint	327
286	lected datasets whose original annotations were cre-	audio–text representations and are commonly used	328
	ated from scratch by listening to the audio, thereby	for retrieval and classification tasks (Elizalde et al.,	329
	avoiding the confounding effect of textual metadata.	2023). Next-token prediction ALMs condition on	330
	Further details on duration, speaker demographics	audio and text inputs to generate free-form textual	331
	and accent distribution are provided in appendix A.	responses (Deshmukh et al., 2023). All models	332
		used are opensource models and also state of the	333
		art models.	334




Figure 2: Examples of two AfriSpeech-derived audio reasoning tasks. Each example uses an audio premise  $P$  (shown as a waveform icon and the verbatim transcript) paired with hypotheses  $H_1$ ,  $H_2$ , and  $H_3$  (or fewer, depending on the task). For Spoken Entailment, hypotheses are labeled ENTAILMENT, NEUTRAL, or CONTRADICTION. For Medical Consistency, hypotheses are labeled CONSISTENT or INCONSISTENT.

For contrastive models, the audio premise and hypothesis are encoded separately, and their similarity is used to predict the semantic relationship between them. For next-token prediction models, the audio premise and hypothesis are provided as input, and the model generates a textual response indicating its judgment. We evaluate ten Audio language models in total, three of which are contrastive models and seven are next-token prediction models.

We evaluate all models in a zero-shot setting unless otherwise stated. Model specifications and checkpoints are summarised in Table 12, and inference hyperparameters are listed in Table 14. These tables provide the necessary context to reproduce our experiments.

## 5.2 Prompt Selection

We observed that some models are sensitive to prompt phrasing for the semantic consistency task. To avoid cherry-picking, we pre-defined three prompt variants and selected the variant that achieved the best macro F1 on a held-out development subset, aggregated across datasets. Table 17 reports the comparison, and Appendix I lists the full prompt templates used. We use the selected prompt variant for all evaluations.

## 5.3 Inference Protocol

To ensure comparability across model types, we adopt a unified inference protocol aligned with the task formulation in Section 3. For contrastive models, similarity scores between audio and hypothesis

embeddings are mapped to entailment, neutral, or contradiction labels using fixed thresholds derived from a validation set. Threshold selection procedures follow standard practice and are detailed in the appendix I.

## 5.4 Evaluation and Label Mapping

Evaluating free-form outputs from next-token prediction models presents challenges due to variability in phrasing and instruction-following behavior. To address this, we adopt a model-based evaluation strategy in which a lightweight language model maps generated responses to discrete labels. This approach is validated against a human-annotated subset and achieves high agreement.

For contrastive models, predictions are obtained directly from thresholded similarity scores, eliminating the need for additional post-processing. All evaluations are conducted at the hypothesis level and aggregated at the dataset and task level.

## 5.5 Metrics

We report standard classification metrics, including accuracy, precision, recall, and macro-averaged F1 score. For multi-hypothesis settings, metrics are computed across all hypotheses associated with an audio premise. In addition, we report class-wise performance to analyze asymmetric error patterns, such as over-entailment and under-detection of contradiction.

To examine how reasoning performance varies across task types, we report results separately for entailment, semantic restraint, plausibility consis-

397 tency, and accent-conditioned semantic drift tasks. 445  
398 Detailed breakdowns and statistical summaries are 446  
399 provided in the appendix C. 447

## 400 5.6 Reproducibility 448

401 All datasets, fixed splits, inference prompts, and 449  
402 evaluation scripts will be released to support repro- 450  
403 ducibility. Hyperparameters and implementation 451  
404 details necessary to replicate our results are docu- 452  
405 mented in the table 14. 453

## 406 6 Results 454

407 To interpret the scores listed in the following tables, 455  
408 we first provide a high-level summary of model be- 456  
409 haviour. We evaluate eleven generative audio lan- 457  
410 guage models and three contrastive models across 458  
411 four corpora and five semantic reasoning tasks. Our 459  
412 primary metrics are accuracy and macro-averaged 460  
413 F1, supplemented by class-specific accuracies to 461  
414 detect asymmetric error patterns. In the aggregate, 462  
415 generative models substantially outperform con- 463  
416 trastive approaches on tasks that require nuanced 464  
417 reasoning, though contrastive baselines offer useful 465  
418 lower bounds. 466

### 419 6.1 Overall performance across tasks 468

420 Across all datasets, we observe a wide spread of 469  
421 performance. On the AfriSpeech-200 corpus, the 470  
422 strongest generative models (e.g., Qwen2.5Omni 471  
423 and Qwen2AudioInstruct) achieve macro F1 scores 472  
424 above 0.82 on plausibility and consistency tasks, 473  
425 while weaker baselines such as SALMONN lag 474  
426 markedly. Results on the AfriSpeech-Gen and 475  
427 Medical sets show similar trends, with Qwen2- 476  
428 based models achieving F1 scores around 0.85– 477  
429 0.95 in many settings. The contrastive models 478  
430 (LAION-CLAP and MSCLAP variants) perform 479  
431 near chance on most reasoning tasks, highlight- 480  
432 ing the limitations of embedding-only approaches 481  
433 for fine-grained semantics. Detailed per-task and 482  
434 per-model results are tabulated below. Qualitative 483  
435 examples comparing model outputs on these tasks 484  
436 are presented in Table 13 (Appendix E). 485

### 437 6.2 Task-wise analysis 486

438 **Audio Plausibility and Consistency.** The au- 487  
439 dio plausibility task measures whether models can 488  
440 distinguish statements that are plausible but un- 489  
441 supported by the audio from those that are im- 490  
442 plausible. As shown in Tables 3 and 7, gener- 491  
443 ative models tend to accept plausible but unsup- 492  
444 ported statements, with accuracy ranges from 0.41 493

to 0.97. Qwen2.5Omni and AudioFlamingo mod-  
els often over-accept plausible statements, indicat-  
ing a propensity for hallucination. Consistency,  
on the other hand, probes whether a hypothesis  
aligns or conflicts with the audio without a neu-  
tral option. Generative models again dominate,  
with Kimi-Audio and Qwen2.5Omni achieving F1  
scores above 0.8 on AfriSpeech-Gen (Table 5). Full  
results for contrastive baselines on these tasks are  
provided in Table 7 and Table 8.

**Audio Entailment.** The audio entailment task  
asks whether a hypothesis is entailed, contradicted,  
or unsupported by the audio premise. Table 4  
shows that even the best models struggle on this  
three-way classification: F1 scores rarely exceed  
0.71 on AfriSpeech-200, with frequent confusion  
between neutral and contradiction. Contrastive  
models perform poorly, reflecting their limited ca-  
pacity to discriminate fine-grained semantic rela-  
tions (Table 6). Qwen2-based models outperform  
others, but still exhibit a tendency to over-entail,  
as evidenced by lower neutral and contradiction  
accuracies.

**Accent Drift and Restraint.** The AfriNames  
subset isolates reasoning under accent variation  
and low-semantic-content utterances. Table 9 re-  
ports bias rates (fraction of accent-sensitive infer-  
ences) and accept rates (fraction of accent-invariant  
predictions). Qwen2AudioInstruct shows the low-  
est bias (33.25%) while AudioFlamingo2 exhibits  
substantial accent bias (96.75%). The restraint eval-  
uation in Table 10 underscores that models often  
hallucinate unsupported content; SALMONN and  
LAION-CLAP produce hallucinations in more than  
60% of cases. Models such as Qwen2.5Omni strike  
a better balance between suppressing hallucination  
and affirming supported content, achieving a se-  
mantic restraint accuracy (SRA) of 66.0%.

## 483 7 Discussion 483

484 The empirical results prompt a number of take- 484  
485 aways about the current state of audio-semantic 485  
486 reasoning. First, even the best-performing models 486  
487 exhibit systematic over-entailment: hypotheses that 487  
488 are plausible but not entailed by the audio are fre- 488  
489 quently marked as true. This suggests that models 489  
490 rely heavily on linguistic priors and commonsense 490  
491 knowledge rather than strictly grounding their pre- 491  
492 dictions in the acoustic evidence. Second, domain 492  
493 shift remains a challenge. Performance on the Med-

Dataset	ALM	Acc ↑	P ↑	R ↑	F1 ↑	Acc_P ↑	Acc_I ↑
Afri-200	AudioFlamingo2	0.2585	0.2548	0.2573	0.2560	0.5146	0.0000
	AudioFlamingo3	0.9512	0.9520	0.9511	<b>0.9512</b>	0.9709	0.9314
	GAMA	0.4390	0.8211	0.4374	0.4469	0.7670	0.1078
	Kimi	0.6927	0.7878	0.6941	0.6659	0.4078	0.9804
	Qwen2.5 Omni	0.8293	0.8723	0.8301	0.8244	0.6602	1.0000
	Qwen2 Audio 7B	0.8146	0.8722	0.8155	0.8180	0.6408	0.9902
	SALMONN	0.6439	0.7630	0.6455	0.5999	0.3107	0.9804
Afri-Gen	AudioFlamingo2	0.3707	0.2590	0.3707	0.3050	0.7414	0.0000
	AudioFlamingo3	0.9138	0.9552	0.9138	0.9339	0.9310	0.8966
	GAMA	0.4741	0.8597	0.4741	0.5529	0.7414	0.2069
	Kimi	0.8103	0.9194	0.8103	0.8506	0.9655	0.6552
	Qwen2.5 Omni	0.9569	0.9570	0.9569	<b>0.9569</b>	0.9483	0.9655
	Qwen2 Audio 7B	0.8103	0.8523	0.8103	0.8138	0.6724	0.9483
	SALMONN	0.6724	0.8021	0.6724	0.6330	0.3448	1.0000

Table 3: Zero-shot performance on Audio Plausibility (Generative Models). ↑ indicates higher is better.

Dataset	ALM	Acc ↑	P ↑	R ↑	F1 ↑	E-Acc ↑	N-Acc ↑	C-Acc ↑
Afri-200	AudioFlamingo2	0.3333	0.1111	0.3333	0.1667	0.0000	1.0000	0.0000
	AudioFlamingo3	0.6367	0.7398	0.6367	0.5466	0.9800	0.0400	0.8900
	GAMA	0.2967	0.1739	0.2967	0.1936	0.8400	0.0500	0.0000
	Kimi	0.6333	0.7499	0.6333	0.5383	0.8700	0.0700	0.9600
	Qwen2.5 Omni	0.6800	0.7076	0.6800	0.6731	0.8600	0.3400	0.8400
	Qwen2 Audio 7B	0.7133	0.7283	0.7133	<b>0.7123</b>	0.7400	0.5300	0.8700
	SALMONN	0.3967	0.4520	0.3967	0.2814	0.0000	1.0000	0.1900
Medical	AudioFlamingo2	0.3057	0.1024	0.3278	0.1561	0.0000	0.9833	0.0000
	AudioFlamingo3	0.6218	0.5512	0.5954	0.5160	0.9863	0.0167	0.7833
	GAMA	0.3782	0.2621	0.3591	0.3030	0.6438	0.4333	0.0000
	Kimi	0.6500	0.6726	0.6500	<b>0.5995</b>	0.8250	0.2000	0.9250
	Qwen2.5 Omni	0.5492	0.6414	0.5335	0.5274	0.7671	0.5500	0.2833
	Qwen2 Audio 7B	0.5521	0.5802	0.5546	0.5534	0.5139	0.6833	0.4667
	SALMONN	0.3679	0.6042	0.3737	0.2960	0.2877	0.8000	0.0333

Table 4: Zero-shot performance on Audio Entailment (Generative Models). ↑ indicates higher is better.

ical corpus, which contains spontaneous clinical dialogues with colloquial phrasing, lags behind performance on the read-speech AfriSpeech-Gen set. Models that excel on one domain may falter on another, indicating that domain-specific fine-tuning or broader training corpora may be necessary.

Accent variation further complicates semantic reasoning. The accent-drift experiments reveal that models often infer different meanings from semantically equivalent utterances when those utterances are spoken with different accents. Such bias underscores the risk of deploying audio systems in multilingual, multicultural settings without careful calibration. The accent restraint task, which measures hallucination on low-semantic-content utterances, shows that most models readily invent content when little is present. Among generative models, Qwen2-based variants strike a better balance between sensitivity and restraint, but there is ample room for improvement.

Finally, the stark contrast between generative

and contrastive models highlights the limits of embedding-only approaches for semantic reasoning. Although contrastive models perform well on retrieval-style tasks, they struggle to make fine-grained entailment judgments. Future work might explore hybrid architectures or training objectives that explicitly align representations with reasoning labels. We hope that the benchmark and analyses presented here will spur more nuanced evaluation and lead to audio language models that reason as carefully as they speak.

## 8 Caption-before-Reasoning

To explore whether structured prompting strategies improve audio-semantic reasoning, we experimented with caption-before-reasoning. In the caption-before-reasoning setup, models were first prompted to generate an explicit audio caption before performing the downstream semantic reasoning task. Contrary to our expectations, this strategy did not yield consistent performance gains. Error

Dataset	ALM	Acc $\uparrow$	P $\uparrow$	R $\uparrow$	F1 $\uparrow$	Acc_C $\uparrow$	Acc_I $\uparrow$
Afri-200	AudioFlamingo2	0.6019	0.6493	0.6019	0.5677	0.3204	0.8835
	AudioFlamingo3	0.5000	0.2500	0.5000	0.3333	0.0000	1.0000
	GAMA	0.2573	0.7802	0.2573	0.2819	0.4951	0.0194
	Kimi	0.8301	0.8545	0.8301	0.8271	0.6990	0.9612
	Qwen2.5 Omni	0.7136	0.8179	0.7136	0.6880	1.0000	0.4272
	Qwen2 Audio 7B	0.8447	0.8452	0.8447	<b>0.8446</b>	0.8641	0.8252
	SALMONN	0.7379	0.7393	0.7379	0.7375	0.7767	0.6990
Afri-Gen	AudioFlamingo2	0.8793	0.9022	0.8793	0.8815	0.7759	0.9828
	AudioFlamingo3	0.5000	0.2500	0.5000	0.3333	0.0000	1.0000
	GAMA	0.2759	0.8684	0.2759	0.3562	0.4828	0.0690
	Kimi	0.8190	0.8418	0.8190	0.8159	0.6897	0.9483
	Qwen2.5 Omni	0.9138	0.9265	0.9138	<b>0.9131</b>	1.0000	0.8276
	Qwen2 Audio7B	0.8276	0.8625	0.8276	0.8233	0.6724	0.9828
	SALMONN	0.9052	0.9053	0.9052	0.9052	0.8966	0.9138
Medical	AudioFlamingo2	0.8125	0.8175	0.8125	<b>0.8118</b>	0.7500	0.8750
	AudioFlamingo3	0.5000	0.2500	0.5000	0.3333	0.0000	1.0000
	GAMA	0.3500	0.7429	0.3500	0.4210	0.5500	0.1500
	Kimi	0.7375	0.8279	0.7375	0.7181	0.4750	1.0000
	Qwen2.5Omni	0.7250	0.8226	0.7250	0.7025	1.0000	0.4500
	Qwen2 Audio	0.7625	0.7640	0.7625	0.7622	0.7250	0.8000
	SALMONN	0.7750	0.7757	0.7750	0.7749	0.8000	0.7500

Table 5: Zero-shot performance on Audio Consistency (Generative Models).  $\uparrow$  indicates higher is better.

Dataset	ALM	Acc $\uparrow$	P $\uparrow$	R $\uparrow$	F1 $\uparrow$	E-Acc $\uparrow$	N-Acc $\uparrow$	C-Acc $\uparrow$
Afri-200	LAION-CLAP	0.3333	0.3333	0.3333	0.3325	0.3000	0.3200	0.3800
	MSCLAP_23	0.3200	0.2127	0.3200	0.2321	0.2000	0.0000	0.7600
	MSCLAP_22	0.3500	0.3448	0.3500	0.3444	0.2200	0.4200	0.4100
Medical	LAION-CLAP	0.3782	0.3868	0.3868	0.3725	0.2603	0.5500	0.3500
	MSCLAP_23	0.3005	0.2019	0.3064	0.2246	0.2192	0.0000	0.7000
	MSCLAP_22	0.3834	0.3988	0.3607	0.3286	0.6986	0.1167	0.2667

Table 6: Zero-shot performance on audio entailment (Contrastive Models).  $\uparrow$  indicates higher is better.

analysis revealed two primary causes: (1) model refusals, where models declined to provide a response or reasoning (e.g., “I cannot provide that analysis”), and (2) missing labels, where models produced a caption but failed to output the required classification label, rendering the response unusable for evaluation.

## 9 Conclusion

We have introduced a comprehensive benchmark for evaluating semantic reasoning in audio language models across diverse domains, tasks, and accents. By combining large-scale hypothesis generation with careful human verification, our datasets isolate distinct reasoning phenomena including entailment, plausibility, consistency, accent-conditioned drift and semantic restraint that challenge current models beyond transcription quality. Our results show that next-token prediction models, particularly Qwen2-based variants and AudioFlamingo, substantially outperform contrastive baselines on most reasoning tasks, yet still exhibit

significant over-entailment and susceptibility to commonsense bias. The benchmark also surfaces performance gaps under domain shift and accent variation, underscoring the need for robustness to linguistic diversity. We hope that these resources and analyses will catalyze the development of audio language models that ground their inferences in acoustic evidence and handle the richness of spoken language with care.

## Limitations

This work has several limitations. First, although we curated diverse datasets across multiple African accents and domains, the benchmark still reflects a finite selection of languages, topics and speakers; performance may not generalize to other dialects, spontaneous discourse genres or low-resource languages outside our coverage. Second, while our human verification protocol mitigates hallucinated hypotheses, annotator judgments and edits remain subjective; some subtle distinctions could be missed or misclassified. Third, the reliance on

Dataset	ALM	Acc ↑	P ↑	R ↑	F1 ↑	Acc_P ↑	Acc_I ↑
Afri-200	LAION-CLAP	0.4976	0.4968	0.4970	0.4906	0.6117	0.3824
	MSCLAP_23	0.5122	0.5124	0.5124	<b>0.5116</b>	0.4757	0.5490
	MSCLAP_22	0.4976	0.4987	0.4997	0.3841	0.0680	0.9314
Afri-Gen	LAION-CLAP	0.5603	0.5626	0.5603	<b>0.5564</b>	0.6552	0.4655
	MSCLAP_23	0.5172	0.5176	0.5172	0.5149	0.5862	0.4483
	MSCLAP_22	0.5431	0.5550	0.5431	0.5169	0.3103	0.7759
Medical	LAION-CLAP	0.5875	0.6068	0.5875	<b>0.5680</b>	0.8000	0.3750
	MSCLAP_23	0.4000	0.3990	0.4000	0.3985	0.4500	0.3500
	MSCLAP_22	0.5375	0.5419	0.5375	0.5250	0.3750	0.7000

Table 7: Zero-shot performance on audio Plausibility (Contrastive Models). ↑ indicates higher is better.

Dataset	ALM	Acc ↑	P ↑	R ↑	F1 ↑	Acc_C ↑	Acc_I ↑
Afri-200	LAION-CLAP	0.5049	0.5050	0.5049	<b>0.5018</b>	0.4272	0.5825
	MSCLAP_23	0.4660	0.4467	0.4660	0.4128	0.7670	0.1650
	MSCLAP_22	0.5340	0.5514	0.5340	0.4908	0.2427	0.8252
Afri-Gen	LAION-CLAP	0.5603	0.5618	0.5603	<b>0.5577</b>	0.6379	0.4828
	MSCLAP_23	0.4483	0.4483	0.4483	0.4483	0.4483	0.4483
	MSCLAP_22	0.5000	0.5000	0.5000	0.3967	0.0862	0.9138
Medical	LAION-CLAP	0.5750	0.5758	0.5750	0.5739	0.5250	0.6250
	MSCLAP	0.6250	0.6374	0.6250	<b>0.6164</b>	0.7750	0.4750
	MSCLAP_22	0.5000	0.5000	0.5000	0.4972	0.5750	0.4250

Table 8: Zero-shot performance on Audio Consistency (Contrastive Models). ↑ indicates higher is better.

Model	Bias Rate ↓	Accept Rate ↑
AudioFlamingo2	96.75%	97.75%
AudioFlamingo3	81.50%	<b>98.25%</b>
GAMA	58.75%	68.25%
Kimi	55.25%	84.50%
Qwen2.5Omni	41.50%	95.50%
Qwen2AudioInstruct	33.25%	88.75%
SALMONN	1.50%	3.50%

Table 9: AfriNames accent-drift evaluation across models. ↓ indicates lower is better; ↑ indicates higher is better.

Model	HLU Rate ↓	SPRT Rate ↑	SRA ↑
AudioFlamingo3	88.00%	100.00%	66.00%
GAMA	96.83%	98.50%	<b>72.62%</b>
Kimi	17.17%	80.50%	12.88%
Qwen2.5Omni	2.33%	62.50%	1.75%
Qwen2AudioInstruct	39.17%	97.50%	29.38%
SALMONN	27.17%	35.50%	20.38%
LAION-CLAP	60.17%	68.00%	45.12%

Table 10: AfriNames restraint evaluation across models. The SRA (↑) metric balances the model’s ability to identify supported content against its tendency toward hallucination (↓). HLU stands for Hallucination and SPRT stands for support

large language models for hypothesis generation and label mapping introduces their own biases and may not capture all error modes. Finally, our evaluation focuses on zero-shot inference; fine-tuning or prompting strategies may yield different patterns of success and failure. Future work should expand the dataset to additional languages and domains, incorporate multiple annotation phases for quality control, and explore training-time interventions to reduce over-entailment and accent sensitivity.

## References

Henrique Lopes Cardoso, Rui Sousa-Silva, Maarit Koponen, and Antonio Pareja-Lora. Proceedings of 2nd LUHME Workshop.

Cheng-Han Chiang, Xiaofei Wang, Chung-Ching Lin,

Kevin Lin, Linjie Li, Radu Kopetz, Yao Qian, Zhen-dong Wang, Zhengyuan Yang, Hung-yi Lee, and Lijuan Wang. 2025. [Audio-Aware Large Language Models as Judges for Speaking Styles](#). *arXiv preprint*. ArXiv:2506.05984 [eess].

Yunfei Chu, Jin Xu, Qian Yang, Haojie Wei, Xipin Wei, Zhifang Guo, Yichong Leng, Yuanjun Lv, Jinzheng He, Junyang Lin, Chang Zhou, and Jingren Zhou. 2024. [Qwen2-audio technical report](#). *Preprint*, arXiv:2407.10759.

Yunfei Chu, Jin Xu, Xiaohuan Zhou, Qian Yang, Shiliang Zhang, Zhijie Yan, Chang Zhou, and Jingren Zhou. 2023. [Qwen-Audio: Advancing Universal Audio Understanding via Unified Large-Scale Audio-Language Models](#). *arXiv preprint*. ArXiv:2311.07919 [eess].

608	Soham Deshmukh, Benjamin Elizalde, Rita Singh, and Huaming Wang. 2023. <a href="#">Pengi: An Audio Language Model for Audio Tasks</a> . <i>Advances in Neural Information Processing Systems</i> , 36:18090–18108.	666
609		667
610		668
611		669
612	Soham Deshmukh, Shuo Han, Hazim Bukhari, Benjamin Elizalde, Hannes Gamper, Rita Singh, and Bhiksha Raj. Audio Entailment: Assessing Deductive Reasoning for Audio Understanding.	670
613		671
614		672
615		673
616	Benjamin Elizalde, Soham Deshmukh, Mahmoud Al Ismail, and Huaming Wang. 2023. <a href="#">CLAP Learning Audio Concepts from Natural Language Supervision</a> . In <i>ICASSP 2023 - 2023 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)</i> , pages 1–5. ISSN: 2379-190X.	674
617		675
618		676
619		677
620		
621		
622	Sreyan Ghosh, Zhifeng Kong, Sonal Kumar, S. Sakshi, Jaehyeon Kim, Wei Ping, Rafael Valle, Dinesh Manocha, and Bryan Catanzaro. 2025. <a href="#">Audio Flamingo 2: An Audio-Language Model with Long-Audio Understanding and Expert Reasoning Abilities</a> . <i>arXiv preprint</i> . ArXiv:2503.03983 [cs].	678
623		679
624		680
625		681
626		682
627		683
628	Sreyan Ghosh, Sonal Kumar, Ashish Seth, Chandra Kiran Reddy Evuru, Utkarsh Tyagi, S. Sakshi, Oriol Nieto, Ramani Duraiswami, and Dinesh Manocha. 2024. <a href="#">GAMA: A Large Audio-Language Model with Advanced Audio Understanding and Complex Reasoning Abilities</a> . <i>arXiv preprint</i> . ArXiv:2406.11768 [cs].	684
629		685
630		686
631		687
632		688
633		689
634		690
635	Arushi Goel, Sreyan Ghosh, Jaehyeon Kim, Sonal Kumar, Zhifeng Kong, Sang-gil Lee, Chao-Han Huck Yang, Ramani Duraiswami, Dinesh Manocha, Rafael Valle, and Bryan Catanzaro. 2025. <a href="#">Audio Flamingo 3: Advancing Audio Intelligence with Fully Open Large Audio Language Models</a> . <i>arXiv preprint</i> . ArXiv:2507.08128 [cs].	691
636		692
637		693
638		694
639		695
640		
641		
642	KimiTeam, Ding Ding, Zeqian Ju, Yichong Leng, Songxiang Liu, Tong Liu, Zeyu Shang, Kai Shen, Wei Song, Xu Tan, Heyi Tang, Zhengtao Wang, Chu Wei, Yifei Xin, Xinran Xu, Jianwei Yu, Yutao Zhang, Xinyu Zhou, Y. Charles, and 21 others. 2025. <a href="#">Kimi-Audio Technical Report</a> . <i>arXiv preprint</i> . ArXiv:2504.18425 [eess].	696
643		697
644		698
645		699
646		700
647		701
648		702
649	Marek Kubis, Paweł Skórzewski, Iwona Christop, Mateusz Czyżnikiewicz, Jakub Kubiak, Łukasz Bondaruk, and Marcin Lewandowski. 2025. <a href="#">Preservation of Language Understanding Capabilities in Speech-aware Large Language Models</a> . <i>arXiv preprint</i> . ArXiv:2509.12171 [cs].	703
650		704
651		705
652		706
653		707
654		708
655	Oduayo Ogundepo, Tajuddeen R. Gwadabe, Clara E. Rivera, Jonathan H. Clark, Sebastian Ruder, David Ifeoluwa Adelani, Bonaventure F. P. Dossou, Abdou Aziz DIOP, Claytone Sikasote, Gilles Hacheme, Happy Buzaaba, Ignatius Ezeani, Roowether Mabuya, Salomey Osei, Chris Emezue, Albert Njoroge Kahira, Shamsuddeen H. Muhammad, Akintunde Oladipo, Abraham Toluwase Owodunni, and 33 others. 2023. <a href="#">AfriQA: Cross-lingual Open-Retrieval Question Answering for African Languages</a> . <i>arXiv preprint</i> . ArXiv:2305.06897 [cs].	709
656		710
657		711
658		712
659		713
660		
661		
662		
663		
664		
665		
	Tobi Olatunji, Tejumade Afonja, Aditya Yadavalli, Chris Chinenye Emezue, Sahib Singh, Bonaventure F. P. Dossou, Joanne Osuchukwu, Salomey Osei, Atnafu Lambebo Tonja, Naome Etori, and Clinton Mbataku. 2023. <a href="#">AfriSpeech-200: Pan-African accented speech dataset for clinical and general domain ASR</a> . <i>Transactions of the Association for Computational Linguistics</i> , 11:1669–1685.	714
		715
		716
		717
		718
	Jing Peng, Yucheng Wang, Yu Xi, Xu Li, Xizhuo Zhang, and Kai Yu. 2025. <a href="#">A Survey on Speech Large Language Models</a> . <i>arXiv preprint</i> . ArXiv:2410.18908 [eess] version: 3.	719
		720
		721
		722
	S. Sakshi, Utkarsh Tyagi, Sonal Kumar, Ashish Seth, Ramaneswaran Selvakumar, Oriol Nieto, Ramani Duraiswami, Sreyan Ghosh, and Dinesh Manocha. 2024. <a href="#">MMAU: A Massive Multi-Task Audio Understanding and Reasoning Benchmark</a> . <i>arXiv preprint</i> . ArXiv:2410.19168 [eess].	
	Mardhiyah Sanni, Tassallah Abdullahi, Devendra D. Kayande, Emmanuel Ayodele, Naome A. Etori, Michael S. Mollé, Moshood Yekini, Chibuzor Okocha, Lukman E. Ismaila, Folafunmi Omofoye, Boluwatife A. Adewale, and Tobi Olatunji. 2025. <a href="#">Afrispeech-Dialog: A Benchmark Dataset for Spontaneous English Conversations in Healthcare and Beyond</a> . <i>arXiv preprint</i> . ArXiv:2502.03945 [cs].	
	Ayushman Sarkar, Mohd Yamani Idna Idris, and Zhenyu Yu. 2025. <a href="#">Reasoning in Computer Vision: Taxonomy, Models, Tasks, and Methodologies</a> . <i>arXiv preprint</i> . ArXiv:2508.10523 [cs].	
	Jiatong Shi, Shih-Heng Wang, William Chen, Martijn Bartelds, Vanya Bannihatti Kumar, Jinchuan Tian, Xuankai Chang, Dan Jurafsky, Karen Livescu, Hung-yi Lee, and Shinji Watanabe. 2024. <a href="#">ML-SUPERB 2.0: Benchmarking Multilingual Speech Models Across Modeling Constraints, Languages, and Datasets</a> . <i>arXiv preprint</i> . ArXiv:2406.08641 [cs].	
	Changli Tang, Wenyi Yu, Guangzhi Sun, Xianzhao Chen, Tian Tan, Wei Li, Lu Lu, Zejun Ma, and Chao Zhang. 2023. <a href="#">Salmonn: Towards generic hearing abilities for large language models</a> . <i>arXiv preprint</i> . ArXiv:2310.13289.	
	Bin Wang, Xunlong Zou, Geyu Lin, Shuo Sun, Zhuohan Liu, Wenyu Zhang, Zhengyuan Liu, AiTi Aw, and Nancy F. Chen. 2024. <a href="#">Audiobench: A universal benchmark for audio large language models</a> . <i>arXiv preprint</i> . ArXiv:2406.16020.	
	Bin Wang, Xunlong Zou, Geyu Lin, Shuo Sun, Zhuohan Liu, Wenyu Zhang, Zhengyuan Liu, AiTi Aw, and Nancy F. Chen. 2025. <a href="#">AudioBench: A Universal Benchmark for Audio Large Language Models</a> . <i>arXiv preprint</i> . ArXiv:2406.16020 [cs].	
	Wanqi Yang, Yanda Li, Yunchao Wei, Meng Fang, and Ling Chen. 2025. <a href="#">SpeechR: A Benchmark for Speech Reasoning in Large Audio-Language Models</a> . <i>arXiv preprint</i> . ArXiv:2508.02018 [cs] version: 1.	

723  
724  
725  
726  
727  
728

## A Dataset Details

We utilize a diverse collection of Pan-African speech and text datasets to evaluate semantic reasoning across clinical and general domains. Table 11 provides a consolidated overview of the dataset statistics and accessibility.

Dataset	Primary Domain
AfriSpeech-200 <sup>5</sup>	Clinical/General ASR
AfriSpeech-Dialog <sup>6</sup>	Conversational ASR/SLU
Afri-Names <sup>7</sup>	Named Entity/Commands
Afrispeech-Medical <sup>8</sup>	Clinical Dialogues

Table 11: Summary of datasets. These resources support evaluation across entailment, consistency, plausibility, and accent-conditioned reasoning tasks.

729  
730  
731  
732  
733  
734

**AfriSpeech-200** This corpus contains 67,577 audio–transcript pairs from 2,463 unique speakers across 13 African countries. It serves as the benchmark for reasoning tasks that require high-fidelity transcription of diverse African accents in both medical and everyday contexts.

735  
736  
737  
738  
739  
740

**AfriSpeech-Dialog** This dataset consists of simulated spontaneous conversations. Unlike read-speech corpora, it captures the nuances of natural disfluencies and conversational flow, specifically curated to test the robustness of spoken language understanding (SLU) models.

741  
742  
743  
744  
745  
746

**Afri-Names** A specialized read-speech dataset containing 6,307 samples. It focuses on high-precision segments—specifically numbers, African named entities, and voice commands—spanning 12 accents across 4 countries. It is used primarily to evaluate accent-conditioned reasoning and NER.

747  
748  
749  
750  
751  
752

**Med-Convo-Nig** Sourced from real-world Nigerian doctor–patient tele-consultations, this dataset provides high-stakes clinical dialogues. It is critical for evaluating model performance on local linguistic variations in healthcare-specific semantic tasks, such as clinical consistency and entailment.

<sup>5</sup><https://huggingface.co/datasets/intronhealth/afrispeech-200>

<sup>6</sup><https://huggingface.co/datasets/intronhealth/afrispeech-dialog>

<sup>7</sup><https://huggingface.co/datasets/intronhealth/afri-names>

<sup>8</sup><https://huggingface.co/datasets/intronhealth/med-convo-nig>

## B Human Verification Protocol

All candidate hypotheses produced by the language model were audited by a team of three trained annotators with backgrounds in linguistics and speech technology. The annotators followed a detailed guideline document that emphasised:

- Listening to the entire audio premise, including pauses and prosodic cues, before reading the hypothesis.
- Classifying each hypothesis as supported, contradicted or unsupported based on the audio alone, without using external world knowledge.
- Editing hypotheses that contained hallucinated details, ambiguous wording, or reliance on unstated background information. Edits were constrained to preserve the intended semantic relationship and remain faithful to the original audio.
- Flagging any problematic audio segments (e.g., very low signal-to-noise ratio) for exclusion from the benchmark.

Each hypothesis was seen by two annotators; disagreements were resolved through discussion with a third annotator acting as arbiter. Random spot checks were performed by one of the authors to ensure consistency across the entire corpus. This human verification step proved especially valuable for accented speech and unfamiliar proper names, where automatic generation alone often led to subtle semantic drift.

## C Evaluation Metrics

We evaluate audio–semantic reasoning performance using a combination of classification, calibration, and robustness-oriented metrics, following prior work on audio entailment and audio–language model evaluation. Metrics are computed at the hypothesis level and aggregated per model and dataset.

### C.1 Primary Classification Metrics

For multi-class and binary decision tasks, we report standard classification metrics derived from the confusion matrix.

753  
754  
755  
756  
757  
758  
759  
760  
761  
762  
763  
764  
765  
766  
767  
768  
769  
770  
771  
772  
773  
774  
775  
776  
777  
778  
779  
780  
781  
782  
783  
784  
785  
786  
787  
788  
789  
790  
791  
792  
793  
794  
795

**Accuracy (ACC).** Accuracy measures the proportion of correctly classified instances:

$$ACC = \frac{TP + TN}{TP + TN + FP + FN} \quad (1)$$

where  $TP$ ,  $TN$ ,  $FP$ , and  $FN$  denote true positives, true negatives, false positives, and false negatives, respectively.

Accuracy is reported for all tasks but may obscure class imbalance effects, especially in entailment-style settings.

**Precision (P).** Precision measures the proportion of predicted positives that are correct:

$$P = \frac{TP}{TP + FP} \quad (2)$$

**Recall (R).** Recall measures the proportion of true positives that are correctly identified:

$$R = \frac{TP}{TP + FN} \quad (3)$$

**F1 Score (F1).** The F1 score is the harmonic mean of precision and recall:

$$F1 = \frac{2 \cdot P \cdot R}{P + R} \quad (4)$$

For multi-class tasks (e.g., entailment, neutral, contradiction), we report macro-averaged precision, recall, and F1 unless otherwise stated.

## C.2 Entailment-Aware Accuracy Metrics

Following prior audio entailment benchmarks, we additionally report label-specific accuracies to capture asymmetric error behavior.

**Entailment Accuracy (EACC).**

$$EACC = \frac{\# \text{ correctly predicted entailment instances}}{\# \text{ entailment instances}} \quad (5)$$

**Neutral Accuracy (NACC).**

$$NACC = \frac{\# \text{ correctly predicted neutral instances}}{\# \text{ neutral instances}} \quad (6)$$

**Contradiction Accuracy (CACC).**

$$CACC = \frac{\# \text{ correctly predicted contradiction instances}}{\# \text{ contradiction instances}} \quad (7)$$

These metrics are especially informative for diagnosing model bias toward entailment or over-rejection behavior.

## C.3 Task Applicability of Metrics

The applicability of each metric varies by task:

- **Audio Entailment.** We report ACC, P, R, F1, along with EACC, NACC, and CACC.
- **Audio-Text Semantic Consistency (Binary).** We report ACC, P, R, and F1. Label-specific accuracies reduce to positive and negative class accuracy.
- **Semantic Plausibility Judgment.** We report ACC and F1. Precision and recall are emphasized for the *implausible* class to measure hallucination susceptibility.

### C.3.1 Robustness and Over-Inference Metrics (AfriNames)

For AfriNames-style datasets, which lack rich semantic content, standard NLI metrics are insufficient. Instead, we focus on restraint and robustness.

**Semantic Restraint Accuracy (SRA).** Semantic restraint accuracy measures the proportion of cases in which the model correctly refrains from asserting unsupported semantic content:

$$SRA = \frac{\# \text{ correct neutral or abstain predictions}}{\# \text{ total AfriNames instances}} \quad (8)$$

### C.3.2 Interpretation Across Models

Together, these metrics allow us to characterize:

- Logical inference capability (NLI, consistency),
- Pragmatic and intent-level reasoning,
- Commonsense integration from speech,
- Hallucination propensity and over-inference,
- Robustness to accent and low-semantic-content inputs.

This multi-metric evaluation provides a comprehensive and task-aligned assessment of audio-language models across diverse spoken domains.

## C.4 Handling Multiple Hypotheses per Label

For several datasets and tasks, including Audio-Text Semantic Consistency and Spoken Natural Language Inference, we generate multiple hypotheses per semantic label (e.g., two consistent and two inconsistent hypotheses per audio instance). This

design choice reflects the inherent variability in how a single semantic relation can be linguistically expressed, while maintaining a fixed underlying label.

**Evaluation Strategy.** We adopt a unified evaluation strategy in which all hypotheses sharing the same semantic label are treated equivalently. Specifically, each hypothesis–audio pair is evaluated independently by the model, and the resulting predictions are aggregated at the label level. For binary tasks such as semantic consistency, hypotheses labeled as *consistent* are treated as positive instances, while those labeled as *inconsistent* are treated as negative instances. For ternary tasks such as entailment, hypotheses are grouped into *entails*, *neutral*, and *contradicts* categories.

This approach allows us to preserve hypothesis-level diversity without requiring separate inference runs or task-specific evaluation pipelines.

**Implications for Metrics and Tables.** All reported metrics (Accuracy, Precision, Recall, F1, and class-conditional accuracies) are computed over the full set of hypothesis–audio pairs. As a result, performance tables (e.g., Table 4) summarize model behavior at the *task level*, rather than at the individual hypothesis variant level. Each table corresponds to a single task (e.g., entailment or consistency), aggregating over all hypothesis realizations within that task.

This design ensures that evaluation remains comparable across datasets and models, while avoiding fragmentation into multiple near-duplicate tables.

**Duplicate Hypothesis and Correlation Considerations.** Although multiple hypotheses are generated from the same transcript, they are not duplicates in the lexical sense. Each hypothesis differs in phrasing, abstraction level, or semantic emphasis, even when sharing the same label. Consequently, models must generalize across paraphrastic variation rather than exploit surface-level repetition.

To mitigate concerns about correlation between hypotheses derived from the same audio, we emphasize that: (i) hypotheses are evaluated independently, (ii) metrics are reported in aggregate rather than per-audio averages, and (iii) our primary goal is to assess semantic robustness under linguistic variability rather than estimate per-instance uncertainty.

This protocol follows established practices in natural language inference and paraphrase-based

evaluation, and is particularly appropriate for probing robustness in audio–semantic reasoning under accent, domain, and acoustic variation.

**Summary.** Treating multiple hypotheses per label as equivalent instances enables efficient inference, stable metric estimation, and controlled linguistic diversity, while preserving the integrity and interpretability of task-level evaluation.

## D Model Architectures Table

## E Different LLMs and their Generated Hypotheses

To illustrate qualitative differences among next-token prediction models, we include a set of manually curated examples in Table 13. Each block shows the original transcript followed by hypotheses generated by Llama 3.1 8B, Mistral Large 3 and Qwen 2 7B, annotated according to the corresponding semantic reasoning task. These examples highlight how different model architectures navigate plausibility, entailment, consistency, accent-induced drift and restraint.

Model	Model LLM Text Decoder Size
Qwen2.5-Omni	7B Qwen2.5-7B-Instruct
Qwen2-Audio	7B Qwen2-7B-Instruct
SALMONN	13B Vicuna-13B
Kimi-Audio	12.5B Kimi-LLM-v1
GAMA	7B Vicuna-7B (v1.5)
AudioFlamingo2	3B Qwen2.5-3B
AudioFlamingo3	7B Qwen2.5-7B
MSCLAP 2022	- HTSAT / RoBERTa
MSCLAP 2023	- HTSAT / RoBERTa
LAION-CLAP	- Swin / RoBERTa

Table 12: Architectural specifications of evaluated Audio Language Models.

This table specifies the underlying LLM decoder and the total parameter count (where known) for the 10 models.

## F Hyperparameters

This table captures your specific sampling settings and the retry logic. Note that for CLAP-based models, generation parameters are not applicable because they are similarity-based. All Experiments were ran on a single Nvidia Blackwell B200 and 80GB of RAM

948 **G Prompts**

949 In section we show all the prompts used by the  
 950 Large Language Model and prompts used by the  
 951 Audio Language model.

952 **H CLAP Architecture and Results**

953 **Format**

954 In this section, we describe the Clap Evaluation  
 955 framework shown in Figure 3.

956 **I Prompt Variants (v)**

957 **(v1).**

958 Audio statement verification  
 959 task.  
 960 Does the following statement  
 961 match what is said in the audio?  
 962  
 963 Statement: {hypothesis}  
 964  
 965 Answer with exactly one  
 966 word - either CONSISTENT or  
 967 INCONSISTENT:

968 **(v2).**

969 Listen carefully to the audio  
 970 recording. Then read the  
 971 statement below.  
 972 Your task: Decide if the  
 973 statement MATCHES or CONTRADICTS  
 974 what is said in the audio.  
 975 - If the statement accurately  
 976 reflects what is said in the  
 977 audio, respond: CONSISTENT  
 978 - If the statement contradicts  
 979 or misrepresents what is said in  
 980 the audio, respond: INCONSISTENT  
 981 Think about what you heard in  
 982 the audio before answering.  
 983  
 984 STATEMENT: {hypothesis}  
 985 Your answer (CONSISTENT or  
 986 INCONSISTENT):

987 **(v3).**

988 You are given an audio recording  
 989 and a text statement.  
 990 Determine whether the text is  
 991 consistent with the meaning  
 992 conveyed in the audio.  
 993 Respond with one of the following

labels only: 994  
 CONSISTENT 995  
 INCONSISTENT 996  
 STATEMENT: 997  
 {hypothesis} 999

**J Prompt Selection** 1000

Table 17 compares three prompt variants for the  
 1001 semantic consistency task. We report overall accu-  
 1002 racy, precision, recall, and macro F1, along with  
 1003 class-specific accuracies for the CONSISTENT and  
 1004 INCONSISTENT labels. 1005

## Semantic Restraint / Over-Inference Prompt

**Purpose:** Generate hypotheses to test whether models correctly withhold inference when audio content is minimal.  
**Methodological Value:** Measures hallucination/over-inference rates and provides a clean signal for semantic restraint.

**System Prompt:** You are a careful evaluator of spoken language meaning. You are given a verbatim transcript of a very short spoken audio recording. This audio contains LIMITED semantic content. Your task is to generate hypotheses that test whether a model can correctly WITHHOLD inference.

**Task:** Generate the following:

- **SUPPORTED hypotheses (2x):** Clearly supported by the audio; minimal and cautious.
- **UNSUPPORTED hypotheses (2x):** Likely to tempt a model to over-infer; not supported by this specific audio.

**Constraints:**

- Do not quote/paraphrase; no meta-language (“the speaker says”).
- Do not add roles, topics, intent, or domains unless explicitly supported.
- **Prohibited:** Explicit negation terms (“no”, “not”, “never”, “without”).

**Output Format (JSON):** { "supported": ["...", "..."], "unsupported": ["...", "..."] }

## Accent-Conditioned Semantic Drift Prompt

**Purpose:** Test if models infer different meanings from similar utterances spoken with different accents.  
**Methodological Value:** Measures fairness gaps and semantic drift triggered by non-semantic audio features.

**System Prompt:** You are evaluating semantic stability. This task tests whether models infer DIFFERENT meanings from similar short utterances spoken with different accents or pronunciations.

**Task:**

- **ACCENT-INVARIANT (4x):** Truth value depends only on semantics, not speaker identity.
- **ACCENT-SENSITIVE LURES (4x):** Incorrect inferences likely caused by accent or training bias.

**Constraints:**

- Do not assume nationality, ethnicity, gender, or location.
- Do not use explicit negation terms; no quoting the transcript.

**Output Format (JSON):** { "accent\_invariant": [...], "accent\_sensitive\_lures": [...] }

## Audio Entailment

**System Prompt:** You are a helpful assistant with expert knowledge in spoken language understanding and parliamentary discourse. Generate hypotheses for a Spoken Natural Language Inference (NLI) task based on the provided institutional transcript.

**Instructions:** Generate three hypotheses for each:

- **Entailment:** Definitely true given the meaning of the spoken audio.
- **Neutral:** Might be true but cannot be determined from audio alone.
- **Contradiction:** Definitely false given the meaning of the audio.

**Constraints:**

- Reflect semantic inference, not surface wording; do not quote the transcript.
- **Prohibited:** Explicit negation terms (“no”, “not”, “never”).

**Output Format (JSON):** { "entailment": [...], "neutral": [...], "contradiction": [...] }

## Audio–Text Semantic Consistency Prompt

**System Prompt:** You are assisting in the construction of an audio–text semantic consistency dataset using parliamentary audio transcripts.

**Task:** Generate four text statements:

- **Consistent (2x):** Semantically aligned with the audio.
- **Inconsistent (2x):** Semantically conflicting with the audio.

**Constraints:**

- Concern institutional roles, procedures, or formal discourse.
- Do not quote or restate the transcript; do not use explicit negation words.

**Output Format (JSON):** { "consistent": ["...", "..."], "inconsistent": ["...", "..."] }

Dataset / Task	Model	Transcript and Generated Hypotheses
<b>AfriNames — Accent Drift (Over-Inference)</b>		
<i>Transcript:</i> “In the environmental assessment conducted over 34 months, researchers identified 24 endangered species and proposed a . . .”		
	Llama 3.1 8B	<b>Accent-Invariant:</b> The assessment identified multiple endangered species requiring protection. <b>Accent-Sensitive Lure:</b> The researchers are likely affiliated with a prestigious Western university.
	Mistral Large 3	<b>Accent-Invariant:</b> The study revealed significant threats to biodiversity. <b>Accent-Sensitive Lure:</b> The findings were shaped by international conservation agendas.
	Qwen 2 7B	<b>Accent-Invariant:</b> Several species were found to be at risk of extinction. <b>Accent-Sensitive Lure:</b> The research was conducted in an urbanized region.
<b>AfriNames — Accent Restraint (Semantic Minimality)</b>		
<i>Transcript:</i> “The 1921 census projects a population surge to 488 million, indicating a 4% growth rate influenced by immigration.”		
	Llama 3.1 8B	<b>Supported:</b> The population is projected to increase. <b>Unsupported:</b> The census results will directly influence national economic policy.
	Mistral Large 3	<b>Supported:</b> Immigration contributes to population growth. <b>Unsupported:</b> The census was designed to justify housing reforms.
	Qwen 2 7B	<b>Supported:</b> A population surge is anticipated. <b>Unsupported:</b> The growth rate is unusually high for a developed country.
<b>AfriSpeech-200 — Semantic Consistency</b>		
<i>Transcript:</i> “This study builds on her previous work examining what qualities and skills make for stronger middle-grade science teachers.”		
	Llama 3.1 8B	<b>Consistent:</b> The study focuses on identifying characteristics of effective science teachers. <b>Inconsistent:</b> The study explores the impact of dance training on teachers.
	Mistral Large 3	<b>Consistent:</b> The research examines skills linked to strong science instruction. <b>Inconsistent:</b> The work analyzes athletic performance in schools.
	Qwen 2 7B	<b>Consistent:</b> The paper investigates qualities that improve science teaching. <b>Inconsistent:</b> The research evaluates music education programs.
<b>AfriSpeech-200 — Audio Entailment</b>		
<i>Transcript:</i> “Snow arriving from the north later tomorrow, moving south through Thursday morning may lead to some travel disruption.”		
	Llama 3.1 8B	<b>Entailment:</b> Weather conditions may disrupt travel over the next two days. <b>Contradiction:</b> Travel will not be affected by weather conditions.
	Mistral Large 3	<b>Entailment:</b> Snowfall could interfere with transportation schedules. <b>Contradiction:</b> Clear weather will ensure uninterrupted travel.
	Qwen 2 7B	<b>Entailment:</b> Adverse weather may impact travel plans. <b>Contradiction:</b> No travel disruptions are expected.
<b>AfriSpeech-200 — Semantic Plausibility</b>		
<i>Transcript:</i> “Not everyone can run a business effectively, so it is important that younger shoemakers are trained to be recruited by big companies.”		
	Llama 3.1 8B	<b>Plausible:</b> Training increases employment opportunities for younger shoemakers. <b>Implausible:</b> Large companies avoid hiring trained shoemakers.
	Mistral Large 3	<b>Plausible:</b> Professional training prepares shoemakers for industry roles. <b>Implausible:</b> Shoemaking skills are irrelevant to corporate recruitment.
	Qwen 2 7B	<b>Plausible:</b> Skill development improves recruitment prospects. <b>Implausible:</b> Shoemaking is no longer valued by employers.

Table 13: Qualitative examples illustrating how different large language models generate task-specific hypotheses from the same spoken input. Each block presents the original transcript followed by model-generated hypotheses corresponding to the semantic reasoning task.

Model	Max New Tokens	Temp	Top-K	Top-P	Audio Temp/K
Qwen2.5-Omni	512	0.0	5	-	-/-
Qwen2-Audio	512	0.0	5	-	-/-
SALMONN	512	-	-	-	-/-
Kimi-Audio	512	0.0	5	-	0.8 / 10
GAMA	400	0.1	-	0.95	-/-
AudioFlamingo2	512	0.0	5	-	-/-
AudioFlamingo3	512	0.0	5	-	-/-
LAION-CLAP	-	-	-	-	-/-
MSCLAP 2023	-	-	-	-	-/-
MSCLAP 2022	-	-	-	-	-/-

Table 14: Inference hyperparameters. Generative models employ a greedy retry strategy (top\_k=1) if initial sampling fails. CLAP models use similarity-based retrieval.

Prompt 1: Semantic Restraint / Over-Inference Generation
<p>You are a careful evaluator of spoken language meaning.  You are given a verbatim transcript of a very short spoken audio recording.  This audio contains LIMITED semantic content. Your task is to generate hypotheses that test whether a model can correctly WITHHOLD inference when the audio does not provide enough evidence.</p> <p><b>TASK: Generate the following:</b></p> <ol style="list-style-type: none"> <li><b>SUPPORTED hypotheses (2 items)</b> – Statements clearly supported; minimal and cautious.</li> <li><b>UNSUPPORTED hypotheses (6 items)</b> – Statements that sound reasonable but are NOT supported; designed to tempt over-inference.</li> </ol> <p><b>CONSTRAINTS:</b></p> <ul style="list-style-type: none"> <li>Do NOT quote/paraphrase transcript or describe what the speaker "says."</li> <li>Do NOT add roles, topics, locations, intent, or domains unless explicitly supported.</li> <li>Avoid explicit negation terms ("no," "not," "never").</li> </ul> <p><b>GOAL:</b> Unsupported hypotheses should test for: Invented topics, intent, social roles, domains, and situational context.</p> <p><b>OUTPUT FORMAT (JSON):</b>  { "supported": ["...", "..."], "unsupported": ["...", "...", "...", "...", "...", "..."] }</p> <p><b>TRANSCRIPT:</b> {{TRANSCRIPT}}</p>

Table 15: Prompt used to generate diagnostic items for evaluating model hallucination and over-inference.

Prompt 2: Accent-Conditioned Semantic Drift Generation
<p>You are evaluating semantic stability in spoken language understanding.  IMPORTANT: This task tests whether models infer DIFFERENT meanings from similar short utterances spoken with different accents or pronunciations.</p> <p><b>TASK: Generate the following:</b></p> <ol style="list-style-type: none"> <li><b>ACCENT-INVARIANT hypotheses (4 items)</b> – Truth should NOT depend on accent or speaker identity; rely only on semantic content.</li> <li><b>ACCENT-SENSITIVE LURE hypotheses (4 items)</b> – Statements models might incorrectly infer due to accent, pronunciation, or training bias.</li> </ol> <p><b>CONSTRAINTS:</b></p> <ul style="list-style-type: none"> <li>Do NOT assume speaker nationality, ethnicity, gender, age, or location.</li> <li>Do NOT quote/paraphrase. Each hypothesis must be one complete sentence.</li> <li>Avoid explicit negation terms.</li> </ul> <p><b>GOAL:</b> Lures should test for: Assigned social roles, geographic/cultural backgrounds, and injected domain meanings.</p> <p><b>OUTPUT FORMAT (JSON):</b>  { "accent_invariant": [...], "accent_sensitive_lures": [...] }</p> <p><b>TRANSCRIPT:</b> {{TRANSCRIPT}}</p>

Table 16: Prompt used to generate diagnostic items for evaluating fairness and stability under accent variation.

### Audio Semantic Plausibility Prompt

**System Prompt:** You are given a transcript of a spoken medical audio recording.

**Task:** Generate four statements:

- **Plausible (2x):** Align with the medical context and clinical commonsense.
- **Implausible (2x):** Unlikely given the audio context and medical norms.

**Constraints:**

- Plausibility judgments may rely on medical commonsense.
- Do not quote the transcript; do not use explicit negation.

**Output Format (JSON):** { "plausible": ["...", "..."], "implausible": ["...", "..."] }

### ALM Prompt 1: Audio Entailment (Zero-Shot Classification)

**Context:** Evaluation of logical inference between a raw audio signal and a text hypothesis.

**System Prompt:** You are an Audio Reasoning Agent. You are given an audio recording and a hypothesis. Determine the logical relationship between them.

**Task:** Determine whether the hypothesis is:

- **Entailed:** The hypothesis is a direct logical consequence of the audio.
- **Contradicted:** The hypothesis is logically impossible given the audio.
- **Neutral:** The hypothesis is plausible but neither supported nor refuted by the audio.

**Constraint:** Respond with exactly one label from the following set: {entailment, contradiction, neutral}.

**Input Format:** Audio: <audio\_signal> | Hypothesis: {{HYPOTHESIS}}

### ALM Prompt 2: Semantic Consistency (Binary Alignment)

**Context:** Determining the semantic alignment between auditory evidence and a descriptive statement.

**System Prompt:** Given an audio recording and a statement, determine whether the statement is semantically consistent with the audio.

**Constraint:** Respond with exactly one label: {consistent, inconsistent}. Do not provide explanations.

**Input Format:** Audio: <audio\_signal> | Statement: {{STATEMENT}}

### ALM Prompt 3: Semantic Plausibility (Contextual Reasoning)

**Context:** Assessing if a statement is likely/reasonable within the situational context of the audio.

**System Prompt:** Given an audio recording and a statement, determine whether the statement is plausible given the audio context and general world knowledge.

**Constraint:** Respond with exactly one label: {plausible, implausible}.

**Input Format:** Audio: <audio\_signal> | Statement: {{STATEMENT}}

Dataset	Prompt Variant	Acc.	Prec.	Rec.	F1	Acc. (Con.)	Acc. (Inc.)
AfriSpeech-200	AudioFlamingo3 (v1)	0.50	0.13	0.25	0.17	0.00	1.00
AfriSpeech-200	AudioFlamingo3 (v2)	0.53	0.52	0.36	<b>0.28</b>	0.07	1.00
AfriSpeech-200	AudioFlamingo3 (v3)	0.53	0.31	0.21	0.16	0.06	1.00
AfriSpeech-General	AudioFlamingo3 (v1)	0.50	0.17	0.33	0.22	0.00	1.00
AfriSpeech-General	AudioFlamingo3 (v2)	0.54	0.24	0.16	0.14	0.09	1.00
AfriSpeech-General	AudioFlamingo3 (v3)	0.76	0.42	0.38	<b>0.37</b>	0.52	1.00
Medical	AudioFlamingo3 (v1)	0.50	0.17	0.33	0.22	0.00	1.00
Medical	AudioFlamingo3 (v2)	0.53	0.31	0.21	0.16	0.05	1.00
Medical	AudioFlamingo3 (v3)	0.64	0.79	0.64	<b>0.58</b>	0.28	1.00

Table 17: Prompt ablation for AudioFlamingo3 on the semantic consistency task. Best macro F1 per dataset is bolded.

## CLAP Evaluation Framework

**Methodology:** Unlike generative ALMs, CLAP evaluates semantic reasoning through similarity-based alignment between audio embeddings and templated text hypotheses.

**Templated Hypothesis Generation:** For each task, CLAP generates task-specific templates to transform labels into natural language assertions:

- **Consistency:** “Given the audio, the following statement is consistent: {hypothesis}”
- **Entailment:** “Given the audio, the following statement is true: {hypothesis}”
- **Plausibility:** “Given the audio, the following statement is plausible: {hypothesis}”

**Inference Mechanism:** The model computes cosine similarity scores  $S(a, t_i)$  between the audio embedding ( $a$ ) and each templated hypothesis embedding ( $t_i$ ). The final prediction is determined by:

$$\text{Label} = \arg \max_i S(a, t_i)$$

### Data Schema (Output JSON):

- scores: Vector of similarity scores for each label option (e.g., *Consistent* vs. *Inconsistent*).
- best\_match\_idx: Index of the hypothesis template with the highest similarity score.
- best\_match\_hypothesis: The full raw text of the highest-scoring templated statement.
- best\_match\_label: The categorical label extracted from the winning template.
- pred: The binary/multiclass prediction indicator for the sample.

Figure 3: The CLAP evaluation pipeline. This framework adapts contrastive audio-text models for reasoning tasks by wrapping hypotheses in semantic templates and selecting labels based on embedding similarity.

ALM	Acc $\uparrow$	P	R	F1	E-Acc	N-Acc	C-Acc
AudioFlamingo2	0.3109	0.1036	0.3333	0.1581	0.0000	1.0000	0.0000
AudioFlamingo3	0.4663	0.5368	0.4802	0.4872	0.2740	0.4333	0.7333
Kimi	0.3057	0.6168	0.3238	0.2490	0.0548	0.8167	0.1000
Qwen2.5-Omni	0.4767	0.6568	0.4795	0.4673	0.4384	0.7667	0.2333
Qwen2-Audio	0.3523	0.5423	0.3580	0.3036	0.2740	0.7500	0.0500

Table 18: Zero-shot performance on AfriSpeech Medical Entailment. All metrics are macro-averaged where applicable.  $\uparrow$  indicates higher is better. The models struggle to caption and also reason all in the same prompt.

## Prompt: Spoken Natural Language Inference

You are evaluating Spoken Natural Language Inference (Spoken NLI).

You are given: (1) an audio recording (premise), (2) a text hypothesis.

### Step 1 — AUDIO CAPTION (evidence only):

Write a short caption of what is explicitly said in the audio.

- Use 1–2 sentences.
- Do NOT infer unstated details or add background knowledge.
- If audio is unclear, say “unclear” rather than guessing.

### Step 2 — REASONING (use caption as evidence):

Using ONLY the caption from Step 1 as evidence, determine whether the hypothesis is: ENTAILMENT, CONTRADICTION, or NEUTRAL.

### Output format:

CAPTION: <your caption>

LABEL: <ENTAILMENT|CONTRADICTION|NEUTRAL>

Hypothesis: “<HYPOTHESIS\_TEXT>”