Convolutional Transformer-Based Image Compression

Bouzid Arezki L2TI Laboratory University Sorbonne Paris Nord Villetaneuse, France bouzid.arezki@edu.univ-paris13.fr Fangchen Feng L2TI Laboratory University Sorbonne Paris Nord Villetaneuse, France fangchen.feng@univ-paris13.fr Anissa Mokraoui L2TI Laboratory University Sorbonne Paris Nord Villetaneuse, France anissa.mokraoui@univ-paris13.fr

Abstract—In this paper, we present a novel transformer-based architecture for end-to-end image compression. Our architecture incorporates blocks that effectively capture local dependencies between tokens, eliminating the need for positional encoding by integrating convolutional operations within the multi-head attention mechanism. We demonstrate through experiments that our proposed framework surpasses state-of-the-art CNN-based architectures in terms of the trade-off between bit-rate and distortion and achieves comparable results to transformer-based methods while maintaining lower computational complexity.

Index Terms—Image Compression, Rate-Distortion, Transformer, Transform Coding, Attention Mechanism.

I. INTRODUCTION

Transform coding is a widely employed method for compressing images and serves as the foundation for several popular coding standards like JPEG. Codecs that utilize transform coding typically consist of three components for lossy compression: transform, quantization, and entropy coding. These components have seen advancements through the application of deep neural networks and end-to-end training, as evidenced by various studies [1]–[6].

Among the early works, the authors of [1] introduced a CNN-based two-level hierarchical variational autoencoder with a hyper-prior serving as the entropy model. This architecture comprises two sets of encoders/decoders one for the generative model and another for the hyper-prior model.

Recently, transformers [7] have demonstrated remarkable success in computer vision, including neural image compression. The authors of [8] incorporated the attention mechanism into the image compression framework by introducing self-attention in the hyper-prior model. Additionally, More sophisticated Swin block [9] in both the generative and hyper-prior models [10], utilizing shift window-based attention to confine attention to local windows. Unlike convolutional neural networks, transformers possess the ability to adapt their receptive field based on the task, with the attention mechanism's capacity to handle global context. This enhanced understanding of global information enables the capture of long-range dependencies in image compression applications.

Positional encoding holds significant importance in transformers. In the original ViT transformer [7], images are divided into non-overlapping patches, each mapped to a token. The standard transformer layers then process the entire token sequence simultaneously. Therefore, positional encoding plays a crucial role in preserving the sequence order and various approaches have been proposed to better model the positional information and maintain local context [11]–[13]. In the context of image compression, positional encoding has demonstrated benefits in terms of Rate-Distortion (RD) performance, as shown in works such as [8], [10].

Despite its advantages, employing positional encoding in transformers can increase the dimensionality of embeddings, leading to higher computational costs during training and limiting model flexibility. Recently, the authors of [14] demonstrated that positional encoding can be omitted in the attention module for image classification without any performance drop. They achieved this by introducing convolution in the tokenization process of patches and the self-attention block to preserve local spatial information. This combination of convolution and the attention mechanism leverages the advantages of both convolutional neural networks and transformers.

In this paper, we introduce a novel image compression framework called SwinNPE. It's built upon our proposed *convolutional Swin block*, which integrates patch convolution and shift window-based attention in Swin, eliminating the requirement for positional encoding.

We believe that this framework excels in capturing spatial contextual information more effectively. Preliminary experiments demonstrate that SwinNPE achieves comparable results to the SwinT architecture [10] while eliminating the need for positional encoding and utilizing fewer parameters. Some of the results of this paper have been presented at [15].

II. PROPOSED FRAMEWORK

The proposed SwinNPE uses the same architecture as in [10], which is shown in Figure 1. Specifically, the input image x is first encoded by the generative encoder $y = g_a(x)$, and the hyper-latent $z = h_a(y)$ is obtained. The quantized version of the hyper-latent \hat{z} is modeled and entropy-coded with a learned factorized prior to passe through $h_s(\hat{z})$ to obtain μ and σ which are the parameters of a factorized Gaussian distribution $P(y|\hat{z}) = \mathcal{N}(\mu, diag(\sigma))$ to model y. The quantized latent $\hat{y} = Q(y-\mu)+\mu$ is finally entropy-coded (Arithmetic encoding/decoding AE/AD) and sent to $\hat{x} = g_a(\hat{y})$ to reconstruct the image \hat{x} . We use the classical strategy of adding uniform noise to simulate the quantization operation (Q) which makes the operation differentiable. The channelwise autoregressive block [2], [3] is designed to learn the auto-regressive prior which factorizes the distribution of the latent as a product of conditional distributions incorporating prediction from the causal context of the latents [4]–[6].

The generative and the hyper-prior encoder, g_a and h_a , are built with the patch merge block and the convolutional Swin block. The patch merge block contains the *Depth-to-Space* operation [10] for down-sampling, a normalization layer, and a linear layer to project the input to a certain depth C_i . In g_a , the depth C_i of the latent representation increases as the network gets deeper which allows for getting a more abstract representation of the image. The size of the latent representation decreases accordingly. In each stage, we downsample the input feature by a factor of 2.

The convolutional Swin block proposed in this work is an extension of the Swin cell [9], as illustrated in Fig. 3. Instead of employing position-wise linear projections, we utilize convolutions to project the K, Q, and V matrices within the multi-head attention block. Rather than relying on hand-crafted positional encoding, we leverage the convolution layer to capture positional information. More specifically, following [14], we reshape the tokens into 2D dimensions and apply 2D-convolution and flattening operation to get tokens more sensitive to spatial context as illustrated in Fig. 2:

$$K, Q, V =$$
Flatten(Conv2d(Reshape2D(x))) (1)

To achieve parameter efficiency, we employ depth-wise separable convolution [14]. Specifically, the depth-wise separable convolution performs a 2D convolution independently in each feature channel. The results are then concatenated and passed through another convolution layer. This approach reduces the number of parameters and computations while enhancing representational efficiency, as it operates not only on spatial dimensions but also on the depth dimension. Importantly, it should be noted that the proposed block is not limited to convolution operations; different forms of convolution are possible [16], [17], making the convolutional Swin block highly adaptable. Unlike the convolutional attention block mentioned in [14], we retain the shift window structure, which facilitates cross-window connections.

The generative and hyper-prior decoders, denoted as g_s and h_s respectively, are constructed using the patch split block and the convolutional Swin block. In the patch split block, we reverse the merging sequence and *Space-to-Depth* operation [10] for up-sampling.

III. EXPERIMENT AND ANALYSIS

A. Experiment configuration

This section presents an assessment of the SwinNPE architecture and a comparison of its image compression results against state-of-the-art approaches. The SwinNPE was trained on the CLIC2020 training set for 3.3 million steps. During training, each batch consisted of eight randomly cropped images with a size of 256×256 pixels.



Fig. 1. Network architecture of our proposed SwinNPE.

The SwinNPE's performance was evaluated on the Kodak and JPEG-AI test dataset [18], [19] and we center-cropped all images to multiples of 256 to avoid padding. We choose the following loss function to optimize the trade-off between the bit-rate R and the quality of reconstruction D which corresponds to the Mean Squared Error (MSE) in RGB color space:

$$L = D + \beta R, \tag{2}$$

with $\beta \in \{0.003, 0.001, 0.0003, 0.0001\}$.

The schedule learning rate starts at 10^{-4} and the hyperparameters of the architecture shown in Fig. 1 are as follows: $(d_1, d_2, d_3, d_4, d_5, d_6) = (2, 2, 6, 2, 5, 1), (w_g, w_g) =$ $(8, 8), (w_h, w_h) = (4, 4),$ and $(C_1, C_2, C_3, C_4, C_5, C_6) =$ (128, 192, 256, 320, 192, 192). For the autoregressive model, we use the model proposed in [6] with 10 slices. The kernel size in all convolutional Swin blocks for depth-wise separable convolution is set to 3.

B. Analysis

We compare our proposed SwinNPE model with the results of two transformers-based architectures [8], [10] and some of the most used CNN-based image compression architectures and standard codecs. The rate-distortion curves of different methods are shown in Figure 4 and Figure 5 on the Kodak dataset [18] and JPEG-AI test-set [19] respectively. In these two figures, the PSNR and the rate shown are the average values across all images of the respective datasets. We summarize the number of parameters and GMACs of the tested transformer-based architectures in Table I where we also illustrate the Bijønteguard metric [20] using the SwinT-CHARM as the reference for the Kodak dataset [18].

From Figure 4, we can clearly see that the SwinNPE outperforms all of the tested CNN-based architectures in terms of the bit-rate/distortion tradeoff. It is particularly interesting to notice that our proposed approach obtains almost the same results as Entroformer [8] (orange dashed line in Figure 4) with much fewer model parameters (see Table I). Specifically, the saving bit-rate of SwinNPE is 5.46% less than SwinT-CHARM (optimal saving bit-rate) which is at the same level as Entroformer with 4.33% more bit-rate saving compare to SwinT-CHARM. We argue that it is due to the fact that the convolutional layer in the proposed convolutional Swin block can capture the local contextual information. From Figure 4 and Figure 5, we can see that with fewer parameters, the proposed SwinNPE has results comparable to SwinT-CHARM on both datasets. We emphasize that our proposed architecture is particularly advantageous compared to SwinTbased architecture without positional encoding ¹ validating the advantages of combining convolutions and transformers for image compression.

Figure 6 provides the Rate-Distortion (RD) curves on each image of the Kodak dataset [18]. Each curve presents the evaluation of an image with different versions of β value (i.e. different SwinNPE models). As expected, experiments with the same β values reveal variability in PSNR and rate values across different images. From the curves, a significant difference can be seen between images, highlighting the substantial discrepancy in results when using the same approach on different images. This observation highlights the dependence of the results on the individual characteristics of the images in the dataset.

We inspect the visual quality in Figure 7 of the proposed approach with a standard codec as a reference. Figure 7 (a) presents a crop of one original image (K24) from the Kodak dataset [18]. Figure 7 (b) compares the reconstructed cropped image using JPEG2000 with our method, showing that Swin-NPE preserves more details even if the bit-rate is smaller than those of JPEG2000.

IV. CONCLUSION

This paper introduces SwinNPE, an image compression model based on transformers that utilizes convolutional Swin blocks instead of positional encoding. SwinNPE achieves comparable performance to state-of-the-art methods while employing fewer parameters and surpassing CNN-based architectures.

The convolutional Swin block proposed in this work enables enhanced utilization of spatial context without relying on positional encoding, thereby providing increased flexibility and reducing the number of parameters.

In future research, it would be interesting to explore the utilization of diverse convolution operations and sizes within the SwinNPE model. This exploration could enable more precise modeling of complex spatial relationships and patterns, ultimately leading to improved image compression performance.

Furthermore, integrating the convolution operation into the patch merge/split module could leverage the advantages of CNNs. The incorporation of convolutional Swin blocks in the SwinNPE model offers a promising avenue for developing efficient and effective transformer-based models for image compression.

REFERENCES

- Johannes Ballé, David Minnen, Saurabh Singh, Sung Jin Hwang, and Nick Johnston. Variational image compression with a scale hyperprior. 6th International Conference on Learning Representations (ICLR), 2018.
- [2] Mu Li, Wangmeng Zuo, Shuhang Gu, Debin Zhao, and David Zhang. Learning convolutional networks for content weighted image compression. IEEE/CVF Conference on Computer Vision and Pattern Recognition, pages 3214–3223, 2018.
- [3] Fabian Mentzer, Eirikur Agustsson, Michael Tschannen, Radu Timofte, and Luc Van Gool. Conditional probability models for deep image compression. IEEE/CVF Conference on Computer Vision and Pattern Recognition, pages 4394–4402, 2018.
- [4] David Minnen, Johannes Ballé, and George D Toderici. Joint autoregressive and hierarchical priors for learned image compression. Advances in Neural Information Processing Systems, 2018.
- [5] Jooyoung Lee, Seunghyun Cho, and SeungKwon Beack. Contextadaptive entropy model for end-to- end optimized image compression. International Conference on Learning Representations, 2019.
- [6] David Minnen and Saurabh Singh. Channel-wise autoregressive entropy models for learned image compression. IEEE International Conference on Image Processing (ICIP), pages 3339–3343, 2020.
- [7] Alexey Dosovitskiy, Lucas Beyer, Alexander Kolesnikov, Dirk Weissenborn, Xiaohua Zhai, Thomas Unterthiner, Mostafa Dehghani, Matthias Minderer, Georg Heigold, Sylvain Gelly, Jakob Uszkoreit, and Neil Houlsby. An image is worth 16x16 words: Transformers for image recognition at scale. International Conference on Learning Representations, 2021.
- [8] Yichen Qian, Ming Lin, Xiuyu Sun, Tan Zhiyu, and Rong Jin. Entroformer: A transformer-based entropy model for learned image compression. International Conference on Learning Representations (ICLR), 02 2022.
- [9] Z. Liu, Y. Lin, Y. Cao, H. Hu, Y. Wei, Z. Zhang, S. Lin, and B. Guo. Swin transformer: Hierarchical vision transformer using shifted windows. IEEE/CVF International Conference on Computer Vision (ICCV), pages 9992–10002, Los Alamitos, CA, USA, oct 2021.

¹The results are shown in the ablation studies in [10].



Fig. 2. (a) Convolutional Projection. (b) Convolutional Swin Block.

TABLE I

Performance comparison using Bijønteguard metric [20] for Kodak dataset [18] where Δ PSNR measures the average PSNR difference and % Δ rate the average rate saving in percentage between SwinT-CHARM [10] (selected as the reference network) and another given network. -* GMACs of the corresponding model are not provided

Network	#Param. (M)	GMACs	Positional Encoding	Bijønteguard Metric	
				Δ PSNR	$\%\Delta$ rate
SwinT-CHARM [10]	32	223	Positional Relative Encoding 2D	0	0%
Entroformer [8]	142.7	-*	Positional Relative Encoding 2D + Diamond	-0.228	4.33%
SwinNPE (Ours)	27	178	-	-0.311	5.46%



Fig. 3. (a) The attention mechanism scheme for multi-head attention (b) The attention mechanism scheme for convolutional Swin. DS conv means depthwise separable convolution.

- [10] Yinhao Zhu, Yang Yang, and Taco Cohen. Transformer-based transform coding. International Conference on Learning Representations, 2022.
- [11] Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, L slion Jones, Aidan N Gomez, Ł ukasz Kaiser, and Illia Polosukhin. Attention is all you need. I. Guyon, U. Von Luxburg, S. Bengio, H. Wallach, R. Fergus, S. Vishwanathan, and R. Garnett, éditeurs, Advances in Neural Information Processing Systems, volume 30. Curran Associates, Inc., 2017.
- [12] Peter Shaw, Jakob Uszkoreit, and Ashish Vaswani. Self attention with relative position representations. Proceedings of the Conference. of the North American Chapter of the Association for Computational Linguistics : Human Language Technologies, Volume 2 (Short Papers), pages 464–468. Association for Computational Linguistics, Juin 2018.
- [13] Xiangxiang Chu, Zhi Tian, Bo Zhang, Xinlong Wang, and Chunhua



Fig. 4. SwinNPE achieves nearly the same results as Entroformer [8] and SwinT-CHARM [10] that relying on Positional encoding and better RD performance than CNNs-based methods Factorized [21], Scale [1], Mean-Scale [4], Joint hyperprior [4] and standard codecs on the Kodak [18] image set.

Shen. Conditional positional encodings for vision transformers. The Eleventh Inter. Conf. on Learning Representations, 2023.

[14] Haiping Wu, Bin Xiao, Noel Codella, Mengchen Liu, Xiyang Dai, Lu Yuan, and Lei Zhang. Cvt: Introducing convolutions to vision transformers. Pro ceedings of the IEEE/CVF International Conference.



Fig. 5. SwinNPE achieves nearly the same results as SwinT-CHARM [10] and better RD performance than standard codecs on the JPEG-AI test-set [19].

on Computer Vision (ICCV), pages 22-31, October 2021.

- [15] Bouzid Arezki, Fangchen Feng, and Anissa Mokraoui, Transformer-Based Image Compression Without Positional Encoding. Compression et Représentation des Signaux Audiovisuels, CORESA, 7-9 juin, 2023, Lille, France.
- [16] Jifeng Dai, Haozhi Qi, Yuwen Xiong, Yi Li, Guodong Zhang, Han Hu, and Yichen Wei. Deformable convolutional networks. Proceedings of the IEEE International Conference. on computer vision, pages 764–773, 2017.
- [17] Lu Chi, Borui Jiang, and Yadong Mu. Fast Fourier convolution. Advances in Neural Information Processing Systems, 33: 4479–4488, 2020.
- [18] Kodak test images. http://r0k.us/ graphics/kodak/, 1999.
- [19] Johannes Ballé, Valero Laparra, and Eero P Simoncelli. End-to-end optimized image compression. 5th International Conference on Learning Representations (ICLR), 2017.
- [20] JPEG-AI Test Images. https://jpegai.github.io/test_images/, 2020.
- [21] Gisle Bjøntegaard. Calculation of average PSNR differences between rd-curves. 2001.

REFERENCES

- Johannes Ballé, David Minnen, Saurabh Singh, Sung Jin Hwang, and Nick Johnston, "Variational image compression with a scale hyperprior," in 6th Inter. Conf. on Learning Representations (ICLR), 2018.
- [2] Mu Li, Wangmeng Zuo, Shuhang Gu, Debin Zhao, and David Zhang, "Learning convolutional networks for content-weighted image compression," in 2018 IEEE/CVF Conference on Computer Vision and Pattern Recognition, 2018, pp. 3214–3223.
- [3] Fabian Mentzer, Eirikur Agustsson, Michael Tschannen, Radu Timofte, and Luc Van Gool, "Conditional probability models for deep image compression," in 2018 IEEE/CVF Conf. on Computer Vision and Pattern Recognition, 2018, pp. 4394–4402.
- [4] David Minnen, Johannes Ballé, and George D Toderici, "Joint autoregressive and hierarchical priors for learned image compression," in Advances in Neural Information Processing Systems, 2018.
- [5] Jooyoung Lee, Seunghyun Cho, and Seung-Kwon Beack, "Contextadaptive entropy model for end-to-end optimized image compression," in *International Conference on Learning Representations*, 2019.
- [6] David Minnen and Saurabh Singh, "Channel-wise autoregressive entropy models for learned image compression," in 2020 IEEE International Conference on Image Processing (ICIP), 2020, pp. 3339–3343.
- [7] Alexey Dosovitskiy, Lucas Beyer, Alexander Kolesnikov, Dirk Weissenborn, Xiaohua Zhai, Thomas Unterthiner, Mostafa Dehghani, Matthias Minderer, Georg Heigold, Sylvain Gelly, Jakob Uszkoreit, and Neil Houlsby, "An image is worth 16x16 words: Transformers for image recognition at scale," in *Inter. Conf. on Learning Representations*, 2021.

- [8] Yichen Qian, Ming Lin, Xiuyu Sun, Tan Zhiyu, and Rong Jin, "Entroformer: A transformer-based entropy model for learned image compression," 02 2022, Inter. Conf. on Learning Representations (ICLR).
- [9] Z. Liu, Y. Lin, Y. Cao, H. Hu, Y. Wei, Z. Zhang, S. Lin, and B. Guo, "Swin transformer: Hierarchical vision transformer using shifted windows," in 2021 IEEE/CVF International Conference on Computer Vision (ICCV), Los Alamitos, CA, USA, oct 2021, pp. 9992–10002, IEEE Computer Society.
- [10] Yinhao Zhu, Yang Yang, and Taco Cohen, "Transformer-based transform coding," in *Inter. Conf. on Learning Representations*, 2022.
- [11] Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Ł ukasz Kaiser, and Illia Polosukhin, "Attention is all you need," in *Advances in Neural Information Processing Systems*, I. Guyon, U. Von Luxburg, S. Bengio, H. Wallach, R. Fergus, S. Vishwanathan, and R. Garnett, Eds. 2017, vol. 30, Curran Associates, Inc.
- [12] Peter Shaw, Jakob Uszkoreit, and Ashish Vaswani, "Self-attention with relative position representations," in *Proceedings of the 2018 Confe.* of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 2 (Short Papers). June 2018, pp. 464–468, Association for Computational Linguistics.
- [13] Xiangxiang Chu, Zhi Tian, Bo Zhang, Xinlong Wang, and Chunhua Shen, "Conditional positional encodings for vision transformers," in *The Eleventh Inter. Conf. on Learning Representations*, 2023.
- [14] Haiping Wu, Bin Xiao, Noel Codella, Mengchen Liu, Xiyang Dai, Lu Yuan, and Lei Zhang, "Cvt: Introducing convolutions to vision transformers," in *Proceedings of the IEEE/CVF Inter. Conf. on Computer Vision (ICCV)*, October 2021, pp. 22–31.
- [15] Fangchen Feng Bouzid Arezki and Anissa Mokraoui, "Transformerbased image compression without positional encoding," in 22ème édition de la conférence Compression et Représentation des Signaux Audiovisuels (CORESA), 2023.
- [16] Jifeng Dai, Haozhi Qi, Yuwen Xiong, Yi Li, Guodong Zhang, Han Hu, and Yichen Wei, "Deformable convolutional networks," in *Proceedings* of the IEEE inter. conf. on computer vision, 2017, pp. 764–773.
- [17] Lu Chi, Borui Jiang, and Yadong Mu, "Fast fourier convolution," Advances in Neural Information Processing Systems, vol. 33, pp. 4479– 4488, 2020.
- [18] Kodak, "Kodak test images," http://r0k.us/graphics/kodak/, 1999.
- [19] JPEG-AI, "Jpeg-ai test images," https://jpegai.github.io/test_images/,
- 2020.[20] Gisle Bjøntegaard, "Calculation of average psnr differences between rd-curves," 2001.
- [21] Johannes Ballé, Valero Laparra, and Eero P Simoncelli, "End-toend optimized image compression," 5th Inter. Conf. on Learning Representations (ICLR), 2017.



Fig. 6. Rate-Distortion (RD) performance of SwinNPE on each image of Kodak [18] dataset.



Fig. 7. (a) One example (K24) of the original image from Kodak dataset [18]. (b) Left: image compressed with JPEG2000 (0.9257 bpp and PSNR: 30.6395 dB). Right: image compressed with the proposed SwinNPE for $\beta = 0.001$ (0.6987 bpp and PSNR: 32.9314 dB).