

Grounding Agent Memory in Contextual Intent

Anonymous ACL submission

Abstract

Deploying large language models in long-horizon, goal-oriented interactions remains challenging because similar entities and facts recur under different latent goals and constraints, causing memory systems to retrieve context-mismatched evidence. We propose **STITCH** (Structured Intent Tracking in Contextual History), an agentic memory system that *indexes* each trajectory step with a structured retrieval cue, *contextual intent*, and retrieves history by matching the current step’s intent. Contextual intent provides compact signals that disambiguate repeated mentions and reduce interference: (1) the current latent goal defining a thematic segment, (2) the action type, and (3) the salient entity types anchoring which attributes matter. During inference, STITCH filters and prioritizes memory snippets by intent compatibility, suppressing semantically similar but context-incompatible history.

For evaluation, we introduce **CAME-Bench**, a benchmark for context-aware retrieval in realistic, dynamic, goal-oriented trajectories. Across CAME-Bench and LongMemEval, STITCH achieves state-of-the-art performance, outperforming the strongest baseline by 35.6%, with the largest gains as trajectory length increases. Our analysis shows that intent indexing substantially reduces retrieval noise, supporting intent-aware memory for robust long-horizon reasoning.¹

1 Introduction

Large language models (LLMs) are deployed in *long-horizon* tasks (Liu et al., 2024) that require agents to track interleaved goals, resolve references to prior information, and coordinate actions over extended trajectories. Such settings arise across diverse applications, including extended human-agent dialogues (Jiang et al., 2024), deep research

¹We will make the codebase and benchmark publicly available upon publication.




Figure 1: **The Challenges of Long-Horizon Agentic Memory.** We identify four capabilities required for robust agentic memory: (A) Incremental Memory Revision (tracking state changes over time); (B) Context-Aware Factual Recall (distinguishing semantically similar facts by context); (C) Context-Aware Multi-Hop Reasoning (resolving implicit references across distracting turns); and (D) Context-Aware Information Synthesis.

workflows (Shao et al., 2024), and autonomous tool-augmented environments (Xie et al., 2024).

To address the complexity of these environments, recent works (e.g., Pan et al., 2025; Xu et al., 2025; Edge et al., 2024) have introduced *agentic memory* mechanisms that organize context online and *retrieve* relevant information at inference time. This retrieval-centric view aligns with the notion of *retrieval cues* in cognitive science (Tulving and Thomson, 1973; Craik and Lockhart, 1972): structured indices that determine which stored context information is accessed. In long-horizon settings, where many steps are semantically similar but contextually distinct, retrieval is bottlenecked by cue

055 quality. Effective agentic memory must construct
056 cues that reliably surface the right context amidst
057 noisy, interference-prone history.

058 However, existing agentic memory systems re-
059 main misaligned with the demands of long-horizon,
060 goal-oriented reasoning in Figure 1. Memory
061 compression techniques (Sarathi et al., 2024; Pan
062 et al., 2025) summarize semantically or tempo-
063 rally adjacent segments but often fail to link *in-*
064 *terleaved, persistent* goal contexts across non-
065 adjacent segments (Figure 1(C)), complicating
066 state tracing (Figure 1(A)) and information syn-
067 thesis (Figure 1(D)). Similarly, knowledge-graph-
068 based memories (Edge et al., 2024; Xu et al., 2025)
069 encode entity-level relations but often lack explicit
070 goal- or episode-level disambiguation, so repeated
071 mentions of the same entities can correspond to dis-
072 tinct latent goals (Figure 1(B)). While long-context
073 LLMs (OpenAI, 2025; Comanici et al., 2025) can
074 attend to extended trajectories, they become ineffec-
075 tive once trajectories exceed context limits and
076 incur substantial overhead for real-time retrieval.

077 To address these limitations, we propose
078 **STITCH** (§2), an agentic memory system that
079 models the latent intent underlying each step of
080 a task trajectory. Grounded in Event Structure The-
081 ory (Zacks and Tversky, 2001), STITCH is moti-
082 vated by the hypothesis that robust recall requires
083 organizing experience by (i) the superordinate goal
084 context and (ii) recurring action categories. We
085 instantiate **contextual intent**, a structured retrieval
086 cue induced online without a fixed ontology: (1)
087 **thematic scope** (§ 2.2.1), a stable segment label
088 tracking the current goal (e.g., “*Day 2 Itinerary*” or
089 “*Model Optimization*”); (2) **event type** (§ 2.2.2), an
090 action label capturing the operation performed (e.g.,
091 “*Rebuttal*”, “*Hyperparameter Tuning*”, “*Price In-*
092 *quiry*”); and (3) **key entity types** (§ 2.2.3), the
093 entity classes that determine which attributes are
094 relevant in-context (e.g., *Metric, Hyperparameter,*
095 *Price, Rating*). Together, these cues explicate con-
096 textual information otherwise ambiguous in the
097 raw trajectory: thematic scope links non-adjacent,
098 goal-consistent steps for multi-hop reasoning, state
099 tracing, and synthesis (Figure 1(C, A, D)), while
100 event and entity typing disambiguate repeated men-
101 tions by anchoring facts to functional roles and
102 expected attributes, improving recall under inter-
103 ference (Figure 1(B)). At inference time, STITCH
104 filters and prioritizes memory snippets by structural
105 compatibility, suppressing semantically similar but
106 context-mismatched content (§ 2.3).

107 A parallel gap lies in how we evaluate long-
108 horizon memory: existing benchmarks rarely test
109 whether models can retrieve the *right fact in the*
110 *right context*. In realistic agentic settings, success
111 is not determined solely by finding semantically
112 relevant text, but by verifying that retrieved infor-
113 mation matches the contextual constraints under
114 which it was stated or requested (e.g., a hotel “price”
115 is only meaningful when conditioned on dates, loca-
116 tion, and room type). Yet current evaluations often
117 sidestep this requirement. First, many benchmarks
118 segment a long trajectory into largely independent
119 mini-episodes or topic blocks (Wu et al., 2024),
120 which makes retrieval effectively local and reduces
121 the need to track global state across interleaved
122 goals. Second, they enforce strict turn-taking be-
123 tween a user and an assistant (Wu et al., 2024;
124 Maharana et al., 2024), where queries are typically
125 answered immediately after they are posed; this
126 adjacency masks the harder case where requests
127 are interleaved, deferred, and resolved only after
128 several intervening steps.

129 To address these evaluation gaps, we introduce
130 **CAME-Bench** (Context-Aware Agent Memory
131 Evaluation Benchmark) (§3), which targets *context-*
132 *aware retrieval* in long, goal-oriented trajec-
133 tories. CAME-Bench stresses this capability along
134 three axes: interleaved, non-turn-taking interaction
135 structure; multi-domain coverage; and controlled
136 difficulty via diverse question types and length-
137 stratified subsets. These choices make dispersed,
138 often implicit constraints necessary for answering
139 and reveal a complementary failure mode obscured
140 in existing evaluations where strong baselines are
141 near-saturated.

142 Our contributions are threefold:

- 143 1. We propose STITCH, an intent-aware, 144
145 domain-agnostic agentic memory system that 146
147 induces contextual intent online and uses in- 148
149 tent compatibility to filter and prioritize re- 150
151 trieved history. 152
- 153 2. We introduce CAME-Bench, a multi-domain 154
155 benchmark for *context-aware retrieval* in 156
157 long, goal-oriented trajectories, with length- 158
159 stratified subsets. 160
- 161 3. Empirically, STITCH consistently outper- 162
163 forms strong long-context and structured- 164
165 memory baselines on CAME-Bench, validat- 166
167 ing the importance of intent-aware retrieval 168
169 for robust long-horizon reasoning. 170

2 Methods

2.1 Contextual Intent Schema

Our approach, **ST**ructured **I**ntent **T**racking in **C**ontextual **H**istory (STITCH), is grounded in Event Structure Theory (Zacks and Tversky, 2001), which argues that humans comprehend extended activity by building event representations that support prediction and memory. A key implication is that extended experience is not treated as a single flat stream: people naturally organize behavior into segments that maintain a coherent goal context, while also recognizing recurring kinds of actions that reappear across contexts. We mirror this organization with three complementary cues induced online from the trajectory (i.e., without assuming a domain-specific ontology), making the representation applicable across task domains. First, a *partonomy* assigns each trajectory step to a *thematic scope*—a segment label that summarizes the current goal context and remains stable until the latent goal shifts (e.g., “Day 2 Itinerary”) (§2.2.1). Second, a *taxonomy* assigns each step an *event type* that captures its basic operation (e.g., “searching”, “comparing”, “booking”) regardless of which segment it occurs in; the label set is derived on the fly and can expand as new operations appear (§2.2.2). Third, to support retrieval of factual details, we extract *key entity types* that identify the classes of information necessary to satisfy the current goal (Talmy, 1975) (e.g., *Price*, *Rating*), providing a lightweight schema template that anchors which details should be surfaced to make progress on the task (§2.2.3). STITCH tracks these signals at each step and uses them as retrieval cues to retrieve the correct context at inference time.

We formalize these cues as *Contextual Intent*, a structured representation of the latent goal used as a retrieval cue. For a task trajectory $T = \{s_1, s_2, \dots, s_n\}$ where each step is a tuple $s_t = (r_t, a_t, \tau_t)$ specifying the acting agent role r_t , a natural-language description of the action a_t , and a timestamp τ_t , we infer a contextual intent tuple $\iota_t = (\sigma_t, \epsilon_t, \kappa_t)$, where σ_t denotes the thematic scope, ϵ_t is the event type, and κ_t represents the set of key entity types.

2.2 Contextual Intent Construction

2.2.1 Thematic Scope Induction.

Event Perception literature suggests that humans naturally segment continuous activity into discrete units at points of maximal feature change, which

correlate strongly with sub-goal completion (Newtson et al., 1977). While this segmentation captures local intent, treating segments in isolation leads to context loss, since coarse-grained goals (the “macro-structure”) often persist across fine-grained boundaries. To model this *partonomy*, we induce a **thematic scope** σ_t that acts as a coarse-grained container for fine-grained steps. Concretely, we use a sliding window in which an LLM predictor \mathcal{M} analyzes the current step s_t with a recent history buffer H_{scope} and the previously induced scope to detect shifts in the latent goal: $\sigma_t = \mathcal{M}_{\text{scope}}(s_t, H_{\text{scope}}, \sigma_{t-1})$. Consistent with findings that “behavior episodes” (Barker and Wright, 1954) are characterized by continuity in setting and mental sphere (Zacks and Tversky, 2001), σ_t remains constant until the model detects a boundary event (i.e., a goal-state divergence). When a boundary is detected by the LLM, a new scope label is induced; otherwise, the step inherits the prior scope (e.g., persisting in “Day 2 Itinerary” for travel, or “Model Optimization” in machine learning). To prevent context overflow while preserving the ongoing episode’s “gist”, we maintain a compressed summary Σ_σ of the current scope online, which is then provided to subsequent scope predictions (see Appendix E.1 for prompts).

2.2.2 Taxonomic Event Labeling.

While thematic scope captures the *episodic* structure of a specific activity, **event labeling** captures *taxonomic* regularities that recur across distinct scopes. We induce event types directly from the trajectory without a pre-defined ontology, mirroring how humans learn event structure via statistical covariation (Avrahami and Kareev, 1994); this allows the taxonomy to naturally adapt to diverse task domains (see Appendix E.1 for prompts).

We adopt a dynamic label-space evolution strategy. First, we generate a seed vocabulary of event types \mathcal{V}_ϵ via zero-shot inference on the initial N_{start} trajectory steps, producing task-appropriate, interpretable labels. During online processing, for each step s_t , we retrieve the top- k_{event} semantically similar labels from \mathcal{V}_ϵ and prompt $\mathcal{M}_{\text{label}}$ to select the best-fitting event label $\epsilon_t = \mathcal{M}_{\text{label}}(s_t, \text{Retrieve}(\mathcal{V}_\epsilon, s_t, k_{\text{event}}))$. If no suitable label is found, we introduce a new label into \mathcal{V}_ϵ . To maintain a compact and distinct taxonomy, we perform periodic refinement every k_{update} steps to consolidate semantically overlapping (near-synonymous) labels.




Figure 2: **Overview of STITCH.** The framework operates in two phases. **Left (§2.2): Contextual Intent Construction.** From a streaming trajectory, the model dynamically induces three structural cues—Thematic Scope (σ_t), Event Type (ϵ_t), and Key Entity Types (κ_t)—to form a *Contextual Intent* tuple ι_t . This structure guides coreference resolution (e.g., resolving “it”) and summary generation to create a structured Memory Snippet. **Right (§2.3): Intent-Aware Retrieval.** During inference, the evaluation query q is mapped to a structured filter configuration F_q . The retrieval engine applies *Label Density Ranking*, prioritizing memories that strictly match the intended structure before ranking by semantic content.

2.2.3 Key Entity Type Extraction.

Events are often defined by interactions between an actor and specific objects or “figures” (Talmy, 1975). To anchor retrieval of factual details, we extract **key entity types** κ_t , representing the *classes* of detailed information required (e.g., distinguishing “Metric” from “Hyperparameter” in research; distinguishing “Price” from “Rating” in travel). This yields a lightweight “schema template” that enhances generalization, enabling retrieval to target the specific entity *types* required by the current intent rather than being misled by ambiguous surface forms with functionally distinct roles. As with event labeling, entity types are induced online without assuming a fixed domain schema, thus ensuring generalization (see Appendix E.1 for prompts).

We maintain a growing label space of entity types \mathcal{V}_κ . For each step, the model identifies necessary semantic entities and maps them to existing types in \mathcal{V}_κ or generates new types if the class is novel $\kappa_t = \mathcal{M}_{\text{entity}}(s_t, \mathcal{V}_\kappa)$. Similar to the event taxonomy, \mathcal{V}_κ undergoes periodic consolidation to merge semantically overlapping entity classes.

Coreference Resolution via Structural Alignment. Extended goal-directed trajectories often rely on implicit references to prior states (e.g.,

“Book it.”). Zacks and Tversky (2001) note that event coherence relies on tracking participants across temporal boundaries. We resolve these references by leveraging the induced partonomic and taxonomic structure. When a step s_t contains ambiguous references, we retrieve a context set C_{align} consisting of prior steps that share the same *thematic scope* σ_t and/or compatible *event types* ϵ_t . This structurally aligned context is then used to rewrite s_t into a disambiguated form $s'_t = \mathcal{M}_{\text{rewrite}}(s_t, C_{\text{align}})$. This ensures that pronouns (e.g., “it”) are resolved to their referents (e.g., “the Apollo Hotel”) prior to storage. We validate the efficacy of this rewriting module via an automated audit of *Entity Resolution Recall*, ensuring that implicit references are correctly grounded to their canonical entity names (see Appendix E.1 for prompt and B for verification details).

2.2.4 Memory Snippet Construction

To support downstream inference, we augment the raw step content with its inferred structural properties. We generate a canonical summary c_t —a concise natural-language description encapsulating the agentic operation and its contextual intent—via $c_t = \mathcal{M}_{\text{sum}}(s'_t, \iota_t)$. The final **Memory Snippet** is defined as $m_t = (s_t, \iota_t, c_t)$. This composite repre-

310 sentation enables retrieval to query the *structure* of
311 the past (via ι_t) alongside the *content* (via c_t).

312 2.3 Intent-Aware Retrieval

313 During inference, rather than relying solely on un-
314 structured semantic similarity, we perform *intent-*
315 *aware* filtering using contextual intent. Given a
316 query q , we prompt an LLM to produce a *filter*
317 *configuration* F_q that specifies target values over
318 the same schema components as ι_t , i.e., $F_q =$
319 $(\mathcal{S}_q, \mathcal{E}_q, \mathcal{K}_q)$, where \mathcal{S}_q is a set of candidate the-
320 matic scopes, \mathcal{E}_q a set of candidate event types,
321 and \mathcal{K}_q a set of key entity types. In practice, the
322 LLM is conditioned on q and the current label in-
323 ventories (i.e., the induced scope labels and the
324 vocabularies \mathcal{V}_ϵ and \mathcal{V}_κ) to ensure that F_q is ex-
325 pressed in the same label space as stored memories.
326 (Prompt templates and examples are provided in
327 Appendix E.1.) This mirrors how humans recall
328 experiences by indexing through a goal episode
329 (partonomy) and/or a recurring operation (taxon-
330 omy), while using expected participants to anchor
331 required factual details.

332 We then rank memory snippets via *structural*
333 *alignment* with F_q , utilizing semantic similarity
334 as a secondary tie-breaker. We employ a *label*
335 *density ranking* strategy, which prioritizes snippets
336 based on the cardinality of their overlap with the
337 filter configuration (i.e., the number of satisfied
338 constraints in ι_t). This strategy serves as a proxy
339 for contextual relevance: it ensures that memory
340 snippets sharing the highest degree of *contextual*
341 *intent* with the query—and therefore possessing
342 the strongest contextual affinity to the user’s in-
343 formation need—are strictly prioritized. Among
344 snippets with equivalent label density, we rank by
345 semantic similarity between the query and content
346 (e.g., $\text{sim}(q, c_t)$). Finally, we return the top- k_{retrieve}
347 memory snippets.

348 3 CAME-Bench

349 We introduce the **Context-aware Agent Memory**
350 **Evaluation Benchmark** (CAME-Bench), a syn-
351 thetic dataset designed to evaluate agentic mem-
352 ory in continuous, goal-oriented trajectories char-
353 acterized by high *contextual interference*. CAME-
354 Bench constructs dense interaction histories where
355 recurring entities and interleaved goals create sig-
356 nificant ambiguity, specifically designed to evalu-
357 ate an agent’s ability to manage context over long
358 horizons.

359 Formally, each benchmark instance consists of
360 a trajectory $T = \{s_1, s_2, \dots, s_n\}$, where each step
361 is defined as $s_t = (r_t, a_t, \tau_t)$. During evaluation,
362 models are presented with a set of free-response
363 questions Q and must generate answers by reason-
364 ing over the full trajectory. To assess robust gen-
365 eralization, CAME-Bench comprises trajectories
366 spanning distinct domains.

367 We construct CAME-Bench according to three
368 design principles: (i) *symbolically grounded causal*
369 *consistency*, where we decouple storyboard plan-
370 ning from surface generation to ensure logically co-
371 herent long-horizon state transitions; (ii) *controlled*
372 *semantic interference*, utilizing a closed-world en-
373 vironment to densely reuse static entities and chal-
374 lenge models to disambiguate fine-grained context;
375 and (iii) *dynamic referential ambiguity*, which ne-
376 cessitates resolving indirect pragmatic references
377 and tracking incremental state updates rather than
378 relying on static retrieval.

379 Based on these principles, we instantiate the
380 benchmark in two domains: **(i) Travel Plan-**
381 **ning**, in which an LLM-simulated assistant collab-
382 orates with a simulated user to construct multi-day
383 itineraries; and **(ii) Debate**, in which two LLM
384 agents advocate opposing positions in evidence-
385 grounded policy argumentation.

386 3.1 Benchmark Curation

387 Inspired by prior work showing that intermediate
388 structured representations improve dataset consis-
389 tency (Rastogi et al., 2020; Eric et al., 2020), we
390 design a four-stage pipeline that decouples sym-
391 bolic planning from natural-language generation.
392 This approach allows us to enforce complex causal
393 dependencies and maintain logically coherent state
394 transitions prior to surface realization.

395 As detailed in Appendix A.1 and A.2, our
396 pipeline consists of: (1) closed-world environment
397 construction, creating a controlled set of static en-
398 tities and knowledge to mitigate contamination; (2)
399 symbolic storyboard planning, where we predefine
400 action spaces and generate symbolic operations
401 (e.g., latent goals, payloads) subject to pragmatic
402 constraints; (3) storyboard-conditional trajectory
403 generation, translating symbolic plans into natu-
404 ral language using LLMs; and (4) pragmatic re-
405 finement, applying referential remodeling and turn
406 segmentation to mimic natural communication pat-
407 terns and increase difficulty. This structured gen-
408 eration enables faithful automatic annotation of
409 evaluation questions.

3.2 Evaluation Questions and Metrics

For each trajectory, we pose four categories of free-response questions that target complementary aspects of context-aware retrieval and long-horizon reasoning (Figure 1). See Appendix A.7 for illustrative examples; Appendices A.3 and A.6 provide details on ground-truth answer generation and human verification.

Type 1: Incremental Memory Revision. Following (Wu et al., 2024), these questions assess the ability to maintain and update entity states as they evolve (e.g., tracking restaurant candidates as they are added or rejected across turns).

Type 2: Context-Aware Factual Recall. These questions test precise information retrieval amidst semantically similar content. Models must disambiguate details that differ only by context (e.g., retrieving a hotel price for Day 1 vs. Day 2).

Type 3: Context-Aware Multi-Hop Reasoning. These questions require resolving referential expressions before retrieval. For example, answering a question about “the dinner reservation I mentioned earlier” requires first identifying the referent, then retrieving associated attributes.

Type 4: Information Synthesis. These questions assess the ability to aggregate information distributed across multiple steps, such as reconstructing a complete itinerary from scattered bookings and visits.

Metrics. We employ answer-set macro-averaged precision, recall, and F1 score. This metric provides a more nuanced assessment for multi-element answers and captures partial credit scenarios better than binary accuracy.

4 Experiments

Benchmarks. We evaluate STITCH on two long-context QA benchmarks: (i) CAME-Bench (§3), our multi-agent trajectory benchmark; question types and metrics are defined in §3.2; and (ii) LongMemEval (Wu et al., 2024), which embeds task-relevant sessions into unrelated chat history and is stratified by context length.² Following Wu et al. (2024), we report accuracy as the metric.

Baselines We compare our method against 13 baselines categorized into three groups:

²For computational efficiency, we randomly subsample each LongMemEval subset from the original 500 questions.

- **Long-Context LLMs (Zero-Shot):** We evaluate powerful models operating directly on the full context, including gpt-4o-mini, gpt-4.1-mini, gpt-5-mini, qwen3-235B-A22B-Instruct, and deepseek-v3.1. For inputs exceeding the context window, we apply left-truncation (keeping the most recent history).
- **RAG Baselines:** We evaluate standard Retrieval-Augmented Generation using dense retrievers with three embedding models: qwen3-embedding-8B, text-embedding-3-small, and text-embedding-3-large.
- **Structured Memory Agents:** We compare against state-of-the-art memory-augmented systems: RAPTOR (Sarathi et al., 2024), GraphRAG (Edge et al., 2024), HippoRAG 2 (Gutiérrez et al., 2025), A-mem (Xu et al., 2025), and Secom (Pan et al., 2025). See detailed baseline descriptions in Appendix C.

Implementation details. All baseline methods and all intent construction stages of STITCH (§2.2) use gpt-5-mini with medium reasoning effort as the backbone LLM generator; we set $N_{\text{start}}=50$, $k_{\text{update}}=50$, $k_{\text{retrieve}}=40$, and $k_{\text{event}}=5$.

To ensure fair comparison, we enforce a shared retrieval budget for all retrieval-based and memory-augmented methods: the inference context is capped at 4,096 tokens. If retrieved content exceeds the budget, we tail-truncate to the last complete sentence. We automatically evaluate all generated answers against ground truth using an LLM-as-a-judge with gpt-4.1-mini (temperature=0.0, top_p=0.9); we use identical generation and judging prompts across methods (Appendix E.2).

5 Results and Analysis

Overview. Table 1 compares STITCH against baselines on CAME-Bench. While STITCH achieves parity with the strongest baseline (gpt-5-mini) on the small subset, it demonstrates superior scalability. As trajectory lengths scale by a factor of 6 for medium subset and 17 for large subset, performance among standard baselines degrades significantly. In contrast, STITCH remains robust, outperforming the best baseline by **11.6%** (20.5% relative) on the Medium subset and **35.6%** (100% relative) on the Large subset.

Analysis of Baselines. We observe distinct failure modes in the baseline methods. Long-context

Model	CAME-Bench						LongMemEval		
	Prec _S	F1 _S	Prec _M	F1 _M	Prec _L	F1 _L	Acc _O	Acc _S	Acc _M
<i>Long Context Agents</i>									
DeepSeek V3.1 (128k)	0.238	0.228	0.012	0.010	0.000	0.000	0.620	0.240	0.267
Qwen3 (256k)	0.724	0.704	0.192	0.152	0.016	0.016	0.740	0.160	0.333
GPT-4o-mini (128k)	0.336	0.315	0.082	0.075	0.017	0.017	0.560	0.060	0.267
GPT-4.1-mini (1M)	0.715	0.712	0.401	0.362	0.317	0.213	0.720	0.200	0.067
GPT-5-mini (400k)	0.775	0.804	0.576	0.566	0.268	0.212	0.860	0.820	0.533
<i>Embedding RAG Agents</i>									
Qwen 8B	0.306	0.280	0.176	0.157	0.172	0.152	0.740	0.780	0.533
text-embedding-3-small	0.275	0.269	0.224	0.195	0.219	0.182	0.800	0.800	0.200
text-embedding-3-large	0.346	0.317	0.190	0.168	0.236	0.195	0.800	0.800	0.267
<i>Structure-Augmented RAG Agents</i>									
RAPTOR (Sarathi et al., 2024)	0.343	0.329	0.122	0.117	0.168	0.139	0.680	0.480	0.467
GraphRAG (Edge et al., 2024)	0.385	0.371	0.189	0.165	0.196	0.156	0.820	0.840	0.667
HippoRAG 2 (Gutiérrez et al., 2025)	0.405	0.390	0.211	0.191	0.212	0.186	0.820	0.800	0.667
A-mem (Xu et al., 2025)	0.387	0.376	0.217	0.196	0.216	0.186	0.780	0.740	0.667
Secom (Pan et al., 2025)	0.532	0.501	0.141	0.114	0.282	0.236	0.520	0.580	0.600
STITCH (Ours)	0.810	0.844	0.665 [†]	0.682 [†]	0.616 [†]	0.592 [†]	0.860	0.860	0.800
w/o thematic scope	0.457	0.463	0.257	0.257	0.269	0.213	-	-	-
w/o event type	0.730	0.753	0.525	0.527	0.383	0.273	-	-	-
w/o coreference	0.554	0.578	0.508	0.489	0.469	0.404	-	-	-
w/o key entity type	0.713	0.735	0.513	0.511	0.513	0.458	-	-	-

Table 1: Performance on CAME-Bench and LongMemEval. We report answer-set Macro Precision/Macro-F1 (omitting Recall for brevity) on CAME-Bench $S/M/L$ ($N=144/168/61$) and average Accuracy on LongMemEval $O/S/M$ ($N=50/50/15$) (Wu et al., 2024). N is trajectories per subset. Following Pan et al. (2025), the memory-retrieval token budget is 4096. Best results are **bold**. †: paired t-test vs. the strongest baseline within each subset, $p < 0.05$. Appendix E.2 details the prompts for answer generation and LLM-based evaluation.

LLMs remain competitive on the small subset, effectively attending to scattered details. However, they suffer from substantial performance degradation on the Large subset, struggling to link multiple details across extended contexts (the “lost-in-the-middle” phenomenon). Conversely, structured agentic memory baselines perform adequately on simple factual recall but fail on distinguishing semantically similar facts that differ by their context (e.g., distinguishing a hotel price on Day 1 from Day 2). STITCH overcomes this by anchoring retrieval in the *Contextual Intent* structure (t_t), ensuring that semantically similar information is correctly disambiguated by its thematic scope.

5.1 Ablation Study

To understand the source of these gains, we conduct an ablation study on the components of the contextual intent: thematic scope (σ_t), event type (ϵ_t), Key Entity Types (κ_t), and the Coreference

Resolution module. (Appendix D.1 provides detailed error analysis)

Thematic Scopes Effectively Reduce Context Noise. Thematic scope (σ_t) emerges as the most significant factor contributing to performance. By segmenting the trajectory into coarse-grained “behavior episodes,” σ_t establishes necessary boundaries for memory retrieval. This proves critical for all question types, as it allows the model to constrain reasoning to relevant thematic segments, minimizing distraction from irrelevant history.

Granularity Trade-off. Taxonomic Event Labeling (ϵ_t) improves performance on fine-grained lookup tasks but introduces instability in Question Type 4 (Information Synthesis). We attribute this to the inductive nature of our labeling process, which tends to generate highly specific event types (e.g., differentiating “Check Rates” from “Book Hotel”). While these fine-grained labels serve as effective




Figure 3: Results broken down by question type in CAME-Bench. We compare STITCH with the strongest baseline in each category: gpt-5-mini for Long-Context Models, text-embedding-3-large for Embedding RAG Agents, and SeCom (Pan et al., 2025) for Structure-Augmented RAG Agents. The evaluation addresses four distinct capabilities: Incremental Memory Update (Type 1), Context-Aware Factual Recall (Type 2), Context-Aware Multi-Hop Reasoning (Type 3), and Information Synthesis (Type 4). See §3.2 for detailed definitions.

filters for specific queries, they can hinder synthesis tasks that require aggregating information across multiple distinct action types. This suggests a trade-off: while a flat taxonomy is useful, a hierarchical structure is likely required to support both fine-grained filtering and coarse-grained integration.

Resolution Grounds Entities. The structural alignment coreference module serves as a foundational step. Its effectiveness depends heavily on the accuracy of the upstream thematic scope and event type assignments. By resolving ambiguous pronouns (e.g., “it”) to their specific entity referents prior to storage, this module significantly boosts performance across all metrics by preventing the retrieval of ungrounded or ambiguous context snippets (see Appendix B for implementation details and results).

6 Related Works

Memory-Augmented Agent Systems Existing memory architectures address the finite context window of LLMs by externalizing history via vec-

tor retrieval (Karpukhin et al., 2020), hierarchical summarization (Sarathi et al., 2024; Pan et al., 2025), or graph-based storage (Edge et al., 2024; Xu et al., 2025; Gutiérrez et al., 2025). While these methods expand recall capacity, they predominantly optimize for storage efficiency and semantic similarity rather than *contextual validity*. Retrieval mechanisms driven solely by embedding alignment remain susceptible to noise when relevance depends on latent goals or evolving constraints. Furthermore, abstraction-based approaches often sacrifice essential details, while static schemas lack flexibility to adapt to shifting task demands. Consequently, current systems often fail to ground retrieved information in the agent’s active intent, leaving a gap between access and effective state-dependent reasoning.

Long-Context Agentic Benchmarks Recent benchmarks such as LongMemEval (Wu et al., 2024), LongBench (Bai et al., 2024b), and LoCoMo (Maharana et al., 2024) have moved beyond single-turn QA to probe memory retention over extended horizons. While instrumental in revealing performance degradation in long-context settings, these evaluations frequently rely on structural oversimplifications that diverge from realistic workflows. Many employ strict turn-taking dynamics (Bai et al., 2024a) or partition interactions into disjoint topics, allowing models to exploit local adjacency heuristics rather than performing robust context tracking. Unlike open-ended social dialogue (Maharana et al., 2024), goal-oriented agent tasks require rigorous state maintenance across interleaved, non-local dependencies—a challenge that current benchmarks, with their focus on separable sub-tasks, fail to adequately capture.

7 Conclusion

We present **STITCH**, a lightweight, domain-agnostic agentic memory system that models context history via *contextual intent* and uses it to filter and prioritize memory for retrieval. This intent-aware cue suppresses semantically similar but contextually mismatched history, supporting robust long-horizon reasoning. We also introduce **CAME-Bench**, a benchmark that exposes the fragility of existing methods in realistic, goal-oriented trajectories. Across settings, STITCH achieves state-of-the-art performance and scales reliably as context grows, avoiding the degradation observed in long-context baselines on extended trajectories.

612 **Limitations**

613 STITCH is designed to prioritize retrieval robustness and structural coherence in long-horizon contexts, utilizing a design philosophy that favors precision over raw ingestion speed. Consequently, the ingestion pipeline incurs multiple LLM calls to construct rich contextual intent tuples; while this overhead is amortized during retrieval to ensure superior disambiguation, the per-step ingestion cost is higher than lightweight embedding-only baselines. Similarly, our dynamic label evolution involves a trade-off between schema stability and immediate adaptability. While our system supports real-time updates, we employ a buffered update strategy (N=50) in our experiments to stabilize the label space. This choice ensures schema consistency but introduces a minor latency in formalizing novel event types that emerge in the middle of a buffer window. Finally, our induced event taxonomy is currently optimized for fine-grained factual lookup. While this granularity excels at specific queries, broad synthesis tasks may currently require aggregating across multiple event types. These trade-offs highlight promising avenues for future work, particularly in exploring hierarchical schema induction and lightweight structural predictors to further balance efficiency with our established performance gains.

640 **Ethical Considerations**

641 We propose an entirely synthetic benchmark constructed within a closed-world environment. This design strictly prevents the inclusion of personally identifiable information and mitigates privacy risks associated with scraping real-world user data. In the Travel Planning domain, we utilize fictionalized entities to avoid potential harm to real-world businesses. For the Debate domain, we minimize the risk of generating toxic or harmful content by restricting topics to policy argumentation curated by the National Speech & Debate Association and constraining agent generation to specific, retrieved evidence snippets.

654 Regarding human evaluation, we recruited volunteer annotators to validate trajectory quality and ground truth correctness. All participants provided informed consent, and no personal data was collected during the process. Finally, regarding the broader impact of agentic memory, our approach grounds memory in explicit contextual intent. This structural organization offers greater transparency

and interpretability regarding retained information compared to black-box embedding methods, facilitating better auditability and user control over stored history.

References

- Judith Avrahami and Yaakov Kareev. 1994. The emergence of events. *Cognition*, 53(3):239–261.
- Ge Bai, Jie Liu, Xingyuan Bu, Yancheng He, Jiaheng Liu, Zhanhui Zhou, Zhuoran Lin, Wenbo Su, Tiezheng Ge, Bo Zheng, and Wanli Ouyang. 2024a. [MT-bench-101: A fine-grained benchmark for evaluating large language models in multi-turn dialogues](#). In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, Bangkok, Thailand. Association for Computational Linguistics.
- Yushi Bai, Shangqing Tu, Jiajie Zhang, Hao Peng, Xiaozhi Wang, Xin Lv, Shulin Cao, Jiazheng Xu, Lei Hou, Yuxiao Dong, Jie Tang, and Juanzi Li. 2024b. Longbench v2: Towards deeper understanding and reasoning on realistic long-context multitasks. *arXiv preprint arXiv:2412.15204*.
- Roger G Barker and Herbert F Wright. 1954. *Midwest and the USA*. Row, Peterson and Company.
- Gheorghe Comanici, Eric Bieber, Mike Schaeckermann, Ice Pasupat, Noveen Sachdeva, Inderjit Dhillon, Marcel Blistein, Ori Ram, Dan Zhang, Evan Rosen, and 1 others. 2025. Gemini 2.5: Pushing the frontier with advanced reasoning, multimodality, long context, and next generation agentic capabilities. *arXiv preprint arXiv:2507.06261*.
- Fergus IM Craik and Robert S Lockhart. 1972. Levels of processing: A framework for memory research. *Journal of verbal learning and verbal behavior*, 11(6):671–684.
- Darren Edge, Ha Trinh, Newman Cheng, Joshua Bradley, Alex Chao, Apurva Mody, Steven Truitt, Dasha Metropolitanansky, Robert Osazuwa Ness, and Jonathan Larson. 2024. [From local to global: A graph rag approach to query-focused summarization](#).
- Mihail Eric, Rahul Goel, Shachi Paul, Abhishek Sethi, Sanchit Agarwal, Shuyang Gao, Adarsh Kumar, Anuj Goyal, Peter Ku, and Dilek Hakkani-Tur. 2020. [MultiWOZ 2.1: A consolidated multi-domain dialogue dataset with state corrections and state tracking baselines](#). In *Proceedings of the Twelfth Language Resources and Evaluation Conference*, pages 422–428, Marseille, France. European Language Resources Association.
- Bernal Jiménez Gutiérrez, Yiheng Shu, Weijian Qi, Sizhe Zhou, and Yu Su. 2025. [From rag to memory: Non-parametric continual learning for large language models](#). *Preprint*, arXiv:2502.14802.

715	Yucheng Jiang, Yijia Shao, Dekun Ma, Sina Semnani, and Monica Lam. 2024. Into the unknown unknowns: Engaged human learning through participation in language model agent conversations . In <i>Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing</i> , pages 9917–9955, Miami, Florida, USA. Association for Computational Linguistics.	771
716		772
717		773
718		774
719		775
720		776
721		777
722		
723	Vladimir Karpukhin, Barlas Oguz, Sewon Min, Patrick Lewis, Ledell Wu, Sergey Edunov, Danqi Chen, and Wen-tau Yih. 2020. Dense passage retrieval for open-domain question answering . In <i>Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing (EMNLP)</i> , pages 6769–6781, Online. Association for Computational Linguistics.	778
724		779
725		780
726		
727		
728		
729		
730	Nelson F. Liu, Kevin Lin, John Hewitt, Ashwin Paranjape, Michele Bevilacqua, Fabio Petroni, and Percy Liang. 2024. Lost in the middle: How language models use long contexts . <i>Transactions of the Association for Computational Linguistics</i> , 12:157–173.	781
731		782
732		783
733		
734		
735	Adyasha Maharana, Dong-Ho Lee, Sergey Tulyakov, Mohit Bansal, Francesco Barbieri, and Yuwei Fang. 2024. Evaluating very long-term conversational memory of llm agents. <i>arxiv</i> .	784
736		785
737		786
738		787
739	Darren Newton, Gretchen A Engquist, and Joyce Bois. 1977. The objective basis of behavior units. <i>Journal of Personality and social psychology</i> , 35(12):847.	788
740		789
741		790
742	OpenAI. 2025. Introducing GPT-4.1 in the API . Accessed: 2025-11-27.	791
743		792
744	Zhuoshi Pan, Qianhui Wu, Huiqiang Jiang, Xufang Luo, Hao Cheng, Dongsheng Li, Yuqing Yang, Chin-Yew Lin, H. Vicky Zhao, Lili Qiu, and Jianfeng Gao. 2025. Secom: On memory construction and retrieval for personalized conversational agents . In <i>The Thirteenth International Conference on Learning Representations</i> .	793
745		794
746		795
747		
748		
749		
750		
751	Abhinav Rastogi, Xiaoxue Zang, Srinivas Sunkara, Raghav Gupta, and Pranav Khaitan. 2020. Towards scalable multi-domain conversational agents: The schema-guided dialogue dataset. In <i>Proceedings of the AAAI Conference on Artificial Intelligence</i> , volume 34, pages 8689–8696.	796
752		797
753		798
754		799
755		
756		
757	Oscar Sainz, Jon Campos, Iker García-Ferrero, Julen Etxaniz, Oier Lopez de Lacalle, and Eneko Agirre. 2023. NLP evaluation in trouble: On the need to measure LLM data contamination for each benchmark . In <i>Findings of the Association for Computational Linguistics: EMNLP 2023</i> , pages 10776–10787, Singapore. Association for Computational Linguistics.	800
758		801
759		802
760		
761		
762		
763		
764	Parth Sarthi, Salman Abdullah, Aditi Tuli, Shubh Khanna, Anna Goldie, and Christopher D. Manning. 2024. Raptor: Recursive abstractive processing for tree-organized retrieval. In <i>International Conference on Learning Representations (ICLR)</i> .	
765		
766		
767		
768		
769	Yijia Shao, Yucheng Jiang, Theodore Kanell, Peter Xu, Omar Khattab, and Monica Lam. 2024. Assisting	
770		
	in writing Wikipedia-like articles from scratch with large language models . In <i>Proceedings of the 2024 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies (Volume 1: Long Papers)</i> , pages 6252–6278, Mexico City, Mexico. Association for Computational Linguistics.	
	Leonard Talmy. 1975. Semantics and syntax of motion. In <i>Syntax and Semantics volume 4</i> , pages 181–238. Brill.	
	Endel Tulving and Donald M Thomson. 1973. Encoding specificity and retrieval processes in episodic memory. <i>Psychological review</i> , 80(5):352.	
	Di Wu, Hongwei Wang, Wenhao Yu, Yuwei Zhang, Kai-Wei Chang, and Dong Yu. 2024. Longmemeval: Benchmarking chat assistants on long-term interactive memory . <i>Preprint</i> , arXiv:2410.10813.	
	Tianbao Xie, Danyang Zhang, Jixuan Chen, Xiaochuan Li, Siheng Zhao, Ruisheng Cao, Toh Jing Hua, Zhoujun Cheng, Dongchan Shin, Fangyu Lei, Yitao Liu, Yiheng Xu, Shuyan Zhou, Silvio Savarese, Caiming Xiong, Victor Zhong, and Tao Yu. 2024. Os-world: Benchmarking multimodal agents for open-ended tasks in real computer environments . <i>Preprint</i> , arXiv:2404.07972.	
	Wujiang Xu, Zujie Liang, Kai Mei, Hang Gao, Juntao Tan, and Yongfeng Zhang. 2025. A-mem: Agentic memory for llm agents . <i>arXiv preprint arXiv:2502.12110</i> .	
	Jeffrey M Zacks and Barbara Tversky. 2001. Event structure in perception and conception. <i>Psychological bulletin</i> , 127(1):3.	

803	Appendix Table of Contents	
804	A Benchmark Construction and Implementation Details	11
805	A.1 Curation Pipeline Details	11
806	A.2 Domain Specifications	12
807	A.3 Ground Truth Generation and Metrics	12
808	A.4 Implementation Details	13
809	A.5 Benchmark Statistics.	13
810	A.6 Quality Assurance and Verification	13
811	A.7 Example Trajectories and Evaluation Questions	14
812		
813	B Verification of Structural Alignment and Coreference Resolution	14
814	B.1 Metric Definition	14
815	B.2 Implementation Details	14
816	B.3 Results	15
817		
818	C Baseline Descriptions	15
819		
820	D Error Analysis	16
821	D.1 Question-Side Label Selection	16
822	D.2 Failure Modes in Question-Time Label Selection	17
823		
824	E LLM Prompt Specifications	18
825	E.1 Prompts Used by STITCH	18
826	E.2 Prompts for Answer Generation and Evaluation	18
827		
828	F Benchmark Trajectory Showcase	18
829		
830	G Debate Trajectory Showcase	18

A Benchmark Construction and Implementation Details	831
--	------------

In this section, we provide comprehensive details regarding the CAME-Bench construction, implementation, and quality assurance protocols. We first detail the four-stage curation pipeline used to generate valid trajectories (§A.1). We then provide specific configurations for the *Travel Planning* and *Debate* domains (§A.2). Next, we describe the ground truth generation process and metric definitions (§A.3), followed by implementation statistics and reproducibility details (§A.4), and our quality assurance protocols (§A.6). Finally, we include example trajectories and evaluation questions to illustrate the benchmark format (§A.7).

A.1 Curation Pipeline Details	846
--------------------------------------	------------

We employ a four-stage pipeline that decouples symbolic planning from natural-language generation.

Phase I: Closed-World Environment Construction. We first construct a closed-world environment \mathcal{E} containing all static entities and knowledge required for each domain. This controlled environment ensures that agent actions remain grounded, avoids reliance on external tools, and mitigates data contamination. When trajectories require factual queries (e.g., hotel prices), we simulate and perturb real-world examples within \mathcal{E} to avoid the data contamination issue (Sainz et al., 2023); otherwise, we incorporate real-world information directly.

Phase II: Symbolic Storyboard Planning. In parallel, we construct symbolic storyboards capturing the high-level interaction plan. For each domain, we predefine an action space \mathcal{A} and specify pragmatic constraints on permissible action sequences. For *Travel Planning*, we generate multi-day itinerary skeletons with slots for restaurants, accommodations, and attractions that require consistent state tracking. For *Debate*, we employ a probabilistic argumentation planner that samples moves such as ATTACK, DEFEND, CONCEDE, and BACKGROUND subject to dialogue rules (e.g., concessions require preceding successful attacks). Each action is paired with relevant information from the environment \mathcal{E} . To incorporate dense reuse of semantically similar content, the planner ensures some entities in \mathcal{E} are referenced multiple times under different contextual intents.

This produces a symbolic trajectory $T_{\text{sym}} =$

$\{\text{op}_1, \dots, \text{op}_n\}$, where each operation op_t specifies: (i) an agent role r_t , (ii) a latent goal g_t describing potential actions and target entities, (iii) a payload p_t containing domain-relevant details.

Phase III: Storyboard-Conditional Trajectory Generation. We translate symbolic storyboards into natural language using LLMs, producing surface-level actions that retain the structural constraints of the symbolic plan. For each operation op_t , the generator conditions on the role r_t , latent goal g_t , and payload p_t to generate an action realization a_t in natural language. We then assign a synthetic timestamp τ_t (e.g., a monotonically increasing time index) to obtain the trajectory step $s_t = (r_t, a_t, \tau_t)$, yielding the natural-language trajectory $T = \{s_1, \dots, s_n\}$. A separate verification model checks entailment between the generated action a_t and the symbolic specification of op_t to ensure that the realization faithfully instantiates g_t and p_t under role r_t .

Phase IV: Pragmatic Refinement. We apply post-processing refinements that mimic natural communication patterns. First, we perform *referential remodeling*, rewriting explicit entity mentions into complex referring expressions (e.g., “Apollo Hotel” becomes “the second hotel I mentioned for Day 1”), forcing models to resolve coreference chains over long horizons. Second, we apply *turn segmentation*, splitting monolithic generations into smaller discourse units to simulate realistic conversational dynamics. Third, for entities in \mathcal{E} that can be easily disambiguated via surface semantics, we perform *entity normalization*, masking semantic content (e.g., replacing explicit evidence sources with author–year citations in debate settings).

A.2 Domain Specifications

A.2.1 Travel Planning Domain

For the *Travel Planning* domain, we construct a closed-world environment, \mathcal{E}_{travel} , consisting of 100 entities for each category: accommodations, restaurants, and attractions. Each entity possesses canonical descriptions and structured attributes (e.g., price tiers, ratings, cuisine types). This environment \mathcal{E}_{travel} is shared across all travel planning trajectories.

To ensure distinctiveness, all entity names are adapted from ancient Greek mythology (e.g., *Menelaus Spartan Grill*), while pricing and ratings are sampled from plausible real-world ranges.

For the symbolic trajectory T_{sym} , we define an action space \mathcal{A}_{travel} which includes the following operations: `indicate_date`, `propose_option`, `inquire_details`, `compare_options`, and `make_decision`. We enforce pragmatic constraints to ensure logical coherence: for instance, a `propose_option` action must precede any `inquire` or `decision` actions, and a `compare_options` action requires prior proposals to reference.

A.2.2 Debate Domain

For the *Debate* domain,³ a unique closed-world environment $\mathcal{E}_{debate}^{topic_i}$ is generated for each topic. This is achieved by retrieving knowledge snippets that serve as evidence supporting either side of the motion.⁴ On average, the environment contains 50 unique, authoritative and realistic knowledge snippets for the small and medium partitions, and 200 for the large partition.

To enforce our *entity normalization* mechanism, each evidence snippet used in a debate trajectory is cited inline as *Author (Year)* to mask semantic meaning.

For the symbolic trajectory T_{sym} , we define an action space \mathcal{A}_{debate} including: `propose_argument`, `attack`, `defend`, `concede`, `supply_background`, and `summarize`. The pragmatic constraints dictate that:

- A `propose_argument` operation must precede any `attack`, `defend`, or `concede` actions.
- A `concede` action must occur only after both an `attack` and a `defend` action have taken place.
- The `summarize` action must be the terminal operation in T_{sym} .

A.3 Ground Truth Generation and Metrics

Ground Truth Answer Generation. Ground-truth answers are derived deterministically from the symbolic trajectory operations T_{sym} defined in Phase II. For each question $q \in Q$, we identify the subset of operations $Q_{ops}(q) = \{\text{op}_{i_1}, \dots, \text{op}_{i_k}\}$ whose payloads contain the requisite information. These symbolic operations are then processed by an LLM (gpt-4o-mini) to generate natural-language

³We derive our debate topics from the National Speech & Debate Association: <https://www.speechanddebate.org/>

⁴We utilize serper.dev as our internet retriever.

answers. Depending on the question type, the ground truth may be a single information snippet, a set of entities, or a structured response. To ensure correctness, we sample a subset of generated answers and validate them through human annotation.

Evaluation Metric. Because ground-truth answers may consist of single items or sets of entities, we employ answer-set macro-averaged precision, recall, and F1 score as our primary evaluation metrics. For each question, we compute precision and recall by comparing the predicted answer set against the ground truth, derive the F1 score, and average across all questions. This metric provides a more nuanced assessment than binary accuracy, particularly for questions with multi-element answers, and better captures partial credit scenarios.

A.4 Implementation Details

Models used. Across benchmark construction phases (environment construction, storyboard-to-trajectory realization, and pragmatic refinement), we use gpt-5-mini with temperature=1.0 and reasoning_effort=medium. In the Travel Planning domain, surface utterances are generated with gpt-4.1-mini. In the Debate domain, evidence processing (query generation and evidence naming) uses gpt-4.1-mini, while debate utterances are generated with gpt-5-mini.

Prompts, label ontologies, and hyperparameters. We release all prompts used for action rendering, referential remodeling, turn segmentation, and any automated annotation used in the benchmark (see Appendix E.1). We also release the label schema used by STITCH (scope/event/target and optional functional-type), along with all pipeline hyperparameters (e.g., history window sizes, sampling budgets, retrieval caps, and truncation rules) required to reproduce the reported results.

Determinism. LLM outputs are not guaranteed deterministic; we enforce reproducibility where possible via (i) fixed random seeds in non-LLM sampling logic (e.g., itinerary sampling and storyboard planning), and (ii) stable processing order and deterministic identifiers (e.g., stable mapping for evidence IDs). We log all configuration files and random seeds used for each run.

A.5 Benchmark Statistics.

To investigate and evaluate LLM agent memory across varying context lengths, following Wu et al. (2024), we construct three subsets of the benchmark, denoted as CAME-Bench_S, CAME-Bench_M, and CAME-Bench_L representing small, medium, and large partitions as three scales, respectively. The statistics for these partitions are detailed in Table 2. Notably, due to the extreme context length (>400k tokens) and substantial computational cost of generating coherent long-horizon interactions, the Large subset comprises 2 high-density trajectories. Despite the lower trajectory count, this subset contains 61 evaluation questions, providing sufficient granularity to probe memory stability at scale.

Table 2: Statistics for the CAME-Bench partitions. *Context Len.* denotes the average context length in tokens; *Trajs.* indicates the number of unique trajectories; and *Ques.* denotes the total number of evaluation questions.

Subset	Context Len.	Trajs.	Ques.
CAME-Bench _S	23k	6	144
CAME-Bench _M	137k	6	168
CAME-Bench _L	408k	2	61

A.6 Quality Assurance and Verification

To ensure the quality and correctness of the benchmark, we employ a two-stage verification process involving both automatic checks and human annotation.

Automatic Verification. We utilize an LLM (gpt-4.1-mini) as a judge with temperature=0.0 and top_p=0.9 to automatically verify the entailment between each symbolic operation $opt_t \in T_{sym}$ and its natural language realization \tilde{s}_t . We randomly sampled 200 pairs of (opt_t, \tilde{s}_t) for evaluation, consisting of 100 samples from the *Travel Planning* domain and 100 from the *Debate* domain. The LLM-as-judge evaluation indicates a success rate of 99.5%.

Human Verification. To assess the overall trajectory quality and the validity of the automatically generated questions and ground truth answers, we measured agreement with human annotators. Given the scale of the benchmark, we randomly sampled 2 CAME-Bench_S trajectories from each domain (4 trajectories total). We recruited four volunteer human annotators with a master’s degree or higher

Travel Planning Domain. In the Travel Planning dataset, the ground-truth simulation log contains structured payloads for actions such as PROPOSE, DECIDE, and COMPARE. Each payload includes a canonical entity (e.g., “*Apollo Hotel*”). We align generated notes to simulation turns via discrete time steps (t). Both the ground-truth entity and the generated note text undergo normalization (lowercasing, whitespace trimming). For every turn involving a referential action, the script asserts that the canonical entity appears as a substring in the rewritten memory snippet.

Debate Domain. In the Debate dataset, coreference often involves referring to evidence documents (e.g., “*that study we discussed*”). We maintain a closed-world registry mapping every evidence UUID to its `neutral_name` (e.g., “*Smith et al., 2023 Study on Microplastics*”). For any turn where the agent utilizes evidence (indicated by `action_object` or `evidence_used` metadata), we verify that the corresponding `neutral_name` is explicitly present in the memory snippet.

B.3 Results

We conducted this audit across three scales of trajectory complexity (Small, Medium, Large) for both domains. Table 3 summarizes the Entity Resolution Recall. The system demonstrates high resolution in short contexts and maintains robust performance (approximately 80%) even as trajectory length and complexity increase.

Table 3: Entity Resolution Recall (ERR) across domains and trajectory scales. Scores represent the average percentage of implicit references successfully rewritten into explicit entity mentions.

Domain	Scale	Recall (Avg)
Travel Planning	Small	97.4%
	Medium	79.2%
	Large	81.1%
Debate	Small	91.5%
	Medium	78.6%
	Large	81.1%

C Baseline Descriptions

RAPTOR (Sarathi et al., 2024) proposes a tree-structured retrieval system that recursively summarizes text chunks to capture information at varying levels of abstraction. It constructs a hierarchical

tree where leaf nodes represent raw text segments and higher-level nodes represent summarized clusters of child nodes. During inference, RAPTOR retrieves from this multi-layered tree, allowing retrieval at different levels of abstraction, supporting both high-level thematic queries and fine-grained factual queries.

GraphRAG (Edge et al., 2024) is a structured retrieval approach that utilizes Large Language Models (LLMs) to extract a knowledge graph from the corpus, identifying entities and their relationships. Unlike traditional graph methods that rely on strict schema matching, GraphRAG employs community detection algorithms (e.g., Leiden) to partition the graph into modular communities and generates natural language summaries for each community. Retrieval involves matching the query against community-level summaries to support global reasoning, often complemented by local entity-level retrieval.

HippoRAG 2 (Gutiérrez et al., 2025) is a neurobiologically inspired retrieval framework that mimics the hippocampal indexing theory of human memory. It constructs a knowledge graph where nodes serve as associative indices rather than direct factual stores. During retrieval, HippoRAG identifies key entities in the query and uses the Personalized PageRank (PPR) algorithm to spread activation across the graph, identifying paths to relevant information even when there is no direct lexical or semantic overlap. This allows the system to perform multi-hop reasoning by surfacing contextually related passages that are separated in the raw text but connected via shared or related entities in the induced knowledge graph.

A-mem (Xu et al., 2025) introduces an agentic memory system inspired by the Zettelkasten note-taking method. It organizes interaction history into atomic, interconnected “notes” rather than a flat list of turns. A key innovation is its *memory evolution* mechanism: when new information is acquired, the system not only generates new notes but also dynamically updates and refines existing notes and their links. This allows the memory to self-organize and adapt over long horizons, supporting retrieval that combines semantic matching with graph-based contextual expansion over interconnected notes.

SeCom (Pan et al., 2025) focuses on optimizing the granularity of memory units for long-term conversations. The authors argue that traditional turn-level (too fine) and session-level (too coarse) retrieval are suboptimal. Instead,

SeCom introduces a *segment-level* approach, using a specialized model to partition conversation history into discourse-coherent segments. Furthermore, it applies compression-based denoising (via LLMingua-2) to these segments to remove redundancy. This ensures that the retrieval mechanism targets semantically complete discourse units without being distracted by the noise inherent in raw conversational transcripts.

D Error Analysis

D.1 Question-Side Label Selection

To better understand the role and limitations of the question-side label selection component in our retrieval pipeline, we conduct an error analysis that isolates this step from downstream retrieval and generation. The goal of this analysis is not to evaluate end-task performance, but to characterize how well the labels selected for a question align with the labels assigned to ground-truth (GT) turns in the dialogue history.

Methodology. For each question, our method selects a set of labels spanning multiple types (e.g., context scope, event type, target, and key entity). Each candidate turn in the trajectory, including all GT turns, is annotated with structured labels of the same types. We then compute the overlap between the question’s selected labels and each candidate turn’s labels. This overlap-based analysis evaluates the intrinsic discriminative signal provided by the question-side label selection, independent of any retrieval model.

We derive several normalized statistics at the question and turn levels. At the question level, we measure whether at least one GT turn attains the maximum label overlap among all candidate turns ($Q_GT_AT_MAX$), whether any GT turn fully covers the selected labels (Q_GT_FULL), and whether all candidate turns have zero overlap (Q_ZERO). At the turn level, we compute the fraction of GT turns that achieve the maximum overlap (GT_DOM) as well as the average fraction of selected labels supported by GT turns (GT_COV). We additionally report optional diagnostics capturing cases where non-GT turns strictly dominate GT turns in overlap, and the best achievable GT coverage per question. All statistics are first computed per dataset instance and then macro-averaged across datasets within each domain. Table 4 shows detailed statistics.

Overall Findings. Across both debate and travel planning datasets, question-side label selection consistently provides non-zero overlap with candidate turns, as reflected by a near-zero Q_ZERO rate. This indicates that the selected labels are generally relevant to the dialogue trajectory and introduce meaningful constraints.

At the same time, the analysis reveals clear limits in sufficiency. No dataset exhibits full coverage of the selected labels by any single GT turn ($Q_GT_FULL = 0$ across all settings), and average GT coverage remains well below full alignment. Even when GT turns reach the maximum overlap, they typically support only a subset of the selected labels. This pattern suggests that the question-side label selection often encodes constraints that are not jointly realized within a single turn.

Furthermore, overlap density alone is not a reliable indicator of correctness. The GT_DOM metric shows that GT turns rarely dominate the candidate set by overlap, and in a substantial fraction of questions, non-GT turns achieve strictly higher overlap than all GT turns. This implies that while selected labels help surface relevant regions of the trajectory, they do not, by themselves, uniquely identify the correct turn.

Label-Type Behavior. Breaking down the analysis by label type provides additional insight. Context-scope labels frequently enable GT turns to reach the maximum overlap, indicating strong recall-oriented behavior, but their coverage remains low, reflecting coarse granularity. Key entity labels achieve higher coverage when they align with the question, but exhibit greater variance, indicating sensitivity to whether the question provides sufficient cues for reliable selection. Event and target labels offer intermediate behavior, contributing useful signal but rarely achieving high coverage in isolation. These results indicate that no single label type is sufficient on its own, and that their contributions are complementary but partial.

Implications. Taken together, these findings show that question-side label selection plays an important role in structuring the retrieval space, but is not sufficient as a standalone mechanism for precise turn identification. The selected labels capture aspects of the question’s intent and reduce the search space, yet they frequently introduce constraints that are either overly coarse or overly specific relative to the information localized in individual turns. This motivates the need for

Metric	Debate	Travel
Q_GT@MAX	0.50 ± 0.14	0.66 ± 0.08
GT_DOM	0.14 ± 0.07	0.29 ± 0.08
GT_COV	0.15 ± 0.05	0.25 ± 0.03
GT_BEST_COV	0.22 ± 0.06	0.33 ± 0.06
Q_ZERO	0.00	0.00

Table 4: Question-side label selection diagnostics (mean ± std across datasets). Q_GT@MAX: fraction of questions where at least one GT turn attains maximum overlap. GT_DOM: fraction of GT turns that are densest matches. GT_COV / GT_BEST_COV: average and best-case coverage of selected labels by GT turns. Q_ZERO: fraction of questions with zero overlap across all candidates.

downstream mechanisms that can reason over partial label alignment, rather than relying solely on flat overlap counts.

Importantly, they clarify the scope of what question-side label selection can reliably provide, and highlight opportunities for improving how label signals are combined and interpreted in long-horizon retrieval settings.

D.2 Failure Modes in Question-Time Label Selection

In addition to overlap-based diagnostics, we conduct a targeted error analysis to characterize *why* question-time label selection strongly determines the correctness of retrieval. This analysis focuses exclusively on the label selection step and does not depend on retrieved content or generation quality.

Methodology. We analyze questions that lead to incorrect answers under otherwise successful execution, and evaluate the labels selected at question time for each label type (context scope, event type, target, and functional seed). For each such ⟨question, label type⟩ pair, we invoke an LLM-based judge to assess whether the selected labels are appropriate given the question alone. Importantly, the judge is explicitly instructed to rely only on information that can be justified from the question, without assuming access to the dialogue trajectory or downstream retrieval results.

The judge diagnoses failures using a fixed taxonomy with three categories: **Non_Inducible_Label** and **Granularity_Mismatch**. Each judgment is accompanied by a rationale and a confidence score. In this section, we focus on the two most prevalent and structurally consequential error types.

Non-Inducible Label Selection. The most frequent failure mode is **Non_Inducible_Label**, accounting for 78.4% of all observed label selection errors across label types. In these cases, the model selects labels that cannot be justified from the question by explicit lexical cues, clear paraphrase, or necessary semantic entailment. Despite prompt instructions encouraging conservative selection, the model frequently introduces labels that reflect plausible but ungrounded abstractions.

This behavior reflects a fundamental asymmetry in the label selection setting. Candidate labels are derived from full dialogue trajectories and therefore encode rich structural regularities about what commonly occurs in such interactions. In contrast, the question specifies only a narrow and partial information need. When exposed to trajectory-derived label inventories, the model tends to project these latent regularities onto the question, selecting labels that are coherent in the broader conversational context but not inducible from the question itself. As a result, label selection is biased toward what is *typical* of the trajectory rather than what is *licensed* by the question.

These findings indicate that prompt-level constraints alone are insufficient to reliably prevent non-inducible label selection once the model is exposed to trajectory-derived abstractions.

Granularity Mismatch. The second dominant failure mode is **Granularity_Mismatch**, which occurs in 71.8% of label selection errors. This error arises when the abstraction level of selected labels does not align with the scope implied by the question. Overly coarse labels conflate multiple subthreads or contexts, while overly fine-grained labels prematurely commit to specific subcontexts that the question does not warrant.

This failure mode has direct implications for retrieval. Because turn retrieval is strictly gated by the selected labels, a granularity mismatch can exclude relevant turns or admit large numbers of irrelevant ones before any content is examined. Crucially, this error occurs *prior to retrieval*, leaving no opportunity for downstream correction through ranking or reasoning. From the perspective of question-time selection, the model is forced to commit to a single level of abstraction despite uncertainty about the question’s true scope.

The prevalence of granularity mismatch highlights a limitation of flat label spaces: without hierarchical organization, label selection must resolve

Failure Mode	Frequency (%)
NON_INDUCIBLE_LABEL	78.4
GRANULARITY_MISMATCH	71.8

Table 5: Distribution of failure modes in question-time label selection. Percentages are computed over all judged ⟨question, label type⟩ cases. A single case may exhibit multiple failure modes.

abstraction level prematurely, increasing the risk of irreversible filtering errors.

Implications. Together, these findings clarify the role of question-time label selection in long-horizon retrieval, exposing intrinsic challenges in selecting trajectory-derived abstractions from underspecified questions. They motivate extensions that allow label signals to be refined, deferred, or adjusted dynamically, rather than committing irrevocably at question time.

E LLM Prompt Specifications

E.1 Prompts Used by STITCH

The following prompts are utilized by STITCH during annotation, inference, and retrieval-time processing. These prompts operate over existing dialogue trajectories and are executed online or during evaluation. They are instruction-only, contain no in-context examples, and are designed to generalize across domains.

We detail the prompts for thematic scope generation (§2.2.1) in Listing 1 and Listing 2; prompts for event labeling (§2.2.2) in Listing 3; prompts for key entity type labeling (§2.2.3) in Listing 4; and the prompt for memory snippet construction and canonical summary generation in Listing 5.

For retrieval, we utilize an LLM to select candidate labels for each component of contextual intent: thematic scope labels (Listing 6), event type labels (Listing 7), and key entity types (Listing 8).

E.2 Prompts for Answer Generation and Evaluation

To ensure fair comparison, we use consistent prompts and models for answer generation. Listing 9 details the answer generation prompts for the open-domain tasks in the LongMemEval benchmark and the travel planning subset of CAME-Bench. Listing 10 provides the prompt used for answer generation in the debate domain of CAME-Bench.

To evaluate model performance across different question types, we employ two distinct evaluation protocols. For questions requiring a single, definitive answer (e.g., “*What restaurant was selected for Day 1 dinner?*”), we utilize the prompt in Listing 11. This module assigns a binary label (CORRECT/WRONG) by verifying if the ground truth is present in the generated response. For complex queries involving multiple valid items (e.g., “*What attractions were visited on Day 1?*”), we use the prompt in Listing 12. This module counts the number of valid candidates retrieved, enabling the calculation of fine-grained metrics such as Precision, Recall, and F1-score.

F Benchmark Trajectory Showcase

Trajectory 1 is a visualization of a travel planning trajectory from CAME-Bench. The interaction involves a **User** and a **Travel Agent** collaborating to plan a detailed multi-day itinerary. The dialogue encompasses constraint specification, information seeking (e.g., checking prices and ratings), option comparison, and final scheduling decisions. To prevent data contamination in future LLM evaluation, this example is slightly different from trajectories in the CAME-Bench.

G Debate Trajectory Showcase

Trajectory 2 is a visualization of a debate trajectory from CAME-Bench. The interaction alternates between a **Pro-Side Debater** and a **Con-Side Debater** addressing the policy resolution: “Resolved: The United States federal government should substantially reduce its restrictions on legal immigration to the United States.”⁵ The dialogue encompasses contentions, rebuttals, and summaries. To prevent data contamination in future LLM evaluation, this example utilizes a topic distinct from those contained in the actual benchmark dataset.

⁵Topic sourced from <https://www.speechanddebate.org>.

User

2025-05-15T08:00

Let's focus on planning the itinerary for day 1. I'm eager to see what options we have and start organizing the activities.

Travel Agent

2025-05-15T08:00

Great, focusing on day 1 is a smart way to start shaping your trip! Let's explore the best activities and sights to set a wonderful tone for your adventure. Whether you're interested in cultural landmarks, nature spots, or vibrant local neighborhoods, we can tailor the day to your preferences. Just let me know what excites you most, and I'll help organize an itinerary that balances excitement with ease, ensuring you have time to enjoy each experience without feeling rushed.

Travel Agent

2025-05-15T08:00

Starting your trip with a well-planned day can really enhance the overall flow and make sure you hit all the highlights comfortably. What kind of experiences are you most looking forward to on day 1?

User

2025-05-15T08:01

One idea is the Daphne Laurel Hotel. It seems cozy and well-located, which is perfect since I prefer places that are easy to get around from. Plus, I usually appreciate a quiet atmosphere for resting after a day of sightseeing.

Travel Agent

2025-05-15T08:01

It is a truly charming choice, especially for travelers who value a quiet, unpretentious atmosphere combined with easy access to city attractions. Nestled in the serene old riverside quarter, this hotel is wrapped in a rich local story that adds a unique layer of character to your stay. Named after a gentle botanist who cared for the laurel groves nearby, the hotel's air is still gently scented with these fragrant plants, which creates a peaceful ambiance right from the moment you arrive. What makes the Daphne Laurel particularly special is its blend of simplicity and warmth.

Travel Agent

2025-05-15T08:01

Its weathered stone walls and modest design make it feel more like a cozy retreat than a bustling hotel. Guests often speak fondly of the "kettle song," a quaint tradition where the night porter hums softly while preparing communal tea in the lounge at dusk. This little ritual invites guests to relax and connect with a slower, more restful rhythm after a busy day of exploring the city. The rooms are practical yet thoughtful, many oriented to welcome the soft, warm morning light through delicate lace curtains, making waking up a gentle experience.

Travel Agent

2025-05-15T08:01

Free Wi-Fi keeps you connected without overwhelming the tranquil setting, and the continental breakfast provides a simple, satisfying start to your day. Located just steps from lantern-lit streets and lively markets, the hotel offers the perfect balance—close enough to the action but far enough to escape into calm. Many travelers find themselves extending their stay here, appreciating the steady, soothing pace and the blend of local history with genuine hospitality. If you're someone who enjoys stepping into a space that feels both authentic and quietly restorative, it seems like an ideal fit for your trip.

User

2025-05-15T08:02

One idea is to start the day at Hyperion Horizon Dining for breakfast. I've heard they have a great atmosphere and a variety of options, which might be perfect to fuel up for our day ahead.

Travel Agent

2025-05-15T08:02

It is a wonderful choice to start your day! This charming breakfast spot has a rich history, beginning as a cozy little nook on Lantern Lane that welcomed both early risers and late travelers seeking a comforting meal beneath the warm glow of oil lamps. The name itself conjures images of dawn breaking over distant peaks, symbolizing warmth and renewal—a perfect vibe to kick off your morning. What makes Hyperion Horizon truly special is its simple yet soul-soothing fare.

Travel Agent

2025-05-15T08:02

Their sun-kissed stew and earthy root flatbread are standout dishes, rooted in a story about a wandering cook who crafted these hearty recipes from foraged ingredients at daybreak. Guests often partake in the quaint tradition of leaving their spoons upright in their bowls, signaling shared experiences and quiet camaraderie over cups of fragrant spiced tea. The atmosphere is unpretentious and welcoming, with regulars softly chatting at the counter, and the soothing clatter of utensils blending into the hum of morning conversation. The dining room comes alive as the early light filters through weathered windows, mingling with the inviting aromas of freshly brewed herbal infusions.

Travel Agent

2025-05-15T08:02

Many visitors find themselves lingering here, not for extravagance, but for the comforting simplicity and warmth that wrap around you like a gentle embrace. It's a spot that captures the steady rhythm of simple pleasures, setting a peaceful tone for your day ahead. Whether you're looking to recharge or just enjoy a moment of calm, it offers an inviting and memorable start to your adventure.

User

2025-05-15T08:03

One idea for breakfast is the Olympus Summit Dining Hall. It sounds like a great spot to start the day, especially if you like a lively atmosphere with a variety of options. Do you think it would be a good fit for us?

Travel Agent

2025-05-15T08:03

It is indeed a fantastic choice for breakfast, especially if you're looking to start the day with a unique and memorable experience. Perched on a gentle rise with a scenic view of the old riverside quarter, this dining hall is steeped in local lore, offering a setting that feels almost otherworldly. The name itself pays homage to a long-forgotten mountain peak and the legendary feast inspired by it, which sets the tone for an elevated meal. The house specialty, slow-roasted herb lamb with a honeyed glaze, is not only a dish but a ritual—symbolizing abundance and care.

Travel Agent

2025-05-15T08:03

This is a place where the meal unfolds at a thoughtful pace, inviting guests to savor each bite amidst the warm glow of lantern light and polished wood. While it is especially vibrant on weekend evenings, its serene elegance makes it a wonderful spot for a morning meal as well, providing a peaceful yet lively atmosphere. Many guests appreciate the attentive service that makes the dining experience feel personalized and special. If you enjoy a lively atmosphere paired with a variety of rich flavors and a touch of legend and tradition, it could be just the right start to your day.

User

2025-05-15T08:04

One idea for dinner is Bellerophon Pegasus Dining. It sounds like a unique spot, and I usually appreciate places with a distinctive ambiance for evening meals. Maybe it could offer something memorable for our first night's dinner?

Travel Agent

2025-05-15T08:04

It sounds like an enchanting choice for your first night's dinner! This restaurant is truly a gem nestled in the old quarters, where the charm of myth meets culinary artistry. The ambiance is uniquely refined, with softly glowing lanterns and crystal chandeliers that create a warm, inviting atmosphere perfect

for an intimate evening. It's the kind of place where each dish is a story, inspired by the legendary hero who tamed Pegasus, and the signature "Skyward Feast" is a must-try—herb-encrusted meats paired with airy grains that evoke the sensation of flight.

Travel Agent

2025-05-15T08:04

The attention to detail here is remarkable, from the polished service to the ritual of waiting for the silver bell before dessert, making the dining experience feel both special and memorable. Many guests appreciate the slow, unhurried pace, allowing the meal to unfold as a leisurely, almost poetic journey. If you enjoy settings that blend elegance with a touch of mystery and history, this spot is likely to leave a lasting impression and set a wonderful tone for the rest of your trip.

User

2025-05-15T08:05

One idea for lunch could be Ismene Courtyard Dining; it seems like a lovely spot with a nice ambiance, and I usually appreciate places that offer a relaxing courtyard setting for a midday meal.

Travel Agent

2025-05-15T08:05

It sounds like an absolutely enchanting choice for lunch, especially if you're looking to enjoy a serene and elegant atmosphere. This dining spot is known for its exquisite blend of culinary artistry and storytelling, all set beneath a canopy of fragrant wisteria blossoms in a charming courtyard. The restaurant draws inspiration from the myth of Ismene, a muse of generosity and grace, which perfectly reflects in both the dishes served and the warm hospitality extended to guests. One of the highlights is their signature dish—a masterful creation featuring slow-roasted herbs and rare sea truffle, a recipe born from a legend about humble fishermen sharing their bounty with a wandering oracle.

Travel Agent

2025-05-15T08:05

This story sets the tone for the dining experience, weaving a sense of tradition and myth that elevates the meal beyond mere sustenance into something truly memorable. The staff's white-glove service enhances the experience with a poised and attentive manner that ensures you can fully immerse yourself in the flavors without feeling rushed. As you arrive, especially around twilight, the courtyard transforms into a magical space with lanterns softly glowing and candlelight casting a warm, intimate ambiance. This creates a perfect setting not only for enjoying the meal but also for relaxing and savoring the moment, making it ideal for a peaceful midday break or even a lingering early evening meal.

Travel Agent

2025-05-15T08:05

The restaurant has a unique tradition where the dessert is served only when a soft bell chimes from the kitchen, signaling that the evening's story is unfolding perfectly—adding an element of anticipation and ritual to the dining journey. Many guests find themselves drawn to stay longer, captivated by the combination of exquisite cuisine, elegant surroundings, and the inviting atmosphere that encourages leisurely enjoyment and convivial conversation. It's a place that feels both intimate and expansive, where each course is part of a carefully choreographed experience. This makes it particularly well-suited for those who appreciate a relaxed yet refined dining pace, where the meal itself is as much about savoring time and stories as it is about the food.

Travel Agent

2025-05-15T08:05

Whether you're seeking a sophisticated spot for a quiet lunch or a charming place to unwind in the afternoon, it promises a memorable experience that gently elevates the everyday into the extraordinary. It's a choice that not only pleases the palate but also nourishes the spirit with its unique blend of history, ambiance, and culinary excellence.

User

2025-05-15T08:06

Could you tell me about the price range for breakfast at the 1th restaurant I raised before as the breakfast of Day 1's plan? I want to make sure it fits within our budget before we decide.

Travel Agent

2025-05-15T08:06

Certainly! Breakfast at It is priced at around \$76.22, which places it in the higher price range for breakfast options. This price reflects not only the quality of ingredients used but also the exceptional dining experience offered. The restaurant boasts a solid reputation, supported by positive guest reviews that highlight its refined ambiance and attentive service.

Travel Agent

2025-05-15T08:06

Many guests appreciate the thoughtfully curated breakfast menu, which features a blend of classic favorites and innovative dishes prepared with a gourmet touch. It's an excellent choice if you're looking to start your day with a luxurious meal in an elegant setting. Keep in mind that this upscale dining spot is well-suited for travelers who enjoy a leisurely, indulgent breakfast experience, possibly to celebrate a special occasion or to simply treat themselves. If you're mindful of your budget, this is a premium choice, but one that many find worthwhile for the quality and atmosphere it provides.

Travel Agent

2025-05-15T08:06

If you prefer a more casual or budget-friendly option, there might be other dining venues to consider, but It stands out for those who value both taste and presentation. Would you like more information on what the breakfast menu typically includes or suggestions for nearby alternatives?

User

2025-05-15T08:07

Could you tell me more about the price range and the ratings for breakfast at the 2th restaurant I raised before as the breakfast of Day 1's plan? I'm trying to get a sense of whether it's a good value and if it's well-liked by other travelers.

Travel Agent

2025-05-15T08:07

It offers breakfast at around \$170.24, placing it in the higher price range for morning meals, which suggests it caters to guests looking for a premium or unique dining experience. However, its rating is 2.7, which indicates mixed feedback from previous guests. This score might reflect some inconsistency in service or food quality, or perhaps it doesn't quite meet the expectations set by its pricing. Breakfast here might feature specialty dishes or an exclusive ambiance, likely situated in a scenic or prestigious location given the 'Summit' in its name, appealing to travelers seeking a memorable start to their day.

Travel Agent

2025-05-15T08:07

While it may not be the best value for all guests, some visitors might appreciate the atmosphere or the quality of ingredients despite the higher cost. It might suit those who prioritize the experience and are less sensitive to price, but if you're looking for a budget-friendly or consistently highly rated breakfast spot, this may require some consideration. Keep in mind it's always good to read recent reviews or ask about specific menu options to ensure it aligns with your preferences.

User

2025-05-15T08:08

Let's learn more about the 1st activity we want to schedule during the day we are discussing. One idea is to visit the Andromeda Galaxy Dome. I think it could be a fascinating spot since I love astronomy, and it seems like a peaceful place to unwind and learn something new.

Travel Agent

2025-05-15T08:08

It sounds like a wonderful choice, especially for someone with a passion for astronomy. Nestled at the edge of the old riverside quarter, this attraction offers a serene escape into the cosmos. Its geodesic structure is a contemporary homage to ancient stargazing, creating a unique atmosphere that

connects visitors with the night sky in a meaningful way. The dome was created from the vision of a modest stargazer who wanted to share the wonders of the universe affordably, and today it stands as an inviting and economical destination that welcomes both solo explorers and families.

Travel Agent

2025-05-15T08:08

One of the highlights of the dome is the softly glowing projection of the Andromeda constellation, which is accompanied by a gentle musical score during twilight hours. This creates a mesmerizing and calming experience that draws locals and visitors who appreciate the peaceful ambiance before the evening market buzz begins nearby. Guests usually spend about an hour here, seated on simple benches arranged around the dome's edge, where they can quietly reflect or share whispered legends, such as the story of a hidden star that is said to bring clarity of purpose if spotted just before the dome's quiet hour. The setting is thoughtfully designed to maintain a tranquil environment; for instance, there are gentle stairs for easy access, and pets are kindly asked to stay outside to preserve the peacefulness.

Travel Agent

2025-05-15T08:08

The dome's charm lies in its humble yet evocative tribute to the vast universe—it's a space that feels both intimate and mysterious, encouraging visitors to lose themselves in the wonder of the stars. This spot is ideal if you're looking for a place to unwind and soak in some cosmic inspiration. Many guests appreciate the dome's blend of quiet reflection and gentle storytelling, which makes it more than just an astronomy attraction but also a meaningful cultural experience. If you enjoy calm, educational environments with a touch of magic, it will surely resonate with you.

Travel Agent

2025-05-15T08:08

It's also worth noting that its location near the old riverside quarter means you could easily combine this visit with a stroll through charming historic streets afterward. Overall, it's a peaceful, accessible, and enriching destination for your itinerary.

User

2025-05-15T08:09

Let's learn more about the 1st activity we want to schedule during the day we are discussing. Could you tell me about the ticket prices for the the first place I raised before as the first activity of the Day 1's plan? I'm trying to figure out if it fits within our budget for the day.

Travel Agent

2025-05-15T08:09

The ticket price for it is \$33.94, which positions it in the mid-range category for attractions of its kind. This price reflects a balanced investment for an immersive and engaging experience, often featuring high-tech visual displays and interactive exhibits that bring the cosmos to life. The Dome tends to be well-rated for its captivating presentations and educational value, making it a popular choice among visitors interested in astronomy and science. Many guests appreciate the blend of entertainment and learning it offers, making it suitable for families, couples, and solo travelers alike.

Travel Agent

2025-05-15T08:09

It's worth considering that this price includes access to specialized shows that aren't commonly found at other venues, adding to the overall value. Additionally, the Dome is usually located within a science center or museum complex, often surrounded by amenities such as cafes and gift shops, which can enhance your visit. So, if your budget allows for a mid-tier experience that combines fun and education, it is an excellent pick for your day's itinerary.

User

2025-05-15T08:10

Let's learn more about the 1st activity we want to schedule during the day we are discussing. I wonder if we could try visiting the Nyx Twilight Observatory. It seems like a unique spot, especially for

catching a stunning sunset and some star gazing later in the evening. Plus, I usually enjoy quiet, peaceful places like that.

Travel Agent

2025-05-15T08:10

It sounds like a truly enchanting choice for your visit, especially if you cherish quiet, reflective places that offer a deep connection to nature and the cosmos. Perched atop the mist-kissed cliffs of the old riverside quarter, this observatory is more than just a vantage point; it's steeped in local lore and offers an almost mystical experience as twilight descends. Named after Nyx, the guardian of dusk, it embodies the magic of the transition between day and night, creating a setting that feels both timeless and intimate. Visitors often arrive just as daylight fades, drawn to the observatory's distinctive domed silhouette standing out against the evening sky.

Travel Agent

2025-05-15T08:10

It's a place where you can spend hours tracing constellations through carefully polished lenses, guided by the quiet, knowledgeable night porter who enhances the experience with a calm and welcoming presence. The atmosphere is enriched by the subtle scents of aged wood and cooled stone, transporting guests to a serene, almost otherworldly state. One of the most cherished experiences here is the silent "twilight walk" along a lantern-lined path, a ritual said to draw the stars nearer for a clearer view. It's a perfect moment to savor peace and quiet before settling in for the celestial show.

... [Trajectory truncated. Total turns: 186. Showing first 40.] ...

Example trajectory 0: Condensed and truncated example of a travel planning trajectory in CAME-Bench

Pro-Side Debater

2025-01-01T00:00

Reducing restrictions on legal immigration fills labor shortages, increases productivity, and stimulates economic growth—especially in healthcare, STEM, agriculture, and service sectors facing chronic worker gaps.

That contention captures the central practical case: the U.S. faces persistent, observable shortages in specific occupations and industries, and this is precisely what immigration policy can correct. Bringing more legal workers into those fields does three things at once: it supplies the needed hands and skills now, it raises overall output by filling bottlenecks (so capital and domestic labor are used more efficiently), and it lowers prices or stabilizes wages in affected services—benefiting consumers and businesses.

Policy design matters. This is not advocating unfocused open borders; it's about targeted, evidence-driven liberalization: raise employment-based caps, create sector-specific visas tied to demonstrated shortages, and expedite permanent residency for occupations with sustained demand. These measures direct immigration where it produces the most economic benefit while guarding labor standards.

Con-Side Debater

2025-01-01T00:15

Contention: Expanded legal immigration could increase competition for jobs, particularly for low-skilled or vulnerable workers, putting downward pressure on wages and employment opportunities. This contention matters because it highlights a predictable economic mechanism and a real distributional effect. When that many more workers enter a labor market, especially without matching increases in demand for the specific types of labor they supply, this raises labor supply relative to demand in certain occupations and places. That, in turn, tends to reduce the bargaining power of incumbent low-wage workers and can compress their wages or raise unemployment.

There is empirical backing for these concerns. Several respected studies find that immigrant inflows can impose downward pressure on wages and employment for earlier arrivals and for native workers in the same low-skill segments. Rather than sweeping reductions, sensible alternatives include skill- and sector-targeted admissions and stronger wage and labor-enforcement provisions.

Con-Side Debater

2025-01-01T00:30

Here's why that still stands.

First, timing and funding structure matter. Many critical services are financed and planned on multi-year cycles. When population rises quickly, local governments cannot instantly expand capacity: hiring qualified staff and building classrooms take time.

Second, concentrated impacts produce hotspots. Immigrants are not evenly dispersed. They tend to settle where jobs and social networks already exist, which concentrates demand in particular school districts and neighborhoods. One overwhelmed county or city can experience overcrowded classrooms and longer emergency-room waits that aren't visible in aggregate statistics.

All of this shows the contention is not just about aggregate numbers of people but about the practical, institutional realities of local service delivery.

Con-Side Debater

2025-01-01T00:36

I disagree with that contention — it overstates a simple policy link and ignores important trade-offs and practical limits.

1) Correlation isn't causation. Those high-profile innovators often succeed because of U.S. universities and venture capital networks. Easing all restrictions won't reproduce those specific institutional supports.

2) Measurement problems bias the claim. Counting patents or startup founders inflates one dimension of economic contribution but ignores quality and survivorship bias.

3) Distributional and fiscal consequences are overlooked. Large, rapid inflows can raise housing costs and strain schools, harms that fall on lower-income native workers.

In short, the contention assumes a direct, unambiguous causal effect from broad liberalization to more innovation. That link is weak.

Pro-Side Debater

2025-01-01T02:33

This case argues that substantially reducing federal restrictions on legal immigration produces clear economic, fiscal, and social benefits. Those changes would fill chronic labor shortages and raise productivity in high-need fields—healthcare, STEM, agriculture, and services—so that the economy can grow and operate efficiently. This shift would also make it easier to attract and retain global talent who disproportionately found startups and drive research. Finally, this approach offsets population aging and decline, revitalizes communities, and reaffirms America's identity as a nation of opportunity and pluralism.

Con-Side Debater

2025-01-01T02:36

These are the core reasons we oppose substantially reducing federal immigration restrictions. First, this change would intensify competition for jobs, especially among low-skilled and vulnerable workers. Second, this policy would likely accelerate brain drain from poorer countries. Third, these inflows would place real pressure on local public services that often cannot scale funding quickly enough. Finally, a rapid expansion risks overwhelming integration systems, producing social tension and political backlash. Together, these points form a coherent argument that reducing restrictions carries significant costs that should not be underestimated.

... [Trajectory condensed for showcase. Full benchmark contains 53 detailed turns.] ...

```

class TurnScopeSignature(dspy.Signature):
    """
    Determine which context scope this utterance belongs to.

    Guidelines
    1. The granularity of the context scope should be similar to as previous context scopes.
    2. Combined with the utterance, you must consider the best context scope to quickly partition the conversation into
    different scopes.
    3. Observe the current utterance carefully to identify whether it signals a context scope transition or continuation within
    the same context scope.
    4. Compare with prior_structured_notes to check if the utterance refers back to or continues a prior context scope.
    5. Default to continuity:
        Read full utterance carefully, if the utterance does not explicitly introduce a new context scope, assign the same
        context scope as the most recent relevant prior note.
    6. Detect transitions:
        When the speaker introduces a transition to a new context, assign a new context scope label to reflect that shift.
    7. Maintain consistency:
        ALWAYS check the existing_context_scopes list first. If the utterance refers to a topic that matches an existing scope (
        even if semantically similar), reuse that exact string form. Only create a new scope if no existing scope matches.
    """

    turn_id: str = dspy.InputField()
    role: str = dspy.InputField()
    utterance: str = dspy.InputField()
    conversation_type: str = dspy.InputField()
    prior_structured_notes: str = dspy.InputField(
        description="Previously predicted scopes with turn_id, role, and context_scope (last 20 turns).")
    )
    existing_context_scopes: str = dspy.InputField(
        description="JSON list of all unique context scope labels that have been used in this conversation so far. Check this
        list first to reuse existing scopes before creating new ones.")
    )
    context_scope: str = dspy.OutputField()

```

Listing 1: Prompts for thematic scope generation, as detailed in §2.2.1. In the prompt text, we refer to thematic scope as “context scope,” and “prior structure notes” correspond to the recent history H_{scope} .

```

class ContextNoteKeepingSignature(dspy.Signature):
    """Your goal is to maintain a clear, scope-explicit summaries.

    Rules:
        1. Resolve ambiguity or confusion

        - The prior context notes are from the same scope as the current segment.
        - The prior context notes provide all the information mentioned in the same scope
        - Use prior context notes safely to resolve all vague references to disambiguate the current segment

        2. Content

        - Capture only new, semantically meaningful developments
        - List important new targets within each scope as numbered or bulleted items for clarity
        - You should not list any vague references or pronouns that are not resolved by the prior context notes
    """

    context_scope: str = dspy.InputField(description="Name of the context scope shared by this segment.")
    prior_segment_level_notes: str = dspy.InputField(description="JSON list of previous notes for this same scope, ordered chronologically.")
    segment_turns: str = dspy.InputField(description="JSON list of dictionaries with keys (turn_index, role, utterance) for each turn in this scope segment.")
    segment_level_note: str = dspy.OutputField(description="1-3 sentence update capturing new developments for this scope.")

```

Listing 2: Prompts for generating a compressed summary Σ_σ of thematic scope, as detailed in §2.2.1.

```

class EventTypeLabelGenerationSignature(dspy.Signature):
    """
    Generate a list of event type labels that describe the different types of discussions or events that occur in a conversation. Given the first 50 turns of a conversation and the dataset type, identify the distinct event types or discussion themes present. Event types should be concise labels that capture the nature of the events and can be used to describe multiple similar events.
    """

    first_turns_summary: str = dspy.InputField(description="Summary of the first 50 turns (first sentence + '...' + last sentence of each turn)")

    dataset_type: str = dspy.InputField(description="Type of dataset")

    event_type_labels: list[str] = dspy.OutputField(description="List of event type labels for this conversation")

class EventTypeLabelValidationSignature(dspy.Signature):
    """
    Given a batch of consecutive turns and the current set of event type labels, determine if new event types are present that are not covered by existing labels. Also, check if the existing labels have appropriate coverage and description to describe the batch of turns. Make least number of changes to the existing labels. Only add new labels if necessary. Return ONLY the new event type labels that should be added to the existing set.

    If the existing labels are sufficient, return an empty list. Do NOT return the full updated list, only return the new labels to add.
    """

    batch_turns_summary: str = dspy.InputField(description="Summary of a batch of 50 consecutive turns (first sentence + '...' + last sentence of each turn)")

    existing_event_labels: list[str] = dspy.InputField(description="List of existing event type labels")

    dataset_type: str = dspy.InputField(description="Type of dataset")

    new_event_labels: list[str] = dspy.OutputField(description="ONLY the new event type labels to ADD to the existing set. Return empty list if no new labels needed.")

```

Listing 3: Prompts for generating initial event label seeds and evolving the dynamic label space, as detailed in §2.2.2.

```

class FineGrainedFunctionalSeedSignature(dspy.Signature):
    """You are given (1) a dataset description and (2) a sample of turns. Your task is to derive a list of fine-grained functional type that describe how specific details, facts, references, options, or objects are being used to advance the task in this dataset. IMPORTANT: - You ARE generating a list of pragmatic, task-driven functional type names that that represent how fine-grained details participate in argumentation, reasoning, decision-making, planning, critique, or exploration. - Think in terms of what work each detail is doing for the speaker or agent. Method: 1. Understand the dataset 's task type from the description. 2. From the sample turns, identify recurring uses of specific details: - What are these details achieving pragmatically? - How do they drive the conversation or task forward? 3. Abstract the observed uses into general *functional types*. - Names should be concise noun or noun-phrase labels (2-4 words). - Different names should distinguish from each other. - The number of functional type names is limited, so you should use the most general and neutral names that can cover meaningful details in the dataset. 4. Order the list from most representative to least representative.
    """
    dataset_description: str = dspy.InputField()
    sample_turns: str = dspy.InputField()
    functional_type_seeds: list[str] = dspy.OutputField()

```

Listing 4: Prompts for generating key entity type label seeds and evolving the dynamic label space, as detailed in §2.2.3. In the prompt text, we refer to key entity types as “function types.”

```

class TurnNoteContentSignature(dspy.Signature):
    """
    Generate structured note content (act, target, and note_text) for a turn, conditioned on the known context_scope and event
    types.

    Objective:
    Express the speaker's communicative intent in a concise, structured way, identifying their pragmatic action (act), the
    entity/topic it concerns (target), and a short natural-language summary (note_text).

    Guidelines

    1. Act identification:
        Based on the dataset type and the role of the speaker, determine the speaker's pragmatic act
    2. Target identification:
        Identify the specific entity, topic, claim, or object that drives the discussion.

        - If a concrete object or entity name is explicitly mentioned and drives the discussion, select that as the target.
        - If not explicitly mentioned, infer the implicit object from the semantic meaning of the utterance.
        - When ambiguous, refer to prior structured_notes within the same context scope or event types to infer or resolve the
        referent.
        - Resolve pronouns or elliptical expressions (e.g., "it," "this one," "there") by tracing to previously mentioned entities
        or items.

    Note text composition:
    Write one short, functional sentence summarizing what the speaker is doing and about what.

        - If a concrete object or entity name is explicitly mentioned and drives the discussion, include the entity name described
        accurately in the note text.
        - Focus on communicative intent and salient target attributes.
        - Do not include irrelevant details or paraphrase entire utterances.
    4. Functional types selection:
        - The provided functional type candidates are a list of pragmatic and task-driven high-level types aggregating the
        functions of meaningful details in the dataset.
        - Read the utterance carefully and select 0 to any number of functional types that cover the details that drive the
        utterance.
    5. Context-awareness:
        - Ensure the generated act and target align with the given context_scope.
        - The scope defines what sub-topic or thread this turn contributes to.
        Use segment_level_notes to recall prior developments within this scope.
    6. Event-type conditioning:
        - Use event_types to refine your interpretation
    7. Consistency check:
        - If multiple prior turns have similar acts or targets under the same scope, maintain consistent terminology and
        phrasing.

    """

    turn_id: str = dspy.InputField()
    dataset_type: str = dspy.InputField()
    role: str = dspy.InputField()
    utterance: str = dspy.InputField()
    context_scope: str = dspy.InputField()
    event_types: str = dspy.InputField(description="Comma-separated event type labels for the current turn")
    prior_structured_notes: str = dspy.InputField(description="Prior notes sharing the same context scope or event types, used
    for disambiguation.")
    segment_level_notes: str = dspy.InputField(description="JSON list of segment-level summaries for this scope observed up to
    the current turn.")
    functional_type_seeds_candidates: list[str] = dspy.InputField(description="List of functional type candidates to choose
    from for the turn.")
    act: str = dspy.OutputField()
    target: str = dspy.OutputField()
    note_text: str = dspy.OutputField()
    functional_type_seeds: list[str] = dspy.OutputField()

```

Listing 5: Prompts for generating a canonical summary c_t for each step in the trajectory as the final step of memory snippet construction, as detailed in §2.2.4.

```

class ContextScopeLabelSelectionSignature(dspy.Signature):
    """Select appropriate number of labels for context_scope field to filter conversation turns that can help answer the question.

    Your task is, read the label names to judge if the label is useful to answer the question. Don't overthink. The useful label names will implicitly or explicitly tell relevant information to the question. Then select an appropriate number (can be 0) of useful labels.

    Select the label names that are likely to be useful to answer the question.
    """
    question: str = dspy.InputField()
    context_scope_candidates: List[str] = dspy.InputField(description="All unique context_scope values in the dataset")
    selected_context_scopes: List[str] = dspy.OutputField(description="An appropriate number of selected context_scope values (empty list if none relevant)")
    reasoning: str = dspy.OutputField(description="Reasoning for the selected context_scope values")

```

Listing 6: Prompts for selecting thematic scope \mathcal{S}_q during retrieval as detailed in §2.3. In the prompt text, we refer to thematic scope as “context scope”.

```

class EventTypeLabelSelectionSignature(dspy.Signature):
    """Select appropriate number of labels for event_types field to filter conversation turns that can help answer the question.

    Your task is, read the label names to judge if the label is useful to answer the question. Don't overthink. The useful label names will implicitly or explicitly tell relevant information to the question. Then select an appropriate number (can be 0) of useful labels.

    Select the label names that are likely to be useful to answer the question.
    """
    question: str = dspy.InputField()
    event_type_candidates: List[str] = dspy.InputField(description="All unique event_type values in the dataset")
    selected_event_types: List[str] = dspy.OutputField(description="An appropriate number of selected event_type values (empty list if none relevant)")
    reasoning: str = dspy.OutputField(description="Reasoning for the selected event_type values")

```

Listing 7: Prompts for selecting event type \mathcal{E}_q during retrieval as detailed in §2.3.

```

class FunctionalTypeSeedsLabelSelectionSignature(dspy.Signature):
    """Select appropriate number of labels for functional type seeds field to filter conversation turns that can help answer the question.

    Your task is, read the label names to judge if the label is useful to answer the question. Don't overthink. The useful label names will implicitly or explicitly tell relevant information to the question. Then select an appropriate number (can be 0) of useful labels.

    Select the label names that are likely to be useful to answer the question.
    """
    question: str = dspy.InputField()
    functional_type_seeds_candidates: List[str] = dspy.InputField(description="All unique functional type seeds values in the dataset")
    selected_functional_type_seeds: List[str] = dspy.OutputField(description="An appropriate number of selected functional type seeds values (empty list if none relevant)")
    reasoning: str = dspy.OutputField(description="Reasoning for the selected functional type seeds values")

```

Listing 8: Prompts for selecting key entity types \mathcal{K}_q during retrieval as detailed in §2.3. In the prompt text, we refer to key entity types as “function types.”

```

class FreeformAnswerGenerator(dspy.Signature):
    """
    Answer a freeform question using the given set of retrieved conversation turns.
    Read carefully the question. The retrieved turns are a set of relevant and useful turns to answer the question. You need
    review these turns carefully to answer the question correctly.
    In case of doubt or uncertainty, do not guess, say "I don't know".
    """
    question: str = dspy.InputField(description="The question to be answered")
    task_setting: str = dspy.InputField(description="The setting of the task you are answering")
    retrieved_turns: str = dspy.InputField(
        description="A list of conversation turn contents relevant to the question.")
    answer_reasoning: str = dspy.OutputField(description="Provide one sentence reasoning on your answer")
    output: str = dspy.OutputField(
        description="An answer to the question. If the question is not answerable, return 'Question not answerable'")

```

Listing 9: Response generation prompts for open-domain and travel planning question answering in CAME-Bench.

```

class FreeformAnswerGenerator_Debate(dspy.Signature):
    """
    Answer a freeform question using the given set of retrieved conversation turns.
    Read carefully the question. The retrieved turns are a set of relevant and useful turns to answer the question. You need
    review these turns carefully to answer the question correctly. You should not include any irrelevant information in your
    answer. Give the shortest answer that correctly answer the question.
    In case of doubt or uncertainty, do not guess, say "I don't know".
    """
    question: str = dspy.InputField(description="The question to be answered")
    task_setting: str = dspy.InputField(description="The setting of the task you are answering")
    retrieved_turns: str = dspy.InputField(
        description="A list of conversation turn contents relevant to the question.")
    answer_reasoning: str = dspy.OutputField(description="Provide one sentence reasoning on your answer")
    output: str = dspy.OutputField(
        description="An answer to the question. If the question is not answerable, return 'Question not answerable'")

```

Listing 10: Response generation prompts for debate question answering in CAME-Bench.

```

class LLMAnswerEvaluatorSignature(dspy.Signature):
    """Your task is to label an answer to a question as \"CORRECT\" or \"WRONG\".
    You will be given the following data: (1) a question, (2) a gold answer, and (3) a generated answer.
    The gold answer is concise and contains the ground-truth information. The generated answer might be longer.
    Be generous: if the generated answer contains the gold answer information (even verbatim inside a longer response),
    mark it as CORRECT. Otherwise, mark it as WRONG. Respond with either CORRECT or WRONG, and provide a brief reasoning."""
    question: str = dspy.InputField(description="The question being evaluated")
    gold_answer: str = dspy.InputField(description="Gold answer text")
    generated_answer: str = dspy.InputField(description="Generated answer text")
    verdict: str = dspy.OutputField(description="CORRECT or WRONG")
    reasoning: str = dspy.OutputField(description="Short justification")

```

Listing 11: Answer automatic evaluation prompt with LLM for question answer that is a single answer

```

class LLMAnswerEvaluatorNumberSignature(dspy.Signature):
    """Your task is to give the number of correct candidates to a question appearing in the generated answer.
    You will be given the following data: (1) a question, (2) a gold answer containing several correct candidates, and (3) a
    generated answer.
    The gold answer and contains the ground-truth candidates. Go through each candidate in the generated answer carefully and
    check if any of them appear in the gold answer list.
    Respond with the number of correct candidates covered by the generated answer, and provide a brief reasoning."""
    question: str = dspy.InputField(description="The question being evaluated")
    gold_answer: List[str] = dspy.InputField(description="Gold answer candidates (list)")
    generated_answer: List[str] = dspy.InputField(description="Generated answer candidates (list)")
    number_of_correct_candidates: int = dspy.OutputField(description="Number of correct candidates")
    reasoning: str = dspy.OutputField(description="Short justification")

```

Listing 12: Answer automatic evaluation prompt with LLM for question answer that is an answer set