
InstructSAM: A Training-Free Framework for Instruction-Oriented Remote Sensing Object Recognition

Yijie Zheng, Weijie Wu

Aerospace Information Research Institute,
Chinese Academy of Sciences
University of Chinese Academy of Sciences
{zhengyijie23,wuweijie25}@mailsucas.ac.cn

Qingyun Li

Harbin Institute of Technology
21b905003@stu.hit.edu.cn

Xuehui Wang

Shanghai Jiao Tong University
wangxuehui@sjtu.edu.cn

Xu Zhou, Aiai Ren, Jun Shen

University of Wollongong
{xz572,ar243,jshen}@uowmail.edu.au

Long Zhao, Guoqing Li✉

Aerospace Information Research Institute,
Chinese Academy of Sciences
{zhaolong,ligq}@aircas.ac.cn

Xue Yang

SAIS, Shanghai Jiao Tong University
yangxue-2019-sjtu@sjtu.edu.cn

Abstract

Language-guided object recognition in remote sensing imagery is crucial for large-scale mapping and automated data annotation. However, existing open-vocabulary and visual grounding methods rely on explicit category cues, limiting their ability to handle complex or implicit queries that require advanced reasoning. To address this issue, we introduce a new suite of tasks, including Instruction-Oriented Object Counting, Detection, and Segmentation (InstructCDS), covering open-vocabulary, open-ended, and open-subclass scenarios. We further present EarthInstruct, the first InstructCDS benchmark for earth observation. It is constructed from two diverse remote sensing datasets with varying spatial resolutions and annotation rules across 20 categories, necessitating models to interpret dataset-specific instructions. Given the scarcity of semantically rich labeled data in remote sensing, we propose InstructSAM, a training-free framework for instruction-driven object recognition. InstructSAM leverages large vision-language models to interpret user instructions and estimate object counts, employs SAM2 for mask proposal, and formulates mask-label assignment as a binary integer programming problem. By integrating semantic similarity with counting constraints, InstructSAM efficiently assigns categories to predicted masks without relying on confidence thresholds. Experiments demonstrate that InstructSAM matches or surpasses specialized baselines across multiple tasks while maintaining near-constant inference time regardless of object count, reducing output tokens by 89% and overall runtime by over 32% compared to direct generation approaches. We believe the contributions of the proposed tasks, benchmark, and effective approach will advance future research in developing versatile object recognition systems. The code is available at <https://VoyagerXvoyerx.github.io/InstructSAM/>.




Figure 1: Comparison of four task settings in object detection and segmentation. The sample is from DIOR Dataset [34] (a) Close-set: Standard annotation with categories defined in the DIOR dataset. (b) Open-vocabulary: Instruction specifies which categories to detect and segment (e.g., “soccer field”, “football field”, “parking lot”). (c) Open-ended: Instruction requires detection and segmentation of all visible objects without category specification. (d) Open-subclass: Instruction targets all objects within a super-category (e.g., “sports fields”).

1 Introduction

Object recognition in remote sensing imagery captures a vast array of objects and phenomena across diverse environments, providing rich information for supporting achieving the Sustainable Development Goals issued by the United Nations [59, 3], such as wildlife monitoring [82, 96], poverty estimation [1, 50], and disaster response [18]. The recent advent of powerful vision-language models (VLMs), such as CLIP [61], has ushered in a new era of remote sensing oriented open-vocabulary object recognition algorithms (e.g. detection [38, 56] and segmentation [21]). However, existing open-vocabulary approaches predominantly rely on explicit category cues, which restrict their capability to handle complex or implicit queries that demand advanced reasoning and contextual understanding. In other words, the rich diversity of visible objects in remote sensing images, due to the bird’s-eye view, predicates that any predefined, fixed list of categories is inevitably incomplete, limiting its practicality for open-ended analysis in the real world.

To address this issue, we expand the instruction-oriented object detection task [60] and introduce a novel suite of tasks—Instruction-Oriented Object Counting, Detection, and Segmentation (**InstructCDS**) that encompasses open-vocabulary, open-ended, and open-subclass settings, as illustrated in Figure 1. The InstructCDS task entails a more flexible and scalable interpretation beyond fixed category sets and comprehends the complex users’ task requirements. We further present **Earth-Instruct**, the first benchmark for InstructCDS in earth observation. The benchmark is constructed from two generic remote sensing object datasets covering 20 categories with different annotation rules and spatial resolution. EarthInstruct guides models to comprehend complex user instructions beyond the predefined three settings.

Recent advancements in VLMs have demonstrated impressive performance in object detection [45, 40, 60, 57], semantic segmentation [89, 11, 94], visual grounding [2, 7] and reasoning-based segmentation [66, 29] within the natural image domain. However, transferring these methods to remote sensing imagery presents several challenges. **First**, direct inference leads to significant accuracy degradation due to the domain gap between natural and aerial images [14]. **Second**, most existing remote sensing open-vocabulary detection [38, 39, 90, 31] and segmentation [91, 88, 21] methods are trained on datasets with only a limited number of categories, restricting their generalization to diverse unseen categories. **Third**, conventional detectors [35, 10, 51] rely on a threshold to filter predicted bounding boxes, which is not obtainable in zero-shot scenarios.

To tackle these challenges, we decompose the instruction-oriented object detection and segmentation tasks into several tractable steps and propose a framework without task-specific training, **Instruct-SAM**. First, a large vision-language model (LVLM) is employed to interpret user instructions and predict **object categories** and **counts**, with prompts systematically designed to maximize model’s capability. In parallel, SAM2 [63] is utilized to automatically generate **mask proposals**. Next, a CLIP model pre-trained on remote sensing images computes the **semantic similarity** between the predicted objects categories and mask proposals. We then formulate the object detection and segmentation as a **mask-label matching** problem, assigning predicted categories to mask proposals

by integrating semantic similarity and global counting constraints. By inherently integrating three powerful foundation models, InstructSAM achieves superior performance across multiple tasks compared to both generic and remote sensing-specific VLMs trained on large-scale object recognition data. Notably, the inference time of InstructSAM remains nearly constant with respect to the number of predicted objects, reducing output tokens by 89% and overall runtime by 32% compared to directly generating bounding boxes using Qwen2.5-VL [2] in the open-ended setting. Our work paves the way for scalable, instruction-driven remote sensing object detection and segmentation, eliminating the need for costly pre-training or manual threshold tuning. Furthermore, the training-free paradigm allows InstructSAM to recognize objects in natural images when equipped with generic CLIP models.

In summary, our contributions are as follows:

- We introduce the InstructCDS task, which challenges models to interpret user-provided natural language instructions and infer the number and locations of relevant objects.
- We construct EarthInstruct to benchmark InstructCDS in earth observation, covering open-vocabulary, open-ended, and open-subclass settings and counting, detection, and segmentation tasks.
- We develop InstructSAM, a training-free and confidence-free framework achieving near-constant inference time for the InstructCDS task.
- Experiments on the benchmarks demonstrate that InstructSAM matches close-set models in object counting and surpasses generic and remote sensing-specific models in open-vocabulary and open-ended object recognition.

2 Related work

2.1 Instruction-oriented object detection and segmentation

Instruction-oriented methods Instruction-oriented object detection (IOD), first introduced in [60], includes four instruction settings: category-specified (open-vocabulary [80]) detection, detection of all objects (open-ended [40]), detection within a super-category (we name it open-subclass), and detection to achieve certain goals. Ins-DetCLIP [60] trains a detector to identify foreground objects and passes their features to a large language model (LLM) to generate categories based on user instructions. In addition to models specifically designed for the IOD task, Qwen2.5-VL [2], trained on multi-task instruction data, also showcases the ability of dense object detection. However, both approaches require extensive task-specific training data, and their inference times increase substantially with the number of objects.

Open-vocabulary methods Large-vocabulary object detection and segmentation datasets [70, 17, 76] and visual grounding datasets [27, 23] enable various open-vocabulary learning approaches, including knowledge distillation [16] and region-text pre-training [26, 52, 45, 35]. Self-training with confidence threshold-filtered pseudo labels from image-text pairs (e.g., CC3M [5], WebLI2B [6]) further boosts the performance [51, 45, 93, 87]. However, the quality of pseudo labels is highly sensitive to the chosen threshold [51], and these methods require predefined object categories, limiting their flexibility in diverse scenarios.

Open-ended methods GenerateU [40] first formulates the open-ended object detection (OED) problem. Concurrent works such as DetCLIPv3 [87], Florence-2 [83], and DINO-X [65] introduce generative frameworks that jointly predict object categories and bounding boxes using language models. However, constructing large-scale datasets with bounding box and caption pairs is resource-intensive. VL-SAM [41] proposes a training-free approach via attention as prompts, but its iterative mask refinement and multi-prompt ensemble strategies are computationally expensive.

2.2 Instruction-oriented remote sensing object detection and segmentation

Recent advances in VLMs [61, 44] have also enabled open-vocabulary learning in the remote sensing domain. Diverse semantic tags from OpenStreetMap [19] and those generated by LVLMs drive the development of contrastive language-image pre-training in remote sensing images [95, 77]. Following the generic open-vocabulary learning frameworks, methods for remote sensing open-vocabulary

detection [38, 79, 56, 22] and segmentation [91, 88, 21, 32] methods emerge. However, their human-annotated training data, being limited to a few dozen categories [34, 78, 73, 47], hinder generalization to out-of-distribution or zero-shot scenarios. Although some remote sensing LVLMs could support object recognition tasks like single-class object detection [28, 49, 25], visual grounding [54, 58], referring expression segmentation [97, 55], grounded conversation generation [68], and scene graph generation [49], they failed to follow complex reasoning instructions, such as open-vocabulary and open-subclass object detection. To annotate vast-vocabulary training data for remote sensing object detection, LAE-Label [56] employs a generic LVLm [8] to predict categories for cropped mask proposals. However, this approach loses global context for accurate category classification.

In contrast, our InstructSAM adopts a confidence-free paradigm, requires no task-specific pre-training or finetuning, and maintains near-constant inference time regardless of object counts.




Figure 2: Annotation samples from NWPU-VHR-10 (a) and DIOR (b-d) illustrating rules that might differ from common sense. (a) Ships and vehicles are unannotated in low-resolution images (NWPU-VHR-10). (b) Expressway service areas separated by a road are treated as distinct instances (DIOR). (c, d) Airports are annotated only when fully visible (DIOR).

3 EarthInstruct, a benchmark for InstructCDS in remote sensing

3.1 Instruction setup

To enable practical applications in remote sensing such as large-scale mapping [1] and image annotation, we define three distinct settings for InstructCDS:

- 1) **Open-vocabulary**: Counting, detection, and segmentation with user-specified categories.
- 2) **Open-ended**: Counting, detection, and segmentation of all objects without specifying categories.
- 3) **Open-subclass**: Counting, detection, and segmentation of objects within a super-category.

We construct EarthInstruct using NWPU-VHR-10 [9] and DIOR [34] datasets, selected for their widespread use and diverse sensors, resolutions, and annotation rules. Critically, these dataset-specific annotation rules might deviate from common sense (e.g., excluding low-resolution vehicles) or exhibit semantic ambiguities (e.g., “bridge” vs. “overpass”), reflecting the original annotators’ specific goals (Figure 2). Consequently, simple instructions like “count vehicles” would fail to capture the nuances required by dataset conventions or user intent. EarthInstruct therefore necessitates models to interpret detailed instructions that clarify target definitions and handle dataset-specific rules (e.g., “do not count vehicles in images with a spatial resolution lower than 1m.”). To ensure fair evaluation aligned with dataset conventions and user requirements, prompts are designed accordingly, but image-specific prompts are prohibited to maintain scalability for large-area applications where prior content knowledge for each image is unavailable.

3.2 Evaluation metrics

Multi-class object counting Standard counting metrics, such as Mean Absolute Error (MAE) and Root Mean Squared Error (RMSE), used in benchmarks like FSC-147 [62] and RSOC [15], inadequately capture nuanced multi-class evaluation. They cannot distinguish between over-counting and under-counting errors. Additionally, being unnormalized, they allow categories with larger counts to disproportionately skew the overall score when being averaged across classes.

To address these issues, we adopt precision, recall, and F₁-score, whereby offering normalized, per-class insights. We define per-image, per-class counting components as follows: let C_{gt} denote the ground truth count and C_{pred} the predicted count for a class in an image. Then, True Positives (TP) = $\min(C_{gt}, C_{pred})$, False Positives (FP) = $\max(0, C_{pred} - C_{gt})$ for over-counting, and False Negatives (FN) = $\max(0, C_{gt} - C_{pred})$ for under-counting. These definitions enable standard calculation of precision, recall, and F₁-score, aggregated across images per class and then averaged for a final score.

Rethinking metrics for confidence-free detectors Evaluating generative models like Florence-2 [83] or Qwen2.5-VL [2], which output detections without confidence scores, poses a challenge for standard metrics. Average Precision (AP) [12] relies on confidence scores to rank predictions and generate precision-recall curves. Without such ranking, standard AP is ill-defined. Furthermore, practical applications often involve filtering predictions with a fixed threshold, treating all remaining detections equally [1, 51].

To resolve these issues and ensure fair comparison, we adopt confidence-free metrics: mean F₁-score (mF₁) and mean Average Precision with no confidence (mAP_{nc}) [36]. mF₁ measures performance at a single operating point, suitable for fixed-threshold deployment. mAP_{nc} adapts AP by assigning maximum confidence to all predictions. For confidence-free models, these metrics are computed directly (Results in Table 10). For conventional detectors (e.g., [64, 4]) that provide scores, when the confidence threshold is swept from 0 to 1 (step 0.02), the threshold maximizing mF₁ (using an IoU threshold of 0.5) across categories is selected, and the corresponding cusp score is reported.

Evaluating open-ended and open-subclass settings In open-ended and open-subclass settings, LVLMs may generate category names (e.g., “car”) that differ textually from ground truth labels (e.g., “vehicle”). To handle this synonymy during evaluation, we adopt semantic similarity matching by following established protocols [40, 60]. Specifically, we encode generated categories and ground truth categories using the GeoRSCLIP [95] text encoder with the template “a satellite image of a {category}”. A generated category name is deemed equivalent to a ground truth category if their embedding cosine similarity exceeds 0.95. This allows predicted objects associated with the generated name to be accurately evaluated against the matched ground truth category.

4 InstructSAM

Addressing the challenges of instruction-following, domain gaps, and threshold sensitivity in remote sensing object recognition, we propose a training-free framework named InstructSAM. It decomposes InstructCDS into three synergistic steps: instruction-based object counting using an LVLM, class-agnostic mask proposing via SAM2, and a novel counting-constrained mask-label matching procedure. This approach avoids the costly model training and threshold tuning, offering efficient and robust performance.

4.1 Instruction-oriented object counting with LVLM

As illustrated in Section 3, accurately interpreting user intent in remote sensing requires handling dataset-specific rules and semantic ambiguities, which the simple category prompts could fail to capture. We leverage state-of-the-art LVLMs (e.g., GPT-4o [24], Qwen2.5-VL [2]) for this task. Inspired by [20], we utilize structured prompts in JSON format, which allows easy integration of dataset-specific Instructions alongside the core Task (detailed in Appendix C). Given an image I and a detailed prompt P , the LVLM acts as a counter, outputting the target categories $\{cat_j\}$ and their corresponding counts $\{num_j\}$ present in the image: $\{cat_j, num_j\}_{j=1}^M = \text{LVLM-Counter}(I, P)$.

4.2 Class-agnostic mask proposing

Concurrent with counting, SAM2 [63] is employed to generate high-quality, class-agnostic object masks for its strong generalization to remote sensing imagery [75, 81]. Using its automated mask generation mode prompted by a regular point grid, we obtain a dense set of masks proposals $\{mask_i\}_{i=1}^N$. To enhance recall for small objects, mask generation is also applied to image crops (detailed in Appendix C.4).




Figure 3: The InstructSAM framework. Given an input image and a structured counting prompt, the LVLM Counter extracts target categories $\{cat_j\}$ (semantic info) and their counts $\{num_j\}$ (quantitative info). Concurrently, the Mask Proposer generates mask proposals $\{mask_i\}$ (visual info). A CLIP model computes the similarity matrix S between mask embeddings (from scaled crops) $\{v_i\}$ and category embeddings $\{t_j\}$. Finally, the Binary Integer Programming (BIP) Solver optimally assigns categories to masks by maximizing summed similarity, subject to the counting constraints, yielding the final recognition results.

4.3 Mask-label matching with counting constraints

A key innovation of InstructSAM is reframing object detection and segmentation as a constrained mask-label matching problem, by integrating the outputs from previous steps. Rather than using fragile confidence thresholds [10, 51], we utilize global counts $\{num_j\}$ derived from the LVLM to constrain the assignment of semantic labels $\{cat_j\}$ to visual mask proposals $\{mask_i\}$.

Given N mask proposals and M target categories with counts, we compute a semantic similarity matrix $S \in \mathbb{R}^{N \times M}$, where s_{ij} represents the cosine similarity between the CLIP [95] image embedding of a patch cropped around $mask_i$ (scaled by 1.2 for context) and the text embedding of cat_j (using the template “a satellite image of a {category}”). We then seek a binary assignment matrix $X \in \{0, 1\}^{N \times M}$, where $x_{ij} = 1$ assigns $mask_i$ to cat_j , by solving the Binary Integer Programming (BIP) problem:

$$\min_{\mathbf{X}} \sum_{i=1}^N \sum_{j=1}^M (1 - s_{ij}) \cdot x_{ij} \quad (1)$$

$$\text{s.t.} \quad \sum_{j=1}^M x_{ij} \leq 1, \quad \forall i \in \{1, \dots, N\} \quad (2)$$

$$\sum_{i=1}^N x_{ij} = num_j, \quad \forall j \in \{1, \dots, M\}, \quad \text{if } N \geq \sum_{j=1}^M num_j \quad (3)$$

$$\sum_{i=1}^N \sum_{j=1}^M x_{ij} = N, \quad \text{if } N < \sum_{j=1}^M num_j \quad (4)$$

where constraint (2) ensures each mask is assigned to at most one category. Constraint (3) enforces that the number of assigned masks for each category matches the counts provided by the LVLM. Constraint (4) handles cases where the number of proposals is less than the total target count, ensuring all proposals are assigned.

As depicted in Figure 3, this BIP formulation elegantly fuses visual information, semantic information, and quantitative information. The visual information comes from the CLIP embeddings of mask proposals $\{v_i\}$, which contribute to s_{ij} . Semantic information is derived from the categories’ sentence embeddings $\{t_j\}$, also contributing to s_{ij} . Quantitative information from object counts $\{num_j\}$ serves as constraints in (3). The problem is efficiently solvable using open-source BIP solvers like PuLP [53]. The resulting non-zero entries in X define the final set of recognized objects $\{(mask_i, cat_j) | x_{ij} = 1\}$.

Table 1: Zero-shot performance comparison on EarthInstruct under open-vocabulary setting.

Method	NWPU-VHR-10				DIOR			
	Cnt F ₁	Box F ₁	Mask F ₁	IoU	Cnt F ₁	Box F ₁	Mask F ₁	IoU
Grounding DINO [45]	14.9	14.0	-	-	10.7	6.0	-	-
OWLv2 [51]	39.4	27.2	-	-	23.4	14.3	-	-
Qwen2.5-VL [2]	68.0	36.4	-	-	52.0	27.8	-	-
GSNet [88]	-	-	1.3	6.4	-	-	0.0	0.3
SegEarth-OV [32]	-	-	3.5	12.1	-	-	1.2	6.7
InstructSAM-Qwen	73.2	38.9	23.7	12.1	59.3	24.7	24.0	18.5
InstructSAM-GPT4o	83.0	41.8	26.1	14.8	79.9	29.1	28.1	20.2

5 Experiments

5.1 Implementation

We implement InstructSAM using GPT-4o-2024-11-20 [24] (short for InstructSAM-GPT4o) or Qwen2.5-VL-7B [2] (short for InstructSAM-Qwen) as the LVLm counter, SAM2-hiera-large [63] for mask proposal, and GeoRSCLIP-ViT-L [95] for similarity computation. For the open-vocabulary setting, we follow previous works [79, 21, 90] to split base and novel classes, and report mF₁, mean Insert-over-Union (mIoU), or mAP_{nc}. For open-subclass setting, we set two parent class “means of transport” and “sports fields”. We compare InstructSAM with a wide range of models, whose training data and abilities are listed in Table 6.

5.2 Results on EarthInstruct

Open-vocabulary setting We report mean metrics across all classes for generic methods [45, 51, 2] and remote sensing open-vocabulary segmentation models [88, 32] trained on broader vocabularies in Table 1. Zero-shot performance on novel classes for models trained on base classes [90, 79, 21] appears in Table 10. Models using novel class images or trained on entire detection datasets are evaluated on two additional datasets (Table 11).

Table 1 shows InstructSAM (esp. with GPT-4o) leading in all tasks with top counting metrics. On novel classes (Table 10), InstructSAM-Qwen achieves superior or competitive mAP_{nc} against specialized models. This underscores InstructSAM’s training-free, counting-constrained matching advantage over traditional or fine-tuned approaches.

Open-ended setting Table 2 summarizes the results under open-ended setting. InstructSAM consistently achieves equivalent or higher F₁-scores than remote sensing-specific methods, including those trained on grounded description tasks [49, 68]. Notably, InstructSAM surpasses LAE-Label [56] by leveraging a global view of the image to accurately predict object categories. While the absence of class-specific instructions in this setting limits further gains, InstructSAM still demonstrates robust performance (Figure 4).


Table 2: Performance comparison on EarthInstruct under open-ended setting.

Method	NWPU-VHR-10			DIOR		
	Cnt F ₁	Box F ₁	Mask F ₁	Cnt F ₁	Box F ₁	Mask F ₁
Qwen2.5-VL [2]	48.6	32.0	-	36.6	21.7	-
GPT-4o [24] + OWL [51]	32.6	24.0	-	30.6	21.0	-
SkySenseGPT [49]	34.9	1.7	-	39.2	6.5	-
EarthDial [71]	30.0	5.6	-	47.6	22.8	-
LAE-Label [56]	46.2	27.3	24.1	23.3	11.5	10.4
GeoPixel [68]	40.8	29.9	29.1	21.4	13.8	14.7
InstructSAM-Qwen	55.2	29.6	28.5	33.2	14.3	14.4
InstructSAM-GPT4o	57.4	31.3	29.9	47.9	22.1	21.8


Open-subclass setting Table 3 shows that InstructSAM outperforms or matches Qwen2.5-VL across both parent classes. When prompted with categories identified by GPT-4o, OWLv2 performs strongly for “means of transport” but struggles with “sports fields”, likely due to the prevalence of transport-related categories in natural image datasets. These findings are consistent with the open-vocabulary results, where generic detectors, such as Grounding DINO and OWL, struggle with remote sensing categories except for airplane, vehicle, and ship.

Table 3: Performance comparison on EarthInstruct under open-subclass setting. ‘S’ denotes the parent category “sports field”, and ‘T’ denotes “means of transport”.

Method	NWPU-VHR-10						DIOR					
	Cnt F ₁		Box F ₁		Mask F ₁		Cnt F ₁		Box F ₁		Mask F ₁	
	S	T	S	T	S	T	S	T	S	T	S	T
Qwen2.5-VL [2]	54.1	48.9	32.4	42.2	-	-	52.2	51.8	34.0	39.2	-	-
GPT-4o [24] + OWL [51]	40.3	68.0	19.8	65.9	-	-	41.5	73.6	27.6	70.9	-	-
InstructSAM-Qwen	50.9	55.3	33.5	41.9	33.0	39.7	40.4	67.4	22.2	49.3	22.6	49.5
InstructSAM-GPT4o	84.2	60.6	46.9	44.2	45.8	41.6	82.2	53.6	40.9	38.3	40.2	38.6



(a) Open-vocabulary setting



(b) Open-ended setting

(c) Open-subclass setting

Figure 4: Qualitative comparison of object detection and segmentation methods on DIOR dataset. InstructSAM consistently outperforms other methods in generating accurate bounding boxes and segmentation masks across various settings. More qualitative results can be found in Appendix F.




Figure 5: Inference time as a function of bounding box count for InstructSAM-Qwen and baseline methods. Solid lines indicate linear regressions, and scatter points represent individual samples. The shaded regions for InstructSAM illustrate the time composition of different processing steps. Experiments are conducted on an RTX 4090 GPU.

Inference time analysis Figure 5 compares inference times for open-ended methods using 7B LLMs. Mask proposal dominates the runtime of InstructSAM, whereas the PuLP optimizer solves the BIP problem in 0.07 seconds. InstructSAM maintains nearly constant inference time, while other methods scale linearly with the number of objects. Unlike representing bounding boxes as natural language tokens, InstructSAM reduces output tokens by 89% and total inference time by 32% compared to Qwen2.5-VL. This advantage will grow more pronounced as the model size scales up, highlighting the efficiency of our framework.

Table 4: Open vocabulary counting performance (Precision/Recall/F₁-score).

Method	Add Instr	NWPU vehicle	NWPU all	DIOR all
Faster-RCNN	×	15/49/23	77/77/73	91/74/81
Qwen2.5VL	×	11/75/19	80/72/72	73/53/56
Qwen2.5VL	✓	28/70/41	82/71/73	83/51/59
GPT-4o	×	11/80/20	68/79/67	87/65/72
GPT-4o	✓	75/68/71	83/83/83	86/75/80

Table 5: Ablations on model scaling. MP recall is class-agnostic recall of mask proposals.

LVLM Counter	Mask Proposal	CLIP	MP Recall	Box F ₁
GPT-4o	SAM2-L	DFN2B-L [13]	82.4	41.3
GPT-4o	SAM2-L	RemoteCLIP-L [43]	82.4	45.7
GPT-4o	SAM2-L	SkyCLIP-L [77]	82.4	45.8
GPT-4o	SAM2-L	SkyCLIP-B [77]	82.4	45.2
GPT-4o	SAM2-S	SkyCLIP-B [77]	79.1	44.1
Qwen2.5VL	SAM2-S	SkyCLIP-B [77]	79.1	40.6

5.3 Ablation studies

Prompt design Table 4 reveals how additional instructions enhance object counting, particularly for categories with ambiguous or dataset-specific annotation rules. Initially, DIOR-trained Faster-RCNN and LVLM counters exhibit low vehicle precision on NWPU-VHR-10. Explicit annotation rules in instructions significantly boost vehicle precision for Qwen2.5-VL and GPT-4o, and also improve mF₁ by 3% and 8%, respectively, on DIOR. Contrary to [92], these results show that capable foundation models with precise, instruction-driven prompts truly empower LVLMs to match or exceed closed-set model performance.

Model generalization and scaling To assess InstructSAM’s generalization and scalability, we ablate LVLM counters, mask proposers, and CLIP models for the open-vocabulary detection (OVD) task on NWPU-VHR-10 (Table 5). InstructSAM consistently benefits from CLIP models fine-tuned on remote sensing data [43, 77] over generic CLIP [13], whereby yielding higher Box F₁-scores. Performance improves with larger model components, demonstrating the framework’s scalability. Notably, even with a smaller SAM2-S and SkyCLIP-B, InstructSAM coupled with Qwen2.5-VL (40.6 Box F₁) outperforms direct detection using Qwen2.5-VL alone (36.4 Box F₁), underscoring the efficacy of our approach.

Mask-label matching with counting constraints Using fixed thresholds to filter CLIP predictions [10] has inherent limitations. In Figure 6, the green and blue solid curves show InstructSAM without matching, where predictions are filtered by a similarity score (CLIP score) threshold before evaluation. Optimal thresholds vary widely across categories. As a result, a single global value




Figure 6: Threshold sensitivity analysis in open-vocabulary setting. Left: Impact on mean metrics. Right: Category-specific F₁-scores. Dashed lines indicate optimal thresholds maximizing mF₁.

performs poorly, and the results are highly threshold-sensitive, which is consistent with the findings in [36]. In contrast, InstructSAM’s counting-constrained matching removes this dependency by dynamically assigning predictions according to the estimated counts, yielding stronger performance in multi-class and open-world settings.

5.4 Error analysis of OVD task

Error identification reveals distinct error patterns across methods (Figure 7). OWLv2 primarily suffers from classification errors, while Qwen2.5-VL shows improved classification but struggles with missed detections. InstructSAM-GPT4o benefits from SAM2’s localization capabilities, though the background confusion persists due to GeoRSCLIP’s scene-focused training, which prioritizes broader contexts over individual objects.




Figure 7: Error distribution of OVD task on NWPU-VHR-10 dataset. Pie charts show proportions of classification (Cls), localization (Loc), background (Bkg), and missed detection (Miss) errors across models.

6 Limitations

InstructSAM builds on pre-trained foundation models, and its performance inherits their capabilities and biases. For instance, SAM2 can miss the full extent of objects with intricate geometry (e.g., basketball court in Figure 4). CLIP models finetuned on scene-level remote sensing image–text pairs perform suboptimally when aligning object-level crops with semantic cues. More generally, foundation models such as GPT-4o and SAM are trained primarily on optical imagery and struggle to count or segment objects in synthetic aperture radar (SAR) images.

Future work can mitigate these limitations by (i) incorporating foundation models trained on semantically diverse, multi-modal remote sensing data and (ii) leveraging advanced class-agnostic region proposers [84]. Extending InstructSAM to semantic segmentation would further benefit the earth observation community. Although InstructSAM is only a first step, we aim to use it as an automated labeling engine to annotate at scale, enabling large, semantically rich object-recognition datasets.

7 Conclusion

In this paper, we introduce InstructCDS for instruction-driven object counting, detection, and segmentation, along with EarthInstruct, the first benchmark for this task in remote sensing domain. Our training-free InstructSAM framework integrates LVLMs, SAM2, and domain-specific CLIP to handle instruction-oriented scenarios with counting constrained mask-label matching. Experiments demonstrate that InstructSAM outperforms specialized baselines while maintaining near-constant inference time regardless of object counts. As the first approach extending instruction-oriented detection to the broader InstructCDS paradigm, InstructSAM will benefit from advancements in both remote sensing foundation models [42, 85, 86, 67, 69] and general-purpose models [74, 98, 48], paving the way for more scalable, instruction-driven earth observation data analysis.

Acknowledgement

This work was partly supported by the National Earth Observation Data Center Research Project (Grant No. E43Z18020A), National Natural Science Foundation of China (62506229), and Natural Science Foundation of Shanghai (25ZR1402268).

References

- [1] Kumar Ayush, Burak Uzcent, Kumar Tanmay, Marshall Burke, David Lobell, and Stefano Ermon. Efficient poverty mapping from high resolution remote sensing images. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 35, pages 12–20, 2021.
- [2] Shuai Bai, Keqin Chen, Xuejing Liu, Jialin Wang, Wenbin Ge, Sibao Song, Kai Dang, Peng Wang, Shijie Wang, Jun Tang, et al. Qwen2. 5-vl technical report. *arXiv preprint arXiv:2502.13923*, 2025.
- [3] Marshall Burke, Anne Driscoll, David B Lobell, and Stefano Ermon. Using satellite imagery to understand and promote sustainable development. *Science*, 371(6535):eabe8628, 2021.
- [4] Nicolas Carion, Francisco Massa, Gabriel Synnaeve, Nicolas Usunier, Alexander Kirillov, and Sergey Zagoruyko. End-to-end object detection with transformers. In *European conference on computer vision*, pages 213–229. Springer, 2020.
- [5] Soravit Changpinyo, Piyush Sharma, Nan Ding, and Radu Soricut. Conceptual 12m: Pushing web-scale image-text pre-training to recognize long-tail visual concepts. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pages 3558–3568, 2021.
- [6] Xi Chen, Xiao Wang, Soravit Changpinyo, AJ Piergiovanni, Piotr Padlewski, Daniel Salz, Sebastian Goodman, Adam Grycner, Basil Mustafa, Lucas Beyer, et al. Pali: A jointly-scaled multilingual language-image model. *arXiv preprint arXiv:2209.06794*, 2022.
- [7] Zhe Chen, Weiyun Wang, Yue Cao, Yangzhou Liu, Zhangwei Gao, Erfei Cui, Jinguo Zhu, Shenglong Ye, Hao Tian, Zhaoyang Liu, et al. Expanding performance boundaries of open-source multimodal models with model, data, and test-time scaling. *arXiv preprint arXiv:2412.05271*, 2024.
- [8] Zhe Chen, Weiyun Wang, Hao Tian, Shenglong Ye, Zhangwei Gao, Erfei Cui, Wenwen Tong, Kongzhi Hu, Jiapeng Luo, Zheng Ma, et al. How far are we to gpt-4v? closing the gap to commercial multimodal models with open-source suites. *Science China Information Sciences*, 67(12):220101, 2024.
- [9] Gong Cheng, Junwei Han, Peicheng Zhou, and Lei Guo. Multi-class geospatial object detection and geographic image classification based on collection of part detectors. *ISPRS Journal of Photogrammetry and Remote Sensing*, 98:119–132, 2014.
- [10] Tianheng Cheng, Lin Song, Yixiao Ge, Wenyu Liu, Xinggang Wang, and Ying Shan. Yolo-world: Real-time open-vocabulary object detection. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 16901–16911, 2024.
- [11] Seokju Cho, Heeseong Shin, Sunghwan Hong, Anurag Arnab, Paul Hongsuck Seo, and Seungryong Kim. Cat-seg: Cost aggregation for open-vocabulary semantic segmentation. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 4113–4123, 2024.
- [12] Mark Everingham, Luc Van Gool, Christopher KI Williams, John Winn, and Andrew Zisserman. The pascal visual object classes (voc) challenge. *International journal of computer vision*, 88:303–338, 2010.
- [13] Alex Fang, Albin Madappally Jose, Amit Jain, Ludwig Schmidt, Alexander T Toshev, and Vaishaal Shankar. Data filtering networks. In *The Twelfth International Conference on Learning Representations*, 2024.
- [14] Yuqian Fu, Yu Wang, Yixuan Pan, Lian Huai, Xingyu Qiu, Zeyu Shangguan, Tong Liu, Yanwei Fu, Luc Van Gool, and Xingqun Jiang. Cross-domain few-shot object detection via enhanced open-set object detector. In *European Conference on Computer Vision*, pages 247–264. Springer, 2024.
- [15] Guangshuai Gao, Qingjie Liu, and Yunhong Wang. Counting from sky: A large-scale data set for remote sensing object counting and a benchmark method. *IEEE Transactions on geoscience and remote sensing*, 59(5):3642–3655, 2020.
- [16] Xiuye Gu, Tsung-Yi Lin, Weicheng Kuo, and Yin Cui. Open-vocabulary object detection via vision and language knowledge distillation. *arXiv preprint arXiv:2104.13921*, 2021.
- [17] Agrim Gupta, Piotr Dollar, and Ross Girshick. Lvis: A dataset for large vocabulary instance segmentation. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pages 5356–5364, 2019.
- [18] Ritwik Gupta, Bryce Goodman, Nirav Patel, Ricky Hosfelt, Sandra Sajeed, Eric Heim, Jigar Doshi, Keane Lucas, Howie Choset, and Matthew Gaston. Creating xbd: A dataset for assessing building damage from satellite imagery. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition workshops*, pages 10–17, 2019.

- [19] Mordechai Haklay and Patrick Weber. Openstreetmap: User-generated street maps. *IEEE Pervasive computing*, 7(4):12–18, 2008.
- [20] Jia He, Mukund Rungta, David Koleczek, Arshdeep Sekhon, Franklin X Wang, and Sadid Hasan. Does prompt formatting have any impact on llm performance? *arXiv preprint arXiv:2411.10541*, 2024.
- [21] Shiqi Huang, Shuting He, and Bihan Wen. ZoRI: Towards discriminative zero-shot remote sensing instance segmentation. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 39, pages 3724–3732, 2025.
- [22] Ziyue Huang, Yongchao Feng, Shuai Yang, Ziqi Liu, Qingjie Liu, and Yunhong Wang. Openrsd: Towards open-prompts for object detection in remote sensing images. *arXiv preprint arXiv:2503.06146*, 2025.
- [23] Drew A Hudson and Christopher D Manning. Gqa: A new dataset for real-world visual reasoning and compositional question answering. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pages 6700–6709, 2019.
- [24] Aaron Hurst, Adam Lerer, Adam P Goucher, Adam Perelman, Aditya Ramesh, Aidan Clark, AJ Ostrow, Akila Welihinda, Alan Hayes, Alec Radford, et al. Gpt-4o system card. *arXiv preprint arXiv:2410.21276*, 2024.
- [25] Jeremy Andrew Irvin, Emily Ruoyu Liu, Joyce C. Chen, Ines Dormoy, Jinyoung Kim, Samar Khanna, Zhuo Zheng, and Stefano Ermon. TEOChat: A large vision-language assistant for temporal earth observation data. In *The Thirteenth International Conference on Learning Representations*, 2025.
- [26] Aishwarya Kamath, Mannat Singh, Yann LeCun, Gabriel Synnaeve, Ishan Misra, and Nicolas Carion. Mdetr-modulated detection for end-to-end multi-modal understanding. In *Proceedings of the IEEE/CVF international conference on computer vision*, pages 1780–1790, 2021.
- [27] Ranjay Krishna, Yuke Zhu, Oliver Groth, Justin Johnson, Kenji Hata, Joshua Kravitz, Stephanie Chen, Yannis Kalantidis, Li-Jia Li, David A Shamma, et al. Visual genome: Connecting language and vision using crowdsourced dense image annotations. *International journal of computer vision*, 123:32–73, 2017.
- [28] Kartik Kuckreja, Muhammad Sohail Danish, Muzammal Naseer, Abhijit Das, Salman Khan, and Fahad Shahbaz Khan. Geochat: Grounded large vision-language model for remote sensing. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 27831–27840, 2024.
- [29] Xin Lai, Zhuotao Tian, Yukang Chen, Yanwei Li, Yuhui Yuan, Shu Liu, and Jiaya Jia. Lisa: Reasoning segmentation via large language model. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 9579–9589, 2024.
- [30] Chunyuan Li, Haotian Liu, Liunian Li, Pengchuan Zhang, Jyoti Aneja, Jianwei Yang, Ping Jin, Houdong Hu, Zicheng Liu, Yong Jae Lee, et al. Elevater: A benchmark and toolkit for evaluating language-augmented visual models. *Advances in Neural Information Processing Systems*, 35:9287–9301, 2022.
- [31] Jiahao Li, Jiancheng Pan, Yuze Sun, and Xiaomeng Huang. Semantic-aware ship detection with vision-language integration. *arXiv preprint arXiv:2508.15930*, 2025.
- [32] Kaiyu Li, Ruixun Liu, Xiangyong Cao, Xueru Bai, Feng Zhou, Deyu Meng, and Zhi Wang. Segearth-ov: Towards training-free open-vocabulary segmentation for remote sensing images. *arXiv preprint arXiv:2410.01768*, 2024.
- [33] Kaiyu Li, Zepeng Xin, Li Pang, Chao Pang, Yupeng Deng, Jing Yao, Guisong Xia, Deyu Meng, Zhi Wang, and Xiangyong Cao. Segearth-r1: Geospatial pixel reasoning via large language model. *arXiv preprint arXiv:2504.09644*, 2025.
- [34] Ke Li, Gang Wan, Gong Cheng, Liqiu Meng, and Junwei Han. Object detection in optical remote sensing images: A survey and a new benchmark. *ISPRS journal of photogrammetry and remote sensing*, 159:296–307, 2020.
- [35] Liunian Harold Li, Pengchuan Zhang, Haotian Zhang, Jianwei Yang, Chunyuan Li, Yiwu Zhong, Lijuan Wang, Lu Yuan, Lei Zhang, Jenq-Neng Hwang, et al. Grounded language-image pre-training. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pages 10965–10975, 2022.
- [36] Qingyun Li, Yushi Chen, Xinya Shu, Dong Chen, Xin He, Yi Yu, and Xue Yang. A simple aerial detection baseline of multimodal language models. *arXiv preprint arXiv:2501.09720*, 2025.

- [37] Xiang Li, Jian Ding, and Mohamed Elhoseiny. VRSBench: A versatile vision-language benchmark dataset for remote sensing image understanding. In *Advances in Neural Information Processing Systems*, volume 37, pages 3229–3242, 2024.
- [38] Yan Li, Weiwei Guo, Xue Yang, Ning Liao, Dunyun He, Jiaqi Zhou, and Wenxian Yu. Toward open vocabulary aerial object detection with clip-activated student-teacher learning. In *European Conference on Computer Vision*, pages 431–448. Springer, 2024.
- [39] Yan Li, Weiwei Guo, Xue Yang, Ning Liao, Shaofeng Zhang, Yi Yu, Wenxian Yu, and Junchi Yan. Exploiting unlabeled data with multiple expert teachers for open vocabulary aerial object detection and its orientation adaptation. *arXiv preprint arXiv:2411.02057*, 2024.
- [40] Chuang Lin, Yi Jiang, Lizhen Qu, Zehuan Yuan, and Jianfei Cai. Generative region-language pretraining for open-ended object detection. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 13958–13968, 2024.
- [41] Zhiwei Lin, Yongtao Wang, and Zhi Tang. Training-Free Open-Ended Object Detection and Segmentation via Attention as Prompts. In *Advances in Neural Information Processing Systems*, volume 37, pages 69588–69606, 2024.
- [42] Chenyang Liu, Keyan Chen, Rui Zhao, Zhengxia Zou, and Zhenwei Shi. Text2earth: Unlocking text-driven remote sensing image generation with a global-scale dataset and a foundation model. *arXiv preprint arXiv:2501.00895*, 2025.
- [43] Fan Liu, Delong Chen, Zhangqingyun Guan, Xiaocong Zhou, Jiale Zhu, Qiaolin Ye, Liyong Fu, and Jun Zhou. Remoteclip: A vision language foundation model for remote sensing. *IEEE Transactions on Geoscience and Remote Sensing*, 2024.
- [44] Haotian Liu, Chunyuan Li, Qingyang Wu, and Yong Jae Lee. Visual instruction tuning. *Advances in neural information processing systems*, 36:34892–34916, 2023.
- [45] Shilong Liu, Zhaoyang Zeng, Tianhe Ren, Feng Li, Hao Zhang, Jie Yang, Qing Jiang, Chunyuan Li, Jianwei Yang, Hang Su, et al. Grounding dino: Marrying dino with grounded pre-training for open-set object detection. In *European Conference on Computer Vision*, pages 38–55. Springer, 2024.
- [46] Sihan Liu, Yiwei Ma, Xiaoqing Zhang, Haowei Wang, Jiayi Ji, Xiaoshuai Sun, and Rongrong Ji. Rotated multi-scale interaction network for referring remote sensing image segmentation. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 26658–26668, 2024.
- [47] Yanxing Liu, Jiancheng Pan, and Bingchen Zhang. Control copy-paste: Controllable diffusion-based augmentation method for remote sensing few-shot object detection. *arXiv preprint arXiv:2507.21816*, 2025.
- [48] Gen Luo, Xue Yang, Wenhan Dou, Zhaokai Wang, Jiawen Liu, Jifeng Dai, Yu Qiao, and Xizhou Zhu. Mono-intervl: Pushing the boundaries of monolithic multimodal large language models with endogenous visual pre-training. *arXiv preprint arXiv:2410.08202*, 2024.
- [49] Junwei Luo, Zhen Pang, Yongjun Zhang, Tingzhu Wang, Linlin Wang, Bo Dang, Jiangwei Lao, Jian Wang, Jingdong Chen, Yihua Tan, et al. Skysensegpt: A fine-grained instruction tuning dataset and model for remote sensing vision-language understanding. *arXiv preprint arXiv:2406.10100*, 2024.
- [50] Chenlin Meng, Enci Liu, Willie Neiswanger, Jiaming Song, Marshall Burke, David Lobell, and Stefano Ermon. Is-count: Large-scale object counting from satellite images with covariate-based importance sampling. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 36, pages 12034–12042, 2022.
- [51] Matthias Minderer, Alexey Gritsenko, and Neil Houlsby. Scaling open-vocabulary object detection. *Advances in Neural Information Processing Systems*, 36:72983–73007, 2023.
- [52] Matthias Minderer, Alexey Gritsenko, Austin Stone, Maxim Neumann, Dirk Weissenborn, Alexey Dosovitskiy, Aravindh Mahendran, Anurag Arnab, Mostafa Dehghani, Zhuoran Shen, et al. Simple open-vocabulary object detection. In *European conference on computer vision*, pages 728–755. Springer, 2022.
- [53] Stuart Mitchell, Michael OSullivan, and Iain Dunning. Pulp: a linear programming toolkit for python. *The University of Auckland, Auckland, New Zealand*, 65:25, 2011.

- [54] Dilxat Muhtar, Zhenshi Li, Feng Gu, Xueliang Zhang, and Pengfeng Xiao. Lhrs-bot: Empowering remote sensing with vgi-enhanced large multimodal language model. In *European Conference on Computer Vision*, pages 440–457. Springer, 2024.
- [55] Ruizhe Ou, Yuan Hu, Fan Zhang, Jiaxin Chen, and Yu Liu. Geopix: Multi-modal large language model for pixel-level image understanding in remote sensing. *arXiv preprint arXiv:2501.06828*, 2025.
- [56] Jiancheng Pan, Yanxing Liu, Yuqian Fu, Muyuan Ma, Jiahao Li, Danda Pani Paudel, Luc Van Gool, and Xiaomeng Huang. Locate anything on earth: Advancing open-vocabulary object detection for remote sensing community. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 39, pages 6281–6289, 2025.
- [57] Jiancheng Pan, Yanxing Liu, Xiao He, Long Peng, Jiahao Li, Yuze Sun, and Xiaomeng Huang. Enhance then search: An augmentation-search strategy with foundation models for cross-domain few-shot object detection. In *Proceedings of the Computer Vision and Pattern Recognition Conference*, pages 1548–1556, 2025.
- [58] Chao Pang, Xingxing Weng, Jiang Wu, Jiayu Li, Yi Liu, Jiaxing Sun, Weijia Li, Shuai Wang, Litong Feng, Gui-Song Xia, et al. Vhm: Versatile and honest vision language model for remote sensing image analysis. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 39, pages 6381–6388, 2025.
- [59] Claudio Persello, Jan Dirk Wegner, Ronny Hänsch, Devis Tuia, Pedram Ghamisi, Mila Koeva, and Gustau Camps-Valls. Deep learning and earth observation to support the sustainable development goals: Current approaches, open challenges, and future opportunities. *IEEE Geoscience and Remote Sensing Magazine*, 10(2):172–200, 2022.
- [60] Renjie Pi, Lewei Yao, Jianhua Han, Xiaodan Liang, Wei Zhang, and Hang Xu. Ins-detclip: Aligning detection model to follow human-language instruction. In *The Twelfth International Conference on Learning Representations*, 2024.
- [61] Alec Radford, Jong Wook Kim, Chris Hallacy, Aditya Ramesh, Gabriel Goh, Sandhini Agarwal, Girish Sastry, Amanda Askell, Pamela Mishkin, Jack Clark, et al. Learning transferable visual models from natural language supervision. In *International conference on machine learning*, pages 8748–8763. PmLR, 2021.
- [62] Viresh Ranjan, Udbhav Sharma, Thu Nguyen, and Minh Hoai. Learning to count everything. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 3394–3403, 2021.
- [63] Nikhila Ravi, Valentin Gabeur, Yuan-Ting Hu, Ronghang Hu, Chaitanya Ryali, Tengyu Ma, Haitham Khedr, Roman Rädle, Chloe Rolland, Laura Gustafson, et al. Sam 2: Segment anything in images and videos. *arXiv preprint arXiv:2408.00714*, 2024.
- [64] Shaoqing Ren, Kaiming He, Ross Girshick, and Jian Sun. Faster r-cnn: Towards real-time object detection with region proposal networks. *IEEE transactions on pattern analysis and machine intelligence*, 39(6):1137–1149, 2016.
- [65] Tianhe Ren, Yihao Chen, Qing Jiang, Zhaoyang Zeng, Yuda Xiong, Wenlong Liu, Zhengyu Ma, Junyi Shen, Yuan Gao, Xiaoke Jiang, et al. Dino-x: A unified vision model for open-world object detection and understanding. *arXiv preprint arXiv:2411.14347*, 2024.
- [66] Zhongwei Ren, Zhicheng Huang, Yunchao Wei, Yao Zhao, Dongmei Fu, Jiashi Feng, and Xiaojie Jin. Pixellm: Pixel reasoning with large multimodal model. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 26374–26383, 2024.
- [67] Rajat Sahay and Andreas Savakis. On aligning sam to remote sensing data. In *Geospatial Informatics XIV*, volume 13037, pages 10–18. SPIE, 2024.
- [68] Akashah Shabbir, Mohammed Zumri, Mohammed Bennamoun, Fahad S Khan, and Salman Khan. Geopixel: Pixel grounding large multimodal model in remote sensing. *arXiv preprint arXiv:2501.13925*, 2025.
- [69] Zhe Shan, Yang Liu, Lei Zhou, Cheng Yan, Heng Wang, and Xia Xie. Ros-sam: High-quality interactive segmentation for remote sensing moving object. *arXiv preprint arXiv:2503.12006*, 2025.
- [70] Shuai Shao, Zeming Li, Tianyuan Zhang, Chao Peng, Gang Yu, Xiangyu Zhang, Jing Li, and Jian Sun. Objects365: A large-scale, high-quality dataset for object detection. In *Proceedings of the IEEE/CVF international conference on computer vision*, pages 8430–8439, 2019.

- [71] Sagar Soni, Akshay Dudhane, Hiyam Debary, Mustansar Fiaz, Muhammad Akhtar Munir, Muhammad Sohail Danish, Paolo Fraccaro, Campbell D Watson, Levente J Klein, Fahad Shahbaz Khan, et al. Earthdial: Turning multi-sensory earth observations to interactive dialogues. In *Proceedings of the Computer Vision and Pattern Recognition Conference*, pages 14303–14313, 2025.
- [72] Hao Su, Shunjun Wei, Min Yan, Chen Wang, Jun Shi, and Xiaoling Zhang. Object detection and instance segmentation in remote sensing imagery based on precise mask r-cnn. In *IGARSS 2019-2019 IEEE International Geoscience and Remote Sensing Symposium*, pages 1454–1457. IEEE, 2019.
- [73] Xian Sun, Peijin Wang, Zhiyuan Yan, Feng Xu, Ruiping Wang, Wenhui Diao, Jin Chen, Jihao Li, Yingchao Feng, Tao Xu, et al. Fair1m: A benchmark dataset for fine-grained object recognition in high-resolution remote sensing imagery. *ISPRS Journal of Photogrammetry and Remote Sensing*, 184:116–130, 2022.
- [74] Gemma Team, Aishwarya Kamath, Johan Ferret, Shreya Pathak, Nino Vieillard, Ramona Merhej, Sarah Perrin, Tatiana Matejovicova, Alexandre Ramé, Morgane Rivi re, et al. Gemma 3 technical report. *arXiv preprint arXiv:2503.19786*, 2025.
- [75] Di Wang, Jing Zhang, Bo Du, Minqiang Xu, Lin Liu, Dacheng Tao, and Liangpei Zhang. Samrs: Scaling-up remote sensing segmentation dataset with segment anything model. *Advances in Neural Information Processing Systems*, 36:8815–8827, 2023.
- [76] Jiaqi Wang, Pan Zhang, Tao Chu, Yuhang Cao, Yujie Zhou, Tong Wu, Bin Wang, Conghui He, and Dahua Lin. V3det: Vast vocabulary visual detection dataset. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pages 19844–19854, 2023.
- [77] Zhecheng Wang, Rajanie Prabha, Tianyuan Huang, Jiajun Wu, and Ram Rajagopal. Skyscript: A large and semantically diverse vision-language dataset for remote sensing. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 38, pages 5805–5813, 2024.
- [78] Syed Waqas Zamir, Aditya Arora, Akshita Gupta, Salman Khan, Guolei Sun, Fahad Shahbaz Khan, Fan Zhu, Ling Shao, Gui-Song Xia, and Xiang Bai. isaid: A large-scale dataset for instance segmentation in aerial images. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition workshops*, pages 28–37, 2019.
- [79] Guoting Wei, Xia Yuan, Yu Liu, Zhenhao Shang, Kelu Yao, Chao Li, Qingsen Yan, Chunxia Zhao, Haokui Zhang, and Rong Xiao. Ova-detr: Open vocabulary aerial object detection using image-text alignment and fusion. *arXiv preprint arXiv:2408.12246*, 2024.
- [80] Jianzong Wu, Xiangtai Li, Shilin Xu, Haobo Yuan, Henghui Ding, Yibo Yang, Xia Li, Jiangning Zhang, Yunhai Tong, Xudong Jiang, et al. Towards open vocabulary learning: A survey. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 46(7):5092–5113, 2024.
- [81] Qiusheng Wu and Lucas Prado Osco. samgeo: A python package for segmenting geospatial data with the segment anything model (sam). *Journal of Open Source Software*, 8(89):5663, 2023.
- [82] Zijong Wu, Ce Zhang, Xiaowei Gu, Isla Duporge, Lacey F Hughey, Jared A Stabach, Andrew K Skidmore, J Grant C Hopcraft, Stephen J Lee, Peter M Atkinson, et al. Deep learning enables satellite-based monitoring of large populations of terrestrial mammals across heterogeneous landscape. *Nature communications*, 14(1):3072, 2023.
- [83] Bin Xiao, Haiping Wu, Weijian Xu, Xiyang Dai, Houdong Hu, Yumao Lu, Michael Zeng, Ce Liu, and Lu Yuan. Florence-2: Advancing a unified representation for a variety of vision tasks. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 4818–4829, 2024.
- [84] Jianlin Xie, Guanqun Wang, Tong Zhang, Yikang Sun, He Chen, Yin Zhuang, and Jun Li. Llama-unidetector: A llama-based universal framework for open-vocabulary object detection in remote sensing imagery. *IEEE Transactions on Geoscience and Remote Sensing*, 2025.
- [85] Zhitong Xiong, Yi Wang, Weikang Yu, Adam J Stewart, Jie Zhao, Nils Lehmann, Thomas Dujardin, Zhenghang Yuan, Pedram Ghamisi, and Xiao Xiang Zhu. Geolangbind: Unifying earth observation with agglomerative vision-language foundation models. *arXiv preprint arXiv:2503.06312*, 2025.
- [86] Zhiyuan Yan, Junxi Li, Xuexue Li, Ruixue Zhou, Wenkai Zhang, Yingchao Feng, Wenhui Diao, Kun Fu, and Xian Sun. Ringmo-sam: A foundation model for segment anything in multimodal remote-sensing images. *IEEE Transactions on Geoscience and Remote Sensing*, 61:1–16, 2023.
- [87] Lewei Yao, Renjie Pi, Jianhua Han, Xiaodan Liang, Hang Xu, Wei Zhang, Zhenguo Li, and Dan Xu. Detclipv3: Towards versatile generative open-vocabulary object detection. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 27391–27401, 2024.

- [88] Chengyang Ye, Yunzhi Zhuge, and Pingping Zhang. Towards open-vocabulary remote sensing image semantic segmentation. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 39, pages 9436–9444, 2025.
- [89] Qihang Yu, Ju He, Xueqing Deng, Xiaohui Shen, and Liang-Chieh Chen. Convolutions die hard: Open-vocabulary segmentation with single frozen convolutional clip. *Advances in Neural Information Processing Systems*, 36:32215–32234, 2023.
- [90] Zhengqing Zang, Chenyu Lin, Chenwei Tang, Tao Wang, and Jiancheng Lv. Zero-shot aerial object detection with visual description regularization. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 38, pages 6926–6934, 2024.
- [91] Valérie Zermatten, Javiera Castillo-Navarro, Diego Marcos, and Devis Tuia. Learning transferable land cover semantics for open vocabulary interactions with remote sensing images. *ISPRS Journal of Photogrammetry and Remote Sensing*, 220:621–636, 2025.
- [92] Chenhui Zhang and Sherrie Wang. Good at captioning bad at counting: Benchmarking gpt-4v on earth observation data. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 7839–7849, 2024.
- [93] Haotian Zhang, Pengchuan Zhang, Xiaowei Hu, Yen-Chun Chen, Liunian Li, Xiyang Dai, Lijuan Wang, Lu Yuan, Jenq-Neng Hwang, and Jianfeng Gao. Glipv2: Unifying localization and vision-language understanding. *Advances in Neural Information Processing Systems*, 35:36067–36080, 2022.
- [94] Mingjin Zhang, Qian Xu, Yuchun Wang, Xi Li, and Haojuan Yuan. Mirsam: multimodal vision-language segment anything model for infrared small target detection. *Visual Intelligence*, 3(1):1–13, 2025.
- [95] Zilun Zhang, Tiancheng Zhao, Yulong Guo, and Jianwei Yin. Rs5m and georsclip: A large scale vision-language dataset and a large vision-language model for remote sensing. *IEEE Transactions on Geoscience and Remote Sensing*, 2024.
- [96] Yijie Zheng, Jinxuan Yang, Yu Chen, Yaxuan Wang, Yihang Lu, and Guoqing Li. Beluga whale detection from satellite imagery with point labels. *arXiv preprint arXiv:2505.12066*, 2025.
- [97] Yue Zhou, Mengcheng Lan, Xiang Li, Yiping Ke, Xue Jiang, Litong Feng, and Wayne Zhang. Geoground: A unified large vision-language model. for remote sensing visual grounding. *arXiv preprint arXiv:2411.11904*, 2024.
- [98] Jinguo Zhu, Weiyun Wang, Zhe Chen, Zhaoyang Liu, Shenglong Ye, Lixin Gu, Yuchen Duan, Hao Tian, Weijie Su, Jie Shao, et al. Internvl3: Exploring advanced training and test-time recipes for open-source multimodal models. *arXiv preprint arXiv:2504.10479*, 2025.

NeurIPS Paper Checklist

1. Claims

Question: Do the main claims made in the abstract and introduction accurately reflect the paper's contributions and scope?

Answer: [\[Yes\]](#)

Justification: The abstract and introduction clearly outlined the challenge in language-guided remote sensing object recognition and the paper's contribution of introducing the InstructCDS task, EarthInstruct benchmark, and InstructSAM framework.

Guidelines:

- The answer NA means that the abstract and introduction do not include the claims made in the paper.
- The abstract and/or introduction should clearly state the claims made, including the contributions made in the paper and important assumptions and limitations. A No or NA answer to this question will not be perceived well by the reviewers.
- The claims made should match theoretical and experimental results, and reflect how much the results can be expected to generalize to other settings.
- It is fine to include aspirational goals as motivation as long as it is clear that these goals are not attained by the paper.

2. Limitations

Question: Does the paper discuss the limitations of the work performed by the authors?

Answer: [\[Yes\]](#)

Justification: The limitations of this work are discussed in Section 6.

Guidelines:

- The answer NA means that the paper has no limitation while the answer No means that the paper has limitations, but those are not discussed in the paper.
- The authors are encouraged to create a separate "Limitations" section in their paper.
- The paper should point out any strong assumptions and how robust the results are to violations of these assumptions (e.g., independence assumptions, noiseless settings, model well-specification, asymptotic approximations only holding locally). The authors should reflect on how these assumptions might be violated in practice and what the implications would be.
- The authors should reflect on the scope of the claims made, e.g., if the approach was only tested on a few datasets or with a few runs. In general, empirical results often depend on implicit assumptions, which should be articulated.
- The authors should reflect on the factors that influence the performance of the approach. For example, a facial recognition algorithm may perform poorly when image resolution is low or images are taken in low lighting. Or a speech-to-text system might not be used reliably to provide closed captions for online lectures because it fails to handle technical jargon.
- The authors should discuss the computational efficiency of the proposed algorithms and how they scale with dataset size.
- If applicable, the authors should discuss possible limitations of their approach to address problems of privacy and fairness.
- While the authors might fear that complete honesty about limitations might be used by reviewers as grounds for rejection, a worse outcome might be that reviewers discover limitations that aren't acknowledged in the paper. The authors should use their best judgment and recognize that individual actions in favor of transparency play an important role in developing norms that preserve the integrity of the community. Reviewers will be specifically instructed to not penalize honesty concerning limitations.

3. Theory assumptions and proofs

Question: For each theoretical result, does the paper provide the full set of assumptions and a complete (and correct) proof?

Answer: [NA]

Justification: This paper focuses on the experimental demonstration of the proposed framework, and does not include theoretical results or proofs.

Guidelines:

- The answer NA means that the paper does not include theoretical results.
- All the theorems, formulas, and proofs in the paper should be numbered and cross-referenced.
- All assumptions should be clearly stated or referenced in the statement of any theorems.
- The proofs can either appear in the main paper or the supplemental material, but if they appear in the supplemental material, the authors are encouraged to provide a short proof sketch to provide intuition.
- Inversely, any informal proof provided in the core of the paper should be complemented by formal proofs provided in appendix or supplemental material.
- Theorems and Lemmas that the proof relies upon should be properly referenced.

4. Experimental result reproducibility

Question: Does the paper fully disclose all the information needed to reproduce the main experimental results of the paper to the extent that it affects the main claims and/or conclusions of the paper (regardless of whether the code and data are provided or not)?

Answer: [Yes]

Justification: The InstructSAM framework is clearly described in Section 4 and the implementation details to reproduce the main experimental results are thoroughly outlined in Appendix C.

Guidelines:

- The answer NA means that the paper does not include experiments.
- If the paper includes experiments, a No answer to this question will not be perceived well by the reviewers: Making the paper reproducible is important, regardless of whether the code and data are provided or not.
- If the contribution is a dataset and/or model, the authors should describe the steps taken to make their results reproducible or verifiable.
- Depending on the contribution, reproducibility can be accomplished in various ways. For example, if the contribution is a novel architecture, describing the architecture fully might suffice, or if the contribution is a specific model and empirical evaluation, it may be necessary to either make it possible for others to replicate the model with the same dataset, or provide access to the model. In general, releasing code and data is often one good way to accomplish this, but reproducibility can also be provided via detailed instructions for how to replicate the results, access to a hosted model (e.g., in the case of a large language model), releasing of a model checkpoint, or other means that are appropriate to the research performed.
- While NeurIPS does not require releasing code, the conference does require all submissions to provide some reasonable avenue for reproducibility, which may depend on the nature of the contribution. For example
 - (a) If the contribution is primarily a new algorithm, the paper should make it clear how to reproduce that algorithm.
 - (b) If the contribution is primarily a new model architecture, the paper should describe the architecture clearly and fully.
 - (c) If the contribution is a new model (e.g., a large language model), then there should either be a way to access this model for reproducing the results or a way to reproduce the model (e.g., with an open-source dataset or instructions for how to construct the dataset).
 - (d) We recognize that reproducibility may be tricky in some cases, in which case authors are welcome to describe the particular way they provide for reproducibility. In the case of closed-source models, it may be that access to the model is limited in some way (e.g., to registered users), but it should be possible for other researchers to have some path to reproducing or verifying the results.

5. Open access to data and code

Question: Does the paper provide open access to the data and code, with sufficient instructions to faithfully reproduce the main experimental results, as described in supplemental material?

Answer: [Yes]

Justification: The source codes of InstructSAM, and evaluation scripts are provided in the supplemental materials zip file. The complete source code will be released upon acceptance.

Guidelines:

- The answer NA means that paper does not include experiments requiring code.
- Please see the NeurIPS code and data submission guidelines (<https://nips.cc/public/guides/CodeSubmissionPolicy>) for more details.
- While we encourage the release of code and data, we understand that this might not be possible, so “No” is an acceptable answer. Papers cannot be rejected simply for not including code, unless this is central to the contribution (e.g., for a new open-source benchmark).
- The instructions should contain the exact command and environment needed to run to reproduce the results. See the NeurIPS code and data submission guidelines (<https://nips.cc/public/guides/CodeSubmissionPolicy>) for more details.
- The authors should provide instructions on data access and preparation, including how to access the raw data, preprocessed data, intermediate data, and generated data, etc.
- The authors should provide scripts to reproduce all experimental results for the new proposed method and baselines. If only a subset of experiments are reproducible, they should state which ones are omitted from the script and why.
- At submission time, to preserve anonymity, the authors should release anonymized versions (if applicable).
- Providing as much information as possible in supplemental material (appended to the paper) is recommended, but including URLs to data and code is permitted.

6. Experimental setting/details

Question: Does the paper specify all the training and test details (e.g., data splits, hyperparameters, how they were chosen, type of optimizer, etc.) necessary to understand the results?

Answer: [Yes]

Justification: The dataset split of the EarthInstruct benchmark is specified in Appendix B.

Guidelines:

- The answer NA means that the paper does not include experiments.
- The experimental setting should be presented in the core of the paper to a level of detail that is necessary to appreciate the results and make sense of them.
- The full details can be provided either with the code, in appendix, or as supplemental material.

7. Experiment statistical significance

Question: Does the paper report error bars suitably and correctly defined or other appropriate information about the statistical significance of the experiments?

Answer: [Yes]

Justification: Statistical significance analysis on open-vocabulary counting task in NWPU-VHR-10 is presented in Appendix D.3. Error bars for other experiments are not reported due to the inference cost.

Guidelines:

- The answer NA means that the paper does not include experiments.
- The authors should answer "Yes" if the results are accompanied by error bars, confidence intervals, or statistical significance tests, at least for the experiments that support the main claims of the paper.

- The factors of variability that the error bars are capturing should be clearly stated (for example, train/test split, initialization, random drawing of some parameter, or overall run with given experimental conditions).
- The method for calculating the error bars should be explained (closed form formula, call to a library function, bootstrap, etc.)
- The assumptions made should be given (e.g., Normally distributed errors).
- It should be clear whether the error bar is the standard deviation or the standard error of the mean.
- It is OK to report 1-sigma error bars, but one should state it. The authors should preferably report a 2-sigma error bar than state that they have a 96% CI, if the hypothesis of Normality of errors is not verified.
- For asymmetric distributions, the authors should be careful not to show in tables or figures symmetric error bars that would yield results that are out of range (e.g. negative error rates).
- If error bars are reported in tables or plots, The authors should explain in the text how they were calculated and reference the corresponding figures or tables in the text.

8. Experiments compute resources

Question: For each experiment, does the paper provide sufficient information on the computer resources (type of compute workers, memory, time of execution) needed to reproduce the experiments?

Answer: [Yes]

Justification: The comparison of inference time with other methods is presented in Section 5.2.

Guidelines:

- The answer NA means that the paper does not include experiments.
- The paper should indicate the type of compute workers CPU or GPU, internal cluster, or cloud provider, including relevant memory and storage.
- The paper should provide the amount of compute required for each of the individual experimental runs as well as estimate the total compute.
- The paper should disclose whether the full research project required more compute than the experiments reported in the paper (e.g., preliminary or failed experiments that didn't make it into the paper).

9. Code of ethics

Question: Does the research conducted in the paper conform, in every respect, with the NeurIPS Code of Ethics <https://neurips.cc/public/EthicsGuidelines>?

Answer: [Yes]

Justification: The paper fully conforms to the NeurIPS Code of Ethics.

Guidelines:

- The answer NA means that the authors have not reviewed the NeurIPS Code of Ethics.
- If the authors answer No, they should explain the special circumstances that require a deviation from the Code of Ethics.
- The authors should make sure to preserve anonymity (e.g., if there is a special consideration due to laws or regulations in their jurisdiction).

10. Broader impacts

Question: Does the paper discuss both potential positive societal impacts and negative societal impacts of the work performed?

Answer: [Yes]

Justification: Both positive societal impacts and potential negative societal impacts are discussed in Appendix E.

Guidelines:

- The answer NA means that there is no societal impact of the work performed.

- If the authors answer NA or No, they should explain why their work has no societal impact or why the paper does not address societal impact.
- Examples of negative societal impacts include potential malicious or unintended uses (e.g., disinformation, generating fake profiles, surveillance), fairness considerations (e.g., deployment of technologies that could make decisions that unfairly impact specific groups), privacy considerations, and security considerations.
- The conference expects that many papers will be foundational research and not tied to particular applications, let alone deployments. However, if there is a direct path to any negative applications, the authors should point it out. For example, it is legitimate to point out that an improvement in the quality of generative models could be used to generate deepfakes for disinformation. On the other hand, it is not needed to point out that a generic algorithm for optimizing neural networks could enable people to train models that generate Deepfakes faster.
- The authors should consider possible harms that could arise when the technology is being used as intended and functioning correctly, harms that could arise when the technology is being used as intended but gives incorrect results, and harms following from (intentional or unintentional) misuse of the technology.
- If there are negative societal impacts, the authors could also discuss possible mitigation strategies (e.g., gated release of models, providing defenses in addition to attacks, mechanisms for monitoring misuse, mechanisms to monitor how a system learns from feedback over time, improving the efficiency and accessibility of ML).

11. Safeguards

Question: Does the paper describe safeguards that have been put in place for responsible release of data or models that have a high risk for misuse (e.g., pre-trained language models, image generators, or scraped datasets)?

Answer: [NA]

Justification: This paper poses no such risks.

Guidelines:

- The answer NA means that the paper poses no such risks.
- Released models that have a high risk for misuse or dual-use should be released with necessary safeguards to allow for controlled use of the model, for example by requiring that users adhere to usage guidelines or restrictions to access the model or implementing safety filters.
- Datasets that have been scraped from the Internet could pose safety risks. The authors should describe how they avoided releasing unsafe images.
- We recognize that providing effective safeguards is challenging, and many papers do not require this, but we encourage authors to take this into account and make a best faith effort.

12. Licenses for existing assets

Question: Are the creators or original owners of assets (e.g., code, data, models), used in the paper, properly credited and are the license and terms of use explicitly mentioned and properly respected?

Answer: [Yes]

Justification: We have cited all used datasets and pre-trained models. The EarthInstruct benchmark is built upon datasets with CC BY-NC 4.0 license.

Guidelines:

- The answer NA means that the paper does not use existing assets.
- The authors should cite the original paper that produced the code package or dataset.
- The authors should state which version of the asset is used and, if possible, include a URL.
- The name of the license (e.g., CC-BY 4.0) should be included for each asset.
- For scraped data from a particular source (e.g., website), the copyright and terms of service of that source should be provided.

- If assets are released, the license, copyright information, and terms of use in the package should be provided. For popular datasets, paperswithcode.com/datasets has curated licenses for some datasets. Their licensing guide can help determine the license of a dataset.
- For existing datasets that are re-packaged, both the original license and the license of the derived asset (if it has changed) should be provided.
- If this information is not available online, the authors are encouraged to reach out to the asset's creators.

13. **New assets**

Question: Are new assets introduced in the paper well documented and is the documentation provided alongside the assets?

Answer: [Yes]

Justification: The codes, along with the documents of the proposed benchmark and methods is provided in the supplemental materials.

Guidelines:

- The answer NA means that the paper does not release new assets.
- Researchers should communicate the details of the dataset/code/model as part of their submissions via structured templates. This includes details about training, license, limitations, etc.
- The paper should discuss whether and how consent was obtained from people whose asset is used.
- At submission time, remember to anonymize your assets (if applicable). You can either create an anonymized URL or include an anonymized zip file.

14. **Crowdsourcing and research with human subjects**

Question: For crowdsourcing experiments and research with human subjects, does the paper include the full text of instructions given to participants and screenshots, if applicable, as well as details about compensation (if any)?

Answer: [NA]

Justification: This paper does not involve crowdsourcing or research with human subjects.

Guidelines:

- The answer NA means that the paper does not involve crowdsourcing nor research with human subjects.
- Including this information in the supplemental material is fine, but if the main contribution of the paper involves human subjects, then as much detail as possible should be included in the main paper.
- According to the NeurIPS Code of Ethics, workers involved in data collection, curation, or other labor should be paid at least the minimum wage in the country of the data collector.

15. **Institutional review board (IRB) approvals or equivalent for research with human subjects**

Question: Does the paper describe potential risks incurred by study participants, whether such risks were disclosed to the subjects, and whether Institutional Review Board (IRB) approvals (or an equivalent approval/review based on the requirements of your country or institution) were obtained?

Answer: [NA]

Justification: This paper does not involve research with human subjects.

Guidelines:

- The answer NA means that the paper does not involve crowdsourcing nor research with human subjects.
- Depending on the country in which research is conducted, IRB approval (or equivalent) may be required for any human subjects research. If you obtained IRB approval, you should clearly state this in the paper.

- We recognize that the procedures for this may vary significantly between institutions and locations, and we expect authors to adhere to the NeurIPS Code of Ethics and the guidelines for their institution.
- For initial submissions, do not include any information that would break anonymity (if applicable), such as the institution conducting the review.

16. **Declaration of LLM usage**

Question: Does the paper describe the usage of LLMs if it is an important, original, or non-standard component of the core methods in this research? Note that if the LLM is used only for writing, editing, or formatting purposes and does not impact the core methodology, scientific rigorousness, or originality of the research, declaration is not required.

Answer: [\[Yes\]](#)

Justification: The LLM is a key component of the proposed InstructSAM framework. The usage of LLMs is described in Section 4.1.

Guidelines:

- The answer NA means that the core method development in this research does not involve LLMs as any important, original, or non-standard components.
- Please refer to our LLM policy (<https://neurips.cc/Conferences/2025/LLM>) for what should or should not be described.

Technical Appendices

A Comparison with related work

Remote sensing imagery captures a vast, diverse range of contexts. Exemplified by the SkyScript dataset [77], curated from Google Earth and OpenStreetMap [19], featuring 29,000 distinct semantic tags. Despite this richness, annotated training datasets for remote sensing object recognition typically span only a few dozen categories (Table 6). This lexical scarcity hinders effective alignment of semantic and visual information compared to generic models, which are typically trained on millions of human-annotated images and near-infinite vocabularies sourced from the Internet. Similarly, instruction-following datasets for remote sensing, such as FIT-RS [49] and GeoPixelD [68], are also built upon manually annotated data, often inheriting these vocabulary-specific limitations.

Regarding model capabilities, remote sensing LVLMs typically fail to follow complex object recognition instructions as illustrated in Figure 8. Nevertheless, SkysenseGPT [49] and GeoPixel [68], trained on scene graph generation or pixel-grounded conversation generation tasks, deliver comprehensive object detection or segmentation outputs, effectively serving a similar purpose of open-ended object recognition.

Table 6: Comparison of language-guided object recognition methods. We summarize the model, publication, training data, dense segmentation capability, and support for instruction-oriented object detection (open-vocabulary detection (OVD), open-ended detection (OED), and open-subclass detection (OSD)). Green ✓ indicates support, red ✗ indicates not supported.

Method	Publication	Object Recognition Training Data	Dense Segmentation	OVD	OED	OSD
<i>Remote sensing-specified methods</i>						
DesReg [90]	AAAI’24	DIOR	✗	✓	✗	✗
OVA-DETR [79]	arXiv’24	DIOR+DOTA+xDView	✗	✓	✗	✗
CASTDet [38]	ECCV’24	DIOR	✗	✓	✗	✗
LAE-DINO [56]	AAAI’25	LAE-1M	✗	✓	✗	✗
ZORI [21]	AAAI’25	NWPU/DIOR	✓	✓	✗	✗
GSNet [88]	AAAI’25	LandCover-40k	✓	✗	✗	✗
SegEarth-OV [32]	CVPR’25	Image-level Training	✓	✗	✗	✗
SkysenseGPT [49]	arXiv’24	FIT-RS	✗	✗	✓	✗
GeoPixel [68]	ICML’25	GeoPixelD	✓	✗	✓	✗
<i>Generic methods</i>						
GroundingDINO [45]	ECCV’24	FiveODs+GoldG+Cap4M	✗	✓	✗	✗
OWLv2 [51]	NIPS’22	WebLI2B	✗	✓	✗	✗
Florence-2 [83]	CVPR’24	FLA-5B	✗	✓	✓	✗
Qwen2.5-VL [2]	arXiv’25	Various sources	✗	✓	✓	✓
InsDetCLIP [60]	ICLR’24	Object365	✗	✓	✓	✓
VL-SAM [41]	NeurIPS’24	Training-free	✓	✗	✓	✗
InstructSAM	Ours	Training-free	✓	✓	✓	✓

B Benchmark details

The details of the datasets comprising EarthInstruct are as follows:

- **NWPU-VHR-10** [9] is a 10-class dataset for very-high-resolution (VHR) remote sensing object detection. It originally comprises 650 positive images (each containing at least one target object) and 150 negative images (containing no target objects). For constructing EarthInstruct, we utilize the 650 positive images. Instance-level mask annotations were subsequently provided by [72].

Table 8: Comparison between EarthInstruct and other language-guided object recognition benchmark datasets. “OV”, “OE”, “OS” denote open-vocabulary, open-ended, and open-subclass, respectively. Goal-Oriented denotes instructions to detect objects that achieve certain goals. **Content Prior Free** means the benchmark does **not** require image content prior for prompt construction.

Dataset	Publication	OV Instructions	OE Instructions	OS Instructions	Goal- Oriented Instructions	Content Prior Free	Class Num
IOD-Bench [60]	ICLR’24	✓	✓	✓	✓	✗	–
RRSIS-D [46]	CVPR’24	✓	✗	✗	✗	✗	20
VRSBench [37]	NeurIPS’24	✓	✗	✗	✗	✗	26
FIT-RS (OD) [49]	arXiv’24	✓	✗	✗	✗	✗	48
FIT-RS (SGG) [49]	arXiv’24	✗	✓	✗	✗	✓	48
GeoPixelID [68]	ICML’25	✗	✓	✗	✗	✓	15
EarthReason [33]	arXiv’25	✗	✗	✗	✓	✗	28
EarthInstruct	Ours	✓	✓	✓	✗	✓	20

tion [46] and visual grounding [37] benchmarks typically support only single-class or single-object queries, restricting efficiency in large-scale applications.

EarthInstruct addresses these issues by supporting open-vocabulary, open-ended, and open-subclass settings, and uses dataset-specific prompts that encode user intent without relying on image content priors. This enables more comprehensive and efficient evaluation for instruction-driven object recognition.

C Implementation details

This section provides further details on the implementation of our InstructSAM framework and other baselines. A critical component of leveraging LVLMs for the InstructCDS tasks is the design of effective prompts. We employ structured prompts in JSON format to systematically guide the LVLM counter. This structured approach allows for clear delineation of the model’s *Persona*, the specific *Task* to be performed, detailed *Instructions* for execution, the desired *Output* format, and illustrative *Examples*. The *Instructions* field enables the incorporation of dataset-specific annotation rules and disambiguation of category definitions, which are crucial for accurate interpretation the user intension, as discussed in Section 3.1. The subsequent subsections detail the specific prompts used for each setting within the EarthInstruct benchmark.

Here we further clarify how the categories that might have bewildered the model. For example, an “overpass” is defined as “a bridge, road, railway or similar structure that is over another road or railway¹”, while a “bridge” is “a structure built to span a physical obstacle (such as a body of water, valley, road, or railway) without blocking the path underneath².” It is possible that the LVLM counter will recognize overpasses as bridges since overpass is a subset of bridge. Adding clarification such as “bridge in this dataset refers to a structure spanning a body of water” to the *Instructions* field will guild the LVLM to count accurately.

C.1 Prompts in open-vocabulary setting

- Prompt for NWPU-VHR-10 dataset:

```
{
  "Persona": "You are an advanced AI model capable of understanding and
analyzing aerial images.",
  "Task": "Given an input satellite imagery, count the number of objects from
specific categories. Provide the results in JSON format where the keys are
the category names and the values are the corresponding counts.",
  "Instructions": [
```

¹<https://en.wikipedia.org/wiki/Overpass>

²<https://en.wikipedia.org/wiki/Bridge>

```

    "The 10 categories in the dataset are: ['airplane', 'ship',
    'storage_tank', 'baseball_field', 'tennis_court', 'basketball_court',
    'track_field', 'harbor', 'bridge', 'vehicle']",
    "The spatial resolution of the imagery in the dataset ranges from 0.08 m
    to 2 m.",
    "Do not count ships or vehicles that are hard to annotate in the
    relatively low-resolution images as they are not annotated due to the small
    size.",
    "Harbor is defined as a pier to dock ships. If multiple harbors are
    visible in the image, count each distinct pier separately."
  ],
  "Output format": "{\"category1\": count1, \"category2\": count2, ... }",
  "Examples": [
    { "airplane": 2, "ship": 0, "storage_tank": 3, "baseball_field": 1,
    "tennis_court": 0, "basketball_court": 0, "track_field": 0, "harbor": 6,
    "bridge": 0, "vehicle": 0 },
    { "airplane": 5, "ship": 2, "storage_tank": 0, "baseball_field": 0,
    "tennis_court": 1, "basketball_court": 0, "track_field": 0, "harbor": 0,
    "bridge": 1, "vehicle": 10 }
  ]
}

```

- Prompt for DIOR dataset:

```

{
  "Persona": "You are an advanced AI model capable of understanding and
  analyzing remote sensing images."
  "Task": "Given an input satellite imagery, count the number of objects from
  specific categories. Provide the results in JSON format where the keys are
  the category names and the values are the corresponding counts.",
  "Instructions": [
    "The 20 categories in the dataset are: ['airplane', 'airport', 'baseball
    field', 'basketball court', 'bridge', 'chimney', 'expressway service area',
    'expressway toll station', 'dam', 'golf field', 'ground track field',
    'harbor', 'overpass', 'ship', 'stadium', 'storage tank', 'tennis court',
    'train station', 'vehicle', 'windmill']",
    "The spatial resolution of the images is 0.3m-30m.",
    "Airport is a large area of land where aircraft can take off and land. It
    includes runways and other facilities. Do not count airport if the it is not
    completely visible in the image.",
    "Harbor is defined as a pier to dock ships. If multiple harbors are
    visible in the image, count each distinct pier separately.",
    "Expressway toll station is a toll booth at the entrance of the
    expressway and spans the road.",
    "Expressway service area is a rest area along an expressway. If it exists
    on the both sides of the expressway, count them separately.",
    "Overpass is a road crossing over another road. Bridge is a road spanning
    a river. Distinguish them carefully.",
    "If the overpass or bridge is composed of parallel, separate sections
    (for example, different lanes or directions of traffic), each section should
    be counted individually.",
    "Count every ship and vehicle carefully, even the resolution is low and
    the objects are small and dense.",
    "If none of the objects among the categories is visible, output a JSON
    object with all categories set to 0"
  ],
  "Output format": "{\"category1\": count1, \"category2\": count2, ... }",
  "Examples": [
    { "airplane": 2, "airport": 0, "baseball field": 0, "basketball court":
    0, "bridge": 1, ... },
    { "airplane": 0, "airport": 0, "baseball field": 2, "basketball court":
    6, "bridge": 0, ... }
  ]
}

```

C.2 Prompts in open-ended setting

- Prompt for NWPU-VHR-10 dataset:

```
{
  "Persona": "You are an advanced AI model capable of understanding and
analyzing remote sensing images.",
  "Task": "Given an input satellite imagery, count the number of all the
visible remote sensing objects. Provide the results in JSON format where the
keys are the category names and the values are the corresponding counts.",
  "Instructions": [
    "The spatial resolution of the imagery in the dataset ranges from 0.08 m
to 2 m.",
    "Do not count ships or vehicles that are too small and are hard to
annotate in the relatively low-resolution images.",
    "Only count objects that are clearly visible in the imagery. If a
category is not visible, do not include it in the output."
  ],
  "Output format": "{ \"category1\": count1, \"category2\": count2, ... }",
  "Answer": [
    "Ensure the category names are in singular form",
    "Provide the counts as integers."
  ]
}
```

- Prompt for DIOR dataset:

```
{
  "Persona": "You are an advanced AI model capable of understanding and
analyzing remote sensing images.",
  "Task": "Given an input satellite imagery, count the number of all the
visible remote sensing objects or scenes. Provide the results in JSON format
where the keys are the category names and the values are the corresponding
counts.",
  "Instructions": [
    "The spatial resolution of the imagery in the dataset ranges from 0.3 m
to 30 m.",
    "If the resolution is too limited or the scene is too dense to accurately
count certain objects, exclude those objects from the results.",
    "Only count objects that are clearly visible in the imagery."
  ],
  "Output format": "{ \"category1\": count1, \"category2\": count2, ... }",
  "Answer": [
    "Ensure the category names are in singular form",
    "Provide the counts as integers."
  ]
}
```

C.3 Prompts in open-subclass setting

- Prompt for counting “sports field” in NWPU-VHR-10 dataset:

```
{
  "Persona": "You are an advanced AI model capable of understanding and
analyzing remote sensing images."
  "Task": "Given an input satellite imagery, count the number of objects that
belong to the parent category **sports field**. Provide the results in JSON
format where the keys are the names of the subcategories and the values are
the corresponding counts.",
  "Instructions": [
    "The spatial resolution of the images is 0.08m-2m.",
    "Do not count objects that are hard to annotate in the relatively
low-resolution images as they are not annotated due to the small size.",
    "If none of the objects belong to the parent category is visible, output
a empty JSON object like \{\ }"
```

```

    ],
    "Output format": "{ \"subcategory1\": count1, \"subcategory2\": count2, ... }",
    "Answer": [
        "Ensure the category names are in singular form",
        "Provide the counts as integers."
    ]
}

```

- Prompt for counting “means of transport” in NWPU-VHR-10 dataset:

```

{
    "Persona": "You are an advanced AI model capable of understanding and
analyzing remote sensing images."
    "Task": "Given an input satellite imagery, count the number of objects that
belong to the parent category **means of transport**. Provide the results in
JSON format where the keys are the names of the subcategories and the values
are the corresponding counts.",
    "Instructions": [
        "The spatial resolution of the imagery in the dataset ranges from 0.08 m
to 2 m.",
        "Do not count boats or land vehicles that are hard to annotate in the
relatively low-resolution images as they are not annotated due to the small
size.",
        "If none of the objects belong to the parent category is visible, output
a empty JSON object like \{ \}"
    ],
    "Output format": "{ \"subcategory1\": count1, \"subcategory2\": count2, ... }",
    "Answer": [
        "Ensure the category names are in singular form",
        "Provide the counts as integers."
    ]
}

```

- Prompt for counting “sports field” in DIOR dataset:

```

{
    "Persona": "You are an advanced AI model capable of understanding and
analyzing remote sensing images."
    "Task": "Given an input satellite imagery, count the number of visible
objects that belong to the parent category **sports field**. Provide the
results in JSON format where the keys are the names of the subcategories and
the values are the corresponding counts.",
    "Instructions": [
        "The spatial resolution of the images is 0.3m-30m.",
        "Return only the categories and counts that meet the visibility and
resolution criteria. If none of the objects belong to the parent category is
visible, output a empty JSON object like \{ \}."
    ],
    "Output format": "{ \"subcategory1\": count1, \"subcategory2\": count2, ... }",
    "Answer": [
        "Ensure the category names are in singular form",
        "Provide the counts as integers."
    ]
}

```

- Prompt for counting “means of transport” in DIOR dataset:

```

{
    "Persona": "You are an advanced AI model capable of understanding and
analyzing remote sensing images."
    "Task": "Given an input satellite imagery, count the number of visible
objects that belong to the parent category **means of transport**. Provide
the results in JSON format where the keys are the names of the subcategories
and the values are the corresponding counts.",
    "Instructions": [
        "The spatial resolution of the images is 0.3m-30m.",

```

```

    "Return only the categories and counts that meet the visibility and
    resolution criteria. If none of the objects belong to the parent category is
    visible, output a empty JSON object like \{ \}"
  ],
  "Output format": "{ \"subcategory1\": count1, \"subcategory2\": count2, ... }",
  "Answer": [
    "Ensure the category names are in singular form",
    "Provide the counts as integers."
  ]
}

```

C.4 Hyperparameters of InstructSAM

Mask proposer As described in Section 4.2, class-agnostic mask proposals are generated using SAM2-hiera-large [63] in its automatic mask generation mode. The model was configured with the parameters detailed in Table 9 across both NWPU-VHR-10 and DIOR. These settings balance the proposal quality and computational efficiency, ensuring a dense set of high-quality proposals, especially for small objects.

Table 9: Hyperparameters for SAM2.

Parameter	Value
pred_iou_thresh	0.75
stability_score_thresh	0.75
points_per_side	24
crop_n_layers	1
box_nms_thresh	0.5

LVLM counter For Qwen2.5-VL and GPT-4o, the temperature is set at 0.01 and top_p is set at 1 to reduce randomness.

C.5 Implementations of baseline methods

To ensure rigorous and fair comparisons against InstructSAM, baseline methods are implemented or adapted as detailed below. Unless otherwise specified, publicly available pre-trained models and official codebases are utilized, adhering to their recommended configurations.

Open-Vocabulary semantic segmentation methods For SegEarth-OV [32] and GSNet [88], we follow their prescribed inference procedures. This involves providing the target categories along with an explicit “background” category as input. To derive instance-level proposals from the pixel-level segmentation maps produced by these models, we apply a standard connected component labeling algorithm to the per-class binary masks. This allows evaluation using instance-based metrics (Mask F_1).

Open-ended methods

- **SkysenseGPT** [49]: We utilize the prompt “[grounding]Analyze and describe every detail you can identify in the image,” which is a representative of its training data, and set the maximum output token limit to 5000.
- **GeoPixel** [68]: Following the illustrative examples provided in their publication, we employ the prompt “Can you give a thorough description of this image, including interleaved segmentation masks to highlight key objects?”
- **LAE-Label** [56]: For mask proposing, we use SAM2-hiera-large with the same hyperparameters as InstructSAM (see Appendix C.4). For label generation, we replace LAE-Label’s original InterVL2-8B and reasoning prompt with the newer Qwen2.5-VL-7B, guided by a structured prompt for open-ended category identification without explicit reasoning. This change of prompt improves mF_1 by 4.3% on NWPU-VHR-10 and reduces inference time by 92%. The prompt we use is as follows:

```
{
  "Persona": "You are an advanced AI model capable of understanding and
analyzing remote sensing images."
  "Task": "Given an input satellite imagery, identify the most likely object
class visible in the image. Provide the result as a single class name."
  "Instructions": [
    "Consider this is a region of interest cropped from a larger remote
sensing image.",
    "Focus on identifying the main object class visible in the cropped
region.",
    "Be specific with your answer, using a single class name."],
  "Output format": "\"class_name\"",
  "Answer": ["Provide only the class name in quotes, without additional
explanations. If it is not recognized, output \"Unrecognized\" "]
}
```

Qwen2.5-VL Given Qwen2.5-VL’s [2] extensive pre-training on object detection tasks, we request Qwen2.5-VL to generate a prompt template to perform IOD, and specify the output format following the examples in their paper. Taking DIOR dataset as an example, the prompts for each task are as follows.

- Open-vocabulary detection:

```
**Prompt:**
I need assistance with performing an remote sensing object detection task using
the provided category names: ['airplane', 'airport', 'baseball field',
'basketball court', 'bridge', 'chimney', 'expressway service area',
'expressway toll station', 'dam', 'golf field', 'ground track field',
'harbor', 'overpass', 'ship', 'stadium', 'storage tank', 'tennis court',
'train station', 'vehicle', 'windmill'].
Please provide the results in JSON format, where each object is represented as
follows:
- Each object should include a label (category name) and its corresponding
bounding box coordinates (in the format [x1, y1, x2, y2]).
**Example Output:**
[
  {"label": "category_name", "bbox_2d": [x1, y1, x2, y2]},
  {"label": "category_name", "bbox_2d": [x1, y1, x2, y2]},
  ...
]
```

- Open-ended detection:

```
**Prompt:**
Please detect all the visible objects in the satellite image and provide the
results in JSON format, where each object is represented as follows:
- Each object should include a label (category name) in singular form and its
corresponding bounding box coordinates (in the format [x1, y1, x2, y2]).
**Example Output:**
[
  {"label": "category1", "bbox_2d": [x1, y1, x2, y2]},
  {"label": "category2", "bbox_2d": [x1, y1, x2, y2]},
  ...
]
```

- Open-subclass detection (e.g., for “sports field”):

```
**Prompt:**
Please detect all the visible objects in the satellite image that belong to the
parent category **sports field** and provide the results in JSON format,
where each object is represented as follows:
```

```

- Each object should include a label (subcategory name) in singular form and its
  corresponding bounding box coordinates (in the format [x1, y1, x2, y2]).
- If none of the objects belong to the parent category is visible, output a empty
  empty list like [].
**Example Output:**
[
  {"label": "subcategory1", "bbox_2d": [x1, y1, x2, y2]},
  {"label": "subcategory2", "bbox_2d": [x1, y1, x2, y2]},
  ...
]

```

While incorporating detailed dataset-specific instructions into prompts enhances Qwen2.5-VL’s performance for object counting, such elaborations does not benefit direct detection. In fact, such instructions reduce mF₁ by 1% on NWPU-VHR-10 and have little effect on DIOR. The main paper reports open-vocabulary detection results without these instructions.

D Additional experiments

D.1 Comparison with zero-shot remote sensing object recognition methods on EarthInstruct

Direct comparison with some zero-shot remote sensing detection and segmentation methods (e.g., DesReg [90], OVA-DETR [79], ZoRI [21]) is difficult due to differing dataset splits, evaluation metrics, and limited reproducibility. Table 10 shows their reported mAP scores alongside InstructSAM’s mAP_{nc} on novel classes. Notably, InstructSAM-Qwen matches or outperforms these methods on their respective benchmarks (e.g., ZoRI on NWPU-VHR-10, OVA-DETR on DIOR). While these baselines use confidence-based AP, InstructSAM’s confidence-free AP_{nc} results underscore its robustness.

Table 10: Comparison with zero-shot remote sensing object detection and segmentation methods on **novel** classes. ‘-’ means data missing due to limited reproducibility. $\emptyset$ indicates model lacking the segmentation ability. AP_{nc} is reported for InstructSAM, while values in gray for other methods are AP reported in their original papers.

Method	NWPU-VHR-10		DIOR val		DIOR test	
	Box AP	Mask AP	Box AP	Mask AP	Box AP	Mask AP
DesReg [90]	-	$\emptyset$	-	$\emptyset$	7.9	$\emptyset$
OVA-DETR [79]	-	$\emptyset$	7.1	$\emptyset$	-	$\emptyset$
ZoRI [21]	-	12.3	-	-	-	8.5
InstructSAM-Qwen	24.6	24.1	7.6	6.3	4.9	4.3
InstructSAM-GPT4o	26.8	26.5	11.2	8.9	6.6	5.4

D.2 Comparison with open-vocabulary detection methods on out-of-distribution datasets

To compare with open-vocabulary methods that include DIOR into training, we compare the zero-shot performance on two out-of-distribution (OOD) datasets:

- **xBD** [18] is a large-scale building damage assessment dataset with spatial resolution below 0.8m. The test set includes 933 pre- and post-disaster image pairs with instance-level building masks. We use pre-disaster images to evaluate object counting and detection with the single category “building”.
- **Aerial Maritime Drone Large** [30] is a drone-based object detection dataset with 74 aerial maritime images and 1,151 bounding boxes. Categories include “docks”, “boats”, “lifts”, “jetskis”, and “cars”. The entire dataset is used for zero-shot evaluation.

Table 11 shows that LAE-DINO, trained on LAE-1M (including “building”), achieves the highest detection F₁-core (50.6) on xBD. On Aerial Maritime Drone, however, LAE-DINO detects only boats, even struggling with docks and cars despite semantic similarity to harbor and vehicle categories in training. Moreover, the confidence-based detectors (OWL, CASTDet, LAE-DINO) require dataset-

Table 11: Comparison with open-vocabulary detection methods on xBD and Aerial Maritime Drone Large datasets.

Method	xBD			Aerial Maritime Drone Large		
	Best Thr	Cnt mF ₁	Det mF ₁	Best Thr	Cnt mF ₁	Det mF ₁
OWL [51]	0.02	53.0	31.5	0.26	28.3	21.5
CASTDet [38]	0.00	0.0	0.0	0.40	13.3	10.8
LAE-DINO [56]	0.08	79.6	50.6	0.30	13.0	12.5
InstructSAM-GPT4o	-	65.9	37.2	-	44.5	22.5

specific thresholds to optimize zero-shot results, highlighting InstructSAM’s advantage in eliminating threshold tuning.

D.3 Selection of prompt format

We conduct five independent experiments evaluating Qwen2.5-VL and GPT-4o’s open-vocabulary counting ability on NWPU-VHR-10 using Markdown and JSON prompts. Table 12 shows the mean accuracies and standard deviations. Qwen2.5-VL exhibits only a 1.2% difference in mean accuracy between Markdown and JSON, with zero standard deviation for both. GPT-4o shows slight variability: $82.38\% \pm 0.94$ (Markdown) and $82.68\% \pm 0.39$ (JSON). These results indicate that these LVLM counters maintain relatively stable performance across different prompt formats.

Table 12: Mean accuracy and 1-sigma standard deviation for different prompt formats and models.

Model	Prompt Format	Mean Accuracy (%)	1-Sigma (Stand Deviation)
Qwen2.5-VL	Markdown	72.0	0.00
Qwen2.5-VL	JSON	73.2	0.00
GPT-4o	Markdown	82.4	0.94
GPT-4o	JSON	82.7	0.39

E Broader impacts

InstructSAM demonstrates a strong ability to recognize objects in remote sensing imagery with versatile instructions. It accelerates large-scale mapping applications, further supporting public agencies and humanitarian organizations in critical areas such as poverty mapping, disaster response. Its training-free paradigm and near-constant inference speed lower computational costs, decreasing carbon emissions and broadening access to remote sensing applications in resource-limited settings.

InstructSAM’s capabilities also raise privacy concerns as the spatial resolution of satellite imagery is growing higher. Hallucinations or misclassifications, stemming from biases in pre-trained models may produce unreliable outputs, require user verification to ensure accuracy.

F Qualitative results

This section presents qualitative results of InstructSAM across open-vocabulary (Figure 9), open-ended (Figure 10), and open-subclass settings (Figure 11). Additionally, we showcase its versatility in handling instructions to achieve certain goals in Figure 12 and its generalization to natural images in Figure 13.

F.1 Qualitative results in open-vocabulary setting




Figure 9: Qualitative results in open-vocabulary setting. While OWLv2 struggles to distinguish remote sensing objects beyond vehicles, and SegEarth-OV fails to separate foreground objects from the background, InstructSAM demonstrates superior performance in segmenting remote sensing objects.

F.2 Qualitative results in open-ended setting






Figure 10: Qualitative results in open-ended setting. Unlike GeoPixel and SkysenseGPT, which fail to detect classes outside their training set, InstructSAM demonstrates its ability to recognize diverse objects (e.g., pavilion in (a), tree in (c)) and provides more accurate bounding boxes and less fragmented masks.


F.3 Qualitative results in open-subclass setting



(a) Detecting the subclass of “means of transport”



(b) Detecting the subclass of “sports field”



(c) Detecting the subclass of “sports field”

Figure 11: Qualitative results in open-subclass setting. InstructSAM effectively identifies objects within parent categories. In contrast, Qwen2.5-VL struggles with dense objects, and OWLv2 faces challenges in classifying sports fields from a bird’s-eye view.

F.4 Qualitative results on other instructions

Task: Detect the infrastructure necessary to ensure that air ambulances can land effectively in the midst of urban areas in emergencies.

Task: Detect a spot near recreational spaces that would be effective in hosting a highly interactive community sports gathering.

Task: What would be the ideal venue to host swimming classes for a sizable group, ensuring both safety and easy access?




Figure 12: Qualitative results on following versatile instructions. Samples are from EarthReason [33] dataset. InstructSAM successfully recognizes objects based on implicit cues.

F.5 Qualitative results in natural images

Task: Detect all the electronic components in image.

Task: Detect the dice whose letters come before K in the picture.




Figure 13: Qualitative results on natural images. When equipped with generic CLIP models (DFN2B-CLIP [13]), InstructSAM effectively recognizes objects in natural images.