

COEVOL: Constructing Better Responses for Instruction Finetuning through Multi-Agent Cooperation

Anonymous ACL submission

Abstract

In recent years, instruction fine-tuning (IFT) on large language models (LLMs) has garnered considerable attention to enhance model performance on unseen tasks. Attempts have been made on automatic construction and effective selection for IFT data. However, we posit that previous methods have not fully harnessed the potential of LLMs for enhancing data quality. The responses within IFT data could be further enhanced by leveraging the capabilities of LLMs themselves. In this paper, we propose COEVOL, an LLM-based multi-agent cooperation framework for the improvement of responses for instructions. To effectively refine the responses, we develop an iterative framework following a *debate-advise-edit-judge* paradigm. A two-stage multi-agent debate strategy is further devised to ensure the diversity and reliability of editing suggestions within the framework. Empirically, models equipped with COEVOL outperform competitive baselines evaluated by MT-Bench and AlpacaEval, demonstrating its effectiveness in enhancing instruction-following capabilities for LLMs.

1 Introduction

Instruction fine-tuning (IFT) is an effective approach for enhancing the performance of language models in zero-shot and few-shot scenarios on previously unseen tasks. Improving the instruction-following capabilities of large language models (LLMs) has received increasing attentions from the natural language processing (NLP) community (Ouyang et al., 2022; Wei et al., 2022; Wang et al., 2023a; Longpre et al., 2023). Recent research has been focusing on constructing substantial quantities of IFT data with minimal human effort (Wang et al., 2023a; Honovich et al., 2023), where data construction is highlighted by researchers from multiple perspectives, including diversity, instruction complexity, and the quality of responses to

instructions (Liu et al., 2024).

To address the issue of easy or moderately difficult human-crafted instructions, several approaches (Wan et al., 2023; Zhao et al., 2024; Xu et al., 2024) have been developed to generate instructions of varying complexity levels. By emphasizing both complexity and diversity of the instructions, Lu et al. (2024) annotate IFT data using advanced LLMs and introduce a complexity-focused diverse sampling method for data selection. Since LIMA (Zhou et al., 2023) suggested that the quality of IFT data is more important than its quantity, a series of data selection methods have been proposed, focusing on extracting high-quality samples from existing datasets of uneven distribution of qualities (Li et al., 2023d; Liu et al., 2024; Chen et al., 2024; Xia et al., 2024). However, we observe that due to the inherent characteristics of causal language modeling, LLMs sometimes fail to deliver the most comprehensive and reasonable answers they can produce. We posit that previous data construction approaches have not fully harnessed the potential of these LLMs. The responses within IFT data could be further refined by leveraging the capabilities of LLMs themselves.

Due to the diversity and complexity of instructions within IFT data, refining the present response is not a trivial task. Consequently, we are attempting to introduce multi-agents to cooperate in this endeavor. Although multi-agent debate (MAD) has been proven effective in answer improvement (Liang et al., 2023; Du et al., 2023) and evaluation (Chan et al., 2024) by prompting the diversity of thought, strengthening the divergent thinking of agents cost-effectively remains challenging. We categorize these approaches into two types based on their debate strategies: free debate and predetermined-position debate. (1) In a free debate, participants freely express their opinions on the topic, and achieving response diversity requires the inclusion of more participants in the debate




Figure 1: Overview of the proposed multi-agent cooperation framework CoEvol.

framework. (2) In a predetermined-position debate, one debater opposes the other’s views, and a judge decides which side is more persuasive. However, managing the “tit for tat” nature of the debate poses a difficulty, while variables like speaking order and statement length can bias the judge’s decision. All these issues make it challenging to refine responses of IFT data through a multi-agent approach.

In this paper, taking inspiration from human cooperation and competition in real-world society, we endeavor to construct superior responses to instructions with LLM-based multi-agents. Following a *debate-advise-edit-judge* paradigm, we propose a novel framework named COEVOL to iteratively evolve responses through multi-agents cooperation. In each iteration, the framework initially enhances the diversity and reliability of subsequent suggestions through a debate between two debaters. The debate history is then presented to an advisor to inform their proposal, followed by an editor who modifies the original response accordingly. Finally, a judge evaluates the revised response and determines whether further iteration is necessary. This pipeline enables CoEvol to identify clear and rational evolving directions for the original responses through multi-agent cooperation, resulting in high-quality IFT data. Furthermore, to address the aforementioned challenges of previous MAD approaches, we design a two-stage strategy within the proposed framework. By combining the

advantages of previous methods, our strategy maximizes the diversity of viewpoints while reducing the cost of agents. This novel debate strategy enables the framework to guide responses to evolve in a reliable and trustworthy manner.

We summarize our contributions as follows: (1) We introduce a novel CoEvol framework that follows a *debate-advise-edit-judge* paradigm to refine responses within IFT data through multi-agent collaboration. Instead of selecting high-quality data, our approach focuses on editing the low-quality responses of instances to enhance the effectiveness of the IFT data. (2) We propose a two-stage multi-agent debate strategy designed to maximize the diversity of perspectives within the debate while minimizing the cost of agents. (3) Empirical results over competitive baselines demonstrate the effectiveness and universality of CoEvol.

2 Method

In this section, we introduce our proposed framework for efficiently editing IFT data. Figure 1 shows the architecture of CoEvol, where five LLM-based agents: two counter-part debaters, an advisor, an editor, and a judge are assigned in one pipeline to finish the task altogether.

2.1 Task Assignment

Before we delve into the detailed design of CoEvol, concepts involved in the IFT task should be

clarified first. In this paper, an IFT data sample is denoted by x , which comprises the instruction, input, and output components. The instruction typically serves as a description of a task, while the input represents the specific content of this task. When provided with the given instruction and input, the output refers to the response r generated by LLMs.

2.2 Evolution Pipeline

We find that while LLMs may not consistently offer comprehensive and exhaustive responses, they excel in recognizing shortcomings within provided responses and offering recommendations for augmentation. Based on this observation, we conceive the idea of integrating LLM-based multi-agents into one pipeline for the iterative refinement of imperfect data samples.

Concretely, we first initialize an experienced advisor A_{adv} through role-play, and ask it to propose writing suggestions for the given data sample x :

$$h_{adv} \leftarrow A_{adv}(\hat{x}, t_{adv}) \quad (1)$$

where \hat{x} denotes the text sequence constructed by filling a given template with the data sample x , and t_{adv} signifies the task prompt for the agent advisor. It merits attention that when the original response is presented to the LLM, it tends to proffer more specific suggestions, whereas when given only the instruction, it provides more general advice which is less helpful for response improvement. Then we assign an professional editor A_{edt} to modify the original response r referring to the generated suggestions:

$$h_{edt} \leftarrow A_{edt}(\hat{x}, t_{edt}, h_{adv}) \quad (2)$$

where t_{adv} signifies the task prompt for the agent editor. Denote the edited response as r' , a helpful judge A_{jdg} is introduced to compare the helpfulness, relevance, accuracy, and level of details of the original response r and the edited response r' :

$$h_{jdg} \leftarrow A_{jdg}(\hat{x}, t_{jdg}, h_{edt}) \quad (3)$$

Throughout this process, we discern that the numeric outputs of LLMs occasionally do not correspond with their textual content. For this reason, rather than soliciting the judge to rate responses and compare scores, we instruct it to select the superior response or declare a draw directly from the two presented responses. Moreover, to mitigate the existing position bias inherent within LLM

judges (Ko et al., 2020; Shen et al., 2023), we follow Chen et al. (2024) to switch the order of original and edited response and make two judgments.

With these judgments, we then respectively calculate scores for r and r' according to the following criteria:

$$s(r) = \begin{cases} 1, & r \text{ is better or tie} \\ 0, & \text{otherwise} \end{cases} \quad (4)$$

Subsequently, these scores will determine whether to continue data evolution or stop the loop:

- $s(r') > s(r)$: The edited response r' will be forwarded to the next loop, replacing the original response r . In this case, CoEvol will continue to execute the above pipeline.
- $s(r') \leq s(r)$: The original response r will be kept as the final response for model fine-tuning. In this case, CoEvol will stop the loop.

2.3 Debate Strategy

In our framework, the writing suggestions provided by the advisor explicitly determine the direction of response evolution and thus play an important role in the evolution pipeline. To further increase the diversity while ensuring the reliability of these suggestions, we devise a two-stage debate strategy. It combines the advantages of both the predetermined-position debate and the free debate strategy, providing supplemental information from different perspectives to assist the agent advisor in proposing more reliable writing suggestions. More specifically, we employ a predetermined-position debate in the first round, subsequently shifting to a free debate in the second round and conducting a cross-evaluation between the two agents. To mitigate the influence of speaking order on the debate, we allow the debaters to speak concurrently.

predetermined-position Debate. In the first round of the debate, we initialize two debate agents with predetermined-positions. To facilitate better engagement from the positive and critical debaters with our prompts, we initially apply role-play prompts to define their respective characters. Subsequently, we provide them with structured sample content, denoted as \hat{x} , along with a specific task t . This setup helps us acquire their arguments, which are denoted as g_{pos}^{pred} for the positive debater and g_{crt}^{pred} for the critical debater:

$$g_{pos}^{pred} \leftarrow A_{pos}(\hat{x}, t_{pos}^{pred}) \quad (5)$$

$$g_{crt}^{pred} \leftarrow A_{crt}(\hat{x}, t_{crt}^{pred}) \quad (6)$$

Algorithm 1 Pseudocode of CoEvol

Input: x : IFT data sample; r : original response;
 K : maximum rounds of evolution;
Output: x' : evolved sample

- 1: initialize agents A_{pos} , A_{crt} , A_{adv} , A_{edt} , and A_{jdg} ;
- 2: $k \leftarrow 1$;
- 3: **while** $k \leq K$ **do**
- 4: construct structured \hat{x} from x ;
- 5: generate g_{pos}^{pred} with A_{pos} ; ▷ Eq. 5
- 6: generate g_{crt}^{pred} with A_{crt} ; ▷ Eq. 6
- 7: generate g_{pos}^{free} with A_{pos} ; ▷ Eq. 7
- 8: generate g_{crt}^{free} with A_{crt} ; ▷ Eq. 8
- 9: construct debate history G_{dbt} ;
- 10: generate h_{adv} with A_{adv} ; ▷ Eq. 9
- 11: generate h_{edt} with A_{edt} ;
- 12: extract edited response r' ; ▷ Eq. 2
- 13: switch order of responses and generate two judgments h_{jdg} with A_{jdg} ; ▷ Eq. 3
- 14: calculate scores $s(r)$ and $s(r')$; ▷ Eq. 4
- 15: **if** $s(r') > s(r)$ **then**
- 16: update x with r' ;
- 17: refresh the memory of all agents;
- 18: **else**
- 19: **Break**
- 20: **end if**
- 21: $k \leftarrow k + 1$;
- 22: **end while**
- 23: $x' \leftarrow x$;
- 24: **return** x'

where A_{pos} and A_{crt} respectively refer to the initialized positive debater and negative debater, t_{pos}^{pred} and t_{crt}^{pred} denote the task prompts in predetermined-position debate stage. To maximize the initial diversity of the debate, we instruct the two debaters with contrary task prompts. Regarding a debate topic “whether the original response accurately answers the given instruction”, we prompt the positive debater to support the claim and give reasons, while asking the critical debater to argue against it and offer suggestions on how to improve the original response. In this way, we ensure a distinct contrast in viewpoints from the outset of the debate.

Free Debate and Cross-Evaluation. In the second round of the debate, we instruct A_{pos} and A_{crt} to freely express their opinion and do a cross-evaluation regarding to the previous debate topic. Taking debaters’ arguments in the first round as reviews towards the given response, we then re-

quest both debaters to evaluate the plausibility of the opposing debater’s prior review in this stage:

$$g_{pos}^{free} \leftarrow A_{pos}(\hat{x}, t_{pos}^{free}, g_{crt}^{pred}) \quad (7)$$

$$g_{crt}^{free} \leftarrow A_{crt}(\hat{x}, t_{crt}^{free}, g_{pos}^{pred}) \quad (8)$$

where t_{pos}^{free} and t_{crt}^{free} respectively denote the task prompts for the positive debater and the critical debater during the free debate stage. With kept memory from the first debate round, we hope both debaters can make objective arguments, resulting in more reliable evaluations.

2.4 Data Refinement

Based on the proposed two-stage debate strategy, we obtain viewpoints related to the original response, which are diverse and reliable. Then we sent the generated debate history to the agent advisor, asking it to summarize credible ideas from the dialogue and rewrite them into no more than 3 writing suggestions for improving the given response. This process is correspondingly referred to as:

$$h_{adv} \leftarrow A_{adv}(\hat{x}, t_{adv}, G_{dbt}) \quad (9)$$

where $G_{dbt} = \{g_{pos}^{pred}, g_{crt}^{pred}, g_{pos}^{free}, g_{crt}^{free}\}$ denotes the debate history comprising all the arguments presented by both debaters.

To sum up, the proposed framework CoEvol works as follows: For each data sample awaiting improvement, two agent debaters are initially involved in a debate to present their arguments. Then the agent editor raises helpful writing suggestions for response improvement based on the debate history. Referring to these suggestions, an agent editor tries to generate an edited response. Finally, a judge is assigned to compare the original response and the edited response, deciding whether to update the response for further evolution or keep the original one and break the loop. Additionally, a hyperparameter K is set to control the maximum iteration for data evolution. We refresh the memory (session history) of all agents after each iteration. We present the pseudo-code of CoEvol in Algorithm 1. All prompts, including role-play, task assignment, and template used to regularize context for agents are shown in detail in Appendix B.

3 Experimental Results

3.1 Preliminary Experiment

Experimental Setup In this section, we aim to validate the capability of the proposed framework

Table 1: Results of different instruction-tuned models on MT-Bench and AlpacaEval based on the GPT-4 automatic evaluation. We also show the data source, data construction method, data size, and model alignment method for training. The best result is bolded, while the second-best result is underlined. \diamond : results extracted from the official rank list; \heartsuit : results reproduced by ourselves.

Model	Data Source	Data Construction / Size	Alignment	MT-Bench	AlpacaEval (%)
LLaMA2-7B-Chat \diamond	-	- / >100K + 1M	SFT + RLHF	6.27	71.4
Alpaca2-7B \heartsuit		Full / 52K	SFT	3.94	20.15
AlpaGasus2-7B \heartsuit	D_{alpaca}	Select / 9K	SFT	2.86	8.38
LLaMA2-7B-SFT $_{random}$		Random / 9K	SFT	2.28	8.31
CoEvol-LLaMA2-7B $_{CHATGPT}$		Random + Evol / 9K	SFT	<u>4.32</u>	<u>43.55</u>

CoEvol in enhancing the quality of randomly selected IFT data. We use the 52K Alpaca data (Taori et al., 2023) as the base data pool D_{alpaca} . Previously, Chen et al. (2024) select 9K high-quality data from D_{alpaca} according to ratings given by gpt-3.5-turbo (abbreviated as *Select*) and fine-tune a stronger model named ALPAGASUS. Deem it as a competitive baseline approach, we first randomly select the same amount of 9K data from D_{alpaca} to form a dataset (abbreviated as *Random*). Then CoEvol is applied to these data for response improvement and obtain a dataset with higher quality (abbreviated as *Random + Evol*). To fully evolve data samples, we set the maximum number of iterations in CoEvol to 3. We fine-tune the pre-trained language model LLaMA2-7B (Touvron et al., 2023) on aforementioned datasets respectively and evaluate them on MT-Bench (Zheng et al., 2023) as well as AlpacaEval (Li et al., 2023c) automatically. We note there exists another relevant IFT data augmentation method (Subramaniam et al., 2024), where codes and datasets have not been released. Considering the incomplete prompts provided in the paper, we exclude it from the comparative methods in our experiments. Please note that in this section, we employ ChatGPT (gpt-3.5-turbo-1106) (OpenAI, 2022) as multi-agents within CoEvol. Detailed setup of data evolution is reported in Appendix C. Settings of fine-tuning are provided in Appendix D.

Main Results Table 1 illustrates evaluation results of different LLaMA2-7B-based instruction-tuned models on MT-Bench and AlpacaEval. Since AlpaGasus’s data is not officially disclosed, we reproduce AlpaGasus2-7B on 9K filtered data released by an unofficial implementation.¹ Among all these models, LLaMA2-7B-Chat performs the best, leveraging SFT and RLHF on massive data. In models fine-tuned with less data, the model trained

on data evolved by CoEvol performs better. As shown in the results, CoEvol significantly improves the quality of 9K randomly sampled data, leading to a superior model for instruction following. It also outperforms models fine-tuned on full 52K data and 9K data selected by LLM-based scoring. This serves as compelling evidence of the efficacy of CoEvol in enhancing the quality of IFT data.

Furthermore, it is worth noting that MT-Bench assesses the model’s performance using both first-turn and second-turn responses to questions, thereby evaluating the model’s multi-turn instruction-following capability. In contrast, the Alpaca dataset follows a single-turn question-answer format, resulting in a disparity between the model’s fine-tuning and the evaluation phase. To narrow this gap and explore the potential of CoEvol, we introduce a more diversified experimental setup and conduct further experiments on the framework.

3.2 Further Experiment

Experimental Setup In this section, we delve further into the universality and effectiveness of the proposed framework, wherein four questions require answers: (1) Can CoEvol further improve the “high-quality” data mined by advanced data selection approaches? (2) Can CoEvol be applied to different forms of data like multi-turn conversations? (3) Can agents in CoEvol work efficiently based on different LLMs? (4) Can evolved data effectively enhance the instruction-following capability of different pre-trained language models?

We conduct a series of experiments to address the precedent issues. For questions (1) and (2), we construct a data pool D_{single} composed of single-turn IFT data samples, and a data pool D_{multi} composed of multi-turn conversations, separately. Concretely, we construct D_{single} with Alpaca, WizardLM (based on Alpaca and ShareGPT) (Xu et al., 2024), Dolly (Conover et al.,

¹<https://github.com/gpt4life/alpagasus>

Table 2: Results of different instruction-tuned models on MT-Bench and AlpacaEval based on the GPT-4 automatic evaluation. We also show the data source, data construction method, data size, and model alignment method during training. The best result is bolded, while the second-best result is underlined. \diamond : results extracted from the official rank list; \heartsuit : results reproduced by ourselves.

Model	Data Source	Data Construction / Size	Alignment	MT-Bench	AlpacaEval (%)
Mistral-7B-Instruct-v0.1 \diamond	-	-	-	6.84	69.65
DEITA-Mistral-7B \heartsuit		Select / 6K	SFT	6.26	65.49
COEVOL-Mistral-7B _{CHATGPT}	D_{single}	Select + Evol / 6K	SFT	6.45	67.04
COEVOL-Mistral-7B _{MIXTRAL}		Select + Evol / 6K	SFT	6.75	71.43
DEITA-Mistral-7B \heartsuit		Select / 6K	SFT	6.98	80.08
COEVOL-Mistral-7B _{CHATGPT}	D_{multi}	Select + Evol / 6K	SFT	<u>7.16</u>	<u>83.54</u>
COEVOL-Mistral-7B _{MIXTRAL}		Select + Evol / 6K	SFT	7.22	89.76

2023), and LIMA (Zhou et al., 2023); and construct D_{multi} with UltraChat (Ding et al., 2023) and ShareGPT (Chiang et al., 2023). After establishing the two data pools, we employ an efficient IFT data selection method DEITA (Liu et al., 2024) to extract 6K high-quality data from each of these pools. Our aspiration is for the selected “high-quality” data to serve as the cutting-edge baseline for model fine-tuning. Then we further apply CoEvol on these data to enhance the quality of data through response improvement. In response to question (3), we independently employ the proprietary model ChatGPT and the open-sourced model Mixtral-8 \times 7B-Instruct-v0.1 (Jiang et al., 2024) to power CoEvol for data evolution. To answer question (4), we adopt the foundation model Mistral-7B-v0.1 (Jiang et al., 2023) for fine-tuning. Subsequently, we conduct an automatic evaluation using both MT-Bench and AlpacaEval as benchmarks.

Main Results Table 2 illustrates evaluation results of different Mistral-7B-based instruction-tuned models on MT-Bench and AlpacaEval. Among all these models, COEVOL-Mistral-7B_{MIXTRAL} performs the best, beneficial from the data evolution on multi-turn conversation data. Based on evaluation results, even for selected high-quality data, further improvements in model performance can be achieved using CoEvol for data refinement. Through model comparison, we demonstrate the effectiveness of this framework across different data formats and agents. Compared to preliminary experiments, our framework has also proven effective with different base models. Based on the observations mentioned above, the four questions previously posed have all been resolved, demonstrating the universality and effectiveness of this framework.

Table 3: Ablation Study of the proposed framework CoEvol. Different components of the pipeline are respectively applied to the 9K random sampled Alpaca data and are then utilized for model fine-tuning. We report the scores of MT-Bench and AlpacaEval based on the GPT-4 automatic evaluation. The best result is bolded, while the second-best result is underlined.

Model	MT-Bench	AlpacaEval (%)
LLaMA2-7B-SFT _{random}	2.28	8.31
- edit	4.05	26.15
- advise (w/o resp) + edit	3.49	16.38
- advise + edit	4.09	30.17
- debate + advise + edit	<u>4.17</u>	<u>38.25</u>
- full COEVOL	4.32	43.55

4 Analysis

4.1 Ablation Study

To verify the validity of each component within CoEvol, we conduct an ablation study of the framework. Continuing from experiments in Section 3.1, we evolve the 9K randomly sampled data from D_{alpaca} under the following settings:

- **edit**: We solely utilize an agent editor to respond according to the given instruction and the input context. The model trained on this data serves as a baseline, excluding the influence of other agents in the proposed pipeline.
- **advise (w/o resp) + edit**: We include an agent advisor to propose writing suggestions and an agent editor to generate responses accordingly. Note that in this experiment, we only show the given instructions and inputs to the advisor.
- **advise + edit**: We include an agent advisor to propose suggestions and an agent editor to output the response accordingly. In this experiment, the original response is also shown to the advisor.




Figure 2: Statistical results of the data evolution process. The proportion of data with different numbers of rounds of evolution driven by CoEvol is shown in figure (a). The average token length of responses in original and evolved data is shown in figure (b). We report statistical results on different datasets and backbone LLMs for agents.

- **debate + advise + edit**: Two agent debaters with opposite positions are further included to provide more reliable references for the advisor.
- **full CoEvol**: The full proposed framework, where agent debaters, advisor, editor, and judge are all involved in the loop. The maximum number of iterations is set to 3.

With other settings held constantly, we respectively fine-tune LLaMA2-7B on these evolved data. Evaluation results of the ablated models on MT-Bench and AlpacaEval are shown in Table 3. According to the results, we observe that the best result is obtained by the complete CoEvol. The participation of each agent enhances the performance of the model, indicating their contribution within the framework. More rounds of data evolution under the guidance of the agent judge also contribute to the data augmentation. It is worth noting that, prompting agent advisor with only instruction and input compromises the data quality. However, providing the original responses aids the agent advisor in offering more specific suggestions, resulting in an improvement in model performance. We provide more detailed examples of data evolution using ablation models in Appendix E.

4.2 Analysis on Data Evolution

Statistical Results To get deep insight into CoEvol, we investigate the data evolution process from multiple perspectives, including statistical results and evolving directions. As illustrated in Figure 2(a), the proportions of data with different rounds of evolution vary among different datasets




Figure 3: Overview of the evolving direction of CoEvol. Due to space constraints, we merge similar root verbs and show parts of verb-object pairs with top counts.

and backbone LLMs. Considering data that has undergone at least one round of evolution, the randomly sampled data from Alpaca dataset has the highest rate of evolution among all these datasets. We attribute this to its poor initial quality of data. Interestingly, we also observe that CoEvol, when based on Mixtral, has a higher proportion of data that has undergone at least two rounds of evolution compared to that based on ChatGPT.

As longer outputs are preferred by both human and machine evaluators on most datasets (Dubois et al., 2023), the average token length of responses reflects the comprehensiveness of response to some

Table 4: Cases of responses generated by the baseline model DEITA-Mistral-7B and proposed model COEVOL-Mistral-7B_{MIXTRAL}. Instructions are extracted from the AlpacaEval dataset. To highlight the differences between responses, we mark direct responses to instructions in green and additional relevant information in yellow.

Responses from DEITA-Mistral-7B	Responses from COEVOL-Mistral-7B _{MIXTRAL}
<p>#1 Instruction: What is the largest star in our galaxy? The largest star in our galaxy, the Milky Way, is called VY Canis Majoris ... Its mass is estimated to be around 15-20 times the mass of the Sun ...</p>	<p>The largest star in our galaxy, the Milky Way, is a star known as VY Canis Majoris ... To put that into perspective, if the Sun were the size of a small grape, VY Canis Majoris would be the size of a basketball ...</p>
<p>#2 Instruction: What is the name of the windows XP background image? Where was it taken and by who? The default Windows XP background image is called Bliss and it was taken by Charles O’Rear. The image was taken in Napa Valley, California, USA.</p>	<p>The Windows XP background image is called Bliss. It was taken by Charles O’Rear, a professional photographer, in 1996 in Napa Valley, California. The image depicts a rolling hillside with a few trees and a blue sky in the background. The image was chosen by Microsoft to represent the serene and optimistic nature of the Windows XP operating system.</p>
<p>#3 Instruction: Write a daily exercise routine for Monday to Sunday with a rest day in between. Monday: 30 min cardio, 30 min strength training Tuesday: 45 min yoga, 15 min abs Wednesday: Rest day Thursday: 30 min HIIT, 20 min stretching Friday: 45 min Pilates, 15 min arms Saturday: 60 min outdoor activity (e.g. hiking, biking) Sunday: 30 min cardio, 30 min strength training</p>	<p>Sure, here’s a daily exercise routine for Monday to Sunday with a rest day in between: Monday: Start the week with a 30-minute HIIT workout to boost metabolism and burn calories. Tuesday: Strengthen your core with a 20-minute plank challenge, holding the plank position for as long as possible each day ... Remember to warm up before each workout, stay hydrated, and listen to your body to avoid injury.</p>

480 extent. According to Figure 2(b), we observe
 481 that the average token length of a response in the
 482 evolved dataset has significantly increased compared
 483 to the non-evolved dataset.

484 **Evolving Directions** Since the evolving direction
 485 of data is determined by suggestions proposed by
 486 the agent advisor, we try to investigate which parts
 487 of the data are improved by CoEvol. Following
 488 (Taori et al., 2023), we adopt spaCy² to extract
 489 the root verb together with its direct object from
 490 these suggestions. Figure 3 shows an overview of
 491 evolving directions of CoEvol. where root verbs
 492 and direct objects are extracted from suggestions
 493 on 9K randomly sampled Alpaca data. The inner
 494 circle of the plot represents the root verb of the
 495 suggestions, while the outer circle represents the
 496 direct objects. Based on the investigation, a large
 497 part of data is evolved by incorporating details and
 498 explanations (shown in green), while enriching the
 499 existing descriptions (shown in blue) also plays an
 500 important role in the process of data augmentation.
 501 In addition to these relatively common suggestions,
 502 more diverse and specific advice is generated by
 503 the framework, yielding a total of 235 root verbs
 504 and 4,118 verb-object pairs parsed by the tool.

²<https://spacy.io/>

4.3 Case Study

505 Through specific cases, we compare responses
 506 from the baseline model and our proposed model
 507 in Table 4 to illustrate the behavior of CoEvol.
 508 Enhanced with rich details and examples, the evolved
 509 response is more comprehensive and helpful than
 510 the original response, without providing content
 511 beyond the scope of its instruction.
 512

5 Conclusion

513 In this paper, we introduce CoEvol, an innovative
 514 framework for efficient quality improvement on
 515 IFT data through multi-agent cooperation. To fully
 516 exploit the potential of LLMs for response editing,
 517 we propose a two-stage MAD strategy to maximize
 518 the diversity of perspectives within debate while
 519 minimizing the cost of agents. Following a debate-
 520 advise-edit-judge paradigm, we establish a pipeline
 521 to harness the collective power of agents with distinct
 522 roles. Experimental results substantiate the
 523 efficacy of our proposed framework, showcasing its
 524 superiority in evolving better IFT data through
 525 response augmentation. Codes, datasets, and model
 526 weights developed in this paper are publicly available.
 527 We hope this work can offer new perspectives
 528 and references for the automatic construction of
 529 high-quality data.
 530

531 Limitations

532 In this work, we proposed CoEvol, an LLM-based
533 multi-agent cooperation framework for improving
534 IFT data quality through response enhancement.
535 Although experimental results demonstrate that our
536 framework is viable, there are still some limitations
537 that need to be considered: (1) We build multi-
538 agents on top of the same LLM, where the inherent
539 consistency of the model may lead to the accumu-
540 lation of bias. Further experiments should be done
541 to investigate the impact of agents based on dif-
542 ferent LLMs on the proposed framework. (2) Due
543 to time and cost considerations, we conduct our
544 experiments on advanced LLMs like gpt-3.5-turbo
545 and mixtral. We are also wondering how far the
546 most powerful models like GPT-4 and Claude-3
547 can go when equipped with CoEvol. We plan to
548 explore this in the future.

549 References

550 Stephen Bach, Victor Sanh, Zheng Xin Yong, Albert
551 Webson, Colin Raffel, Nihal V. Nayak, Abheesht
552 Sharma, Taewoon Kim, M Saiful Bari, Thibault
553 Fevry, Zaid Alyafeai, Manan Dey, Andrea Santilli,
554 Zhiqing Sun, Srulik Ben-david, Canwen Xu, Gun-
555 jan Chhablani, Han Wang, Jason Fries, Maged Al-
556 shaibani, Shanya Sharma, Urmish Thakker, Khalid
557 Almubarak, Xiangru Tang, Dragomir Radev, Mike
558 Tian-jian Jiang, and Alexander Rush. 2022. [Prompt-Source: An integrated development environment and repository for natural language prompts](#). In *Proceedings of the 60th Annual Meeting of the Association for Computational Linguistics: System Demonstrations*, pages 93–104, Dublin, Ireland. Association for Computational Linguistics.

565 Chi-Min Chan, Weize Chen, Yusheng Su, Jianxuan Yu,
566 Wei Xue, Shanghang Zhang, Jie Fu, and Zhiyuan Liu.
567 2024. [Chateval: Towards better LLM-based evaluators through multi-agent debate](#). In *The Twelfth International Conference on Learning Representations*.

571 Lichang Chen, Shiyang Li, Jun Yan, Hai Wang, Kalpa
572 Gunaratna, Vikas Yadav, Zheng Tang, Vijay Srinivasan,
573 Tianyi Zhou, Heng Huang, and Hongxia Jin.
574 2024. [Alpagasus: Training a better alpaca model with fewer data](#). In *The Twelfth International Conference on Learning Representations*.

577 Wei-Lin Chiang, Zhuohan Li, Zi Lin, Ying Sheng,
578 Zhanghao Wu, Hao Zhang, Lianmin Zheng, Siyuan
579 Zhuang, Yonghao Zhuang, Joseph E. Gonzalez, Ion
580 Stoica, and Eric P. Xing. 2023. [Vicuna: An open-source chatbot impressing gpt-4 with 90%* chatgpt quality](#).

583 Hyung Won Chung, Le Hou, Shayne Longpre, Barret
584 Zoph, Yi Tay, William Fedus, Yunxuan Li, Xuezhi

585 Wang, Mostafa Dehghani, Siddhartha Brahma, et al. 586 2022. [Scaling instruction-finetuned language models](#). 587 *arXiv preprint arXiv:2210.11416*.

588 Mike Conover, Matt Hayes, Ankit Mathur, Jianwei Xie,
589 Jun Wan, Sam Shah, Ali Ghodsi, Patrick Wendell,
590 Matei Zaharia, and Reynold Xin. 2023. [Free dolly: Introducing the world’s first truly open instruction-tuned llm](#). *Company Blog of Databricks*. 592

593 Ning Ding, Yulin Chen, Bokai Xu, Yujia Qin,
594 Shengding Hu, Zhiyuan Liu, Maosong Sun, and
595 Bowen Zhou. 2023. [Enhancing chat language models by scaling high-quality instructional conversations](#). In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing*, pages 3029–3051, Singapore. Association for Computational Linguistics. 600

601 Yilun Du, Shuang Li, Antonio Torralba, Joshua B Tenen-
602 baum, and Igor Mordatch. 2023. [Improving factuality and reasoning in language models through multiagent debate](#). *arXiv preprint arXiv:2305.14325*. 604

605 Yann Dubois, Xuechen Li, Rohan Taori, Tianyi Zhang,
606 Ishaan Gulrajani, Jimmy Ba, Carlos Guestrin, Percy
607 Liang, and Tatsunori Hashimoto. 2023. [AlpacaFarm: A simulation framework for methods that learn from human feedback](#). In *Thirty-seventh Conference on Neural Information Processing Systems*. 610

611 Or Honovich, Thomas Scialom, Omer Levy, and Timo
612 Schick. 2023. [Unnatural instructions: Tuning language models with \(almost\) no human labor](#). In *Proceedings of the 61st Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 14409–14428, Toronto, Canada. Association for Computational Linguistics. 617

618 Albert Q Jiang, Alexandre Sablayrolles, Arthur Mensch,
619 Chris Bamford, Devendra Singh Chaplot, Diego de las Casas,
620 Florian Bressand, Gianna Lengyel, Guillaume Lample,
621 Lucile Saulnier, et al. 2023. [Mistral 7b](#). *arXiv preprint arXiv:2310.06825*. 622

623 Albert Q Jiang, Alexandre Sablayrolles, Antoine
624 Roux, Arthur Mensch, Blanche Savary, Chris Bamford,
625 Devendra Singh Chaplot, Diego de las Casas,
626 Emma Bou Hanna, Florian Bressand, et al. 2024. [Mixtral of experts](#). *arXiv preprint arXiv:2401.04088*. 627

628 Miyoung Ko, Jinhyuk Lee, Hyunjae Kim, Gangwoo
629 Kim, and Jaewoo Kang. 2020. [Look at the first sentence: Position bias in question answering](#). In *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pages 1109–1121, Online. Association for Computational Linguistics. 634

635 Guohao Li, Hasan Abed Al Kader Hammoud, Hani
636 Itani, Dmitrii Khizbullin, and Bernard Ghanem.
637 2023a. [CAMEL: Communicative agents for “mind” exploration of large language model society](#). In *Thirty-seventh Conference on Neural Information Processing Systems*. 639 640

641	Ming Li, Yong Zhang, Zhitao Li, Jiuhai Chen, Lichang	Baolin Peng, Chunyuan Li, Pengcheng He, Michel Gal-	697
642	Chen, Ning Cheng, Jianzong Wang, Tianyi Zhou, and	ley, and Jianfeng Gao. 2023. Instruction tuning with	698
643	Jing Xiao. 2023b. From quantity to quality: Boosting	gpt-4. <i>arXiv preprint arXiv:2304.03277</i> .	699
644	llm performance with self-guided data selection for		
645	instruction tuning. <i>arXiv preprint arXiv:2308.12032</i> .		
646	Xuechen Li, Tianyi Zhang, Yann Dubois, Rohan Taori,	Chen Qian, Xin Cong, Cheng Yang, Weize Chen,	700
647	Ishaan Gulrajani, Carlos Guestrin, Percy Liang, and	Yusheng Su, Juyuan Xu, Zhiyuan Liu, and Maosong	701
648	Tatsunori B. Hashimoto. 2023c. AlpacaEval: An	Sun. 2023. Communicative agents for software de-	702
649	automatic evaluator of instruction-following models.	velopment. <i>arXiv preprint arXiv:2307.07924</i> .	703
650	https://github.com/tatsu-lab/alpaca_eval .		
651	Yunshui Li, Binyuan Hui, Xiaobo Xia, Jiayi Yang,	Jie Ren, Samyam Rajbhandari, Reza Yazdani Am-	704
652	Min Yang, Lei Zhang, Shuzheng Si, Junhao Liu,	inabadi, Olatunji Ruwase, Shuangyan Yang, Minjia	705
653	Tongliang Liu, Fei Huang, et al. 2023d. One shot	Zhang, Dong Li, and Yuxiong He. 2021. {Zero-	706
654	learning as instruction data prospector for large lan-	offload}: Democratizing {billion-scale} model train-	707
655	guage models. <i>arXiv preprint arXiv:2312.10302</i> .	ing. In <i>2021 USENIX Annual Technical Conference</i>	708
656		(<i>USENIX ATC 21</i>), pages 551–564.	709
657	Tian Liang, Zhiwei He, Wenxiang Jiao, Xing Wang,	Chenhui Shen, Liying Cheng, Xuan-Phi Nguyen, Yang	710
658	Yan Wang, Rui Wang, Yujiu Yang, Zhaopeng Tu, and	You, and Lidong Bing. 2023. <i>Large language mod-</i>	711
659	Shuming Shi. 2023. Encouraging divergent thinking	<i>els are not yet human-level evaluators for abstrac-</i>	712
660	in large language models through multi-agent debate.	<i>tive summarization</i> . In <i>Findings of the Association</i>	713
	<i>arXiv preprint arXiv:2305.19118</i> .	<i>for Computational Linguistics: EMNLP 2023</i> , pages	714
661		4215–4233, Singapore. Association for Computa-	715
662	Wei Liu, Weihao Zeng, Keqing He, Yong Jiang, and	tional Linguistics.	716
663	Junxian He. 2024. <i>What makes good data for align-</i>	Vighnesh Subramaniam, Antonio Torralba, and Shuang	717
664	<i>ment? a comprehensive study of automatic data se-</i>	Li. 2024. <i>DebateGPT: Fine-tuning large language</i>	718
665	<i>lection in instruction tuning</i> . In <i>The Twelfth Interna-</i>	<i>models with multi-agent debate supervision</i> .	719
666	<i>tional Conference on Learning Representations</i> .		
667	Shayne Longpre, Le Hou, Tu Vu, Albert Webson,	Rohan Taori, Ishaan Gulrajani, Tianyi Zhang, Yann	720
668	Hyung Won Chung, Yi Tay, Denny Zhou, Quoc V Le,	Dubois, Xuechen Li, Carlos Guestrin, Percy Liang,	721
669	Barret Zoph, Jason Wei, and Adam Roberts. 2023.	and Tatsunori B. Hashimoto. 2023. Stanford alpaca:	722
670	<i>The flan collection: Designing data and methods for</i>	An instruction-following llama model. https://	723
671	<i>effective instruction tuning</i> . In <i>Proceedings of the</i>	github.com/tatsu-lab/stanford_alpaca .	724
672	<i>40th International Conference on Machine Learning</i> ,		
673	volume 202 of <i>Proceedings of Machine Learning</i>	Hugo Touvron, Louis Martin, Kevin Stone, Peter Al-	725
	<i>Research</i> , pages 22631–22648. PMLR.	bert, Amjad Almahairi, Yasmine Babaei, Nikolay	726
674		Bashlykov, Soumya Batra, Prajjwal Bhargava, Shruti	727
675	Keming Lu, Hongyi Yuan, Zheng Yuan, Runji Lin, Jun-	Bhosale, et al. 2023. Llama 2: Open founda-	728
676	yang Lin, Chuanqi Tan, Chang Zhou, and Jingren	tion and fine-tuned chat models. <i>arXiv preprint</i>	729
677	Zhou. 2024. <i>#instag: Instruction tagging for analyz-</i>	<i>arXiv:2307.09288</i> .	730
678	<i>ing supervised fine-tuning of large language models</i> .		
679	In <i>The Twelfth International Conference on Learning</i>	Fanqi Wan, Xinting Huang, Tao Yang, Xiaojun Quan,	731
	<i>Representations</i> .	Wei Bi, and Shuming Shi. 2023. <i>Explore-instruct:</i>	732
680		<i>Enhancing domain-specific instruction coverage</i>	733
681	OpenAI. 2022. <i>Chatgpt: Optimizing language models</i>	<i>through active exploration</i> . In <i>Proceedings of the</i>	734
	<i>for dialogue</i> . <i>OpenAI Blog</i> .	<i>2023 Conference on Empirical Methods in Natural</i>	735
682		<i>Language Processing</i> , pages 9435–9454, Singapore.	736
683	Long Ouyang, Jeffrey Wu, Xu Jiang, Diogo Almeida,	Association for Computational Linguistics.	737
684	Carroll Wainwright, Pamela Mishkin, Chong Zhang,		
685	Sandhini Agarwal, Katarina Slama, Alex Gray, John	Yizhong Wang, Yeganeh Kordi, Swaroop Mishra, Alisa	738
686	Schulman, Jacob Hilton, Fraser Kelton, Luke Miller,	Liu, Noah A. Smith, Daniel Khashabi, and Hannaneh	739
687	Maddie Simens, Amanda Askell, Peter Welinder,	Hajishirzi. 2023a. <i>Self-instruct: Aligning language</i>	740
688	Paul Christiano, Jan Leike, and Ryan Lowe. 2022.	<i>models with self-generated instructions</i> . In <i>Proceed-</i>	741
689	<i>Training language models to follow instructions with</i>	<i>ings of the 61st Annual Meeting of the Association for</i>	742
690	<i>human feedback</i> . In <i>Advances in Neural Information</i>	<i>Computational Linguistics (Volume 1: Long Papers)</i> ,	743
	<i>Processing Systems</i> .	pages 13484–13508, Toronto, Canada. Association	744
691		for Computational Linguistics.	745
692	Joon Sung Park, Joseph O’Brien, Carrie Jun Cai, Mered-	Yizhong Wang, Swaroop Mishra, Pegah Alipoormo-	746
693	ith Ringel Morris, Percy Liang, and Michael S Bern-	labashi, Yeganeh Kordi, Amirreza Mirzaei, Atharva	747
694	stein. 2023. Generative agents: Interactive simulacra	Naik, Arjun Ashok, Arut Selvan Dhanasekaran,	748
695	of human behavior. In <i>Proceedings of the 36th An-</i>	Anjana Arunkumar, David Stap, Eshaan Pathak,	749
696	<i>annual ACM Symposium on User Interface Software</i>	Giannis Karamanolakis, Haizhi Lai, Ishan Puro-	750
	<i>and Technology</i> , pages 1–22.	hit, Ishani Mondal, Jacob Anderson, Kirby Kuznia,	751
		Krima Doshi, Kuntal Kumar Pal, Maitreya Patel,	752
		Mehrad Moradshahi, Mihir Parmar, Mirali Purohit,	753

754	Neeraj Varshney, Phani Rohitha Kaza, Pulkit Verma,	Luke Zettlemoyer, and Omer Levy. 2023. LIMA:	811
755	Ravsehaj Singh Puri, Rushang Karia, Savan Doshi,	Less is more for alignment. In <i>Thirty-seventh Con-</i>	812
756	Shailaja Keyur Sampat, Siddhartha Mishra, Sujan	<i>ference on Neural Information Processing Systems.</i>	813
757	Reddy A, Sumanta Patro, Tanay Dixit, and Xudong		
758	Shen. 2022. Super-NaturalInstructions: Generaliza-		
759	tion via declarative instructions on 1600+ NLP tasks.	A Related Work	814
760	In <i>Proceedings of the 2022 Conference on Empiri-</i>		
761	<i>cal Methods in Natural Language Processing</i> , pages	Instruction Fine-tuning for LLMs In recent	815
762	5085–5109, Abu Dhabi, United Arab Emirates. As-	years, instruction fine-tuning (IFT) has become a	816
763	sociation for Computational Linguistics.	prevalent approach for enhancing the applicability	817
764	Zhenhailong Wang, Shaoguang Mao, Wenshan Wu, Tao	of pre-trained language models (PLMs) and im-	818
765	Ge, Furu Wei, and Heng Ji. 2023b. Unleashing the	proving their generalization capabilities on unseen	819
766	emergent cognitive synergy in large language mod-	tasks (Chung et al., 2022; Wei et al., 2022).	820
767	els: A task-solving agent through multi-persona self-		
768	collaboration. <i>arXiv preprint arXiv:2307.05300.</i>	For instruction fine-tuning (IFT) on LLMs, at-	821
769	Jason Wei, Maarten Bosma, Vincent Zhao, Kelvin Guu,	tempts (Bach et al., 2022; Wang et al., 2022; Zhou	822
770	Adams Wei Yu, Brian Lester, Nan Du, Andrew M.	et al., 2023) have been made to construct IFT data	823
771	Dai, and Quoc V Le. 2022. Finetuned language mod-	with the help of human annotators, yet these meth-	824
772	els are zero-shot learners. In <i>International Confer-</i>	ods are time-consuming and labor-intensive. To	825
773	<i>ence on Learning Representations.</i>	tackle this issue, pipelines (Wang et al., 2023a;	826
774	Mengzhou Xia, Sadhika Malladi, Suchin Gururangan,	Honovich et al., 2023) are proposed to automat-	827
775	Sanjeev Arora, and Danqi Chen. 2024. LESS: Select-	ically generate data instances from seed tasks.	828
776	ing influential data for targeted instruction tuning. In	In addition to single-turn instruction following	829
777	<i>ICLR 2024 Workshop on Navigating and Addressing</i>	data (Taori et al., 2023; Peng et al., 2023), large-	830
778	<i>Data Problems for Foundation Models.</i>	scale multi-turn dialogues for IFT are also con-	831
779	Can Xu, Qingfeng Sun, Kai Zheng, Xiubo Geng,	structed to further enhance LLMs on chat scenar-	832
780	Pu Zhao, Jiazhan Feng, Chongyang Tao, Qingwei	ios (Chiang et al., 2023; Xu et al., 2023; Ding	833
781	Lin, and Daxin Jiang. 2024. WizardLM: Empow-	et al., 2023). Concurrently, a series of studies	834
782	ering large pre-trained language models to follow	show that the complexity, diversity, and quality	835
783	complex instructions. In <i>The Twelfth International</i>	of IFT data significantly influence model align-	836
784	<i>Conference on Learning Representations.</i>	ment. Concerning the complexity of instructions,	837
785	Canwen Xu, Daya Guo, Nan Duan, and Julian McAuley.	approaches (Wan et al., 2023; Zhao et al., 2024; Xu	838
786	2023. Baize: An open-source chat model with	et al., 2024) are designed to create large amounts of	839
787	parameter-efficient tuning on self-chat data. In <i>Pro-</i>	instruction data with different levels of complexity.	840
788	<i>ceedings of the 2023 Conference on Empirical Meth-</i>	Aware of both complexity and diversity of instruc-	841
789	<i>ods in Natural Language Processing</i> , pages 6268–	tions, Lu et al. (2024) tag data with a strong LLM	842
790	6278, Singapore. Association for Computational Lin-	and introduce a complexity-focus diverse sampling	843
791	guistics.	method for data selection. In the pursuit of data	844
792	Yingxiu Zhao, Bowen Yu, Binyuan Hui, Haiyang Yu,	with high-quality response, Chen et al. (2024) pro-	845
793	Minghao Li, Fei Huang, Nevin L. Zhang, and Yong-	pose a data selection strategy that automatically	846
794	bin Li. 2024. Tree-instruct: A preliminary study of	identifies and removes low-quality data. While Li	847
795	the intrinsic relationship between complexity and	et al. (2023b) select cherry samples from the origi-	848
796	alignment. In <i>Proceedings of the 2024 Joint Inter-</i>	nal dataset according to their instruction-following	849
797	<i>national Conference on Computational Linguistics,</i>	difficulty. More recently, Liu et al. (2024) investi-	850
798	<i>Language Resources and Evaluation (LREC-</i>	gate plenty of existing data selection methods and	851
799	<i>COLING 2024)</i> , pages 16776–16789, Torino, Italia.	propose approaches for enhanced data measure-	852
800	ELRA and ICCL.	ment and selection.	853
801	Lianmin Zheng, Wei-Lin Chiang, Ying Sheng, Siyuan	Diverging from prior work, we focus on how to	854
802	Zhuang, Zhanghao Wu, Yonghao Zhuang, Zi Lin,	further improve the quality of responses in IFT data.	855
803	Zhuohan Li, Dacheng Li, Eric Xing, Hao Zhang,	Through our proposed framework CoEvol, the po-	856
804	Joseph E. Gonzalez, and Ion Stoica. 2023. Judging	tential of LLM-based multi-agents is unleashed	857
805	LLM-as-a-judge with MT-bench and chatbot arena.	in collaboration to automatically edit responses,	858
806	In <i>Thirty-seventh Conference on Neural Information</i>	thereby generating high-quality data for fine-tuning	859
807	<i>Processing Systems Datasets and Benchmarks Track.</i>	superior LLMs.	860
808	Chunting Zhou, Pengfei Liu, Puxin Xu, Srini Iyer, Jiao		
809	Sun, Yuning Mao, Xuezhe Ma, Avia Efrat, Ping Yu,		
810	LILI YU, Susan Zhang, Gargi Ghosh, Mike Lewis,		

LLM-based Multi-agent Frameworks As the ability of LLMs to reason and follow instructions continues to emerge, wrapping LLMs with additional memories and planning schemes into autonomous agents is catching increasing attention from researchers. These agents are capable of communicating with natural language, memorizing their experiences, and conducting reflections on assigned tasks.

Previously, Generative Agents (Park et al., 2023) indicate that LLMs are effective in simulating believable human behavior when agents are interactive from perspectives like observation, planning, and reflection. Li et al. (2023a) focus on how communicative agents may collaborate autonomously to finish tasks. Qian et al. (2023) construct a virtual chat-powered company for software development based on multi-agents. Wang et al. (2023b) transform a single LLM into a cognitive synergist by engaging in multi-turn self-collaboration with multiple personas. These practices demonstrate that multi-agent frameworks built over LLMs can effectively solve collaborative tasks. Considering autonomous agents can behave both cooperatively and competitively, multi-agent debate (MAD) is also attracting researchers to explore. Du et al. (2023) find that the quality of responses can be improved through debating over multiple rounds, while (Subramaniam et al., 2024) propose an approach to generate IFT data based on this framework. Liang et al. (2023) adopt MAD to address the Degeneration-of-Thought issue of reflection-style methods. ChatEval (Chan et al., 2024) offers an automatic human-mimicking evaluation process on NLG tasks based on multi-agents.

In this paper, we benefit from the diversity of thoughts introduced by MAD and design a two-stage strategy within our proposed multi-agent cooperation framework CoEvol.

B Prompts of Multi-Agents

In this paper, we allocate five agents within the proposed pipeline to enhance the quality of responses. In this process, each agent is equipped with a role-play and task prompt to guide their generation. For models that allow the specification of system prompts, such as ChatGPT, we utilize the role-play prompts as their system prompts. Conversely, for models that do not support system prompts, such as Mixtral, we incorporate the role-play prompt before the task prompt and provide instructions as a

unified input. We present these prompts in Table 5, Table 6, and Table 7 for reference.

C Details of Data Evolution

To guarantee the stability of the proposed pipeline, we set several hyperparameters to control the framework. In our experiments, we set the maximum number of iterations for data evolution to 3. For LLM-based agents, the maximum generated tokens are restricted to 1000, the temperature is maintained at 0 for reproducibility, and the top_p value is set to 1.0. Regarding the data evolution on multi-turn conversations, the expansion of conversation rounds leads to a cumulative increase in historical information within the instructions targeted for optimization. To mitigate resource consumption, we only retain the most recent 3 rounds of conversation for data refinement in the present turn.

D Details of Model Training

In our experiments, we fine-tune two pre-trained language models on different IFT data. To facilitate model training, we employ DeepSpeed Zero-Stage 2 (Ren et al., 2021) in model fine-tuning. Specifically, we follow (Chen et al., 2024) to train LLaMA2-7B with a batch size of 512 over 3 epochs. The learning rate is set to $2e-5$, and a cosine warmup scheduler with a warm ratio of 0.1 is employed. During fine-tuning, we utilize the LLaMA2-style template to concatenate queries and responses within multi-turn conversations. The maximum input length for the model is set to 4096. Regarding Mistral-7B, we follow (Liu et al., 2024) to train the model with a batch size of 512 over 6 epochs. The learning rate is set to $2e-5$, and a cosine warmup scheduler with a warm ratio of 0.1 is employed. During fine-tuning, we utilize the Mistral-style template to concatenate queries and responses within multi-turn conversations. The maximum input length for the model is set to 8192.

E Examples of Data Evolution

In Table 8 and 9, we show detailed examples of data evolution using CoEvol under different framework settings according to Section 4.1, including the original sample, evolving directions in the form of suggestions, and the evolved responses.

Table 5: Prompts used for two agent debaters.

<i>Prompt for Agent Positive Debater</i>	<i>Prompt for Agent Critical Debater</i>
<p>Role-Play Prompt You are an optimistic person who embodies a mindset that looks for the best in every situation, maintains a positive attitude, and embraces challenges as opportunities for growth and success.</p>	<p>Role-Play Prompt You are a critical person who tends to view things through critical thinking and provide feedback for improvement or identify areas of concern.</p>
<p>Task Assignment Prompt (First Round) {sample} In your opinion, the above response accurately answers the instruction and the input. Please state reasons why the response is accurate if it is used for supervised fine-tuning.</p>	<p>Task Assignment Prompt (First Round) {sample} In your opinion, the above response does not accurately answer the instruction and the input. Please offer suggestions on how to improve the response if it is used for supervised fine-tuning.</p>
<p>Task Assignment Prompt (Second Round) ### Review from others: {crt_pred}</p>	<p>Task Assignment Prompt (Second Round) ### Review from others: {pos_pred}</p>
<p>Above is another review from others, please evaluate the plausibility of each point according to the given instruction and input.</p>	<p>Above is another review from others, please evaluate the plausibility of each point according to the given instruction and input.</p>

Table 6: Prompts used for agent advisor and agent editor.

<i>Prompt for Agent Advisor</i>	<i>Prompt for Agent Editor</i>
<p>Role-Play Prompt You are an experienced advisor who possesses a high level of expertise in summarizing and giving advice.</p> <p>Task Assignment Prompt Below is an instruction that describes a task, paired with an input that provides further context. {sample}</p> <p>The following is a discussion about the given request and response by two reviewers.</p> <p>### Reviewer 1: {pos_pred}</p> <p>### Reviewer 2: {crt_pred}</p> <p>### Reviewer 1: {pos_free}</p> <p>### Reviewer 2: {crt_free}</p> <p>Extract and summarize credible ideas from the above dialogue and rewrite them into no more than 3 writing suggestions for improving the given response. Directly output these suggestions in separate lines without any foreword or explanation.</p>	<p>Role-Play Prompt You are a professional editor who possesses a high level of expertise in refining and improving writing content.</p> <p>Task Assignment Prompt ### Writing Suggestions: {adv_sugg}</p> <p>### Previous Response: {pre_resp}</p> <p>Below is an instruction that describes a task, paired with an input that provides further context. {sample}</p> <p>Referring to the above writing suggestions (MUST ignore suggestions beyond your capabilities), modify the previous response and make sure that it appropriately completes the request. {sample_request}</p> <p>### Response:</p>

Table 7: Prompts used for the agent judge.

<i>Prompt for Agent Judge</i>	<i>Prompt for Agent Judge (In Reverse Order)</i>
<p>Role-Play Prompt You are a helpful and precise assistant for checking the quality of the response.</p> <p>Task Assignment Prompt Below is an instruction that describes a task, paired with an input that provides further context. {sample_request}</p> <p>[The Start of Assistant 1’s Response] {pre_resp} [The End of Assistant 1’s Response]</p> <p>[The Start of Assistant 2’s Response] {new_resp} [The End of Assistant 2’s Response]</p> <p>[System] We would like to request your comparison of the performance of two AI assistants in response to the user request displayed above. Please compare the helpfulness, relevance, accuracy, and level of detail of their responses. Please first output a single line containing a name indicating whose response is better, <assistant 1> or <assistant 2> or <equal>. In the subsequent line, please provide a comprehensive explanation of your comparison, avoiding any potential bias and ensuring that the order in which the responses were presented does not affect your judgment.</p>	<p>Role-Play Prompt You are a helpful and precise assistant for checking the quality of the response.</p> <p>Task Assignment Prompt Below is an instruction that describes a task, paired with an input that provides further context. {sample_request}</p> <p>[The Start of Assistant 1’s Response] {new_resp} [The End of Assistant 1’s Response]</p> <p>[The Start of Assistant 2’s Response] {pre_resp} [The End of Assistant 2’s Response]</p> <p>[System] We would like to request your comparison of the performance of two AI assistants in response to the user request displayed above. Please compare the helpfulness, relevance, accuracy, and level of detail of their responses. Please first output a single line containing a name indicating whose response is better, <assistant 1> or <assistant 2> or <equal>. In the subsequent line, please provide a comprehensive explanation of your comparison, avoiding any potential bias and ensuring that the order in which the responses were presented does not affect your judgment.</p>

Table 8: Examples of data evolution using CoEvol under different framework settings (Section 4.1). For an original sample from Alpaca dataset, we show suggestions and refined responses given by ablated frameworks.

Original Sample	
<p><i>## Instruction</i> How might someone use machine learning to identify fake news?</p>	<p><i>## Response</i> Machine learning could be used to identify fake news by analyzing the content of articles and detecting patterns of deception. The model could take into account factors such as sentence structure, language, and source to identify potentially false information. Additionally, it could also use natural language processing to automatically detect signs of deception in the text.</p>
Edit	
<p><i>## Suggestions</i> (None)</p>	<p><i>## Response</i> One way to use machine learning to identify fake news is by training a model on a large dataset of both real and fake news articles. The model can then analyze various features of the articles, such as the language used, the sources cited, and the tone of the writing, to identify patterns that are indicative of fake news. By continuously updating and refining the model based on new data, it can become increasingly accurate in distinguishing between real and fake news articles. Additionally, natural language processing techniques can be employed to analyze the content of the articles and detect any misleading or false information. This approach can help in automating the process of identifying fake news and flagging potentially deceptive content for further review.</p>
Advise (w/o resp) + Edit	
<p><i>## Suggestions</i></p> <ol style="list-style-type: none"> 1. Start by researching and understanding the common characteristics and patterns of fake news, such as sensationalism, misleading headlines, and biased sources. 2. Consider using natural language processing techniques to analyze the language and sentiment of news articles, as well as to detect any inconsistencies or contradictions within the content. 3. Utilize supervised learning algorithms to train a model on a labeled dataset of both real and fake news articles, and then use this model to classify new articles as either real or fake based on their features. 	<p><i>## Response</i> To identify fake news using machine learning, one approach is to start by researching and understanding the common characteristics and patterns of fake news, such as sensationalism, misleading headlines, and biased sources. Then, consider using natural language processing techniques to analyze the language and sentiment of news articles, as well as to detect any inconsistencies or contradictions within the content. Additionally, utilizing supervised learning algorithms to train a model on a labeled dataset of both real and fake news articles can be effective. This model can then be used to classify new articles as either real or fake based on their features.</p>

Table 9: Examples of data evolution using CoEvol under different framework settings (*continued*).

Advise + Edit	
<p><i>## Suggestions</i></p> <ol style="list-style-type: none"> 1. Consider providing specific examples of machine learning algorithms or techniques that could be used for identifying fake news, such as sentiment analysis or topic modeling. 2. Expand on the potential challenges or limitations of using machine learning to identify fake news, such as the need for large, diverse datasets and the potential for bias in the training data. 3. Include information on the importance of fact-checking and human oversight in conjunction with machine learning for more accurate identification of fake news. 	<p><i>## Response</i></p> <p>Machine learning can be utilized to identify fake news through various algorithms and techniques. For instance, sentiment analysis can be employed to gauge the emotional tone of an article, helping to detect potential bias or manipulation. Additionally, topic modeling can be used to categorize and analyze the content of news articles, enabling the identification of patterns or inconsistencies that may indicate false information. However, it is important to acknowledge the potential challenges and limitations of using machine learning for this purpose. One such challenge is the need for large and diverse datasets to train the model effectively, as fake news can take many different forms and may be context-dependent. Moreover, there is a risk of bias in the training data, which could lead to inaccurate or skewed results.</p> <p>It is crucial to emphasize that while machine learning can be a valuable tool in identifying fake news, it should be complemented by human oversight and fact-checking. Human judgment and critical thinking are essential for verifying the accuracy of information, and they can help mitigate the limitations and potential biases of machine learning algorithms.</p>
Debate + Advise + Edit	
<p><i>## Suggestions</i></p> <ol style="list-style-type: none"> 1. Include specific details and examples of machine learning algorithms that could be used for identifying fake news, such as supervised learning, unsupervised learning, or deep learning. 2. Discuss specific features or indicators that could be used to train the model, such as linguistic patterns, sentiment analysis, or credibility of sources, to provide a more comprehensive understanding of the factors contributing to the effectiveness of machine learning in identifying fake news. 3. Incorporate examples of successful applications of machine learning in identifying fake news to illustrate the practical implementation and impact of machine learning in this domain. Additionally, address potential challenges or limitations in using machine learning for this purpose, such as the need for large and diverse training datasets and the potential for bias in the algorithms. 	<p><i>## Response</i></p> <p>Machine learning can be utilized to identify fake news by employing various algorithms such as supervised learning, unsupervised learning, or deep learning. For instance, supervised learning algorithms can be trained on labeled datasets of fake and real news articles to classify new articles. Unsupervised learning algorithms can identify patterns and anomalies in the data, while deep learning algorithms can process large amounts of unstructured data to detect fake news.</p> <p>To train the model, specific features and indicators can be used, such as linguistic patterns, sentiment analysis, and credibility of sources. Linguistic patterns can include the use of sensational language or inconsistent information within the article. Sentiment analysis can assess the emotional tone of the content, while evaluating the credibility of sources can involve analyzing the reputation and history of the publishing platform.</p> <p>Successful applications of machine learning in identifying fake news include platforms that use natural language processing to analyze news articles and social media posts to detect misinformation. However, challenges in using machine learning for this purpose include the need for large and diverse training datasets to ensure the model’s accuracy and the potential for bias in the algorithms, which may inadvertently label legitimate news as fake based on certain patterns or sources.</p>