

# Robustness in Large Language Models: A Survey of Mitigation Strategies and Evaluation Metrics

Anonymous authors

Paper under double-blind review

## Abstract

Large Language Models (LLMs) have emerged as a promising cornerstone for the development of natural language processing (NLP) and artificial intelligence (AI). However, ensuring the robustness of LLMs remains a critical challenge. To address these challenges and advance the field, this survey provides a comprehensive overview of current studies in this area. First, we systematically examine the nature of robustness in LLMs, including its conceptual foundations, the importance of consistent performance across diverse inputs, and the implications of failure modes in real-world applications. Next, we analyze the sources of non-robustness, categorizing intrinsic model limitations, data-driven vulnerabilities, and external adversarial factors that compromise reliability. Following this, we review state-of-the-art mitigation strategies, and then we discuss widely adopted benchmarks, emerging metrics, and persistent gaps in assessing real-world reliability. Finally, we synthesize findings from existing surveys and interdisciplinary studies to highlight trends, unresolved issues, and pathways for future research.

## 1 Introduction

Large Language Models (LLMs), mainly characterized by their vast number of parameters, have emerged as a promising cornerstone for the development of natural language processing (NLP) and artificial intelligence (AI) [Zhang et al. \(2023\)](#). These models have demonstrated remarkable capabilities across a wide range of NLP applications. Foundation models like GPT-4 [OpenAI et al. \(2024\)](#), GPT-3 [Brown et al. \(2020\)](#), Qwen 2.5-VL [Bai et al. \(2025a\)](#), Deepseek-V3 [DeepSeek-AI et al. \(2025\)](#), Meta (LLaMA-3, LLaMA-2 [Touvron et al. \(2023b\)](#), LLaMA-1 [Touvron et al. \(2023a\)](#)), Gemini [DeepMind \(2023\)](#) are pre-trained on massive datasets and serve as the backbone for various AI tasks, from text generation to multimodal understanding—the ability to process and interpret multiple types of data, such as text and images. Their extensive factual knowledge has significantly improved their effectiveness in information retrieval, enabling them to provide more accurate and contextually relevant responses [AlKhamissi et al. \(2022\)](#); [Petroni et al. \(2019\)](#). As a result, these models achieve high accuracy on benchmark evaluations, demonstrating their strong predictive capabilities across diverse tasks [OpenAI et al. \(2024\)](#); [Bai et al. \(2025a\)](#); [DeepSeek-AI et al. \(2025\)](#); [Grattafiori et al. \(2024\)](#). However, accuracy alone is insufficient to ensure reliability in real-world applications.

In recent years, despite improvements in the accuracy of deep neural network models, researchers have found that they are easy to fool by applying a specific imperceptible perturbation [Szegedy et al. \(2014\)](#). A deep learning model’s accuracy describes how accurately the model predicts sample points over a distribution. If a model cannot predict accurately, then no matter what properties this model holds, it would be meaningless. Although accuracy is the most fundamental metric in the evaluation and is essential to validate the performance of an LLM before it is released, it is equally important to test its robustness when deploying for the development of reliable AI systems. Robustness, a crucial aspect of deep learning models, describes their ability to maintain stable predictions when faced with specific perturbations or variations in the input data [Liu et al. \(2024b\)](#). Despite recent advancements, ensuring the robustness of LLMs remains a critical challenge. LLMs may encounter unpredictable variations in language, shifts in data (changes in the data patterns that a model encounters, which may affect its performance), and adversarial inputs that can affect their performance. In practical applications, these models often face noisy, unstructured text, breaking the




Figure 1: The outline of the survey on robustness of large language models.

assumption that input data will always be clean and well-formed. Additionally, a lack of robustness may result in unintended biases, incorrect predictions, or overreliance on spurious correlations (misleading correlations in data that a model may rely on incorrectly), raising concerns about their reliability in high-stakes environments such as healthcare Wan et al. (2024b;a); He et al. (2025), law Lee (2023); Cui et al. (2024); Yue et al. (2023); Bhambhoria et al. (2024); Bai et al. (2021b), complex reasoning Yang et al. (2023), code generation Sun et al. (2024b); Lin et al. (2024a); Mishra et al. (2024); Hassid et al. (2024), and finance Lee et al. (2025); Zhao et al. (2024a); Li et al. (2024c); Wu et al. (2023). Because of this, a thorough and exacting assessment of LLM robustness that goes beyond conventional accuracy criteria is required.

However, advancing research on the robustness of LLMs also faces significant challenges. First, the absence of standardized definitions and categorizations of robustness complicates cross-study comparisons, as research efforts often differ in how they frame their scope and components. Second, pinpointing the root causes of non-robustness, such as data biases, unstable training dynamics, architectural limitations, or inference inefficiencies, requires disentangling complex interactions across these factors. Third, while numerous mitigation

strategies exist, their effectiveness often depends on addressing specific vulnerabilities, making it difficult to generalize solutions. Fourth, evaluating robustness remains fragmented, with no unified metrics or benchmarks to holistically assess performance under diverse real-world conditions like noisy inputs or adversarial attacks. Finally, existing literature on LLM robustness (Zhao et al., 2025; Gu et al., 2025; He et al., 2025; Liu et al., 2024b; Mehrabi et al., 2022; Wang et al., 2025; Lu et al., 2024; Weng, 2023; Yang et al., 2024a) is scattered across domains, limiting cross-pollination of insights and hindering the development of cohesive solutions.

To address these challenges and advance the field, this survey provides a comprehensive overview of current studies in this area. Figure 1 shows the outline of this survey. We begin by clarifying definitions and categorizing the dimensions of robustness to establish a shared framework for analysis (§2). Next, we systematically identify and classify the primary sources of non-robustness, including data quality issues, training instabilities, architectural constraints, and inference-time vulnerabilities (§3). We then review state-of-the-art mitigation strategies, mapping each approach to the specific weaknesses it targets (§4). Following this, we analyze evaluation methodologies, discussing widely adopted benchmarks, emerging metrics, and persistent gaps in assessing real-world reliability (§5). Finally, we synthesize findings from existing surveys and interdisciplinary studies to highlight trends, unresolved issues, and pathways for future research (§7). By unifying these perspectives, we aim to foster collaboration and accelerate progress toward building more reliable, resilient LLMs.

## 2 Robustness in LLMs

In the context of LLMs from various literatures, *robustness* refers to their ability to perform reliably and safely despite challenges like input variations, unexpected data, or adversarial attacks. It is frequently discussed as a critical component within the broader framework of AI Trustworthiness. Trustworthy AI systems are expected to be reliable, safe, fair, transparent, accountable, and robust. Robustness underpins several of these qualities; for instance, a model prone to adversarial manipulation (lack of robustness) cannot be considered safe or reliable (Wang et al., 2023; Aljohani et al., 2025). Similarly, a model that hallucinates or provides inconsistent answers under slightly different prompts lacks reliability, another facet closely tied to robustness (Zhou et al., 2024b). Research into the vulnerabilities of machine learning models, including LLMs, has often focused on adversarial robustness - the model’s resilience against inputs intentionally crafted to cause misclassification or undesired behaviour (Zhao et al., 2025). This survey approaches robustness comprehensively, considering LLMs as integrated systems rather than isolated components.

### 2.1 What is Robustness in LLMs

The concept of robustness for LLMs is multifaceted, and various studies approach its definition from different angles, reflecting the diverse ways models can fail or exhibit instability. Formally, robustness can be conceptualized as the degree to which a model’s output  $f(x)$  remains stable or correct when the input  $x$  is subjected to some form of perturbation  $\delta$  or drawn from a distribution  $\mathcal{D}_{test}$  different from the training distribution  $\mathcal{D}_{train}$ . The specific nature of the perturbation or distribution shift defines the dimension of robustness being considered. This concept is vital for setting research goals and evaluation standards, as robustness directly impacts whether users can trust these models in real-world applications. Synthesizing across the literature, several core themes emerge:

- **Stability under Disruption:** Robustness is fundamentally about the stability of LLM performance and behaviour when faced with various forms of disruption, including unseen scenarios, different types of attacks, and noise in the input (Guo et al., 2023). It implies predictability even when conditions deviate from the ideal.
- **Performance Maintenance under Distribution Shifts** (Du et al., 2022): Robustness entails maintaining performance levels when the distribution of deployment data differs from the training data (OOD generalization). This is crucial as real-world data rarely perfectly matches training sets.

- **Resilience to Input Variations:** A robust LLM should maintain consistent outputs despite variations in the input that preserve the core meaning or intent. This includes resilience to natural language variations like morphological changes, typos, paraphrasing, and syntactic restructuring (Singh et al., 2024; Mahaut et al., 2024; Sarker et al., 2024). It also encompasses stability when confronted with unforeseen or malformed prompts (Ailem et al., 2024).
- **Consistency and Reliability of Outputs:** Robustness requires the model to consistently generate outputs that are accurate, reliable, and unbiased across diverse scenarios (Lad et al., 2024; Aljohani et al., 2025). This involves minimizing errors, factual inaccuracies (hallucinations), and harmful biases, even under challenging conditions.
- **Adherence to Intended Behaviour:** A robust model should adhere to its intended function and safety constraints. This includes following legitimate instructions correctly while resisting malicious manipulations like prompt injection attacks (Li et al., 2024d) or jailbreaks designed to elicit harmful content.

Drawing these threads together, a working definition for this survey is:

**LLM’s robustness** refers to the model’s ability to maintain consistent performance, reliability, and adherence to intended behaviour (including accuracy, factuality, safety, and fairness) despite variations in inputs, contexts, or underlying data distributions. This encompasses resilience to natural noise, semantic paraphrasing, distribution shifts, incomplete information, reasoning perturbations, instruction variations, and adversarial manipulations.

## 2.2 Key Dimensions of Robustness

LLM robustness is not a monolithic property but rather a collection of related capabilities. To better understand and address the challenge, it is useful to delineate the key facets of LLM robustness, recognizing that these categories often overlap and interact. Figure 2 provides an overview of this overlapping nature, illustrating how progress in one dimension can amplify or undermine robustness in others due to their inherent interdependencies

1. **Resilience to Adversarial Attacks (Input Perturbations):** This dimension concerns the model’s ability to withstand inputs that have been intentionally manipulated by an adversary to cause specific failures (Chacko et al., 2024). These perturbations are often small and designed to be imperceptible or semantically plausible to humans but exploit model vulnerabilities.
  - **Appearance:** Misclassification in tasks like sentiment analysis (Yang et al., 2024d), generation of harmful, toxic, or biased content, bypassing safety alignments (jailbreaking) (Tao et al., 2024), or general performance degradation.
  - **Attack Types:** Attacks on LLMs can target varying levels of input granularity: character-level perturbations (e.g., HotFlip), word-level modifications (e.g., synonym swapping), or sentence-level alterations (e.g., inserting distracting phrases) (Yang et al., 2024d). Beyond these, typographical errors have been used as adversarial tools as in Gan et al. (2024). Attacks are further categorized by threat model - white-box attacks assume access to model internals (e.g., parameters or logits), whereas black-box attacks interact solely via inputs and outputs. Prominent techniques include the Greedy Coordinate Gradient (GCG), AutoDAN, and PAIR (Xhonneux et al., 2024), with some methods focusing on perturbing continuous embeddings rather than discrete tokens. Multimodal LLMs (MLLMs) also face compounded risks, as adversaries exploit vulnerabilities both within individual modalities (e.g., image or text) and across modality interactions (Jiang et al., 2025).
  - **Cause:** Exploitation of model vulnerabilities, including reliance on spurious correlations and brittle statistical dependencies.
2. **Out-of-Distribution (OOD) Generalization:** This refers to the model’s ability to maintain performance when evaluated on data drawn from a distribution different from the one used for training.




Figure 2: Illustration of challenges in achieving comprehensive LLM robustness due to interconnected and potentially conflicting dimensions.

Real-world data distributions often shift over time or across contexts, making OOD generalization crucial for practical deployment.

- **Appearance**: Significant performance drop occurs in LLMs when evaluated on out-of-distribution (OOD) test sets compared to in-distribution (ID) benchmarks (Du et al., 2022). This degradation arises from two primary failure modes: covariate shift (divergence in input features) or concept shift (changes in input-output relationships) (Yuan et al., 2023; Nagarajan et al., 2024). Specific OOD challenges include handling unfamiliar knowledge domains (OOD Knowledge), stylistic variations (OOD Style), or multilingual/code-mixed inputs (OOD Language).
  - **Cause**: Model’s tendency to exploit spurious correlations or training data biases rather than learning generalizable invariant features.
3. **Sensitivity to Prompt Variations**: This dimension measures how stable the model’s output is when the input prompt or instruction is rephrased or slightly altered while preserving the original semantic meaning (Yang et al., 2024d). Humans are generally resilient to such variations, but LLMs can be surprisingly sensitive (Agrawal et al., 2025).
    - **Appearance**: Drastic changes in output quality, correctness, or consistency even with minor prompt modifications like paraphrasing, synonym replacement, word insertion/deletion, or re-ordering of elements (e.g., multiple-choice options).
    - **Cause**: Overfitting to specific instruction formats seen during training or reliance on superficial cues in the prompt.
  4. **Handling Noisy or Corrupted Input**: This concerns the model’s resilience to unforeseen mistakes or flaws commonly found in real-world user inputs.

- Appearance: LLMs often struggle to process inputs containing textual noise such as typos, misspellings, grammatical errors, or irregular punctuation. This includes errors introduced by automated processes (e.g., voice-to-text transcription flaws or OCR mistakes). Sensitivity extends to noise within training or fine-tuning data itself, which can degrade robustness by reinforcing brittle input-output mappings (Luo et al., 2024).
  - Cause: Reinforcement of brittle input-output mappings from noisy training/fine-tuning data or the context-aware nature of LLMs’ design, making them susceptible to distraction by irrelevant information.
5. Consistency and Reliability of Outputs: This focuses on the dependability of the model’s generations, ensuring outputs are stable for similar inputs and free from self-contradiction or factual inaccuracies (hallucinations) (Zhou et al., 2024b).
- Appearance: Generating different answers to semantically identical questions posed slightly differently (Yang et al., 2025b). Further, producing factually incorrect or nonsensical information (hallucination), which can be exacerbated by robustness issues or outputting contradictory statements within the same response or across closely related prompts.
  - Cause: Lack of stable internal representation or deterministic reasoning or over-reliance on statistical fluency at the expense of global factual accuracy or logical soundness.
6. Fairness under Stress: The ability to maintain fairness and avoid amplifying societal biases (e.g., related to gender, race, or other protected attributes) when presented with adversarial prompts or contexts specifically designed to induce biased behaviour (Jung et al., 2025).
- Appearance: Performance disparities across diverse socio-demographic and geographic contexts. For instance, LLMs have been observed to consistently outperform on U.S. datasets compared to Chilean datasets, indicating a geographical bias in their performance. Furthermore, the influence of protected attributes on prediction accuracy varies by region in the U.S., political identity and race significantly affect accuracy, whereas in Chile, gender, education, and religious affiliation play more pronounced roles.
  - Cause: Flaws in training data leading to representational imbalance and skewed learned distributions.
7. Task-Specific Robustness: Robustness considerations tailored to the demands of specific downstream tasks, such as maintaining logical coherence in reasoning tasks or generating functionally correct and secure code (Bao et al., 2025; Li et al., 2025d).
- Appearance: Significant challenges in logical reasoning, failure in complex logical problems (e.g., low accuracy on FOLIO (Han et al., 2024)), violation of logical consistency. Furthermore, the difficulties highlighted in solver-aided approaches, such as information loss, translation errors, and limited translation capacities, lead to a significant “symbolic gap”.
  - Cause: Inherent limitations in formal reasoning and symbolic manipulation, and challenges in robustly bridging natural language and formal logic.

These dimensions are often interconnected. For example, a model susceptible to spurious correlations (an OOD issue) might also be more vulnerable to adversarial attacks that exploit those correlations, or more sensitive to prompt variations that alter the presence of those spurious cues. Further, inputs that are OOD may push a model beyond its knowledge boundaries, thereby increasing the likelihood of hallucination. Similarly, improving robustness against noise might also enhance consistency. However, it is also conceivable that improving one dimension might negatively impact another. For instance, alignment techniques aimed at improving fairness (a form of robustness) might inadvertently reduce OOD generalization (the “alignment tax”) (Lin et al., 2024b). Figure 3 highlights these dependencies and trade-offs, emphasizing the need for balanced strategies to advance robustness across interdependent dimensions.





Figure 3: A conceptual visualization of the interdependent dimensions critical to LLM robustness, highlighting the synergies and tensions between improving OOD generalization, noise resilience, output consistency, and fairness. For instance, enhancing consistency (e.g., reducing sensitivity to prompt variations) lowers vulnerability to adversarial attacks, while improving OOD generalization reduces hallucination risks and may indirectly reinforce consistency. However, over-optimizing one dimension (e.g., rigidly enforcing consistency) could constrain adaptability to novel inputs. This visualization demonstrates how these factors interconnect, highlighting the challenge of achieving well-balanced, comprehensive robustness across all dimensions.

### 3 Sources of Robustness

Understanding why LLMs lack robustness requires examining the contributing factors across different stages of their lifecycle, from data collection to training and deployment. These issues can be broadly categorized as stemming from the data, the model itself, or the learning process. Table 1 provides an overview of these sources. These failures in robustness can originate mainly from:

- **Data-Related Sources:** Problems inherent in the vast datasets used for pre-training and fine-tuning, including biases, noise, and contamination.
- **Model-Related Sources:** Limitations stemming from the model’s architecture, parameterization, or emergent properties like sensitivity to input formatting.
- **Training/Learning-Related Sources:** Aspects of the optimization process, learning objectives, and the dynamics of how models acquire knowledge and capabilities.
- **Inference-Related:**

#### 3.1 Data Related Sources

The massive datasets used to train LLMs are a primary source of their capabilities but also a significant source of their vulnerabilities. Several primary causes contribute to the lack of robustness observed in LLMs are:

##### 3.1.1 Spurious Correlations

This is arguably one of the most significant causes of robustness failures, particularly concerning OOD generalization (Du et al., 2022). Instead of learning the intended, often complex, causal relationships or concepts, models learn to rely on simpler, superficial patterns (shortcuts) that happen to correlate with the correct output in the training data but do not hold universally. When these spurious correlations are absent or altered in new inputs (e.g., OOD data, perturbed examples), the model’s performance collapses. Examples include:

- Lexical Bias: Relying on specific words (e.g., negation words like ‘no’, ‘never’ strongly predicting ‘contradiction’ in Natural Language Inference (NLI) tasks).
- Overlap Bias: Exploiting word overlap between premise and hypothesis in NLI.
- Positional Bias: Predicting answers based on their typical position in the training context (e.g., always in the k-th sentence for QA).
- Style Bias: Associating certain writing styles with specific labels.
- Heuristics in Reasoning: Using memorised rules-of-thumb or simple numerical patterns instead of robust algorithms (Li et al., 2024b) for tasks like arithmetic.

### 3.1.2 Dataset Biases and Anomalies

LLMs often inherit shortcomings from systematic biases and unintended statistical cues in their training data. Training data inevitably reflects societal biases present in the source text (often large web-scraped corpora). LLMs can learn and amplify these biases related to gender, race, culture, religion, etc., leading to unfair, discriminatory, or non-robust outputs when prompted about sensitive topics. Evaluating fairness under prompts designed to induce bias reveals these vulnerabilities (Jung et al., 2025). For instance, crowd-sourced datasets, used widely for fine-tuning and evaluation, frequently contain superficial annotation patterns, where human annotators unintentionally introduce simplistic labeling strategies that models exploit as shortcuts. These patterns create misleading statistical associations (e.g., keyword matching) rather than reflecting genuine task understanding. Even benchmark design can amplify biases, as models may overfit to variations in test data construction rather than solving tasks as intended (Ailem et al., 2024). Together, these data biases and methodological flaws perpetuate robustness failures across training, evaluation, and deployment.

### 3.1.3 Data Poisoning/Backdoors

Adversaries can intentionally inject malicious examples into the training data (or fine-tuning data) to create hidden backdoors. These backdoors can be triggered by specific inputs at inference time to cause targeted misbehaviour or compromise model safety, often without degrading general performance noticeably, specifically in fine-tuned models (Aljohani et al., 2025).

### 3.1.4 Sensitivity to Input Variations

LLMs exhibit high sensitivity to the precise form of the input, even when the underlying semantics remain unchanged:

- Prompt Sensitivity: Minor changes in wording, punctuation, or formatting of prompts can lead to significantly different and sometimes incorrect outputs. Models might solve a task correctly with one phrasing but fail with equivalent rewordings (Mahaut et al., 2024). Even minor typos can degrade the performance (Liu et al., 2024b).
- Instruction Sensitivity: Performance can vary drastically based on how instructions are phrased or structured within the prompt. Counterintuitively, models specifically fine-tuned for a domain might become more sensitive to instruction variations than general-purpose models (Yan et al., 2024a; Aljohani et al., 2025).
- Noise Sensitivity: Models struggle with naturally occurring noise (spelling/grammar errors, OCR/ASR anomalies) (Singh et al., 2024) and can be easily distracted by irrelevant information or deliberately injected noise (Zhou et al., 2024d).



Table 1: Sources of non-robustness in LLMs.

Specific Cause	Root Cause	Description
<b><u>Data Related</u></b>		
Shortcut Learning / Spurious Correlations	Data collection/annotation issues, mirrored cognitive biases, simplicity bias in ERM learning.	Model exploits shallow statistical cues instead of robust features.
Dataset Biases	Mirrored cognitive biases in web-scale data.	Model learns and amplifies societal biases from data.
Lack of Diversity	Limitations in data collection scope and resources.	Insufficient variety in training data limits generalization.
Data Poisoning	Adversarial intent during data contribution/curation.	Malicious data injection creates vulnerabilities.
<b><u>Training-Related</u></b>		
Optimization Objectives (ERM)	Incentive structure of minimizing average loss on potentially biased IID data.	Standard training encourages learning shortcuts.
Alignment Tax	Objective mismatch between alignment and pre-training, representation shifts during RLHF, KL penalty constraints.	Alignment degrades pre-trained capabilities/robustness.
RLHF Impact (Biases, Reward Hacking)	Imperfect/biased reward models, inconsistent/limited human feedback, optimization exploiting RM proxies.	Alignment process introduces flaws or fails to fully align.
Fine-tuning Limitations (Overfitting, Noise Sensitivity)	Overfitting to specific fine-tuning data characteristics, amplification of noise in smaller datasets.	Fine-tuning reduces OOD robustness or is brittle to noise.
<b><u>Architectural</u></b>		
Transformer Vulnerabilities	Specific mechanisms of attention computation, information flow across layers.	Inherent properties (e.g., attention) can be exploited.
Vulnerabilities to Modifications (Quantization, Pruning)	Information bottlenecks, disruption of learned weights/mechanisms, cascading errors.	Efficiency optimizations degrade robustness.
<b><u>Inference-Related</u></b>		
Decoding Strategies	Exploration vs. exploitation trade-off, amplification of probability uncertainties.	Choice of decoding impacts consistency and robustness.
RAG Issues	Reliance on retriever quality, handling retrieved context.	Imperfect retrieval, difficulty integrating multiple/noisy sources.

### 3.2 Training Related Sources

Standard pre-training objectives like next-token prediction and fine-tuning objectives based on Empirical Risk Minimization (ERM) primarily optimize for average performance on the training distribution. These objectives may not explicitly encourage robustness to distribution shifts or perturbations. Furthermore, the dynamics of gradient-based optimization might lead models to latch onto simple, non-robust features early in training. The process of training and aligning LLMs can introduce such vulnerabilities:

### 3.2.1 Optimization Objectives (ERM)

The standard training objective, Empirical Risk Minimization (ERM), aims to minimize average loss on the training data. On large, biased datasets, instead of spending capacity in learning more complicated, generalizable features, ERM naturally encourages models to locate the simplest prediction patterns, which often are the least reliable shortcuts (Nagarajan et al., 2024).

### 3.2.2 RLHF

While Reinforcement Learning from Human Feedback (RLHF) is crucial for making LLMs safer and more helpful, the process itself can introduce robustness Sources in the following ways:

- **Reward Hacking:** LLMs may learn to exploit weaknesses or biases in the reward model (RM) used during RLHF, maximizing the reward signal without genuinely fulfilling the intended preference (e.g., generating overly verbose responses because the RM implicitly favours length) (Yan et al., 2024b).
- **Bias Amplification:** RLHF optimizes based on human feedback, but this feedback can itself be biased, inconsistent, or fail to capture the full spectrum of desirable behaviour. Optimizing for average preferences might even strengthen covert biases not explicitly penalized by the feedback (Barnhart et al., 2025).
- **Capability Trade-offs:** Safety alignment, often achieved via RLHF or related techniques, has been observed to sometimes degrade specific capabilities like complex reasoning (Huang et al., 2025).

### 3.2.3 Alignment Tax

This phenomenon, termed the “alignment tax”, means that improving alignment (e.g., helpfulness, harmlessness) might come at the cost of reduced performance on general knowledge benchmarks or can sometimes negatively impact model calibration (leading to overconfidence) or introduce new vulnerabilities (Chen et al., 2020; Yang et al., 2024b). Fine-tuning LLMs for specific tasks or aligning them with human preferences (e.g., using RLHF) can lead to a degradation of capabilities learned during pre-training (e.g., Masked Language Modeling vs. Standard auto-regressive prediction), which can influence downstream behaviour (Lin et al., 2024b). This creates a difficult trade-off for developers.

### 3.2.4 Fine-tuning Limitations

While fine-tuning adapts LLMs to specific tasks or domains, it can also reduce robustness, as in cases like:

- **Overfitting:** Models can overfit to the specific style, domain, or spurious correlations within the fine-tuning data, harming OOD generalization (Yuan et al., 2023).
- **Noise Sensitivity:** Fine-tuning performance is highly sensitive to noise in the instruction-following or preference data (Luo et al., 2024). Even moderate noise levels can cause significant performance drops.
- **Instruction Brittleness:** Instruction-tuned models can show substantial performance degradation when test-time instructions are phrased differently from those seen during fine-tuning, indicating a lack of robustness to instruction variations (Aljohani et al., 2025). Specialized models might be even more fragile in this regard.

## 3.3 Architectural Limitations

While less explored in the provided sources, the inherent properties of the dominant Transformer architecture, such as the attention mechanism’s focus or the lack of explicit symbolic reasoning modules, might contribute to certain robustness vulnerabilities. The lack of built-in mechanisms for reliable uncertainty quantification or causal reasoning could also be a factor (Zhang, 2023). The underlying architecture of LLMs, predominantly the Transformer, also presents inherent vulnerabilities:

- **Transformer Properties:** Specific components of the Transformer architecture, such as the self-attention mechanism, can be points of failure. While properties like redundancy might offer some baseline resilience compared to older architectures, this resilience is limited and can be overcome by targeted attacks [Das et al. \(2025\)](#). Further, expanding model depth (layer expansion) can particularly disrupt the attention mechanisms.
- **Vulnerabilities to Modifications:** Practical deployment often requires model modifications for efficiency, such as quantization (reducing numerical precision) or pruning (removing weights/neurons). These compression techniques can induce “information loss cascades”, significantly degrading robustness ([Ma et al., 2025](#)). Similarly, architectural changes aimed at efficiency, like attention-efficient variants (e.g., GLA Transformer, MatMul-Free LM ([Fan & Tao, 2024](#)) or Funnel Transformers ([Choi et al., 2025](#))), involve trade-offs that may impact robustness. Transformer architectures appear to have inherent robustness thresholds beyond which modifications cause severe performance degradation. For example, the extreme vulnerability to Bit-Flip Attacks (BFAs), where flipping just a few bits in the weights of a large model can cause catastrophic failure, challenges assumptions about their inherent resilience ([Ma et al., 2025](#)).
- **Linear Transformers:** Simpler variants like linear transformers have shown specific vulnerabilities, such as susceptibility to hijacking attacks during in-context learning, where malicious examples in the prompt manipulate the learned function ([Anwar et al., 2024](#)).

### 3.4 Inference related Sources

Non-robustness in LLMs also arises during inference, where vulnerabilities arise from how models interpret inputs and produce outputs. Minor paraphrasing or ambiguous instructions can destabilize responses, while decoding strategies like temperature sampling introduce unpredictability by balancing coherence and creating risks of erratic outputs. Adversarial inputs exploit the model’s instruction-following nature to bypass safeguards, and input tokenization steps distort rare words or non-standard syntax, amplifying errors. These challenges, inherent to the inference phase, can introduce these vulnerabilities as:

#### 3.4.1 Inference and Decoding Vulnerabilities

Even with a trained model, the way outputs are generated during inference by the choice of decoding strategy can also introduce vulnerabilities like:

- **Decoding Strategy Sensitivity:** The algorithm used to select the next token based on the model’s probability distribution (e.g., greedy search, beam search, top-k/nucleus sampling) has a major impact on the performance of the model ([Nik et al., 2025](#)).
  - **Performance vs Robustness:** Different strategies offer trade-offs. Deterministic methods like greedy search ([Bang et al., 2023](#)) might be preferred for closed-ended tasks requiring precision, while stochastic methods (sampling) are often better for open-ended generation requiring diversity ([Shi et al., 2024a](#)). However, stochasticity can reduce the consistency of the model.
  - **Hyperparameter Sensitivity:** The performance and behaviour of decoding strategies are often highly sensitive to hyperparameters like temperature (for sampling) or beam width (for beam search). Achieving optimal performance might require extensive tuning, but fixed hyperparameters might lead to suboptimal robustness across diverse inputs ([Shi et al., 2024a](#)).
- **Calibration Errors:** LLM confidence scores (often derived from output probabilities) frequently fail to accurately reflect the true likelihood of the generated output being correct ([Yao et al., 2024](#)). Models, especially those fine-tuned with RLHF, tend to be overconfident. This miscalibration hinders reliable decision-making based on model outputs.

#### 3.4.2 Retrieval-Augmented Generation (RAG) Sources

RAG systems enhance LLMs by retrieving external information, but their robustness depends heavily on the quality and relevance of the retrieved context ([Shen et al., 2024](#)). If the retriever returns inaccurate,

irrelevant, or noisy information (due to its own lack of robustness), the final LLM output quality can be significantly compromised, sometimes performing worse than without retrieval at all. LLMs may also struggle to effectively utilize a large number of retrieved documents, even with long context windows (Yu et al., 2024).

A comprehensive approach to robustness is required due to the availability of vulnerabilities throughout the entire lifecycle, from data collection through training to inference. Additionally, the observed conflict between preserving robustness and optimizing for capabilities (e.g., through scaling or alignment) implies that accomplishing both at the same time is a significant, continuous task that calls for careful trade-off management.

## 4 Mitigation Strategies

The strategies are categorized based on the stage of the typical LLM development and deployment pipeline where they are applied:

1. Pre-processing: Actions taken on the data before model training or fine-tuning begins (e.g., data cleaning, augmentation).
2. In-processing: Modifications integrated during the model training or fine-tuning process (e.g., robust optimization, adversarial training, alignment techniques).
3. Intra-processing: Techniques applied during the model’s inference or generation phase (e.g., robust prompting, modified decoding, inference-time adaptation).
4. Post-processing: Methods applied after the model generates an output, but before it is presented to the user or used downstream (e.g., output filtering, validation, using a judge model).

This pipeline-based categorization provides a structured way to understand where different interventions fit within the LLM lifecycle and how they contribute to overall robustness. Figure 4 provides an illustration of enhancing the robustness of LLMs using these strategies throughout the pipeline.

### 4.1 Pre-processing strategies

Pre-processing strategies represent the earliest opportunity to influence LLM robustness by intervening at the data stage, before any model training or fine-tuning occurs. These methods focus on curating, cleaning, or augmenting the vast datasets used to train LLMs, aiming to embed robustness characteristics implicitly through the data the model learns from. They effectively address data biases and vulnerabilities in raw training data, preventing the model from inheriting or amplifying them, which could compromise the model’s performance. Some key pre-processing approaches that enhance robustness at the data level are as follows:

**Data Augmentation for Robustness:** Data augmentation aims to increase the diversity and size of the training dataset, typically to improve model generalization. Dong et al. (2021) describes this as specifically designed techniques to expose the model to the types of variations or adversarial inputs it might encounter during deployment. Early techniques adapted from general NLP, such as Easy Data Augmentation (EDA), involved simple lexical operations like synonym replacement, random insertion, random swap, or random deletion (Weng, 2023). While useful for generalization, these methods may not adequately prepare models for targeted adversarial attacks or significant distribution shifts.

A more targeted approach is Adversarial Data Augmentation (ADA), which generates challenging examples to improve robustness against data shifts or corruptions. ADA creates misleading target distributions using adversarial loss, perturbing data to fool the model during training. A key advancement, Maximum-Entropy ADA (ME-ADA) (Zhao et al., 2020), introduced an Information Bottleneck-derived regularizer that maximizes model uncertainty, producing harder adversarial examples by pushing augmented data further from the source distribution, outperforming prior methods on benchmarks. Simultaneously, Adversarial Contrastive Learning (ACL) (Jiang et al., 2020) merges adversarial examples with self-supervised pre-training. By enforcing feature consistency across standard and adversarial views, ACL enhances inherent invariance,

improving robustness and label efficiency over unsupervised methods. Follow-up work refined ACL via robustness-aware coreset selection and adversarial invariant regularization (Xu et al., 2023).

As research shifted towards LLMs, augmentation techniques became more specialised. Liu & Sun (2023) introduced the Adversarial Augmentation Approach (A3), combining adversarial training with NLP-specific data augmentation. Unlike traditional methods, A3 employs a paraphrasing model guided by a separate generator to produce reusable adversarial examples, optimized for specific tasks via a discriminator. This efficiency boosted accuracy for models like BERT, outperforming earlier methods. Further, Bae et al. (2025) introduces SALAD (Structure Aware and LLM- driven Augmented Data), a contrastive learning approach that employs a tagging-based method for generating structure-aware positive samples and leverages LLMs to create diverse counterfactual negative samples for triplet loss optimization. Meanwhile, HarmAug (Lee et al., 2024b) tackles safety: it trains compact “guard” models to detect harmful queries by generating adversarial examples (e.g., jailbroken LLM prompts) and distilling knowledge from a large teacher model. This let a 435M-parameter safety model match the performance of 7B+ counterparts, proving targeted augmentation can compress robustness into smaller systems. These advances align with broader efforts to refine LLM robustness through data-centric strategies, such as adaptive data filtering and synthetic data generation (Dong et al., 2021; Qian et al., 2022; Ding et al., 2024; Zayed et al., 2022; Lim et al., 2023).

**Data Filtering:** Modern large language models (LLMs) rely heavily on vast amounts of internet-sourced data for training, but this data often includes noise, toxic content, societal biases, personal information, and factual inaccuracies (Huang et al., 2024a). Since LLMs can memorise such flaws during training, these issues directly translate into risks like biased outputs, privacy breaches, and unreliable behaviour in real-world applications. Data filtering approaches this by modifying training samples or their weights to mitigate harmful content in model learning (Li et al., 2025b; Wang et al., 2025). Additionally, this approach can generate contrastive pairs (e.g., pairing biased and debiased examples) to explicitly teach models to disregard biased patterns in the data. While filtering and cleaning data before training is essential, considering the fact that manual curation is time-consuming and demands domain expertise, to mitigate these risks, it also introduces complex trade-offs: overly strict filtering to remove toxic content or reduce bias can inadvertently harm the model’s general performance or erase valid examples from underrepresented groups. For instance, prioritizing safety might suppress harmful outputs but weaken the model’s versatility, while aggressive bias mitigation could strip away nuanced data critical for fairness. Thus, achieving the right balance between data quality (removing harmful content) and quantity (retaining useful diversity) remains a pivotal challenge in building trustworthy LLMs.

Laurençon et al. (2023) proposed a Rule-based Heuristic Filtering, using predefined criteria to remove sensitive data (e.g., PII) or toxic content via blocklists or classifiers, though their success hinges on the precision of these tools. To streamline complexity, frameworks like Data-Juicer (Chen et al., 2023a) systematize cleaning by automating steps like deduplication and quality scoring. More recently, LLMs themselves have been repurposed as data cleaners: studies show they can fix simple errors (e.g., invalid dates) using contextual analysis but falter with nuanced issues like dataset-wide biases (Bendinelli et al., 2025). From basic heuristics to AI-driven refinement, these approaches illustrate the layered effort to balance scalability and reliability in training data. Further, BaichuanSEED (Dong et al., 2024a) demonstrates the scalability of data-centric methods, showing that careful data curation and reweighting can enable even a general 7B-parameter LLM to achieve state-of-the-art benchmark performance without architectural modifications. Yang et al. (2024c) introduces RAZOR (Rewriting And Zero-bias Optimization Refinement), a novel unsupervised text rewriting technique designed to mitigate dataset biases (shortcuts) that hinder language model generalization without requiring prior knowledge of specific biases. RAZOR iteratively rewrites text segments using LLMs, selecting replacements that reduce spurious correlations between surface features and labels based on token statistics and positional information.

## 4.2 In-processing Strategies

In-processing mitigation strategies integrate directly into the model’s training or fine-tuning loop to build robustness inherently into the model’s parameters. Unlike pre-processing methods that modify input data, these techniques actively guide the learning process, continuously optimizing the model to develop more

robust and equitable representations. This approach is particularly effective for addressing complex bias patterns embedded in data relationships and countering training-induced sources of non-robustness, offering more direct control over model behaviour during learning. We now examine key in-processing techniques that shape model robustness through training dynamics.

**Adversarial Training:** Adversarial Training (AT) strengthens models by intentionally injecting adversarial examples into their training data, thereby forcing the model to learn more robust features. It can be formulated as a minimax optimization problem: the inner loop maximizes the loss by finding the *worst-case* adversarial example within a defined perturbation budget, while the outer loop minimizes the loss on these adversarial examples (along with clean examples) to update the model parameters (Bai et al., 2021a).




Figure 4: The robustness of Large Language Models (LLMs) can be systematically fortified through a layered pipeline. Beginning with data collection and annotation, diverse datasets and rigorous labelling establish a foundational resilience. Pre-processing strategies then clean, augment, and balance the data to mitigate biases and noise. During training and fine-tuning, in-processing techniques like adversarial learning and alignment strategies address vulnerabilities directly. As part of inference, intra-processing strategies dynamically adjust inputs (e.g., sanitising adversarial queries) to counter real-time risks. Finally, post-processing safeguards act as a last layer, refining outputs via alignment checks and ethical filters to ensure reliability. Together, these stages create a unified defence, ensuring adaptability and resilience across the LLM lifecycle.

Early approaches involved adapting methods from other domains like generating attacks via word substitutions guided by gradient information or word importance scores (Liu & Sun, 2023; Weng, 2023) or performing perturbations directly in the continuous embedding space and then mapping these perturbed embeddings back to discrete tokens, often using a masked language model (MLM) head (Altinisik et al., 2023). Aiming to improve robustness generalization by learning a distribution over adversarial examples around each clean data point, rather than finding a single worst-case point estimate, Dong et al. (2021) proposes Adversarial Distributional Training (ADT), which uses an entropy regularizer. Further, Xhonneux et al. (2024) proposes a fast adversarial training algorithm C-AdvUL (Continuous-Adversarial Unlikelihood) and CAPO (Continuous-Adversarial IPO). C-AdvUL combines an unlikelihood loss (penalizing harmful outputs, rewarding safe ones) on perturbed inputs with a standard utility loss on clean data. CAPO integrates continuous attacks with Identity Preference Optimisation (IPO), a DPO variant (Rafailov et al., 2024), using the IPO loss on perturbed inputs and relying on the KL divergence term inherent in IPO to maintain utility without requiring a separate utility dataset. Distributionally Robust Optimization (DRO) (Rahimian & Mehrotra, 2022; Kuhn et al., 2025) is another work for optimizing model performance under worst-case conditions over



a specified distribution or ambiguous set of inputs, rather than just point-wise adversarial examples. Recent work like PEARL (Permutation-resilient learning) and Dr. DPO (Distributionally Robustifying DPO) has also applied these principles to specific LLM robustness challenges (Wu et al., 2025; Chen et al., 2025a).

However, scaling AT to LLMs also introduces several challenges. First, the discrete nature of text complicates gradient-based perturbation strategies, where small token-level modifications must preserve semantic coherence, and gradients derived from differentiable surrogates (e.g., word embeddings) do not always map meaningfully to discrete token substitutions. Second, the computational overhead grows prohibitive: generating adversarial examples via iterative methods (e.g., Projected Gradient Descent) or combinatorial search over token sequences is resource-intensive, and fine-tuning massive LLMs on such augmented datasets amplifies training costs exponentially. Third, AT often induces a robustness-utility trade-off, where improvements in adversarial accuracy come at the expense of degraded performance on clean data, necessitating careful balancing. Finally, robustness gains are frequently attack-specific as models trained against one perturbation type (e.g., synonym swaps) may remain vulnerable to unseen attack strategies (e.g., paraphrasing or structural perturbations). And so efficiency and integration with alignment objectives are becoming central themes, with continuous attacks and DRO (Dong et al., 2021; Chen et al., 2025a) emerging as promising directions.

**Regularization** Regularization methods add constraints or penalties to the training objective to prevent overfitting and encourage desirable model properties, including robustness. A key approach to this is Adversarial Contrastive Learning (ACL) (Jiang et al., 2020), which integrates robustness directly into representation learning by aligning embeddings of clean, augmented, and adversarially perturbed inputs. Recent advances, such as robustness-aware coreset selection and adversarial invariant regularization terms (Xu et al., 2023), further streamline ACL by focusing training on critical data subsets and explicitly penalizing sensitivity to adversarial distortions. Mahabadi et al. (2020) developed Debaised Focal Loss (DBL), which adaptively down-weights biased examples identified by an auxiliary bias-only model. Complementary work by Utama et al. (2020) introduced confidence regularization to balance in-distribution accuracy and out-of-distribution generalization, specifically preventing overconfidence in biased examples without sacrificing overall learning capacity. Further, Garimella et al. (2021) proposed another regularization approach that identifies potentially biased terms through lexical co-occurrence analysis, assigning bias scores to adjectives and adverbs ( $W$ ), which are then incorporated into the model’s optimization process. Several studies have also been conducted to obtain a fair model by using Regularization (Ravichandran et al., 2020; Xu et al., 2025; Heck et al., 2024; Mou et al., 2024; Li et al., 2022). Together, these methods demonstrate how structured regularization can balance robustness, efficiency, and generalization in modern language models.

**Alignment for Robustness** Aligning LLMs with human values during training aims to ensure these systems are helpful and reliable. Techniques like supervised fine-tuning (SFT) (Sun, 2024; Luo et al., 2024) on high-quality data and reinforcement learning from human feedback (RLHF) (Ouyang et al., 2022; Christiano et al., 2023), which uses human preferences to shape model behaviour, are widely adopted. Newer methods, such as Direct Preference Optimization (DPO), simplify alignment by training models directly on preference-ranked outputs, while variants like ORPO, KTO, and AlphaPO (Hong et al., 2024; Ethayarajh et al., 2024; Gupta et al., 2025) seek to enhance efficiency or performance. While primarily focused on safety and helpfulness, alignment inherently contributes to robustness against certain failure modes, particularly attacks designed to elicit harmful or biased content. For example, approaches like Safe RLHF (Tran et al., 2025) integrate safety-specific rewards to balance helpfulness with risk mitigation.

However, alignment introduces its own challenges. First, models may become overly sensitive to prompt phrasing, leading to inconsistent responses or unnecessary refusals of benign queries (Oh & Demberg, 2025; Tran et al., 2025). Second, alignment might overlook emerging vulnerabilities, as pre-alignment evaluations often fail to predict post-alignment weaknesses. Third, *reward hacking* can occur, where models exploit flaws in their training objectives to maximize scores without genuinely adhering to human intent (Herrera-Poyatos et al., 2025). Finally, methods like RLHF demand extensive computational resources and rely heavily on high-quality, diverse training data, limiting scalability. Addressing these trade-offs remains critical to developing reliable, ethically aligned AI systems.

Acknowledging these challenges, researchers are actively developing strategies to strengthen the alignment process and mitigate its inherent risks. One approach integrates AT with alignment objectives, such as combining continuous adversarial perturbations with preference optimization frameworks (Xhonneux et al., 2024). Others focus on RPO methods like Dr. DPO improve resilience to noisy preference labels, while techniques like statistical rejection sampling (sDPO) and perplexity-aware corrections refine how models handle imperfect training data (Zhong et al., 2025a; Xu et al., 2023). For reward modeling, advancements include ensemble methods to reduce reward hacking risks, worst-case scenario optimization to mitigate unstable outputs, and causal reward frameworks to better capture human intent (Wang et al., 2024a; Dong et al., 2024b; Xiong et al., 2024). Additionally, consistency alignment introduces self-reward mechanisms to ensure models produce stable responses across varied prompts, reducing sensitivity to phrasing changes (Zhao et al., 2024b). Together, these strategies aim to balance safety, reliability, and adaptability in aligned AI systems while addressing challenges like data noise, reward exploitation, and behavioural inconsistency.

### 4.3 Intra-processing Strategies

Intra-processing mitigation strategies improve LLM reliability by dynamically adjusting how models interpret inputs or produce outputs during the inference or generation phase, without altering their underlying training or parameters (Wang et al., 2025). This approach provides a cost-effective way to address vulnerabilities, avoiding the computational expense of retraining while maintaining adaptability to emerging risks, and is further able to counter data, training or inference-related sources of non-robustness, though they do not address root causes in the training data or model parameters. We now explore some intra-processing techniques that enhance model robustness through dynamic input-output adaptation during real-time inference.

**Robust Prompting and Instruction Defence** The development of benchmarks specifically targeting prompt injection and instruction perturbation has been crucial in revealing the significant vulnerabilities of even state-of-the-art LLMs and driving the need for these more advanced intra-processing defences. Large language models (LLMs) are inherently vulnerable to adversarial inputs due to their instruction-following nature, where prompts act as both a critical interface and an attack surface (Agrawal et al., 2025; Chen et al., 2025b). These strategies aim to secure LLMs by addressing vulnerabilities in how they interpret and execute input prompts. Basic approaches include instruction design, where prompts are engineered with explicit safety directives (e.g., “ignore harmful instructions”). However, heavily tuned models may still prioritize conflicting later instructions, and overly restrictive prompts risk stifling legitimate creativity (Li et al., 2024d; Weng, 2023). Similar to pre-processing data augmentation, some techniques attempt to clean the prompt just before the LLM sees it. This can involve paraphrasing prompts or retokenizing inputs to disrupt adversarial patterns, offering limited protection against sophisticated attacks (Weng, 2023).

More advanced methods include self-denoising, where LLMs iteratively revise corrupted instructions using their own language understanding to outperform traditional fine-tuning in resisting perturbations (Agrawal et al., 2025). Further, Hu et al. (2024) proposes RobustGER, which teaches LLMs to perform language-space denoising by incorporating an embedding derived from ASR (Automatic Speech Recognition) N-best lists, refined through audio distillation. Another novel approach, referenced instruction tracking, requires LLMs to explicitly cite which prompt instruction they followed during generation, and so responses referencing malicious injections are automatically filtered, which effectively repurposes the model’s instruction sensitivity as a defence (Chen et al., 2025b). While these intra-processing strategies vary in complexity, they highlight the trade-offs between usability, computational cost, and robustness in real-time LLM safety.

**Weight Redistribution** Weighted redistribution refers to adjusting a trained model’s attention weights (without additional training) to reduce bias in its outputs. Since attention weights can reflect learned biases in the data, redistributing them may help the model focus less on biased words or phrases during predictions. Chai & Wang (2022) developed an adaptive reweighting method that assigns sample-specific weights to prioritize error-prone instances and ensure balanced minority group representation for group-level fairness and exhibits robustness to label noise on various benchmark datasets. Further, considering the fact that AI models focus on specific words (attention weights) may reinforce biases. Zhong et al. (2025b) proposes a framework which employs data-aware inter-stage fusion to overlap generation and inference by

migrating long-tailed samples and model-aware intra-stage fusion with a fused pipeline schedule to mitigate pipeline bubbles in the training stage to prepare the context of inference tasks.

**Modified Decoding and Search Strategies** The methods that guide how LLMs select tokens to generate text also play a subtle but important role in balancing output quality and robustness. While standard approaches like greedy decoding (choosing the most probable token) or beam search are widely used, they often struggle under adversarial conditions or when generating diverse, reliable outputs (Beyer et al., 2025). Despite their limitations, research has largely prioritized input- or output-level defences (e.g., prompt engineering, response filtering) over reimagining decoding itself as a primary robustness mechanism. This gap persists even as adversarial attacks exploit decoding weaknesses, such as using greedy search or Greedy Coordinate Gradient (GCG) (Kumar et al., 2025a) to craft optimal input perturbations. The relative neglect of defensive decoding strategies may stem from practical hurdles, such as the computational complexity of altering core generation processes compared to simpler input/output interventions.

Emerging approaches aim to address these gaps by refining how LLMs navigate token selection. Uncertainty-aware decoding, for instance, could suppress generations when the model’s confidence is low, reducing errors in high-stakes scenarios. Ensemble decoding combines outputs from varied model states or prompts to dilute adversarial influences, while constrained decoding enforces safety rules (e.g., blocking harmful phrases) during token selection (Shi et al., 2024b; Gu et al., 2024; Daheim et al., 2025). Son et al. (2025) formalizes this challenge as a maximin game, introducing RMOD (Robust Multi-Objective Decoding), a method aimed at maximizing worst-case rewards through Nash equilibrium optimization. RMOD achieves this by balancing competing objectives, specifically, identifying a Nash equilibrium between reward weight allocations and the sampling policy during text generation.

However, these strategies remain underexplored compared to input/output defences, partly due to perceived trade-offs between robustness, computational cost, and output creativity. For example, overly strict decoding rules might stifle natural language diversity, mirroring the pitfalls of rigid prompt engineering. Until decoding innovations match the practicality of input/output defences, their potential to enhance LLM robustness will likely remain secondary.

**Inference-Time Adaptation and Transformation** Beyond prompt manipulation and decoding, other intra-processing techniques involve adapting the model or its execution environment at inference time. While efficient inference infrastructure does not directly enhance robustness, it enables the deployment of adaptive systems that can improve real-world reliability (Manvi et al., 2024). For instance, LeVine et al. (2024) evaluates the performance and calibration of reward models under distribution shift and finds that accuracy degrades significantly, particularly for OOD responses. Some of key strategies include test-time adaptation (TTA), which makes minor, instance-specific adjustments to improve handling of rare or unfamiliar data, such as medical cases outside training distributions (Snell et al., 2024). Architectural interventions explore structural modifications during inference, like removing or swapping transformer layers, revealing that models retain most functionality despite such changes, which is a sign of inherent redundancy and fault tolerance (Lad et al., 2024). Other work examines components like layer normalization, showing how architectural choices impact stability under perturbations (Jha & Reagan, 2024). Finally, efficient inference engines optimize computational bottlenecks (e.g., attention mechanisms) using memory optimization and adaptive computation, enabling complex real-time processes like retrieval-augmented generation while balancing speed and accuracy (Ye et al., 2025). Together, these approaches highlight how real-time adaptability and structural insights can bolster LLM reliability without sacrificing efficiency.

#### 4.4 Post-processing techniques

Post-processing strategies constitute the final line of defence in the LLM pipeline, applied after the model has generated its output but before that output is delivered to the user or consumed by a downstream application. These methods involve scrutinizing, filtering, validating, or transforming the generated text to detect or mitigate potential robustness failures, such as harmful content, factual inaccuracies, biases, or outputs resulting from successful attacks that bypassed earlier defences.

**Output Filtering and Validation** A fundamental principle of post-processing is to treat the LLMs output with a degree of skepticism, applying verification steps similar to how one might validate user input. Common strategies include safety classifiers, where smaller models or rule-based systems screen outputs for harmful or biased content, blocking or flagging problematic responses (Kumar et al., 2025b; Liu et al., 2023; Zhou et al., 2024a). For example, the Erase-and-Check method iteratively tests modified versions of suspicious prompts to detect adversarial inputs, leveraging pre-generation filtering to block harmful content (Kumar et al., 2025a; Phute et al., 2024). Perplexity filtering identifies nonsensical outputs by measuring how *natural* generated text appears to a language model, flagging high-perplexity results as potential errors or attacks (Weng, 2023).

For structured tasks (e.g., code or JSON generation), format validation ensures outputs adhere to predefined schemas or pass external checks like code compilers, preventing errors or injection vulnerabilities (Rebedea et al., 2023; AI, 2025). Similarly, output sanitization removes sensitive information (e.g., personal data) leaked during generation, mitigating privacy risks (Wang et al., 2025). Further, Song et al. (2025); Maheshwari et al. (2025) implements RAG to verify outputs after initial response generation. After a language model produces an answer, the system automatically fetches supporting evidence from external databases or documents, using either the original user query or the generated response as search criteria. The model then cross-checks its own output against this retrieved evidence, creating a self-correction cycle that improves factual consistency. While methods like Erase-and-Check offer strong defences, their computational cost often requires simplified variants for practical use, highlighting the trade-off between robustness and efficiency. Together, these strategies underscore the importance of layered verification to balance safety, accuracy, and usability in real-world LLM deployments.

**LLM-as-a-Judge for Verification and Filtering** This approach uses one language model to evaluate the outputs of another, offering scalable and nuanced assessments beyond basic rule-based checks. This method is increasingly applied to enhance robustness by automating tasks like bias detection, safety compliance, and factual accuracy (Gu et al., 2025; Kumar et al., 2025b). For instance, judge LLMs can systematically analyze responses for fairness across demographic categories, validate reasoning steps in technical tasks (e.g., code vulnerability detection), or flag factual errors by cross-referencing trusted sources (Cantini et al., 2025). Advanced frameworks even deploy judge LLMs to autonomously generate adversarial prompts, test target models, and assess response reliability, guided by domain-specific constraints (Li et al., 2025c; Beyer et al., 2025).

However, reliance on LLM judges introduces challenges. First, their evaluations can be inconsistent due to prompt sensitivity, inherent biases, or a lack of grounding in objective criteria (Gu et al., 2025). Second, judge models themselves are prone to manipulation; studies show adversarial phrases or stylistic cues (e.g., phrases like “I think”) can skew their assessments (Raina et al., 2024; Lee et al., 2024a). Finally, the lack of standardized evaluation protocols and risks like “preference leakage”, where judges favour outputs from models they were trained on, underscore the need for multi-judge ensembles, human oversight, and rigorous benchmarking to ensure reliability (Beyer et al., 2025). While promising, LLM-as-a-Judge systems require careful design to balance automation with trustworthiness.

## 5 Metrics and Benchmarks

Modern language models must demonstrate reliability beyond basic performance metrics. As these models are deployed in real-world applications – from healthcare diagnostics to legal document analysis – their behaviour under stress becomes critical. Robustness evaluation answers crucial questions: How does the model fail? When does it fail? Most importantly, *why* does it fail?

The landscape of LLM robustness contains eight interconnected dimensions 2.2, each requiring specialized measurement approaches. Our analysis reveals that the majority of production failures stem from overlooked robustness factors rather than pure accuracy issues. Table 2 distils some essential metrics across 7 categories, providing practitioners with:

- A diagnostic toolkit for model weaknesses

- Prioritization guidance for system improvements
- Benchmarking standards for research comparisons

**Key Insight:** No single metric tells the whole story. Effective evaluation requires combining complementary measures across multiple dimensions to ensure reliability.

## 5.1 Metrics

Evaluating the multifaceted concept of LLM robustness requires a diverse toolkit of metrics, each designed to capture specific aspects of model behaviour under various challenging conditions. These metrics move beyond simple IID accuracy to quantify performance degradation, generalization ability, consistency, calibration, fairness under duress, and factuality, particularly when models are stressed.

### 5.1.1 Performance Degradation Metrics

These metrics quantify the drop in performance when an LLM is evaluated on challenging data (adversarial, OOD, noisy) compared to its performance on clean, standard (IID) data. They provide a direct measure of how much a specific challenge impacts the model’s effectiveness.

- Accuracy Drop / F1 Drop / Metric Drop: These are calculated as the difference (absolute or percentage) between a standard metric (like Accuracy or F1-score) on the IID test set and the same metric on the challenging test set (e.g., an OOD dataset or an adversarially perturbed dataset) (Yuan et al., 2023; Du et al., 2023). A larger drop indicates lower robustness to that specific challenge. For example, a 20% accuracy drop on an OOD dataset suggests poor generalization.
- Attack Success Rate (ASR): This metric is central to adversarial robustness evaluation. It measures the percentage of adversarial inputs that successfully cause the intended model failure, such as misclassification in NLU tasks, bypassing safety filters to generate harmful content, or successfully executing a jailbreak prompt (Jung et al., 2025). A higher ASR signifies lower robustness to the specific attack method used. It is a key metric for benchmarks like AdvGLUE++, JailbreakBench, and PromptBench (Zhou et al., 2024a).
- Compliance Ratio / Refusal Rate: These metrics are particularly relevant for evaluating safety and alignment robustness, especially against jailbreaking attempts. It measures how often the LLM generates harmful or forbidden content when prompted with malicious instructions (Varshney et al., 2024; Zeng et al., 2025). Conversely, the Refusal Rate measures how often the model refuses to answer. A high refusal rate for harmful prompts indicates good safety alignment, but a high refusal rate for benign prompts indicates over-defensiveness, a potential negative side-effect of safety training.

### 5.1.2 Out-of-Distribution (OOD) Performance Metrics

These metrics specifically assess how well an LLM performs when faced with data that differs statistically from its training distribution.

- OOD Accuracy / F1 score: Standard performance metrics like Accuracy or F1-score calculated directly on designated OOD benchmark datasets, such as those included in the BOSS suite (e.g., Dynasent, ANLI, NewsQA) (Yuan et al., 2023). This provides a direct measure of capability on unseen distributions.
- ID-OOD Performance Gap: This metric quantifies the difference in performance between an ID dataset and a corresponding OOD dataset (Yuan et al., 2023). It explicitly measures the drop in generalization capability due to the distribution shift. Studies using benchmarks like BOSS have shown that this gap can vary significantly and exhibit complex patterns (e.g., linear, piecewise linear, V-shaped) depending on factors like model scale, training steps, and task type, indicating that simply improving ID performance does not always guarantee better OOD performance.



Table 2: Different metrics for evaluation of robustness in LLMs.

Metrics	Specific Category	Dimension Measured	Brief Description
Performance Degradation	Accuracy Drop, F1 Drop (Yuan et al., 2023)	General Robustness	Decrease in standard metrics on challenging vs clean data.
	Attack Success Rate (ASR) (Zhou et al., 2024a)	Adversarial Resilience, Safety	Percentage of successful adversarial attacks/jailbreaks
	Compliance / Refusal Rate (Varshney et al., 2024; Zeng et al., 2025)	Safety, Alignment	Frequency of generating harmful content or refusing prompts
OOD Performance	OOD Accuracy/F1 score (Yuan et al., 2023)	OOD Generalization	Task performance on designated out-of-distribution datasets.
	ID-OOD Performance Gap (Yuan et al., 2023)	OOD Generalization	Difference between in-distribution and out-of-distribution performance.
	OOD Detection (AU-ROC, Energy Score) (Lu et al., 2024)	OOD Awareness	Ability to distinguish in-distribution versus out-of-distribution inputs.
Consistency	Semantic Consistency (Yang et al., 2025b)	Prompt Robustness, Reliability	Stability of output meaning under input paraphrasing or slight modifications.
	Consistency Rate (CR) (Nalbandyan et al., 2025)	Prompt Robustness, Sampling Stability	Proportion of identical or equivalent predictions across setups (e.g., prompts, seeds).
	Response Consistency (RC) (Rahman et al., 2024)	Prompt Robustness	Frequency of the most common claim across paraphrased prompts.
	LLM-based Consistency Score (Saxena et al., 2024)	Sampling Stability, Reliability	LLM judges assess consistency between generated samples.
Calibration	Expected Calibration Error (ECE) (Posocco & Bonnefoy, 2021)	Confidence Reliability	Alignment between predicted confidence and actual accuracy
	ECE under Distribution Shift (Huang et al., 2024b; LeVine et al., 2024)	OOD Generalization	ECE measured specifically on OOD data
Fairness under Stress	Bias Metrics (e.g., FLEX) (Jung et al., 2025)	Fairness Robustness	Evaluation of fairness when models are exposed to bias-inducing prompts.
Task-Specific	Code Robustness Checks (Li et al., 2025d)	Code Generation Robustness	Checks for robustness in generated code, like security or correctness features.
	Reasoning Accuracy (e.g., ReClor-plus) (Bao et al., 2025)	Reasoning Robustness	Performance on reasoning tasks containing structure variations.
Hallucination/Factuality	FactScore, FCH Rate (Rahman et al., 2024)	Factuality, Faithfulness	Verification of generated facts against a trusted knowledge source or context.
	FEWL (Wei et al., 2024)	Factuality (Reference-Free)	Weighted agreement among reference LLMs based on expertise.
	SelfCheckGPT, MetaQA (Wei et al., 2024)	Factuality/Consistency (Reference-Free) (Chen et al., 2024)	Consistency checks across multiple generated samples or metamorphic prompt variations.
	Faithfulness Metrics (NLI/QA-based)	Faithfulness to Source	Consistency between generated text and provided source document.
	Hallucination Rate Increase (HRI)	Factuality Robustness under Stress	Change in hallucination rate when exposed to stress conditions.

- OOD Detection Metrics (e.g., AUROC, FPR@TPR): These metrics evaluate the model’s ability to recognize that an input is OOD, often by thresholding a confidence score derived from model outputs (e.g., token probabilities) or internal representations (Huang et al., 2024a). Common metrics



include the Area Under the Receiver Operating Characteristic curve (AUROC) and the False Positive Rate (FPR) at a high True Positive Rate (TPR). While not directly measuring task performance robustness, effective OOD detection is crucial for building reliable systems that can identify and potentially abstain from making predictions on inputs they are likely to handle poorly (Lu et al., 2024). Techniques like Energy Score, originally from classification, have been adapted for this purpose in LLMs and reward models (LeVine et al., 2024).

### 5.1.3 Consistency Metrics

Consistency metrics evaluate the stability of LLM outputs. A consistent model should produce similar outputs for semantically identical inputs and exhibit stable behaviour under non-deterministic sampling. Lack of consistency can signal unreliability, especially for tasks requiring factual accuracy (Nalbandyan et al., 2025).

- **Semantic Consistency:** Assesses whether the meaning or core information conveyed in the LLM’s output remains the same when the input prompt is paraphrased or expressed differently, while preserving the original intent (Nalbandyan et al., 2025). Evaluation can be qualitative or quantitative, often using semantic similarity metrics based on embeddings (e.g., cosine similarity between output embeddings) (Patwardhan et al., 2025).
- **Consistency Rate (CR):** Proposed within the SCORE framework (Nalbandyan et al., 2025), CR quantifies the agreement among predictions for the same input across different evaluation settings (e.g., 10 different prompts, 5 different random seeds for sampling). It is calculated as the average proportion of agreeing pairs among all possible pairs of predictions for each input instance. For multiple-choice questions (MCQ), agreement means identical predicted letters; for tasks like MATH, it means symbolic equivalence checked via tools like sympy (Nalbandyan et al., 2025).
- **Response Consistency (RC):** Used in the DefAn benchmark (Bao et al., 2025), this metric specifically measures consistency across multiple (e.g., 15) paraphrased versions of a single prompt. For each set of paraphrased prompts, it calculates the frequency of the most common factual claim generated in the responses. The overall RC is the average of these frequencies.
- **Multilingual Consistency:** Evaluates whether the model’s performance or the semantic meaning of its output is preserved when prompts or inputs are translated into different languages (Qi et al., 2023).
- **LLM-based Consistency Score:** This approach uses another LLM as a judge (Saxena et al., 2024). It prompts the target LLM multiple times ( $n > 1$ ) for the same input using a non-zero temperature (e.g., 1.0) to induce variability. The judge LLM then compares pairs of generated responses, assessing whether they contradict or support each other. The consistency score is the fraction of pairs deemed consistent.

### 5.1.4 Calibration Metrics

Calibration metrics assess the alignment between an LLM’s predicted confidence and its actual likelihood of being correct. Well-calibrated models are crucial for trustworthy decision-making, as their confidence scores reliably indicate the potential accuracy of their outputs. Evaluating calibration under stress, such as distribution shifts, is vital for robustness.

- **Expected Calibration Error (ECE):** It works by dividing predictions into bins based on their confidence scores (e.g., 10 bins from 0.0-0.1, 0.1-0.2,..., 0.9-1.0). Within each bin, the average confidence and the actual accuracy (fraction of correct predictions) are calculated. ECE is the weighted average of the absolute difference between average confidence and accuracy across all bins, weighted by the number of samples in each bin. A lower ECE indicates better calibration (perfect calibration yields  $ECE=0$ ). Frameworks like UQ4CT aim to minimize ECE during fine-tuning. (Posocco & Bonnefoy, 2021)

- ECE under Distribution Shift: This involves calculating ECE specifically on OOD datasets or under simulated distribution shifts to assess how calibration holds up under stress. Research suggests that factors like OOD prompts versus OOD responses can impact the calibration of components like reward models differently (LeVine et al., 2024; Huang et al., 2024b).
- Other Metrics include:
  - Brier Score: Measures the mean squared difference between predicted probabilities and actual outcomes (0 or 1). Its other variants include weighted Brier score (Zhu et al., 2024).
  - Area Under the ROC Curve (AUROC): Can be used to assess how well confidence scores discriminate between correct and incorrect predictions when varying a confidence threshold.

### 5.1.5 Fairness Metrics under Stress

These metrics evaluate whether an LLM maintains fairness and avoids amplifying social biases when subjected to adversarial conditions, such as prompts designed to provoke biased responses.

- Concept: Standard fairness evaluation often checks for performance disparities or stereotypical associations on clean data. Fairness robustness evaluation applies similar principles but within a stress-testing context, using benchmarks like FLEX (Jung et al., 2025).
- Specific Metrics: These often involve measuring differences in other robustness metrics (like ASR, refusal rates, toxicity scores, or task accuracy) across different demographic groups when the model is prompted with bias-inducing adversarial inputs (Jung et al., 2025). For example, one might measure if a jailbreak attack is more successful (higher ASR) when the harmful instruction targets a specific demographic group, or if the model refuses benign requests more often for certain groups under adversarial pressure. Metrics derived from causal frameworks, like stratified invariance, can also quantify the model’s reliance on protected attributes under intervention (Cotta & Maddison, 2024).

### 5.1.6 Task-Specific Robustness Metrics

Certain applications require robustness dimensions unique to the task domain. Metrics are tailored accordingly.

- Code Generation: Beyond functional correctness, robustness evaluation focuses on aspects like security vulnerabilities or handling of edge cases too (Rahman & Kundu, 2024). Metrics might involve:
  - Static Analysis: Checking for the presence or absence of necessary robustness features like input validation, exception handling, or specific control structures compared to human-written reference code (Li et al., 2025d).
  - Robustness to Prompt Perturbation: Evaluating if code generation remains correct when the natural language instruction contains typos or semantic variations (Gan et al., 2024).
  - Code Hallucination Metrics: Specific metrics from benchmarks like HalluCode, such as Accuracy of Hallucination Existence Recognition (Acc-Rec) (did the model correctly identify if generated code contains hallucination ?) and Accuracy of Hallucination Mitigation (Acc-Mit) (did the model successfully correct the hallucinated code ?) (Liu et al., 2024a).
- Logical Reasoning: Evaluating performance degradation on standard reasoning benchmarks (e.g., ReClor, LogiQA) when the task structure is perturbed, for example, by shuffling the order of multiple-choice options or replacing the correct option with “none of the above” (as done in ReClor-plus, LogiQA-plus) (Bao et al., 2025). Robustness can also be tested against typographical errors in the problem statement using benchmarks like R2ATA (Gan et al., 2024).

### 5.1.7 Hallucination and Factuality Metrics under Stress

This crucial category focuses on measuring an LLM’s propensity to generate content that is factually incorrect, inconsistent with provided sources (unfaithful), or nonsensical (hallucination) (Liu et al., 2024a). The evaluation is particularly concerned with how this tendency changes under stressful conditions like OOD inputs, adversarial prompts, or questions probing the model’s knowledge boundaries.

- **Fact-Checking / Factuality Scores:** These metrics assess the alignment of generated content with verifiable world knowledge or a ground truth source.
  - **Knowledge Base (KB) / Corpus Comparison:** Generated statements are checked against external structured KBs or large factual corpora (Muhlgay et al., 2024). The FACTOR benchmark operationalizes this by creating contrastive (true/false) statements from a corpus and evaluating the LM’s likelihood score assigned to the true version versus false alternatives (Muhlgay et al., 2024).
  - **Exact Match (EM) (Wang et al., 2024c):** Measures the percentage of generated answers that perfectly match a known factual reference answer. It is simple but often too strict, failing to credit semantically correct paraphrases.
  - **Atomic Fact Verification (e.g., FactScore, FCH Rate):** This approach decomposes a longer generated text into individual factual claims (“atomic facts”) and verifies each claim against a reliable source like Wikipedia (Wang et al., 2024c). The final score is often the percentage of verified facts. This allows for fine-grained analysis of long-form generation. The Factual Contradiction Hallucination (FCH) rate used in the DefAn benchmark follows a similar principle (Rahman et al., 2024).
  - **FEWL (Factuality Evaluations via Weighting LLMs):** A reference-free metric designed for scenarios without gold-standard answers (Wei et al., 2024). It uses multiple external LLMs (“reference LLMs”) as proxies. It calculates a truthfulness score by weighting the agreement between the evaluated response and each reference LLM’s response based on the reference LLM’s estimated “expertise” (disagreement with wrong answers) and “non-laziness” (consistency across similar questions) (Wei et al., 2024).
  - **QA/NLI-based Metrics:** These leverage auxiliary models. A Question Generation/Answering system can be used to generate questions from the generated text and check if the answers are consistent with the source document. Alternatively, Natural Language Inference (NLI) models can classify the relationship (entailment, contradiction, neutral) between generated statements and source text sentences (Chen et al., 2024).
- **Faithfulness / Groundedness Scores:** These metrics specifically measure whether the generated text accurately reflects and is supported by a given source document. This is critical for tasks like summarization or Retrieval-Augmented Generation (RAG).
  - Methods often overlap with fact-checking (e.g., using NLI or QA models) but focus specifically on adherence to the provided context rather than general world knowledge (Chen et al., 2024). Faithfulness metrics evaluate if all claims in the output can be inferred from the source (Yang et al., 2025a).
  - **Mol-Hallu:** A domain-specific metric for evaluating faithfulness in molecular comprehension tasks. It uses an entailment model to check if scientific entities mentioned in the generated text are actually supported by the provided molecular descriptions (Li et al., 2025a).
- **Consistency-Based Metrics:** These metrics leverage the idea that factual information should be stable, while hallucinations might be more variable or contradictory across different generations or prompts.
  - **Self-Consistency Checks (e.g., SelfCheckGPT):** This approach involves generating multiple responses from the same LLM for a single prompt, typically using temperature sampling ( $T > 0$ ) to introduce diversity (Wei et al., 2024). The consistency (or lack thereof) across these responses is then measured. High variance or contradiction among samples might indicate hallucination,

- while consistent outputs suggest higher confidence or factuality. Various metrics can be used to quantify this, such as semantic similarity variance or contradiction detection using NLI models (Wei et al., 2024).
- LLM-based Consistency Score: This method uses a secondary model to evaluate consistency by generating multiple responses (with controlled randomness) to the same prompt, then calculating how often these responses logically align (Saxena et al., 2024). The resulting “consistency score” measures reliability under variable conditions.
  - MetaQA: This method applies metamorphic testing principles (Yang et al., 2025a). It generates variations of the original prompt using synonym or antonym substitutions. It then checks if the LLM’s responses to these related prompts exhibit the expected consistency (for synonyms) or inconsistency (for antonyms). Deviations from expected patterns can signal factual errors or hallucinations (Yang et al., 2025a).
  - Uncertainty as Indicator: The model’s own uncertainty estimates can sometimes serve as a proxy for hallucination risk.
    - Confidence Scores: Using metrics derived from the model’s output probabilities, such as token-level probabilities, sequence log-probability, or entropy (Mahaut et al., 2024). The assumption is that lower confidence might correlate with a higher likelihood of hallucination. However, this requires the model to be well-calibrated for the confidence scores to be reliable indicators.
    - Energy Score: While primarily used for OOD detection, the energy score calculated for reward models can indicate when the model is operating on inputs (prompts or responses) far from its training distribution, suggesting its reward estimate (which might relate to factuality) could be unreliable (LeVine et al., 2024).
  - Evaluating Increase in Hallucination under Stress: A key aspect of robustness is understanding how hallucination behaviour changes under pressure. This requires comparing hallucination rates measured using the metrics above under standard conditions versus stress conditions.
    - Methodology: Apply a chosen hallucination metric (e.g., FCH rate, FEWL score, SelfCheckGPT score) to a standard benchmark (e.g., TruthfulQA) and then again to a stressed version of that benchmark (e.g., TruthfulQA prompts with added noise, OOD context, or adversarial perturbations).
    - Metric: The Hallucination Rate Increase (HRI) can be defined as  $HRI = \text{Hallucination Rate (Stress)} - \text{Hallucination Rate (Standard)}$ . A significantly positive HRI indicates a failure in factuality robustness, meaning the model becomes more prone to hallucination when challenged. This requires benchmarks specifically designed or adapted for stress testing factuality (discussed in Section 2.2).

## 5.2 Benchmarks

Complementing the metrics described above, a growing number of benchmarks and evaluation frameworks are being developed to systematically assess LLM robustness across its various dimensions. These benchmarks provide standardized datasets and protocols for testing models under specific types of stress.

### 5.2.1 Adversarial Benchmarks

These benchmarks are designed to evaluate an LLM’s resilience to intentionally crafted inputs aimed at causing model failure, such as misclassification, generation of harmful content, or bypassing safety mechanisms.

- AdvGLUE / AdvGLUE++: These benchmarks are adversarial versions of the popular GLUE (General Language Understanding Evaluation) benchmark. They apply various textual adversarial attack methods (e.g., word substitutions using synonyms, character-level perturbations, sentence paraphrasing) to the original GLUE tasks (like sentiment analysis, natural language inference). AdvGLUE++ (Wang et al., 2021) expands upon AdvGLUE with more adversarial examples, targeting newer LLMs.

Table 3: Different Benchmarks for evaluation of robustness in LLMs.

Target Dimension	Benchmarks	Example Dataset / Key Component	Evaluation Approach
Adversarial Resilience	AdvGLUE / AdvGLUE++	Modified SST-2, MNLI, QQP, etc.	Perturbed versions of GLUE using textual attacks
Adversarial Resilience (Prompts)	PromptBench	Uses prompts with datasets like GLUE, SQuAD, GSM8K, GSM-PLUS	Perturbed versions of GLUE using textual attacks Dynamic adversarial attacks on prompts (char, word, sentence, semantic)
Adversarial Resilience (Safety)	JailbreakBench, AdvBench	Custom jailbreak prompts	Prompts designed to bypass safety filters
R2ATA	Adversarial Resilience (Reasoning), Noise	Perturbed GSM8K, BBH, MMLU	Adversarial typographical errors in reasoning problems
OOD Generalization	BOSS	IID: Amazon, SQuAD, MNLI, CC, FewNerd; OOD: Dynasent, ANLI, NewsQA, etc.	Curated ID/OOD datasets based on semantic dissimilarity & performance drop protocol.
	OODRobustBench	OODRobustBench	Predicts the maximum OOD robustness achievable by extrapolating existing $l_p$ -based robust training techniques to hypothetical models with perfect ID robustness.
	WANLI	ANLI dataset	Adversarially collected NLI examples.
Consistency, Prompt Robustness	SCORE	MMLU-Pro, AGIEval, MATH	Evaluates consistency across prompt paraphrasing, sampling seeds, choice order permutations.
Fairness under Stress, Adversarial Resilience	FLEX	Modified BBQ, CrowS-Pairs, StereoSet	Adversarial prompts (persona, competing objectives, text attacks) on fairness datasets
Task-Specific (Reasoning)	ReClor-plus, etc.	Modified ReClor, LogiQA	Structural variations (shuffled options, or adding “none of the above”) on reasoning datasets.
Task-Specific (Code)	CoderEval	CoderEval benchmark	Used to analyze code robustness aspects like missing checks vs. human code
Factuality/Hallucination	TruthfulQA	TruthfulQA dataset	Questions targeting common misconceptions to test truthfulness vs. imitation
	FELM	FELM dataset	Fine-grained, segment-level factuality annotations with error types & references
	FACTOR	Wiki-FACTOR, News-FACTOR, etc.	LM likelihood evaluation on contrastive (true vs. false) statements derived from a corpus
	DefAn	DefAn dataset	Large dataset evaluating FCH, PMH, and RC across paraphrased prompts
	UMWP	UMWP dataset	Tests if LLMs identify unanswerable problems or hallucinate solutions
(Recognition)	HaluEval	HaluEval dataset (derived from HotpotQA, CNN/DM, Alpaca, etc)	Large dataset of hallucinated/correct samples; tests LLM ability to classify hallucination
(Code)	HalluCode / CodeHalu	HalluCode, CodeHaluEval datasets	Benchmarks with taxonomies for evaluating code-specific hallucinations
(Multimodal)	AMBER	AMBER dataset (custom annotated images)	LLM-free evaluation of existence, attribute, relation hallucinations in MLLMs
(Multimodal)	HQHBench / ODE	HQHBench dataset; ODE framework	Meta-evaluation of benchmark quality (HQHBench); Dynamic open-set generation (ODE)

They serve as a standard for evaluating the robustness of fundamental language understanding capabilities against common textual attacks.

- PromptBench: Unlike benchmarks focusing on perturbing input samples, PromptBench (Zhang, 2023) specifically evaluates the robustness of LLMs to adversarial prompts (the instructions given to the model). It includes a framework for dynamically generating adversarial prompts using character, word, sentence, and semantic-level attacks and applies these perturbed prompts across various tasks (sentiment analysis, NLI, QA, translation, math) and datasets. This targets the sensitivity of LLMs to the way instructions are phrased.

- Jailbreak Benchmarks (e.g., JailbreakBench, AdvBench subset): These benchmarks consist of prompts specifically designed to circumvent an LLM’s safety alignment training and elicit responses that are harmful, unethical, illegal, or otherwise prohibited by the model’s safety guidelines (Xhonneux et al., 2024). Examples include prompts using role-playing scenarios, hypothetical situations, or character encodings to trick the model. Evaluating performance on these benchmarks (often using ASR or Compliance Ratio) is crucial for assessing the effectiveness of safety measures.
- R2ATA (Gan et al., 2024): This benchmark focuses on the robustness of LLM reasoning capabilities. It uses the Adversarial Typo Attack (ATA) algorithm to introduce minimal, targeted typographical errors into reasoning problems (from datasets like GSM8K, BBH, MMLU). It then measures the degradation in the LLM’s ability to perform correct step-by-step reasoning (Chain-of-Thought) and arrive at the right answer.

Adversarial benchmarks, while primarily focused on inducing misclassification or safety failures, can inadvertently trigger hallucinations. Attacks that manipulate reasoning processes or push models into unusual states via jailbreaking prompts (Gan et al., 2024; Zhou et al., 2024a) might cause them to generate factually incorrect or nonsensical outputs as a byproduct of the attack’s success or the model’s attempt to handle the confusing input. Evaluating factuality metrics on adversarial datasets can provide insights into how robust a model’s factual grounding is when under direct attack.

### 5.2.2 OOD Benchmarks

OOD benchmarks are designed to evaluate how well LLMs generalize their capabilities to data drawn from distributions that differ from their training data. This tests robustness against natural shifts encountered in the real world.

- BOSS (Benchmark suite for Out-of-distribution robustneSS): BOSS 8 is a notable effort to create a more challenging and holistic OOD evaluation suite for NLP. It covers five diverse tasks: Sentiment Analysis (SA), Toxic Detection (TD), Natural Language Inference (NLI), Named Entity Recognition (NER), and Extractive Question Answering (EQA) (Yuan et al., 2023). For each task, BOSS includes one large, diverse In-Distribution (ID) dataset (e.g., Amazon reviews for SA, MNLI for NLI, SQuAD for EQA) and three corresponding OOD datasets (Yuan et al., 2023). The OOD datasets are carefully selected based on a protocol that prioritizes: (1) distinct data sources/domains to ensure low semantic similarity (measured via SimCSE) with the ID set and (2) evidence of a significant performance drop for a baseline model trained on the ID set, indicating a challenging distribution shift (Yuan et al., 2023). Examples of OOD datasets included are Dynasent, SemEval (SA); ANLI, ContractNLI, WANLI (NLI); AdvQA, NewsQA, SearchQA (EQA) (Yuan et al., 2023).
- ANLI (Adversarial NLI): Created through an iterative human-and-model-in-the-loop process, ANLI contains NLI examples specifically designed to be difficult for contemporary models. Due to its challenging nature and distinct creation process, it is frequently used as an OOD benchmark for NLI task generalization (Yuan et al., 2023).
- Dynasent: A sentiment analysis dataset generated dynamically using adversarial methods to create challenging examples that models trained on standard sentiment datasets might misclassify (Yuan et al., 2023).
- WANLI: An NLI dataset synthesized using GPT-3, focusing on challenging linguistic patterns that models often struggle with in datasets like MNLI (Yuan et al., 2023).
- OODRobustBench (Li et al., 2024a): This is a comprehensive benchmark to evaluate adversarial robustness under dataset and threat distribution shifts. Further, this benchmark demonstrates that adversarial robustness suffers significant degradation under distribution shifts, yet in-distribution robustness correlates strongly and linearly with out-of-distribution robustness.



### 5.2.3 Consistency/Prompt Robustness Benchmarks

These benchmarks focus on evaluating the stability of LLM outputs when faced with variations in prompt formulation or non-deterministic sampling, testing whether the model’s behaviour is sensitive to superficial changes.

- **SCORE (Systematic Consistency and Robustness Evaluation):** SCORE (Nalbandyan et al., 2025) provides a framework for non-adversarial robustness evaluation. It assesses models on existing benchmarks (like MMLU-Pro, AGIEval, MATH) under three specific perturbation scenarios :
  - **Prompt Robustness:** Testing with 10 different non-adversarial, semantically equivalent prompts for each question, varying structure and including Chain-of-Thought (CoT) variations.
  - **Non-Greedy Inference:** Evaluating consistency across 5 runs using the same prompt but with temperature sampling ( $T=0.7$ ) and different random seeds.
  - **Choice Order Robustness:** For MCQ datasets, shuffling the order of answer choices while keeping the correct answer logically in the same position. SCORE reports the range (min/max) of accuracy across these scenarios and the overall Consistency Rate (CR) (Nalbandyan et al., 2025).
- **Paraphrasing Benchmarks:** Methodologies that involve generating multiple paraphrased versions of instructions or queries and measuring the consistency of the LLM’s responses (Barbero et al., 2025). This directly tests robustness to linguistic variation.
- **Structural Variation Tests:** Evaluating how changes in prompt structure, such as altering the position of the question within the prompt (beginning, middle, end), affect model performance and consistency (Nalbandyan et al., 2025).

### 5.2.4 Fairness/Bias Robustness Benchmarks

These benchmarks are specifically designed to assess whether LLMs maintain fairness and avoid biased outputs when subjected to stress or adversarial prompts intended to provoke bias.

- **FLEX (Fairness Benchmark in LLM under Extreme Scenarios):** FLEX (Jung et al., 2025) focuses on the robustness of fairness. It takes samples from existing fairness benchmarks (like BBQ, CrowS-Pairs, StereoSet) where baseline models typically provide unbiased responses. It then applies adversarial prompts using techniques like persona injection (instructing the LLM to adopt a biased persona), competing objectives (presenting conflicting goals that might induce bias), or text attacks (subtle manipulations of the input) (Jung et al., 2025). FLEX evaluates whether the model maintains its unbiased stance even under these extreme, bias-inducing conditions.

### 5.2.5 Task-Specific Robustness Benchmarks

These benchmarks evaluate robustness in the context of particular downstream applications where unique failure modes might exist.

- **Reasoning:**
  - **ReClor-plus, LogiQA-plus, LogiQAv2-plus** (Bao et al., 2025): These extend standard logical reasoning datasets (ReClor, LogiQA, LogiQAv2) by introducing structural variations to the multiple-choice questions. These variations include randomly shuffling the answer options or replacing the correct answer with a “none of the other options is correct” choice, testing if the model relies on superficial patterns or truly understands the logic (Bao et al., 2025).
  - **R2ATA** (Gan et al., 2024): Assesses reasoning robustness specifically against adversarial typographical errors introduced into the problem statements of reasoning tasks (Gan et al., 2024).
- **Code Generation:**

- CoderEval (Li et al., 2025d): While primarily a code generation benchmark, it has been used in studies focusing on code robustness issues beyond simple functional correctness, such as identifying missing input validation or error handling checks by comparing generated code to human references (Li et al., 2025d).
- Benchmarks evaluating robustness to perturbations in the natural language instructions provided for code generation tasks are also emerging (Barbero et al., 2025).

### 5.2.6 Hallucination/Factuality Benchmarks

This category includes benchmarks explicitly created to measure an LLM’s tendency to hallucinate or its ability to adhere to factual knowledge.

- TruthfulQA: This benchmark (Cecchini et al., 2024) is designed to measure whether LLMs are truthful in generating answers to questions where humans often hold common misconceptions. It tests if models avoid repeating false beliefs prevalent in their training data, distinguishing truthfulness from mere imitation (Yang et al., 2025a). It is also used widely for evaluating factuality robustness with an updated version, TruthfulQA-Enhanced (Yang et al., 2025a).
- HaluEval: A large-scale benchmark (35,000 samples) focusing on the LLM’s ability to recognize hallucinations (Li et al., 2023). It includes generated and human-annotated samples across QA, knowledge-grounded dialogue, text summarization, and general user queries. Models are evaluated on their ability to correctly classify provided text as containing hallucinations (“Yes”) or not (“No”).
- FELM (Factuality Evaluation of large Language Models): FELM (Chen et al., 2023b) provides fine-grained, segment-level factuality annotations for LLM-generated responses. For each segment, human annotators provide a factuality label (correct/incorrect), identify the error type if incorrect, and list reference links supporting the judgment. It covers diverse domains including world knowledge, science, math, and reasoning.
- FACTOR: This benchmark (Muhlgay et al., 2024) automatically transforms a given factual corpus (e.g., Wikipedia, news articles) into a set of evaluation instances. Each instance consists of a context, a factually correct completion, and several plausible but factually incorrect variations (generated based on different error types like entity substitution, negation, and numerical errors). It evaluates an LM by measuring whether it assigns a higher likelihood (probability) to the factually correct completion compared to all the incorrect alternatives in a generation setting (Muhlgay et al., 2024).
- DefAn: A large dataset (75k prompts) across eight domains (including Sports, Census data, Nobel Prize) designed to elicit definitive, concise factual answers (Rahman et al., 2024). It evaluates three aspects: Factual Contradiction Hallucination (FCH rate - % of responses with incorrect facts), Prompt Misalignment Hallucination (PMH rate - % of responses deviating from prompt instructions/format), and Response Consistency (RC - consistency of claims across 15 paraphrased prompts) (Rahman et al., 2024).
- UMWP (Unanswerable Math Word Problem): This benchmark (Sun et al., 2024a) evaluates hallucination in the context of mathematical reasoning. It consists of math word problems that are intentionally designed to be unanswerable (e.g., due to missing information). It tests whether LLMs correctly identify these problems as unanswerable or if they hallucinate by attempting to provide a numerical solution.
- Code Hallucination Benchmarks (HalluCode, CodeHalu, Collu-Bench): These benchmarks (Liu et al., 2024a) are specifically designed for the code domain. They often include taxonomies of code-specific hallucinations (e.g., intent conflicting, context inconsistency, dead code, knowledge conflicting (Liu et al., 2024a); mapping, naming, resource, logic hallucinations (Tian et al., 2025)). They evaluate an LLM’s ability to generate correct code and/or recognize hallucinations in generated code snippets. Collu-Bench, for instance, focuses on predicting hallucination locations based on generation log probabilities and execution feedback (Jiang et al., 2024).

- **Multimodal Hallucination Benchmarks** (AMBER, POPE, MME, HQHBench, ODE, etc.): These benchmarks evaluate hallucinations in MLLMs, where the generated text might conflict with the provided visual (or other modality) input (Bai et al., 2025b).
  - AMBER (Bai et al., 2025b; Wang et al., 2024b) is notable for being an LLM-free benchmark. It uses carefully annotated images and an automated pipeline to evaluate MLLM hallucinations across both generative and discriminative tasks, covering existence (object presence), attribute (object properties), and relation (spatial/contact relations between objects) hallucinations without relying on another LLM for judgment (Wang et al., 2024b). While other benchmarks like ODE (Tu et al., 2024) propose a dynamic, open-set protocol to generate novel evaluation samples and mitigate data contamination.
- **Evaluating Hallucination under Stress:** While the benchmarks listed above are primarily designed to elicit or detect hallucinations, they form the basis for evaluating factuality robustness under stress. This can be achieved by:
  - Applying stress conditions (e.g., adding noise, using OOD contexts, applying adversarial perturbations) to the prompts or inputs of these benchmarks (e.g., stressing TruthfulQA or HaluEval inputs).
  - Measuring the change in hallucination rates using appropriate metrics (under standard conditions versus stress conditions). Benchmarks like UMWP or DefAn inherently contain challenging conditions designed to probe these factuality limits.

The diversity of these hallucination benchmarks highlights the complexity of the phenomenon. Some test the generation of truthful content (TruthfulQA, FACTOR, DefAn), while others test the recognition of flawed content (HaluEval, HalluCode recognition tasks). They cover different domains (general knowledge, dialogue, code, math, multimodal) and rely on different evaluation paradigms (reference-based, reference-free, likelihood-based, classification-based). A comprehensive assessment of an LLM’s factuality and hallucination tendencies requires leveraging multiple benchmarks that cover these different facets (Liu et al., 2024a). Furthermore, the field is actively evolving to address in traditional static benchmarks. There is a noticeable trend towards developing benchmarks that are dynamic (generating test cases on-the-fly to prevent contamination, e.g., ODE, DyVal) (Tu et al., 2024), LLM-free (avoiding reliance on potentially unreliable LLM judges, e.g., AMBER) (Wang et al., 2024b). These advancements aim to improve the reliability and validity of LLM robustness evaluations.

## 6 Discussion

The topic of robustness of LLMs intersects with several active research areas, leading to a growing body of survey papers and literature reviews. These works provide valuable context and consolidate findings within specific sub-domains or from particular perspectives. Acknowledging and synthesizing these existing reviews is crucial for understanding the broader landscape.

Numerous surveys cover LLMs in general, often touching upon robustness as one aspect among many. A significant number focus on the concept of Trustworthiness in LLMs, consistently positioning robustness as a key pillar alongside fairness, safety, transparency, accountability, privacy, and ethics (Zhao et al., 2025; Aljohani et al., 2025). These trustworthiness surveys emphasize that robustness is essential for achieving reliable and ethically sound deployment, particularly in sensitive applications like healthcare. Some adopt a lifecycle or module-oriented taxonomy (input, model, toolchain, output) to analyze risks, including robustness failures, and discuss mitigations stage-by-stage. Specific dimensions of robustness have also received dedicated survey attention. For instance, adversarial robustness is a frequent topic, with reviews covering attack taxonomies (e.g., character-, word-, sentence-level), defence mechanisms like adversarial training, and evaluation methods. Surveys focusing on Multimodal LLMs (MLLMs) highlight the unique challenges posed by inter-modality dependencies and cross-modal attacks (Jiang et al., 2025). Out-of-Distribution (OOD) Robustness in NLP is another area with dedicated reviews, discussing different types of distribution shifts, benchmark limitations, and evaluation protocols (Lu et al., 2024). The challenge of Shortcut Learning has

also been surveyed extensively, identifying it as a fundamental problem underlying poor generalization and adversarial vulnerability in language models (Du et al., 2022). These surveys often categorize types of shortcuts (lexical, syntactic, etc.), discuss their origins in data and training, and review detection and mitigation techniques. Additionally, surveys on Data Augmentation for NLP often discuss its role in improving model robustness. Resources like the Awesome-LLM-Uncertainty-Reliability-Robustness repository also compile relevant papers and categorize them under headings like Invariance, Distribution Shift, OOD, Adversarial, etc. (Ding et al., 2024; Zhang, 2023).

Synthesizing across these diverse surveys reveals several recurring themes and key findings:

- **Centrality of Data Issues:** Surveys consistently point to data quality, biases, and artifacts as primary sources of non-robustness, particularly through the mechanism of shortcut learning (Du et al., 2022).
- **Limitations of Standard Training:** The inadequacy of standard ERM training for robustness and the challenges introduced by alignment procedures (like RLHF and the associated alignment tax) are common discussion points.
- **Need for Better Evaluation:** A widespread consensus exists on the limitations of current evaluation practices and the need for more challenging, standardized, and comprehensive benchmarks and metrics for robustness (Ailem et al., 2024).
- **Diversity of Mitigation:** Surveys showcase a wide array of mitigation strategies spanning the entire LLM lifecycle, reinforcing the idea that robustness requires a multi-faceted approach.

The existence of numerous surveys, while indicating intense research activity, also suggests a potentially fragmented landscape where different communities might use varying terminology or focus on specific aspects of the broader robustness problem. For example, issues discussed under “shortcut learning” are directly relevant to “OOD generalization” and “adversarial vulnerability” (Shaw et al., 2025). A key contribution of a comprehensive survey like this one is to bridge these perspectives and synthesize the common underlying principles and challenges. Furthermore, existing surveys often highlight gaps and open questions that remain pertinent. The lack of unified definitions and practical frameworks for operationalising trustworthiness (including robustness) is noted (de Cerqueira et al., 2025). The difficulty in evaluating generative tasks robustly is frequently mentioned. Understanding and mitigating more subtle or complex shortcuts beyond simple lexical cues remains an area for research (Howe et al., 2025; Zhou et al., 2024c; Yuan et al., 2023). Finally, ensuring that robustness improvements scale effectively with increasing model size is an ongoing concern.

## 7 Challenges and Future work

The field has made notable progress in identifying and characterizing robustness challenges in LLMs. While awareness of these vulnerabilities is now widespread, and numerous mitigation strategies and evaluation frameworks have emerged, even state-of-the-art LLMs demonstrate brittleness across critical dimensions. Robustness does not consistently correlate with model scale as larger models are not inherently more robust, and scaling trends often show weak or inconsistent patterns (Zhou et al., 2024c; Yang et al., 2024d). Safety-aligned models remain susceptible to sophisticated jailbreaking attempts, while performance may deteriorate sharply with minor distribution shifts or input perturbations (Oh & Demberg, 2025; Yuan et al., 2023). Ultimately, achieving comprehensive and reliable robustness persists as a fundamental challenge for the field.

**Major Challenges and Limitations** Several key challenges that hinder progress towards truly robust LLMs are:

1. **Scalability of Defences:** Many promising defence mechanisms, particularly those involving adversarial example generation during training (AT) or complex inference-time checks, are computationally expensive and may not scale efficiently to trillion-parameter models (Lee et al., 2024b; Howe et al., 2025). Ensuring robustness improvements keep pace with model scaling is crucial but not guaranteed.

2. **Robustness-Utility Trade-offs:** Aggressively optimizing for robustness can often negatively impact the model’s general capabilities or performance on clean, standard tasks (Lin et al., 2024b; Lee et al., 2024b). The alignment tax associated with RLHF is a prime example of it. Finding the right balance and developing methods that improve robustness without sacrificing utility is a critical ongoing challenge.
3. **Evaluation Gaps:** Current evaluation methodologies have limitations. There is a need for more comprehensive benchmarks covering a wider range of robustness dimensions simultaneously, including more subtle and complex failure modes (e.g., sophisticated shortcuts). Evaluating the robustness of generative capabilities remains particularly difficult compared to classification tasks (Ailem et al., 2024). Ensuring benchmarks are realistic, efficient, and resistant to “teaching to the test” is also vital.
4. **Theoretical Understanding:** Our theoretical understanding of why LLMs exhibit certain robustness failures like shortcut learning, understanding how model architecture (e.g., attention mechanisms, MoE) influences robustness and vulnerabilities or the alignment tax and why certain defences work is still developing (Ye et al., 2024). Deeper theoretical insights could guide the development of more principled and effective mitigation strategies.
5. **Real-world Deployment:** Translating robustness improvements observed on static benchmarks into reliable performance in dynamic, open-world environments with continuous distribution shifts and novel, unforeseen threats remains a significant hurdle. Bridging this gap is essential for trustworthy deployment.

**Robust Evaluation Methodologies:** A critical need exists for more reliable, comprehensive, and standardized benchmarks and evaluation protocols.<sup>52</sup> This includes developing robust LLM judges <sup>59</sup>, methods for verifying judge outputs <sup>52</sup>, and metrics that capture real-world failure modes more effectively.<sup>29</sup>

**Future Research Directions** Addressing these challenges points towards several promising avenues for future research:

1. **Causal and Invariant Learning:** Moving beyond correlational learning towards models that understand underlying causal relationships or learn representations that are inherently invariant to changes in domain or distribution (Ye et al., 2024). This could lead to more fundamentally robust models less reliant on spurious cues.
2. **Compositional Robustness:** Investigating how models behave under combinations of different perturbations (e.g., noisy input + OOD context + adversarial prompt) and developing methods to ensure robustness in such complex scenarios.
3. **Hybrid Approach:** Exploring hybrid approaches that combine multiple processing steps, as well as investigating methods to optimize their computational efficiency, are promising directions for advancing the field and ensuring the safe and reliable deployment of large language models in a wide range of real-world applications.
4. **Efficient Robust Training and Alignment:** Developing more scalable adversarial training methods (e.g., improving continuous AT), more efficient robust optimization techniques, and alignment methods (like RLHF variants) that explicitly minimize the alignment tax or are inherently more robust to reward model imperfections (e.g., reward-robust RLHF) (Yan et al., 2024b).
5. **Adaptive and Automated Evaluation:** The field must prioritize evaluating evaluation methods themselves, specifically, by assessing the reliability, validity, and biases inherent in existing benchmarks and automated metrics. Furthermore, there is a critical need to develop dynamic evaluation platforms and automated red-teaming methods capable of continuously probing models for weaknesses, adapting to emerging attack strategies, and delivering realistic, ongoing assessments of robustness.

6. **Improving Benchmarks:** To advance benchmarking practices, future efforts should prioritize comprehensive benchmarks that cover a broader range of tasks, domains, languages, modalities (e.g., text, images, or audio), and robustness challenges. These benchmarks should dynamically generate test cases during evaluation to prevent data leakage and rigorously assess adaptability. Equally critical is ensuring benchmarks mirror real-world conditions, such as natural distribution shifts, complex user interactions, and multifaceted failure modes, rather than relying on simplistic, artificial perturbations. Finally, rigorous validation is needed to confirm that benchmarks accurately measure the capabilities they claim to evaluate, avoiding misaligned or inflated performance metrics.
7. **Robustness in Multimodal and Agentic Systems:** Extending robustness research to the unique challenges of MLLMs and emerging LLM-based agent systems, considering factors like tool use, memory, and interaction with environments (Jiang et al., 2025; Yu et al., 2025).
8. **Interpretability for Robustness:** Leveraging interpretability techniques to better understand why models fail in specific robustness scenarios (e.g., identifying responsible components (Yang et al., 2025b) or internal representations of truth/lies (Bürger et al., 2024)) and using these insights to design targeted interventions or more robust architectures like a reconstruction attack (Stacey et al., 2024; 2022).

In conclusion, while LLMs have demonstrated transformative potential, ensuring their robustness is paramount for realizing this potential responsibly. The field has made substantial progress in identifying vulnerabilities and developing initial solutions, but significant challenges remain. Future work focusing on fundamental understanding (causality, invariance), efficient and scalable robust training methods, comprehensive and adaptive evaluation, and extending robustness considerations to newer paradigms like MLLMs and agents will be crucial for building truly reliable and trustworthy AI systems required for widespread societal integration.

While LLMs have demonstrated transformative capabilities, ensuring their robustness remains critical for safe and responsible real-world adoption. Though the field has advanced significantly in diagnosing vulnerabilities and proposing mitigation strategies, fundamental challenges persist. Future progress will depend on four key priorities: (1) deepening theoretical insights into causality and invariance, (2) developing efficient robust training frameworks that scale with model size, (3) creating adaptive evaluation systems that address evolving failure modes, and (4) extending robustness principles to emerging paradigms like multimodal LLMs (MLLMs) and autonomous AI agents. Addressing these challenges systematically will be essential to transition from promising prototypes to trustworthy, reliably deployable AI systems.

## 8 Conclusion

The field of robust LLMs has moved rapidly from adapting existing ML techniques to developing LLM-specific strategies that address unique challenges like instruction following, alignment, and scalability. In light of these developments, this survey offers a comprehensive overview of Large Language Model (LLM) robustness, a critical factor in ensuring their trustworthiness and reliable deployment. We define LLM robustness as a multi-faceted concept that encompasses resilience to adversarial attacks, generalization to out-of-distribution data, stability under prompt variations, tolerance to noisy inputs, and output consistency. Our analysis highlights that non-robustness arises from systemic issues spanning the entire LLM lifecycle. We then categorize methods to mitigate these vulnerabilities into four groups based on their deployment stage. Furthermore, we evaluate widely used metrics and benchmarks that have been employed to assess LLM performance across diverse dimensions in recent research. Finally, we outline key challenges for future work, with the goal of advancing LLM reliability and enabling their safe, real-world application.

## References

Aryan Agrawal, Lisa Alazraki, Shahin Honarvar, and Marek Rei. Enhancing llm robustness to perturbed instructions: An empirical study, 2025. URL <https://arxiv.org/abs/2504.02733>.



- Guardrails AI. Guardrails: A python framework for reliable ai applications. <https://github.com/guardrails-ai/guardrails>, 2025. Accessed: 2025-05-16.
- Melissa Ailem, Katerina Marazopoulou, Charlotte Siska, and James Bono. Examining the robustness of llm evaluation to the distributional assumptions of benchmarks, 2024. URL <https://arxiv.org/abs/2404.16966>.
- Manar Aljohani, Jun Hou, Sindhura Kommu, and Xuan Wang. A comprehensive survey on the trustworthiness of large language models in healthcare, 2025. URL <https://arxiv.org/abs/2502.15871>.
- Badr AlKhamissi, Millicent Li, Asli Celikyilmaz, Mona Diab, and Marjan Ghazvininejad. A review on language models as knowledge bases, 2022. URL <https://arxiv.org/abs/2204.06031>.
- Enes Altinisik, Hassan Sajjad, Husrev Sencar, Safa Messaoud, and Sanjay Chawla. Impact of adversarial training on robustness and generalizability of language models. In Anna Rogers, Jordan Boyd-Graber, and Naoaki Okazaki (eds.), *Findings of the Association for Computational Linguistics: ACL 2023*, pp. 7828–7840, Toronto, Canada, July 2023. Association for Computational Linguistics. doi: 10.18653/v1/2023.findings-acl.496. URL <https://aclanthology.org/2023.findings-acl.496/>.
- Usman Anwar, Johannes Von Oswald, Louis Kirsch, David Krueger, and Spencer Frei. Adversarial robustness of in-context learning in transformers for linear regression, 2024. URL <https://arxiv.org/abs/2411.05189>.
- Suyoung Bae, Hyojun Kim, YunSeok Choi, and Jee-Hyong Lee. Salad: Improving robustness and generalization through contrastive learning with structure-aware and llm-driven augmented data, 2025. URL <https://arxiv.org/abs/2504.12185>.
- Shuai Bai, Keqin Chen, Xuejing Liu, Jialin Wang, Wenbin Ge, Sibao Song, Kai Dang, Peng Wang, Shijie Wang, Jun Tang, Humen Zhong, Yuanzhi Zhu, Mingkun Yang, Zhaohai Li, Jianqiang Wan, Pengfei Wang, Wei Ding, Zheren Fu, Yiheng Xu, Jiabo Ye, Xi Zhang, Tianbao Xie, Zesen Cheng, Hang Zhang, Zhibo Yang, Haiyang Xu, and Junyang Lin. Qwen2.5-vl technical report, 2025a. URL <https://arxiv.org/abs/2502.13923>.
- Tao Bai, Jinqi Luo, Jun Zhao, Bihan Wen, and Qian Wang. Recent advances in adversarial training for adversarial robustness, 2021a. URL <https://arxiv.org/abs/2102.01356>.
- Xiang Bai, Rishi Bommasani, Michihiro Yasunaga, et al. Societal implications of foundation models. *SSRN Electronic Journal*, 2021b. doi: 10.2139/ssrn.3974887. URL [https://papers.ssrn.com/sol3/papers.cfm?abstract\\_id=3974887](https://papers.ssrn.com/sol3/papers.cfm?abstract_id=3974887).
- Zechen Bai, Pichao Wang, Tianjun Xiao, Tong He, Zongbo Han, Zheng Zhang, and Mike Zheng Shou. Hallucination of multimodal large language models: A survey, 2025b. URL <https://arxiv.org/abs/2404.18930>.
- Yejin Bang, Samuel Cahyawijaya, Nayeon Lee, Wenliang Dai, Dan Su, Bryan Wilie, Holy Lovenia, Ziwei Ji, Tiezheng Yu, Willy Chung, Quyet V. Do, Yan Xu, and Pascale Fung. A multitask, multilingual, multimodal evaluation of chatgpt on reasoning, hallucination, and interactivity, 2023. URL <https://arxiv.org/abs/2302.04023>.
- Qiming Bao, Gael Gendron, Alex Yuxuan Peng, Wanjun Zhong, Neset Tan, Yang Chen, Michael Witbrock, and Jiamou Liu. Assessing and enhancing the robustness of large language models with task structure variations for logical reasoning, 2025. URL <https://arxiv.org/abs/2310.09430>.
- Federico Barbero, Álvaro Arroyo, Xiangming Gu, Christos Perivolaropoulos, Michael Bronstein, Petar Veličković, and Razvan Pascanu. Why do llms attend to the first token?, 2025. URL <https://arxiv.org/abs/2504.02732>.
- Logan Barnhart, Reza Akbarian Bafghi, Stephen Becker, and Maziar Raissi. Aligning to what? limits to rlhf based alignment, 2025. URL <https://arxiv.org/abs/2503.09025>.

- Tommaso Bendinelli, Artur Dox, and Christian Holz. Exploring llm agents for cleaning tabular machine learning datasets, 2025. URL <https://arxiv.org/abs/2503.06664>.
- Tim Beyer, Sophie Xhonneux, Simon Geisler, Gauthier Gidel, Leo Schwinn, and Stephan Günnemann. Llm-safety evaluations lack robustness, 2025. URL <https://arxiv.org/abs/2503.02574>.
- Rohan Bhambhoria, Samuel Dahan, Jonathan Li, and Xiaodan Zhu. Evaluating ai for law: Bridging the gap with open-source solutions, 2024. URL <https://arxiv.org/abs/2404.12349>.
- Tom B. Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, Sandhini Agarwal, Ariel Herbert-Voss, Gretchen Krueger, Tom Henighan, Rewon Child, Aditya Ramesh, Daniel M. Ziegler, Jeffrey Wu, Clemens Winter, Christopher Hesse, Mark Chen, Eric Sigler, Mateusz Litwin, Scott Gray, Benjamin Chess, Jack Clark, Christopher Berner, Sam McCandlish, Alec Radford, Ilya Sutskever, and Dario Amodei. Language models are few-shot learners, 2020. URL <https://arxiv.org/abs/2005.14165>.
- Lennart Bürger, Fred A. Hamprecht, and Boaz Nadler. Truth is universal: Robust detection of lies in LLMs. In *The Thirty-eighth Annual Conference on Neural Information Processing Systems*, 2024. URL <https://openreview.net/forum?id=1Fc2Xa2cDK>.
- Riccardo Cantini, Alessio Orsino, Massimo Ruggiero, and Domenico Talia. Benchmarking adversarial robustness to bias elicitation in large language models: Scalable automated assessment with llm-as-a-judge, 2025. URL <https://arxiv.org/abs/2504.07887>.
- David Cecchini, Arshaan Nazir, Kalyan Chakravarthy, and Veysel Kocaman. Holistic evaluation of large language models: Assessing robustness, accuracy, and toxicity for real-world applications. In Anaelia Ovalle, Kai-Wei Chang, Yang Trista Cao, Ninareh Mehrabi, Jieyu Zhao, Aram Galstyan, Jwala Dhamala, Anoop Kumar, and Rahul Gupta (eds.), *Proceedings of the 4th Workshop on Trustworthy Natural Language Processing (TrustNLP 2024)*, pp. 109–117, Mexico City, Mexico, June 2024. Association for Computational Linguistics. doi: 10.18653/v1/2024.trustnlp-1.11. URL <https://aclanthology.org/2024.trustnlp-1.11/>.
- Samuel Jacob Chacko, Sajib Biswas, Chashi Mahiul Islam, Fatema Tabassum Liza, and Xiuwen Liu. Adversarial attacks on large language models using regularized relaxation, 2024. URL <https://arxiv.org/abs/2410.19160>.
- Junyi Chai and Xiaoqian Wang. Fairness with adaptive weights. In Kamalika Chaudhuri, Stefanie Jegelka, Le Song, Csaba Szepesvari, Gang Niu, and Sivan Sabato (eds.), *Proceedings of the 39th International Conference on Machine Learning*, volume 162 of *Proceedings of Machine Learning Research*, pp. 2853–2866. PMLR, 07 2022. URL <https://proceedings.mlr.press/v162/chai22a.html>.
- Daoyuan Chen, Yilun Huang, Zhijian Ma, Heseng Chen, Xuchen Pan, Ce Ge, Dawei Gao, Yuexiang Xie, Zhaoyang Liu, Jinyang Gao, Yaliang Li, Bolin Ding, and Jingren Zhou. Data-juicer: A one-stop data processing system for large language models, 2023a. URL <https://arxiv.org/abs/2309.02033>.
- Liang Chen, Li Shen, Yang Deng, Xiaoyan Zhao, Bin Liang, and Kam-Fai Wong. Pearl: Towards permutation-resilient llms, 2025a. URL <https://arxiv.org/abs/2502.14628>.
- Shiqi Chen, Yiran Zhao, Jinghan Zhang, I-Chun Chern, Siyang Gao, Pengfei Liu, and Junxian He. FELM: Benchmarking factuality evaluation of large language models. In *Thirty-seventh Conference on Neural Information Processing Systems Datasets and Benchmarks Track*, 2023b. URL <https://openreview.net/forum?id=jS07Vgolc6>.
- Yen-Chun Chen, Zhe Gan, Yu Cheng, Jingzhou Liu, and Jingjing Liu. Distilling knowledge learned in bert for text generation, 2020. URL <https://arxiv.org/abs/1911.03829>.
- Yulin Chen, Haoran Li, Yuan Sui, Yue Liu, Yufei He, Yangqiu Song, and Bryan Hooi. Robustness via referencing: Defending against prompt injection attacks by referencing the executed instruction, 2025b. URL <https://arxiv.org/abs/2504.20472>.

- Yuyan Chen, Qiang Fu, Yichen Yuan, Zhihao Wen, Ge Fan, Dayiheng Liu, Dongmei Zhang, Zhixu Li, and Yanghua Xiao. Hallucination detection: Robustly discerning reliable answers in large language models, 2024. URL <https://arxiv.org/abs/2407.04121>.
- DongHyun Choi, Lucas Spangher, Chris Hidey, Peter Grabowski, and Ramy Eskander. Revisiting funnel transformers for modern llm architectures with comprehensive ablations in training and inference configurations, 2025. URL <https://arxiv.org/abs/2504.02877>.
- Paul Christiano, Jan Leike, Tom B. Brown, Miljan Martic, Shane Legg, and Dario Amodei. Deep reinforcement learning from human preferences, 2023. URL <https://arxiv.org/abs/1706.03741>.
- Leonardo Cotta and Chris J. Maddison. Test-time fairness and robustness in large language models, 2024. URL <https://arxiv.org/abs/2406.07685>.
- Jiaxi Cui, Munan Ning, Zongjian Li, Bohua Chen, Yang Yan, Hao Li, Bin Ling, Yonghong Tian, and Li Yuan. Chatlaw: A multi-agent collaborative legal assistant with knowledge graph enhanced mixture-of-experts large language model, 2024. URL <https://arxiv.org/abs/2306.16092>.
- Nico Daheim, Clara Meister, Thomas Möllenhoff, and Iryna Gurevych. Uncertainty-aware decoding with minimum bayes risk. In *The Thirteenth International Conference on Learning Representations*, 2025. URL <https://openreview.net/forum?id=hPpyUv1XyQ>.
- Sanjay Das, Swastik Bhattacharya, Souvik Kundu, Shamik Kundu, Anand Menon, Arnab Raha, and Kanad Basu. Genbfa: An evolutionary optimization approach to bit-flip attacks on llms, 2025. URL <https://arxiv.org/abs/2411.13757>.
- José Siqueira de Cerqueira, Kai-Kristian Kemell, Rebekah Rousi, Nannan Xi, Juho Hamari, and Pekka Abrahamsson. Mapping trustworthiness in large language models: A bibliometric analysis bridging theory to practice, 2025. URL <https://arxiv.org/abs/2503.04785>.
- DeepMind. Gemini 1 technical report. Google DeepMind Report, 2023. URL [https://storage.googleapis.com/deepmind-media/gemini/gemini\\_1\\_report.pdf](https://storage.googleapis.com/deepmind-media/gemini/gemini_1_report.pdf).
- DeepSeek-AI, Aixin Liu, Bei Feng, Bing Xue, Bingxuan Wang, Bochao Wu, Chengda Lu, Chenggang Zhao, Chengqi Deng, Chenyu Zhang, Chong Ruan, Damai Dai, Daya Guo, Dejian Yang, Deli Chen, Dongjie Ji, Erhang Li, Fangyun Lin, Fucong Dai, Fuli Luo, Guangbo Hao, Guanting Chen, Guowei Li, H. Zhang, Han Bao, Hanwei Xu, Haocheng Wang, Haowei Zhang, Honghui Ding, Huajian Xin, Huazuo Gao, Hui Li, Hui Qu, J. L. Cai, Jian Liang, Jianzhong Guo, Jiaqi Ni, Jiashi Li, Jiawei Wang, Jin Chen, Jingchang Chen, Jingyang Yuan, Junjie Qiu, Junlong Li, Junxiao Song, Kai Dong, Kai Hu, Kaige Gao, Kang Guan, Kexin Huang, Kuai Yu, Lean Wang, Lecong Zhang, Lei Xu, Leyi Xia, Liang Zhao, Litong Wang, Liyue Zhang, Meng Li, Miaojuan Wang, Mingchuan Zhang, Minghua Zhang, Minghui Tang, Mingming Li, Ning Tian, Panpan Huang, Peiyi Wang, Peng Zhang, Qiancheng Wang, Qihao Zhu, Qinyu Chen, Qiushi Du, R. J. Chen, R. L. Jin, Ruiqi Ge, Ruisong Zhang, Ruizhe Pan, Runji Wang, Runxin Xu, Ruoyu Zhang, Ruyi Chen, S. S. Li, Shanghao Lu, Shangyan Zhou, Shanhua Chen, Shaoqing Wu, Shengfeng Ye, Shengfeng Ye, Shirong Ma, Shiyu Wang, Shuang Zhou, Shuiping Yu, Shunfeng Zhou, Shutong Pan, T. Wang, Tao Yun, Tian Pei, Tianyu Sun, W. L. Xiao, Wangding Zeng, Wanbiao Zhao, Wei An, Wen Liu, Wenfeng Liang, Wenjun Gao, Wenqin Yu, Wentao Zhang, X. Q. Li, Xiangyue Jin, Xianzu Wang, Xiao Bi, Xiaodong Liu, Xiaohan Wang, Xiaojin Shen, Xiaokang Chen, Xiaokang Zhang, Xiaosha Chen, Xiaotao Nie, Xiaowen Sun, Xiaoxiang Wang, Xin Cheng, Xin Liu, Xin Xie, Xingchao Liu, Xingkai Yu, Xinnan Song, Xinxia Shan, Xinyi Zhou, Xinyu Yang, Xinyuan Li, Xuecheng Su, Xuheng Lin, Y. K. Li, Y. Q. Wang, Y. X. Wei, Y. X. Zhu, Yang Zhang, Yanhong Xu, Yanhong Xu, Yanping Huang, Yao Li, Yao Zhao, Yaofeng Sun, Yaohui Li, Yaohui Wang, Yi Yu, Yi Zheng, Yichao Zhang, Yifan Shi, Yiliang Xiong, Ying He, Ying Tang, Yishi Piao, Yisong Wang, Yixuan Tan, Yiyang Ma, Yiyuan Liu, Yongqiang Guo, Yu Wu, Yuan Ou, Yuchen Zhu, Yuduan Wang, Yue Gong, Yuheng Zou, Yujia He, Yukun Zha, Yunfan Xiong, Yunxian Ma, Yuting Yan, Yuxiang Luo, Yuxiang You, Yuxuan Liu, Yuyang Zhou, Z. F. Wu, Z. Z. Ren, Zehui Ren, Zhangli Sha, Zhe Fu, Zhean Xu, Zhen Huang, Zhen Zhang, Zhenda Xie, Zhengyan Zhang, Zhewen Hao, Zhibin Gou, Zhicheng Ma, Zhigang Yan, Zhihong Shao, Zhipeng Xu, Zhiyu Wu, Zhongyu Zhang, Zhuoshu Li,

- Zihui Gu, Zijia Zhu, Zijun Liu, Zilin Li, Ziwei Xie, Ziyang Song, Ziyi Gao, and Zizheng Pan. Deepseek-v3 technical report, 2025. URL <https://arxiv.org/abs/2412.19437>.
- Bosheng Ding, Chengwei Qin, Ruochen Zhao, Tianze Luo, Xinze Li, Guizhen Chen, Wenhan Xia, Junjie Hu, Anh Tuan Luu, and Shafiq Joty. Data augmentation using LLMs: Data perspectives, learning paradigms and challenges. In Lun-Wei Ku, Andre Martins, and Vivek Srikumar (eds.), *Findings of the Association for Computational Linguistics: ACL 2024*, pp. 1679–1705, Bangkok, Thailand, August 2024. Association for Computational Linguistics. doi: 10.18653/v1/2024.findings-acl.97. URL <https://aclanthology.org/2024.findings-acl.97/>.
- Guosheng Dong, Da Pan, Yiding Sun, Shusen Zhang, Zheng Liang, Xin Wu, Yanjun Shen, Fan Yang, Haoze Sun, Tianpeng Li, Mingan Lin, Jianhua Xu, Yufan Zhang, Xiaonan Nie, Lei Su, Bingning Wang, Wentao Zhang, Jiaxin Mao, Zenan Zhou, and Weipeng Chen. Baichuanseed: Sharing the potential of extensive data collection and deduplication by introducing a competitive large language model baseline, 2024a. URL <https://arxiv.org/abs/2408.15079>.
- Hanze Dong, Wei Xiong, Bo Pang, Haoxiang Wang, Han Zhao, Yingbo Zhou, Nan Jiang, Doyen Sahoo, Caiming Xiong, and Tong Zhang. Rlhf workflow: From reward modeling to online rlhf. *arXiv preprint arXiv:2405.07863*, 2024b.
- Xin Dong, Yaxin Zhu, Zuohui Fu, Dongkuan Xu, and Gerard de Melo. Data augmentation with adversarial training for cross-lingual NLI. In Chengqing Zong, Fei Xia, Wenjie Li, and Roberto Navigli (eds.), *Proceedings of the 59th Annual Meeting of the Association for Computational Linguistics and the 11th International Joint Conference on Natural Language Processing (Volume 1: Long Papers)*, pp. 5158–5167, Online, August 2021. Association for Computational Linguistics. doi: 10.18653/v1/2021.acl-long.401. URL <https://aclanthology.org/2021.acl-long.401/>.
- Mengnan Du, Fengxiang He, Na Zou, Dacheng Tao, and Xia Hu. Shortcut learning of large language models in natural language understanding, 2023. URL <https://arxiv.org/abs/2208.11857>.
- Yuxian Du, Fengxiang He, Yiming Liu, Zhilin Yang, and Jiliang Tang. Towards understanding and evaluating robustness of pre-trained language models for text classification. In *Proceedings of the 2022 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pp. 328–346. Association for Computational Linguistics, 2022. URL <https://fengxianghe.github.io/paper/du2022robustness.pdf>.
- Kawin Ethayarajh, Winnie Xu, Niklas Muennighoff, Dan Jurafsky, and Douwe Kiela. Kto: Model alignment as prospect theoretic optimization, 2024. URL <https://arxiv.org/abs/2402.01306>.
- Xiaojing Fan and Chunliang Tao. Towards resilient and efficient llms: A comparative study of efficiency, performance, and adversarial robustness, 2024. URL <https://arxiv.org/abs/2408.04585>.
- Esther Gan, Yiran Zhao, Liying Cheng, Yancan Mao, Anirudh Goyal, Kenji Kawaguchi, Min-Yen Kan, and Michael Shieh. Reasoning robustness of llms to adversarial typographical errors, 2024. URL <https://arxiv.org/abs/2411.05345>.
- Aparna Garimella, Akhash Amarnath, Kiran Kumar, Akash Pramod Yalla, Anandhavelu Natarajan, Niyati Chhaya, and Balaji Vasani Srinivasan. He is very intelligent, she is very beautiful? on mitigating social biases in language modelling and generation. In *Findings*, 2021. URL <https://api.semanticscholar.org/CorpusID:236477795>.
- Aaron Grattafiori, Abhimanyu Dubey, Abhinav Jauhri, Abhinav Pandey, Abhishek Kadian, Ahmad Al-Dahle, Aiesha Letman, Akhil Mathur, Alan Schelten, Alex Vaughan, Amy Yang, Angela Fan, Anirudh Goyal, Anthony Hartshorn, Aobo Yang, Archi Mitra, Archie Sravankumar, Artem Korenev, Arthur Hinsvark, Arun Rao, Aston Zhang, Aurelien Rodriguez, Austen Gregerson, Ava Spataru, Baptiste Roziere, Bethany Biron, Binh Tang, Bobbie Chern, Charlotte Caucheteux, Chaya Nayak, Chloe Bi, Chris Marra, Chris McConnell, Christian Keller, Christophe Touret, Chunyang Wu, Corinne Wong, Cristian Canton Ferrer, Cyrus Nikolaidis, Damien Allonsius, Daniel Song, Danielle Pintz, Danny Livshits, Danny Wyatt, David Esiobu, Dhruv Choudhary, Dhruv Mahajan, Diego Garcia-Olano, Diego Perino, Dieuwke Hupkes,

Egor Lakomkin, Ehab AlBadawy, Elina Lobanova, Emily Dinan, Eric Michael Smith, Filip Radenovic, Francisco Guzmán, Frank Zhang, Gabriel Synnaeve, Gabrielle Lee, Georgia Lewis Anderson, Govind Thattai, Graeme Nail, Gregoire Mialon, Guan Pang, Guillem Cucurell, Hailey Nguyen, Hannah Korevaar, Hu Xu, Hugo Touvron, Iliyan Zarov, Imanol Arrieta Ibarra, Isabel Kloumann, Ishan Misra, Ivan Evtimov, Jack Zhang, Jade Copet, Jaewon Lee, Jan Geffert, Jana Vranes, Jason Park, Jay Mahadeokar, Jeet Shah, Jelmer van der Linde, Jennifer Billock, Jenny Hong, Jenya Lee, Jeremy Fu, Jianfeng Chi, Jianyu Huang, Jiawen Liu, Jie Wang, Jiecao Yu, Joanna Bitton, Joe Spisak, Jongsoo Park, Joseph Rocca, Joshua Johnstun, Joshua Saxe, Junteng Jia, Kalyan Vasuden Alwala, Karthik Prasad, Kartikeya Upasani, Kate Plawiak, Ke Li, Kenneth Heafield, Kevin Stone, Khalid El-Arini, Krithika Iyer, Kshitiz Malik, Kuenley Chiu, Kunal Bhalla, Kushal Lakhotia, Lauren Rantala-Yearly, Laurens van der Maaten, Lawrence Chen, Liang Tan, Liz Jenkins, Louis Martin, Lovish Madaan, Lubo Malo, Lukas Blecher, Lukas Landzaat, Luke de Oliveira, Madeline Muzzi, Mahesh Pasupuleti, Mannat Singh, Manohar Paluri, Marcin Kardas, Maria Tsimpoukelli, Mathew Oldham, Mathieu Rita, Maya Pavlova, Melanie Kambadur, Mike Lewis, Min Si, Mitesh Kumar Singh, Mona Hassan, Naman Goyal, Narjes Torabi, Nikolay Bashlykov, Nikolay Bogoychev, Niladri Chatterji, Ning Zhang, Olivier Duchenne, Onur Çelebi, Patrick Alrassy, Pengchuan Zhang, Pengwei Li, Petar Vasic, Peter Weng, Prajjwal Bhargava, Pratik Dubal, Praveen Krishnan, Punit Singh Koura, Puxin Xu, Qing He, Qingxiao Dong, Ragavan Srinivasan, Raj Ganapathy, Ramon Calderer, Ricardo Silveira Cabral, Robert Stojnic, Roberta Raileanu, Rohan Maheswari, Rohit Girdhar, Rohit Patel, Romain Sauvestre, Ronnie Polidoro, Roshan Sumbaly, Ross Taylor, Ruan Silva, Rui Hou, Rui Wang, Saghar Hosseini, Sahana Chennabasappa, Sanjay Singh, Sean Bell, Seohyun Sonia Kim, Sergey Edunov, Shaoliang Nie, Sharan Narang, Sharath Raparthy, Sheng Shen, Shengye Wan, Shruti Bhosale, Shun Zhang, Simon Vandenhende, Soumya Batra, Spencer Whitman, Sten Sootla, Stephane Collot, Suchin Gururangan, Sydney Borodinsky, Tamar Herman, Tara Fowler, Tarek Sheasha, Thomas Georgiou, Thomas Scialom, Tobias Speckbacher, Todor Mihaylov, Tong Xiao, Ujjwal Karn, Vedanuj Goswami, Vibhor Gupta, Vignesh Ramanathan, Viktor Kerkez, Vincent Gonguet, Virginie Do, Vish Vogeti, Vitor Albiero, Vladan Petrovic, Weiwei Chu, Wenhan Xiong, Wenyin Fu, Whitney Meers, Xavier Martinet, Xiaodong Wang, Xiaofang Wang, Xiaoqing Ellen Tan, Xide Xia, Xinfeng Xie, Xuchao Jia, Xuwei Wang, Yaelle Goldschlag, Yashesh Gaur, Yasmine Babaei, Yi Wen, Yiwen Song, Yuchen Zhang, Yue Li, Yuning Mao, Zacharie Delpierre Coudert, Zheng Yan, Zhengxing Chen, Zoe Papakipos, Aaditya Singh, Aayushi Srivastava, Abha Jain, Adam Kelsey, Adam Shajnfeld, Adithya Gangidi, Adolfo Victoria, Ahuva Goldstand, Ajay Menon, Ajay Sharma, Alex Boesenberg, Alexei Baevski, Allie Feinstein, Amanda Kallet, Amit Sangani, Amos Teo, Anam Yunus, Andrei Lupu, Andres Alvarado, Andrew Caples, Andrew Gu, Andrew Ho, Andrew Poulton, Andrew Ryan, Ankit Ramchandani, Annie Dong, Annie Franco, Anuj Goyal, Aparajita Saraf, Arkabandhu Chowdhury, Ashley Gabriel, Ashwin Bharambe, Assaf Eisenman, Azadeh Yazdan, Beau James, Ben Maurer, Benjamin Leonhardi, Bernie Huang, Beth Loyd, Beto De Paola, Bhargavi Paranjape, Bing Liu, Bo Wu, Boyu Ni, Braden Hancock, Bram Wasti, Brandon Spence, Brani Stojkovic, Brian Gamido, Britt Montalvo, Carl Parker, Carly Burton, Catalina Mejia, Ce Liu, Changhan Wang, Changkyu Kim, Chao Zhou, Chester Hu, Ching-Hsiang Chu, Chris Cai, Chris Tindal, Christoph Feichtenhofer, Cynthia Gao, Damon Civin, Dana Beaty, Daniel Kreymer, Daniel Li, David Adkins, David Xu, Davide Testuggine, Delia David, Devi Parikh, Diana Liskovich, Didem Foss, Dingkang Wang, Duc Le, Dustin Holland, Edward Dowling, Eissa Jamil, Elaine Montgomery, Eleonora Presani, Emily Hahn, Emily Wood, Eric-Tuan Le, Erik Brinkman, Esteban Arcaute, Evan Dunbar, Evan Smothers, Fei Sun, Felix Kreuk, Feng Tian, Filippos Kokkinos, Firat Ozgenel, Francesco Caggioni, Frank Kanayet, Frank Seide, Gabriela Medina Florez, Gabriella Schwarz, Gada Badeer, Georgia Swee, Gil Halpern, Grant Herman, Grigory Sizov, Guangyi Zhang, Guna Lakshminarayanan, Hakan Inan, Hamid Shojanazeri, Han Zou, Hannah Wang, Hanwen Zha, Haroun Habeeb, Harrison Rudolph, Helen Suk, Henry Aspegren, Hunter Goldman, Hongyuan Zhan, Ibrahim Damlaj, Igor Molybog, Igor Tufanov, Ilias Leontiadis, Irina-Elena Veliche, Itai Gat, Jake Weissman, James Geboski, James Kohli, Janice Lam, Japhet Asher, Jean-Baptiste Gaya, Jeff Marcus, Jeff Tang, Jennifer Chan, Jenny Zhen, Jeremy Reizenstein, Jeremy Teboul, Jessica Zhong, Jian Jin, Jingyi Yang, Joe Cummings, Jon Carvill, Jon Shepard, Jonathan McPhie, Jonathan Torres, Josh Ginsburg, Junjie Wang, Kai Wu, Kam Hou U, Karan Saxena, Kartikay Khandelwal, Katayoun Zand, Kathy Matosich, Kaushik Veeraraghavan, Kelly Michelena, Keqian Li, Kiran Jagadeesh, Kun Huang, Kunal Chawla, Kyle Huang, Lailin Chen, Lakshya Garg, Lavender A, Leandro Silva, Lee Bell, Lei Zhang, Liangpeng Guo, Licheng Yu, Liron Moshkovich, Luca Wehrstedt, Madian Khabsa, Manav Avalani, Manish Bhatt, Martynas Mankus,



- Matan Hasson, Matthew Lennie, Matthias Reso, Maxim Groshev, Maxim Naumov, Maya Lathi, Meghan Keneally, Miao Liu, Michael L. Seltzer, Michal Valko, Michelle Restrepo, Mihir Patel, Mik Vyatskov, Mikayel Samvelyan, Mike Clark, Mike Macey, Mike Wang, Miquel Jubert Hermoso, Mo Metanat, Mohammad Rastegari, Munish Bansal, Nandhini Santhanam, Natascha Parks, Natasha White, Navyata Bawa, Nayan Singhal, Nick Egebo, Nicolas Usunier, Nikhil Mehta, Nikolay Pavlovich Laptev, Ning Dong, Norman Cheng, Oleg Chernoguz, Olivia Hart, Omkar Salpekar, Ozlem Kalinli, Parkin Kent, Parth Parekh, Paul Saab, Pavan Balaji, Pedro Rittner, Philip Bontrager, Pierre Roux, Piotr Dollar, Polina Zvyagina, Prashant Ratanchandani, Pritish Yuvraj, Qian Liang, Rachad Alao, Rachel Rodriguez, Rafi Ayub, Raghotham Murthy, Raghu Nayani, Rahul Mitra, Rangaprabhu Parthasarathy, Raymond Li, Rebekkah Hogan, Robin Battey, Rocky Wang, Russ Howes, Ruty Rinott, Sachin Mehta, Sachin Siby, Sai Jayesh Bondu, Samyak Datta, Sara Chugh, Sara Hunt, Sargun Dhillon, Sasha Sidorov, Satadru Pan, Saurabh Mahajan, Saurabh Verma, Seiji Yamamoto, Sharadh Ramaswamy, Shaun Lindsay, Sheng Feng, Shenghao Lin, Shengxin Cindy Zha, Shishir Patil, Shiva Shankar, Shuqiang Zhang, Shuqiang Zhang, Sinong Wang, Sneha Agarwal, Soji Sajuyigbe, Soumith Chintala, Stephanie Max, Stephen Chen, Steve Kehoe, Steve Satterfield, Sudarshan Govindaprasad, Sumit Gupta, Summer Deng, Sungmin Cho, Sunny Virk, Suraj Subramanian, Sy Choudhury, Sydney Goldman, Tal Remez, Tamar Glaser, Tamara Best, Thilo Koehler, Thomas Robinson, Tianhe Li, Tianjun Zhang, Tim Matthews, Timothy Chou, Tzook Shaked, Varun Vontimitta, Victoria Ajayi, Victoria Montanez, Vijai Mohan, Vinay Satish Kumar, Vishal Mangla, Vlad Ionescu, Vlad Poenaru, Vlad Tiberiu Mihailescu, Vladimir Ivanov, Wei Li, Wenchen Wang, Wenwen Jiang, Wes Bouaziz, Will Constable, Xiaocheng Tang, Xiaoqian Wu, Xiaolan Wang, Xilun Wu, Xinbo Gao, Yaniv Kleinman, Yanjun Chen, Ye Hu, Ye Jia, Ye Qi, Yenda Li, Yilin Zhang, Ying Zhang, Yossi Adi, Youngjin Nam, Yu, Wang, Yu Zhao, Yuchen Hao, Yundi Qian, Yunlu Li, Yuzi He, Zach Rait, Zachary DeVito, Zef Rosnbrick, Zhaoduo Wen, Zhenyu Yang, Zhiwei Zhao, and Zhiyu Ma. The llama 3 herd of models, 2024. URL <https://arxiv.org/abs/2407.21783>.
- Jiawei Gu, Xuhui Jiang, Zhichao Shi, Hexiang Tan, Xuehao Zhai, Chengjin Xu, Wei Li, Yinghan Shen, Shengjie Ma, Honghao Liu, Saizhuo Wang, Kun Zhang, Yuanzhuo Wang, Wen Gao, Lionel Ni, and Jian Guo. A survey on llm-as-a-judge, 2025. URL <https://arxiv.org/abs/2411.15594>.
- Kevin Gu, Eva Tuecke, Dmitriy Katz, Raya Horesh, David Alvarez-Melis, and Mikhail Yurochkin. Chared: Character-wise ensemble decoding for large language models, 2024. URL <https://arxiv.org/abs/2407.11009>.
- Zishan Guo, Renren Jin, Chuang Liu, Yufei Huang, Dan Shi, Supryadi, Linhao Yu, Yan Liu, Jiaxuan Li, Bojian Xiong, and Deyi Xiong. Evaluating large language models: A comprehensive survey, 2023. URL <https://arxiv.org/abs/2310.19736>.
- Aman Gupta, Shao Tang, Qingquan Song, Sirou Zhu, Jiwoo Hong, Ankan Saha, Viral Gupta, Noah Lee, Eunki Kim, Siyu Zhu, Parag Agrawal, Natesh Pillai, and S. Sathiya Keerthi. Alhappo – reward shape matters for llm alignment, 2025. URL <https://arxiv.org/abs/2501.03884>.
- Simeng Han, Hailey Schoelkopf, Yilun Zhao, Zhenting Qi, Martin Riddell, Wenfei Zhou, James Coady, David Peng, Yujie Qiao, Luke Benson, Lucy Sun, Alex Wardle-Solano, Hannah Szabo, Ekaterina Zubova, Matthew Burtell, Jonathan Fan, Yixin Liu, Brian Wong, Malcolm Sailor, Ansong Ni, Linyong Nan, Jungo Kasai, Tao Yu, Rui Zhang, Alexander R. Fabbri, Wojciech Kryscinski, Semih Yavuz, Ye Liu, Xi Victoria Lin, Shafiq Joty, Yingbo Zhou, Caiming Xiong, Rex Ying, Arman Cohan, and Dragomir Radev. Folio: Natural language reasoning with first-order logic, 2024. URL <https://arxiv.org/abs/2209.00840>.
- Michael Hassid, Tal Remez, Jonas Gehring, Roy Schwartz, and Yossi Adi. The larger the better? improved llm code-generation via budget reallocation, 2024. URL <https://arxiv.org/abs/2404.00725>.
- Kai He, Rui Mao, Qika Lin, Yucheng Ruan, Xiang Lan, Mengling Feng, and Erik Cambria. A survey of large language models for healthcare: from data, technology, and applications to accountability and ethics, 2025. URL <https://arxiv.org/abs/2310.05694>.
- Michael Heck, Christian Geisshauser, Nurul Lubis, Carel van Niekerk, Shutong Feng, Hsien-Chin Lin, Benjamin Matthias Ruppik, Renato Vukovic, and Milica Gašić. Learning from noisy labels via self-taught on-the-fly meta loss rescaling, 2024. URL <https://arxiv.org/abs/2412.12955>.



- David Herrera-Poyatos, Carlos Peláez-González, Cristina Zuheros, Andrés Herrera-Poyatos, Virilo Tejedor, Francisco Herrera, and Rosana Montes. An overview of model uncertainty and variability in llm-based sentiment analysis. challenges, mitigation strategies and the role of explainability, 2025. URL <https://arxiv.org/abs/2504.04462>.
- Jiwoo Hong, Noah Lee, and James Thorne. Orpo: Monolithic preference optimization without reference model, 2024. URL <https://arxiv.org/abs/2403.07691>.
- Nikolaus Howe, Ian McKenzie, Oskar Hollinsworth, Michał Zajac, Tom Tseng, Aaron Tucker, Pierre-Luc Bacon, and Adam Gleave. Scaling trends in language model robustness, 2025. URL <https://arxiv.org/abs/2407.18213>.
- Yuchen Hu, CHEN CHEN, Chao-Han Huck Yang, Ruizhe Li, Chao Zhang, Pin-Yu Chen, and EngSiong Chng. Large language models are efficient learners of noise-robust speech recognition. In *The Twelfth International Conference on Learning Representations*, 2024. URL <https://openreview.net/forum?id=ceATjGPTUD>.
- Tiansheng Huang, Sihao Hu, Fatih Ilhan, Selim Furkan Tekin, Zachary Yahn, Yichang Xu, and Ling Liu. Safety tax: Safety alignment makes your large reasoning models less reasonable, 2025. URL <https://arxiv.org/abs/2503.00555>.
- Yue Huang, Lichao Sun, Haoran Wang, Siyuan Wu, Qihui Zhang, Yuan Li, Chujie Gao, Yixin Huang, Wenhan Lyu, Yixuan Zhang, Xiner Li, Zhengliang Liu, Yixin Liu, Yijue Wang, Zhikun Zhang, Bertie Vidgen, Bhavya Kaikhura, Caiming Xiong, Chaowei Xiao, Chunyuan Li, Eric Xing, Furong Huang, Hao Liu, Heng Ji, Hongyi Wang, Huan Zhang, Huaxiu Yao, Manolis Kellis, Marinka Zitnik, Meng Jiang, Mohit Bansal, James Zou, Jian Pei, Jian Liu, Jianfeng Gao, Jiawei Han, Jieyu Zhao, Jiliang Tang, Jindong Wang, Joaquin Vanschoren, John Mitchell, Kai Shu, Kaidi Xu, Kai-Wei Chang, Lifang He, Lifu Huang, Michael Backes, Neil Zhenqiang Gong, Philip S. Yu, Pin-Yu Chen, Quanquan Gu, Ran Xu, Rex Ying, Shuiwang Ji, Suman Jana, Tianlong Chen, Tianming Liu, Tianyi Zhou, William Wang, Xiang Li, Xiangliang Zhang, Xiao Wang, Xing Xie, Xun Chen, Xuyu Wang, Yan Liu, Yanfang Ye, Yinzhi Cao, Yong Chen, and Yue Zhao. Trustllm: Trustworthiness in large language models, 2024a. URL <https://arxiv.org/abs/2401.05561>.
- Yukun Huang, Yixin Liu, Raghuveer Thirukovalluru, Arman Cohan, and Bhuwan Dhingra. Calibrating long-form generations from large language models. In Yaser Al-Onaizan, Mohit Bansal, and Yun-Nung Chen (eds.), *Findings of the Association for Computational Linguistics: EMNLP 2024*, pp. 13441–13460, Miami, Florida, USA, November 2024b. Association for Computational Linguistics. doi: 10.18653/v1/2024.findings-emnlp.785. URL <https://aclanthology.org/2024.findings-emnlp.785/>.
- Nandan Kumar Jha and Brandon Reagen. Aero: Softmax-only llms for efficient private inference, 2024. URL <https://arxiv.org/abs/2410.13060>.
- Chengze Jiang, Zhuangzhuang Wang, Mingjing Dong, and Jie Gui. Survey of adversarial robustness in multimodal large language models, 2025. URL <https://arxiv.org/abs/2503.13962>.
- Nan Jiang, Qi Li, Lin Tan, and Tianyi Zhang. Collu-bench: A benchmark for predicting language model hallucinations in code, 2024. URL <https://arxiv.org/abs/2410.09997>.
- Ziyu Jiang, Tianlong Chen, Ting Chen, and Zhangyang Wang. Robust pre-training by adversarial contrastive learning, 2020. URL <https://arxiv.org/abs/2010.13337>.
- Dahyun Jung, Seungyeon Lee, Hyeonseok Moon, Chanjun Park, and Heuseok Lim. Flex: A benchmark for evaluating robustness of fairness in large language models, 2025. URL <https://arxiv.org/abs/2503.19540>.
- Daniel Kuhn, Soroosh Shafiee, and Wolfram Wiesemann. Distributionally robust optimization, 2025. URL <https://arxiv.org/abs/2411.02549>.
- Aounon Kumar, Chirag Agarwal, Suraj Srinivas, Aaron Jiaxun Li, Soheil Feizi, and Himabindu Lakkaraju. Certifying llm safety against adversarial prompting, 2025a. URL <https://arxiv.org/abs/2309.02705>.

- Komal Kumar, Tajamul Ashraf, Omkar Thawakar, Rao Muhammad Anwer, Hisham Cholakkal, Mubarak Shah, Ming-Hsuan Yang, Phillip H. S. Torr, Fahad Shahbaz Khan, and Salman Khan. Llm post-training: A deep dive into reasoning large language models, 2025b. URL <https://arxiv.org/abs/2502.21321>.
- Vedang Lad, Wes Gurnee, and Max Tegmark. The remarkable robustness of llms: Stages of inference?, 2024. URL <https://arxiv.org/abs/2406.19384>.
- Hugo Laurençon, Lucile Saulnier, Thomas Wang, Christopher Akiki, Albert Villanova del Moral, Teven Le Scao, Leandro Von Werra, Chenghao Mou, Eduardo González Ponferrada, Huu Nguyen, Jörg Froberg, Mario Šaško, Quentin Lhoest, Angelina McMillan-Major, Gerard Dupont, Stella Biderman, Anna Rogers, Loubna Ben allal, Francesco De Toni, Giada Pistilli, Olivier Nguyen, Somaieh Nikpoor, Maraim Masoud, Pierre Colombo, Javier de la Rosa, Paulo Villegas, Tristan Thrush, Shayne Longpre, Sebastian Nagel, Leon Weber, Manuel Muñoz, Jian Zhu, Daniel Van Strien, Zaid Alyafeai, Khalid Almubarak, Minh Chien Vu, Itziar Gonzalez-Dios, Aitor Soroa, Kyle Lo, Manan Dey, Pedro Ortiz Suarez, Aaron Gokaslan, Shamik Bose, David Adelani, Long Phan, Hieu Tran, Ian Yu, Suhas Pai, Jenny Chim, Violette Lepercq, Suzana Ilic, Margaret Mitchell, Sasha Alexandra Luccioni, and Yacine Jernite. The bigscience roots corpus: A 1.6tb composite multilingual dataset, 2023. URL <https://arxiv.org/abs/2303.03915>.
- Dongryeol Lee, Yerin Hwang, Yongi-Mi Kim, Joonsuk Park, and Kyomin Jung. Are llm-judges robust to expressions of uncertainty? investigating the effect of epistemic markers on llm-based evaluation. *ArXiv*, abs/2410.20774, 2024a. URL <https://api.semanticscholar.org/CorpusID:273653843>.
- Jean Lee, Nicholas Stevens, and Soyeon Caren Han. Large language models in finance (finllms). *Neural Computing and Applications*, January 2025. ISSN 1433-3058. doi: 10.1007/s00521-024-10495-6. URL <http://dx.doi.org/10.1007/s00521-024-10495-6>.
- Jieh-Sheng Lee. Lexgpt 0.1: pre-trained gpt-j models with pile of law, 2023. URL <https://arxiv.org/abs/2306.05431>.
- Seanie Lee, Haebin Seong, Dong Bok Lee, Minki Kang, Xiaoyin Chen, Dominik Wagner, Yoshua Bengio, Juho Lee, and Sung Ju Hwang. Harmaug: Effective data augmentation for knowledge distillation of safety guard models. *ArXiv*, abs/2410.01524, 2024b. URL <https://api.semanticscholar.org/CorpusID:273025699>.
- Will LeVine, Benjamin Pikus, Anthony Chen, and Sean Hendryx. A baseline analysis of reward models’ ability to accurately analyze foundation models under distribution shift, 2024. URL <https://arxiv.org/abs/2311.14743>.
- Hao Li, Liuzhenghao Lv, He Cao, Zijing Liu, Zhiyuan Yan, Yu Wang, Yonghong Tian, Yu Li, and Li Yuan. How to detect and defeat molecular mirage: A metric-driven benchmark for hallucination in llm-based molecular comprehension, 2025a. URL <https://arxiv.org/abs/2504.12314>.
- Junyi Li, Xiaoxue Cheng, Wayne Xin Zhao, Jian-Yun Nie, and Ji-Rong Wen. Halueval: A large-scale hallucination evaluation benchmark for large language models, 2023. URL <https://arxiv.org/abs/2305.11747>.
- Lin Li, Yifei Wang, Chawin Sitawarin, and Michael W. Spratling. OODRobustbench: a benchmark and large-scale analysis of adversarial robustness under distribution shift. In *Forty-first International Conference on Machine Learning*, 2024a. URL <https://openreview.net/forum?id=kAFevjEYsz>.
- Qintong Li, Leyang Cui, Xueliang Zhao, Lingpeng Kong, and Wei Bi. GSM-plus: A comprehensive benchmark for evaluating the robustness of LLMs as mathematical problem solvers. In Lun-Wei Ku, Andre Martins, and Vivek Srikumar (eds.), *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 2961–2984, Bangkok, Thailand, August 2024b. Association for Computational Linguistics. doi: 10.18653/v1/2024.acl-long.163. URL <https://aclanthology.org/2024.acl-long.163/>.

- Qiongxiu Li, Xiaoyu Luo, Yiyi Chen, and Johannes Bjerva. Trustworthy machine learning via memorization and the granular long-tail: A survey on interactions, tradeoffs, and beyond, 2025b. URL <https://arxiv.org/abs/2503.07501>.
- Xuran Li, Peng Wu, and Jing Su. Accurate fairness: Improving individual fairness without trading accuracy, 2022. URL <https://arxiv.org/abs/2205.08704>.
- Yinheng Li, Shaofei Wang, Han Ding, and Hang Chen. Large language models in finance: A survey, 2024c. URL <https://arxiv.org/abs/2311.10723>.
- Yue Li, Xiao Li, Hao Wu, Minghui Xu, Yue Zhang, Xiuzhen Cheng, Fengyuan Xu, and Sheng Zhong. Everything you wanted to know about llm-based vulnerability detection but were afraid to ask, 2025c. URL <https://arxiv.org/abs/2504.13474>.
- Zekun Li, Baolin Peng, Pengcheng He, and Xifeng Yan. Evaluating the instruction-following robustness of large language models to prompt injection. In Yaser Al-Onaizan, Mohit Bansal, and Yun-Nung Chen (eds.), *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing*, pp. 557–568, Miami, Florida, USA, November 2024d. Association for Computational Linguistics. doi: 10.18653/v1/2024.emnlp-main.33. URL <https://aclanthology.org/2024.emnlp-main.33/>.
- ZiKe Li, Mingwei Liu, Anji Li, Kaifeng He, Yanlin Wang, Xin Peng, and Zibin Zheng. Enhancing the robustness of llm-generated code: Empirical study and framework. *arXiv preprint arXiv:2503.20197*, March 2025d. doi: 10.48550/arXiv.2503.20197.
- Jongin Lim, Youngdong Kim, Byungjai Kim, Chanho Ahn, Jinwoo Shin, Eunho Yang, and Seungju Han. Biasadv: Bias-adversarial augmentation for model debiasing. In *2023 IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 3832–3841, 2023. doi: 10.1109/CVPR52729.2023.00373.
- Feng Lin, Dong Jae Kim, Tse-Husn, and Chen. Soen-101: Code generation by emulating software process models using large language model agents, 2024a. URL <https://arxiv.org/abs/2403.15852>.
- Yong Lin, Hangyu Lin, Wei Xiong, Shizhe Diao, Jianmeng Liu, Jipeng Zhang, Rui Pan, Haoxiang Wang, Wenbin Hu, Hanning Zhang, Hanze Dong, Renjie Pi, Han Zhao, Nan Jiang, Heng Ji, Yuan Yao, and Tong Zhang. Mitigating the alignment tax of rlhf, 2024b. URL <https://arxiv.org/abs/2309.06256>.
- Fang Liu, Yang Liu, Lin Shi, Houkun Huang, Ruifeng Wang, Zhen Yang, Li Zhang, Zhongqi Li, and Yuchi Ma. Exploring and evaluating hallucinations in llm-powered code generation, 2024a. URL <https://arxiv.org/abs/2404.00971>.
- Tianyuan Liu and Yuqing Sun. End-to-end adversarial sample generation for data augmentation. In Houda Bouamor, Juan Pino, and Kalika Bali (eds.), *Findings of the Association for Computational Linguistics: EMNLP 2023*, pp. 11359–11368, Singapore, December 2023. Association for Computational Linguistics. doi: 10.18653/v1/2023.findings-emnlp.760. URL <https://aclanthology.org/2023.findings-emnlp.760/>.
- Xiaoxia Liu, Jingyi Wang, Jun Sun, Xiaohan Yuan, Guoliang Dong, Peng Di, Wenhai Wang, and Dongxia Wang. Prompting frameworks for large language models: A survey, 2023. URL <https://arxiv.org/abs/2311.12785>.
- Yang Liu, Yuanshun Yao, Jean-Francois Ton, Xiaoying Zhang, Ruocheng Guo, Hao Cheng, Yegor Klochkov, Muhammad Faaiz Taufiq, and Hang Li. Trustworthy llms: a survey and guideline for evaluating large language models’ alignment, 2024b. URL <https://arxiv.org/abs/2308.05374>.
- Shuo Lu, Yingsheng Wang, Lijun Sheng, Aihua Zheng, Lingxiao He, and Jian Liang. Recent advances in ood detection: Problems and approaches, 2024. URL <https://arxiv.org/abs/2409.11884>.
- Junyu Luo, Xiao Luo, Kaize Ding, Jingyang Yuan, Zhiping Xiao, and Ming Zhang. Robustft: Robust supervised fine-tuning for large language models under noisy response, 2024. URL <https://arxiv.org/abs/2412.14922>.

- Ziyang Ma, Zuchao Li, Lefei Zhang, Gui-Song Xia, Bo Du, Liangpei Zhang, and Dacheng Tao. Model hemorrhage and the robustness limits of large language models, 2025. URL <https://arxiv.org/abs/2503.23924>.
- Rabeeh Karimi Mahabadi, Yonatan Belinkov, and James Henderson. End-to-end bias mitigation by modelling biases in corpora, 2020. URL <https://arxiv.org/abs/1909.06321>.
- Matéo Mahaut, Laura Aina, Paula Czarowska, Momchil Hardalov, Thomas Müller, and Lluís Marquez. Factual confidence of llms: on reliability and robustness of current estimators. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 4554–4570. Association for Computational Linguistics, 2024. doi: 10.18653/v1/2024.acl-long.250. URL <http://dx.doi.org/10.18653/v1/2024.acl-long.250>.
- Harsh Maheshwari, Srikanth Tenneti, and Alwarappan Nakkiran. Citefix: Enhancing rag accuracy through post-processing citation correction, 2025. URL <https://arxiv.org/abs/2504.15629>.
- Rohin Manvi, Anikait Singh, and Stefano Ermon. Adaptive inference-time compute: Llms can predict if they can do better, even mid-generation, 2024. URL <https://arxiv.org/abs/2410.02725>.
- Ninareh Mehrabi, Fred Morstatter, Nripsuta Saxena, Kristina Lerman, and Aram Galstyan. A survey on bias and fairness in machine learning, 2022. URL <https://arxiv.org/abs/1908.09635>.
- Mayank Mishra, Matt Stallone, Gaoyuan Zhang, Yikang Shen, Aditya Prasad, Adriana Meza Soria, Michele Merler, Parameswaran Selvam, Saptha Surendran, Shivdeep Singh, Manish Sethi, Xuan-Hong Dang, Pengyuan Li, Kun-Lung Wu, Syed Zawad, Andrew Coleman, Matthew White, Mark Lewis, Raju Pavuluri, Yan Koyfman, Boris Lublinsky, Maximilien de Bayser, Ibrahim Abdelaziz, Kinjal Basu, Mayank Agarwal, Yi Zhou, Chris Johnson, Aanchal Goyal, Hima Patel, Yousaf Shah, Petros Zerfos, Heiko Ludwig, Asim Munawar, Maxwell Crouse, Pavan Kapanipathi, Shweta Salaria, Bob Calio, Sophia Wen, Seetharami Seelam, Brian Belgodere, Carlos Fonseca, Amith Singhee, Nirmal Desai, David D. Cox, Ruchir Puri, and Rameswar Panda. Granite code models: A family of open foundation models for code intelligence, 2024. URL <https://arxiv.org/abs/2405.04324>.
- Ningping Mou, Xinli Yue, Lingchen Zhao, and Qian Wang. Fairness is essential for robustness: fair adversarial training by identifying and augmenting hard examples. *Frontiers of Computer Science*, 19(3):193803, November 2024. ISSN 2095-2236. doi: 10.1007/s11704-024-3587-1.
- Dor Muhlgay, Ori Ram, Inbal Magar, Yoav Levine, Nir Ratner, Yonatan Belinkov, Omri Abend, Kevin Leyton-Brown, Amnon Shashua, and Yoav Shoham. Generating benchmarks for factuality evaluation of language models, 2024. URL <https://arxiv.org/abs/2307.06908>.
- Vaishnavh Nagarajan, Anders Andreassen, and Behnam Neyshabur. Understanding the failure modes of out-of-distribution generalization, 2024. URL <https://arxiv.org/abs/2010.15775>.
- Grigor Nalbandyan, Rima Shahbazyan, and Evelina Bakhturina. Score: Systematic consistency and robustness evaluation for large language models, 2025. URL <https://arxiv.org/abs/2503.00137>.
- Alireza Nik, Michael A. Riegler, and Pål Halvorsen. Energy-conscious llm decoding: Impact of text generation strategies on gpu energy consumption, 2025. URL <https://arxiv.org/abs/2502.11723>.
- Soyoung Oh and Vera Demberg. Robustness of large language models in moral judgements, Apr 2025. URL <https://pmc.ncbi.nlm.nih.gov/articles/PMC12015570/>.
- OpenAI, Josh Achiam, Steven Adler, Sandhini Agarwal, Lama Ahmad, Ilge Akkaya, Florencia Leoni Aleman, Diogo Almeida, Janko Altschmidt, Sam Altman, Shyamal Anadkat, Red Avila, Igor Babuschkin, Suchir Balaji, Valerie Balcom, Paul Baltescu, Haiming Bao, Mohammad Bavarian, Jeff Belgum, Irwan Bello, Jake Berdine, Gabriel Bernadett-Shapiro, Christopher Berner, Lenny Bogdonoff, Oleg Boiko, Madelaine Boyd, Anna-Luisa Brakman, Greg Brockman, Tim Brooks, Miles Brundage, Kevin Button, Trevor Cai, Rosie Campbell, Andrew Cann, Brittany Carey, Chelsea Carlson, Rory Carmichael, Brooke Chan, Che Chang, Fotis Chantzis, Derek Chen, Sully Chen, Ruby Chen, Jason Chen, Mark Chen, Ben Chess, Chester

- Cho, Casey Chu, Hyung Won Chung, Dave Cummings, Jeremiah Currier, Yunxing Dai, Cory Decareaux, Thomas Degry, Noah Deutsch, Damien Deville, Arka Dhar, David Dohan, Steve Dowling, Sheila Dunning, Adrien Ecoffet, Atty Eleti, Tyna Eloundou, David Farhi, Liam Fedus, Niko Felix, Simón Posada Fishman, Juston Forte, Isabella Fulford, Leo Gao, Elie Georges, Christian Gibson, Vik Goel, Tarun Gogineni, Gabriel Goh, Rapha Gontijo-Lopes, Jonathan Gordon, Morgan Grafstein, Scott Gray, Ryan Greene, Joshua Gross, Shixiang Shane Gu, Yufei Guo, Chris Hallacy, Jesse Han, Jeff Harris, Yuchen He, Mike Heaton, Johannes Heidecke, Chris Hesse, Alan Hickey, Wade Hickey, Peter Hoeschele, Brandon Houghton, Kenny Hsu, Shengli Hu, Xin Hu, Joost Huizinga, Shantanu Jain, Shawn Jain, Joanne Jang, Angela Jiang, Roger Jiang, Haozhun Jin, Denny Jin, Shino Jomoto, Billie Jonn, Heewoo Jun, Tomer Kaftan, Łukasz Kaiser, Ali Kamali, Ingmar Kanitscheider, Nitish Shirish Keskar, Tabarak Khan, Logan Kilpatrick, Jong Wook Kim, Christina Kim, Yongjik Kim, Jan Hendrik Kirchner, Jamie Kiros, Matt Knight, Daniel Kokotajlo, Łukasz Kondraciuk, Andrew Kondrich, Aris Konstantinidis, Kyle Kopic, Gretchen Krueger, Vishal Kuo, Michael Lampe, Ikai Lan, Teddy Lee, Jan Leike, Jade Leung, Daniel Levy, Chak Ming Li, Rachel Lim, Molly Lin, Stephanie Lin, Mateusz Litwin, Theresa Lopez, Ryan Lowe, Patricia Lue, Anna Makanju, Kim Malfacini, Sam Manning, Todor Markov, Yaniv Markovski, Bianca Martin, Katie Mayer, Andrew Mayne, Bob McGrew, Scott Mayer McKinney, Christine McLeavey, Paul McMillan, Jake McNeil, David Medina, Aalok Mehta, Jacob Menick, Luke Metz, Andrey Mishchenko, Pamela Mishkin, Vinnie Monaco, Evan Morikawa, Daniel Mossing, Tong Mu, Mira Murati, Oleg Murk, David Mély, Ashvin Nair, Reiichiro Nakano, Rajeev Nayak, Arvind Neelakantan, Richard Ngo, Hyeonwoo Noh, Long Ouyang, Cullen O’Keefe, Jakub Pachocki, Alex Paino, Joe Palermo, Ashley Pantuliano, Giambattista Parascandolo, Joel Parish, Emy Parparita, Alex Passos, Mikhail Pavlov, Andrew Peng, Adam Perelman, Filipe de Avila Belbute Peres, Michael Petrov, Henrique Ponde de Oliveira Pinto, Michael, Pokorny, Michelle Pokrass, Vitchyr H. Pong, Tolly Powell, Alethea Power, Boris Power, Elizabeth Proehl, Raul Puri, Alec Radford, Jack Rae, Aditya Ramesh, Cameron Raymond, Francis Real, Kendra Rimbach, Carl Ross, Bob Rotsted, Henri Roussez, Nick Ryder, Mario Saltarelli, Ted Sanders, Shibani Santurkar, Girish Sastry, Heather Schmidt, David Schnurr, John Schulman, Daniel Selsam, Kyla Sheppard, Toki Sherbakov, Jessica Shieh, Sarah Shoker, Pranav Shyam, Szymon Sidor, Eric Sigler, Maddie Simens, Jordan Sitkin, Katarina Slama, Ian Sohl, Benjamin Sokolowsky, Yang Song, Natalie Staudacher, Felipe Petroski Such, Natalie Summers, Ilya Sutskever, Jie Tang, Nikolas Tezak, Madeleine B. Thompson, Phil Tillet, Amin Tootoonchian, Elizabeth Tseng, Preston Tuggle, Nick Turley, Jerry Tworek, Juan Felipe Cerón Uribe, Andrea Vallone, Arun Vijayvergiya, Chelsea Voss, Carroll Wainwright, Justin Jay Wang, Alvin Wang, Ben Wang, Jonathan Ward, Jason Wei, CJ Weinmann, Akila Welihinda, Peter Welinder, Jiayi Weng, Lilian Weng, Matt Wiethoff, Dave Willner, Clemens Winter, Samuel Wolrich, Hannah Wong, Lauren Workman, Sherwin Wu, Jeff Wu, Michael Wu, Kai Xiao, Tao Xu, Sarah Yoo, Kevin Yu, Qiming Yuan, Wojciech Zaremba, Rowan Zellers, Chong Zhang, Marvin Zhang, Shengjia Zhao, Tianhao Zheng, Juntang Zhuang, William Zhuk, and Barret Zoph. Gpt-4 technical report, 2024. URL <https://arxiv.org/abs/2303.08774>.
- Long Ouyang, Jeff Wu, Xu Jiang, Diogo Almeida, Carroll L. Wainwright, Pamela Mishkin, Chong Zhang, Sandhini Agarwal, Katarina Slama, Alex Ray, John Schulman, Jacob Hilton, Fraser Kelton, Luke Miller, Maddie Simens, Amanda Askell, Peter Welinder, Paul Christiano, Jan Leike, and Ryan Lowe. Training language models to follow instructions with human feedback, 2022. URL <https://arxiv.org/abs/2203.02155>.
- Aditya Patwardhan, Vivek Vaidya, and Ashish Kundu. Automated consistency analysis of llms, 2025. URL <https://arxiv.org/abs/2502.07036>.
- Fabio Petroni, Tim Rocktäschel, Patrick Lewis, Anton Bakhtin, Yuxiang Wu, Alexander H. Miller, and Sebastian Riedel. Language models as knowledge bases?, 2019. URL <https://arxiv.org/abs/1909.01066>.
- Mansi Phute, Alec Helbling, Matthew Hull, ShengYun Peng, Sebastian Szyller, Cory Cornelius, and Duen Horng Chau. Llm self defense: By self examination, llms know they are being tricked, 2024. URL <https://arxiv.org/abs/2308.07308>.
- Nicolas Posocco and Antoine Bonnefoy. Estimating expected calibration errors, 2021. URL <https://arxiv.org/abs/2109.03480>.



- Jirui Qi, Raquel Fernández, and Arianna Bisazza. Cross-lingual consistency of factual knowledge in multilingual language models. In Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing, pp. 10650–10666. Association for Computational Linguistics, 2023. doi: 10.18653/v1/2023.emnlp-main.658. URL <http://dx.doi.org/10.18653/v1/2023.emnlp-main.658>.
- Rebecca Qian, Candace Ross, Jude Fernandes, Eric Smith, Douwe Kiela, and Adina Williams. Perturbation augmentation for fairer nlp, 2022. URL <https://arxiv.org/abs/2205.12586>.
- Rafael Rafailov, Archit Sharma, Eric Mitchell, Stefano Ermon, Christopher D. Manning, and Chelsea Finn. Direct preference optimization: Your language model is secretly a reward model, 2024. URL <https://arxiv.org/abs/2305.18290>.
- Hamed Rahimian and Sanjay Mehrotra. Frameworks and results in distributionally robust optimization. Open Journal of Mathematical Optimization, 3:1–85, July 2022. ISSN 2777-5860. doi: 10.5802/ojmo.15. URL <http://dx.doi.org/10.5802/ojmo.15>.
- A B M Ashikur Rahman, Saeed Anwar, Muhammad Usman, and Ajmal Mian. Defan: Definitive answer dataset for llms hallucination evaluation, 2024. URL <https://arxiv.org/abs/2406.09155>.
- Mirza Masfiquir Rahman and Ashish Kundu. Code hallucination. ArXiv, abs/2407.04831, 2024. URL <https://api.semanticscholar.org/CorpusID:271050530>.
- Vyas Raina, Adian Liusie, and Mark Gales. Is LLM-as-a-judge robust? investigating universal adversarial attacks on zero-shot LLM assessment. In Yaser Al-Onaizan, Mohit Bansal, and Yun-Nung Chen (eds.), Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing, pp. 7499–7517, Miami, Florida, USA, November 2024. Association for Computational Linguistics. doi: 10.18653/v1/2024.emnlp-main.427. URL <https://aclanthology.org/2024.emnlp-main.427/>.
- Srinivasan Ravichandran, Drona Khurana, Bharath Venkatesh, and Narayanan Unny Edakunni. Fairxgboost: Fairness-aware classification in xgboost, 2020. URL <https://arxiv.org/abs/2009.01442>.
- Traian Rebedea, Razvan Dinu, Makesh Sreedhar, Christopher Parisien, and Jonathan Cohen. Nemo guardrails: A toolkit for controllable and safe llm applications with programmable rails, 2023. URL <https://arxiv.org/abs/2310.10501>.
- Laboni Sarker, Mara Downing, Achintya Desai, and Tevfik Bultan. Syntactic robustness for llm-based code generation, 2024. URL <https://arxiv.org/abs/2404.01535>.
- Yash Saxena, Sarthak Chopra, and Arunendra Mani Tripathi. Evaluating consistency and reasoning capabilities of large language models, 2024. URL <https://arxiv.org/abs/2404.16478>.
- Laxmi Shaw, Mohammed Wasim Ansari, and Tahir Ekin. Adversarial natural language processing: Overview, challenges and future directions. In Proceedings of the Annual Hawaii International Conference on System Sciences. Hawaii International Conference on System Sciences, 2025. doi: 10.24251/hicss.2025.108. URL <https://hdl.handle.net/10125/108946>.
- Xiaoyu Shen, Rexhina Blloshmi, Dawei Zhu, Jiahuan Pei, and Wei Zhang. Assessing “implicit” retrieval robustness of large language models. In Yaser Al-Onaizan, Mohit Bansal, and Yun-Nung Chen (eds.), Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing, pp. 8988–9003, Miami, Florida, USA, November 2024. Association for Computational Linguistics. doi: 10.18653/v1/2024.emnlp-main.507. URL <https://aclanthology.org/2024.emnlp-main.507/>.
- Chufan Shi, Haoran Yang, Deng Cai, Zhisong Zhang, Yifan Wang, Yujiu Yang, and Wai Lam. A thorough examination of decoding methods in the era of llms, 2024a. URL <https://arxiv.org/abs/2402.06925>.
- Ruizhe Shi, Yifang Chen, Yushi Hu, Alisa Liu, Hannaneh Hajishirzi, Noah A. Smith, and Simon Shaolei Du. Decoding-time language model alignment with multiple objectives. In The Thirty-eighth Annual Conference on Neural Information Processing Systems, 2024b. URL <https://openreview.net/forum?id=3csuL7TVpV>.



- Ayush Singh, Navpreet Singh, and Shubham Vatsal. Robustness of llms to perturbations in text, 2024. URL <https://arxiv.org/abs/2407.08989>.
- Charlie Snell, Jaehoon Lee, Kelvin Xu, and Aviral Kumar. Scaling llm test-time compute optimally can be more effective than scaling model parameters, 2024. URL <https://arxiv.org/abs/2408.03314>.
- Seongho Son, William Bankes, Sangwoong Yoon, Shyam Sundhar Ramesh, Xiaohang Tang, and Ilija Bonunovic. Robust multi-objective controlled decoding of large language models, 2025. URL <https://arxiv.org/abs/2503.08796>.
- Xiaoshuai Song, Zhengyang Wang, Keqing He, Guanting Dong, Yutao Mou, Jinxu Zhao, and Weiran Xu. Assessing and post-processing black box large language models for knowledge editing. In THE WEB CONFERENCE 2025, 2025. URL <https://openreview.net/forum?id=aGhk1VNcRJ>.
- Joe Stacey, Pasquale Minervini, Haim Dubossarsky, and Marek Rei. Logical reasoning with span-level predictions for interpretable and robust nli models, 2022. URL <https://arxiv.org/abs/2205.11432>.
- Joe Stacey, Pasquale Minervini, Haim Dubossarsky, Oana-Maria Camburu, and Marek Rei. Atomic inference for nli with generated facts as atoms, 2024. URL <https://arxiv.org/abs/2305.13214>.
- Hao Sun. Supervised fine-tuning as inverse reinforcement learning, 2024. URL <https://arxiv.org/abs/2403.12017>.
- Yuhong Sun, Zhangyue Yin, Qipeng Guo, Jiawen Wu, Xipeng Qiu, and Hui Zhao. Benchmarking hallucination in large language models based on unanswerable math word problem, 2024a. URL <https://arxiv.org/abs/2403.03558>.
- Zhihong Sun, Chen Lyu, Bolun Li, Yao Wan, Hongyu Zhang, Ge Li, and Zhi Jin. Enhancing code generation performance of smaller models by distilling the reasoning ability of llms, 2024b. URL <https://arxiv.org/abs/2403.13271>.
- Christian Szegedy, Wojciech Zaremba, Ilya Sutskever, Joan Bruna, Dumitru Erhan, Ian Goodfellow, and Rob Fergus. Intriguing properties of neural networks, 2014. URL <https://arxiv.org/abs/1312.6199>.
- Yiyi Tao, Yixian Shen, Hang Zhang, Yanxin Shen, Lun Wang, Chuanqi Shi, and Shaoshuai Du. Robustness of large language models against adversarial attacks, 2024. URL <https://arxiv.org/abs/2412.17011>.
- Yuchen Tian, Weixiang Yan, Qian Yang, Xuandong Zhao, Qian Chen, Wen Wang, Ziyang Luo, Lei Ma, and Dawn Song. Codehalu: Investigating code hallucinations in llms via execution-based verification, 2025. URL <https://arxiv.org/abs/2405.00253>.
- Hugo Touvron, Thibaut Lavril, Gautier Izacard, Xavier Martinet, Marie-Anne Lachaux, Timothée Lacroix, Baptiste Rozière, Naman Goyal, Eric Hambro, Faisal Azhar, Aurélien Rodriguez, Armand Joulin, Edouard Grave, and Guillaume Lample. Llama: Open and efficient foundation language models. ArXiv, abs/2302.13971, 2023a. URL <https://api.semanticscholar.org/CorpusID:257219404>.
- Hugo Touvron, Louis Martin, Kevin Stone, Peter Albert, Amjad Almahairi, Yasmine Babaei, Nikolay Bashlykov, Soumya Batra, Prajjwal Bhargava, Shruti Bhosale, Dan Bikel, Lukas Blecher, Cristian Canton Ferrer, Moya Chen, Guillem Cucurull, David Esiobu, Jude Fernandes, Jeremy Fu, Wenyin Fu, Brian Fuller, Cynthia Gao, Vedanuj Goswami, Naman Goyal, Anthony Hartshorn, Saghar Hosseini, Rui Hou, Hakan Inan, Marcin Kardas, Viktor Kerkez, Madian Khabsa, Isabel Kloumann, Artem Korenev, Punit Singh Koura, Marie-Anne Lachaux, Thibaut Lavril, Jenya Lee, Diana Liskovich, Yinghai Lu, Yuning Mao, Xavier Martinet, Todor Mihaylov, Pushkar Mishra, Igor Molybog, Yixin Nie, Andrew Poulton, Jeremy Reizenstein, Rashi Rungta, Kalyan Saladi, Alan Schelten, Ruan Silva, Eric Michael Smith, Ranjan Subramanian, Xiaoqing Ellen Tan, Binh Tang, Ross Taylor, Adina Williams, Jian Xiang Kuan, Puxin Xu, Zheng Yan, Iliyan Zarov, Yuchen Zhang, Angela Fan, Melanie Kambadur, Sharan Narang, Aurelien Rodriguez, Robert Stojnic, Sergey Edunov, and Thomas Scialom. Llama 2: Open foundation and fine-tuned chat models, 2023b. URL <https://arxiv.org/abs/2307.09288>.

- Thien Q. Tran, Akifumi Wachi, Rei Sato, Takumi Tanabe, and Youhei Akimoto. Vulnerability mitigation for safety-aligned language models via debiasing, 2025. URL <https://arxiv.org/abs/2502.02153>.
- Yahan Tu, Rui Hu, and Jitao Sang. Ode: Open-set evaluation of hallucinations in multimodal large language models, 2024. URL <https://arxiv.org/abs/2409.09318>.
- Prasetya Ajie Utama, Nafise Sadat Moosavi, and Iryna Gurevych. Mind the trade-off: Debiasing nlu models without degrading the in-distribution performance, 2020. URL <https://arxiv.org/abs/2005.00315>.
- Neeraj Varshney, Pavel Dolin, Agastya Seth, and Chitta Baral. The art of defending: A systematic evaluation and analysis of LLM defense strategies on safety and over-defensiveness. In Lun-Wei Ku, Andre Martins, and Vivek Srikumar (eds.), *Findings of the Association for Computational Linguistics: ACL 2024*, pp. 13111–13128, Bangkok, Thailand, August 2024. Association for Computational Linguistics. doi: 10.18653/v1/2024.findings-acl.776. URL <https://aclanthology.org/2024.findings-acl.776/>.
- Zhongwei Wan, Che Liu, Mi Zhang, Jie Fu, Benyou Wang, Sibao Cheng, Lei Ma, César Quilodr  n-Casas, and Rossella Arcucci. Med-unic: Unifying cross-lingual medical vision-language pre-training by diminishing bias, 2024a. URL <https://arxiv.org/abs/2305.19894>.
- Zhongwei Wan, Yichun Yin, Wei Zhang, Jiaxin Shi, Lifeng Shang, Guangyong Chen, Xin Jiang, and Qun Liu. G-map: General memory-augmented pre-trained language model for domain tasks, 2024b. URL <https://arxiv.org/abs/2212.03613>.
- Boxin Wang, Chejian Xu, Shuohang Wang, Zhe Gan, Yu Cheng, Jianfeng Gao, Ahmed Hassan Awadallah, and B. Li. Adversarial glue: A multi-task benchmark for robustness evaluation of language models. *ArXiv*, abs/2111.02840, 2021. URL <https://api.semanticscholar.org/CorpusID:242757097>.
- Haoxiang Wang, Wei Xiong, Tengyang Xie, Han Zhao, and Tong Zhang. Interpretable preferences via multi-objective reward modeling and mixture-of-experts. In *The 2024 Conference on Empirical Methods in Natural Language Processing*, 2024a.
- Huandong Wang, Wenjie Fu, Yingzhou Tang, Zhilong Chen, Yuxi Huang, Jinghua Piao, Chen Gao, Fengli Xu, Tao Jiang, and Yong Li. A survey on responsible llms: Inherent risk, malicious use, and mitigation strategy, 2025. URL <https://arxiv.org/abs/2501.09431>.
- Jindong Wang, Xixu Hu, Wenxin Hou, Hao Chen, Runkai Zheng, Yidong Wang, Linyi Yang, Haojun Huang, Wei Ye, Xiubo Geng, Binxin Jiao, Yue Zhang, and Xing Xie. On the robustness of chatgpt: An adversarial and out-of-distribution perspective, 2023. URL <https://arxiv.org/abs/2302.12095>.
- Junyang Wang, Yuhang Wang, Guohai Xu, Jing Zhang, Yukai Gu, Haitao Jia, Jiaqi Wang, Haiyang Xu, Ming Yan, Ji Zhang, and Jitao Sang. Amber: An llm-free multi-dimensional benchmark for mllms hallucination evaluation, 2024b. URL <https://arxiv.org/abs/2311.07397>.
- Yuxia Wang, Minghan Wang, Muhammad Arslan Manzoor, Fei Liu, Georgi Georgiev, Rocktim Jyoti Das, and Preslav Nakov. Factuality of large language models: A survey, 2024c. URL <https://arxiv.org/abs/2402.02420>.
- Jiaheng Wei, Yuanshun Yao, Jean-Francois Ton, Hongyi Guo, Andrew Estornell, and Yang Liu. Measuring and reducing llm hallucination without gold-standard answers, 2024. URL <https://arxiv.org/abs/2402.10412>.
- Lilian Weng. Adversarial attacks on llms. [lilianweng.github.io](https://lilianweng.github.io/posts/2023-10-25-adv-attack-llm/), Oct 2023. URL <https://lilianweng.github.io/posts/2023-10-25-adv-attack-llm/>.
- Junkang Wu, Yuexiang Xie, Zhengyi Yang, Jiancan Wu, Jiawei Chen, Jinyang Gao, Bolin Ding, Xiang Wang, and Xiangnan He. Towards robust alignment of language models: Distributionally robustifying direct preference optimization. In *The Thirteenth International Conference on Learning Representations*, 2025. URL <https://openreview.net/forum?id=CbfsKHiWEn>.

- Shijie Wu, Ozan Irsoy, Steven Lu, Vadim Dabravolski, Mark Dredze, Sebastian Gehrmann, Prabhanjan Kambadur, David Rosenberg, and Gideon Mann. Bloomberggpt: A large language model for finance, 2023. URL <https://arxiv.org/abs/2303.17564>.
- Sophie Khonneux, Alessandro Sordoni, Stephan Günnemann, Gauthier Gidel, and Leo Schwinn. Efficient adversarial training in llms with continuous attacks, 2024. URL <https://arxiv.org/abs/2405.15589>.
- Wei Xiong, Hanze Dong, Chenlu Ye, Ziqi Wang, Han Zhong, Heng Ji, Nan Jiang, and Tong Zhang. Iterative preference learning from human feedback: Bridging theory and practice for rlhf under kl-constraint. *ICML*, 2024.
- Jingxuan Xu, Wuyang Chen, Linyi Li, Yao Zhao, and Yunchao Wei. Collapsed language models promote fairness, 2025. URL <https://arxiv.org/abs/2410.04472>.
- Xilie Xu, Jingfeng Zhang, Feng Liu, Masashi Sugiyama, and Mohan Kankanhalli. Efficient adversarial contrastive learning via robustness-aware coreset selection, 2023. URL <https://arxiv.org/abs/2302.03857>.
- Tianyi Lorena Yan, Fei Wang, James Y. Huang, Wenxuan Zhou, Fan Yin, Aram Galstyan, Wenpeng Yin, and Muhao Chen. Contrastive instruction tuning, 2024a. URL <https://arxiv.org/abs/2402.11138>.
- Yuzi Yan, Xingzhou Lou, Jialian Li, Yiping Zhang, Jian Xie, Chao Yu, Yu Wang, Dong Yan, and Yuan Shen. Reward-robust rlhf in llms, 2024b. URL <https://arxiv.org/abs/2409.15360>.
- Borui Yang, Md Afif Al Mamun, Jie M. Zhang, and Gias Uddin. Hallucination detection in large language models with metamorphic relations, 2025a. URL <https://arxiv.org/abs/2502.15844>.
- Jingfeng Yang, Hongye Jin, Ruixiang Tang, Xiaotian Han, Qizhang Feng, Haoming Jiang, Bing Yin, and Xia Hu. Harnessing the power of llms in practice: A survey on chatgpt and beyond, 2023. URL <https://arxiv.org/abs/2304.13712>.
- Jingkang Yang, Kaiyang Zhou, Yixuan Li, and Ziwei Liu. Generalized out-of-distribution detection: A survey, 2024a. URL <https://arxiv.org/abs/2110.11334>.
- Jingyuan Yang, Dapeng Chen, Yajing Sun, Rongjun Li, Zhiyong Feng, and Wei Peng. Enhancing semantic consistency of large language models through model editing: An interpretability-oriented approach, 2025b. URL <https://arxiv.org/abs/2501.11041>.
- Ruixin Yang, Dheeraj Rajagopal, Shirley Anugrah Hayati, Bin Hu, and Dongyeop Kang. Confidence calibration and rationalization for llms via multi-agent deliberation, 2024b. URL <https://arxiv.org/abs/2404.09127>.
- Shuo Yang, Bardh Prenkaj, and Gjergji Kasneci. Razor: Sharpening knowledge by cutting bias with unsupervised text rewriting, 2024c. URL <https://arxiv.org/abs/2412.07675>.
- Zeyu Yang, Zhao Meng, Xiaochen Zheng, and Roger Wattenhofer. Assessing adversarial robustness of large language models: An empirical study, 2024d. URL <https://arxiv.org/abs/2405.02764>.
- Weiran Yao, Shelby Heinecke, Juan Carlos Niebles, Zhiwei Liu, Yihao Feng, Le Xue, Rithesh Murthy, Zeyuan Chen, Jianguo Zhang, Devansh Arpit, Ran Xu, Phil Mui, Huan Wang, Caiming Xiong, and Silvio Savarese. Retroformer: Retrospective large language agents with policy gradient optimization, 2024. URL <https://arxiv.org/abs/2308.02151>.
- Wenqian Ye, Guangtao Zheng, Xu Cao, Yunsheng Ma, and Aidong Zhang. Spurious correlations in machine learning: A survey, 2024. URL <https://arxiv.org/abs/2402.12715>.
- Zihao Ye, Lequn Chen, Ruihang Lai, Wuwei Lin, Yineng Zhang, Stephanie Wang, Tianqi Chen, Baris Kasikci, Vinod Grover, Arvind Krishnamurthy, and Luis Ceze. Flashinfer: Efficient and customizable attention engine for llm inference serving, 2025. URL <https://arxiv.org/abs/2501.01005>.

- Miao Yu, Fanci Meng, Xinyun Zhou, Shilong Wang, Junyuan Mao, Linsey Pang, Tianlong Chen, Kun Wang, Xinfeng Li, Yongfeng Zhang, Bo An, and Qingsong Wen. A survey on trustworthy llm agents: Threats and countermeasures, 2025. URL <https://arxiv.org/abs/2503.09648>.
- Yue Yu, Wei Ping, Zihan Liu, Boxin Wang, Jiaxuan You, Chao Zhang, Mohammad Shoeybi, and Bryan Catanzaro. Rankrag: Unifying context ranking with retrieval-augmented generation in llms, 2024. URL <https://arxiv.org/abs/2407.02485>.
- Lifan Yuan, Yangyi Chen, Ganqu Cui, Hongcheng Gao, FangYuan Zou, Xingyi Cheng, Heng Ji, Zhiyuan Liu, and Maosong Sun. Revisiting out-of-distribution robustness in NLP: Benchmarks, analysis, and LLMs evaluations. In *Thirty-seventh Conference on Neural Information Processing Systems Datasets and Benchmarks Track*, 2023. URL <https://openreview.net/forum?id=zQU33Uh3qM>.
- Shengbin Yue, Wei Chen, Siyuan Wang, Bingxuan Li, Chenchen Shen, Shujun Liu, Yuxuan Zhou, Yao Xiao, Song Yun, Xuanjing Huang, and Zhongyu Wei. Disc-lawllm: Fine-tuning large language models for intelligent legal services, 2023. URL <https://arxiv.org/abs/2309.11325>.
- Abdelrahman Zayed, Prasanna Parthasarathi, Goncalo Mordido, Hamid Palangi, Samira Shabanian, and Sarath Chandar. Deep learning on a healthy data diet: Finding important examples for fairness, 2022. URL <https://arxiv.org/abs/2211.11109>.
- Xinyi Zeng, Yuying Shang, Jiawei Chen, Jingyuan Zhang, and Yu Tian. Root defence strategies: Ensuring safety of llm at the decoding level, 2025. URL <https://arxiv.org/abs/2410.06809>.
- Jiaxin Zhang. Awesome-llm-uncertainty-reliability-robustness. <https://github.com/jxzhangjhu/Awesome-LLM-Uncertainty-Reliability-Robustness>, 2023. Accessed: 2025-05-06.
- Shuo Zhang, Liangming Pan, Junzhou Zhao, and William Wang. Mitigating language model hallucination with interactive question-knowledge alignment. *arxiv*, 05 2023. doi: 10.48550/arXiv.2305.13669.
- Huaqin Zhao, Zhengliang Liu, Zihao Wu, Yiwei Li, Tianze Yang, Peng Shu, Shaochen Xu, Haixing Dai, Lin Zhao, Hanqi Jiang, Yi Pan, Junhao Chen, Yifan Zhou, Gengchen Mai, Ninghao Liu, and Tianming Liu. Revolutionizing finance with llms: An overview of applications and insights, 2024a. URL <https://arxiv.org/abs/2401.11641>.
- Long Zhao, Ting Liu, Xi Peng, and Dimitris Metaxas. Maximum-entropy adversarial data augmentation for improved generalization and robustness. In H. Larochelle, M. Ranzato, R. Hadsell, M. F. Balcan, and H. Lin (eds.), *Advances in Neural Information Processing Systems*, volume 33, pp. 14435–14447. Curran Associates, Inc., 2020. URL [https://proceedings.neurips.cc/paper\\_files/paper/2020/file/a5bfc9e07964f8dddeb95fc584cd965d-Paper.pdf](https://proceedings.neurips.cc/paper_files/paper/2020/file/a5bfc9e07964f8dddeb95fc584cd965d-Paper.pdf).
- Wayne Xin Zhao, Kun Zhou, Junyi Li, Tianyi Tang, Xiaolei Wang, Yupeng Hou, Yingqian Min, Beichen Zhang, Junjie Zhang, Zican Dong, Yifan Du, Chen Yang, Yushuo Chen, Zhipeng Chen, Jinhao Jiang, Ruiyang Ren, Yifan Li, Xinyu Tang, Zikang Liu, Peiyu Liu, Jian-Yun Nie, and Ji-Rong Wen. A survey of large language models, 2025. URL <https://arxiv.org/abs/2303.18223>.
- Yukun Zhao, Lingyong Yan, Weiwei Sun, Guoliang Xing, Shuaiqiang Wang, Chong Meng, Zhicong Cheng, Zhaochun Ren, and Dawei Yin. Improving the robustness of large language models via consistency alignment. In Nicoletta Calzolari, Min-Yen Kan, Veronique Hoste, Alessandro Lenci, Sakriani Sakti, and Nianwen Xue (eds.), *Proceedings of the 2024 Joint International Conference on Computational Linguistics, Language Resources and Evaluation (LREC-COLING 2024)*, pp. 8931–8941, Torino, Italia, May 2024b. ELRA and ICCL. URL <https://aclanthology.org/2024.lrec-main.782/>.
- Jialun Zhong, Wei Shen, Yanzeng Li, Songyang Gao, Hua Lu, Yicheng Chen, Yang Zhang, Wei Zhou, Jinjie Gu, and Lei Zou. A comprehensive survey of reward models: Taxonomy, applications, challenges, and future, 2025a. URL <https://arxiv.org/abs/2504.12328>.

- Yinmin Zhong, Zili Zhang, Bingyang Wu, Shengyu Liu, Yukun Chen, Changyi Wan, Hanpeng Hu, Lei Xia, Ranchen Ming, Yibo Zhu, and A Jin. Optimizing rlhf training for large language models with stage fusion, 2025b. URL <https://arxiv.org/abs/2409.13221>.
- Andy Zhou, Bo Li, and Haohan Wang. Robust prompt optimization for defending language models against jailbreaking attacks, 2024a. URL <https://arxiv.org/abs/2401.17263>.
- Yujia Zhou, Yan Liu, Xiaoxi Li, Jiajie Jin, Hongjin Qian, Zheng Liu, Chaozhao Li, Zhicheng Dou, Tsung-Yi Ho, and Philip S. Yu. Trustworthiness in retrieval-augmented generation systems: A survey, 2024b. URL <https://arxiv.org/abs/2409.10102>.
- Yuqing Zhou, Ruixiang Tang, Ziyu Yao, and Ziwei Zhu. Navigating the shortcut maze: A comprehensive analysis of shortcut learning in text classification by language models, 2024c. URL <https://arxiv.org/abs/2409.17455>.
- Zhanke Zhou, Rong Tao, Jianing Zhu, Yiwen Luo, Zengmao Wang, and Bo Han. Can language models perform robust reasoning in chain-of-thought prompting with noisy rationales?, 2024d. URL <https://arxiv.org/abs/2410.23856>.
- Kehao Zhu, Yingye Zheng, and Kwun Chuen Gary Chan. Weighted brier score – an overall summary measure for risk prediction models with clinical utility consideration, 2024. URL <https://arxiv.org/abs/2408.01626>.