

Hetero-Designer: Automated Design of Multi-Agent Systems with Heterogeneous LLMs

Anonymous ACL submission

Abstract

LLM-based Multi-agent systems (MAS) have shown strong capabilities across a wide range of domains. Their success largely hinges on the collaboration topology design, which has emerged as a central research focus in the automated MAS design. However, existing approaches are fundamentally constrained by their reliance on homogeneous LLMs, which significantly limits overall system intelligence. In response to this limitation, we for the first time propose the concept of **Automated Design of Heterogeneous-LLMs-based MAS (ADHM)**. ADHM sheds light on a promising avenue for advancing collective intelligence, which focuses on the automated design of cost-effective MAS composed of diverse LLMs and roles to suit various queries. Toward this challenging goal, we propose **Hetero-Designer**, a novel pipeline that efficiently encodes intricate dependencies among queries, LLMs and roles through a novel Binary-Star Transformer and constructs Hetero-MAS in an autoregressive graph generation process. Extensive experiments demonstrate that **Hetero-Designer** is: (i) high-performing on various benchmarks, (ii) economical in reducing overhead, (iii) extensible to unseen LLMs and roles.

1 Introduction

Large Language Model (LLM)-based agents (Richards, 2023; Nakajima, 2023; Park et al., 2023), have demonstrated impressive capabilities across a wide range of tasks (Zhang et al., 2024; Li et al., 2025a; Schmidgall et al., 2025). Building on the success of individual agent, recent research has increasingly focused on multi-agent systems (MAS) (Du et al., 2024; Hong et al., 2024; Liang et al., 2024), which open up new avenues for advancing collective intelligence through synergistic interactions among agents with diverse expertise and specialized roles. Central to MAS lies the design of **collaboration topology**, a graph that defines how




Figure 1: A comparison case and complex intrinsic connection within Hetero-MAS.

agents with various roles are structured and how they exchange information (Zhang et al., 2025c; Li et al., 2025b; Yang et al., 2025; Liu et al., 2025).

Early research on MAS topology design focused on manually crafted static topologies, such as chain (Wei et al., 2022; Hong et al., 2024), tree (Yao et al., 2023; Wu et al., 2024) and complete graphs (Qian et al., 2025). Although such elaborately designed topologies can facilitate coordination in specific scenarios, Zhang et al. highlighted that their inherent rigidity results in significant variations in MAS performance and cost across tasks. To improve flexibility and efficiency, contemporary studies have progressively explored **automated topology design** (Yang et al., 2025), which leverages data-driven graph learning to adaptively tailor MAS to specific domains (Zhang et al., 2025c; Wang et al., 2025b) or fine-grained queries (Zhang et al., 2025d; Li et al., 2025b; Wang et al., 2025a).

Despite these advances, most automated frameworks rely on a homogeneous LLM (e.g., GPT-4o) to drive all agents. This one-LLM-fits-all paradigm is steadily exposing fundamental bottlenecks in the

overall intelligence of the system: recent studies reveal that homogeneous models often result in redundant topology design (Zhang et al., 2025c,g), constrained reasoning diversity and critical thinking (Zhang et al., 2025e), and a suboptimal balance between performance and cost (Yue et al., 2025). Empirical evidence, as illustrated in Figure 1(a), further underscores these limitations: a lightweight heterogeneous MAS with fewer agents can actually outperform a complex homogeneous system while incurring substantially lower token costs. Consequently, we for the first time introduce the concept of **Automated Design of Heterogeneous-LLMs-based MAS (ADHM)**, which sheds light on a promising avenue for advancing collective intelligence. ADHM focuses on the automated design of cost-effective MAS composed of diverse LLMs and roles to suit various queries.

Although several studies like LLM routing (Chen et al., 2024; Ong et al., 2025; Yue et al., 2025), and LLM & role assignment on predefined topologies (Ye et al., 2025; Hegazy, 2025) have made progress, these methods exhibit limitations for ADHM in: (i) **Predefined Topology**. They still rely on manually predefined topologies, which lack the structural flexibility to autonomously adapt to the specific nuances of each query; (ii) **Inadequate Modeling of Implicit Correlations**. As shown in Figure 1(b), designing cost-effective topologies requires precise modeling of the coupling agent roles and LLM capabilities under diverse queries. However, existing methods, following homogeneous MAS design (Zhang et al., 2025d), rely excessively on static semantic embeddings extracted by text encoder. Such static representations fail to capture the nuanced interrelations among heterogeneous LLMs, specialized roles and queries. Moreover, this information insufficiency further propagates through the topological construction process, resulting in suboptimal Hetero-MAS orchestration.

In response to these limitations, we propose **Hetero-Designer**, a novel pipeline that explicitly models and utilizes these complex interrelations to enable automated design of *flexible* and *cost-effective* Hetero-MAS. Technically, **Hetero-Designer** first encodes queries, LLMs and roles into semantic vectors. Subsequently, we design a Binary-Star Transformer (BSFormer) to synergize static features into enriched, dependency-aware representations by contextualizing the latent interplay among queries, LLMs, and roles. Specifically, BSFormer consists of two symmetric star-

shaped modules: LLM-former and Role-former, where the query serves as the central relay node and LLMs (or roles) act as satellite nodes. Within each module, multi-head attention extracts fine-grained representations; between modules, cross-attention facilitates bidirectional information coupling. Finally, **Hetero-Designer** formulates MAS construction as a flexible autoregressive graph generation problem, leveraging the efficient representations produced by BSFormer and a GRU-based graph encoder to alternately predict nodes (LLMs and roles) and edges, thereby step-by-step synthesizing the complete Hetero-MAS topology.

Our contributions can be summarized as follows:

- **Problem Definition:** We for the first time define Automated Design of Heterogeneous-LLM-based MAS (ADHM) and highlight that its challenge lies in modeling complex intrinsic connections among queries, LLMs and roles, which are essential for cost-effective Hetero-MAS topology design.
- **Practical Solution:** We introduce a novel pipeline, **Hetero-Designer**, which leverages a Binary-Star Transformer to model complex dependencies and flexibly constructs MAS through an autoregressive process.
- **Experimental Validation:** Extensive experiments across diverse benchmarks demonstrate that our method outperforms state-of-the-art baselines in both accuracy and cost-saving, demonstrating superior collective intelligence.

2 Formalization

2.1 Hetero-Multi-Agent-System

We model a MAS as a directed acyclic graph (DAG) $\mathcal{G} = \{\mathcal{V}, \mathcal{E}\}$, where $\mathcal{V} = \{v_i, \dots, v_{N_g}\}$ represents the set of nodes and edges $\mathcal{E} \subseteq \mathcal{V} \times \mathcal{V}$ denotes the flow of information among them. Each Node $v_i \in \mathcal{V}$ represents an agent instance, formalized as: $v_i = \{m_i, r_i, \text{State}_i, \text{Tool}_i\}$, where $m_i \in \mathbb{M} = \{m_1, m_2, \dots, m_{N_m}\}$ is the LLM powering v_i , while prior research employed homogeneous LLM to drive; $r_i \in \mathbb{R} = \{r_1, r_2, \dots, r_{N_r}\}$ indicates the agent’s role; State_i captures its memory and interaction history, Tool_i is a set of plugins available to v_i (e.g., code compilers, search engine). An edge $e_{ji} = (v_j, v_i) \in \mathcal{E}$ indicates that the output of agent v_j is propagated as an input to agent v_i . The set of direct predecessors of agent v_i is denoted by $\mathcal{N}_{in}(v_i) = \{v_j | (v_j, v_i) \in \mathcal{E}\}$. $\mathcal{G}$ executes tasks following a topological ordering derived from

$\mathcal{E}$. Each agent v_i generates a response o_i conditioned on its role-specific prompt, the global query Q , and the output set $\{o_j \mid v_j \in \mathcal{N}_{in}(v_i)\}$ from its predecessor agents. Finally, the final response a of $\mathcal{G}$ is produced by an aggregation function $\text{Aggregate}\{o_i \mid v_i \in \mathcal{V}\}$ (e.g., a summarizer agent).

2.2 Definition of ADHM

Based on the MAS defined above, we formalize Automated Design of Heterogeneous-LLMs-based MAS (ADHM): Given a query Q , a set of heterogeneous LLMs $\mathbb{M}$, and a set of candidate roles $\mathbb{R}$, ADHM aims to learn a mapping function: $f : (Q, \mathbb{M}, \mathbb{R}) \rightarrow \mathcal{G}$. The objective of f is to facilitate automated MAS design, achieving an ideal trade-off between task performance and costs:

$$\max_{P(\mathcal{G}|Q)} \mathbb{E}_{\substack{(Q, \hat{a}) \sim \mathcal{D}, \\ \mathcal{G} \in \mathcal{G} \sim P(\mathcal{G}|Q)}} [\underbrace{U(\mathcal{G}; Q, \hat{a})}_{\text{Performance}} - \lambda \cdot \underbrace{C(\mathcal{G}; Q)}_{\text{Cost}}], \quad (1)$$

where $(Q, \hat{a})$ denotes training instance in dataset $\mathcal{D}$, $\hat{a}$ is the ground-truth answer. $U(\cdot)$ denotes the performance on $\mathcal{D}$, while $C(\cdot)$ represents the corresponding API token cost. The probability of DAG $\mathcal{G}$ is specifically defined as a joint distribution:

$$P(\mathcal{G}|Q, \mathbb{M}, \mathbb{R}) = \prod_{i=1}^{|\mathcal{V}|} \underbrace{P(v_i | \mathcal{G}_{<i}, Q, \mathbb{M}, \mathbb{R})}_{\text{node probability}} \times \prod_{j=1}^{i-1} \underbrace{P(e_{ji} | v_i, \mathcal{G}_{<i}, Q)}_{\text{edge probability}} \quad (2)$$

where $\mathcal{G}_{<i}$ denotes the subgraph induced by the first $i-1$ nodes. The first term represents the joint probability of assigning role r_i and LLM m_i to node v_i . Within the ADHM paradigm, the topology, agent roles, and LLM selection are jointly designed. This departs from existing techniques such as pruning homogeneous graphs (Zhang et al., 2025c) or routing within predefined topologies (Yue et al., 2025).

2.3 Autoregressive Graph Generation

To make MAS topology generation process more tractable, we reformulate the problem as an autoregressive graph generation task (Zhang et al., 2019), where the model sequentially predicts node attributes v_i and their connectivity e_{ji} to preceding nodes. By decomposing global design into local decision-making steps, the model effectively navigates the vast search space (You et al., 2018; Wang et al., 2025a; Li et al., 2025b). To enable adaptive termination, we introduce a terminal node v_{end} ; its prediction signals that the MAS architecture is sufficient, concluding the generation process.

3 Hetero-Designer

Figure 2 illustrates the overall framework of **Hetero-Designer**. It begins by (i) encoding query, LLMs, roles, and the v_{end} into semantic embeddings. (ii) These embeddings are subsequently fed into a Binary-Star Transformer to capture the complex inter-dependencies. (iii) Ultimately, these enriched representations facilitate the autoregressive generation of the MAS. In addition, we train the model by cold-start supervision and reinforcement learning to enable superior Hetero-MAS Design.

3.1 Input Representation

Hetero-Designer first encodes all textual conditioning information into dense vector representations. Specifically, the textual instructions of query Q , is mapped into a fixed-dimensional vector $\mathbf{q} \in R^{d_i}$ by a pre-trained sentence encoder. This vector is then processed through a feed-forward network (FFN) with Layer Normalization (LN):

$$\mathbf{q} = \text{FFN}(\text{LN}(\text{SentenceEncoder}(Q))) \quad (3)$$

Similarly, each available LLM $m_i \in \mathbb{M}$, role $r_j \in \mathbb{R}$, and the end token v_{end} are projected into respective embeddings $\mathbf{m}_i$, $\mathbf{r}_j$, and $\mathbf{e}$. The representations are aggregated into embedding matrices $\mathbf{M} \in R^{N_m \times d_i}$ and $\mathbf{R} \in R^{N_r \times d_i}$, which serve as the foundational feature sets for the MAS Design.

3.2 Binary-Star Transformer

ADHM’s challenge lies in modeling the intricate correlations among queries, LLMs, and roles. Consequently, static semantic vectors ($\mathbf{q}$, $\mathbf{M}$, $\mathbf{R}$) alone fail to capture the complex dependencies essential for sophisticated MAS design. To this end, we propose a novel Binary-Star Transformer (BSFormer), which extends the architectural principles of the Star-Transformer (Guo et al., 2019).

Specifically, BSFormer comprises two symmetric modules: the LLM-Former and the Role-Former. Each module adopts a star-shaped topology consisting of a central relay node and $n+1$ satellite nodes. The relay nodes represent the query, and the satellite nodes represent the candidate set of either LLMs or agent roles, and the end token. Relay nodes in both modules are linked via cross-attention, enabling bidirectional information exchange between LLMs and roles. This bridges the semantic gap between model capabilities and functional roles, producing contextualized representations informed by global system dependencies.




Figure 2: The overall framework of our proposed **Hetero-Designer**.

Update of BSFormer. In the l -th layer, we denote the hidden states of the relay nodes as $\tilde{\mathbf{q}}_{llm}^l$ and $\tilde{\mathbf{q}}_{role}^l$, respectively. Correspondingly, the sets of satellite node representations are defined as $\tilde{\mathbf{S}}_{llm}^l = [\tilde{\mathbf{M}}^l; \tilde{\mathbf{e}}_{llm}^l]$ and $\tilde{\mathbf{S}}_{role}^l = [\tilde{\mathbf{R}}^l; \tilde{\mathbf{e}}_{role}^l]$. The input features are initialized using semantic embeddings, specifically $\mathbf{q}$, $[\mathbf{M}; \mathbf{e}]$, and $[\mathbf{R}; \mathbf{e}]$.

Based on multi-head attention, BSFormer updates satellite nodes and relay nodes sequentially. Each satellite node $\tilde{\mathbf{s}}_i^l$ is updated by integrating contextual information from the relay node $\tilde{\mathbf{q}}^{l-1}$, its own previous state $\tilde{\mathbf{s}}_i^{l-1}$, and its initial state $\tilde{\mathbf{s}}_i^0$:

$$\tilde{\mathbf{s}}_i^l = \text{MHAttn}(\tilde{\mathbf{s}}_i^{l-1}, \mathbf{C}_i^l), \mathbf{C}_i^l = [\tilde{\mathbf{s}}_i^{l-1}; \tilde{\mathbf{s}}_i^0; \tilde{\mathbf{q}}^{l-1}] \quad (4)$$

where $\mathbf{C}_i^l$ denotes the context of the i -th satellite node. The relay nodes $\tilde{\mathbf{q}}_{llm}^l$ and $\tilde{\mathbf{q}}_{role}^l$ are updated via their respective satellites and prior states, followed by information exchange via cross-attention:

$$\begin{aligned} \tilde{\mathbf{q}}_{llm}^l &= \text{MHAttn}(\tilde{\mathbf{q}}_{llm}^{l-1}, [\tilde{\mathbf{q}}_{llm}^{l-1}; \tilde{\mathbf{S}}_{llm}^l]) \\ \tilde{\mathbf{q}}_{role}^l &= \text{MHAttn}(\tilde{\mathbf{q}}_{role}^{l-1}, [\tilde{\mathbf{q}}_{role}^{l-1}; \tilde{\mathbf{S}}_{role}^l]) \\ \tilde{\mathbf{q}}_{llm}^l &= \text{CrossAttn}(\tilde{\mathbf{q}}_{llm}^l, [\tilde{\mathbf{q}}_{llm}^l; \tilde{\mathbf{q}}^0; \tilde{\mathbf{q}}_{role}^l]) \\ \tilde{\mathbf{q}}_{role}^l &= \text{CrossAttn}(\tilde{\mathbf{q}}_{role}^l, [\tilde{\mathbf{q}}_{role}^l; \tilde{\mathbf{q}}^0; \tilde{\mathbf{q}}_{llm}^l]) \end{aligned} \quad (5)$$

Afterwards, the updated nodes are regularized through a layer normalization. The enriched representations from last layer N_l of BSFormer serve as the foundational input for the autoregressive MAS generation process, which subsequent empirical results demonstrate these representations' capability for cost-effective MAS design.

3.3 Autoregressive MAS Generation

After modeling the complex correlations, we designed a GRU-based network (Chung et al., 2014) to organize information into a structured topology. Specifically, at each time step t , the model first encodes graph to obtain the node embeddings $\mathbf{H}^t \in R^{(t+1) \times d_g}$ and the graph embedding $\mathbf{g}^t \in R^{d_g}$. Subsequently, we utilize the updated representations $\mathbf{H}^t$ and $\mathbf{g}^t$ to alternately perform Node and Edge Prediction, thereby constructing the MAS step by step in an autoregressive manner. **DAG Graph Encoder.** The encoder input $\mathbf{x}_{i,j}^t$ is synthesized by aggregating information from LLM and role of v^t via $\text{MLP}([\tilde{\mathbf{m}}_i^{N_l}; \tilde{\mathbf{r}}_j^{N_l}])$. At $t = 0$, we employ $\text{MLP}([\tilde{\mathbf{q}}_{llm}^{N_l}; \tilde{\mathbf{q}}_{role}^{N_l}])$ as the initial graph input $\mathbf{x}^0$, thereby enabling query-adaptive MAS design. Additionally, to enhance topological awareness of DAG, we concatenate positional encodings to each input feature $\hat{\mathbf{x}}^t = [\mathbf{x}^t; \mathbf{PE}(v^t)]$.

Following the DAG modeling approach established by Zhang et al., node hidden states are updated according to their topological ordering:

$$\begin{aligned} \mathbf{h}^t &= \mathcal{U}(\hat{\mathbf{x}}^t, \mathbf{h}_{in}^t) \\ \mathbf{h}_{in}^t &= \mathcal{A}(\{\mathbf{h}^k : v^k \in \mathcal{N}_{in}(v^t)\}) \end{aligned} \quad (6)$$

where $\mathcal{U}$ and $\mathcal{A}$ denote the update and aggregation functions. Specifically, we employ a GRU for node updates, and $\mathcal{A}$ is a gated sum:

$$\mathbf{h}_{in}^t = \sum_{v^k \in \mathcal{N}_{in}(v^t)} \varphi(\mathbf{h}^k) \odot \sigma(\mathbf{h}^k) \quad (7)$$

where φ is a mapping network and σ is a gating network. Once all node hidden states are sequentially

Method	LLM	Mul.	Hetero.	Flex.	MMLU	GSM8K	MATH	HumanEval	MBPP	Avg.
Vanilla	gpt-4o-mini	✗	✗	✗	77.81	93.17	66.09	85.71	72.20	79.00
	claude-3.5-haiku	✗	✗	✗	67.97	92.16	65.89	86.33	73.40	77.15
	gemini-1.5-flash	✗	✗	✗	80.04	92.67	74.39	82.61	73.00	80.54
	llama-3.1-70b	✗	✗	✗	79.08	92.68	60.31	80.75	68.20	76.20
CoT	gpt-4o-mini	✗	✗	✗	78.43	93.68	67.24	86.69	69.60	79.13
	gemini-1.5-flash	✗	✗	✗	81.35	92.92	74.34	81.37	73.00	80.60
SC(CoT)	gpt-4o-mini	✗	✗	✗	81.05	93.32	66.28	87.58	73.00	80.25
	gemini-1.5-flash	✗	✗	✗	81.66	93.43	74.37	80.75	72.00	80.44
Chain	gpt-4o-mini	✓	✗	✗	82.01	94.40	64.72	85.63	75.40	80.43
Tree	gemini-1.5-flash	✓	✗	✗	83.01	93.13	72.10	82.50	73.20	80.79
	gpt-4o-mini	✓	✗	✗	82.98	93.89	65.11	87.50	75.60	81.02
Complete Graph	gemini-1.5-flash	✓	✗	✗	81.74	94.91	71.36	77.50	73.60	79.82
	gpt-4o-mini	✓	✗	✗	83.06	94.66	67.63	85.00	75.20	81.11
LLM-Debate	gemini-1.5-flash	✓	✗	✗	81.35	94.40	68.60	83.75	74.20	80.46
	gpt-4o-mini	✓	✗	✗	81.04	94.66	64.68	84.38	73.60	79.67
Agentprune	gemini-1.5-flash	✓	✗	✗	80.40	93.98	72.45	79.38	73.40	79.92
	gpt-4o-mini	✓	✗	✗	83.02	94.89	68.45	86.80	75.40	81.71
AFlow	gemini-1.5-flash	✓	✗	✗	83.10	93.88	73.54	82.55	75.80	81.77
	gpt-4o-mini	✓	✗	✗	83.10	92.30	73.35	90.06	82.20	84.20
MaAS	gemini-1.5-flash	✓	✗	✗	82.35	94.91	72.70	85.69	76.00	82.33
	gpt-4o-mini	✓	✗	✗	83.01	92.30	74.45	<u>92.85</u>	82.17	84.96
FrugalGPT	gemini-1.5-flash	✓	✗	✗	83.42	93.36	75.18	90.55	82.69	85.04
	LLM pool	✗	✓	✗	76.24	90.76	67.05	87.31	74.40	79.15
RouterDC	LLM Pool	✗	✓	✗	82.01	93.68	73.46	87.75	75.20	82.42
MasRouter	LLM Pool	✓	✓	✗	84.25	95.45	75.42	90.62	84.00	85.93
Hetero-Designer	LLM Pool	✓	✓	✓	89.54	95.92	79.52	93.80	84.60	88.68

Table 1: Performance comparison against baseline methods. The best results are shown in **bold**, and the second-best results is underlined. "Mul." and "Hetero." indicate support for multi-agent and heterogeneous LLMs settings. "Flex." denotes flexible topology design. ✗, ✗, and ✓ signifies no/partial/full support in these aspects.

updated, a readout function ϕ aggregates these representations into a global graph embedding $\mathbf{g}^t$.

Node Prediction. We perform joint prediction for both LLM and role. This manner captures the inherent coupling of specific LLM-role pairs. Concretely, we use an extensible metric learning-based module for node generation, the score $s_{i,j}^t$ of a LLM-role pair ($m_i \& r_j$) is acquired by a dot product operation: $\text{MLP}_g(\mathbf{g}^t) \cdot \text{MLP}_{node}([\tilde{\mathbf{m}}_i^{N_l}; \tilde{\mathbf{r}}_j^{N_l}])$. Similarly, $s_{end}^t = \text{MLP}_g(\mathbf{g}^t) \cdot \text{MLP}_{node}([\tilde{\mathbf{e}}_{llm}^{N_l}; \tilde{\mathbf{e}}_{role}^{N_l}])$. Finally, we can obtain the predicted probability:

$$P(v^t | \mathcal{G}_{<t}, \mathcal{Q}, \mathbb{M}, \mathbb{R}) = \text{softmax}(\{s_{i,j}^t\} \cup \{s_{end}^t\}) \quad (8)$$

Edge Prediction. Once agent node v^t is chosen, the edge generator determines its incoming connections from existing agents $v^1, \dots, v^{t-1}$ through:

$$s_{edge}^{i,t} = \text{MLP}_{pre}([\mathbf{h}^i; \mathbf{g}^t]) \cdot \text{MLP}_{cur}([\tilde{\mathbf{m}}_{cur}^{N_l}; \tilde{\mathbf{r}}_{cur}^{N_l}]) \quad (9)$$

We can then obtain the probability of edge $e_{i,t}$ by:

$$P(e_{i,t} = 1 | v^t, \mathcal{G}_{<t}, \mathcal{Q}) = \text{Sigmoid}(s_{edge}^{i,t}) \quad (10)$$

3.4 Optimization

Cold Start. We collect a subset $\mathcal{D}_{\text{cold}}$ containing successful instances for supervised training. This stage aims to (i) train the model to generate valid

collaboration topologies, and (ii) characterize the initial cost and capability distributions of LLMs and roles. This cold-start training equips the model with a foundational capacity for topology generation, enabling the next RL phase to focus on exploring and optimizing high-value strategic designs. Specifically, for each query, we randomly sample multiple candidate topologies and retain only those instances that successfully complete the task.

Reinforcement Learning. Subsequently, we conduct reinforcement learning on $\mathcal{D} \setminus \mathcal{D}_{\text{cold}}$, optimizing the network via the objective in Eq. 1 to discover superior strategies. To account for varying query complexities and resource costs, we perform K independent samplings per query to facilitate robust exploration. We employ an empirical Bayes Monte Carlo procedure (Carlin and Louis, 2000; Zhang et al., 2025b) to estimate the gradient loss:

$$\begin{aligned} \nabla \mathcal{L} &\approx \frac{1}{K} \sum_{(\mathcal{Q}, a) \in \mathcal{D}_{RL}} \sum_{k=1}^K [A_k \nabla_{\pi} P(\mathcal{G}_k | \mathcal{Q}, \mathbb{M}, \mathbb{R})], \\ A_k &= \frac{p(a | \mathcal{Q}, \mathcal{G}_k)}{\sum_i p(a | \mathcal{Q}, \mathcal{G}_i)} - \lambda \cdot \frac{C(\mathcal{G}_k; \mathcal{Q})}{\sum_i C(\mathcal{G}_i; \mathcal{Q})}, \end{aligned} \quad (11)$$

where A_k denotes the cost-aware importance weights of the MAS, $p(a | \mathcal{Q}, \mathcal{G}_k) \in \{0, 1\}$ is the task success indicator for $\mathcal{G}_k$. In addition to the current samples $\mathcal{D}_{\text{cur}}$, we sample several strategies




Figure 3: Comparison of performance and inference cost on Humaneval. Different shapes of the scatter points represent various types of baselines, and different colors of the points indicate different LLM backbones.

from historical trajectories $\mathcal{D}_{\text{replay}}$ and $\mathcal{D}_{\text{cold}}$. The resulting training pool $\mathcal{D}_{\text{RL}}$ facilitates efficient experience replay and robust exploration.

Extended technical details on model architectures, training and inference specifics and the algorithmic workflow, are provided in Appendix B.

4 Experiments

4.1 Experimental Setup

Benchmarks & Metric. Following Yue et al., we evaluated model on three categories of datasets: ■ **General Reasoning:** MMLU (Hendrycks et al., 2021a); ■ **Mathematical Reasoning:** GSM8K (Cobbe et al., 2021), MATH (Hendrycks et al., 2021b); ■ **Code:** HumanEval (Chen et al., 2021), MBPP (Austin et al., 2021). We use Accuracy to evaluate MMLU, GSM8K, and MATH, and Pass@1 to evaluate MBPP and HumanEval.

Baselines. We compare our method with (i) single-agent approaches, including COT (Wei et al., 2022), Self-Consistency (Wang et al., 2023); (ii) fixed topologies including Chain, Tree, and Complete Graph (Qian et al., 2025), LLM-Debate (Du et al., 2025); (iii) dynamic MAS like AgentPrune (Zhang et al., 2025c), AFlow (Zhang et al., 2025f) and MaAS (Zhang et al., 2025b); (iv) LLM routers, FrugalGPT (Chen et al., 2023), RouterDC (Chen et al., 2024) and MasRouter (Yue et al., 2025).

LLM Backbones. For fair comparison, we adopt the same LLM backbones with varying sizes and capacities as Yue et al., including: gpt-4o-mini, claude-3.5-haiku, gemini-1.5-Flash and llama-3.1-70b. Furthermore, we selected several cutting-edge models along a chronological timeline to evaluate the inductive capabilities of Hetero-Designer, including: DeepSeek-V3 (2024.12),

gpt-5-mini (2025.8), claude-4.5-Haiku (2025.10), and gemini-3-Flash (2025.12)

Implementation Details. We set the learning rate $lr_{\text{cold}} = 1e - 4$ for cold start and $lr_{\text{RL}} = 1e - 5$ for reinforcement learning. The temperature $\tau = 1$. To mitigate the structural imbalance, we employ a weight $\alpha = 0.7$ to scale the log-probability, assigning α to nodes and $1 - \alpha$ to edges. The cost penalty $\lambda \in \{5e - 2, 1e - 1\}$. Both our model and the MAS baselines employ a maximum agent count of $\gamma = 6$. We use all-MiniLM-L6-v2 (Wang et al., 2020) as the semantic encoder. The semantic and graph embedding dim set to $d_i = 128$ and $d_g = 256$, respectively. The layer num $N_l = 4$. Following Yue et al., our role pool features 26 distinct roles, ranging from programmers with compilers to researchers leveraging Wikipedia for information retrieval.

4.2 Main Results

In this section, we evaluate Hetero-Designer against multiple baselines across five benchmarks. We verify our methods is:

High-performing. The experimental results in Table 1 demonstrates that **Hetero-Designer** excels at constructing an effective Hetero-MAS. Specifically, (i) **Hetero-Designer** achieves the best performance across all five benchmarks, consistently outperforming a wide range of baselines. The superior performance demonstrates the effectiveness of Hetero-MAS designed by **Hetero-Designer**. (ii) Compared to the strongest automated baseline, MaAS, **Hetero-Designer** achieves an average improvement of 3.68%. This markedly outperforms homogeneous systems, demonstrating that the efficient integration of heterogeneous LLMs leads to superior collective intelligence. (iii) Compared to router-based methods, the success of **Hetero-Designer** suggests that MAS benefits more from query-adaptive topology synthesis rather than relying on static, predefined structures. **Token-economical.** **Hetero-Designer** leverages hetero-LLMs to construct adaptive topologies, thereby mitigating over-engineering and reducing operational costs. Consequently, it achieves the best cost-performance trade-off on the HumanEval Pareto front (Figure 3). Notably, in Math benchmarks, our model exhibits a notable decline in expenditures (from 1.59\$ to 0.68\$ on GSM8K and 3.59\$ to 0.73\$ on MATH, compared to MasRouter), alongside a 0.47%–4.1% accuracy improvement. This underscores **Hetero-Designer**’s capacity to achieve superior intelligence with sig-

Dataset	GSM8K		MATH	
Metric	Accuracy (%)	Cost (\$)	Accuracy (%)	Cost (\$)
Hetero-Designer	95.92	0.68	79.52	0.73
w/o q	94.98	1.10	64.34	0.68
w/o LLM Pool	93.27	0.48	65.78	0.59
w/o BSFormer	94.31	0.57	70.12	0.49
w/o Cold Start	93.65	1.04	72.77	0.76
w/o $C(\cdot)$	95.73	1.21	80.96	0.89

Table 2: Ablation results of Hetero-Designer on GSM8K and MATH.

nificantly higher resource efficiency.

4.3 Ablation Study

We conduct an ablation study on the key modules of **Hetero-Designer**: (i) *w/o q*, the query embeddings are set to zero vectors, (ii) *w/o LLM Pool*, which replaces the Hetero-LLMs with the same LLM (gpt-4o-mini), (iii) *w/o BSFormer*, which uses the raw semantic embeddings without BSFormer. (iv) *w/o Cold Start*, which removes the cold start training, (v) *w/o $C(\cdot)$* , which removes the cost penalty in Eq.1. As shown in Table 2, removing the query information, the model fails to adaptively design MAS based on task difficulty, leading to suboptimal performance and inflated costs. A significant performance degradation is observed when using homogeneous LLM, underscoring its inherent limitations. The exclusion of BSFormer precludes the effective modeling of intricate connections, confirming that raw semantic features alone are inadequate for synthesizing high-performance MAS topologies. Furthermore, the absence of a cold-start hinders effective exploration of superior policies during the reinforcement learning phase. Meanwhile, removing the cost penalty results in uneconomical designs with inflated costs.

4.4 Inductive & Extensible Ability Analysis

In this section, we validate the inductive and extensible capabilities of **Hetero-Designer**. Specifically, we demonstrate that our model consistently generalizes to unseen LLMs and roles without the need for intensive re-training.

Generalization to Unseen LLMs. Figure 4 illustrates the evolution of system performance and cost on MATH as additional LLMs are progressively incorporated into the LLM pool. Correspondingly, Figure 5 presents the selection distribution across available LLMs. With the continuous integration of new models, the system’s performance exhibits




Figure 4: Evolution of performance and cost on MATH benchmark as models are added over time.




Figure 5: The selected LLM distribution of Hetero-Designer on MATH benchmark.

a steady increase, rising from 79.52% to 93.01%. Furthermore, the system does not experience a cost explosion; instead, it maintains a reasonable equilibrium and even exhibits a downward trend with the incorporation of Gemini-3-Flash. The distribution reveals that new models are effectively utilized, with legacy versions exhibiting a clear substitution trend (e.g., GPT-5-mini accounts for 19.3%, whereas GPT-4o-mini decreases to 8.5%).

Extensibility to Novel Roles. Figure 6 illustrates the performance across MMLU subsets as new roles are progressively integrated, alongside a case of designed MAS on expanded roles. Specifically, we generated domain-specific roles for each subset (e.g. Cell Biologist for Biology and Programming Expert for Computer Science). Increasing role diversity boosts MAS performance by 6% in Math and 5% in Computer Science, confirming that **Hetero-Designer** successfully capitalizes on specialized roles to strengthen system synergy. The case study demonstrates that the system effectively performs role substitution and seamlessly integrates these roles into the original topological design, thereby yielding superior responses.

4.5 Representation Analysis

To verify whether Hetero-Designer captures the fine-grained features of LLM-role pairs and forms




Figure 6: (a) Performance evolution on MMLU subsets with the incremental addition of new roles. (b) A design case of expanded agent role pool on College Biology.




Figure 7: (a) Embedding of different roles for the same LLM. (b) Embedding of different LLM-role pair.

discriminative representations, we employ t-SNE (Maaten and Hinton, 2008) in Figure 7 to visualize the learned embeddings by BSFormer of LLM-role pairs of different queries in MATH. In Figure 7(a), the representations of various roles within gpt-4o-mini retain a clear separation, suggesting that the model effectively captures and distinguishes the unique functional characteristics of each role. Figure 7 (b) further demonstrates a distinct separation in the representations space of various LLM-role pairs, suggesting that the embeddings generated by BSFormer effectively capture the implicit associations between LLMs and roles, thereby facilitating subsequent MAS design.

4.6 Case Study & sensitivity Analysis

In Appendix C.1, we showcase various Hetero-MAS examples constructed by **Hetero-Designer** across five datasets, illustrating how it adaptively tailors MAS architectures to tasks of varying difficulty. Furthermore, we provide a detailed sensitivity analysis of three core parameters—the number of agents γ , the cost penalty λ , and the sampling count K in Appendix C.2.

5 Related Work

Multi-Agent System Design. Contemporary LLM-based MAS has evolved through three stages: (i) **Static topology.** From chain (Wei et al., 2022; Hong et al., 2024), tree (Yao et al., 2023; Wu et al., 2024), complete graph (Qian et al., 2025), sparse graph (Li et al., 2024), LLM-Debate (Du et al., 2024) to optimizable graph (Zhuge et al., 2024). (ii) **Task-Specific Design.** Subsequently, research shifted toward automated design universal topologies for specific-task, including: edge pruning (Zhang et al., 2025c), joint node-and-edge pruning (Wang et al., 2025b; Zhang et al., 2025g), and search-based paradigms (Zhang et al., 2025f; Hu et al., 2025a). (iii) **query-specific Design.** Recently, researchers have shifted focus toward query-

specific MAS design, such as GNN-based network (Zhang et al., 2025d), agent supernet search (Zhang et al., 2025b) and autoregressive generation (Wang et al., 2025a; Li et al., 2025b), provide unparalleled flexibility and results. Inspired by this, we build MAS in autoregressive generation manner.

Heterogeneous LLM Collaboration. However, contemporary MAS design approaches remain LLM-homogeneous, failing to effectively organize heterogeneous LLM-agents. Ye et al. highlights promising prospects of hetero-MAS through a comprehensive analysis. Despite progress in routing and assignment strategies (Yue et al., 2025; Ye et al., 2025; Zhang et al., 2025a; Hegazy, 2025), these methods fail to achieve fully topological flexibility, as they dependent on predefined topology rather than automated design. We define the ADHM framework for the first time and identify its core challenge: modeling the intricate, implicit correlations between queries, LLMs, agent roles, and topologies. To this end, we propose **Hetero-Designer**, a novel model designed for the effective construction synergistic hetero-MAS.

6 Conclusion

In this paper, we for the first time define the concept of **Automated Design of Heterogeneous-LLMs-based MAS (ADHM)**, which aims to automatically design the MAS topology alongside the assignment of agent roles with heterogeneous LLM backbones to suit various queries. Toward this challenging goal, we propose **Hetero-Designer**, a novel pipeline that captures complex interactions among query, LLMs and roles via a Binary-Star Transformer and construct Hetero-MAS through an autoregressive graph generation process. Extensive experimental results demonstrate that **Hetero-Designer** is: (i) high-performing across various benchmarks, (ii) cost-effective in reducing overhead, and (iii) highly extensible to previously unseen models and roles.

7 Limitations

We argue that the main limitations of our work are mainly twofold:

(i) Fixed Agent Role Set. Following existing literature, our study assumes a set of predefined agent roles. However, in complex real-world scenarios, agent roles may need to be dynamically generated and optimized to meet evolving task requirements. While our framework currently lacks the capability for autonomous role discovery, our experiments demonstrate that **Hetero-Designer** possesses robust role-modeling and extensibility capabilities. This foundation paves the way for integrating our heterogeneous MAS design with role-optimization techniques proposed by Wang et al.; Yuan et al., thereby further enhancing the openness and adaptability of the system.

(ii) Lack of Collaborative Memory Accumulation. The collaboration among heterogeneous LLMs in our framework does not explicitly model the accumulation and evolution of long-term memory (Hu et al., 2025b; Wei et al., 2025). While **Hetero-Designer** focuses on optimizing collaboration topologies within a single task, it does not yet account for experience retention or capability evolution across multiple tasks. This limitation hinders the system from developing continuously refined coordination patterns. Future work could incorporate shared memory architectures or evolutionary parameter updates to support the collaborative co-evolution of multi-agents during long-term interactions.

References

- Jacob Austin, Augustus Odena, Maxwell Nye, Maarten Bosma, Henryk Michalewski, David Dohan, Ellen Jiang, Carrie Cai, Michael Terry, Quoc Le, and 1 others. 2021. [Program synthesis with large language models](#). *arXiv preprint arXiv:2108.07732*.
- Bradley P Carlin and Thomas A Louis. 2000. [Empirical bayes: Past, present and future](#). *Journal of the American Statistical Association*, 95(452):1286–1289.
- Lingjiao Chen, Matei Zaharia, and James Zou. 2023. [Frugalgpt: How to use large language models while reducing cost and improving performance](#). *Transactions on Machine Learning Research*.
- Mark Chen, Jerry Tworek, Heewoo Jun, Qiming Yuan, Henrique Ponde de Oliveira Pinto, Jared Kaplan, Harri Edwards, Yuri Burda, Nicholas Joseph, Greg Brockman, Alex Ray, Raul Puri, Gretchen Krueger, Michael Petrov, Heidy Khlaaf, Girish Sastry, Pamela

- Mishkin, Brooke Chan, Scott Gray, and 39 others. 2021. [Evaluating large language models trained on code](#). *Preprint*, arXiv:2107.03374.
- Shuhao Chen, Weisen Jiang, Baijiong Lin, James Kwok, and Yu Zhang. 2024. [RouterDC: Query-based router by dual contrastive learning for assembling large language models](#). In *The Thirty-eighth Annual Conference on Neural Information Processing Systems*.
- Junyoung Chung, Caglar Gulcehre, KyungHyun Cho, and Yoshua Bengio. 2014. [Empirical evaluation of gated recurrent neural networks on sequence modeling](#). *Advances in neural information processing systems*.
- Karl Cobbe, Vineet Kosaraju, Mohammad Bavarian, Mark Chen, Heewoo Jun, Lukasz Kaiser, Matthias Plappert, Jerry Tworek, Jacob Hilton, Reiichiro Nakano, and 1 others. 2021. [Training verifiers to solve math word problems](#). *arXiv preprint arXiv:2110.14168*.
- Yilun Du, Shuang Li, Antonio Torralba, Joshua B Tenenbaum, and Igor Mordatch. 2024. [Improving factuality and reasoning in language models through multiagent debate](#). In *International Conference on Machine Learning*, pages 11733–11763. PMLR.
- Yilun Du, Shuang Li, Antonio Torralba, Joshua B. Tenenbaum, and Igor Mordatch. 2025. [Improving factuality and reasoning in language models through multiagent debate](#). In *Proceedings of the 41st International Conference on Machine Learning*.
- Qipeng Guo, Xipeng Qiu, Pengfei Liu, Yunfan Shao, Xiangyang Xue, and Zheng Zhang. 2019. [Star-transformer](#). In *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers)*, pages 1315–1325, Minneapolis, Minnesota. Association for Computational Linguistics.
- Mahmood Hegazy. 2025. [Diversity of thought elicits stronger reasoning capabilities in multi-agent debate frameworks](#). *Preprint*, arXiv:2410.12853.
- Dan Hendrycks, Collin Burns, Steven Basart, Andy Zou, Mantas Mazeika, Dawn Song, and Jacob Steinhardt. 2021a. [Measuring massive multitask language understanding](#). In *International Conference on Learning Representations*.
- Dan Hendrycks, Collin Burns, Saurav Kadavath, Akul Arora, Steven Basart, Eric Tang, Dawn Song, and Jacob Steinhardt. 2021b. [Measuring mathematical problem solving with the math dataset](#). In *Thirty-fifth Conference on Neural Information Processing Systems Datasets and Benchmarks Track*.
- Sirui Hong, Mingchen Zhuge, Jonathan Chen, Xiawu Zheng, Yuheng Cheng, Jinlin Wang, Ceyao Zhang, Zili Wang, Steven Ka Shing Yau, Zijuan Lin, Liyang Zhou, Chenyu Ran, Lingfeng Xiao, Chenglin Wu,

695	and Jürgen Schmidhuber. 2024. MetaGPT: Meta programming for a multi-agent collaborative framework . In <i>The Twelfth International Conference on Learning Representations</i> .	749
696		750
697		751
698		752
699	Shengran Hu, Cong Lu, and Jeff Clune. 2025a. Automated design of agentic systems . In <i>The Thirteenth International Conference on Learning Representations</i> .	753
700		754
701		755
702		
703	Yuyang Hu, Shichun Liu, Yanwei Yue, Guibin Zhang, Boyang Liu, Fangyi Zhu, Jiahang Lin, Honglin Guo, Shihan Dou, Zhiheng Xi, Senjie Jin, Jiejun Tan, Yanbin Yin, Jiongnan Liu, Zeyu Zhang, Zhongxiang Sun, Yutao Zhu, Hao Sun, Boci Peng, and 28 others. 2025b. Memory in the age of ai agents . <i>Preprint</i> , arXiv:2512.13564.	756
704		757
705		758
706		759
707		760
708		761
709		
710	Junkai Li, Yunghwei Lai, Weitao Li, Jingyi Ren, Meng Zhang, Xinhui Kang, Siyu Wang, Peng Li, Ya-Qin Zhang, Weizhi Ma, and Yang Liu. 2025a. Agent hospital: A simulacrum of hospital with evolvable medical agents . <i>Preprint</i> , arXiv:2405.02957.	762
711		763
712		
713		
714		
715	Shiyuan Li, Yixin Liu, Qingsong Wen, Chengqi Zhang, and Shirui Pan. 2025b. Assemble your crew: Automatic multi-agent communication topology design via autoregressive graph generation . <i>Preprint</i> , arXiv:2507.18224.	764
716		765
717		766
718		767
719		768
720	Yunxuan Li, Yibing Du, Jiageng Zhang, Le Hou, Peter Grabowski, Yeqing Li, and Eugene Ie. 2024. Improving multi-agent debate with sparse communication topology . In <i>Findings of the Association for Computational Linguistics: EMNLP 2024</i> , pages 7281–7294, Miami, Florida, USA. Association for Computational Linguistics.	769
721		770
722		771
723		772
724		773
725		
726		
727	Tian Liang, Zhiwei He, Wenxiang Jiao, Xing Wang, Yan Wang, Rui Wang, Yujiu Yang, Shuming Shi, and Zhaopeng Tu. 2024. Encouraging divergent thinking in large language models through multi-agent debate . In <i>Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing</i> , pages 17889–17904, Miami, Florida, USA. Association for Computational Linguistics.	774
728		775
729		776
730		777
731		
732		
733		
734		
735	Yixin Liu, Guibin Zhang, Kun Wang, Shiyuan Li, and Shirui Pan. 2025. Graph-augmented large language model agents: Current progress and future prospects . <i>Preprint</i> , arXiv:2507.21407.	778
736		779
737		780
738		781
739	Laurens van der Maaten and Geoffrey Hinton. 2008. Visualizing data using t-sne . <i>Journal of machine learning research</i> , 9(Nov):2579–2605.	782
740		783
741		784
742	Yohei Nakajima. 2023. Babyagi. <i>GitHub repository</i> .	785
743		786
744		787
745		788
746		
747		
748		
	Joon Sung Park, Joseph O’Brien, Carrie Jun Cai, Meredith Ringel Morris, Percy Liang, and Michael S. Bernstein. 2023. Generative agents: Interactive simulacra of human behavior . In <i>Proceedings of the 36th Annual ACM Symposium on User Interface Software and Technology</i> , New York, NY, USA. Association for Computing Machinery.	789
		790
		791
		792
		793
		794
		795
		796
		797
		798
	Chen Qian, Zihao Xie, YiFei Wang, Wei Liu, Kunlun Zhu, Hanchen Xia, Yufan Dang, Zhuoyun Du, Weize Chen, Cheng Yang, Zhiyuan Liu, and Maosong Sun. 2025. Scaling large language model-based multi-agent collaboration . In <i>The Thirteenth International Conference on Learning Representations</i> .	799
		800
		801
		802
		803
		804
	Toran Bruce Richards. 2023. Auto-gpt: An autonomous gpt-4 experiment .	
	Samuel Schmidgall, Yusheng Su, Ze Wang, Ximeng Sun, Jialian Wu, Xiaodong Yu, Jiang Liu, Michael Moor, Zicheng Liu, and Emad Barsoum. 2025. Agent laboratory: Using llm agents as research assistants . <i>Preprint</i> , arXiv:2501.04227.	
	Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Łukasz Kaiser, and Illia Polosukhin. 2017. Attention is all you need . <i>Advances in neural information processing systems</i> , 30.	
	Song Wang, Zhen Tan, Zihan Chen, Shuang Zhou, Tianlong Chen, and Jundong Li. 2025a. Anymac: Cascading flexible multi-agent collaboration via next-agent prediction . <i>Preprint</i> , arXiv:2506.17784.	
	Wenhui Wang, Furu Wei, Li Dong, Hangbo Bao, Nan Yang, and Ming Zhou. 2020. Minilm: Deep self-attention distillation for task-agnostic compression of pre-trained transformers . <i>Advances in neural information processing systems</i> , 33:5776–5788.	
	Xuezhi Wang, Jason Wei, Dale Schuurmans, Quoc V Le, Ed H Chi, Sharan Narang, Aakanksha Chowdhery, and Denny Zhou. 2023. Self-consistency improves chain of thought reasoning in language models . In <i>The Eleventh International Conference on Learning Representations</i> .	
	Zhenhailong Wang, Shaoguang Mao, Wenshan Wu, Tao Ge, Furu Wei, and Heng Ji. 2024. Unleashing the emergent cognitive synergy in large language models: A task-solving agent through multi-persona self-collaboration . In <i>Proceedings of the 2024 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies (Volume 1: Long Papers)</i> , pages 257–279, Mexico City, Mexico. Association for Computational Linguistics.	
	Zhexuan Wang, Yutong Wang, Xuebo Liu, Liang Ding, Miao Zhang, Jie Liu, and Min Zhang. 2025b. Agent-Dropout: Dynamic agent elimination for token-efficient and high-performance LLM-based multi-agent collaboration . In <i>Proceedings of the 63rd Annual Meeting of the Association for Computational</i>	

805	<i>Linguistics (Volume 1: Long Papers)</i> , pages 24013–	Guibin Zhang, Kaijie Chen, Guancheng Wan, Heng	862
806	24035, Vienna, Austria. Association for Computa-	Chang, Hong Cheng, Kun Wang, Shuyue Hu, and	863
807	tional Linguistics.	Lei Bai. 2025a. EvoFlow: Evolving diverse agentic	864
808	Jason Wei, Xuezhi Wang, Dale Schuurmans, Maarten	workflows on the fly . <i>Preprint</i> , arXiv:2502.07373.	865
809	Bosma, brian ichter, Fei Xia, Ed H. Chi, Quoc V Le,	Guibin Zhang, Luyang Niu, Junfeng Fang, Kun Wang,	866
810	and Denny Zhou. 2022. Chain of thought prompt-	LEI BAI, and Xiang Wang. 2025b. Multi-agent archi-	867
811	ing elicits reasoning in large language models . In	tecture search via agentic supernet . In <i>Forty-second</i>	868
812	<i>Advances in Neural Information Processing Systems</i> .	<i>International Conference on Machine Learning</i> .	869
813	Tianxin Wei, Noveen Sachdeva, Benjamin Coleman,	Guibin Zhang, Yanwei Yue, Zhixun Li, Sukwon Yun,	870
814	Zhankui He, Yuanchen Bei, Xuying Ning, Mengting	Guancheng Wan, Kun Wang, Dawei Cheng, Jef-	871
815	Ai, Yunzhe Li, Jingrui He, Ed H Chi, and 1 oth-	frey Xu Yu, and Tianlong Chen. 2025c. Cut the	872
816	ers. 2025. Evo-memory: Benchmarking llm agent	crap: An economical communication pipeline for	873
817	test-time learning with self-evolving memory . <i>arXiv</i>	LLM-based multi-agent systems . In <i>The Thirteenth</i>	874
818	<i>preprint arXiv:2511.20857</i> .	<i>International Conference on Learning Representa-</i>	875
819	Qingyun Wu, Gagan Bansal, Jieyu Zhang, Yiran Wu,	<i>tions</i> .	876
820	Beibin Li, Erkang Zhu, Li Jiang, Xiaoyun Zhang,	Guibin Zhang, Yanwei Yue, Xiangguo Sun, Guancheng	877
821	Shaokun Zhang, Jiale Liu, Ahmed Hassan Awadallah,	Wan, Miao Yu, Junfeng Fang, Kun Wang, Tianlong	878
822	Ryen W White, Doug Burger, and Chi Wang. 2024.	Chen, and Dawei Cheng. 2025d. G-designer: Ar-	879
823	Autogen: Enabling next-gen LLM applications via	chitecting multi-agent communication topologies via	880
824	multi-agent conversations . In <i>First Conference on</i>	graph neural networks . In <i>ICLR 2025 Workshop on</i>	881
825	<i>Language Modeling</i> .	<i>Foundation Models in the Wild</i> .	882
826	Jiaxi Yang, Mengqi Zhang, Yiqiao Jin, Hao Chen, Qing-	Hangfan Zhang, Zhiyao Cui, Jianhao Chen, Xinrun	883
827	song Wen, Lu Lin, Yi He, Weijie Xu, James Evans,	Wang, Qiaosheng Zhang, Zhen Wang, Dinghao Wu,	884
828	and Jindong Wang. 2025. Topological structure learn-	and Shuyue Hu. 2025e. Stop overvaluing multi-agent	885
829	ing should be a research priority for llm-based multi-	debate – we must rethink evaluation and embrace	886
830	agent systems . <i>Preprint</i> , arXiv:2505.22467.	model heterogeneity . <i>Preprint</i> , arXiv:2502.08788.	887
831	Shunyu Yao, Dian Yu, Jeffrey Zhao, Izhak Shafran,	Jiayi Zhang, Jinyu Xiang, Zhaoyang Yu, Fengwei Teng,	888
832	Thomas L. Griffiths, Yuan Cao, and Karthik R	Xiong-Hui Chen, Jiaqi Chen, Mingchen Zhuge, Xin	889
833	Narasimhan. 2023. Tree of thoughts: Deliberate	Cheng, Sirui Hong, Jinlin Wang, and 1 others. 2025f.	890
834	problem solving with large language models . In	Aflow: Automating agentic workflow generation . In	891
835	<i>Thirty-seventh Conference on Neural Information</i>	<i>The Thirteenth International Conference on Learning</i>	892
836	<i>Processing Systems</i> .	<i>Representations</i> .	893
837	Rui Ye, Xiangrui Liu, Qimin Wu, Xianghe Pang, Zhen-	Kechi Zhang, Jia Li, Ge Li, Xianjie Shi, and Zhi Jin.	894
838	fei Yin, Lei Bai, and Siheng Chen. 2025. X-mas:	2024. CodeAgent: Enhancing code generation with	895
839	Towards building multi-agent systems with heteroge-	tool-integrated agent systems for real-world repo-	896
840	neous llms . <i>Preprint</i> , arXiv:2505.16997.	level coding challenges . In <i>Proceedings of the 62nd</i>	897
841	Jiaxuan You, Rex Ying, Xiang Ren, William Hamilton,	<i>Annual Meeting of the Association for Computational</i>	898
842	and Jure Leskovec. 2018. GraphRNN: Generating	<i>Linguistics (Volume 1: Long Papers)</i> , pages 13643–	899
843	realistic graphs with deep auto-regressive models . In	13658, Bangkok, Thailand. Association for Computa-	900
844	<i>International conference on machine learning</i> , pages	tional Linguistics.	901
845	5708–5717. PMLR.	Muhan Zhang, Shali Jiang, Zhicheng Cui, Roman Gar-	902
846	Siyu Yuan, Kaitao Song, Jiangjie Chen, Xu Tan, Dong-	nett, and Yixin Chen. 2019. D-vae: A variational	903
847	sheng Li, and Deqing Yang. 2025. EvoAgent: To-	autoencoder for directed acyclic graphs . <i>Advances in</i>	904
848	wards automatic multi-agent generation via evolu-	<i>neural information processing systems</i> .	905
849	tionary algorithms . In <i>Proceedings of the 2025 Con-</i>	Ruijia Zhang, Xinyan Zhao, Ruixiang Wang, Sigeng	906
850	<i>ference of the Nations of the Americas Chapter of the</i>	Chen, Guibin Zhang, An Zhang, Kun Wang,	907
851	<i>Association for Computational Linguistics: Human</i>	and Qingsong Wen. 2025g. Safesieve: From	908
852	<i>Language Technologies (Volume 1: Long Papers)</i> ,	heuristics to experience in progressive pruning for	909
853	pages 6192–6217, Albuquerque, New Mexico. Asso-	llm-based multi-agent communication . <i>Preprint</i> ,	910
854	ciation for Computational Linguistics.	arXiv:2508.11733.	911
855	Yanwei Yue, Guibin Zhang, Boyang Liu, Guancheng	Mingchen Zhuge, Wenyi Wang, Louis Kirsch,	912
856	Wan, Kun Wang, Dawei Cheng, and Yiyan Qi. 2025.	Francesco Faccio, Dmitrii Khizbullin, and Jürgen	913
857	MasRouter: Learning to route LLMs for multi-agent	Schmidhuber. 2024. GPTSwarm: Language agents	914
858	systems . In <i>Proceedings of the 63rd Annual Meeting</i>	as optimizable graphs . In <i>Proceedings of the 41st</i>	915
859	<i>of the Association for Computational Linguistics (Vol-</i>	<i>International Conference on Machine Learning</i> , vol-	916
860	<i>ume 1: Long Papers)</i> , pages 15549–15572, Vienna,	ume 235 of <i>Proceedings of Machine Learning Re-</i>	917
861	Austria. Association for Computational Linguistics.	<i>search</i> , pages 62743–62767. PMLR.	918

A Notations

We conclude the commonly used notations in Table 3 for reference.

B Model supplementary details

In this section, we elaborate the extended technical details of model architectures, the specifics of training and inference, and the formal algorithmic workflow.

B.1 Multi-Head Attention & Cross Attention

Multi-Head Attention. The update process of BSFormer is built upon the attention mechanism (Vaswani et al., 2017). Specifically, given an input sequence $\mathbf{Z} \in \mathbb{R}^{k \times d_{mha}}$, where k and d_{mha} denote the sequence length and hidden dimension, a query vector $\mathbf{q}_{mha} \in \mathbb{R}^{1 \times d}$ is used to extract relevant features via scaled dot-product attention:

$$\text{Attn}(Q, K, V) = \text{softmax} \left(\frac{QK^T}{\sqrt{d_{mha}}} \right) V \quad (12)$$

where $[Q; K; V] = [\mathbf{q}_{mha}W_q; \mathbf{Z}W_k; \mathbf{Z}W_v]$, and W_q, W_k, W_v denote learnable parameters.

The multi-head attention layer generalizes the scaled dot-product attention by executing h attention operations in parallel. The resulting outputs are subsequently concatenated and linearly projected to aggregate the multi-faceted information:

$$\begin{aligned} \text{MHAttn}(\mathbf{q}_{mha}, \mathbf{Z}) &= [\text{head}_1, \dots, \text{head}_h]W_o \\ \text{head}_i &= \text{Attn}(Q_i, K_i, V_i), i \in [1, h], \end{aligned} \quad (13)$$

where $[Q_i; K_i; V_i]$ represent the i -th head partitioned from $[Q; K; V]$ with dimension d/h , and W_o is the learnable output projection matrix. we set all the number of attention heads to $h = 4$.

Cross Attention. To enable effective information exchange between different star Transformers, we introduce a cross-attention mechanism that allows one Transformer to attend to the representations produced by another. Specifically, given a query vector $\mathbf{q}_{ca} \in \mathbb{R}^{1 \times d_{ca}}$ and a source representation $\mathbf{Z}^s \in \mathbb{R}^{k_s \times d_{ca}}$ from another sequence (e.g., query from the relay node of Role-Former and source representation contains information from LLM-Former), cross attention is computed by projecting queries from $\mathbf{q}_{ca}$ and keys and values from $\mathbf{Z}^s$:

$$\text{CrossAttn}(Q, K, V) = \text{softmax} \left(\frac{QK^T}{\sqrt{d_{ca}}} \right) V, \quad (14)$$

$[Q; K; V] = [\mathbf{q}_{ca}W_q; \mathbf{Z}^sW_k; \mathbf{Z}^sW_v]$. Similarly, we employ multi-head attention to capture multi-faceted and fine-grained features across different representation subspaces.

B.2 Supplementary details of the DAG encoder

DAG Positional Encoding. To encode the topological positions of nodes within a DAG, we implement a structure-aware positional encoding (PE) scheme designed to capture both hierarchical depth and intra-layer ordering. Given that DAG nodes are only partially ordered, traditional sequential PE methods are inherently inapplicable. Our approach addresses this by assigning each node a dual-component embedding, derived from its topological depth and its relative rank within the corresponding level. Given a DAG $\mathcal{G} = (\mathcal{V}, \mathcal{E})$, we first compute a topological ordering of the nodes. During this process, the depth of each node $v_i \in \mathcal{V}$ is defined as the length of the longest path from any source node to v :

$$\text{depth}(v_i) = \max_{v_j \in \mathcal{N}_{in}(v_i)} (\text{depth}(v_j) + 1), \quad (15)$$

We let the first node as the initial vertex v_0 . For any node v_i with an empty in-degree set $\mathcal{N}_{in}(v_i) = \emptyset$, we establish a directed edge from v_0 to v_i , where v_0 encapsulates the query-LLM-role information to provide necessary task context. After computing node depths, we group nodes into layers according to their depth values. For nodes within the same layer, we assign an intra-layer rank based on their prediction order, which serves to break symmetry among nodes at the same depth level.

The final positional encoding for each node v_i is constructed by concatenating two sinusoidal embeddings that encode its depth and intra-layer rank:

$$\text{PE}(v_i) = [\text{PE}_{\text{depth}}(v_i); \text{PE}_{\text{rank}}(v_i)] \quad (16)$$

where each component occupies $d/2$ dimensions. Specifically, for $k = 0, \dots, \frac{d}{4} - 1$, the sinusoidal encodings are defined as:

$$\begin{aligned} \text{PE}_{\text{depth}}^{(2k)}(v) &= \sin \left(\frac{\text{depth}(v)}{10000^{2k/(d/2)}} \right), \\ \text{PE}_{\text{depth}}^{(2k+1)}(v) &= \cos \left(\frac{\text{depth}(v)}{10000^{2k/(d/2)}} \right), \\ \text{PE}_{\text{rank}}^{(2k)}(v) &= \sin \left(\frac{\text{rank}(v)}{10000^{2k/(d/2)}} \right), \\ \text{PE}_{\text{rank}}^{(2k+1)}(v) &= \cos \left(\frac{\text{rank}(v)}{10000^{2k/(d/2)}} \right). \end{aligned} \quad (17)$$

Notation	Definition
$\mathbb{M} = \{m_1, m_2, \dots, m_{N_m}\}$	Pool of available LLM backbones, where N_m is the number of LLMs in $\mathbb{M}$
$\mathbb{R} = \{r_1, r_2, \dots, r_{N_r}\}$	Set of predefined agent roles, where N_r is the number of roles in $\mathbb{R}$
$\mathcal{G} = \{\mathcal{V}, \mathcal{E}\}, \mathcal{V} = \{v_1, v_2, \dots, v_{N_g}\}$	A DAG representation of the MAS, where v_i is an agent and N_g is the number of agents in $\mathcal{G}$
v_{end}	Termination token
$\mathcal{N}_{\text{in}}(v_i) = \{v_j (v_j, v_i) \in \mathcal{E}\}$	in-neighbors of agent v_i
$a = \text{Aggregate}\{o_i v_i \in \mathcal{V}\}$	a is the output of $\mathcal{G}$, which aggregates all agent output o_i
$\mathcal{Q}$	Input query to the multi-agent system
$U(\mathcal{G}; \mathcal{Q}, \hat{a})$	Utility function measuring MAS performance, $\hat{a}$ is the oracle answer corresponding to $\mathcal{Q}$
$C(\mathcal{G}; \mathcal{Q})$	Cost function quantifying token expenditure, computed based on the API token price
$P(\mathcal{G} \mathcal{Q}, \mathbb{M}, \mathbb{R})$	The probability of MAS $\mathcal{G}$
$\mathbf{q}, \mathbf{m}_i, \mathbf{r}_j, \mathbf{e}$	Semantic embedding of query, LLM, role and end token
$\tilde{\mathbf{q}}_{llm}^l, \tilde{\mathbf{q}}_{role}^l$	Relay node representation of BSFormer at l layer
$\tilde{\mathbf{s}}_{llm}^l, \tilde{\mathbf{s}}_{role}^l$	Satellite node representation of BSFormer at l layer
N_l	The number of BSFormer layer
$\mathbf{x}_{i,j}^t = \text{MLP}([\tilde{\mathbf{m}}_i^{N_l}; \tilde{\mathbf{r}}_j^{N_l}])$	graph encoder input representation of t -th agent
$\hat{\mathbf{x}} = [\mathbf{x}^t; \mathbf{PE}(v^t)]$	graph encoder input representation concat with position encodings of t -th agent $\mathbf{H}^t, \mathbf{g}^t$
node and graph embeddings of $\mathcal{G}_{< t}$	
$\mathcal{U}(\cdot), \mathcal{A}(\cdot)$	Update function and Aggregation function of graph encoder
$\varphi(\cdot), \sigma(\cdot), \phi(\cdot)$	mapping network, gating network and readout function of graph encoder
$s_{i,j}^t, s_{\text{end}}^t$	node prediction score of llm-role pair $m_i \& r_j$ and end token v_{end}
$s_{\text{edge}}^{i,t}$	edge prediction score of edge $i \rightarrow t$
$\mathcal{D}, \mathcal{D}_{\text{cold}}, \mathcal{D}_{RL}, \mathcal{D}_{\text{replay}}$	training dataset, cold start dataset, reinforcement learning dataset and replay dataset
γ	Maximum number of agents
$f_s(\cdot), f_{BS}(\cdot), f_{DAG}(\cdot)$	Semantic encoder, Binary-Star Transformer and DAG encoder

Table 3: The notations that are commonly used throughout the manuscript.

This simple yet effective positional encoding enhances the topological awareness of the DAG, facilitating the seamless integration of nodal features with the structural information. This encoding allows the model to more distinctly localize specific roles within the topology. For instance, a Reflector node typically occupies the terminal position (*i.e.*, the last node of the final layer).

Network details. Following Zhang et al., we implement the mapping network and gating network using simple linear layers. Specifically, the mapping network $\varphi(\cdot)$ is defined as:

$$\varphi(\mathbf{h}^k) = W_\varphi \mathbf{h}^k \quad (18)$$

and gating network $\sigma(\cdot)$ is defined as:

$$\sigma(\mathbf{h}^k) = \text{sigmoid}(W_\sigma \mathbf{h}^k + b_\sigma) \quad (19)$$

In addition, we employ $\phi(\mathbf{H}^t) = \text{MHAttn}(\mathbf{q}, \mathbf{H}^t)$, to compute a global readout of the entire graph.

B.3 Training Specifics

The DAG probability of Hetero-Designer. While Eq. 2 defines the basic probability of the DAG structure, we here provide a more comprehensive

formulation for Hetero-Designer by incorporating the terminal node v_{end} . The joint probability, augmented by the existence of v_{end} , is defined as:

$$P(\mathcal{G} | \mathcal{Q}, \mathbb{M}, \mathbb{R}) = \prod_{i=1}^{|\mathcal{V}|} \underbrace{P(v_i | \mathcal{G}_{< i}, \mathcal{Q}, \mathbb{M}, \mathbb{R})}_{\text{node probability}} \times \prod_{j=1}^{i-1} \underbrace{P(e_{ji} | v_i, \mathcal{G}_{< i}, \mathcal{Q})}_{\text{edge probability}} \times P(v_{\text{end}} | \mathcal{G}, \mathcal{Q}, \mathbb{M}, \mathbb{R}) \quad (20)$$

We introduce a balancing factor α to weight node and edge log-probabilities, counteracting the numerical dominance of edges (up to $\frac{n(n-1)}{2}$) over nodes (n) to stabilize training. In addition, we can leverage Teacher Forcing for off-policy probability re-evaluation, which helps maximize data utility and avoid premature sample discarding.

Details of Cold Start Training. We split the training data into two subsets using a ratio of 2 : 3: $\mathcal{D}_{\text{cold}}$ for cold-start pre-training and $\mathcal{D}_{RL}$ for reinforcement learning. For $\mathcal{Q}$ in $\mathcal{D}_{\text{cold}}$, we collect four successful samples for each query through random sampling. We iterate through the number of agents starting from one, continuing until either the

Algorithm 1: MAS Sample & Inference & Forward pass Workflow of Hetero-Designer

Input : Task Query $\mathcal{Q}$, Semantic encoder $f_s(\cdot)$, Binary-star Transformer $f_{BS}(\cdot)$, DAG encoder $f_{DAG}(\cdot)$, LLM pool $\mathbb{M}$, Role Pool $\mathbb{R}$, termination token v_{end} , (Option: Forward pass need a generated MAS $\hat{\mathcal{G}}$ as Input)

// **Input Representation**

1 Encode $\mathcal{Q}, \mathbb{M}, \mathbb{R}, v_{end}$ through f_s into $\mathbf{q}, \mathbf{M}, \mathbf{R}, \mathbf{e}$ // Section 3.1

// **Binary-Star Transformer Encoding**

// **Feature Initialization**

2 Initialize $\tilde{\mathbf{q}}_{llm}^0, \tilde{\mathbf{q}}_{role}^0 \leftarrow \mathbf{q}, \mathbf{q}$

3 Initialize $\tilde{\mathbf{S}}_{llm}^0, \tilde{\mathbf{S}}_{role}^0 \leftarrow [\mathbf{M}; \mathbf{e}], [\mathbf{R}; \mathbf{e}]$

4 **for** $l = 1$ to N_l **do**

// **Update the satellite nodes of LLM-former and Role-former**

5 **for** $i = 1$ to $N_m + 1$ **do**

6 $\mathbf{C}_{llm,i}^l = [\tilde{\mathbf{s}}_{llm,i}^{l-1}; \tilde{\mathbf{s}}_{llm,i}^0; \tilde{\mathbf{q}}_{llm}^{l-1}]$

7 $\tilde{\mathbf{s}}_{llm,i}^l = \text{MHAttn}(\tilde{\mathbf{s}}_{llm,i}^{l-1}, \mathbf{C}_{llm,i}^l)$

8 $\tilde{\mathbf{s}}_{llm,i}^l = \text{Layernorm}(\text{GeLU}(\tilde{\mathbf{s}}_{llm,i}^l))$

9 **for** $j = 1$ to $N_r + 1$ **do**

10 $\mathbf{C}_{role,i}^l = [\tilde{\mathbf{s}}_{role,i}^{l-1}; \tilde{\mathbf{s}}_{role,i}^0; \tilde{\mathbf{q}}_{role}^{l-1}]$

11 $\tilde{\mathbf{s}}_{role,i}^l = \text{MHAttn}(\tilde{\mathbf{s}}_{role,i}^{l-1}, \mathbf{C}_{role,i}^l)$

12 $\tilde{\mathbf{s}}_{role,i}^l = \text{Layernorm}(\text{GeLU}(\tilde{\mathbf{s}}_{role,i}^l))$

// **Update the relay node**

13 $\tilde{\mathbf{q}}_{llm}^l = \text{MHAttn}(\tilde{\mathbf{q}}_{llm}^{l-1}, [\tilde{\mathbf{q}}_{llm}^{l-1}; \tilde{\mathbf{S}}_{llm}^l]), \tilde{\mathbf{q}}_{role}^l = \text{MHAttn}(\tilde{\mathbf{q}}_{role}^{l-1}, [\tilde{\mathbf{q}}_{role}^{l-1}; \tilde{\mathbf{S}}_{role}^l])$

14 $\tilde{\mathbf{q}}_{llm}^l = \text{Layernorm}(\text{GeLU}(\tilde{\mathbf{q}}_{llm}^l)), \tilde{\mathbf{q}}_{role}^l = \text{Layernorm}(\text{GeLU}(\tilde{\mathbf{q}}_{role}^l))$

15 $\tilde{\mathbf{q}}_{llm}^l = \text{CrossAttn}(\tilde{\mathbf{q}}_{llm}^l, [\tilde{\mathbf{q}}_{llm}^l; \tilde{\mathbf{q}}^0; \tilde{\mathbf{q}}_{role}^l]), \tilde{\mathbf{q}}_{role}^l = \text{CrossAttn}(\tilde{\mathbf{q}}_{role}^l, [\tilde{\mathbf{q}}_{role}^l; \tilde{\mathbf{q}}^0; \tilde{\mathbf{q}}_{llm}^l])$

16 $\tilde{\mathbf{q}}_{llm}^l = \text{Layernorm}(\text{GeLU}(\tilde{\mathbf{q}}_{llm}^l)), \tilde{\mathbf{q}}_{role}^l = \text{Layernorm}(\text{GeLU}(\tilde{\mathbf{q}}_{role}^l))$ // Section 3.2

// **Autoregressive MAS Generation**

17 Initialize $\mathcal{V} \leftarrow \{v_{start}^0\}, \mathbf{X}^0 \leftarrow \hat{\mathbf{x}}^0, t \leftarrow 1, \log P_G = 0$

18 **while** $t \leq \gamma$ **do**

19 Graph Encoding: $\mathbf{H}^t, \mathbf{g}^t = f_{DAG}(\mathcal{G}_{<t})$

// **Node Generation**

20 **if** Inference **then**

21 $v^t = \arg \max [P(v^t | \mathcal{G}_{<t}, \mathcal{Q}, \mathbb{M}, \mathbb{R})] = \arg \max (\text{softmax}(\{s_{i,j}^t\} \cup \{s_{end}^t\}))$

22 **else if** Sample **then**

23 Sample $v^t \sim P(v^t | \mathcal{G}_{<t}, \mathcal{Q}, \mathbb{M}, \mathbb{R}) = \text{softmax}(\{s_{i,j}^t\} \cup \{s_{end}^t\})$

24 **else**

25 $v^t = \hat{v}^t$ in $\hat{\mathcal{G}}$

26 $\log P_G \leftarrow \log P_G + \alpha \cdot \log (P(v^t | \mathcal{G}_{<t}, \mathcal{Q}, \mathbb{M}, \mathbb{R}))$

27 **if** $v^t = v_{end}$ **then**

28 **break**

29 **else**

30 $\mathcal{V} \leftarrow \mathcal{V} \cup \{v^t\}, \mathbf{X}^t \leftarrow [\mathbf{X}^{t-1}; \hat{\mathbf{x}}^t]$

// **Edge Generation**

31 **for** $i = 1$ to $t - 1$ **do**

32 **if** Inference **then**

33 **if** $P(e_{i,t} = 1 | v^t, \mathcal{G}_{<t}, \mathcal{Q}) = \text{Sigmoid}(s_{edge}^{i,t}) \geq 0.5$ **then**

34 $e_{i,t} = 1$

35 **else**

36 $e_{i,t} = 0$

37 **else if** Sample **then**

38 Sample $e_{i,t} \sim P(e_{i,t} = 1 | v^t, \mathcal{G}_{<t}, \mathcal{Q})$

39 **else**

40 $e_{i,t} = \hat{e}_{i,t}$

41 **if** $e_{i,t} = 1$ **then**

42 $\mathcal{V} \leftarrow \mathcal{V} \cup \{e_{i,t} = 1\}, P_G + (1 - \alpha) \cdot \log P(e_{i,t} = 1 | v^t, \mathcal{G}_{<t}, \mathcal{Q})$

43 **else**

44 $\mathcal{V} \leftarrow \mathcal{V} \cup \{e_{i,t} = 0\}, P_G + (1 - \alpha) \cdot \log (1 - P((e_{i,t} = 1 | v^t, \mathcal{G}_{<t}, \mathcal{Q})))$

45 // Section 3.3

maximum number of agents γ is reached or four samples are collected, with a maximum of four iterations allowed for each specific agent count. The final training objective for the cold-start phase is:

$$\mathcal{L}_{cold} = \alpha \cdot \mathcal{L}_{node} + (1 - \alpha) \cdot \mathcal{L}_{edge} \quad (21)$$

The individual loss terms are defined as:

$$\begin{aligned} \mathcal{L}_{node} = & - \sum_{(\mathcal{G}, \mathcal{Q}, \mathcal{C}) \in \mathcal{D}_{cold}} (1 - \lambda' \mathcal{C}) \\ & \sum_{t=1}^{|\mathcal{V}|} \log P(v^t | \mathcal{G}_{<t}, \mathcal{Q}, \mathbb{M}, \mathbb{R}) \\ \mathcal{L}_{edge} = & - \sum_{(\mathcal{G}, \mathcal{Q}, \mathcal{C}) \in \mathcal{D}_{cold}} (1 - \lambda' \mathcal{C}) \\ & \sum_{t=1}^{|\mathcal{V}|} \sum_{i=1}^{t-1} \log P(e_{i,t} | v^t, \mathcal{G}_{<t}, \mathcal{Q}). \end{aligned} \quad (22)$$

where $\mathcal{C}$ is the cost of graph $\mathcal{G}$, and $\lambda' \in \{15, 25\}$ is the cost penalty for cold start.

Replay Data. We perform random sampling of trajectories from both $\mathcal{D}_{cold}$ and the historical replay buffer $\mathcal{D}_{replay}$ during reinforcement learning to enhance data utilization. By executing a new forward pass through these trajectories, we derive the action probabilities under the current policy, thereby supporting efficient off-policy updates.

Following the methodology established by Yue et al., we performed stratified sampling on the MATH to select 519 problems across various difficulty levels. The sampled data was then partitioned into training and test sets using a 1:4 ratio.

B.4 Inference Specifics

During inference, we employ a greedy decoding strategy. Specifically, the next node is determined by selecting the candidate with the maximum conditional probability $P(v^t | \mathcal{G}_{<t}, \mathcal{Q}, \mathbb{M}, \mathbb{R})$. As for edge generation, an edge $e_{i,t}$ is instantiated if its predicted probability $P(e_{i,t} = 1 | v^t, \mathcal{G}_{<t}, \mathcal{Q})$ meets or exceeds the threshold of 0.5.

B.5 Algorithm Workflow

We summarize the overall algorithmic workflow in Algorithm 1, which details the MAS sampling procedure, the inference process, and the forward pass of the Hetero-Designer.

C Case Study & sensitivity Analysis

C.1 Case Study

As shown in Figures 9 to 13, we present the customized MAS designed by Hetero-Designer across

Method	Prompt	Completion	Cost (\$)
AFlow	321,813,314	28,083,445	21.75
MasRouter	3,235,288	2,499,530	3.56
Hetero-Designer	2,656,711	1,549,446	2.87

Table 4: Token usage and cost comparison on MATH.




Figure 8: Parameter sensitivity analysis of Hetero-Designer. The unit of cost (right) and performance (left) is \$ and pass@1 (%), respectively.

diverse query complexities for the five benchmarks. For straightforward queries, the model exhibits a preference for utilizing cost-effective and well-balanced LLMs alongside specialized agent roles to achieve an efficient solution. Conversely, for more challenging instances, the model tends to architect increasingly sophisticated systems.

Furthermore, we observe that the model's decision-making process is closely aligned with the semantic context of the query. For instance, Hetero-Designer incorporates an "Economist" role for economics-related questions in the MMLU benchmark and strategically deploys a "Programmer" to handle MATH problems that are amenable to algorithmic solutions. This behavior demonstrates that Hetero-Designer possesses a fine-grained domain awareness, allowing it to dynamically reconfigure both the agent composition and the interaction topology based on the underlying task semantics.

C.2 Sensitivity Analysis

We analyze the sensitivity of **Hetero-Designer** to three core parameters: the number of agents γ , the cost penalty coefficient λ in Eq. 2, and the sampling count K in Eq. 11. The results are presented in Figure 8. While performance scales with the agent count γ , the associated computational cost exhibits only a marginal increase. This efficiency is primarily attributed to the introduction of the termination token v_{end} , which enables dynamic termination and prevents the generation of redundant agent nodes. As the penalization strength λ increases, the model prioritizes structural sparsity and simplicity, leading to a more parsimonious topology at the



 Query	 Hetero-Designer Workflow
Compute $i + i^2 + i^3 + \dots + i^{258} + i^{259}$ Option A: -1 Option B: 1 Option C: i Option D: 0	 gpt-4o-mini knowledge Expert
Which of the following transactions would be included in the official computation of gross domestic product? Option A: Josh buys a new pair of running shoes. Option B: Nancy offers to babysit her granddaughter. Option C: Max buys his dad's used car. Option D: Eli cannot go to a concert so he resells his ticket to a friend.	

Figure 9: Case study on MMLU dataset.

expense of task performance. Regarding the sample size K , insufficient sampling leads to unstable performance-cost trade-offs, primarily due to restricted exploration and high gradient variance. As K increases, the model more effectively navigates the strategy space, eventually achieving a superior balance.

D Training cost statistics

Table 4 presents the training costs on the MATH benchmark, where we observe that expenditures remain relatively modest. This cost-efficiency is primarily attributed to the early acquisition of economical strategies during the cold-start phase and the improved sample efficiency afforded by the experience replay mechanism. These components allow the model to refine its policy using high-quality historical trajectories, thereby achieving convergence with minimal financial overhead.

E The Module Profile

In this section, we present the profiles of each module. Follow Yue et al., we use the same role pool and llm pool for fair comparison. Furthermore, we utilize GPT-4o-mini to generate a dedicated termination token v_{end} , providing the model with an explicit signal to conclude the generation process. We provide a series of profile examples for each category in Figures 14, 15, 16, 17 and 18.


 Query	 Hetero-Designer Workflow
Adam has \$100 and wants to spend it to open a rock stand. He can buy rocks for \$5 each and sell them for \$7 each. If he invests all his money in the rock stand but only sells 60% of his inventory, how much money does he lose?	 Claude-3.5-haiku Mathematician
Grandma walks 3 miles every day on her favorite walking trail, which includes 2 miles of walking on the beach and 1 mile of walking on the sidewalk. On the sidewalk, Grandma walks at twice the rate of speed that she does on the beach. If 40 minutes of her walk is spent on the beach, how long does it take for her to complete the entire 3-mile walk, in minutes?	

Figure 10: Case study on GSM8K dataset.



 Query	 Hetero-Designer Workflow
What is the value of x in the equation $\frac{17^6 - 17^5}{16} = 17^x$	
For any number x, we are told that $x \& = 7 - x$ and $\&x = x - 7$. What is the value of $15\&$?	

Figure 11: Case study on MATH dataset.



 Query	 Hetero-Designer Workflow
<pre>def anti_shuffle(s: str) -> str: Write a function that takes a string and returns an ordered version of it. Ordered version of string, is a string where all words (separated by space) are replaced by a new word where all the characters arranged in ascending order based on ascii value. Note: You should keep the order of words and blank spaces in the sentence. For example: >>> anti_shuffle('Hi') 'Hi' >>> anti_shuffle('hello') 'ehllo' >>> anti_shuffle('Hello World!!!') 'Hello !T!Wdlor'</pre>	 gemini-1.5-flash Plan Solver
<pre>from typing import List def sort_even(l: List[int]) -> List[int]: This function takes a list l and returns a list l' such that l' is identical to l in the odd indicies, while its values at the even indicies are equal to the values of the even indicies of l, but sorted. >>> sort_even([1, 2, 3]) [1, 2, 3] >>> sort_even([5, 6, 3, 4]) [3, 6, 5, 4]</pre>	 gemini-1.5-flash Plan Solver llama Programming Expert gpt-4o-mini Reflect Programmer Claude-3.5-haiku Reflect Programmer

Figure 12: Case study on humaneval dataset.



 Query	 Hetero-Designer Workflow
<pre>**Task**:</pre> Write a function to remove all elements from a given list present in another list. Your code should pass these tests: <pre>assert remove_elements([1,2,3,4,5,6,7,8,9,10],[2,4, 6,8])==[1, 3, 5, 7, 9, 10] assert remove_elements([1, 2, 3, 4, 5, 6, 7, 8, 9, 10],[1, 3, 5, 7])==[2, 4, 6, 8, 9, 10] assert remove_elements([1, 2, 3, 4, 5, 6, 7, 8, 9, 10],[5,7])==[1, 2, 3, 4, 6, 8, 9, 10]</pre>	 gemini-1.5-flash Plan Solver llama Bug fixer
<pre>**Task**:</pre> Write a python function to check whether one root of the quadratic equation is twice of the other or not. Your code should pass these tests: <pre>assert Check_Solution(1,3,2) == "Yes" assert Check_Solution(1,2,3) == "No" assert Check_Solution(1,-5,6) == "No"</pre>	 gemini-1.5-flash Plan Solver gemini-1.5-flash Plan Solver gpt-4o-mini Reflect Programmer Claude-3.5-haiku Reflect Programmer llama Bug fixer

Figure 13: Case study on MBPP dataset.



LLM Profile

```
[
  {
    "Name": "gpt-4o-mini",
    "Description": "GPT-4o Mini is a smaller version of the GPT-4o language model, designed for faster inference and reduced memory usage. It retains the same capabilities as the full-size model, but with fewer parameters. The model costs $0.15 per million input tokens and $0.6 per million output tokens. In General Q&A Benchmark MMLU, GPT-4o-mini achieves an accuracy of 77.8. In Reasoning Benchmark GPQA, GPT-4o-mini achieves an accuracy of 40.2. In Coding Benchmark HumanEval, GPT-4o-mini achieves an accuracy of 85.7. In Math Benchmark MATH, GPT-4o-mini achieves an accuracy of 66.09."
  },
  {
    "Name": "claude-3-5-haiku-20241022",
    "Description": "The new Claude 3.5 Haiku combines rapid response times with improved reasoning capabilities, making it ideal for tasks that require both speed and intelligence. Claude 3.5 Haiku improves on its predecessor and matches the performance of Claude 3 Opus. The model costs $0.1 per million input tokens and $0.5 per million output tokens. In General Q&A Benchmark MMLU, claude-3-5-haiku achieves an accuracy of 67.9. In Reasoning Benchmark GPQA, claude-3-5-haiku achieves an accuracy of 41.6. In Coding Benchmark HumanEval, claude-3-5-haiku achieves an accuracy of 86.3. In Math Benchmark MATH, claude-3-5-haiku achieves an accuracy of 65.9."
  },
  {
    "Name": "gemini-1.5-flash-latest",
    "Description": "Gemini 1.5 Flash was purpose-built as our fastest, most cost-efficient model yet for high volume tasks, at scale, to address developers feedback asking for lower latency and cost. The model costs $0.15 per million input tokens and $0.6 per million output tokens. In General Q&A Benchmark MMLU, gemini-1.5-flash achieves an accuracy of 80.0. In Reasoning Benchmark GPQA, gemini-1.5-flash achieves an accuracy of 39.5. In Coding Benchmark HumanEval, gemini-1.5-flash achieves an accuracy of 82.6. In Math Benchmark MATH, gemini-1.5-flash achieves an accuracy of 74.4."
  },
  {
    "Name": "Meta-Llama-3.1-70B-Instruct",
    "Description": "The Meta Llama 3.1 multilingual large language model (LLM) is a pretrained and instruction tuned generative model in 70B (text in/text out). The model costs $0.2 per million input tokens and $0.2 per million output tokens. In General Q&A Benchmark MMLU, Llama 3.1 achieves an accuracy of 79.1. In Reasoning Benchmark GPQA, Llama 3.1 achieves an accuracy of 46.7. In Coding Benchmark HumanEval, Llama 3.1 achieves an accuracy of 80.7. In Math Benchmark MATH, Llama 3.1 achieves an accuracy of 60.3."
  }
]
```

Figure 14: The LLM profile of main backbones.



Math_role_Profile

```
[
  {
    "Name": "MathAnalyst",
    "MessageAggregation": "Normal",
    "Description": "You are a mathematical analyst. You will be given a math problem , analysis and code from other agents. You need to first analyze the problem solving process , where the variables are represented by letters. Then you substitute the values into the analysis process to perform calculations and get the results.",
    "OutputFormat": "Calculation",
    "PostProcess": "None",
    "PostDescription": "None",
    "PostOutputFormat": "None"
  },
  {
    "Name": "Inspector",
    "MessageAggregation": "Normal",
    "Description": "You are an Inspector. You will be given a math problem , analysis and code from other agents. Check whether the logic/calculation of the problem solving and analysis process is correct(if present). Check whether the code corresponds to the solution analysis(if present). Give your own solving process step by step based on hints",
    "OutputFormat": "Answer",
    "PostProcess": "None",
    "PostDescription": "None",
    "PostOutputFormat": "None"
  }
]
```

Figure 15: Example profile of math role.



Coding_role_Profile

```
[
  {
    "Name": "BugFixer",
    "Description": "You are a programming expert. You will be given a function signature and its docstring by the user. Use a Python code block to write your full implementation (restate the function signature).",
    "OutputFormat": "CodeCompletion",
    "PostProcess": "PythonInnerTest",
    "PostDescription": "You need to provide modified and improved python code based on the current code implementation and problems that arise during testing. You can refer to specific examples. Write your full implementation (restate the function signature). ",
    "PostOutputFormat": "CodeCompletion"
  },
  {
    "Name": "Test Analyst",
    "MessageAggregation": "PythonInnerTest",
    "Description": "You are a Test Analyst. You will be given a function signature and its docstring by the user. You need to provide problems in the current code or solution based on the test data and possible test feedback in the question. You need to provide additional special use cases , boundary conditions , etc . that should be paid attention to when writing code. You can point out any potential errors in the code. Your reply should be more concise. Preferably within fifty words.",
    "OutputFormat": "Text",
    "PostProcess": "None",
    "PostDescription": "You are a programming expert. You will be given a function signature and its docstring by the user. Give your own answers to problems that arise in other implementations. Use a Python code block to write your full implementation (restate the function signature).",
    "PostOutputFormat": "CodeCompletion"
  }
]
```

Figure 16: Example profile of coding role.




Figure 17: Example profile of commensense role.




Figure 18: Profile of termination token v_{end} .