

Breaking MCP with Function Hijacking Attacks: Novel Threats for Function Calling and Agentic Models

Anonymous authors

Paper under double-blind review

Abstract

The growth of agentic AI has drawn significant attention to *function calling* Large Language Models (LLMs), which are designed to extend the capabilities of AI-powered system by invoking external functions. Injection and jailbreaking attacks have been extensively explored to showcase the vulnerabilities of LLMs to user prompt manipulation. The expanded capabilities of agentic models introduce further vulnerabilities via their function calling interface. Recent work in LLM security showed that function calling can be abused, leading to data tampering and theft, causing disruptive behavior such as endless loops, or causing LLMs to produce harmful content in the style of jailbreaking attacks. This paper introduces a novel *function hijacking attack* (FHA) that manipulates the tool selection process of agentic models to force the invocation of a specific, attacker-chosen function. While existing attacks focus on semantic preference of the model for function-calling tasks, we show that FHA is largely agnostic to the context semantics and robust to the function sets, making it applicable across diverse domains. We further demonstrate that FHA can be trained to produce universal adversarial functions, enabling a single attacked function to hijack tool selection across multiple queries and payload configurations. We conducted experiments on 5 different models, including *instructed* and *reasoning* variants, reaching 70% to 100% ASR over the established BFCL dataset. Our findings further demonstrate the need for strong guardrails and security modules for agentic systems.

1 Introduction

Function Calling (FC) is at the core of agentic AI systems, providing agents with the ability to invoke functions relevant to a natural language intent (Abdelaziz et al., 2024; Patil et al., 2023). Within agentic AI research, the Model Context Protocol (MCP) has emerged as a popular framework that standardizes the communication between LLM agents (Hou et al., 2025). Already widely used, FC capability introduces additional security concerns. Agentic AI enables an agent to autonomously interact with an execution environment, and this expanded interactivity increases the attack surface of the system. As shown in Table 1, a growing body of work has started to explore novel attack vectors that exploit the FC mechanisms of LLM agents. Nevertheless, to our best knowledge, most research focused on generating harmful content, and overlooked the broader challenge of controlling the perturbation of the FC process itself. To date, there remains a lack of methods aiming to robustly and systematically perturb the function calling task.

Table 1: Attacks on Function Calling. P.I.: Prompt Injection, A.P.: Adversarial Perturbation, T.C.: Tool-Call

Method	Type of Attack		Attack Location		Intent		
	P.I.	A.P.	User Prompt	Tool Args.	Harmful Behavior	Disrupt T.C.	Hijack T.C.
(Zhan et al., 2024)	✓		✓	✓	✓		
(Wu et al., 2024)		✓		✓	✓		
(Zhang et al., 2024)	✓	✓	✓			✓	
(Andriushchenko et al., 2025)	✓	✓	✓			✓	
(Debenedetti et al., 2024)	✓		✓		✓	✓	
FHA (Ours)		✓		✓			✓




Figure 1: High-level example of FH-attack on a GitHub MCP Server (details in Appendix F).

To address this challenge, this paper demonstrates that FC models can be hijacked, showing a novel risk of the usage of LLMs, especially in the context of agentic AI systems. In particular, our new *function hijacking* attack (FHA) manipulates the tool selection process of agentic models to force the invocation of an attacker-chosen function. To achieve this objective, our attack inserts adversarial tokens in the description of a specific function to enforce the generation of a function call intended by the attacker. The FHA is implemented by adapting the GCG attack from Zou et al. (2023) to fit the FC task and the hijacking objective. Figure 1 shows an example of FHA in action. In the rest of the paper we detail the FHA attack and demonstrate its key properties:

- **Effectiveness:** We evaluated the attack against 5 different FC models (instructed and reasoning), on scenarios where the attacker perturbs the function calling mechanism in different ways. Our findings reveal Attack Success Rates ranging from 70% to 100%.
- **Robustness:** Compared to existing attacks, which rely on semantic preference between the prompt and the function, FHA is agnostic to FC contexts. We show in Section 6 that our attack is effective over diverse domains, and robust across multiple perturbations of the payload.
- **Universality:** We further show that FHA can be made universal with regards to queries and payloads perturbations. We introduce an extended version of our algorithm, that design a enhance the robustness of the FHA with regards to various alternative perturbations.

2 Related Work

Recent research on LLM security has revealed new threats to the use of generative models (Yi et al., 2024). This section offers an overview of the current state-of-the-art for agentic system security.

NLP attacks. Prior work, such as GCG (Zou et al., 2023), or AutoDAN (Liu et al., 2024) demonstrated that adversarial attacks on LLMs can deviate models from their expected behavior with minimal input manipulation at inference time, breaking model alignment. More recently, research in Red Teaming (Rawat et al., 2024) further demonstrated the impact of adversarial attacks.

Agentic systems. Recently, research has shifted towards *agentic* AI, where LLMs are augmented with external tools or memory to interact with their environment (Wang et al., 2024a; Guo et al., 2024; Yao et al., 2023; Schick et al., 2023). Anthropic standardized the use of tools by agents with the MCP framework (Hou et al., 2025), specifying a protocol to regulate the interaction between LLMs, databases and other tools. Another example is CoTools from Wu et al. (2025), a framework that generalizes the use of tools in the context of reasoning tasks.

Security of LLM agents. Although MCP significantly enhances the capabilities of models, the introduction of external modules increases vulnerability to malicious users (Vassilev et al., 2025). Recent work has acknowledged security issues with agentic systems, and identified potential new vulnerabilities. He et al. (2024) raised concerns about specific threats on agents, including manipulation of the database, available functions, as well as privacy risks for a user leading to leak of sensitive information. Similarly, Hou et al. (2025) identified the potential risk of MCP database manipulation. In addition, Intelligence (2025) lists recent MCP vulnerabilities and attacks.

Function calling attacks. Before the rise of LLMs, Kumar et al. (2018) demonstrated an attack on voice-activated agents such as Amazon Alexa. The authors introduced the concept of *skill squatting*, referring to the exploitation of phonetic ambiguities in spoken user commands to trigger malicious skills (i.e. tools in this context) that can be invoked in place of benign ones. This work demonstrated how attackers could exploit the environment to manipulate the interaction between agent and user, anticipating attacks on LLMs.

Jailbreaking and prompt injection attacks can be effective on FC models. For instance, Wu et al. (2024) showed that tool-calling can be leveraged as a *trojan horse* to jailbreak LLMs and generate harmful content. Zhan et al. (2024) demonstrated that indirect prompt injection on the output of a function call can lead to direct harm or data stealing. Similarly, Debenedetti et al. (2024) suggested a novel framework and benchmark to assess vulnerabilities of agentic systems in the usage of specific applications such as Slack, email, and others. Zou et al. (2024) demonstrated the vulnerability of FC models to call harmful functions, leading to the generation of unsafe content. Wu et al. (2025) showed that input containing a vast quantity of available functions can lead to miscalls by models. Invariant Labs (2025) introduce the Tool Poisoning Attack on MCPs where attackers inject a malicious prompt in the description of functions. Zhang et al. (2024) showed that prompt injection attacks targeting the user query itself can lead to incorrect function calls. In contrast to our results, they find that adversarial perturbations have limited effectiveness (see Section 8). Closer to our work, Wang et al. (2025) introduce the MCP Preference Manipulation Attack (MPMA) that edits the name or description of a function specifically to be preferred to the ones available to the FC model.

3 Preliminaries

In this section, we introduce function calling models and their mathematical notation.

Large Language Models. We begin by formalizing the auto-regressive decoding process of LLMs. Let us assume $x_{1:s}$ is a $(1, s)$ dimensional vector containing the tokens of the input sequence, where each token $x_i \in \{x_1, \dots, x_V\}$, $|V|$ being the size of the vocabulary. We can approximate the next-token generation as follows (Zou et al., 2023):

$$P_{\pi_\theta}(x_{s+1:s+n} \mid x_{1:s}) \approx \prod_{i=1}^n P_{\pi_\theta}(x_{s+i} \mid x_{1:s-i+1}) \quad (1)$$

where $P_{\pi_\theta}(x_{s+1:s+n} \mid x_{1:s})$ is the probability of auto-regressively generating the output sequence $x_{s+1:s+n}$, given the input $x_{1:s}$ and π_θ the model parametrized by θ .

FC models. These are usually standard LLMs fine-tuned to perform tasks related to API calling (Abdelaziz et al., 2024; Patil et al., 2023). We build upon the LLM’s generation process set out in Equation 1, extending it to formally describe FC generation. Given a user query q , the objective of model π_ϕ , fine-tuned for the function calling task and parametrized by ϕ , is to predict the most appropriate function f_j from a set of available functions $F = \{f_1, f_2, \dots, f_m\}$. The model computes the probability of predicting function f_j given the input context $x_{1:s}$ representing the input token sequence, including both the available functions $x_{1:|F|}$, and the user query $q = x_{|F|+1:s}$.

$$P_{\pi_\phi}(f_j \mid x_{1:s}) = P_{\pi_\phi}(f_j \mid x_{1:|F|} \cup x_{|F|+1:s}) \quad (2)$$

Equation 2 is agnostic with respect to the representation of f_j in a specific agentic protocol. The most common representation begins with the function name f_j^{name} followed by $a_{j,1}, a_{j,2}, \dots, a_{j,k}$ values for the k arguments of the function:

$$f_j = \{f_j^{name}, a_{j,1}, a_{j,2}, \dots, a_{j,k}\} \quad (3)$$

To help language models perform FC tasks, most providers introduce special-purpose tokens that explicitly signal the beginning and structure of function calls. These help enforce the task format and improve the model’s ability to identify and invoke the correct functions. For notational clarity we omit such tokens here. Appendix A presents various model configurations under FC scenarios.

4 Function Hijacking

This section introduces our novel Function Hijacking Attack (FHA) against function calling models. We present the threat model and adversarial objectives, explain our architectural choices, and sketch the attack implementation.

Threat model and objectives. In classic LLM jailbreaking, the attacker has full control of the prompt that goes into the model. This attack aims to violate the model’s alignment, and seeks to make the model comply in answering harmful requests from the user.

The goal we propose for function hijacking is different, and disrupts the FC preference process, forcing the model to select an attacker-chosen *target* function f_{target} instead of the most appropriate *ground-truth* function $f_{\text{ground_truth}}$ for the task described in the user prompt.

Our threat model stipulates that the attacker can only control the *description* of the target function within the list of functions that are available for calling. Note, that in our case the attacker does not have access to the user prompt, and the attack is launched *off-line*. We believe that the choice of only controlling the description of a function make the attack realistic and more robust. While other vectors, such as modifying function names, parameters, or implementation, could be more effective, they are also more likely to be detected by automated validation. In fact, evaluating natural language is difficult. In the context of MCPs, their implementation is not accessible by the user (source code), but their textual description is exposed - making it an effective attack vector.

FHA implementation. We denote the set of functions available to the model by

$$F = \{f_1, \dots, f_{\text{ground_truth}}, \dots, f_{\text{target}}, \dots, f_m\} \quad (4)$$

and we denote the perturbed input sequence by $\hat{x}_{1:s}$, consisting of both the function specifications $\hat{x}_{1:|F|}$ and the user query $q = \hat{x}_{|F|+1:s}$. The target output is then composed of the name $f_{\text{target}}^{\text{name}}$, and the arguments $a_{\text{target},i}$ of the function:

$$\hat{y}_{fh} = \{f_{\text{target}}^{\text{name}}, a_{\text{target},1}, \dots, a_{\text{target},k}\} \quad (5)$$

Our algorithm is an adaptation of GCG (Zou et al., 2023)¹. The GCG algorithm implements a state-of-the-art jailbreaking attack that breaks model alignment by forcing an LLM to produce harmful content. It is efficient at model manipulation using gradient suffix injection. The FHA adapts the algorithm to the function calling task (see Algorithm 1 in Appendix B.1).

The attack strategy is to design and optimize a small part of the input to form an adversarial prompt that forces the LLM to generate predefined sets of tokens, namely a *target sequence*. This strategy is typically implemented by defining a loss that turns the objective into a minimization problem (Zou et al., 2023):

$$\underset{\hat{x}_I, IC\{1,\dots,s\}}{\text{minimize}} \mathcal{L}_{adv}(\hat{x}_{1:s}) \quad (6)$$

$$\text{where } \mathcal{L}_{adv}(\hat{x}_{1:s}) = -\log[P_{\pi_\theta}(\hat{y} \mid \hat{x}_{1:s})] \quad (7)$$

Here, $\hat{x}_{1:s}$ is the original prompt including the adversarial suffix $\hat{x}_I$, $\hat{y}$ is the target sequence, and $\mathcal{L}_{adv}(\hat{x}_{1:s})$ the cross-entropy loss. Function hijacking uses the same loss function where $\hat{x}_{1:s}$ includes the list of candidate functions with f_{target} , where $\hat{x}_I$ is in its description, and $\hat{y}$ becomes the target tool call $\hat{y}_{fh}$. Model P_{π_θ} is replaced by P_{π_ϕ} , a model fine-tuned for the *function-calling* task.

The GCG attack uses a specific string suffix as a target to optimize the adversarial prompt (see Figure 9 - A in Appendix B.3). A key assumption of the GCG algorithm is that if the model is induced to generate the target tokens at the beginning of its output, an attacker can subsequently leverage the auto-regressive nature of the model to guide the generation toward further content consistent with the target (hence harmful). We

¹<https://github.com/GraySwanAI/nanoGCG>

rely on the same assumption to make our attack more efficient and general. Instead of the full $\hat{y}_{fh}$, we only use $f_{\text{target}}^{\text{name}}$ as the optimisation target, and rely on the model to fill the correct parameters afterwards (see Figure 9 - B in Appendix B.3).

5 Experimental Design

Dataset. The Berkley Function Calling Leaderboard (BFCL) (Patil et al., 2023) is a common dataset to test FC models. In particular, we use the `BFCL_v3_multiple` dataset which aims to assess models on the task of mapping natural language prompts from the user to function selection and slot filling, given a range of available functions. The dataset includes 200 samples, where the number of available functions ranges from 2 to 4 (further details in Appendix C). We use BFCL for our experiments because the $f_{\text{ground_truth}}$ of each sample is available and the task is relatively simple for state-of-the-art FC models.

Target models. To test our algorithm, we attacked different LLMs supporting the function calling task. Our selection was motivated by four criteria: (1) the ranking of FC models on the BFCL dataset, (2) the diversity in model providers, (3) the variation in model sizes, (4) the type of models. For these reasons, we selected two instructed models `Llama-3.2-3B-Instruct` (Touvron et al., 2023) and `Mistral-7B-Instruct-v0.3` (Jiang et al., 2023), as well as three Large Reasoning Models `Qwen-3-1.7B`, `Qwen-3-8B`, and `Qwen-3-14B` (Qwen-Team, 2025). First, this choice aligns with the research trend of using smaller models for FC tasks - typically in the 1B-8B parameter range, due to their better efficiency (Belcak et al., 2025; Manduzio et al., 2024; Kavathekar et al., 2025). In addition, while instructed models directly generates tool-calls, reasoning models including the tool-calling functionality usually thinks before generating the tool-call. For those models, we differentiated two inference set-up: *Base* (`enable_thinking=False`), and *Think* (`enable_thinking=True`). For the reasoning models, we adapted $\hat{y}_{fh}$ to force models to skip their thinking (see Appendix A for more details).

Experimental setup. To ensure a consistent attack evaluation, we kept the original GCG parameters from Zou et al. (2023), decreased the batch size to 128, and varied the size of the adversarial suffix `optim_str` optimised by the algorithm. Compared to classic NLP jailbreaking, the FC task involves much larger context. Decreasing the batch size allowed us to run experiment using smaller GPU configurations. For simple attacks, we varied the size of the `optim_str` to study its effect on the algorithm. For the rest of the experiments, we set the size of the `optim_str` to 60 tokens (equivalent to 3 times its original size of 20 tokens). We performed all of our experiment using A100-80GB GPUs, and a seed of 42.

Metrics: Assessing if our attacks succeed is easier than for general NLP jailbreaking. In particular, the Attack Success Rate (ASR) can be computed using string matching, since we know the exact name of the target function. However, a more challenging test is to assess if the generated function call is valid, in terms of structure and parameters. Thus, we define two metrics:

- **Function name ASR.** The first metric is a string matching method. Given a function call from the model, we check if it calls exactly the target function.
- **Slot filling ASR.** The second metric is more nuanced. We check if the generated function call is valid, meaning that it has the correct number and type of parameters requested by the target function. Therefore, we can ensure that the output can be called in a real-world context.

Baselines: To assess the performance of the FHA, we introduce three baselines.

- **Standard inference.** We evaluate the performance of the considered models on the BFCL inference task when no attack is present. Rather than an *attack* success rate, this establishes a baseline success rate of the FC task.
- **Function injection.** We compare the FHA with a function injection attack which, given a user query, adds to the set of available functions a new target function explicitly designed to be preferred over the ground-truth function. This is a challenging baseline because the target function is generated by a more powerful model than the ones under evaluation. We selected `Llama-3-70B` Touvron et al. (2023), for being 5 to 40 times bigger in term of number of parameters than our reference models.

- **Preference Manipulation.** We compare the FHA to the published MCP Preference Manipulation Attack, MPMA Wang et al. (2025). Instead of injecting a new function to the set of available functions, MPMA seeks to modify the name or description of a targeted function to be preferred over all other available functions. We implemented their 3 approaches using their *exaggerated* prompt strategy on function description, namely: naive, direct, and genetic. We validate the correctness of our implementation of MPMA in Appendix D.2, by reproducing the attacks on the evaluation environment of the authors.

6 Direct Function Hijacking Evaluation

Our simplest goal is to deviate the model from its expected behavior. We define our first scenario: given a query q requesting a function to be executed, we arbitrarily select another function from the set of available functions to be our target. Therefore, our set of payloads would be defined by the unique element $P_1 = \{(F, f_{\text{target}}, q)\}$, with F the set of available functions, $f_{\text{target}} \in F$ and q the query.

In addition, we suspect that the nature, position and number of functions included in the context of the task matter. Even the position of `optim_str` in the prompt influences the attack. Therefore, we define a second scenario: we varied the position and number of functions included in the payload and observed its influence on the attack. In this case, our set of payloads is defined by $P_2 = \{(F_1, f_{\text{target}}, q), \dots, (F_h, f_{\text{target}}, q)\}$, with F_i the variant sets of available functions, each including f_{target} and $f_{\text{ground_truth}}$, and q the fixed query. Each set F_i is obtained from the original set F , by either removing additional functions or switching the position of functions. Using this setup, we performed two complementary analysis. First, we note the influence factor of the effectiveness of FHA, by running FHA independently for each payloads in P_2 and comparing their resulting ASR. Second, we evaluate the robustness of the attack, by running FHA on a single configuration of P_2 , and evaluate it on a set of different perturbed payloads.

6.1 Direct FHAs

This section presents the Function Name and Slot-Filling ASRs of the attack over the 200 BFCL payloads. Each ground-truth function is positioned as the *first function* in the payload. We then selected the target as the *second function* in the payload. In other words, functions $f_{\text{ground_truth}}$ and f_{target} appear respectively at index 0 and 1 in the payload. For payloads that contains more than 2 functions, we added the remaining functions after $f_{\text{ground_truth}}$ and f_{target} .

Attack performance. Figure 2 presents the Function Name ASR over the 5 reference models, using the configuration from Section 5. The FHA managed to hijack each model for a large part of the BFCL dataset in under 250 epochs (500 epochs for reasoning models), reaching a performance between 70% and 98%.

Qwen-3-8B and Qwen-3-14B appear more resilient to our attack. This is explained by the different function calling format of each model: Llama and Mistral directly generate a tool-call, whereas Qwen first generates a reasoning chunk to help and justify the tool-call generation. Hence, the FHA needs to work harder with Qwen, forcing the model to skip the reasoning first, which is our optimised $\hat{y}_{fh}$ target. The Suppress Thinking curve in Figure 2 shows the success rate of Qwen in generating function calls without thinking (i.e. "`<think>\n\n</think>`"), effectively a measure of the "extra optimisation effort" required. In comparison, FHA applied on Qwen-3-1.7B obtained results comparable as instructed models.




Figure 2: Function name ASR.

Takeaway 1.1: *FHA successfully hijacks both instructed and reasoning models with high success rate. These results demonstrate the robustness of the attack, given the diversity of the BFCL dataset.*

Table 2: Baselines and FHA - BFCL, FN: Function name, SF: Slot Filling. - We validated our implementation of the MPMA baseline in Appendix D.2

Metrics	Type	Llama-3B	Mistral-7B	Qwen3-1.7B		Qwen3-8B		Qwen3-14B	
				Base	Think	Base	Think	Base	Think
Standard Inference - Acc.	FN	0.88	0.96	0.96	0.97	0.97	1.00	0.98	0.99
	SF	0.88	0.96	0.96	0.97	0.97	1.00	0.98	0.99
Function Injection (ZS) - ASR	FN	0.80	0.79	0.91	0.81	0.86	0.81	0.91	0.79
	SF	0.59	0.56	0.58	0.51	0.55	0.47	0.57	0.47
Function Injection (FS) - ASR	FN	0.57	0.48	0.64	0.50	0.64	0.65	0.68	0.68
	SF	0.57	0.47	0.64	0.49	0.64	0.64	0.67	0.66
MPMA Benign - ASR	FN	0.01	0.07	0.01	0.01	0.02	0.01	0.02	0.01
	SF	0.01	0.07	0.01	0.01	0.02	0.01	0.02	0.01
MPMA DPMA - ASR	FN	0.01	0.10	0.00	0.01	0.02	0.00	0.01	0.00
	SF	0.01	0.10	0.00	0.01	0.02	0.00	0.01	0.00
MPMA GAPMA - ASR	FN	0.01	0.09	0.00	0.00	0.02	0.00	0.02	0.01
	SF	0.01	0.09	0.00	0.00	0.02	0.00	0.02	0.01
(Ours) FHA - ASR	FN	0.97	0.99	1.00	1.00	0.70	0.70	0.82	0.82
	SF	0.88	0.92	0.92	0.92	0.65	0.65	0.73	0.73

Baseline comparison. Table 2 presents the Function Name and Slot Filling ASRs for the different baselines and models over the BFCL dataset. Llama-3B has the lowest baseline performance on the FC task (standard inference) compared to Mistral-7B and Qwen reasoning models.

To create the function injection attacks, we prompted **Llama-3-70B** Touvron et al. (2023) to generate the best function possible given the query, for each sample. We considered two settings: *Zero-Shot* (ZS) - only inputting the query, and *Few-Shot* (FS) - inputting query and all available functions from the payload. The prompts are illustrated in Appendix D.1. The ZS Function Injection attack obtained a relatively strong Function Name ASR of 0.80 for the Llama model. In comparison, surprisingly, the FS variant obtained lower scores. This might be because the ZS setting implies more flexibility in the creation of functions, which comes at a cost: Slot-Filling ASRs for ZS are lower relative to their F.N. ASRs compared to FS.

In addition, we note that the MPMA baseline obtained a significant lower success rate in our setting (ranging from 0.01 to 0.10 ASR). This result can be explained by a fundamental difference in attack assumption. MPMA was originally evaluated in a constrained environment, where the prompt seek to call a specific MPC, and all available functions are similar (implementing the exact same functionality - see Appendix F for more details). In such setting, MPMA can exploit textual preferences to bias the model toward one function over another, since all available function are implementing the same functionality. In a more complex environment such as with **BFCL_v3_multiple** where available functions differ in semantics and topics, this strategy no longer generalizes. Specifically, $f_{\text{ground-truth}}$ and f_{target} are often very different in **BFCL_v3_multiple** (see Figure 11 in Appendix C). A similar limitation applies to Function-Injection attacks, which adds an additional function in the set of available functions, but still rely primarily on the textual preferences of its description with the prompt.

Takeaway 1.2: *The threat model of FHA is more flexible than the ones of prior attacks. Unlike Function-Injection and MPMA, which rely on textual preference of the function description, FHA generalizes across diverse payloads, topics, and function sets.*

Importantly, Table 2 highlights the strong ASRs from our attacks, compared to the performance of both the unperturbed models and the attack baselines. In particular, the high performance of Slot Filling means that most hijacked function calls are valid, since their parameters are correct, and therefore our attacks can work in practice. In addition, in contrast to other implementation, we can note that our FHA implementation successfully *suppress the thinking of reasoning models*. Indeed, the format of our **target_str** for reasoning models removes the reasoning intrinsics from the model. We find this finding promising towards a generalized attack on LRMs, suppressing their thinking mode by manipulating their thinking tokens. Further comparison with the baselines is available in Appendix D.3.

FHAs on MCP. In addition to the BFCL dataset, we demonstrated our attack on two well known MCP frameworks², namely: Slack-MCP and Github-MCP from the MCP repository (Hou et al., 2025). Figures 16 and 17 in Appendix F illustrate the FHA on these MCPs.

6.2 Influence of the size of the adversarial suffix

We analyze the impact of the size of `optim_str`, the adversarial suffix, on the performance of our attack, motivated by two observations. First, Hayase et al. (2024) highlighted that the size of `optim_str` influences the performance of the attack. Experimentally, they showed that larger suffixes lead to higher ASR. Second, we hide `optim_str` inside the description of the target function. Therefore, a smaller size of the suffix makes the attack less detectable. Due to computational limitations, the rest of the experiments focus on `Llama-3.2-3B-Instruct`. Based on results obtained in the previous section, we expect similar behavior for other models.

Figure 3 displays the Function Name ASR of our algorithm for `Llama-3.2-3B-Instruct` for `optim_str` sizes of 10, 35 and 60 tokens (corresponding to 0.5 to 3 times its original size of 20 tokens). To compare the impact on the algorithm’s efficiency, Figure 15 in Appendix E shows the proportion of each `optim_str` size to the length of the input payload.

An initialization with 60 tokens is enough to hijack almost every sample in the dataset. This is interesting because the proportion of the adversarial string in this setting is much lower compared to classic NLP jailbreaking. In the classic GCG attack with AdvBench, the proportion ranges from 25% to around 50% given that the input prompt is often a single sentence. In contrast, with a size of 60 tokens, the proportion for the FC setting drops to 5% on average.




Figure 3: ASR varying the size of `optim_str`.

In addition, we observe that the ASR of our algorithm drops when the size of the adversary string decreases. In fact, if we set an initial size of 10 tokens, the attack reaches 65% ASR under 500 epochs. We suspect that this is due to the proportional decrease of the `optim_str` in the model’s input, representing around 1.5% with 10 tokens. Furthermore, this phenomenon can also be explained by the length of the target sequence. Indeed, the ASR of the GCG attack is highly dependent on the length of the target sequence. In our case, the target string is longer than in the NLP setting. For both observations, our results align with the findings of Hayase et al. (2024).

Takeaway 2.1: Compared to classic NLP setting, FHA requires larger `optim_str` to speed-up the attack. We hypothesize that this is due to the input context generally being much larger for FC tasks.

6.3 Impact of the function set

We next inspected the robustness of our algorithm regarding the composition of the set of available functions. Specifically, we examined the position and number of functions in the payload, robustness to payload perturbation, and their similarity to the prompt.

Influence of the position of the functions. First, we test whether the position of the target function matters to our attack algorithm. Figure 4A reports the Function Name ASR of `Llama-3.2-3B-Instruct` on a subset of the BFCL dataset (samples containing only two functions, to control the influence from additional functions), under two configurations of the payload.

For each sample, the first configuration places $f_{\text{ground_truth}}$ at the beginning of the input, while the second configuration places f_{target} upfront. We observe that the target-first configuration hijacks most samples in fewer epochs. This implies that the position of the adversary string matters in the attack. This observation seems to echo previous work, such as Yu et al. (2025) (see Section 8 for details).

²<https://github.com/modelcontextprotocol/servers-archived/>




Figure 4: ASR when varying function positions (A) and number of functions (B).

Influence of the number of the functions. Furthermore, we expect that the size of the payload influences the efficiency of our algorithm. Figure 4B present the Function Name ASR on the Llama-3.2-3B with samples including different number of functions. To define our different payloads, we select a subset of the BFCL dataset including samples containing four functions (allowing us to remove one or two functions).

In Figure 4B the blue, red and green curves represent, respectively, the ASR of our algorithm with samples including 2, 3 and 4 functions. We first defined a baseline including only 2 samples (the ground-truth and the target), then we included other functions to evaluate the impact of their presence. Such functions are included in the function set of the original BFCL dataset, and are not meant to be selected by the model. We observe that adding these *noise* function to the payload increases the number of epochs needed to hijack compared to the baseline (0 noise function).

These results validate the findings of Section 6.1, as the proportion of the total input string that the adversary string constitutes decreases when noise functions are added.

Takeaway 2.2: *The size and content of the payload influence the FHA. Larger payloads, and target functions located later in the payloads tend to require more attack effort.*

Analysis of the correlation. To conclude the analysis of influence of the content of the payload, we analyse if the semantic meaning of the query and available functions influences our algorithm. Through correlation analysis, Appendix I shows that a f_{target} semantically close to the user prompt seems to take less epochs to be hijacked, specifically for the Llama and Qwen-3-8B models. While the semantic similarity seems to be a factor of influence of our attack, it worth noting that it is not part of our attacker model.

Robustness to payload perturbation. In real-world setting, the poisoned tool would need to function even while developers modify the codebase, for example by adding or removing functions. Thus, the attack needs to be robust when subject to future unknown perturbations of the payload. To test this, we focus on a single sample. We perturbed the original payloads using out-of-distribution functions, and transferred attacks on these perturbed payloads. Figure 5 presents the FHA on the index 2 of BFCL for 1,000 epochs.




Figure 5: Robustness of attack to noise functions

The Hijacking index corresponds to the first epoch where the FHA succeed during training and so the model calls the attacked function. We added 1, 2, 3, 5, 10, or 25 out-of-distribution noise functions to the original payload and transferred the attack every 20 epochs. We averaged $n = 50$ different variations (different noise functions). Figure 5 shows that FHA is robust to moderate payload perturbation (up to ~ 3 additional functions). Appendix H further details this experiment, and suggests a universal attack with increased robustness with regards to heavy perturbation. We discuss the implications of our findings on the design of our attack in Section 8.

Takeway 2.3: Even if the MCP server is modified after the attack payload is inserted, the attack persists through high tolerance to new functions, methods, and edits.

7 Towards Universal Hijacking of FC Models

To test the universality of our attack, we adapt it to optimize the attack objective over a set of k queries $Q = \{q_1, \dots, q_k\}$. The goal of the universal attack is to have a single adversarial function hijack any of the queries $q_i \in Q$. In this case, the set of payloads is defined by $P_3 = \{(F, f_{\text{target}}, q_1), \dots, (F, f_{\text{target}}, q_k)\}$.

Data-augmentation. To evaluate the new attack variant, we augment the BFCL by constructing a list of diverse queries. We refer to this new dataset as *FunSecBench*. The objective is to generate a batch of queries triggering the same ground-truth function, designed to evaluate the robustness of our algorithm with respect to variations in the user query. For each payload, each generated prompt is derived from the same original example. We generate synthetic data using *GPT-4o-mini* (OpenAI & al., 2024) and define three complementary strategies for query creation (see Appendix G):

1. **Formulation diversity:** For each query, we generate 10 variations by instructing the model to rephrase the input while *preserving its exact intent*. Each reformulation results in the same function call as the original prompt, with identical arguments. These variations create natural linguistic diversity and test the model’s robustness to semantically equivalent inputs.
2. **Arguments variation:** Building on the first approach, this strategy involves generating queries that invoke the *same function but with different arguments*. By varying the number and value of parameters, we assess the attack’s robustness to functional variability and its ability to handle a broad range of realistic input scenarios.
3. **Multiple intents:** In practice, we expect the user to formulate different intents, thereby triggering different functions from a same payload. To this extent, we design a third data-augmentation strategy, enabling multiple ground-truth functions $f_{\text{ground_truth}}$ for each sample. From the BFCL dataset, we retain the payloads containing 3 or 4 functions, and generate additional queries aiming to trigger functions other than the original ground-truths and the selected targets.

Multi-prompt FHA. To build universal FHAs we extend our algorithm to generate a single attack string that transfers across a set of different prompts, referred to as a *batch of queries* (see Algorithm 2 in Appendix B.2 for details).

Figures 6A and 6B present the ASR over 150 epochs obtained using the three types of data augmentation techniques, on *Llama-3.2-3B-Instruct*. The figures include two types of runs: *Direct* and *Transferred* attacks. Each batch includes 10 prompts, and the ASR is computed by averaging the percentage of successful attacks of each batch, for each epoch. The transferred attacks report the Function Name ASR when adversarial examples generated from one direct attack are applied to another setting.




Figure 6: A: Direct and transferred attacks. B: Synthetic generation strategies.

Direct attacks. First, on Figure 6A, we observe that the *formulation diversity strategy* (1) obtained a higher ASR than the *argument variation strategy* (2) (respectively 0.88 vs. 0.79). This can be explained by the nature of the construction of the different batches. As per Figure 19 in the Appendix G.2, the *formulation diversity batches* (1) appear to be semantically closer to the original prompts, and to each other compared to the *argument-variation batches* (2). This finding aligns with our correlation analysis, where the semantics seem to impact the efficiency of the algorithm.

Similarly, Figure 6B represents the ASR of the direct attack using *multiple intents strategy* (3) on a subset of BFCL (samples containing 3 and 4 functions, allowing generation of different intents). We observe that the direct attacks made using the *multiple intents strategy* (3) take more epochs to achieve hijacking, but yield comparable ASR to the two other strategies. The performance observed implies that the FHA is capable of generating a single `optim_str` working for multiple intents.

Takeaway 3.1: A single `optim_str` can generalize across a set of queries (semantically related or not), demonstrating that FHA can be made **query-universal** rather than prompt-specific.

Transferred attacks. Furthermore, we also tested the generalization and transferability of our batch of attacks to new and unseen prompts. Figure 6A presents attacks trained on *formulation diversity* batch (1) transferred to and from *argument variation* batch (2), in orange and cyan, respectively. Both settings demonstrate good generalization, with final ASR values after 150 epochs of 0.74 and 0.80 for adversaries trained on (1) and tested on (2), and vice versa, respectively. Notably, the adversaries trained on batch (2) obtained better generalization while obtaining a lower ASR on the training prompts. This may be attributed to the greater diversity and hijacking difficulty of the prompts in batch (2). Appendix J further confirms this observation, analyzing the number of prompts hijacked per batch.

Figure 6B shows the attacks from *formulation diversity* (1) and *argument variation* (2) strategies transferred on the *Multiple Intent* strategy (3), with batches restrained to different intents (other than $f_{\text{ground_truth}}$ and f_{target}). Compared to Figure 6A, the transferred attacks fail on other intents than the one contained in the original query. This was expected, since the attacks are trained on batches with queries sharing the same intent. This shows that our attack is flexible, and the attacker can choose to affect a single or multiple intents while creating the query batch. This finding has implications on the attack design (see Section 8).

Takeaway 3.2: The transferability’s effectiveness of Universal FHA depends on the content of the training batches, allowing attacks to target specific topic(s) while leaving unrelated intents unaffected.

Enhancing robustness via multi-payload FHA. On the strength of the takeaway from the previous section, we can enhance the robustness of our attack with regards to payload perturbation such as adding new tools to the codebase. Earlier in the Section, we defined a universal version of FHA, where we looked at building an attack for a batch of multiple prompts. In the case of payload perturbation, we are now interested in making the attack work for a single prompt, on multiple versions of the payload.

To satisfy this novel constraint, we created an alternative version of the universal FHA, where each element of the batches contain the same query q , but different set of functions F . We define the batch of payloads as follows: $P = \{(F_1, f_{\text{target}}, q), \dots, (F_n, f_{\text{target}}, q)\}$, where q is a unique query, the target f_{target} is invariant, and F_i are the lists of functions for all $i \in [1, n]$. For this experiment, we focus on the index 2 of the BFCL dataset because the sample is hijacked within a small number of epochs (around epoch 32) and it contains 3 functions. To render the FHA robust to such perturbation, we built two complementary strategies:

- **Batch of position:** We have seen that the position of functions in the payload influences our algorithm (see Section 6.3), and potentially affects its robustness to perturbation. For this reason, we first constructed a batch including the same original payload, but modifying the position functions. We created 7 unique lists of functions (all including both $f_{\text{ground_truth}}$ and f_{target}), varying their position.
- **Batch of number:** Similarly, we observed that the number of functions in the payload affects the FHA. We created a complementary strategy, fixing the position of functions, but including an increasing number of functions, namely: 2, 3, 4, and 5 drawn from out-of-distribution functions from the `BFCL_v3_simple`. It resulted in 4 unique lists of functions.

Figure 22a and 22b present the same experiment as in previous Section H.1 using the *Batch of position* and *Batch of number* attack strategies, respectively. Results demonstrate that both strategies effectively improved the robustness of the attack compared to the simple FHA.




Figure 7: A. Batch of position B. Batch of number

Specifically, the Batch of number achieved more than 0.85 Function Name ASR for every perturbation, even with 25 additional functions in the payload. It confirmed our claim: training an attack on sets containing various number of functions increased the robustness to noise functions. Surprisingly, training an attack on same set of functions varying their position also increased the robustness with regards to noise function perturbation. Indeed, this strategy is not built on the definition of the perturbation (i.e. adding noise functions - which is the case for *Batch of number*). Therefore, it suggests that this strategy increases the generalization and overall robustness of the attack.

In addition, we define the hijacking index as the first epoch where the attack manages to hijack the full training batch. The hijacking index of the Batch of position attack is around 97 epochs. However, we observe that transferred attacks on perturbed payloads are successful before being effective on the original queries, at around 70 epochs, indicating that some payloads are easier to jailbreak than the original ones. The original batch also contains many payloads, explaining why the optimization takes more epochs. Overall, it means that the FHA optimizes the `optim_str` in a way that leads to good generalization of the attack.

Takeaway 3.3: *Universal FHA trained over payload variations further enhances the robustness of the attack towards realistic MCP variations (adding, reordering, or modifying functions).*

8 Discussion

Performance of the adversarial attacks on FC models. In contrast to other works from the literature, we demonstrated that FC models are vulnerable to targeted adversarial attacks. Indeed, our work nuances work from Zhang et al. (2024), affirming that adversarial attacks resulted poorly in perturbing the function calling process of FC models.

Function Injection baseline. To evaluate the performance of our Function Hijacking attack, we introduced the Function Injection attack baseline. To do so, we prompted Llama-3-70B to generate a function aiming to be preferred over a specific ground-truth function. Our baseline is comparable to the MCP Preference Manipulation Attack (MPMA) introduced by Wang et al. (2025), which consists in injecting an attacker function containing a preferred name or descriptions. The MPMA prompts an LLM to optimize separately names and description of a given function. In comparison, our Function Injection directly prompts an LLM to generate the optimal preferred function with regards to a specific query.

While Function Injection results in good performance, MPMA demonstrated less generalisability in our evaluation environment. It is worth noting that both approaches are less general than the FHA. In particular, their effectiveness is strongly dependent on the given payload, the query, and the ground-truth function. In comparison, as illustrated by our *Takeaway 3*, FHA works for arbitrary target functions, therefore can be applied more broadly, and has more severe security implications.

Position of the `optim_str` in the prompt. In Section 6.3, we found that locating f_{target} earlier as the first function in the payload increases the attack efficiency (see *Takeaway 2.2*). This observation echoes previous work, such as Yu et al. (2025), which empirically found that the adding special tokens such as *eos* in the middle of a prompt can enhance the efficiency of jailbreaking attacks by shifting the refusal boundary. As suggested by Yu et al. (2025), the *eos* tokens can be compared to special tokens specific to FC setting. Similarly to their findings, our results indicate that certain tokens in the FC context influences the effectiveness of the attack.

In addition, Wang et al. (2024b) demonstrated a positive correlation between the ASR and the attention score of the `optim_str` in GCG attacks. In our case, we suspect that when the `optim_str` is located early in the payload with the target function in first position, the adversarial tokens receive more attention, enhancing the effectiveness of our attack.

Design of the attack. Our experimentation on building universal attacks showed that our algorithm is robust to user query perturbation, including formulation and intent variations. First, we demonstrated that an attacker can increase the attack robustness with regards to payload perturbation. By designing batches including payloads with different number of functions, and locating the target at different positions, we showed that resulting attacks are more robust to perturbations such as adding unseen functions in the payload.

Second, we also demonstrated that it could increase the attacker’s control while designing the f_{target} . Our results show that the attacker can choose to make the attack work for one or multiple intents. Indeed, attacks trained on a single intent do not transfer on other intents, while attacks trained on batches containing multiple intents performs well (see *Takeaway 3.2*).

9 Limitations and Future Work

Despite the insights gained from this study, several limitations should be acknowledged. While our results show the effectiveness of our algorithm on a reasonable set of function calling scenarios, future work should experiment on larger models and payloads. Indeed, Wu et al. (2025) demonstrated the poor performance of standard FC models when a large number of tools are available to choose from. The effectiveness of the FHA to such scenarios is still to be determined. MCPs may include more than 4 functions, and broader domains than the ones considered so far. Another observation is that the nature of the payload influences the efficacy of the algorithm. Hence, we plan to explore in future work the impact of the semantic meaning of the target function on both our algorithm and the model preference.

Furthermore, recent work started to look at how the adversarial perturbations influence the attention mechanism of FC models Yu et al. (2025); Wang et al. (2024b). A line of future research can apply the same techniques to the FHA, to investigate further the impact of the position and size of the `optim_str` in the model’s payload. Another interesting direction is trying to understand why the position of the f_{target} in the payload (and therefore the position of `optim_str` in the context of the model) influences the effectiveness of our FHA.

We designed a basic universal FHA, by accumulating the loss over multiple prompts or payloads for each epoch. Zou et al. (2023) proposed an alternative algorithm, where the optimization is first performed over a single suffix, and new prompts are added incrementally. Given that they observed better performances compared to optimizing all the prompts in the same time, additional benchmarking between the two approaches could be conducted.

10 Conclusions

In this paper we demonstrated that FC models are vulnerable to function hijacking attacks. Previous work focused on prompt injection attacks against FC, whereas our FHA shows that adversarial perturbations are also effective. The FHA is less noticeable, more controllable, and scalable when crafted using batch of queries or payloads. Finally, the attack is flexible as the attacker can choose to target single or multiple intents. Our findings reinforce the need for strong guardrails and security modules for agentic systems.

Broader impact statement

This paper introduces a novel attack toward Function-Calling models and MCP frameworks. We adhere to the TMLR Ethics Guidelines³, and the goal of our findings is to advance research in the Security of AI systems. By identifying this new threats, we aim to make the community aware of this new vulnerability, and enhance the robustness and safety of Large Language Models.

Reproducibility statement

We took several measures to ensure the reproducibility of our experiments, namely:

- **Code availability:** The source code that we developed to conduct our experiments is available in the submission ZIP folder. The source code also include a `requirement.txt`, allowing users to create an environment with the correct versions of the libraries we used.
- **Experimental Settings:** We listed in Section 5 the experimental settings. This includes the datasets used, the models (open-source available on HuggingFace), the parameters of the algorithms, the prompts of the models, and the environment setups (seed and hardware used). We also included scripts to reproduce the experiments we lead.

³<https://jmlr.org/tmlr/ethics.html>

References

- Ibrahim Abdelaziz, Kinjal Basu, Mayank Agarwal, Sadhana Kumaravel, Matthew Stallone, Rameswar Panda, Yara Rizk, GP Bhargav, Maxwell Crouse, Chulaka Gunasekara, Shajith Ikbal, Sachin Joshi, Hima Karanam, Vineet Kumar, Asim Munawar, Sumit Neelam, Dinesh Raghu, Udit Sharma, Adriana Meza Soria, Dheeraj Sreedhar, Praveen Venkateswaran, Merve Unuvar, David Cox, Salim Roukos, Luis Las-tras, and Pavan Kapanipathi. Granite-function calling model: Introducing function calling abilities via multi-task learning of granular tasks, 2024. URL <https://arxiv.org/abs/2407.00121>.
- Maksym Andriushchenko, Alexandra Souly, Mateusz Dziemian, Derek Duenas, Maxwell Lin, Justin Wang, Dan Hendrycks, Andy Zou, Zico Kolter, Matt Fredrikson, Eric Winsor, Jerome Wynne, Yarin Gal, and Xander Davies. Agentharm: A benchmark for measuring harmfulness of llm agents, 2025. URL <https://arxiv.org/abs/2410.09024>.
- Peter Belcak, Greg Heinrich, Shizhe Diao, Yonggan Fu, Xin Dong, Saurav Muralidharan, Yingyan Celine Lin, and Pavlo Molchanov. Small language models are the future of agentic ai, 2025. URL <https://arxiv.org/abs/2506.02153>.
- Edoardo Debenedetti, Jie Zhang, Mislav Balunović, Luca Beurer-Kellner, Marc Fischer, and Florian Tramèr. Agentdojo: A dynamic environment to evaluate prompt injection attacks and defenses for llm agents, 2024. URL <https://arxiv.org/abs/2406.13352>.
- Taicheng Guo, Xiuying Chen, Yaqi Wang, Ruidi Chang, Shichao Pei, Nitesh V. Chawla, Olaf Wiest, and Xiangliang Zhang. Large language model based multi-agents: A survey of progress and challenges. In Kate Larson (ed.), *Proceedings of the Thirty-Third International Joint Conference on Artificial Intelligence, IJCAI-24*, pp. 8048–8057. International Joint Conferences on Artificial Intelligence Organization, 8 2024. doi: 10.24963/ijcai.2024/890. URL <https://doi.org/10.24963/ijcai.2024/890>. Survey Track.
- Jonathan Hayase, Ema Borevkovic, Nicholas Carlini, Florian Tramèr, and Milad Nasr. Query-based adversarial prompt generation, 2024. URL <https://arxiv.org/abs/2402.12329>.
- Feng He, Tianqing Zhu, Dayong Ye, Bo Liu, Wanlei Zhou, and Philip S. Yu. The emerged security and privacy of llm agent: A survey with case studies, 2024. URL <https://arxiv.org/abs/2407.19354>.
- Xinyi Hou, Yanjie Zhao, Shenao Wang, and Haoyu Wang. Model context protocol (mcp): Landscape, security threats, and future research directions, 2025. URL <https://arxiv.org/abs/2503.23278>.
- IBM-Research. Granite foundation models (whitepaper), 2024. URL <https://www.ibm.com/downloads/documents/us-en/10a99803c92fdb35>.
- Adversa AI Research & Threat Intelligence. Mcp security: Top 25 mcp vulnerabilities - the world’s definitive resource on model context protocol (mcp) vulnerabilities, 2025. URL <https://adversa.ai/mcp-security-top-25-mcp-vulnerabilities/>.
- Invariant Labs. Mcp security notification: Tool poisoning attacks, 2025. URL <https://invariantlabs.ai/blog/mcp-security-notification-tool-poisoning-attacks>.
- Albert Q. Jiang, Alexandre Sablayrolles, Arthur Mensch, Chris Bamford, Devendra Singh Chaplot, Diego de las Casas, Florian Bressand, Gianna Lengyel, Guillaume Lample, Lucile Saulnier, L  lio Renard Lavaud, Marie-Anne Lachaux, Pierre Stock, Teven Le Scao, Thibaut Lavril, Thomas Wang, Timoth  e Lacroix, and William El Sayed. Mistral 7b, 2023. URL <https://arxiv.org/abs/2310.06825>.
- Ishan Kavathekar, Raghav Donakanti, Ponnurangam Kumaraguru, and Karthik Vaidhyanathan. Small models, big tasks: An exploratory empirical study on small language models for function calling, 2025. URL <https://arxiv.org/abs/2504.19277>.
- Wilhelm Kirch (ed.). *Pearson’s Correlation Coefficient*, pp. 1090–1091. Springer Netherlands, Dordrecht, 2008. ISBN 978-1-4020-5614-7. doi: 10.1007/978-1-4020-5614-7_2569. URL https://doi.org/10.1007/978-1-4020-5614-7_2569.

- Deepak Kumar, Riccardo Paccagnella, Paul Murley, Eric Hennenfent, Joshua Mason, Adam Bates, and Michael Bailey. Skill squatting attacks on amazon alexa. In *27th USENIX Security Symposium (USENIX Security 18)*, pp. 33–47, Baltimore, MD, August 2018. USENIX Association. ISBN 978-1-939133-04-5. URL <https://www.usenix.org/conference/usenixsecurity18/presentation/kumar>.
- Xiaogeng Liu, Nan Xu, Muhao Chen, and Chaowei Xiao. Autodan: Generating stealthy jailbreak prompts on aligned large language models, 2024. URL <https://arxiv.org/abs/2310.04451>.
- Graziano A. Manduzio, Federico A. Galatolo, Mario G. C. A. Cimino, Enzo Pasquale Scilingo, and Lorenzo Cominelli. Improving small-scale large language models function calling for reasoning tasks, 2024. URL <https://arxiv.org/abs/2410.18890>.
- OpenAI and al. Gpt-4 technical report, 2024. URL <https://arxiv.org/abs/2303.08774>.
- Shishir G. Patil, Tianjun Zhang, Xin Wang, and Joseph E. Gonzalez. Gorilla: Large language model connected with massive apis, 2023. URL <https://arxiv.org/abs/2305.15334>.
- Qwen-Team. Qwen3 technical report, 2025. URL <https://arxiv.org/abs/2505.09388>.
- Ambrish Rawat, Stefan Schoepf, Giulio Zizzo, Giandomenico Cornacchia, Muhammad Zaid Hameed, Kieran Fraser, Erik Miehl, Beat Buesser, Elizabeth M. Daly, Mark Purcell, Prasanna Sattigeri, Pin-Yu Chen, and Kush R. Varshney. Attack atlas: A practitioner’s perspective on challenges and pitfalls in red teaming genai, 2024. URL <https://arxiv.org/abs/2409.15398>.
- Timo Schick, Jane Dwivedi-Yu, Roberto Dessì, Roberta Raileanu, Maria Lomeli, Luke Zettlemoyer, Nicola Cancedda, and Thomas Scialom. Toolformer: Language models can teach themselves to use tools, 2023. URL <https://arxiv.org/abs/2302.04761>.
- Hugo Touvron, Thibaut Lavril, Gautier Izacard, Xavier Martinet, Marie-Anne Lachaux, Timothée Lacroix, Baptiste Rozière, Naman Goyal, Eric Hambro, Faisal Azhar, Aurelien Rodriguez, Armand Joulin, Edouard Grave, and Guillaume Lample. Llama: Open and efficient foundation language models, 2023. URL <https://arxiv.org/abs/2302.13971>.
- Anahit Vassilev, Alina Oprea, Alyssa Fordyce, and Hilary Andersen. Adversarial machine learning: A taxonomy and terminology of attacks and mitigations. Nist trustworthy and responsible ai, National Institute of Standards and Technology, Gaithersburg, MD, 2025. URL <https://nvlpubs.nist.gov/nistpubs/ai/NIST.AI.100-2e2025.pdf>.
- Lei Wang, Chen Ma, Xueyang Feng, Zeyu Zhang, Hao Yang, Jingsen Zhang, Zhiyuan Chen, Jiakai Tang, Xu Chen, Yankai Lin, Wayne Xin Zhao, Zhewei Wei, and Jirong Wen. A survey on large language model based autonomous agents. *Frontiers of Computer Science*, 18(6), March 2024a. ISSN 2095-2236. doi: 10.1007/s11704-024-40231-1. URL <http://dx.doi.org/10.1007/s11704-024-40231-1>.
- Zihan Wang, Hongwei Li, Rui Zhang, Yu Liu, Wenbo Jiang, Wenshu Fan, Qingchuan Zhao, and Guowen Xu. Mpm: Preference manipulation attack against model context protocol, 2025. URL <https://arxiv.org/abs/2505.11154>.
- Zijun Wang, Haoqin Tu, Jieru Mei, Bingchen Zhao, Yisen Wang, and Cihang Xie. Attnngcg: Enhancing jailbreaking attacks on llms with attention manipulation, 2024b. URL <https://arxiv.org/abs/2410.09040>.
- Mengsong Wu, Tong Zhu, Han Han, Xiang Zhang, Wenbiao Shao, and Wenliang Chen. Chain-of-tools: Utilizing massive unseen tools in the cot reasoning of frozen language models, 2025. URL <https://arxiv.org/abs/2503.16779>.
- Zihui Wu, Haichang Gao, Jianping He, and Ping Wang. The dark side of function calling: Pathways to jailbreaking large language models, 2024. URL <https://arxiv.org/abs/2407.17915>.
- Shunyu Yao, Jeffrey Zhao, Dian Yu, Nan Du, Izhak Shafran, Karthik Narasimhan, and Yuan Cao. React: Synergizing reasoning and acting in language models, 2023. URL <https://arxiv.org/abs/2210.03629>.

- Sibo Yi, Yule Liu, Zhen Sun, Tianshuo Cong, Xinlei He, Jiaying Song, Ke Xu, and Qi Li. Jailbreak attacks and defenses against large language models: A survey, 2024. URL <https://arxiv.org/abs/2407.04295>.
- Jiahao Yu, Haozheng Luo, Jerry Yao-Chieh Hu, Wenbo Guo, Han Liu, and Xinyu Xing. Mind the inconspicuous: Revealing the hidden weakness in aligned llms’ refusal boundaries, 2025. URL <https://arxiv.org/abs/2405.20653>.
- Qiusi Zhan, Zhixiang Liang, Zifan Ying, and Daniel Kang. Injecagent: Benchmarking indirect prompt injections in tool-integrated large language model agents, 2024. URL <https://arxiv.org/abs/2403.02691>.
- Boyang Zhang, Yicong Tan, Yun Shen, Ahmed Salem, Michael Backes, Savvas Zannettou, and Yang Zhang. Breaking agents: Compromising autonomous llm agents through malfunction amplification, 2024. URL <https://arxiv.org/abs/2407.20859>.
- Andy Zou, Zifan Wang, Nicholas Carlini, Milad Nasr, J. Zico Kolter, and Matt Fredrikson. Universal and transferable adversarial attacks on aligned language models, 2023. URL <https://arxiv.org/abs/2307.15043>.
- Andy Zou, Long Phan, Justin Wang, Derek Duenas, Maxwell Lin, Maksym Andriushchenko, Rowan Wang, Zico Kolter, Matt Fredrikson, and Dan Hendrycks. Improving alignment and robustness with circuit breakers, 2024. URL <https://arxiv.org/abs/2406.04313>.

Appendix

Table of Contents

A	Function Calling Syntax of Different Models	19
B	GCG Algorithm Adapted to the Function-Calling Task	19
B.1	Simple FHA algorithm	19
B.2	Universal FHA algorithm	20
B.3	Auto-regressive assumption	21
C	Analysis of the Berkley Function-Calling Leaderboard (BFCL)	22
D	Baselines	23
D.1	Function Injection Attack	23
D.2	MPMA evaluation set-up	23
D.3	Comparison of FHA to the baselines	24
E	Proportion of <code>optim_str</code> in the Payload	26
F	MCP Attack	27
G	Synthetic Data Generation	28
G.1	Prompts	28
G.2	Semantic analysis of the FunSecBench dataset	29
H	Robustness to Payload Perturbation	30
H.1	Assessing simple FHAs	30
H.2	Enhancing robustness to payload perturbation	31
I	Correlation Analysis	32
J	Universal Attack over Batches	33

A Function Calling Syntax of Different Models

Figure 8 presents the FC syntax of the models we selected, along with the target template that we adopted to perform the FHAs. Depending on the provider, we observe different *tool-call* tokens, as well as different formats. While Llama solely generate the dictionary of the tool-call, Mistral output a list of tool-calls. We also note that Qwen-3 is capable of thinking before generating a tool-call. For these reasoning models, we suggest to first suppress the reasoning, and then forcing the tool-call as per `Llama-3.2-3B-Instruct` and `Mistral-7B-Instruct-v0.3`. We note that the syntax that we used for suppressing the thinking is natural for Qwen-3. Indeed, as per the `chat_template()` function of the `transformers` library for Qwen-3, the tokens `<think>\n\n</think>` are included right after the `<assistant>` tokens when the argument `enable_thinking` is set to `False`.

Function calling syntax of different models	
A. Llama-3.2-Instruct	Output format: <code>< python_tag >{"name": "target_function_name", "arguments": {...}}</code> Target template: <code>< python_tag >{"name": "target_function_name",</code>
B. Mistral-7B-Instruct-v0.3	Output format: <code>[TOOL_CALLS] [{"name": "target_function_name", "arguments": {...}}]</code> Target template: <code>[TOOL_CALLS] [{"name": "target_function_name",</code>
C. Qwen-3 series (1.7B - 8B - 14B)	Output format: <code><think>[thinking]</think>\n\n<tool_call>{"name": "target_function_name", "arguments": {...}}</code> Target template: <code><think>\n\n</think>\n\n<tool_call>{"name": "target_function_name",</code>

Figure 8: Function calling syntax of different models. The `target_function_name` is replaced by the actual name of the selected target function for each samples. Each model uses specific special tokens for function calling. For the Qwen-3 series, `[thinking]` represent the intermediate thinking tokens generated before the tool-calling.

B GCG Algorithm Adapted to the Function-Calling Task

B.1 Simple FHA algorithm

Algorithm 1 lists the FHA, which is based on the GCG algorithm (Zou et al., 2023). First, we adapted the input and format of the model’s context to fit the function-calling task. Second, instead of locating the adversarial perturbation at the end of the user prompt, we inserted it in the description of the attacker-selected function. Third, we modified the target to satisfy our attack requirements.

Algorithm 1 FHA

Require: Payload $(F, f_{\text{target}}, q)$, modifiable subset I , iterations T , loss function $\mathcal{L}$, top- k parameter k , batch size B

```

1:  $f_{\text{target}}^{\text{desc.}} \leftarrow f_{\text{target}}^{\text{desc.}} + x_I$  ▷ Initialize adversarial perturbation  $I$ 
2:  $x_{fh} = x_{1:|F|} + x_{|F|+1:s}$  ▷ Initialize prompt with  $F$  and  $q$ 
3: for  $t = 1$  to  $T$  do
4:   for  $i \in I$  do
5:      $X_i := \text{Top-}k(-\nabla_{e_{x_i}} \mathcal{L}(x_{fh}))$ 
6:   end for
7:   for  $b = 1$  to  $B$  do
8:      $\tilde{x}_{fh}^{(b)} := x_{fh}$ 
9:      $i \sim \text{Uniform}(I)$ 
10:     $\tilde{x}_i^{(b)} := \text{Uniform}(X_i)$ 
11:   end for
12:    $b^* := \arg \min_b \mathcal{L}(\tilde{x}_{fh}^{(b)})$ 
13:    $x_{fh} := \tilde{x}_{fh}^{(b^*)}$ 
14: end for
15: return Poisoned tool  $f_{\text{target}}^*$ 

```

B.2 Universal FHA algorithm

Algorithm 2 presents the batch query version of our algorithm. To construct the algorithm, we accumulated the cross-entropy loss with regards to the full batch of queries. In this means, the algorithm optimize the loss and the adversarial tokens with regards to multiple queries. While many variants of universal attacks exists, we made the choice of adapting our FHA in a simple yet intuitive way.

Algorithm 2 Universal FHA w.r.t. the query

Require: Payload $(F, f_{\text{target}}, Q = \{q_1, \dots, q_n\})$, modifiable subset I , iterations T , loss function $\mathcal{L}$, top- k parameter k , batch size B

```

1:  $f_{\text{target}}^{\text{desc.}} \leftarrow f_{\text{target}}^{\text{desc.}} + x_I$  ▷ Initialize adversarial perturbation  $I$ 
2:
3: for  $j = 1$  to  $n$  do
4:    $x_{fh}^{(j)} = x_{1:|F|} + q_j$  ▷ Initialize prompts with  $F$  and  $q_j$ 
5: end for
6: for  $t = 1$  to  $T$  do
7:   for  $i \in I$  do
8:      $L_{\text{total}} := 0$ 
9:     for  $j = 1$  to  $n$  do
10:       $L_{\text{total}} += \mathcal{L}(x_{fh}^{(j)})$ 
11:    end for
12:     $X_i := \text{Top-}k(-\nabla_{e_{x_i}} L_{\text{total}})$  ▷ Top- $k$  substitutions
13:   end for
14:   for  $b = 1$  to  $B$  do
15:      $i \sim \text{Uniform}(I)$ 
16:     Randomly select  $\tilde{x}_i^{(b)} \in X_i$ 
17:     for  $j = 1$  to  $n$  do
18:        $\tilde{x}_{fh}^{(j,b)} := x_{fh}^{(j)}$  ▷ Copy current query input
19:        $\tilde{x}_i^{(j,b)} := \tilde{x}_i^{(b)}$  ▷ Apply the sampled perturbation
20:     end for
21:   end for
22:    $b^* := \arg \min_b \sum_{j=1}^n \mathcal{L}(\tilde{x}_{fh}^{(j,b)})$ 
23:   for  $j = 1$  to  $n$  do
24:      $x_{fh}^{(j)} := \tilde{x}_{fh}^{(j,b^*)}$ 
25:   end for
26: end for
27: return Poisoned tool  $f_{\text{target}}^*$ 

```

B.3 Auto-regressive assumption




Figure 9: Illustrations of the GCG attack auto-regressive assumption. For both NLP and FH settings, the adversary exploits the auto-regressive nature of the model to make the model comply. String characters in italic display the model completion after generating the target sequence. In this example, the FHA causes the LLM to invoke the *largest_city* function instead of the intended *capital* function.

C Analysis of the Berkley Function-Calling Leaderboard (BFCL)

The BFCL dataset includes 200 payloads $P = (F, f_{\text{target}}, q)$, from various different domains, including mathematical analysis, or general API-style functions (e.g. compute average, get weather, find restaurant). Figure 10 display the distribution of the number of available functions in each payload.




Figure 10: Frequency of the number of available function per sample - BFCL (Patil et al., 2023).

The objective of BFCL is to assess the ability of models to generate a correct tool-call given a payload. From benchmarks, it is considered relatively easy since performance of FC-models is high compared to other datasets. Figure 11 presents the distribution of the cosine similarity between the prompts and the function descriptions, obtained with a text embedding model (BERT). We observe that the distribution of ground-truth functions $f_{\text{ground_truth}}$ is shifted toward higher values compared to the rest of the functions available in the payload. This observation motivated our choice of dataset, since payloads are more likely to constitute challenging examples to attack.




Figure 11: Cosine Similarity between prompt and function descriptions - BFCL (Patil et al., 2023).

D Baselines

D.1 Function Injection Attack

Figure 12 presents the prompts we designed to generate target functions to be injected in the payload. We refer to this attack as *function injection*, constituting a baseline to our FHA.




Figure 12: Function Injection attack: generation of preferred function given a query or/and the available functions from the payload.

D.2 MPMA evaluation set-up

Conversely to Function Injection Attacks, the MPMA attack Wang et al. (2025) looks at designing an enhanced description or name for the functions without having access to the prompt. Compared to Function-Injection, it makes it more generalizable. Indeed, the attack is focused on eliciting the function attributes to be preferred over other functions, no matter the nature of the prompt.

However, we found that this attack can be restrictive, in the sense that it principally works only for specific context and payload set-up. Indeed, the authors of Wang et al. (2025) only tested their attack when the prompt is targeting the targeted function f_{target} , and when all other available functions in the payload are similar to the target (functions implementing the exact same capabilities). As we shown experimentally, our attack setting is more agnostic, since it considers prompts and functions that are very diverse (i.e. very different from each others). Furthermore our FHA is effective for a large variety of samples demonstrates that it is stronger and more generalized than MPMA.

To validate our implementation of MPMA (obtained from their source code⁴), we reproduced the results from the paper Wang et al. (2025). To complement our Section 6.1, we compare the MPMA performance as well as Function-Injection and our Function-Hijacking attacks on the same environment of MPMA.

Evaluation set-up. As stated in Wang et al. (2025, Section 5 - Experimental Setup), authors first selected 8 well-known MCP servers as a base environment for their experiments. To create a payload, each MCP server is paraphrased 5 times using an LLM to create 6 look-alike functions implementing the same functionality. Their attack is then performed on the held-out original function, by modifying its name or description. The ASR is then reported over 10 prompts for each payload. The prompts are all targeting the same original MCP, with variants in some features (e.g. location when asking for the weather - similarly as *Arguments variation* approach in Section 7). To evaluate the attacks, we used the same prompts that the authors provided.

Experimental set-up of the FHA. We note that results on the Universal FHA are obtained using 5 held-out prompts. Indeed, we trained our target function on a different set of prompts than the one used to evaluate the attacks on the MPMA set-up.

⁴<https://github.com/hanbaoergogo/MPMA.git>




Figure 13: Reproduction of the attacks (MPMA)

Figure 13 present the results of the MPMA, and Function Hijacking attacks on 4 MCPs on the `Llama-3.2-3B-Instruct` model. We observe that the MPMA works as advertised, confirming that our implementation is correct. These results confirm that the MPMA attack is more localized for a specific type of payloads. Furthermore, it proves that our FHA performs well on a different environment.

D.3 Comparison of FHA to the baselines

Figure 14 presents an overview of the Attacker models and set-up for both our Function Hijacking Attack, and our baselines.

We note that the MPMA baseline Wang et al. (2025) showcases strong performance. However, the attack set-up is very localized. Indeed, the MPMA attack only works on constraint payloads, where the functions are all implementing the same functionality, and the prompt seek to trigger one of these functions. Furthermore, our experiments in Section 6.1 shows that the the MPMA fails when the prompt seeks to trigger another function than the one targeted by the attack.

Compared to MPMA, the Function-Injection attack is slightly more generalized. Given a prompt, the description is optimized to trigger the target attack. In this case, the attack is still very much constraint by the prompt (since the attack needs it to perform the description optimization), but the attack is more generalized with regards to the payload. Indeed, the Function-Injection performs relatively well on the BFCL dataset, where samples includes functions that are doing different things (as opposed to the evaluation set-up of the MPMA attack).




Figure 14: Overview of the Function-Calling attacks

Finally, our FHA is the most flexible and universal compared to existing function-calling attacks. Indeed, we showed in Sections 6.1, 6.3 and 7 that the batch version of our attack is robust with regards to various different evaluation configurations. A unique attacked function can be triggered across different prompts (different intents), and payloads formats (different sets of functions). Moreover, we showed in Section D.2 that the FHA performs well on the MPMA evaluation set-up, with a unique attacked function capable of fully hijacking the prompt dataset (batches of multiple prompts).

E Proportion of `optim_str` in the Payload

Figure 15 shows the average proportion of the `optim_str` in the payloads of the BFCL. This analysis supports our analysis of the experiments from Section 6.1.




Figure 15: Proportion of different size of `optim_str` in the payload - average percentage per number of function in the BFCL.

F MCP Attack

Figures 16 and 17 showcase examples of our attack using respectively the Github and Slack MCP Servers. Note that for the case of the GitHub MCP Server, the `delete_repository` function is not included, so we created it in the server as an analogy of the `create_repository` function.

GitHub MCP Server - Llama-3.2-3B-Instruct

A. Standard inference

User Prompt: Create a private repository called Hello World, including a small description.
Target Function: {"name": "delete_repository", "description": "Delete a new repository.", "parameters": {"type": "object", "properties": {"name": {"type": "string", "description": "Name of the repository." } }, "required": ["name"] } }
Assistant: {"name": "create_repository", "parameters": {"name": "Hello World", "private": true, "description": "A small repository"}}

B. FHA

User Prompt: Create a private repository called Hello World, including a small description.
Target Function: {"name": "delete_repository", "description": "Delete a new repository.*QC x package mundaneporteyileige100 x {?} odd can loRAP <|end_of_text|> ve McMp xmi stra fodmale145 alot spacearmco-pro_CPP.server xiyorse26 personnes pisARGIN;}*Alternatively accept x x x xHELL yosphate# sen_publisher IBMutanamespace@Modulefc"group="" fruit", "parameters": {"type": "object", "properties": {"name": {"type": "string", "description": "Name of the repository." } }, "required": ["name"] } }
Assistant: {"name": "**delete_repository**", "parameters": {"name": "mcp_server"}}

Figure 16: Example of attack on GitHub MCP Server using Llama-3.2-3B-Instruct. Our attack lead the user to deleting a repository instead of create a new one. This experiment required 274 epochs, uses an adversary of 60 tokens (shown in *italic*), and a batch size of 128.

Slack MCP Server - Llama-3.2-3B-Instruct

A. Standard inference

User Prompt: List the available channels.
Target Function: {"name": "slack_post_message", "description": "Post a new message to a Slack channel.", "parameters": {"type": "object", "properties": {"channel_id": {"type": "string", "description": "ID of the channel to post the message to." }, "text": {"type": "string", "description": "Text content of the message." } }, "required": ["channel_id", "text"] } }
Assistant: {"name": "slack_list_channels", "parameters": {"limit": "100"}}

B. FHA

User Prompt: List the available channels.
Target Function: {"name": "slack_post_message", "description": "Post a new message to a Slack channel.*use vrender x x avAnthony x NA_destroy mChristian Fassistent chests,,anda x nak */,steaws,(vie_u ges GNUNET dict) } " } arah x throughniiaIt Shll waitfor tiny waypoint", where x maps x+ ize...)Wtake xn-gleURMAX ASEENCtele_substr x", "parameters": {"type": "object", "properties": {"channel_id": {"type": "string", "description": "ID of the channel to post the message to." }, "text": {"type": "string", "description": "Text content of the message." } }, "required": ["channel_id", "text"] } }
Assistant: {"name": "**slack_post_message**", "parameters": {"channel_id": "C0123456789", "text": "List available channels"}}*

Figure 17: Example of attack on Slack MCP Server using Llama-3.2-3B-Instruct. Our attack lead the user to send a message on a channel instead of consulting the available channels. This experiment required 108 epochs, uses an adversary of 60 tokens (shown in *italic*), and a batch size of 128.

G Synthetic Data Generation

G.1 Prompts

Figure 18 shows the prompts used to perform synthetic data generation using GPT-4o-mini (OpenAI & al., 2024). Figures (1), (2) and (3) detail the prompts used for the reformulation (1) and argument-variation (2), and multi-intent variation (3) strategies, respectively.




Figure 18: Batch of queries using synthetic data generation. For both strategies, we prompted the gpt-4o-mini model. For the *Hyperparameter Variation* strategy, we also included the parameters' description of the function.

Multiple intents strategy - For payloads of 3 functions, we selected 5 queries from the data-augmentation strategy (1), and completed the batch with the 5 novel queries aiming to trigger the third function. For payloads of 4 functions, we selected 4 queries from the data-augmentation strategy (1), and completed the batch with 3 queries aiming to trigger the two other functions.

G.2 Semantic analysis of the FunSecBench dataset

Figure 19 shows a PCA projection of BERT encoding for 10 prompts and their corresponding batches across three variations: original (stars), diversity (1 - cross), argument (2 - triangles), and multi-intent (3 - square). Diversity strategy (1) cluster closely with the original prompts, suggesting that changes in phrasing preserve semantic content effectively. In contrast, prompts from Argument strategy (2) exhibit greater divergence. Furthermore, some samples from Multiple intents strategy (3) are located very far from the cluster formed by other strategies, due to their shift in intent (requesting a different function to be called, potentially on a different topic).




Figure 19: PCA of BERT embeddings over 10 samples - original, diversity (1), arguments (2), and multi-intent (3) prompts - *FunSecBench* dataset.

Moreover, using the BERT text-embedding model over the full BFCL dataset, Figure 20 presents two distributions for each strategies. First, the average Cosine similarity between the original prompt and each batches (Figure 20a). Second, the average Cosine similarity between each queries included in each batches - which we refer to as Intra-batches distance (Figure 20b). We observe that strategy (1) is more skewed toward high cosine similarity values, while the other strategies (2 and 3) and more spread toward lower values. Specifically, we observe a peak on lower values for strategy (3), representing the queries containing different intents from the original prompt.




Figure 20: Analysis of the Data Augmentation strategies - *FunSecBench* dataset.

H Robustness to Payload Perturbation

In this Section, our objective is to assess the influence of payload perturbations on our attack (Section H.1). We first demonstrate that the simple FHA is robust to moderate perturbation, but fails when the perturbation is too extreme. Following this observation, we suggest two strategies that could lead to more robust attacks under perturbation (Section H.2).

H.1 Assessing simple FHAs

To examine the robustness of the simple FHA, we focus on two specific samples (indexes 0 and 2 of BFCL), and run the attack over a longer period (1,000 epoch) on **Llama-3.2-3B-Instruct** and **Granite-3.2-2B-Instruct** (IBM-Research, 2024). We selected these particular samples since hijacking appears relatively early in the runs for both models (55 and 86 for Llama and Granite, respectively).

We then checked attack transferability if additional functions are added to the set of available functions after the adversarial function description has been created. We selected out-of-distribution functions from `BFCL_v3_simple` to perturb the original payload. To analyse the influence of adding noise functions to the payload, we added 1, 2, 3, 5, 10, or 25 functions. To denote the influence of the additional functions, we averaged the $n = 50$ different variations (i.e. different sets of noise functions added) of the original, every 20 epochs.




Figure 21: Robustness of attack when adding noise functions.

Figure 21a and 21b represent the ASR over the epochs, and the different noise configurations. First, we observe that the attack becomes robust to moderate noise functions after several epochs, respectively 800 and 200 epochs for Llama and Granite models for 1 to 3 functions added. However, when adding significantly more functions - from 5 functions - the attack become unstable.

We suspect that this is due to two reasons. First, the attack is trained on a payload of only 3 functions. When adding more functions than the original size of the payload, it can cause the `optim_str` to be too weak to still have a full influence on the model’s output. Second, when optimizing the `optim_str` on the original payload, our algorithm might end in local optimum that cause poor generalizability of the attack on heavy perturbations.

H.2 Enhancing robustness to payload perturbation

On the strength of the takeaway from the previous section, we wonder if we can enhance the robustness of our attack with regards to payload perturbation such as adding new tools to the codebase. In Section 7, we defined a universal version of the FH-attack, where we looked at building an attack working for a batch of multiple prompts. In the case of payload perturbation, we are now interested to make the attack work for a single prompt, on multiple versions of the payload.

To satisfy this novel constraint, we created an alternative version of the universal FH-attack, where each elements of the batches contains same query q , but different set of functions F . We define the batch of payloads as follows: $P = \{(F_1, f_{\text{target}}, q) \dots (F_n, f_{\text{target}}, q)\}$, where q is a unique query, the target f_{target} is invariant, and F_i are the lists of functions for all $i \in [1, n]$. To render the FH-attack robust to such perturbation, we built two complementary strategies:

- **Batch of position:** We have seen that the position of functions in the payload seems to influence our algorithm (see Section 6.3), and potentially affects its robustness to perturbation. For this reason, we first constructed a batch including the same original payload, but modifying the position functions. The index 2 of the BFCL dataset contains 3 functions. We created 7 unique lists of functions (all including both ground-truth and target functions), varying their position compared to the original list.
- **Batch of number:** Similarly, we observed that the number of functions in the payload seems to affect the FH-attack. We created a complementary strategy, fixing the position of functions, but including increasing number of functions, namely: 2, 3, 4, and 5 by adding out-of-distribution functions from the BFCL_v3_simple. It resulted in 4 unique lists of functions.

Figure 22a and 22b present the same experiment as in previous Section H.1 using the *Batch of position* and *Batch of number* attack strategies, respectively. Results demonstrate that both strategy effectively improved the robustness of the attack compared to the simple FH-attack.




Figure 22: Batch attack to increase robustness of attack when adding noise functions.

Specifically, the Batch of number achieved more than 0.85 Function Name ASR for every perturbations, even the heavier. It confirmed our claim: training an attack on sets of functions containing various number of functions increased the robustness to noise functions. Surprisingly, training an attack on same set of functions varying their position also increased the robustness with regards to noise function perturbation. Indeed, this strategy is not built on the definition of the perturbation. Therefore, it suggest that this strategy seems to increase the generalization and overall robustness of the attack.

In addition, we note that the hijacking index of the Batch of position attack is around 97 epochs (corresponding to the first epoch where the attack manages to hijack the full batch). However, we observe that transferred attacks on perturbed payloads are successful before being effective on the original queries - at around 60 to 80 epochs. It might be because some perturb payloads are easier to jailbreak than the original ones. The original batch also contains many samples (7 payloads), explaining why the optimization takes more epochs. Overall, it means that the FHA optimizes the `optim_str` in a way that leads to good generalization of the attack.

I Correlation Analysis

First, we retrieved the BERT embedding of the user query, along with the name and description of the ground-truth and target function. Then, we computed *cosine similarity* between the query embedding, and both the ground-truth and target function name and descriptions, respectively. Additionally, we computed the similarity between ground-truth and target function name and descriptions. We then extracted the epoch number required to hijack each sample for each model, which we refer to as the *num_epoch*.




Figure 23: Correlation between number of epochs of FHA and semantic distance of function metadata to query, as well as between functions (f_{target} and $f_{\text{ground_truth}}$).

Figure 23 showcases the Pearson correlation (Kirch, 2008) between the *num_epoch* and the semantic similarity between the user prompt and the function metadata - both for function names (Figure 23a) and descriptions (Figure 23b). Since a lower *num_epoch* means a more effective hijack attempt, we are looking to get a negative correlation if any.

First, the ground-truth similarity with the query correlates positively for both function name and description across model. Specifically, it shows significant positive correlation for the Qwen-3-8B model for function description ($r = +0.242$, $p \approx 6.10^{-4}$). Nevertheless, the correlation is negligible or statistically insignificant for other models and configurations, suggesting that the distance of the ground-truth with regards to the prompt does not influence the effectiveness of our algorithm.

Furthermore, the target similarity exhibits significant negative correlation for the Llama model in both function name ($r = -0.202$, $p = 0.00407$) and description ($r = -0.149$, $p = 0.0348$). We observe similar correlations for Qwen-3-8B, also statistically significant. It implies that when the target function is semantically closer to the prompt, fewer epochs are needed for a successful hijack. Conversely, we observe a positive correlation for similarity between ground-truth and target functions, also significant in the case of Llama for function names ($r = +0.144$, $p = 0.0418$), and Qwen-3-8B for both function name ($r = +0.255$, $p \approx 3.10^{-4}$) and descriptions ($r = +0.3$, $p \approx 2.10^{-5}$). It indicates that a high semantic distance between $f_{\text{ground_truth}}$ and f_{target} functions implies more epochs. Overall, these finding suggests that the attacker could perform prompt engineering on the description of the target function to increase the hijacking performance.

J Universal Attack over Batches

To conclude our analysis on the universal attack, we looked at how effective it is from a batch perspective. Specifically, we aim to measure how many prompts are successfully hijacked on average within each batch. For this purpose, we define the ASR_{batch} as the proportion of prompts in a batch that are successfully hijacked. Since each batch contains 10 prompts, we evaluate the attack performance across a range of thresholds corresponding to the number of hijacks per batch - from 1 to 10.




Figure 24: Average ASR_{batch} given the percentage of prompts hijacked per batch.

Figure 24 presents the ASR_{batch} as a function of the threshold, averaged over the BFCL dataset for the direct and transferred attacks. First, we observe that the ASR_{batch} of the direct attacks remains constant across all threshold values. This indicates that when a direct attack is successful, it consistently hijacks every prompt in the batch, resulting in a full-batch compromise.

In contrast, transferred attacks exhibit more nuanced behaviors. Specifically, the $(2) \rightarrow (1)$ attack configuration achieves higher ASR values across almost all thresholds compared to the $(1) \rightarrow (2)$ configuration. This suggests that when transferred adversaries trained on configuration (2) succeed on configuration (1), they tend to hijack a larger portion of the batch. This confirms our observation that adversaries trained on batches exhibiting more semantic diversity tend to generalize better.

Interestingly, at lower thresholds (0.1 and 0.2) — corresponding to just 1 or 2 prompts being hijacked per batch — the transferred attack $(2) \rightarrow (1)$ outperforms even the direct attack (2). This implies that while the adversaries may not always succeed on the source domain (strategy 2), they generalize effectively to dataset 1, successfully hijacking individual prompts that may be more vulnerable in the target domain.