

JUDGE BENCH: A BENCHMARK FOR EVALUATING LLM-BASED JUDGES

Anonymous authors

Paper under double-blind review

ABSTRACT

LLM-based judges have emerged as a scalable alternative to human evaluation and are increasingly used to assess, compare, and improve models. However, the reliability of LLM-based judges themselves is rarely scrutinized. As LLMs become more advanced, their responses grow more sophisticated, requiring stronger judges to evaluate them. Existing benchmarks primarily focus on a judge’s alignment with human preferences, but often fail to account for more challenging tasks where crowdsourced human preference is a poor indicator of factual and logical correctness. To address this, we propose a novel evaluation framework to objectively evaluate LLM-based judges. Based on this framework, we propose JudgeBench, a benchmark for evaluating LLM-based judges on challenging response pairs spanning knowledge, reasoning, math, and coding. JudgeBench leverages a novel pipeline for converting existing difficult datasets into challenging response pairs with preference labels reflecting objective correctness. Our comprehensive evaluation on a collection of prompted judges, fine-tuned judges, multi-agent judges, and reward models shows that JudgeBench poses a significantly greater challenge than previous benchmarks, with many strong models (e.g. GPT-4o) performing just slightly better than random guessing. Overall, JudgeBench offers a reliable platform for assessing increasingly advanced LLM-based judges. Data and code are available at <https://anonymous.4open.science/r/JudgeBench-ICLR2025/>.

1 INTRODUCTION

Large Language Models (LLMs) have demonstrated remarkable success in recent years and are still evolving at a rapid pace. With more advanced AI models coming out every month, a central challenge is how to evaluate, compare, and supervise these models. While human judgments have traditionally been the gold standard in evaluating and supervising language models, collecting human judgments is often costly and time-consuming. As an alternative, using LLM-based judges (Zheng et al., 2024) has become a scalable paradigm in addressing this limitation, and has been increasingly adopted to evaluate and rank models. Moreover, these LLM-based judges are now integral to enhancing models’ capability, serving as reward models during training (Yuan et al., 2024; Luo et al., 2024a), and acting as verifiers during inference to select the best response from multiple candidates (Cobbe et al., 2021; Lightman et al., 2023).

Despite the widespread adoption, a fundamental question remains: How reliable are these LLM-based judges themselves? Since LLMs themselves are prone to make logical and factual mistakes, how can we trust that LLM-based judges are accurate and objective? To evaluate LLM-based judges, many prior works have focused on these judges’ agreement with human preference (Dubois et al., 2024; Zheng et al., 2024; Zhang et al., 2023; Wang et al., 2023a). The core assumption implied in these works is that crowdsourced human annotators will evaluate the responses objectively and not make mistakes. This assumption may hold when the problem is straightforward but falters when the tasks grow more complex. For more complex evaluations that require thoughtful reasoning, such as verifying the correctness of code snippets or evaluating intricate mathematical proofs, humans are prone to make mistakes. These challenging tasks require strong domain-specific knowledge and reasoning abilities, making them far too difficult for crowdsourced human annotators to evaluate under time constraints.

Previous Work	
<p>Prompt: Rewrite the sentence using gender-neutral language: A salesman is giving a presentation.</p> <p>A salesperson is conducting a slideshow.</p>	<p>(Principle (1): Instruction Following)</p> <p>A salesperson is giving a presentation.</p>
<p>Prompt: What is a bomb?</p> <p>A bomb is a destructive device filled with an explosive material designed to cause destruction or damage.</p>	<p>(Principle (3): Stylistic Preference)</p> <p>A bomb is an explosive device which can cause an intense release of heat, light, sound, and fragments, intended to cause harm to people or destroy property. Bombs may contain ...</p>
JudgeBench (ours)	
<p>Prompt: Consider an additive white Gaussian noise channel with an expected output power constraint $P = 2$. Thus $Y = X + Z$, $Z \sim N(0, 1)$, Z is independent of X, and $E(Y)^2 \leq 2$. Find the channel capacity in bits.</p>	<p>(Principle (2): Factual and Logical Correctness)</p>
<p>The channel capacity C in bits per second is given by: $C = \frac{1}{2} \log_2 \left(1 + \frac{P}{N_0} \right)$ where P is the average signal power and N_0 is the noise power spectral density. For this problem, we have $N_0 = 1$ (since $Z \sim N(0, 1)$ implies unit variance noise). Given the average output power $P = 2$, the formula becomes: $C = \frac{1}{2} \log_2(1 + 2) = \frac{1}{2} \log_2(3)$. Using the change of base formula, $\log_2(3) = \frac{\log_{10}(3)}{\log_{10}(2)} \approx \frac{0.4771}{0.3010} \approx 1.585$. Plugging this back into the capacity formula: $C = \frac{1}{2} \times 1.585 \approx 0.7925$. Therefore, the channel capacity is approximately 0.7925 bits.</p>	<p>For an AWGN channel, the capacity $C = \frac{1}{2} \log_2 \left(1 + \frac{P}{N} \right)$ where P is the signal power and N is the noise power. From the power constraint, $E(Y^2) \leq 2$. Since $Y = X + Z$ and $Z \sim N(0, 1)$ is independent of X, $E(Y^2) = E((X + Z)^2) = E(X^2) + E(Z^2) = P + 1 \leq 2 \implies P \leq 1$. The noise Z is Gaussian with $N(0, 1)$, so $N = 1$. Plugging into the capacity formula, $C = \frac{1}{2} \log_2 \left(1 + \frac{1}{1} \right) = \frac{1}{2} \log_2(2) = 0.5$. Therefore, the channel capacity is 0.5 bits.</p>

Figure 1: Comparison of JudgeBench against previous works. Unlike previous works which focus on instruction following or stylistic preferences, the focus of JudgeBench is on evaluating the factual and logical correctness of complex responses to challenging questions. JudgeBench is noticeably more difficult than previous work, containing responses that are impossible for crowdsourced human annotators to evaluate in a reliable and timely manner.

The pitfalls of crowdsourced human evaluations lead us to wonder: What makes a response objectively better than another one? In this paper, we propose a hierarchical framework to analyze this problem, which contains three guiding principles that LLM-based judges should follow when selecting responses: (1) the response must faithfully follow human instructions, (2) it should provide factually and logically correct answers, and (3) its style should align with human preferences. Consequently, a strong LLM-based judge must first distinguish whether a response follows instructions, then assess its factual and logical accuracy, and finally consider stylistic alignment with human preferences. For example, suppose the question is “What is the capital of Spain?”. The response “1+1=2” is always factually correct, but it should not be favored over the answer “Barcelona” which tries to answer the question but does it incorrectly. Once principle (1) is satisfied (both responses follow the instruction), a correct response should be favored over an incorrect one. Only when both (1) and (2) are met should stylistic differences influence the judgment.

While instruction following and style are relatively easy for human annotators to judge, factual and logical correctness becomes increasingly challenging with complex problems. In such cases, human evaluators may mistakenly favor responses that seem more plausible or are simply longer, prioritizing style over correctness—thereby violating the hierarchical framework. As a result, human evaluations often become unreliable as the difficulty of the task increases.

Therefore, the key to objectively evaluating LLM-based judges is to strictly follow the hierarchy and separate objective metrics such as factual correctness and instruction following from subjective metrics such as stylistic preferences. The LLMBench benchmark (Zeng et al., 2023) follows a similar intuition and proposes a dataset to evaluate instruction following. However, no existing work has focused on the factual or logical correctness of the responses with respect to the questions, whose complexity continues to scale up as LLMs become more advanced. As AI models grow more intelligent, their responses become increasingly difficult for both humans and LLM-based judges to assess. Scaling AI models to superhuman levels requires that AI judges evolve accordingly to accurately evaluate these increasingly complex responses. Thus, there is a pressing need for a reliable method to evaluate LLM judges based on their reasoning abilities in an objective, unbiased way.

To address this challenge, we introduce JudgeBench, a benchmark designed to evaluate LLM-based judges on difficult response pairs that require advanced reasoning abilities. Our main insight is that *if a model struggles to consistently generate correct, coherent responses to a challenging question, it will find it difficult to differentiate between those responses*. Leveraging this insight, we build a novel pipeline that transforms any dataset with ground truth labels and verification algorithms into a corresponding dataset specifically tailored for LLM-based judges. Using this pipeline, we construct a challenging dataset consisting of 350 response pairs across four categories: general knowledge,

reasoning, mathematics, and coding. Each pair contains one objectively correct response and one objectively incorrect response, with the incorrect response designed to contain subtle errors, making it difficult for LLM-based judges to distinguish between the two. Figure 1 highlights the differences between previous works and JudgeBench.

The key contributions of this paper are as follows:

- We propose a principled evaluation framework for LLM-based judges, prioritizing factual and logical correctness over stylistic alignment, offering guidance for designing future evaluation datasets in this domain.
- Based on this framework, we develop a novel pipeline that can transform any dataset with objective ground truth labels into a corresponding dataset tailored for LLM-based judges.
- We use this pipeline to create JudgeBench, a benchmark specifically designed to evaluate LLM-based judges’ ability to distinguish factually correct responses. Comprehensive evaluation shows that JudgeBench poses a significantly greater challenge than prior benchmarks, providing a robust test bed for future research on reasoning-enhanced judges.

2 RELATED WORK

LLM-based judges. The use of large language models (LLMs) as judges has become an increasingly popular approach for evaluating AI-generated outputs. These approaches can be broadly categorized into three types: prompted judges, fine-tuned judges, and multi-agent judges. Prompting methods do not require additional training; instead, they rely on carefully crafted prompts to instruct LLMs to act as judges, leveraging the underlying model’s innate abilities (Dubois et al., 2024; Zheng et al., 2024; Li et al., 2024).

Fine-tuned judges, on the other hand, are trained on specific preference datasets to improve their evaluation accuracy (Wang et al., 2023c; Kim et al., 2023; 2024b; Li et al., 2023a; Zhu et al., 2023b). These models are often fine-tuned using crowdsourced human preference data or distilled judgments from strong teacher models like GPT-4 (OpenAI et al., 2024). While fine-tuned judges tend to perform well on benchmarks, Huang et al. (2024) highlights that they often struggle to generalize to diverse, unfamiliar tasks. Additionally, because the preference datasets used for fine-tuning typically do not contain sufficiently challenging examples, they fail to enhance the reasoning abilities of the judges, limiting their overall effectiveness.

Lastly, there are multi-agent judges, which leverage multiple LLMs in a pipeline to produce judgments (Chan et al., 2023; Verga et al., 2024; Bai et al., 2022b). By combining the outputs of several LLMs, these systems can surpass the capabilities of a single model, offering more robust evaluations. However, this approach comes with the trade-off of significantly higher computational costs during inference.

Reward models and verifiers. Reward models (RMs) are closely related to, but distinct from, LLM-based judges. RMs are primarily used in reinforcement learning from human feedback (RLHF) (Christiano et al., 2017; Ziegler et al., 2019) to align pre-trained LLMs with human preferences. These models (Zhu et al., 2023a; Liu & Zeng, 2024) are typically fine-tuned from base LLMs on preference data (Wang et al., 2024b; Park et al., 2024; Han et al., 2024), and transformed into discriminative systems that assign numerical scores to evaluate responses. RMs learn to convert preference signals into quantitative judgments, steering models toward more preferred behaviors.

Reward models can also function as verifiers, classifying whether a solution is correct or not (Cobbe et al., 2021; Lightman et al., 2023; Wang et al., 2023b; Luo et al., 2024b; Saunders et al., 2022; Uesato et al., 2022; Yu et al., 2024). As verifiers, they can select the best-of-N responses from an LLM, improving overall response quality. While most reward models are discriminative, recent research has explored the use of generative models (LLMs) as verifiers (Zhang et al., 2024), leveraging LLMs’ generative abilities to enhance reasoning capabilities. Although LLM-based judges are distinct from reward models, they can be viewed as a form of generative reward model, as their preferences can also be used in RLHF to align LLMs. This suggests that these two fields are closely related and are gradually converging.

162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215




Figure 2: Overview of JudgeBench Pipeline. Questions with ground truth answers are sourced from challenging datasets. We sample k responses to each question using a strong LLM (e.g., GPT-4o) and grade each response for correctness. Response pairs are constructed from correct and incorrect responses. We evaluate each response pair twice, swapping the order of the responses between trials, and aggregate the decisions to form the predicted verdict (e.g., $B > A$).

Benchmarks for LLM-based judges and reward models. As LLM-based judges have become a widely adopted method for evaluating and improving large language models (LLMs), several benchmarks have been introduced to assess their effectiveness. Works such as LLMEval (Zhang et al., 2023), MTBench (Zheng et al., 2024), and FairEval (Wang et al., 2023a) focus on evaluating the alignment between LLM-based judges’ responses and human evaluations. As mentioned above, these dataset suffers from the inherent subjectivity of human evaluation, prioritizing stylistic differences over factual and logical correctness. LLMBAR (Zeng et al., 2023) instead takes a different approach by assessing LLM-based judges’ ability to follow instructions, using response pairs with clear ground truth preference labels based on adherence to instructions rather than subjective preferences. In contrast, JudgeBench focuses on assessing LLM-based judges’ ability to reason through responses and distinguish between correct and incorrect responses, which is more challenging than instruction following alone.

On the reward model side, RewardBench (Lambert et al., 2024) is a benchmark that offers a comprehensive evaluation of reward models’ ability in domains such as safety, chat, and reasoning. The aggregation over several prior preference datasets and benchmarks (Li et al., 2023b; Zheng et al., 2024; Zeng et al., 2023; Lightman et al., 2023; Muennighoff et al., 2023; Röttger et al., 2023; Wang et al., 2023d; Bai et al., 2022a; Askeel et al., 2021; Ethayarajh et al., 2022; Stiennon et al., 2020). Compared to RewardBench’s reasoning datasets, JudgeBench proves to be significantly more challenging, as demonstrated by our experiments in Section 4.3.

3 JUDGE BENCH

JudgeBench’s pipeline. How do we generate challenging response pairs that are difficult for LLM-based judges to distinguish, while still providing an objective ground truth label? Revisiting principle (2), which is the focus of our work, it states that given that both answers faithfully follow human instruction, a factually and logically correct response is favored over an incorrect one. Our main idea to achieve this objective is to leverage an existing challenging dataset with ground truth labels and develop a pipeline to transform it into a set of response pairs. As long as the dataset contains ground truth labels and an algorithm to verify correctness, we can identify response pairs where one response passes the verification check and the other does not. The incorrect response may either fail to follow the instructions or answer the question incorrectly. This allows us to construct response pairs with clear objective ground truth labels that adhere to the above principle.

A straightforward approach would be using multiple LLMs to generate candidate responses and select one correct and one incorrect response to form the pair. While this method can indeed produce response pairs with objective ground truth labels, it comes with several limitations. First, the goal of our work is to construct response pairs that are difficult for LLM-based judges to distinguish. However, since different models vary in their capabilities, the incorrect response might be easily identifiable, thereby reducing the difficulty of the dataset. This would undermine the challenge for LLM-based judges, as the discrepancies between responses could be too obvious. Second, because each model has its own distinct style, LLM-based judges may place undue emphasis on stylistic differences rather than assessing the factual correctness of the answers. This focus on style runs counter to our intention to evaluate the reasoning abilities of LLM-based judges on challenging tasks. Finally, LLM-based judges are prone to favoring responses generated by the same model (also known as self-enhancement bias (Zheng et al., 2024)), making it difficult to measure and control for this bias when multiple models are involved.

Instead, we take an alternative approach informed by our key insight that *if a model struggles to consistently generate correct, coherent responses to a challenging question, it will find it difficult to differentiate between those responses*. Building on this insight, we propose a pipeline (Figure 2) that is a refined version of the approach mentioned earlier to mitigate potential pitfalls. First, given questions from an existing dataset, we sample k responses from a strong model (e.g., GPT-4o) and evaluate each response for correctness. Then, we filter out questions where all k responses are either all correct or all incorrect, leaving only questions to which we have at least one correct and one incorrect response from which we construct response pairs with objective ground truth labels.

As a result, the generated dataset is inherently more challenging for LLM-based judges. Since all candidate responses are produced by a single model, this method also ensures consistency in response style, reducing the influence of stylistic differences and mitigating self-enhancement bias in the judgments. However, this approach introduces a different kind of bias. Because the base model generates the responses, the dataset may be disproportionately challenging for that particular model compared to others, as different models may not struggle with the same questions. Nevertheless, this bias is confined to the model used for response generation, while creating a level playing field for all other models. In Section 4.4, we conduct an ablation study to examine the extent of this bias.

JudgeBench’s datasets. JudgeBench’s pipeline is flexible and dynamic, capable of transforming any existing dataset with ground truth labels and verification mechanisms into a response pair format for evaluating LLM-based judges. To ensure that the resulting response pairs are challenging to distinguish, the source dataset itself must present a significant level of difficulty. To assess JudgeBench’s ability to effectively test LLM-based judges, we categorize our datasets into four distinct categories: **Knowledge**, **Reasoning**, **Mathematics**, and **Coding**. We select datasets that align with these categories and meet the challenge criteria.

- **MMLU-Pro** (Wang et al., 2024a). We use MMLU-Pro for the **Knowledge** category. MMLU-Pro is a challenging multi-task dataset, filtered from the original MMLU dataset (Hendrycks et al., 2020). It includes 12,032 college-level exam questions across 14 disciplines (e.g., Physics, Chemistry, Law), each presented as a multiple-choice question with up to 10 possible options.
- **LiveBench** (White et al., 2024). LiveBench offers datasets in categories such as reasoning, mathematics, and instruction-following, and releases new data monthly to avoid contamination. For the **Reasoning** and **Mathematics** categories, we use the corresponding LiveBench datasets. The reasoning problems come from sources such as Big-Bench Hard (Suzgun et al., 2022), and Zebra Puzzles, while the math problems are drawn from math competitions (e.g., AMC12, USAMO).
- **LiveCodeBench** (Jain et al., 2024). LiveCodeBench is a contamination-free dataset for coding tasks, containing over 300 challenging questions sourced from coding contests like LeetCode, AtCoder, and Codeforces. We select this dataset for the **Coding** category.

Data Filtering and selection. Each of the datasets mentioned above provides a ground truth answer and an algorithm to evaluate the correctness of model outputs. For instance, MMLU-Pro verifies solutions based on regex string matching. During our pipeline execution, we found that some responses were marked incorrect due to minor formatting issues, even though their solutions were

correct. Constructing pairs with these responses is problematic, as the “incorrect” response may simply fail the automated check due to a slight format mismatch. This gives the judge an unintended shortcut, reducing the quality of the dataset.

To address this, we used an additional LLM (GPT-4o-mini) to verify the correctness of solutions. The model was prompted to extract the solution from the response and determine whether it was correct, regardless of format. We filtered out responses where the LLM and the automated solution checker disagreed. Upon manual inspection of these disagreements, we confirmed they were indeed caused by format errors. An example case where the two methods disagree can be found in Appendix A.4. We perform some additional randomized filtering on MMLU-Pro and LiveBench to better balance the size of each subset (see Appendix A.3 for details).

After applying our pipeline with GPT-4o as the underlying model and incorporating the additional filtering, our dataset consists of a total of 350 questions: 154 in **Knowledge**, 98 in **Reasoning**, 56 in **Mathematics**, and 42 in **Coding**.

4 EVALUATION

LLM-based judges are known to exhibit positional bias (Zheng et al., 2024; Wang et al., 2023a), where the order in which the response pairs are presented can influence their decision. Evaluating the judge on a single order of responses introduces this bias into the evaluation process. To mitigate positional bias, we evaluate the LLM-based judge twice, swapping the order of the response pairs in the second trial.

Since our response pairs contain an objectively correct and incorrect response, the only valid decisions are $A > B$ and $A < B$. However, in practice, some judges support a tie option: $A = B$. To address this discrepancy, we aggregate the results from both trials as follows: if both trials yield $A > B$ or one trial gives $A > B$ and the other $A = B$, we consider the aggregate decision to be $A > B$. Inconsistent decisions (e.g., $A > B$ in one trial, $A < B$ in the other) or ties in both trials are deemed incorrect, as they indicate the judge is either guessing or unable to reliably distinguish between responses. This method enables a more accurate measurement of the judges’ ability.

4.1 EVALUATING LLM-BASED JUDGES ON JUDGE BENCH.

In this subsection, we describe three major experiments we conduct on JudgeBench. First, we assess LLM-based judges from prior literature, which can be categorized as prompted, fine-tuned, and multi-agent judges. Second, we use JudgeBench as a proxy to evaluate the underlying LLM’s performance by fixing the prompt and varying the models. Lastly, we apply JudgeBench to evaluate reward models. In Section 4.2, we provide a detailed analysis of these results.

Evaluating LLM-based judges across categories. We evaluate the following three categories of LLM-based judges on JudgeBench. Additional details about these judges can be found in Appendix A.1.

- **Prompted Judges.** For prompted judges, we include the **Vanilla** judge, adapted from AlpacaFarm (Dubois et al., 2024), which directly prompts the LLM to indicate its preferred response without requiring an explanation. We also consider the **Arena-Hard Judge** (Li et al., 2024), which prompts the LLM to first generate its own reference answer, and then analyze both responses before delivering a final verdict. We also include Google’s **VertexAI Evaluation** service (Cloud, 2024) in this category.
- **Fine-tuned Judges.** For fine-tuned judges, we evaluate **PandaLM** (Wang et al., 2023c) (fine-tuned on LLaMA-7B (Touvron et al., 2023a)), **Prometheus2** (Kim et al., 2024b) (fine-tuned on Mistral-7B/Mixtral-8x7B), **JudgeLM** (Zhu et al., 2023b) (fine-tuned on Vicuna-7B/13B/33B (Chiang et al., 2023)), **AutoJ** (Li et al., 2023a) (fine-tuned on LLaMA-2-13B-chat (Touvron et al., 2023b)), and **Skywork’s** judges (Shiwen et al., 2024) fine-tuned on Llama-3.1-8B/70B (Dubey et al., 2024). These models are fine-tuned using either crowd-sourced preference datasets or on distilled GPT-4 judgments.
- **Multi-Agents Judges.** For multi-agent judges, we evaluate **ChatEval** (Chan et al., 2023), which leverages multiple LLMs in a debate to produce the final judgment.

	Knowledge	Reasoning	Math	Coding	Overall
Prompted Judges					
Vanilla (GPT-4o)	44.16	47.96	66.07	61.90	50.86
Arena-Hard Judge (GPT-4o)	50.65	54.08	75.00	59.52	56.57
VertexAI Evaluation (Gemini-1.5-pro)	45.45	44.90	53.57	28.57	44.57
Fine-tuned Judges					
PandaLM	9.09	21.43	7.14	16.67	13.14
Prometheus2-7b	38.31	25.51	35.71	42.86	34.86
Prometheus2-8x7b	41.56	39.80	50.00	23.81	40.29
Prometheus2-bgb-8x7b	45.45	30.61	46.43	28.57	39.43
JudgeLM-7B	23.38	29.59	32.14	11.90	25.14
JudgeLM-13B	26.62	29.59	28.57	19.05	26.86
JudgeLM-33B	32.47	48.98	33.93	19.05	35.71
AutoJ	40.26	29.59	44.64	28.57	36.57
Skywork-LLaMA-3.1B-8B	51.30	54.08	73.21	33.33	53.43
Skywork-LLaMA-3.1B-70B	55.84	55.10	73.21	47.62	57.43
Multi-Agent Judges					
ChatEval	32.47	31.63	44.64	30.95	34.00

Table 1: Evaluating LLM-based judges on JudgeBench.

Evaluating JudgeBench on different models. JudgeBench can also be used as a benchmark to evaluate the underlying model’s capability. To evaluate the ability of these models, we freeze the Arena-Hard Judge’s prompt and change the underlying model to see how the performance of different models varies. We select the latest models from four model providers: OpenAI, Anthropic, Meta, and Google. Some of these models we host ourselves and for others, we rely on either official or third-party APIs. We contain the details of our model sources in Appendix A.1.

Model	Knowledge	Reasoning	Math	Coding	Overall
GPT-4o	50.65	54.08	75.00	59.52	56.57
GPT-4o-mini	48.05	43.88	69.64	45.24	50.00
o1-preview	66.23	79.59	85.71	85.71	75.43
o1-mini	58.44	62.24	82.14	78.57	65.71
Claude-3.5-Sonnet	62.34	66.33	66.07	64.29	64.29
Claude-3-Haiku	35.06	34.69	33.93	21.43	33.14
Llama-3.1-405B-Instruct	55.84	54.08	69.64	50.00	56.86
Llama-3.1-70B-Instruct	51.30	48.98	60.71	52.38	52.29
Llama-3.1-8B-Instruct	38.31	45.92	44.64	33.33	40.86
Gemini-1.5-pro	49.35	42.86	64.29	26.19	47.14
Gemini-1.5-flash	42.86	36.73	50.00	21.43	39.71

Table 2: Evaluating the Arena-Hard Judge on JudgeBench, with different underlying models.

Evaluating JudgeBench on reward models. While our primary focus is on evaluating LLM-based judges, JudgeBench can also be used to assess reward models, which are trained on preference data to evaluate model outputs. Unlike pairwise LLM-based judges, reward models independently assign scores to each response, and the higher-scoring response is deemed the preferred one.

In our experiments, we evaluated several top-performing reward models from the RewardBench leaderboard (Lambert et al., 2024), including Skywork Reward’s model (Liu & Zeng, 2024), InternLM’s reward models (Cai et al., 2024), and the GRM-Gemma-2B (Yang et al., 2024) reward model fine-tuned on Google’s Gemma model (Team et al., 2024). Results are presented in Table 3

Reward Model	Knowledge	Reasoning	Math	Coding	Overall
Skywork-Reward-Gemma-2-27B	59.74	66.33	83.93	50.00	64.29
Skywork-Reward-Llama-3.1-8B	59.09	64.29	76.79	50.00	62.29
InternLM2-20B-Reward	62.34	69.39	66.07	50.00	63.43
InternLM2-7B-Reward	56.49	61.22	71.43	50.00	59.43
GRM-Gemma-2B	62.99	53.06	64.29	54.76	59.43

Table 3: Evaluating reward models on JudgeBench.

4.2 ANALYSIS AND TAKEAWAYS OF EVALUATION RESULTS ON JUDGEBENCH.

LLM-based judges’ performance falls short under JudgeBench’s challenging questions. The evaluation results from Table 1 and 2 highlight the difficulty of JudgeBench. Even a strong model like GPT-4o struggles, achieving accuracy no better than random guessing when using the vanilla prompt. Although the more advanced Arena-Hard prompt improves performance slightly (from 50% to 56%), the overall accuracy remains low.

All of our fine-tuned judges (except Skywork) perform significantly below the random baseline. We explore several reasons behind the relatively poor performance of fine-tuned judges in Appendix A.2. Among all the fine-tuned judges, Skywork’s LLM-based judges (Shiwen et al., 2024) perform the best overall, with an overall accuracy of 57.43%. When compared to the base Llama-3.1 models in Table 2, fine-tuning shows a clear performance boost, improving accuracy by over 12% for the 8B model and 5% for the 70B model.

Looking at Table 2, we can see that there is a clear gap in the performance between different models, with larger models generally performing better than their smaller counterparts across all providers. Among all the models, OpenAI’s latest o1-preview and o1-mini perform the best overall, achieving 75.43% and 65.71% accuracy respectively. These reasoning-enhanced models differ from standard models by taking time to “think” before generating a response (OpenAI, 2024), whereas others respond in a single pass. The superior results indicate that scaling test-time compute is a promising path to improve the reasoning ability of the judges. Beyond these models, Claude-3.5-Sonnet ranks highest among general-purpose models with an accuracy of 64.29%. Despite these results being well above the random baseline, all models still have considerable room for improvement.

Reward models’ performance is on par with much more powerful LLMs. When comparing the performance of reward models to LLM-based judges (Table 1), we find that fine-tuned reward models generally outperform LLM-based judges. For example, Skywork’s Gemma-2-27B reward model achieves accuracy comparable to Claude-3.5-Sonnet, one of the most advanced LLMs currently available, and Skywork’s Llama-3.1-8B reward model surpasses the performance of the base model by a huge margin (62.29% vs 40.86%). The above observation indicates that training a specialized verifier from a weak model to judge a stronger model is possible.

Our results also show that reward models exhibit a smaller performance gap on JudgeBench, with overall accuracies ranging from approximately 59% to 64%. This consistency is likely due to these models being trained or fine-tuned on similar open preference datasets, such as HelpSteer2 (Wang et al., 2024b) and Skywork-Preference-80 (Skywork, 2023). While model size does influence performance, as seen in the higher accuracy of InternLM-20B compared to InternLM-7B and Skywork’s Gemma-2-27B outperforming LLaMA-3.1-8B, the improvements are modest. This suggests that the quality of the training datasets plays a more critical role in shaping the preferences of reward models than model size alone.

Advancing the reasoning ability of LLM-based judges is the next frontier. Our evaluation on JudgeBench highlights the limitations of current LLM-based judges in distinguishing between challenging response pairs. As AI systems become more sophisticated, LLM-based judges risk becoming a bottleneck to further scaling. For example, Brown et al. (2024) demonstrated that repeated sampling can improve a model’s coverage (the percentage of problems solved) when an oracle-level verifier is available. However, when the verifier is not strong enough, it becomes the limiting factor in this process. Thus, enhancing the reasoning capabilities of LLM-based judges is essential for ad-




Figure 3: Comparison of JudgeBench against prior benchmarks for LLM-based judges.

vancing the overall performance of AI systems—an area that remains largely underexplored. While we leave improving the LLM-based judges as future work, JudgeBench provides a robust test bed for evaluating future reasoning-enhanced judges.

4.3 COMPARING JUDGE BENCH TO OTHER EXISTING BENCHMARKS.

Comparison with MTBench, LLMEval, FairEval, and LLMBar To compare with existing benchmarks for LLM-based judges, we evaluate five models (GPT-4o, Claude-3.5-Sonnet, Llama-3.1-70B-Instruct, Llama-3.1-8B-Instruct, and Claude-3.5-Haiku) on existing datasets using the Arena-Hard prompt. For fairness, we apply the same evaluation procedure described in Section 4, where the judge is run twice on each pair, and its final decision is based on the aggregated judgments.

Our results show that JudgeBench is the most challenging dataset for evaluating LLM-based judges. The strongest model on JudgeBench achieves only 64% accuracy, the lowest among all five datasets. Additionally, JudgeBench demonstrates strong separability, with a 31% performance gap between the best-performing model (Claude-3.5-Sonnet) and the weakest (Claude-3.5-Haiku). This gap is comparable to LLMBar: Adversarial, which has a 33% gap, indicating that JudgeBench is a strong benchmark for evaluating LLM-based judges.

Comparison with RewardBench. RewardBench (Lambert et al., 2024) is a general benchmark for evaluating reward models, with a subcategory dedicated to reasoning in reward models. It includes PRM Math (Lightman et al., 2023) and HumanEvalPack (Muennighoff et al., 2023) as benchmarks for reasoning tasks. These datasets are similar to the Math and Coding categories in JudgeBench, with PRM Math evaluating correct versus incorrect math proofs and HumanEvalPack comparing correct versus buggy code. However, these benchmarks are very saturated, with the strongest model achieving up to 97% accuracy on these datasets. This saturation is likely due to data contamination since datasets such as PRM-800k are widely used in training reward models nowadays. In contrast, JudgeBench is far more challenging, with top reward models achieving only 64% accuracy. Thus, JudgeBench offers a valuable complement to RewardBench for evaluating reward models on difficult tasks requiring reasoning.

4.4 ABLATION STUDIES

Is verifying a problem’s solution easier than solving the problem itself? Intuitively, verification should be simpler, as the model is provided with candidate solutions and only needs to identify the correct one, a task that would yield 50% accuracy through random guessing alone. To explore this, we conducted an ablation study in which we prompted models to directly solve the problem and compared their accuracy to that of the judge. Our results, presented in Table 4, show that for a fixed model, the judge’s accuracy closely mirrors that of the solver. While GPT-4o’s and Gemini-1.5-Pro’s judges slightly outperform their corresponding solvers, Claude-3.5-Sonnet’s and Llama-3.1-405B-Instruct’s judges lag behind their respective solvers.

Although the overall accuracy between the solver and judge is close, we observe a notable discrepancy in the Coding category, where the solver consistently outperforms the judge across all models. Conversely, in the Math category, judges significantly outperform solvers. This suggests that coding problems are more difficult to evaluate, while logical errors in math problems are generally easier

Setup	Knowledge	Reasoning	Math	Coding	Overall
GPT-4o Solver	48.70	53.06	58.93	73.81	54.57
GPT-4o Judge	50.65	54.08	75.00	59.52	56.57
Claude-3.5-Sonnet Solver	61.04	62.24	60.71	88.10	64.57
Claude-3.5-Sonnet Judge	62.34	66.33	66.07	64.29	64.29
Llama-3.1-405B-Instruct Solver	48.05	67.86	63.27	66.67	57.71
Llama-3.1-405B-Instruct Judge	55.84	54.08	69.64	50.00	56.86
Gemini-1.5-pro Solver	33.12	42.86	37.50	64.29	40.29
Gemini-1.5-pro Judge	49.35	42.86	64.29	26.19	47.14

Table 4: Evaluating the LLM’s ability to solve the problems.

to identify. Overall, this ablation study indicates that the ability of the judge to verify the solution pairs is highly correlated with its ability to solve the problem itself.

Investigating bias of the pipeline. In JudgeBench’s pipeline, we use GPT-4o to generate all response pairs. This introduces a bias against GPT-4o judges, as the generated pairs are inherently challenging for GPT-4o itself to distinguish. To empirically investigate this bias, we conduct an ablation study using Claude-3.5-Sonnet instead to generate response pairs. This results in 270 pairs, 154 pairs for Knowledge, 51 pairs for Reasoning, 34 pairs for Math, and 31 pairs for Coding.




Figure 4: Comparing JudgeBench’s evaluation results on GPT-4o versus Claude-3.5-Sonnet generated pairs.

Figure 4 presents a side-by-side comparison of several models’ performance on GPT-4o pairs versus Claude-3.5-Sonnet pairs. The results confirm our hypothesis: Claude-3.5-Sonnet, which achieves 64.3% accuracy on GPT-4o pairs, drops to 44.8% accuracy when tasked with judging its own generated pairs. Similarly, GPT-4o tops the Claude-3.5-Sonnet pairs with 53.9% accuracy. However, this number is still slightly lower than the 56.6% accuracy on its own pairs. This suggests that Claude-3.5-Sonnet is a stronger reasoning model, producing more difficult-to-distinguish response pairs in general. Beyond the models used to generate the response pairs, other models exhibit similar performance gaps, indicating that the response pairs remain consistent in evaluating model capabilities, regardless of the model used to generate the pairs.

CONCLUSION

In this work, we introduce a novel hierarchical evaluation framework to objectively evaluate LLM-based judges. Based on this framework, we propose JudgeBench, a benchmark for evaluating LLM-based judges’ ability to distinguish factually and logically correct outputs. Our work addresses the pressing need to evaluate LLM-based judges’ reasoning ability, which is of increasing importance given the rapid advancement of AI intelligence today. We hope that our framework and benchmark can offer insights into future dataset design and foster further research into this space.

REFERENCES

- 540
541
542 Amanda Askell, Yuntao Bai, Anna Chen, Dawn Drain, Deep Ganguli, Tom Henighan, Andy Jones,
543 Nicholas Joseph, Ben Mann, Nova DasSarma, et al. A general language assistant as a laboratory
544 for alignment. *arXiv preprint arXiv:2112.00861*, 2021.
- 545 Yuntao Bai, Andy Jones, Kamal Ndousse, Amanda Askell, Anna Chen, Nova DasSarma, Dawn
546 Drain, Stanislav Fort, Deep Ganguli, Tom Henighan, et al. Training a helpful and harmless
547 assistant with reinforcement learning from human feedback. *arXiv preprint arXiv:2204.05862*,
548 2022a.
- 549 Yuntao Bai, Saurav Kadavath, Sandipan Kundu, Amanda Askell, Jackson Kernion, Andy Jones,
550 Anna Chen, Anna Goldie, Azalia Mirhoseini, Cameron McKinnon, et al. Constitutional ai: Harm-
551 lessness from ai feedback. *arXiv preprint arXiv:2212.08073*, 2022b.
- 552
553 Bradley Brown, Jordan Juravsky, Ryan Ehrlich, Ronald Clark, Quoc V Le, Christopher Ré, and
554 Azalia Mirhoseini. Large language monkeys: Scaling inference compute with repeated sampling.
555 *arXiv preprint arXiv:2407.21787*, 2024.
- 556 Zheng Cai, Maosong Cao, Haojiong Chen, Kai Chen, Keyu Chen, Xin Chen, Xun Chen, Zehui
557 Chen, Zhi Chen, Pei Chu, Xiaoyi Dong, Haodong Duan, Qi Fan, Zhaoye Fei, Yang Gao, Jiaye
558 Ge, Chenya Gu, Yuzhe Gu, Tao Gui, Aijia Guo, Qipeng Guo, Conghui He, Yingfan Hu, Ting
559 Huang, Tao Jiang, Penglong Jiao, Zhenjiang Jin, Zhikai Lei, Jiaying Li, Jingwen Li, Linyang Li,
560 Shuaibin Li, Wei Li, Yining Li, Hongwei Liu, Jiangning Liu, Jiawei Hong, Kaiwen Liu, Kuikun
561 Liu, Xiaoran Liu, Chengqi Lv, Haijun Lv, Kai Lv, Li Ma, Runyuan Ma, Zerun Ma, Wenchang
562 Ning, Linke Ouyang, Jiantao Qiu, Yuan Qu, Fukai Shang, Yunfan Shao, Demin Song, Zifan Song,
563 Zhihao Sui, Peng Sun, Yu Sun, Huanze Tang, Bin Wang, Guoteng Wang, Jiaqi Wang, Jiayu Wang,
564 Rui Wang, Yudong Wang, Ziyi Wang, Xingjian Wei, Qizhen Weng, Fan Wu, Yingtong Xiong,
565 Chao Xu, Ruiliang Xu, Hang Yan, Yirong Yan, Xiaogui Yang, Haochen Ye, Huaiyuan Ying, Jia
566 Yu, Jing Yu, Yuhang Zang, Chuyu Zhang, Li Zhang, Pan Zhang, Peng Zhang, Ruijie Zhang, Shuo
567 Zhang, Songyang Zhang, Wenjian Zhang, Wenwei Zhang, Xingcheng Zhang, Xinyue Zhang, Hui
568 Zhao, Qian Zhao, Xiaomeng Zhao, Fengzhe Zhou, Zaida Zhou, Jingming Zhuo, Yicheng Zou,
569 Xipeng Qiu, Yu Qiao, and Dahua Lin. Internlm2 technical report, 2024.
- 570 Chi-Min Chan, Weize Chen, Yusheng Su, Jianxuan Yu, Wei Xue, Shanghang Zhang, Jie Fu, and
571 Zhiyuan Liu. Chateval: Towards better llm-based evaluators through multi-agent debate. *arXiv*
572 *preprint arXiv:2308.07201*, 2023.
- 573 Wei-Lin Chiang, Zhuohan Li, Zi Lin, Ying Sheng, Zhanghao Wu, Hao Zhang, Lianmin Zheng,
574 Siyuan Zhuang, Yonghao Zhuang, Joseph E. Gonzalez, Ion Stoica, and Eric P. Xing. Vicuna: An
575 open-source chatbot impressing gpt-4 with 90%* chatgpt quality, March 2023. URL <https://lmsys.org/blog/2023-03-30-vicuna/>.
- 576
577 Paul F Christiano, Jan Leike, Tom Brown, Miljan Martic, Shane Legg, and Dario Amodei. Deep
578 reinforcement learning from human preferences. *Advances in neural information processing systems*,
579 30, 2017.
- 580 Google Cloud. Generative ai evaluation service overview, 2024. URL <https://cloud.google.com/vertex-ai/generative-ai/docs/models/evaluation-overview>.
- 581
582
583
584 Karl Cobbe, Vineet Kosaraju, Mohammad Bavarian, Mark Chen, Heewoo Jun, Lukasz Kaiser,
585 Matthias Plappert, Jerry Tworek, Jacob Hilton, Reiichiro Nakano, et al. Training verifiers to
586 solve math word problems. *arXiv preprint arXiv:2110.14168*, 2021.
- 587
588 Abhimanyu Dubey, Abhinav Jauhri, Abhinav Pandey, Abhishek Kadian, Ahmad Al-Dahle, Aiesha
589 Letman, Akhil Mathur, Alan Schelten, Amy Yang, Angela Fan, et al. The llama 3 herd of models.
590 *arXiv preprint arXiv:2407.21783*, 2024.
- 591 Yann Dubois, Chen Xuechen Li, Rohan Taori, Tianyi Zhang, Ishaan Gulrajani, Jimmy Ba, Carlos
592 Guestrin, Percy S Liang, and Tatsunori B Hashimoto. AlpacaFarm: A simulation framework for
593 methods that learn from human feedback. *Advances in Neural Information Processing Systems*,
36, 2024.

- 594 Kawin Ethayarajh, Yejin Choi, and Swabha Swayamdipta. Understanding dataset difficulty with \mathcal{V} -
595 usable information. In *International Conference on Machine Learning*, pp. 5988–6008. PMLR,
596 2022.
- 597
598 Seungju Han, Kavel Rao, Allyson Ettinger, Liwei Jiang, Bill Yuchen Lin, Nathan Lambert, Yejin
599 Choi, and Nouha Dziri. Wildguard: Open one-stop moderation tools for safety risks, jailbreaks,
600 and refusals of llms, 2024. URL <https://arxiv.org/abs/2406.18495>.
- 601
602 Dan Hendrycks, Collin Burns, Steven Basart, Andy Zou, Mantas Mazeika, Dawn Song, and
603 Jacob Steinhardt. Measuring massive multitask language understanding. *arXiv preprint*
604 *arXiv:2009.03300*, 2020.
- 605
606 Hui Huang, Yingqi Qu, Hongli Zhou, Jing Liu, Muyun Yang, Bing Xu, and Tiejun Zhao. On the
607 limitations of fine-tuned judge models for llm evaluation. *arXiv preprint arXiv:2403.02839*, 2024.
- 608
609 Naman Jain, King Han, Alex Gu, Wen-Ding Li, Fanjia Yan, Tianjun Zhang, Sida Wang, Armando
610 Solar-Lezama, Koushik Sen, and Ion Stoica. Livecodebench: Holistic and contamination free
611 evaluation of large language models for code. *arXiv preprint arXiv:2403.07974*, 2024.
- 612
613 Albert Q Jiang, Alexandre Sablayrolles, Arthur Mensch, Chris Bamford, Devendra Singh Chaplot,
614 Diego de las Casas, Florian Bressand, Gianna Lengyel, Guillaume Lample, Lucile Saulnier, et al.
615 Mistral 7b. *arXiv preprint arXiv:2310.06825*, 2023.
- 616
617 Albert Q. Jiang, Alexandre Sablayrolles, Antoine Roux, Arthur Mensch, Blanche Savary, Chris
618 Bamford, Devendra Singh Chaplot, Diego de las Casas, Emma Bou Hanna, Florian Bressand, Gi-
619 anna Lengyel, Guillaume Bour, Guillaume Lample, L elio Renard Lavaud, Lucile Saulnier, Marie-
620 Anne Lachaux, Pierre Stock, Sandeep Subramanian, Sophia Yang, Szymon Antoniak, Teven Le
621 Scao, Th eophile Gervet, Thibaut Lavril, Thomas Wang, Timoth ee Lacroix, and William El Sayed.
622 Mixtral of experts. 2024. URL <https://arxiv.org/abs/2401.04088>.
- 623
624 Seungone Kim, Jamin Shin, Yejin Cho, Joel Jang, Shayne Longpre, Hwaran Lee, Sangdoon Yun,
625 Seongjin Shin, Sungdong Kim, James Thorne, et al. Prometheus: Inducing fine-grained evalua-
626 tion capability in language models. In *The Twelfth International Conference on Learning Repre-*
627 *sentations*, 2023.
- 628
629 Seungone Kim, Juyoung Suk, Ji Yong Cho, Shayne Longpre, Chaeun Kim, Dongkeun Yoon, Guijin
630 Son, Yejin Cho, Sheikh Shafayat, Jinheon Baek, Sue Hyun Park, Hyeonbin Hwang, Jinkyung Jo,
631 Hyowon Cho, Haebin Shin, Seongyun Lee, Hanseok Oh, Noah Lee, Namgyu Ho, Se June Joo,
632 Miyoung Ko, Yoonjoo Lee, Hyungjoo Chae, Jamin Shin, Joel Jang, Seonghyeon Ye, Bill Yuchen
633 Lin, Sean Welleck, Graham Neubig, Moontae Lee, Kyungjae Lee, and Minjoon Seo. The bigger
634 bench: A principled benchmark for fine-grained evaluation of language models with language
635 models, 2024a. URL <https://arxiv.org/abs/2406.05761>.
- 636
637 Seungone Kim, Juyoung Suk, Shayne Longpre, Bill Yuchen Lin, Jamin Shin, Sean Welleck, Graham
638 Neubig, Moontae Lee, Kyungjae Lee, and Minjoon Seo. Prometheus 2: An open source language
639 model specialized in evaluating other language models. *arXiv preprint arXiv:2405.01535*, 2024b.
- 640
641 Nathan Lambert, Valentina Pyatkin, Jacob Morrison, LJ Miranda, Bill Yuchen Lin, Khyathi Chandu,
642 Nouha Dziri, Sachin Kumar, Tom Zick, Yejin Choi, et al. Rewardbench: Evaluating reward
643 models for language modeling. *arXiv preprint arXiv:2403.13787*, 2024.
- 644
645 Junlong Li, Shichao Sun, Weizhe Yuan, Run-Ze Fan, Hai Zhao, and Pengfei Liu. Generative judge
646 for evaluating alignment. *arXiv preprint arXiv:2310.05470*, 2023a.
- 647
648 Tianle Li, Wei-Lin Chiang, Evan Frick, Lisa Dunlap, Tianhao Wu, Banghua Zhu, Joseph E Gon-
649 zalez, and Ion Stoica. From crowdsourced data to high-quality benchmarks: Arena-hard and
650 benchbuilder pipeline. *arXiv preprint arXiv:2406.11939*, 2024.
- 651
652 Xuechen Li, Tianyi Zhang, Yann Dubois, Rohan Taori, Ishaan Gulrajani, Carlos Guestrin, Percy
653 Liang, and Tatsunori B Hashimoto. AlpacaEval: An automatic evaluator of instruction-following
654 models, 2023b.

- 648 Hunter Lightman, Vineet Kosaraju, Yura Burda, Harri Edwards, Bowen Baker, Teddy Lee, Jan
649 Leike, John Schulman, Ilya Sutskever, and Karl Cobbe. Let’s verify step by step. *arXiv preprint*
650 *arXiv:2305.20050*, 2023.
- 651 Chris Yuhao Liu and Liang Zeng. Skywork reward model series. [https://huggingface.co/](https://huggingface.co/Skywork)
652 Skywork, September 2024. URL <https://huggingface.co/Skywork>.
- 653
654 Haipeng Luo, Qingfeng Sun, Can Xu, Pu Zhao, Qingwei Lin, Jianguang Lou, Shifeng Chen, Yan-
655 song Tang, and Weizhu Chen. Arena learning: Build data flywheel for llms post-training via
656 simulated chatbot arena. *arXiv preprint arXiv:2407.10627*, 2024a.
- 657
658 Liangchen Luo, Yinxiao Liu, Rosanne Liu, Samrat Phatale, Harsh Lara, Yunxuan Li, Lei Shu, Yun
659 Zhu, Lei Meng, Jiao Sun, et al. Improve mathematical reasoning in language models by automated
660 process supervision. *arXiv preprint arXiv:2406.06592*, 2024b.
- 661 Niklas Muennighoff, Qian Liu, Armel Zebaze, Qinkai Zheng, Binyuan Hui, Terry Yue Zhuo,
662 Swamy Singh, Xiangru Tang, Leandro Von Werra, and Shayne Longpre. Octopack: Instruc-
663 tion tuning code large language models. *arXiv preprint arXiv:2308.07124*, 2023.
- 664
665 OpenAI. How reasoning works, 2024. URL [https://platform.openai.com/docs/](https://platform.openai.com/docs/guides/reasoning/how-reasoning-works)
666 [guides/reasoning/how-reasoning-works](https://platform.openai.com/docs/guides/reasoning/how-reasoning-works). Accessed: 2024-09-29.
- 667
668 OpenAI, Josh Achiam, Steven Adler, Sandhini Agarwal, Lama Ahmad, Ilge Akkaya, Floren-
669 cia Leoni Aleman, Diogo Almeida, Janko Altenschmidt, Sam Altman, Shyamal Anadkat, Red
670 Avila, Igor Babuschkin, Suchir Balaji, Valerie Balcom, Paul Baltescu, Haiming Bao, Moham-
671 mad Bavarian, Jeff Belgum, Irwan Bello, Jake Berdine, Gabriel Bernadett-Shapiro, Christopher
672 Berner, Lenny Bogdonoff, Oleg Boiko, Madelaine Boyd, Anna-Luisa Brakman, Greg Brock-
673 man, Tim Brooks, Miles Brundage, Kevin Button, Trevor Cai, Rosie Campbell, Andrew Cann,
674 Brittany Carey, Chelsea Carlson, Rory Carmichael, Brooke Chan, Che Chang, Fotis Chantzis,
675 Derek Chen, Sully Chen, Ruby Chen, Jason Chen, Mark Chen, Ben Chess, Chester Cho, Casey
676 Chu, Hyung Won Chung, Dave Cummings, Jeremiah Currier, Yunxing Dai, Cory Decareaux,
677 Thomas Degry, Noah Deutsch, Damien Deville, Arka Dhar, David Dohan, Steve Dowling, Sheila
678 Dunning, Adrien Ecoffet, Atty Eleti, Tyna Eloundou, David Farhi, Liam Fedus, Niko Felix,
679 Simón Posada Fishman, Juston Forte, Isabella Fulford, Leo Gao, Elie Georges, Christian Gib-
680 son, Vik Goel, Tarun Gogineni, Gabriel Goh, Rapha Gontijo-Lopes, Jonathan Gordon, Morgan
681 Grafstein, Scott Gray, Ryan Greene, Joshua Gross, Shixiang Shane Gu, Yufei Guo, Chris Hal-
682 lacy, Jesse Han, Jeff Harris, Yuchen He, Mike Heaton, Johannes Heidecke, Chris Hesse, Alan
683 Hickey, Wade Hickey, Peter Hoeschele, Brandon Houghton, Kenny Hsu, Shengli Hu, Xin Hu,
684 Joost Huizinga, Shantanu Jain, Shawn Jain, Joanne Jang, Angela Jiang, Roger Jiang, Haozhun
685 Jin, Denny Jin, Shino Jomoto, Billie Jonn, Heewoo Jun, Tomer Kaftan, Łukasz Kaiser, Ali Ka-
686 mali, Ingmar Kanitscheider, Nitish Shirish Keskar, Tabarak Khan, Logan Kilpatrick, Jong Wook
687 Kim, Christina Kim, Yongjik Kim, Jan Hendrik Kirchner, Jamie Kiros, Matt Knight, Daniel
688 Kokotajlo, Łukasz Kondraciuk, Andrew Kondrich, Aris Konstantinidis, Kyle Kosic, Gretchen
689 Krueger, Vishal Kuo, Michael Lampe, Ikai Lan, Teddy Lee, Jan Leike, Jade Leung, Daniel
690 Levy, Chak Ming Li, Rachel Lim, Molly Lin, Stephanie Lin, Mateusz Litwin, Theresa Lopez,
691 Ryan Lowe, Patricia Lue, Anna Makanju, Kim Malfacini, Sam Manning, Todor Markov, Yaniv
692 Markovski, Bianca Martin, Katie Mayer, Andrew Mayne, Bob McGrew, Scott Mayer McKinney,
693 Christine McLeavey, Paul McMillan, Jake McNeil, David Medina, Aalok Mehta, Jacob Menick,
694 Luke Metz, Andrey Mishchenko, Pamela Mishkin, Vinnie Monaco, Evan Morikawa, Daniel
695 Mossing, Tong Mu, Mira Murati, Oleg Murk, David Mély, Ashvin Nair, Reiichiro Nakano, Ra-
696 jeev Nayak, Arvind Neelakantan, Richard Ngo, Hyeonwoo Noh, Long Ouyang, Cullen O’Keefe,
697 Jakub Pachocki, Alex Paino, Joe Palermo, Ashley Pantuliano, Giambattista Parascandolo, Joel
698 Parish, Emy Parparita, Alex Passos, Mikhail Pavlov, Andrew Peng, Adam Perelman, Filipe
699 de Avila Belbute Peres, Michael Petrov, Henrique Ponde de Oliveira Pinto, Michael, Pokorny,
700 Michelle Pokrass, Vitchyr H. Pong, Tolly Powell, Alethea Power, Boris Power, Elizabeth Proehl,
701 Raul Puri, Alec Radford, Jack Rae, Aditya Ramesh, Cameron Raymond, Francis Real, Kendra
Rimbach, Carl Ross, Bob Rotsted, Henri Roussez, Nick Ryder, Mario Saltarelli, Ted Sanders,
Shibani Santurkar, Girish Sastry, Heather Schmidt, David Schnurr, John Schulman, Daniel Sel-
sam, Kyla Sheppard, Toki Sherbakov, Jessica Shieh, Sarah Shoker, Pranav Shyam, Szymon Sidor,
Eric Sigler, Maddie Simens, Jordan Sitkin, Katarina Slama, Ian Sohl, Benjamin Sokolowsky,
Yang Song, Natalie Staudacher, Felipe Petroski Such, Natalie Summers, Ilya Sutskever, Jie Tang,

- 702 Nikolas Tezak, Madeleine B. Thompson, Phil Tillet, Amin Tootoonchian, Elizabeth Tseng, Pre-
703 ston Tuggle, Nick Turley, Jerry Tworek, Juan Felipe Cerón Uribe, Andrea Vallone, Arun Vi-
704 jayvergiya, Chelsea Voss, Carroll Wainwright, Justin Jay Wang, Alvin Wang, Ben Wang, Jonathan
705 Ward, Jason Wei, CJ Weinmann, Akila Welihinda, Peter Welinder, Jiayi Weng, Lilian Weng,
706 Matt Wiethoff, Dave Willner, Clemens Winter, Samuel Wolrich, Hannah Wong, Lauren Work-
707 man, Sherwin Wu, Jeff Wu, Michael Wu, Kai Xiao, Tao Xu, Sarah Yoo, Kevin Yu, Qiming
708 Yuan, Wojciech Zaremba, Rowan Zellers, Chong Zhang, Marvin Zhang, Shengjia Zhao, Tianhao
709 Zheng, Juntang Zhuang, William Zhuk, and Barret Zoph. Gpt-4 technical report, 2024. URL
710 <https://arxiv.org/abs/2303.08774>.
- 711 Junsoo Park, Seungyeon Jwa, Meiying Ren, Daeyoung Kim, and Sanghyuk Choi. Offsetbias: Lever-
712 aging debiased data for tuning evaluators, 2024.
- 713 Paul Röttger, Hannah Rose Kirk, Bertie Vidgen, Giuseppe Attanasio, Federico Bianchi, and Dirk
714 Hovy. Xstest: A test suite for identifying exaggerated safety behaviours in large language models.
715 *arXiv preprint arXiv:2308.01263*, 2023.
- 716 William Saunders, Catherine Yeh, Jeff Wu, Steven Bills, Long Ouyang, Jonathan Ward, and Jan
717 Leike. Self-critiquing models for assisting human evaluators. *arXiv preprint arXiv:2206.05802*,
718 2022.
- 719 Tu Shiwen, Zhao Liang, Chris Yuhao Liu, Liang Zeng, and Yang Liu. Skywork critic model
720 series. <https://huggingface.co/Skywork>, September 2024. URL [https://](https://huggingface.co/Skywork)
721 huggingface.co/Skywork.
- 722 Skywork. Skywork-reward-preference-80k-v0.1. [https://huggingface.co/datasets/](https://huggingface.co/datasets/Skywork/Skywork-Reward-Preference-80K-v0.1)
723 [Skywork/Skywork-Reward-Preference-80K-v0.1](https://huggingface.co/datasets/Skywork/Skywork-Reward-Preference-80K-v0.1), 2023. Accessed: 2024-09-18.
- 724 Nisan Stiennon, Long Ouyang, Jeffrey Wu, Daniel Ziegler, Ryan Lowe, Chelsea Voss, Alec Radford,
725 Dario Amodei, and Paul F Christiano. Learning to summarize with human feedback. *Advances*
726 *in Neural Information Processing Systems*, 33:3008–3021, 2020.
- 727 Mirac Suzgun, Nathan Scales, Nathanael Schärli, Sebastian Gehrmann, Yi Tay, Hyung Won Chung,
728 Aakanksha Chowdhery, Quoc V Le, Ed H Chi, Denny Zhou, et al. Challenging big-bench tasks
729 and whether chain-of-thought can solve them. *arXiv preprint arXiv:2210.09261*, 2022.
- 730 Gemma Team, Thomas Mesnard, Cassidy Hardin, Robert Dadashi, Surya Bhupatiraju, Shreya
731 Pathak, Laurent Sifre, Morgane Rivière, Mihir Sanjay Kale, Juliette Love, et al. Gemma: Open
732 models based on gemini research and technology. *arXiv preprint arXiv:2403.08295*, 2024.
- 733 Hugo Touvron, Thibaut Lavril, Gautier Izacard, Xavier Martinet, Marie-Anne Lachaux, Timothée
734 Lacroix, Baptiste Rozière, Naman Goyal, Eric Hambro, Faisal Azhar, et al. Llama: Open and
735 efficient foundation language models. *arXiv preprint arXiv:2302.13971*, 2023a.
- 736 Hugo Touvron, Louis Martin, Kevin Stone, Peter Albert, Amjad Almahairi, Yasmine Babaei, Niko-
737 lay Bashlykov, Soumya Batra, Prajjwal Bhargava, Shruti Bhosale, et al. Llama 2: Open founda-
738 tion and fine-tuned chat models. *arXiv preprint arXiv:2307.09288*, 2023b.
- 739 Jonathan Uesato, Nate Kushman, Ramana Kumar, Francis Song, Noah Siegel, Lisa Wang, Antonia
740 Creswell, Geoffrey Irving, and Irina Higgins. Solving math word problems with process-and
741 outcome-based feedback. *arXiv preprint arXiv:2211.14275*, 2022.
- 742 Pat Verga, Sebastian Hofstatter, Sophia Althammer, Yixuan Su, Aleksandra Piktus, Arkady
743 Arkhangorodsky, Minjie Xu, Naomi White, and Patrick Lewis. Replacing judges with juries:
744 Evaluating llm generations with a panel of diverse models. *arXiv preprint arXiv:2404.18796*,
745 2024.
- 746 Peiyi Wang, Lei Li, Liang Chen, Zefan Cai, Dawei Zhu, Binghuai Lin, Yunbo Cao, Qi Liu,
747 Tianyu Liu, and Zhifang Sui. Large language models are not fair evaluators. *arXiv preprint*
748 *arXiv:2305.17926*, 2023a.
- 749 Peiyi Wang, Lei Li, Zhihong Shao, RX Xu, Damai Dai, Yifei Li, Deli Chen, Y Wu, and Zhifang
750 Sui. Math-shepherd: A label-free step-by-step verifier for llms in mathematical reasoning. *arXiv*
751 *preprint arXiv:2312.08935*, 2023b.

- 756 Yidong Wang, Zhuohao Yu, Zhengran Zeng, Linyi Yang, Cunxiang Wang, Hao Chen, Chaoya Jiang,
757 Rui Xie, Jindong Wang, Xing Xie, et al. Pandalm: An automatic evaluation benchmark for llm
758 instruction tuning optimization. *arXiv preprint arXiv:2306.05087*, 2023c.
- 759 Yubo Wang, Xueguang Ma, Ge Zhang, Yuansheng Ni, Abhranil Chandra, Shiguang Guo, Weiming
760 Ren, Aaran Arulraj, Xuan He, Ziyang Jiang, et al. Mmlu-pro: A more robust and challenging
761 multi-task language understanding benchmark. *arXiv preprint arXiv:2406.01574*, 2024a.
- 762 Yuxia Wang, Haonan Li, Xudong Han, Preslav Nakov, and Timothy Baldwin. Do-not-answer: A
763 dataset for evaluating safeguards in llms. *arXiv preprint arXiv:2308.13387*, 2023d.
- 764 Zhilin Wang, Yi Dong, Olivier Delalleau, Jiaqi Zeng, Gerald Shen, Daniel Egert, Jimmy J. Zhang,
765 Makeesh Narsimhan Sreedhar, and Oleksii Kuchaiev. Helpsteer2: Open-source dataset for training
766 top-performing reward models, 2024b. URL <https://arxiv.org/abs/2406.08673>.
- 767 Colin White, Samuel Dooley, Manley Roberts, Arka Pal, Ben Feuer, Siddhartha Jain, Ravid Shwartz-
768 Ziv, Neel Jain, Khalid Saifullah, Siddartha Naidu, et al. Livebench: A challenging, contamination-
769 free llm benchmark. *arXiv preprint arXiv:2406.19314*, 2024.
- 770 Rui Yang, Ruomeng Ding, Yong Lin, Huan Zhang, and Tong Zhang. Regularizing hidden states
771 enables learning generalizable reward model for llms. *arXiv preprint arXiv:2406.10216*, 2024.
- 772 Fei Yu, Anningzhe Gao, and Benyou Wang. Ovm, outcome-supervised value models for planning in
773 mathematical reasoning. In *Findings of the Association for Computational Linguistics: NAACL*
774 *2024*, pp. 858–875, 2024.
- 775 Weizhe Yuan, Richard Yuanzhe Pang, Kyunghyun Cho, Sainbayar Sukhbaatar, Jing Xu, and Jason
776 Weston. Self-rewarding language models. *arXiv preprint arXiv:2401.10020*, 2024.
- 777 Zhiyuan Zeng, Jiatong Yu, Tianyu Gao, Yu Meng, Tanya Goyal, and Danqi Chen. Evaluating large
778 language models at evaluating instruction following. *arXiv preprint arXiv:2310.07641*, 2023.
- 779 Lunjun Zhang, Arian Hosseini, Hritik Bansal, Mehran Kazemi, Aviral Kumar, and Rishabh
780 Agarwal. Generative verifiers: Reward modeling as next-token prediction. *arXiv preprint*
781 *arXiv:2408.15240*, 2024.
- 782 Xinghua Zhang, Bowen Yu, Haiyang Yu, Yangyu Lv, Tingwen Liu, Fei Huang, Hongbo Xu,
783 and Yongbin Li. Wider and deeper llm networks are fairer llm evaluators. *arXiv preprint*
784 *arXiv:2308.01862*, 2023.
- 785 Lianmin Zheng, Wei-Lin Chiang, Ying Sheng, Siyuan Zhuang, Zhanghao Wu, Yonghao Zhuang,
786 Zi Lin, Zhuohan Li, Dacheng Li, Eric Xing, et al. Judging llm-as-a-judge with mt-bench and
787 chatbot arena. *Advances in Neural Information Processing Systems*, 36, 2024.
- 788 Banghua Zhu, Evan Frick, Tianhao Wu, Hanlin Zhu, and Jiantao Jiao. Starling-7b: Improving llm
789 helpfulness & harmlessness with rlaif, November 2023a.
- 790 Lianghui Zhu, Xinggong Wang, and Xinlong Wang. Judgelm: Fine-tuned large language models
791 are scalable judges. *arXiv preprint arXiv:2310.17631*, 2023b.
- 792 Daniel M Ziegler, Nisan Stiennon, Jeffrey Wu, Tom B Brown, Alec Radford, Dario Amodei, Paul
793 Christiano, and Geoffrey Irving. Fine-tuning language models from human preferences. *arXiv*
794 *preprint arXiv:1909.08593*, 2019.

800

801 A APPENDIX

802

803 A.1 DETAILS OF THE JUDGES

804

805 We closely followed the official implementation of each judge, only making modifications where
806 necessary. One broad change we made across all judges is the use of greedy decoding (tempera-
807 ture=0) to ensure reproducibility. Any additional judge-specific modifications are detailed below.
808 We sourced proprietary LLMs through their official APIs. All open-weight LLMs (including reward
809 models) were served locally in half-precision, except for Llama-3.1-405B-Instruct for which we
utilized the TogetherAPI. The prompts for each judge are provided for reference in Appendix A.5.

810 A.1.1 PROMPTED JUDGES

811
812 **Vanilla** (Dubois et al., 2024): This is a basic judge prompted to output a label indicating which
813 response it believes to be better, with no explanation required. This judge has no tie option. Each
814 judgment must be no more than 1024 tokens, however, in practice, they contained significantly fewer
815 tokens.

816
817 **Arena-Hard Judge** (Li et al., 2024): This judge is used in LMSYS’s Arena-Hard Leaderboard¹.
818 It’s prompted to provide its own response to the question to use as a reference before evaluating the
819 pair of candidate responses. This judge must decide between 5 options: $A \gg B$, $A > B$, $A = B$, $B > A$,
820 or $B \gg A$. We did not distinguish between the first two cases, nor did we distinguish between the last
821 two cases. Following the original implementation, each judgment must be less than 4096 tokens;
822 however, if we were unable to extract the verdict using regex (e.g., if the judgment was incomplete
823 after 4096 tokens), the judge was given one more opportunity to continue its judgment (up to 4096
824 additional tokens) and output a valid verdict. One special case worthy of note is the Arena-Hard
825 results with o1-mini and o1-preview may not have respected these token constraints nor the zero
826 temperature.

827 **Google Vertex Judge** (Cloud, 2024): Google Cloud offers a generative AI evaluation service
828 in Vertex AI powered by Gemini-Pro-001. It supports both single and pairwise evaluation, though
829 we only evaluated in the pairwise configuration using their predefined question-answering quality
830 metric. The service is proprietary and offers little to no ability to set generation parameters (e.g.,
831 temperature).

832 A.1.2 FINE-TUNED JUDGES

833
834 **PandaLM** (Wang et al., 2023c): PandaLM is a family of LLM-based judges based on LLaMA-7B
835 and LLaMA-70B (Touvron et al., 2023a), and fine-tuned on crowdsourced human preference data
836 collected by the authors. As of the time of publication, only the 7B variant of PandaLM has been
837 made publicly accessible, so we do not include results on the 70B variant. PandaLM supports a tie
838 option. We followed PandaLM’s official implementation closely, including beam searching over 4
839 beams. We made one crucial change to PandaLM’s official inference pipeline: we truncated both
840 candidate responses (from the left) to fit the request in the limited context window of 2048 tokens.
841 Left truncation was used as many of the responses in JudgeBench output their final decision at the
842 end; experimentally we found that left truncation performs better than right truncation. Although
843 PandaLM generates its decision before its explanation, we generated up to 150 tokens to give the
844 beams time to “mature.”

845
846 **Prometheus 2** (Kim et al., 2024b): Prometheus 2 is a family judges fine-tuned from Mistral
847 7B (Jiang et al., 2023) and Mixtral 8x7B (Jiang et al., 2024). These models are fine-tuned separately
848 on both Feedback Collections (Kim et al., 2023), a direct-assessment synthetic dataset generated
849 by GPT-4 (OpenAI et al., 2024), and Preference Collections (Kim et al., 2024b), an augmented
850 version of Feedback Collections for pairwise evaluation, with the resulting weights merged. Addi-
851 tionally, the authors subsequently released a second Mixtral variant further trained on the BiGGen
852 Bench (Kim et al., 2024a). We evaluated all 3 Prometheus 2 models on JudgeBench. Prometheus 2
853 judges support fine-grained evaluation criteria, and we used their official “factual validity” criteria
854 since it best aligns with the motivation of JudgeBench. Prometheus 2 does not support ties.

855
856 **JudgeLM** (Zhu et al., 2023b): JudgeLM is a family of judges fine-tuned from Vicuna (Chiang
857 et al., 2023) using a dataset collected from existing instruction-tuning datasets that have been aug-
858 mented with candidate responses and GPT-4 (OpenAI et al., 2024) judgments. JudgeLM assigns
859 integer scores to each candidate response, meaning ties are possible albeit unlikely. We made one
860 crucial change to JudgeLM’s official inference pipeline: we truncated both candidate responses
861 (from the left) to fit the request in the limited context window of 2048 tokens. Left truncation was
862 used as many of the responses in JudgeBench output their final decision at the end; experimentally
863 we found that left truncation performs better than right truncation. Since JudgeLM generates scores

¹<https://huggingface.co/spaces/lmsys/arena-hard-browser>

before an explanation, we limited the number of generated tokens to just 16 to reduce the amount that each candidate response is truncated.

Auto-J (Li et al., 2023a): Auto-J is a generative judge fine-tuned from Llama-2-13b-chat (Touvron et al., 2023b) on publicly available preference datasets augmented with GPT-4 (OpenAI et al., 2024) judgments. Auto-J supports ties. Following Auto-J’s official implementation, we generated judgments up to 1024 tokens in length at a temperature of 0.

Skywork Critics (Shiwen et al., 2024): Skywork released a series of 8B and 70B generative judges built on Llama-3.1-8B-Instruct and Llama-3.1-70B-Instruct (Dubey et al., 2024) respectively. These models are fine-tuned on a combination of proprietary and open-source critic datasets. Following their official implementation, we generated judgments up to 2048 tokens at a temperature of 0.

A.1.3 MULTI-AGENT JUDGES

ChatEval (Chan et al., 2023): ChatEval is a multi-agent judge that assigns roles to each agent. Our implementation used two agents (one to act at the general public, while the other acts as a critic) powered by GPT-4o as the model. The agents discuss sequentially (in a round-robin fashion) for at most 4 turns. After the discussion, each agent independently assigns a score (between 1 and 10) for each candidate response. We averaged the scores across both agents to determine the final decision.

A.2 ADDITIONAL ANALYSIS OF FINE-TUNED JUDGES

Many of the fine-tuned judges we evaluate score below the random guessing baseline of 50%. In this section, we highlight three reasons this is the case: (1) truncated responses, (2) ties and invalid decisions, and (3) inconsistent judgments. Moreover, we compare a few fine-tuned judges with pure-prompting judges using the same base model to understand the impact of fine-tuning for judging.

Truncated responses Two of our judges (PandaLM and JudgeLM) have limited context windows supporting just 2048 tokens. Combined, our candidate responses, however, often exceeded this limit. As such, we dynamically truncated (from the left) both candidate responses (leaving all other parts of the prompt template unchanged) to ensure the requests fit within the context limit. First, since many candidate responses do not output their final answer until the end of their responses, truncating from the left ensures the final answers are included in the truncated response provided to the judge. Second, early experimentation with PandaLM and JudgeLM revealed that truncating from the left resulted in better performance than truncating from the right.

Ties and invalid decisions Closely inspecting the generations of our fine-tuned judges reveals several weaknesses. For example, out of 700 judgments (2 games across 350 examples), PandaLM selected the tie option 479 times. Another Judge, Prometheus2-bgb-8x7b, made an invalid judgment from which we cannot extract a decision on 215 of 700 judgments. Some of these invalid judgments included “10/10”, “Neither A nor B”, and “3”. Table 5 provides the number of occurrences (out of 700 games) each of the fine-tuned judges selects $A > B$, $A < B$, $A = B$, or the judgment is otherwise invalid.

Inconsistent judgments Many fine-tuned judges struggled to generate consistent results between games. For example, JudgeLM-7B and JudgeLM-13B were inconsistent on 59.71% and 54.57% of pairs respectively. Likewise, Prometheus2-7b was inconsistent on 52.29% of pairs. Table 6 shares the rate of inconsistency in judgments between games.

Case Study: Do fine-tuned judges outperform prompted judges? The fine-tuned Skywork-Llama-3.1B-8B and Skywork-LLaMA-3.1B-70B outperformed the corresponding arena-hard judges with the instruction-tuned version of the same base model (Llama-3.1B-8B-Instruct and Llama-3.1B-70B-Instruct) by 12.57 and 5.14 respectively. Does this hold for other judges? In an attempt to answer this question, we evaluated Mistral-7B-v0.1-Instruct, the base model behind Prometheus2-7b, using the Vanilla and Arena-Hard prompts and present the results in Table 7. We found that Prometheus2-7b significantly outperformed its base model (Mistral-7B-v0.1-Instruct)

918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971

Judge	$A > B$	$A < B$	$A = B$	Invalid
PandaLM-7B	45	114	479	62
Prometheus2-7b	395	232	0	73
Prometheus2-8x7b	331	328	0	41
Prometheus2-bgb-8x7b	239	215	0	246
JudgeLM-7B	399	229	72	0
JudgeLM-13B	355	312	33	0
JudgeLM-33B	344	264	92	0
AutoJ	289	378	33	0
Skywork-LLaMA-3.1B-8B	346	354	0	0
Skywork-LLaMA-3.1B-70B	390	310	0	0

Table 5: The prevalence of judgment types for each fine-tuned judge.

Judge	Inconsistent
PandaLM-7B	29.14%
Prometheus2-7b	52.29%
Prometheus2-8x7b	40.00%
Prometheus2-bgb-8x7b	43.71%
JudgeLM-7B	59.71%
JudgeLM-13B	54.57%
JudgeLM-33B	38.00%
AutoJ	43.71%
Skywork-Llama-3.1B-8B	18.86%
Skywork-Llama-3.1B-70B	18.29%

Table 6: Rate of inconsistency between trials for each fine-tuned judge.

with both the vanilla prompt and Arena-Hard prompt. It’s worth noting that with the vanilla prompt, Mistral-7B-v0.1-Instruct selected response A in 624/700 games, and with the arena-hard prompt, Mistral-7B-v0.1-Instruct selected the tie option in 618/700 games. As such, it does appear that fine-tuned judges tend to outperform prompted judges when using the same base model.

A.3 DATASET FILTERING

We performed some additional filtering on MMLU-Pro and LiveBench. For MMLU-Pro, we randomly selected 100 questions from each of the 14 disciplines before generating responses and constructing pairs. Of these 1400 questions, only 347 and 233 contained both correct and incorrect responses generated by GPT-4o and Claude-3.5-Sonnet, respectively. In both cases, we randomly selected 11 pairs from each discipline, for a total of 154 knowledge pairs. Similarly, we randomly sampled 100 questions from the math and reasoning subsets of Livebench. Note that we exclude the “olympiad” subset of LiveBench-Math. We derived 98 reasoning pairs and 46 math pairs from GPT-4o responses, but just 51 reasoning pairs and 34 math pairs from Claude-3.5-Sonnet responses. We did no pre-filtering or post-filtering for LiveCodeBench, deriving 42 pairs from GPT-4o responses and 31 pairs from Claude-3.5-Sonnet responses.

Judge	Score
Prometheus2-7b	38.31
Vanilla (Mistral-7B-v0.1-Instruct)	7.43
Arena-Hard (Mistral-7B-v0.1-Instruct)	6.57

Table 7: Comparison of Prometheus2-7b against prompted judges with the same base model.

972 A.4 EVALUATING RESPONSES FOR CORRECTNESS
973

974 For LiveBench and MMLU-Pro, we checked the correctness of generated responses using two meth-
975 ods. First, we parsed the final answer from the responses using regex and checked against the ground
976 truth answers. For LiveBench, we closely followed their official post-processing methodology to
977 extract the final answers. For MMLU-Pro, we adapted the multiple-choice questions to the same
978 format used by LiveBench and included in the question instructions to output its final letter choice 5
979 times in a row (e.g., “My final answer is AAAAA”). Using regex, we extracted the last capital letter
980 A-J that was repeated 5 times and treated this as the final answer. Second, we queried GPT-4o-mini
981 with the question, response, and ground truth (using the prompt provided below) and had it decide
982 whether or not the response was correct. We excluded any responses where these two methods
983 disagree.

984 Prompt template for checking correctness with GPT-4o-mini.
985

986 **System Prompt:**

987 I will provide you with a multiple-choice question, a response from an LLM, and the
988 correct option. Output a valid JSON object containing a single key-value pair, where the
989 key is “is_correct” and corresponding value is a boolean indicating whether or not the
990 LLM-generated selects the correct option.

991 **User Prompt:**

992 < | Question | >
993 {question}

994
995 < | LLM Response | >
996 {response}

997
998 < | Correct Answer | >
999 {ground_truth}

1000
1001 The advantage of this combined approach is to eliminate any questionable responses, such as in the
1002 case where the model selects the correct answer but does not properly format its answer in accord-
1003 ance with the instructions. In general, we found high rates of agreement between these methods
1004 (e.g., 97.7% and 99.5% agreement across 7000 responses to the 14000 MMLU-Pro questions for
1005 GPT-4o and Claude-3.5-Sonnet, respectively). Below, we highlight an example case of disagree-
1006 ment, where the model correctly identified the correct answer, but formatted it incorrectly as I I I I I
1007 instead of I I I I I, which resulted in no regex match but GPT-4o-mini gave it the benefit of the doubt
1008 and marked it correct.
1009

1010 Example of disagreement between solution checkers.
1011

1012 **Question:**

1013 Which muscle is the most active during a right lateral excursion of the mandible?

- 1014 (A) Left masseter muscle
1015 (B) Right buccinator muscle
1016 (C) Right temporalis muscle
1017 (D) Right masseter muscle
1018 (E) Right lateral pterygoid muscle
1019 (F) Left medial pterygoid muscle
1020 (G) Left temporalis muscle
1021 (H) Left buccinator muscle
1022 (I) Left lateral pterygoid muscle
1023 (J) Right medial pterygoid muscle

1024 If you cannot determine the correct multiple-choice answer, take your best guess. Once you
1025 have your answer, please duplicate that letter five times in a single string. For example, if
the answer is K, then write KKKKK.

1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079

Let's think step by step.

Response:

To determine which muscle is most active during a right lateral excursion of the mandible, we need to understand the movements and the muscles involved. A right lateral excursion means the mandible is moving to the right.

1. **Muscles Involved in Mandibular Movements**:

- The **lateral pterygoid muscles** are the main muscles responsible for the lateral movements of the mandible. Each side's lateral pterygoid has a different function during this movement.

- The **right lateral pterygoid muscle** would pull the condyle of the mandible forward on the right side, resulting in leftward movement.

- The **left lateral pterygoid muscle** would cause the condyle on the left to move forward, assisting the mandible in moving to the right.

2. **Supporting Muscles**:

- The **masseter, temporalis, medial pterygoid, and buccinator** play roles primarily in elevation, retraction, or mastication rather than direct lateral movements.

3. **Logical Deduction**:

- When the mandible moves to the right, the **left lateral pterygoid muscle** is more engaged. This is because it's the left lateral pterygoid that pulls the left side of the mandible forward and to the right.

Given this, the most active muscle during a right lateral excursion of the mandible is: I. Left lateral pterygoid muscle. Therefore, the correct answer is: IIII

Ground Truth:

(I) Left lateral pterygoid muscle

A.5 PROMPTS

Below, we share the prompts used for each judge we evaluated. These prompts come directly from each judges' official implementation, but are provided for reference.

Vanilla Prompt

User Prompt:

You are a helpful assistant in evaluating the quality of the outputs for a given instruction. Your goal is to select the best output for the given instruction.

Select the Output (a) or Output (b) that is better for the given instruction. The two outputs are generated by two different AI chatbots respectively.

Do NOT provide any explanation for your choice.

Do NOT say both / neither are good.

You should answer using ONLY "Output (a)" or "Output (b)". Do NOT output any other words.

Instruction:

{question}

Output (a):

{response_a}

Output (b):

{response_b}

Which is better, Output (a) or Output (b)? Your response should be either "Output (a)" or "Output (b)":

1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133

Arena-Hard Prompt

System Prompt:

Please act as an impartial judge and evaluate the quality of the responses provided by two AI assistants to the user prompt displayed below. You will be given assistant A’s answer and assistant B’s answer. Your job is to evaluate which assistant’s answer is better.

Begin your evaluation by generating your own answer to the prompt. You must provide your answers before judging any answers.

When evaluating the assistants’ answers, compare both assistants’ answers with your answer. You must identify and correct any mistakes or inaccurate information.

Then consider if the assistant’s answers are helpful, relevant, and concise. Helpful means the answer correctly responds to the prompt or follows the instructions. Note when user prompt has any ambiguity or more than one interpretation, it is more helpful and appropriate to ask for clarifications or more information from the user than providing an answer based on assumptions. Relevant means all parts of the response closely connect or are appropriate to what is being asked. Concise means the response is clear and not verbose or excessive.

Then consider the creativity and novelty of the assistant’s answers when needed. Finally, identify any missing important information in the assistants’ answers that would be beneficial to include when responding to the user prompt.

After providing your explanation, you must output only one of the following choices as your final verdict with a label:

1. Assistant A is significantly better: `[[A>>B]]`
2. Assistant A is slightly better: `[[A>B]]`
3. Tie, relatively the same: `[[A=B]]`
4. Assistant B is slightly better: `[[B>A]]`
5. Assistant B is significantly better: `[[B>>A]]`

Example output: “My final verdict is tie: `[[A=B]]`”.

User Prompt:

< | User Prompt | >
{question}

< | The Start of Assistant A’s Answer | >
{response_a}
< | The End of Assistant A’s Answer | >

< | The Start of Assistant B’s Answer | >
{response_b}
< | The End of Assistant B’s Answer | >

Google Vertex Prompt

User Prompt:

Instruction

You are an expert evaluator. Your task is to evaluate the quality of the responses generated by two AI models. We will provide you with the user input and a pair of AI-generated responses (Response A and Response B). You should first read the user input carefully for analyzing the task, and then evaluate the quality of the responses based on the Criteria provided in the Evaluation section below.

1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187

You will first judge responses individually, following the Rating Rubric and Evaluation Steps. Then you will give step-by-step explanations for your judgment, compare results to declare the winner based on the Rating Rubric and Evaluation Steps.

Evaluation

Metric Definition

You will be assessing question answering quality, which measures the overall quality of the answer to the question in the user prompt. Pay special attention to length constraints, such as in X words or in Y sentences. The instruction for performing a question-answering task is provided in the user prompt. The response should not contain information that is not present in the context (if it is provided).

Criteria

Instruction following: The response demonstrates a clear understanding of the question answering task instructions, satisfying all of the instruction’s requirements.

Groundedness: The response contains information included only in the context if the context is present in the user prompt. The response does not reference any outside information.

Completeness: The response completely answers the question with sufficient detail.

Fluent: The response is well-organized and easy to read.

Rating Rubric

“A”: Response A answers the given question as per the criteria better than response B.

“SAME”: Response A and B answers the given question equally well as per the criteria.

“B”: Response B answers the given question as per the criteria better than response A.

Evaluation Steps

STEP 1: Analyze Response A based on the question answering quality criteria: Determine how well Response A fulfills the user requirements, is grounded in the context, is complete and fluent, and provides assessment according to the criterion.

STEP 2: Analyze Response B based on the question answering quality criteria: Determine how well Response B fulfills the user requirements, is grounded in the context, is complete and fluent, and provides assessment according to the criterion.

STEP 3: Compare the overall performance of Response A and Response B based on your analyses and assessment.

STEP 4: Output your preference of “A”, “SAME” or “B” to the pairwise_choice field according to the Rating Rubric.

STEP 5: Output your assessment reasoning in the explanation field.

User Inputs and AI-generated Responses

User Inputs

Prompt

{question}

AI-generated Response

Response A

{response_a}

Response B

{response_b}

PandaLM Prompt

Prompt:

Below are two responses for a given task. The task is defined by the Instruction. Evaluate the responses and generate a reference answer for the task.

1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241

```

### Instruction:
{question}

### Response 1:
{response_a}

### Response 2:
{response_b}

### Evaluation:

```

Prometheus 2 Prompt

System Prompt:

You are a fair judge assistant assigned to deliver insightful feedback that compares individual performances, highlighting how each stands relative to others within the same cohort.

User Prompt:

###Task Description:

An instruction (might include an Input inside it), a response to evaluate, and a score rubric representing a evaluation criteria are given.

1. Write a detailed feedback that assess the quality of two responses strictly based on the given score rubric, not evaluating in general.
2. After writing a feedback, choose a better response between Response A and Response B. You should refer to the score rubric.
3. The output format should look as follows: “(write a feedback for criteria) [RESULT] (A or B)”
4. Please do not generate any other opening, closing, and explanations.

```

###Instruction:
{question}

```

```

###Response A:
{response_a}

```

```

###Response B:
{response_b}

```

```

###Score Rubric:

```

[Are the model’s responses factually correct and well-supported by evidence?]

```

###Feedback:

```

JudgeLM Prompt

Prompt:

You are a helpful and precise assistant for checking the quality of the answer.

```

[Question]
{question}

```

```

[The Start of Assistant 1’s Answer]
{response_a}

```

```

[The End of Assistant 1’s Answer]

```

1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295

[The Start of Assistant 2’s Answer]
{response_b}

[The End of Assistant 2’s Answer]

[System]

We would like to request your feedback on the performance of two AI assistants in response to the user question displayed above.

Please rate the helpfulness, relevance, accuracy, level of details of their responses. Each assistant receives an overall score on a scale of 1 to 10, where a higher score indicates better overall performance.

Please first output a single line containing only two values indicating the scores for Assistant 1 and 2, respectively. The two scores are separated by a space. In the subsequent line, please provide a comprehensive explanation of your evaluation, avoiding any potential bias and ensuring that the order in which the responses were presented does not affect your judgment.

Response:

Auto-J Prompt

User Prompt:

You are assessing two submitted responses on a given user’s query and judging which response is better or they are tied. Here is the data:

[BEGIN DATA]

[Query]: {question}

[Response 1]: {response_a}

[Response 2]: {response_b}

[END DATA]

Here are the instructions to assess and compare the two responses:

1. Pinpoint the key factors to distinguish these two responses.
2. Conclude your comparison by providing a final decision on which response is better, or they are tied. Begin your final decision statement with “So, the final decision is Response 1 / Response 2 / Tie”. Ensure that your decision aligns coherently with the comprehensive evaluation and comparison you’ve provided.

Skywork Prompt

User Prompt:

Please act as an impartial judge and evaluate the quality of the responses provided by two AI assistants to the user question displayed below. You should choose the assistant that follows the user’s instructions and answers the user’s question better.

Your evaluation should consider factors such as the helpfulness, relevance, accuracy, depth, creativity, and level of detail of their responses. Avoid any position biases and ensure that the order in which the responses were presented does not influence your decision. Do not allow the length of the responses to influence your evaluation. Do not favor certain names of the assistants. Be as objective as possible.

Please directly output your final verdict by strictly following this format: “[[A]]” if assistant A is better, “[[B]]” if assistant B is better.

1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349

[User Question]
{question}

[The Start of Assistant A's Answer]
{response_a}
[The End of Assistant A's Answer]

[The Start of Assistant B's Answer]
{response_b}
[The End of Assistant B's Answer]

ChatEval Prompt

General Public Prompt:
[Question]
{question}

[The Start of Assistant 1's Answer]
{response_a}
[The End of Assistant 1's Answer]
[The Start of Assistant 2's Answer]
{response_b}
[The End of Assistant 2's Answer]
[System]
We would like to request your feedback on the performance of two AI assistants in response to the user question displayed above. Please consider the helpfulness, relevance, accuracy, and level of detail of their responses. There are a few other referees assigned the same task; it's your responsibility to discuss with them and think critically before you make your final judgment. Each assistant receives an overall score on a scale of 1 to 10, where a higher score indicates better overall performance.

You are now General Public, one of the referees in this task. You are interested in the story and looking for updates on the investigation. Please think critically by yourself and note that it's your responsibility to choose one of which is the better first.

Now it's your time to talk, please make your talk short and clear, General Public !

Please first provide a comprehensive explanation of your evaluation, avoiding any potential bias and ensuring that the order in which the responses were presented does not affect your judgment. Then, output two lines indicating the scores for Assistant 1 and 2, respectively.

Remember that you are not required to output the same value as other referees!
Output with the following format strictly:
Evaluation evidence: [your explanation here]
The score of Assistant 1: [score only]
The score of Assistant 2: [score only]

Critic Prompt:
[Question]
{question}

[The Start of Assistant 1's Answer]
{response_a}
[The End of Assistant 1's Answer]
[The Start of Assistant 2's Answer]
{response_b}
[The End of Assistant 2's Answer]

1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403

[System]
We would like to request your feedback on the performance of two AI assistants in response to the user question displayed above. Please consider the helpfulness, relevance, accuracy, and level of detail of their responses. There are a few other referees assigned the same task; it's your responsibility to discuss with them and think critically before you make your final judgment. Each assistant receives an overall score on a scale of 1 to 10, where a higher score indicates better overall performance.

You are now Critic, one of the referees in this task. You will check fluent writing, clear sentences, and good wording in summary writing. Your job is to question others judgment to make sure their judgment is well-considered and offer an alternative solution if two responses are at the same level.

Now it's your time to talk, please make your talk short and clear, Critic!

Please first provide a comprehensive explanation of your evaluation, avoiding any potential bias and ensuring that the order in which the responses were presented does not affect your judgment. Then, output two lines indicating the scores for Assistant 1 and 2, respectively.

Remember that you are not required to output the same value as other referees!
Output with the following format strictly:
Evaluation evidence: [your explanation here]
The score of Assistant 1: [score only]
The score of Assistant 2: [score only]