OpenCodeInterpreter: Integrating Code Generation with Execution and Refinement

Anonymous ACL submission

Abstract

The introduction of large language models has significantly advanced code generation. However, open-source models often lack the execution capabilities and iterative refinement of advanced systems like the GPT-4 Code Interpreter. To address this, we introduce OpenCodeInterpreter, a family of open-source code systems designed for generating, executing, and iteratively refining code. Supported by Code-Feedback, a dataset featuring 68K multi-turn interactions, OpenCodeInterpreter integrates execution and human feedback for dynamic code refinement. Our comprehensive evaluation of OpenCodeInterpreter across key benchmarks such as HumanEval, MBPP, and their enhanced versions from EvalPlus reveals its exceptional performance. Notably, OpenCodeInterpreter-017 33B achieves an accuracy of 83.2 (76.4) on the average (and plus versions) of HumanEval and MBPP, closely rivaling GPT-4's 84.2 (76.2) and further elevates to 91.6 (84.6) with synthesized human feedback from GPT-4. OpenCodeInter*preter* brings the gap between open-source code generation models and proprietary systems like GPT-4 Code Interpreter.¹

1 Introduction

Code generation has been a pivotal challenge within computer science for several decades. Recently, the landscape of code generation has been revolutionized by the advent of large language models (LLMs) pre-trained on extensive code corpora (Nijkamp et al., 2022; Christopoulou et al., 2022; Zheng et al., 2023; Li et al., 2023a; Wang et al., 2023c; Roziere et al., 2023; Guo et al., 2024). These models have showcased remarkable capabilities in generating code that accurately aligns with user intents, thus providing substantial support for software development (GitHub, 2023).



Figure 1: Overview of the *OpenCodeInterpreter* and its pass@1 accuracy on the HumanEval. With appropriate feedback, *OpenCodeInterpreter*-33B achieves performance comparable to that of the GPT-4 Code Interpreter.

To unleash the capabilities of pre-trained code models, instruction-tuning methods have been developed. For instance, CodeAlpaca (Chaudhary, 2023) comprises 20K code instructions automatically generated by applying self-instruct (Wang et al., 2023b) to ChatGPT, utilizing 21 seed tasks as

¹Our code and dataset are available at: anonymous link.

the foundation. To further refine the coding proficiency of LLMs, Luo et al. (2023) introduces Code Evol-Instruct, a method that applies a variety of heuristics to enrich the complexity of initial code instructions, building upon the dataset provided by CodeAlpaca. Meanwhile, MagicCoder (Wei et al., 2023) employs a robust LLM to generate novel coding challenges, sourcing inspiration from a diverse range of open-source code snippets. Additionally, WaveCoder (Yu et al., 2023) implements an LLM generator-discriminator framework for creating code instruction data, offering customization and control over the data generation process.

045

046

054

057

061

063

880

Despite these advancements, current code models are constrained by their capacity to utilize feedback for refinement. Essentially, feedback can have two forms: (1) *execution feedback*, which includes execution outputs and diagnostics, and (2) *human feedback*, comprising follow-up guidance or instructions from users. Execution feedback plays a vital role in enabling models to rectify syntactic and logical errors, and human feedback aids models in better understanding user instructions, facilitating the generation of solutions that more closely align with user expectations.

To address these challenges, we propose *Open-CodeInterpreter*, a family of open-source code systems designed for generating, executing, and iteratively refining code. *OpenCodeInterpreter* is trained on our constructed Code-Feedback dataset, which features 68K multi-turn interactions between users, code models, and compilers. *OpenCodeInterpreter* uniquely integrates both execution and human feedback, employing compiler diagnostics to rectify errors and human insights to refine code generation. This approach allows *OpenCodeInterpreter* to produce solutions that are both technically sound and closely matched to user requirements, significantly boosting its overall performance.

Our thorough evaluation of *OpenCodeInterpreter* on widely recognized benchmarks, such as HumanEval (Chen et al., 2021), MBPP (Austin et al., 2021), and their augmented counterparts from EvalPlus (Liu et al., 2023), highlights its superior ability to generate and iteratively refine code, achieving exemplary standards of quality and functionality. Remarkably, *OpenCodeInterpreter*-33B secures an impressive accuracy of 83.2 (76.4) on the average (and plus versions) of HumanEval and MBPP, showcasing performance on par with GPT-4's 84.2 (76.2). Furthermore, when augmented with synthesized human feedback from GPT-4, *Open*- *CodeInterpreter*'s performance notably increases to 91.6 (84.6). *OpenCodeInterpreter* thereby establishes a new benchmark in code generation, effectively narrowing the performance gap between open-source models and sophisticated proprietary systems like the GPT-4 Code Interpreter. 097

098

099

100

101

102

103

104

105

107

108

109

110

111

112

113

114

115

116

117

118

119

120

121

122

123

124

125

126

127

128

129

131

132

133

134

135

136

137

138

139

140

2 Code-Feedback

In this section, we detail the creation of our code instruction tuning dataset, Code-Feedback (Figure 2), designed to train OpenCodeInterpreter. Code-Feedback is crafted to meet specific criteria: 1) Diverse and challenging real-world queries: The dataset should encompass a wide range of queries derived from real-world coding tasks, presenting both diversity and complexity. 2) Multi-turn dialogue structure: Code-Feedback is structured as multi-turn dialogues, incorporating two types of feedback: execution feedback, which includes outputs and diagnostics from compilers, and human feedback, consisting of additional guidance or instructions from users. 3) Interleaved text and code responses: Each response is expected to provide responses that blend natural language explanations with code snippets, offering a holistic approach to solving coding queries.

To assemble a dataset that fulfills these desiderata, we have employed five distinct methods. Examples of these five categories can be found in Appendix E. The sources of our queries fall into two main categories: *a variety of open-source datasets* and *coding challenges from LeetCode*. In the next subsections, we will discuss how we develop data construction methods to meet the three aforementioned criteria from the two data sources.

2.1 Coding Queries from Open-source Data

We have aggregated 287k queries from four distinguished open-source code instruction tuning datasets: Magicoder-OSS-Instruct², Python code subset of ShareGPT³, Magicoder-Evol-Instruct⁴, and Evol-Instruct-Code ⁵. To refine this extensive collection and isolate the most intricate and informative instructions, we employ a very capable open-source chat model, Qwen-72B-Chat (Bai et al., 2023), for a selective filtering process. This

¹hf.co/datasets/HuggingFaceH4/CodeAlpaca_20K

²hf.co/datasets/ise-uiuc/Magicoder-OSS-Instruct-75K ³hf.co/datasets/ajibawa-2023/Python-Code-23k-ShareGPT

⁴hf.co/datasets/ise-uiuc/Magicoder-Evol-Instruct-110K ⁵hf.co/datasets/nickrosh/Evol-Instruct-Code-80k-v1



Figure 2: Summary of our proposed dataset Code-Feedback construction and comparison with existing code instruction tuning datasets. M.T: Multi Turn, E.F: Execute Feedback, H.F: Human Feedback.

involves the LLM assessing each code query and its corresponding response within the compiled datasets on a complexity score from 1 to 5. Only the most challenging queries, with ratings of 4 or 5, were retained for our seed set, ensuring a focus on the most difficult instructions. To guarantee the robustness of our selection, this filtering operation is repeated with two distinct prompts (detailed in Appendix A), thereby solidifying the complexity of our final query selection. This meticulous process resulted in 156k high-quality single-turn code instructions as the challenging query pool. Detailed statistics of this data compilation are provided in Appendix A.

141

142

143

144

145

146

147

148

149

150

151

152

153

154

155

156

158

159

161

164

165

166

Subsequently, we describe three methods employed to transform this curated single-turn data into multi-turn dialogues enriched with both execution and human feedback.

Singe-turn Packing. A direct approach to crafting multi-turn data is to group single-turn queryresponse pairs into multi-turn formats. Inspired by in-context pre-training techniques (Shi et al., 2023), which consolidate similar sequences to foster model learning of dependencies among related documents, we merge similar single-turn queryresponse pairs to form multi-turn dialogues.

Utilizing the BERT-base embedding (Devlin et al., 2019), we convert queries into vectorized rep-168 resentations. For each query, the k-nearest neigh-169 bors algorithm is employed to identify its four closest counterparts. From these, we randomly select 172 two or three to assemble multi-turn sequences. To maintain data uniqueness, once a query is chosen 173 as a neighbor, it is exempt from future selections as 174 a neighboring query, ensuring no single instruction 175 is repeated across the dataset. Should a query's 176

potential neighbors have been previously utilized, that query is bypassed. This method results in the creation of 16.6K multi-turn instances derived from 105K single-turn instances. 177

178

179

180

181

182

183

184

185

186

187

189

190

191

192

193

194

195

196

197

198

199

200

201

202

203

204

205

206

207

208

210

211

212

Interaction Simulation. Real human interaction data is hard to collect. To mimic the code interpreter real-use scenario, we create a simulator based on GPT-3.5 and GPT-4. Specifically, given a sampled query, we first let the GPT-3.5 generate an initial response. We extract the code snippet from the response and run the code. We then pass the execution output or compiler diagnostics (if any) to the GPT-4 model and let it generate the followup. We repeat the process until GPT-4 thinks it outputs a correct solution or reaches the 3 maximum iterations. Next, we simulate the human follow-up question and feedback. We pre-define 10 common feedback types including syntax and formatting, efficiency, functionality enhancements, code clarity and documentation, bug identification, security improvements, compatibility and testing, resource optimization, scalability, and adherence to best practices. The details of each type of feedback are illustrated in Appendix B. Then, we prompt GPT-4 to automatically decide which type of feedback is the most proper in the current scenario and generate potential feedback under that category. Finally, we append the generated feedback to the dialog history, prompting GPT-4 to generate solutions that address the feedback. This simulates complex user-model interactions, along with interleaving multi-turn execution feedback loops, where GPT-4 also makes self-corrections based on human feedback to improve the proposed solutions. This method results in 51K examples in total.

Code Correction. To enhance the model's robust-

ness, an additional step was incorporated into our 213 data collection process, focusing on the creation of 214 500 specific error correction interactions. Specif-215 ically, we prompt GPT-4 to deliberately generate 216 incorrect code snippets (Appendix B). Following 217 this, the model utilized the error messages resulting 218 from the execution of these incorrect codes as a ba-219 sis for making corrections. This approach not only simulates a realistic coding environment where programmers iteratively debug and refine their code 222 but also enriches our dataset with a wide range of error-handling examples. After that, the instructions that originally prompted the generation of incorrect code were replaced with commands aimed 226 at producing correct code outputs. This method-227 ology ensures that the model learns not only from accurate code generation tasks but also gains the ability to identify and correct errors, thereby significantly improving its problem-solving capabilities and understanding of the debugging process.

2.2 Coding Challenges from LeetCode

234

235

239

241

242

243

246

247

254

258

259

260

LeetCode Similar Problem. Inspired by the common practice of human programmers who often master a shared knowledge base by solving similar LeetCode problems, we extract similar LeetCode questions and their corresponding solutions from the LeetCode dataset in TACO (Li et al., 2023b). LeetCode⁶ tags related questions in their UI, allowing us to easily extract the related questions. TACO verifies that the LeetCode dataset has been decontaminated to avoid influencing the downstream task datasets, e.g., HumanEval and MBPP. By concatenating related LeetCode questions, we generate a total of 303 multi-turn instances.

LeetCode Follow-up Question. Additionally, we parse the solutions in the LeetCode dataset to extract solutions of the same LeetCode questions with different time or space complexity or using different programming languages. By concatenating different solutions to the same LeetCode questions, we generate a total of 200 multi-round instances.

Due to the lack of natural language explanations of initial LeetCode solutions, we prompt GPT-4 to make the response containing interleaved text explanations and code snippets. Subsequently, all instances are unified into the same format. The prompt provided to GPT-4 during this process can be found in Appendix C.

3 Experimental Setup

Training Setup. We fine-tune the base models for 3 epochs, with all models sharing identical hyperparameter settings. The base models chosen for our study include CodeLlama-Python and DeepSeek-Coder of different capacities to demonstrate the consistent benefit of the dataset we constructed across different series and sizes of Code LLM baselines. We adopt the optimal mix of high-quality single-turn data, i,e. data randomly sampled from WizardCoder 110k dataset, with our constructed data as 2:1 to finetune all OpenInterpreter Series Models in Table 1. Employing a cosine scheduler, we set the initial learning rate at 2e-5, using a warmup ratio of 0.05. The token cutoff length is fixed at 4096, and BF16 is utilized.

Evaluation Setup. We mainly utilize HumanEval (Chen et al., 2021) and MBPP (Austin et al., 2021), standing as two of the most widely recognized benchmarks for code generation, for evaluating our models. Given that the original test suites accompanying these benchmarks may not sufficiently cover all edge cases (Liu et al., 2023), we also use the expanded versions, HumanEval+ and MBPP+, powered by the EvalPlus framework (Liu et al., 2023). Following (Liu et al., 2023; Chen et al., 2023), our evaluation for OpenCodeInterpreter adopts greedy decoding to generate solutions. Additionally, when generating solutions with GPT-3.5 Turbo (OpenAI, 2022) and GPT-4 Turbo (OpenAI, 2023), we set the temperature to 0. We post-process the generated solutions using the unified sanitizer tool provided by EvalPlus, and then evaluate them on four benchmarks using the EvalPlus's evaluation tool.

As for **single-turn** code generation, we employ a simple instruction to wrap the original prompt, which serves as the new prompt input to the model. The detailed prompts are provided in the Appendix D. Following EvalPlus, we evaluate the model's pass@1 performance.

We also evaluate **multi-turn** pass rates, aiming to gauge the model's effectiveness when refining code through iterative interactions. This evaluation utilizes system-generated execution results and human-like feedback generated by GPT models (OpenAI, 2022, 2023) as inputs. Through this approach, we aim to showcase *OpenCodeInterpreter*'s versatility and efficacy in a dynamic coding environment, highlighting its potential as an influential tool in software development and code refinement.

310

311

261

262

263

⁶https://leetcode.com/problemset/

Model	Size	Туре	Open-s Model	ource Data	HumanEval (+)	MBPP (+)	Average (+)
GPT-4 Turbo + Execution Feedback GPT 3 5 Turbo	-	-	0	0	85.4 (81.7) 88.0 (84.2) 72.6 (65.9)	83.0 (70.7) 92.0 (78.2) 81.7 (69.4)	84.2 (76.2) 90.0 (81.2)
+ Execution Feedback	-	-	0	0	72.0 (05.9) 76.8 (70.7)	81.7 (09.4) 87.0 (73.9)	81.9 (72.3)
Gemini Pro (Google et al., 2023)	-	-	0	0	63.4 (55.5)	72.9 (57.9)	68.2 (56.7)
		\sim 7H	3 Scale				
StarCoder (Li et al., 2023a)	7B	Base	•	•	24.4 (20.7)	33.1 (28.8)	28.8 (24.8)
CodeT5+ (Wang et al., 2023c)	6B	Base	•	•	29.3 (23.8)	51.9 (40.9)	40.6 (32.4)
CodeGen-Mono (Nijkamp et al., 2022) Mistral (Jiang et al., 2023)	6B 7B	Base	•	•	29.3 (25.6)	49.9 (42.1)	39.6 (33.9)
OpenChat (Wang et al., 2023)	7B	Instruct	•	•	72.0 (67.1)	62.7 (52.9)	67.4 (60.0)
CodeLlama-Python (Roziere et al., 2023)	7B	Base	•	0	37.8 (34.1)	57.6 (45.4)	47.7 (39.8)
WizardCoder-CL (Luo et al., 2023)	7B	Instruct	0	0	48.2 (40.9)	56.6 (47.1)	52.4 (44.0)
Magicoder-CL (Wei et al., 2023) Magicoders S. CL (Wei et al., 2023)	7B 7D	Instruct	•	•	60.4 (55.5) 70 7 (66 5)	64.2 (52.6)	62.3 (54.1)
OpenCodeInterpreter-CL	/ D	Instruct	·	•	72.6 (67.7)	66.4 (55.4)	69.5 (61.6)
+ Execution Feedback	7B	Instruct	•	•	75.6 (70.1)	69.9 (60.7)	72.8 (65.4)
DeepseekCoder (Guo et al., 2024)	6.7B	Base	•	0	47.6 (39.6)	70.2 (56.6)	58.9 (48.1)
DeepseekCoder-Instruct	6.7B	Instruct	•	0	73.8 (70.1)	73.2 (63.4)	73.5 (66.8)
+ Execution Feedback Magicoder-DS (Wei et al. 2023)	6 7B	Instruct	•	•	80.5 (75.6) 66 5 (60.4)	75.4 (61.9)	80.2 (73.0)
Magicoder-S-DS (Wei et al., 2023)	6.7D	Instruct	_		76.8 (70.7)	75.7 (64.4)	76.3 (67.6)
+ Execution Feedback	0./B	Instruct	•	•	77.4 (72.0)	73.2 (62.4)	75.3 (67.2)
OpenCodeInterpreter-DS					76.2 (72.0)	76.2 (72.0)	75.1 (67.9)
+ Execution Feedback + Synth Human Feedback	6.7B	Instruct	•	•	81.1 (78.7) 87 2 (86.6)	82.7 (72.4) 86.2 (74.2)	81.9 (75.6) 86 7 (80.4)
+ Synth. Human Feedback (Oracle)					89.7 (86.6)	87.2 (75.2)	88.5 (80.9)
		~13	B Scale				
CodeGen-Mono (Nijkamp et al., 2022)	16B	Base	•	•	32.9 (27.4)	52.6 (43.6)	42.8 (35.5)
StarCoder (Li et al., 2023a)	15B	Base	•	0	34.1 (29.3)	55.1 (46.1)	44.6 (37.7)
CodeT5+ (Wang et al., 2023c)	_16B	Base	•	0	31.7 (26.2)	54.6 (44.4)	43.2 (35.3)
CodeLlama-Python (Roziere et al., 2023)	13B	Base	•	0	42.7 (36.6)	61.2 (50.9)	52.0 (43.8)
<i>UpenCodeInterpreter</i> -CL + Execution Feedback	13B	Instruct	•	•	77.4 (73.8) 81 1 (76 8)	70.7 (59.2)	74.1 (66.5)
+ Execution Feedback 81.1 (70.8) 78.2 (67.2) 79.7 (72.0)							
CodeL lama Python (Roziere et al. 2023)	3/B	Base	·	0	51 8 (43 9)	67.2 (52.9)	50 5 (48 4)
Speechless-CL-v2.0 (speechless, 2023)	34B	Instruct	•	•	77.4 (71.3)	72.4 (59.1)	74.9 (65.2)
XwinCoder-CL (Xwin-LM, 2023)	34B	Instruct	•	•	75.6 (67.7)	76.2 (62.4)	75.9 (65.1)
Phind-CL-v2 (Phind, 2023)	34B	Instruct	•	0	71.3 (67.1)	-	-
WizardCoder-CL (Luo et al., 2023) OpenCodeInterpreter-CL	34B	Instruct	•	0	73.2 (64.6)	73.2 (59.9)	75.7 (62.3)
+ Execution Feedback	34B	Instruct	•	•	81.7 (78.7)	80.2 (67.9)	81.0 (73.3)
DeepSeekCoder (Guo et al., 2024)	33B	Base	•	0	51.2 (44.5)	-	
+ Execution Feedback	33B	Instruct	•	0	81.1 (75.0) 81.1 (76.2)	78.7 (66.7) 82 7 (73.4)	79.9 (70.9) 81 9 (74 8)
WizardCoder-V1.1 (Luo et al., 2023)	220	T	_		79.9 (73.2)	78.9 (66.9)	79.4 (70.1)
+ Execution Feedback	33B	Instruct	•	0	74.4 (69.5)	79.9 (68.2)	77.2 (68.9)
OpenCodeInterpreter-DS					79.3 (74.3)	78.7 (66.4)	79.0 (70.4)
+ Synth. Human Feedback	33B	Instruct	•	•	88.4 (86.0)	87.5 (72.2)	88.0 (81.0)
+ Synth. Human Feedback (Oracle)					92.7 (89.7)	90.5 (79.5)	91.6 (84.6)
~70B Scale							
CodeLlama-Python (Roziere et al., 2023)	70B	Base	•	0	55.5 (50.0)	65.4 (53.4)	60.5 (51.7)
CodeLlama-Instruct	70B	Instruct	•	0	72.0 (65.2)	75.4 (61.7)	73.7 (63.5)
<i>OpenCodeInterpreter</i> -CL + Execution Feedback	70B	Instruct	•	•	76.2 (70.7) 79.9 (77.4)	73.0 (61.9) 81.5 (69.9)	74.6 (66.3) 80.7 (73.7)

Table 1: Pass@1 accuracy of different code models on HumanEval (+), MBPP (+) and their average (+). 'CL': based on CodeLlama; 'DS': based on DeepseekCoder. Baseline results are copied from the EvalPlus Leaderboard or replicated by running the official checkpoints. We highlight strong baselines and our methods for each scale.

388

389

390

391

392

393

394

395

396

397

398

399

400

401

402

403

404

405

406

407

408

409

360

312Our experimental framework consists of three313distinct scenarios to comprehensively evaluate the314model's capacity for dynamic code refinement:

315

319

321

323

325

330

333

337

338

341

343

345

351

353

355

359

- Execution Feedback: The model autonomously utilizes execution output and compiler diagnosis to identify and rectify code issues. This scenario assesses the model's independent error diagnosis and correction capabilities, akin to a developer refining code based on Execution Feedback.
 - Synthetic Human Feedback: Here, GPT-4 mimics human feedback by analyzing the task description, the initial model response, and any execution feedback, then generating human-like feedback. This scenario evaluates *OpenCodeInterpreter*'s ability to adjust code based on complex, human-like input, simulating feedback from peers or end-users.
 - Synthetic Human Feedback (Oracle): In addition to the information utilized in the previous scenario, GPT-4 also has additional access to the correct solution. This assesses *OpenCodeInterpreter*'s ceiling performance of code refinements if given accurate feedback.

For a given task, the process of code generation and evaluation ceases when the solution generated by the model passes the evaluation or when the maximum number of rounds (2 in this paper) for generation is reached.

Upon completion of the initial code generation round, the generated solutions will undergo execution testing. If a generated code sample fails the evaluation, both the solution and the test results are added back to the prompt. Three main non-passing cases could result from the process: (1) Exception handling: Any exception or errors raised during execution would be captured and reported back in the form or error messages; (2) Not-expected: If the test results do not match expectations, the test inputs, expected outputs, and the actual outputs would be returned; (3) Timeout handling: A timeout threshold is set to ensure solutions with inefficient or infinite runtime do not stall the evaluation process. Any code exceeding this limit would result in an "Execution timed out" notification.

4 Main Results

This section reports *OpenCodeInterpreter* and baselines in single-turn and multi-turn code generation settings. The results are in Table 1.

4.1 **Results of Single-turn Code Generation**

We compare *OpenCodeInterpreter*'s single-turn code generation performance against premier models such as CodeLlama-Python (Roziere et al., 2023), WizardCoder (Luo et al., 2023), Deepseek-Coder (Guo et al., 2024), GPT Turbo (OpenAI, 2022, 2023), CodeT5+ (Wang et al., 2023c). Leveraging data from the EvalPlus leaderboard as of February 10th, 2024, we examine *OpenCodeInterpreter*'s achievements on the HumanEval and MBPP benchmarks, as well as their advanced versions, HumanEval+ and MBPP+. For a clear comparison, the results of different scales are compiled into a single table.

Our experimental analysis reveals *OpenCodeInterpreter*'s strong performance, with several configurations matching or surpassing leading benchmarks. The *OpenCodeInterpreter*-DS 33B variant achieves the highest scores among open-source models. This accomplishment is remarkable, especially considering the significant presence of lowquality or incorrect data in the initial training set.

4.2 Results of Multi-turn Code Generation

This section evaluates the proficiency of *Open-CodeInterpreter* in multi-turn interactions through iterative refinement, leveraging interpreter diagnostics and human insights.

Our experimental evaluation imposes a tworound limit on iterations to maintain fairness and consistency across tasks. While some issues may benefit from multiple refinements, others require fewer. This limitation offers clear insights into the model's iterative capabilities. In the execution feedback scenario, our models across all scales exhibited superiority over state-of-the-art (SOTA) benchmarks, with the *OpenCodeInterpreter* 33B model achieving parity with GPT-4 Turbo's single-round score, thus establishing a new SOTA benchmark among the evaluated code models.

Due to budget constraints, our Human Feedback and Human Feedback (Oracle) assessments concentrate on the *OpenCodeInterpreter* 6.7B and *Open-CodeInterpreter* 33B models. The outcomes reveal that with Human Feedback, the *OpenCodeInterpreter* 6.7B model significantly outperformed GPT-4 Turbo's single-round score, while in the Human Feedback (Oracle) scenario, the *OpenCodeInterpreter* 33B model's average score notably exceeded the 90 benchmark in the HumanEval/MBPP benchmarks. These results highlight the signifi-

Ratio	E.F	HumanEval (+)	MBPP (+)	Average (+)
2:1	×	76.2 (72.0) 81.1 (78.7)	73.9 (63.7) 82.7 (72.4)	75.1 (67.9) 81.9 (75.6)
1:1	×	77.3 (72.6) 78.0 (72.6)	74.6 (62.6) 78.4 (65.9)	76.0 (67.6) 78.2 (69.3)
1:2	×	75.7 (71.9) 78.7 (75.6)	72.9 (62.9) 77.9 (65.9)	74.3 (67.4) 78.3 (70.8)
1:3	× •	76.2 (72.0) 78.0 (75.0)	75.4 (65.4) 79.2 (69.9)	75.8 (68.7) 78.6 (72.5)
1:5	×	70.7 (67.0) 75.6 (70.7)	73.4 (63.1) 79.2 (67.9)	72.1 (65.1) 77.4 (69.3)
0:1	×	73.8 (68.9) 76.2 (71.3)	73.9 (62.9) 66.7 (76.6)	73.9 (65.9) 71.5 (74.0)

Table 2: Performance of *OpenCodeInterpreter* with data mixed ratios of single round data and Code-Feedback. "E.F" indicates the use of execution feedback.

cant role of iterative feedback and refinement in advancing code generation models, establishing *OpenCodeInterpreter* as a leader in software development tools. Through this refined approach, *OpenCodeInterpreter* not only demonstrates its remarkable adaptability and code refinement based on diverse feedback but also sets a new benchmark for future code generation technologies.

4.3 Ablations of Data Sources

410

411

412

413

414

415

416

417

418

419

420

421

422

423

424

425

426

427

428

429

430

431

432

433

434

435

436

437

438

439

440

441

442

443

444

This section systematically explores the impact of various data sources on the performance of *Open-CodeInterpreter*. We conduct a series of ablation studies to evaluate the influence of high-quality single-turn data and diverse multi-turn feedback mechanisms on the model's code generation, debugging, and refinement capabilities.

Impact of High-Quality Single-Turn Data. To evaluate the effect of high-quality single-turn data on *OpenCodeInterpreter*'s efficacy, we incorporate the WizardCoder 110K dataset, renowned for its syntactic accuracy and logical coherence, into our extensive multi-turn dataset. This integration seeks to identify the optimal mix of precise, single-turn code generation and the advanced, iterative refinement enabled by multi-turn interactions.

Our experiments employ a soft-target fine-tuning strategy across six configurations, varying the proportion of WizardCoder 110K data in our multiturn dataset. These configurations span from full incorporation to total exclusion of the WizardCoder dataset, assessing the performance of the model in two versions: DeepSeekCoder-Base-6.7B and DeepSeekCoder-Base-33B.

Our findings are illustrated in Table 1. It shows that *incorporating high-quality single-turn data*

Datasets	E.F	Average (+)
Single-turn Packing	×	75.0 (66.9) 77.5 (69.5)
Interaction Simulation	×	75.1 (66.9) 78.5 (69.6)
Single-turn Packing + Interaction Simulation	×	74.7 (66.5) 78.2 (70.1)
Single-turn Packing + Interaction Simulation + Code Correction	×	75.2 (65.4) 79.1 (71.3)
Code-Feedback (Full)	×	75.1 (67.9) 81.9 (75.6)

Table 3: Performance comparison of the model across different settings with incremental data source integration. "E.F" indicates the use of execution feedback.

445

446

447

448

449

450

451

452

453

454

455

456

457

458

459

460

461

462

463

464

465

466

467

468

469

470

471

472

473

474

475

476

477

478

479

(e.g., WizardCoder dataset) significantly improves our model's multi-turn performance. This strategic incorporation ensures that the model benefits from the syntactic accuracy and logical coherence inherent in single-turn tasks, thereby enriching its capacity for nuanced, iterative refinement in subsequent turns. It reveals the critical role of high-quality single-turn inputs in setting the stage for more effective multi-turn code generation and refinement. Benefits of Diverse Multi-Turn Data Sources. Following the enhanced baseline established by fully integrating the WizardCoder dataset, this subsection investigates the advantages of different data sources on the model's refinement and debugging efficacy. We add diverse data sources to our training regimen, including Single-turn Packing, Interaction Simulation, and Code Correction Data, both individually and in combination.

The use of these multi-turn data sources, including Single-turn Packing, Interaction Simulation, and Code Correction Data, individually and in combination, demonstrably enhances *OpenCodeInterpreter* 's debugging and refinement functions. Notably, the inclusion of Code Correction Data significantly elevates the model's efficiency in correcting errors. This underscores the profound impact of a varied and targeted training approach on advancing the capabilities of sophisticated code generation models. Such an approach enables these models to more effectively address complex coding challenges, correct errors, and refine outputs via extensive feedback mechanisms.

4.4 Case Study: Coding Queries in the Wild

This section delves into three distinct case studies to demonstrate *OpenCodeInterpreter*'s operational

482

483

484

485

486

487

488

489

490

491

492

493

494

495

496

497

498

499

500

502

507

508

509

510

511

512

513

514

515

516

517

518

521

523

525

529

dynamics when faced with "wild" user queries. The motivation behind these case studies is to showcase the practical applications of *OpenCodeInterpreter*.

In a notable success story (Figure A8), we tasked *OpenCodeInterpreter* with developing a function to calculate all prime numbers within the 1-100 range, later extending the solution to any arbitrary range x-y. Another commendable instance (Figure A9) involved *OpenCodeInterpreter* implementing a Python function to validate IPv6 addresses using regular expressions. Demonstrating its capability to iteratively refine its approach, *OpenCodeInterpreter* not only identified and corrected errors but also enhanced the solution based on human feedback. These two cases exemplify *OpenCodeInterpreter*'s strength in understanding mathematical logic and dynamically adjusting algorithms to meet specified criteria.

A challenging case (Figure A10) arose when *OpenCodeInterpreter* was asked to design a function identifying the intersection of two input lists, returning tuples of distinct elements present in both lists alongside their occurrence frequencies. Despite *OpenCodeInterpreter*'s attempts at correction, it addressed errors incrementally, ultimately exceeding the maximum number of attempts (three). This case sheds light on *OpenCodeInterpreter*'s limitations in simultaneously tackling multiple challenging errors.

Through these case studies, we gain invaluable insights into *OpenCodeInterpreter*'s capabilities and limitations. These insights are crucial for guiding future enhancements to *OpenCodeInterpreter*.

5 Related Work

LLMs for Code. It becomes a common practice to include code data for pre-training LLMs. For example, 5% of PaLM's (Chowdhery et al., 2023) pre-training data is code, and this ratio for LaMDA (Thoppilan et al., 2022), Galactica (Taylor et al., 2022), LLaMA (Touvron et al., 2023), Gopher (Rae et al., 2021), GPT-NeoX (Black et al., 2022) is 13%, 7%, 5%, 3%, and 8%, respectively.

Additionally, specialized LLMs have been pretrained for generating code, e.g., CodeGen (Nijkamp et al., 2022), PanGu-Coder (Christopoulou et al., 2022), CodeGeeX (Zheng et al., 2023), CodeFuse (Di et al., 2023), CodeT5+ (Wang et al., 2023d), AlphaCode (Li et al., 2022), In-Coder (Fried et al., 2022), StarCoder (Li et al., 2023a), DeepSeek-Coder (Guo et al., 2024). On the other hand, code LLMs can be fine-tuned from general-purpose LLMs, e.g., CodeLlama (Roziere et al., 2023), WizardCoder (Luo et al., 2023), which is the approach we take here. Compared to specialized LLMs, the fine-tuning paradigm enables us to explore ways to improve code generation capabilities by leveraging pre-trained general-purpose LLMs, especially because these LLMs have already been trained on an extensive amount of code data.

530

531

532

533

534

535

536

537

538

539

540

541

542

543

544

545

546

547

548

549

550

551

552

553

554

555

556

557

558

559

560

561

562

563

564

565

566

567

568

569

570

571

572

573

574

575

576

577

578

Iterative Code Generation and Refinement. For many sequence generation tasks, iterative approaches are often taken to improve the generation quality, e.g., script generation (Tandon et al., 2021), summarization (Scheurer et al., 2022), and other tasks as shown in (Madaan et al., 2022; Saunders et al., 2022). Notably, in Self-Refine (Madaan et al., 2023), an LLM generates feedback after generating initial outputs, and the LLM iteratively updates the outputs with the feedback. Whereas it focuses on a general-purpose LLM setting, we focus on code generation tasks. As for code generation with LLMs, DebugBench (Tian et al., 2024) observes that incorporating runtime feedback improves code LLMs' debugging performance. A most recent and relevant work is StepCoder (Dou et al., 2024), where, following the paradigm of relying on reinforcement learning with compiler feedback (Le et al., 2022; Shojaee et al., 2023), the authors further divide the original exploration problems into a sequence of easier sub-tasks. However, our approach does not rely on reinforcement learning and has access to the intermediate generation, which makes the training easier and more stable.

6 Conclusion

In conclusion, *OpenCodeInterpreter* represents a significant leap forward in the field of code generation, bridging the previously identified gap between open-source models and the advanced capabilities of proprietary systems like the GPT-4 Code Interpreter. By integrating compiler diagnostics and human feedback into an iterative refinement process, *OpenCodeInterpreter* not only surpasses traditional one-off generation approaches but also introduces a level of adaptability and precision previously unseen in open-source models. The introduction of Code-Feedback, with its extensive multi-turn interactions, further empowers *OpenCodeInterpreter* to dynamically refine code in response to evolving user intents and complex coding tasks.

Ethics Statement

The development and deployment of OpenCodeInterpreter, alongside the use of Code-Feedback, take 581 ethical considerations to ensure responsible usage. 582 We have made efforts to ensure that the dataset rep-583 resents a diverse range of coding styles, problem domains, and user scenarios to prevent the propaga-585 tion of biased or unfair outcomes. Given that Open-CodeInterpreter can generate and refine code based on user inputs, we strictly check out the dataset to ensure that it does not expose sensitive information or create security vulnerabilities. OpenCodeInterpreter has the potential to democratize coding by lowering the barrier to entry for non-experts and developers. We open-source all our code, models, and datasets to maximize accessibility. 594

Limitations

While OpenCodeInterpreter introduces significant advancements in automated code generation, it is 597 important to acknowledge the limitations inherent in the system and the Code-Feedback that supports it. Although OpenCodeInterpreter is designed to support multi-language code generation and understand a wide range of programming contexts, its performance may vary across different languages and specific domains. While OpenCodeInterpreter excels at interpreting and responding to a variety of coding tasks, it may struggle with extremely complex or ambiguous user intents. The ability to accurately capture and address such intents is limited by the model's current understanding and the specificity of the data in Code-Feedback.

References

612

613

617 618

619

620

621

624

- Jacob Austin, Augustus Odena, Maxwell Nye, Maarten Bosma, Henryk Michalewski, David Dohan, Ellen Jiang, Carrie Cai, Michael Terry, Quoc Le, et al. 2021. Program synthesis with large language models. *ArXiv preprint*, abs/2108.07732.
- Jinze Bai, Shuai Bai, Yunfei Chu, Zeyu Cui, Kai Dang, Xiaodong Deng, Yang Fan, Wenbin Ge, Yu Han, Fei Huang, et al. 2023. Qwen technical report. *ArXiv preprint*, abs/2309.16609.
- Sidney Black, Stella Biderman, Eric Hallahan, Quentin Anthony, Leo Gao, Laurence Golding, Horace He, Connor Leahy, Kyle McDonell, Jason Phang, Michael Pieler, Usvsn Sai Prashanth, Shivanshu Purohit, Laria Reynolds, Jonathan Tow, Ben Wang, and Samuel Weinbach. 2022. GPT-NeoX-20B: An opensource autoregressive language model. In *Proceedings of BigScience Episode #5 – Workshop on Chal-*

lenges & Perspectives in Creating Large Language Models, pages 95–136, virtual+Dublin. Association for Computational Linguistics. 629

630

631

632

633

634

635

636

637

638

639

640

641

642

643

644

645

646

647

648

649

650

651

652

653

654

655

656

657

658

659

660

661

662

663

664

665

666

667

668

669

670

671

672

673

674

675

676

677

678

679

680

681

682

- Sahil Chaudhary. 2023. Code Alpaca: An instruction-following llama model for code generation. https://github.com/sahil280114/ codealpaca. Accessed: 2024-02-13.
- Mark Chen, Jerry Tworek, Heewoo Jun, Qiming Yuan, Henrique Ponde de Oliveira Pinto, Jared Kaplan, Harri Edwards, Yuri Burda, Nicholas Joseph, Greg Brockman, et al. 2021. Evaluating large language models trained on code. *ArXiv preprint*, abs/2107.03374.
- Xinyun Chen, Maxwell Lin, Nathanael Schärli, and Denny Zhou. 2023. Teaching large language models to self-debug. *ArXiv preprint*, abs/2304.05128.
- Aakanksha Chowdhery, Sharan Narang, Jacob Devlin, Maarten Bosma, Gaurav Mishra, Adam Roberts, Paul Barham, Hyung Won Chung, Charles Sutton, Sebastian Gehrmann, et al. 2023. Palm: Scaling language modeling with pathways. *Journal of Machine Learning Research*, 24(240):1–113.
- Fenia Christopoulou, Gerasimos Lampouras, Milan Gritta, Guchun Zhang, Yinpeng Guo, Zhongqi Li, Qi Zhang, Meng Xiao, Bo Shen, Lin Li, et al. 2022. Pangu-coder: Program synthesis with function-level language modeling. *ArXiv preprint*, abs/2207.11280.
- Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. 2019. BERT: Pre-training of deep bidirectional transformers for language understanding. In Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers), pages 4171–4186, Minneapolis, Minnesota. Association for Computational Linguistics.
- Peng Di, Jianguo Li, Hang Yu, Wei Jiang, Wenting Cai, Yang Cao, Chaoyu Chen, Dajun Chen, Hongwei Chen, Liang Chen, et al. 2023. Codefuse-13b: A pretrained multi-lingual code large language model. *ArXiv preprint*, abs/2310.06266.
- Shihan Dou, Yan Liu, Haoxiang Jia, Limao Xiong, Enyu Zhou, Junjie Shan, Caishuang Huang, Wei Shen, Xiaoran Fan, Zhiheng Xi, et al. 2024. Stepcoder: Improve code generation with reinforcement learning from compiler feedback. *ArXiv preprint*, abs/2402.01391.
- Daniel Fried, Armen Aghajanyan, Jessy Lin, Sida Wang, Eric Wallace, Freda Shi, Ruiqi Zhong, Wen-tau Yih, Luke Zettlemoyer, and Mike Lewis. 2022. Incoder: A generative model for code infilling and synthesis. *ArXiv preprint*, abs/2204.05999.
- GitHub. 2023. Github copilot. https://github. com/features/copilot. Accessed: 2024-02-14.

- Gemini Google, Rohan Anil, Sebastian Borgeaud, Yonghui Wu, Jean-Baptiste Alayrac, Jiahui Yu, Radu Soricut, Johan Schalkwyk, Andrew M Dai, Anja Hauth, et al. 2023. Gemini: a family of highly capable multimodal models. *ArXiv preprint*, abs/2312.11805.
 - Daya Guo, Qihao Zhu, Dejian Yang, Zhenda Xie, Kai Dong, Wentao Zhang, Guanting Chen, Xiao Bi, Y Wu, YK Li, et al. 2024. Deepseek-coder: When the large language model meets programming–the rise of code intelligence. *ArXiv preprint*, abs/2401.14196.
- Albert Q Jiang, Alexandre Sablayrolles, Arthur Mensch, Chris Bamford, Devendra Singh Chaplot, Diego de las Casas, Florian Bressand, Gianna Lengyel, Guillaume Lample, Lucile Saulnier, et al. 2023. Mistral 7b. ArXiv preprint, abs/2310.06825.

700

701

703

704

710

711

712

713

714

716

719

721

723

725

726

727

728

729

730

731

732

734

737

738

739

- Hung Le, Yue Wang, Akhilesh Deepak Gotmare, Silvio Savarese, and Steven Chu Hong Hoi. 2022. Coderl: Mastering code generation through pretrained models and deep reinforcement learning. *Advances in Neural Information Processing Systems*, 35:21314–21328.
- Raymond Li, Loubna Ben Allal, Yangtian Zi, Niklas Muennighoff, Denis Kocetkov, Chenghao Mou, Marc Marone, Christopher Akiki, Jia Li, Jenny Chim, et al. 2023a. Starcoder: may the source be with you! *ArXiv preprint*, abs/2305.06161.
- Rongao Li, Jie Fu, Bo-Wen Zhang, Tao Huang, Zhihong Sun, Chen Lyu, Guang Liu, Zhi Jin, and Ge Li. 2023b.
 Taco: Topics in algorithmic code generation dataset. *ArXiv preprint*, abs/2312.14852.
- Yujia Li, David Choi, Junyoung Chung, Nate Kushman, Julian Schrittwieser, Rémi Leblond, Tom Eccles, James Keeling, Felix Gimeno, Agustin Dal Lago, et al. 2022. Competition-level code generation with alphacode. *Science*, 378(6624):1092–1097.
- Jiawei Liu, Chunqiu Steven Xia, Yuyao Wang, and LINGMING ZHANG. 2023. Is your code generated by chatGPT really correct? rigorous evaluation of large language models for code generation. In *Thirty-seventh Conference on Neural Information Processing Systems.*
- Ziyang Luo, Can Xu, Pu Zhao, Qingfeng Sun, Xiubo Geng, Wenxiang Hu, Chongyang Tao, Jing Ma, Qingwei Lin, and Daxin Jiang. 2023. Wizardcoder: Empowering code large language models with evolinstruct. ArXiv preprint, abs/2306.08568.
- Aman Madaan, Niket Tandon, Peter Clark, and Yiming Yang. 2022. Memory-assisted prompt editing to improve GPT-3 after deployment. In Proceedings of the 2022 Conference on Empirical Methods in Natural Language Processing, pages 2833–2861, Abu Dhabi, United Arab Emirates. Association for Computational Linguistics.
- Aman Madaan, Niket Tandon, Prakhar Gupta, Skyler Hallinan, Luyu Gao, Sarah Wiegreffe, Uri Alon, Nouha Dziri, Shrimai Prabhumoye, Yiming Yang,

et al. 2023. Self-refine: Iterative refinement with self-feedback. *ArXiv preprint*, abs/2303.17651.

740

741

742

743

745

746

747

748

749

750

751

752

753

754

755

756

757

758

759

760

761

762

763

764

765

766

767

768

769

770

771

772

773

774

775

776

778

780

781

782

783

784

785

786

787

789

- Erik Nijkamp, Bo Pang, Hiroaki Hayashi, Lifu Tu, Huan Wang, Yingbo Zhou, Silvio Savarese, and Caiming Xiong. 2022. Codegen: An open large language model for code with multi-turn program synthesis. *ArXiv preprint*, abs/2203.13474.
- OpenAI. 2022. ChatGPT: Optimizing Language Models for Dialogue. https://openai.com/ blog/chatgpt/. Accessed on 14 Feb. 2024.
- OpenAI. 2023. Gpt-4 technical report.
- Phind. 2023. Phind/phind-codellama-34b-v2.
- Jack W Rae, Sebastian Borgeaud, Trevor Cai, Katie Millican, Jordan Hoffmann, Francis Song, John Aslanides, Sarah Henderson, Roman Ring, Susannah Young, et al. 2021. Scaling language models: Methods, analysis & insights from training gopher. *ArXiv preprint*, abs/2112.11446.
- Baptiste Roziere, Jonas Gehring, Fabian Gloeckle, Sten Sootla, Itai Gat, Xiaoqing Ellen Tan, Yossi Adi, Jingyu Liu, Tal Remez, Jérémy Rapin, et al. 2023. Code llama: Open foundation models for code. *ArXiv preprint*, abs/2308.12950.
- William Saunders, Catherine Yeh, Jeff Wu, Steven Bills, Long Ouyang, Jonathan Ward, and Jan Leike. 2022. Self-critiquing models for assisting human evaluators. *ArXiv preprint*, abs/2206.05802.
- Jérémy Scheurer, Jon Ander Campos, Jun Shern Chan, Angelica Chen, Kyunghyun Cho, and Ethan Perez. 2022. Training language models with natural language feedback. *ArXiv preprint*, abs/2204.14146.
- Weijia Shi, Sewon Min, Maria Lomeli, Chunting Zhou, Margaret Li, Victoria Lin, Noah A Smith, Luke Zettlemoyer, Scott Yih, and Mike Lewis. 2023. Incontext pretraining: Language modeling beyond document boundaries. ArXiv preprint, abs/2310.10638.
- Parshin Shojaee, Aneesh Jain, Sindhu Tipirneni, and Chandan K Reddy. 2023. Execution-based code generation using deep reinforcement learning. *ArXiv preprint*, abs/2301.13816.

speechless. 2023. speechless-codellama-34b-v2.0.

- Niket Tandon, Aman Madaan, Peter Clark, Keisuke Sakaguchi, and Yiming Yang. 2021. Interscript: A dataset for interactive learning of scripts through error feedback. *ArXiv preprint*, abs/2112.07867.
- Ross Taylor, Marcin Kardas, Guillem Cucurull, Thomas Scialom, Anthony Hartshorn, Elvis Saravia, Andrew Poulton, Viktor Kerkez, and Robert Stojnic. 2022. Galactica: A large language model for science. *ArXiv preprint*, abs/2211.09085.

Romal Thoppilan, Daniel De Freitas, Jamie Hall, Noam Shazeer, Apoorv Kulshreshtha, Heng-Tze Cheng, Alicia Jin, Taylor Bos, Leslie Baker, Yu Du, et al. 2022. Lamda: Language models for dialog applications. ArXiv preprint, abs/2201.08239.

790

791

793

795

804

805 806

807

810

811

812 813

814

815

816

817

818

819

820 821

824

837

839

- Runchu Tian, Yining Ye, Yujia Qin, Xin Cong, Yankai Lin, Zhiyuan Liu, and Maosong Sun. 2024. Debugbench: Evaluating debugging capability of large language models. *ArXiv preprint*, abs/2401.04621.
- Hugo Touvron, Thibaut Lavril, Gautier Izacard, Xavier Martinet, Marie-Anne Lachaux, Timothée Lacroix, Baptiste Rozière, Naman Goyal, Eric Hambro, Faisal Azhar, et al. 2023. Llama: Open and efficient foundation language models. *ArXiv preprint*, abs/2302.13971.
- Guan Wang, Sijie Cheng, Xianyuan Zhan, Xiangang Li, Sen Song, and Yang Liu. 2023a. Openchat: Advancing open-source language models with mixed-quality data. *ArXiv preprint*, abs/2309.11235.
- Yizhong Wang, Yeganeh Kordi, Swaroop Mishra, Alisa Liu, Noah A. Smith, Daniel Khashabi, and Hannaneh Hajishirzi. 2023b. Self-instruct: Aligning language models with self-generated instructions. In Proceedings of the 61st Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers), ACL 2023, Toronto, Canada, July 9-14, 2023, pages 13484–13508.
- Yue Wang, Hung Le, Akhilesh Deepak Gotmare, Nghi DQ Bui, Junnan Li, and Steven CH Hoi. 2023c. Codet5+: Open code large language models for code understanding and generation. *ArXiv preprint*, abs/2305.07922.
- Yue Wang, Hung Le, Akhilesh Deepak Gotmare, Nghi DQ Bui, Junnan Li, and Steven CH Hoi. 2023d. Codet5+: Open code large language models for code understanding and generation. *ArXiv preprint*, abs/2305.07922.
- Yuxiang Wei, Zhe Wang, Jiawei Liu, Yifeng Ding, and Lingming Zhang. 2023. Magicoder: Source code is all you need. *ArXiv preprint*, abs/2312.02120.
- Xwin-LM. 2023. Xwin-lm.
 - Zhaojian Yu, Xin Zhang, Ning Shang, Yangyu Huang, Can Xu, Yishujie Zhao, Wenxiang Hu, and Qiufeng Yin. 2023. Wavecoder: Widespread and versatile enhanced instruction tuning with refined data generation. ArXiv preprint, abs/2312.14187.
 - Qinkai Zheng, Xiao Xia, Xu Zou, Yuxiao Dong, Shan Wang, Yufei Xue, Zihan Wang, Lei Shen, Andi Wang, Yang Li, et al. 2023. Codegeex: A pre-trained model for code generation with multilingual evaluations on humaneval-x. *ArXiv preprint*, abs/2303.17568.

A Source Data Filtering

841 842

Here, we outline the prompts used for source data filtering.

Query Filtering Prompt 1

Rate the following code queries on a scale of 1 to 5 based on their complexity, where 1 is the easiest and 5 is the most difficult. Consider the complexity of the query

Query: [{query}]

You are obliged to choose only from the following list.

Scoring Criteria:

1 Point - Very Basic: The query involves simple operations or common issues

2 Points - Basic: The query involves fundamental programming concepts or commonly used functions

3 Points - Intermediate: The query requires some programming experience, possibly involving multiple steps

4 Points - Difficult: The query involves advanced programming skills, including complex logic, algorithms, or data structures

5 Points - Very Difficult: The query requires extensive expertise, potentially involving innovative problem-solving approaches or unique algorithm design

Please give the score first then explain why

843

Query Filtering Prompt 2

Rate the following code queries on a scale of 1 to 5 based on their complexity, where 1 is the easiest and 5 is the most difficult. Consider the complexity of the query

Query: [{query}]

You are obliged to choose only from the following list.

Scoring Criteria:

1 Point - Moderately Difficult: Involves understanding specific programming concepts or libraries, and may include medium complexity algorithms or data structures like basic sorting algorithms or tree structures.

2 Points - Challenging: Requires handling more complex logic or algorithms such as advanced sorting algorithms, recursive logic, or intermediate data structures like hash tables and heaps.

3 Points - Highly Challenging: Demands deeper knowledge in algorithms and data structures, potentially including graph algorithms, dynamic programming, or complex string manipulation techniques.

4 Points - Advanced: Focuses on proficiency in programming and algorithm design, dealing with complex system architecture issues, performance optimization, or solving advanced algorithmic challenges like NP-hard problems. 5 Points - Expert Level: The highest difficulty level, requiring innovative problem-solving approaches or unique algorithm design, possibly involving interdisciplinary knowledge or the application of cutting-edge technologies.

Please give the score first then explain why

Below is an overview of the data filtering process applied to the initial seed dataset, with Figure A1 summarizing the data quantity after each filtering stage.



845

Figure A1: Overview of Data Filtering Process and Corresponding Data Quantities

The pie chart in Figure A2 illustrates the distribution of programming languages in our dataset after849filtering.850



Figure A2: Distribution of Programming Languages in Filtered Dataset

B Simulating Interactions for Data Collection

We illustrate the prompts used in multi-turn execution feedback and multi-turn human feedback respectively.

System prompt for multi-turn execution feedback

You are an AI code interpreter.

Your goal is to help users do a variety of jobs by executing Python code.

You should:

- 1. Comprehend the user's requirements carefully & to the letter.
- 2. Give a brief description for what you plan to do & call the provided function to run code.
- 3. Provide results analysis based on the execution output.
- 4. If error occurred, try to fix it.
- 5. Response in the same language as the user.

System prompt for multi-turn human feedback

You are a user who gives feedback to the latest generated code. If no available code is found in the conversation, you should give a feedback to encourage assistant to generate code. NOTE: your feedback should be WITHIN 2 SHORT SENTENCES.

You can refer to the following types of feedback:

1. **Syntax and Formatting**: Checking for syntax errors, inconsistent formatting, and suggesting adherence to standard coding styles for readability and maintainability.

2. **Efficiency**: Identifying parts of the code that can be optimized for better performance, such as reducing time complexity, optimizing loops, or suggesting more efficient data structures.

3. **Functionality Enhancements**: Suggesting additional features or enhancements that could make the code more functional or user-friendly.

4. **Code Clarity and Documentation**: Recommending improvements in code comments and documentation to make the code more understandable and easier to maintain.

5. **Bug Identification**: Pointing out any potential bugs or logical errors in the code and suggesting ways to fix them. 6. **Security Improvements**: Highlighting any security vulnerabilities in the code and suggesting best practices to enhance security.

7. ******Compatibility and Testing******: Advising on making the code more compatible with different environments or platforms and suggesting more comprehensive testing scenarios.

8. **Resource Optimization**: Identifying areas where the code might be using more resources than necessary (like memory or CPU) and suggesting optimizations.

9. **Scalability**: Providing insights on how the code can be made more scalable to handle larger data sets or more users.

10. **Adherence to Best Practices**: Ensuring the code follows the best practices specific to the language or framework being used.

Your output MUST be in a json format like this:

{
"satisfied": "The points that have been achieved in generated code",

"not_satisfied": "The points that have not yet been achieved in generated code",

"feedback": "The actual feedback. Your feedback should be WITHIN 2 SHORT SENTENCES. Feedback must come from a point included in 'not_satisfied' field. You can ask the assistant here to generate code if no available code is found in previous conversations."

856

852

System prompt for deliberately generating incorrect code

You are an AI code interpreter.

Your goal is to generate and execute Python code.

Your code MUST contain at least one of the following types of errors:

1. Syntax Error: This type of error occurs when the code violates the grammar rules of the programming language. For example, forgetting to close a parenthesis or a quotation mark, or misspelling a keyword.

2. Logical Error: These errors sneak into your code when there's a misunderstanding of the problem you're solving, leading to incorrect results despite the code running without crashing. For example, calculating the average of a list of numbers by summing them up but forgetting to divide by the count of the numbers.

3. Type Error: This error occurs when an operation is applied to an object of an inappropriate type. For example, attempting to concatenate a string with an integer without converting the integer to a string first.

4. Name Error: This happens when the code attempts to reference a variable or a function name that hasn't been defined. For example, trying to print a variable that hasn't been declared.

5. Timeout Error: This error occurs when your code gets stuck in a loop that never ends, either due to a logic flaw or a condition that never becomes false. In programming, such an error can cause your application to hang indefinitely, consuming resources and potentially leading to a crash if not handled properly. For example, writing a loop that waits for a certain condition to change, but the condition is never updated within the loop.

NOTE:

1. You MUST make mistakes in the generated code!

2. Do not explain the errors within. Just write your thoughts and code as normal.

3. Do not tell me you are writing the wrong code in any form (e.g., in text/code/comments). Just pretend you are writing the correct code and still not recognizing the errors.

C Natural Language Explanations Generation

We use the following prompt to generate explanations for code using GPT-4.

Prompt for generating natural language explanations using GPT-4

Here is a list containing a series of dialogues between a user and a programmer assistant.

Following the previous dialogues, the user posed a latest problem.

The assistant has now crafted the correct code based on the previous dialogues and the latest problem.

Assuming you are this programmer assistant, please add some text before the code.

The purpose of this text is to respond to the latest problem and to introduce the code that follows.

This text may include: language used in the code, algorithm used in the code, step-by-step implementation overview, and other relevant content.

You may use phrases like "The following code", "My code", "My solution", to refer to the @@Code.

Your response should ONLY contain the text that you add before the code.

Your only task is to write the text, never modify the code or remind me something. Never restate the previous dialogues and the problem.

@ @ Previous Dialogues
{previous dialogues}

@@Recent Problem:
{recent problem}

Add the text there. @@Code: {code}

D Model Evaluation Prompts

For different benchmarks, distinct prompts were employed during the initial turn of solution generation: identical prompts were utilized for HUMANEVAL and HUMANEVAL+, while MBPP and MBPP+ shared a similar prompt. The prompts are illustrated in the below.

Prompt for HumanEval and HumanEval+

You are an exceptionally intelligent coding assistant that consistently delivers accurate and reliable responses to user instructions.

@ @ Instruction Here is the given code to do completion: "`{language} {original prompt}

Please continue to complete the function with {language} programming language. You are not allowed to modify the given code and do the completion only.

Please return all completed codes in one code block. This code block should be in the following format: ""{language} # Your codes here

865

861

864

Prompt for MBPP and MBPP+

You are an exceptionally intelligent coding assistant that consistently delivers accurate and reliable responses to user instructions.

@ @ Instruction
Here is the given problem and test examples:
{original prompt}

Please use the {language} programming language to solve this problem. Please make sure that your code includes the functions from the test samples and that the input and output formats of these functions match the test samples.

Please return all completed codes in one code block. This code block should be in the following format: "`{language} # Your codes here ".

@@ Response

@@ Response

We employ GPT models to emulate human behavior in generating feedback. The prompts provided to the GPT models are presented as follows.

Prompt for GPT models mimicking human feedback with canonical solution

You are tasked with providing guidance to a programmer who has drafted a code for a programming problem. Your role is to mimic human-like responses and offer suggestions for modifying the code based on the canonical solution and the observed execution results.

You should NOT directly revealing contents of the @@Canonical Solution or mentioning terms such as "canonical solution."

You should refrain from directly writing code.

Begin by thoroughly examining the existing code and its functionality.

Compare the @@Existing Code with the @@Canonical Solution provided. Note any discrepancies in logic, approach, or implementation.

Analyze the @@Execution Result obtained from running the @@Existing Code. Identify any errors, unexpected behavior, or deviations from the expected output.

Consider potential edge cases, optimization opportunities, or alternative approaches based on insights from both the @@Canonical Solution and @@Execution Result.

Offer guidance in a clear and understandable manner, explaining the rationale behind each suggestion.

Refrain from providing actual code solutions, but instead focus on conceptual modifications or strategies.

Provide constructive feedback to help the programmer improve their coding skills.

Remember, your role is to simulate human-like guidance and expertise in programming without directly implementing solutions.

Please respond in no more than three sentences.

@ @ Problem
{original prompt}

@@Existing Code
{sanitized code}

@@Execution Result
{execution result}

@@Canonical Solution
{canonical solution}

@@Guidance

Prompt for GPT models mimicking human feedback without canonical solution

You are tasked with providing guidance to a programmer who has drafted a code for a programming problem. Your role is to mimic human-like responses and offer suggestions for modifying the code based on the observed execution results.

You should refrain from directly writing code.

Begin by thoroughly examining the existing code and its functionality.

Analyze the @@Execution Result obtained from running the @@Existing Code. Identify any errors, unexpected behavior, or deviations from the expected output.

Consider potential edge cases, optimization opportunities, or alternative approaches based on insights from the @@Execution Result.

Offer guidance in a clear and understandable manner, explaining the rationale behind each suggestion.

Refrain from providing actual code solutions, but instead focus on conceptual modifications or strategies.

Provide constructive feedback to help the programmer improve their coding skills.

Remember, your role is to simulate human-like guidance and expertise in programming without directly implementing solutions.

Please respond in no more than three sentences.

@@Problem
{original prompt}

@@Existing Code
{sanitized code}

@@Execution Result
{execution result}

@ @Guidance

Ε **Examples of Methods used in Data Collection**

Here we listed examples of each method in data collection process, including similar query packing, human feedback simulation and code correction for coding queries from open-source data (Section 2.1), and similar problem packing and follow-up Q&A for coding challenges from LeetCode (Section 2.2).

```
User:
You are tasked with creating a Python script that will search for specific files within a given directory and its subdirectories. Your script should be
able to identify files with a particular file extension and return a list of these files. Additionally, the script should be able to handle cases where the
specified directory does not exist or is empty.
Write a function `find files(directory, extension)` that takes in two parameters:
- 'directory': A string representing the directory path to search for files.
- 'extension': A string representing the file extension to search for (e.g., ".txt", ".csv", ".py").
The function should return a list of file paths that have the specified file extension within the given directory and its subdirectories. If the directory
does not exist or is empty, the function should return an empty list.
Example:
 ``python
print(find_files('/path/to/directory', '.txt'))
# Output: ['/path/to/directory/file1.txt', '/path/to/directory/subdirectory/file2.txt']
Assistant:
  ``pvthon
import os
def find files(directory, extension):
  file_list = []
  if os.path.exists(directory):
     for root, dirs, files in os.walk(directory):
        for file in files:
          if file.endswith(extension):
             file_list.append(os.path.join(root, file))
  return file list
User:
You are tasked with creating a Python function that processes a given directory and calculates the total size of all files within it. Additionally, the
function should exclude any files with a ".torrent" extension from the total size calculation. You are provided with a code snippet that demonstrates the
use of the 'os' module to join a path and a filename, as well as the use of a custom 'Torrent' class to read the total size of files in a torrent file.
Create a function `calculate_directory_size` that takes a directory path as input and returns the total size of all files within the directory, excluding any
files with a ".torrent" extension.
Example:
Given the directory structure:
my_directory/
  file1.txt
  file2.jpg
  file3.torren
The function call `calculate_directory_size('my_directory')` should return the total size of `file1.txt` and `file2.jpg` in bytes.
Assistant:
 ``python
import os
def calculate_directory_size(directory_path):
   total size = 0
   for dirpath, _, filenames in os.walk(directory_path):
     for filename in filenames:
        if not filename.endswith('.torrent'):
          file_path = os.path.join(dirpath, filename)
          total_size += os.path.getsize(file_path)
  return total size
The 'calculate_directory_size' function uses the 'os.walk' method to traverse the directory and its subdirectories, and iterates through the files within
each directory. For each file, it checks if the file does not have a ".torrent" extension and adds its size to the `total_size`. Finally, the function returns
the accumulated `total_size` of all non-torrent files within the directory.
```

Figure A3: An example of similar query packing for challenging query pools.

User:

Develop a program in Python to implement a Simple Linear Regression model.

Problem Statement

Write a Python program to implement a Simple Linear Regression model to predict the salary of employees based on their years of experience.

Instructions

1. The program should ask the user for the number of data points to be entered.

2. The program should then ask the user to enter the years of experience and the corresponding salary for each data point.

3. The program should calculate the slope and intercept of the

regression line using the least squares method.

4. The program should use the calculated slope and intercept to predict the salary for a given number of years of experience entered by the user.5. The program should display the regression line equation, the predicted salary, and a scatter plot of the data points and the regression line.

Constraints

- The number of data points should be a positive integer.

- The years of experience and salary should be non-negative integers.

- You may assume that the input will be valid and no error checking is required.

Assistant:

I have implemented the Python program to implement a Simple Linear Regression model based on the instructions provided. The program calculates the regression line slope and intercept using the least squares method and then predicts the salary for the given number of years of experience.

```python # Importing required libraries import numpy as np

# Simulating user input num\_points = 5 data\_points = [(2, 50000), (5, 80000), (10, 120000), (3, 60000), (8, 100000)] years\_to\_predict = 7

# Separating years of experience and salary X = np.array([x[0] for x in data\_points]) Y = np.array([x[1] for x in data\_points])

# Calculating the mean of X and y
mean\_x = np.mean(X)
mean\_y = np.mean(Y)

# Calculating the terms needed for the num and den of formula of slope (b1) and intercept (b0) m = len(X) numer = 0 denom = 0 for i in range(m): numer += (X[i] - mean\_x) \* (Y[i] - mean\_y) denom += (X[i] - mean\_x) \*\* 2 b1 = numer / denom # slope b0 = mean\_y - (b1 \* mean\_x) # intercept

# Displaying the regression line equation print('Regression line equation:  $y = \{:.2f\} + \{:.2f\}x'$ .format(b0, b1))

# Predicting the salary for the given number of years of experience predicted\_salary = b0 + b1 \* years\_to\_predict print('Predicted salary for {} years of experience: {:.2f}'.format(years\_to\_predict, predicted\_salary))

### User:

Execution result: Regression line equation: y = 34424.78 + 8495.58x Predicted salary for 7 years of experience: 93893.81

# (Continued)

Assistant:

The Python code provided uses the Simple Linear Regression model to predict the salary based on years of experience. The model was trained using 5 data points, each consisting of years of experience and corresponding salary.

The calculated regression line equation from the model is: y = 34424.78 + 8495.58x From this equation, the predicted salary for 7 years of experience is: 93893.81

A scatter plot was generated, which visually represents the data points and the predicted regression line. The red points represent the input data points, and the blue line represents the regression line or the salary prediction line.

This plot visually expresses how the model predicts salary based on years of experience. The closer these red points are to the blue line, the better the model is at predicting.

Please let me know if anything else is needed.

#### User:

Consider optimizing the loop for calculating the slope and intercept to enhance code efficiency. Please ensure consistent formatting for better readability.

### Assistant:

```python # Importing required libraries import numpy as np

Simulating user input num_points = 5 data_points = [(2, 50000), (5, 80000), (10, 120000), (3, 60000), (8, 100000)] years_to_predict = 7

Separating years of experience and salary X = np.array([x[0] for x in data_points]) Y = np.array([x[1] for x in data_points])

Calculating the slope and intercept of the regression line b1 = (np.sum((X - np.mean(X)) * (Y - np.mean(Y)))) / np.sum((X np.mean(X)) ** 2) b0 = np.mean(Y) - (b1 * np.mean(X))

Displaying the regression line equation print('Regression line equation: $y = \{:.2f\} + \{:.2f\}x'.format(b0, b1))$

Predicting the salary for the given number of years of experience predicted_salary = b0 + b1 * years_to_predict print(Predicted salary for {} years of experience: {:.2f}'.format(years_to_predict, predicted_salary))

User: Execution result:

Regression line equation: y = 34424.78 + 8495.58xPredicted salary for 7 years of experience: 93893.81

Assistant:

The Python program has been improved for better code efficiency and readability.

The loop for computing the slope (b1) and intercept (b0) of the regression line is eliminated and replaced with an optimized computation using numpy. This change enhances performance, especially when dealing with larger data sets.

The formatted regression line equation is: y = 34424.78 + 8495.58xThe predicted salary for 7 years of experience is: 93893.81

Please let me know if any further assistance is needed.

Figure A4: An example of human feedback simulation for challenging query pools.

(Continued) User: Here's a piece of Python code I got from an OCR scan. Can you help me User: Execution result: {'grades': ['A+', 'B', 'C-', 'C', 'A-'], 'average grade': 'B-', 'lowest grade': 4.0, 'highest grade': 1.7, 'letter count': {'A+': 1, clean it up? def s7udert_qrad€s(gpva1s, prev_9pva1s): if_len{gqu&ls) 1=13n(pr3v_qpvals): re7vrr "€rror:_Input ve<tor\$ are rOt t#e 5&m€ leng7h" lettens = {'At':o, 'A':0. '&-':0, '13+':0. 'B':0, 'B-':0, 'CT':O, 'C':o, '<=':0, 'A': 0, 'A-': 1, 'B+': 0, 'D':0, 'T':0] gr@des = [] 'B': 1, 'B-': 0, progress = ["impnOved":0, "maint&ined":0, "d€ciined":0} $t0 + al_{=} = 0$ B-:0, 'C+':0, 'C':1, 'C-':1, 'D':0, 'F':0}, d&f g3+_l&ten(gpa): if gpa > 4.0 or gqa < 0.0: neturm "3rrOr: Inualid GPA" elit qp& >= 3,85: 'progress': {'improved': 4, 'maintained': 1, 'declined': 0}} neturn 'At' Assistant: It looks like there was a mistake in the logic for determining the ellf qpa >= 3.65: elif qpa >= 3.65: return 'A' €lif g9a >= 3.S0: lowest_grade and highest_grade. The current approach mistakenly tries to use the get_letter function with the min and max functions, which neturn 'A=' does not work as intended because get letter is designed to return a letter grade based on a GPA value, not to compare GPA values directly. e|1f_gpa >= E.15: neturn 'B+' elif gpa_>= z.bs: neturn "B" Here's how to correctly calculate the lowest_grade and highest_grade: Calculate the lowest_grade and highest_grade based on GPA values directly, not through the get_letter function. This will give us the actual lowest and highest GPA values in the list.
 Correct the calculation to ensure it reflects the actual GPA values, are the instrument of the second secon elit gpa >= 2.50: return_'8-' elif $qq\bar{4} >= 2.15$: n€tvrn 'C+' not their letter grades. 3lif gpa >=_1.8s: n€turn '<' Let's correct the code: ellf 9pa >= 1.s0: "'python # Correct calculation for lowest and highest GPA values re+urm '<-' el!f gqa $\geq = 1.0$: re+unn 'D' def student_grades(gpvals, prev_gpvals): [truncated code] else: returm 'T' average_grade = get_letter(total_gpa / len(gpvals))
lowest_gpa = min(gpvals) # This will correctly identify the lowest
GPA value. 03f get progress(pr€v, curr): if prev < (urr: ne+urn "improved" highest_gpa = max(gpvals) # This will correctly identify the highest GPA value el!t qnev == curr # Then, if needed, you can get their corresponding letter grades lowest_grade_letter = get_letter(lowest_gpa) highest_grade_letter = get_letter(highest_gpa) re7urn "m&intaimed" els€: return "o€c1ineo" return 'grades': grades, 'average grade': average_grade, 'lowest grade': lowest_grade_letter, # Use letter grade for lowest for i in r@nge[len(gpvals)): |etter_gra03 - g€+_l€tten(gpvals[i]) grad3s.appemd(le+ter grade] GPA 1ett3rs[let7er_grade] += 1 'highest grade': highest_grade_letter, # Use letter grade for highest GPA 'letters_count': letters, 'progress': progress to7al += qpu&l\$[i] 9nogr3zs[g37 9nOqr35s(preu 9pvals[i], gpval5[i]} += 1 $\label{eq:starsest} \begin{array}{l} avera9e_gnad€ - get_|et+er(tota|/ler(gpu&l\$)) \\ lowest_grade = min(gpvais, k€y=qet_l37t3r\} \\ highezt_gn&d€ = nak(gpvals,_key=get_let+er) \end{array}$ # Example usage: gpvals = [4.0, 3, 1.7, 2, 3.5] prev_gpvals = [3.5, 3, 1.4, 1.8, 3.2] student_grades(gpvals, prev_gpvals) r€turn {'gnade\$':_gnades, '@v3na9e grade': &u3rage grade, 'lowest gnade':_lovvest_9na03, 'highest 9r@de': nighest 9rad€' 'l3tters_(0unt':_let7ers, 'progress': pnogress} User: Execution result: {'grades': ['A+', 'B', 'C-', 'C', 'A-'], 'average grade': 'B-', 'lowest grade': 'C-', # 3xampl3 vsage: gpuals_= (4.o, 3, 1.7, 2, 3.5] pnev_gpual5 - [E.5` 3` 1.4, 1.8, 3.2] 'highest grade': 'A+', 'letters_count': {'A+': 1, s7voent_9radez{gpvals,_prev_gpv&|s] 'A': 0. 'A': 0, 'A-': 1, 'B+': 0, 'B': 1, 'B-': 0, 'C+': 0, 'C': 1, 'C-': 1, 'D': 0, 'F': 0}, Assistant: `python def student_grades(gpvals, prev_gpvals): [truncated code] average_grade = get_letter(total/len(gpvals)) lowest_grade = min(gpvals, key=get_letter) highest_grade = max(gpvals, key=get_letter) 'progress': {'improved': 4, 'maintained': 1, 'declined': 0}} return {'grades': grades, 'average grade': average_grade, 'lowest grade': lowest_grade, 'highest grade': highest_grade, Assistant: With the corrected logic in place, the execution result now accurately reflects the grades distribution, progress, and identifies the lowest and highest grades based on the GPA values. 'letter count': letters, 'progress': progress} # Example usage: gpvals = [4.0, 3.0, 1.7, 2.0, 3.5] prev_gpvals = [3.5, 3.0, 1.4, 1.8, 3.2] student_grades(gpvals, prev_gpvals)

Figure A5: An example of code correction for challenging query pools.

User:

A city's **skyline** is the outer contour of the silhouette formed by all the buildings in that city when viewed from a distance. Given the locations and heights of all the buildings, return _the **skyline** formed by these buildings collectively .

The geometric information of each building is given in the array 'buildings' where 'buildings[i] = [lefti, righti, heighti]':

- * `lefti` is the x coordinate of the left edge of the `ith` building.
- 'righti' is the x coordinate of the right edge of the `ith' building.
 'heighti' is the height of the `ith' building.

You may assume all buildings are perfect rectangles grounded on an absolutely flat surface at height '0'.

The **skyline** should be represented as a list of "key points " **sorted by their x-coordinate** in the form `[[x1,y1],[x2,y2],...]`. Each key point is the left endpoint of some horizontal segment in the skyline except the last point in the list, which always has a ycoordinate `0` and is used to mark the skyline's termination where the rightmost building ends. Any ground between the leftmost and rightmost buildings should be part of the skyline's contour.

Note: There must be no consecutive horizontal lines of equal height in the output skyline. For instance, `[...,[2 3],[4 5],[7 5],[11 5],[12 7],...]` is not acceptable; the three lines of height 5 should be merged into one in the final output as such: `[...,[2 3],[4 5],[12 7],...]`

[Examples are truncated]

Constraints:

- * `1 <= buildings.length <= 104`
- * `0 <= lefti < righti <= 231 1`
- * `1 <= heighti <= 231 1`
- * `buildings` is sorted by `lefti` in non-decreasing order.

Assistant:

In the following code, we tackle the problem of computing a city skyline from a given set of buildings. Each building is defined by its x-coordinate boundaries and height, and our goal is to construct the contour of these buildings when collectively observed from a distance.

The algorithm used can be summarized in the following steps:

[Steps are truncated]

My solution is designed to handle the input efficiently and conforms to the problem's constraints regarding sorting and eliminating redundant horizontal lines. Let's proceed with the code that solves the skyline problem.

```python

from sortedcontainers import SortedList

```
def getSkyline(buildings):
  points = []
  for l, r, h in buildings:
     points.append((1, -h))
     points.append((r, h))
  points.sort()
  heights = SortedList([0])
  prev = 0
  skyline = []
  for x, h in points:
     if h < 0:
       heights.add(-h)
     else:
       heights.remove(h)
     cur = heights[-1]
     if cur != prev:
       skyline.append([x, cur])
       prev = cur
 return skyline
```

(Continued)

```
User:
```

There are several squares being dropped onto the X-axis of a 2D plane.

You are given a 2D integer array 'positions' where 'positions[i] = [lefti, sideLengthi]' represents the 'ith' square with a side length of 'sideLengthi' that is dropped with its left edge aligned with X-coordinate 'lefti'.

Each square is dropped one at a time from a height above any landed squares. It then falls downward (negative Y direction) until it either lands **on the top side of another square** or **on the X-axis**. A square brushing the left/right side of another square does not count as landing on it. Once it lands, it freezes in place and cannot be moved.

After each square is dropped, you must record the **height of the current tallest stack of squares**.

Return _an integer array_ `ans` _where_ `ans[i]` _represents the height described above after dropping the_ `ith` _square_.

[Examples are truncated]

Constraints:

- * $1 \le \text{positions.length} \le 1000^{\circ}$
- * `1 <= lefti <= 108`
- * `1 <= sideLengthi <= 106`

Assistant:

In the provided code snippet, I have implemented a solution to calculate the height of the tallest stack after dropping each square on a 2D plane. The algorithm processes a list of squares, represented by their left edge and side length, and follows these main steps:

[steps are truncated]

```
```python
def fallingSquares(positions):
 ans = []
 intervals = []

for p in positions:
 L, size = p
 R = L + size
 h = size
 for h2, R2 in intervals:
 if R2 > L and R > R2:
 h = max(h, size + h2)
 maxHeight = max((h2 for h2, R2 in intervals),
```

default=0) ans.append(max(maxHeight, h)) intervals.append((h, R))

return ans

Figure A6: An example of similar problem packing for LeetCode problems.

### User:

Please solve this problem:

In a galaxy far away, there is a constant battle between the republic and the droid army. The droid army decided to launch their final attack on the republic. They have N space-fighters.

Initially the  $i^{th}$  fighter is located at  $(x_{i}, y_{i})$ . All of the space-fighters move with constant velocity V units/sec in the positive X direction.

i.e., fighter at  $(x_{i}, y_{i})$  moves to  $(x_{i}+V, y_{i})$  in 1 second. The  $i^{th}$  space-fighter broadcasts enemy information at a frequency  $f_{i}$ .

The republic is not scared of the artificially intelligent droid force as they have Yoda. Yoda has a special power, at any time T he can choose a region of the droid army and block one specific frequency F. This power has one constraint; it can be applied only in the form of a two sided unbounded axis parallel rectangular box open towards the both the directions across X axis (refer image below for clarity). If a frequency (F) is blocked all the space-fighters in the region having the frequency F can't communicate.

Given the initial positions of the space-fighters, and their velocity, you are to answer queries of the following form:

### YU YD T

where YU, YD are the bounds on y-axis inside which YODA can block a frequency at time T.  $\,$ 

In the region described by the query, after a time T seconds from the start, if Yoda can chose one frequency (F) he wishes to, what is the maximum number of communications he can block?

### Input Format

Each test case is described as follows; the first line contains 3 space separated integers N - the number of space-fighters, Q - the number of queries you have to answer, and V - the velocity of the space-fighters separated by a single space.

N lines follow, each containing 3 space separated integers  $x_{i}$ ,  $y_{i}$ , and  $f_{i}$ , denoting the x co-ordinate, y co-ordinate and the frequency at which the  $i^{t}$  ship broadcasts respectively. Each of the next Q lines contain 3 space separated integers representing YU, YD, T respectively. Refer the figure for more clarity

Note: Points on the boundaries should be counted as well.

### Output Format

For each query you are to output a single integer denoting the result.

 $\begin{array}{l} \text{Constraints} \\ 1 <= N <= 50000 \\ 1 <= Q <= 30000 \\ 1 <= V <= 10000 \\ \$-10^{9} \$ <= x_{\{i\}} <= \$10^{9} \$ \\ \$-10^{9} \$ <= y_{\{i\}} <= \$10^{9} \$ \\ 1 <= f_{\{i\}} <= \$10^{9} \$ \\ \$-10^{9} \$ <= YU <= \$10^{9} \$ \\ \$-10^{6} \$ \$ <= YU <= \$10^{6} \$ \\ \$-10^{6} \$ \$ <= YU <= \$10^{6} \$ \\ \$-10^{6} \$ \\ 1 <= T <= 10000 \\ YU >= YD \end{array}$ 

[sample input, output and explanation are truncated]

### (Continued) Assistant:

To address your request, I've developed a Python code that evaluates the situations presented in this interstellar conflict scenario. The program is designed to take input details for the droid army's space-fighters regarding their initial positions, frequencies, and velocities, and then process multiple queries to determine the maximum number of communications Yoda can block at a given time within specified regions of space.

Here's a step-by-step implementation overview: [steps are truncated]

The following code encapsulates the logic detailed above, and executes the required queries to produce the desired output.

```
``python
import bisect
from collections import defaultdict
(N, Q, _) = map(int, input().split())
a = defaultdict(list)
y = list()
for _ in range(N):
 (_, y_, freq) = map(int, input().split())
 a[freq].append(y_)
 y.append(y_)
a = \{freq: sorted(y) \text{ for } (freq, y) \text{ in } a.items() \text{ if } len(y) > 1\}
y = sorted(y)
res = []
for _ in range(Q):
 (y_max, y_min, T) = map(int, input().split())
 lres = 0
 index_start = bisect.bisect_left(y, y_min)
 if y[index_start] <= y_max:
 lres = 1
 for freq in a:
 index_start = bisect.bisect_left(a[freq],
y_min)
 index_stop = bisect.bisect_right(a[freq],
y max)
 lres = max(lres, index_stop - index_start)
 res.append(lres)
print(*res, sep='\n')
```

### User:

What is the difficulty of this question?

```
Assistant:
The difficulty of the problem described can be considered
HARD.
```

**User:** Do you have any other way to solve this problem?

### Assistant:

To provide an alternative solution to the given problem, I've utilized the Square Root Decomposition algorithm, which is often used to optimize the computational complexity of problems involving range queries.

[remaining content and generated code are truncated]

Figure A7: An example of follow-up Q&A for LeetCode problems.

# F Case Study

	1
User:	(Continued)
Write code to calculate all prime numbers in the range of 1-100.	User:
1 6	I want you to extend the existing solution to fit the
Assistant	arbitrary range y y. Also, places add comments to your
Assistant.	arbitrary range x-y. Also, prease and comments to your
Sure, here is a simple Python code to calculate all prime numbers in	code for better readability.
the range of 1 to 100.	
	Assistant:
```python	Sure thing, here is the updated Python code, now with
def is_prime(n):	parameters for the range and added comments.
if $n \le 1$:	
return False	```python
$elifn \le 3$:	def is prime(n):
raturn True	"""Chacks if a number is prime """
2 = 0 = 0 = 0 = 0	if $n < -1$.
$\sin \frac{1}{3} \sqrt{2} = 0$ of $\frac{1}{3} \sqrt{3} = 0$.	
return False	return False # numbers less than or equal to 1 are not
i = 1	prime
while $i * i \le n$:	elif n <= 3:
if n % i == 0 or n % (i + 2) == 0:	return True # 2 and 3 are prime
return False	elif n % 2 == 0 or n % 3 == $\hat{0}$:
i += 1	return False # eliminate multiples of 2 and 3
return True	i = 5
tenan trae	while $i * i \leq n$
(1, 101)	where $1 \le 1 \le 1$.
for num in range(1, 101):	# eliminate multiples of primes already found
it is_prime(num):	if $n \% i == 0$ or $n \% (i + 2) == 0$:
print(num)	return False
***	i += 6 # increment by 6 to check for prime of form 6k
	±1
This and a includes a function 'is $prime(p)$ ' to check if a number 'p' is	raturn Trua
prime. It then iterates over the numbers 1 to 100 and prints the	Tetulii Tiuc
prime. It then iterates over the numbers 1 to 100 and primes the	
numbers for which is_prime(n) returns I rue.	def print_primes(x, y):
	"""Prints all prime numbers in the range x to y."""
User:	for num in range(x, y + 1):
Execution Result:	if is_prime(num):
2	print(num)
3	1 · · · /
	# Now you can call print primes with any range you want
Assistant	# For example, to get primes between 50 and 100, use
Assistant.	mint mim or (50, 100)
apologize for the confusion, there seems to have been an error in the	print_printes(30, 100)
code. The function to check if a number is prime was not correctly	
implemented. Here is the corrected Python code:	
	In this code, `print_primes(x, y)` is a function that prints
```python	all prime numbers between 'x' and 'y', inclusive. It does
def is prime(n):	this by iterating over all numbers in the range and printing
$\inf n \le 1$ :	the ones for which 'is prime(num)' returns 'True'. You
return False	can call this function with any range of numbers you want
$a = \frac{1}{2}$	can can this function with any range of numbers you want.
	There
return 1 rue	User:
elif n % 2 == 0 or n % 3 == 0:	Execution Result:
return False	53
i = 5	59
while $i * i \le n$ :	61
if n % i == 0  or  n % (i + 2) == 0:	67
return False	71
i +- 6	73
	75
return 1 rue	/9
	83
for num in range(1, 101):	89
if is prime(num):	97
print(num)	
	Assistant:
	I'm glad to see the code worked as expected! Those are
In the bin minute) for the last had been been been been been	indeed the prime numbers in the second secon
in the is_prime(n) function, the loop should start from 5 and	indeed the prime numbers in the range from 50 to 100. If
increment by 6 each time. This is because all primes are of the form	you have any other questions or need further assistance,
$6k \pm 1$ , with the exception of 2 and 3.	feel free to ask!
i de la construcción de la constru	

Figure A8: A good case where we required our model to write code to calculate all prime numbers in the range of 1-100, and then generalize the function to arbitrary range x-y. Our model successfully corrected the error and made improvements according to human feedback.

### User:

Implement a Python function to check if a string is a valid IPv6 address with regular expressions.

#### Assistant:

Sure, here is a Python function using Regular Expression (regex) to check if a string is a valid IPv6 address:

```python

import re

def is_valid_ipv6(ip):

Checks if a given string is a valid IPv6 address.

 $\begin{array}{l} pattern = re.compile(r'(([0-9a-fA-F] \{1,4\}:)|\{7,7\}[0-9a-fA-F] \{1,4\}([0-9a-fA-F] \{1,4\}:)\{1,5\}([0-9a-fA-F] \{1,4\}:)\{1,5\}([0-9a-fA-F] \{1,4\}:)\{1,4\}([0-9a-fA-F] \{1,4\}:)\{1,5\}([0-9a-fA-F] \{1,4\}:)\{1,4\}([0-9a-fA-F] \{1,4\}:)\{1,3\}([0-9a-fA-F] \{1,4\}:)\{1,3\}([0-9a-fA-F] \{1,4\}:)\{1,3\}([0-9a-fA-F] \{1,4\}:)\{1,3\}([0-9a-fA-F] \{1,4\}:)\{1,3\}([0-9a-fA-F] \{1,4\}:)\{1,3\}([0-9a-fA-F] \{1,4\}:)\{1,3\}([0-9a-fA-F] \{1,4\}:)\{1,5\}([0-9a-fA-F] \{1,4\}:)\{1,2\}([0-9a-fA-F] \{1,4\}:)\{1,3\}([0-9a-fA-F] \{1,4\}:)\{1,3\}([0-9a-fA-F] \{1,4\}:)\{1,5\}([0-9a-fA-F] \{1,4\}:)\{1,3\}([0-9a-fA-F] \{1,4\}:)\{1,3\}([0-9a-fA-F] \{1,4\}:)\{1,3\}([0-9a-fA-F] \{1,4\}:)\{1,3\}([0-9a-fA-F] \{1,4\}:)\{1,3\}([0-9a-fA-F] \{1,4\}:)\{1,3\}([0-9a-fA-F] \{1,4\}:)\{1,3\}([0-9a-fA-F] \{1,4\}:)\{1,4\}((25[0-5]](2[0-4]]] \{0,1\}[0-9])([0-9a-fA-F] \{1,4\}:)\{1,4\}:((25[0-5]](2[0-4]]] \{0,1\}[0-9])(0,1\}[0-9])([(0-9a-fA-F] \{1,4\}:)\{1,4\}:((25[0-5]](2[0-4]]] \{0,1\}[0-9])((2-9a-fA-F] \{1,4\}:)\{1,4\}:((25[0-5]](2[0-4]]] \{0,1\}[0-9])((2-9a-fA-F] \{1,4\}:)\{1,4\}:((25[0-5]](2[0-4]]] \{0,1\}[0-9])((2-9a-fA-F] \{1,4\}:)\{1,4\}:((25[0-5]](2[0-4]]] \{0,1\}[0-9])(2-9a-fA-F] \{1,4\}:)[0-9])(2-9a-fA-F] \{1,4\}:((25[0-5]](2[0-4]]] \{0,1\}[0-9])(2-9a-fA-F] \{1,4\}:)[0-9a-fA-F] \{1,4\}:((25[0-5]](2[0-4]]] \{0,1\}[0-9])(2-9a-fA-F] \{1,4\}:)[0-9])(2-9a-fA-F] \{1,4\}:((25[0-5]](2[0-4]]] \{0,1\}[0-9])(2-9a-fA-F] \{1,4\}:)[0-9])(2-9a-fA-F] \{1,4\}:((25[0-5]](2[0-4]]] \{0,1\}[0-9])(2-9a-fA-F] \{1,4\}:)[0-9])(2-9a-fA-F] \{1,4\}:((25[0-5]](2[0-4]]] \{0,1\}[0-9])(2-9a-fA-F] \{1,4\}:)[0-9])(2-9a-fA-F] \{1,4\}:((25[0-5]](2[0-4]]] \{0,1\}[0-9])(2-9a-fA-F] \{1,4\}:((25[0-5]](2[0-4]]] \{0,1\}[0-9])(2-9a-fA-F] \{1,4\}:((25[0-5]](2[0-4]]] \{0,1\}[0-9])(2-9a-fA-F] \{1,4\}:((25[0-5]](2[0-4]]] \{0,1\}[0-9])(2-9a-fA-F] \{1,4\}:((25[0-5])(2[0-4]]] \{0,1\}[0-9])(2-9a-fA-F] \{1,4\}:((25[0-5])(2[0-4]]] \{0,1\}[0-9])(2-9a-fA-F] \{1,4\}:((25[0-5])(2[0-4]]] \{0,1\}[0-9])(2-9a-fA-F] \{1,4\}:((25[0-5])(2[0-4]]] \{0,1\}[0-9])(2-9a-fA-F] \{1,4\}:((25[0-5])(2[0-4]]] \{0,1\}[0-9])(2-9a-fA-F] \{1,4\}:((25[0-5])(2[0-4]]] \{1,4\}:((25[0-5])(2[0-4]]] \{1,4\}:((25[0-5])(2[0-4]]])(2-9a-fA-F] \{1,4\}:((25[0-5])(2[0-4]]]](2-9a-fA-F] \{1,4\}:((25[0-5])(2[0-4]]])(2-9a-fA-F])(2-9a-fA-F$

return bool(pattern.match(ip))

print(is_valid_ipv6("2404:6800:4003:c02::8a")) # True print(is_valid_ipv6("2404:6800:4003:804::200e")) # True print(is_valid_ipv6("102.192.230.21")) # False print(is_valid_ipv6("2404:6800:4003:804:200e")) # False

This function uses a complex regular expression which covers all possible valid IPv6 formats according to RFC 3986. It checks for hexadecimal values which are represented in 8 groups of 4 hexadecimal digits.

User:

Execution Result:

error Traceback (most recent call last) Input In [1], in <cell line: 11>() [output is truncated]

error: nothing to repeat at position 21

Assistant:

I apologize for the confusion. It seems like there was a mistake in the regular expression pattern. Let's correct that. Here is the corrected function:

```python import re

def is\_valid\_ipv6(ip):

Checks if a given string is a valid IPv6 address.

 $\begin{array}{l} pattern = re.compile(r'(([0-9a-fA-F] \{1,4\}:)\{7,7\}[0-9a-fA-F] \{1,4\}([0-9a-fA-F] \{1,4\}:)\{1,5\}([0-9a-fA-F] \{1,4\}:)\{1,5\}([0-9a-fA-F] \{1,4\}:)\{1,4\}([0-9a-fA-F] \{1,4\}:)\{1,5\}([0-9a-fA-F] \{1,4\}:)\{1,4\}([0-9a-fA-F] \{1,4\}:)\{1,3\}([0-9a-fA-F] \{1,4\}:)\{1,3\}([0-9a-fA-F] \{1,4\}:)\{1,3\}([0-9a-fA-F] \{1,4\}:)\{1,3\}([0-9a-fA-F] \{1,4\}:)\{1,3\}([0-9a-fA-F] \{1,4\}:)\{1,3\}([0-9a-fA-F] \{1,4\}:)\{1,3\}([0-9a-fA-F] \{1,4\}:)\{1,5\}[[0-9a-fA-F] \{1,4\}:\{1,2\}:([0-9a-fA-F] \{1,4\}:)\{1,2\}([0-9a-fA-F] \{1,4\}),\{1,5\}[[0-9a-fA-F] \{1,4\}:)\{1,5\}([0-9a-fA-F] \{1,4\}),\{1,5\}([0-9a-fA-F] \{1,4\}:)\{1,5\}([0-9a-fA-F] \{1,4\}),\{1,5\}([0-9a-fA-F] \{1,4\}),\{1$ 

return bool(pattern.match(ip))

```
print(is_valid_ipv6("2404:6800:4003:c02::8a")) # True
print(is_valid_ipv6("2404:6800:4003:804::200e")) # True
print(is_valid_ipv6("102.192.230.21")) # False
print(is_valid_ipv6("2404:6800:4003:804:200e")) # False
```

This function should now correctly validate IPv6 addresses. It should return True for valid IPv6 addresses and False for invalid ones.

- (Continued) User:
- Execution Result: True True False False

### Assistant:

Great! The function appears to be working as expected now.

It correctly identifies the strings "2404:6800:4003:c02::8a" and "2404:6800:4003:804::200e" as valid IPv6 addresses (returning 'True'), and it correctly identifies the strings "102.192.230.21" and "2404:6800:4003:804:200e" as invalid IPv6 addresses (returning 'False').

Remember that this function uses regular expressions to match the input string against the patterns of IPv6 addresses. It checks for hexadecimal values which are represented in 8 groups of 4 hexadecimal digits.

Let me know if there's anything else I can assist you with!

#### User:

Can you explain the generated regular expression in detail and make this function more maintainable?

#### Assistant:

Sure, let me break down the regular expression for you:

- `([0-9a-fA-F]{1,4}:){7,7}[0-9a-fA-F]{1,4}`: This pattern matches an IPv6 address that consists of eight groups of hexadecimal digits, separated by colons.

- `([0-9a-fA-F] {1,4}:) {1,7}:`: This pattern matches an IPv6 address that has a trailing colon and at least one leading group of hexadecimal digits.

[explanations are truncated]

These patterns are all combined with the `|` operator, which means that a match on any of these patterns will result in a match for the entire regular expression.

Here is the code with step-by-step explanation:

```
```python
```

import re

```
def is_valid_ipv6(ip):
```

Checks if a given string is a valid IPv6 address.

```
# Compile a regular expression pattern into a regular expression
object, which can be used for matching using its match() method
pattern = re.compile(
```

r"""(

Matches 8 groups of hexadecimal digits separated by colons ([0-9a-fA-F]{1,4}:){7,7}[0-9a-fA-F]{1,4}|

Matches an IPv6 address with a trailing colon and at least one leading group of hexadecimal digits

([0-9a-fA-F] {1,4}:){1,7}:| # Matches an IPv6 address that has a group of hexadecimal digits both before and after a double colon ((0-9a-fA-F] {1,4}:){1,6}:[0-9a-fA-F] {1,4}|

[generated code is truncated]

```
""", re.VERBOSE)
```

If the whole string matches the regular expression pattern, return True. Otherwise, return False return bool(pattern.match(ip))

This code uses the `re.VERBOSE` flag to allow the regular expression to be spread out over multiple lines, with comments in between. It makes the regular expression more readable and maintainable.

Figure A9: A good case that asked our model to implement a Python function to check if a string is a valid IPv6 address with regular expressions. Inspired by errors raised in the execution result, our model managed to recognize the small error from complex regular expression. Then, our model successfully generated explanation for this regular expression and improve its readability with thorough in-line comments.

```
User:
                                                                              (Continued)
Design a function that finds the intersection of two input lists, and
                                                                              User:
returns a list of tuples, each containing a distinct element that is
                                                                              Execution result:
present in both lists and its frequency of occurrence. For this task,
                                                                              [(1, 3), (5, 3), (653, 2)]
avoid using Python's built-in list functions or any libraries to sort the
                                                                              [(2, 2), (3, 3)]
result and remove duplicates. Also, implement your own hash table
data structure for this task.
                                                                              Assistant:
                                                                              Oops, looks like the output gives the total count of each number from
def shared_elements(list1: list, list2: list):
     'Return a list of tuples of unique elements that appeared in both
                                                                              both lists, but we only want the count per list. Need to adjust this.
input lists and their frequency, sorted in ascending order without
                                                                              Also, it seems like the test results from shared elements function give
using Python's built-in list functions or any libraries. Implement your
                                                                              the correct elements but wrong frequencies, which indicates a logical
own hash table for this task.
                                                                              error. It's counting total occurrences in both lists rather than in each
    >>> shared_elements([1, 4, 1, 3, 4, 653, 2, 5], [5, 7, 1, 5, 9, 653,
                                                                              list. Let's fix this.
121)
                                                                                 `python
  [(1, 2), (5, 3), (653, 2)]
                                                                              class HashMap:
      > shared_elements([5, 3, 3, 2, 8], [3, 2])
                                                                              [code is truncated]
  [(2, 1), (3, 2)]""
Assistant:
                                                                              def shared_elements(list1, list2):
  python
                                                                              [code is truncated]
class HashMap:
[code is truncated]
                                                                                 for i in range(hash map1.size):
                                                                                   if hash_map1.get(i) is not None and hash_map2.get(i) is not
def shared elements(list1, list2):
                                                                              None
[code is truncated]
                                                                                      intersection.append((i, min(hash_map1.get(i),
                                                                              hash map2.get(i))))
  for i in range(hash map1.size)
     if hash_map1.get(i) is not None and hash_map2.get(i) is not
None:
                                                                                 insertion sort(intersection)
        intersection.append((i, hash_map1.get(i) + hash_map2.get(i)))
                                                                                 print("Insertion sort result: "+intersection)
  insertion_sort(intersection)
                                                                                 return intersection
  return intersection
                                                                              def insertionsort(lst):
def insertion_sort(lst):
                                                                                 for i in range(len(lst)):
  for i in range(len(lst)):
     while j > 0 and lst[j - 1] > lst[j]:
                                                                                    while j > 0 and lst[j - 1] > lst[j]:
       lst[j - 1], lst[j] = lst[j], lst[j - 1]
                                                                                      lst[j - 1], lst[j] = lst[j], lst[j - 1]
                                                                                      j -= 1
samples = [[1, 4, 1, 3, 4, 653, 2, 5], [5, 7, 1, 5, 9, 653, 121]], [[5, 3, 3,
                                                                               samples = [[1, 4, 1, 3, 4, 653, 2, 5], [5, 7, 1, 5, 9, 653, 121]], [[5, 3, 3,
2, 8], [3, 2]]
                                                                              2, 8], [3, 2]]
for sample in samples:
print(shared_elements(sample[0], sample[1]))
                                                                              for sample in samples:
                                                                               print(shared_elements(sample[0], sample[1]))
User:
Execution result:
                                                                              User:
 Cell In[2], line 45
                                                                              Execution result:
  for i in range(hash map1.size)
                                                                              TypeError
                                                                                                               Traceback (most recent call last)
SyntaxError: invalid syntax
                                                                              Cell In[4], line 64
                                                                                  62 samples = [[1, 4, 1,
Assistant:
                                                                              [Output too much, the middle part output is omitted]
Sorry, seems like there is a small mistake. Let me correct it.
                                                                               End part of output:
class HashMap:
                                                                              (i), hash_map2.get(i))))
[code is truncated]
                                                                                  49 insertion_sort(intersection)
                                                                               ---> 51 print("Insertion sort result: "+intersection)
def shared elements(list1, list2):
                                                                                  53 return intersection
[code is truncated]
                                                                              TypeError: can only concatenate str (not "list") to str
  for i in range(hash map1.size):
     if hash_map1.get(i) is not None and hash_map2.get(i) is not
                                                                              [max retries are exceeded, so this session stops here]
None:
        intersection.append((i, hash map1.get(i) + hash map2.get(i)))
  insertion sort(intersection)
  return intersection
def insertion sort(lst):
  for i in range(len(lst)):
     while j > 0 and lst[j - 1] > lst[j]:
       lst[j - 1], lst[j] = lst[j], lst[j - 1]
       j -= 1
samples = [[1, 4, 1, 3, 4, 653, 2, 5], [5, 7, 1, 5, 9, 653, 121]], [[5, 3, 3,
2, 8], [3, 2]]
for sample in samples:
  print(shared_elements(sample[0], sample[1]))
```

Figure A10: In this bad case, we tried to ask our model to design a function that finds the intersection of two input lists and returns a list of tuples, each containing a distinct element that is present in both lists and its frequency of occurrence. Although our model tried to make corrections, it only corrected one error at a time and finally exceeded max number of attempts (3).