# FASTER CASCADES VIA SPECULATIVE DECODING

## **Anonymous authors**

Paper under double-blind review

### **ABSTRACT**

Cascades and speculative decoding are two common approaches to improving language models' inference efficiency. Both approaches involve interleaving models of different sizes, but via fundamentally distinct mechanisms: cascades employ a deferral rule that invokes the larger model only for "hard" inputs, while speculative decoding uses speculative execution to primarily invoke the larger model in parallel verification mode. These mechanisms offer different benefits: empirically, cascades offer better cost-quality trade-offs, often even outperforming the large model, while theoretically, speculative decoding offers a guarantee of quality-neutrality. In this paper, we leverage the best of both these approaches by designing new speculative cascading techniques that implement their deferral rule through speculative execution. We characterize the optimal deferral rule for our speculative cascades, and employ a plug-in approximation to the optimal rule. Experiments with Gemma and T5 models on a range of language benchmarks show that our approach yields better cost-quality trade-offs than cascading and speculative decoding baselines.

### 1 Introduction

Large language models (LLMs) have yielded significant advances in quality on a range of natural language processing tasks (Radford et al., 2018; Raffel et al., 2020a; Brown et al., 2020; Black et al., 2022; Chowdhery et al., 2022; Wei et al., 2022; Chung et al., 2022; Tay et al., 2023; Anil & et al., 2023; Touvron et al., 2023; Team et al., 2023), at the cost of an increase in inference latency. This has sparked a growing body of literature on reducing LMs' inference costs without (overly) compromising on quality (Elbayad et al., 2020; Pope et al., 2022; Schuster et al., 2022; Leviathan et al., 2023; Chen et al., 2023a; Sheng et al., 2023; Sun et al., 2024). One such line of work involves constructing a family of models of various sizes (e.g., a small and large model), and suitably orchestrating amongst them to make a prediction. Two canonical instantiations of this strategy are *model cascading* (Wang et al., 2020; Mamou et al., 2022; Varshney & Baral, 2022; Khalili et al., 2022; Dohan et al., 2022; Chen et al., 2023b; Gupta et al., 2024; Ding et al., 2024) and *speculative decoding* (Stern et al., 2018; Chen et al., 2023a; Leviathan et al., 2023; Sun et al., 2024; Li et al., 2024a; Xia et al., 2024a).

While similar in spirit, cascades and speculative decoding are fundamentally different in details. Cascades employ a *deferral rule* to identify "hard" inputs, and only invoke larger models on such inputs. For example, in a two-model cascade, one first invokes the smaller model, and uses its associated probability of the generated output to decide whether to defer to the larger model. By contrast, speculative decoding uses a small model to *draft* a block of tokens via standard autoregressive decoding, which are then *verified* in parallel by a large model. One then accepts all drafted tokens until the first "implausible" one, which is rolled back based on the larger LM's prediction.

Owing to their different mechanisms, both methods have complementary strengths. Cascades seek to output distributions that have the best quality for a given cost budget, and potentially provide better cost-quality trade-offs, sometimes even yielding better accuracies than the individual models they are constructed with (Jitkrittum et al., 2023; Kim et al., 2023) (§3). By contrast, speculative decoding is theoretically guaranteed to match the output distribution (or a close approximation thereof (Tran-Thien, 2023)), and are practically observed to provide impressive speed-ups (Stern et al., 2018; Chen et al., 2023a; Leviathan et al., 2023; Sun et al., 2024). Given the complementary nature of these two approaches, a natural question arises: can we leverage the best of both techniques?

In this paper, we do so by designing new techniques for two-model cascades that implement their deferral rule in a speculative manner: we have the smaller model generate drafts auto-regressively,

and the larger model execute in parallel on the drafts to decide *whether or not to defer on them*. We show that this *speculative cascading* approach yields better cost-quality trade-offs than both standard cascades and speculative decoding. In detail, we make the following contributions:

- (i) We introduce a general recipe for speculative execution, where we seek to mimic a general *target* distribution that interleaves the drafter's and verifier's distributions. Lossy speculative sampling (Tran-Thien, 2023) is a special case of this recipe for a particular target distribution (§4.1).
- (ii) We show how common cascading rules, such as Chow's rule (Chow, 1970) and confidence-difference thresholding (Jitkrittum et al., 2023), can be implemented speculatively by plugging in their target distribution into our framework. We refer to these as *speculative cascades* (§4.2).
- (iii) We characterize the *theoretically optimal* deferral rule for a speculative cascade, and design a speculative cascading technique that implements a plug-in estimate to the optimal rule (§4.3, Lemma 4, Table 1). We also present token-specific variants of our deferral rules (§4.4).
- (iv) Through experiments with Gemma (Team et al., 2024) and T5 models (Raffel et al., 2020b) on a range of benchmark language tasks including summarization, translation, reasoning, coding and QA, we show that speculative cascades are able to provide better cost-quality trade-offs than their sequential cascade and speculative decoding counterparts (§6).

## 2 A Tale of Two Efficient LM Inference Strategies

Let  $\mathcal V$  denote a finite vocabulary of *tokens*, with  $\mathcal V^*$  denoting the set of all *sequences* generated by this vocabulary. Let  $\Delta_{\mathcal V}$  denote the set of all probability distributions over tokens in  $\mathcal V$ . Given an arbitrary length sequence  $x=x_1x_2\dots x_L\in \mathcal V^*$  and index  $i\leq L$ , denote by  $x_{< i}=x_1x_2\dots x_{i-1}$ . A *language model* (LM) is a probability distribution over  $\mathcal V^*$ . Let  $\mathbb P$  denote the ground-truth probability distribution over  $\mathcal V^*$ . This could be, for example, a distribution over prompt-response pairs that the LM may encounter during deployment, or a distribution of sequences used to pre-train the LM. We will measure the quality of an LM based on how closely it mimics  $\mathbb P$ .

Suppose we are provided two LMs q and p, where p is the larger (more expensive) model. Our goal is to design an inference strategy that selectively invokes q and p to trade-off between quality and latency (which may be approximated by the fraction of times that p is invoked). We will denote by  $q(x_t|x_{< t})$  the probability q associates to token  $x_t \in \mathcal{V}$  given prefix  $x_{< t} \in \mathcal{V}^{t-1}$ , and by  $p(x_t|x_{< t})$  the same distribution from model p. Whenever it is clear from context, we will hide the conditioning on prefix  $x_{< t}$ , and use the shorthand  $p_t(\cdot)$  for  $p(\cdot|x_{< t})$  and  $q_t(\cdot)$  for  $q(\cdot|x_{< t})$ .

Cascades are an effective strategy to trade-off cost and quality by having the smaller model q handle the "easy" samples, and the larger model p handle the "hard" ones (Gupta et al., 2024; Yue et al., 2024). A common cascading approach is confidence thresholding or Chow's rule (Chow, 1970; Jitkrittum et al., 2023), where we first run q on the input, and defer to p when q's confidence for its generated response is sufficiently low. This strategy is typically implemented at the *sequence-level*, where for a given prefix  $x_{< m}$  we invoke q to generate a complete response  $x_m \dots x_{m+n}$ . We evaluate q's predicted probability for the response, and check whether it falls below a threshold  $\alpha \in [0,1]$ :

$$q(x_m \dots x_{m+n} \mid x_{\leq m}) < 1 - \alpha. \tag{1}$$

If the above holds, we defer to p to generate a new response; otherwise, we retain q's response. One may tune the threshold to achieve a desired cost-quality trade-off. The literature also offers variants of Chow's rule that use a more nuanced aggregation of per-token uncertainties (Gupta et al., 2024).

**Speculative decoding** is an alternate strategy that applies *token-level* interleaving between q and p, resulting in *provably* matching the larger model quality at a reduced inference cost (Stern et al., 2018; Leviathan et al., 2023). Given a prefix  $x_{< t}$ , we *draft*  $\gamma$  draft tokens  $x_t, \ldots, x_{t+\gamma-1}$  via auto-regressive sampling from q, and *verify* if these tokens can be accepted by running p in parallel on the  $\gamma$  prefixes  $x_{< t}, \ldots, x_{< t+\gamma-1}$ . We then rollback to the first rejected token  $t+j^*$  (where  $j^* \in \{0, 1, \ldots, \gamma-1\}$ ), replace  $x_{t+j^*}$  with a new token, and repeat the process with prefix  $x_{< t+j^*+1}$ .

During the verification stage, a draft token  $x_{t+j}$  generated by q is accepted with probability  $\min\left(1,\frac{p_{t+j}(x_{t+j})}{q_{t+j}(x_{t+j})}\right)$  and rejected otherwise, recalling the shorthand  $q_{t+j}(\cdot)=q(\cdot|x_{< t+j})$  and  $p_{t+j}(\cdot)=p(\cdot|x_{< t+j})$ . A rejected token is then replaced by a new token sampled from a modified distribution norm  $(\max\{0,p_{t+j}(\cdot)-q_{t+j}(\cdot)\})$ , where  $\operatorname{norm}(\cdot)$  denotes normalization to sum

Table 1: Target distributions associated with different inference algorithms, where  $\alpha$  is a free parameter and  $\beta \geq 1-\alpha$  depends on  $\alpha$ , q and p. The last column indicates whether the execution is sequential (Algorithm 2), via an oracle (Algorithm 3), or speculative (Algorithm 5) (Leviathan et al., 2023). See (6) for details on  $\delta$ . The third row presents a variant of the BiLD algorithm of Kim et al. (2023), where D(q,p) is a measure of discrepancy between q and p; the original algorithm differs in the use of a deterministic speculative decoding procedure with a dynamic draft window (see §5).

Inference strategy	Deferral decision $\delta(q,p)$	Target distribution $\pi(x)$	Execution
SpecDecoding (Leviathan et al., 2023)	-	p(x)	Speculative
Lossy SpecDecoding (Tran-Thien, 2023)	-	$\max\{\min\{q(x),\frac{p(x)}{1-\alpha}\},\frac{p(x)}{\beta}\}$	Speculative
BiLD* (Kim et al., 2023)	$1\big(D(q,p) > \alpha\big)$	$(1-\delta)\cdot q(x) + \delta \cdot p(x)$	Speculative
TokenCascade [Chow] (Chow, 1970)	$1\big(\max_v q(v) < 1 - \alpha\big)$	$(1 - \delta) \cdot q(x) + \delta \cdot p(x)$	Sequential
Oracle [Diff] (Jitkrittum et al., 2023)	$1\big(\max_{v} q(v) < \max_{v} p(v) - \alpha\big)$	$(1 - \delta) \cdot q(x) + \delta \cdot p(x)$	Oracle
SpecCascade [Chow]	$1(\max_{v} q(v) < 1 - \alpha)$	$(1 - \delta) \cdot q(x) + \delta \cdot p(x)$	Speculative
SpecCascade [Diff]	$1(\max_{v} q(v) < \max_{v} p(v) - \alpha)$	$(1 - \delta) \cdot q(x) + \delta \cdot p(x)$	Speculative
SpecCascade [OPT]	$1\big(\max_{v} q(v) < \max_{v} p(v) - \alpha \cdot D_{TV}(p, q)\big)$	$(1 - \delta) \cdot q(x) + \delta \cdot p(x)$	Speculative

to 1. This sampling process is provably equivalent to sampling  $\gamma$  tokens auto-regressively from p for prefix  $x_{< t}$  (Leviathan et al., 2023). We summarize this speculative sampling procedure in Algorithm 1. Each invocation of this algorithm generates at most  $\gamma+1$  next tokens (and at least one) for a given prefix  $x_{< t}$ . One may run this algorithm multiple times to generate a complete output sequence.

In practice, one may employ a lossy variant (Tran-Thien, 2023) of the above sampling that allows some *deviation* from verifier's distribution p. In this case, a draft token  $x_{t+j}$  is accepted with probability  $\min\left(1,\frac{p_{t+j}(x_{t+j})}{(1-\alpha)\cdot q_{t+j}(x_{t+j})}\right)$ , where  $\alpha\in[0,1)$  is a strictness parameter, with higher values indicating greater deviation from p. A rejected token may then be replaced by a token sampled from the residual distribution norm  $\left(\max\left\{0,\frac{1}{\beta}\cdot p_{t+j}(\cdot)-q_{t+j}(\cdot)\right\}\right)$ , where  $\beta\geq 1-\alpha$  is a parameter that depends on  $\alpha$ , q and p. A common heuristic is to simply set  $\beta=1$  (Zhou et al., 2024).

## 3 CASCADES MEET SPECULATIVE DECODING

Both cascades and speculative decoding interleave models of different sizes to reduce inference cost, but fundamentally differ in the mechanisms they use. As a step towards comparing the strengths and weaknesses of these approaches, we first describe how one may design a *token-level cascade*.

## 3.1 WARM-UP: TOKEN-LEVEL CASCADES

It is straightforward to extend the sequence-level Chow's rule from §2 to form a *token-level cascade* between q and p. For a prefix  $x_{< t}$ , we first compute the smaller model's distribution  $q(\cdot|x_{< t})$ , and check whether  $\max_{v \in \mathcal{V}} q(v|x_{< t})$  is below a pre-chosen threshold. If so, we evaluate  $p(\cdot|x_{< t})$ , and sample  $x_t \sim p(\cdot|x_{< t})$ ; otherwise, we sample  $x_t \sim q(\cdot|x_{< t})$ .

More generally, we may design a token-level deferral rule  $r: \mathcal{V}^{t-1} \to \{0,1\}$  that takes the prefix  $x_{< t}$  as input and outputs a binary decision, with  $r(x_{< t}) = 1$  indicating that we defer to p (i.e., draw a sample from p rather than q). For example, token-level Chow's rule can be written as:

$$r_{\mathsf{Chow}}(x_{< t}) = 1 \iff \max_{v \in \mathcal{V}} q(v|x_{< t}) < 1 - \alpha, \tag{2}$$

where  $\alpha$  is a threshold parameter; the higher the value, the lower is the frequency of deferral to p. One may also use other confidence measures than the maximum probability, such as the entropy of the small model's probability distribution. We elaborate in §B that the choice of confidence measure would depend on the evaluation metric of interest; Equation 2 is typically prescribed when the cascade's quality is evaluated in terms of its accuracy against the ground-truth distribution on individual tokens, whereas entropy is prescribed when the metric of interest is the cross-entropy loss.

### 3.2 OPTIMAL TOKEN-LEVEL CASCADE DEFERRAL

While Chow's rule equation 2 is easy to implement, it can be sub-optimal if the smaller model's max-token probability is not reflective of which of the two models are better equipped to predict the

next token for a given prefix (Jitkrittum et al., 2023). Given this, it is natural to ask what the *optimal* deferral rule r for a token-cascade looks like, and whether we can reasonably approximate this rule.

For this, we must first specify an objective to minimize at each step t. Following the prior cascade literature (Jitkrittum et al., 2023; Gupta et al., 2024), a reasonable objective to minimize is the expected loss from the deferral rule against the ground-truth distribution  $\mathbb{P}$ , with an added cost for deferring to the larger model. We state this below for a fixed prefix  $x_{< t}$ , using as before the short-hand  $q_t(\cdot)$  for  $q(\cdot|x_{< t})$  and  $p_t(\cdot)$  for  $p(\cdot|x_{< t})$ :

$$L_{\text{def}}(r; x_{< t}) = \mathbb{E}_{v \sim \mathbb{P}(\cdot \mid x_{< t})} \Big[ \Big( 1 - r(x_{< t}) \Big) \cdot \ell(v, q_t) + r(x_{< t}) \cdot \Big( \ell(v, p_t) + \alpha \Big) \Big], \tag{3}$$

for a cost penalty  $\alpha \geq 0$  and loss function  $\ell : \mathcal{V} \times \Delta_{\mathcal{V}} \to \mathbb{R}_+$ . Common choices for  $\ell$  include the 0-1 loss  $\ell_{0\text{-}1}(v,q_t) = \mathbf{1} \, (v \neq \arg\max_{v'} q_t(v'))$  and the log loss  $\ell_{\log}(v,q_t) = -\log(q_t(v))$ .

**Lemma 1** (Optimal deferral for token-level cascades (Jitkrittum et al., 2023)). The minimizer of equation 3 is of the form:

$$r^*(x_{< t}) = 1 \iff \mathbb{E}_{v \sim \mathbb{P}(\cdot \mid x_{< t})} \left[ \ell(v, q_t) \right] > \mathbb{E}_{v \sim \mathbb{P}(\cdot \mid x_{< t})} \left[ \ell(v, p_t) \right] + \alpha. \tag{4}$$

Intuitively, we compare the expected loss from q with the expected cost of invoking p, and decide to defer when the latter is smaller. We note here that this optimization problem is set up for a *fixed* prefix  $x_{< t}$ . One may also consider the coupled optimization problem across all positions.

Plug-in estimator for equation 4. The optimal rule in equation 4 requires computing expectations over the ground-truth distribution  $\mathbb{P}(\cdot|x_{>t})$ , which is not available during inference time. A common approach in the cascades literature is to replace the expected losses with the models' confidence estimates (Jitkrittum et al., 2023). For example, when  $\ell = \ell_{0-1}$ , it may be reasonable to use  $1 - \max_v q_t(v)$  as an estimate of the expected 0-1 loss  $\mathbb{E}_{x_t \sim \mathbb{P}(\cdot|x_{<t})}\left[\ell_{0-1}(x_t,q_t)\right]$  and  $1 - \max_v p_t(v)$  as an estimate of  $\mathbb{E}_{x_t \sim \mathbb{P}(\cdot|x_{<t})}\left[\ell_{0-1}(x_t,q_t)\right]$ . The extent to which these estimates are accurate depend on how well q and p are calibrated (Guo et al., 2017). The resulting plug-in estimator for (4) thresholds the difference of confidence estimates from both distributions:

$$\hat{r}_{\text{Diff}}(x_{< t}) = 1 \iff \max_{v} q_t(v) < \max_{v} p_t(v) - \alpha.$$
 (5)

Similarly, when  $\ell = \ell_{\log}$ , we may use the entropy  $-\sum_v q_t(v) \cdot \log(q_t(v))$  from  $q_t$  as an estimate of its expected log-loss, and similarly for  $p_t$  (see Appendix C).


**Remark 1** (Oracle deferral rules). For efficiency reasons,  $\hat{r}_{Diff}$  cannot be directly used in a token-level cascade, as it needs the large model to be invoked at every step t. However, it serves as an oracle that allows to analyze the head-room available to improve upon Chow's rule. See also Remark 2.

#### 3.3 CONTRASTING TOKEN-LEVEL CASCADE AND SPECULATIVE DECODING TRADE-OFFS

Token-level cascades and speculative decoding differ in the distribution over tokens they seek to mimic. Speculative decoding seeks to mimic the large model's output distribution, and is usually used when one wants to match the quality of the large model. On the other hand, token-level cascades seek to output distributions that closely approximate the ground-truth label distribution and potentially offer *good cost-quality trade-offs*, sometimes yielding better quality than even the large model.

Cascades are useful when the draft model fares better than the verifier on some inputs, and one may want to retain the drafter's predictions even when it disagrees with the verifier. Even in cases where both the drafter and verifier fare poorly on some inputs (e.g., due to label noise), one may want to ignore the disagreement between the drafter and verifier to avoid triggering unnecessary roll-backs.

As a concrete example, we consider token-level cascades of T5 models (Raffel et al., 2020b) of two different sizes finetuned on a WMT EN  $\rightarrow$  DE translation Bojar et al. (2014b) and an extreme summarization (XSum) task (Narayan et al., 2018). We construct these cascades using both (token-level) Chow's rule in equation 2 and the oracle Diff rule in equation 5, and also apply speculative decoding with the smaller (larger) model as the drafter (verifier). In Figure 1, we plot quality as a function of fraction of samples deferred to the large model (number of deferrals divided by number of generated tokens), as we vary the cost parameter  $\alpha$ . Note that with speculative decoding, each verification step verifies  $\gamma$  tokens in parallel, but is counted as a single deferral to the large model. While speculative decoding matches the quality of the large model (right-most point), the oracle yields






Figure 1: Plots of quality as a function of the *number of deferrals to the larger model divided by the total number of generated tokens* for cascades constructed from T5 models (under temperature sampling with T=1). The left-most point represents the small model and the right-most represents the large model. We compare token-level cascades constructed with Chow's rule (Chow) and an oracle deferral rule (Diff), and speculative decoding with block size  $\gamma=5$ . With a cascade, each call to the large model yields exactly one token, whereas with speculative decoding, a single call scores  $\gamma$  draft tokens in parallel. While speculative decoding matches the quality of the large model (see dashed horizontal line), the oracle deferral rule yields significantly better quality on a range of deferral rates; this however comes at the cost of higher number of deferrals to the large model.

significantly better cost-qualty trade-offs. Even Chow's rule, which is sub-optimal for cascading (Jitkrittum et al., 2023), offers better trade-offs, and outperforms speculative decoding in a small region. As noted by Kim et al. (2023), this may be attributed to the ensembling effect in a cascade.

However, as also evident from the plots, token-level cascades require a significantly larger number of deferrals to the large model to achieve the same quality. This is because token-level cascades are executed *sequentially*: whenever q defers, we execute p once to generate one next token for the prefix accumulated so far, and the control transfers back to q. In contrast, speculative decoding runs p in *scoring* mode to verify  $\gamma$  draft tokens from q in parallel. Moreover, the stochastic verification algorithm in speculative decoding often results in fewer tokens from q getting rejected compared to the deterministic deferral rules used in a cascade. These observations motivate a natural question: given their complementary strengths, how can we leverage the best of both these techniques?

## 4 Speculative Cascades: Leveraging the Best of Both Worlds

In addressing the above question, we present our main contribution: a principled approach to combining the better trade-offs cascades offer with the faster execution of speculative decoding.

### 4.1 SPECULATIVE DECODING WITH GENERAL TARGET DISTRIBUTIONS

We begin by considering a generic version of speculative sampling that seeks to mimic a *general* target distribution derived from the drafter's and verifier's distributions. In the proposed sampling procedure outlined in Algorithm 4, we sample tokens auto-regressively as before from the drafter's distribution. During the verification step, however, we do not compare the drafter's token probabilities against the verifier's distribution. Instead, we use a user-specified target distribution  $\pi = \mathbb{T}(q,p) \in \Delta_{\mathcal{V}}$  derived from the drafter's and verifier's distributions at position t, for some function  $\mathbb{T}(\cdot,\cdot)$  that is inexpensive to compute. We accept a draft token  $x_t$  when  $q(x_t) \leq \pi(x_t)$  and reject it otherwise with probability  $1 - \frac{\pi(x_t)}{q(x_t)}$ . Upon rejection, we re-sample from the residual distribution norm  $(\max\{0,\pi(\cdot)-q(\cdot)\})$ .

This general procedure not only encompasses standard speculative decoding (Leviathan et al., 2023) for  $\mathbb{T}(q,p)=p$ , but also includes lossy speculative decoding (Tran-Thien, 2023) as a special case:

**Lemma 2.** Algorithm 4 reduces to the lossy speculative sampling procedure in (Tran-Thien, 2023) with parameters  $\alpha$  and  $\beta$  when  $\mathbb{T}(q, p)(v) = \max\{\min\{q(v), \frac{p(v)}{1-\alpha}\}, \frac{p(v)}{\beta}\}$ .

#### 4.2 From Sequential to Speculative Cascades

Equipped with Algorithm 4, we now propose new cascading techniques that implement their deferral rule in a speculative manner. Recall from §3.1 that a token-level cascade of two models q and p is defined by a deferral rule  $r: \mathcal{V}^{t-1} \to \{0,1\}$ . For a prefix  $x_{< t}$ , the next-token distribution at position

# Algorithm 1 SpecDecode

```
Input: Models q, p, Prefix x_{< t}, Block size \gamma \mathbb{T}(q, p) \doteq p Output: GenSpecSample(q, p, \mathbb{T}, x_{< t}, \gamma)
```

### Algorithm 2 TokenCascade

```
Input: Models q, p, Deferral logic \delta, Prefix x_{< t} q_t(\cdot) \doteq q(\cdot|x_{< t}) if \delta(q_t, \emptyset) = 0 then Sample x_t \sim q_t(\cdot) else p_t(\cdot) \doteq p(\cdot|x_{< t}); Sample x_t \sim p_t(\cdot) end if Output: x_t
```

## Algorithm 3 OracleCascade

```
Input: Models q, p, Deferral logic \delta, Prefix x_{< t} q_t(\cdot) \doteq q(\cdot|x_{< t}); \quad p_t(\cdot) \doteq p(\cdot|x_{< t}) if \delta(q_t, p_t) = 0 then Sample x_t \sim q_t(\cdot) else Sample x_t \sim p_t(\cdot) end if Output: x_t
```

## Algorithm 4 GenSpecSample

```
Input: Models q, p, Target distr. \mathbb{T}, Prefix x_{< t}, Block size \gamma [\gamma] \equiv \{0, \dots, \gamma\}

Sample \gamma tokens auto-regressively from q

for j = 0 to \gamma - 1 do

q_{t+j}(\cdot) \doteq q(\cdot|x_{< t+j}); \quad x_{t+j} \sim q_{t+j}(\cdot)

end for

Run p in parallel to score \gamma draft tokens

p_{t+j}(\cdot) \doteq p(\cdot|x_{< t+j}), \ \forall j \in [\gamma]

\pi_{t+j} = \mathbb{T}(q_{t+j}, p_{t+j})

Find the earliest draft token that gets rejected

a_j \sim \text{Ber}\left(\min\left\{1, \frac{\pi_{t+j}(x_{t+j})}{q_{t+j}(x_{t+j})}\right\}\right), \ \forall j \in [\gamma - 1]; \quad a_\gamma = 0

j^* = \min\{j \in [\gamma] : a_j = 0\}

Sample a new token from residual distribution

a_j(\cdot) = \int \text{norm}(\max\{0, \pi_{t+j^*}(\cdot) - q_{t+j^*}(\cdot)\}) \quad \text{if } j^* < 0
```

$$p_{\text{res}}(\cdot) = \begin{cases} \text{norm}(\max\{0, \pi_{t+j^*}(\cdot) - q_{t+j^*}(\cdot)\}) & \text{if } j^* < \gamma \\ \pi_{t+\gamma}(\cdot) & \text{else} \end{cases}$$
Sample  $x_{t+j^*} \sim p_{\text{res}}(\cdot)$ 

Output:  $x_t, \ldots, x_{t+j^*}$ 

## Algorithm 5 SpecCascade

```
Input: Models q, p, Deferral logic \delta, Prefix x_{< t}, Block size \gamma \mathbb{T}_{\delta}(q,p) \doteq (1-\delta(q,p)) \cdot q + \delta(q,p) \cdot p Output: GenSpecSample(q,p,\mathbb{T}_{\delta},x_{< t},\gamma)
```

t modeled by this cascade can be written as:

$$\pi(v) = (1 - r(x_{< t})) \cdot q_t(v) + r(x_{< t}) \cdot p_t(v).$$

In fact, for all the deferral rules described in §2, the resulting distribution can be described by a target distribution function  $\mathbb{T}_{\delta}$  of the form:

$$\mathbb{T}_{\delta}(q,p)(v) = (1 - \delta(q,p)) \cdot q(v) + \delta(q,p) \cdot p(v), \tag{6}$$

for some function  $\delta: \Delta_{\mathcal{V}} \times \Delta_{\mathcal{V}} \to \{0,1\}$  that maps distributions (q,p) to a binary decision. For example, for Chow,  $\delta(q,p) = \mathbf{1} \Big( \max_v q(v) < 1 - \alpha \Big)$ , and for Diff,  $\delta(q,p) = \mathbf{1} \Big( \max_v q(v) < \max_v p(v) - \alpha \Big)$ . See Table 1 for a summary of target distributions for different deferral rules.

Our proposal is to then invoke the speculative sampling procedure in Algorithm 4 with  $\mathbb{T}_{\delta}$  as the target distribution function. We outline this generic *speculative cascading* approach in Algorithm 5, and contrast it with the sequential execution of a deferral rule in Algorithm 2.

**Remark 2** (Exact implementation of oracle deferral rule Diff). In a sequential cascade, the large model's distribution p cannot be used at the time the deferral decision is made (see Remark 1), as this would defeat the purpose of the cascade. With a speculative cascade, however, we can employ rules like Diff that depend on both q and p. This is because we run the large model p in parallel on drafts generated by the small model q, allowing us to compute both  $p(\cdot)$  and  $q(\cdot)$  on every prefix.

So far we have considered deferral rules designed for sequential cascades. In what follows, we derive the optimal deferral rule r for a speculative cascade, where we sample speculatively from a target distribution  $\pi = (1 - r(x_{< t})) \cdot q_t + r(x_{< t}) \cdot p_t$  using  $q_t$  as the drafter.

#### 4.3 OPTIMAL SPECULATIVE CASCADE DEFERRAL

We seek a deferral rule  $r: \mathcal{V}^{t-1} \to \{0,1\}$  that trades-off between quality and inference cost. As with §2, we measure quality in terms of the loss incurred against the ground-truth distribution. The inference cost, on the other hand, crucially depends on how frequently a draft token is rejected in the verification phase, triggering a rollback. To this end, we seek to minimize the expected loss from the deferral rule subject to a constraint on the resulting rejection rate. More specifically, (i) we show

that the rejection rate can be computed using a simple closed-form expression (Lemma 3); (ii) we formulate a constrained optimization objective (7) and the corresponding the Lagrangian (8); (iii) we derive the optimal deferral rule that minimizes the Lagrangian (Lemma 4), approximate it with a plug-in rule (10), and provide a regret bound guarantee for the approximation (Lemma 5).

**Lemma 3.** For a given prefix  $x_{< t}$ , and target distribution  $\pi = (1 - r(x_{< t})) \cdot q_t + r(x_{< t}) \cdot p_t$ , the probability of a token drawn from draft distribution  $q_t$  being rejected is equal to:  $r(x_{< t}) \cdot D_{\text{TV}}(p_t, q_t)$ , where  $D_{\text{TV}}(p, q) = \sum_{v \in \mathcal{V}} \max\{0, p(v) - q(v)\}$  is the TV distance between p and q.

Intuitively, whenever  $r(x_{< t}) = 0$ ,  $\pi(v) = q_t(v)$ , and therefore there is no rejection or roll-back; when  $r(x_{< t}) = 1$ , the rejection rate equals  $D_{\text{TV}}(p_t, q_t)$ .

For a fixed prefix  $x_{\leq t}$ , we formulate the goal of finding a solution to:

$$\min_{r} \mathbb{E}_{v \sim \mathbb{P}(\cdot | x_{< t})} \Big[ \Big( 1 - r(x_{< t}) \Big) \cdot \ell(v, q_t) + r(x_{< t}) \cdot \ell(v, p_t) \Big) \Big] \text{ s.t. } r(x_{< t}) \cdot D_{\text{TV}}(p_t, q_t) \leq B, \quad (7)$$

for some budget B > 0. Equivalently, one may minimize an unconstrained objective similar to equation 3, for suitable cost parameter  $\alpha > 0$  (see §C.4):

$$L_{\text{spec}}(r; x_{< t}) = \mathbb{E}_{v \sim \mathbb{P}(\cdot \mid x_{< t})} \left[ \left( 1 - r(x_{< t}) \right) \cdot \ell(v, q_t) + r(x_{< t}) \cdot \left( \ell(v, p_t) + \alpha \cdot D_{\text{TV}}(p_t, q_t) \right) \right], \quad (8)$$

Contrasting equation 8 with the deferral risk in equation 3 for a sequential cascade, a key difference is that the cost of deferring to the larger model is *no longer a constant*, but depends on the similarity between  $q_t$  and  $p_t$ , as measured by the TV distance between them.

We next derive the optimal deferral rule for equation 8, and construct a feasible estimator for it.

**Lemma 4** (Optimal deferral for speculative cascades). *The minimizer of equation 8 is of the form:* 

$$r^*(x_{< t}) = 1 \iff \mathbb{E}_{v \sim \mathbb{P}(\cdot | x_{< t})} \left[ \ell(v, q_t) \right] > \mathbb{E}_{v \sim \mathbb{P}(\cdot | x_{< t})} \left[ \ell(v, p_t) \right] + \alpha \cdot D_{\text{TV}}(p_t, q_t). \tag{9}$$

When  $p_t$  and  $q_t$  are similar, the rejection rate for  $q_t$  is low, and hence the deferral decision will depend largely on which of the two models yields a lower expected loss. When  $p_t$  and  $q_t$  are very different, the optimal decision is to defer to  $p_t$  only when it yields a substantially lower loss than  $q_t$ .

*Plug-in estimator for equation* 9. The optimal rule requires estimating expectations with respect the ground-truth distribution  $\mathbb{P}(\cdot|x_{< t})$ . We employ similar plug-in estimators as the ones used with sequential cascades (§3). When  $\ell = \ell_{0-1}$ , we replace the expected 0-1 loss with (one minus) the maximum probability from the model, giving us:

$$\hat{r}_{\text{OPT}}(x_{< t}) = 1 \iff \max_{v} q_t(v) < \max_{v} p_t(v) - \alpha \cdot D_{\text{TV}}(p_t, q_t).$$
(10)

The efficacy of the plug-in estimator depends on how closely the individual models approximate the ground-truth distribution  $\mathbb{P}(\cdot|x_{\leq t})$ ; this is formalized by the following regret bound:

**Lemma 5** (Regret bound for  $\hat{r}_{OPT}$ ). Suppose  $\ell = \ell_{0-1}$ . Then for a fixed prefix  $x_{< t}$ :

$$L_{\operatorname{spec}}(\hat{r}_{\operatorname{OPT}}; x_{< t}) - \min_{r} \ L_{\operatorname{spec}}(r; x_{< t}) \ \leq \ \max_{v \in \mathcal{V}} \left| \mathbb{P}(v|x_{< t}) - q_t(v) \right| \ + \ \max_{v \in \mathcal{V}} \left| \mathbb{P}(v|x_{< t}) - p_t(v) \right|.$$

One can now run the speculative cascading procedure in Algorithm 5 using equation 10 as the deferral rule; the corresponding  $\delta(\cdot)$  is listed in Table 1. See §C.2 for a similar derivation for  $\ell = \ell_{\log}$ .

#### 4.4 TOKEN-SPECIFIC SPECULATIVE CASCADES

The plug-in deferral rules in (5) and (10) decide between the drafter's distribution  $q_t(\cdot)$  and the verifier's distribution  $p_t(\cdot)$  by comparing their maximum token probabilities. A downside to this approach is that the draft token  $x_t \sim q_t(\cdot)$  may not maximize  $q_t(\cdot)$ . Thus, even when  $x_t$  is of poor quality, we may end up accepting it because  $q_t$  happens to be *more peaked* than  $p_t$ .

To alleviate this problem, we propose the use of token-specific deferral rules  $r: \mathcal{V}^{t-1} \times \mathcal{V} \to \{0,1\}$  that use both the prefix  $x_{< t}$  and a candidate token v to provide a binary decision  $r(x_{< t},v) \in \{0,1\}$ , with 0 indicating that the token is of acceptable quality. We may then construct a target distribution of the following form:

$$\pi_{\text{Token}}(v) = q_t(v) \cdot (1 - r(x_{\le t}, v)) + p_t(v) \cdot \eta, \tag{11}$$

379

380

381

382

384

386 387

388

389

390

391

392

393

394

395

396 397

398

399 400

401 402

403

404

405

406

407

408

409

410

411

412

413

414

415

416 417

418

419

420

421

422

423

424

425 426 427

428

429

430

431

where  $\eta = \sum_{v' \in \mathcal{V}} r(x_{< t}, v') \cdot q_t(v')$  is a normalizing term chosen to ensure that  $\sum_v \pi_{\mathtt{Token}}(v) = 1$ . This target distribution closely mimics  $q_t(\cdot)$  on tokens that the deferral rule r deems to be of acceptable quality, and defers to  $p_t(\cdot)$  otherwise. One can modify the generic speculative sampling algorithm in Algorithm 4 to use  $\pi_{\text{Token}}$  as the target distribution, as shown in Algorithm 6 in §D.

To design r, we propose a heuristic variant of the Diff rule in equation 4 that compares the expected 0-1 loss from the candidate token v with the expected 0-1 loss from distribution  $p_t$  (in §D, we discuss deriving a similar variant of the OPT rule in equation 9):

$$r(x_{< t}, v) = 1 \iff 1 - \mathbb{P}(v|x_{< t}) > \mathbb{E}_{v \sim \mathbb{P}(\cdot|x_{< t})} [\ell_{0-1}(v, p_t)] + \alpha,$$
 (12)

for a cost parameter  $\alpha$ . The following are some simple plug-in approximations to equation 12:

$$\hat{r}_{\text{TokenV1}}(x_{< t}, v) = 1 \iff q_t(v) < \max_{v'} p_t(v') - \alpha$$

$$\hat{r}_{\text{TokenV2}}(x_{< t}, v) = 1 \iff p_t(v) < \max_{v'} p_t(v') - \alpha$$
(13)

$$\hat{r}_{\text{TokenV2}}(x_{< t}, v) = 1 \iff p_t(v) < \max_{v'} p_t(v') - \alpha$$
(14)

$$\hat{r}_{\text{TokenV3}}(x_{< t}, v) = 1 \iff p_t(v) < \max_{v'} p_t(v') \cdot (1 - \alpha), \tag{15}$$

where we approximate  $\mathbb{P}(v|x_{< t})$  with either  $q_t(v)$  or  $p_t(v)$ . Equation 15 is a multiplicative plug-in approximation that has similarities to the rejection criterion used by Leviathan et al. (2023) for lossy speculative greedy decoding, and results in an intuitive target distribution:

$$\pi_{\texttt{TokenV3}}(v) = q_t(v) \cdot \mathbf{1} \big( v \in \texttt{Top}_{\alpha} \big) + p_t(v) \cdot \sum_{v' \notin \texttt{Top}} q_t(v'),$$

where  $\operatorname{Top}_{\alpha} = \{v \in \mathcal{V} : p_t(v) \geq \max_{v'} p_t(v') \cdot (1 - \alpha)\}$  is the set of top ranked tokens by  $p_t(\cdot)$ . For these top-ranked tokens,  $\pi_{\text{TokenV3}}$  approximates  $q_t(\cdot)$ ; for the rest, it is a re-scaled version of  $p_t(\cdot)$ .

## FURTHER RELATED WORK AND CONCLUSIONS

There has been a stream of work on improving the draft generation process in speculative decoding; these include having the drafter and verifier share the same backbone (Stern et al., 2018; Kim et al., 2024; Cai et al., 2024; Monea et al., 2023; Hooper et al., 2023; Zhang et al., 2023; Elhoushi et al., 2024; Liu et al., 2024), using multiple small draft models Chen et al. (2023c); Wang et al. (2024), using tree-structured draft batches (Spector & Re, 2023; Miao et al., 2024), distilling the drafter with the verifier (Zhou et al., 2024), and leveraging multiple sampled draft candidates Sun et al. (2024).

The work that is most closely related to our specific proposal is the Big Little Decoder (BiLD) (Kim et al., 2023), which can be seen as another lossy variant of speculative decoding (Leviathan et al., 2023; Tran-Thien, 2023; Zhou et al., 2024). BiLD has two phases: a fallback phase, during which the drafter q is run auto-regressively until its maximum predicted probability is sufficiently low; and a rollback phase, during which the verifier p is run in parallel on the prefixes generated by q and rolls back to the point where  $D(q, p) > \alpha$ , for a metric D that measures discrepancy and threshold  $\alpha$ . The fallback phase implements Chow's deferral rule in (2), and allows for the draft window size to vary dynamically based on an estimate of how likely the draft tokens will be accepted; the rollback phase can be seen as a deterministic variant of the rejection sampling algorithm of Leviathan et al. (2023).

An advantage of BiLD over the rejection sampling algorithm in (Leviathan et al., 2023) is the use of Chow's rule to vary the draft window size. However, the final target distribution it seeks to mimic,  $\mathbb{T}_{BiLD}(q, p)(v) = \mathbf{1}(D(q, p) \le \alpha) \cdot q(v) + \mathbf{1}(D(q, p) > \alpha) \cdot p(v)$ , is an approximation to p; specifically, the target distribution  $\pi = \mathbb{T}_{BiLD}(q,p)$  is chosen to satisfy  $D(\pi,p) \leq \alpha$ . Hence, in cases where q deviates substantially from p, BiLD would choose p as the target distribution, even when qoffers better quality on a prefix (where quality can be measured using a suitable loss function). In contrast, our proposed approach in §4 uses speculative decoding to approximate target distributions that seek to optimally cascade between q and p. In our experiments, we compare the efficacy of using  $\mathbb{T}_{BiLD}$  as the target distribution with the target distributions we propose in this paper (see Table 1).

## EXPERIMENTAL RESULTS

We compare our speculative cascading techniques with both sequential cascades and standard speculative decoding on a range of language benchmarks, including translation, reasoning, coding, QA, etc. We evaluate speculative cascades constructed from both the T5 v1.1 family of encoderdecoder models (Raffel et al., 2020a), and Gemma v2 decoder-only models (Team et al., 2024).

Table 2: Reduction in latency ( $T=1, \gamma=5$ ) when matching the quality of the large model (cols 2–7), and the best quality metric without exceeding the latency of the large model (cols 8–13). Quality is measured in terms of the BLEU for WMT and ROUGE-2 for XSum and CNNDM. See Figure 2 for T=0.5 and §E.2 for T=0. We have the baselines in rows 1–4, the proposed method with old deferral rules (§3) in rows 5–6, and the proposed method with new deferral rules (§4) in rows 7–8.

Method	Latency↓ when matching large model's quality				Best quality without exceeding large model's latency							
	Small → Large		$Small \rightarrow XL$		$Small \rightarrow Large$		$Small \rightarrow XL$					
	WMT	XSum	CNNDM	WMT	XSum	CNNDM	WMT	XSum	CNNDM	WMT	XSum	CNNDM
SeqCascade [Chow]	1.55×	0.84×	0.98×	2.46×	0.93×	0.94×	16.56	12.97	9.91	16.29	16.40	11.18
TokenCascade [Chow]	$1.03 \times$	$0.93 \times$	$1.40 \times$	1.46×	$0.82 \times$	1.51×	16.52	13.30	10.36	16.65	17.09	11.44
SpecDecode [Lossy]	1.61×	1.10×	1.57×	2.17×	$1.28 \times$	$2.07 \times$	17.26	13.90	10.43	16.94	17.36	11.53
BiLD*	1.34×	$1.04 \times$	1.38×	1.85×	$1.28 \times$	$1.84 \times$	16.49	13.81	10.14	15.90	17.35	11.35
SpecCascade [Chow]	1.43×	1.04×	1.41×	2.01×	1.28×	1.97×	17.76	13.82	10.28	16.35	17.36	11.39
SpecCascade [Diff]	1.79×	$1.17 \times$	1.75×	$2.44 \times$	$1.30 \times$	2.15×	18.04	14.00	10.64	18.07	17.37	11.67
SpecCascade [OPT]	1.95×	1.17×	1.80×	2.61×	1.34×	2.21×	18.33	14.10	10.86	18.09	17.48	11.85
SpecCascade [Token]	$1.85 \times$	1.18×	$1.89 \times$	$2.50 \times$	$1.40 \times$	1.89×	22.50	15.85	12.63	22.70	18.79	12.63




Figure 2: Latency-quality trade-off plots for methods that interleave T5-small with T5-large ( $\gamma = 5$ ). Latency is measured *relative* to that of calling T5-large on all inputs. The horizontal dotted line denotes the quality of T5-large. §E.3–E.4 contain more plots with varying temperatures and  $\gamma$ .

Cascades versus SpecDecode evaluation. Our evaluation protocol is markedly different from the standard evaluation of speculative decoding algorithms, where the goal is to speed up inference with a large model while preserving its output distribution. In contrast, our focus is on **trading-off** quality for lower inference costs by cascading two models of different sizes. We also **do not** claim to develop a new state-of-the-art method for fast LM inference. Furthermore, the speculative cascades we design build on the original speculative decoding algorithm Leviathan et al. (2023). While one could potentially also adapt our proposal to other recent variants of speculative decoding (Cai et al., 2024; Li et al., 2024b), these involve a wholly orthogonal suite of techniques to what we propose (such as architectural changes, allowing for multiple drafts, distillation, and so on; see §5).

**Proposed methods and baselines.** We evaluate our proposed speculative cascades with four deferral rules: (i) Chow in (2), (ii) Diff in (5), (iii) OPT in (10), and (iv) the Token-specific rule in (15). Of these, (i) and (ii) are existing deferral rules, while (iii) and (iv) are new rules we propose. We also present results for the V1 and V2 variants of the token-specific rules in §E.7.

We compare these with the following cascading and speculative decoding baselines:

- (i) Sequence-level cascade (Jitkrittum et al., 2023; Gupta et al., 2024) based on sequence-level Chow's rule in equation 1 (SeqCascade [Chow]).
- (ii) *Token-level cascade* outlined in Algorithm 2, with token-level Chow's rule in equation 2 used for deferral (Chow, 1970; Gupta et al., 2022) (TokenCascade [Chow]).
- (iii) Lossy speculative decoding described in §2, with both  $\beta = 1$  (Leviathan et al., 2023; Zhou et al., 2024) (SpecDecode [Lossy]) and  $\beta$  tuned using the procedure in Tran-Thien (2023) (Lossy\*).
- (iv) Big-Little Decoder approach (Kim et al., 2023), with both the original deterministic version (BiLD), and the variant where we apply Algorithm 4 to the target distribution  $\mathbb{T}_{BiLD}$  in §5 (BiLD\*).

**Fine-tuned T5 cascades.** Our experiments on T5 models are based on the setup in Zhou et al. (2024); see §E.1 for details. We use T5-small (77M) as the small model, and either T5-large (800M) or T5-XL (3B) as the large model. In each case, we supervised fine-tune these models on three tasks: WMT




Figure 3: Plots of quality vs. rejection rate for methods that interleave Gemma 2B with Gemma 27B ( $\gamma = 1$ ). We use instruction-tuned models; for MBPP we report additional results with pre-trained models. See §E.7 for remaining plots, comparison to (13–14) and results on 2B  $\rightarrow$  9B cascades.

EN $\rightarrow$ DE translation (Bojar et al., 2014a), CNN/DM summarization (Hermann et al., 2015), and XSum abstractive summarization (Narayan et al., 2018). We use temperatures T=0,0.1,0.5,1.0, and block sizes  $\gamma=3,5,7$  (full results in §E). Following the protocol in Leviathan et al. (2023); Zhou et al. (2024), to measure latency, we evaluate the wall-clock decoding time with batch size 1.

In Figure 2, we present plots of quality vs. latency for the different methods. In each case, we vary the lenience parameter  $\alpha$ , and plot either the BLEU or ROUGE-2 metric as a function of the relative latency to the larger model. For brevity, we include the three main baselines; in §E.5–E.6, we compare to SpecDecode [Lossy\*] (Tran-Thien, 2023) and the original BiLD algorithm Kim et al. (2023). Methods that use speculative execution are considerably faster than sequential token-level cascades (TokenCascade [Chow]), although sequential cascades do have an advantage in the low-latency regimes. This is because unlike speculative approaches, which always call the large model after every  $\gamma$  steps, a sequential cascade only invokes the large model when the small model defers.

In Table 2, we report (i) the reduction in latency from T5 cascades when matching the quality of the large model, and (ii) the best quality that each method can deliver without exceeding the latency of the large model. SpecCascade [Token] often yields the highest speed-up and the best quality metrics, with OPT coming in second. The cascading approaches are often seen to fare poorly on both quality and latency metrics, with the exception of WMT, where SeqCascade yields non-trivial speed-ups. The reason the Token-specific rule fares better than OPT and Diff is because the latter compute their deferral decisions based on which of  $q_t(\cdot)$  and  $p_t(\cdot)$  is more peaked; this can be a disadvantage when the sampled token is not close to the distribution mode, which is likely to happen with higher temperatures. As shown in §E.3, with lower temperatures, the gap between these rules diminishes.

**Few-shot Gemma cascades.** To evaluate the Gemma model cascades, we use few-shot prompting with 8 language benchmarks: WMT, CNN/DM, GSM8K, MBPP, SQuAD 2.0, WebQuestions, NaturalQA and TriviaQA; many of these feature in the SpecBench suite (Xia et al., 2024b). Figure 3 presents plots of quality vs. rejection rate with a 2B drafter and 27B verifier for  $\gamma=1$ . For brevity, we only compare the methods that fare the best in the previous experiments. With the exception of TriviaQA, SpecCascade [Token] is able to both match the 27B's quality at a lower rejection rate and yield the best overall quality, often better than 27B. Since all three methods use the exact same implementation for speculative execution, a lower rejection rate directly translates to a lower latency.

Interestingly, OPT is not as effective as with T5. We attribute this to the differences in distributions between the two setups: with T5, the maximum token probability served as a good indicator of token accuracy for both q and p; with Gemma, we expect the large model to have a closer alignment with the ground-truth distribution (due to it being several billion parameters apart from the smaller model), and hence using the large model probabilities to measure confidence for both the small and large model (15) yields better trade-offs than comparing the modes from the two model distributions.

### REFERENCES

- Rohan Anil and et al. PaLM 2 technical report, 2023.
- Jacob Austin, Augustus Odena, Maxwell Nye, Maarten Bosma, Henryk Michalewski, David Dohan, Ellen Jiang, Carrie Cai, Michael Terry, Quoc Le, et al. Program synthesis with large language models. *arXiv preprint arXiv:2108.07732*, 2021.
- Jonathan Berant, Andrew Chou, Roy Frostig, and Percy Liang. Semantic parsing on freebase from question-answer pairs. In *Proceedings of the 2013 conference on empirical methods in natural language processing*, pp. 1533–1544, 2013.
- Sidney Black, Stella Biderman, Eric Hallahan, Quentin Anthony, Leo Gao, Laurence Golding, Horace He, Connor Leahy, Kyle McDonell, Jason Phang, Michael Pieler, Usvsn Sai Prashanth, Shivanshu Purohit, Laria Reynolds, Jonathan Tow, Ben Wang, and Samuel Weinbach. GPT-NeoX-20B: An open-source autoregressive language model. In Angela Fan, Suzana Ilic, Thomas Wolf, and Matthias Gallé (eds.), *Proceedings of BigScience Episode #5 Workshop on Challenges & Perspectives in Creating Large Language Models*, pp. 95–136, virtual+Dublin, May 2022. Association for Computational Linguistics. doi: 10.18653/v1/2022.bigscience-1.9. URL https://aclanthology.org/2022.bigscience-1.9.
- Ondrej Bojar, Christian Buck, Christian Federmann, Barry Haddow, Philipp Koehn, Johannes Leveling, Christof Monz, Pavel Pecina, Matt Post, Herve Saint-Amand, Radu Soricut, Lucia Specia, and Ale s Tamchyna. Findings of the 2014 workshop on statistical machine translation. In *Proceedings of the Ninth Workshop on Statistical Machine Translation*, pp. 12–58, Baltimore, Maryland, USA, June 2014a. Association for Computational Linguistics. URL http://www.aclweb.org/anthology/W/W14/W14-3302.
- Ondřej Bojar, Christian Buck, Christian Federmann, Barry Haddow, Philipp Koehn, Johannes Leveling, Christof Monz, Pavel Pecina, Matt Post, Herve Saint-Amand, et al. Findings of the 2014 workshop on statistical machine translation. In *Proceedings of the ninth workshop on statistical machine translation*, pp. 12–58, 2014b.
- Tom Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared D Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, Sandhini Agarwal, Ariel Herbert-Voss, Gretchen Krueger, Tom Henighan, Rewon Child, Aditya Ramesh, Daniel Ziegler, Jeffrey Wu, Clemens Winter, Chris Hesse, Mark Chen, Eric Sigler, Mateusz Litwin, Scott Gray, Benjamin Chess, Jack Clark, Christopher Berner, Sam McCandlish, Alec Radford, Ilya Sutskever, and Dario Amodei. Language models are few-shot learners. In H. Larochelle, M. Ranzato, R. Hadsell, M. F. Balcan, and H. Lin (eds.), *Advances in Neural Information Processing Systems*, volume 33, pp. 1877–1901. Curran Associates, Inc., 2020.
- Tianle Cai, Yuhong Li, Zhengyang Geng, Hongwu Peng, Jason D Lee, Deming Chen, and Tri Dao. Medusa: Simple LLM inference acceleration framework with multiple decoding heads. *arXiv* preprint arXiv:2401.10774, 2024.
- Charlie Chen, Sebastian Borgeaud, Geoffrey Irving, Jean-Baptiste Lespiau, Laurent Sifre, and John Jumper. Accelerating large language model decoding with speculative sampling. *arXiv preprint arXiv:2302.01318*, 2023a.
- Lingjiao Chen, Matei Zaharia, and James Zou. FrugalGPT: How to use large language models while reducing cost and improving performance, 2023b.
- Ziyi Chen, Xiaocong Yang, Jiacheng Lin, Chenkai Sun, Jie Huang, and Kevin Chen-Chuan Chang. Cascade speculative drafting for even faster LLM inference. *arXiv preprint arXiv:2312.11462*, 2023c.
- C Chow. On optimum recognition error and reject tradeoff. *IEEE Transactions on information theory*, 16(1):41–46, 1970.
- Aakanksha Chowdhery, Sharan Narang, Jacob Devlin, Maarten Bosma, Gaurav Mishra, Adam Roberts, Paul Barham, Hyung Won Chung, Charles Sutton, Sebastian Gehrmann, Parker Schuh, Kensen Shi, Sasha Tsvyashchenko, Joshua Maynez, Abhishek Rao, Parker Barnes, Yi Tay, Noam

Shazeer, Vinodkumar Prabhakaran, Emily Reif, Nan Du, Ben Hutchinson, Reiner Pope, James Bradbury, Jacob Austin, Michael Isard, Guy Gur-Ari, Pengcheng Yin, Toju Duke, Anselm Levskaya, Sanjay Ghemawat, Sunipa Dev, Henryk Michalewski, Xavier Garcia, Vedant Misra, Kevin Robinson, Liam Fedus, Denny Zhou, Daphne Ippolito, David Luan, Hyeontaek Lim, Barret Zoph, Alexander Spiridonov, Ryan Sepassi, David Dohan, Shivani Agrawal, Mark Omernick, Andrew M. Dai, Thanumalayan Sankaranarayana Pillai, Marie Pellat, Aitor Lewkowycz, Erica Moreira, Rewon Child, Oleksandr Polozov, Katherine Lee, Zongwei Zhou, Xuezhi Wang, Brennan Saeta, Mark Diaz, Orhan Firat, Michele Catasta, Jason Wei, Kathy Meier-Hellstern, Douglas Eck, Jeff Dean, Slav Petrov, and Noah Fiedel. PaLM: Scaling language modeling with pathways, 2022.

- Hyung Won Chung, Le Hou, Shayne Longpre, Barret Zoph, Yi Tay, William Fedus, Eric Li, Xuezhi Wang, Mostafa Dehghani, Siddhartha Brahma, Albert Webson, Shixiang Shane Gu, Zhuyun Dai, Mirac Suzgun, Xinyun Chen, Aakanksha Chowdhery, Sharan Narang, Gaurav Mishra, Adams Yu, Vincent Zhao, Yanping Huang, Andrew Dai, Hongkun Yu, Slav Petrov, Ed H. Chi, Jeff Dean, Jacob Devlin, Adam Roberts, Denny Zhou, Quoc V. Le, and Jason Wei. Scaling instruction-finetuned language models, 2022. URL https://arxiv.org/abs/2210.11416.
- Karl Cobbe, Vineet Kosaraju, Mohammad Bavarian, Mark Chen, Heewoo Jun, Lukasz Kaiser, Matthias Plappert, Jerry Tworek, Jacob Hilton, Reiichiro Nakano, et al. Training verifiers to solve math word problems. arXiv preprint arXiv:2110.14168, 2021.
- Dujian Ding, Ankur Mallick, Chi Wang, Robert Sim, Subhabrata Mukherjee, Victor Rühle, Laks V. S. Lakshmanan, and Ahmed Hassan Awadallah. Hybrid LLM: Cost-efficient and quality-aware query routing. In *The Twelfth International Conference on Learning Representations*, 2024. URL https://openreview.net/forum?id=02f3mUtqnM.
- David Dohan, Winnie Xu, Aitor Lewkowycz, Jacob Austin, David Bieber, Raphael Gontijo Lopes, Yuhuai Wu, Henryk Michalewski, Rif A. Saurous, Jascha Sohl-dickstein, Kevin Murphy, and Charles Sutton. Language model cascades, 2022. URL https://arxiv.org/abs/2207.10342.
- Maha Elbayad, Jiatao Gu, Edouard Grave, and Michael Auli. Depth-adaptive transformer. In *International Conference on Learning Representations*, 2020. URL https://openreview.net/forum?id=SJg7KhVKPH.
- Mostafa Elhoushi, Akshat Shrivastava, Diana Liskovich, Basil Hosmer, Bram Wasti, Liangzhen Lai, Anas Mahmoud, Bilge Acun, Saurabh Agarwal, Ahmed Roman, et al. Layer skip: Enabling early exit inference and self-speculative decoding. *arXiv preprint arXiv:2404.16710*, 2024.
- Chuan Guo, Geoff Pleiss, Yu Sun, and Kilian Q. Weinberger. On calibration of modern neural networks. In *Proceedings of the 34th International Conference on Machine Learning Volume 70*, ICML'17, pp. 1321–1330. JMLR.org, 2017.
- Neha Gupta, Jamie Smith, Ben Adlam, and Zelda E Mariet. Ensembles of classifiers: a bias-variance perspective. *Transactions of Machine Learning Research*, 2022. URL https://openreview.net/forum?id=lIOQFVncY9.
- Neha Gupta, Harikrishna Narasimhan, Wittawat Jitkrittum, Ankit Singh Rawat, Aditya Krishna Menon, and Sanjiv Kumar. Language model cascades: Token-level uncertainty and beyond. In *The Twelfth International Conference on Learning Representations*, 2024. URL https://openreview.net/forum?id=KgaBScZ4VI.
- Karl Moritz Hermann, Tomas Kocisky, Edward Grefenstette, Lasse Espeholt, Will Kay, Mustafa Suleyman, and Phil Blunsom. Teaching machines to read and comprehend. *Advances in neural information processing systems*, 28, 2015.
- Coleman Hooper, Sehoon Kim, Hiva Mohammadzadeh, Hasan Genc, Kurt Keutzer, Amir Gholami, and Sophia Shao. Speed: Speculative pipelined execution for efficient decoding. *arXiv preprint arXiv:2310.12072*, 2023.
- Wittawat Jitkrittum, Neha Gupta, Aditya K Menon, Harikrishna Narasimhan, Ankit Rawat, and Sanjiv Kumar. When does confidence-based cascade deferral suffice? *Advances in Neural Information Processing Systems*, 36, 2023.

- Mandar Joshi, Eunsol Choi, Daniel Weld, and Luke Zettlemoyer. TriviaQA: A large scale distantly supervised challenge dataset for reading comprehension. In *Proceedings of the 55th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 1601–1611, Vancouver, Canada, July 2017. Association for Computational Linguistics. doi: 10.18653/v1/P17-1147. URL https://aclanthology.org/P17-1147.
- Leila Khalili, Yao You, and John Bohannon. Babybear: Cheap inference triage for expensive language models, 2022. URL https://arxiv.org/abs/2205.11747.
- Sehoon Kim, Karttikeya Mangalam, Suhong Moon, Jitendra Malik, Michael W Mahoney, Amir Gholami, and Kurt Keutzer. Speculative decoding with big little decoder. In *Thirty-seventh Conference on Neural Information Processing Systems*, 2023.
- Taehyeon Kim, Ananda Theertha Suresh, Kishore Papineni, Michael Riley, Sanjiv Kumar, and Adrian Benton. Towards fast inference: Exploring and improving blockwise parallel drafts. *arXiv preprint arXiv:2404.09221*, 2024.
- Tom Kwiatkowski, Jennimaria Palomaki, Olivia Redfield, Michael Collins, Ankur Parikh, Chris Alberti, Danielle Epstein, Illia Polosukhin, Jacob Devlin, Kenton Lee, Kristina Toutanova, Llion Jones, Matthew Kelcey, Ming-Wei Chang, Andrew M. Dai, Jakob Uszkoreit, Quoc Le, and Slav Petrov. Natural questions: A benchmark for question answering research. *Transactions of the Association for Computational Linguistics*, 7:452–466, 2019. doi: 10.1162/tacl\_a\_00276. URL https://aclanthology.org/Q19-1026.
- Yaniv Leviathan, Matan Kalman, and Yossi Matias. Fast inference from transformers via speculative decoding. In Andreas Krause, Emma Brunskill, Kyunghyun Cho, Barbara Engelhardt, Sivan Sabato, and Jonathan Scarlett (eds.), *Proceedings of the 40th International Conference on Machine Learning*, volume 202 of *Proceedings of Machine Learning Research*, pp. 19274–19286. PMLR, 23–29 Jul 2023. URL https://proceedings.mlr.press/v202/leviathan23a.html.
- Yuhui Li, Fangyun Wei, Chao Zhang, and Hongyang Zhang. EAGLE: Speculative sampling requires rethinking feature uncertainty. In *International Conference on Machine Learning*, 2024a.
- Yuhui Li, Fangyun Wei, Chao Zhang, and Hongyang Zhang. Eagle: Speculative sampling requires rethinking feature uncertainty. *arXiv preprint arXiv:2401.15077*, 2024b.
- Fangcheng Liu, Yehui Tang, Zhenhua Liu, Yunsheng Ni, Kai Han, and Yunhe Wang. Kangaroo: Lossless self-speculative decoding via double early exiting. *arXiv preprint arXiv:2404.18911*, 2024.
- Jonathan Mamou, Oren Pereg, Moshe Wasserblat, and Roy Schwartz. TangoBERT: Reducing inference cost by using cascaded architecture, 2022. URL http://arxiv.org/abs/2204.06271.
- Xupeng Miao, Gabriele Oliaro, Zhihao Zhang, Xinhao Cheng, Zeyu Wang, Zhengxin Zhang, Rae Ying Yee Wong, Alan Zhu, Lijie Yang, Xiaoxiang Shi, et al. Specinfer: Accelerating large language model serving with tree-based speculative inference and verification. In *Proceedings of the 29th ACM International Conference on Architectural Support for Programming Languages and Operating Systems, Volume 3*, pp. 932–949, 2024.
- Giovanni Monea, Armand Joulin, and Edouard Grave. Pass: Parallel speculative sampling. *arXiv* preprint arXiv:2311.13581, 2023.
- Shashi Narayan, Shay B Cohen, and Mirella Lapata. Don't give me the details, just the summary! topic-aware convolutional neural networks for extreme summarization. In *Proceedings of the 2018 Conference on Empirical Methods in Natural Language Processing*, pp. 1797–1807, 2018.
- Reiner Pope, Sholto Douglas, Aakanksha Chowdhery, Jacob Devlin, James Bradbury, Anselm Levskaya, Jonathan Heek, Kefan Xiao, Shivani Agrawal, and Jeff Dean. Efficiently scaling transformer inference, 2022.
- Alec Radford, Karthik Narasimhan, Tim Salimans, Ilya Sutskever, et al. Improving language understanding by generative pre-training. https://cdn.openai.com/research-covers/language-unsupervised/language\_understanding\_paper.pdf, 2018.

- Colin Raffel, Noam Shazeer, Adam Roberts, Katherine Lee, Sharan Narang, Michael Matena, Yanqi Zhou, Wei Li, and Peter J. Liu. Exploring the limits of transfer learning with a unified text-to-text transformer. *J. Mach. Learn. Res.*, 21:140:1–140:67, 2020a. URL http://jmlr.org/papers/v21/20-074.html.
- Colin Raffel, Noam Shazeer, Adam Roberts, Katherine Lee, Sharan Narang, Michael Matena, Yanqi Zhou, Wei Li, and Peter J Liu. Exploring the limits of transfer learning with a unified text-to-text transformer. *Journal of machine learning research*, 21(140):1–67, 2020b.
- Pranav Rajpurkar, Jian Zhang, Konstantin Lopyrev, and Percy Liang. SQuAD: 100,000+ questions for machine comprehension of text. In *Proceedings of the 2016 Conference on Empirical Methods in Natural Language Processing*, pp. 2383–2392, Austin, Texas, November 2016. Association for Computational Linguistics. doi: 10.18653/v1/D16-1264. URL https://aclanthology.org/D16-1264.
- Tal Schuster, Adam Fisch, Jai Gupta, Mostafa Dehghani, Dara Bahri, Vinh Q. Tran, Yi Tay, and Donald Metzler. Confident adaptive language modeling. In Alice H. Oh, Alekh Agarwal, Danielle Belgrave, and Kyunghyun Cho (eds.), *Advances in Neural Information Processing Systems*, 2022. URL https://openreview.net/forum?id=uLYc4L3C81A.
- Ying Sheng, Lianmin Zheng, Binhang Yuan, Zhuohan Li, Max Ryabinin, Beidi Chen, Percy Liang, Christopher Re, Ion Stoica, and Ce Zhang. FlexGen: High-throughput generative inference of large language models with a single GPU. In Andreas Krause, Emma Brunskill, Kyunghyun Cho, Barbara Engelhardt, Sivan Sabato, and Jonathan Scarlett (eds.), *Proceedings of the 40th International Conference on Machine Learning*, volume 202 of *Proceedings of Machine Learning Research*, pp. 31094–31116. PMLR, 23–29 Jul 2023. URL https://proceedings.mlr.press/v202/sheng23a.html.
- Benjamin Spector and Chris Re. Accelerating LLM inference with staged speculative decoding. *arXiv preprint arXiv:2308.04623*, 2023.
- Mitchell Stern, Noam Shazeer, and Jakob Uszkoreit. Blockwise parallel decoding for deep autoregressive models. *CoRR*, abs/1811.03115, 2018. URL http://arxiv.org/abs/1811.03115.
- Ziteng Sun, Ananda Theertha Suresh, Jae Hun Ro, Ahmad Beirami, Himanshu Jain, and Felix Yu. Spectr: Fast speculative decoding via optimal transport. *Advances in Neural Information Processing Systems*, 36, 2024.
- Yi Tay, Mostafa Dehghani, Vinh Q. Tran, Xavier Garcia, Jason Wei, Xuezhi Wang, Hyung Won Chung, Dara Bahri, Tal Schuster, Steven Zheng, Denny Zhou, Neil Houlsby, and Donald Metzler. UL2: Unifying language learning paradigms. In *The Eleventh International Conference on Learning Representations*, 2023. URL https://openreview.net/forum?id=6ruVLB727MC.
- Gemini Team, Rohan Anil, and et al. Gemini: A family of highly capable multimodal models, 2023.
- Gemma Team, Morgane Riviere, Shreya Pathak, Pier Giuseppe Sessa, Cassidy Hardin, Surya Bhupatiraju, Léonard Hussenot, Thomas Mesnard, Bobak Shahriari, Alexandre Ramé, et al. Gemma 2: Improving open language models at a practical size. *arXiv preprint arXiv:2408.00118*, 2024.
- Hugo Touvron, Thibaut Lavril, Gautier Izacard, Xavier Martinet, Marie-Anne Lachaux, Timothée Lacroix, Baptiste Rozière, Naman Goyal, Eric Hambro, Faisal Azhar, Aurelien Rodriguez, Armand Joulin, Edouard Grave, and Guillaume Lample. Llama: Open and efficient foundation language models, 2023.
- Vivien Tran-Thien. An optimal lossy variant of speculative decoding, 2023. URL https://vivienooo.github.io... Unsupervised Thoughts (Blog). URL: https://github.com/vivienooo/mentored\_decoding.
- Neeraj Varshney and Chitta Baral. Model cascading: Towards jointly improving efficiency and accuracy of nlp systems. *arXiv preprint arXiv:2210.05528*, 2022.

- Siqi Wang, Hailong Yang, Xuezhu Wang, Tongxuan Liu, Pengbo Wang, Xuning Liang, Kejie Ma, Tianyu Feng, Xin You, Yongjun Bao, et al. Minions: Accelerating large language model inference with adaptive and collective speculative decoding. *arXiv* preprint arXiv:2402.15678, 2024.
- Xiaofang Wang, Dan Kondratyuk, Eric Christiansen, Kris M Kitani, Yair Alon, and Elad Eban. Wisdom of committees: An overlooked approach to faster and more accurate models. *arXiv* preprint arXiv:2012.01988, 2020.
- Jason Wei, Maarten Bosma, Vincent Zhao, Kelvin Guu, Adams Wei Yu, Brian Lester, Nan Du, Andrew M. Dai, and Quoc V Le. Finetuned language models are zero-shot learners. In *International Conference on Learning Representations*, 2022. URL https://openreview.net/forum?id=gEZrGCozdqR.
- Heming Xia, Zhe Yang, Qingxiu Dong, Peiyi Wang, Yongqi Li, Tao Ge, Tianyu Liu, Wenjie Li, and Zhifang Sui. Unlocking efficiency in large language model inference: A comprehensive survey of speculative decoding, 2024a.
- Heming Xia, Zhe Yang, Qingxiu Dong, Peiyi Wang, Yongqi Li, Tao Ge, Tianyu Liu, Wenjie Li, and Zhifang Sui. Unlocking efficiency in large language model inference: A comprehensive survey of speculative decoding, 2024b.
- Murong Yue, Jie Zhao, Min Zhang, Liang Du, and Ziyu Yao. Large language model cascades with mixture of thought representations for cost-efficient reasoning. In *The Twelfth International Conference on Learning Representations*, 2024. URL https://openreview.net/forum?id=60kaSfANzh.
- Jun Zhang, Jue Wang, Huan Li, Lidan Shou, Ke Chen, Gang Chen, and Sharad Mehrotra. Draft & verify: Lossless large language model acceleration via self-speculative decoding. arXiv preprint arXiv:2309.08168, 2023.
- Yongchao Zhou, Kaifeng Lyu, Ankit Singh Rawat, Aditya Krishna Menon, Afshin Rostamizadeh, Sanjiv Kumar, Jean-François Kagy, and Rishabh Agarwal. Distillspec: Improving speculative decoding via knowledge distillation. In *The Twelfth International Conference on Learning Representations*, 2024. URL https://openreview.net/forum?id=rsy6J3ZaTF.

## A Proofs

#### A.1 PROOF OF LEMMA 1

*Proof.* Expanding the loss in equation 3, we have:

$$L_{\text{def}}(r; x_{< t}) = \left(1 - r(x_{< t})\right) \cdot \mathbb{E}_{x_t \sim \mathbb{P}(\cdot \mid x_{< t})} \left[\ell(x_t, q_t)\right] + r(x_{< t}) \cdot \left(\mathbb{E}_{x_t \sim \mathbb{P}(\cdot \mid x_{< t})} \left[\ell(x_t, p_t)\right] + \alpha\right)$$

$$= r(x_{< t}) \cdot \left(\mathbb{E}_{x_t \sim \mathbb{P}(\cdot \mid x_{< t})} \left[\ell(x_t, p_t)\right] + \alpha - \mathbb{E}_{x_t \sim \mathbb{P}(\cdot \mid x_{< t})} \left[\ell(x_t, q_t)\right]\right) + \mathbb{E}_{x_t \sim \mathbb{P}(\cdot \mid x_{< t})} \left[\ell(x_t, q_t)\right]$$

This objective is minimized by a deferral rule  $r: \mathcal{V}^{t-1} \to \{0,1\}$  that minimizes, for each prefix  $x_{< t}$ , the term within the parenthesis. Therefore the minimizer  $r^*(x_{< t}) = 1$  whenever the term within the parenthesis is negative:

$$\mathbb{E}_{x_t \sim \mathbb{P}(\cdot \mid x_{< t})} \left[ \ell(x_t, p_t) \right] + \alpha - \mathbb{E}_{x_t \sim \mathbb{P}(\cdot \mid x_{< t})} \left[ \ell(x_t, q_t) \right] < 0,$$

and  $r^*(x_{\le t}) = 0$  otherwise. Re-arranging the terms completes the proof.

## A.2 PROOF OF LEMMA 2

*Proof.* The proof follows straight-forwardly from the results in (Tran-Thien, 2023). Recall from  $\S 2$  that the lossy speculative decoding procedure of (Tran-Thien, 2023) accepts a draft token x with probability:

$$\kappa(x) = \min\left\{1, \frac{p(x)}{(1-\alpha) \cdot q(x)}\right\},\tag{16}$$

and replaces a rejected draft token with a token sampled from the residual distribution:

$$p_{\text{res}}(x) = \text{norm}\left(\max\left\{0, \frac{1}{\beta} \cdot p(x) - q(x)\right\}\right),\tag{17}$$

for parameters  $\alpha \in [0,1)$  and  $\beta \geq 1-\alpha$ .

We need to show that running Algorithm 4 with the target distribution:

$$\pi(x) = \max \left\{ \min \left\{ q(x), \frac{p(x)}{1-\alpha} \right\}, \frac{p(x)}{\beta} \right\}$$

results in the same acceptance probability equation 16 and residual distribution equation 17.

The acceptance probability for a draft token x when running Algorithm 4 on  $\pi$  is given by:

$$\kappa^{\pi}(x) = \min\left\{1, \frac{\pi(x)}{q(x)}\right\}.$$

The corresponding residual distribution is given by:

$$p_{\text{res}}^{\pi}(x) = \text{norm} \left( \max \{0, \pi(x) - q(x) \} \right).$$

We consider three possible cases:

Case (i):  $q(x) > \frac{1}{1-\alpha} \cdot p(x) \ge \frac{1}{\beta} \cdot p(x)$ . In this case,  $\pi(x) = \frac{1}{1-\alpha} \cdot p(x)$ . As a result:

$$\kappa^{\pi}(x) = \min\left\{1, \frac{p(x)}{(1-\alpha) \cdot q(x)}\right\} = \kappa(x);$$

$$\begin{split} p_{\text{res}}^{\pi}(x) &= \text{norm}\left(\max\left\{0,\, \frac{1}{1-\alpha}\cdot p(x) - q(x)\right\}\right) \\ &= 0 = \text{norm}\left(\max\left\{0,\, \frac{1}{\beta}\cdot p(x) - q(x)\right\}\right) = p_{\text{res}}(x). \end{split}$$

Case (ii):  $\frac{1}{1-\alpha} \cdot p(x) \ge \frac{1}{\beta} \cdot p(x) > q(x)$ . In this case,  $\pi(x) = \frac{1}{\beta} \cdot p(x)$ . As a result:

$$\kappa^\pi(x) = \min\left\{1, \frac{p(x)}{\beta \cdot q(x)}\right\} = 1 = \min\left\{1, \frac{p(x)}{(1-\alpha) \cdot q(x)}\right\} = \kappa(x);$$

$$p_{\text{res}}^{\pi}(x) = \text{norm}\left(\max\left\{0, \frac{1}{\beta} \cdot p(x) - q(x)\right\}\right) = p_{\text{res}}(x).$$

Case (iii):  $\frac{1}{1-\alpha} \cdot p(x) \ge q(x) \ge \frac{1}{\beta} \cdot p(x)$ . In this case,  $\pi(x) = q(x)$ . As a result:

$$\kappa^{\pi}(x) = 1 = \min\left\{1, \frac{p(x)}{(1-\alpha) \cdot q(x)}\right\} = \kappa(x);$$

$$p_{\text{res}}^{\pi}(x) = 0 = \text{norm}\left(\max\left\{0, \frac{1}{\beta} \cdot p(x) - q(x)\right\}\right) = p_{\text{res}}(x).$$

In all three cases, the acceptance probabilities and residual distributions are identical.

#### A.3 PROOF OF LEMMA 3

 *Proof.* Under a target distribution  $\pi_t$ , the probability of a draft token drawn from  $q_t$  being is rejected is given by (Leviathan et al., 2023):

$$\begin{split} \text{rejection probability} &= \sum_{v \in \mathcal{V}} q_t(v) \cdot \left(1 - \min\left\{1, \frac{\pi_t(v)}{q_t(v)}\right\}\right) \\ &= 1 - \sum_{v \in \mathcal{V}} \min\left\{q_t(v), \pi_t(v)\right\} \\ &= \sum_{v \in \mathcal{V}} \pi_t(v) - \sum_{v \in \mathcal{V}} \min\left\{q_t(v), \pi_t(v)\right\} \\ &= \sum_{v \in \mathcal{V}} \max\left\{0, \pi_t(v) - q_t(v)\right\}. \end{split}$$

Expanding  $\pi$ , the rejection probability becomes:

rejection probability = 
$$\sum_{v \in \mathcal{V}} \max \left\{ 0, \ (1 - r(x_{< t})) \cdot q_t(v) + r(x_{< t}) \cdot p_t(v) - q_t(v) \right\}$$

When  $r(x_{< t}) = 1$ , we have:

$$\text{rejection probability} = \sum_{v \in \mathcal{V}} \min \left\{ 0, \ p_t(v) - q_t(v) \right\} = D_{\text{TV}}(p_t, q_t) = r(x_{< t}) \cdot D_{\text{TV}}(p_t, q_t).$$

When  $r(x_{\leq t}) = 0$ , we have:

rejection probability = 
$$0 = r(x_{< t}) \cdot D_{TV}(p_t, q_t)$$
,

as desired.

#### A.4 PROOF OF LEMMA 4

*Proof.* Expanding the deferral risk in equation 8, we have:

$$\begin{split} L_{\text{spec}}(r; x_{< t}) &= r(x_{< t}) \cdot \left( \mathbb{E}_{x_t \sim \mathbb{P}(\cdot \mid x_{< t})} \left[ \ell(x_t, p_t) \right] + \alpha \cdot D_{\text{TV}}(p_t, q_t) - \mathbb{E}_{x_t \sim \mathbb{P}(\cdot \mid x_{< t})} \left[ \ell(x_t, q_t) \right] \right) \\ &+ \mathbb{E}_{x_t \sim \mathbb{P}(\cdot \mid x_{< t})} \left[ \ell(x_t, q_t) \right]. \end{split}$$

This objective is minimized by a deferral rule  $r: \mathcal{V}^{t-1} \to \{0,1\}$  that minimizes, for each prefix  $x_{< t}$ , the term within the parenthesis. Therefore the minimizer  $r^*(x_{< t}) = 1$  whenever the term within the parenthesis is negative:

$$\mathbb{E}_{x_t \sim \mathbb{P}(\cdot \mid x_{< t})} \left[ \ell(x_t, p_t) \right] + \alpha \cdot D_{\text{TV}}(p_t, q_t) - \mathbb{E}_{x_t \sim \mathbb{P}(\cdot \mid x_{< t})} \left[ \ell(x_t, q_t) \right] < 0,$$

and  $r^*(x_{< t}) = 0$  otherwise. Re-arranging the terms completes the proof.

#### A.5 PROOF OF LEMMA 5

For a fixed prefix  $x_{< t}$ , we can write the deferral risk in equation 8 as:

$$L_{\text{spec}}(r; x_{< t}) = r(x_{< t}) \cdot \left( \mathbb{E}_{x_t \sim \mathbb{P}(\cdot \mid x_{< t})} \left[ \ell(x_t, p_t) \right] + \alpha \cdot D_{\text{TV}}(p_t, q_t) - \mathbb{E}_{x_t \sim \mathbb{P}(\cdot \mid x_{< t})} \left[ \ell(x_t, q_t) \right] \right) + C,$$

where C is a term independent of the deferral rule r. Let  $r^*: \mathcal{V}^{t-1} \to \{0,1\}$  denote the optimal deferral rule that minimizes  $L_{\text{spec}}$  for any prefix  $x_{\leq t}$ . We then have:

$$L_{\text{spec}}(\hat{r}_{\text{OPT}}; x_{< t}) - L_{\text{spec}}(r^*; x_{< t}) \\ = (\hat{r}_{\text{OPT}}(x_{< t}) - r^*(x_{< t})) \cdot \left(\mathbb{E}_{x_t \sim \mathbb{P}(\cdot | x_{< t})} \left[\ell(x_t, p_t)\right] + \alpha \cdot D_{\text{TV}}(p_t, q_t) - \mathbb{E}_{x_t \sim \mathbb{P}(\cdot | x_{< t})} \left[\ell(x_t, q_t)\right]\right).$$

Adding and subtracting  $\max_v q_t(v) - \max_v p_t(v)$  to the term within the second parenthesis, we get:

$$\begin{aligned} & L_{\text{spec}}\left(\hat{r}_{\text{OPT}};x_{< t}\right) - L_{\text{spec}}\left(r^{*};x_{< t}\right) \\ & = \left(\hat{r}_{\text{OPT}}(x_{< t}) - r^{*}(x_{< t})\right) \cdot \left(\max_{v} q_{t}(v) + \alpha \cdot D_{\text{TV}}(p_{t},q_{t}) - \max_{v} p_{t}(v)\right) \\ & + \left(\hat{r}_{\text{OPT}}(x_{< t}) - r^{*}(x_{< t})\right) \cdot \left(\mathbb{E}_{x_{t} \sim \mathbb{P}(\cdot|x_{< t})}\left[\ell(x_{t},p_{t})\right] - \mathbb{E}_{x_{t} \sim \mathbb{P}(\cdot|x_{< t})}\left[\ell(x_{t},q_{t})\right] - \max_{v} q_{t}(v) + \max_{v} p_{t}(v)\right) \\ & = \left(\hat{r}_{\text{OPT}}(x_{< t}) - r^{*}(x_{< t})\right) \cdot \left(\mathbb{E}_{x_{t} \sim \mathbb{P}(\cdot|x_{< t})}\left[\ell(x_{t},p_{t})\right] - \max_{v} q_{t}(v)\right) \\ & + \left(\hat{r}_{\text{OPT}}(x_{< t}) - r^{*}(x_{< t})\right) \cdot \left(\mathbb{E}_{x_{t} \sim \mathbb{P}(\cdot|x_{< t})}\left[\ell(x_{t},p_{t})\right] - 1 + \max_{v} p_{t}(v)\right) \\ & + \left(\hat{r}_{\text{OPT}}(x_{< t}) - r^{*}(x_{< t})\right) \cdot \left(\mathbb{E}_{x_{t} \sim \mathbb{P}(\cdot|x_{< t})}\left[\ell(x_{t},p_{t})\right] - 1 + \max_{v} p_{t}(v)\right) \\ & + \left(\hat{r}_{\text{OPT}}(x_{< t}) - r^{*}(x_{< t})\right) \cdot \left(\max_{v} p_{t}(v) - \mathbb{E}_{x_{t} \sim \mathbb{P}(\cdot|x_{< t})}\left[\ell(x_{t},q_{t})\right]\right) \\ & = \left(\hat{r}_{\text{OPT}}(x_{< t}) - r^{*}(x_{< t})\right) \cdot \left(\mathbb{E}_{x_{t} \sim \mathbb{P}(\cdot|x_{< t})}\left[\ell(x_{t},p_{t})\right] - 1 + \max_{v} p_{t}(v)\right) \\ & + \left|\hat{r}_{\text{OPT}}(x_{< t}) - r^{*}(x_{< t})\right| \cdot \left|\mathbb{E}_{x_{t} \sim \mathbb{P}(\cdot|x_{< t})}\left[\ell(x_{t},p_{t})\right] - 1 + \max_{v} p_{t}(v)\right| \\ & + \left|\hat{r}_{\text{OPT}}(x_{< t}) - r^{*}(x_{< t})\right| \cdot \left|\mathbb{E}_{x_{t} \sim \mathbb{P}(\cdot|x_{< t})}\left[\ell(x_{t},p_{t})\right] - 1 + \max_{v} p_{t}(v)\right| \\ & + \left|\mathbb{E}_{x_{t} \sim \mathbb{P}(\cdot|x_{< t})}\left[\ell(x_{t},p_{t})\right] - 1 + \max_{v} p_{t}(v)\right| \\ & + \left|\mathbb{E}_{x_{t} \sim \mathbb{P}(\cdot|x_{< t})}\left[\ell(x_{t},p_{t})\right] - 1 + \max_{v} p_{t}(v)\right| \\ & + \left|\mathbb{E}_{x_{t} \sim \mathbb{P}(\cdot|x_{< t})}\left[\ell(x_{t},p_{t})\right] - 1 + \max_{v} p_{t}(v)\right| \\ & + \left|\mathbb{E}_{x_{t} \sim \mathbb{P}(\cdot|x_{< t})}\left[\ell(x_{t},p_{t})\right] - 1 + \max_{v} p_{t}(v)\right| \\ & + \left|\mathbb{E}_{x_{t} \sim \mathbb{P}(\cdot|x_{< t})}\left[\ell(x_{t},p_{t})\right] - 1 + \max_{v} p_{t}(v)\right| \\ & + \left|\mathbb{E}_{x_{t} \sim \mathbb{P}(\cdot|x_{< t})}\left[\ell(x_{t},p_{t})\right] - 1 + \max_{v} p_{t}(v)\right| \\ & + \left|\mathbb{E}_{x_{t} \sim \mathbb{P}(\cdot|x_{< t})}\left[\ell(x_{t},p_{t})\right] - 1 + \max_{v} p_{t}(v)\right| \\ & + \left|\mathbb{E}_{x_{t} \sim \mathbb{P}(\cdot|x_{< t})}\left[\ell(x_{t},p_{t})\right] - 1 + \min_{v} p_{t}(v)\right| \\ & + \left|\mathbb{E}_{x_{t} \sim \mathbb{P}(\cdot|x_{< t})}\left[\ell(x_{t},p_{t})\right] - 1 + \min_{v} p_{t}(v)\right| \\ & + \left|\mathbb{E}_{x_{t} \sim \mathbb{P}(\cdot|x_{< t})}\left[\ell(x_{t},p_{t})\right] - 1 + \min_{v} p$$

where we have used the fact that  $|\hat{r}_{\mathtt{OPT}}(x_{< t}) - r^*(x_{< t})| \leq 1$ .

We bound each term separately. For the first term, consider two cases: (i)  $\max_v p_t(v) + \alpha \cdot D_{\text{TV}}(p_t, q_t) - \max_v q_t(v) \leq 0$  and (ii)  $\max_v p_t(v) + \alpha \cdot D_{\text{TV}}(p_t, q_t) - \max_v q_t(v) > 0$ . When (i) holds,  $\hat{r}_{\text{OPT}}(x_{< t}) = 1$ ; so irrespective of whether  $r^*(x_{< t})$  is 0 or 1,

$$\operatorname{term}_{1} \leq \max_{v} p_{t}(v) + \alpha \cdot D_{\text{TV}}(p_{t}, q_{t}) - \max_{v} q_{t}(v) \leq 0$$

When (ii) holds,  $\hat{r}_{\mathtt{OPT}}(x_{< t}) = 0$ ; so irrespective of whether  $r^*(x_{< t})$  is 0 or 1,

$$\operatorname{term}_{1} \leq -\left(\max_{v} p_{t}(v) + \alpha \cdot D_{\text{TV}}(p_{t}, q_{t}) - \max_{v} q_{t}(v)\right) < 0.$$

Thus we have:

$$term_1 < 0. (19)$$

We next move to the second term. Since  $\ell = \ell_{0-1}$ , we have:

$$\begin{aligned} \text{term}_2 &= \left| \mathbb{E}_{x_t \sim \mathbb{P}(\cdot \mid x_{< t})} \left[ \ell(x_t, p_t) \right] - 1 + \max_{v} p_t(v) \right| \\ &= \left| \mathbb{E}_{x_t \sim \mathbb{P}(\cdot \mid x_{< t})} \left[ 1 \left( x_t \neq \arg\max_{v} p_t(v) \right) \right] - 1 + \max_{v} p_t(v) \right| \end{aligned}$$

Inference strategy	Deferral decision $\delta(q,p)$	Target distribution $\pi(x)$	Execution
SpecDecoding Leviathan et al. (2023)	-	p(x)	Speculative
Lossy SpecDecoding (Tran-Thien, 2023)	-	$\max\{\min\{p(x), \frac{q(x)}{1-\alpha}\}, \frac{q(x)}{\beta}\}$	Speculative
BiLD* (Kim et al., 2023)	$1\big(D(q,p) > \alpha\big)$	$(1-\delta)\cdot q(x) + \delta\cdot p(x)$	Speculative
Cascade [Chow] (Chow, 1970)	$1\big(\max_v q(v) < 1 - \alpha\big)$	$(1 - \delta) \cdot q(x) + \delta \cdot p(x)$	Sequential
Cascade [ChowLog]	$1 \big( \operatorname{entropy}(q) > \alpha \big)$	$(1 - \delta) \cdot q(x) + \delta \cdot p(x)$	Sequential
Oracle [Diff] (Jitkrittum et al., 2023)	$1\big(\max_{v} q(v) < \max_{v} p(v) - \alpha\big)$	$(1 - \delta) \cdot q(x) + \delta \cdot p(x)$	Oracle
Oracle [DiffLog]	$1(\operatorname{entropy}(p) < \operatorname{entropy}(q) - \alpha)$	$(1 - \delta) \cdot q(x) + \delta \cdot p(x)$	Oracle
SpecCascade [Chow]	$1\big(\max_{v} q(v) < 1 - \alpha\big)$	$(1 - \delta) \cdot q(x) + \delta \cdot p(x)$	Speculative
SpecCascade [ChowLog]	$1(\text{entropy}(q) > \alpha)$	$(1 - \delta) \cdot q(x) + \delta \cdot p(x)$	Speculative
SpecCascade [Diffo1]	$1\big(\max_{v} q(v) < \max_{v} p(v) - \alpha\big)$	$(1 - \delta) \cdot q(x) + \delta \cdot p(x)$	Speculative
SpecCascade [DiffLog]	$1(\operatorname{entropy}(p) < \operatorname{entropy}(q) - \alpha)$	$(1 - \delta) \cdot q(x) + \delta \cdot p(x)$	Speculative
SpecCascade [0PTo1]	$1(\max_{v} q(v) < \max_{v} p(v) - \alpha \cdot D_{TV}(p,q))$	$(1 - \delta) \cdot q(x) + \delta \cdot p(x)$	Speculative
SpecCascade [OPTLog]	$1$ (entropy(p) < entropy(q) - $\alpha \cdot D_{\text{TV}}(p, q)$ )	$(1 - \delta) \cdot q(x) + \delta \cdot p(x)$	Speculative

Table 3: Target distributions associated with different inference algorithms, where  $\alpha$  is a free parameter and  $\beta \geq 1-\alpha$  is a parameter dependent on q,p and  $\alpha$ . The last column indicates whether the execution is sequential (Algorithm 2), via an oracle (Algorithm 3), or speculative (Algorithm 5) (Leviathan et al., 2023). The third row presents a variant of the BiLD algorithm of Kim et al. (2023), where D(q,p) is a measure of discrepancy between q and p; the original algorithm differs from (Leviathan et al., 2023) in the use of a deterministic speculative decoding procedure with a dynamic draft window (see §5).

$$= \left| \max_{v} p_t(v) - \sum_{x_t} \mathbb{P}(x_t|x_{< t}) \cdot 1 \left( x_t = \arg\max_{v} p_t(v) \right) \right|$$

Suppose  $v^* \in \arg\max_{v} p_t(v)$ , then:

$$\operatorname{term}_{2} = |p_{t}(v^{*}) - \mathbb{P}(v^{*}|x_{< t})| \le \max_{v} |p_{t}(v) - \mathbb{P}(v|x_{< t})|.$$
(20)

Similarly, we can show that:

$$\operatorname{term}_{3} \leq \max_{v} |q_{t}(v) - \mathbb{P}(v|x_{< t})|. \tag{21}$$

Substituting equation 19–equation 21 in equation 18 completes the proof.

## B DERIVATION OF CHOW'S RULE

We show below that Chow's rule is a plug-in estimator to the optimal solution to the following objective

$$L_{\text{rej}}(r; x_{< t}) = \mathbb{E}_{x_t \sim \mathbb{P}(\cdot \mid x_{< t})} \left[ \left( 1 - r(x_{< t}) \right) \cdot \ell(x_t, q_t) + r(x_{< t}) \cdot \alpha \right], \tag{22}$$

where the deferral rule is penalized with a constant penalty  $\alpha \in [0, 1]$  for choosing to defer to the large model.

Following the same steps as Lemma 1, it is easy to show:

**Lemma 6.** The minimizer of equation 22 is of the form:

$$r^*(x_{\leq t}) = 1 \iff \mathbb{E}_{x_t \sim \mathbb{P}(\cdot | x_{\leq t})} \left[ \ell(x_t, q_t) \right] > \alpha. \tag{23}$$

If  $\ell = \ell_{0-1}$ , one may employ a plug-in estimator to equation 23 by replacing the expected 0-1 loss over  $q_t$  with  $1 - \max_v q_t(v)$ , giving us  $\hat{r}_{\mathsf{Chow}}(x_{< t})$  in equation 2. If  $\ell = \ell_{\log}$ , one may replace the expected log loss over  $q_t$  with the entropy of  $q_t$ , giving us:

$$\hat{r}_{\mathsf{ChowLog}}(x_{< t}) = 1 \iff \mathsf{entropy}(q(\cdot|x_{< t})) > \alpha,$$
 (24)

where  $\operatorname{entropy}(q) = -\sum_{v \in \mathcal{V}} q(v) \cdot \log(q(v))$ .

## C OPTIMAL DEFERRAL: ADDITIONAL DISCUSSION

We provide additional discussion for the optimal deferral rules derived in §3 and §4.

 $_{1031}$  C.1 Optimal sequential deferral when  $\ell=\ell_{\mathrm{log}}$ 

Recall that the optimal deferral rule for a sequential cascade in Lemma 1 takes the form:

$$r^*(x_{< t}) = 1 \iff \mathbb{E}_{x_t \sim \mathbb{P}(\cdot \mid x_{< t})} \left[ \ell(x_t, q_t) \right] > \mathbb{E}_{x_t \sim \mathbb{P}(\cdot \mid x_{< t})} \left[ \ell(x_t, p_t) \right] + \alpha \cdot D_{\text{TV}}(p_t, q_t).$$

When  $\ell = \ell_{\log}$ , we may use the entropy  $-\sum_v q_t(v) \cdot \log(q_t(v))$  from  $q_t$  as an estimate of its expected log-loss, and similarly for  $p_t$ , giving us the plug-in estimator:

$$\hat{r}_{\text{DiffLog}}(x_{< t}) = 1 \iff \sum_{v} q_t(v) \cdot \log(q_t(v)) < \sum_{v} p_t(v) \cdot \log(p_t(v)) - \alpha. \tag{25}$$

## C.2 Optimal speculative deferral when $\ell=\ell_{\mathrm{log}}$

Recall that the optimal deferral rule for a speculative cascade in Lemma 4 takes the form:

$$r^*(x_{< t}) = 1 \iff \mathbb{E}_{x_t \sim \mathbb{P}(\cdot \mid x_{< t})} \left[ \ell(x_t, q_t) \right] > \mathbb{E}_{x_t \sim \mathbb{P}(\cdot \mid x_{< t})} \left[ \ell(x_t, p_t) \right] + \alpha \cdot D_{\text{TV}}(p_t, q_t).$$

When  $\ell = \ell_{\log}$ , one may construct a *plug-in* estimator for the above rule by replacing the expected log loss with the entropy from the distribution:

$$\hat{r}_{\mathsf{OPTLog}}(x_{< t}) = 1 \iff \sum_{v} q_t(v) \cdot \log(q_t(v)) < \sum_{v} p_t(v) \cdot \log(p_t(v)) - \alpha \cdot D_{\mathsf{TV}}(p_t, q_t). \tag{26}$$

**Lemma 7** (Regret bound for  $\hat{r}_{\mathtt{OPTLog}}$ ). Suppose  $\ell = \ell_{\mathtt{log}}$ . Suppose for a fixed  $x_{< t}$ ,  $|\log(q(v))| \leq B_q$  and  $|\log(p(v))| \leq B_p$ ,  $\forall v \in \mathcal{V}$ , for some  $B_q$ ,  $B_p > 0$ . Then:

$$L_{\operatorname{spec}}(r_{\mathtt{OPT}}; x_{< t}) - \min_{r} L_{\operatorname{spec}}(r; x_{< t}) \ \leq \ B_q \cdot \sum_{v \in \mathcal{V}} \left| \mathbb{P}(v|x_{< t}) - q_t(v) \right| + B_p \cdot \sum_{v \in \mathcal{V}} \left| \mathbb{P}(v|x_{< t}) - p_t(v) \right|.$$

*Proof.* The proof follows similar steps to that for Lemma 5, except in bounding the resulting term<sub>2</sub> and term<sub>3</sub> for the log loss. In this case,

$$\begin{aligned} \text{term}_2 &= \left| \mathbb{E}_{x_t \sim \mathbb{P}(\cdot \mid x_{< t})} \left[ \log(p_t(x_t)) \right] - \sum_v p_t(v) \cdot \log(p_t(v)) \right| \\ &= \left| \sum_v \mathbb{P}(v \mid x_{< t}) \cdot \log(p_t(v)) - \sum_v p_t(v) \cdot \log(p_t(v)) \right| \\ &\leq \sum_v \left| \mathbb{P}(v \mid x_{< t}) - \sum_v p_t(v) \right| \cdot \log(p_t(v)) \\ &\leq B_p \cdot \sum_v \left| \mathbb{P}(v \mid x_{< t}) - \sum_v p_t(v) \right|. \end{aligned}$$

Similarly,

$$\operatorname{term}_{3} \leq \sum_{v} \left| \mathbb{P}(v|x_{< t}) - \sum_{v} p_{t}(v) \right| \cdot \log(p_{t}(v))$$

$$\leq B_{q} \cdot \sum_{v} \left| \mathbb{P}(v|x_{< t}) - \sum_{v} q_{t}(v) \right|.$$

Plugging these bounds into the equivalent of equation 18 in Lemma 5 for the log-loss completes the proof.

## C.3 OPTIMAL SPECULATIVE DEFERRAL FOR GREEDY DECODING

**Lemma 8.** When  $T \to 0$ , running Algorithm 5 with  $\tilde{r}_{OPT}$  as the deferral rule and  $\tilde{q}_t$  as the drafter is equivalent to running it with  $\hat{r}_{Diff}$  in equation 5 as the deferral rule and  $\tilde{q}_t$  as the drafter.

*Proof.* Note that under greedy inference,  $\tilde{q}_t$   $\tilde{p}_t$  are one-hot encodings of  $\arg\max_v q_t(v)$  and  $\arg\max_v p_t(v)$  respectively. As a result,

$$D_{\text{TV}}(\tilde{q}_t, \tilde{p}_t) = \mathbf{1} \left( \underset{v}{\text{arg max}} q_t(v) \neq \underset{v}{\text{arg max}} p_t(v) \right).$$

When running Algorithm 5 with  $\tilde{r}_{\mathtt{OPT}}$  as the deferral rule, we will accept a draft token v with probability:

$$\kappa(v) = \min \left\{ 1, \frac{(1 - \delta_{\mathrm{OPT}}(q, p)) \cdot \tilde{q}(v) + \delta_{\mathrm{OPT}}(q, p) \cdot \tilde{p}(v)}{\tilde{q}(v)} \right\}$$

where  $\delta_{\mathrm{OPT}}(q,p) = \mathbf{1} (\max_v q(v) < \max_v p(v) - \alpha \cdot \mathbf{1} (\arg\max_v q(v) \neq \arg\max_v p(v)))$ . When  $\arg\max_v q(v) = \arg\max_v p(v)$ , then  $\tilde{q} = \tilde{p}$ , and irrespective of the outcome of  $\delta(q,p)$ , we have that  $\pi(v) = 1$ . When  $\arg\max_v q(v) \neq \arg\max_v p(v)$ , then

$$\pi(v) = 1 - \delta_{\mathrm{OPT}}(q, p) = \mathbf{1} \left( \max_v q(v) \, \geq \, \max_v p(v) - \alpha \right) = 1 - \delta_{\mathtt{Diff}}(q, p).$$

When a token gets rejected, we sample a new token from the residual distribution:

$$p_{\rm res}(v) \propto \min\{0, (1 - \delta_{\rm OPT}(q, p)) \cdot \tilde{q}(v) + \delta_{\rm OPT}(q, p) \cdot \tilde{p}(v) - \tilde{q}(v)\} = \delta_{\rm OPT}(q, p) \cdot \min\{0, \tilde{p}(v) - \tilde{q}(v)\}$$

When  $\arg \max_{v} q(v) = \arg \max_{v} p(v)$ ,  $p_{res}(v) = 0$ . When  $\arg \max_{v} q(v) \neq \arg \max_{v} p(v)$ ,

$$p_{\rm res}(v) \propto \delta_{\rm OPT}(q,p) \cdot \min\{0,\tilde{p}(v) - \tilde{q}(v)\} = \delta_{\rm Diff}(q,p) \cdot \min\{0,\tilde{p}(v) - \tilde{q}(v)\}.$$

Thus both the acceptance probability and the residual distribution are the same as the one we would have used had we run Algorithm 5 with  $\hat{r}_{\text{Diff}}$  as the deferral rule.

## C.4 EQUIVALENCE BETWEEN EQUATION 7 AND EQUATION 8

Since the prefix  $x_{< t}$  is fixed in equation 7, the constrained optimization we seek to solve is of essentially of the following form:

$$\min_{r \in \{0,1\}} (1-r) \cdot c_0 + r \cdot c_1 \quad \text{s.t.} \quad r \cdot c_2 \le B,$$

for some coefficients  $c_0, c_1, c_2 > 0$ . Since r is a binary variable, we may formulate an equivalent unconstrained problem with the same minimizer:

$$\min_{r \in \{0,1\}} (1-r) \cdot c_0 + r \cdot c_1 + \alpha \cdot r \cdot c_2,$$

where we choose  $\alpha=0$  when  $c_2 \leq B$  and choose an  $\alpha>\frac{1}{c_2}\cdot(c_0-c_1)$  otherwise. This unconstrained optimization problem is of the form in equation 8.

#### D TOKEN-SPECIFIC SPECULATIVE CASCADE

We provide a modification of Algorithm 5 to accommodate the token-specific deferral rules in §4.4.

## Algorithm 6 TokenSpecCascade

**Input:** Models q, p, Token-specific deferral rule r, Prefix  $x_{< t}$ , Block size  $\gamma$   $\mathbb{T}_{\text{Token}}(q, p)(v) \doteq q(v) \cdot (1 - r(x_{< t}, v)) + p(v) \cdot \sum_{v' \in \mathcal{V}} r(x_{< t}, v') \cdot q(v')$ 

**Output:** GenSpecSample $(q, p, \mathbb{T}_{\text{Token}}, x_{< t}, \gamma)$ 




Figure 4: Plots of quality vs. latency for T5 models with temperature T=1 and block size  $\gamma=5$ . We include **T5 plots not included in Figure 2** in the main text. Each method interleaves T5-small with T-large (or T5-XL). The x-axis tracks the latency *relative* to that of calling the large model on all inputs. The horizontal dotted line denotes the quality of the large model.

**Optimal token-specific deferral.** Similar to §4.3, we may consider deriving the optimal token-specific deferral rule. We start by formulating a similar optimization objective. For a fixed prefix  $x_{< t}$ , this would look like:

$$\min_{r} \mathbb{E}_{v \sim \mathbb{P}(\cdot | x_{< t})} \left[ \ell(v, \pi_{\mathsf{Token}}) \right]$$
s.t.  $D_{\mathsf{TV}}(\pi_{\mathsf{Token}}, q_t) \leq B,$ 

where  $\pi_{\text{Token}}(v) \doteq (1 - r(x_{< t}, v)) \cdot q_t(v) + \eta \cdot p_t(v)$  is the target distribution resulting from the choice of  $r, \eta = \sum_{v' \in \mathcal{V}} r(x_{< t}, v') \cdot q_t(v')$  is a normalization term, and B > 0 is a budget parameter.

However, unlike §4.3, the above constrained optimization problem does not lend itself to a simple closed-form solution. In some highly simplistic special cases, we may be able to derive a solution. For example, suppose  $\ell = \ell_{0-1}$ , and the mode of  $q_t$  coincides with that of  $\mathbb{P}(\cdot|x_{< t})$ , i.e.,  $\arg\max_v q_t(v) = \arg\max_v \mathbb{P}(v|x_{< t})$ ; then the optimal token-specific rule is given by  $r(x_{< t}, v) = 0$ , for all  $v \in \mathcal{V}$ .

Under more realistic cases, we may not be able to derive a solution as simple as the OPT rule in equation 10. Therefore, in our experiments, we employ the three heuristic rules in equations 13–15, which are motivated by the form of the simpler Diff rule in equation 5.

### E ADDITIONAL EXPERIMENTAL DETAILS

We provide additional details about our experimental setup and additional experimental results. We will release code and an illustrative tutorial notebook along with the final manuscript.

#### E.1 EXPERIMENTAL SETUP AND HYPER-PARAMETERS

We elaborate on our experimental setup and the hyper-parameters used.

**T5 datasets.** For the WMT English to German translation task (Bojar et al., 2014a), we use a validation sample of size 3000 provided with the dataset. We set the maximum input length to 80 and the maximum output length to 80. For the Extreme Summarization (XSum) task (Narayan et al., 2018), we use a validation sample of size 11305, and set the maximum input length to 1024 and




Figure 5: Plots of quality vs. latency for T5 models with **greedy decoding** with temperature T=0 and block size  $\gamma=5$ . Each method interleaves T5-small with T-large (or T5-XL). The x-axis tracks the latency *relative* to that of calling the large model on all inputs. The horizontal dotted line denotes the quality of the large model.

the maximum output length to 64. For the CNN/Daily Mail summarization task (Hermann et al., 2015), we use a validation sample of size 13368, and set the maximum input length to 2048 and the maximum output length to 128. Following (Zhou et al., 2024), we use ROUGE-2 as the evaluation metric for the summarization tasks.

We note that Kim et al. (2023) report ROUGE-L metrics for CNN/DM, which generally tend to evaluate to higher values than ROUGE-2. Furthermore, most of their experimental results are with greedy decoding (T=0), and hence, the ROUGE-L evaluation metrics they report in their paper tend to be higher for the same T5 models when compared to our numbers for ROUGE-2 with temperature sampling.

Gemma datasets. In addition to the WMT EN→DE translation and the CNN/DM summarization datasets, we use the GSM8K (Cobbe et al., 2021) math reasoning dataset, the MBPP (Austin et al., 2021) Python programming dataset, and four question-answering datasets: Natural Questions (Kwiatkowski et al., 2019), TriviaQA (Joshi et al., 2017), WebQuestions (Berant et al., 2013) and the Stanford Question-Answering Dataset (SQuAD) 2.0 (Rajpurkar et al., 2016). In each case, we sample 1000 prompts for evaluation. We employ few-shot inference, and set the maximum output length to 80 for WMT, to 128 for CNN/DM, to 320 for GSM8K and MBPP, and to 5 for all the question-answering datasets.

**Models.** We construct cascades from T5 v1.1 family of encoder-decoder models (Raffel et al., 2020a), of different sizes T5-small (77M), T5-base (250M), T5-large (800M) and T5-XL (3B). We follow the protocol in (Zhou et al., 2024): we initialize with the public checkpoints, pre-train them further for 100K steps, and supervise **finetune** pre-trained models on the three respective tasks. We finetune them for a maximum of 250K steps on WMT, a maximum of 100K steps on XSum and a maximum of 200K steps on CNNDM.

We construct the Gemma cascades from *instruction-tuned* decoder-only v2 models. For MBPP alone we additionally experiment with *pre-trained* models. We use a 2B drafter, and either a 9B verifier or a 27B verifier (Team et al., 2024).

**Evaluation.** For each dataset, we evaluate the quality metrics on the entire validation set. For the run-time analysis, we adopt the protocol followed in Leviathan et al. (2023); Zhou et al. (2024). We randomly sample 500 examples from the validation set, and calculate the wall-clock time taken for decoding with a batch size of 1. We repeat this for three trials and report the average running time. All methods are run on the same TPUv4 device. The drafter and verifier models are run without model parallelism.

**Hyper-parameters.** We set the block-size  $\gamma$  to 5 for all methods that use speculative execution. For the token-level cascades, we allow the small model to predict for a maximum of 10 tokens (similar to (Kim et al., 2023)), before invoking the large model. This was needed, as otherwise, the small model would predict a long sequence, and when it eventually defers to the large model, the large model is bottle-necked by the pre-filling of the long prefix accumulated by the small model. We vary the lenience parameter  $\alpha$  to vary the latency and plot quality as a function of latency. We vary this parameter in the range 0 to 1 for all methods where the thresholding is on a probability metric; the exceptions to this are the BiLD variants, for which, we use a longer range, as detailed below.

**BiLD baseline.** For the BiLD method, we adopt the same discrepancy metric D as (Kim et al., 2023) for greedy decoding:

$$D(q,p) = -\log\left(p\left(\arg\max_{v}q(v)\right)\right),$$

and pick the value of the threshold  $\alpha$  on this metric from the range [0, 10]. For temperature sampling with a non-zero temperature, we use the following natural analogue to the above D:

$$D(q, p) = -\mathbb{E}_{v \sim q} \left[ \log(p(v)) \right] = -\sum_{v \in \mathcal{V}} q(v) \cdot \log(p(v)).$$

In §E.5, we present comparisons between different implementations of this method.

**Lossy speculative decoding.** See §E.6 for details.

## E.2 ADDITIONAL EXPERIMENTAL PLOTS

In Figures 4 and 5, we provide additional plots of quality vs. latency for different inference strategies under temperature sampling (T=1) and greedy decoding respectively.

As noted in §C.3, with greedy decoding, the OPT deferral rule coincides with the Diff deferral rule. When temperature  $T \to 0$ ,  $D_{\text{TV}}(\tilde{p}_t, \tilde{q}_t) = 1$  whenever  $\arg \max_v p_t(v) \neq \arg \max_v q_t(v)$ , and is zero otherwise. In this case, running Algorithm 5 with  $\tilde{r}_{\text{OPT}}$  as the deferral rule (and  $\tilde{q}_t$  as the drafter) is equivalent to running it with  $\hat{r}_{\text{Diff}}$  in equation 5 as the deferral rule. In other words, for greedy decoding, the optimal deferral rules for a speculative cascade coincides with that for a sequential cascade.

Note that under greedy decoding, all methods yield better quality metrics compared to their performance under temperature sampling.

### E.3 COMPARING SPECULATIVE DEFERRAL RULES UNDER DIFFERENT TEMPERATURES

In Figure 6, we present latency-quality trade-off plots for T5 cascades under temperature sampling with different temperatures. We compare lossy speculative decoding with two speculative cascade

<sup>&</sup>lt;sup>1</sup>The pre-trained checkpoints we use are available here.




Figure 6: Plots of quality vs. latency for T5 models with **varying temperatures**. Each method interleaves T5-small with T-large. The *x*-axis tracks the latency *relative* to that of calling the large model on all inputs. The horizontal dotted line denotes the quality of the large model.

deferral rules: OPT rule in equation 5 and the Token-specific rule in equation 15. We find that the gap between OPT and the Token-specific rule diminishes as the temperature decreases.

The reason the Token-specific rule fares better than OPT is because the latter compute their deferral decisions based on which of  $q_t(\cdot)$  and  $p_t(\cdot)$  is more peaked; this can be a disadvantage when the sampled token is not be close the distribution mode, which is likely to happen with higher temperatures. With lower temperatures, however, the sampled token is likely to be close the distribution mode, and as a result, the advantage that the Token-specific rule has over OPT diminishes.

#### E.4 Comparing speculative deferral rules under different block sizes $\gamma$

In Figure 7, we present latency-quality trade-off plots for T5 cascades under different block sizes  $\gamma$ . In each case, we find that the proposed speculative cascading techniques outperform lossy speculative decoding across different latency values. Furthermore, higher values of  $\gamma$  are seen to yield a wider range of trade-offs, with lower quality operating points shifting to the left, and better quality operating points shifting to the right. For example, with XSum, SpecDecode [Lossy] with  $\gamma=3$  matches the small model's quality at 0.64 relative latency, and matches the large model's quality at 0.85 relative latency; with  $\gamma=7$ , it matches the small model's quality at an even lower latency, but practically provides no speed-up when matching the larger model's quality. The reason a larger block size can hurt speed-up at the higher quality regime is because it can result in frequent rollbacks, thus defeating the purpose of using speculative execution.




Figure 7: Plots of quality vs. latency for T5 models with **with varying block sizes**  $\gamma$ . Each method interleaves T5-small with T-large. The x-axis tracks the latency relative to that of calling the large model on all inputs. The horizontal dotted line denotes the quality of the large model.

## E.5 BIG LITTLE DECODER (BILD) VARIANTS

In §6, we compared against a version of the Big Little Decoder method (Kim et al., 2023) that applied Algorithm 4 to the target distribution  $\mathbb{T}_{BiLD}$  the authors seek to mimic (§5). We now show that this version performs similarly to the original BiLD algorithm in (Kim et al., 2023).

A key difference to the original algorithm in (Kim et al., 2023) is the use of the fallback phase, where the drafter is run until its maximum predicted probability  $\max_v q(v) < 1 - \alpha_f$ , for a threshold  $\alpha_f \in [0,1]$  (or until a maximum block size of 10 is reached), and the use of a deterministic rollback policy where the verifier rejects a draft token whenever  $D(q,p) > \alpha$ . In our implementation, we adopt the speculative sampling algorithm from (Leviathan et al., 2023): we do not have the fallback policy and replace the determinisic rollback policy with the rejection sampling in Algorithm 4.

Figure 8 (top) compares the original version of BiLD with the version we use in §6. We interleave between a T5-small and T5-large model on WMT, using greedy decoding (T=0) for inference. As prescribed by the authors (Kim et al., 2023), we use the following discrepancy metric for greedy decoding:

$$D(q, p) = \log p \left( \arg \max_{v} q(v) \right).$$

We compare our implementation (BilD\*), where we set the block size 5 (same as our proposed speculative cascading approaches) with the original BilD for different choices of maximum block size  $\gamma$  and different fallback thresholds  $\alpha_f$ . For both methods, we vary the threshold  $\alpha$  on D(q,p) to vary the latency and plot the resulting BLEU score.

A higher fallback threshold  $\alpha_f$  results in larger draft generation windows; this gives an advantage in the low latency regime, where most of the draft tokens are accepted. As a result, BiLD [ $\gamma = 10, \alpha = 0.9$ ] yields the lowest latencies, but also yields lower quality. A low fallback threshold results




Figure 8: Top: Plots of quality vs. latency **comparing BiLD\* with the original BiLD algorithm** in Kim et al. (2023) with varying maximum draft window size  $\gamma$  and fallback confidence threshold  $\alpha_f$ . Bottom: Comparison of lossy speculative decoding with  $\beta=1$  [Lossy] and  $\beta$  tuned using the procedure in (Tran-Thien, 2023) [Lossy\*].

in very small draft generation windows, and consequently, in higher latencies. This is why BiLD  $[\gamma=5,\alpha=0.1]$  is the slowest but yields high quality metrics.

Our implementation BilD\* is seen to perform comparable to the best parameter choices for the original BilD algorithm in Figure 8.

**Note:** It is worth noting that while we view  $\mathbb{T}_{BiLD}$  as the target distribution that algorithm in (Kim et al., 2023) seeks to mimic, the presence of the fallback phase could mean that on some inputs a output response is generated without the verification (or rollback) phase being invoked. In such cases, the output will be a sample from the drafter even if it turns out that it contains tokens for which  $D(q_t, p_t) > \alpha$ .

### E.6 LOSSY SPECULATIVE DECODING VARIANTS

In §6, we compared against the lossy speculative decoding Tran-Thien (2023); Zhou et al. (2024) described in §2, with the parameter  $\beta$  set to 1. We now present results for this method with  $\beta$  tuned according to the procedure in Tran-Thien (2023), and show that choosing  $\beta = 1$  fares at least as well as tuning  $\beta$ .

The goal in Tran-Thien (2023) is to choose  $\alpha$  and  $\beta$  so as to maximize the acceptance rate for the draft token, while ensuring that the KL divergence between the resulting target distribution and p is within an allowable limit R. The authors prescribe specifying R, and for each prefix, tuning  $\alpha$  and  $\beta$  to solve the resulting constrained optimization problem. To be consistent with the rest of our experimental setup, we vary  $\alpha$  to vary the draft acceptance rate (note that each choice of  $\alpha$  corresponds to a particular KL divergence to p), and tune  $\beta \geq 1 - \alpha$  to satisfy the following condition

outlined in Tran-Thien (2023):

$$\sum_{v} \max \left\{ 0, q(v) - \frac{p(v)}{1 - \alpha} \right\} = \sum_{v} \max \left\{ 0, \frac{p(v)}{\beta} - q(v) \right\}$$

We pick  $\beta$  using a grid-search over 1000 values between  $\alpha$  and 10. Since this tuning procedure, in turn, can add to the method's latency, for a fair comparison, we analyze quality as a function of the fraction of calls to the large model. In Figure 8 (bottom), we plot these trade-off curves for loss speculative decoding with  $\beta=1$  (Lossy) and for speculative decoding with  $\beta$  tuned using the above procedure (Lossy\*). We compare performances on WMT and XSum, and in each case, interleave a T5-small model with a T5-large model.

In both cases, setting  $\beta=1$  provides trade-offs comparable to or better than using a tuned value of  $\beta$ . The reason using a tuned value of  $\beta$  fares worse than setting  $\beta=1$  might be because we are measuring quality in terms of BLEU or ROUGE-2, which is different from the KL divergence to p objective that the tuning procedure in Tran-Thien (2023) seeks to optimize.

#### E.7 TOKEN-SPECIFIC SPECULATIVE CASCADES

In Figure 9, we present latency-quality trade-off plots for cascades constructed from a T5 small and a T5 large model. We include in these comparisons, all three token-specific deferral rules in equations 13–15. In Figure 10, we present trade-off plots for cascades constructed from Gemma 2B and Gemma 27B models with all three token-specific rules, and in Figure 11, we include similar plots for cascades constructed from Gemma 2B and Gemma 9B models. We note that the trends with the  $2B \rightarrow 9B$  are similar to those seen with the  $2B \rightarrow 27B$  cascades.

With the T5 models, the results are mixed, with the V1 and V2 variants sometime surpassing the V3 variant (which is the variant we included in the main experiments results in  $\S6$ ) Interestingly, with the Gemma models, the V3 variant is seen to outperform the others for most rejection rates, with the exception of the  $2B \rightarrow 27B$  cascade on SQuAD 2.0, where the V2 variant is better.

The reason the V3 variant outperforms V1 and V2 on the Gemma models could be due to the fact that it uses the larger model's distribution  $p_t(\cdot)$  to measure confidence for both the drafter and verifier (see LHS and RHS in equation 13). We expect this to be particularly helpful when there is a larger gap in sizes between q and p, and the larger model's distribution is better aligned with the ground-truth distribution compared to the smaller model. Furthermore, as noted in §4.4, the multiplicative form of the rule results in a target distribution that has an intuitive form: it seeks to mimic  $q_t(\cdot)$  on the top- $\alpha$  ranked tokens by  $p_t(\cdot)$  and uses a re-scaled version of  $p_t(\cdot)$  for the other tokens.

## F LIMITATIONS

One of the limitations of our proposal is the use of plug-in estimators to approximate the optimal rule equation 9. While these approximations are effective in practice, they rely on the individual models being calibrated. An alternative to the use of plug-in estimators is to use a router model explicitly trained to mimic the optimal rule using a validation sample drawn from  $\mathbb{P}$  (Gupta et al., 2024). Another limitation is that the optimization objectives we seek to minimize are local objectives that seek to make the best deferral decision at the current position t. In doing so, they ignore the downstream effects of choosing a particular model in the current step. Devising a global deferral objective that takes downstream errors into account would be an interesting direction for future work. More broadly, our paper seeks to improve cost-quality trade-offs in LM inference. It is important that such improvements do not unfairly advantage one slice of the data or a subset of the population, at the cost of others. Ensuring that the trade-off gains that our approach offers is equitable across different slices of the data is another important direction for the future.




Figure 9: Plots of quality vs. latency for **T5 models with all three token-specific speculative cascade deferral rules** in equations 13–15. Each method interleaves a T5 small and a T5 large model. The *x*-axis tracks the latency *relative* to that of calling the large model on all inputs. The horizontal dotted line denotes the quality of the large model.




Figure 10: Plots of quality vs. rejection rate for **Gemma models with all three token-specific speculative cascade deferral rules** in equations 13–15. Each method interleaves a Gemma 2B drafter with a Gemma 27B verifier. The horizontal dotted line denotes the quality of the large model. We include all three token-specific speculative cascade deferral rules in equations 13–15.




Figure 11: Plots of quality vs. rejection rate with **Gemma 2B**  $\rightarrow$  **9B** speculative cascades. Each method interleaves a Gemma 2B drafter with a Gemma 9B verifier. The horizontal dotted line denotes the quality of the large model. We include all three token-specific speculative cascade deferral rules in equations 13–15.