# **TOAD:** Task-Oriented Automatic Dialogs with Diverse Response Styles

Anonymous ACL submission

#### Abstract

In light of recent advances in large language models (LLMs), the expectations for the next generation of virtual assistants include enhanced naturalness and adaptability across diverse usage scenarios. However, the creation of high-quality annotated data for Task-Oriented Dialog (TOD) is recognized to be slow and costly. To address these challenges, we introduce Task-Oriented Automatic Dialogs (TOAD), a novel and scalable TOD dataset along with its automatic generation pipeline. The TOAD dataset simulates realistic app context interaction and provide a variety of system response style options. Two aspects of system response styles are considered, verbosity level and users' expression mirroring. We benchmark TOAD on two response generation tasks and the results show that modeling more verbose or responses without user expression mirroring is more challenging. The data and code will be released.

## 1 Introduction

004

011

017

034

040

Task-Oriented Dialog (TOD) stands as a fundamental task of machine intelligence (Young, 2010), involving goal-driven conversations between a human and a system to achieve specific tasks. It has been used in training virtual assistant systems for various real-world applications, including mobile phones (Hoy, 2018), virtual reality devices (VR) (Kottur et al., 2021), smart home devices (Duong et al., 2019), online shopping assistants (Yan et al., 2017), and trip booking helpers (El Asri et al., 2017b).

Advancements in developing TOD systems face a challenge posed by conflicting requirements (Hu et al., 2023): the demand for extensive datasets clashes with the substantial time and financial investments (months if not years) required for data collection (Larson and Leach, 2022). Looking ahead to the next generation of virtual assistants, an expectation arises for them to adapt their response



Figure 1: A dialog example from TOAD, with all system response styles. LV, MV, HV and M stand for Low, Mid, High Verbosity and Mirroring. The underscored responses are selected as the default styles.

styles to different usage scenarios, e.g. if equipped with a screen, ensuring a sustained level of naturalness and communication efficiency and ultimately enhancing the user experience. However, existing datasets lack consideration for **adaptive response styles** and neglect to simulate **interactions with app contexts** like calendars or alarms. 042

043

044

046

051

053

055

057

060

061

062

063

This paper presents Task-Oriented Automatic Dialog, TOAD, a highly automatic generated dataset, along with its generation pipeline, designed to address the challenges mentioned above. In TOAD, we not only simulate realistic interactions with app context and diverse conversational phenomena, but also analyze two aspects of response style—**verbosity level** and **users' expressions mirroring**, aiming to enhance naturalness and adaptiveness for various usage scenarios. As shown in the dialog example in Fig. 1, for each turn of system utterance, we provide a spectrum of six responses style options. The dataset is constructed using an automatic generation pipeline, leveraging the zeroshot generation capability of the latest Large Lan-

	MultiWoZ	PRSTO	ABCD	SGD	STAR	TOAD
Number of dialogs	8,438	95,671	8,034	16,142	5,820	8,087
Number of services	7	34	30	16	13	11
Total number of turns	115,434	-	177,407	329,964	127,833	37,678
Average tokens / turn	13.1	9.0	9.1	11.2	11.2	10.6
Context app interaction	×	$\checkmark$	×	×	×	$\checkmark$
Response style control	×	×	×	×	×	$\checkmark$
Highly automatic	×	×	×	×	×	$\checkmark$

Table 1: Comparison of our TOAD dataset to other existing TOD datasets.

064guage Models (LLMs), such as ChatGPT<sup>1</sup>. Due to065its automatic nature, the TOAD dataset is scalable066in terms of data size and service coverage. To pro-067vide a benchmark for future studies, we establish068reference scores for two TOD Natural Language069Generation (NLG) tasks, evaluating a variety of070baseline models. The results indicate that modeling071more verbose or responses without user expression072mirroring is more challenging.

The contributions of this work are three-fold: 1) A new TOD dataset with multiple response styles and realistic app context interaction, such as revising or deleting calendar events. 2) TOAD is the first that investigates the naturalness and adaptiveness of system response, providing insights into the dimensions of style that virtual assistants should consider. 3) An automatic TOD data generation pipeline for scalable, cost-effective expansion of data size and domains.

# 2 Related Works

076

077

081

086

089

091

100

101

102

### 2.1 Task-Oriented Dialog Dataset

To our best knowledge, TOAD stands out as the first highly automatically generated TOD dataset. All previous datasets relied on human annotations or paraphrasing, which makes the collection process costly and time-consuming. Moreover, our dataset also admits all of the unique properties listed in Section 1.

Previous TOD datasets mainly fall into two categories based on how dialog utterances are collected: Machine-to-Machine (M2M) and Wizardof-Oz (WOz). In the M2M setup, proposed by Shah et al. (2018), systems or schemas exhaustively simulate dialog with skeleton plots, represented in structured formats. The dialog plots are realized into natural language by crowd workers. A representative dataset is the SGD (Rastogi et al., 2020), which consists of dialogs across 16 domains. They defined a list of meta information as schema, such as valid slots and supporting intents for each domain and utilize the slot-filling strategy to simulate the dialog plots. Another dataset, STAR (Mosig et al., 2020), defined explicit ideal dialog flows for each domain and simulated realistic user behaviors such as small-talk interruptions. 103

104

105

106

107

108

109

110

111

112

113

114

115

116

117

118

119

120

121

122

123

124

125

126

127

128

129

130

131

132

133

134

135

136

137

138

139

140

141

142

143

Another line of TOD data collection setup, the WOz (Kelley, 1984), employs crowd workers playing roles both of the user and the system, to directly produce utterances in a more improvised manner. The user is provided with an overall goal to achieve throughout the conversation, while the "system" needs to respond with access to a database based on the user's preference. Such WOZ set-up has been successfully validated by WOz (Wen et al., 2017) and FRAMES (El Asri et al., 2017a). A popular dataset MultiWOZ (Budzianowski et al., 2018) designed a user-friendly interface for the Wizards and easy-to-follow user goals, resulting in diverse and semantically rich data. The recent Multi3WOZ (Hu et al., 2023) expands this paradigm, collecting a large-scale multilingual TOD dataset with parallel utterances in four languages over the same conversational flows.

## 2.2 Dialog Distillation

Recent advancements in LLMs have demonstrated their improved ability to follow human instructions and generate fluent conversation utterances for a range of understanding and generation tasks. A list of recent works embrace this concept, extracting knowledge and dialog from LLMs to train student or in-domain models. SODA (Kim et al., 2023) distilled social interactions dialogue by contextualizing commonsense knowledge from a social knowledge graph. PLACES (Chen et al., 2023) generated a multi-party social dialog by prompting the OPT (Zhang et al., 2022) model with topic, facts, and dialog as in-context learning examples. Math-Dial (Macina et al., 2023) distilled teacher-student math reasoning tutoring dialog through pairing human teachers with a LLM. There are also works

<sup>&</sup>lt;sup>1</sup>https://openai.com/blog/chatgpt



Figure 2: Overview of the TOAD Automatic Generation Pipeline in 3 Steps: (i) Persona-grounded user device context generation, (ii) Action plot generation, and (iii) Dialog utterance realization.

that distil multi-turn open-domain instructional conversations, such as Baize (Xu et al., 2023) and UltraChat (Ding et al., 2023). Our TOAD represents the first work in distilling TOD dialog with multiple response style options, which requires more nuanced control over the conversation content.

### **3** Data Generation Pipeline

144

145

146

147

148

149

150

151

152

153

155

156

160

161

162

164

166

168

170

171

172

173

174

175

176

177

178

The TOAD pipeline, depicted in Fig. 2, comprises three key stages for the automated creation of dialogues. The initial stage involves the generation of device context, simulating users' personas and their device app contexts. In the second stage, essential conversation attributes, including conversational content, flow, and language phenomena, are determined and incorporated into a dialog plot. The final stage involves the realization of the dialog plot into dialog utterances by a dialog generator. This generator simulates user speaking habits and provides a spectrum of system response styles.

### 3.1 Persona-Grounded Context Generation

Interacting with on-device context information such as calendar and alarms is an important part of real-life virtual assistant use-cases. A recent dataset, PRESTO (Goel et al., 2023), provides simulated structured contexts, but their influence is very limited as most dialogs are irrelevant to their contexts and there is no interaction such as modification or deletion.

Data diversity is important to the model's robustness and generalization. However, LLM-generated data given the same input prompt often lacks diversity. To address the two issues mentioned above, we develop a persona-grounded context generation pipeline, which combines sampling from external data sources and chain-of-thought generation (Wei

#### et al., 2022).

We synthesize each persona in 3 steps: 1) We synthesize random occupation information, by sampling from work statuses including employed, unemployed/retired, and student. For students or the employed, occupations are based on NAICS 6-digit industries.<sup>2</sup> Additional occupation details such as location, affiliation, and job level are generated by prompting the LLM. 2) We sample surname and race together from the 2010 US Census data,<sup>3</sup> and sample other attributes such as gender, MBTI personality from pre-defined sets. 3) The sampled information is input into the LLM to write an introduction with additional fictionalized details (e.g. first name, age, marital status, hobbies).

179

180

181

182

183

184

185

186

187

188

189

190

191

193

194

195

196

197

198

199

200

201

202

203

204

205

206

207

208

209

210

211

Based on each persona's introduction, attributes and a random 'current time', we prompt the LLM to generate app context instances for each service. Details about the supporting services are provided in Section 5. There are dependencies across services, e.g. information of generated contacts might be shared by messages and calendar.

### **3.2** Plot Generation

**Schema** Our pipeline, inspired by the approach in SGD (Rastogi et al., 2020), establishes a schema for each service by outlining supported intents, associated slots and relevant meta-data. For example, the *calendar\_events* service has four supporting intents (*create*, *modify*, *check* and *delete*). Each intent specifies required slots like *start\_time*, *date* and *duration* along with optional slots such as *attendees*, *name* and *location*. Additionally, we also specify a list of meta-indicators for each in-

<sup>&</sup>lt;sup>2</sup>https://www.census.gov/naics/2022NAICS/2022\_ NAICS\_Structure.xlsx

<sup>&</sup>lt;sup>3</sup>https://www2.census.gov/topics/genealogy/ 2010surnames/names.zip

Phenomena	Actions	Utterance
Compound	<pre>restaurant_booking_reserve_table(restaurant ="French Brasserie", time="8:00 PM"), hotel_booking_search_hotel(location="Las Vegas")</pre>	I would like to reserve a table at the French Brasserie for 8:00 PM. Also, can you help me find a hotel in Las Vegas?
Compositional	<pre>weather_get_weather(date=get_calendar_events(     name="Art Class").calendar_events_check(date).date)</pre>	What's the weather like on the day of my Art Class event?
Self-correction	<pre>get_movie_time(movie_name="Fast &amp; Furious Presents: Hobbs &amp; Shaw", location="Miami").self_correction( location="Houston")</pre>	Could you find the showtimes for Fast & Furious Presents: Hobbs & Shaw in Miami? Actually, make that Houston instead.
Complex referral	<pre>get_alarms(ordered_by="time", index=0).check(time)</pre>	What's the time for my earliest alarm?

Table 2: Dialog Phenomena Examples. Actionns and utterance for initial query examples, For multi-intent phenomena, compound and compositional, we concate service name as prefix to the intent actions.

212tent to control the conversation flow. For instance,213the intent of *reserve\_table* is marked as for "*re-*214*quire\_confirmation=True*", indicating the need for215an additional confirmation in the dialog flow. Fur-216ther details about the schema are provided in Ap-217pendix A.

218 **Dialog Phenomena** To enhance the authentic-219 ity of our conversation flows, we simulate various dialog phenomena, exemplified in Tab. 2. These phenomena are categorized into multi-intent and 221 single-intent types. Compound and compositional 223 dialogs fall into the multi-intent category, where users pursue related or unrelated goals simultaneously or their initial intent depends on another 225 implicit intent. In the Tab. 2 example, to obtain the weather information for the day of the "Art 227 Class", an implicit intent check is needed to get 228 the actual date of the "Art Class". Self-correction and complex referral are phenomena that simulate real-life conversation dynamics. In self-correction, users correct themselves or alter their requests mid-232 sentence or afterward. In complex referral, users 233 employ realistic referring expressions that require additional logic to comprehend. For instance, an oral expression like "earliest alarm" requires ranking all alarms in app context by time to pinpoint 237 the user's reference accurately.

> **Intent Sampling** In TOAD, intent represents user's intention and determines the conversation content and goal. To compose the dialog, we sample services and intents, and generate corresponding slot values through LLM prompts. For consistency, all slot values are generated simultaneously.

239

240

241

242

243

245

246

247

For multi-intent compound dialog, two intents and their respective slot values are independently sampled. While for compositional dialog, as the output of the implicit intent will be used as the input of the initial intent, the two intents are jointly sampled with a slot matching strategy. Further details on the intents sampling and slot values generation are provided in Appendix C.

251

252

253

254

255

257

258

259

260

261

262

263

265

266

267

268

269

270

271

272

273

274

275

276

277

278

279

281

282

283

284

**Plot Representation** As illustrated in Fig. 2, a plot serves as a conversation skeleton, consisting of a sequence of Meaning Representations (MRs) that encapsulate all the necessary dialog information. The manipulation of these MRs allows control over the dialog's content and flow. In contrast to SGD and STAR, which rely on a finite set of function-like actions for MRs, TOAD opts for a pseudocode format to represent actions. This choice avoids dependence on a fixed set of predefined actions, enriching the meaning space, particularly in terms of referring expressions. Furthermore, the decision to use pseudocode aligns with the fact that most latest LLMs have been pre-trained on code, ensuring their comprehension of code-like MRs.

**Plot Construction** Dialog plot construction follows the flowchart in Fig. 3. The core mechanism employs a slot-filling strategy, with the system asking the user to fill all required slots to achieve their intent. The meta-indicators specified in the intent schema also determine the plot components, e.g. including additional confirmation turns or replying with search result summarization. For multi-intent dialogues, the plots are composed by merging individual plots for each intent in a natural order. The details of the merging policy are provided in Appendix D.

**Context Interaction** Dialogues involving interactions with context apps are ubiquitous in real-life scenarios but have not been adequately addressed in existing datasets. TOAD is the first work that includes conversations with context interactions, supporting generic intents of checking, deleting, and modifying on app services such as calendar



Figure 3: Plot construction for single intent dialog based on slot-filling strategy.

events, alarms, and messages.

This expansion significantly broadens the scope for simulating dialogues with natural referring expressions and introduces the concept of proper referring expressions. Users can refer to a calendar event using any slots, but the system should adhere to a preference order: While multiple slots may be unambiguous, certain slots are more intuitive for users. For instance, when referring to a calendar event, "the 9 a.m. meeting" is preferred over "the meeting in the office." Therefore, referring by time is prioritized over referring by location. For each intent, we define a preference order for the slots, enhancing the naturalness of the system response.

Database queryTraditional TOD datasets support intents that require database queries, such asrestaurant or movie searching. In contrast to SGD'suse of FreeBase for realistic slot values, our TOADpipeline leverages LLMs as a knowledge database.ro ensure consistent query results, we prompt theLLMs with input slot values as conditions. Foreach query, we instruct LLMs to generate five different instances, simulating the search operationand ensuring diversity in the returned values. Theadvantages of using LLMs as a knowledge baseinclude: 1) It avoids the issues of empty or noisysearching results. 2) The query outcomes are moreconsistent with other slot values.

#### 3.3 Dialog Generator

The dialog generator realizes the composed plots into natural utterances. Similar to SGD and STAR, we adopt the Machine-to-Machine (M2M) approach, where different LLMs take turns to play the roles of user and system for generating conversation utterances.

318

319

320

321

322

323

324

325

326

327

329

330

331

332

333

334

335

336

337

338

339

341

342

343

344

345

346

347

348

349

350

351

352

353

355

356

357

358

359

360

361

362

363

364

365

366

367

**Style Control** To offer natural responses across various scenarios, we generate a spectrum of response styles for each system turn as shown in the example in Fig. 1, including combinations of low, mid and high verbosity and mirroring or no mirroring. This is achieved by providing In-Context Learning (ICL) examples and style definitions for different styles to LLMs. The motivations behind these style designs are explained in Section 4.

Given the six style options for each system turn, a selection must be made to construct the dialog history, which will shape the subsequent generation. The dialog history significantly influences the generation of future conversation utterances. For instance, if the system consistently responds with low verbosity, user utterances tend to become shorter as well. Hence, the most natural style for a given conversation context should be selected, referred to as the default style, which should balance between efficient communication and minimizing the risk of misoperation. The selection rules are explained in detail in Section 4.

**Prompt Template** The prompt templates for user and system encapsulate three key pieces of information: 1) Current turn dialog action, 2) dialog history, and 3) style instruction. ICL demostration for action-to-utterance are also provided to guide the utterance realization. For user turns, the style instruction describes the user's speaking habit based on the sampled persona. For system turns, the style instruction provides a brief definition of each style with corresponding ICL examples. Examples of prompt templates can be found in Appendix H.

For efficiency and cost considerations, TOAD prompts LLMs to generate all system styles in a single inference pass. While generating one style utterance at a time improves textual quality and control performance, it represents a trade-off between quality and cost.

# 3.4 Dataset Quality Control

Following the generation pipeline, we filter the dataset to ensure its quality, which involved two filtering conditions: 1) Removing datapoints with utterances with unnatural formats, such as canonical datetime expressions like '2025-12-16'. 2) Removing datapoints that have missing slot values

- 368
- 369

375

376

390

395

397

400

401

402

403

404

405

406

407

408

409

410

411

412

413

414

415

416

in the corresponding utterances. This filtering process resulted in the removal of 2.2% of the data, yielding a final dataset size of 8087 dialogs.

# 4 System Response Style

The primary evaluation criterion for today's virtual assistants is their accuracy in responding and assisting users in achieving their goals. The next generation of virtual assistants is expected to exhibit increased naturalness and adaptability to various usage scenarios, which means the systems should be able to respond with different styles. TOAD stands as the first work in investigating the dimensions of style that virtual assistants should consider. We aim to open the discussion on optimal response styles to encourage future exploration. In this work, our focus centers on two main aspects: verbosity level and mirroring.

# 4.1 Verbosity

Verbosity refers to the degree of details or amount of information expressed in a response utterance. In many cases, clear and concise communication is preferred as it ensures efficient delivery and easy comprehension. However, certain contexts may demand a higher verbosity to provide comprehensive explanations and avoid ambiguity. It's essential to strike a balance and use an appropriate level of verbosity based on the specific communication situation and user needs.

In TOAD, we define three levels of verbosity, illustrated through examples in Fig. 1: Low verbosity responses should only contain a few words and may not necessarily be a complete sentence. Mid verbosity responses should use pronouns to refer any previously mentioned events. High verbosity responses should refer to events with proper and detailed expression and provide all relevant information. System verbosity critically impacts user experience, and we propose a set of rules to determine the most natural response for a given context, which we consider the default style.

- 1. If there is special language phenomena in the user's last query, the system should employ higher verbosity.
- 2. If the system needs to respond with new information, verbosity should be mid or high.
- 3. If the system is requesting user confirmation for an irreversible operation, such as calender deleting or ticket booking, verbosity should be high.

4. Otherwise, the system should exhibit low verbosity for efficient communication.

417

418

419

420

421

422

423

424

425

426

427

428

429

430

431

432

433

434

435

436

437

438

439

440

441

442

443

444

445

446

447

448

449

450

451

452

453

454

455

456

457

458

459

460

461

462

463

464

We note that this approach is subjective, and different styles may be favored in various situations.

# 4.2 Mirroring

Extensive research (Liao and He, 2020; Vartanov et al., 2023) demonstrates the benefits of mirroring user behavior, emotions, personas, and expressions in psychological tasks. Mirroring enhances mutual understanding, promotes efficient communication, and consequently leads to improved user feedback (Garrod and Pickering, 2009). In TOAD, the response style of mirroring refers to the reuse of noun or verb phrases from the user's expression whenever feasible, as illustrated in Fig. 1. In contrast, a non-mirroring style avoids directly copying the user's expression.

Mirroring is generally a favorable strategy, fostering natural conversation. However, caution is warranted, as a virtual assistant should consistently maintain professionalism and ensure positive communication. Instances where mirroring may be inappropriate include:

- Emotional and improper phrasing: In real-life scenarios, users may use sentimental or inappropriate language, such as cursing words.
- Bias: Users' expressions may contain negative connotations related to gender, culture, race, or politics. A virtual assistant should avoid reinforcing these biases.
- Non-factual information: Users may not always provide accurate information, particularly in knowledge domains. For instance, asking "Who is the king of the United States?".
- Ambiguous terms or referring expressions: Mirroring potentially ambiguous expressions could be confusing to the user. For example, a user might mention "my meeting with David," and if the system copies this referring expression, the user could be uncertain when identifying the event, as they may not be aware of the possibility of having more than one scheduled meeting with David.

Mirroring user expressions is not universally safe or appropriate, and it is challenging to exhaustively enumerate all misuse cases. The outlined situations provide a foundation for identifying potential challenges, and we encourage future exploration.



Figure 4: (i) Distribution of the dialog lengths. (ii) Distribution of the word count in dialog utterance. (iii) Service Coverage Distribution in Dialogs. (iv) Distribution of plot actions (Actions with > 3% inclusion). Note: All distributions are flattened, e.g. each service or action in multi-intent dialogs individually

#### **5** Dataset Statistics

The current TOAD dataset covers 11 service domains with 37,678 turns (18,839 user turn and 113,034 system response variations, 131,873 turns in total) in 8,087 dialogues. It's worth highlighting that as TOAD operates as an automatic generation pipeline, both datasize and covered service can be scaled up. Additionally, the creation of a new service schema typically requires only 15 minutes.

Across the 8087 dialogs, 40.5% are multi-intent compound, 20.9% are compositional and 38.6% are single intent. The distributions of the number of turns and word counts in utterances are shown in Fig. 4(i) and (ii) respectively. As for local phenomena, 19.0% dialog are self-revision, 15.1% have complex referral, 3.3% have both and 62.6% have no local phenomena. Note that local phenomena can appear in both single and multi-intent dialog.

Fig. 4(iii) illustrates the service distribution which is relatively uniform for single intent and compound dialogs. However, in compositional dialog, due to the joint sample requirement, certain services may have less matchable slots. Scaling up the supporting services in the schema can potentially expand the joint service sample pool.

As mentioned above, TOAD does not have a fixed set of plot actions. Fig. 4(iv) displays the distribution of actions whose occurrences are greater than 3%. Based on the selection rules for the default response style, 61.7% of the system responses are default high verbosity, 28.8% and 9.5% are mid and low verbosity. The average word counts for

these three levels are 17.6, 9.0 and 2.5 respectively.

497

498

499

500

501

502

504

505

506

507

508

509

510

511

512

513

514

515

516

517

518

519

520

521

522

523

524

525

526

527

## 6 Evaluation

TOAD data supports a range of TOD tasks, including Intent Detection, Slot Labeling in Natural Language Understanding, Dialog or Action State Tracking (D/AST) and Natural Language Generation (NLG). This paper establishes benchmarks for two response generation setups, aligning with TOAD's primary objective of producing more natural, realistic dialogues and diverse response styles.

## 6.1 **Response Generation Benchmarks**

The first benchmark setup is a traditionally surface realization setup, where a dialog action is aimed to convert into a natural language utterance (Williams and Young, 2007) The second, following Hu et al. (2023), is 'oracle' language model setup, where both previous dialog history and current action are available to produce the target utterance. For both setups, the target verbosity and mirroring option are given as part of the input.

We partition the TOAD dataset into three sets: a training set ( $\approx 81.8\%$ ), a test set (10%), and a zero-shot test set ( $\approx 8.2\%$ ) containing dialogs exclusively related to the 'banking' service. The zeroshot test set aims to assess models' generalization ability to unseen services.

Each response style option is treated as an individual datapoint. The surface realization setup only includes non-mirroring response options, as it does not have access to previous dialog utterances. Whereas, the oracle language model setup consid-

495

496

465

466

	Act to Text					DH+Act to Text								
Model	Test			Zer	Zero-shot Test			Test			Ze	Zero-shot Test		
	В	R	Μ	В	R	Μ		В	R	Μ	В	R	Μ	
FlanT5-250m	44.8	61.8	65.0	28.4	51.5	55.1		54.2	67.2	69.4	38.3	55.3	59.3	
FlanT5-3b	45.5	62.4	65.6	34.2	54.3	56.9		52.8	67.5	70.9	41.9	59.2	64.0	
FlanT5-11b	43.0	60.9	64.2	35.9	57.8	60.8		54.9	68.9	72.0	44.7	59.2	63.3	
Llama2-7b	41.4	61.1	63.5	31.3	52.2	54.0		48.2	62.9	65.1	40.6	54.6	61.5	
Llama2-13b	41.4	59.6	64.8	34.8	55.5	57.5		49.4	64.0	68.7	42.7	56.0	62.0	

Table 3: Results for two benchmarks, Action to utterance and Dialog History (DH)+Action to utterance, reported in BLEU(B), Rouge-L(R) and Meteor(M) scores. All models are fine-tuned on the train set and evaluated on test and zero-shot test sets.

ers all six options. In total, the two setups have 56.5K and 113K datapoints respectively

We applied supervised fine-tuning (SFT) to five baseline models from two LM families: Encoderdecoder models, including FlanT5-(base, XL and XXL) (Chung et al., 2022), with parameter sizes of 250M, 3B and 11B respectively, and decoder-only models Llama2-(7b, 13b) (Touvron et al., 2023). The SFT hyper-parameters are provided in Appendix F.

We evaluate model predictions using three widely-used NLG metrics: BLEU (Papineni et al., 2002), ROUGE-L (Lin and Hovy, 2002) and ME-TEOR (Banerjee and Lavie, 2005) scores. The results are reported in Tab. 3. In both setups, we observed that performance is generally better on the test set compared to the zero-shot test set, and increasing model sizes can improve the performance on both sets. However, the performance gaps between the test and zero-shot test sets become smaller for LMs with increasing sizes, which we believe is due to the increasing zero-shot generalization ability of larger LMs.

Additionally, we consistently observe that the oracle language model setup outperforms the surface realization setup, which means having extra information of the dialog history can steadily improve the response generation performance.

## 6.2 Predictions on Different Response Styles

In this section, we explore the modeling difficulty posed by different response styles. In Tab. 4, we compare the performances on mirroring and nonmirroring responses as well as the performances across different verbosity styles. All results are evaluated on the predictions generated by the oracle language model setup on the test set.

We consistently noting that the performance on mirroring responses is better than non-mirroring

Model	Mirror			Verbosity				
WIGGET	w.	w./o.		High	Mid	l Low		
FlanT5-250m	56.0	47.8		45.3	49.8	51.0		
FlanT5-3b	59.4	49.0		45.8	49.9	52.6		
FlanT5-11b	59.2	49.4		46.4	50.1	53.2		
Llama2-7b	49.3	43.6		38.1	43.6	50.5		
Llama2-13b	51.5	45.3		39.7	45.8	52.3		

Table 4: Results for inferring mirroring and nonmirroring responses, reported in BLEU score. All LMs are fine-tuned with the train set under DH+Act to utterance setting.

ones, as expected, given that mirroring allows the system to replicate user expressions directly from the dialog history, making it easier to predict. We also observe that as verbosity increases, performance tends to decrease. This decline is likely attributed to lower verbosity resulting in shorter utterances with a reduced vocabulary, making them easier to model.

Another observation worth noticing is that, even for non-mirroring options, having access to dialog history can yield improved modeling performance, as evident when comparing the left-most column of Tab.3 with the second left-most column of Tab.4.

# 7 Conclusion

In conclusion, our study explores the naturalness and adaptiveness of system responses for the next generation of TOD virtual assistants. We introduce TOAD, a dataset designed to train TOD systems for diverse verbosity levels, mirroring styles, and realistic app context interactions. Additionally, we present a cost-effective and scalable automatic data generation pipeline as a practical alternative to traditional human annotations. By addressing those critical gaps, we aim for TOAD to inspire future exploration in modeling and analyzing system response styles.

558

559

560

561

564

528

572

573

574

575

576

577

578

579

580

581

582

583

584

585

586

587

588

589

590

591

566

567

8

Limitations

TOAD's construction:

**Entities** The names and entities are generated by

ChatGPT, therefore some of them are figures from

Difficult cases for style modeling When produc-

ing the six response styles, certain scenarios pose

challenges to model desired styles, which means

the difference between some styles might become

less evident. We listed some observations during

• In cases when the system needs to present

new information to the user, such as report-

ing database search results, in order to pro-

vide necessary information, sometimes low

verbosity option can be relatively lengthy.

• When the system is requesting value for a new

may not have mentioned the required slots. The use of proper referring expressions in user

slot, it usually struggles to mirror users, who

interactions with contextual apps can result in

responses that are very similar between mir-

**Term of Use** The dataset and generation pipeline

Persona Bias in TOAD The persona, e.g., eth-

nicity, gender, and occupation distributions of

the TOAD dataset are elaborated in detail in Ap-

Satanjeev Banerjee and Alon Lavie. 2005. METEOR:

An automatic metric for MT evaluation with im-

proved correlation with human judgments. In Pro-

ceedings of the ACL Workshop on Intrinsic and Ex-

trinsic Evaluation Measures for Machine Transla-

tion and/or Summarization, pages 65–72, Ann Arbor,

Michigan. Association for Computational Linguis-

Paweł Budzianowski, Tsung-Hsien Wen, Bo-Hsiang

Tseng, Iñigo Casanueva, Stefan Ultes, Osman Ra-

madan, and Milica Gašić. 2018. MultiWOZ - a large-

scale multi-domain Wizard-of-Oz dataset for task-

oriented dialogue modelling. In Proceedings of the

2018 Conference on Empirical Methods in Natural

Language Processing, pages 5016–5026, Brussels,

Belgium. Association for Computational Linguistics.

Tao, Seokhwan Kim, Andy Rosenbaum, Yang Liu,

and Dilek Hakkani-Tür. 2023. Places: Prompting

Maximillian Chen, Alexandros Papangelis, Chenyang

of TOAD is released under CC-BY 4.0 license.

roring and non-mirroring styles.

**Ethics and Risks** 

9

pendix E.

tics.

References

publications, such as movies or novels.

- 594
- 595

- 599

- 604

- 610
- 611
- 612
- 613
- 615

616

619

622

623 624

- 631
- 632 633

634 635

636 637

638

language models for social conversation synthesis. In EACL 2023.

641

642

643

644

645

646

647

648

649

650

651

652

653

654

655

656

657

658

659

660

661

662

663

664

665

666

667

670

671

672

673

674

675

676

677

678

679

680

682

683

684

685

686

687

688

689

690

691

692

693

694

695

696

- Hyung Won Chung, Le Hou, Shayne Longpre, Barret Zoph, Yi Tay, William Fedus, Yunxuan Li, Xuezhi Wang, Mostafa Dehghani, Siddhartha Brahma, et al. 2022. Scaling instruction-finetuned language models. arXiv preprint arXiv:2210.11416.
- Ning Ding, Yulin Chen, Bokai Xu, Yujia Qin, Zhi Zheng, Shengding Hu, Zhiyuan Liu, Maosong Sun, and Bowen Zhou. 2023. Enhancing chat language models by scaling high-quality instructional conversations. arXiv preprint arXiv:2305.14233.
- Long Duong, Vu Cong Duy Hoang, Tuyen Quang Pham, Yu-Heng Hong, Vladislavs Dovgalecs, Guy Bashkansky, Jason Black, Andrew Bleeker, Serge Le Huitouze, and Mark Johnson. 2019. An adaptable task-oriented dialog system for stand-alone embedded devices. In Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics: System Demonstrations, pages 49–57, Florence, Italy. Association for Computational Linguistics.
- Layla El Asri, Hannes Schulz, Shikhar Kr Sarma, Jeremie Zumer, Justin Harris, Emery Fine, Rahul Mehrotra, and Kaheer Suleman. 2017a. Frames: a corpus for adding memory to goal-oriented dialogue systems. In Proceedings of the 18th Annual SIGdial Meeting on Discourse and Dialogue, pages 207–219.
- Layla El Asri, Hannes Schulz, Shikhar Sharma, Jeremie Zumer, Justin Harris, Emery Fine, Rahul Mehrotra, and Kaheer Suleman. 2017b. Frames: a corpus for adding memory to goal-oriented dialogue systems. In Proceedings of the 18th Annual SIGdial Meeting on Discourse and Dialogue, pages 207-219, Saarbrücken, Germany. Association for Computational Linguistics.
- Simon Garrod and Martin J Pickering. 2009. Joint action, interactive alignment, and dialog. Topics in *Cognitive Science*, 1(2):292–304.
- Rahul Goel, Waleed Ammar, Aditya Gupta, Siddharth Vashishtha, Motoki Sano, Faiz Surani, Max Chang, HyunJeong Choe, David Greene, Kyle He, et al. 2023. Presto: A multilingual dataset for parsing realistic task-oriented dialogs. arXiv preprint arXiv:2303.08954.
- Matthew B Hoy. 2018. Alexa, Siri, Cortana, and more: an introduction to voice assistants. Medical reference services quarterly, 37(1):81-88.
- Songbo Hu, Han Zhou, Mete Hergul, Milan Gritta, Guchun Zhang, Ignacio Iacobacci, Ivan Vulić, and Anna Korhonen. 2023. Multi3woz: A multilingual, multi-domain, multi-parallel dataset for training and evaluating culturally adapted task-oriented dialog systems. arXiv preprint arXiv:2307.14031.
- JF Kelley. 1984. Iterative design methodology for userfriendly natural language office information applications. ACM Trans. Off. Syst.; (United States), 1.
- 9

Hyunwoo Kim, Jack Hessel, Liwei Jiang, Peter West, Ximing Lu, Youngjae Yu, Pei Zhou, Ronan Le Bras, Malihe Alikhani, Gunhee Kim, Maarten Sap, and Yejin Choi. 2023. Soda: Million-scale dialogue distillation with social commonsense contextualization.

700

704

706

707

711

712

713

715

716

719

722

725

731

735

736

737

738

739

740

741

742

743

744

745

746

747

749

- Satwik Kottur, Seungwhan Moon, Alborz Geramifard, and Babak Damavandi. 2021. SIMMC 2.0: A taskoriented dialog dataset for immersive multimodal conversations. In *Proceedings of the 2021 Conference on Empirical Methods in Natural Language Processing*, pages 4903–4912, Online and Punta Cana, Dominican Republic. Association for Computational Linguistics.
- Stefan Larson and Kevin Leach. 2022. A survey of intent classification and slot-filling datasets for task-oriented dialog.
- Yuting Liao and Jiangen He. 2020. Racial mirroring effects on human-agent interaction in psychotherapeutic conversations. In *Proceedings of the 25th international conference on intelligent user interfaces*, pages 430–442.
- Chin-Yew Lin and Eduard Hovy. 2002. Manual and automatic evaluation of summaries. In *Proceedings of the ACL-02 Workshop on Automatic Summarization*, pages 45–51.
- Jakub Macina, Nico Daheim, Sankalan Pal Chowdhury, Tanmay Sinha, Manu Kapur, Iryna Gurevych, and Mrinmaya Sachan. 2023. Mathdial: A dialogue tutoring dataset with rich pedagogical properties grounded in math reasoning problems.
- Johannes EM Mosig, Shikib Mehri, and Thomas Kober. 2020. Star: A schema-guided dialog dataset for transfer learning. *arXiv preprint arXiv:2010.11853*.
- Kishore Papineni, Salim Roukos, Todd Ward, and Wei-Jing Zhu. 2002. Bleu: a method for automatic evaluation of machine translation. In *Proceedings of the* 40th annual meeting of the Association for Computational Linguistics, pages 311–318.
- Abhinav Rastogi, Xiaoxue Zang, Srinivas Sunkara, Raghav Gupta, and Pranav Khaitan. 2020. Towards scalable multi-domain conversational agents: The schema-guided dialogue dataset. In *Proceedings of the AAAI conference on artificial intelligence*, volume 34, pages 8689–8696.
- Pararth Shah, Dilek Hakkani-Tür, Gokhan Tür, Abhinav Rastogi, Ankur Bapna, Neha Nayak, and Larry Heck.
  2018. Building a conversational agent overnight with dialogue self-play. arXiv preprint arXiv:1801.04871.
- Hugo Touvron, Louis Martin, Kevin Stone, Peter Albert, Amjad Almahairi, Yasmine Babaei, Nikolay Bashlykov, Soumya Batra, Prajjwal Bhargava, Shruti Bhosale, et al. 2023. Llama 2: Open foundation and fine-tuned chat models. *arXiv preprint arXiv:2307.09288*.

Alexander V Vartanov, Sofia A Izbasarova, Yulia M Neroznikova, Igor M Artamonov, Yana N Artamonova, and Irine I Vartanova. 2023. The effect of psychological mirroring in telecommunicative dialogue. *Cognitive Systems Research*, 80:110–117. 751

752

753

754

755

756

757

758

759

761

762

763

765

766

767

768

769

770

771

772

773

774

775

776

777

778

779

780

781

782

783

784

785

789

790

791

792

793

794

795

796

797

798 799

800

801

802

803

804

805

- Jason Wei, Xuezhi Wang, Dale Schuurmans, Maarten Bosma, Fei Xia, Ed Chi, Quoc V Le, Denny Zhou, et al. 2022. Chain-of-thought prompting elicits reasoning in large language models. *Advances in Neural Information Processing Systems*, 35:24824–24837.
- Tsung-Hsien Wen, David Vandyke, Nikola Mrkšić, Milica Gasic, Lina M Rojas Barahona, Pei-Hao Su, Stefan Ultes, and Steve Young. 2017. A network-based end-to-end trainable task-oriented dialogue system. In *Proceedings of the 15th Conference of the European Chapter of the Association for Computational Linguistics: Volume 1, Long Papers*, pages 438–449.
- Jason D Williams and Steve Young. 2007. Partially observable markov decision processes for spoken dialog systems. *Computer Speech & Language*, 21(2):393– 422.
- Canwen Xu, Daya Guo, Nan Duan, and Julian McAuley. 2023. Baize: An open-source chat model with parameter-efficient tuning on self-chat data.
- Zhao Yan, Nan Duan, Peng Chen, Ming Zhou, Jianshe Zhou, and Zhoujun Li. 2017. Building task-oriented dialogue systems for online shopping. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 31.
- Steve Young. 2010. Cognitive user interfaces. *IEEE* Signal Processing Magazine, 27(3):128–140.
- Susan Zhang, Stephen Roller, Naman Goyal, Mikel Artetxe, Moya Chen, Shuohui Chen, Christopher Dewan, Mona Diab, Xian Li, Xi Victoria Lin, Todor Mihaylov, Myle Ott, Sam Shleifer, Kurt Shuster, Daniel Simig, Punit Singh Koura, Anjali Sridhar, Tianlu Wang, and Luke Zettlemoyer. 2022. Opt: Open pretrained transformer language models.

## A Schema Details and Example

The schema is defined in JSON format. For each service, there are a list of supporting intents and a list of slots. For each intent, there are lists of "required\_slots", "optional\_slots" and "result\_slots". There are also meta-indicators to control the plot construction for that intent.

```
{
    "service_name": "calendar_events",
    "intent_operations": [
    {
        "name": "create",
        "description": "Create a calendar
        event.",
        "require_input_values": true,
        "require_context": false,
        "require_confirmation": false,
```

```
"return_list": false,
                   "report_result": false,
                   "check_on_input": false,
808
                   "can_refer_to_input_slot": true,
                   "minimum_input_slot_number": 1,
810
                   "minimum_initial_slots": [],
                   "summary_emphasis_slots": [],
812
                   "required_slots": [
                     "date",
814
815
                     "start_time",
                     "duration_time'
816
817
                   ],
818
                    optional_slots": [
                      attendees",
819
                     "name",
820
                     "location"
                   ],
                   "result_slots": []
823
824
                }
              ],
825
              "slots": [
826
                {
                   "name": "date",
"description": "The date of the
830
                       calendar event."
                   "potential_values": [],
                   "alias": ["start_date"]
832
833
                }
835
                   "name": "start_time",
                   "description": "The time of the
837
                       calendar event."
838
                   "potential_values": [],
                   "alias": ["time"]
840
                },
                {
                   "name": "duration_time",
                   "description": "The duration_time
                       of the calendar event.",
                   "potential_values": [],
                   "alias": []
                }
              ]
849
            }
```

813

821

822

827

841

847

850

852

853

Listing 1: Schema example for intent "create" of service "calendar\_events" with parts of the relevent slots.

#### B **Data Structure**

Each datapoint contains a multi-turn dialog action plot and corresponding utterances, each system turn contains 6 styles of responses and an indicator of the default style. Each datapoint also contains a user persona, relevant app contexts and labels for services, intents and phenomena.

#### С Intents and slot values sampling

The intent sampling for single-intent dialog is straightforward. A service is randomly sampled 859 first and then one of the supported intents is ran-860 domly sampled. For compound dialog, two intents are sampled by this method.

As for compositional dialog, intents are sampled based on the slot matching strategy, because the output slot of the inner intent,  $s_{output}^{inner}$ , will be used as the input slot of the outer intent,  $s_{input}^{outer}$ . As shown in the compositional example in Tab. 2, the output slot of the inner intent "check" is "date", which is passed to the outer intent "get weather" The slot matching strategy as the input slot. does not require  $s_{output}^{inner}$  and  $s_{input}^{outer}$  to be exactly the same, instead, it only requires  $s_{input}^{outer}$  being a super-set of  $s_{output}^{inner}$ . For example, in the phrase "Book an alarm at the time when the show begins," the  $s_{input}^{outer}$  ="time" is the super-set of the  $s_{output}^{inner}$  ="showtime". As shown in the schema example in Listing 1, for each slot, its parent slot is assigned in "alias".

863

864

865

866

867

868

869

870

871

872

873

874

875

876

877

878

879

880

881

882

883

884

885

886

887

888

889

891

892

893

894

895

896

897

898

899

900

901

902

903

904

905

906

907

908

909

910

To ensure the consistency among the slot values, all values are generated by LLM within one inference. The input slot values are generated first, such that the output slot values can condition on them.

#### **Multi-intent plot merging** D

Compound dialog contains two intents. When constructing the plot for compound dialog, the plots for two individual intents are merged into one, but with certain merging rules to maintain the naturalness of the conversation flow. Here are the merging policy:

- Initial user query: Concatenate the actions of two individual initial queries and realize them into one single user utterance.
- For system response: If both system responses require user information, arrange the responses into two subsequent turns. Otherwise, combine two system responses into a single turn, but re-ordered to keep confirmation responses first.
- For subsequent user turn: Only answer the system response.

As for compositional dialog, the initial user queries will be merged by substituting the matching input slot of the outer intent with the inner intent action, as illustrated in Tab.2. Then the rest of the plots will be rearranged that the system should always finish the plot for the inner intent first.

#### Persona and App Context Statistics Е

In TOAD, we simulate 300 personas with diverse backgrounds, with one persona randomly assigned to each dialog as the user's information source. 911The gender distribution of the simulated personas912is approximately 52% male and 48% female.

913

914

915

916

917

918

919

921

922

923

924

926

927

928

929 930

931

932

933

Examining the racial distribution, we find that 17% are White, 10% Hispanic or Latino, 6% Black or African American, 4% Asian or Pacific Islander, 4% American Indian or Alaska Native, and 59% are not specified. The job descriptions encompass a total of 67 distinct occupations categorized into four job levels: senior (18%), intermediate (31%), entry-level (22%), and not-specified (29%).

In terms of context app distribution, the dialogs are diversified with 17.9% involving calendar events, 13.5% messages, 13.5% reminders, 13.1% alarms, 8.9% contacts, and 33.1% having no specified context.

# F SFT hyperparameters

SFT batch sizes for FlanT5-250m, 3b, 11b are 16, 16, and 4, respectively. Llama2-7b and 13b have batch sizes set at 2. The learning rates are 3e - 5, and fine-tuning halts upon meeting the early stopping criterion, which is 5 consecutive increases in validation set loss.

G Plot and Dialog Examples

We show more dialog and action plot examples inTab. 5.

App Context	Action Plot	Dialog Utterances
<pre>{'today':'Wed 2025-04-16', 'alarms':[{'time':'07:00', 'name':'Morning Workout', ' if_repeat':True}, {'time':' 18:30', 'name':'Family Dinner', 'if_repeat':True }]</pre>	<pre>User: [get_alarms(ordered_by=" time", index=0).alarms_delete( name), get_alarms(ordered_by=" time", index=1).alarms_check(name )] System: [alarms_ask_confirm(get_ alarms(name="Morning Workout"). delete(name)), alarms_inform_ result(name="Family Dinner")] User: alarms_confirm() System: alarms_notify_done(get_ alarms(name="Morning Workout"). delete(name))</pre>	<pre>User: Can you delete my earliest alarm and check the next one? System: { HV M: Are you sure you want to delete the ' Morning Workout' alarm? Your next alarm is ' Family Dinner' at 18:30. HV no_M: Do you confirm the deletion of your earliest alarm, 'Morning Workout'? The following alarm is 'Family Dinner' at 18:30. MV M: You want to delete the 'Morning Workout' alarm, correct? Your next one is 'Family Dinner ' at 18:30. MV no_M: Confirm to delete this alarm? The next one is at 18:30 for 'Family Dinner'. LV M: Delete 'Morning Workout'? Next: 'Family Dinner' 18:30. LV no_M: Confirm deletion? Next: 18:30 'Family Dinner'. } User: Yes, go ahead and delete it. System: { HV M: Your 'Morning Workout' alarm has been deleted. HV no_M: The earliest alarm has been deleted. MV M: 'Morning Workout' alarm is deleted. MV M: 'Morning Workout' alarm is deleted. MV M: Deleted. LV no_M: Done.}</pre>
{'today':'Mon 2026-12-28'}	<pre>User: purchase_tickets(movie_name ="Joker", date="Tue 2026-12-29", cinema_name="Regal Cinemas", ticket_quantity=1, movie_format ="3d") System: request_infomation( showtime) User: inform_infomation(showtime ="20:00") System: ask_confirm(purchase_ tickets(movie_name="Joker", ticket_quantity=1, date="Tue 2026-12-29", showtime="20:00", movie_format="3d", cinema_name=" Regal Cinemas")) User: confirm() System: notify_done(purchase_ tickets(movie_name="Joker", ticket_quantity=1, date="Tue 2026-12-29", showtime="20:00", movie_format="3d", cinema_name=" Regal Cinemas"))</pre>	<pre>User: I'd like to buy a 3D ticket for Joker at Regal Cinemas tomorrow, please. System: { HY M: What time would you like to watch Joker at Regal Cinemas tomorrow? HY no_M: What showtime do you prefer? MY M: When would you like to see it? MY no_M: When is the preferred time? LV M: Showtime? LV no_M: Time? } User: At 20:00. System: { HY M: So, you'd like to purchase a 3D ticket for Joker at Regal Cinemas on Tue 2026-12-29 at 20:00. Is that correct? HY no_M: Just to confirm, you want to buy a 3D ticket for the movie Joker at Regal Cinemas on Tue 2026-12-29 at 20:00, right? MY M: You're buying a 3D ticket for Joker at Regal Cinemas tomorrow at 20:00. Correct? MY no_M: So, you're purchasing a ticket for Joker in 3D at Regal Cinemas tomorrow at 20:00. Is that right? LV M: Confirm purchase? LV no_M: Confirm? } User: Yes, that's correct. System: { HY M: Your 3D ticket for Joker at Regal Cinemas on Tue 2026-12-29 at 20:00 has been purchased. HY M: Your 3D ticket has been successfully purchased. MY M: I've bought your ticket for that movie at that time. MY no_M: It's done, the ticket is bought. LV M: Done. LV no_M: Purchased. }</pre>

Table 5: Datapoint examples showing app context, action plots and dialog utterances with all response style options.

# H Dialog Generator template

936

#### Prompt template for user utterance generation

```
""" " \
You are a smartphone user and you are testing your virtual assistant on your phone
by ∖
engaging in a multi-turn conversations with it.
Here is your personal introduction: {{ user_intro }}
Instructions:
1. You need to communicate with the assistant following the guidance of "actions".
2. Based on the introduction, think about what speech habit you should have and \
communicate with this pattern.
3. The "message" should have minimum words possible.
4. You must return in JSON format, following the provided examples.
The context information is: {{ context }}.
You are using these apps: {{ situation }}.
Begin conversation (you are identified as "user").
user: {"actions": ["hello()"], "message": "Hi."}
assistant: {"actions": ["offer_help()"], "message": "Hello, how can I help?"}
{% if dialog_history | length>0 %}{{ dialog_history }}{% endif %}
The "actions" you need to follow is {{ action[cur_turn] }}. What are you going to
say next? ∖
{{ user_style_instruction }}
user:\
......
```

Table 6: Prompt template example for the user role in the dialog generator

Prompt template for system utterance generation

```
" " " \
Instructions:
1. You are a virtual assistant. Your goal is to assist the user to accomplish their
goal.
2. Your responses should strictly follow the given actions and be helpful, natural,
professional and concise.
3. Your response should strictly follow the corresponding "actions".
The user is interacting with these apps: {{ situation }}.
Style instruction:
'verbosity_low': Your response must only have a couple of words, such as "when", \setminus
"how long" or "done".
'verbosity_mid': Your response should be a concise but complete sentence and must \
replace the nouns or noun phrases mentioned by user with pronouns, such as "it",
that" and "its".
'verbosity_high': Your response should use full expressions with all the details.
'mirroring': Your response should use the user's noun phrase or verb expressions
when possible.
'no_mirroring': Ignore all previous dialog. Do not affect by user expression.
'summary': Your response should be a brief report of the given summary.
Response Example:
assistant actions: {"verbosity_low mirroring": ["notify_done()"], \
"verbosity_low no_mirroring": ["notify_done()"], \
"verbosity_mid mirroring": ["notify_done(operation_on_device()"]
operation="turn_off", device="heating", home_space="bedroom"))"], \
"verbosity_mid no_mirroring": ["notify_done(operation_on_device(\
operation="turn_off", device="heating", home_space="bedroom"))"], \
"verbosity_high mirroring": ["notify_done(operation_on_device(\
operation="turn_off", device="heating", home_space="bedroom"))"], \
"verbosity_high no_mirroring": ["notify_done(operation_on_device(\
operation="turn_off", device="heating", home_space="bedroom"))"]}
assistant: {"verbosity_low mirroring": "Turned off.", \
"verbosity_low no_mirroring": "Done.", \
"verbosity_mid mirroring": "I have turned off the heating in that room.", \
"verbosity_mid no_mirroring": "I have turned it off in that room.", \
"verbosity_high mirroring": "I have turned off the bedroom heating.",
"verbosity_high no_mirroring": "Sure, I have turned off the heating in the bedroom
. "}
Conversation history:
{% if dialog_history | length>0 %}{{ dialog_history }}{% endif %}
New turn:
You should return in JSON format with 6 keys: ["verbosity_low mirroring", \setminus
"verbosity_low no_mirroring", "verbosity_mid mirroring", "verbosity_mid no_mirroring
 . \
"verbosity_high mirroring", "verbosity_high no_mirroring"].
assistant actions: {{ action[cur_turn] }}.
assistant: ∖
.....
```

Table 7: Prompt template example for the system role in the dialog generator