

# An Evaluation of Large Language Models in Bioinformatics Research

Anonymous authors

Paper under double-blind review

## Abstract

Large language models (LLMs) such as ChatGPT have gained considerable interest across diverse research communities. Their notable ability for text completion and generation has inaugurated a novel paradigm for language-interfaced problem solving. However, the potential and efficacy of these models in bioinformatics remain incompletely explored. In this work, we study the performance GPT variants on a wide spectrum of crucial bioinformatics tasks. These tasks include the identification of potential coding regions, extraction of named entities for genes and proteins, detection of antimicrobial and anti-cancer peptides, molecular optimization, and resolution of educational bioinformatics problems. Our findings indicate that, given appropriate prompts, LLMs like GPT variants can successfully handle most of these tasks. In addition, we provide a thorough analysis of their limitations in the context of complicated bioinformatics tasks. We envision this work to provide new perspectives and motivate future research in the field of both LLM applications and bioinformatics.

## 1 Introduction

Large language models (LLMs) (Birhane et al., 2023; Katz et al., 2022; Li et al., 2022) such as GPT variants, which are neural network models trained on large amounts of unlabeled data, have recently attracted significant attention across a variety of research communities. Trained with a combination of unsupervised pre-training, supervised fine-tuning, and human feedback, LLMs can generate fluid and reasonable contextual conversations with text-based input queries, i.e. *prompts*. Such a natural language interface offers a versatile problem-solving platform, addressing tasks from text drafting to mathematical problem solving (Ouyang et al., 2022; Xu et al., 2023), which exceeds the capabilities of traditional single natural language processing models (Pang et al., 2002; Marrero et al., 2013; Lee et al., 2011). It is particularly noted that LLMs have demonstrated remarkable proficiency in human-like language generation and exhibited a discernible level of reasoning ability (Liu et al., 2023a; Sun et al., 2022).

In an endeavor to comprehensively understand the capabilities of LLMs, numerous studies have assessed their performance across a variety of language tasks (Zhang et al., 2023; Beltagy et al., 2022). These tasks include reasoning (Bang et al., 2023; Xu et al., 2023), machine translation (Jiao et al., 2023), and question-answering (Tan et al., 2023). Furthermore, the scope of research has been expanded to encompass broader domains. For instance, the applicability of LLMs in AI-assisted medical education has been explored through their ability to answer questions from medical licensing exams Kung et al. (2023); Patel & Lam (2023); Lu et al. (2022). Collectively, these studies suggest that LLMs have the potential to achieve new state-of-the-art performance in traditional tasks and can even establish a new paradigm of research based on interactions with a language model.

So far, a wide range of language models have achieved a great success for bioinformatics tasks (Otmakhova et al., 2022), such as evolutionary scale modeling (ESM) (Lin et al., 2023) and pre-trained models for proteins (Elnaggar et al., 2021). These pre-trained models can be used to predict structure, functionality, and other protein properties, or convert proteins into embedding for downstream tasks. For example, AMP-BERT (Lee et al., 2023) is a fine-tuned model by leveraging protein language model (Elnaggar et al., 2021), which achieves remarkable performance in antimicrobial peptide function prediction. However, these previous

studies often utilize pre-trained language models specific to their domain, and hence they may not be powerful as modern LLMs that are trained using a wide-ranging corpus of text. Moreover, their research typically concentrates on a limited set of tasks, resulting in a lack of systematic and comprehensive investigations into the potential of LLMs for broader bioinformatics research. Evaluating bioinformatics tasks using LLMs can offer a new, effective approach to understanding and solving complex bioinformatics problems, and thus is a research direction of great significance.

In this work, we investigate the potential applications of GPTs on several popular bioinformatics tasks. Our investigation includes a diverse set of tasks that provide a comprehensive evaluation of LLMs within the context of bioinformatics. These tasks comprise the identification of potential coding regions, extraction of named entities for genes and proteins, detection of antimicrobial and anti-cancer peptides, molecular optimization, and addressing educational problems within bioinformatics. To conduct our experiments, we represent chemical compounds, DNA and protein sequences in text format and convert the problem in natural language processing. Then, we feed them into the GPT variants to generate predictions. Our experiments indicate that, given appropriate prompts, GPTs can partially solve these tasks, underscoring the potential utility of GPTs in bioinformatics research. Further analysis of the extensive evaluation leads to three observations. Firstly, with appropriate prompts, GPTs can achieve performance on par with competitive baselines for simple bioinformatics tasks. Secondly, the model has difficulties when faced with more complex tasks; for instance, it may generate non-existing gene name mentions for gene and protein named entity recognition. Lastly, some prompts and model variants could lead to fluctuating the performance, which indicates their choices would require further investigation. By shedding light on the strengths and limitations of LLMs in bioinformatics, we hope this work can enhance the utility of LLMs in supporting data-driven research and problem solving within bioinformatics and pave the way for future research directions.

## 2 Related Work

### 2.1 Large Language Models (LLMs)

With the development of ChatGPT, LLMs have become popular in the artificial intelligence community, which involve billions of parameters. Among various LLMs, ChatGPT has made impressive impacts by showing remarkable performance in zero-shot human-machine interaction (Jahan et al., 2023). To understand the capacity and limitations of LLMs, the evaluation of these LLMs has received extensive interest, especially on NLP tasks such as reasoning (Bang et al., 2023), machine translation (Jiao et al., 2023) and question answering (Tan et al., 2023). For example, ChatGPT has shown extraordinary performance on zero-shot dialogue understanding with the help of proper prompts (Wysocka et al., 2023; Liu et al., 2023b). Although ChatGPT suffers from several limitations in several tasks, the evaluation can also help the enhancement of ChatGPT as the version is updated. However, existing works on the evaluation of LLMs mostly focus on NLP tasks (Biswas, 2023; Shyr et al., 2023; Li et al., 2023; Pu & Demberg, 2023) while the evaluation for Bioinformatics is still underexplored. As a result, we aim to evaluate LLMs on a range of bioinformatics tasks to give insights to the AI for science community.

### 2.2 Language Models for Bioinformatics

Bioinformatics has been an important field involving the collection and analysis of biological data such as DNA sequences and protein structures. Language models have been applied to solve various bioinformatics tasks, such as transforming amino acids into different embeddings using protein language models, which can be used for downstream protein understanding. Recently, one of the most impressive applications is AlphaFold2 (Cramer, 2021), which employs a transformer architecture to predict protein structures from amino acid sequences. It has demonstrated remarkable accuracy in predicting protein folding, outperforming traditional methods and highlighting the potential of large-scale models in this domain. Language models have inspired the development of drug discovery and design tasks as well (Deng et al., 2022). For instance, inspired by the success of BERT (Devlin et al., 2018), MolBERT (Fabian et al., 2020) is developed for predicting molecular properties and generating novel molecular structures. MolBERT demonstrates the capacity of language models to generate de novo molecules and predict their physicochemical properties,

which can be invaluable in the drug discovery process. In this paper, we study the power of LLMs to directly solve various bioinformatics problems, which can inspire the development of AI for science.

We also notice that there are two works on the evaluation of LLMs related to bioinformatics (Shue et al., 2023; Piccolo et al., 2023). Piccolo et al. (2023) investigate the performance of ChatGPT on bioinformatics programming tasks in educational settings. Shue et al. (2023) produce a tool based on ChatGPT for bioinformatics education. However, these works are a preliminary exploration of ChatGPT for bioinformatics beginners while our work goes deeper and explores more complicated and typical tasks. We believe our work can help gain a more profound understanding of LLMs’ potential in advancing the field of bioinformatics, opening new avenues for data analysis, hypothesis generation, and further automation of complex computational tasks in this area.

### 3 Evaluated Tasks

#### 3.1 Identifying Potential Coding Regions from DNA Sequences

The coding sequence (CDS) (Lubahn et al., 1989; Zhu et al., 2010) are some regions of a DNA or RNA sequence that contain essential information for protein encoding. Identifying these potential coding regions within viral sequences could be a crucial task, as it can aid us in understanding the biological characteristics of the corresponding virus as well as the expression of DNA sequences and genes (Badger & Olsen, 1999). We formalize the task as follows:

**Task 1. (Identifying Coding Regions)** *Our objective is to leverage a machine learning approach to identify as many potential coding regions as possible in the given DNA sequence.*

**Prompts:** *Based on your knowledge, describe as many possible potential coding regions if they exist in frame 1.*

#### 3.2 Identifying Antimicrobial Peptide

Antimicrobial resistance poses a significant threat to public health (Wise et al., 1998). As a potential solution, antimicrobial peptides (AMPs) (Bahar & Ren, 2013) have emerged as a promising solution, due to their broad-spectrum mechanism of action. Typically, AMPs exterminate bacteria and other hazardous organisms through interfering with vital biological components, such as the cell membrane as well as DNA replication mechanisms (Zasloff, 2002). Therefore, the identification of candidate peptides with antimicrobial functions is crucial for developing novel therapeutics. The task is formalized as follows:

**Task 2. (Identifying Antimicrobial Peptide)** *Given the training set, we train a machine learning model which can identify antimicrobial peptides in massive protein sequences.*

**Prompts:** *You are a peptide design researcher. Please tell me if the given peptide sequence has antimicrobial properties.*

#### 3.3 Identifying Anti-cancer Peptide

The majority of anti-cancer drugs have inadequate selectivity, killing both normal and cancer cells without discrimination (Liu et al., 2015). However, anti-cancer peptides (ACPs) function as molecularly targeted peptides that can directly bind to specific cancer cells or organelle membranes, or as binding peptides associated with anti-cancer drugs (Li et al., 2011). As minuscule peptides contain sequences of amino acids, ACPs are cancer-selective and toxic (Tyagi et al., 2015). Therefore, they have emerged as a novel therapeutic strategy that targets some cancer cells specifically (Chiangjong et al., 2020). Considering the extensive time and high costs associated with identifying ACPs through biochemical experimentation, the development of deep learning algorithms for ACPs identification is vital. We formalize the task (Li et al., 2020) as follows:

**Task 3. (Identifying Anti-cancer Peptide)** *Given a training set, we train a machine learning model which can identify anti-cancer peptides in these massive protein sequences.*

**Prompts:** *You are a peptide design researcher. Please tell me whether a peptide with a sequence: N could be an anti-cancer peptide.*

### 3.4 Molecule Optimization

To evaluate the extent of knowledge that GPTs possess in the realms of chemistry and pharmacology, we study their proficiency in optimizing molecular properties. The optimization of molecules represents a pivotal phase in the process of drug discovery (Verdonk & Hartshorn, 2004), allowing for enhancing the desired characteristics (e.g., octanol-water partition coefficients (Sangster, 1997), synthetic accessibility (Ouyang et al., 2021) and drug-likeness (Bickerton et al., 2012)) of drug candidates via targeted chemical modifications. The task is formalized as follows:

**Task 4. (Molecule Optimization)** *Our objective is to modify a given molecule while preserving the primary molecular scaffold, such that certain properties can be enhanced.*

**Prompts:** *You are an expert in the Named Entity Recognition field. Given a token and a sentence that contains gene mentions, you are to generate an ASCII list of identified gene names. Each gene mention will be formatted as follows: sentence-identifier / start-offset end-offset / optional text. Each gene mention from the same sentence will be listed on a separate line. If a sentence doesn't have any gene mentions, it won't be included in the list. Counting numbers need to exclude spaces, sentence-identifiers, and start from 1.*

### 3.5 Gene and Protein Named Entities Extraction

For genes and proteins, a wide variety of alternative names are used in abundant scientific literature or public biological databases, which poses a significant challenge to the gene and protein named mentions finding task. Meanwhile, as new biological entities are continuously discovered (Bruford et al., 2020; Fundel & Zimmer, 2006; Rindfleisch et al., 1999; Blaschke et al., 2002), the diversity of gene and protein nomenclatures also brings some challenges to the gene and proteins named mention extraction task. For instance, the gene names in *Drosophila* (Yeh et al., 2005), a.k.a., the fruit fly (Wangler et al., 2015), can be common English words such as *white*, *dumpy* and *forked*. This nature could lead to a misleading algorithm or recognition model, making it a challenge to accurately extract gene and protein names. Here, we formalize the task as follows:

**Task 5. (Gene and Protein Named Entities Extraction)** *Our objective is to identify potential gene and protein named entities from the given sentences in life science literature.*

**Prompts:** *Assume that you were a medicinal chemist, please make big modifications that go beyond just changing the charge to the following molecule to optimize the octanol-water partition coefficient penalized by synthetic accessibility and ring size. Here's the SMILE string for the molecule, \$SMILES\$, and output the optimized SMILE string, please.*

### 3.6 Evaluation on Educational Bioinformatics Problem-Solving Set

In addition to using various datasets and different case scenarios to demonstrate the performance of GPTs, we also employ a set containing 105 bioinformatics questions for evaluation. These problems originate from Rosalind<sup>1</sup>, an educational platform dedicated to learning bioinformatics and programming through problem solving. The task is formalized as follows:

**Task 6. (Educational Bioinformatics Problem Solving)** *Our objective is to generate corresponding answers to a bioinformatics problem set. These problems primarily encompass seven topics, i.e., String Algorithms, Combinatorics, Dynamic Programming, Alignment, Phylogeny, Probability, and Graph Algorithms.*

**Prompts:** *Each question will be provided as a prompt.*

<sup>1</sup><https://rosalind.info/problems/list-view/>




Figure 1: Illustration of identifying coding regions using GPT-4.

## 4 Results and Discussions

### 4.1 Performance on Identifying Potential Coding Regions

As for identifying potential coding regions (CDS) (Furuno et al., 2003) from DNA sequences, we utilize the understanding abilities of GPT-4 with a corresponding prompt. Since GPT-4 has been trained a variety of internet texts, the analyzing capability of GPT-4 allows it to generate meaningful and contextually appropriate responses.

Our test subject is the DNA sequence of the Vaccinia virus (Goebel et al., 1990) using partial sequence (GeneID: 3707616, ACCESSION Id: NC\_006998.1), and we require GPT-4 to give potential CDS in the first frame. The results are shown in Figure 1. From the results, GPT-4 can successfully deliver the definitions of CDS and Open Reading Frames (ORFs), accurately pinpointing the start codon (usually AUG in RNA or ATG in DNA) and stop codons (UAA, UAG, UGA for RNA or TAA, TAG, TGA for DNA). It generates a list of potential coding regions, specifying their nucleotide lengths and corresponding start and stop codons.

Despite the superior advantage, GPT-4 still misses some potential coding regions. When we directly ask GPT-4 to identify the longest coding region in the first frame, it starts by translating the DNA sequence into an amino acid sequence using the standard genetic code. It then provides a detailed explanation of the

standard genetic code. Unfortunately, it fails to deliver the longest CDS, incorrectly identifying an ORF with 83 codons instead. When we give the hint by raising the ground truth, it can realize its fault. Despite this shortfall, the ability of GPT-4 to solve such a complex task demonstrates its potential as a valuable tool in the analysis of genetic data. In addition, domain experts are necessary to ensure its correctness.

## 4.2 Performance on Identifying Antimicrobial Peptide

As for identifying antimicrobial peptides, in this subsection, we fine-tune the Davinci model<sup>2</sup> to distinguish between AMPs and non-AMPs. We set the number of epochs, batch size and learning rate multiplier during training to 20, 3 and 0.3, respectively. Our selected prompt is as follows: *Assuming the role of a peptide design researcher, please evaluate if a peptide with this particular sequence could qualify as an antimicrobial peptide.*

To access the performance of our fine-tuned model (Davinci-ft), we compared it with several machine learning-based methods, i.e., XGBoost (XGB) (Chen et al., 2015), Multinomial Naive Bayes (MNB) (Kibriya et al., 2005), Support Vector Machines (SVM) (Jakkula, 2006), K-Nearest Neighbor (KNN) (Guo et al., 2003), Logistic Regression (LR) (Maalouf, 2011), MultiLayer Perceptron (MLP) (Pinkus, 1999), Random Forest (RF) (Biau & Scornet, 2016), GBoost (GB) (Saigo et al., 2009), and AMP-BERT (Lee et al., 2023) using two datasets from (Lee et al., 2023). We utilize six widely accepted metrics to assess the performance, namely, sensitivity (SN), specificity (SP), F1-score (F1), accuracy (ACC), area under the Receiver Operating Characteristic curve (AUROC), and area under the Precision-Recall curve (AUPR).

The training set (Lee et al., 2023) is comprised of 1778 AMPs paired with an equal number of non-AMPs. The testing set constitutes 2065 AMPs and 1908 non-AMPs. Importantly, these two data sets have no overlap. In alignment with the comparison methodology outlined by (Lee et al., 2023), we initially perform a 5-repeated 10-fold cross-validation during the fine-tuning stage on the training set. Subsequently, the Davinci-ft model is tested to the testing set. The results for different models on the training and testing sets are shown in Table 1 and Table 2, respectively. From the results, we have the following observations: (1) *Davinci-ft demonstrates the best performance during the 5-repeated 10-fold cross-validation process.* We are surprised by the performance of Davinci-ft. Different from AMP-BERT which is based on ProtTrans (Elnaggar et al., 2021) specifically trained on proteins, Davinci-ft is not a model targeting at proteins. Nevertheless, after fine-tuning procedure, Davinci-ft outperforms the AMP-BERT model across a variety of metrics. In terms of F1-score, Davinci-ft also significantly surpasses the other models. Specifically, it outperforms XGB, MNB, SVM, KNN, LR, MLP, RF, GB, and AMP-BERT by margins of 0.340, 0.190, 0.180, 0.300, 0.180, 0.250, 0.200, 0.310, and 0.042 respectively, which validates the strong capacity of LLMs. (2) *Davinci-ft has the potential to tackle the imbalanced testing set.* As shown in Table 2, for the metrics of SN, ACC, F1, and AUC, AMP-BERT achieves the best performance with scores of 0.876, 0.792, 0.760, and 0.818, respectively. On the SP metric, MNB demonstrates the best performance with a score of 0.750. Though, Davinci-ft achieves the best performance on AUPR with a score of 0.810. This suggests that it still has the potential in handling the imbalance between positive and negative instances in the testing set.

## 4.3 Performance on Identifying Anti-cancer Peptide

As for identifying anti-cancer peptides (ACPs), we also fine-tune the Davinci model (Davinci-ft) to distinguish between ACPs and non-ACPs. We use the same setting during the training process. Our selected prompt is as follows: *Assuming the role of a peptide design researcher, please evaluate if a peptide with this particular sequence could qualify as an anti-cancer peptide.*

Our dataset originates from (Li et al., 2020) encompassing a total of 138 ACPs and 206 non-ACPs. To evaluate the performance of the Davinci-ft model, we compare it with several machine learning-based methods utilizing widely accepted metrics as detailed in Section 4.2. The compared results are shown in Table 3. We observe that for the SN metric, MNB, SVM, LR, MLP, RF, GB and Davinci-ft all achieved top performances. In terms of SP, KNN achieves the highest performance, indicating its superior ability to identify non-ACPs. More importantly, Davinci-ft achieves the best performance in terms of most matrices including MCC,

<sup>2</sup><https://platform.openai.com/docs/models/moderation>

Table 1: The compared cross-validation results of different models for identifying antimicrobial peptides on the training set.

MODEL	SN	SP	F1	ACC	AUROC	AUPR
XGB	0.702	0.566	0.630	0.641	0.734	0.783
MNB	0.815	0.739	0.780	0.800	0.870	0.912
SVM	0.872	0.717	0.790	0.796	0.843	0.897
KNN	0.709	0.622	0.670	0.703	0.674	0.722
LR	0.843	0.735	0.790	0.804	0.836	0.889
MLP	0.792	0.654	0.720	0.731	0.776	0.802
RF	0.867	0.691	0.770	0.772	0.834	0.870
GB	0.775	0.583	0.660	0.646	0.708	0.789
AMP-BERT	0.926	0.930	0.928	0.928	0.966	0.965
Davinci-ft	<b>0.979</b>	<b>0.962</b>	<b>0.970</b>	<b>0.968</b>	<b>0.968</b>	<b>0.978</b>

Table 2: The compared results of different models for identifying antimicrobial peptides on the test dataset.

MODEL	SN	SP	ACC	F1	AUC	AUPR
XGB	0.695	0.630	0.660	0.654	0.714	0.700
MNB	0.687	<b>0.750</b>	0.711	0.746	0.757	0.720
SVM	0.740	0.675	0.706	0.702	0.749	0.697
KNN	0.608	0.687	0.632	0.698	0.691	0.738
LR	0.724	0.676	0.699	0.702	0.746	0.711
MLP	0.701	0.715	0.707	0.730	0.749	0.715
RF	0.714	0.692	0.703	0.715	0.739	0.692
GB	0.708	0.606	0.646	0.616	0.699	0.691
AMP-BERT	<b>0.876</b>	0.635	<b>0.792</b>	<b>0.760</b>	<b>0.818</b>	0.787
Davinci-ft	0.844	0.745	0.718	0.759	0.782	<b>0.810</b>

AUC and AUPRC. In particular, Davinci-ft displays exceptional performance on the crucial AUC metric, outperforming XGB, MNB, SVM, KNN, LR, MLP, RF, and GB by respective margins of 0.187, 0.020, 0.027, 0.063, 0.030, 0.044, 0.003, and 0.136. These results collectively indicate that LLMs can achieve superior performance in identifying anti-cancer peptides.

#### 4.4 Performance on Molecule Optimization

As for molecule optimization, we target at the enhancement of partition coefficients, a.k.a., logP, which can be quantified by Crippen’s logP methodology (Wildman & Crippen, 1999). Meanwhile, we also consider penalties incurred by synthetic accessibility (SA) (Ertl & Schuffenhauer, 2009). Following Bickerton et al. (2012), we also evaluate quantitative results in terms of drug-likeness (QED) scores, which can reflect whether a molecular can be a drug candidate or not. To evaluate the performance of GPT-4, we present a comparative analysis with Modof (Chen et al., 2021), a sophisticated deep generative model. Modof harnesses the capabilities of the junction tree methodology for molecular representation, modifying discrete fragments of the molecule through the employment of variational autoencoders (VAE) (Jin et al., 2018). A molecule dataset is randomly drawn from the Modof test set, which originates from the ZINC database (Sterling & Irwin, 2015).

We summarize the quantitative results in Table 4, and the test examples can be found in Table 6. From the results, we have the following observations:

- *GPT-4 can successfully generate valid SMILES in most cases.* It becomes evident that it has assimilated fundamental principles of physical chemistry. In the 12 cases, GPT-4 can provide valid optimized

Table 3: The compared results of different methods for identifying anti-cancer peptides.

MODEL	SN	SP	ACC	MCC	AUC	AUPRC
XGB	0.846	0.864	0.857	0.700	0.806	0.845
MNB	<b>1.000</b>	0.913	0.943	0.885	0.973	0.973
SVM	<b>1.000</b>	0.875	0.914	0.829	0.966	0.964
KNN	0.929	<b>0.952</b>	0.943	0.881	0.930	0.943
LR	<b>1.000</b>	0.840	0.886	0.775	0.963	0.962
MLP	<b>1.000</b>	0.913	<b>0.943</b>	0.885	0.949	0.958
RF	<b>1.000</b>	0.875	0.914	0.829	0.990	0.984
GB	<b>1.000</b>	0.778	0.829	0.667	0.857	0.875
Davinci-ft	<b>1.000</b>	0.875	0.914	<b>0.892</b>	<b>0.993</b>	<b>0.991</b>

Table 4: The average property improvements of the twelve molecules by GPT-4 and Modof.

Method	$\Delta\log P$	$\Delta SA$	$\Delta QED$
Modof	<b>3.29</b>	0.67	-0.16
GPT-4	1.38	<b>1.04</b>	<b>0.09</b>

molecules for 10 cases, which achieves the comparable performance compared with the superior baseline Modof. In particular, for two cases that Modof fails, GPT-4 can generate valid molecules as in lines 4 and 6.

- *GPT-4 has an advantage in improving both SA and QED.* GPT-4 can achieve higher scores in terms of both SA and QED in most cases. Remarkably, owing to its advanced conversation diagram, GPT-4 is capable of articulating the executed modifications, providing rudimentary rationales behind the alterations.
- *GPT-4 still falls short in improving logP.* The average  $\Delta \log P$  achieved by GPT-4 is about 39.6% of that achieved by Modof. The potential reason is that GPT-4 would tend to remove atomic charges in an attempt to improve the octanol-water partition coefficient instead of modifying the hydrophobic fragments into hydrophilic ones. Such a practice could potentially obliterate significant pharmacophores of a drug. Furthermore, GPT-4 often adopts a more conservative approach to modifying the original molecule, primarily excising some fragments to facilitate synthesis, whereas Modof typically opts to append larger new fragments to the molecule. As a result, the simple and direct modification learned by GPT-4 could be insufficient for improving logP significantly as Modof does.

#### 4.5 Performance on Gene and Protein Named Entity Recognition

As for gene and protein named entity recognition (NER), we evaluate the performance of GPT-3.5 on BioCreative II gene mention (GM) corpus (Yeh et al., 2005). This dataset comprises extensive annotated sentences from MEDLINE (Greenhalgh, 1997), with a primary goal to focus on the extraction of gene and protein named entities. Here, the testing set contains 5,000 sequences. We leverage a prompt to call an API (gpt-3.5-turbo-0613), which evaluates the performance on the testing set without utilizing the training set.

Table 5: The compared results of different models for extracting gene and protein name mention in GM testing set.

Type	Model	P	R	F
Partial matching	BiLSTM	87.98	88.25	88.11
	gpt-3.5-turbo-0613	24.07	7.26	11.17
Strict matching	BiLSTM	72.22	72.44	72.33
	gpt-3.5-turbo-0613	14.5	4.37	6.72






Figure 2: Illustration of gene and protein NER using gpt-3.5-turbo-0613.

We compare the API model with the baseline BiLSTM (Cho & Lee, 2019) using three metrics. The compared results are shown in Table 5, and we observe that the API model would achieve poor performance for extracting genes or proteins from sequences in terms of both partial and strict matching criteria. The former requires the prediction should exactly match the ground truth while the latter allows partially overlaps (Zhang et al., 2021). Here, we analyze two limitations of the API model: (1) *The API model could miss gene mention entities in sentences.* As in Figure 2, in the cases beginning by BC2GM001536665 and BC2GM002436660, the ground truth is "*ERCC3Dm protein*; '*helicase*' domains" and "*Htf9-a gene*; *RanBP1 protein*; *Ran GTPase*", respectively. The API model misses "*helicase*' domains" and reports "*Htf9-a gene*; *RanBP1*; *Ran GTPase*", which results from the confounding gene names in the large corpus. (2) *The API model could misunderstand the gene name.* In the case beginning by BC2GM062242948, the ground truth is supposed to be "*AD1 Ag*"




Figure 3: Comparative performance of GPT-3.5 and GPT-4 in various bioinformatics problem-solving tasks.

while the API model reports "*AD1; Ag; 2H3*", which validates that the API model cannot understand that "*AD1 Ag*" should be considered as a whole rather than separately. Therefore, existing GPT's API models cannot succeed in this complicated task and we would try different prompts and more advanced models to improve the performance.

#### 4.6 Performance on Educational Bioinformatics Problem Solving

As for the evaluation of educational bioinformatics problem solving, we check the performance of two GPT models, GPT-3.5 and GPT-4, across a set of 105 varied problems within the Bioinformatics Stronghold. This collection primarily encompasses seven basic topics as follows: (1) String Algorithms (Baeza-Yates, 1989): This topic focuses on the manipulation and exploration of properties inherent to symbol chains. (2) Combinatorics (Lovász & Prömel, 2004): This scope of problems quantifies distinct objects mathematically. (3) Dynamic Programming (Bellman & Dreyfus, 2015): This topic involves progressively building up solutions to complex problems. (4) Alignment (Edgar & Batzoglou, 2006): This process superimposes symbols of one string over another, inserting gap symbols into the strings as necessary to represent insertions, deletions, and substitutions. (5) Graph Algorithms (Even, 2011): This field involves interpreting and manipulating network structures or graphs. (6) Phylogeny (Field et al., 1988): This topic models the evolutionary trajectories of taxa. (7) Probability (Grinstead & Snell, 1997): This branch of mathematics studies the likelihood of random event occurrences.

We manually collect these 105 problems, individually take them as chat dialogue, and put them into GPT-3.5 and GPT-4. We use the example data set for querying and assessing accuracy. The results related to the seven distinct topics are presented in Figure 3. For a more intuitive illustration, we also select several examples to demonstrate the incorrect and correct responses from GPT-3.5 and GPT-4, as well as their differing performances on the same problems in Figure 4. From the results, we can make the following observations:

- *GPT-4 demonstrates an overall improvement compared to GPT-3.5 across various types of problems.* This is especially evident in *combinatorics* and *graph algorithms*, where GPT-4 achieves success rates of 81.82% and 72.73% respectively, substantially higher than those achieved by GPT-3.5. Even in *Phylogeny* and *Probability*, where both models showed relatively lower performance, GPT-4 again leads with 52.63% and 46.15% success rates, outperforming GPT-3.5's 21.05% and 38.46%. These findings, collated from a




Figure 4: Comparison of GPT-3.5 and GPT-4 in dealing with different tasks.

total of 105 problems, highlight the superior capabilities of GPT-4 in a broad spectrum of bioinformatics challenges, answering 71 questions correctly, compared to GPT-3.5 which correctly solves 53 questions.

- *The performance of GPT-3.5 and GPT-4 is almost consistent across different topics.* Simultaneously, we notice that for probability-related problems, both GPT-3.5 and GPT-4 could only achieve accuracy rates of 36.4% and 46.2% respectively. In contrast, both models are good at solving Combinatorics-related problems, achieving higher accuracy rates of 63.3% for GPT-3.5 and 81.8% for GPT-4.
- *GPT-3.5 exhibits excellent performance in handling relatively simple problems.* As illustrated in Figure 4, when tasked with finding common segments between two DNA sequences, GPT-3.5 is able to respond accurately, providing appropriate program solutions and methods. However, when faced with more complex problems, such as determining the maximum local alignment score of two protein strings, GPT-3.5 could propose incorrect results which are seemingly correct.
- *GPT-4 demonstrates a limited capacity in tackling complex problems.* For instance, as illustrated in Figure 4, when given the exons and introns of a DNA string, we test GPT-4 by deleting the introns, concatenating the exons to form a new string, and then transcribing and translating this newly formed string. GPT-4 successfully manages to remove the introns and translate the DNA into an amino acid sequence. However, for complex logical problems, such as calculating the number of all basepair edges in a bonding graph that can be exactly matched, GPT-4 manages to outline a correct approach but ultimately provides an incorrect answer. Perhaps we need multi-turn interactions to thoroughly solve these complicated problems.

## 5 Conclusion

This paper explores the applications of GPTs in bioinformatics research and evaluates them in six basic tasks, including gene and protein named entities extraction, solving educational bioinformatics problems and identifying potential coding regions, antimicrobial and anti-cancer peptides. Extensive experiments demonstrate that LLMs like GPTs can achieve remarkable performance on the majority of these tasks with proper prompts and models. We hope this work can facilitate researchers in bioinformatics about using advanced LLMs and thus promote the development of AI for science.

## 6 Limitations

Although this work makes the evaluation on six basic bioinformatics tasks, a wide range of sub-regions in bioinformatics have not been considered. In future works, we will build more bioinformatics datasets and make the evaluation on more sub-regions and summarize the strengths and weaknesses more comprehensively.

## References

- Jonathan H Badger and Gary J Olsen. Critica: coding region identification tool invoking comparative analysis. *Molecular Biology and Evolution*, 16(4):512–524, 1999.
- Ricardo A. Baeza-Yates. Algorithms for string searching. In *ACM SIGIR Forum*, volume 23, pp. 34–58, 1989.
- Ali Adem Bahar and Dacheng Ren. Antimicrobial peptides. *Pharmaceuticals*, 6(12):1543–1575, 2013.
- Yejin Bang, Samuel Cahyawijaya, Nayeon Lee, Wenliang Dai, Dan Su, Bryan Wilie, Holy Lovenia, Ziwei Ji, Tiezheng Yu, Willy Chung, et al. A multitask, multilingual, multimodal evaluation of chatgpt on reasoning, hallucination, and interactivity. *arXiv preprint arXiv:2302.04023*, 2023.
- Richard E Bellman and Stuart E Dreyfus. *Applied dynamic programming*, volume 2050. Princeton University Press, 2015.
- Iz Beltagy, Arman Cohan, Robert Logan IV, Sewon Min, and Sameer Singh. Zero-and few-shot nlp with pretrained language models. In *Proceedings of the Annual Meeting of the Association for Computational Linguistics: Tutorial Abstracts*, pp. 32–37, 2022.
- Gérard Biau and Erwan Scornet. A random forest guided tour. *TEST*, 25:197–227, 2016.
- G Richard Bickerton, Gaia V Paolini, Jérémy Besnard, Sorel Muresan, and Andrew L Hopkins. Quantifying the chemical beauty of drugs. *Nature Chemistry*, 4(2):90–98, 2012.
- Abeba Birhane, Atoosa Kasirzadeh, David Leslie, and Sandra Wachter. Science in the age of large language models. *Nature Reviews Physics*, pp. 1–4, 2023.
- Som S Biswas. Role of chat gpt in public health. *Annals of Biomedical Engineering*, 51(5):868–869, 2023.
- Christian Blaschke, Lynette Hirschman, and Alfonso Valencia. Information extraction in molecular biology. *Briefings in Bioinformatics*, 3(2):154–165, 2002.
- Elsbeth A Bruford, Bryony Braschi, Paul Denny, Tamsin EM Jones, Ruth L Seal, and Susan Tweedie. Guidelines for human gene nomenclature. *Nature Genetics*, 52(8):754–758, 2020.
- Tianqi Chen, Tong He, Michael Benesty, Vadim Khotilovich, Yuan Tang, Hyunsu Cho, Kailong Chen, Rory Mitchell, Ignacio Cano, Tianyi Zhou, et al. Xgboost: extreme gradient boosting. *R package version 0.4-2*, 1(4):1–4, 2015.
- Ziqi Chen, Martin Renqiang Min, Srinivasan Parthasarathy, and Xia Ning. A deep generative model for molecule optimization via one fragment modification. *Nature Machine Intelligence*, 3(12):1040–1049, 2021.

- Wararat Chiangjong, Somchai Chutipongtanate, and Suradej Hongeng. Anticancer peptide: Physicochemical property, functional aspect and trend in clinical application. *International Journal of Oncology*, 57(3): 678–696, 2020.
- Hyejin Cho and Hyunju Lee. Biomedical named entity recognition using deep neural networks with contextual information. *BMC bioinformatics*, 20:1–11, 2019.
- Patrick Cramer. Alphafold2 and the future of structural biology. *Nature Structural & Molecular Biology*, 28(9):704–705, 2021.
- Jianyuan Deng, Zhibo Yang, Iwao Ojima, Dimitris Samaras, and Fusheng Wang. Artificial intelligence in drug discovery: applications and techniques. *Briefings in Bioinformatics*, 23(1), 2022.
- Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. Bert: Pre-training of deep bidirectional transformers for language understanding. *arXiv preprint arXiv:1810.04805*, 2018.
- Robert C Edgar and Serafim Batzoglou. Multiple sequence alignment. *Current Opinion in Structural Biology*, 16(3):368–373, 2006.
- Ahmed Elnaggar, Michael Heinzinger, Christian Dallago, Ghalia Rehawi, Yu Wang, Llion Jones, Tom Gibbs, Tamas Feher, Christoph Angerer, Martin Steinegger, et al. Prottrans: Toward understanding the language of life through self-supervised learning. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 44(10):7112–7127, 2021.
- Peter Ertl and Ansgar Schuffenhauer. Estimation of synthetic accessibility score of drug-like molecules based on molecular complexity and fragment contributions. *Journal of Cheminformatics*, 1:1–11, 2009.
- Shimon Even. *Graph algorithms*. Cambridge University Press, 2011.
- Benedek Fabian, Thomas Edlich, Hélène Gaspar, Marwin Segler, Joshua Meyers, Marco Fiscato, and Mohamed Ahmed. Molecular representation learning with language models and domain-relevant auxiliary tasks. *arXiv preprint arXiv:2011.13230*, 2020.
- Katharine G Field, Gary J Olsen, David J Lane, Stephen J Giovannoni, Michael T Ghiselin, Elizabeth C Raff, Norman R Pace, and Rudolf A Raff. Molecular phylogeny of the animal kingdom. *Science*, 239(4841):748–753, 1988.
- Katrin Fundel and Ralf Zimmer. Gene and protein nomenclature in public databases. *BMC Bioinformatics*, 7(1):1–13, 2006.
- Masaaki Furuno, Takeya Kasukawa, Rintaro Saito, Jun Adachi, Harukazu Suzuki, Richard Baldarelli, Yoshihide Hayashizaki, and Yasushi Okazaki. Cds annotation in full-length cdna sequence. *Genome Research*, 13(6b):1478–1487, 2003.
- Scott J Goebel, Gerard P Johnson, Marion E Perkus, Stephen W Davis, Joseph P Winslow, and Enzo Paoletti. The complete dna sequence of vaccinia virus. *Virology*, 179(1):247–266, 1990.
- Trisha Greenhalgh. How to read a paper: the medline database. *Bmj*, 315(7101):180–183, 1997.
- Charles Miller Grinstead and James Laurie Snell. *Introduction to probability*. American Mathematical Soc., 1997.
- Gongde Guo, Hui Wang, David Bell, Yaxin Bi, and Kieran Greer. Knn model-based approach in classification. In *On The Move to Meaningful Internet Systems 2003: CoopIS, DOA, and ODBASE: OTM Confederated International Conferences, CoopIS, DOA, and ODBASE 2003, Catania, Sicily, Italy, November 3-7, 2003. Proceedings*, pp. 986–996, 2003.
- Israt Jahan, Md Tahmid Rahman Laskar, Chun Peng, and Jimmy Huang. Evaluation of chatgpt on biomedical tasks: A zero-shot comparison with fine-tuned generative transformers. *arXiv preprint arXiv:2306.04504*, 2023.

- Vikramaditya Jakkula. Tutorial on support vector machine (svm). *School of EECS, Washington State University*, 37(2.5):3, 2006.
- Wenxiang Jiao, Wenxuan Wang, Jen-tse Huang, Xing Wang, and Zhaopeng Tu. Is chatgpt a good translator? a preliminary study. *arXiv preprint arXiv:2301.08745*, 2023.
- Wengong Jin, Kevin Yang, Regina Barzilay, and Tommi Jaakkola. Learning multimodal graph-to-graph translation for molecular optimization. *arXiv preprint arXiv:1812.01070*, 2018.
- Uri Katz, Mor Geva, and Jonathan Berant. Inferring implicit relations in complex questions with language models. In *Findings of the Association for Computational Linguistics: EMNLP 2022*, pp. 2548–2566, 2022.
- Ashraf M Kibriya, Eibe Frank, Bernhard Pfahringer, and Geoffrey Holmes. Multinomial naive bayes for text categorization revisited. In *AI 2004: Advances in Artificial Intelligence: 17th Australian Joint Conference on Artificial Intelligence, Cairns, Australia, December 4-6, 2004. Proceedings 17*, pp. 488–499, 2005.
- Tiffany H Kung, Morgan Cheatham, Arielle Medenilla, Czarina Sillos, Lorie De Leon, Camille Elepaño, Maria Madriaga, Rimel Aggabao, Giezel Diaz-Candido, James Maningo, et al. Performance of chatgpt on usmle: Potential for ai-assisted medical education using large language models. *PLoS Digital Health*, 2(2): e0000198, 2023.
- Hansol Lee, Songyeon Lee, Ingo Lee, and Hojung Nam. Amp-bert: Prediction of antimicrobial peptide function based on a bert model. *Protein Science*, 32(1):e4529, 2023.
- Kathy Lee, Diana Palsetia, Ramanathan Narayanan, Md Mostofa Ali Patwary, Ankit Agrawal, and Alok Choudhary. Twitter trending topic classification. In *Proceedings of the International Conference on Data Mining Workshops*, pp. 251–258, 2011.
- J Li, S Tan, X Chen, C-Y Zhang, and Y Zhang. Peptide aptamers with biological and therapeutic applications. *Current Medicinal Chemistry*, 18(27):4215–4222, 2011.
- Qingwen Li, Wenyang Zhou, Donghua Wang, Sui Wang, and Qingyuan Li. Prediction of anticancer peptides using a low-dimensional feature model. *Frontiers in Bioengineering and Biotechnology*, 8:892, 2020.
- Xiang Lorraine Li, Adhiguna Kuncoro, Jordan Hoffmann, Cyprien de Masson d’Autume, Phil Blunsom, and Aida Nematzadeh. A systematic investigation of commonsense knowledge in large language models. In *Proceedings of the Conference on Empirical Methods in Natural Language Processing*, pp. 11838–11855, 2022.
- Xinyi Li, Yongfeng Zhang, and Edward C Malthouse. A preliminary study of chatgpt on news recommendation: Personalization, provider fairness, fake news. *arXiv preprint arXiv:2306.10702*, 2023.
- Zeming Lin, Halil Akin, Roshan Rao, Brian Hie, Zhongkai Zhu, Wenting Lu, Nikita Smetanin, Robert Verkuil, Ori Kabeli, Yaniv Shmueli, et al. Evolutionary-scale prediction of atomic-level protein structure with a language model. *Science*, 379(6637):1123–1130, 2023.
- Bingya Liu, Lewis Ezeogu, Lucas Zellmer, Baofa Yu, Ningzhi Xu, and Dezhong Joshua Liao. Protecting the normal in order to better kill the cancer. *Cancer Medicine*, 4(9):1394–1403, 2015.
- Yiheng Liu, Tianle Han, Siyuan Ma, Jiayue Zhang, Yuanyuan Yang, Jiaming Tian, Hao He, Antong Li, Mengshen He, Zhengliang Liu, et al. Summary of chatgpt/gpt-4 research and perspective towards the future of large language models. *arXiv preprint arXiv:2304.01852*, 2023a.
- Yongkang Liu, Shi Feng, Daling Wang, Yifei Zhang, and Hinrich Schütze. Evaluate what you can’t evaluate: Unassessable generated responses quality. *arXiv preprint arXiv:2305.14658*, 2023b.
- László Lovász and Hans Jürgen Prömel. Combinatorics. *Oberwolfach Reports*, 1(1):5–110, 2004.
- Qiuhaio Lu, Dejing Dou, and Thien Nguyen. Clinicalt5: A generative language model for clinical text. In *Findings of the Association for Computational Linguistics: EMNLP 2022*, pp. 5436–5443, 2022.

































- Dennis B Lubahn, Terry R Brown, Jorge A Simental, Henry N Higgs, Claude J Migeon, Elizabeth M Wilson, and Frank S French. Sequence of the intron/exon junctions of the coding region of the human androgen receptor gene and identification of a point mutation in a family with complete androgen insensitivity. *Proceedings of the National Academy of Sciences*, 86(23):9534–9538, 1989.
- Maher Maalouf. Logistic regression in data analysis: an overview. *International Journal of Data Analysis Techniques and Strategies*, 3(3):281–299, 2011.
- Mónica Marrero, Julián Urbano, Sonia Sánchez-Cuadrado, Jorge Morato, and Juan Miguel Gómez-Berbís. Named entity recognition: fallacies, challenges and opportunities. *Computer Standards & Interfaces*, 35(5):482–489, 2013.
- Julia Otmakhova, Karin Verspoor, Timothy Baldwin, Antonio Jimeno Yepes, and Jey Han Lau. M3: Multi-level dataset for multi-document summarisation of medical studies. In *Findings of the Association for Computational Linguistics: EMNLP 2022*, pp. 3887–3901, 2022.
- Bin Ouyang, Jingyang Wang, Tanjin He, Christopher J Bartel, Haoyan Huo, Yan Wang, Valentina Lacivita, Haegyeom Kim, and Gerbrand Ceder. Synthetic accessibility and stability rules of nasicons. *Nature Communications*, 12(1):5752, 2021.
- Long Ouyang, Jeffrey Wu, Xu Jiang, Diogo Almeida, Carroll Wainwright, Pamela Mishkin, Chong Zhang, Sandhini Agarwal, Katarina Slama, Alex Ray, et al. Training language models to follow instructions with human feedback. In *Proceedings of the Conference on Neural Information Processing Systems*, pp. 27730–27744, 2022.
- Bo Pang, Lillian Lee, and Shivakumar Vaithyanathan. Thumbs up? sentiment classification using machine learning techniques. *arXiv preprint cs/0205070*, 2002.
- Sajan B Patel and Kyle Lam. Chatgpt: the future of discharge summaries? *The Lancet Digital Health*, 5(3):e107–e108, 2023. ISSN 2589-7500.
- Stephen R Piccolo, Paul Denny, Andrew Luxton-Reilly, Samuel Payne, and Perry G Ridge. Many bioinformatics programming tasks can be automated with chatgpt. *arXiv preprint arXiv:2303.13528*, 2023.
- Allan Pinkus. Approximation theory of the mlp model in neural networks. *Acta Numerica*, 8:143–195, 1999.
- Dongqi Pu and Vera Demberg. Chatgpt vs human-authored text: Insights into controllable text summarization and sentence style transfer. *arXiv preprint arXiv:2306.07799*, 2023.
- Thomas C Rindfleisch, Lorraine Tanabe, John N Weinstein, and Lawrence Hunter. Edgar: extraction of drugs, genes and relations from the biomedical literature. In *Biocomputing 2000*, pp. 517–528. World Scientific, 1999.
- Hiroto Saigo, Sebastian Nowozin, Tadashi Kadowaki, Taku Kudo, and Koji Tsuda. gboost: a mathematical programming approach to graph classification and regression. *Machine Learning*, 75:69–89, 2009.
- James M Sangster. *Octanol-water partition coefficients: fundamentals and physical chemistry*, volume 1. John Wiley & Sons, 1997.
- Evelyn Shue, Li Liu, Bingxin Li, Zifeng Feng, Xin Li, and Gangqing Hu. Empowering beginners in bioinformatics with chatgpt. *bioRxiv*, pp. 2023–03, 2023.
- Cathy Shyr, Yan Hu, Paul A. Harris, and Hua Xu. Identifying and extracting rare disease phenotypes with large language models. *arXiv preprint arXiv:2306.12656*, 2023.
- Teague Sterling and John J Irwin. Zinc 15–ligand discovery for everyone. *Journal of Chemical Information and Modeling*, 55(11):2324–2337, 2015.
- Tianxiang Sun, Zhengfu He, Hong Qian, Yunhua Zhou, Xuan-Jing Huang, and Xipeng Qiu. Bbtv2: towards a gradient-free future with large language models. In *Proceedings of the Conference on Empirical Methods in Natural Language Processing*, pp. 3916–3930, 2022.

- Yiming Tan, Dehai Min, Yu Li, Wenbo Li, Nan Hu, Yongrui Chen, and Guilin Qi. Evaluation of chatgpt as a question answering system for answering complex questions. *arXiv preprint arXiv:2303.07992*, 2023.
- Atul Tyagi, Abhishek Tuknait, Priya Anand, Sudheer Gupta, Minakshi Sharma, Deepika Mathur, Anshika Joshi, Sandeep Singh, Ankur Gautam, and Gajendra PS Raghava. Cancerppd: a database of anticancer peptides and proteins. *Nucleic Acids Research*, 43(D1):D837–D843, 2015.
- Marcel L Verdonk and Michael J Hartshorn. Structure-guided fragment screening for lead discovery. *Current Opinion in Drug Discovery & Development*, 7(4):404–410, 2004.
- Michael F Wangler, Shinya Yamamoto, and Hugo J Bellen. Fruit flies in biomedical research. *Genetics*, 199(3):639–653, 2015.
- Scott A Wildman and Gordon M Crippen. Prediction of physicochemical parameters by atomic contributions. *Journal of Chemical Information and Computer Sciences*, 39(5):868–873, 1999.
- Richard Wise, Tony Hart, Otto Cars, Marc Streulens, Reinen Helmuth, Pentti Huovinen, and Marc Sprenger. Antimicrobial resistance, 1998.
- Magdalena Wysocka, Oskar Wysocki, Maxime Delmas, Vincent Mutel, and Andre Freitas. Large language models, scientific knowledge and factuality: A systematic analysis in antibiotic discovery. *arXiv preprint arXiv:2305.17819*, 2023.
- Fangzhi Xu, Qika Lin, Jiawei Han, Tianzhe Zhao, Jun Liu, and Erik Cambria. Are large language models really good logical reasoners? a comprehensive evaluation from deductive, inductive and abductive views. *arXiv preprint arXiv:2306.09841*, 2023.
- Alexander Yeh, Alexander Morgan, Marc Colosimo, and Lynette Hirschman. Biocreative task 1a: gene mention finding evaluation. *BMC Bioinformatics*, 6:1–10, 2005.
- Michael Zasloff. Antimicrobial peptides of multicellular organisms. *Nature*, 415(6870):389–395, 2002.
- Tao Zhang, Congying Xia, Philip S Yu, Zhiwei Liu, and Shu Zhao. Pdaln: Progressive domain adaptation over a pre-trained model for low-resource cross-domain named entity recognition. In *Proceedings of the Conference on Empirical Methods in Natural Language Processing*, 2021.
- Tianyi Zhang, Faisal Ladhak, Esin Durmus, Percy Liang, Kathleen McKeown, and Tatsunori B Hashimoto. Benchmarking large language models for news summarization. *arXiv preprint arXiv:2301.13848*, 2023.
- Wenhan Zhu, Alexandre Lomsadze, and Mark Borodovsky. Ab initio gene identification in metagenomic sequences. *Nucleic Acids Research*, 38(12):e132–e132, 2010.



## A More Results on Molecule Optimization

Table 6: The result of GPT-4 and Modof in the modification of twelve molecules.

Molecule	GPT-4			Modof					
	Optimized Molecule	$\Delta \log P(\uparrow)$	$\Delta SA(\uparrow)$	$\Delta QED(\uparrow)$	Optimized Molecule	$\Delta \log P$	$\Delta SA$	$\Delta QED$	
1			1.19	1.72	0.0		1.90	0.58	-0.38
2			3.1	1.24	0.15		3.65	0.79	0.07
3			1.68	0.28	0.05		7.81	-0.54	-0.57
4			1.61	1.20	0.06	-	-	-	-
5		-	-	-	-		3.79	0.35	-0.26
6			2.49	1.34	0.07	-	-	-	-
7			1.56	1.14	0.05		1.58	2.30	-0.18
8			2.04	1.63	0.05		2.74	0.43	0.07
9			0.12	1.47	0.0		-0.04	1.29	-0.11
10		-	-	-	-		4.70	1.38	-0.14
11			0.54	0.17	0.25		2.74	0.08	-0.03
12			-0.46	0.17	0.28		3.98	0.02	-0.04