

# ConlangCrafter: Constructing Languages with a Multi-Hop LLM Pipeline

## Anonymous ACL submission

té mè k'íri k'íleka sána  
if walk man sing.FUT woman warrior-ERG tree-ACC see<3SG.I.3SG.III>  
*If the man walks, the woman will sing. The warrior sees the tree*

majak<sup>h</sup>alɛt<sup>h</sup>in      ɕɕiɪl ʝi.ɕiɪ k'aɪɪ-d ɣa.ɤa.haɪ-t      ʃɪy tɪʌʂkɾa pɔɔɔɔɔ-ɬa-y hɬaɾkθɔ  
NEG-ABS.I-1sg.ERG-see-NEG eat big dog-ERG food-ACC DEF man run-I.SG-PRS.CONT all  
*I do not see him. The big dog eats food. All men run.*

Figure 1: **ConlangCrafter outputs**, showing random examples of sample sentences and glosses in diverse conlangs generated with our multi-hop LLM pipeline. Each language is designed to be internally consistent, while being typologically unique in its phonology and morpho-syntax.

## Abstract

Constructed languages (*conlangs*) such as Esperanto and Quenya have played diverse roles in art, philosophy, and international communication. Meanwhile, foundation models have revolutionized creative generation in text, images, and beyond. In this work, we leverage modern LLMs as computational creativity aids for end-to-end conlang creation. We introduce *ConlangCrafter*, a multi-hop pipeline that decomposes language design into modular stages – phonology, morphology, syntax, lexicon generation, and translation. At each stage, our method leverages LLMs’ metalinguistic reasoning capabilities, injecting randomness to encourage diversity and leveraging self-refinement feedback to encourage consistency in the emerging language description. We construct a novel, scalable evaluation framework for this task, evaluating metrics measuring consistency and typological diversity. Automatic and manual evaluations demonstrate ConlangCrafter’s ability to produce coherent and varied conlangs without human linguistic expertise. We will release our code and data.

## 1 Introduction

“*p<sup>h</sup>án dzáwali-li a-ga-galúnta-mi áta-li.*”

every language-INTR EVID.NEUT-IPFV-be\_a\_world-3SG.INTR he/she/it-INTR.

“**Every language is a world.**” (conlang)

As humans have long wondered what alternative methods of communication might look like, the art of constructing languages has evolved into

a creative and scholarly pursuit. Constructed languages, or *conlangs*, span the gamut from artistic endeavors to bring fictional worlds to life (e.g. J.R.R. Tolkien’s Elvish and Dothraki in Game of Thrones), to attempts to bridge international divides for worldwide communication (e.g. Esperanto), to tests of philosophical ideas (e.g. Lojban and Toki Pona). Conlangers may spend years or even decades designing their creations, which are marvels of linguistic ingenuity but require Sisyphean effort to achieve the scope and complexity of natural languages.

As foundation models are now being used for various creative tasks, including generation of novel artistic content, we ask: Can these models be used to create conlangs? By introducing the new paradigm of *computational conlanging*, we investigate three core research questions: **(RQ1)** Can LLMs generate internally consistent linguistic systems that are distinct from those seen during training? **(RQ2)** Can LLMs generate diverse yet coherent outputs for this creative application? **(RQ3)** Can we develop objective, scalable evaluation metrics for this task with no ground-truth?

To tackle these questions, we propose a multi-hop reasoning-based LLM pipeline, *ConlangCrafter*. This constructs a language layer by layer, using insights from linguistic typology and documentation, resulting in languages with diverse phonologies and grammars as shown in Figure 1. Our checklist-based prompting method with injected randomness ensures diverse, typologically interesting output languages, while our proposed




Figure 2: **Our Method.** ConlangCrafter constructs languages with a multi-hop LLM pipeline, generating a language sketch as a sequence of linguistic layers (phonology, grammar, lexicon). We encourage typological diversity using checklist-based prompting and a random number generator (RNG), and enhance internal consistency via self-refinement. ConlangCrafter conditions on this sketch to translate and gloss new sentences, potentially including new lexical items and grammar points which may be dynamically added back to the language sketch. Prompts above are abridged and some intermediate steps are omitted.

066 *self-refine* loop enhances the consistency of gener- 089  
 067 erated language descriptions. We also propose a 090  
 068 novel framework for *constructive translation* into 091  
 069 conlangs where lexemes and grammar may not be 092  
 070 fully specified a priori. Finally, we introduce a 093  
 071 novel evaluation framework that systematically as- 094  
 072 sesses the quality of generated conlangs and their 095  
 073 translations with scalable, automatic metrics. To 096  
 074 support the validity of automatic evaluation, we 097  
 075 assess agreement with manual expert judgements, 098  
 076 as well as performing qualitative evaluation. 099

077 Computational conlanging offers significant theo- 100  
 078 retical and practical value. As a challenging 101  
 079 logically-grounded task, it tests the complex meta- 102  
 080 linguistic and logical reasoning abilities of LLMs 103  
 081 on an inherently out-of-distribution language; be- 104  
 082 cause the target language does not yet exist, the 105  
 083 model cannot rely on memorized training data. 106  
 084 From a practical perspective, it may serve as a 107  
 085 computational creativity aid for hobbyist or pro- 108  
 086 fessional conlangers, promising to ease laborious 109  
 087 aspects of conlanging such as lexicon generation 110  
 088 while allowing for creative control. Moreover, it

has direct applications in procedural world or soci-  
 ety generation in systems such as open-world video  
 games. Finally, we see potential applications of our  
 methodology to low-resource languages, where our  
 framework’s focus on logical consistency with set  
 grammatical rules may be relevant for languages  
 documented mostly through written grammars.

## 2 Method

ConlangCrafter is an LLM-driven stochastic  
 pipeline which generates a random conlang either  
 fully from scratch, or in accordance with optional  
 user-input specifications. It leverages LLMs’ abil-  
 ity to perform creative generation that is not fac-  
 tually grounded, exploiting “hallucination” as a  
 desirable feature, as well as exploiting their meta-  
 linguistic knowledge (Begus et al., 2025) (i.e. abil-  
 ity to explicitly reason about language). As these  
 models struggle out-of-the-box to produce diverse  
 and coherent outputs, ConlangCrafter is designed  
 to encourage typological diversity and to mitigate  
 contradictions while splitting the overall task of  
 conlang generation into tractable sub-problems.

Our full method is illustrated in Figure 2, and we proceed to describe its overall structure (Section 2.1) and core concepts (Sections 2.2 and 2.3).

## 2.1 Overall Pipeline

ConlangCrafter has the following core components

- An LLM  $M$ . In practice this is a large reasoning model, i.e. a modern LLM using chain-of-thought inference-time scaling (Guo et al., 2025).
- A memory bank  $S$ , referred to as the *language sketch*. This consists of free text containing the language’s structure description, which may be retrieved from or dynamically altered throughout the pipeline. Examples of languages sketches are provided in Appendix B.1.
- An optional user-input string  $c$ , with specifications or constraints on the generated conlang. By default, this is the empty string  $\emptyset$ .

The pipeline proceeds in two stages:

**Stage A: Language Sketch Bootstrapping.** We first generate an initial description of the language’s core structure and store it in  $S$ . Generating this description is a challenging task since it must be both sufficiently detailed and as internally consistent as possible, and our results show that a single LLM prompt is insufficient to adequately generate  $S$ . To this end, we address the problem with a multi-hop pipeline that incrementally updates  $S$  with linguistic information.

Linguistic theory identifies aspects of language such as phonology as objects of independent study (Genetti, 2018), and language documentation materials such as Visser (2022) commonly split a language’s description into sections based on these aspects. Following this practice, we divide a language into three key layers: *phonology*, *grammar* (morpho-syntax), and *lexicon*. Because these layers depend on one another, we generate them sequentially (e.g., phonology precedes grammar to provide word forms). This structure parallels multi-hop approaches to other complex reasoning tasks with LLMs (Khot et al., 2022). We also note that this minimalistic structure deliberately omits additional potential layers describing linguistic aspects such as semantics, pragmatics, and orthography, which could be addressed in future work.

Each layer is produced through multiple sub-steps, prompting  $M$  with the current state of  $S$ , optional user input  $c$ , and the target language aspect; the result is incorporated back into  $S$ . To ensure diversity and consistency, we apply randomness

injection (Section 2.2) and self-refinement (Section 2.3). Once  $S$  is initialized, it can guide translation and be expanded dynamically.

Prompts at each stage include a slot for optional user input, specifying that it takes priority if present. This permits user control for applications such as generating full conlangs from high-level ideas or initial hand-crafted conlang sketches<sup>1</sup>.

**Stage B: Constructive Translation.** Given  $S$ , ConlangCrafter translates and glosses new texts by conditioning on the explicit language description, building a corpus while dynamically updating  $S$  as needed. We term this task *constructive translation* as it has the unique aspect that the existing language description may be under-specified and require new, creative additions to translate a given text. This is unlike low-resource translation (Tanzer et al., 2023; Zhang et al., 2024; Zhang et al.) and glossing (Ginn et al., 2024a,b), in which explicit hallucination is undesirable.

During translation, ConlangCrafter prompts the model  $M$  with a source text  $t$  and instructions tasking it translate it consistently with the language description in  $S$ . Its output includes fields for the translation and interlinear gloss, as well as optional fields for new lexical items and grammar rules, which may be output as needed to resolve under-specification in  $S$ . The latter can be added back to  $S$  to expand the language description and ensure that they are used consistently in future translations. Logical consistency of these translations with  $S$  is enhanced using self-refinement (Section 2.3). This iterative process builds a translation corpus while expanding the language’s grammar and lexicon.

## 2.2 Randomness Injection.

While LLMs display awareness of language typology, they often fail to produce diverse outputs across runs (Hopkins and Renda, 2023), resulting in limited typological variety in language sketches  $S$ . To address this, we inject randomness into the phonology and grammar stages during sketch bootstrapping. At the start of each stage, the LLM  $M$  generates a typological checklist of ten linguistic features, each with five multiple-choice options. A random number generator (RNG) then selects one option per feature, and  $M$  instantiates the language description accordingly. This leverages the model’s

<sup>1</sup>Online repositories such as <https://conlang.fandom.com/wiki/Portal:Main> contain many partial conlang sketches, as developing complete grammars and lexicons requires substantial time and effort.

metalinguistic knowledge of typology while of-  
floating control of diversity to the external RNG.

### 2.3 Self-Refinement.

Internal consistency is crucial, as contradictions saved to the language sketch may propagate to later stages, and translations must adhere to the language’s constructed grammar. Therefore, we enhance the logical consistency of generations by leveraging a key observation – evaluating generated content is often more straightforward than producing it, enabling iterative refinement through self-feedback mechanisms where LLMs model critique and revise their own outputs (Wu et al., 2024; Simonds et al., 2025; Madaan et al., 2023). We adopt a similar paradigm: a critic model identifies errors and ambiguities in generated content, and an editor model revises accordingly. These are both implemented with the base LLM  $M$ , prompted with  $S$  and the text under revision (as well as the list of identified errors in the case of the editor model). This process is repeated iteratively until no further issues are detected or a maximum number of iterations is reached to prevent infinite revision cycles.

## 3 Experiments

We test the utility of ConlangCrafter and its potential for creative, consistent conlang generation. We present our experimental setup (Section 3.1); quantitative evaluation framework (Section 3.2); results (Section 3.3); ablations (Section 3.4); and examples, analysis, and applications (Section 3.5).

### 3.1 Experimental Setup

For base LLMs, we use DeepSeek-R1 (Guo et al., 2025), and Gemini 2.5 (Comanici et al., 2025) in two variants (Flash, Pro). For automatic evaluations, we use OpenAI o3<sup>2</sup> as the judge LLM, selected to avoid introducing bias by both generating and evaluating with the same model. For metric calculations in our experiments, we sample  $N \approx 20$  languages. Lacking a prior method for full conlang generation, we create a reasonable baseline via a single-stage generation method. This attempts to generate a full language sketch and translations of given sentences in our format with a single prompt, without multi-hop reasoning or iterative self-refinement. Further experimental details are provided in the appendix.

<sup>2</sup>Described in [OpenAI’s system announcement](#)

### 3.2 Quantitative Evaluation Framework

A key challenge to evaluating conlang generation is the lack of an existing framework for this novel, partially subjective task. Unlike typical machine translation, there is no inherent ground-truth for languages which do not exist. Human evaluation for attributes such as logical consistency and diversity requires expert knowledge and painstaking attention to detail, failing to scale to a sufficient sample size of languages for rigorous evaluation.

To tackle this challenge, we develop a comprehensive automatic evaluation framework using the LLM-as-a-judge approach (Zheng et al., 2023; Gu et al., 2024) as a scalable proxy for expert evaluation. We support its overall validity by assessing agreement with manual expert judgments performed on a smaller scale, demonstrating moderate agreement with manual evaluation on this challenging task. Despite the known limitations of such automatic metrics, this framework addresses an existing gap by enabling large-scale, quantitative evaluation of computational conlanging methods, previously infeasible with manual evaluation alone.

#### 3.2.1 Typological Diversity Analysis

To evaluate the breadth of typological variation captured by ConlangCrafter, we select a fixed set of  $k = 16$  basic typological features from the World Atlas of Language Structures (WALS) (wal, 2013) covering fundamental aspects of language. These features are chosen to cover the most fundamental and broad range of basic typological dimensions differentiating natural languages. For example, the feature “Basic word order” (WALS 81) indicates the relative order of subject, verb, and object in basic sentences (e.g. SVO, SOV, VSO, etc.). The full list of features used is provided in the appendix. Each feature is assigned a categorical value (e.g., “SOV”, “Postpositions”, “Tonal”). While the majority of feature values can be determined, missing or underspecified values are recorded as empty for the purpose of diversity calculations.

We generate languages  $L_1, L_2, \dots, L_N$ , use a judge LLM to encode each  $L_i$  as a one-hot vector  $\mathbf{x}_i \in \mathbb{Z}_2^k$  over these features, and calculate the **diversity score**  $D_{\text{mean}} = \frac{2}{N(N-1)} \sum_{1 \leq i < j \leq N} \frac{\text{Ham}(\mathbf{x}_i, \mathbf{x}_j)}{k}$ , where  $\text{Ham}(\cdot, \cdot)$  is the Hamming distance. This reflects the average proportion of differing features between languages.

To ground these values in the distribution of existing languages, we also extract the same WALS




Figure 3: **t-SNE visualization of typological diversity.** Each point represents a generated language, where spatial proximity reflects typological similarity based on WALS features. The dispersed distribution of ConlangCrafter-generated languages highlights their higher typological diversity.

features for all natural languages in the WALS database with sufficient coverage, yielding a sample of 1874 languages. We calculate the same diversity score on this sample and compare to values produced by ConlangCrafter and baseline methods.

### 3.2.2 Internal Consistency Evaluation

We evaluate internal consistency by testing for validity of a fixed set of translations conditioned on a language sketch. This tests whether the language’s rules are logically valid and can be applied coherently. For each language, we prompt the model to translate a predefined set of  $N_{t,t} = 10$  test sentences (via constructive translation, when evaluating ConlangCrafter). A separate judge-based evaluation prompt then assesses each of the generated translations to determine if its phonology, morphology, and syntax adhere to the rules specified in the language sketch. The **translation consistency rate** is defined as the ratio  $\frac{N_{c,t}}{N_{t,t}}$  of correctly formed translations to total translations, averaged over all generated languages. While this is limited in equally penalizing minor and major errors, it nevertheless provides an indication of the degree to which the language can be parsed.

### 3.2.3 Manual Expert Evaluation

Human evaluation in our setting is only feasible on a small scale, as it requires cross-referencing with a language sketch in order to assess language traits and consistency of a translation with all relevant details. Unlike standard NLP annotation tasks,

each judgment requires a holistic consistency check against a novel, custom-designed grammar, rather than comparison to a fixed reference. In addition, this may only be performed by experts with linguistic training to understand technical linguistic materials. To support the validity of our larger-scale automatic evaluation, we perform a manual human evaluation parallel to Sections 3.2.1 and 3.2.2 on all  $N = 20$  languages and  $N_{t,t} = 10$  translations output by a single model. We briefly describe the annotation procedure below, with further details and full task instructions provided in the appendix.

For evaluating diversity calculations, annotators received browsable HTML files containing each language’s sketch and automatically inferred WALS features. They were instructed to label each inferred feature based on correctness given the language sketch. We report the error rate of automatic WALS features relative to these annotations as well as inter-annotator agreement (Cohen’s  $\kappa$ ).

Translation consistency was evaluated similarly, with browsable HTML files containing language sketches and candidate translations paired with interlinear glosses. An automated LLM judgement was displayed alongside each candidate as an auxiliary cue only; The annotation task instructions requested the annotators to rely on their own reading of the language sketch when scoring. We report agreement (Spearman  $\rho$ ) between mean manual and automatic scores. These are both on ordinal scales from 0=*fully inconsistent* to 2=*fully consistent* (noting that the final automatic metric in Section 3.2.2 only counts fully consistent translations). We also report inter-annotator agreement (weighted  $\kappa$ ).

Our manual evaluation was performed by two PhD students in linguistics with expertise in language documentation and typology, recruited through our institution. Participant compensation complied with applicable institutional policies. Each annotation required detailed expert analysis, involving cross-referencing between the generated sentence, its gloss, and the full language sketch. In total, the manual evaluation required approximately 35 hours of expert labor by PhD-level linguists. The goal of manual evaluation is therefore not to provide large-scale human scoring, but to validate that our automatic metrics meaningfully track expert judgments on this challenging task.

## 3.3 Results

Quantitative results are shown in Table 1, evaluating ConlangCrafter with base LLMs as well as the

Metric	Gemini-2.5-Flash		Gemini-2.5-Pro		DeepSeek-R1	
	Baseline	Ours	Baseline	Ours	Baseline	Ours
Diversity ( $\uparrow$ )	$0.25 \pm 0.01$	$0.60 \pm 0.01$	$0.26 \pm 0.02$	$0.58 \pm 0.01$	$0.35 \pm 0.01$	$0.56 \pm 0.02$
Consistency ( $\uparrow$ )	$0.30 \pm 0.04$	$0.38 \pm 0.04$	$0.32 \pm 0.05$	$0.54 \pm 0.05$	$0.21 \pm 0.04$	$0.39 \pm 0.05$

Table 1: **Typological diversity and consistency** comparison between the baseline method and ConlangCrafter, measured using the automatic metrics described in Section 3.2. Results are shown with  $\pm$  stderr.

Metric	Baseline	+MH	+MH+RNG	+MH+RNG+SR (Full)
Diversity ( $\uparrow$ )	$0.26 \pm 0.02$	$0.52 \pm 0.01$	$0.60 \pm 0.02$	$0.58 \pm 0.01$
Consistency ( $\uparrow$ )	$0.32 \pm 0.05$	$0.40 \pm 0.05$	$0.43 \pm 0.05$	$0.54 \pm 0.05$

Table 2: **Ablation study of ConlangCrafter’s components** showing the cumulative effects of adding key components – Multi-Hop reasoning (MH), RNG randomness injection, and Self-Refinement (SR) – on automatic metrics over 20 languages generated by Gemini-2.5-Pro. Results are shown with  $\pm$  stderr.

Temp.	RNG	Diversity	Consistency
0.6	$\times$	$0.46 \pm 0.02$	$0.59 \pm 0.08$
1.0	$\times$	$0.50 \pm 0.02$	$0.40 \pm 0.09$
1.4	$\times$	$0.56 \pm 0.02$	$0.34 \pm 0.03$
1.6	$\times$	$0.54 \pm 0.02$	$0.25 \pm 0.06$
0.6	$\checkmark$	$0.60 \pm 0.02$	$0.43 \pm 0.05$

Table 3: **Comparison of diversity enhancement methods:** temperature sampling (above) and our RNG-based randomness injection (below). We achieve high diversity without the severe consistency penalty associated with high-temperature sampling. Self-refinement was disabled in this ablation.

baseline method (Section 3.1). Our method outperforms the baseline in both diversity and consistency metrics. For diversity scores, all comparisons between the baseline and our method are highly significant (two-sided t-tests,  $p < 10^{-6}$ ) with large effect sizes (Cohen’s  $d > 3.0$ ). For consistency scores, baseline comparisons are significant (two sided t-tests, paired by sentence) for Gemini-2.5-Pro ( $p \approx 0.023$ ) and DeepSeek-R1 ( $p \approx 0.014$ ) with large effect sizes ( $d > 1.4$ ). For Gemini-2.5-Flash, the small effect ( $d \approx 0.37$ ) does not reach significance ( $p \approx 0.294$ ) at our sample size, but is consistent with findings that ConlangCrafter increases diversity without reducing consistency. In addition, we see moderate differences between the different LLMs in performance, with the stronger Gemini-2.5-Pro and DeepSeek-R1 performing better at this challenging task. Overall, generation of

fully consistent translations remains a challenge, although our full method yields a better diversity-consistency tradeoff relative to the baseline.

In Figure 3, we apply t-distributed stochastic neighbor embedding (t-SNE) to visualize the pairwise Hamming distance matrix in two dimensions, where spatial proximity reflects typological similarity. The scattered distribution of languages across the 2D space visually confirms the high typological diversity compared with the baseline. These findings confirm that ConlangCrafter’s randomness injection and modular prompting yield a diverse typological sample, even when evaluated against a fixed, expert-selected set of WALS features.

We also calculate diversity values for natural languages (Section 3.2.1), yielding  $D = 0.43 \pm 0.003$ , which falls between baseline and ConlangCrafter values in Table 1. All pairwise comparisons are statistically significant (t-tests, all  $p < 10^{-6}$ ). This indicates that the baseline method generates languages with lower typological diversity than natural languages, while ConlangCrafter exceeds this level of diversity. Thus, despite our base LLMs exhibiting strong performance on general multilingual benchmarks, they fail to match the diversity of natural languages when used without our method, failing to leverage their knowledge of cross-lingual variation. By contrast, our method demonstrates successful exploration of the full typological space including novel feature combinations. For creative generation applications, exceeding natural language diversity is desirable, as it allows for imaginative world-building and testing of linguistic hy-

403  
404  
405  
406  
407  
408  
409  
410  
411  
412  
413  
414  
415  
416  
417  
418  
419  
420  
421  
422  
423  
424  
425  
426  
427  
428  
429  
430  
431  
432  
433  
434  
435

	Sample Sentences	Key Features
“The big dog is sleeping.”	“She will give him water.”	
tsɔɔ ɔp-snat̪ kɔaŋ laŋ.θɔɔ PRS 3SG.NHUM.S-sleep big dog.NOM	ʃi.ɬ.tu.ɬ-iŋ ɔp- o/ doɔ-sul̪-boɬ-dʒoɬ man-ACC 3SG.HUM.S-FUT 3SG.HUM.O-water-have-CAUS	Click consonants, polysynthetic morphology, noun incorporation, OVS word order, switch-reference, double marking
nɔ-k'a <sup>h</sup> da ʒɔk'ɔ to-hoto <sup>m</sup> bulo hɛ PAT-sleep dog.SG.ABS 3SG.N.ABS-be.STAT big.ADJ PRF	sɛ tɔ-nɔ-p'aɟɛ hɛ wuwolo hɛ tu IRR AGT-PAT-give 3SG water 3SG to	ATR harmony, ejectives and prenasalized stops, active-stative alignment, VSO word order, ejective-conditioned word order changes
'g <sup>w</sup> aŋk 'k'ɛspə n'ɔ.ska'm'i ʃi big dog sleep 3S.PAT	n <sup>w</sup> a'co.ɬ'ɔ 'gr'ɔ.bə k <sup>w</sup> o ʃi ʃi FUT give 3S.AGT 3S.PAT 3S.PAT	Frequent secondary articulations, isolating morphology, evidentiality marking, SOV word order with post-verbal particles marking person
ʂãŋ tɔm-ʒɔ nã.tã-sã-n dog big-ERG.ANIM sleep-IPFV.VIS.LOW-T-3SG	nó.kà qá mã.nã.a lóm.ət kjã.là.n FUT to man-ABS.ANIM water-ABS.INAN give-PFV.VIS-3SG	Vertical vowel system, dental-alveolar-retroflex distinction, split ergativity by aspect, tonal polarity in verb inflection, animacy-governed adposition order, serial verb constructions

Table 4: **Qualitative examples** of ConlangCrafter-generated languages. Each language was generated unconditionally (without user guidance), and demonstrates unique typological properties.

436 hypotheses with typologically unusual combinations.

437 For manual evaluation of diversity calculations, 438 we examined automatic WALS features for all 439 cases where annotators agreed (Cohen’s  $\kappa = 0.58$ ; 440 moderate agreement). The most common issue was 441 due to underspecification issues; 12% of potential 442 features were mistakenly left unspecified, while 4% 443 of features that were not specified had incorrectly 444 inferred automatic values. Excluding underspecifi- 445 cation issues, automatic feature extraction achieved 446 91% accuracy. This demonstrates that our diversity 447 metric is based on largely accurate typological anal- 448 ysis, with the main existing limitation regarding the 449 treatment of underspecified features.

450 For manual evaluation of translation consistency, 451 we find significant agreement between manual and 452 automatic metrics, with Spearman  $\rho = 0.68$  ( $p <$  453  $10^{-27}$ ). Inter-annotator agreement is quadratic 454 weighted  $\kappa = 0.43$  ( $p < 10^{-4}$ ), indicating mod- 455 erate agreement between annotators. This level 456 of agreement is expected, as judgments require in- 457 terpreting underspecified grammars and weighing 458 minor versus major inconsistencies, decisions for 459 which multiple valid analyses may exist. Overall, 460 automatic scores tend to be stricter than manual 461 evaluations, but still reasonably track human judge- 462 ments when calibrated for this strictness level.

### 463 3.4 Ablation Analysis

464 In Table 2 we ablate key components of our system: 465 multi-hop reasoning (MH), randomness injection

(RNG), and iterative self-refinement (SR). We add 466 each of these in turn to the baseline method (de- 467 scribed in Section 3.1) and observe their cumulative 468 effect. Multi-hop reasoning and randomness injec- 469 tion significantly improve diversity, key for generat- 470 ing typologically interesting and varied languages. 471 This reduces consistency, as expected, since di- 472 verse outputs may be more logically challenging. 473 However, self-refinement mitigates this issue, sig- 474 nificantly increasing consistency approaching or 475 beyond baseline levels. This matches qualitative 476 observations that multi-hop reasoning and random- 477 ness injection are key for interesting, diverse out- 478 puts, while self-refinement succeeds in correcting 479 many salient logical errors in generations. 480

481 To further test the importance of random- 482 ness injection, we compare to standard diversity- 483 enhancing techniques reliant on sampling temper- 484 ature, under our generation settings (without self- 485 refinement). While increasing the sampling temper- 486 ature (using nucleus sampling with  $p = 0.95$ ) effec- 487 tively increases variation, it operates at the token 488 level rather than the typological level. As shown 489 in Table 3, approaching the diversity score of our 490 method (0.60) via standard sampling requires rais- 491 ing the temperature to  $T \approx 1.4$  resulting in a sharp 492 trade-off with consistency, which crashes to 0.34. 493 By contrast, our method injects randomness di- 494 rectly into the typological feature selection (e.g., 495 randomly sampling relative order of subject, object,

and verb), allowing the language model to generate the description at a lower temperature ( $T = 0.6$ ) to ensure logically coherent and fluent text. This maintains higher internal consistency (0.43) while achieving high typological diversity (0.60). We further note that alternative diversity-enhancing methods, such as specialized decoding strategies (Hewitt et al., 2022; Chang et al., 2025) or internal interventions (Chung et al., 2025; Zhou et al., 2025), typically require access to model logits or gradients. These are not feasible in our setting as we focus on state-of-the-art large reasoning models, which are either closed-weights (e.g., Gemini-2.5-pro) or prohibitively large to run locally (e.g. DeepSeek-R1).

### 3.5 Qualitative Analysis and Application

Beyond metrics, we examine the creative and linguistic quality of generations. Table 4 illustrates unconditional ConlangCrafter generations. The incorporation of unique typological features demonstrates the system’s grasp of cross-linguistic variation beyond major world languages, and its effectiveness at diversity between generations. In the appendix (Table 6) we show examples of languages generated with user-input constraints, which illustrate our system’s ability to assist user exploration of creative linguistic and philosophical ideas.

## 4 Related Work

**Computational Conlanging.** While various software tools<sup>3</sup> have been created by the conlanging community to automate various aspects of conlanging, machine learning-based methods are limited and piecemeal. Prior works have explored generating words in isolation (Zacharias et al., 2022), assigning or interpreting visual associations with nonsense words (Alper and Averbuch-Elor, 2023; Matsuhira et al., 2024; Kouwenhoven et al., 2025), and the ability of neural models to learn constructed languages with controlled linguistic properties (McCoy et al., 2018, 2021; Kallini et al., 2024; McCoy and Griffiths, 2025) or constructed via cryptographic substitutions (Marmonier et al., 2025). Recent work has also studied statistical properties of generated text when prompting LLMs to construct languages (Marmonier et al., 2025), but this is done in a single prompt and does not output fine-grained interpretable linguistic structure. By contrast, our approach constructs languages end-to-end with LLMs, with linguistically interpretable

<sup>3</sup>Such as those listed at the FrathWiki

structure enabling downstream translation.

**Computational Creativity.** Generative models are increasingly being leveraged for creative tasks, with recent works exploring the use of LLMs for applications such as story generation (Venkatraman et al., 2025; Teleki et al., 2025), collaborative narrative modeling (Qiu and Hu, 2025), and research ideation (Si et al., 2025). Besides fully autonomous systems, human-computer interaction studies have explored the use of generative models as a creativity aid (Chakrabarty et al., 2024; Kumar et al., 2025). Similarly to our work, some studies have explored the invention of novel words (Malkin et al., 2021) and visual concepts (Richardson et al., 2024). A key challenge is evaluating performance on tasks which are inherently open-ended, which has motivated various evaluation frameworks and benchmarks for creativity (Li et al., 2025; Hou et al., 2025; Zhao et al., 2025). In this vein, we address a novel creative domain that requires both typological diversity and strict logical consistency, distinct from typical creative generation tasks.

**Diverse Text Generation.** LLMs often suffer from limited diversity, as common decoding strategies fail to match human text statistics (Holtzman et al., 2020), potentially exacerbated by post-training (Kirk et al., 2023; Yun et al., 2025). Mitigation strategies include temperature, nucleus (Holtzman et al., 2020), and min-p sampling (Nguyen et al., 2024), as well as handcrafted prompting techniques (Tian et al., 2024; Wang et al., 2025; Hu et al., 2025). These address token-level or semantic diversity, while we require targeted structural diversity at the level of linguistic typology.

## 5 Conclusion

We have proposed the novel paradigm of computational conlanging, showing that ConlangCrafter can construct coherent artificial languages through a novel multi-hop pipeline, validated by a new scalable evaluation framework for this task as well as manual expert judgements. ConlangCrafter offers a new computational creativity tool for language construction, and we foresee future work exploring directions such as scaling to larger grammars and lexicons, exploring additional language aspects (e.g. semantics, multi-modality), and modeling languages as evolving communication tools between agents across time, space, and culture.

## 592 Limitations

593 Our method has several limitations. While our  
594 pipeline is designed to encourage diversity and  
595 avoid collapse to existing languages, LLMs may  
596 still be biased towards English and other high-  
597 resource languages observed during training. The  
598 limited nature of linguistic typological informa-  
599 tion seen during training (and the limited coverage  
600 of the worlds’ languages in the linguistic litera-  
601 ture overall) may prevent our method from generat-  
602 ing extremely unusual features. Moreover, LLMs  
603 cannot capture the full range of human creativity  
604 and may lack the insight to invent novel, higher-  
605 level philosophical ideas. Our evaluation method  
606 is limited due to the extensive labor required for  
607 manual evaluation and the difficulty in formulat-  
608 ing automated metrics for conlanging; future work  
609 could design more scalable evaluation frameworks  
610 for this task. Our language summaries only de-  
611 scribe fundamental language components (phonol-  
612 ogy, morpho-syntax, lexicon) while disregarding  
613 aspects such as semantics, pragmatics, discourse  
614 strategies, and orthography, which could be added  
615 in future work. These summaries are too short to  
616 capture a fraction of the complexity occurring in  
617 real languages; future research could study how to  
618 scale up their size, which currently is incompatible  
619 with our prompting methods which are limited by  
620 the context length of current LLMs. Finally, our  
621 pipeline incurs a substantial computational cost due  
622 to repeated LLM calls with long contexts, partic-  
623 ularly in self-refinement loops; future work could  
624 distill ConlangCrafter to achieve similar results  
625 with efficient inference.

## 626 Ethical Considerations

627 As with other uses of LLMs and other genera-  
628 tive models, our method requires responsible use  
629 and disclaimers accompanying generated content  
630 to avoid disseminating misinformation. Repeated  
631 calls to LLM generation may consume significant  
632 compute resources, and we look to future work  
633 to improve the efficiency of our method. Finally,  
634 while our work may have future applications to  
635 low-resource languages, we emphasize that gen-  
636 eration of fictional content must not come at the  
637 expense of research attention and resources being  
638 directed toward living communities.

639 Regarding manual annotation, no personally  
640 identifying information or sensitive data were col-  
641 lected, and only aggregated results are reported.

We did not obtain IRB approval because the re- 642  
search does not involve human subjects. Individ- 643  
uals’ participation was limited to professional lin- 644  
guistic annotation, and the research questions con- 645  
cern language model behavior, not the annotators. 646

## References 647

2013. [The world atlas of language structures online \(wals\)](https://wals.info). Max Planck Institute for Evolutionary Anthropology [Data set]. Version v2020.4; accessed 2025-08-02 at <https://wals.info>. 648  
649  
650  
651
- Morris Alper and Hadar Averbuch-Elor. 2023. Kiki or bouba? sound symbolism in vision-and-language models. *Advances in Neural Information Processing Systems*, 36:78347–78359. 652  
653  
654  
655
- Gasper Begus, Maksymilian Dabkowski, and Ryan Rhodes. 2025. Large linguistic models: Investigating llms’ metalinguistic abilities. *IEEE Transactions on Artificial Intelligence*. 656  
657  
658  
659
- Tuhin Chakrabarty, Vishakh Padmakumar, Faeze Brahman, and Smaranda Muresan. 2024. Creativity support in the age of large language models: An empirical study involving professional writers. In *Proceedings of the 16th Conference on Creativity & Cognition*, pages 132–155. 660  
661  
662  
663  
664  
665
- Haw-Shiuan Chang, Nanyun Peng, Mohit Bansal, Anil Ramakrishna, and Tagyoung Chung. 2025. Real sampling: Boosting factuality and diversity of open-ended generation by extrapolating the entropy of an infinitely large lm. *Transactions of the Association for Computational Linguistics*, 13:760–783. 666  
667  
668  
669  
670  
671
- John Joon Young Chung, Vishakh Padmakumar, Melissa Roemmele, Yuqian Sun, and Max Kreminski. 2025. Modifying large language model post-training for diverse creative writing. *arXiv preprint arXiv:2503.17126*. 672  
673  
674  
675  
676
- Gheorghe Comanici, Eric Bieber, Mike Schaekermann, Ice Pasupat, Noveen Sachdeva, Inderjit Dhillon, Marcel Blistein, Ori Ram, Dan Zhang, Evan Rosen, and 1 others. 2025. Gemini 2.5: Pushing the frontier with advanced reasoning, multimodality, long context, and next generation agentic capabilities. *arXiv preprint arXiv:2507.06261*. 677  
678  
679  
680  
681  
682  
683
- Carol Genetti. 2018. *Introduction: Language, Languages, and Linguistics*. Cambridge University Press. 684  
685  
686
- Michael Ginn, Mans Hulden, and Alexis Palmer. 2024a. Can we teach language models to gloss endangered languages? In *Findings of the Association for Computational Linguistics: EMNLP 2024*, pages 5861–5876. 687  
688  
689  
690  
691
- Michael Ginn, Ali Marashian, Bhargav Shandilya, Claire Post, Enora Rice, Juan Vásquez, Marie McGregor, Matthew Buchholz, Mans Hulden, and Alexis 692  
693  
694

695	Palmer. 2024b. On the robustness of neural models for full sentence transformation. In <i>Proceedings of the 4th Workshop on Natural Language Processing for Indigenous Languages of the Americas (AmericasNLP 2024)</i> , pages 159–173.	751
696		752
697		753
698		
699		
700	Jiawei Gu, Xuhui Jiang, Zhichao Shi, Hexiang Tan, Xuehao Zhai, Chengjin Xu, Wei Li, Yinghan Shen, Shengjie Ma, Honghao Liu, and 1 others. 2024. A survey on llm-as-a-judge. <i>arXiv preprint arXiv:2411.15594</i> .	754
701		755
702		756
703		757
704		758
705	Daya Guo, Dejian Yang, Haowei Zhang, Junxiao Song, Ruoyu Zhang, Runxin Xu, Qihao Zhu, Shitong Ma, Peiyi Wang, Xiao Bi, and 1 others. 2025. Deepseek-r1: Incentivizing reasoning capability in llms via reinforcement learning. <i>arXiv preprint arXiv:2501.12948</i> .	759
706		760
707		761
708		762
709		763
710		764
711	John Hewitt, Christopher Manning, and Percy Liang. 2022. Truncation sampling as language model desmoothing. In <i>Findings of the Association for Computational Linguistics: EMNLP 2022</i> , pages 3414–3427, Abu Dhabi, United Arab Emirates. Association for Computational Linguistics.	765
712		766
713		767
714		768
715		769
716		770
717	Ari Holtzman, Jan Buys, Li Du, Maxwell Forbes, and Yejin Choi. 2020. The curious case of neural text degeneration. In <i>International Conference on Learning Representations</i> .	771
718		772
719		773
720		774
721	Aspen K Hopkins and Alex Renda. 2023. Can llms generate random numbers? evaluating llm sampling in controlled domains. Sampling and Optimization in Discrete Space (SODS) ICML 2023 Workshop.	775
722		776
723		777
724		778
725	Zhaoyi Joey Hou, Bowei Alvin Zhang, Yining Lu, Bhi-man Kumar Baghel, Anneliese Brei, Ximing Lu, Meng Jiang, Faeze Brahman, Snigdha Chaturvedi, Haw-Shiuan Chang, and 1 others. 2025. Creativityprism: A holistic benchmark for large language model creativity. <i>arXiv preprint arXiv:2510.20091</i> .	779
726		780
727		781
728		782
729		783
730		784
731	Wenyang Hu, Gregory Kang Ruey Lau, Liu Diwen, Chen Jizhuo, See Kiong Ng, and Bryan Kian Hsiang Low. 2025. Dipper: Diversity in prompts for producing large language model ensembles in reasoning tasks. In <i>Proceedings of the 2025 Conference on Empirical Methods in Natural Language Processing</i> , pages 35546–35560.	785
732		786
733		787
734		788
735		789
736		790
737		791
738	Julie Kallini, Isabel Papadimitriou, Richard Futrell, Kyle Mahowald, and Christopher Potts. 2024. Mission: Impossible language models. In <i>Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)</i> , pages 14691–14714.	792
739		793
740		794
741		795
742		796
743		797
744	Tushar Khot, Harsh Trivedi, Matthew Finlayson, Yao Fu, Kyle Richardson, Peter Clark, and Ashish Sabharwal. 2022. Decomposed prompting: A modular approach for solving complex tasks. <i>arXiv preprint arXiv:2210.02406</i> .	798
745		799
746		800
747		801
748		802
749		803
750	Robert Kirk, Ishita Mediratta, Christoforos Nalmpantis, Jelena Luketina, Eric Hambro, Edward Grefenstette, and Roberta Raileanu. 2023. Understanding the effects of rlhf on llm generalisation and diversity. <i>arXiv preprint arXiv:2310.06452</i> .	804
		805
	Tom Kouwenhoven, Max Peeperkorn, Roy De Kleijn, and Tessa Verhoef. 2025. Shaping shared languages: Human and large language models’ inductive biases in emergent communication. <i>arXiv preprint arXiv:2503.04395</i> .	
	Harsh Kumar, Jonathan Vincentius, Ewan Jordan, and Ashton Anderson. 2025. Human creativity in the age of llms: Randomized experiments on divergent and convergent thinking. In <i>Proceedings of the 2025 CHI Conference on Human Factors in Computing Systems</i> , pages 1–18.	
	Ruizhe Li, Chiwei Zhu, Benfeng Xu, Xiaorui Wang, and Zhendong Mao. 2025. Automated creativity evaluation for large language models: A reference-based approach. In <i>Findings of the Association for Computational Linguistics: EMNLP 2025</i> , pages 21475–21488, Suzhou, China. Association for Computational Linguistics.	
	Aman Madaan, Niket Tandon, Prakhar Gupta, Skyler Hallinan, Luyu Gao, Sarah Wiegrefe, Uri Alon, Nouha Dziri, Shrimai Prabhumoye, Yiming Yang, and 1 others. 2023. Self-refine: Iterative refinement with self-feedback. <i>Advances in Neural Information Processing Systems</i> , 36:46534–46594.	
	Nikolay Malkin, Sameera Lanka, Pranav Goel, Sudha Rao, and Nebojsa Jojic. 2021. Gpt perdetry test: Generating new meanings for new words. In <i>2021 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies</i> , pages 5542–5553. Association for Computational Linguistics.	
	Malik Marmonier, Rachel Bawden, and Benoît Sagot. 2025. Explicit learning and the llm in machine translation. <i>arXiv preprint arXiv:2503.09454</i> .	
	Chihaya Matsuhira, Marc A Kastner, Takahiro Komamizu, Takatsugu Hirayama, and Ichiro Ide. 2024. Investigating conceptual blending of a diffusion model for improving nonword-to-image generation. In <i>Proceedings of the 32nd ACM International Conference on Multimedia</i> , pages 7307–7315.	
	R Thomas McCoy and Thomas L Griffiths. 2025. Modeling rapid language learning by distilling bayesian priors into artificial neural networks. <i>Nature Communications</i> , 16(1):1–14.	
	Richard Thomas McCoy, Jennifer Culbertson, Paul Smolensky, and Géraldine Legendre. 2021. Infinite use of finite means? evaluating the generalization of center embedding learned from an artificial grammar. In <i>Proceedings of the annual meeting of the cognitive science society</i> , volume 43.	
	Thomas R McCoy, Robert Frank, and Tal Linzen. 2018. Revisiting the poverty of the stimulus: hierarchical	

806	generalization without a hierarchical bias in recurrent neural networks. In <i>Proceedings of the Annual Meeting of the Cognitive Science Society</i> , volume 40.	Tianhao Wu, Weizhe Yuan, Olga Golovneva, Jing Xu, Yuandong Tian, Jiantao Jiao, Jason Weston, and Sainbayar Sukhbaatar. 2024. Meta-rewarding language models: Self-improving alignment with llm-as-a-meta-judge. <i>arXiv preprint arXiv:2407.19594</i> .	862
807			863
808			864
809	Minh Nhat Nguyen, Andrew Baker, Clement Neo, Allen Roush, Andreas Kirsch, and Ravid Shwartz-Ziv. 2024. Turning up the heat: Min-p sampling for creative and coherent llm outputs. <i>arXiv preprint arXiv:2407.01082</i> .	Longfei Yun, Chenyang An, Zilong Wang, Letian Peng, and Jingbo Shang. 2025. The price of format: Diversity collapse in llms. <i>arXiv preprint arXiv:2505.18949</i> .	865
810			866
811			867
812			868
813			869
814	Ziliang Qiu and Renfen Hu. 2025. Deep associations, high creativity: A simple yet effective metric for evaluating large language models. In <i>Proceedings of the 2025 Conference on Empirical Methods in Natural Language Processing</i> , pages 10870–10883.	Thomas Zacharias, Ashutosh Taklikar, and Raja Giryes. 2022. Extending the vocabulary of fictional languages using neural networks. <i>arXiv preprint arXiv:2201.07288</i> .	870
815			871
816			872
817			873
818			874
819	Elad Richardson, Kfir Goldberg, Yuval Alaluf, and Daniel Cohen-Or. 2024. Conceptlab: Creative concept generation using vlm-guided diffusion prior constraints. <i>ACM Transactions on Graphics</i> , 43(3):1–14.	Chen Zhang, Mingxu Tao, Quzhe Huang, Zhibin Chen, and Yansong Feng. Can llms learn a new language on the fly? a case study on zhuang. In <i>The Second Tiny Papers Track at ICLR 2024</i> .	875
820			876
821			877
822			878
823	Chenglei Si, Diyi Yang, and Tatsunori Hashimoto. 2025. Can llms generate novel research ideas? a large-scale human study with 100+ nlp researchers. In <i>The Thirteenth International Conference on Learning Representations</i> .	Kexun Zhang, Yee Man Choi, Zhenqiao Song, Taiqi He, William Yang Wang, and Lei Li. 2024. Hire a linguist!: Learning endangered languages with in-context linguistic descriptions. <i>arXiv preprint arXiv:2402.18025</i> .	879
824			880
825			881
826			882
827			883
828	Toby Simonds, Kevin Lopez, Akira Yoshiyama, and Dominique Garmier. 2025. Self rewarding self improving. <i>arXiv preprint arXiv:2505.08827</i> .	Yunpu Zhao, Rui Zhang, Wenyi Li, and Ling Li. 2025. Assessing and understanding creativity in large language models. <i>Machine Intelligence Research</i> , 22(3):417–436.	884
829			885
830			886
831	Garrett Tanzer, Mirac Suzgun, Eline Visser, Dan Jurafsky, and Luke Melas-Kyriazi. 2023. A benchmark for learning to translate a new language from one grammar book. <i>arXiv preprint arXiv:2309.16575</i> .	Lianmin Zheng, Wei-Lin Chiang, Ying Sheng, Siyuan Zhuang, Zhanghao Wu, Yonghao Zhuang, Zi Lin, Zhuohan Li, Dacheng Li, Eric Xing, and 1 others. 2023. Judging llm-as-a-judge with mt-bench and chatbot arena. <i>Advances in neural information processing systems</i> , 36:46595–46623.	887
832			888
833			889
834			890
835	Maria Teleki, Vedangi Bengali, Xiangjue Dong, Sai Tejas Janjur, Haoran Liu, Tian Liu, Cong Wang, Ting Liu, Yin Zhang, Frank Shipman, and 1 others. 2025. A survey on llms for story generation. In <i>Findings of the Association for Computational Linguistics: EMNLP 2025</i> , pages 13954–13966.	Kuan Lok Zhou, Jiayi Chen, Siddharth Suresh, Reuben Narad, Timothy T. Rogers, Lalit K Jain, Robert D Nowak, Bob Mankoff, and Jifan Zhang. 2025. <b>Bridging the creativity understanding gap: Small-scale human alignment enables expert-level humor ranking in LLMs</b> . In <i>Findings of the Association for Computational Linguistics: EMNLP 2025</i> , pages 16273–16287, Suzhou, China. Association for Computational Linguistics.	891
836			892
837			893
838			894
839			895
840			896
841	Yufei Tian, Abhilasha Ravichander, Lianhui Qin, Ronan Le Bras, Raja Marjeh, Nanyun Peng, Yejin Choi, Thomas L Griffiths, and Faeze Brahman. 2024. Macgyver: Are large language models creative problem solvers? In <i>Proceedings of the 2024 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies (Volume 1: Long Papers)</i> , pages 5303–5324.		897
842			898
843			899
844			900
845			901
846			902
847			
848			
849	Saranya Venkatraman, Nafis Irtiza Tripto, and Dongwon Lee. 2025. Collabstory: Multi-llm collaborative story generation and authorship analysis. In <i>Findings of the Association for Computational Linguistics: NAACL 2025</i> , pages 3665–3679.	<b>A Implementation Details</b>	903
850			
851			
852			
853			
854	Eline Visser. 2022. <i>A grammar of Kalamang</i> . Language Science Press.	<b>A.1 Pipeline Design and Prompts</b>	904
855			
856	Qihan Wang, Shidong Pan, Tal Linzen, and Emily Black. 2025. <b>Multilingual prompting for improving LLM generation diversity</b> . In <i>Proceedings of the 2025 Conference on Empirical Methods in Natural Language Processing</i> , pages 6378–6400, Suzhou, China. Association for Computational Linguistics.	Full prompts used in our pipeline are provided in Figures 4 to 9. In each prompt, fields in curly braces { } are values that are filled in at inference time; these include configuration variable (e.g. {n_questions} has default value 10) as well as outputs of previous steps (e.g. {checklist} in the second prompt in Figure 4 is filled in with the output from the previous prompt).	905
857			906
858			907
859			908
860			909
861			910
			911
			912
			913
			914

WALS#	Feature	Description/Options
1	Consonant inventory	Small ( $\leq 20$ ) vs. Large ( $> 20$ )
2	Vowel inventory	Large ( $\geq 9$ ) vs. Small ( $< 9$ )
13	Tone	Tonal vs. non-tonal systems
20	Morphological fusion	Isolating, agglutinating, fusional, etc.
26	Affixation balance	Relative preference for prefixing vs. suffixing
30	Gender inventory	Number of gender distinctions (including none)
49	Case inventory	Minimal, moderate, or extensive case systems
69	Numeral classifiers	Classifier vs. non-classifier systems
81	Basic word order	SVO, SOV, VSO, etc.
85	Adposition type	Prepositions vs. postpositions
86	Genitive–noun order	Genitive before vs. after noun
87	Adjective–noun order	Adjectives precede or follow nouns
90	Relative-clause order	Head-initial vs. head-final
98	Alignment typology	Nominative–accusative vs. active–stative
107–111	Valence morphology	Presence/absence of causative, passive, applicative
116	Question-marking strategy	Interrogative particle vs. inversion

Table 5: Linguistic features for typological analysis, with WALS numbers (WALS#) listed.

(bottom of Figure 6) is run in a loop until the lexicon contains a minimum number of items (100 by default). The self-refinement prompts (Figures 7 to 8) are run after corresponding steps; the critic prompts there are used to identify issues, and the amendment prompts edit to address these issues. These are run in a loop until the critic returns an overall score above a fixed threshold.

We proceed to describe core design choices motivating this pipeline, beyond the overall multi-hop structure, randomness injection, and self-refinement components described in the main paper. Figure 4 includes a third step discussing word shapes to encourage diverse word shapes as we find that otherwise languages are prone to collapsing to monosyllables (typologically attested but limiting diversity of generations). Figure 5 includes an expansion step to achieve a more satisfying level of detail in the output grammar, with an additional merger step to holistically incorporate these details into the grammar. Many prompts explicitly request interesting and unusual outputs, which complements our goal of constructing diverse and interesting languages.

## A.2 Baseline Prompt

The single prompt used for baseline comparisons is given in Figure 10. This uses the same output fields as the full ConlangCrafter pipeline, while requesting an entire language sketch and all sentence translations in a single prompt.

## A.3 Evaluation Prompts

The prompts used for evaluation metrics are shown in Figures 11 to 12. This includes the prompt used for WALS feature extraction and the prompt used for the judge evaluating translation consistency.

## A.4 Constructive Translation

For constructive translation, we translate the following fixed sentences which include a variety of syntactic structures as detailed below:

- The big dog is sleeping. (*Attributive adjective, present continuous, definite article*)
- Where is my book? (*WH-interrogative, possessive, copula*)
- She will give him water. (*Ditransitive, future tense, pronouns*)
- This child walked to that house yesterday. (*Demonstratives, past tense, directional, temporal adverb*)
- Are you hungry? (*Yes/no question, adjectival predicate*)
- Give me the red bird! (*Imperative, indirect object pronoun, attributive adjective*)
- The woman and the man are talking. (*Coordination, present continuous*)

969	• I do not see three cats. ( <i>Negation, transitive, numeral, plural</i> )	text. In practice, the phonology and grammar sections are markdown-formatted, while the lexicon is in CSV format.	1014
970			1015
971	• There is a black mountain. ( <i>Existential construction, indefinite article, attributive adjective</i> )		1016
972		<b>B.2 Qualitative Results with User-Input Constraints</b>	1017
973			1018
974	• Two children played in the garden. ( <i>Numeral, past tense, locative prepositional phrase</i> )	In Table 6, we show qualitative examples from languages generated with user-input constraints, which our system accepts as free text. These illustrate that our system succeeds in generating creative conlangs that adhere to the user-input specifications, allowing users to test creative, linguistic, and philosophical ideas beyond what is attested in natural languages.	1019
975			1020
976	New lexical items and grammar may be appended to the language sketch, though in our evaluations we translate each sentence independently (without re-adding new lexical items and grammar rules to the language sketch).		1021
977			1022
978			1023
979			1024
980			1025
981	<b>A.5 WALS Features</b>	<b>C Computation Usage</b>	1027
982	WALS features that are extracted and used for typological diversity calculations are shown in Table 5. We include their numbers from the WALS database, along with an overall description of the contents of each feature.	as our tests focus on large models run via external APIs, we focus on token counts as the primary measurement of computation. This value fluctuates depending on the exact model used and due to randomness between runs. When using DeepSeek-R1, our full pipeline (with self-refinement and sentence translations) consumes approximately 660K tokens for a single language, costing about \$4 USD on the Together AI platform. This is largely attributable to self-refinement loops; generating a single language sketch without self-refinement or sentence translations consumes approximately 70K tokens, a ten-fold decrease.	1028
983			1029
984			1030
985			1031
986			1032
987	<b>A.6 Language Generation Details</b>		1033
988	LLM generation uses the maximum values for maximum output tokens and otherwise using default recommended hyperparameters for decoding (temperature, top-p). For metric calculations in our experiments, we sample $N \approx 20$ languages.		1034
989			1035
990	Due to resource constraints, the number of languages generated for metric calculations varies between $N = 17$ and $N = 21$ depending on setting. We use rejection sampling to remove degenerate outputs that do not obey the required language sketch format.		1036
991			1037
992			1038
993			1039
994			1040
995			1041
996			1042
997			1043
998			1044
999			1045
1000			1046
1001			1047
1002			1048
1003			1049
1004			1050
1005			1051
1006	<b>B Additional Results</b>		1052
1007	<b>B.1 Example Language Sketches</b>		1053
1008	In the supplementary material, we provide various ConlangCrafter-generated language sketches and translations as a browsable HTML page. In addition, we provide the full text of a single language sketch and constructive translation outputs in Figures 13 to 19. Note that the sketch is saved as free	<b>D Annotator Instructions and Protocol</b>	1054
1009			1055
1010			1056
1011			1057
1012			1058
1013			1059
			1060

User-Input Control	Sample Sentence	Notes
The language is a creole combining Japanese and Esperanto.	mat:a-o amai pāno-un ?amiko wait-NPST sweet bread-ACC friend “A friend waits for the sweet bread.”	Cf. Esperanto <i>amiko</i> “friend”, <i>pano</i> , “bread”; Japanese <i>matta</i> “waited”, <i>amai</i> “sweet”, <i>pan</i> “bread”
This language is nasal-centric, with all consonants and vowels nasalized and a rich vocabulary and grammar centered around smells.	ʰ  ə̃m-ʰgə̃ má-ʰ  ə̃:n-ŋà̃n sleep-3SG.I.AGR I.SG-person-NOM “The person is sleeping (I can smell their sleeping scent).”	Smell-based grammar includes smell-based noun classes and olfactory evidentiality (for events experienced by smell).
There are no consonant phonemes.	a-a.o.-a-úu-óu 1.SUBJ-see-2.OBJ-PFV-DIRECT “I have seen you”	Non-phonemic glottal and pharyngeal onsets appear phonetically depending on syllable nucleus vowel quality.
All inflectional forms are suppletive, and words in a sentence are ordered alphabetically.	janta kasa sake see[3S.S/3S.O,INFER] person.ACC person.NOM “The person sees the person (I infer).”	Example sentence shows suppletion (of “person”) and is in alphabetical order: j < k < s. Other suppletive forms of “to see” include fans (see[3S.S/3S.O,VIS]), teso (seeing.NMLZ), pote (see[3S.S/3S.O,REPOR]), and more.
Verbless constructions (null verb) are common and have a variety of meanings depending on the argument frame present, being used for many functions that are typically lexical verbs (far beyond copular functions).	stʷ ũ kʰo.ne mē.ʰa ɲa.pʰi.na ʱa pʷ.jeʰ PFV.PST ERG.III teacher(III) DAT.III person(III) water(IV) “The teacher made the person drink water.”	Lit. “(Did) teacher to person water”; stʷ ũ is a TAM particle and the predicate “made drink” is implied.
Triple center embeddings are common.	pʰu:ʰmor-wo=o [pʰesi-e=je [oʰqʰos-om=jom tʰeʰkʰi:sir-na] jeʰkwe:tʰis-na] ruʰpʰuj-om=om oʰxo: tʰsʰɛn man-AGT=3A [dog-INTR=LOGO.S [rock-PAT=LOGO.P chase-CONV] see-CONV] food-PAT=3P FUT eat “The man, who sees his dog which is chasing his (the man’s) rock, will eat the food.”	From the grammar: “A defining syntactic feature is its routine use of deep center-embedding... The system allows for multiple, nested embeddings, with triple center-embeddings being common in narrative and formal speech.”
The language is produced by an alien cephalopod species. Phonemes are color values and gestures rather than consonants or vowels. Indicate each one with a two-character ASCII code.	PB BR SRHC.PWHC(Peak) SRSW(Peak) PFV VIS CL1.AGT-move(V.PEAK) this.one(CL1) “Did this being move?”	“Chromemes” (color-based) have codes indicating dynamic features like static (S-) and pulsating (P-), and hue features like warm (-R) and cool (-B). “Kinemes” (gesture-based) such as HC involve curling tentacles. Contour “tones” such as “Peak” indicate movement patterns through the water.

Table 6: **Qualitative examples** of ConlangCrafter-generated languages with user-input conditions, demonstrating user control and the ability to test creative, linguistic, and philosophical ideas.

1061	<i>(e.g. automatic value said SOV but language is actually SVO)</i>	<b>D.2 Manual Consistency Evaluation</b>	1071
1062		<b>Materials shown to annotators.</b> Annotators were shown full language sketches along with constructive translation results. Each translation entry presented:	1072
1063	• 1: <i>If the automatic feature value is correct</i>	1. the source English sentence (prompt),	1073
1064	• 2: <i>If the automatic feature value is undefined but should be defined (e.g. automatic value is empty but should be SVO)</i>	2. the generated target sentence (surface form),	1074
1065		3. an interlinear gloss,	1075
1066		4. optional fields documenting any <i>new lexical items</i> or <i>new grammatical rules</i> the generator introduced,	1076
1067	• 3: <i>If the automatic feature value is defined but should be undefined (e.g. automatic value is SVO but word order is actually not defined anywhere in the language sketch)</i>	1. the source English sentence (prompt),	1077
1068		2. the generated target sentence (surface form),	1078
1069		3. an interlinear gloss,	1079
1070		4. optional fields documenting any <i>new lexical items</i> or <i>new grammatical rules</i> the generator introduced,	1080
			1081

1082 5. an automatically produced LLM judgement  
1083 (inconsistent / mostly consistent / consist-  
1084 ent) with a brief rationale, shown as a non-  
1085 authoritative hint.

• Consider a translation valid as long as it  
is consistent with the language's description,  
even if new words and/or grammar points had  
to be invented to translate it.

1129  
1130  
1131  
1132

1086 **Full Instructions Provided.** The following is the  
1087 full text of the instructions provided for annotation:  
1088 [You are provided with] a browsable HTML file  
1089 with 20 generated languages for the eval. Each  
1090 language has its description (phonology and gram-  
1091 mar) followed by the translations of ten sentences.  
1092 This time, each sentence translation is shown with  
1093 the result of an LLM judge which tries to decide if  
1094 the translation is consistent with the language de-  
1095 scription – it judges it as either consistent, mostly  
1096 consistent, or inconsistent, along with its reasoning.  
1097 It may sometimes be wrong, but you can use it as a  
1098 hint to try to decide if a translation is valid.

[In the provided spreadsheet], for each sentence  
in each language, please enter 0 if the sentence  
is inconsistent with the language, 1 if it is mostly  
consistent, and 2 if it is fully consistent with the  
language.

Each translation has the following format:

- *Top, in italics:* The English sentence to be translated.
- **Bold:** The attempted translation of this sentence into the language
- *Typewriter font:* The attempted interlinear gloss of this translation.
- "New Words": If the language description was missing some words required to translate the sentence, this should list new words that were invented for the language to be able to translate the sentence.
- "New Grammar Rules": If the language description was missing some grammar points needed to be able to translate the sentence, this lists these new invented grammar points ("rule"), along with explanations ("justification") for why they should make sense given the language's description.
- LLM judgement – inconsistent / mostly consistent / consistent + explanation. As stated above, these are not guaranteed to be correct, but may help you decide if a translation is really consistent with the language or not.

Important guidelines:

• Different translations of different sentences might make different decisions for new words and grammar. They do not need to be consistent with each other – only judge if a single translation is consistent with the language's original description.

1133  
1134  
1135  
1136  
1137  
1138

<p>I am designing a hypothetical language's phonology. Provide me with {n_questions} sliders with scales from 1 to {scale_size}, and/or multiple-choice questions with {n_answers} possible answers (numbered 1-{scale_size}), to determine the most important typological features to construct this language's phonology. There should be {n_questions} of them total (counting sliders and multiple-choice questions together). Provide no additional explanation or discussion.</p>
<p>I am designing a hypothetical language's phonology. Consider the following checklist: == START CHECKLIST == {checklist} == END CHECKLIST == Use values {values} for those respectively. It should also obey the following constraint(s); if these contradict the above, these take priority: {custom} Now write a summary of its phonology. Make sure there are a couple of aspects that are unusual, creative, interesting, or surprising, while still obeying the constraints from above. Format your output as follows. Give no additional explanation or discussion. # Phonology ## Consonants (IPA chart of consonants, as markdown table) ## Vowels (IPA chart of vowels, as markdown table) ## Phonotactics (Brief, single-paragraph explanation) ## Suprasegmentals (Brief, single-paragraph explanation)</p>
<p>A hypothetical language has the following phonology: === START === {phonology} === END === Write a description of the distribution of word shapes in this language, touching content vs. function items and the distribution of word lengths and syllable counts. Use qualitative descriptors (like "most," "many," "some," "few," "rare") rather than specific percentages or numbers. Include at least {n} diverse lexical items that illustrate the points discussed. Give the words in IPA (underlying phonemic representation only), making sure all phonemic features are indicated, including contrastive suprasegmentals (if relevant). Do not give their translations in English; only note if they are content or function items and how common or uncommon they are. The new lexical items should obey the following constraints: {custom} If these contradict anything above, these constraints take priority. Format your output as follows. Give no additional explanation or discussion. ## Word Shapes and Lexical Statistics (description here)</p>

Figure 4: Phonology prompts.

<p>I am designing a hypothetical language's grammar (morphology and syntax). Provide me with {n_questions} sliders with scales from 1 to {scale_size}, and/or multiple-choice questions with {n_answers} possible answers (numbered 1-{{scale_size}}), to determine the most important typological features to construct this language's grammar (morphology and syntax). There should be {n_questions} of them total (counting sliders and multiple-choice questions together). Provide no additional explanation or discussion.</p>
<p>I am designing a hypothetical language's grammar (morphology and syntax). Consider the following checklist:  == START CHECKLIST ==  {checklist}  == END CHECKLIST ==  Use values {values} for those respectively.  It should also obey the following constraint(s); if these contradict the above, these take priority: {custom}  The language has the following phonology:  === START ===  {phonology}  === END ===  Now write a summary of its grammar (morphology and syntax).  Make sure there are a couple of aspects that are unusual, creative, interesting, or surprising, while still obeying the constraints from above.  For any statement, include examples with interlinear glosses and English translations. When possible, use words/roots from the list above in examples. Examples should be provided right next to the statements that they illustrate (not all at the end).  Format your output as follows. Give no additional explanation or discussion.  # Grammar  ## Morphology  (summary of morphology here)  ## Syntax  (summary of syntax here)</p>
<p>A hypothetical language has the following phonology:  === START ===  {phonology}  === END ===  Here is a summary of its grammar (morphology and syntax):  === START ===  {grammar}  === END ===  Write expanded grammar sections including important points that are missing above, that would be needed to understand or use the language.  Make sure there are a couple of aspects that are unusual, creative, interesting, or surprising, while still obeying the constraints from above.  It should also obey the following constraint(s); if these contradict the above, these take priority: {custom}  For any statement, include examples with interlinear glosses and English translations. When possible, use words/roots from the list above in examples. Examples should be provided right next to the statements that they illustrate (not all at the end).</p>
<p>Combine the summaries below together. If there are any contradictions, amend as needed to make everything consistent. Make sure to include all information and examples that appear anywhere in any of the summaries.  Only return the new summary (do not give any further commentary or explain your amendments).  {summaries}  Format your output as follows. Make sure it contains all information from the summaries above. Examples include both interlinear glosses and English translations, and should be provided right next to the statements that they illustrate (not all at the end). Give no additional explanation or discussion.  # Grammar  ## Morphology  (morphological information here)  ## Syntax  (syntactic information here)</p>

Figure 5: Grammar prompts.

A hypothetical language has the following phonology and grammar:

```

=== START ===
{phonology}
{grammar}
=== END ===

```

Output a CSV with a lexicon of the language, including all lexical items that appear in the language's information above. The CSV column names and their contents should be:

- \* "ipa": Lexical item as IPA (without brackets)
- \* "pos": Part of speech
- \* "translation": Translation of item into English
- \* "grammar": Any grammar points or information specific to that lexical item (e.g. inflectional or conjugational classes, irregularities, ...)
- \* "derivation": If the item is derived, note its derivation here
- \* "notes": Any additional notes

Provide translations for all lexical items, even those whose translations are not explicitly specified in the provided background above (i.e. don't list any translations as "unknown"). Do not provide any further explanation or text, only the CSV.

---

A hypothetical language has the following phonology:

```

=== START ===
{phonology}
=== END ===

```

It has the following grammar:

```

=== START ===
{grammar}
=== END ===

```

It has the following lexicon:

```

=== START ===
{lexicon}
=== END ===

```

Propose at least {n} additional lexical items to add to the lexicon, including a diverse set of items covering common and uncommon concepts and different parts of speech. Make sure they obey the language's phonology and morphology, including following the word shape distribution described in "Word Shapes and Lexical Statistics". Also make sure they do not overlap any existing lexical items.

Output a CSV in the same format as the lexicon above. The CSV column names and their contents should be:

- \* "ipa": Lexical item as IPA (without brackets)
- \* "pos": Part of speech
- \* "translation": Translation of item into English
- \* "grammar": Any grammar points or information specific to that lexical item (e.g. inflectional or conjugational classes, irregularities, ...)
- \* "derivation": If the item is derived, note its derivation here
- \* "notes": Any additional notes

Do not provide any further explanation or text, only the CSV.

Figure 6: Lexicon prompts.

<p>Here is a hypothetical language's {content_type}:  === START ===  {content}  === END ===</p> <p>Is the description of the language's {content_type} consistent? Return a JSON with keys:  * "overall_score": Integer from 1 (completely inconsistent) to 10 (completely consistent), scoring the {content_type} overall. If there are not issues that are strictly contradictions or errors (for example, if the only issues are ambiguities/unclear points), the score should be 9 (consistent but somewhat unclear). If there are only minor contradictions or errors, the score should be 8 (very minor inconsistencies).  * "issues": List of errors and inconsistencies found (if any) and their corrections. Each item in this list should be an object with the following keys and values:  * "issue": String describing issue  * "type": One of "inconsistency"/"error"/"ambiguity", indicating if the issue is an inconsistency (contradiction), error (other mistake), or ambiguity (not strictly a mistake but unclear)  * "correction": String describing how it should be corrected  * "priority": 1 (high - severe issue), 2 (medium), or 3 (low - minor or very minor issue)  Be as exhaustive as possible in your search for issues.  Output only this JSON object. Give no additional explanation or discussion.</p>
<p>Here is a hypothetical language's {content_type}:  === START ===  {content}  === END ===</p> <p>For context, here is the language's {context_type}:  === START ===  {context}  === END ===</p> <p>Is the description of the language's {content_type} consistent with itself and with its {context_type}? Return a JSON with keys:  * "overall_score": Integer from 1 (completely inconsistent) to 10 (completely consistent), scoring the {content_type} overall. If there are not issues that are strictly contradictions or errors (for example, if the only issues are ambiguities/unclear points), the score should be 9 (consistent but somewhat unclear). If there are only minor contradictions or errors, the score should be 8 (very minor inconsistencies).  * "issues": List of errors and inconsistencies found (if any) and their corrections. Each item in this list should be an object with the following keys and values:  * "issue": String describing issue  * "type": One of "inconsistency"/"error"/"ambiguity", indicating if the issue is an inconsistency (contradiction), error (other mistake), or ambiguity (not strictly a mistake but unclear)  * "correction": String describing how it should be corrected in the {content_type}. Note that only the {content_type} can be corrected, not the {context_type}. If the issue is due to a conflict with the {context_type}, make sure this description will be clear to an editor who does not have the {context_type} in front of them when amending the {content_type}.  * "priority": 1 (high - severe issue), 2 (medium), or 3 (low - minor or very minor issue)  Be as exhaustive as possible in your search for issues.  Output only this JSON object. Give no additional explanation or discussion.</p>
<p>Here is a hypothetical language's phonology:  === START ===  {content}  === END ===</p> <p>Here is a judgement of its overall consistency on a scale of 1 (completely inconsistent) - 5 (completely consistent), and specific issues found (if any) and their priorities (from 1=high to 3=low) and how to correct them:  {judgement}</p> <p>Correct these points (and any other errors or inconsistencies, if any), outputting an amended version (without === START === / === END === lines). Give no additional explanation or discussion.</p>

Figure 7: Self-refinement prompts.

```

Here is a translation result for a constructed language:
=== START ===
{content}
=== END ===
For context, here is the language specification:
=== START ===
{context}
=== END ===
Evaluate the quality and accuracy of this translation. Return a JSON with keys:
* "overall_score": Integer from 1 (completely incorrect) to 10 (excellent translation), scoring the
translation overall. Consider:
- Adherence to phonological rules (10: fully consistent, 8-9: minor violations, 5-7: some violations,
1-4: major violations)
- Adherence to grammatical rules (10: fully consistent, 8-9: minor violations, 5-7: some violations,
1-4: major violations)
- Appropriate use of lexicon (10: excellent use, 8-9: mostly appropriate, 5-7: some issues, 1-4:
poor lexical choices)
- Quality of glossing (10: accurate and complete, 8-9: mostly accurate, 5-7: some errors, 1-4: poor
glossing)
- Semantic accuracy (10: meaning preserved, 8-9: mostly preserved, 5-7: some meaning lost, 1-4:
meaning significantly altered)
* "issues": List of problems found (if any). Each item should be an object with:
* "issue": String describing the problem
* "type": One of "phonological_violation"/"grammatical_violation"/"lexical_error"/"glossing_error"/
"semantic_error"/"consistency_error"
* "correction": String describing how the translation should be corrected
* "priority": 1 (high - major error affecting meaning or violating core rules), 2 (medium -
noticeable error), or 3 (low - minor issue or style preference)
Be thorough in checking:
1. Phonological consistency: Do invented words follow the sound patterns and constraints?
2. Grammatical consistency: Are word order, morphology, and syntax rules followed?
3. Lexical appropriateness: Are existing words used correctly? Are new words justified and
well-formed?
4. Glossing accuracy: Does the gloss correctly break down morphemes and grammatical functions?
5. Semantic preservation: Does the translation convey the intended meaning?
6. Internal consistency: Are new rules and words consistent with each other?
Output only this JSON object. Give no additional explanation or discussion.

```

---

```

Here is a translation result for a constructed language that might need improvement:
=== START ===
{content}
=== END ===
Based on this quality assessment:
=== START ===
{judgement}
=== END ===
Please provide an improved version of the translation that addresses the identified issues. Make
sure to:
1. Fix any phonological violations by adjusting words to follow the sound patterns
2. Correct grammatical errors to match the specified rules
3. Improve lexical choices and justify any new words created
4. Ensure accurate glossing with proper morpheme breakdown
5. Preserve semantic meaning while fixing technical issues
6. Maintain consistency across all elements
Return the corrected translation in the same JSON format as the original:
{{
  "sentences": [
    {{
      "conlang_sentence": "<corrected sentence in the constructed language only - no glosses, morpheme
breaks, or explanations>",
      "gloss": "<corrected word-by-word breakdown with morphemes and grammatical functions>",
      "new_words": [{{"<new_word>": "<english_translation>"}}],
      "new_grammar_rules": [{{"rule": "<description_of_new_rule>", "justification":
"<explanation_of_why_needed_and_consistency>"}]}]
    }}
  ]
}}
Output only this JSON object. Give no additional explanation or discussion.

```

Figure 8: Self-refinement prompts (translation).

```

You are a skilled linguist working with a constructed language. You have been provided with a
complete language specification including vocabulary, grammar and phonology.
A hypothetical language has the following phonology:
=== START ===
{phonology}
=== END ===
It has the following grammar:
=== START ===
{grammar}
=== END ===
{lexicon_section}
Your task is to translate the following English sentence into this constructed language:
English sentence: {input_sentence}
Instructions:
1. Use the vocabulary provided in the language specification (if available)
2. Follow the grammatical rules and patterns described
3. Apply the phonological conventions
4. If a word is not in the vocabulary, invent a new word that is consistent with the specifications
5. If a grammatical construction is needed but not specified, invent a new grammar rule that is
consistent with the existing language patterns
6. Ensure the translation follows the word order and morphological patterns specified
If you create new words, ensure they:
- Follow the phonological constraints of the language
- Have appropriate semantic scope for the meaning needed
- Use appropriate derivational processes if applicable
If you create new grammar rules, ensure they:
- Are consistent with existing grammatical patterns
- Follow the language's morphological and syntactic tendencies
- Are plausible extensions of the existing system
Provide a gloss line: break down the conlang sentence word by word, showing morphemes and their
grammatical functions using standard linguistic abbreviations (e.g., FUT, SBJ, OBJ, ACC, etc.). The
gloss should use English abbreviations and morpheme breakdowns, NOT the conlang words.
Return the result in JSON format only:
{{
  "sentences": [
    {{
      "conlang_sentence": "<sentence in the constructed language>",
      "gloss": "<word-by-word breakdown with morphemes and grammatical functions>",
      "new_words": [{{"new_word": "<english_translation>"}]},
      "new_grammar_rules": [{{"rule": "<description_of_new_rule>", "justification":
      "<explanation_of_why_needed_and_consistency>"}]}]
    }}
  ]
}}

```

Figure 9: Translation prompt.

```

Create a conlang (constructed language). Include a description of its phonology, grammar (morphology
and syntax), and lexicon. Use the following format:
# Phonology
## Consonants
(IPA chart of consonants, as markdown table)
## Vowels
(IPA chart of vowels, as markdown table)
## Phonotactics
(Brief, single-paragraph explanation)
## Suprasegmentals
(Brief, single-paragraph explanation)
## Word Shapes and Lexical Statistics
(description here)
# Grammar
## Morphology
(morphological information here in markdown format)
## Syntax
(syntactic information here)
# Lexicon
(list of at least 100 lexical items in the language in a csv format)
# Corpus
give translations and interlinear glosses for the following 10 sentences. Invent new words or
grammar rules, if needed, for each sentence.
Provide a gloss line: break down the conlang sentence word by word, showing morphemes and their
grammatical functions using standard linguistic abbreviations (e.g., FUT, SBJ, OBJ, ACC, etc.). The
gloss should use English abbreviations and morpheme breakdowns, NOT the conlang words.
1. The big dog is sleeping.
2. Where is my book?
3. She will give him water.
4. This child walked to that house yesterday
5. Are you hungry?
6. Give me the red bird!
7. The woman and the man are talking.
8. I do not see three cats.
9. There is a black mountain.
10. The two children played in the garden.
Return the translation results in JSON format:
{{
  "sentences": [
    {{
      "english_sentence": "<original English sentence 1>",
      "conlang_sentence": "<sentence in the constructed language>",
      "gloss": "<word-by-word breakdown with morphemes and grammatical functions>",
      "new_words": [{{"new_word": "<english_translation>"}]},
      "new_grammar_rules": [{{"rule": "<description_of_new_rule>", "justification":
      "<explanation_of_why_needed_and_consistency>"}]}]
    }},
    {{
      "english_sentence": "<original English sentence 2>",
      "conlang_sentence": "<sentence in the constructed language>",
      "gloss": "<word-by-word breakdown with morphemes and grammatical functions>",
      "new_words": [{{"new_word": "<english_translation>"}]},
      "new_grammar_rules": [{{"rule": "<description_of_new_rule>", "justification":
      "<explanation_of_why_needed_and_consistency>"}]}]
    }}
  ]
}}

```

Figure 10: Baseline single prompt.

```

Please analyze the following documentation for the constructed language "{your_language_name}" and return the typological analysis as a JSON object.
A hypothetical language has the following phonology:
=== START ===
{phonology}
=== END ===
It has the following grammar:
=== START ===
{grammar}
=== END ===
It has the following lexicon:
=== START ===
{lexicon}
=== END ===
## JSON Schema to Populate
{
  "language_name": "{your_language_name}",
  "analysis_timestamp_utc": "{current_utc_iso_timestamp}",
  "typology": {
    "wals_81A_svo_order": {
      "value": "SVO | SOV | VSO | VOS | OVS | OSV | No Dominant Order | null",
      "confidence": "High | Medium | Low"
    },
    "wals_85A_adpositions": {
      "value": "Prepositions | Postpositions | Inpositions | No Adpositions | null",
      "confidence": "High | Medium | Low"
    },
    "wals_87A_adjective_noun": {
      "value": "Adjective-Noun | Noun-Adjective | null",
      "confidence": "High | Medium | Low"
    },
    "wals_20A_fusion": {
      "value": "Isolating | Agglutinative | Fusional | null",
      "confidence": "High | Medium | Low"
    },
    "wals_26A_affixation": {
      "value": "Strongly Suffixing | Weakly Suffixing | Equal Prefixing/Suffixing | Weakly Prefixing | Strongly Prefixing | null",
      "confidence": "High | Medium | Low"
    },
    "wals_13A_tone": {
      "value": "Tonal | Non-tonal | null",
      "confidence": "High | Medium | Low"
    },
    "wals_30A_gender_count": {
      "value": "None | Two | Three | Four | Five or more | null",
      "confidence": "High | Medium | Low"
    },
    "wals_49A_case_count": {
      "value": "None (0-1) | Minimal (2-3) | Moderate (4-5) | Extensive (6+) | null",
      "confidence": "High | Medium | Low"
    },
    "wals_alignment": {
      "value": "Accusative | Ergative | Active-Stative | Split | null",
      "confidence": "High | Medium | Low"
    },
    "wals_87B_relative_clause_order": {
      "value": "Head-initial | Head-final | Mixed | null",
      "confidence": "High | Medium | Low"
    },
    "wals_genitive_order": {
      "value": "Genitive-Noun | Noun-Genitive | null",
      "confidence": "High | Medium | Low"
    },
    "wals_question_marking": {
      "value": "Intonation | Particle | Morphological | Inversion | null",
      "confidence": "High | Medium | Low"
    },
    "phoneme_inventory": {
      "vowels": "Small (<=5) | Medium (6-8) | Large (>=9) | null",
      "consonants": "Small (<=20) | Medium (21-35) | Large (>=36) | null",
      "confidence": "High | Medium | Low"
    },
    "valence_morphology": {
      "causative": "Yes | No | null",
      "passive": "Yes | No | null",
      "applicative": "Yes | No | null"
    },
    "numeral_classifiers": {
      "value": "Classifier language | Non-classifier | null",
      "confidence": "High | Medium | Low"
    }
  }
}

```

Figure 11: Diversity evaluation prompt.

You are a senior linguist specializing in constructed languages. Your task is to check the internal consistency of a single translated sentence from a conlang, examining how well the translation aligns with the given phonology, grammar, and lexicon.

- Carefully read the three language sections (PHONOLOGY, GRAMMAR, LEXICON).
- Examine the provided sentence translation, including the conlang sentence, gloss, and claimed new words/grammar rules.
- Identify every inconsistency, error, or mismatch you can find in this specific translation (for example: phonotactic violations, grammatical rule violations, lexicon mismatches, gloss errors, etc.).

Only account for linguistic errors, not formatting or stylistic errors.

- For each issue, decide how serious it is:
  - minor – cosmetic problems that don't affect comprehension or linguistic accuracy
  - moderate – noticeable errors that affect clarity or violate established rules but don't break the translation entirely
  - major – serious violations that make the translation incorrect or incomprehensible given the language system
- Produce your answer ONLY in the JSON format specified below. No additional keys, no comments, no markdown fences.

Required output JSON format:

```
{
  "inconsistencies": [
    {
      "area": "string (Phonology | Grammar | Lexicon | Translation | Gloss | Cross-domain)",
      "description": "string (describe what is inconsistent)",
      "severity": "string (minor | moderate | major)"
    }
    ... (0 or more items)
  ],
  "final_verdict": "string (consistent | mostly consistent | inconsistent)"
}
```

Guidelines for the final verdict:

- If no inconsistencies are found, return "consistent".
- If only minor issues are found, or one moderate issue, return "mostly consistent".
- If any major issue, or multiple moderate issues are found, return "inconsistent".

```
=== LANGUAGE DATA STARTS ===
Phonology:
=== START ===
{phonology}
=== END ===
Grammar:
=== START ===
{grammar}
=== END ===
Lexicon:
=== START ===
{lexicon}
=== END ===
=== TRANSLATION TO EVALUATE ===
English sentence: {english_sentence}
Conlang translation: {conlang_sentence}
Gloss: {gloss}
New words claimed: {new_words}
New grammar rules claimed: {new_grammar_rules}
```

Figure 12: Consistency evaluation prompt.

## # Phonology

### ## Consonants

| | Labial | Alveolar | Palatal | Velar | Uvular | Glottal |

| :-: | :-: | :-: | :-: | :-: | :-: | :-: |

| \*\*Plosive\*\* | p | t | k | q | |

| \*\*Ejective\*\* | p' | t' | k' | q' | |

| \*\*Nasal\*\* | m | n | | | |

| \*\*Prenasalized Stop\*\* | mb | nd | ng | | |

| \*\*Fricative\*\* | s | | | h | |

| \*\*Liquid\*\* | | | | | |

| \*\*Glide\*\* | | | j | w | | |

### ## Vowels

| | Front | Central | Back |

| :-: | :-: | :-: | :-: |

| \*\*High (+ATR)\*\* | i | | u |

| \*\*High (-ATR)\*\* | ɪ | | ʊ |

| \*\*Mid (+ATR)\*\* | e | | o |

| \*\*Mid (-ATR)\*\* | ɛ | | ɔ |

| \*\*Low (-ATR)\*\* | a | | |

### ## Phonotactics

The language has a strict CV syllable structure. All words consist of one or more CV syllables, with no consonant clusters, codas, or vowel-initial words permitted. There are significant co-occurrence restrictions: ejectives (*p'*, *t'*, *k'*, *q'*) may only be followed by -ATR vowels (*ɪ*, *ʊ*, *ɛ*, *ɔ*, *a*), while prenasalized stops (*mb*, *nd*, *ng*) may only be followed by +ATR vowels (*i*, *u*, *e*, *o*). The low vowel */a/* is neutral to front/back harmony but acts as a -ATR vowel for the purposes of consonant co-occurrence and ATR harmony.

### ## Suprasegmentals

The language has no phonemic tone. Primary stress is fixed on the first syllable of a word. Two interlocking vowel harmony systems are present: front/back harmony and ATR/RTR harmony. All vowels in a word must agree in tongue root position (either all +ATR or all -ATR). Within a word, all vowels other than */a/* must also agree in backness (either all front or all back). The low vowel */a/* is exempt from the front/back harmony requirement and can co-occur with a series of front vowels or a series of back vowels, provided the ATR harmony is maintained. These harmony rules are triggered by the root's vowels and apply to all affixes.

### ## Word Shapes and Lexical Statistics

All words in the language are composed of one or more CV syllables. The smallest possible word is a single CV syllable, and there is no theoretical maximum length, though words longer than four or five syllables are rare.

Monosyllabic and disyllabic words are very common and constitute the vast majority of the lexicon. Most function items are monosyllabic, while most content words are disyllabic or trisyllabic. Longer words are almost exclusively derived or compounded content words.

The strict vowel harmony systems create distinct "sets" of vowels that can appear in a given word: front +ATR, front -ATR, back +ATR, and back -ATR. The vowel */a/* can appear with either the front -ATR set or the back -ATR set. This, combined with the co-occurrence restrictions on ejective and prenasalized consonants, means that certain phoneme combinations are common while others are impossible. For instance, words containing prenasalized stops will only ever feature the vowels */i*, *u*, *e*, *o*, while words with ejectives will only ever feature */ɪ*, *ʊ*, *ɛ*, *ɔ*, *a*. This gives words containing these consonant types a distinct phonetic character. Words with only plain plosives, nasals, fricatives, liquids, and glides are the most numerous and phonologically flexible.

### ### Lexical Items

#### \*\*Content Items (Common)\*\*

\* *'k'osa/*

\* *'ndoku/*

\* *'pele/*

\* *'huti/*

\* *'q'ala/*

\* *'me'dile/*

\* *'sot'a/*

\* *'weje/*

\* *'mbulo/*

\* *'jok'ɔ/*

\* *'quno/*

\* *'t'uha/*

\* *'p'ela/*

#### \*\*Content Items (Uncommon)\*\*

\* *'p'ot'a/*

\* *'ngombiso/*

\* *'t'esɪtɪ/*

\* *'q'uk'at'a/*

\* *'wuwo/*

\* *'tjɛɛɛ/*

#### \*\*Function Items (Common)\*\*

\* *'se/*

\* *'ko/*

\* *'na/*

\* *'tu/*

\* *'le/*

Figure 13: Sample language sketch, page 1/7.

<p><b>**Function Items (Uncommon)**</b></p> <p>* /q'o/</p> <p>* /'do/</p> <p># Grammar</p> <p>## Morphology</p> <p>The language is primarily analytic, with most grammatical information conveyed by word order and free-standing particles. Nouns are invariant and do not decline for case or number. The key exception to the analytic structure is the verb, which is strictly head-marking and carries a small set of agglutinative prefixes that cross-reference its core arguments.</p> <p>The language has an active-stative morphosyntactic alignment. Verbs are obligatorily prefixed to indicate the semantic role of their arguments. There are two sets of prefixes: an Agentive set (for volitional actors) and a Patientive set (for entities that are in a state or are affected by an action). The choice of prefix for an intransitive verb depends on the semantics of the verb and its subject.</p> <p>* An intransitive verb with a volitional agent takes an Agentive prefix ('Sa').</p> <p>* An intransitive verb with a patient-like subject takes a Patientive prefix ('Sp').</p> <p>* A transitive verb takes both an Agentive ('A') and a Patientive ('P') prefix, in that order.</p> <p>The prefixes are single CV syllables and obey the language's vowel harmony rules, assimilating to the front/back and ATR quality of the verb root.</p> <p>  Role   Prefix Form   Example (with root 'hoto' "run")   Example (with root 'k'osa' "break")  </p> <p>  :---   :---   :---   :---  </p> <p>  <b>**Agentive**</b>   'to-' / 'tu-'   'to-hoto'   'tu-k'osa'  </p> <p>  <b>**Patientive**</b>   'no-' / 'no-'   'no-hoto'   'no-k'osa'  </p> <p>*To-hoto hoto.*</p> <p>...</p> <p>to-hoto hoto</p> <p>AGT-run man</p> <p>"The man runs." (volitional)</p> <p>...</p> <p>*No-k'osa p'ela.*</p> <p>...</p> <p>no-k'osa p'ela</p> <p>PAT-break rock</p> <p>"The rock broke." (stative)</p> <p>...</p>	<p>*Tu-no-k'osa hoto p'ela.*</p> <p>...</p> <p>tu-no-k'osa hoto p'ela</p> <p>AGT-PAT-break man rock</p> <p>"The man broke the rock."</p> <p>...</p> <p>*Se to-hoto hoto.*</p> <p>...</p> <p>se to-hoto hoto</p> <p>IRR AGT-run man</p> <p>"The man will run / might run."</p> <p>...</p> <p><b>### Verbal Derivation</b></p> <p>The verb root can be modified by derivational suffixes to change its meaning. These suffixes, like the prefixes, obey the language's vowel harmony rules. They are added directly to the root.</p> <p><b>#### 1. Causative Suffix '-lo' / '-lb'</b></p> <p>The causative suffix adds an agent that causes the action to occur, increasing the verb's valency. The newly introduced causer is always marked by the Agentive prefix ('to-' / 'tu-'), which harmonizes with the verb root as usual.</p> <p>* <b>**Intransitive to Transitive:**</b> When added to an intransitive verb, it makes it transitive.</p> <p>* *No-k'osa p'ela.* ("The rock broke.")</p> <p>* *Tu-no-k'osa-lo hoto p'ela.*</p> <p>...</p> <p>tu-no-k'osa-lo hoto p'ela</p> <p>AGT-PAT-break-CAUS man rock</p> <p>"The man made the rock break."</p> <p>...</p> <p>(This is semantically distinct from the base transitive form, emphasizing the causing of a state rather than a direct action.)</p> <p>* <b>**Transitive to Ditransitive:**</b> When added to a transitive verb, it makes it ditransitive. The original agent is demoted to a secondary object (the "causee"), and the original patient remains the patient. The original Agentive prefix is replaced by one marking the new causer, while the Patientive prefix is retained to mark the original patient.</p>
--	--

Figure 14: Sample language sketch, page 2/7.

<p>* *Tu-no-sot'a weje jk'o.* ("The child saw the dog.")</p> <p>* *Tu-no-sot'a-lo hoto weje jk'o.*</p> <p>...</p> <p>tu-no-sot'a-lo hoto weje jk'o</p> <p>AGT-PAT-see-CAUS man child dog</p> <p>"The man made the child see the dog." / "The man showed the dog to the child."</p> <p>...</p>	<p>  Singular   Plural  </p> <p>  :-:   :-:   :-:  </p> <p>  **1st Person**   `me`   `meje`  </p> <p>  **2nd Person**   `so`   `soje`  </p> <p>  **3rd Person**   `he`   `heje`  </p>
<p>#### 2. Reciprocal Suffix '-so' / '-so'</p> <p>The reciprocal suffix indicates that the action is performed by members of a group on each other. It is used with a plural or coordinated subject and requires an Agentive prefix. Because the action is directed at another agent within the subject group, the verb becomes syntactically intransitive.</p>	<p>* *To-hoto.* ("He/she runs.")</p> <p>* *To-hoto **he**.*</p> <p>...</p> <p>to-hoto he</p> <p>AGT-run 3SG</p> <p>***He/She** runs." (in contrast to someone else)</p> <p>...</p>
<p>* *Tu-sot'a-so hoto na weje.*</p> <p>...</p> <p>tu-sot'a-so hoto na weje</p> <p>AGT-see-RECIP man and child</p> <p>"The man and the child see each other."</p> <p>...</p>	<p>* *Tu-no-sot'a **me** **he**.*</p> <p>...</p> <p>tu-no-sot'a me he</p> <p>AGT-PAT-see 1SG 3SG</p> <p>***I** see **him/her**."</p> <p>...</p>
<p>#### 3. Stative/Adjectival Suffix '-mo' / '-mo' and '-me' / '-me'</p> <p>This suffix derives a stative adjective from a verb root. The resulting word can be used as a modifier in a noun phrase. The suffix has four forms to obey vowel harmony: '-mo' (back, +ATR), '-mo' (back, -ATR), '-me' (front, +ATR), '-me' (front, -ATR).</p>	<p>### Negation</p> <p>Negation is marked by a particle, 'k'a', which is placed directly after the verb complex (i.e., after the prefixed verb and any derivational suffixes). The presence of 'k'a' forces the entire verb complex it modifies (both prefixes and root) to take on [-ATR] vowel harmony.</p>
<p>* **Verb root:** *k'osa' ("to break")</p> <p>* **Stative Adjective:** *k'osamo' ("broken")</p> <p>* *Tu-no-sot'a weje quno k'osamo.*</p> <p>...</p> <p>tu-no-sot'a weje quno k'osamo</p> <p>AGT-PAT-see child house broken</p> <p>"The child sees the broken house."</p> <p>...</p> <p>(The derived adjective 'k'osamo' contains an ejective from its root, so it follows the noun it modifies, obeying the phonologically conditioned syntax rule.)</p>	<p>* **Affirmative:** *To-hoto hoto.* ("The man runs.")</p> <p>(The verb 'to-hoto' is [+ATR].)</p> <p>* **Negative:** *Tu-hoto k'a hoto.*</p> <p>...</p> <p>tu-hoto k'a hoto</p> <p>AGT-run NEG man</p> <p>"The man does not run."</p> <p>...</p> <p>(The negative particle 'k'a' forces the entire verb 'to-hoto' to become its [-ATR] counterpart, 'tu-hoto'.)</p>
<p>### Pronouns and Pro-Drop</p> <p>Because the verb's prefixes clearly mark the agent and patient, overt noun phrases for the subject and object are often dropped when understood from context (pro-drop). Independent pronouns exist for emphasis, contrast, or clarity. They are not marked for case; their role is understood from the verb's prefixes. There is no gender distinction.</p>	<p>## Syntax</p> <p>The basic constituent order is Verb-Subject-Object (VSO). Overt noun phrases for the subject and object are often dropped when understood from context.</p>

Figure 15: Sample language sketch, page 3/7.

<p>*Tu-no-sot'a weje jk'ò.* ... tu-no-sot'a weje jk'ò AGT-PAT-see child dog "The child sees the dog." ...  *Tù-no-sot'a.* ... tu-no-sot'a AGT-PAT-see "(He/she/it) sees (him/her/it)." ...  The language uses postpositions almost exclusively. A postposition forms a phrase with the preceding noun.  *To-hoto hoto quno ko.* ... to-hoto hoto quno ko AGT-run man house in "The man runs in the house." ...  ### Noun Phrase Structure and Ejective Displacement  Noun phrase structure is typically head-final: adjectives and genitives (possessors) precede the noun they modify (Modifier-Possessor-Noun).  *Tu-no-sot'a mbulo weje pele jk'ò.* ... tu-no-sot'a mbulo weje pele jk'ò AGT-PAT-see big child small dog "The big child sees the small dog." ...  However, this order is subject to a phonologically conditioned rule called <b>**Ejective Displacement**</b>. Any item within a noun phrase that contains an ejective consonant—be it a modifier, possessor, or the head noun itself—disrupts the standard head-final NP order.  1. <b>**Standard Order (Modifier-Possessor-Noun):**</b>  * mbulo hoto quno* ... mbulo hoto quno</p>	<p>big man house "the big man's house" ...  2. <b>**Ejective in Modifier/Possessor (Displaces Element):**</b> A modifier or possessor containing an ejective must follow the rest of the noun phrase.  * hoto quno p'èla* ... hoto quno p'èla man house small "the man's small house" (adjective 'p'èla' has /p'/) ... * quno mbulo t'ùha* ... quno mbulo t'ùha house big chief "the chief's big house" (possessor 't'ùha' "chief" has /t'/) ... * *Tu-no-sot'a weje jk'ò q'ala.* ... tu-no-sot'a weje jk'ò q'ala AGT-PAT-see child dog bad "The child sees the bad dog." (Adjective 'q'ala' follows noun due to /q'/. ) ...  3. <b>**Ejective in Head Noun (Inverts Entire Phrase):**</b> If the head noun itself contains an ejective, the entire phrase inverts to a head-initial structure. The head noun comes first, followed by its possessors and then its other modifiers.  * <b>**Noun:**</b> 'jk'ò' ("dog", no ejective) -&gt; *pele jk'ò* ("small dog") * <b>**Noun:**</b> 'p'èla' ("rock", has /p'/) -&gt; *p'èla mbulo* ("the big rock") * <b>**Complex Example:**</b> 'p'èla hoto mbulo' ... p'èla hoto mbulo rock man big "the man's big rock" ...  ### Question Formation  #### 1. Yes/No Questions  Yes/no questions are formed with the sentence-final particle 'he'. This particle is phonologically neutral and does not affect harmony.</p>
--	---

Figure 16: Sample language sketch, page 4/7.

<p>* Tu-no-sot'a weje jk'o **he**?</p> <p>...</p> <p>tu-no-sot'a weje jk'o he</p> <p>AGT-PAT-see child dog Q</p> <p>"Does the child see the dog?"</p> <p>...</p>	<p>#### 1. Medial Verbs in Clause Chains</p> <p>A series of clauses can be linked together, with only the final verb in the chain being fully prefixed. All preceding, non-final verbs are "medial verbs," which appear as bare roots. These medial verbs share their subject with the following clause.</p>
<p>#### 2. Content (Wh-) Questions</p> <p>Content questions use question words that are fronted to the beginning of the sentence, before the verb. This is an exception to the standard VSO word order.</p>	<p>*hoto, sot'a p'ela, to-no-quno.*</p> <p>...</p> <p>run, see rock, AGT-PAT-take</p> <p>"(He) ran, saw the rock, and took it."</p> <p>...</p>
<p>**Common Question Words:**</p> <p>* `haje` ("who?", "what?" - for animates)</p> <p>* `nama` ("what?" - for inanimates)</p> <p>* `lele` ("where?")</p> <p>* `sese` ("when?")</p> <p>* `koke` ("why?")</p>	<p>#### 2. Medial Verbs in Relative Clauses</p> <p>Relative clauses are formed without a relative pronoun. The modifying clause is placed directly before the noun it modifies, and its verb is in the bare root (medial verb) form. The medial verb shares its agent with the head noun it modifies.</p>
<p>***Haje** tu-no-sot'a jk'o?*</p> <p>...</p> <p>haje tu-no-sot'a jk'o</p> <p>who AGT-PAT-see dog</p> <p>"Who sees the dog?"</p> <p>...</p>	<p>* Tu-no-sot'a weje [**sot'a jk'o**] hoto.*</p> <p>...</p> <p>tu-no-sot'a weje [sot'a jk'o] hoto</p> <p>AGT-PAT-see child [see dog] man</p> <p>"The child sees the man who saw the dog."</p> <p>...</p>
<p>***Nama** tu-no-sot'a weje?*</p> <p>...</p> <p>nama tu-no-sot'a weje</p> <p>what AGT-PAT-see child</p> <p>"What does the child see?"</p> <p>...</p>	<p>word,translation,pos,notes</p> <p>-lo/-lo,suffix,"Causative suffix",Verbal derivational suffix. Harmonizes for ATR and backness with the verb root.,,-lo (+ATR back), -lo (-ATR back), -le (+ATR front), -le (-ATR front)</p> <p>-mo/-mo/-me/-me,suffix,"Stative/Adjectival suffix",Verbal derivational suffix. Harmonizes for ATR and backness with the verb root.,,k'osa (v) &gt; k'osamo (adj),-mo (+ATR back), -mo (-ATR back), -me (+ATR front), -me (-ATR front)</p> <p>-so/-so/-se/-se,suffix,"Reciprocal suffix",Verbal derivational suffix. Harmonizes for ATR and backness with the verb root.,,-so (+ATR back), -so (-ATR back), -se (+ATR front), -se (-ATR front)</p> <p>/ ha/,postposition,"with; using",[-ATR] neutral vowel,,</p> <p>/ hopo-lo/,verb,"send; make go",Requires [+ATR] back harmony verb root.,Derived from verb root 'hopo' + causative suffix 'lo',.</p> <p>/ hopo-so/,verb,"go together; travel together",Requires [+ATR] back harmony verb root.,Derived from verb root 'hopo' + reciprocal suffix '-so',.</p> <p>/ hopo/,verb,"go",Requires [+ATR] back harmony verb root.,</p> <p>/ henz/,verb,"laugh",Requires [-ATR] front harmony verb root.,</p> <p>/ jeps/,noun,"hand",Requires [-ATR] front harmony,,</p> <p>/ kela/,noun,"tree",Requires [-ATR] front harmony,,</p> <p>/ kite/,noun,"knife",Requires [+ATR] front harmony,,</p> <p>/ k'at'a/,noun,"fire",Requires [-ATR] back harmony. Contains ejectives /k/ and /t/, triggering Ejective Displacement when it is the head noun.,</p>
<p>***Lele** to-hoto hoto?*</p> <p>...</p> <p>lele to-hoto hoto</p> <p>where AGT-run man</p> <p>"Where does the man run?"</p> <p>...</p>	
<p>### Subordination and Clause Chaining</p> <p>Subordination is handled through clause chaining and medial verbs. The bare verb root serves as a medial verb in two distinct constructions.</p>	

Figure 17: Sample language sketch, page 5/7.

*/k'a'da/*,verb,"sleep",Requires [-ATR] back harmony verb root. Contains an ejective /k/ and a prenasalized stop /ʔd/.,Irregular: Contains a prenasalized stop /ʔd/ followed by a [-ATR] vowel /a/, violating the rule that prenasalized stops must be followed by [+ATR] vowels.

*/k'i/*,particle,"completive aspect marker",Post-verbal particle. Forces the verb complex to take [-ATR] harmony. Contains ejective /k/.,,This particle forces [-ATR] harmony. Example: to-pete > tu-pete k'i.

*/k'otb/*,adjective,"hot",Requires [-ATR] back harmony. Contains ejective /k/,, triggering Ejective Displacement.,,

*/k'ele-sɛ/*,verb,"sing together",Requires [-ATR] front harmony verb root. Contains ejective /k/.,,Derived from verb root 'k'ele' (to sing) + reciprocal suffix '-sɛ'.,,

*/k'ele/*,verb,"sing",Requires [-ATR] front harmony verb root. Contains ejective /k/.,,

*/k'ub/*,verb,"drink",Requires [-ATR] back harmony verb root. Contains ejective /k/.,,

*/lolo/*,adjective,"red",Requires [+ATR] back harmony.,,

*/lɔk'o/*,noun,"blood",Requires [-ATR] back harmony. Contains ejective /k/,, triggering Ejective Displacement when it is the head noun.,,

*/lɛpe-le/*,verb,"feed",Requires [-ATR] front harmony verb root.,,Derived from verb root 'lɛpe' + causative suffix '-le'.,,

*/lɛpe/*,verb,"eat",Requires [-ATR] front harmony verb root.,,

*/muna/*,noun,"moon; month",Requires [+ATR] back harmony.,,

*/mekɛ/*,noun,"eye",Requires [-ATR] front harmony.,,

*/ne/*,postposition,"on",[-ATR] front vowel.,,

*/pete-le/*,verb,"catch (a fish); make swim",Requires [+ATR] front harmony verb root.,,Derived from verb root 'pete' (to swim) + causative suffix '-le'.,,The verb root 'pete' is inferred to be polysemous with the noun 'pete' (fish).

*/pete/*,noun,"fish",Requires [+ATR] front harmony.,,

*/pete/*,verb,"swim",Requires [+ATR] front harmony verb root.,,Inferred from the noun 'pete' (fish).

*/pete/*,verb,"speak",Requires [+ATR] front harmony verb root.,,

*/p'aje/*,verb,"give",Requires [-ATR] front harmony verb root. Contains ejective /p/.,,

*/p'a'a/*,noun,"head",Requires [-ATR] back harmony. Contains ejectives /p/ and /t/,, triggering Ejective Displacement when it is the head noun.,,

*/p'usu/*,noun,"mouth",Requires [-ATR] back harmony. Contains ejective /p/,, triggering Ejective Displacement when it is the head noun.,,

*/q'at'a-lo/*,verb,"burn; set on fire",Requires [-ATR] back harmony verb root. Contains ejectives /q/ and /t/.,,Derived from verb root 'q'at'a' (to be on fire) + causative suffix '-lo'.,,

*/q'at'a/*,verb,"be on fire",Requires [-ATR] back harmony verb root. Contains ejectives /q/ and /t/.,,Inferred from the noun 'k'at'a' (fire), with a plausible phonological shift from /k/ to /q/ to distinguish the verb.

*/q'ese/*,adjective,"white",Requires [-ATR] front harmony. Contains ejective /q/,, triggering Ejective Displacement.,,

*/sani/*,adjective,"good",Requires [+ATR] front harmony.,,

*/sola/*,noun,"sun; day",Requires [-ATR] back harmony.,,

*/sot'amo/*,adjective,"visible; seen",Requires [-ATR] back harmony. Contains ejective /t/ from its root, triggering Ejective Displacement.,,Derived from verb root 'sot'a' + stative suffix '-mo'.,,

*/sek'e/*,noun,"leaf",Requires [-ATR] front harmony. Contains ejective /k/,, triggering Ejective Displacement when it is the head noun.,,

*/teli/*,adjective,"cold",Requires [+ATR] front harmony.,,

*/t'aka-mo/*,adjective,"pierced; speared",Requires [-ATR] back harmony. Contains ejective /t/ from its root, triggering Ejective Displacement.,,Derived from verb root 't'aka' (to spear) + stative suffix '-mo'.,,

*/t'aka/*,noun,"spear",Requires [-ATR] back harmony. Contains ejective /t/,, triggering Ejective Displacement when it is the head noun.,,

*/t'aka/*,verb,"spear; pierce",Requires [-ATR] back harmony verb root. Contains ejective /t/.,,Inferred from the noun 't'aka' (spear).

*/t'eselme/*,adjective,"cut; sharp",Requires [-ATR] front harmony. Contains ejective /t/ from its root, triggering Ejective Displacement.,,Derived from verb root 't'ese' (to cut) + causative suffix '-le' + stative suffix '-me'.,,

*/t'ele/*,noun,"foot",Requires [-ATR] front harmony. Contains ejective /t/,, triggering Ejective Displacement when it is the head noun.,,

*/t'ip'a/*,noun,"stone",Requires [-ATR] front harmony. Contains ejectives /t/ and /p/,, triggering Ejective Displacement when it is the head noun.,,

*/wop'a/*,noun,"sky",Requires [-ATR] back harmony. Contains a historical ejective /p/,, and still triggers Ejective Displacement as an irregularity.,,Irregular: Triggers Ejective Displacement despite lacking an overt ejective.

*/wota/*,noun,"cloud",Requires [-ATR] back harmony.,,

*/wola/*,verb,"die",Requires [-ATR] back harmony verb root.,,

*/wolamo/*,adjective,"dead",Requires [-ATR] back harmony.,,Derived from verb root 'wola' + stative suffix '-mo'.,,

*/m'beke/*,noun,"song",Requires [+ATR] front harmony. Contains prenasalized stop /m'b/.,,

*/m'babu/*,adjective,"black",Requires [+ATR] back harmony. Contains prenasalized stop /m'b/.,,

*/ngaja/*,noun,"river",Requires [-ATR] back harmony. Contains a prenasalized stop /ng/.,,Irregular: Contains a prenasalized stop but has [-ATR] vowels.

*/ngino/*,verb,"think",Requires [+ATR] front harmony verb root. Contains prenasalized stop /ng/.,,

*/ngene/*,noun,"path; road",Requires [+ATR] front harmony. Contains prenasalized stop /ng/.,,

*/ndemi/*,verb,"know",Requires [+ATR] front harmony verb root. Contains prenasalized stop /nd/.,,

*/nde/*,adjective,"long",Requires [+ATR] front harmony. Contains prenasalized stop /nd/.,,

*/ndumo/*,noun,"heart",Requires [+ATR] back harmony. Contains prenasalized stop /nd/.,,

haje,interrogative pronoun,"who; what (animate)",Sentence-initial question word.,,

he,particle,"yes/no question marker",Sentence-final particle.,,

hoto,noun,"man",Requires [+ATR] back harmony.,,

huto,noun,"woman",Requires [+ATR] back harmony.,,

he,pronoun,"he; she; it (3rd person singular)",,

heje,pronoun,"they; them (3rd person plural)",Derived from 'he' + pluralizer '-je'.,,

jok'o,noun,"dog",Requires [-ATR] back harmony. Contains ejective /k/,, triggering Ejective Displacement when it is the head noun.,,

jijehe,noun,"bird",Requires [-ATR] front harmony.,,

koke,interrogative adverb,"why",Sentence-initial question word.,,

ko,postposition,"in; at",[-ATR] back vowel.,,

k'a,particle,"negation marker",Post-verbal particle. Forces the verb complex to take [-ATR] harmony. Contains ejective /k/.,,

k'osa,verb,"break",Stative intransitive verb root; requires [-ATR] back harmony. Contains ejective /k/.,,

k'osamo,adjective,"broken",Requires [-ATR] back harmony. Contains ejective /k/ from its root, triggering Ejective Displacement.,,Derived from verb root 'k'osa' + stative suffix '-mo'.,,

Figure 18: Sample language sketch, page 6/7.

le,postposition,"from",[-ATR] front vowel,,

lele,interrogative adverb,"where",Sentence-initial question word,,

me,pronoun,"I; me (1st person singular)",,

meje,pronoun,"we; us (1st person plural)",Derived from 'me' + pluralizer '-je',,

me'dile,noun,"food",Requires [+ATR] front harmony. Contains prenasalized stop /ɗ/,,,

na,conjunction,"and",[-ATR] neutral vowel,,

nama,interrogative pronoun,"what (inanimate)",Sentence-initial question word,,

no-/no-,prefix,"Patientive prefix (Sp/P)",Verbal prefix for patients/stative subjects. Harmonizes for ATR and backness with the verb root.,no- (+ATR), no- (-ATR)

/p'ela/,noun,"rock",Requires [-ATR] front harmony. Contains ejective /p/, triggering Ejective Displacement when it is the head noun.,,

/p'ela/,adjective,"small",Requires [-ATR] front harmony. Contains ejective /p/, triggering Ejective Displacement.,,

p'ot'a,verb,"hit",[-ATR] back harmony verb root. Contains ejective /p/ and /t/,,,

quno,noun,"house",Requires [+ATR] back harmony.,,

quno,verb,"take",[+ATR] back harmony verb root.,,Example of use: to-no-quno. Gloss: AGT-PAT-take. "(He/she) took (it)".

q'ala,adjective,"bad",Requires [-ATR] back harmony. Contains ejective /q/, triggering Ejective Displacement.,,

q'o,particle,"emphatic marker",[-ATR] back vowel. Contains ejective /q/,,,

q'uk'at'a,verb,"crush",[-ATR] back harmony verb root. Contains ejectives /q/, /k/, /t/,,,

se,particle,"irrealis marker",Pre-verbal particle marking future, hypothetical, or potential events. [+ATR] front vowel.,,

sese,interrogative adverb,"when",Sentence-initial question word,,

so,pronoun,"you (2nd person singular)",,

soje,pronoun,"you (2nd person plural)",Derived from 'so' + pluralizer '-je',,

so't'a,verb,"see",[-ATR] back harmony verb root. Contains ejective /t/,,,

to-/tu-,prefix,"Agentive prefix (Sa/A)",Verbal prefix for volitional agents. Harmonizes for ATR and backness with the verb root.,to- (+ATR), tu- (-ATR)

tu,postposition,"to; for",Requires [+ATR] back harmony.,,

t'ese,verb,"cut",[-ATR] front harmony verb root. Contains ejective /t/,,,

t'uha,noun,"chief",Requires [-ATR] back harmony. Contains ejective /t/, triggering Ejective Displacement when it is the head noun.,,

wuwolo,noun,"water",Requires [+ATR] back harmony.,,

weje,noun,"child",Requires [-ATR] front harmony.,,

mbulo,adjective,"big",Requires [+ATR] back harmony. Contains prenasalized stop /ɱb/,,,

ŋgo'mbiso,verb,"gather",Requires [+ATR] back harmony. Contains prenasalized stops /ŋg/ and /ɱb/,,,

ɲdo,particle,"topic marker",Requires [+ATR] back harmony. Contains prenasalized stop /ɲd/,,,

ɲdoku,noun,"stick",Requires [+ATR] back harmony.,,

# Translation

English sentence: "The big dog is sleeping."

Conlang sentence: "no-k'a'da jɔk'o. to-hoto ɱbulo he."

Gloss: "PAT-sleep dog.SG.ABS 3SG.N.ABS-be.STAT big.ADJ PRF"

New words:

"to-": "3rd person singular non-human absolutive prefix"

"hoto": "stative verb 'to be'"

"he": "perfective aspect particle"

New grammar rules:

Rule: "Stative Predication for Adjectives"

Justification: "When an adjective cannot agree in ATR harmony with the noun it modifies, it cannot form a direct noun phrase. Instead, the adjective is predicated of the noun in a separate stative clause using the verb 'hoto' and a resumptive pronoun. This resolves the harmony clash while preserving the meaning, a common strategy in languages with strong vowel harmony."

English sentence: "Where is my book?"

Conlang sentence: "Lele no-kɔpɔ sɔpɔ me"

Gloss: " where PAT-exist book-1SG"

New\_words:

"kɔpɔ": "to be (in a place), exist""hoto": "stative verb 'to be'"

"sɔpɔ": "book"

New grammar rules:

Rule: "Possession is indicated by juxtaposing a pronoun after the noun it possesses (Noun-Pronoun)."

Justification: "The language specification provides a Possessor-Noun structure for nominal possessors (e.g., 'hoto quno' for 'the man's house'), but does not specify how pronominal possession is handled. This new rule establishes a distinct structure for pronouns, which often follow different syntactic rules than full noun phrases. Placing the pronoun post-nominally is a common typological pattern that avoids ambiguity. This Noun-Pronoun order takes precedence over the Ejective Displacement rule, meaning the pronoun always follows the noun it possesses, regardless of ejectives in the noun."

Figure 19: Sample language sketch, page 7/7.