FLASHDLM: ACCELERATING DIFFUSION LANGUAGE MODEL INFERENCE VIA EFFICIENT KV CACHING AND GUIDED DIFFUSION

Anonymous authorsPaper under double-blind review

000

001

002

004

006

008 009 010

011 012 013

014

015

016

017

018

019

021

023

025

026

027

028

029

031

033

034

035

037

038

040

041

042

043

044

046

047

048

051

052

ABSTRACT

Diffusion language models offer parallel token generation and inherent bidirectionality, promising more efficient and powerful sequence modeling compared to autoregressive approaches. However, state-of-the-art diffusion models (e.g., Dream 7B, LLaDA 8B) suffer from slow inference. While they match the quality of similarly sized Autoregressive (AR) Models (e.g., Qwen2.5 7B, Llama3 8B), their iterative denoising requires multiple full-sequence forward passes, resulting in high computational costs and latency, particularly for long input prompts and long-context scenarios. Furthermore, parallel token generation introduces token incoherence problems, and current sampling heuristics suffer from significant quality drops with decreasing denoising steps. We address these limitations with two training-free techniques. First, we propose FreeCache, a Key-Value (KV) approximation caching technique that reuses stable KV projections across denoising steps, effectively reducing the computational cost of DLM inference. Second, we introduce Guided Diffusion, a training-free method that uses a lightweight pretrained autoregressive model to supervise token unmasking, dramatically reducing the total number of denoising iterations without sacrificing quality. We conduct extensive evaluations on open-source reasoning benchmarks, and our combined methods deliver an average of 12.14× end-to-end speedup across various tasks with negligible accuracy degradation. For the first time, diffusion language models achieve a comparable and even faster latency as the widely adopted autoregressive models. Our work successfully paved the way for scaling up the diffusion language model to a broader scope of applications across different domains. Our code and implementation are available at https: //anonymous.4open.science/r/anon-flash-dlm-A42B/.

1 Introduction

Large language model (LLM) Liu et al. (2024a); Bai et al. (2023); Touvron et al. (2023) have shown great success across multiple domains in human life with strong intelligence. In particular, most of the current state-of-the-art (SoTA) LLM models are autoregressive (AR) models with transformer-based architecture Vaswani et al. (2017). However, autoregressive models sequentially generate new tokens at inference time for each decoding step, preserving the logic of semantics (e.g., logic) with the cost of insufficient parallelism and the limitation of mono-direction generation. Diffusion Language Models (DLMs) Ye et al. (2025); Nie et al. (2025); Arriola et al. (2025) have emerged as an appealing alternative. By iteratively denoising a masked sequence in parallel, DLM enables parallel token generation and bidirectional context, which allows all tokens to be generated simultaneously at each step, while keeping the coherence between past and future tokens.

However, DLMs exhibit fundamental challenges that remain under-explored. The comparable quality between the SoTA DLM and AR model comes with the cost of extensive computation latency and insufficient *long-context* ability. These drawbacks largely limit the scalability and practicality of diffusion models, which motivates this work to investigate the following problem:

How to effectively accelerate SoTA DLM while maintaining model performance?

Essentially, the efficiency bottleneck of DLM is caused by the incompatibility with the caching strategy, which has been widely used in auto regressive models (ARM). Recently proposed Block Diffusion Arriola et al. (2025) have shown promising results on diffusion model with Key-Value caching strategy, whereas the overhead of additional fine-tuning and training hinder the fast deployment of DLM. More importantly, the scalability of caching remains questionable against large-sized DLMs (e.g., Dream-7B-Instruct Ye et al. (2025), LLaDA-8B-Instruct Nie et al. (2025))

To address the efficiency challenge of the SoTA DLM models, this work proposes two novel methods: ① FreeCache, a training-free caching strategy that enables diffusion acceleration; ② Guided Diffusion, a training-free technique that guides token unmasking in long-context diffusion generation. Unlike the conventional compression algorithm (e.g., quantization, pruning) that requires a dedicated calibration run, the proposed method directly accelerate the model off the shelf. Specifically, we reveal the fact that the impact of future tokens on earlier positions rapidly diminishes over denoising steps. Therefore, direct caching of the earlier unmasked clean tokens can be considered as a KV state approximation with the result of negligible impact on output quality.

In addition to FreeCache, we introduce guided unmasking assisted by a lightweight autoregressive model. The proposed Guided Diffusion introduces the mechanism of "big diffusion model generation followed by small model unmasking guidance." Our guidance-only approach selects plausible tokens to unmask, minimizing this overhead and preserving the full reasoning power of the DLM. By doing so, the proposed method elegantly combines the advantages of both DLM and autoregressive models. The diffusion process can be easily parallelized, while the autoregressive model is **exempt** from repetitive and expensive speculative correction. Overall, the contributions of this work are:

- **Simplicity.** The proposed method achieves 12.14× and 13.29× speedup on the Dream-7B-Instruct and LLaDA-8B-Instruct models with negligible accuracy drop, respectively. For the first time, the DLM based architecture achieves comparable (even better) generation speed compared to a same-sized AR-based LLM models.
- **Versatility.** The proposed method exhibits strong performance across multiple knowledge domains, including both simple and complex reasoning tasks.
- **Scalability.** With the proposed training-free auto-regressive guidance, our work enables the long-context diffusion (>1024 tokens) **without** hurting the model performance.

Together, these techniques make it feasible to deploy DLMs in long-context and high-throughput applications without compromising quality. Our method retains the desirable properties of parallel generation and bidirectional conditioning of DLMs while overcoming the challenge of key inefficiencies. We demonstrate that diffusion-based language models can achieve competitive inference performance with autoregressive LLM baselines, paving the way for their practical adoption in real-world scenarios.

2 RELATED WORK

2.1 DIFFUSION LANGUAGE MODELS

The emergence of the diffusion language model (DLM) opens up an alternative path for language generation. Recent works like Dream Ye et al. (2025), LLaDA Nie et al. (2025), MDLM Sahoo et al. (2024), and BD3-LM Arriola et al. (2025) adapt diffusion processes to text generation. While promising, these methods are computationally expensive for computation, leading to incompetent latency compared to the conventional AR-based language model despite the high scalability. With some preliminary trials, recent work imposes cached diffusion models Arriola et al. (2025) for accelerated diffusion and reinforcement learning-based reasoning enhancement Zhao et al. (2025). However, the fundamental latency issue still persists, which largely limits the practicality and scalability of DLM. More importantly, diffusion and autoregressive-based language models are not orthogonal. The potential compatibility between DLM and Autoregressive Model is worth further exploration.

2.2 KV CACHING FOR AUTOREGRESSIVE LLM

The overhead of KV Cache has been one of the most critical memory and computation overheads throughout the long-context generation with autoregressive LLM decoding. Compressing the KV cache has been one of the major focuses of efficient LLM research. The emergence of FlashAttention Dao et al. (2022); Dao (2023); Shah et al. (2024) and PageAttention Kwon et al. (2023) aims to alleviate the challenge from the system perspective, leading to a promising performance with high scalability across different LLM architectures. From the perspective of compression algorithms, KV cache eviction Yang et al. (2024); Cai et al. (2024b), quantization Liu et al. (2024c); Hooper et al. (2024), structured pruning Lu et al. (2024); Xu et al. (2025) are proposed to save memory traffic. Due to the irregularity of the diffusion process, the diffusion language model (DLM) requires the full-sized Key and Values for attention computation, where the bottleneck of memory bound largely degrades the latency, limiting the practicality of DLM on a larger scale. A recent study on block diffusion Arriola et al. (2025) proposes the sequential block with intra-block diffusion, whereas the cost of training overhead and under-verified scalability makes the diffusion model questionable for large-scale deployment.

2.3 Speculative Decoding

In addition to the conventional compression algorithms (e.g., pruning and quantization), speculative decoding Leviathan et al. (2023) provides an alternative perspective on accelerating autoregressive LLM decoding without hurting the performance (e.g., accuracy). The lightweight assistant model generates a multi-token "draft", followed by the speculation and correction of the target model. The reliability and acceleration of the speculative decoding system is determined by the matching ratio between the draft model output and target model speculation. In particular, the poor matching ratio between the draft and target model leads to frequent execution of the target model, which eventually deteriorates the system level latency. Recent studies on autoregressive models focus on self-drafting Elhoushi et al. (2024); Liu et al. (2024b), multi-head decoding Cai et al. (2024a), optimized token sampling Chen et al. (2024) and search strategy. Regardless the design of speculative decoding, the speculation and correction of the target model is actively required to ensure the lossless computation. In the meantime, the diffusion model-based big-small model collaboration is largely under investigation. Recent work Christopher et al. (2024) explores speculative decoding with small-scale diffusion models as the drafter, relying on a more competent AR model for output quality and generation, whereas cross-model methods for accelerating large, pre-trained diffusion language models remain under-explored.

3 METHODOLOGY

3.1 PRELIMINARY OF DIFFUSION LANGUAGE MODEL

Diffusion language models (DLMs) generate sequences by iteratively unmasking an initially masked token sequence over T denoising steps. Mathematically, let $\mathbf{x}_T \in \mathbb{N}^L$ be the fully masked input (all positions set to <code>[MASK]</code>), where the still masked position M_t is represented as:

$$M_t = \left\{ i : x_t[i] = [\text{MASK}] \right\} \tag{1}$$

At each iteration t = T, ..., 1, the model f_{θ} produces logits

$$z_t = f_{\theta}(\mathbf{x}_t) \quad \text{for } i \in M_t,$$
 (2)

from which a subset $U_t \subseteq M_t$ of positions is selected (e.g. by confidence scoring) and filled via:

$$\mathbf{x}_{t-1}[i] = \arg\max_{v \in \mathcal{V}} \left[\text{Softmax}(z_t[i]) \right], \quad i \in U_t,$$
(3)

yielding the next mask set $M_{t-1} = M_t \setminus U_t$. By repeating this denoising and unmasking process until $M_0 = \emptyset$, the model produces the final fully unmasked sequence \mathbf{x}_0 .

3.1.1 BOTTLENECK OF DIFFUSION LANGUAGE MODEL INFERENCE

While diffusion models allow parallelized generation of tokens, this comes at the expense of extra computation overhead per forward pass. Given the input x_T with sequence length L, each forward

Module	Operation	Auto-Regressive LM (decode)	
МНА	W_Q, W_K, W_V projections Query × Key (QK^\top) Attention Score × Value	$egin{array}{c} \mathcal{O}(d^2) \ \mathcal{O}(l^2d/h) \ \mathcal{O}(ld/h) \end{array}$	$\mathcal{O}(Ld^2) \ \mathcal{O}(L^2d/h) \ \mathcal{O}(L^2d/h)$
	Output projection (W_{out})	$\mathcal{O}(d^2)$	$\mathcal{O}(Ld^2)$
FFN	W_1 projection W_2 projection	$egin{aligned} \mathcal{O}(d\dot{d}_{ m ff}) \ \mathcal{O}(dd_{ m ff}) \end{aligned}$	$\mathcal{O}(Ldd_{\mathrm{ff}}) \ \mathcal{O}(Ldd_{\mathrm{ff}})$

Table 1: Compute complexity of Transformer modules: AR decodes a prefix of length l per token vs. DLM processes full length L each denoising step.

pass of the diffusion model f_{θ} requires full-sized computation (both current and past tokens) throughout the multi-head attention (MHA) block and feed-forward network (FFN) of the transformer model. Unlike the autoregressive model where the past tokens are cached for the new token generation, diffusion model produces output without the consideration of causality. As shown in Table 1, DLM models introduce an additional computational complexity of O(L) at each module of a transformer-based model architecture. As a result, the latency overhead introduced by the DLM architecture is massive compared to the Auto-Regressive Model, as shown in the comparison in Section 4. Based on the theoretical analysis above, the first challenge of the diffusion model is:

Challenge(1): How to alleviate the latency and computation overhead caused by the liability of full sized cache computation of DLM?

3.1.2 TOKEN INCOHERENCE IN PARALLEL GENERATION

As introduced in Section 3.1, DLM irregularly unmasks output token positions throughout diffusion process. As a result, simultaneously unmasking token positions without semantical correlation leads to insufficient semantical consistency, which can further degrades the model performance. While the desire of preserving the parallel diffusion persists. Figure 1a shows accuracy degradation with decreasing denoising steps for three diffusion sampling methods: MaskGIT Chang et al. (2022), entropy-based, and Top-K Margin Kim et al. (2025). The challenge arises as follows:

Challenge *(2) How to enhance the semantic correlation of the diffusion process without introducing additional training and fine-tuning effort?*


Motivated by the aforementioned challenges, we propose a novel approach which directly accelerates the diffusion model in a simple, effective, and systematic manner.


3.2 Proposed Method

3.2.1 FreeCache: Reducing Window Caching for DLM Inference

A key insight for optimizing the generation process in Diffusion Language Models is that the Key and Value (KV) projections for the clean portions of a sequence exhibit high temporal stability. Although these projections are not strictly unchanging, they quickly converge and undergo only negligible changes once a token is finalized.

Figure 2 shows a heatmap that validates the rationale behind our FreeCache method: the temporal stability of KV projections for clean tokens. The y-axis represents the denoising step and the x-axis represents the token position, while the color intensity shows the similarity of a token's value projection to its previous step. Bright yellow indicates high similarity (minimal change), while dark blue signifies a large difference. We observed that the prompt region remains stable across denoising steps, and the generation region illustrates how tokens transition from a low-similarity, unstable state (dark blue) to a high-similarity, stable state (bright yellow) as they become unmasked.





- (a) Quality degradation from aggressive unmasking. (b) Latency-accuracy tradeoff. Pareto front com-Heuristic methods suffer from significant accuracy loss with decreasing denoising steps.
 - paring the standard autoregressive baseline with our KV-cache optimized method, highlighting substantial latency reductions at equivalent accuracy levels.

Figure 1: (a) Quality degradation under aggressive unmasking. (b) Pareto front of accuracy vs. latency (log-scale) for baseline and optimized cached methods.




Figure 2: Rationale behind the proposed FreeCache: The variation of K and V projections of clean tokens is small throughout the subsequent diffusion steps.

To exploit this, we propose FreeCache, a reducing window caching strategy where the set of actively computed tokens dynamically shrinks as blocks of the sequence are finalized. The algorithm proceeds as follows: Initialization and Partitioning: The post-prompt generation sequence is partitioned into fixed-size blocks $(B_1, ..., B_N)$, and an initial forward pass computes and saves the full KV projections for the entire sequence (prompt + all blocks). Windowed Re-computation: To generate a block B_i , the active computation window is defined as B_i and all subsequent blocks $(B_{i+1},...,B_N)$. KV projections are recomputed only for tokens within this window until B_i is fully unmasked, using all prior frozen blocks and the prompt as context. Progressive Caching: Upon completion of a block B_i , its KV projections are **frozen** for subsequent steps. The active window then shrinks to exclude this block for all subsequent generation steps.

This cascaded approach means that the computational cost per step progressively decreases throughout the inference process, as the active window shrinks with each completed block. This effectively reduces the overall computational overhead, especially for long sequences.


We quantify the performance degradation caused by the FreeCache in Figure 1b with the 8-shot GSM8K dataset. The reducing window caching strategy introduces up to $5\times$ speedup compared to the vanilla Dream-7B, while preserving the minimal accuracy drop. As shown in Table 2, the proposed FreeCache achieves up to 4.42× speedup for Dream-7B-Instruct and 6.32× for LLaDA-8B-Instruct,

Models	Method	GSM8K (8-shot) Accuracy (%)	Raw Latency (s)	Speedup
Dream-7B-Instruct Ye et al. (2025)	Baseline	79.68	48.05	1.0 ×
2020)	FreeCache (This work)	77.40	10.87	4.42×
LLaDA-8B-Instruct Nie et al. (2025)	Baseline	79.30	56.89	1.0 ×
EDADIT OD Instruct (100 et al. (2023)	FreeCache (This work)	77.18	9.02	6.32×

while maintaining accuracy close to the baseline. We solidify the performance of the proposed method in Section 4 with further analysis with benchmarks across different domains.

3.2.2 GUIDING DIFFUSION WITH LIGHTWEIGHT AUTOREGRESSIVE MODEL

To address this token incoherence challenge (Challenge ②) from Section 3.1.2 and fully exploit the parallelism of diffusion process, we propose Guided Diffusion.



Guided Sequence: Only unmask the matched tokens for the next step of diffusion

Figure 3: AR-guided Diffusion Model. The diffusion model performs a one-step diffusion process, followed by a one-time forward pass of the AR guider. The matched tokens are unmasked for the next step of diffusion.

Specifically, we leverage the diffusion model as the "drafter" model by first unmasking **all** the tokens with one step. The masked tokens predicted by the diffusion model are only unmasked when they are consistent with the predictions from the autoregressive LM model, as shown in Figure 3. For the scenario when the matching ratio between the diffusion drafter and auto-regressive model is zero, the guided diffusion will only accept the one free tokens from the AR model output.

This cross-model agreement serves as a lightweight coherence prior, enabling the model to safely unmask multiple tokens in parallel, without requiring any additional training or fine-tuning.

Guided diffusion performs iterative unmasking by coordinating predictions from a diffusion language model (DLM) and a frozen autoregressive model (ARM). At each denoising step, instead of relying on heuristic confidence thresholds, it uses agreement between the two models to decide how many tokens to safely unmask.

Formally, let $x_T \in \mathbb{N}^L$ be the current sequence containing masked and unmasked tokens. The diffusion model f_{θ} predicts logits over vocabulary tokens at all masked positions, from which we take the Top-1 predictions:

 $t^{\text{DLM}} = \operatorname{argmax}(\operatorname{Softmax}(f_{\theta}(x))).$

These proposed tokens are fed to the ARM g_{ϕ} , which produces a second set of logits:

$$t^{\text{ARM}} = \operatorname{argmax}(\operatorname{Softmax}(g_{\phi}(t^{\text{DLM}}))).$$

Let $M=[i_1,\ldots,i_m]\subseteq\{1,\ldots,L\}$ denote the current masked positions in x. We compute the largest prefix length k such that

$$t_{i_j}^{\text{DLM}} = t_{i_j}^{\text{ARM}}$$
 for all $j \leq k$.

If k > 0, we unmask positions i_1, \ldots, i_k using the DLM proposals. If no agreement is found, we conservatively unmask only the first token i_1 . This process is repeated until all tokens are unmasked.

This decoding strategy allows the model to adaptively control the amount of parallel unmasking based on model confidence and alignment, enabling efficient generation without compromising output quality. We present the details of the proposed method in Algorithm 1.

We would like to highlight that the proposed Guided Diffusion properly combines the advantages of **both** diffusion model and auto-regressive model. For each guiding step, **both** one-time diffusion process from the drafter and the one-time forward pass of the auto-regressive model are fast, while the guidance from the auto-regressive model facilitates the coherence of the diffused output tokens with improved semantical logic.

Guided Diffusion vs. Speculative Decoding. Unlike speculative decoding, Guided Diffusion does not require token-wise correction from the auto-regressive model. In other words, the proposed method produces output sequence without introducing the repetitive correction process, which guarantees the latency benefits obtained from the fast diffusion process. Speculative decoding uses a small AR model for autoregressive drafting, followed by the big model correction. On the contrary, the proposed guided diffusion flips the paradigm by maximizing the drafting efficiency of the big diffusion model. To that end, the reasoning power of the diffusion model is fully preserved, while the AR guider model simply ensures the causality of the output.

Algorithm 1 Guided Diffusion

```
Input: masked sequence x, DLM f_{\theta}, AR q_{\phi}
Output: fully unmasked x
while \exists i : x[i] = mask
                                                          // loop until all unmasked do
   logits_{DLM} \leftarrow softmax(f_{\theta}(x))
                                                          // DLM predicts masked tokens
     tok_{DLM} \leftarrow \arg\max logits_{DLM}
                                                                           // DLM predictions
                                                               // AR processes DLM output
     logits_{AR} \leftarrow softmax(g_{\phi}(tok_{DLM}))
     tok_{AR} \leftarrow \arg\max logits_{AR}
                                                                             // AR predictions
     Let M = [i_1, \dots, i_m] be masked indices
                                                             // remaining mask positions
     k \leftarrow \text{size}(\{\text{tok}_{\text{DLM}} = \text{tok}_{\text{AR}}\})
                                                                                // find matches
   if k > 0
                                                                         // models agree then
       Unmask i_1:i_k with tok<sub>DLM</sub>[i_1:i_k]
                                                                      // accept matching run
       Unmask i_1 with tok<sub>DLM</sub>[i_1]
                                                                 // fallback: accept first
```

4 EXPERIMENTS

We evaluated the proposed method against a wide range of benchmarks across different types of tasks. Due to the limited option of DLM models with multi-billion parameters, we choose Dream-Instruct-7B Ye et al. (2025) as the selected SoTA model to validate the proposed method. To fully solidify the effectiveness of our work, both question-answer (QA) and reasoning tasks are solved via multi-sentence and multi-step text-based diffusion, instead of directly outputting the final answer. The detailed experimental setup and data pre-processing are summarized in the supplementary.

Metrics and Baselines. The performance of the proposed method and other baselines are evaluated based on accuracy and wall clock latency for solving each problem. We first compare the performance

Table 3: Outstanding acceleration achieved by the proposed methods with negligible accuracy drop on Dream-7B-Instruct Ye et al. (2025). The latency value represents the end-to-end problem solving time per problem.

		Vanilla DLM	Dr	eam-Instruct-7B with Guided Diffe	usion (This Work)
		Baseline Dream-Instruct-7B	FreeCache Only	FreeCache + QWen-1.5B-Instruct	FreeCache + QWen-7B-Instruct
	Acc. (%)	46.92	45.18	46.64	48.20
MMLU-PRO	Latency (s)	20.73	6.68	1.66	2.77
	Speedup (s)	1×	3.11×	12.48×	7.48 ×
	Acc. (%)	79.68	77.40	80.33	81.41
GSM8K (8-shot)	Latency (s)	48.05	10.87	2.70	2.74
	Speedup	1×	4.42×	17.80×	17.53×
	Acc. (%)	85.56	84.83	85.15	85.85
PiQA	Latency (s)	14.62	4.21	0.43	1.05
	Speedup	1×	3.47×	34.1×	13.92×
	Acc. (%)	80.87	80.61	80.89	80.72
ARC-C	Latency (s)	10.64	4.25	3.12	4.58
	Speedup	1×	2.50×	3.41×	2.32×
	Acc. (%)	87.53	86.24	87.50	87.44
ARC-E	Latency (s)	10.59	5.54	3.25	5.03
	Speedup	1×	1.91×	3.26×	2.11×
	Acc. (%)	39.29	43.30	49.55	49.33
GPQA	Latency (s)	21.50	9.91	12.02	15.26
	Speedup	1×	2.12×	1.78×	1.41×

of the proposed method against the vanilla Dream model Ye et al. (2025). On top of that, we evaluate the proposed method with the comparison of the mainstream auto-regressive models.

Experimental Setup. The models are deployed on a single NVIDIA RTX 6000 Ada GPU (48GB). The latency is measured directly via torch.cuda. Event across each benchmark dataset.

Long-context Diffusion. For all the tasks, we intentionally encourage the model to generate the complete reasoning process, followed by the indication of the final answer. We would like to highlight the long context response is critical for problem solving and question-answering due to the widely adopted reasoning-based response in the SoTA LLM models. For all the selected reasoning, math problems, and question-answering, we set the max_new_tokens to 1024. The final answers are extracted after the dedicated prompt trigger.

4.1 COMPARISON WITH THE BASELINE DIFFUSION LANGUAGE MODEL

Compared to the vanilla Dream-7B-Instruct model, the proposed method achieves consistent and outstanding speedup across all the tasks from different domains. For the complex reasoning tasks (e.g., MMLU-PRO, GPQA), the proposed <code>FreeCache</code> first induces $3.11\times$ speedup with minimal quality degradation. Rewarded by the guided diffusion method, the overall system can achieve an average of $12.48\times$ speedup with negligible accuracy degradation. For the tasks with long-context input prompt (e.g., GSM8K with 8-shot), the proposed method accelerates the diffusion process with $34.1\times$ end-to-end average speedup on all the math problems, as presented in Table 3.

With guided unmasking, the diffusion model exhibits stronger reasoning power with recovered accuracy. More importantly, the existence of the lightweight autoregressive model recovers the accuracy degradation caused by the approximated cache, even with the long-context generation (e.g., 1024 tokens). As introduced in Section 1, the guided diffusion process exclude the "correction" step. As a result, increasing the size of the guider model (e.g., from 1.5B to 7B) only leads to marginal accuracy improvements, with the cost of minimal latency overhead.

Empowered by Guided Diffusion, diffusion model is compatible with different variants of the AR model guider in different domains of knowledge. By employing a dedicated auto-regressive LLM for math (e.g., Qwen-2.5-Math-1.5B), the performance of the Dream-Instruct-7B model can be further facilitated with better reasoning ability on the GSM8K dataset. In addition to the experimental results in Table 3, we present the evaluation results with other benchmarks in the supplementary.

The strong speedup achieved by the proposed method allows us to compare the diffusion model against the conventional autoregressive LLM models.

Table 4 shows the comparison between Guided Diffusion and vanilla Auto-regressive on the GSM8K dataset with the standard 8-shot chain-of-thought prompt. Crucially, the quality of generation is governed by the DLM's reasoning capacity. This ensures that accuracy is maintained regardless of guider competence, with latency remaining on par with autoregressive models. Admittedly, Dream-7B-Instruct and LLaDA-8B currently exhibit weaker reasoning ability compared to some state-of-the-art autoregressive models of similar size (e.g., Qwen2.5-7B-Instruct). Nevertheless, Guided Diffusion provides significant acceleration, and as future work continues to enhance the reasoning ability of diffusion models, its benefits are expected to become even more pronounced.

Table 4: Comprehensive performance comparison on the GSM8K dataset, showing both standard autoregressive (AR) and AR-guided results for various models.

Models / Guiders	Stand-alone AR LLM		Guided Diffusion (w/ Dream-7B-Instruct)		Guided Diffusion (w/ LLaDA-8B-Instruct)	
	Accuracy (%)	Latency (s)	Accuracy (%)	Latency (s)	Accuracy (%)	Latency (s)
Qwen2.5-1.5B-Instruct	68.54	2.26	80.3	2.55	79.91	4.29
Qwen2.5-Math-1.5B-Instruct	78.24	1.59	82.9	3.19	81.96	5.31
Qwen2.5-7B-Instruct	91.13	3.23	82.3	3.43	79.68	4.42

4.3 MODEL GPU MEMORY USAGE

Table 9 and Table 10 show the GPU memory usage (in Gigabytes) of the proposed method with LLaDA-8B-Instruct and Dream-7B-Instruct as diffusion models, respectively. The GPU memory is recorded directly via torch.cuda.max_memory_allocated(). As shown in the tables, the proposed guided unmasking scheme introduces minimal memory overhead compared to the combined memory consumption of the single auto-regressive and baseline diffusion models.

Table 5: LLaDA-8B-Instruct Guided Diffusion Memory Usage (GB).

Table 6: Dream-Instruct-7B Guided Diffusion
Memory Usage (GB).

ŀ	b	ì	2	
ļ	6	ò	3	
ļ	6)	4	

AR Guider	DLM (GB)	Guide (GB)	Total (GB)
Qwen2.5-1.5B-Instruct	20.7	4.1	24.8
Qwen2.5-7B-Instruct		17.3	38.0

AR Guider	DLM	Guide	Total
	(GB)	(GB)	(GB)
Qwen2.5-1.5B-Instruct	14.6	4.1	18.7
Qwen2.5-7B-Instruct		17.3	31.9

5 CONCLUSION AND DISCUSSION

This paper presents a novel method designed for diffusion language models. The proposed FreeCache enables training-free caching with an off-the-shelf diffusion model. On top of that, Guided Diffusion facilitates the quality of diffusion by guiding the direct diffusion process with outstanding speedup. Different from prior works that relies on training or additional finetuning effort, the proposed method enables the end-to-end speedup by using the off-the-shelf diffusion model only. Compared to the baseline diffusion language models, the proposed method achieves an average of $12.14 \times$ speedup across different reasoning tasks with negligible accuracy degradation. More importantly, for the first time, our method enables diffusion model to achieve the comparable performance compared to the autoregressive language models while maintaining the similar accuracy.

REFERENCES

Marianne Arriola, Subham Sekhar Sahoo, Aaron Gokaslan, Zhihan Yang, Zhixuan Qi, Jiaqi Han, Justin T Chiu, and Volodymyr Kuleshov. Block diffusion: Interpolating between autoregressive and diffusion language models. In *The Thirteenth International Conference on Learning Representations (ICLR)*, 2025.

Jinze Bai, Shuai Bai, Yunfei Chu, Zeyu Cui, Kai Dang, Xiaodong Deng, Yang Fan, Wenbin Ge, Yu Han, Fei Huang, et al. Qwen technical report. *arXiv preprint arXiv:2309.16609*, 2023.

Tianle Cai, Yuhong Li, Zhengyang Geng, Hongwu Peng, Jason D Lee, Deming Chen, and Tri Dao. Medusa: Simple llm inference acceleration framework with multiple decoding heads. In *International Conference on Machine Learning (ICML)*. PMLR, 2024a.

- Zefan Cai, Yichi Zhang, Bofei Gao, Yuliang Liu, Tianyu Liu, Keming Lu, Wayne Xiong, Yue Dong, Baobao Chang, Junjie Hu, et al. Pyramidky: Dynamic ky cache compression based on pyramidal information funneling. *arXiv preprint arXiv:2406.02069*, 2024b.
- Huiwen Chang, Han Zhang, Lu Jiang, Ce Liu, and William T. Freeman. Maskgit: Masked generative image transformer, 2022. URL https://arxiv.org/abs/2202.04200.
- Zhuoming Chen, Avner May, Ruslan Svirschevski, Yuhsun Huang, Max Ryabinin, Zhihao Jia, and Beidi Chen. Sequoia: Scalable, robust, and hardware-aware speculative decoding. *CoRR*, 2024.
- Jacob K Christopher, Brian R Bartoldson, Tal Ben-Nun, Michael Cardei, Bhavya Kailkhura, and Ferdinando Fioretto. Speculative diffusion decoding: Accelerating language generation through diffusion. *arXiv preprint arXiv:2408.05636*, 2024.
- Tri Dao. Flashattention-2: Faster attention with better parallelism and work partitioning. *arXiv* preprint arXiv:2307.08691, 2023.
- Tri Dao, Dan Fu, Stefano Ermon, Atri Rudra, and Christopher Ré. Flashattention: Fast and memory-efficient exact attention with io-awareness. *Advances in neural information processing systems* (*NeurIPS*), 2022.
- Mostafa Elhoushi, Akshat Shrivastava, Diana Liskovich, Basil Hosmer, Bram Wasti, Liangzhen Lai, Anas Mahmoud, Bilge Acun, Saurabh Agarwal, Ahmed Roman, et al. Layerskip: Enabling early exit inference and self-speculative decoding. *arXiv preprint arXiv:2404.16710*, 2024.
- Coleman Hooper, Sehoon Kim, Hiva Mohammadzadeh, Michael W Mahoney, Sophia Shao, Kurt Keutzer, and Amir Gholami. Kvquant: Towards 10 million context length llm inference with kv cache quantization. *Advances in Neural Information Processing Systems (NeurIPS)*, 2024.
- Jaeyeon Kim, Kulin Shah, Vasilis Kontonis, Sham Kakade, and Sitan Chen. Train for the worst, plan for the best: Understanding token ordering in masked diffusions, 2025. URL https://arxiv.org/abs/2502.06768.
- Woosuk Kwon, Zhuohan Li, Siyuan Zhuang, Ying Sheng, Lianmin Zheng, Cody Hao Yu, Joseph Gonzalez, Hao Zhang, and Ion Stoica. Efficient memory management for large language model serving with pagedattention. In *Proceedings of the 29th Symposium on Operating Systems Principles*, 2023.
- Yaniv Leviathan, Matan Kalman, and Yossi Matias. Fast inference from transformers via speculative decoding. In *International Conference on Machine Learning (ICML)*, 2023.
- Aixin Liu, Bei Feng, Bing Xue, Bingxuan Wang, Bochao Wu, Chengda Lu, Chenggang Zhao, Chengqi Deng, Chenyu Zhang, Chong Ruan, et al. Deepseek-v3 technical report. *arXiv preprint arXiv:2412.19437*, 2024a.
- Fangcheng Liu, Yehui Tang, Zhenhua Liu, Yunsheng Ni, Duyu Tang, Kai Han, and Yunhe Wang. Kangaroo: Lossless self-speculative decoding for accelerating LLMs via double early exiting. In *The Thirty-eighth Annual Conference on Neural Information Processing Systems (NeurIPS)*, 2024b.
- Zirui Liu, Jiayi Yuan, Hongye Jin, Shaochen Zhong, Zhaozhuo Xu, Vladimir Braverman, Beidi Chen, and Xia Hu. Kivi: A tuning-free asymmetric 2bit quantization for kv cache. *arXiv preprint arXiv:2402.02750*, 2024c.
- Xudong Lu, Qi Liu, Yuhui Xu, Aojun Zhou, Siyuan Huang, Bo Zhang, Junchi Yan, and Hongsheng Li. Not all experts are equal: Efficient expert pruning and skipping for mixture-of-experts large language models. *arXiv preprint arXiv:2402.14800*, 2024.

Shen Nie, Fengqi Zhu, Zebin You, Xiaolu Zhang, Jingyang Ou, Jun Hu, JUN ZHOU, Yankai Lin, Ji-Rong Wen, and Chongxuan Li. Large language diffusion models. In *ICLR 2025 Workshop on Deep Generative Model in Machine Learning: Theory, Principle and Efficacy*, 2025.

- Subham Sekhar Sahoo, Marianne Arriola, Aaron Gokaslan, Edgar Mariano Marroquin, Alexander M Rush, Yair Schiff, Justin T Chiu, and Volodymyr Kuleshov. Simple and effective masked diffusion language models. In *The Thirty-eighth Annual Conference on Neural Information Processing Systems*, 2024. URL https://openreview.net/forum?id=L4uaAR4ArM.
- Jay Shah, Ganesh Bikshandi, Ying Zhang, Vijay Thakkar, Pradeep Ramani, and Tri Dao. Flashattention-3: Fast and accurate attention with asynchrony and low-precision. Advances in Neural Information Processing Systems (NeurIPS), 2024.
- Hugo Touvron, Thibaut Lavril, Gautier Izacard, Xavier Martinet, Marie-Anne Lachaux, Timothée Lacroix, Baptiste Rozière, Naman Goyal, Eric Hambro, Faisal Azhar, et al. Llama: Open and efficient foundation language models. *arXiv preprint arXiv:2302.13971*, 2023.
- Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Łukasz Kaiser, and Illia Polosukhin. Attention is all you need. *Advances in neural information processing systems (NeurIPS)*, 2017.
- Yuhui Xu, Zhanming Jie, Hanze Dong, Lei Wang, Xudong Lu, Aojun Zhou, Amrita Saha, Caiming Xiong, and Doyen Sahoo. Think: Thinner key cache by query-driven pruning. In *The Thirteenth International Conference on Learning Representations (ICLR)*, 2025.
- Dongjie Yang, XiaoDong Han, Yan Gao, Yao Hu, Shilin Zhang, and Hai Zhao. Pyramidinfer: Pyramid kv cache compression for high-throughput llm inference. *arXiv preprint arXiv:2405.12532*, 2024.
- Jiacheng Ye, Zhihui Xie, Lin Zheng, Jiahui Gao, Zirui Wu, Xin Jiang, Zhenguo Li, and Lingpeng Kong. Dream 7b, 2025. URL https://hkunlp.github.io/blog/2025/dream.
- Siyan Zhao, Devaansh Gupta, Qinqing Zheng, and Aditya Grover. d1: Scaling reasoning in diffusion large language models via reinforcement learning. *arXiv preprint arXiv:2504.12216*, 2025.

A LLM USAGE

We used large language models, specifically ChatGPT (GPT-4, OpenAI) and Gemini (Google), in limited ways during this work. First, we used them to improve grammar, phrasing, and clarity of exposition, but not to generate substantive technical content. Second, we occasionally consulted them to help identify potentially relevant related work, while ensuring that all citations were independently checked and verified by the authors. Third, we used them at early stages as brainstorming aids to generate alternative perspectives or potential problem framings. All research directions, methods, and experiments were conceived, designed, and validated by the authors. All outputs from large language models were critically evaluated before inclusion, and the intellectual contributions of the paper are entirely the authors' own.

B SUPPLEMENTARY MATERIAL

B.1 CODE & DATA RELEASE PLAN

The implementation of our methods are available at https://anonymous.4open.science/r/anon-flash-dlm-A42B/.

C ADDITIONAL EXPERIMENTAL RESULTS

C.1 ADDITIONAL EXPERIMENTAL RESULTS OF LLADA-8B-INSTRUCT

Besides the comprehensive evaluation with the SoTA Dream-v0-Instruct-7B diffusion model, we further validate the effectiveness of the proposed method with LLaDA-8B-Instruct Nie et al. (2025). As presented in Table 7, the proposed FreeCache and guided unmasking have demonstrated the consistent speedup on the GSM8K dataset with 8-shot chain-of-thought (CoT).

The baseline LLaDA-8B-Instruct Nie et al. (2025) can optionally support semi-autoregressive unmasking by dividing the sequence into several blocks and unmasking them from left to right. The user-defined hyperparameter block length defines the size of the block Nie et al. (2025). However, this does not make the generation autoregressive, and the model still processes the full sequence length at each denoising step.

In our proposed guided diffusion method, block length is not used or needed since the diffusion model generates all draft tokens at each step, while the AR model is used to guide the unmasking process. In other words, the "effective block length" of the guided unmasking is the length of all the diffused draft tokens at each step of drafting.

C.2 ADDITIONAL EXPERIMENTAL RESULTS ON DREAM-v0-INSTRUCT-7B

In addition to the benchmarks reported in Table 3, Table 8 shows HellaSwag (5-shot) results for Dream-v0-Instruct-7B with FreeCache and guided diffusion, highlighting substantial speedup and accuracy gains over the baseline.

Table 8: HellaSwag accuracy, latency, and speedup relative to the Dream-v0-Instruct-7B Baseline.

Model / Variant	Accuracy (%)	Latency (s)	Speedup
Baseline	73.30	21.99	$1.00 \times$
FreeCache + Qwen2.5-1.5B-Instruct Guided (This work)	76.63	2.46	8.94 ×
FreeCache + Qwen2.5-7B-Instruct Guided (This work)	76.84	3.31	6.64 ×

C.3 MODEL GPU MEMORY USAGE

Table 9 and Table 10 show the GPU memory usage (in gigabytes) of the proposed method with LLaDA-8B-Instruct and Dream-v0-Instruct-7B as diffusion models, respectively. The GPU memory is recorded directly via torch.cuda.max_memory_allocated(). As shown in the tables, the

Table 7: GSM8K (8-shot) accuracy, latency, and speedup for LLaDA-8B-Instruct with block sizes 32 and 64 and guided diffusion with Qwen2.5-Instruct models. Speedups are relative to the corresponding LLaDA baseline latency.

Model / Setting	Details	Accuracy (%)	Latency (s)	Speedup
	LLaDA I	Baselines		
Block Length = 32				
Baseline		81.52	57.02	$1.00 \times$
FreeCache (This work)		79.76	9.20	6.20 ×
Block Length = 64				
Baseline		79.30	56.89	$1.00 \times$
FreeCache (This work)		77.18	9.02	6.32 ×
Guided Diff	fusion (Qwen2.5	-Instruct) with Fr	eeCache	
Qwen2.5-1.5B-Instruct	Top-1 Match	79.91	4.29	13.29 ×
Qwen2.5-3B-Instruct	Top-1 Match	79.53	5.16	$11.05 \times$
Qwen2.5-7B-Instruct	Top-1 Match	79.30	5.21	$10.94 \times$
Qwen2.5-1.5B-Instruct	Top-2 Match	78.85	4.40	12.96 ×
Qwen2.5-3B-Instruct	Top-2 Match	79.75	4.40	12.96 ×
Qwen2.5-7B-Instruct	Top-2 Match	79.68	4.50	12.67 ×
Qwen2.5-1.5B-Instruct	Top-5 Match	79.91	3.80	15.01 ×
Qwen2.5-3B-Instruct	Top-5 Match	80.06	4.29	13.29 ×
Qwen2.5-7B-Instruct	Top-5 Match	79.76	4.42	12.90 ×

proposed guided unmasking scheme introduces minimal memory overhead compared to the combined memory consumption of the single auto-regressive and baseline diffusion models.

Table 9: LLaDA-8B-Instruct Guided Diffusion Memory Usage (GB)

Table 10: Dream-v0-Instruct-7B Guided Diffusion Memory Usage (GB)

AR Guider	Diff. (GB)	Guide (GB)	Total (GB)	AR Guider	Diff. (GB)	Guide (GB)	Total (GB)
Qwen2.5-0.5B		1.9	22.6	Qwen2.5-0.5B		1.9	16.5
Qwen2.5-1.5B Qwen2.5-3B	20.7	4.1 6.7	24.8 27.4	Qwen2.5-1.5B Qwen2.5-3B	14.6	4.1 6.7	18.7 21.3
Qwen2.5-7B		17.3	38.0	Qwen2.5-7B		17.3	31.9

C.4 IMPLEMENTATION DETAILS

The proposed method directly employs the off-the-shelf diffusion and auto-regressive large language models (for guided masking) from HuggingFace. The proposed method uses the same set of configurations for all tasks. We believe a more fine-grained hyper-parameter setting can lead to improved performance, but we keep a single set of configurations to demonstrate the generality and practicality. Table 11 shows the detailed experimental configuration of the proposed method with Dream-v0-Instruct-7B Ye et al. (2025) and LLaDA-8B-Instruct Nie et al. (2025).

Stochastic Guided Unmasking. Please note that during guided unmasking, we only consider the Top-K logits of the AR-guider model as the guidance logits \log_a . In addition to the deterministic guidance strategy (Algorithm 1 and Algorithm 2), if the maximum token logit of the diffusion output (of each token) is greater $\tau \times \max(\log_a)$, the token will be unmasked. Otherwise, it will remain silent, where τ is the Guidance Confidence Threshold (default = 0.5).

C.5 PROMPT TEMPLATES

Prompt Configuration for Question Answering and Reasoning. We would like to highlight that our evaluation protocol encourages the diffusion model to generate the output tokens with the sense

Table 11: Diffusion configuration of the Dream-v0-Instruct-7B Ye et al. (2025) and LLaDA-8B-Instruct Nie et al. (2025) employed in this work.

Setting	Dream-v0-Instruct-7B Ye et al. (2025)	LLaDA-8B-Instruct Nie et al. (2025)
	Configuration of FreeCache (This wor	k)
Block Cache Size	256	256
Max Output Tokens	256	256
Block Length Nie et al. (2025)	-	64
Configur	ration of FreeCache + Guided Unmasking	g (This work)
Max Output Tokens	1024	1024
Speculation Block Size	32	32
Top-K Assisted Tokens Selection	2	2
Guidance Confidence Threshold τ	0.5	0.5

of reasoning for **both** math solving and basic common QA tasks (e.g., PiQA). As a result, the model achieves higher accuracy compared to the reported performance in Ye et al. (2025). To solidify the fact that we are not heavily relying on prompt engineering, we release the prompt templates as follows:

ARC (-C/E):

You are a careful reasoning assistant. A commonsense sentence is shown with a blank and **four** Answers that could fill the blank. Think step by step about which option makes the sentence most sensible, then decide.

Sentence: <sentence>

What you should do:

- 1. Briefly explain your reasoning.
- 2. On a **new line**, write exactly: "The final answer is [answer]" where **[answer]** is either **Answer1**, **Answer2**, **Answer3**, or **Answer4**. Do **not** output anything after that line.

GPQA:

You are a careful reasoning assistant. A question is shown with **four** possible answers. Think step by step about which option is correct, then decide.

Question: <question>

In your response:

- 1. First reason and explain your reasoning briefly before providing the final answer to the question.
- 2. Then at the end of your explanation, on a **new line**, write exactly: "The final answer is [answer]" where **[answer]** is one of **Answer1**, **Answer2**, **Answer3**, or **Answer4**. Do **not** output anything after that line.

GSM8K:

Given the following problem, reason and give a final answer to the problem.

Problem:

Your response should end with "The final answer is [answer]" where [answer] is just the final number to the problem.

HellaSwag:

You are a careful reasoning assistant. A commonsense sentence is shown with a blank and **four** Endings that could fill the blank. Think step by step about which option makes the sentence most sensible, then decide.

Sentence: <sentence>

In your response:

- 1. First reason and explain your reasoning briefly before answering this question.
- 2. Then at the end of your explanation, on a **new line**, write exactly: "The final answer is [answer]" where **[answer]** is either **Ending1**, **Ending2**, **Ending3**, or **Ending4**. Do **not** output anything after that line.

PIQA:

Below is an instruction that describes a task. Write a response that appropriately completes the request.

Instruction: <instruction>

Your response should end with "The final answer is [answer]" where [answer] is the response to the problem.

MMLU-PRO:

The following are multiple choice questions (with answers) about a subject. Think step by step and then finish your answer with "the answer is (X)" where X is the correct letter choice.

The prompt of MMLU-PRO is adopted from the official repository of MMLU-PRO benchmark.