Improving Retrieval Augmented Open-Domain Question-Answering with Vectorized Contexts

Anonymous ACL submission

Abstract

In the era of large language models, applying techniques such as Retrieval Augmented Generation can better address Open-Domain Question-Answering problems. Due to constraints including model sizes and computing resources, the length of context is often limited, and it becomes challenging to empower the model to cover overlong contexts while answering questions from open domains. This paper proposes a general and convenient method to cover longer contexts in Open-Domain Question-Answering tasks. It leverages a small encoder and cross-attention mechanism and effectively encodes contexts. With our method, the original language models can cover several times longer contexts while keeping the computing requirements close to the baseline. Our experiments demonstrate that after fine-tuning, there is improved performance across two held-in datasets, four heldout datasets, and also in two In Context Learning settings. Our code will be released at url.

1 Introduction

004

014

016

017

034

040

Transformer-based (Vaswani et al., 2017) architectures with pre-training on large corpus have become popular in recent Natural Language Processing research (Brown et al., 2020; Workshop et al., 2022; Chowdhery et al., 2023). An increasing number of Natural Language Processing (NLP) tasks need to process long contexts such as Open-Domain Question Answering (ODQA) with Retrieval Augmented Generation (RAG) (Lewis et al., 2020; Izacard and Grave, 2020; Gu et al., 2018). However, the fine-tuning and inference stages in downstream tasks are still constrained by the input length, e.g., 2048 tokens for Bloomz (Muennighoff et al., 2022) and Llama-1 (Touvron et al., 2023).

With RAG, the input can easily surpass the maximum length the model can handle and it becomes challenging for the model to perform both finetuning and inference on overlong contexts. More-



Figure 1: A comparison of our method (lower) and retrieval augmented ODQA without vectorization (upper). In the upper part, limited retrieved contexts are processed by the task model to finish the task. The lower part illustrates our method in which an encoder is incorporated to encode overlong retrieved contexts.

over, in the in-context learning (ICL) (Dong et al., 2022; Kim et al., 2022) setting, the context will be much longer together with retrieved contexts. In such cases, the demand for the model to handle longer input text significantly increases.

To enable the model to cover longer context during both fine-tuning and inference stages, this paper proposes a method that leverages a 100 millionlevel encoder model in downstream ODQA tasks with a 1 billion-level language model as illustrated in the lower part of Fig. 1. With our method, the length of context that the model can cover increases from 2k (in text form) to a maximum of 10k (in dense form, which is condensed by the encoder). Experiments are designed under three settings to validate the effectiveness of our method. In the experiments, we first fine-tune the model, optionally including the encoder, on two popular ODQA datasets with retrieved contexts and evaluate our method in held-in, held-out, and ICL settings. Ex-



Figure 2: Speed illustration. Run time is measured on a single A100 GPU and the batch size is set to 1 for all curves. "2k" on the horizontal axis represents the baseline model's run time to train or infer on data of length 2k. "5k" and "10k" correspond to two variants of our method that can cover at most 5k and 10k tokens when training and inferring. Training time measures the average over five consecutive training steps. Inference time measures the average over five consecutive generation steps. Specifically, we measure the execution duration of functions Trainer.training_step and model.generate based onhuggingface.

perimental results show that our method outperforms the baseline, which is fine-tuned on data of length 2k, in all three settings.

Regarding the speed of our method, we measure the run time of each training and inference step. Compared with work that compresses the contexts with the original task model (Chevalier et al., 2023), which requires techniques to reduce the computation graph during backpropagation, we employ a 10x smaller model to perform the encoding of excessive texts, so a complete gradient descent procedure can be kept. To sum up, our contributions are as follows:

- 1. We propose a method that incorporates a small encoder model for excessively long context encoding by applying cross-attention mechanism with the original task model.
- 2. We evaluate our method in two held-in, four held-out, and two ICL settings after being finetuned on two ODQA datasets and obtain improved performance.
- 3. The computing resource requirements of our method are consistent with those of the baseline and the run time remains competitive.

2 Method

062

063

2.1 Backgrourd

Consider an example query q with gold answer a and independent C pieces of corresponding con-



Figure 3: Method illustration of model architecture (purple blocks) and data flows (along black/purple arrows). The purple dashed arrows mean that the output of MLP module will be the "query" to the next layer of Cross-attn module. $\times N$ means that the modules with dotted backgrounds are repeated with multiple layers in the task model.

text information $k = \{k_1, k_2, ..., k_C\}$, with each being a sequence of tokens, where k is retrieved by some retriever from a given corpus¹

$$k = \text{Retriever}(q, \text{corpus})$$

Ideally, the C retrieved contexts contain the knowledge needed to answer q correctly, but there may also be noise. Given a decoder model *Dec* parameterized by θ , the output sequence y is usually modeled by

$$P_{\theta}(\boldsymbol{y}|\boldsymbol{q}, \boldsymbol{k_{max}}, \boldsymbol{P}) = Dec(\boldsymbol{y}|\boldsymbol{q}, \boldsymbol{k_{max}}, \boldsymbol{P})$$

where $k_{max} = \{k_1, k_2, ..., k_m\} \in k, m < C$. *m* refers to the number of contexts that reach the model's throughput. *P* stands for the prompts that connect related content². Given the model, k_{max} is usually a subset of *k* because the maximum length of contexts is often constrained by the model's throughput or computing resources, and

089

091

094

¹Refer to Sec. 3.1 for detailed definition of corpus and retriever in our experiments.

²The forms of \boldsymbol{P} vary with different settings, and there will be detailed definitions in Sec. 3.1.

During training, we aim to maximize the term $P_{\theta}(a|q, k_{max}, P)$, and formalize the ODQA problem as a language modeling task. Specifically, for a query q, its gold answer a and contexts k_{max} , they are connected linguistically with proper prompts P, together denoted as an input sequence $x(q, a, k_{max}, P) = \{x_1, x_2, ...\}$. Then we aim to minimize the language modeling loss over the set D of all training examples:

$$L_{\theta}(\mathcal{D}) = -\sum_{\boldsymbol{x}(\boldsymbol{q}, \boldsymbol{a}, \boldsymbol{k_{max}}, \boldsymbol{P}) \in \mathcal{D} \quad i} \sum_{i} (1)$$
$$log(P_{\theta}(x_i | x_{< i}))$$

2.2 Encoding and Cross-Attention

104

105

106 107

108

109

110

111

112

113

114

115

116

117

118

119

120

121

122

123

124

125

127

129

130 131

132

We propose a method that can utilize additional contexts $k_{add} = \{k_{m+1}, k_{m+2}, ...\}$ several times longer than k_{max} . First, we introduce an encoder parameterized by ϕ . Then we apply crossattention with the original task model and introduce a projector, a cross-attention module and a Multi-Layer Perceptron (MLP) in each layer, together denoted the parameters as π . Denote $\omega = \{\phi, \pi, \theta\}$ as all the parameters in our model. On the whole, our method models the output y by an encoderdecoder model Enc-Dec

$$Q_{\omega}(\boldsymbol{y}|\boldsymbol{q}, \boldsymbol{k_{max}}, \boldsymbol{P}, \boldsymbol{k_{add}})$$

= Enc-Dec($\boldsymbol{y}|\boldsymbol{q}, \boldsymbol{k_{max}}, \boldsymbol{P}, \boldsymbol{k_{add}})$

During training, inputs $x(q, a, k_{max}, P)$ are embedded by the origin task model's embedding layer Emb

$$\boldsymbol{h}_{\boldsymbol{q}} = Emb(\boldsymbol{x}(\boldsymbol{q}, \boldsymbol{a}, \boldsymbol{k_{max}}, \boldsymbol{P}))$$

and each of the additional contexts k_i in k_{add} is encoded by the encoder Enc

$$h_{add}^{(i)} = Enc(k_i)$$

Note that the length of encoding from the encoder is flexible practically and we compress each k_i into one vector. Following the output of the encoder, a projector Proj is used to align the highdimensional hidden spaces between the encoder and task model in each layer

$$h_{kv} = Proj(h_{add})$$

where h_{add} is concatenated of all $h_{add}^{(i)}$ calculated from last step. Each layer of the task model is assigned to an independent projector as different layers may learn different representations.

In each layer, to incorporate the information stored in k_{add} we add a cross-attention module, where representations of additional contexts h_{kv} serve as "key" and "value", followed by an MLP. In the first layer, the embeddings of original input h_q act as "query", and in the rest of the layers output h'_q from the previous layer act as "query" (h'_q will be defined later).

$$h_c = Cross-attn(h_a/h'_a, h_{kv})$$
 145

135

136

137

138

139

140

141

142

143

144

147

152

153

154

155

156

157

159

160

161

164

166

$$\boldsymbol{h_m} = MLP(\boldsymbol{h_c})$$
 146

 $Cross-attn(h_q, h_{kv})$ is calculated as follows

$$Q = W^Q h_q$$
 148

$$K, V = W^K \boldsymbol{h}_{\boldsymbol{k}\boldsymbol{v}}, W^V \boldsymbol{h}_{\boldsymbol{k}\boldsymbol{v}}$$
 145

$$o = softmax(\frac{QK^T}{\sqrt{d_k}})V$$
150

$$\boldsymbol{h_c} = W^O \boldsymbol{o}$$
 151

where W^Q, W^K, W^V, W^O refer to weight matrices and d_k refers to the dimension of each attention head. Then the output of cross-attention and MLP is normally processed by a self-attention and another MLP module. The output acts as "query" input to the cross-attention module in the next layer.

$$\boldsymbol{h}_{\boldsymbol{q}}' = MLP(Self\text{-}attn(\boldsymbol{h}_{\boldsymbol{m}}))$$
 158

At last, the output of the last layer is expanded to the vocabulary-size dimension to predict the next token (not shown in Fig. 3 for simplicity), and we aim to maximize the probability

$$Q_{\omega}(oldsymbol{a}|oldsymbol{q},oldsymbol{k_{max}},oldsymbol{P},oldsymbol{k_{add}})$$

Consistent with the setup mentioned before, to maximize term $Q_{\omega}(a|q, k_{max}, P, k_{add})$, we turn it into minimizing the language modeling loss

$$J_{\omega}(\mathcal{D}) = -\sum_{\boldsymbol{x}(\boldsymbol{q}, \boldsymbol{a}, \boldsymbol{k_{max}}, \boldsymbol{P}), \boldsymbol{k_{add}} \in \mathcal{D}} \sum_{i} log(Q_{\omega}(x_i | x_{< i}, \boldsymbol{k_{add}}))$$
(2)

2.3 ICL Setting

Our method can also be applied to ICL settings. Based on the aforementioned setup, we denoted ICL samples as $l_{max} = \{l_1, l_2, ..., l_m\}$, with each 167 168

169 170

171

172

174 175 176

177

178

194

195

198

199

201

202

205

207

173

 l_i composed of another pair of query and answer. We optimize objective 3 below on data where each $l_i(q', a')$ refers to only query-answer ICL samples (without context) and q' a' refer to another queryanswer pair:

$$J_{\omega}^{'}(\mathcal{D}) = -\sum_{\boldsymbol{s}(\boldsymbol{q}, \boldsymbol{a}, \boldsymbol{l}_{max}, \boldsymbol{P}), \boldsymbol{k}_{\boldsymbol{a}\boldsymbol{d}\boldsymbol{d}} \in \mathcal{D} \quad i} \log(Q_{\omega}^{'}(s_{i} | \boldsymbol{s}_{< i}, \boldsymbol{k}_{\boldsymbol{a}\boldsymbol{d}\boldsymbol{d}}))$$
(3)

 $\boldsymbol{s} = \{s_1, s_2, ...\}$ refers to the inputs composed of (q, a, l_{max}, P) and Q' shares a similar definition to Q in objective 2. Additional contexts k_{add} are utilized in the same way as in Sec. 2.2 by performing encoding, cross-attention, etc.

2.4 Training

Theoretically, training processes stated in Sec. 2.2 179 all remain differentiable and thus all the parame-180 ters can be optimized via normal gradient descent 181 w.r.t. objective 2. Note that the parameters ϕ 182 of the encoder can be initialized from a well-pre-183 trained model on a large scale corpus and the pretrained parameters possess good performance in many downstream tasks based on text encoding. 186 However, the parameters in the projector module are randomly initialized. Thus at the start of the training, according to the chain rule, the gradients to the whole encoder will be random as well, which 190 poses a risk of breaking the encoding utility of the 191 encoder. This intuition proves to be true in our 192 experiments. 193

Therefore, we design two strategies of training:

- 1. Directly freeze parameters ϕ and make parameters (π, θ) trainable during the whole training process.
- 2. In the first few training steps (e.g., one epoch), ϕ is kept frozen to prevent random gradients from breaking its well-pre-trained parameters. After that, ϕ is optimized w.r.t. objective 2 together with the other modules (π, θ) .

3 Experiment

Experiment settings 3.1

Data To evaluate our method, we first fine-tune our model on two ODQA datasets separately, TriviaQA (Joshi et al., 2017) and Natural Questions

Settings	Data format
Held-in Held-out	Answer the question: Knowledge: {context k_1 } {context k_m }. Q: Who got the first nobel prize in physics A:
ICL format w/ contexts	Answer the following questions based on the Knowledge: Knowledge: {context k'_1 } Q: Who developed the first printing press in 1430s A: Johannes Gutenberg (Knowledge: Q: A:) Knowledge: {context k''_1 } Q: Who got the first nobel prize in physics A:
ICL format w/o contexts (Sec. 2.3)	Answer the following questions: Q: Who developed the first printing press in 1430s A: Johannes Gutenberg (Q: A:) Q: Who got the first nobel prize in physics A:
Additional Contexts	{context k_{m+1} }; {context k_{m+2} };

Table 1: Examples of data format. Gray tokens refer to prompts P mentioned in Sec. 2 and the context is omitted here.

(NQ) (Kwiatkowski et al., 2019). Besides evaluating our method on the held-in data, we also evaluate four held-out data, namely CommonsenseQA (Talmor et al., 2019), SQuAD2.0 (Rajpurkar et al., 2016), Webquestions (Berant et al., 2013) and ComplexWebQuestions (Talmor and Berant, 2018). Specifically, samples in CommonsenseQA dataset are formulated as multi-choice problems, and we evaluate the performance in both multi-choice and sequence-to-sequence formats. Refer to App. A.1 for the detailed format.

209

210

211

212

213

214

215

216

217

218

219

220

221

222

223

224

225

227

Format of input x in Sec. 2.2 is formulated as "Held-in Held-out" format in Table 1, and we evaluate the model's performance on samples of ICL format with context. Format of input s in Sec. 2.3 is formulated as "ICL format w/o contexts" in Table 1.

Additional contexts k_{m+1}, k_{m+2} are encoded by the encoder separately and independently without prompts. The forms of prompts P defined previously are shown in gray tokens in Table 1.

Retriever For contexts of the datasets TriviaQA and NQ, we utilize those collected by Karpukhin et al. (2020), which are collected with BM25 (Robertson et al., 2009) and Dense Passage Retrieval techniques. For contexts of the four heldout datasets, we follow Izacard et al. (2022) and Shi et al. (2023) and use Contriver (Izacard et al., 2021) as our retriever. Contexts k are retrieved from Wikipedia dump dated December 20, 2018, the version released by Karpukhin et al. (2020).

229

230

238

239

242

243

244

245

247

251

256

259

260

261

263

264

265

267

271

272

273

Baseline Recent decoder-only models like Bloomz (Muennighoff et al., 2022) and GPTs (Radford et al., 2019; Achiam et al., 2023) have shown good performance in generation-like tasks, and we use *Bloomz-1b7*³ for the task model θ . When fine-tuning the baseline model, inputs are constructed according to the "Held-in Held-out" setting as stated in Table 1. The length of the input is extended to utilize as many contexts as possible, consistent with the maximum input length (2k) of the model while doing pre-training (Workshop et al., 2022).

Additionally, note that the context information k_{max} provided in the inputs is ranked from best to worst based on Dense Retrieval (Karpukhin et al., 2020), which means the baseline we adopt is rather stronger than randomly providing as many contexts as possible without considering the quality. The baseline can be seen as a model fine-tuned on the most relevant contexts incorporating reranking techniques (Karpukhin et al., 2020; Khalifa et al., 2023).

Initialization and Training Settings Weights of popular pre-trained encoder models like BERT (Devlin et al., 2018) should be good initialization for the encoder ϕ and thus we adopt *BERT-baseuncased*⁴ for initialization of ϕ . Parameters of attention and MLP modules are also adapted from *Bloomz-1b7*. To keep the encoding process efficient, we use a simple Linear module as the projector that is randomly initialized and fine-tuned to align the hidden dimension of 768 (*BERT-baseuncased*) to 2048 (*Bloomz-1b7*).

In our experiment, we use BERT to independently encode additional contexts on 10 or 20 contexts, which can cover approximately 5k to 10k additional context tokens. Then the hidden states of the *[CLS]* token are concatenated and fed-forward

Learning Rate 2e-5 Optimizer AdamW Lr scheduler cosine Warmup ratio 0.03 FP 16 True FP 16 eval True Globa batch size 8 Save steps 4000 Eval steps 4000 4 Max epochs GPU name NVIDIA A100-SXM 80G

Table 3:	Hyperparameters
----------	-----------------

to subsequent modules as illustrated in Fig. 3. For both the baseline and our method, we evaluate the model checkpoint with the lowest language modeling loss on the development set and report the Exact Match (EM) metric. 277

278

279

280

281

283

284

285

287

290

292

293

294

295

296

298

299

300

301

302

303

304

305

306

307

308

310

As discussed in Sec. 2.4, there are mainly two choices of training strategies of which parts of our proposed model are optimized. We experiment with both strategies and report the results of the "frozen encoder" setting in Sec. 3.2 and the "training encoder" setting in Sec. 4.1 respectively. We report important hyperparameters in App. 3.

Hyperparameters We list important hyperparameters in our experiments in Table 3.

3.2 Main Results

We present our main result of the first training strategy discussed in Sec. 2.4 in Table 4. Upon fine-tuning on two datasets and evaluating on three (held-in, held-out and ICL) settings, our method achieves performance superior to that of the baseline in five out of six settings, except for one setting on one dataset.

In held-in settings (training on TriviaQA/NQ and evaluating on TriviaQA/NQ), our model consistently demonstrates superior performance relative to the baseline. Moreover, it demonstrates stable improved performance as more contexts are encoded by our method, showing the potential of our model to encode even longer contexts.

In held-out settings, our method outperforms the baseline in all the datasets after being fine-tuned on TriviaQA and outperforms three of four datasets after being fine-tuned on NQ, suggesting the general applicability of our method. From the "Com.QA

³https://huggingface.co/bigscience/bloomz-1b7 ⁴https://huggingface.co/bert-base-uncased

Train \ Evaluate		Trivi	aQA	N	Q	Com.	QA test	SQuAD	Web.Q	Comp.Q	Triviaq	a (ICL)	NQ (ICL)
		dev	test	dev	test	choice	seq2seq	test	test	test	dev	test	dev	test
TriviaQA	baseline	45.740	46.203	14.868	16.288	17.199	2.785	10.191	9.524	4.490	31.764	31.857	8.999	9.058
	+ 5k	47.686	47.742	17.506	19.307	19.328	3.194	12.684	10.053	5.513	32.341	32.034	10.677	11.136
	+ 10k	47.901	48.245	18.465	19.529	17.363	2.539	12.667	11.111	6.024	34.027	34.235	11.671	11.801
NQ	baseline	42.809	43.976	37.159	37.978	19.410	4.095	21.199	14.815	13.498	35.521	35.967	19.242	21.136
	+ 5k	43.669	44.657	37.01	38.698	19.656	4.095	22.724	15.344	13.214	35.883	35.985	19.265	21.413
	+ 10k	44.189	45.107	37.581	39.114	21.294	4.423	22.918	15.873	13.413	36.381	36.569	19.447	21.662

Table 4: Main results of performance with frozen encoder on held-in, held-out and ICL settings. **Boldface** marks the best results in each setting. Com.QA refers to CommonsenseQA. Web.Q refers to WebQuestions. Comp.Q refers ComplexWebQuestions. TriviaQA (ICL) and NQ (ICL) show the results evaluated on ICL setting where the data is formed as illustrated in Table 1 ICL.

choice" setting we can see that though our model is not trained to answer multi-choice questions, it performs better in selecting choices than baseline.

In the last two columns TriviaQA (ICL) and NQ (ICL), we evaluate whether the optimized model can generalize to a similar ICL setting. Specifically, with optimized parameter ω^* after fine-tuning objective 2 we evaluate how well we can model $Q_{\omega^*}(a|q, l_{max}, P, k_{add})$ where each $l_i(q', a', k')$ is an ICL sample composed of another query, context and answer. Surprisingly, we obtain a similar improved performance to the heldin setting. Steadily improved performance indicates that the training method we adopt is robust, maintaining both the encoder and decoder's efficacy in retrieving useful information while the evaluation data format diverges from the training data.

In summary, from the results presented in Table 4, it is observable that in comparison with the baseline, employing our method to encode a greater volume of retrieval information offers a predominantly positive enhancement to the model's performance across various settings, including held-in, held-out, and ICL.

4 Analysis

311

312

313

314

315

317

318

319

321

323

324

325

327

329

330

331

332

333

335

337

338

339

340

341

342

343

In this section, we present the results of three analytical experiments. The first one shows the result of the other training strategy discussed in Sec. 2.4. The second shows the evaluation results of optimizing objective 3. The third shows the effectiveness of our method in a more challenging setting.

4.1 Encoder Training

In our experiments, we first try optimizing the encoder ϕ with the other parameters (π, θ) from the very beginning of the training process. Results turn out to verify our anticipation: newly introduced random parameters (the projector) easily mess up with the parameters in the encoder, consequently undermining its capability to encode information and resulting in worse performance than baseline. 345

346

347

348

350

351

352

353

354

355

356

357

358

359

360

361

362

363

364

365

366

367

368

369

370

371

372

373

374

375

376

377

378

379

Here we evaluate the training strategy we proposed in Sec. 2.4 that aims to fix this problem. The encoder is optimized after several training steps, and in our experiment, we set it to one epoch. Besides, the parameters in the cross-attention module are initialized by those in the pre-trained selfattention module to minimize the amount of randomly initialized parameters.

Evaluations are done in the same settings as in Table 4. By applying this two-step training method, we succeed in obtaining better performance than the baseline in most of the settings. It can be inferred that compared with the setting of a frozen encoder (i.e., ϕ is not optimized), further introducing trainable encoder parameters did not further enhance the model's performance as anticipated. Although we can achieve better results in most settings than baseline, performance in held-in and held-out settings seems to be less stable compared to the "frozen encoder" setting. Particularly, we find that optimizing the encoder results in degraded performance in the ICL setting, especially after being fine-tuned on TriviaQA datasets. We attribute this to the fact that million-scale parameter models, after fine-tuning on certain data, cannot guarantee to generalize the encoding capability to a broader range of scenarios, e.g. the ICL setting, as defined in Table 1. We present the results of the second training strategy discussed in Sec. 2.4 in Table 5.

Train \ Evaluate		Trivi	iaQA	N	Q	Com.	QA test	SQuAD	Web.Q	Comp.Q	Triviaq	a (ICL)	NQ (ICL)
		dev	test	dev	test	choice	seq2seq	test	test	test	dev	test	dev	test
	baseline	45.740	46.203	14.868	16.288	17.199	2.785	10.191	9.524	4.490	31.764	31.857	8.999	9.058
TriviaQA	+ 5k	48.082	47.803	15.896	16.898	14.333	3.112	10.755	11.640	4.945	16.646	16.645	6.178	6.676
	+ 10k	47.980	47.750	16.079	17.008	15.807	2.867	10.823	11.111	5.058	16.103	16.300	6.383	7.008
NQ	baseline	42.809	43.976	37.159	37.978	19.410	4.095	21.199	14.815	13.498	35.521	35.967	19.242	21.136
	+ 5k	43.397	44.524	37.387	39.03	15.889	4.095	22.092	14.286	12.958	33.993	34.341	17.951	19.640
	+ 10k	43.284	44.047	37.205	39.28	16.790	3.931	22.143	16.402	12.788	33.122	33.404	18.933	20.914

Table 5: Analysis of training encoder along with the task model when fine-tuning. Experiments are conducted under the same setting to Sec. 3.2

ICL samples	Trivi	aQA	NQ			
w/o contexts	dev	test	dev	test		
baseline	20.052	20.083	19.242	19.529		
+ 10 vec	19.939	20.233	19.539	19.668		
+ 20 vec	20.358	20.578	19.333	19.501		

Table 6: Result of fine-tuning on data with ICL samples (without context information) and evaluating on held-in setting.

4.2 ICL Setting w/o Contexts

We also experiment with optimizing objective 3 defined in Sec. 2.3 where only query-answer pairs are provided in the ICL format input. The detailed data format is shown in Table 1 "ICL format w/o contexts" and the query-answer pair is sampled as many as possible from the held-in dataset. The utility of the encoder remains the same as it encodes 10 (+ 10 vec) or 20 (+ 20 vec) pieces of context and is kept frozen during the training.

The model is fine-tuned on TriviaQA and NQ and evaluated in held-in settings. We report the result in Table 6. First, we see that our method can still enhance the model in this setting but the improvements seem to be not consistent or prominent. Second, notice that the improvement on each dataset is not as remarkable as that in the ICL setting in Table 4, where each ICL sample is provided along with one piece of context.

To summarize the findings here, our method for encoding context exhibits a more pronounced performance enhancement in ICL settings that incorporate context information. We posit that the underlying reason for this is that the cross-attention mechanism, which facilitates information interchange between inputs (embedded by the task model) and dense context information (encoded by the encoder), is particularly effective when context interacts with context, instead of context with ICL samples with only query-answer pairs.

4.3 A More Challenging Setting

In our method presented in Sec. 2.2, we adopt a projector module that is applied to align the high-dimensional hidden spaces and adopt crossattention mechanism to incorporate the dense context information in each layer. In this section, we evaluate the effectiveness of our method in a more challenging setting.

Specifically, compared to the data format stated in the "Held-in Held-out" setting in Table 1, we remove the contexts in input x and keep only questions and answers in the training data, i.e., x in objective 2 becomes $(q, a, \{\}, P)$. Only several contexts are supplied as "Additional Contexts" encoded by the encoder. Note that though supplying text-form contexts can greatly enhance models in ODQA tasks, here we remove them to test the effectiveness of the encoder and cross-attention mechanism in a more challenging setting.

Results are shown in Table. 7. "+ 1/5/10 vec" means we utilize 1/5/10 pieces of contexts and encode them into 1/5/10 vectors by taking the *[CLS]* tokens' hidden states. It can be inferred that, firstly, with only one encoded vector, our method can enhance the model. Secondly, we observe consistent improvement across two datasets and three variants of our method that incorporating more contexts leads to better performance (+ 10 vec > + 5 vec > + 1 vec).

5 Related Work

5.1 Retrieval Augmentation

Recently, retrieval augmentation has been utilized to improve a large amount of Natural Language

404

405

406

411 412 413 414 414

416

417

418

419

420

421

422

423

424

425

426

427

428

429

430

431

432

433

434

435

436

437

438

439

440

441

442

407

408

409

h - ()	Trivi	iaQA	NQ			
$\kappa_{max} - \{\}$	dev	test	dev	test		
baseline	20.391	20.472	18.968	19.889		
+ 1 vec	21.636	21.533	20.041	20.637		
+ 5 vec	21.942	22.010	20.258	20.942		
+ 10 vec	21.964	22.072	22.268	22.632		

Table 7: Effectiveness of our method on encoding when we remove the influence on text form context information in \boldsymbol{x} .

Processing downstream tasks such as questionanswering (Chen et al., 2017; Lewis et al., 2020; Kwiatkowski et al., 2019; Fan et al., 2019), dialogue (Moghe et al., 2018), language modeling (Khandelwal et al., 2020), NER (Wang et al., 2022, 2021) and machine translation (Gu et al., 2018; Xu et al., 2022). In the aforementioned work, the utilization of retrieval information has been fundamentally capable of enhancing model performance across all dimensions.

5.2 Related Model Architectures

443

444

445

446

447

448

449

450

451

452

453

454

455

456

457

458

459

460

461

462

463

464

465

466

467

468

469

470

471

472

473

474

475

476

477 478

479

480

481

Referring to the base model, there has been increasing interest in using models of encoder-decoder or decoder-only architectures in solving downstream tasks with retrieval augmentation recently.

Allaouzi et al. (2019) and Zhou et al. (2023) employ models of encoder-decoder architectures to solve visual question answering task in the medical domain. In their work, the encoder model is responsible for extracting prominent features from a medical image and the decoder part generates the answer. Li et al. (2023) utilizes an encoderdecoder model with constrained decoding to solve extractive question answering task.

Decoder-only models, e.g., ChatGPT and GPT-4 (Achiam et al., 2023), are more famous for their surprisingly great performance on tasks like question answering (Ali et al., 2022) and there is abundant work that tries to improve the performance based on GPTs (Pereira et al., 2023). Kim and Min (2024) introduce a chatbot model that utilizes generative AI and the Retrieval Augmented Generation method to address the issue that achieving regulatory compliance necessitates the intricate navigation of exceptionally complex and voluminous guidelines in the pharmaceutical industry.

In our work, we also incorporate an encoder for context encoding. However, compared to the traditional encoder-decoder models, the encoder part in our method is several times smaller than the decoder part. Although our method does not alter the quadratic complexity of the attention mechanism, it instead processes the long contexts in a much lower dimension, thus being able to quintuple the capacity to cover context information without the need to utilize additional computing resources. 482

483

484

485

486

487

488

489

490

491

492

493

494

495

496

497

498

499

500

501

502

503

504

505

506

507

508

510

511

512

513

514

515

516

517

518

519

520

521

522

523

524

525

526

527

528

529

530

5.3 Utilizing Long Contexts

To handle contexts with excessive length, recently proposed techniques such as context compression are increasingly investigated in NLP research.

Chevalier et al. (2023) proposes "AutoCompressors" that uses OPT (Zhang et al., 2022) and Llama-2 (Touvron et al., 2023) to compress texts into summary vectors and show that utilizing long contexts can improve perplexity. In their method, the compression is done by the billion-level language model, and in one of their experiments, they train on sequence with 30720 tokens with 20 compression steps. However, the complete computation graph cannot be fully kept in such settings, and the optimizing process has to rely on stopping gradients, which poses potential risks to the mathematical principle behind gradient descent. Similarly in Zhang et al. (2024)'s work, the long context is first partitioned into multiple intervals, and then a sliding window is employed to sequentially process one interval at a time and the compressed token embeddings are kept for the next token prediction. It is implemented by introducing additional trainable parameters to the origin language model to finish the task of "Activation Condensing", and origin parameters are frozen throughout the training process.

6 Conclusion

In this paper, we propose a method that incorporates a small encoder model for excessively long context encoding by applying cross-attention mechanism with the origin task model. The method is simple and general for transformer-based language models. In our experiments, after fine-tuning on ODQA dataset, we find improved performance across two held-in, four held-out and two ICL settings, compared to a baseline that incorporates the reranking technique on training data, showing the effectiveness of our method in utilizing long contexts. Regarding the efficiency, the need for GPU quantity remains unchanged and the run time remains competitive to the baseline.

531 532

533

534

535

537

539

540

544

545

547

548

549

550

551

554

555

558

560

561

563

568

569

570

571

574

576

577

578

579 580

581

582

7 Limitations

First, we have only tested our method in 1B7 models with a 110M encoder, and yet we have not tested the effectiveness of our method on larger language models, e.g., 7B and 70B, due to limited computing resources.

Second, we observe that our method exhibits relatively modest performance under setting 4.2, with only a slight improvement compared to the baseline. We attribute the potential reasons for this to the cross-attention mechanism being unsuitable for modeling the relationship between context and ICL samples (without contexts).

References

- Josh Achiam, Steven Adler, Sandhini Agarwal, Lama Ahmad, Ilge Akkaya, Florencia Leoni Aleman, Diogo Almeida, Janko Altenschmidt, Sam Altman, Shyamal Anadkat, et al. 2023. Gpt-4 technical report. *arXiv preprint arXiv:2303.08774*.
- Rohaid Ali, Oliver Y Tang, Ian D Connolly, Jared S Fridley, John H Shin, Patricia L Zadnik Sullivan, Deus Cielo, Adetokunbo A Oyelese, Curtis E Doberstein, Albert E Telfeian, et al. 2022. Performance of chatgpt, gpt-4, and google bard on a neurosurgery oral boards preparation question bank. *Neurosurgery*, pages 10–1227.
- Imane Allaouzi, Mohamed Ben Ahmed, and Badr Benamrou. 2019. An encoder-decoder model for visual question answering in the medical domain. In *CLEF* (*working notes*).
- Jonathan Berant, Andrew Chou, Roy Frostig, and Percy Liang. 2013. Semantic parsing on Freebase from question-answer pairs. In *Proceedings of the 2013 Conference on Empirical Methods in Natural Language Processing*, pages 1533–1544, Seattle, Washington, USA. Association for Computational Linguistics.
- Tom Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared D Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, et al. 2020. Language models are few-shot learners. *Advances in neural information processing systems*, 33:1877–1901.
- Danqi Chen, Adam Fisch, Jason Weston, and Antoine Bordes. 2017. Reading Wikipedia to answer opendomain questions. In Proceedings of the 55th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers), pages 1870–1879, Vancouver, Canada. Association for Computational Linguistics.
- Alexis Chevalier, Alexander Wettig, Anirudh Ajith, and Danqi Chen. 2023. Adapting language models to compress contexts. *arXiv preprint 2305.14788*.

Aakanksha Chowdhery, Sharan Narang, Jacob Devlin, Maarten Bosma, Gaurav Mishra, Adam Roberts, Paul Barham, Hyung Won Chung, Charles Sutton, Sebastian Gehrmann, et al. 2023. Palm: Scaling language modeling with pathways. *Journal of Machine Learning Research*, 24(240):1–113. 584

585

587

588

590

591

592

593

594

595

596

597

598

600

601

602

603

604

605

606

607

608

609

610

611

612

613

614

615

616

617

618

619

620

621

622

623

624

625

626

627

628

629

630

631

632

633

634

635

636

637

638

- Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. 2018. Bert: Pre-training of deep bidirectional transformers for language understanding. *arXiv preprint arXiv:1810.04805*.
- Qingxiu Dong, Lei Li, Damai Dai, Ce Zheng, Zhiyong Wu, Baobao Chang, Xu Sun, Jingjing Xu, and Zhifang Sui. 2022. A survey for in-context learning. *arXiv preprint arXiv:2301.00234*.
- Angela Fan, Yacine Jernite, Ethan Perez, David Grangier, Jason Weston, and Michael Auli. 2019. ELI5: Long form question answering. In Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics, pages 3558–3567, Florence, Italy. Association for Computational Linguistics.
- Jiatao Gu, Yong Wang, Kyunghyun Cho, and Victor OK Li. 2018. Search engine guided neural machine translation. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 32.
- Gautier Izacard, Mathilde Caron, Lucas Hosseini, Sebastian Riedel, Piotr Bojanowski, Armand Joulin, and Edouard Grave. 2021. Unsupervised dense information retrieval with contrastive learning. *arXiv preprint arXiv:2112.09118*.
- Gautier Izacard and Edouard Grave. 2020. Leveraging passage retrieval with generative models for open domain question answering. *arXiv preprint arXiv:2007.01282*.
- Gautier Izacard, Patrick Lewis, Maria Lomeli, Lucas Hosseini, Fabio Petroni, Timo Schick, Jane Dwivedi-Yu, Armand Joulin, Sebastian Riedel, and Edouard Grave. 2022. Few-shot learning with retrieval augmented language models. *arXiv preprint arXiv:2208.03299*.
- Mandar Joshi, Eunsol Choi, Daniel Weld, and Luke Zettlemoyer. 2017. TriviaQA: A large scale distantly supervised challenge dataset for reading comprehension. In *Proceedings of the 55th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 1601–1611, Vancouver, Canada. Association for Computational Linguistics.
- Vladimir Karpukhin, Barlas Oguz, Sewon Min, Patrick Lewis, Ledell Wu, Sergey Edunov, Danqi Chen, and Wen-tau Yih. 2020. Dense passage retrieval for opendomain question answering. In Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing (EMNLP). Association for Computational Linguistics.
- Muhammad Khalifa, Lajanugen Logeswaran, Moontae Lee, Honglak Lee, and Lu Wang. 2023. Fewshot reranking for multi-hop QA via language model

748

749

752

696

prompting. In Proceedings of the 61st Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers), pages 15882–15897, Toronto, Canada. Association for Computational Linguistics.

641

649

667

671

672

674

675

677

681

682

684

687

690

691

- Urvashi Khandelwal, Omer Levy, Dan Jurafsky, Luke Zettlemoyer, and Mike Lewis. 2020. Generalization through memorization: Nearest neighbor language models.
- Hyuhng Joon Kim, Hyunsoo Cho, Junyeob Kim, Taeuk Kim, Kang Min Yoo, and Sang-goo Lee. 2022.
 Self-generated in-context learning: Leveraging autoregressive language models as a demonstration generator. arXiv preprint arXiv:2206.08082.
- Jaewoong Kim and Moohong Min. 2024. From rag to qa-rag: Integrating generative ai for pharmaceutical regulatory compliance process. *arXiv preprint arXiv:2402.01717*.
- Tom Kwiatkowski, Jennimaria Palomaki, Olivia Redfield, Michael Collins, Ankur Parikh, Chris Alberti, Danielle Epstein, Illia Polosukhin, Jacob Devlin, Kenton Lee, Kristina Toutanova, Llion Jones, Matthew Kelcey, Ming-Wei Chang, Andrew M. Dai, Jakob Uszkoreit, Quoc Le, and Slav Petrov. 2019. Natural questions: A benchmark for question answering research. *Transactions of the Association for Computational Linguistics*, 7:452–466.
 - Patrick Lewis, Ethan Perez, Aleksandra Piktus, Fabio Petroni, Vladimir Karpukhin, Naman Goyal, Heinrich Küttler, Mike Lewis, Wen-tau Yih, Tim Rocktäschel, et al. 2020. Retrieval-augmented generation for knowledge-intensive nlp tasks. *Advances in Neural Information Processing Systems*, 33:9459–9474.
 - Shaobo Li, Chengjie Sun, Bingquan Liu, Yuanchao Liu, and Zhenzhou Ji. 2023. Modeling extractive question answering using encoder-decoder models with constrained decoding and evaluation-based reinforcement learning. *Mathematics*, 11(7).
 - Nikita Moghe, Siddhartha Arora, Suman Banerjee, and Mitesh M. Khapra. 2018. Towards exploiting background knowledge for building conversation systems. In Proceedings of the 2018 Conference on Empirical Methods in Natural Language Processing, pages 2322–2332, Brussels, Belgium. Association for Computational Linguistics.
- Niklas Muennighoff, Thomas Wang, Lintang Sutawika, Adam Roberts, Stella Biderman, Teven Le Scao, M Saiful Bari, Sheng Shen, Zheng-Xin Yong, Hailey Schoelkopf, et al. 2022. Crosslingual generalization through multitask finetuning. *arXiv preprint arXiv:2211.01786*.
- Jayr Pereira, Robson Fidalgo, Roberto Lotufo, and Rodrigo Nogueira. 2023. Visconde: Multi-document qa with gpt-3 and neural reranking. In *European Conference on Information Retrieval*, pages 534–543. Springer.

- Alec Radford, Jeffrey Wu, Rewon Child, David Luan, Dario Amodei, Ilya Sutskever, et al. 2019. Language models are unsupervised multitask learners. *OpenAI blog*, 1(8):9.
- Pranav Rajpurkar, Jian Zhang, Konstantin Lopyrev, and Percy Liang. 2016. Squad: 100,000+ questions for machine comprehension of text. In *Proceedings of the 2016 Conference on Empirical Methods in Natural Language Processing*, pages 2383–2392.
- Stephen Robertson, Hugo Zaragoza, et al. 2009. The probabilistic relevance framework: Bm25 and beyond. *Foundations and Trends*® *in Information Retrieval*, 3(4):333–389.
- Weijia Shi, Sewon Min, Michihiro Yasunaga, Minjoon Seo, Rich James, Mike Lewis, Luke Zettlemoyer, and Wen-tau Yih. 2023. Replug: Retrievalaugmented black-box language models. *arXiv preprint arXiv:2301.12652.*
- Alon Talmor and Jonathan Berant. 2018. The web as a knowledge-base for answering complex questions.
- Alon Talmor, Jonathan Herzig, Nicholas Lourie, and Jonathan Berant. 2019. Commonsenseqa: A question answering challenge targeting commonsense knowledge. In Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers), pages 4149–4158.
- Hugo Touvron, Thibaut Lavril, Gautier Izacard, Xavier Martinet, Marie-Anne Lachaux, Timothée Lacroix, Baptiste Rozière, Naman Goyal, Eric Hambro, Faisal Azhar, et al. 2023. Llama: Open and efficient foundation language models. *arXiv preprint arXiv:2302.13971*.
- Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Łukasz Kaiser, and Illia Polosukhin. 2017. Attention is all you need. *Advances in neural information processing systems*, 30.
- Xinyu Wang, Yong Jiang, Nguyen Bach, Tao Wang, Zhongqiang Huang, Fei Huang, and Kewei Tu. 2021. Improving Named Entity Recognition by External Context Retrieving and Cooperative Learning. In the Joint Conference of the 59th Annual Meeting of the Association for Computational Linguistics and the 11th International Joint Conference on Natural Language Processing (ACL-IJCNLP 2021). Association for Computational Linguistics.
- Xinyu Wang, Yongliang Shen, Jiong Cai, Tao Wang, Xiaobin Wang, Pengjun Xie, Fei Huang, Weiming Lu, Yueting Zhuang, Kewei Tu, Wei Lu, and Yong Jiang. 2022. DAMO-NLP at SemEval-2022 task 11: A knowledge-based system for multilingual named entity recognition. In *Proceedings of the 16th International Workshop on Semantic Evaluation (SemEval-2022)*, pages 1457–1468, Seattle, United States. Association for Computational Linguistics.

BigScience Workshop, Teven Le Scao, Angela Fan, Christopher Akiki, Ellie Pavlick, Suzana Ilić, Daniel Hesslow, Roman Castagné, Alexandra Sasha Luccioni, François Yvon, et al. 2022. Bloom: A 176bparameter open-access multilingual language model. *arXiv preprint arXiv:2211.05100*.

753

754 755

756

759

765

766

767

768

770 771

772

774

775

776

777

778

780

781

782

785

786

- Jitao Xu, Josep Crego, and Jean Senellart. 2022. Boosting neural machine translation with similar translations. In Proceedings of the 15th Biennial Conference of the Association for Machine Translation in the Americas (Volume 2: Users and Providers Track and Government Track), pages 282–292, Orlando, USA. Association for Machine Translation in the Americas.
 - Peitian Zhang, Zheng Liu, Shitao Xiao, Ninglu Shao, Qiwei Ye, and Zhicheng Dou. 2024. Soaring from 4k to 400k: Extending llm's context with activation beacon. *arXiv preprint arXiv:2401.03462*.
 - Susan Zhang, Stephen Roller, Naman Goyal, Mikel Artetxe, Moya Chen, Shuohui Chen, Christopher Dewan, Mona Diab, Xian Li, Xi Victoria Lin, Todor Mihaylov, Myle Ott, Sam Shleifer, Kurt Shuster, Daniel Simig, Punit Singh Koura, Anjali Sridhar, Tianlu Wang, and Luke Zettlemoyer. 2022. Opt: Open pretrained transformer language models.
 - Yuan Zhou, Jing Mei, Yiqin Yu, and Tanveer Syeda-Mahmood. 2023. Medical visual question answering using joint self-supervised learning. *arXiv preprint arXiv:2302.13069*.

A Appendix

A.1 CommonsenseQA Format

We show how we reformat data from CommonsenseQA in Table 8. Reformated *choice* turn A/B/C/D/E into 1/2/3/4/5 to avoid causing ambiguity with "A:" in prompts **P**. The choices are removed in *seq2seq* format and the problem becomes more challenging.

Format
A revolving door is convenient for two direction travel, but it also
serves as a security measure at a what?
A: bank
B: library
C: department storeD: mall
E: new york
Answer: A
Q: A revolving door is convenient for two direction travel, but it also
serves as a security measure at a what? Choose from 1-5 given below.
1: bank
2: library
3: department store
4: mall
5: new york
A:
Answer: 1 or bank
Q: A revolving door is convenient for two direction travel, but it also
serves as a security measure at a what?
A:
Answer: bank

Table 8