# **GUIDEX: Guided Synthetic Data Generation for Zero-Shot** Information Extraction

# **Anonymous ACL submission**

#### Abstract

Information Extraction (IE) systems are traditionally domain-specific, requiring costly adaptation that involves expert schema design, data annotation, and model training. While Large 004 Language Models (LLMs) have shown promise in zero-shot IE, performance degrades signif-007 icantly in unseen domains where label definitions differ. This paper introduces GUIDEX, a novel method that automatically defines domain-specific schemas, infers guidelines, and generates synthetically labeled instances, allowing for better out-of-domain generaliza-012 tion. Fine-tuning LLaMa 3.1 with GUIDEX sets a new state-of-the-art across seven zeroshot Named Entity Recognition (NER) benchmarks. Models trained with GUIDEX gain up to 10 F1 points over previous methods with-017 out human-labeled data, and nearly 4 F1 points higher when combined with it. Models trained on GUIDEX demonstrating enhanced comprehension of complex, domain-specific annotation schemas. Code, models, and synthetic datasets will be released upon acceptance.

## 1 Introduction

027

034

036

Information Extraction (IE) tasks (Grishman, 1997) are structured around two core components: a formal schema specifying target entities/relations and human-readable guidelines defining their interpretation. Despite their utility, IE systems face significant scalability challenges due to domain dependence. Adapting to new domains requires substantial resources, including (1) domain experts to design schemas and annotation rules, (2) trained annotators to label data accordingly, and (3) machine learning specialists to develop performant models. This complex process creates a bottleneck for real-world applications where label definitions frequently evolve across contexts.

> Early attempts to remove the need for annotated data (zero-shot IE) framed the task through



Figure 1: Impact of GUIDEX for zero-shot NER on different domains. In  $Gold_{FT}$ , the model is trained solely on gold training data, whereas in  $GuideX_{FT}$  +  $Gold_{FT}$  it is also trained on our synthetic dataset.

Question Answering (Levy et al., 2017) or Natural Language Inference (Obamuyide and Vlachos, 2018; Sainz et al., 2021) paradigms, leveraging supervised data from these auxiliary tasks. While showing initial promise, these methods remained constrained by their reliance on manually crafted schemas and limited cross-domain generalization.

More recent advancements leveraging Large Language Models (LLMs) have streamlined schema definition processes (Li et al., 2024), facilitating adaptation to new domains. However, performance gaps persist when deploying these systems in unseen domains where label semantics diverge from training distributions (Sainz et al., 2024). Our work addresses this challenge by automating the generation of domain-specific schemas, guidelines, and annotated data to bridge the seen-unseen domain divide.

Data Augmentation (Feng et al., 2021) and Synthetic Data Generation (Teknium, 2023; Xu et al., 2025) have proven particularly valuable in the era of LLMs. In IE, traditional techniques like distant supervision (Mintz et al., 2009) aim to enhance model performance but often introduce noisy annotations. While effective for achieving high recall, 041

042

166

116

117

distant supervision frequently generates spurious labels due to its reliance on imperfect heuristics. Similarly, LLM distillation (Hinton, 2015)—where smaller student models learn from larger teacher models—faces inherent limitations: student performance is constrained by the teacher's capabilities and often fails to capture all valid instances. Both methods also require predefined annotation schemas, severely limiting their adaptability to novel domains where label definitions may shift.

066

067

068

071

072

079

087

094

100

101

103

105

106

107

108

109

110

111

112

113

In this paper, we tackle the aforementioned limitations by introducing GUIDEX, a novel data generation method inspired by the work of domain experts. It is designed to generate schemas, guidelines and annotated examples for any new domain which allows to improve IE performance on new as well as on unseen domains. This approach consists of four main steps. Given a set of documents from the target domain, an LLM is used to identify the key information within each document, summarizing and synthesizing its content into a set of bulleted ideas. Next, the extracted information is structured into a standardized format, typically a JSON file. Then, the model is asked to generate the annotation schema and the corresponding annotation guidelines based on the previously structured annotations. This approach ensures that the annotations align with the guidelines and remain comprehensive. This step is particularly crucial, as it guarantees the correctness of the schema and significantly reduces potential annotation errors in the generated data. Finally, we ask the model to generate the final annotations following a standard code-style format.

We validated our data generation approach by training state-of-the-art models using the synthetic data produced through our methodology. When fine-tuning base models, such as LLaMa 3.1 (Grattafiori et al., 2024), exclusively on our dataset, we observed an average improvement of 10 F1 points across seven Named Entity Recognition (NER) benchmarks in zero-shot evaluation. Furthermore, when leveraging our data to enhance state-of-the-art approaches, we achieved a notable improvement of nearly 4 F1 points on the same benchmarks (see Figure 1), establishing a new stateof-the-art.

### 2 Related Work

In this section, we review the literature related to our work. We begin by highlighting the most significant studies that involve LLMs for IE. Following that, we will focus on methods for generating synthetic data aimed at the same task.

LLM-Based IE. Recent advances in IE increasingly leverage LLMs to tackle tasks such as Named Entity Recognition (NER), Relation Extraction (RE), and Event Extraction (EE) in both zero-shot and few-shot settings (Brown et al., 2020; Raffel et al., 2020; Xu et al., 2024a). By prompting (Li et al., 2022; Ashok and Lipton, 2023; Wang et al., 2021; Wei et al., 2024, 2023; Xu et al., 2024b; Mo et al., 2024) or fine-tuning (Zhou et al., 2023; Lou et al., 2023a; Gui et al., 2025) these models can be guided to extract relevant spans (e.g., entities, relationships) in raw text. Methods like InstructUIE (Wang et al., 2023), and RUIE (Liao et al., 2025) build on the idea of formulating IE as an instruction-following or retrieval-based generation task, showing that well-structured prompts can improve performance without extensive humanannotated data.

A specialized subtrend emphasizes schema and guideline guided strategies, where the LLM is trained to follow explicit annotation rules (Sainz et al., 2024; Pang et al., 2023; Bai et al., 2024). These methods demonstrate that providing precise definitions and examples of valid or invalid annotations can significantly enhance zero-shot IE outcomes, reducing error rates from ambiguous token boundaries or unclear entity types. Similarly, KnowCoder (Li et al., 2024) encodes structured knowledge into LLMs to facilitate universal IE across multiple domains, underscoring the value of carefully specified label schemas. Although these guideline-oriented approaches maintain higher consistency across domains, they often depend on timeconsuming, manual curation of instructions. As new tasks or domains emerge, the annotation guidelines must be updated or expanded, posing a key scalability challenge.

**Synthetic Data Generation for IE.** Distant supervision remains one of the earliest forms of synthetic data labeling, aligning knowledge-base facts with textual mentions to automate the creation of large-scale IE datasets (Mintz et al., 2009). While this technique helped address the scarcity of annotated data, it is susceptible to label noise because the mere co-occurrence of entities in a sentence does not necessarily confirm their relationship (Surdeanu et al., 2012). More recent developments incorporate multi-instance multi-label learning and



Figure 2: GUIDEX process overview. The approach transforms raw text into structured annotations by dynamically inferring schemas, generating executable guidelines, and resulting annotations.

noise reduction heuristics to mitigate erroneous matches (Hoffmann et al., 2011; Lin et al., 2016; Han and Sun, 2016; Xiao et al., 2020), yet these pipelines often rely on rigid predefined schemas, making it challenging to adapt to novel entity or relation types.

167

168

169

170

171

172

173

174

175

178

179

181

183

184

186

188

189

190

191

192

194

Beyond distant supervision, emerging methods leverage LLMs themselves to generate synthetic data for IE tasks (Josifoski et al., 2023; Chen et al., 2017). UniNER (Zhou et al., 2023) and Know-Coder (Li et al., 2024) generate additional training instances by prompting an LLM to produce sentences conforming to a particular label schema. This broadens coverage and reduces the requirement for human annotation. However, the resulting data can suffer from stylistic repetition, domain mismatch, or incomplete label application if the model fails to follow the schema consistently (Xu et al., 2024a). Moreover, existing synthetic data generation techniques often do not provide robust mechanisms to manage data structure or coverage, resulting in partially accurate guidelines and noisy annotations.

In light of these observations, our work introduces GUIDEX, a data generation approach that integrates both schema-driven and synthetic paradigms while addressing key limitations in diversity and noise control. Rather than relying on fully manual guidelines or naive LLM-based generation, GUIDEX dynamically constructs annotation schemas and guidelines for each document, then synthesizes labeled text aligned with those rules. This approach reduces the costs of manual schema creation and mitigates the spurious annotations often seen in unconstrained synthetic data generation. Crucially, we show that incorporating the resulting dataset into zero-shot IE training significantly boosts performance across multiple benchmarks, surpassing existing approaches whether they rely on synthetic data and guidelines or not. By unifying explicit guideline creation with data synthesis, GUIDEX offers a low-noise strategy for robust zero-shot IE across increasingly diverse domains. 195

196

197

198

199

201

202

203

204

205

206

207

208

209

210

211

212

213

214

215

216

217

218

219

220

# **3** GUIDEX: Guided Synthetic Data Generation

In this section, we introduce GUIDEX, a structured synthetic data generation approach designed to enhance IE capabilities of LLMs. Unlike traditional LLM distillation approaches or distant supervision, which often rely on predefined annotation schemas, GUIDEX dynamically infers annotation schemas. This approach reduces annotation inconsistencies, enhances flexibility across different IE tasks, and enables high-quality, guideline-driven annotations.

316

317

318

319

320

321

271

272

As shown in Figure 2, the GUIDEX approach consists of four sequential steps: document summarization, structured representation synthesis, annotation guideline generation, and instance extraction. Prior work has shown that LLMs struggle with information extraction in zero-shot settings, and attempting to perform the entire task in a single step leads to poor results. Instead, our structured process progressively refines raw text through these four stages, ensuring high-quality, structured annotations that align with inferred guidelines. Below, we describe each step in detail.

233

235

236

240

241

243

244

245

246

247

248

249

258

261

263

265

266

267

270

**Document summarization.** The first step in the pipeline focuses on identifying the most important concepts within a document. To achieve this, the LLM generates a summary highlighting the key points, effectively recognizing relevant entities and events while structuring the extracted information. Instead of relying on a predefined annotation schema, this approach allows the model to determine the relevant elements autonomously, resulting in more diverse and domain-specific annotations.

Figure 2.I presents a sample summary generated for an article discussing Machine Learning frameworks in AI research. The model successfully identifies key frameworks (*TensorFlow* and *PyTorch*), along with relevant entity details, including their developers and notable features.

**Structured representation.** IE aims to identify specific spans of text that contain relevant information. In the second step of our approach, the model leverages both the previously generated summary and the original document to organize the extracted information into a structured JSON format. This representation ensures that key elements are systematically categorized while maintaining direct references to the source text. To improve accuracy and conciseness, we enforce constraints that limit the extracted spans to the shortest possible length while preserving their full meaning.

As depicted in Figure 2.II, the extracted information is transformed into a structured JSON format, where each entity is assigned meaningful labels and attributes. This structured representation enables better organization and downstream usability, ensuring that information is both interpretable and machine-readable.

**Guideline generation.** Annotation guidelines play a critical role in improving zero-shot IE performance by ensuring consistency and reducing ambiguity in annotations (Sainz et al., 2024; Li et al., 2024). However, manually crafting such guidelines is a complex task, as it requires defining precise rules that account for variations across different domains. To address this challenge, our approach dynamically generates annotation guidelines based on the structured JSON representation, the document summary, and the original text. Instead of relying on predefined schemas, the model autonomously derives comprehensive descriptions for each entity type, ensuring that all relevant attributes are clearly captured.

Each generated guideline is formulated as a Python dataclass, embedding a long and detailed description of the entity type within the class docstring. The expected attributes of the entity are also explicitly defined, with each field accompanied by comments explaining its meaning and expected format. By structuring the annotation schema in this manner, the model produces a standardized and interpretable representation of the information.

Figure 2.III shows how this process results in a set of structured dataclasses that define both entity types and their relationships while preserving flexibility. Unlike static annotation guidelines, which may be limited in adaptability, this approach ensures that each document receives tailored guidelines that align precisely with its content. By encoding these guidelines into Python code, the approach maintains a high level of structural consistency.

**Instance Extraction** The final step of the GUIDEX approach involves extracting concrete instances of the entities and attributes defined in the annotation guidelines. Using the structured JSON representation and the inferred annotation schema, the model populates entity classes with specific values derived directly from the original document. This step ensures that the extracted instances strictly adhere to the predefined structure and maintain high fidelity to the source text.

To achieve this, the model generates a Python list where each entry corresponds to an instance of one of the dataclasses created in the guideline generation step. Each instance is populated with concise values extracted from the text, prioritizing single words or short phrases over verbose descriptions to maximize precision and clarity. The model is explicitly instructed to return only the structured instances, without additional explanations or extraneous text.

As illustrated in Figure 2.IV, this process results

in a structured dataset where each entity and its attributes are instantiated according to the inferred 323 schema. This format ensures seamless integration 324 into downstream applications, enabling models to leverage high-quality, structured annotations for training or evaluation. By enforcing a standardized representation of extracted instances, GUIDEX 328 maintains consistency across different documents and domains

331

335

341

345

346

347

354

357

GUIDEX enhances synthetic data reliability by structuring annotation guidelines and extracted instances as executable Python code, enabling automated validation to detect hallucinations and inconsistencies. A consistency-checking mechanism systematically executes each dataset entry, flagging logical errors such as undefined entity types 337 or misaligned attributes. An automated filtering script discards invalid annotations while retaining 339 only schema-compliant ones, significantly reducing spurious relationships and annotation noise. This structured validation process ensures highquality, guideline-aligned synthetic data, leading to more robust and trustworthy IE models.

#### The GUIDEX dataset 4

This section presents the dataset constructed using the proposed method. We begin by detailing the document collection process that served as the foundation for our dataset. Then, we provide statistical insights to illustrate its composition and characteristics.

Document Collection. The dataset was constructed using FineWeb-edu (Penedo et al., 2024), a high-quality subset of the larger FineWeb dataset, specifically curated for educational content. From this collection, we randomly sampled ~10,000 documents. The dataset exhibits a wide range of document lengths, spanning from 194 to 22.6k words. To preserve the coherence of the textual structure and maximize contextual understanding, we retain entire documents rather than segmenting them into smaller units such as paragraphs or sentences.

**Dataset Statistics.** The GUIDEX dataset covers a diverse range of topics, as illustrated by the distribution of the most and least frequent labels in Table 1. It includes a strong presence of categories related to Medicine (Symptom, Cause, Study, Treatment), Economics (Benefit, Resource, Application, Activity), and History (Event, HistoricalEvent, Study). Additionally, it covers domains such as Music (Mu-370

Most common		Least common			
Freq.	Label	Freq.	Label		
1820	Symptom	1	MusicOrigin		
1459	Benefit	1	AttitudesTowardsMusic		
929	Resource	1	MusicStudy		
927	Topic	1	DietRecommendations		
837	Cause	1	FilterInformation		
830	Location	1	AsyncDataSharing		
786	Event	1	SoundMakingInformation		
689	Study	1	MOOCDefinition		
679	Treatment	1	MOOCDesign		
609	HistoricalEvent	1	MOOCContent		
586	Application	1	TeachingAndLearning		
572	Activity	1	BenefitsAndChallenges		

Table 1: Most and Least frequent labels in the GUIDEX dataset.

sicOrigin, AttitudesTowardsMusic, MusicStudy) and Education (MOOCDefinition, MOOCDesign, *TeachingAndLearning*). In total, the dataset has 28,677 unique labels, with an average of 5.34 distinct labels per document. Each document contains an average of 11.39 annotations, highlighting the dataset's richness and granularity.

371

372

373

374

375

376

378

379

380

381

382

383

385

388

389

390

391

392

394

395

396

397

398

399

400

401

402

#### 5 **Experimental Setting**

In this section we outline the details of our experiments. We begin by introducing the models used for both synthetic dataset generation and finetuning on manually annotated (gold) data. Next, we describe the IE datasets utilized for training and evaluation. Finally, we present the baselines and state-of-the-art systems used for comparison.

## 5.1 Models

Synthetic data generation. For generating synthetic data, we utilized the 70B variant of the LLaMa 3.1 Instruct model. After evaluating various alternatives, this model demonstrated consistent reliability in generating high-quality outputs. Although proprietary models exhibited marginally better performance in some cases, we prioritized reproducibility by selecting an open-source solution for this research.

Model fine-tuning. All the models we trained are based on the 8B variant of LLaMa 3.1 (Grattafiori et al., 2024). We adopted the standard code-style format for IE (Sainz et al., 2024; Li et al., 2024, 2023; Qi et al., 2024). To avoid negative impacts derived by the input format discrepancies, we use the base LLaMa 3.1 over the instruct variant.

<b>GUIDEX</b> <sub>FT</sub>	$\boldsymbol{Gold}_{\boldsymbol{FT}}$	AI	Literature	Music	Science	Politics	Movie	Restaurant	AVERAGE
×	×	24.13	25.83	33.87	21.67	31.94	40.86	32.27	30.08
1	×	37.81	45.52	48.75	33.36	37.01	36.09	45.77	40.62
×	1	60.68	63.21	64.26	60.17	64.64	62.98	54.50	61.49
✓	✓	64.02	60.43	66.82	67.79	73.41	66.33	56.46	65.04

Table 2: Impact of GUIDEX fine-tuning and gold fine-tuning on zero-shot NER performance with LLaMa 3.1 8B. GUIDEX<sub>FT</sub> denotes finetuning on GUIDEX data, while Gold<sub>FT</sub> fine-tuning on manually annotated data.  $\checkmark$  shows the presence of a training stage,  $\varkappa$  shows its absence. Results are reported as F1-scores on out-of-domain datasets.

#### 5.2 Datasets

403

404

405

406

407

408

409

410

411

412

413

414

415

416

417

418

419

420

421

422

423

424

425

426

427

428

429

430

431

432

433

434

435

436

437

438

439

**Training Datasets.** Beyond the GUIDEX dataset, we trained our system using the same manually annotated gold-standard data as Sainz et al. (2024). This gold-standard data comes from multiple sources and covers several IE tasks including Named Entity Recognition (NER), Event Extraction (EE), Event Argument Extraction (EAE), Relation Extraction (RE), and Slot Filling (SF). Specifically, we utilized ACE 2005 (Walker et al., 2006) for NER, EE, EAE, and RE, while TA-CRED (Zhang et al., 2017) was employed for SF<sup>1</sup>. Additional NER datasets used for training include BC5CDR (Li et al., 2016), CoNLL 2003 (Tjong Kim Sang and De Meulder, 2003), DIANN (Fabregat et al., 2018), NCBDisease (Doğan et al., 2014), Ontonotes 5 (Pradhan et al., 2013), and WNUT17 (Derczynski et al., 2017).

**Evaluation Datasets.** To assess the effectiveness of our approach, we conducted evaluations on standard zero-shot NER benchmarks. Specifically, we tested on multiple CrossNER (Liu et al., 2020) splits, as well as the MIT Movie and MIT Restaurant datasets (Liu et al., 2013).

#### 5.3 Baselines

We established two primary baselines: the base LLaMa 3.1 model and its fine-tuned counterpart using the manually annotated training datasets described in Section 5.2. From now on, we refer to the fine-tuned version as  $Gold_{FT}$ . These baselines will be compared to their variants pretrained on GUIDEX synthetic data: GUIDEX<sub>FT</sub> (trained solely on synthetic data) and GUIDEX<sub>FT</sub> + Gold<sub>FT</sub> (trained sequentially on both datasets).

Beyond these controlled comparisons, we benchmark our approach against seven state-of-theart models. We include general-purpose conversational LLMs such as Vicuna (Chiang et al., 2023) and ChatGPT (Ouyang et al., 2022), as reported by Zhou et al. (2023). Additionally, we evaluate against specialized IE models, including USM (Lou et al., 2023b), InstructUIE (Wang et al., 2023), GoLLIE (Sainz et al., 2024), Know-Coder (Li et al., 2024), and GLiNER (Zaratiana et al., 2023). We also compare our method to UniNER (Zhou et al., 2023), a synthetic data generation-based approach for NER.

440

441

442

443

444

445

446

447

448

449

450

451

452

453

454

455

456

457

458

459

460

461

462

463

464

465

466

467

468

469

470

471

472

473

474

475

476

477

### 5.4 Implementation details

All models were trained using QLoRA (Dettmers et al., 2023), with hyperparameters optimized based on the validation splits of the training datasets (see Appendix A). We followed the same code-based input format as Sainz et al. (2024). The data generation process was conducted on four NVIDIA A100 GPUs with 80GB of memory each, while model training was performed using two GPUs of the same type.

#### 6 Results

In this section, we discuss our experimental findings by examining GUIDEX's impact on performance and comparing our approach against the state-of-the-art.

**Impact of synthetic data.** Table 2 summarizes our main comparisons by divding them into two scenarios: when no manually annotated data is available, and when it is. In the first scenario, we evaluate the raw impact of our dataset, particularly analyzing the extent to which it can assist a baseline LLM in learning the task. In the second scenario, we observe how the addition of manually annotated data (and thus domain-specific knowledge) further affects performance.

The top two rows of Table 2 show results when no manual annotations are available for fine-tuning. Without any task-specific data points, LLaMa 3.1

<sup>&</sup>lt;sup>1</sup>Originally designed for RE, we followed Sainz et al. (2024) in converting it into an SF task.

Model	Params	Backbone	Movie	Restaurant	AI	Literature	Music	Politics	Science	Avg
Vicuna-7B	7B	LLaMa	06.0	05.3	12.8	16.1	17.0	20.5	13.0	13.0
Vicuna-13B	13B	LLaMa	00.9	00.4	22.7	22.7	26.6	27.0	22.0	17.5
USM	0.3B		37.7	17.7	28.2	56.0	44.9	36.1	44.0	37.8
ChatGPT	-	_	05.3	32.8	52.4	39.8	66.6	68.5	67.0	47.5
InstructUIE	11B	FlanT5	63.0	21.0	49.0	47.2	53.2	48.1	49.2	47.2
UniNER-7B	7B	LLaMa	42.4	31.7	53.6	59.3	67.0	60.9	61.1	53.7
UniNER-13B	13B	LLaMa	48.7	36.2	54.2	60.9	64.5	61.4	63.5	55.6
GoLLIE	7B	CodeLLaMa	63.0	43.4	59.1	62.7	67.8	57.2	55.5	58.0
KnowCoder	7B	LLaMa 2	50.0	48.2	60.3	61.1	70.0	72.2	59.1	60.1
GLiNER-L	0.3B	DeBERTa-V3	57.2	42.9	57.2	64.4	69.6	72.6	62.6	60.9
Gold <sub>FT</sub>	8B	LLaMa 3.1	63.0	54.5	60.7	63.2	64.2	60.2	64.6	61.5
$GUIDEX_{FT} + Gold_{FT}$	8B	LLaMa 3.1	66.3	56.5	64.0	60.4	66.8	73.4	67.8	65.0

Table 3: Zero-Shot F1-scores on Out-of-Domain NER Benchmarks, reporting state-of-the-art systems and two systems fine-tuned with and without GUIDEX

achieves an average F1 score of 30.08 across all seven datasets. While significant, it falls short of the best performing models. However, when trained with GUIDEX, the average F1 score improves significantly, with an increase of 10.5 points. Although not all seven tasks show improvement, those that do improve see notable gains. This demonstrates that our synthetic data effectively teaches the task to a baseline model and integrates domain-specific knowledge where it matters.

478

479

480

481

482

483

484

485

486

487

488

489

490

491

492

493

494

495

496

497

498

499

501

502

503 504

506

507

508

509

510

511

The third row illustrates the impact of manually annotated data (Gold<sub>FT</sub>). As anticipated, these sentence-level annotations substantially boost results. Unlike our GUIDEX dataset—largely based on documents—both the training and evaluation sets in Gold<sub>FT</sub> focus on sentence-level IE tasks. This alignment phase allows the model to tackle sentence-specific zero-shot tasks more accurately. Even so, the improvements we achieve with Gold<sub>FT</sub> are complementary to those achieved with GUIDEX<sub>FT</sub>.

Lastly, the bottom row presents a model finetuned first with GUIDEX<sub>FT</sub> and then with Gold<sub>FT</sub>. It can be seen that both steps jointly increase performance by an average of 35 F1 points over the plain LLaMa 3.1 baseline (24.4 points over GUIDEX<sub>FT</sub> alone and 3.5 over Gold<sub>FT</sub>). Moreover, applying GUIDEX<sub>FT</sub> to a model already trained with Gold<sub>FT</sub> yields up to 7.6 additional F1 points, improving on six of the seven datasets. This indicates that the GUIDEX<sub>FT</sub> data can significantly enhance the model's performance in various specific domains. We analyze the impact on a label-by-label basis in Section 7.

512 **Comparison with the state-of-the-art.** Table 3 513 presents a comparison of our best-performing model, which was fine-tuned on  $GUIDEX_{FT}$  and Gold<sub>FT</sub>, against various state-of-the-art zero-shot NER systems. Our best approach achieves an average F1 score of 65.0, surpassing all other models in the benchmark. Notably, it outperforms GoLLIE by 7.0 F1 points. GoLLIE is a system similar to Gold<sub>FT</sub> but based on CodeLLaMa. Additionally, when compared to KnowCoder, another system akin to Gold<sub>FT</sub> that uses a pretraining dataset to better follow annotation schemas, our approach shows a 4.9-point improvement. It is worth mentioning that the pretraining proposed by (Li et al., 2024) could provide complementary enhancements to our method. In addition to its overall performance, GUIDEX shows strong generalization across various domains. It achieves the highest F1 scores in five out of seven benchmarks: Movie (66.3), Restaurant (56.5), AI (64.0), Politics (73.4), and Science (67.8).

514

515

516

517

518

519

520

521

522

523

524

525

526

527

528

529

530

531

532

533

534

535

536

537

538

539

540

541

542

543

544

545

546

547

548

These results highlight the effectiveness of our approach in adapting to unfamiliar domains, surpassing conventional instruction tuning and guideline-based baselines. By utilizing LLMs and domain-specific documents to generate synthetic data, GUIDEX offers a reliable method for enhancing zero-shot IE.

## 7 Analysis

This section examines the impact of GUIDEX across different labels, highlighting its benefits and limitations. Table 4 provides a breakdown of performance gains in various domains and identifies cases where GUIDEX still struggles.

**Do Guidelines Improve Domain-Specific Labels?** GUIDEX effectively mitigates the overgeneralization tendency in zero-shot IE (Sainz et al.,

Dataset	Label	Summarized Guideline	Gold <sub>FT</sub>	$GUIDEX + Gold_{FT}$
Natural Science	Scientist	A person who is studying or has expert knowledge of a natural science field.	38.43	51.21
	Person	Individuals that are not scientist.	48.53	53.02
Politics	Politician	A person who is actively engaged in politics, holding a public office, involved in political activities or part of a political party.	35.12	44.37
	Person	Individuals that are not politician.	59.48	62.86
Politics	PoliticalParty	An organization that coordinates candidates to compete in a particular country's elections.	58.55	65.30
	Organization	A structured group, institution, company, or association that is not a political party.	54.34	58.38
AI	Location	A specific geographical or structural location.	75.36	75.86
Music	Country	A sovereign nation.	81.62	82.45
Music	Other	Named entities that are not included in any other category.	15.99	13.02
Literature	Other	Named entities that are not included in any other category.	23.19	20.78

Table 4: F1 scores for specific labels from different datasets with summarized guideline descriptions. On green, the labels where the domain knowledge acquired by training in GUIDEX is helpful for the model. On blue, the labels where there is no improvement. And, on red, those labels that both systems struggle to identify correctly.

549 2024) by teaching models to differentiate between broad and fine-grained entity labels through structured annotation schemas. Table 4 shows how baseline models frequently default to generic labels like Person instead of recognizing domain-specific entities such as Scientist and Politician, leading to misclassifications. Fine-tuning with GUIDEX significantly improves precision, with F1 gains of up to 12.8 points for these cases, as well as a 6.75point increase in distinguishing PoliticalParty from the broader Organization category. The model, trained on explicit contextual definitions, applies labels more accurately, reducing errors where, for instance, political parties were misclassified as organizations due to linguistic similarities. These results highlight the impact of structured guidelinedriven learning in improving model adaptability, reinforcing context-aware predictions, and enabling more precise entity differentiation in specialized domains. For inherently generic labels, such as Location and Country, the model already achieves strong performance without GUIDEX. This suggests that our approach is most beneficial for refining entity granularity rather than improving wellestablished, domain-agnostic categories.

574 Remaining challenges. Some labels, such as Other and Miscellaneous, remain problematic even 575 with GUIDEX (see Figure 4). These categories often lack clear definitions, making it difficult to apply them consistently. Since GUIDEX generates 578

precise guidelines, the absence of well-defined annotation criteria for these broad labels limits its effectiveness. This aligns with findings (Sainz et al., 2024) suggesting that guideline-driven models struggle with vague or catch-all entity types.

579

580

581

582

584

585

586

587

588

590

591

592

593

594

595

596

597

598

599

600

601

602

603

604

605

606

607

#### 8 Conclusions

In this paper, we introduce GUIDEX, a novel approach for synthetic data generation aimed at IE. We utilize GUIDEX to generate data suitable for a variety of domains using documents from FineWebedu. As a demonstration of the method, we generate a dataset with 10,000 annotated documents, featuring a wide range of labels, from generic to highly domain-specific. Using this generated data, we train an IE model that surpasses the performance of current state-of-the-art zero-shot NER systems. Furthermore, we demonstrate that our method effectively generates domain-specific annotations, which can be utilized to train robust IE systems across multiple domains.

GUIDEX paves the way for two key research directions: (1) advancing document-level IE methodologies, and (2) developing automated techniques for handling ill-defined or generic labels like Other and Miscellaneous. These challenges are critical for IE applications but remain largely unexplored, offering potential for future work. Our method provides a foundation to address these open problems systematically.

### 18 Limitations

609 In this work, we present an approach for generating synthetic data, which we used to enhance the 610 performance of IE models on NER datasets across various domains. However, our evaluation does not encompass all potential applications of this ap-613 614 proach. For example, the automatically generated dataset consists of document-level texts rather than 615 individual sentences. Our evaluation framework, on the other hand, focuses solely on sentence-level tasks. In the future, we aim to investigate the im-618 619 pact of our approach on document-level tasks.

#### References

621

624

625

627

631

632

633

634

636

637

641

642

643

644

647

649

656

657

- Dhananjay Ashok and Zachary C. Lipton. 2023. Promptner: Prompting for named entity recognition. *Preprint*, arXiv:2305.15444.
- Fan Bai, Junmo Kang, Gabriel Stanovsky, Dayne Freitag, Mark Dredze, and Alan Ritter. 2024. Schemadriven information extraction from heterogeneous tables. In *Findings of the Association for Computational Linguistics: EMNLP 2024*, pages 10252– 10273, Miami, Florida, USA. Association for Computational Linguistics.

Tom Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared D Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, Sandhini Agarwal, Ariel Herbert-Voss, Gretchen Krueger, Tom Henighan, Rewon Child, Aditya Ramesh, Daniel Ziegler, Jeffrey Wu, Clemens Winter, and 12 others. 2020. Language models are few-shot learners. In Advances in Neural Information Processing Systems, volume 33, pages 1877–1901. Curran Associates, Inc.

- Yubo Chen, Shulin Liu, Xiang Zhang, Kang Liu, and Jun Zhao. 2017. Automatically labeled data generation for large scale event extraction. In Proceedings of the 55th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers), pages 409–419, Vancouver, Canada. Association for Computational Linguistics.
- Wei-Lin Chiang, Zhuohan Li, Zi Lin, Ying Sheng, Zhanghao Wu, Hao Zhang, Lianmin Zheng, Siyuan Zhuang, Yonghao Zhuang, Joseph E. Gonzalez, Ion Stoica, and Eric P. Xing. 2023. Vicuna: An opensource chatbot impressing gpt-4 with 90%\* chatgpt quality.
- Leon Derczynski, Eric Nichols, Marieke van Erp, and Nut Limsopatham. 2017. Results of the WNUT2017 shared task on novel and emerging entity recognition. In *Proceedings of the 3rd Workshop on Noisy User-generated Text*, pages 140–147, Copenhagen, Denmark. Association for Computational Linguistics.

Tim Dettmers, Artidoro Pagnoni, Ari Holtzman, and Luke Zettlemoyer. 2023. Qlora: efficient finetuning of quantized llms. In *Proceedings of the 37th International Conference on Neural Information Processing Systems*, NIPS '23, Red Hook, NY, USA. Curran Associates Inc. 661

662

664

665

666

667

668

669

670

671

672

673

674

675

676

677

678

679

680

681

682

683

684

685

686

687

688

689

690

691

692

693

694

695

696

697

698

699

700

702

703

704

705

706

707

708

709

710

711

712

713

714

715

716

- Rezarta Islamaj Doğan, Robert Leaman, and Zhiyong Lu. 2014. Ncbi disease corpus: a resource for disease name recognition and concept normalization. *Journal of biomedical informatics*, 47:1–10.
- Hermenegildo Fabregat, Juan Martinez-Romo, and Lourdes Araujo. 2018. Overview of the diann task: Disability annotation task. In *IberEval@ SEPLN*, pages 1–14.
- Steven Feng, Varun Gangal, Jason Wei, Sarath Chandar, Soroush Vosoughi, Teruko Mitamura, and Eduard Hovy. 2021. A survey of data augmentation approaches for nlp. *Findings of the Association for Computational Linguistics: ACL-IJCNLP 2021*.
- Aaron Grattafiori, Abhimanyu Dubey, Abhinav Jauhri, Abhinav Pandey, Abhishek Kadian, Ahmad Al-Dahle, Aiesha Letman, Akhil Mathur, Alan Schelten, Alex Vaughan, Amy Yang, Angela Fan, Anirudh Goyal, Anthony Hartshorn, Aobo Yang, Archi Mitra, Archie Sravankumar, Artem Korenev, Arthur Hinsvark, and 542 others. 2024. The Ilama 3 herd of models. *Preprint*, arXiv:2407.21783.
- Ralph Grishman. 1997. Information extraction: Techniques and challenges. In *International Summer School on Information Extraction*.
- Honghao Gui, Shuofei Qiao, Jintian Zhang, Hongbin Ye, Mengshu Sun, Lei Liang, Jeff Z. Pan, Huajun Chen, and Ningyu Zhang. 2025. Instructie: A bilingual instruction-based information extraction dataset. In *The Semantic Web – ISWC 2024*, pages 59–79, Cham. Springer Nature Switzerland.
- Xianpei Han and Le Sun. 2016. Global distant supervision for relation extraction. In *Proceedings of the AAAI conference on artificial intelligence*, volume 30.
- Geoffrey Hinton. 2015. Distilling the knowledge in a neural network. *arXiv preprint arXiv:1503.02531*.
- Raphael Hoffmann, Congle Zhang, Xiao Ling, Luke Zettlemoyer, and Daniel S. Weld. 2011. Knowledgebased weak supervision for information extraction of overlapping relations. In *Proceedings of the 49th Annual Meeting of the Association for Computational Linguistics: Human Language Technologies*, pages 541–550, Portland, Oregon, USA. Association for Computational Linguistics.
- Martin Josifoski, Marija Sakota, Maxime Peyrard, and Robert West. 2023. Exploiting asymmetry for synthetic training data generation: SynthIE and the case of information extraction. In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing*, pages 1555–1574, Singapore. Association for Computational Linguistics.

824

825

826

827

828

829

830

Omer Levy, Minjoon Seo, Eunsol Choi, and Luke Zettlemoyer. 2017. Zero-shot relation extraction via reading comprehension. In *Proceedings of the 21st Conference on Computational Natural Language Learning (CoNLL 2017)*, pages 333–342, Vancouver, Canada. Association for Computational Linguistics.

717

718

719

721

725

726

729

730

731

734

738

739

740

741

742

743

745

746

747

751

754

762

763

765

767

770

771

772

773

- Dongfang Li, Baotian Hu, and Qingcai Chen. 2022. Prompt-based text entailment for low-resource named entity recognition. In *Proceedings of the 29th International Conference on Computational Linguistics*, pages 1896–1903, Gyeongju, Republic of Korea. International Committee on Computational Linguistics.
- Jiao Li, Yueping Sun, Robin J Johnson, Daniela Sciaky, Chih-Hsuan Wei, Robert Leaman, Allan Peter Davis, Carolyn J Mattingly, Thomas C Wiegers, and Zhiyong Lu. 2016. Biocreative v cdr task corpus: a resource for chemical disease relation extraction. *Database*, 2016.
- Peng Li, Tianxiang Sun, Qiong Tang, Hang Yan, Yuanbin Wu, Xuanjing Huang, and Xipeng Qiu. 2023.
  Codeie: Large code generation models are better few-shot information extractors. *arXiv preprint arXiv:2305.05711*.
- Zixuan Li, Yutao Zeng, Yuxin Zuo, Weicheng Ren, Wenxuan Liu, Miao Su, Yucan Guo, Yantao Liu, Xiang Li, Zhilei Hu, and 1 others. 2024. Knowcoder: Coding structured knowledge into llms for universal information extraction. *arXiv preprint arXiv:2403.07969*.
- Xincheng Liao, Junwen Duan, Yixi Huang, and Jianxin Wang. 2025. RUIE: Retrieval-based unified information extraction using large language model. In *Proceedings of the 31st International Conference on Computational Linguistics*, pages 9640–9655, Abu Dhabi, UAE. Association for Computational Linguistics.
- Yankai Lin, Shiqi Shen, Zhiyuan Liu, Huanbo Luan, and Maosong Sun. 2016. Neural relation extraction with selective attention over instances. In Proceedings of the 54th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers), pages 2124–2133, Berlin, Germany. Association for Computational Linguistics.
- Jingjing Liu, Panupong Pasupat, Scott Cyphers, and James R. Glass. 2013. Asgard: A portable architecture for multilingual dialogue systems. In *IEEE International Conference on Acoustics, Speech and Signal Processing, ICASSP 2013, Vancouver, BC, Canada, May 26-31, 2013*, pages 8386–8390. IEEE.
- Zihan Liu, Yan Xu, Tiezheng Yu, Wenliang Dai, Ziwei Ji, Samuel Cahyawijaya, Andrea Madotto, and Pascale Fung. 2020. Crossner: Evaluating cross-domain named entity recognition.
- Jie Lou, Yaojie Lu, Dai Dai, Wei Jia, Hongyu Lin, Xianpei Han, Le Sun, and Hua Wu. 2023a. Universal information extraction as unified semantic matching.

In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 37, pages 13318–13326.

- Jie Lou, Yaojie Lu, Dai Dai, Wei Jia, Hongyu Lin, Xianpei Han, Le Sun, and Hua Wu. 2023b. Universal information extraction as unified semantic matching. In Proceedings of the Thirty-Seventh AAAI Conference on Artificial Intelligence and Thirty-Fifth Conference on Innovative Applications of Artificial Intelligence and Thirteenth Symposium on Educational Advances in Artificial Intelligence, AAAI'23/IAAI'23/EAAI'23. AAAI Press.
- Mike Mintz, Steven Bills, Rion Snow, and Dan Jurafsky. 2009. Distant supervision for relation extraction without labeled data. In *Proceedings of the Joint Conference of the 47th Annual Meeting of the ACL and the 4th International Joint Conference on Natural Language Processing of the AFNLP*, pages 1003– 1011.
- Ying Mo, Jiahao Liu, Jian Yang, Qifan Wang, Shun Zhang, Jingang Wang, and Zhoujun Li. 2024. C-ICL: Contrastive in-context learning for information extraction. In *Findings of the Association for Computational Linguistics: EMNLP 2024*, pages 10099– 10114, Miami, Florida, USA. Association for Computational Linguistics.
- Abiola Obamuyide and Andreas Vlachos. 2018. Zeroshot relation classification as textual entailment. In *Proceedings of the First Workshop on Fact Extraction and VERification (FEVER)*, pages 72–78, Brussels, Belgium. Association for Computational Linguistics.
- Long Ouyang, Jeff Wu, Xu Jiang, Diogo Almeida, Carroll L. Wainwright, Pamela Mishkin, Chong Zhang, Sandhini Agarwal, Katarina Slama, Alex Ray, John Schulman, Jacob Hilton, Fraser Kelton, Luke Miller, Maddie Simens, Amanda Askell, Peter Welinder, Paul Christiano, Jan Leike, and Ryan Lowe. 2022. Training language models to follow instructions with human feedback. *Preprint*, arXiv:2203.02155.
- Chaoxu Pang, Yixuan Cao, Qiang Ding, and Ping Luo. 2023. Guideline learning for in-context information extraction. In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing*, pages 15372–15389, Singapore. Association for Computational Linguistics.
- Guilherme Penedo, Hynek Kydlíček, Loubna Ben allal, Anton Lozhkov, Margaret Mitchell, Colin Raffel, Leandro Von Werra, and Thomas Wolf. 2024. The fineweb datasets: Decanting the web for the finest text data at scale. In *The Thirty-eight Conference on Neural Information Processing Systems Datasets and Benchmarks Track.*
- Sameer Pradhan, Alessandro Moschitti, Nianwen Xue, Hwee Tou Ng, Anders Björkelund, Olga Uryupina, Yuchen Zhang, and Zhi Zhong. 2013. Towards robust linguistic analysis using ontonotes. In *Proceedings* of the Seventeenth Conference on Computational Natural Language Learning, pages 143–152.

887

888

927

928

929

832

831

- 842 844 845 847 849 850
- 851
- 855
- 856
- 857 858

870

873

- 874
- 875 876

878 879

- Yunjia Qi, Hao Peng, Xiaozhi Wang, Bin Xu, Lei Hou, and Juanzi Li. 2024. Adelie: Aligning large language models on information extraction. arXiv preprint arXiv:2405.05008.
- Colin Raffel, Noam Shazeer, Adam Roberts, Katherine Lee, Sharan Narang, Michael Matena, Yanqi Zhou, Wei Li, and Peter J. Liu. 2020. Exploring the limits of transfer learning with a unified text-to-text transformer. J. Mach. Learn. Res., 21(1).
- Oscar Sainz, Oier Lopez de Lacalle, Gorka Labaka, Ander Barrena, and Eneko Agirre. 2021. Label verbalization and entailment for effective zeroand few-shot relation extraction. arXiv preprint arXiv:2109.03659.
- Oscar Sainz, Iker García-Ferrero, Rodrigo Agerri, Oier Lopez de Lacalle, German Rigau, and Eneko Agirre. 2024. GoLLIE: Annotation guidelines improve zero-shot information-extraction. In The Twelfth International Conference on Learning Representations.
- Mihai Surdeanu, Julie Tibshirani, Ramesh Nallapati, and Christopher D Manning. 2012. Multi-instance multi-label learning for relation extraction. In Proceedings of the 2012 joint conference on empirical methods in natural language processing and computational natural language learning, pages 455-465.
- Teknium. 2023. Openhermes 2.5: An open dataset of synthetic data for generalist llm assistants.
- Erik F. Tjong Kim Sang and Fien De Meulder. 2003. Introduction to the CoNLL-2003 shared task: Language-independent named entity recognition. In Proceedings of the Seventh Conference on Natural Language Learning at HLT-NAACL 2003, pages 142-147.
- Christopher Walker, Stephanie Strassel, Julie Medero, and Kazuaki Maeda. 2006. ACE 2005 multilingual training corpus LDC2006T06.
- Chenguang Wang, Xiao Liu, Zui Chen, Haoyun Hong, Jie Tang, and Dawn Song. 2021. Zero-shot information extraction as a unified text-to-triple translation. In Proceedings of the 2021 Conference on Empirical Methods in Natural Language Processing, pages 1225-1238, Online and Punta Cana, Dominican Republic. Association for Computational Linguistics.
- Xiao Wang, Weikang Zhou, Can Zu, Han Xia, Tianze Chen, Yuansen Zhang, Rui Zheng, Junjie Ye, Qi Zhang, Tao Gui, Jihua Kang, Jingsheng Yang, Siyuan Li, and Chunsai Du. 2023. Instructuie: Multitask instruction tuning for unified information extraction. Preprint, arXiv:2304.08085.
- Xiang Wei, Xingyu Cui, Ning Cheng, Xiaobin Wang, Xin Zhang, Shen Huang, Pengjun Xie, Jinan Xu, Yufeng Chen, Meishan Zhang, Yong Jiang, and Wenjuan Han. 2024. Chatie: Zero-shot information extraction via chatting with chatgpt. Preprint, arXiv:2302.10205.

- Xiang Wei, Xingyu Cui, Ning Cheng, Xiaobin Wang, Xin Zhang, Shen Huang, Pengjun Xie, Jinan Xu, Yufeng Chen, Meishan Zhang, and 1 others. 2023. Zero-shot information extraction via chatting with chatgpt. arXiv preprint arXiv:2302.10205.
- Chaojun Xiao, Yuan Yao, Ruobing Xie, Xu Han, Zhiyuan Liu, Maosong Sun, Fen Lin, and Leyu Lin. 2020. Denoising relation extraction from documentlevel distant supervision. In Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing (EMNLP), pages 3683-3688, Online. Association for Computational Linguistics.
- Derong Xu, Wei Chen, Wenjun Peng, Chao Zhang, Tong Xu, Xiangyu Zhao, Xian Wu, Yefeng Zheng, Yang Wang, and Enhong Chen. 2024a. Large language models for generative information extraction: A survey. Frontiers of Computer Science, 18(6):186357.
- Jun Xu, Mengshu Sun, Zhiqiang Zhang, and Jun Zhou. 2024b. ChatUIE: Exploring chat-based unified information extraction using large language models. In Proceedings of the 2024 Joint International Conference on Computational Linguistics, Language Resources and Evaluation (LREC-COLING 2024), pages 3146-3152, Torino, Italia. ELRA and ICCL.
- Zhangchen Xu, Fengqing Jiang, Luyao Niu, Yuntian Deng, Radha Poovendran, Yejin Choi, and Bill Yuchen Lin. 2025. Magpie: Alignment data synthesis from scratch by prompting aligned LLMs with nothing. In The Thirteenth International Conference on Learning Representations.
- Urchade Zaratiana, Nadi Tomeh, Pierre Holat, and Thierry Charnois. 2023. Gliner: Generalist model for named entity recognition using bidirectional transformer. Preprint, arXiv:2311.08526.
- Yuhao Zhang, Victor Zhong, Danqi Chen, Gabor Angeli, and Christopher D Manning. 2017. Position-aware attention and supervised data improve slot filling. In Conference on empirical methods in natural language processing.
- Wenxuan Zhou, Sheng Zhang, Yu Gu, Muhao Chen, and Hoifung Poon. 2023. Universalner: Targeted distillation from large language models for open named entity recognition.

# A Implementation Details

930

931

932

934

935 936

938

941

943

949

951 952

953

955

957

959

960 961

962

963

965

966

967

968

In this section, we further detail the whole process of GUIDEX. In Section A.1 we explain how we built the dataset, focusing on the hyperparameters used, the multi-step generation prompts, and the filtering process that ensures consistent annotations. In A.2 we describe the hyperparameters for both GUIDEX<sub>FT</sub> and Gold<sub>FT</sub>, outlining how they were tuned to achieve the outcomes showcased on Section 6.

#### A.1 GUIDEX Dataset generation

The GUIDEX dataset was built through a structured multi-step process designed to ensure high-quality, consistent annotations and guidelines. The dataset generation pipeline follows a systematic approach involving prompt-based multi-step generation, filtering for consistency, and the use of hyperparameter tuning to optimize the outputs.

Model and Hyperparameters. The synthetic dataset was generated using LLaMA 3.1-70B Instruct, leveraging vLLM for efficient inference. The detailed hyperparameter settings used in the generation process are available in Table 5.

Multi-Step Generation Process. To ensure structured and meaningful outputs, the dataset was built using a four-step generation pipeline. The first step involved extracting key points from the input text, reducing redundancy while preserving essential information. The second step transformed this summarized content into a structured JSON representation, ensuring a consistent and standardized format. Next, annotation guidelines were generated to define the expected attributes and structure, facilitating consistency across all annotations. Finally, the model extracted instances based on these guidelines, ensuring that the final dataset adhered to a coherent format. The complete set of prompts used for each step can be found in Figure 3.

### A.2 GUIDEX<sub>FT</sub> & Gold<sub>FT</sub>

This section summarizes the fine-tuning configu-969 rations for GUIDEX<sub>FT</sub> and Gold<sub>FT</sub>. Both models 970 use LLaMa 3.1-8B with 4-bit LoRA, AdamW op-971 timization, and a cosine scheduler. GUIDEX<sub>FT</sub> 973 supports longer sequences (8192 tokens) as it is suited for document-level input texts, and employs 974 gradient accumulation, while Gold<sub>FT</sub> uses a larger 975 per-device batch size without accumulation. Training is conducted on 2× A100 (80GB) GPUs with 977

Category	Hyperparameter	Value
Model Setup	Model Name Tokenizer Dtype Max Seq. Length Tensor Parallel Size	LLaMa 3.1-70B Instruct LLaMa 3.1-70B Instruct bfloat16 8192 tokens 2
Generation Config	Temperature Top-p Max New Tokens	0.7 0.95 1024
Batching	Batch Size Processing Mode	32 Batched prompts via vLLM
Hardware	GPUs Used CPU per Task	4× A100 (80GB) 16

Table 5: Hyperparameter Settings for the GUIDEX Synthetic Data Generation Stage.

DeepSpeed Zero-3, differing in sequence length, batch sizes, and the number of training epochs. A full overview is provided in Table 6.

#### I DOCUMENT SUMMARIZATION PROMPT

Use bullet points to summarize the main ideas of the following text, keeping the most important information. Text: '{text}'. Summarize these points concisely.

#### II STRUCTURED REPRESENTATION PTOMPT

Based on the extracted summary and the original text, synthesize the information into a JSON output.Keep it as less verbose as possible. The strings in the JSON must match the original text.The name of each key should be properly chosen and general, similar fields should be merged.

You should populate all the attributes and be as concise as possible. The attributes can't be populated with full sentences; they must be as short as possible. Remember that it should match the contents of the text accurately.

The only thing that you should return is a single JSON that contains the required content, nothing else, no text introducing the JSON, no text saying how you hope it is ok. JUST THE JSON.

#### **III** GUIDELINE GENERATION PROMPT

Based on the JSON output, the summary and the original text, generate annotation guidelines that include: 1. A high-quality, complete, and extensive description that is long enough. 2. The expected format for each field.
Then, turn these annotations into a Python file consisting of Python dataclass objects.Description of the class should be given as a docstring and descriptions of the attributes must be given as comments, without examples. Create a class that wraps all the information together. Return only one Python file that contains these annotation guidelines. The kind of output I am expecting is similar (but not limited) to this, but substituting the placeholders with the specifics of the text being discussed, and creating as many classes as needed and naming them properly:
```python from dataclasses import dataclass from typing import List, Optional
@dataclass class EntityA: """
A generic but long enough description for EntityA, explaining its purpose and characteristics in a general context without specific details. """
identifier: str
A brief explanation of what the identifier represents in a general sense.
attribute1: str # A short comment explaining this attribute generically attribute2: List[str] """
A multi-line comment explaining what this list typically contains and its significance to EntityA. """
# Add more attributes as needed
@dataclass class EntityB: """
A generic description for EntityB, explaining its purpose and characteristics in a general context without specific details. """
mention: str
An explanation of what the mention represents for EntityB.
<pre>date: str # A comment about what this date signifies location: str # A comment about what this location represents element: str # A comment about what this element represents # Add more attributes as needed</pre>
IV INSTANCE EXTRACTION PROMPT

Based on the annotation guidelines, you will provide a Python list called `result\_instances` containing instances of the dataclasses based on the
information in the text. Be as concise as possible when extracting the instances, which should be single words or numbers when possible, not
longer. You should only provide the Python `result\_instances` list with the instances, nothing else. Do not provide explanations nor extra data
apart from what's contained in the `result\_instances` list.
The kind of output I am expecting is similar (but not limited) to this, but substituting the placeholders with the specifics of the text being
discussed:
```python
result\_instances = [
EntityB(name="EntityB\_Name1", date="Date1", location1="Location1A", element="element1"),
EntityA(identifier="EntityA\_ID1", attribute1="AttributeValue1", attribute2=["Item1", "Item3"])
]
...

Figure 3: GUIDEX follows a multi-step prompting pipeline which allows for the creation of the synthetic guidelines and annotations that conform GUIDEX and are used for  $GUIDEX_{FT}$ .

| Category               | Hyperparameter                                                          | GUIDEX <sub>FT</sub>                                                                                          | Gold <sub>FT</sub>                                                                                    |
|------------------------|-------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------|
| Model & Quantization   | Base Model                                                              | LLaMa 3.1-8B                                                                                                  | LLaMa 3.1-8B                                                                                          |
|                        | Quantization                                                            | 4-bit LoRA                                                                                                    | 4-bit LoRA                                                                                            |
|                        | LoRA Rank (r)                                                           | 128                                                                                                           | 128                                                                                                   |
|                        | LoRA α                                                                  | 256                                                                                                           | 256                                                                                                   |
|                        | LoRA Dropout                                                            | 0.08                                                                                                          | 0.05                                                                                                  |
|                        | Dtype                                                                   | bfloat16                                                                                                      | bfloat16                                                                                              |
| Optimization           | Optimizer<br>Learning Rate<br>Weight Decay<br>Scheduler<br>Warmup Steps | $\begin{array}{c c} A damW \\ 3 \times 10^{-4} \\ 0.001 \\ Cosine \\ 10\% \text{ of total steps} \end{array}$ | $\begin{array}{c} A damW\\ 3\times10^{-4}\\ 0.001\\ Cosine\\ 10\% \text{ of total steps} \end{array}$ |
| Batching & Seq. Length | Per-device Batch Size                                                   | 4                                                                                                             | 16                                                                                                    |
|                        | Gradient Accumulation Steps                                             | 2                                                                                                             | None                                                                                                  |
|                        | Effective Batch Size                                                    | 8                                                                                                             | 16                                                                                                    |
|                        | Max Sequence Length (tokens)                                            | 8192                                                                                                          | 2048                                                                                                  |
| Epochs & Checkpoints   | Epochs                                                                  | 3                                                                                                             | 1                                                                                                     |
|                        | Checkpoint Strategy                                                     | End of each epoch                                                                                             | End of each epoch                                                                                     |
| Hardware               | GPUs Used                                                               | 2× A100 (80GB)                                                                                                | 2× A100 (80GB)                                                                                        |
|                        | Multi-GPU Support                                                       | DeepSpeed Zero-3                                                                                              | DeepSpeed Zero-3                                                                                      |
|                        | CPU per Task                                                            | 22                                                                                                            | 22                                                                                                    |

Table 6: Hyperparameter Settings for  $\ensuremath{\mathsf{GUIDEX_{FT}}}$  and  $\ensuremath{\mathsf{Gold_{FT}}}.$