

Neural incomplete factorization: learning preconditioners for the conjugate gradient method

Anonymous authors

Paper under double-blind review

Abstract

The convergence of the conjugate gradient method to solve large-scale and sparse linear equation systems depends on the conditioning of the system matrix, which can be improved by preconditioning. In this paper, we develop a computationally efficient data-driven approach to accelerate the generation of effective preconditioners. We, therefore, replace the typically hand-engineered preconditioners by the output of graph neural networks. Optimizing the condition number of the linear system directly is computationally infeasible. Instead, our method generates an incomplete factorization of the matrix and is, therefore, referred to as neural incomplete factorization (NeuralIF). For efficient training, we utilize a stochastic approximation of the Frobenius loss which only requires matrix-vector multiplications. At the core of our method is a novel message-passing block, inspired by sparse matrix theory, that aligns with the objective of finding a sparse factorization of the matrix. We evaluate our proposed method on both synthetic problem instances and on problems arising from the discretization of the Poisson equation on varying domains. Our experiments show that by utilizing data-driven preconditioners within the conjugate gradient method we are able to speed up the convergence of the iterative procedure.

1 Introduction

Solving large-scale systems of linear equations is a fundamental problem in computing science. Available solving techniques can be divided into *direct* and *iterative* methods. While direct methods, which rely on computing the inverse or factorizing the matrix, obtain accurate solutions they do not scale well for large-scale problems. Therefore, iterative methods, which repeatedly refine an initial guess to approach the exact solution, are used in practice when an approximation of the solution is sufficient (Golub & Van Loan, 2013).

The conjugate gradient method is a classical iterative method for solving equation systems of the form $\mathbf{Ax} = \mathbf{b}$ where the matrix \mathbf{A} is symmetric and positive definite. Further, the matrix is typically assumed to be sparse in the sense that it only contains few non-zero elements (Carson et al., 2023). Problems of this form arise naturally in the discretization of elliptical PDEs, such as the Poisson equation, and a wide range of optimization problems, such as quadratic programs (Pearson & Pestana, 2020; Potra & Wright, 2000). The convergence speed of the method thereby depends on the spectral properties of the matrix \mathbf{A} (Golub & Van Loan, 2013). Therefore, it is common practice to improve the spectral properties of the equation system before solving it through the means of preconditioning. Despite the critical importance of preconditioners for practical performance, it has proven notoriously difficult to find good designs for a general class of problems (Saad, 2003).

Recent advances in data-driven optimization combine classical optimization algorithms with data-driven methods. A common approach is replacing hand-crafted heuristics with parameterized functions such as neural networks that are trained against data (Banert et al., 2024; Chen et al., 2022). In this work, we combine this methodology with results known from sparse matrix theory by representing the matrix of the linear equation system as a graph that forms the input to a graph neural network. We then train the network to predict a suitable preconditioner for the given input matrix.

To train our model in a computationally feasible way we are inspired by the incomplete factorization methods. These methods, which include the popular incomplete Cholesky factorization, compute a sparse approximation

of the Cholesky factor of the matrix \mathbf{A} that is applied to precondition the linear system (Golub & Van Loan, 2013; Scott & Tũma, 2023). However, these methods can suffer from breakdown, require significant time to compute, and are hard to parallelize on modern hardware (Benzi, 2002; Naumov, 2012). We overcome some of these limitations by introducing a scalable way to compute efficient preconditioners that do not suffer from breakdown. Our training scheme relies on matrix-vector multiplications only which can be implemented efficiently and allows us to train the method on large-scale problems. Further, we show how to control the obtained sparsity pattern of the learned preconditioner to obtain flexible preconditioning matrices (Saad, 2003).

In contrast to the NeuralPCG model introduced by Li et al. (2023), our model utilizes insights from graph theory to motivate the underlying computational framework and aligns with the training objective. This allows us to obtain more effective preconditioners – in the sense of required iterations for the preconditioned system – using a smaller model. Reducing the number of parameters, in turn, leads to a faster inference time which is critical to amortize the cost of training and applying the neural network. Furthermore, our method is fully self-supervised while previous data-driven preconditioners rely on the solution of the linear equation system during training which increases the time required to generate a suitable dataset significantly.

In summary, we introduce (i) a novel GNN architecture and (ii) an efficient way to compute the loss function, tailored to obtaining effective incomplete factorization preconditioners; finally, (iii) we show how to obtain flexible sparsity patterns of the output within this framework. Our data-driven method exhibits state-of-the-art results for data-driven preconditioners and performs on par with the baseline incomplete factorization methods.

2 Background

After introducing the conjugate gradient method, we briefly summarize the basics of graph neural networks which form the computational backend for our proposed method.

2.1 Conjugate gradient method

The conjugate gradient method (CG) is a well-established iterative method for solving symmetric and positive-definite (spd denoted by S_n^{++}) systems of linear equations of the form $\mathbf{A}\mathbf{x} = \mathbf{b}$. The algorithm does not require any matrix-matrix multiplications, making CG particularly effective when dealing with large-scale and sparse matrices (Saad, 2003). The method creates a sequence of search directions \mathbf{p}_i from the corresponding Krylov subspace which are orthogonal in \mathbf{A} -norm to each other i.e. $\mathbf{p}_i^\top \mathbf{A} \mathbf{p}_j = 0$ for $i \neq j$. In other words, the search directions are *conjugate* to each other. These search directions are used to update the solution iterate \mathbf{x}_k . Since it is possible to compute the optimal step size in closed form for each search direction, the method is guaranteed to converge within n steps (Shewchuk, 1994). Typically, the initial search direction \mathbf{p}_0 is chosen as the *gradient* of the corresponding quadratic program given by $\mathbf{b} - \mathbf{A}\mathbf{x}_0$ (Nazareth, 2009). The iterative scheme is shown in Algorithm 1.

Convergence The convergence of CG to the true solution \mathbf{x}_\star depends on the spectral properties of the matrix \mathbf{A} . Using the condition number $\kappa(\mathbf{A})$, a linear bound of the error in the number of taken CG steps k is given by (Carson et al., 2023)

$$\|\mathbf{x}_\star - \mathbf{x}_k\|_{\mathbf{A}} \leq 2 \|\mathbf{x}_\star - \mathbf{x}_0\|_{\mathbf{A}} \left(\frac{\sqrt{\kappa(\mathbf{A})} - 1}{\sqrt{\kappa(\mathbf{A})} + 1} \right)^k. \quad (1)$$

However, in practice the CG method often converges significantly faster and the convergence also depends on the distribution of eigenvalues and the initial residual. Clustered eigenvalues hereby lead to faster convergence. Further, a large condition number needs not imply a slow convergence of the iterative scheme (Carson et al., 2023). A common approach to accelerate the convergence is to precondition the linear equation system to improve its spectral properties leading to faster convergence (Benzi, 2002).

Preconditioning The underlying idea of preconditioning is to compute a cheap approximation of the inverse of \mathbf{A} that is used to improve the convergence properties. A common way to achieve this is to approximate the matrix $\mathbf{P} \approx \mathbf{A}$ with an easily invertible preconditioning matrix \mathbf{P} . This allows us to compute the

Algorithm 1 Preconditioned conjugate gradient method (Nocedal & Wright, 1999)

```

1: Input: System of linear equations  $\mathbf{A} \in S_n^{++}$ ,  $\mathbf{b} \in \mathbb{R}^n$ , Preconditioner  $\mathbf{P} \approx \mathbf{A}$ ,  $\mathbf{P} \in S_n^{++}$ 
2: Output: Solution to the linear equation system  $\hat{\mathbf{x}}_*$ 
3: Initialize starting guess  $\mathbf{x}_0$ 
4:  $\mathbf{r}_0 = \mathbf{b} - \mathbf{A}\mathbf{x}_0$ 
5: Solve  $\mathbf{P}\mathbf{y}_0 = \mathbf{r}_0$  and set  $\mathbf{p}_0 = \mathbf{y}_0$ 
6: for  $k = 0, 1, \dots$ , until convergence do
7:    $a_k = \langle \mathbf{r}_k, \mathbf{y}_k \rangle / \langle \mathbf{A}\mathbf{p}_k, \mathbf{p}_k \rangle$ 
8:    $\mathbf{x}_{k+1} = \mathbf{x}_k + a_k \mathbf{p}_k$ 
9:    $\mathbf{r}_{k+1} = \mathbf{r}_k - a_k \mathbf{A}\mathbf{p}_k$ 
10:  Solve  $\mathbf{P}\mathbf{y}_{k+1} = \mathbf{r}_{k+1}$ 
11:   $\beta_k = \langle \mathbf{r}_{k+1}, \mathbf{y}_{k+1} \rangle / \langle \mathbf{r}_k, \mathbf{y}_k \rangle$ 
12:   $\mathbf{p}_{k+1} = \mathbf{y}_{k+1} + \beta_k \mathbf{p}_k$ 
13: return  $\mathbf{x}_k$ 

```

preconditioned search directions for each iteration in line 5 and line 10 of Algorithm 1 efficiently. This can be achieved by constructing a (block) diagonal preconditioner or finding a (triangular) factorization (Benzi, 2002).

Finding a good preconditioner requires a trade-off between the time required to compute the preconditioner and the resulting speed-up in convergence (Golub & Van Loan, 2013). The Jacobi preconditioner simply approximates \mathbf{A} with a diagonal matrix. The incomplete Cholesky (IC) preconditioner is a more advanced, but widely adopted, method. As the name suggests, the idea is to approximate the Cholesky decomposition of the matrix. The IC(0) preconditioner restricts the non-zero elements in the obtained triangular factor \mathbf{L} to exactly the non-zero elements in the lower triangular part of \mathbf{A} . Thus, no fill-ins during the factorization are allowed. More general versions allow additional fill-ins of the matrix based on the position or the value of the matrix elements (Benzi, 2002; Scott & Tuma, 2023) or allow flexible positions of non-zero elements such as the modified incomplete Cholesky (MIC) preconditioner (Lin & Moré, 1999).

Finding new preconditioners is an active research area but is often done on a case-by-case basis. Thus, newly developed methods are often tailor-made for specific problem classes and often do not generalize to new problem domains (Benzi, 2002; Pearson & Pestana, 2020).

Stopping criterion In practice, due to numerical rounding errors, the residual is only approaching but never reaching zero. Further, the true solution \mathbf{x}_* is typically not available and therefore, equation (1) can not be used as a stopping criterion for the algorithm either. Instead, the relative residual error $\|\mathbf{r}\|_2$ which is computed recursively in line 9 of Algorithm 1 is widely adopted (Shewchuk, 1994).

2.2 Graph neural networks

Graph neural networks (GNN) belong to an emerging family of neural network architectures that are well-suited to many real-world problems which possess a natural graph structure (Veličković, 2023).

A graph $\mathcal{G} = (V, E)$ is a tuple consisting of a set of nodes V and directed edges E connecting two nodes in the graph $E \subseteq V \times V$. We assign every node $v \in V$ a node feature vector $\mathbf{x}_v \in \mathbb{R}^n$ and respectively every directed edge e_{ij} , connecting nodes i and j , an edge feature vector $\mathbf{z}_{ij} \in \mathbb{R}^m$.

The widely adopted message-passing GNNs consist of multiple layers updating the node and edge feature vectors of the graph iteratively using permutation invariant aggregations over the neighborhoods and learned update functions (Bronstein et al., 2021). Here, we follow the blueprint presented Battaglia et al. (2018) to describe the update functions for a simple message-passing GNN layer. In each layer l the edge features are updated first by the network computing the features of the next layer $l + 1$ as

$$\mathbf{z}_{ij}^{(l+1)} = \phi_{\theta_z^{(l)}} \left(\mathbf{z}_{ij}^{(l)}, \mathbf{x}_i^{(l)}, \mathbf{x}_j^{(l)} \right), \quad (2)$$

where ϕ is a parameterized function. The outputs of this function are also referred to as *messages*. Then, for each node $i \in V$ the features from its neighboring edges, in other words, the incoming messages, are aggregated using a suitable aggregation function. Typical choices include sum, mean and max aggregations. Any such permutation invariant aggregation function is denoted here by \oplus . The aggregation of incoming messages over the neighborhood \mathcal{N} of node n_i , which is defined as the set of adjacent nodes in the graph $\mathcal{N}(i) = \{j \mid (i, j) \in E\}$, is computed as

$$\mathbf{m}_i^{(l+1)} = \bigoplus_{j \in \mathcal{N}(i)} \mathbf{z}_{ji}^{(l+1)}. \quad (3)$$

Note that the neighborhood structure is typically kept fixed in GNNs and no edges are added or removed between the different layers. The final step of the message-passing GNN layer is updating the node features as

$$\mathbf{x}_i^{(l+1)} = \psi_{\theta_x^{(l)}} \left(\mathbf{x}_i^{(l)}, \mathbf{m}_i^{(l+1)} \right). \quad (4)$$

The node and edge update functions ϕ and ψ are parameterized using neural networks. The equations (2)–(4) describe the iterative scheme of message passing that is implemented by many popular GNNs. By choosing a permutation invariant function in the neighborhood aggregation step (3) and since the update functions only act locally on the node and edge features, the learned function represented by the GNN itself is permutation equivariant and can handle inputs of varying sizes (Battaglia et al., 2018).

Many known algorithms share a common computational structure with this message-passing scheme making GNNs a natural parameterization for learned variants. This correspondence is typically referred to as algorithmic alignment in the literature (Dudzik & Veličković, 2022).

3 Method

We formulate the learning problem for a data-driven preconditioner and derive an efficient loss function. Then, we introduce a problem-tailored GNN architecture, and demonstrate how to extend the framework to yield flexible sparsity patterns.

Learning problem Our final goal is to learn a mapping $f_\theta : S_n^{++} \rightarrow S_n^{++}$ that takes an spd matrix \mathbf{A} and predicts a suitable preconditioner \mathbf{P} that improves the spectral properties of the system – and therefore also the convergence behavior of the conjugate gradient method.

In order to ensure convergence, the output of the learned mapping needs to be spd and is in practice often required to be sparse due to resource constraints. To ensure these properties, we restrict the mapping to lower triangular matrices with strictly positive elements on the diagonal denoted as \mathcal{L}_n^+ . We then learn a mapping $\Lambda_\theta : S_n^{++} \rightarrow \mathcal{L}_n^+$. This can be achieved by using a suitable activation function and network architecture as discussed later. The elements in \mathcal{L}_n^+ are guaranteed to be invertible and the computation thereof is computationally efficient since using forward-backward substitution requires only $\mathcal{O}(n^2)$ operations (Golub & Van Loan, 2013). However, for sparse matrices the triangular system, that needs to be solved to obtain the preconditioned search direction in line 5 and 10 within Algorithm 1, can often be solved more efficiently and scales with the number of non-zero elements (Davis et al., 2016). The parameterized function outputs a factorization of the preconditioning matrix that can be obtained via

$$\mathbf{P}_\theta(\mathbf{A}) = \Lambda_\theta(\mathbf{A})\Lambda_\theta(\mathbf{A})^\top, \quad (5)$$

which is a spd matrix if the diagonal elements of the triangular matrix are strictly positive i.e. $\Lambda_\theta(\mathbf{A}) \in \mathcal{L}_n^+$ and can be easily inverted. To improve the convergence properties we aim to improve the condition number of the preconditioned system. However, computing the condition number scales very poorly for large problems as it requires $\mathcal{O}(n^3)$ floating-point operations. Therefore, we can not optimize the spectral properties of the matrix directly. Instead, we are inspired by incomplete factorization methods (Benzi, 2002). These methods try to find a sparse approximation of the Cholesky factor of the input matrix while remaining computationally tractable. In order to learn a good approximation model we assume matrices of interest are generated by a matrix-valued random variable \mathbb{A} with an unknown distribution describing the underlying class of problems.

We train our learned preconditioner to approximately solve the matrix factorization optimization problem with additional sparsity constraints. The training objective for the data-driven model is given by

$$\hat{\boldsymbol{\theta}} \in \arg \min_{\boldsymbol{\theta}} \mathbb{E}_{\mathbf{A} \sim \mathbb{A}} [\|\Lambda_{\boldsymbol{\theta}}(\mathbf{A})\Lambda_{\boldsymbol{\theta}}(\mathbf{A})^{\top} - \mathbf{A}\|_F] \quad (6a)$$

$$\text{s.t. } \Lambda_{\boldsymbol{\theta}}(\mathbf{A})_{ij} = 0 \text{ if } \mathbf{A}_{ij} = 0, \Lambda_{\boldsymbol{\theta}}(\mathbf{A}) \in \mathcal{L}_n^+. \quad (6b)$$

Equation (6a) aims to minimize the distance between the learned factorization and the input matrix using the Frobenius norm distance. It is, however, also possible to use a different distance metric instead (Vemulapalli & Jacobs, 2015). When considering more advanced preconditioners, the no fill-in sparsity constraint (6b) can be relaxed slightly allowing more non-zero elements in the preconditioner. However, it is desirable that the required storage for the preconditioner is known beforehand and does not increase too much compared to the original system (Benzi, 2002).

Scalable training A practical problem with objective (6a) is that we cannot compute the expectation since we lack access to the distribution of \mathbb{A} . On the other hand, we have access to training data $\mathbf{A}_1, \mathbf{A}_2, \dots, \mathbf{A}_n \sim \mathbb{A}$, so we consider the empirical counterpart of equation (6) – empirical risk minimization – where the intractable expected value is replaced by the sample mean which we can optimize using stochastic gradient descent to obtain an approximation of $\hat{\boldsymbol{\theta}}$.

To enhance computational efficiency we circumvent computing the matrix-matrix multiplication $\Lambda_{\boldsymbol{\theta}}(\mathbf{A})\Lambda_{\boldsymbol{\theta}}(\mathbf{A})^{\top}$ in the objective, by approximating the Frobenius norm using Hutchinson’s trace estimator (Hutchinson, 1989)

$$\|\mathbf{B}\|_F^2 = \text{trace}(\mathbf{B}^{\top}\mathbf{B}) \approx \frac{1}{m} \sum_{i=1}^m \mathbf{w}_i^{\top} \mathbf{B}^{\top} \mathbf{B} \mathbf{w}_i, \quad (7)$$

where the elements in the vector \mathbf{w}_i are iid normal distributed random variables. By setting $\mathbf{B} = \Lambda_{\boldsymbol{\theta}}(\mathbf{A})\Lambda_{\boldsymbol{\theta}}(\mathbf{A})^{\top} - \mathbf{A}$ and taking the square root of equation (7), we obtain an unbiased estimator of the loss which requires only matrix-vector products (Martinsson & Tropp, 2020). The resulting objective is similar to the loss proposed by Li et al. (2023) but does not rely on computing the true solution to the problem beforehand making it computationally more efficient as it avoids solving linear equation systems before the training. We show that using the approximation leads to similar results as training using the full Frobenius norm as a loss in Appendix C.2.

Model architecture Due to the strong connection of graph neural networks with matrices and numerical linear algebra (Moore et al., 2023), graph neural networks are a natural choice to parameterize the function $\Lambda_{\boldsymbol{\theta}}$. Furthermore, this allows us to enforce the sparsity constraints (6b) directly through the network architecture and avoids scalability issues arising in other network architectures since GNNs can exploit the sparse problem structure.

On a high level, we interpret the matrix \mathbf{A} of the input problem as the adjacency matrix of the corresponding graph. Thus, the nodes of the graph represent the columns/rows – the system is symmetric – of the input matrix and are augmented with an additional feature vector. The edges of the corresponding graph are the non-zero elements in the adjacency matrix. This transformation from a matrix to a graph is known as Coates graph (Coates, 1959; Grementieri & Galeone, 2022). We use a total of eight node features related to sparsity structure and diagonal dominance of the matrix (Cai & Wang, 2019; Tang et al., 2022). For the details about the network architecture we refer to Appendix B.

Since our learned function $\Lambda_{\boldsymbol{\theta}}$ is mapping to a lower-triangular matrix, we implicitly fix an ordering of the nodes in the graph. To align our computational framework to the underlying objective of finding a sparse factorization, we introduce a novel GNN block that extends the Coates graph representation to execute the feature updates. Instead of using matrix \mathbf{A} directly as the underlying structure for message passing, we only use the lower triangular part in the first step to update node and edge features in the graph. This lower triangular structure also aligns with sparsity pattern of the final output $\Lambda_{\boldsymbol{\theta}}$. The corresponding graph used for message passing is depicted in Figure 1.

In a second step, the message-passing scheme is executed over the upper triangular part of the matrix \mathbf{A} . However, the edge features between the two consecutive layers are shared, in other words $\mathbf{z}_{ij}^{(n)} = \mathbf{z}_{ji}^{(n)}$. After




Figure 1: Classical linear algebra (left) and lower triangular graph (right) representation of a spd matrix. Each node corresponds to the labeled row/column of the matrix. The upper triangular representation is obtained by flipping the edges. Color is used to visualize edge and matrix element correspondence. Diagonal elements are in bold.

the two message-passing steps are computed, the original matrix \mathbf{A} is used to augment the edge features by introducing skip connections. The block implementation shares node features across the layer, resulting in an equivalent Coates graph representation with two distinct set of edges \mathbf{L} and \mathbf{L}^\top . For each set of edges, an individual message-passing step is performed which consists of the node update, neighborhood aggregation, and edge update as described in Section 2.2. The detailed forward pass through the network architecture is described in Appendix B.

The underlying motivation of the message-passing block introduced in the previous paragraph is the fact that matrix multiplication can be represented in graph format by concatenating the graph representations of the two factors. Each element in the product matrix can then be computed as the sum of the weights connecting the two corresponding nodes in the concatenated graphs. The skip connections are introduced as they represent an element-wise addition of the two matrices (Doob, 1984; Brualdi & Cvetkovic, 2008). Furthermore, the proposed splitting into lower and upper parts directly encodes the ordering used to obtain the triangular output into the network structure.

Our model consists of three blocks resulting in a total of six message-passing steps. To enforce the positive definiteness of the learned preconditioner the final diagonal elements of the output are transformed via

$$\Lambda_{\theta}(\mathbf{A})_{ii} = \exp\left(\frac{1}{2} \cdot z_{ii}^{(N)}\right). \quad (8)$$

This activation function forces the diagonal elements to be strictly positive. Multiplying the final edge embedding by the constant term one half before applying the non-linear activation avoids numerical problems and, based on our experiments, improves the convergence during training. Due to the connection to incomplete factorization methods, we refer to our model as neural incomplete factorization (NeuralIIF).

Additional fill-ins and droppings Similar to the incomplete Cholesky method with additional fill-ins (Saad, 2003), processing on the graph can be applied to obtain both static and dynamic sparsity patterns for the learned preconditioner. Static level of fill-ins can be obtained by adding additional edges to the graph prior to the message passing during the symbolic phase. This corresponds to relaxing constraint (6b) to allow more non-zero elements for example by allowing all entries corresponding to the sparsity pattern of \mathbf{A}^2 .

To obtain a dynamic sparsity pattern, we add a ℓ_1 -penalty on the elements in the learned preconditioning matrix $\|\Lambda_{\theta}(\mathbf{A})\|_1$ to the training objective (6a). This encourages the network to produce sparse outputs (Jenatton et al., 2011). During inference, we drop elements with a small magnitude to obtain an even sparser preconditioner. This can lead to faster overall solving times since the step to find the search direction in line 9 of Algorithm 1 scales with the number of non-zero elements in the preconditioner (Davis et al., 2016). Both of these approaches can also be combined to obtain a learned preconditioner similar to the dual threshold incomplete factorization (Saad, 1994).

By including additional edges, the forward pass of the GNN becomes computationally more expensive. Therefore, it is important to avoid increasing the non-zero elements too much to maintain the computational efficiency. Dropping additional elements, on the other hand, can be achieved with nearly no overhead during inference.

Inference and amortization When the trained model is used during inference time to generate preconditioners, the output $\mathbf{P}_\theta(\mathbf{A}) = \Lambda_\theta(\mathbf{A})\Lambda_\theta(\mathbf{A})^\top \approx \mathbf{A}$ is used within Algorithm 1 to find the preconditioned search direction. The implementation details can be found in Appendix B.

4 Results

The overall goal of preconditioning techniques is to reduce total computational time required to solve the problem up to a given precision (here, we choose 10^{-6}) measured by the residual norm as described in Section 3. The time used to compute the preconditioner beforehand, therefore, needs to be traded off with the achieved speed-up through the usage of the preconditioner. We compare the different methods based on both the time required to compute the preconditioner (P-time) and the time needed to solve the preconditioned linear equation system (CG-time) which is related to the number of iterations required. However, the type and the sparsity of the obtained preconditioner also influences the time-per-iteration. For instance in factorized preconditioners the sparse triangular solve method scales with the number of non-zero elements (Davis et al., 2016).

We consider two different datasets in our experiments. The first dataset consists of synthetically generated problems where we can easily control the size and sparsity of the generated problem instances. The other class is motivated by problems arising in scientific computing by discretizing the Poisson PDE on varying grids using the finite element method (FEM). The details for the dataset generation can be found in Appendix A and implementation details of the different baselines and methods are described in Appendix B.

For numerical experiments we use a single NVIDIA-Titan Xp with 12 GB memory. For baseline preconditioners, which are not able to be accelerated directly using GPUs, we use 6 Intel Core i7-6850K @ 3.60 GHz processors for the computations. The (preconditioned) conjugate gradient method is always run on the CPU to ensure a fair comparison between the performance of the preconditioners.

Further acceleration of our neural network-based preconditioner can be obtained by batching the problem instances. This allows parallelization of the computation for the preconditioners leading to a smaller precomputation overhead. However, to ensure a fair comparison in our experiments, we handle each problem individually in our experiments.

4.1 Synthetic problems

The results and statistics about the preconditioned systems from the experiments using the synthetic dataset are shown in Table 1. As a baseline, we include the standard CG implementation without any additional preconditioner. We can see that our learned preconditioner is significantly faster to compute while maintaining similar performance in terms of reduction in number of iterations as the incomplete Cholesky (IC) method without additional fill-ins. This makes our approach, in terms of total solving time, on average $\sim 25\%$ faster than incomplete Cholesky.

All data-driven methods are trained using the stochastic approximation of the Frobenius norm loss from equation (7) until convergence is achieved on the validation data. Compared to the data-driven NeuralPCG (Li et al., 2023) method, our method is faster to compute during inference which leads to a smaller P-time, since the number of parameters is significantly smaller. Further, we are able to reduce the number of required iterations to solve the problem using preconditioned CG significantly more. In summary, our data-driven approach shows the ability of the learned preconditioner to accelerate the solving procedure.

Dynamic sparsity pattern The results for the learned preconditioner with additional sparsity, through dropping elements by value as described in Section 3, are shown as NeuralIF-sp. Even though the output of the model contains only around half of the elements compared to the methods without fill-ins, the performance in terms of iterations does not suffer significantly. This can be exploited within the forward-backward solves which scale with the number of non-zero elements. Therefore, the overall time to solve the system is on average shortest using the sparsified NeuralIF preconditioner across all tested preconditioning methods.

Solving times The distribution of total solving times is shown in Figure 2, where each point represents a single test problem instance that is solved with each respective method. The time shown includes both the

Table 1: Mean results for the synthetic dataset for $n = 10\,000$ with 1% non-zero elements on 100 test instances. The first column shows the condition number of the preconditioned system $\mathbf{L}^{-1}\mathbf{A}\mathbf{L}^{-\top}$. The second column lists the preconditioner’s sparsity. Remaining columns list performance-related figures for the preconditioned conjugate gradient method: the third column lists the computation time for the preconditioner (P-time), the fourth lists the time for finding the solution and the number of iterations required running the preconditioned conjugate gradient method (CG-time/Its.) and the fifth column shows the combined time for computing the preconditioner and solving the system. All times are in seconds.

Preconditioner	Cond. number $\kappa \downarrow$	Sparsity \uparrow	P-time \downarrow	CG-time (its.) \downarrow	Total time \downarrow
None	60 834.17	-	-	2.79 (935.99)	2.79
Jacobi	33 428.86	99.99%	0.005	1.83 (689.82)	1.84
IC(0)	4 707.17	99.49%	0.247	1.16 (260.64)	1.40
NeuralPCG	7 240.72	99.49%	0.123	1.54 (318.86)	1.66
NeuralIF (ours)	4 921.76	99.49%	0.028	1.16 (267.08)	1.19
NeuralIF-sp (ours)	5 581.44	99.77%	0.021	1.01 (286.02)	1.03

time required to compute the preconditioner (P-time) and the time to run the preconditioned CG method (CG-time). Overall, the variance of solving time between different problems is small for all considered methods which is due to the fact that the generated problems are very similar. The Jacobi and incomplete Cholesky preconditioner are effective for most problems. In comparison, the NeuralPCG method is not able to speed up the computational time compared to the other preconditioning baselines. We can see that both of our NeuralIF preconditioners outperforms the other preconditioning methods on nearly all problem instances but similar to other methods exhibit slightly worse performance on a few problem instances.

Eigenvalue distribution In Figure 3, the ordered eigenvalues of the preconditioned linear equation system for one test problem are shown. Here, we can see that NeuralIF is especially able to reduce large eigenvalues compared to all the other preconditioners. However, compared to incomplete Cholesky the smaller eigenvalues of the NeuralIF preconditioned system decrease earlier and the smallest eigenvalue of the system is slightly smaller. This results in a slightly worse convergence behavior in the limit of our data-driven method.

Breakdown One inherent limitation of the incomplete Cholesky method is that it suffers from breakdown in 4% of the synthetic test problems due to the numerical instabilities of the method (Benzi, 2002). These instances are not included in solving time in Table 1 but are very costly in practice since it requires a restart of the solving procedure. In contrast, our data-driven approach consistently generates a suitable preconditioner.




Figure 2: Total solving time for each test problem instance from the synthetic dataset.




Figure 3: Ordered eigenvalues of the preconditioned linear equation system in log-scale.

4.2 Poisson PDE problems

In the second problem, we are focusing on problems arising from the discretization of Poisson PDEs using the finite element method. In order to train our learned preconditioner efficiently, we create a subset of small training problems with matrices of size between 20 000 and 100 000 with up to 500 000 non-zero elements. The results for these problems are summarized in Table 2. Here, MIC is the modified incomplete Cholesky method with the same number of non-zero elements as IC(0) but potentially different locations of the non-zero elements which is determined dynamically (Lin & Moré, 1999). Allowing a more flexible sparsity pattern can lead to better results but additional pre-computation time is required to determine the position of non-zero elements. Among all preconditioners without fill-ins, our data-driven method performs best as it is very efficient to compute and reduces the required iterations vastly.

Additional fill-ins Among the preconditioners with additional fill-ins, the MIC+ preconditioner further allows additional elements based on the number of non-zero elements in each row of the matrix which improves the preconditioner at the cost of a more expensive pre-computation time. Our NeuralIF(1) preconditioner is obtained by allowing non-zero elements in the non-zero locations of the matrix \mathbf{A}^2 which is a widely-adopted heuristic (Chow, 2000). Here, computing the static sparsity pattern before the message passing requires a significant amount of time and only minimal performance optimization of our algorithm is implemented. Therefore, the highly optimized implementation of the modified incomplete Cholesky method performs slightly better but the learned preconditioner improves significantly due to the added fill-ins compare to the previous methods without fill-ins.

Generalization to larger problems Since real-world problems are often significantly larger than the training instances, we evaluate our methods also on problem instances of sizes up to 500 000 containing 3 000 000 non-zero elements. Since the problems in the dataset containing large instances are more diverse in terms of size, number of non-zero elements, and difficulty in solving them compared to the training dataset, we show a pairwise comparison in Figure 4. Here, we compare the total time it takes to solve the system using NeuralIF to solving the problem using various other preconditioners. We can see that for the larger problem instances, the NeuralIF preconditioner performs on par with the IC(0) method and even outperforms MIC, even though the problems are significantly larger than the training instances showing the generalization abilities of our method on problems very different from the training domain.

We additionally compare the scaling of NeuralIF with the incomplete Cholesky method in Figure 5 using the PDE dataset as it contains a natural variety of differently sized problems. In the plot, we compare the number of non-zero matrix elements – which strongly correlates with the size of the matrix – with the time that is required to compute the preconditioner (P-time) (Figure 5a) as well as the time required to run the preconditioned conjugate gradient method (Figure 5b).

The results show that our model exhibits a very good size generalization as it is able to produce efficient preconditioners even for matrices which are a magnitude of size bigger than the training instances. Further,




Figure 4: Pairwise comparison of total solving times (computation time of the precondition and solving time of the preconditioned linear system) of the NeuralIF preconditioner with the other preconditioners without fill-ins on the 300 large PDE problem instances. Instances towards the lower right part of the plot indicate that our method is faster, otherwise the baseline. Note that there are different axis scales for each comparison.

Table 2: Results for the small Poisson PDE problems from the training distribution using a subset of the columns shown in Table 1. The first set of method does not use fill-ins while in the second part additional non-zeros are added based on the position and value of the non-zero elements.

Preconditioner	P-time	CG-time (its.)	Total time
None	-	1.72 (856.38)	1.72
Jacobi	0.004	1.01 (466.85)	1.02
IC(0)	0.022	0.51 (166.05)	0.53
MIC	0.029	0.56 (180.94)	0.59
NeuralPCG	0.018	0.57 (189.97)	0.59
NeuralIF(0) (ours)	0.014	0.51 (168.09)	0.52
MIC+	0.044	0.39 (100.95)	0.43
NeuralIF(1) (ours)	0.030	0.44 (111.37)	0.47




Figure 5: Comparison of the computational time required for the incomplete Cholesky and NeuralIF preconditioner with respect to the matrix size measure in number of non-zero elements on both the instances from the training distribution and problem instances outside of the training domain. We are using 600 problem instances from the generated Poisson PDE problems. The generated outputs have by construction the same number of non-zero elements as the input matrix.

we can see that the learned preconditioner scales better in terms of P-time for larger matrices than the incomplete Cholesky method.

Additional results for both datasets can be found in Appendix C.

5 Discussion & Limitations

Here, we discuss several limitations and potential improvements with our proposed framework. However, we emphasize that many of these problems affect all learning-to-optimize methods and are not specific to our learned preconditioner.

Training To train data-driven preconditioners, we assume that there is a sufficiently large set of problem instances from of a distribution \mathbb{A} that share some similarity. In practice, not all problem domains give rise to such a distribution. Further, the time invested in the model training needs to be amortized over the speedup obtained during the inference phase of the learned preconditioner. However, this model training replaces the otherwise time-consuming manual tuning of preconditioners and is not a specific issue with our method but a limitation of the general learning-to-optimize framework (Chen et al., 2022). This also motivates following

our self-supervised learning approach since it allows us to train the model on unsolved problem instances. The trained model can then, in principle, be applied to accelerate solving the training instances making it easier to amortize the model training.

Convergence While the method works well in our numerical experiments, no guarantees about the convergence speed can be made and it is likely that for some problem classes the usage of the learned preconditioner leads to an increase in overall solving time. That said, as seen in the experiments also classical preconditioners suffer from this problem and our method avoids pitfalls such as breakdowns in incomplete Cholesky (Benzi, 2002).

Future work A promising future research direction is to learn more flexible sparsity patterns used for preconditioners alongside the values to fill in. This can be achieved by changing the graph structure used for message passing but requires additional care due to the combinatorial nature of the problem. Further, the incomplete factorization loss used to train our model is only a heuristic and not directly related to the complex convergence behavior of the conjugate gradient method. Extending the approach to directly take into account the downstream task has the potential to further improve the learned preconditioner and lead to faster convergence (Bansal et al., 2023).

6 Related work

Data-driven optimization or “learning-to-optimize (L2O)” is an emerging field aiming to accelerate numerical optimization methods by combining them with data-driven techniques (Amos, 2023; Chen et al., 2022). For example, a neural network can be trained to directly predict the solution to an optimization problem (Grementieri & Galeone, 2022) or replace some typically hand-crafted heuristic within a known optimization algorithm (Bengio et al., 2021).

L2O using GNNs Graph neural networks have been recognized as a suitable computational backend for problems in data-driven optimization (Moore et al., 2023). Chen et al. (2023) study the expressiveness of GNNs with respect to their power to represent linear programs on a theoretical level. Using the Coates graph representation, Grementieri & Galeone (2022) develop a sparse linear solver for linear equation systems. They represent the linear equation system as the input to a graph neural network which is trained to approximate the solution to the equation system directly. However, no guarantees for the solution can be obtained. In contrast, our method benefits from the convergence properties of the preconditioned conjugate gradient method.

Following an AutoML approach, Tang et al. (2022) instead try to predict a good combination of solver and preconditioner from a predefined list of techniques using supervised training. The NeuralIF preconditioner instead focuses on further accelerating the existing CG method and does not need any explicit supervision during training. Sjölund & Bånkestad (2022) use the König graph representation instead to accelerate low-rank matrix factorization algorithms by representing the matrix multiplication as a concatenation graph similar to our approach. However, their architecture utilizes a graph transformer while our approach works in a fully sparse setting. This avoids the scalability issues of transformer architectures and makes it better suited for large-scale problems.

Data-driven CG Incorporating deep learning into the conjugate gradient method has been utilized in several ways previously. Kaneda et al. (2023) suggest replacing the search direction in the conjugate gradient method with the output of a neural network. This approach can, however, not be integrated with existing solutions for accelerating the CG method and does not allow further improvements through preconditioning. Furthermore, to ensure convergence all previous search directions need to be saved and the full Gram–Schmidt orthonormalization needs to be computed in every iteration making it prohibitively expensive.

There have also been some earlier approaches to learning preconditioners for the conjugate gradient method following similar ideas as our proposed NeuralIF method. Ackmann et al. (2021) use a fully-connected neural network to predict the preconditioner for climate modeling using a supervised loss. Suppl et al. (2019) use a convolutional neural network (CNN) to learn a preconditioner for applications in water engineering by optimizing the condition number directly. However, both of these approaches are only able to handle

small-scale problems and their architecture and training is limited due to their poor scalability compared to our suggested approach. Utilizing CNN architectures, predicting sparsity patterns for specific types of preconditioners (Götz & Anzt, 2018) and general incomplete factorizations (Stanaityte, 2020) has also been suggested previously. In comparison, our learned method is far more general and can be applied to a significantly larger class of problems. Even though CNNs are widely adopted in the previous approaches, they are not well-suited to represent the underlying problem in contrast to GNNs.

Preconditioning Incomplete factorization methods are a large area of research. In most cases, the aim is to reduce computational time and memory requirements by ignoring elements based on either position or value. However, if done too aggressively, the method may break down due to numerical issues and require expensive restarts. Perturbation and pivoting techniques can mitigate but not completely eliminate such problems (Scott & Tuma, 2023). In contrast, our method does not suffer from breakdown as the positive-definiteness of the output is ensured a posteriori. Numerical efficiency can also be improved by reordering to reduce fill-in (for $IC(\ell)$ with $\ell > 0$) or by finding rows of the matrix that can be eliminated in parallel (Gonzaga de Oliveira et al., 2018).

Chow & Patel (2015) formulate incomplete factorization as the problem of finding a factorization that is exact on the given sparsity pattern as a feasibility problem that can be solved approximately. In contrast, our method only approximates the Frobenius norm minimization in equation (6) without enforcing constraints, which reduces pre-computation times. However, both approaches are quite similar in the sense that both methods aim to minimize the difference of the sparse factorization and the original matrix. While our method is using a fully-amortized learned optimization approach to minimize the full Frobenius norm distance (Amos, 2023), Chow & Patel (2015) directly optimize the residuals of non-zero elements in the approximate factorization. The latter approach also allows further acceleration using methods from distributed computing (Anzt et al., 2018) but typically requires highly optimized implementations to achieve competitive results.

For problems arising from elliptical PDEs, multigrid preconditioning techniques have shown to be very effective. These type of methods utilize the underlying geometric structure of the problem to obtain a preconditioner (Pearson & Pestana, 2020). Multigrid methods have also been successfully combined with deep learning techniques (Azulay & Treister, 2022). A potential drawback of this type of preconditioner is, however, that the technique is computationally quite expensive compared to other methods and the resulting preconditioner is typically non-sparse.

7 Conclusions

In this paper we introduce NeuralIF, a novel and computationally efficient data-driven preconditioner for the conjugate gradient method to accelerate solving large-scale and sparse linear equation systems. Our method is trained to predict the sparse Cholesky factor of the input matrix following the widespread idea of incomplete factorization preconditioners (Benzi, 2002). To obtain a computationally efficient loss function, we derive a stochastic approximation of the Frobenius loss based on Hutchinson’s trace estimator (Hutchinson, 1989). This allows us to train our model using matrix-vector multiplications only which can be efficiently implemented for the large-scale sparse matrices.

We use the problem matrix \mathbf{A} as an input to a graph neural network, which processes the input and produces the desired approximate factorization. The network architecture aligns with the objective to minimize the distance between the learned output and the input using the Frobenius norm as a distance measure using insights from graph theory. Our experiments show that the proposed method is competitive against general-purpose preconditioners both on synthetic and real-world problems and allows the creation of both dynamic and static sparsity patterns. Our work shows the large potential of data-driven techniques in combination with insights from numerical optimization and the usefulness of graph neural networks as a natural computational backend for problems arising in computational linear algebra (Moore et al., 2023).

References

Jan Ackmann, Peter Düben, Tim Palmer, and Piotr Smolarkiewicz. Machine-Learned Preconditioners for Linear Solvers in Geophysical Fluid Flows. In *EGU General Assembly Conference Abstracts*, EGU General

- Assembly Conference Abstracts, pp. EGU21–5507, April 2021.
- Brandon Amos. Tutorial on amortized optimization. *Foundations and Trends in Machine Learning*, 16(5): 592–732, 2023. ISSN 1935-8237.
- Hartwig Anzt, Edmond Chow, and Jack Dongarra. Parilut—a new parallel threshold lu factorization. *SIAM Journal on Scientific Computing*, 40(4):C503–C519, 2018.
- Yael Azulay and Eran Treister. Multigrid-augmented deep learning preconditioners for the helmholtz equation. *SIAM Journal on Scientific Computing*, (0):S127–S151, 2022.
- Sebastian Banert, Jevgenija Rudzusika, Ozan Öktem, and Jonas Adler. Accelerated forward-backward optimization using deep learning. *SIAM Journal on Optimization*, 34(2):1236–1263, 2024.
- Dishank Bansal, Ricky TQ Chen, Mustafa Mukadam, and Brandon Amos. Taskmet: Task-driven metric learning for model learning. *Advances in Neural Information Processing Systems*, 2023.
- Peter W Battaglia, Jessica B Hamrick, Victor Bapst, Alvaro Sanchez-Gonzalez, Vinicius Zambaldi, Mateusz Malinowski, Andrea Tacchetti, David Raposo, Adam Santoro, Ryan Faulkner, et al. Relational inductive biases, deep learning, and graph networks. *arXiv preprint arXiv:1806.01261*, 2018.
- Yoshua Bengio, Andrea Lodi, and Antoine Prouvost. Machine learning for combinatorial optimization: a methodological tour d’horizon. *European Journal of Operational Research*, 290(2):405–421, 2021.
- Michele Benzi. Preconditioning techniques for large linear systems: a survey. *Journal of computational Physics*, 182(2):418–477, 2002.
- Michael M Bronstein, Joan Bruna, Taco Cohen, and Petar Veličković. Geometric deep learning: Grids, groups, graphs, geodesics, and gauges. *arXiv preprint arXiv:2104.13478*, 2021.
- Richard A Brualdi and Dragos Cvetkovic. *A combinatorial approach to matrix theory and its applications*. CRC press, 2008.
- Chen Cai and Yusu Wang. A simple yet effective baseline for non-attributed graph classification. *ICLR Workshop: Representation Learning on Graphs and Manifolds*, 2019.
- Tianle Cai, Shengjie Luo, Keyulu Xu, Di He, Tie yan Liu, and Liwei Wang. Graphnorm: A principled approach to accelerating graph neural network training. *International Conference on Machine Learning*, 2021.
- Erin Carson, Jörg Liesen, and Zdeněk Strakoš. Solving linear algebraic equations with Krylov subspace methods is still interesting! *arXiv preprint arXiv:2211.00953*, 2023.
- Tianlong Chen, Xiaohan Chen, Wuyang Chen, Zhangyang Wang, Howard Heaton, Jialin Liu, and Wotao Yin. Learning to optimize: A primer and a benchmark. *Journal of Machine Learning Research*, 23(1), 2022.
- Ziang Chen, Jialin Liu, Xinshang Wang, and Wotao Yin. On representing linear programs by graph neural networks. In *The Eleventh International Conference on Learning Representations*, 2023.
- Edmond Chow. A priori sparsity patterns for parallel sparse approximate inverse preconditioners. *SIAM Journal on Scientific Computing*, 21(5):1804–1822, 2000.
- Edmond Chow and Aftab Patel. Fine-grained parallel incomplete lu factorization. *SIAM journal on Scientific Computing*, 37(2):C169–C193, 2015.
- C. Coates. Flow-graph solutions of linear algebraic equations. *IRE Transactions on Circuit Theory*, 6(2): 170–187, 1959.
- Timothy A Davis, Sivasankaran Rajamanickam, and Wissam M Sid-Lakhdar. A survey of direct methods for sparse linear systems. *Acta Numerica*, 25:383–566, 2016.

- Michael Doob. Applications of graph theory in linear algebra. *Mathematics Magazine*, 57(2):67–76, 1984.
- Andrew J Dudzik and Petar Veličković. Graph neural networks are dynamic programmers. *Advances in Neural Information Processing Systems*, 35:20635–20647, 2022.
- Matthias Fey and Jan E. Lenssen. Fast graph representation learning with PyTorch Geometric. In *ICLR Workshop on Representation Learning on Graphs and Manifolds*, 2019.
- Gene H Golub and Charles F Van Loan. *Matrix computations*. JHU press, 2013.
- Sanderson L Gonzaga de Oliveira, JAB Bernardes, and GO Chagas. An evaluation of reordering algorithms to reduce the computational cost of the incomplete Cholesky-conjugate gradient method. *Computational and Applied Mathematics*, 37:2965–3004, 2018.
- Luca Gremontieri and Paolo Galeone. Towards Neural Sparse Linear Solvers. *arXiv preprint arXiv:2203.06944*, 2022.
- Tom Gustafsson and G. D. McBain. scikit-fem: A Python package for finite element assembly. *Journal of Open Source Software*, 5(52):2369, 2020.
- Markus Götz and Hartwig Anzt. Machine learning-aided numerical linear algebra: Convolutional neural networks for the efficient preconditioner generation. In *2018 IEEE/ACM 9th Workshop on Latest Advances in Scalable Algorithms for Large-Scale Systems (scalA)*, pp. 49–56, 2018.
- Clemens Hofreither. ilupp – ilu algorithms for c++ and python, 2020. URL <https://github.com/c-f-h/ilupp>.
- Michael F Hutchinson. A stochastic estimator of the trace of the influence matrix for laplacian smoothing splines. *Communications in Statistics-Simulation and Computation*, 18(3):1059–1076, 1989.
- Rodolphe Jenatton, Jean-Yves Audibert, and Francis Bach. Structured variable selection with sparsity-inducing norms. *The Journal of Machine Learning Research*, 12:2777–2824, 2011.
- Ayano Kaneda, Osman Akar, Jingyu Chen, Victoria Kala, David Hyde, and Joseph Teran. A deep gradient correction method for iteratively solving linear systems. *International Conference in Machine Learning*, 2023.
- Hans Petter Langtangen and Anders Logg. *Solving PDEs in minutes-the FEniCS tutorial I*, volume 3 of *Simula SpringerBriefs on Computing*. Springer, 2016.
- Yichen Li, Peter Yichen Chen, Tao Du, and Wojciech Matusik. Learning preconditioner for conjugate gradient pde solvers. *International Conference in Machine Learning*, 2023.
- Chih-Jen Lin and Jorge J Moré. Incomplete Cholesky factorizations with limited memory. *SIAM Journal on Scientific Computing*, 21(1):24–45, 1999.
- Per-Gunnar Martinsson and Joel A Tropp. Randomized numerical linear algebra: Foundations and algorithms. *Acta Numerica*, 29:403–572, 2020.
- Jan Mayer. Ilu++: A new software package for solving sparse linear systems with iterative methods. In *PAMM: Proceedings in Applied Mathematics and Mechanics*, volume 7, pp. 2020123–2020124. Wiley Online Library, 2007.
- Nicholas S Moore, Eric C Cyr, Peter Ohm, Christopher M Siefert, and Raymond S Tuminaro. Graph neural networks and applied linear algebra. *arXiv preprint arXiv:2310.14084*, 2023.
- Maxim Naumov. Parallel incomplete-lu and cholesky factorization in the preconditioned iterative methods on the gpu. *Nvidia Technical Report NVR-2012-003*, 2012.
- John L Nazareth. Conjugate gradient method. *Wiley Interdisciplinary Reviews: Computational Statistics*, 1(3):348–353, 2009.

- Jorge Nocedal and Stephen J Wright. *Numerical optimization*. Springer, 1999.
- Nicolas Nytko, Ali Taghibakhshi, Tareq Uz Zaman, Scott MacLachlan, Luke N. Olson, and Matt West. Optimized sparse matrix operations for reverse mode automatic differentiation. *arXiv preprint arXiv:2212.05159*, 2022.
- Adam Paszke, Sam Gross, Francisco Massa, Adam Lerer, James Bradbury, Gregory Chanan, Trevor Killeen, Zeming Lin, Natalia Gimelshein, Luca Antiga, et al. Pytorch: An imperative style, high-performance deep learning library. *Advances in neural information processing systems*, 32, 2019.
- John W. Pearson and Jennifer Pestana. Preconditioners for Krylov subspace methods: An overview. *GAMM-Mitteilungen*, 43(4), November 2020. ISSN 0936-7195, 1522-2608.
- Florian A. Potra and Stephen J. Wright. Interior-point methods. *Journal of Computational and Applied Mathematics*, 124(1):281–302, 2000. ISSN 0377-0427. Numerical Analysis 2000. Vol. IV: Optimization and Nonlinear Equations.
- Yousef Saad. Ilut: A dual threshold incomplete lu factorization. *Numerical linear algebra with applications*, 1(4):387–402, 1994.
- Yousef Saad. *Iterative Methods for Sparse Linear Systems*. SIAM, Philadelphia, 2nd edition, 2003. ISBN 978-0-89871-534-7.
- Johannes Sappl, Laurent Seiler, Matthias Harders, and Wolfgang Rauch. Deep learning of preconditioners for conjugate gradient solvers in urban water related problems. *arXiv preprint arXiv:1906.06925*, 2019.
- Jennifer Scott and Miroslav Tůma. *Algorithms for Sparse Linear Systems*. Springer International Publishing, Cham, 2023.
- Jonathan Richard Shewchuk. An introduction to the conjugate gradient method without the agonizing pain. *Carnegie-Mellon University. Department of Computer Science Pittsburgh*, 1994.
- Jens Sjölund and Maria Bånkestad. Graph-based neural acceleration for nonnegative matrix factorization. *arXiv preprint arXiv:2202.00264*, 2022.
- Rita Stanaityte. *ILU and Machine Learning Based Preconditioning For The Discretized Incompressible Navier-Stokes Equations*. PhD thesis, University of Houston, 2020.
- Bartolomeo Stellato, Goran Banjac, Paul Goulart, Alberto Bemporad, and Stephen Boyd. OSQP: An operator splitting solver for quadratic programs. *Mathematical Programming Computation*, 12(4):637–672, 2020.
- Ziyuan Tang, Hong Zhang, and Jie Chen. Graph Neural Networks for Selection of Preconditioners and Krylov Solvers. *NeurIPS 2022 New Frontiers in Graph Learning Workshop*, 2022.
- Petar Veličković. Everything is connected: Graph neural networks. *Current Opinion in Structural Biology*, 79:102538, 2023.
- Raviteja Vemulapalli and David W Jacobs. Riemannian metric learning for symmetric positive definite matrices. *arXiv preprint arXiv:1501.02393*, 2015.

A Dataset details

The (preconditioned) conjugate gradient method is a standard iterative method for solving large-scale systems of linear equations of the form

$$\mathbf{A}\mathbf{x} = \mathbf{b} \quad (9)$$

where \mathbf{A} is symmetric and positive definite (spd) i.e. $\mathbf{A} = \mathbf{A}^\top$ and $\mathbf{x}^\top \mathbf{A} \mathbf{x} > 0$ for all $\mathbf{x} \neq 0$. We also write $\mathbf{A} \in S_n^{++}$ to indicate that \mathbf{A} is a $n \times n$ spd matrix (Golub & Van Loan, 2013). The method is especially efficient when the matrix \mathbf{A} is large-scale and sparse since the required matrix-vector products shown in Algorithm 1 can efficiently exploit the structure of the matrix in this case (Saad, 2003).

In this section, we specify different problem settings leading to distributions \mathbf{A} over matrices of the desired form such that the conjugate gradient method is a natural choice for solving the problem. Given a distribution we accessing via a number of samples, our goal is to train a model using the empirical risk minimization objective shown in the main paper to compute an incomplete factorization of a given input and utilize the resulting output as an effective preconditioner in the CG algorithm.

In total, we are testing our method on two different datasets but vary the parameters used to generate these datasets. The first problem dataset considers synthetic problem instances. The other test problem arises in scientific computing where large-scale spd linear equation systems can be obtained naturally from the discretization of elliptical PDEs. In Section C, the results presented in the main paper on these problem settings are extended.

The size of the matrices considered in the experiments is between $n = 10\,000$ and $n = 200\,000$ for all datasets in use. Throughout the paper we assume that the problem at hand is (very) sparse and spd. Thus, the preconditioned conjugate gradient method is a natural choice for all these problems. We ensure that the matrices are different by using unique and non-overlapping seeds for the problem generation. The datasets are summarized in Table 3. For the graph representation used in the learned preconditioner, the matrix size corresponds to the number of nodes in the graph and the number of non-zero elements corresponds to the number of edges connecting the nodes. In the following, the details for the problem generation are explained for each of the datasets.

Table 3: Summary of the datasets used with some additional statistics on size of the matrices and the number of corresponding non-zero elements. Samples refer to number of generated problems in the train, validation and test set respectively.

Dataset	Samples	Matrix size	Non-zero elements (nnz)	Sparsity
Synthetic	1 000/10/100	10 000	$\sim 1\,000\,000$	99%
Poisson PDE - train	750/15/300	20 000 – 150 000	800 000 – 500 000	$> 99.9\%$
Poisson PDE - test	-/-/300	100 000 – 500 000	500 000 – 3 000 000	$> 99.9\%$

A.1 Synthetic problem

The set of random test matrices is constructed by choosing a sparsity parameter p which indicates the expected percentage of non-zero elements in the matrix. It is also possible to specify p itself as a distribution. We choose the non-zero probability such that the resulting spd matrices which are generated with equation (10) have around 99% total sparsity (therefore the generated problems have 1 million non-zero elements). For the out-of-distribution data, we sample the sparsity probability uniform such that the resulting matrices have between 50 000 and 5 000 000 non-zero elements. We then create the problem by sampling a matrix \mathbf{A} with $p(\mathbf{A}_{ij} = 0) = p$ and $p(\mathbf{A}_{ij} | \mathbf{A}_{ij} \neq 0) \sim \mathcal{N}(0, 1)$. The final problem is then given by

$$\mathbf{M} = \mathbf{A}\mathbf{A}^\top + \alpha \mathbf{I} \quad (10)$$

where $\alpha \approx 10^{-3}$ is used to ensure the resulting problem is positive definite. The right hand side of the linear equation system is sampled uniformly $\mathbf{b} \sim \mathcal{U}[0, 1]^n$.




Figure 6: Sample meshes for each of the three different domain distributions used to generate training data for the Poisson PDE problem.

Problems of this form also arise when minimizing quadratic programs since the equation (9) represents the first-order optimality condition for an unconstrained QP (Stellato et al., 2020). Thus, the problem represented here can be encountered in various settings making it an interesting case study.

A.2 Poisson equation

The Poisson equation is an elliptical partial differential equation (PDE) and one of the most fundamental problems in numerical computational science (Langtangen & Logg, 2016). The problem is stated as solving the boundary value problem

$$-\nabla^2 u(x) = f(x) \quad x \in \Omega \quad (11a)$$

$$u(x) = u_D(x) \quad x \in \partial\Omega \quad (11b)$$

where $f(x)$ is the source function and $u = u(x)$ is the unknown function to be solved for. By discretizing this problem using the finite element method and writing it in matrix form a system of linear equations of the form $\mathbf{L}\mathbf{x} = \mathbf{b}$ is obtained where the stiffness matrix \mathbf{L} is sparse and spd. For large n , this problem therefore can be efficiently solved using the conjugate gradient method given a good preconditioner.

In order to obtain a distribution \mathbb{A} over a large number of Poisson equation PDE problems, we consider a set of meshes that are generated by sampling from a normal distribution and creating a mesh based on the sampled points. We consider three different cases for the mesh generation: (a) we form the convex hull of the sampled points and triangulate the resulting shape, (b) we sample two sets of points and transform them into convex shapes as before. The second samples have a significantly smaller variance. The final shape that is used for triangulation is then obtained as the difference between the two samples. Finally, (c) we generate a simple polytope from the sampled points. An example for each of the generated shapes is shown in Figure 6. The sampled meshes are discretized using the finite-element method and refined using the scikit-fem python library (Gustafsson & McBain, 2020). Due to the discretization based on the provided mesh the size of the generated matrix is variable. Based on the stiffness matrices arising from the discretized problems the NeuralIF preconditioner is trained.

B Implementation details

In the following, we describe the details of the network architecture our NeuralIF model uses as well as the details of the model training, testing, and inference. Our method is implemented using PyTorch (Paszke et al., 2019) and PyTorch Geometric (Fey & Lenssen, 2019).

B.1 Model architecture

Here, we summarize in detail the architecture choices for our NeuralIF preconditioner and provide details on the implementation and training of the method. In total, our model consists of 1 780 learnable parameters.

Table 4: List of node features used in the graph neural network.

Feature name	Description
$\text{deg}(v)$	Degree of node v
$\max \text{deg}(u)$	Maximum degree of neighboring nodes
$\min \text{deg}(u)$	Minimum degree of neighboring nodes
$\text{mean deg}(u)$	Average degree of neighboring nodes
$\text{var deg}(u)$	Variance in the degrees of neighboring nodes
dominance	Diagonal dominance
decay	Diagonal decaying
pos	The position of the node in the matrix

Node and edge features . In total eight features are used for each node thus $\mathbf{x}_i \in \mathbb{R}^8$. The first five node features listed in Table 4 are implemented following the *local degree profile* introduced by Cai & Wang (2019). The dominance and decay features shown in the table are originally introduced by Tang et al. (2022).

As edge feature, only the scalar value of the matrix entry is used. In deeper layers of the network, when skip connections are introduced, the edges are augmented with the original matrix entries. This effectively leads to having two edge features in these layers: the computed edge embedding of the current layer $\mathbf{z}_{ij}^{(l)}$ as well as the original matrix entry a_{ij} . However, from these only a one-dimensional output is computed $\mathbf{z}_{ij}^{(l+1)}$ as described in the following.

Message passing block . At the core of our method, we introduce a novel message passing block which aligns with the objective of our training. The underlying idea is that matrix multiplication can be represented in graph form by concatenating the two Coates graph representations as described previously (Doob, 1984). The pseudocode for the message passing scheme is shown in Algorithm 2. The message passing block consists of two GNN layers as introduced in Section 3 which are concatenated to mimic the matrix multiplication. To align the block with our objective, we only consider the edges in the lower triangular part of the matrix in the first layer (see lines 8–11 in Algorithm 2) while in the second layer of the block only edges from the upper triangular part of the matrix are used (lines 14–17). However, the same edge embedding for the two steps are used (line 13). In the final step of the message passing block, we introduce skip connections and concatenate the edge features in the current layer with the original matrix entries (lines 18–23). Note that, since the matrix \mathbf{A} is symmetric it holds that $(i, j) \in L \Leftrightarrow (j, i) \in U$ where U and L are the index set corresponding to the non-zero elements in the upper and lower triangular matrix.

Here, we denote the updates after the first message passing layer with the superscript $(l + \frac{1}{2})$ to explicitly indicate that it is an intermediate update step. The final output from the block is then computed based on another message passing step which utilizes the computed intermediate embedding. Further, $\mathcal{N}_L(i)$ denotes the neighborhood of node i with respect to the edges in the lower triangular part \mathbf{L} and $\mathcal{N}_U(i)$ the ones from the upper triangular part \mathbf{U} respectively which are utilized for the message passing. There are always at least the diagonal elements in the neighborhood of each node and therefore, the message computation is well defined.

Network design . Both the parameterized edge update ϕ and the node update ψ functions in every layer are implemented using two layer fully-connected neural networks. The inputs to the edge update network ϕ are formed by the node features of the corresponding edge and the edge features themselves leading to a total of $8 + 8 + 1 = 17$ inputs in the first message passing step and one additional input in later steps. The edge network outputs a scalar value. For each network, eight hidden units are used and the **tanh** activation function is applied as a non-linearity. To compute the aggregation over the neighborhood \oplus , the **mean** and **sum** aggregation functions are used – respectively in the first and second step of the message passing block – which is applied component-wise to the set of neighborhood edge feature vectors. The node update function ψ takes the aggregation of the incoming edge features as well as the current node feature as an input ($1 + 8 = 9$).

The NeuralIF model used in the experiments consists of 3 of the message passing blocks introduced in Section 3. Resulting in a total of six GNN message passing steps with two skip connections from the input matrix \mathbf{A} . Graph normalization prior to the message passing leads to faster overall convergence of the training

Algorithm 2 Pseudo-code for NeuralIF preconditioner.

-
- 1: **Input:** Graph representation of the spd system of linear equations $\mathbf{Ax} = \mathbf{b}$.
 - 2: **Output:** Lower-triangular sparse preconditioner for the linear system which is an incomplete factorization.
 - 3: \triangleright NeuralIF preconditioner computation:
 - 4: Compute node features \mathbf{x}_i shown in Table 4
 - 5: Apply graph normalization
 - 6: Split graph adjacency matrix into index set for the lower and upper triangular parts, L and U .
 - 7: **for** each message passing block l in $0, 1, \dots, N-1$ **do**
 - 8: \triangleright update using the lower-triangular matrix part
 - 9: $z_{ij}^{(l+\frac{1}{2})} \leftarrow \phi_{\theta_{z,1}^l}(z_{ij}^{(l)}, \mathbf{x}_i^{(l)}, \mathbf{x}_j^{(l)})$ for all $(i, j) \in L$
 - 10: $m_i^{(l+\frac{1}{2})} \leftarrow \bigoplus_{j \in \mathcal{N}_L(i)}^{(1)} z_{ji}^{(l+\frac{1}{2})}$
 - 11: $\mathbf{x}_i^{(l+\frac{1}{2})} \leftarrow \psi_{\theta_{e,1}^l}(\mathbf{x}_i^{(l)}, m_i^{(l+\frac{1}{2})})$
 - 12: \triangleright share the computed edge updates between the layers
 - 13: $z_{ji}^{(l+\frac{1}{2})} \leftarrow z_{ij}^{(l+\frac{1}{2})}$ for all $(i, j) \in L$
 - 14: \triangleright update using the upper triangular matrix part
 - 15: $z_{ji}^{(l+1)} \leftarrow \phi_{\theta_{z,2}^l}(z_{ji}^{(l+\frac{1}{2})}, \mathbf{x}_j^{(l+\frac{1}{2})}, \mathbf{x}_i^{(l+\frac{1}{2})})$ for all $(j, i) \in U$
 - 16: $m_i^{(l+1)} \leftarrow \bigoplus_{j \in \mathcal{N}_U(i)}^{(2)} z_{ji}^{(l+1)}$
 - 17: $\mathbf{x}_i^{(l+1)} \leftarrow \psi_{\theta_{e,2}^l}(\mathbf{x}_i^{(l)}, m_i^{(l+1)})$
 - 18: **if** not final layer in the network **then**
 - 19: \triangleright add skip connections
 - 20: $z_{ij}^{(l+1)} \leftarrow [z_{ji}^{(l+1)}, a_{ji}]^\top$ for all $(j, i) \in U$
 - 21: **else**
 - 22: $z_{ij}^{(l+1)} \leftarrow z_{ji}^{(l+1)}$ for all $(j, i) \in U$
 - 23: Apply $\sqrt{\exp(\cdot)}$ -activation function to final edge embedding of diagonal matrix entries $z_{ii}^{(N)}$.
 - 24: Return lower triangular matrix with elements $z_{ij}^{(N)}$ for $i \leq j$.
-

process (Cai et al., 2021). Note, that the graph normalization step is independent of the graph topology and only operates on the node feature vectors. In total the NeuralIF GNN model has 1 870 learnable parameters. The forward pass through the model is described in Algorithm 2.

Network training. We are training our model for a total of 50 epochs using a batch size of 5 for the synthetic problems and 1 for PDE problems. The Adam optimizer with initial learning rate 0.001 is used. Due to the small batch size and the loss landscape, we utilize gradient clipping to restrict the length of the allowed update steps and reduce the variance during stochastic gradient descent. While we use the Hutchinson’s trace estimator with $m = 1$ during training which allows a full vectorized implementation of the problem loss function. We compute the full Frobenius norm during the validation phase to avoid overfitting and ensure convergence. We use early stopping in order to avoid overfitting of the model based on the validation set performance by using the number of iterations the learned preconditioner takes on the validation data as the target.

B.2 Baselines

Conjugate gradient method. The conjugate gradient method is implemented both in the preconditioned form (as shown in Algorithm 1) and, as a baseline, without preconditioner using PyTorch only relying on matrix-vector products which can be computed efficiently in sparse format (Paszke et al., 2019). In order to ensure an efficient utilization of the computed preconditioners, the forward-backward substitution to solve for the search direction is implemented using the triangular solve method provided in the numml package for sparse linear algebra (Nytka et al., 2022). The conjugate gradient method is run until the normalized residual reaches a threshold of 10^{-6} , see Section 3 for details.

Compute. To avoid overhead due to the initialization of the CUDA environment, we run a model warm-up with a dummy input, before running inference tests with our model. The (preconditioned) conjugate gradient method – including the sparse forward-backward triangular solves for the utilized preconditioner – is run on a single-thread CPU.

Preconditioner. The Jacobi is due to its computational simplicity, directly implemented in PyTorch and scipy using a fully vectorized implementation. It can be seen in the numerical experiments that the overhead for computing this method is very small compared to the more advanced preconditioners. The incomplete Cholesky preconditioners and its modified variants with dynamic sparsity patterns and additional fill-ins are implemented using the highly efficient C++ implementation of ILU++ with provided bindings to python (Mayer, 2007; Hofreither, 2020).

The data-driven NeuralPCG baseline – which uses a simple encoder-decoder GNN architecture – (Li et al., 2023) is implemented in pyTorch and pyTorch geometric following a very similar approach to NeuralIF. The hyper-parameters for the model are chosen as specified in the paper: using 16 hidden units with a single hidden layer for encoder, decoder and GNN update functions and a total of 5 message passing steps. This results in a total of 10 177 parameters in the model which means the parameter count is over 5 times higher than our proposed architecture which makes inference using the NeuralPCG model more expensive during inference. Due to computational limits, the batch size is reduced during training compared to the original paper.

The results obtained from the model are similar to the one presented by Li et al. (2023). However, in our experiments we observed a higher pre-computation time which can be explained by the fact that different hardware acceleration is used. Further, in our experiments different sparsity patterns are used showing the poor computational scaling of the NeuralPCG model. In terms of resulting number of conjugate gradient iterations, our experiments match the results from the paper.

C Additional Results

Here, we present additional results and extensions of the baseline NeuralIF preconditioner. We both describe how to include reordering and fill-ins into the learned preconditioner as well as show more in-depth results. In Section C.2, we conduct an ablation study, probing the different loss functions proposed to train the learned preconditioner. Finally, we show the convergence behavior of the PCG algorithm for the different preconditioner.

C.1 Model improvements

It is possible to combine our learned preconditioner with existing reordering methods. Classical reordering schemes such as COLMAD are executed in the symbolic phase before obtaining the values for the non-zero elements in the preconditioner (Gonzaga de Oliveira et al., 2018). Since our message passing scheme implicitly takes into account the ordering of the nodes, the nodes can simply be relabeled prior to running the forward pass of the neural network which influences the split into lower and upper triangular matrices that are used for the message passing.

In our experiments we also tried enforcing the diagonal residuals in the loss function (6a) to be zero by choosing the diagonal elements of the preconditioner appropriately following a similar approach to the classic incomplete Cholesky. However, this neither improved the overall objective nor the performance of the model as a preconditioner.

C.2 Comparison of loss functions

In this section, we compare the different loss functions proposed to train the learned preconditioner. Computing the condition number as proposed in Sappl et al. (2019) as a loss function, is computationally infeasible in our approach since the underlying problems are large-scale compared to the problems encountered in the previous work. For the matrices used in our experiments, computing the condition number in the forward process is often computationally very expensive and therefore, the approach is omitted. We compare instead

Table 5: Comparison of NeuralIF preconditioner performance on the synthetic problem set trained using different loss functions. The validation loss is the Frobenius norm distance given in equation (6a). Time-per-epoch lists the training time for one epoch of training data (consisting of 1000 samples), using a batch size of 1, in seconds.

Loss function	Validation Loss ↓	Time-per-epoch ↓
Frobenius	324.2	850
Stochastic	325.7	90

the full Frobenius norm as a loss as shown in objective (6a), the stochastic approximation we suggest using Hutchinson’s trace estimator as shown in equation (7), and the supervised loss proposed by (Li et al., 2023).

The main drawback of utilizing the loss function proposed by Li et al. (2023) is that it is a supervised loss meaning it requires a dataset of already solved optimization problems. In contrast, our loss is self-supervised and thus it is sufficient to have access to the problem data $\mathbf{A}_i, \mathbf{b}_i$ but not the solution vector \mathbf{x}_i . This saves significant time in the dataset generation. Further, it allows us to train a preconditioner on an existing dataset without solving all problems beforehand or even applying the learned preconditioner on the training data. The full Frobenius loss is also self-supervised but requires a matrix-matrix multiplication which leads to a large memory consumption and expensive forward and backward computation leading to longer training times. Further, matrix-vector multiplications are significantly easier to optimize and build a cornerstone of the CG algorithm allowing for example matrix-free implementations.

The stochastic and full Froebnius loss functions are compared in Table 5. We are training all models for 20 epochs and use a batch size of 1 on the synthetic dataset. Thus, the number of parameter updates in the training for all models is the same. We can see that computing the full Frobenius norm as a loss function is significantly more expensive in terms of computational time than utilizing the stochastic approximation or and further requires significantly more memory which means we can not apply it to large-scale problems. Training a model for 20 epochs with the full loss takes roughly 5 hours, while using the stochastic approximation or supervised loss, training is finished in around 30 minutes without decreasing the obtained preconditioner performance. Further, the reduced memory consumption allows us to increase the batch size in other experiments leading to an even larger speedup in training time and additional noise reduction during the training process.

Even though we use a stochastic approximation to train our model, the validation loss computed as the full objective does not increase significantly. Both the training loss and the validation loss for the different loss functions are compared in Figure 7. One explanation for this is that the noise in the stochastic gradient descent method is already very large influencing the optimization procedure. Further, the added noise might help prevent overfitting on the training samples leading to a better performance of the stochastic loss in terms of validation loss.

We can see that for small problem instances, the two methods lead to nearly the same time overhead required to compute the preconditioner. However, for larger problem instances with more than 1 000 000 elements, our NeuralIF preconditioner clearly outperforms the incomplete Cholesky method in the time it is required to compute the preconditioner. Further, our method scales better when considering large problem instances. One possible explanation for this is that the overhead of our method is dominating the reported precomputation time for the small instances since the implementation of the GNN-based method is not optimized. For larger problems, this overhead becomes less relevant. However, larger problem instances are more interesting since the amortization of small instances is more difficult to start with. Further, our method leads to significantly less variance in the precomputation time. Further, we can see that for problems with large size, the precomputation time of the incomplete Cholesky method can vary a lot. In comparison, the neural network-based preconditioner is able to output the preconditioning matrix nearly in constant time for a given problem size. This is valuable since it allows a predictable cost to utilize our preconditioner when applying it to new problems.




Figure 7: Comparison of the training and validation loss for the Frobenius norm minimization and the stochastic approximation of the loss proposed by us. Here, we only compare the loss functions based on iteration count, not the actual time required to run the model training.

For the time required to solve the problem – ignoring the previously spent time to compute the preconditioner – using the conjugate gradient method, we can see that both CG and NeuralIF perform very similar. The results, which are shown in Figure 5b, show that the learned preconditioner clearly generalizes to the significantly larger problem instances and continues to produce well-performing preconditioners in terms of reduction in iterations and solving time of the CG algorithm.

Thus, in summary, we can see that the data-driven method is easier to compute and scales better for large problems while maintaining the performance of the incomplete Cholesky method in terms of the required solving time for the preconditioned problem.

C.3 PCG convergence

Synthetic problem. Here, additional results for the synthetic dataset are shown. Notably, Figure 8 shows the convergence of the different (preconditioned) CG runs on a single problem instance from the synthetic dataset where both the residual – which is also used as a stopping criterion – and the usually unavailable distance between the true solution and the iterate are shown. Further, for each problem the $\kappa(\mathbf{A})$ worse case bound is displayed.

The distribution of the eigenvalues of the linear equation system – shown in Figure 3 in the main paper for this problem instance – directly influence the convergence behavior of the method. However, as it is commonly observed in the CG method, the $\kappa(\mathbf{A})$ -bound only describes the convergence behavior locally and overall, the algorithm converges significantly faster than the worst-case bound (Carson et al., 2023). We can, however, observe that the better conditioning still improves the convergence significantly and the obtained speedup is proportional to the speedup obtained in the worse-case bound making the condition number – at least for the problem instances considered in this dataset – a good measure for the performance of the conjugate gradient method. Further, we can see that our learned NeuralIF preconditioner is especially effective in the beginning of the CG algorithm and is able to outperform IC(0) for the first 100 iterations.




Figure 8: Convergence of the different preconditioned linear systems on a synthetic problem instance.