

GoT: ROBUST INFORMATION SEEKING WITH LLMs USING GAME THEORY

Anonymous authors

Paper under double-blind review

ABSTRACT

Large Language Models (LLMs) are increasingly deployed in real-world settings where key task information is missing, making active information seeking essential. Many existing approaches impose simplifying assumptions that can degrade *worst-case* performance, which is problematic in high-stakes applications. In this work, we use the game of Twenty Questions to evaluate the information-seeking ability of LLMs. We introduce and formalize its adversarial counterpart, the Strategic Language Search (SLS) problem along with its variants as a two-player zero-sum extensive form game. We propose Game of Thought (GoT), a framework that applies game-theoretic techniques to approximate a Nash equilibrium (NE) strategy for the restricted variant of the game. Across all evaluated settings, GoT consistently improves worst-case performance over pure prompting and heuristic-guided search baselines.

1 INTRODUCTION

Large language models (LLMs) are increasingly being deployed in high-stakes environments like planning Zhang et al. (2024a), medical diagnosis Li et al. (2024), as well as other tasks exhibiting partial observability Li et al. (2025). In such environments, the LLM may not have sufficient information to complete its assigned task. This necessitates an information-seeking process, typically via clarification questions. To quantitatively assess information-seeking ability, we turn to the *Game of 20 Questions* Siegler (1977). Here, an item is chosen from a known set. The player then sequentially asks up to twenty Yes/No questions to identify the item using as few questions as possible.

Information seeking often requires some lookahead. Well-known methods involve a combination of prompting and LLM-based reasoning, such as Self-Consistency (SC) Wang et al. (2022) and Tree of Thought (ToT) Yao et al. (2023). More recently, Hu et al. (2024) propose Uncertainty of Thought (UoT), which utilizes tree search to *explicitly model and optimize* for the information gained from clarification questions. However, they assume that the item is chosen uniformly at random. This is unlikely to hold in the real world, either because (i) the context itself does not naturally admit a probabilistic interpretation Jain (2016), or (ii) even if a distribution exists, it might not be easily obtainable, and is likely non-uniform Choudhury et al. (2025). Particularly for high-stakes environments, we argue that one should assume the *worst case*. That is, the item is chosen *adversarially*, and our goal is to utilize a questioning strategy that optimizes the worst-case performance.

Motivated by this, we propose Game of Thought (GoT), a game-theoretic framework designed to handle such scenarios. We model information-seeking process as a two-player, zero-sum game with imperfect information. In this formulation, the item (distribution) is assumed to be selected by an adversary seeking to impede the information seeker. GoT optimizes for the worst-case performance by approximating the Nash equilibrium (NE) of this game, avoiding any need for strong prior assumptions on item distribution.

Contributions We (i) formulate the Strategic Language Search (SLS) problem and its variants, (ii) establish game theoretic solutions that solve SLS and its variants optimally, highlighting these strategies are necessarily randomized, (iii) propose GoT to approximate the NE in SLS-restricted variant, (iv) empirically demonstrate that in various settings, GoT is superior to (a) pure prompting-based and (b) UoT-based methods in the worst-case.

2 RELATED WORK

Uncertainty of Thought GoT can be regarded as an extension of *Uncertainty of Thought* (UoT) by Hu et al. (2024). The authors propose performing depth limited search over possible questions asked, seeking to maximize expected information gain under the assumption that the items are *chosen uniformly at random*. GoT performs similar explicit lookahead, but obviates this assumption via game-theoretic approaches to optimize for the worst-case item chosen.

Natural Language in Games We formulate games that implicitly consider natural language as the action space. Language is often used in games for communication between players as means to negotiate Kramár et al. (2022), share information Ri et al. (2022), and coordinate Bishop et al. (2020). Studying language in this context poses an interesting challenge due to the difficulty of providing a well-defined notion of optimality and in analyzing its effect. These communications resemble signals in signaling games Lewis (1969); Farrell & Rabin (1996); Gintis et al. (2001). However, these games typically consider a finite set of signals, unlike communications in natural language. Prior studies have attempted to reconcile this difference via various techniques such as sentiment analysis Capraro et al. (2024); Houser & Xiao (2011), or by sampling from LLMs conditioned on the game context Gemp et al. (2024); Kempinski et al. (2025), leveraging its reasoning to filter irrelevant utterances while using game theory inspired techniques to design strategy.

Information-seeking ability of LLMs Prior studies examined LLM information seeking ability in the context of ambiguous queries or under-specified tasks. In these settings, the LLM is initially missing details needed to complete the task and must pose clarifying questions to identify either user intent Kuhn et al. (2022); Zhang et al. (2024a); Xu et al. (2019) or elicit user preferences Handa et al. (2024); Li et al. (2023). Framed this way, the problem becomes one of reasoning about which additional information would make the task well specified. Exploration based prompting has been shown to help (SC, ToT Wang et al. (2022); Yao et al. (2023); Choudhury et al. (2025)), while other approaches select queries using heuristics such as expected information gain Grand et al. (2024); Piriyakulkij et al. (2023), including UoT Hu et al. (2024). Benchmarks evaluating information-seeking ability of LLMs have been constructed in the context of underspecified tasks Li et al. (2025), medical diagnosis Li et al. (2024); Chen et al. (2025), and troubleshooting Raghu et al. (2021), demonstrating the importance of this capability in actual application.

3 PROBLEM FORMULATION

While the Game of 20 Questions is not strictly adversarial, we present an adversarial variant which we refer to as Strategic Language Search (SLS) to enable utilization of game theoretic methods to optimize for the worst-case. A SLS game is played over a finite set \mathcal{S} of n distinct items between two competitive (zero-sum) players, the *Item Chooser* and *Questioner*. We will assume a countable set of binary (i.e., true-false) questions \mathcal{Q} . Each question is uniquely specified by a finite-length natural language string. For every item $s \in \mathcal{S}$, we denote by $f : \mathcal{Q} \times \mathcal{S} \rightarrow \{0, 1\}$ the *answer* to $q \in \mathcal{Q}$ for some $s \in \mathcal{S}$. A natural but degenerate \mathcal{Q} is one which we denote by \mathcal{Q}_∞ . A possible textual representation of \mathcal{Q}_∞ would be the set of questions stated in boolean form “Is the Item 1 or Item 3, but not Item 2 or Item 4?”

A SLS is defined by $(\mathcal{S}, \mathcal{Q}, f)$ and proceeds in two phases. In the first phase, the Item Chooser privately selects a single item $s^* \in \mathcal{S}$. In the second phase, the Questioner elicits information about s^* by sequentially asking and obtaining answers to a series of questions $q_1, a_1, \dots, q_T, a_T$ where $q_t \in \mathcal{Q}$ and $a_t = f(q_t, s^*)$, i.e., the answer to q_t for s^* .

The history of questions and answers up to and including time $t \geq 0$ is given by $H_t = (Q_t, A_t)$, where $Q_t = (q_1, \dots, q_t)$, $A_t = (a_1, \dots, a_t)$ such that $Q_t(\tau) = q_\tau$ and $A_t(\tau) = a_\tau$. Given history H , we denote by $H'(q, a)$ the new history when a new question q is asked with answer a . The Questioner selects its questions online, i.e., q_t may depend on its observed history H_{t-1} . The length of history H is denoted by $|H|$. The set of items consistent with history $H = (Q, A)$ is denoted by

$$S(H) = \{s \in \mathcal{S} \mid \forall \tau \in [|H|], f(Q(\tau), s) = A(\tau)\} \subseteq \mathcal{S}.$$

Note that $S(H)$ is never empty, as it must contain at least s^* . The game continues until the Questioner can identify s^* with certainty, i.e., $|S(H)| = 1$, after which the game ends with the Item

108 Chooser (resp. Questioner) incurring a reward (resp. cost) of $|H|$. The objective for the Questioner
 109 is to find a strategy (or equivalently, policy) that minimizes its expected cost regardless of how the
 110 Item Chooser chooses s^* , optimizing its worst-case performance. This corresponds to the *NE* of a
 111 zero-sum game and will typically be randomized. We will define the solution concept formally after
 112 stating several assumptions and variants.

113 **Assumption 3.1.** Each question-item pair $(q, s) \in \mathcal{Q} \times \mathcal{S}$ has a unique answer $f(q, s)$ independent
 114 of history.

115 **Assumption 3.2.** After fixing s^* , the Item Chooser cannot lie with regard to its answers to questions.
 116

117 **Assumption 3.3.** \mathcal{S} , \mathcal{Q} and f are common-knowledge.

118 **Assumption 3.4.** Constant time oracle access to f .

119 **Assumption 3.5.** For every pair of distinct items $s, s' \in \mathcal{S}$, there exists some $q \in \mathcal{Q}$ where $f(q, s) \neq$
 120 $f(q, s')$.
 121

122 Theorems 3.1 and 3.2 are implicit assumptions baked into the definition of f while Theorem 3.5 is
 123 a technical assumption imposed on \mathcal{Q} and f . It ensures that there exists a strategy that allows the
 124 Questioner to find the correct item in finite time. Note that it is trivially satisfied when \mathcal{Q} includes
 125 “identity” questions such as “is the item ‘ s ’?”.
 126

127 **Example 1.** Consider the SLS with \mathcal{S} and \mathcal{Q} :

$$128 \left\{ \begin{array}{l} s^{(1)} : \text{‘Oppenheimer’} \\ s^{(2)} : \text{‘Alan Turing’} \\ s^{(3)} : \text{‘A Beautiful Mind’} \end{array} \right\}, \left\{ \begin{array}{l} q^{(1)} : \text{‘Related to codes?’} \\ q^{(2)} : \text{‘Is it a movie?’} \\ q^{(3)} : \text{‘Is it a person?’} \end{array} \right\}$$

132 Then $f(q^{(i)}, s^{(j)}) = 0$ if $j = i$, 1 otherwise.
 133

134 It is easy to verify that Theorem 3.5 holds in Example 1. By selecting $q^{(1)}$ and $q^{(2)}$ in sequence, one
 135 can guarantee that the Questioner asks no more than 2 questions. The best the Item Chooser can do
 136 against this strategy is to select $s^* = s^{(2)}$ or $s^{(3)}$, since doing so guarantees that there are always two
 137 items consistent after the first question, i.e., $|S(H_1)| = 2$. However, the Questioner can do better
 138 by choosing the first question uniformly at random. This guarantees that regardless of the choice
 139 of s^* , there is $1/3$ probability that the item can be determined with exactly one question, thus the
 140 expected number of questions asked is $1/3 \cdot 1 + 2/3 \cdot 2 < 2$. This strategy minimizes the worst-case
 141 cost regardless of what s^* the Item Chooser chose. In this example, we are lucky that the optimal
 142 strategy for the Questioner is symmetric due to the circular symmetric nature of \mathcal{Q} and f . This is
 143 not true for more general \mathcal{Q} , f .

144 So far, SLS has been presented mostly as a combinatorial problem. Indeed, when \mathcal{Q} is finite, we
 145 have:

146 **Theorem 3.6.** Given a known (deterministic) s^* , deciding if there exists a sequence of k questions
 147 $Q \subseteq \mathcal{Q}$ such that $S(H) = \{s^*\}$ is NP-complete.
 148

149 The reduction is straightforward from set-cover and included in the appendix. In game theoretic
 150 parlance, this implies that the *best-response* of the Questioner to any deterministic Item Chooser
 151 strategy is hard to compute.

152 **Theorem 3.7.** Let $(\mathcal{S}, \mathcal{Q}_\infty, f)$ be a SLS, where $|\mathcal{S}| = 2^k$ for some $k \in \mathbb{Z}^+$. An “even-split” strategy
 153 where $\forall t, q_{t+1}$ is selected such that $|S(H'_t(q_{t+1}, 0))| = |S(H'_t(q_{t+1}, 1))|$ minimizes the number of
 154 questions asked in the worst-case for the Questioner and costs exactly k questions.

155 Theorem 3.7 states that in the special case where $\mathcal{Q} = \mathcal{Q}_\infty$ the problem becomes easy, agreeing with
 156 the intuition that splitting the items evenly is optimal. We show in the appendix that the even-split
 157 strategy is optimal in UoT’s setting where s^* is chosen uniformly at random Hu et al. (2024); in fact,
 158 they constitute a NE in game setting. This justifies their implicit approach of maximizing entropy
 159 loss and usage of LLM prompts that encourage even-splits.
 160

161 **SLS-Restricted (SLSR)** Vanilla SLS can be quite cumbersome to reason about for larger n and
 \mathcal{Q} . As such, we propose a SLSR, a restricted variant where questions are generated based on the

162 remaining items $S(H)$. A SLSR is formally given by $(\mathcal{S}, \mathcal{Q}, f, g)$, where $g : 2^{\mathcal{S} \setminus \phi} \rightarrow 2^{\mathcal{Q} \setminus \phi}$ is a
 163 set function taking a nonempty set of items $S \subseteq \mathcal{S}$ and outputs a nonempty set of no more than
 164 $m \geq 1$ questions; here m is a parameter associated with g . The rules and payoffs in SLSR are
 165 identical to SLS, except that the Questioner is restricted to selecting $q_t \in g(S(H_{t-1}))$. To ensure
 166 that progress can always be made, we impose a stronger version of Assumption 3.5 and require that
 167 g outputs at least one question that strictly reduces the set of consistent items. Note that in a SLSR
 168 game, an optimal Questioner can perform no better than in the corresponding SLS game. Thus its
 169 performance in the SLSR game can be seen as an underestimation of its performance in SLS. This
 170 design is motivated by our goal of examining the worst-case performance.

171 **Assumption 3.8.** For every subset $S \subseteq \mathcal{S}$, there exists some $q \in g(S)$ and a pair of distinct items
 172 $s, s' \in S$ where $f(q, s) \neq f(q, s')$

173
 174 **Weighted-SLS (WSLS)** In real-world scenarios, certain items may carry greater importance and
 175 should be prioritized during the information-seeking process. For instance, in medical diagnosis,
 176 delays in identifying life-threatening conditions can have more severe consequences. Hence, we
 177 propose weighted-SLS, a variant of SLS defined by $(\mathcal{S}, \mathcal{Q}, f, w)$, where $w : \mathcal{S} \rightarrow \mathbb{R}^+$. The cost
 178 incurred by the Questioner with s^* as the selected item is redefined to be $w(s^*) \cdot |H|$, imposing
 179 greater penalties for prolonged interactions involving high-weight items. Weighted SLSR (WSLSR)
 180 is defined in a similar manner by $(\mathcal{S}, \mathcal{Q}, f, g, w)$. The corresponding weighted variant of the non-
 181 adversarial game of Twenty Questions is defined similarly.

182 **Example 2.** SLSR $(\mathcal{S}, \mathcal{Q}, f, g)$ with $\mathcal{S}, \mathcal{Q}, f$ identical to Example 1, $g(S) = \{q^{(1)}, q^{(2)}\}$ when $S = \mathcal{S}$
 183 and \mathcal{Q} otherwise.

184 In Example 2, the first question is restricted to be either $q^{(1)}$ or $q^{(2)}$. Regardless of how the Ques-
 185 tioner randomizes between them, the Item Chooser can always select $s^* = s^{(3)}$; this guarantees that
 186 $a_1 = 1$ and hence $|S(H_1)| = 2$. Thus, the Questioner requires at least one additional question,
 187 taking 2 questions in total.

188 **Example 3.** WSLS $(\mathcal{S}, \mathcal{Q}, f, w)$ with $\mathcal{S}, \mathcal{Q}, f$ identical to Example 1, $w(s^{(1)}) = 3, w(s^{(2)}) =$
 189 $w(s^{(3)}) = 2$.

190
 191 In Example 3, Questioner can select $q^{(1)}, q^{(2)}, q^{(3)}$ with probability $3/4, 1/8, 1/8$ as q_1 . This ensures
 192 the expected cost is no greater than $15/4$. In contrast, selecting q_1 uniformly incurs a cost of 5 when
 193 $s^* = s^{(1)}$ is chosen.

194
 195 **Defining SLS via Large Language Models.** For many applications, \mathcal{S} is too large for us to realis-
 196 tically hand-curate a set of \mathcal{Q} , noting that we would like to avoid “unnatural” questions that involve
 197 long, complicated boolean expressions. Therefore, in this paper we define \mathcal{Q}, f , and g implicitly
 198 using Large Language Models (LLM). Specifically, \mathcal{Q} is the set of questions that a LLM can pro-
 199 pose asking based on certain prompts, and f is the response of a LLM to a prompt of q when asked
 200 about s^* . For instance, Is Oppenheimer a movie?. We wish to emphasize that f can be
 201 implemented by any oracle, such as human experts. We chose to implement it via LLMs for the
 202 ease of experimentation. Furthermore, g in SLSR and WSLSR can be defined as the output of a
 203 LLM with respect to a prompt asking for $m \geq 1$ questions after defining the rules of SLS and $S(H)$,
 204 the items remaining. An example of this is Currently the set of possible items is
 205 $\{\text{Oppenheimer}, \text{Alan Turing}\}$. Propose m best questions.

206 **Assumption 3.9.** The LLM for f makes no mistakes when used as an oracle for $f(q, s^*)$.

207
 208 Assumption 3.9 and 3.1 enable the practical usage of LLMs as a black-box for defining SLS. For
 209 most LLMs, Assumption 3.4 is also satisfied, though the constant factor may be large. We discuss
 210 all assumptions made in the appendix.

211 4 SLS AS ZERO-SUM EXTENSIVE FORM GAMES

212
 213 A vanilla SLS $(\mathcal{S}, \mathcal{Q}, f)$ may be expressed as a two-player zero-sum extensive form game (EFG)
 214 with imperfect information. EFGs are rooted game trees, where each vertex corresponds to the
 215 game’s entire history. Edges represent actions available to the player-to-move at that vertex. EFGs

are endowed with information sets (infosets), which partition vertices belonging to the same player; vertices in the same infoset are indistinguishable to the player owning them. This captures the notion of imperfect information.




Figure 1: EFG representation of Example 1. The root node \blacktriangle belongs to the Item Chooser and the other nodes ∇ belong to the Questioner. Edges in black correspond to the choice of item s^* . Colored edges in red, blue, and green refer to questions $q^{(1)}$, $q^{(2)}$, and $q^{(3)}$ respectively. Vertices connected by dotted lines belong to the same infoset. Payoffs (resp. costs) to the Item Chooser (resp. Questioner) are shown in the leaves. We omit edges (and their descendants) where the same question is asked more than once; these are never optimal and correspond to dominated actions.

In the EFG formulation, the Item Chooser only takes an action at the root, after which the Questioner asks up to $n - 1$ questions in sequence.¹ Every state apart from the root can be uniquely identified by the tuple (s^*, H) which describes item s^* chosen and a (potentially empty) history of past questions and answers. Leaf vertices are those where either (i) $|H| = n - 1$, where the maximum number of questions are asked, or (ii) $|S(H)| = 1$, where s^* is identified. At a leaf, the reward (resp. cost) to the Item Chooser (resp. Questioner) is $|H|$. All non-leaf vertices with the same history H belong to the same infoset, which we denote by $I(H)$. Figure 1 illustrates the SLS for Example 1.

A deterministic strategy π of the questioner is given by a mapping from every infoset $I(H)$ to some question $q \in \mathcal{Q}$ to be chosen for $q_{|H|+1}$. Following π when s^* is chosen yields the following history H_0, \dots, H_T , given by

$$q_{t+1} = \pi(I(H_t)), a_{t+1} = f(\pi(I(H_t)), s^*),$$

where T is the time the game ends, i.e., $|S(H_T)| = 1$. The corresponding utility for the Item Chooser (resp. cost for the Questioner) at the end of the game is $u(\pi, s^*) = |H_T|$.

Let the set of all deterministic strategies be Π , Δ_Π the probability simplex over Π , Δ_S the probability simplex over \mathcal{S} . Then the expected utility under random policies $x \in \Delta_\Pi$ and $y \in \Delta_S$ for Questioner and Item Chooser respectively is (with some abuse of notation) denoted by

$$u(x, y) = \mathbb{E}_{\pi \sim x, s^* \sim y} [u(\pi, s^*)].$$

The NE of this zero-sum game is given by the solution to the bilinear saddle-point problem


$$\min_{x \in \Delta_\Pi} \max_{y \in \Delta_S} u(x, y) = \max_{y \in \Delta_S} \min_{x \in \Delta_\Pi} u(x, y) \quad (1)$$

where equality holds as a consequence of Von Neumann’s minimax theorem v. Neumann (1928). The solution (x^*, y^*) yields optimal randomized strategies for each player, i.e., each player is best-responding to the other. In particular, x^* is the *distribution* over Questioner policies that is robust against the worst-case choice of s^* . EFGs for SLSR, WLS and WLSLR may also be constructed by one or both of (i) restricting the actions available at each infoset to $g(S(H))$ or (ii) adjusting leaf payoffs to depend on w and s^* .

Solving EFGs. In general, two-player zero-sum EFGs with perfect recall (including SLS and its variants) can be solved in time polynomial to the size of the game tree. Some classical methods include linear programming Von Stengel (1996) and counterfactual regret (CFR) minimization Zinkevich et al. (2007). Efficient game-solving and strategy representation in EFGs is a well studied topic and beyond the scope of this paper, though we give a brief overview in the appendix. Instead, we will simply employ off-the-shelf solvers Liu et al. (2024); Lanctot et al. (2019).

¹This keeps the game tree finite, and is justified since asking the same question more than once is suboptimal.

270 5 GAME-OF-THOUGHT AND SUBGAME SEARCH
 271
 272



273
 274
 275
 276
 277
 278
 279
 280 Figure 2: **An overview of GoT.** To choose the question at time step t , we (1) perform depth limited
 281 simulation (2) Construct a subgame (3) Solve it for a local strategy which (4) informs the choice of
 282 the question. Steps 1 to 3 devise the strategy, while step 4 plays the game.

283
 284 The space of natural language questions is naturally large. Thus for practicality, we focus on the
 285 restricted variants of SLS with a small candidate questions set size m . Nonetheless even under
 286 this restriction, explicitly constructing and solving the full (W)SLSR game tree is impractical for
 287 larger hypothesis spaces, as it entails querying an LLM at every infoset to propose questions and
 288 provide answers, with each call incurring multi-second latency. In our experiments, building the
 289 complete tree for a 25-item set required 5–6 hours to construct 3763 infosets. For larger datasets
 290 (approximately 100 items), this quickly becomes infeasible. To address this challenge, GoT employs
 291 an iterative, on-demand strategy construction paradigm, computing strategies only when an infoset
 292 is reached. Inspired by the subgame search techniques used in poker bots Brown & Sandholm (2018;
 293 2019), GoT constructs a subgame rooted at the current infoset and truncates it to a fixed depth d . The
 294 leaf nodes of this subgame are evaluated using heuristic functions. This truncated subgame is then
 295 solved to obtain a local strategy for the questioner, which informs the selection of the next question.
 296 An overview is provided in Figure 2.

297
 298 **1. Depth Limited Simulation** We begin by exploring the possible future outcomes and questions
 299 for the Questioner. At infoset $I(H_t)$, a set of candidate questions $g(S(H_t))$ is generated using a
 300 LLM. For each candidate, we use a LLM as f to identify the set of items for which the answer to c_i
 301 is yes, denoted by $Y(S(H_t), c_i)$, where

$$Y(S, q) = \{s \in S \mid f(q, s) = 1\} \text{ for some } S \subseteq \mathcal{S}.$$

302
 303 and the complement set denoted by $\bar{Y}(S(H_t), c_i) = S(H_t) \setminus Y(S(H_t), c_i)$. These sets represents
 304 the two possible outcomes of asking candidate question c_i at step t , with $Y(S(H_t), c_i)$ (resp.
 305 $\bar{Y}(S(H_t), c_i)$) representing the set of items consistent with the history $H'_t(c_i, 1)$ (resp. $H'_t(c_i, 0)$).
 306 The corresponding infosets $I(H'_t(c_i, 1))$, $I(H'_t(c_i, 0))$ are constructed based on these outcomes.
 307 This process is repeated to construct the infosets for d steps, resulting in a simulation tree as seen in
 308 step 1 of Figure 2. Note that this step is similar to the question simulation and generation step of the
 309 UoT framework, and incurs a similar number of LLM calls when the same d and m are used.

310
 311 **2. Translation to EFG** We then construct a subgame based on the simulation tree. The tree is
 312 converted into an EFG representation of the truncated subgame, as shown in step 2 of Figure 2.
 313 Note that the subgame begins with the Item Chooser “re-choose” a new distribution over $S(H_t)$
 314 at each iteration even if $I(H_t)$ is not at the beginning of the game (i.e. $t \neq 0$), which seemingly
 315 accord more power to the Item Chooser. This lets us perform *safe* subgame search Moravcik et al.
 316 (2016), which is discussed in the appendix. Each leaf node in the game tree l is assigned a payoff
 317 of $d(l) - 1 + h(l)$ for the Item Chooser (and the negative of that for the Questioner) where $d(l)$
 318 is the depth of node l in the tree representing the number of questions asked after step t before
 319 reaching the node l , and h is a heuristic function that estimates the number of questions that remain
 320 to be asked for the Questioner to identify the correct item. In our experiments for SLSR we set
 321 $h(l) := \log_2(|S(l)|)$, which provides an optimistic estimation on the remaining turns.

322
 323 **3. Extensive Form Game Solving** To solve the subgame, we used LiteEFG’s Liu et al. (2024)
 implementation of CFR minimization to obtain an approximate NE.

324 **4. Selecting the Next Question** To choose the question to ask at step $t + 1$, one question q_{t+1}
325 is sampled from $g(S(H_t))$ using the the Questioner strategy from the NE. We move to the infoset
326 $I(H'_t(q_{t+1}, 0))$ if $f(q_{t+1}, s^*) = 0$, and $I(H'_t(q_{t+1}, 1))$ otherwise.

327 This process is repeated until an infoset $I(H_n)$ where $|S(H_n)| = \{s^*\}$ is reached. Note that most
328 of the computational cost of GoT is incurred in Step 1 due to LLM response latency. The remaining
329 steps contribute negligibly.

330 **Theorem 5.1.** *GoT is safe with respect to value estimates that only depend on $S(H_t)$.*

332 6 EXPERIMENTS AND RESULTS

333 We are interested in answering the following: *Does GoT improve the worst-case performance com-*
334 *pared to other methods in all settings?* We also examine how the (i) quality of the questions (ii)
335 simulation depth d affect its performance, and (iii) the trade-offs between average and worst-case.

336 6.1 DATASETS AND SETTINGS

337 **20 Questions(20Q):** Each dataset is a collection of distinct items. Prior studies Bertolazzi et al.
338 (2023); Zhang et al. (2024b) used datasets such as *Things* Hebart et al. (2019) and *Celebrities*,
339 which we found to be too large for this study. This led to us constructing several datasets: (i)
340 *Common*: A set of 136 items built upon the dataset collected for UoT Hu et al. (2024), which
341 we further modified by adding more items. (ii) *Breeds*: A set of 25 popular cat and dog breeds
342 collected by us. (iii) *S128*: A set of 128 items, consisting of 2 weapons, 6 scientists, 24 dishes, and
343 96 animals collected by us. In addition to the setting of 20Q, we also present results in two more
344 practical domains. **Medical Diagnosis(MD):** A doctor seeks to diagnose a patient by asking about
345 the symptoms they are experiencing. We use *DXBench(DX)* Chen et al. (2025), and randomly select
346 100 out of the 461 unique diseases in the dataset as the hypothesis space. **Troubleshooting(TS)**
347 A car mechanic attempts to help a customer diagnose the car fault they are experiencing by asking
348 about the symptoms. We use *FloDial* Raghu et al. (2021), consisting of 2,738 dialogs grounded on
349 12 different troubleshooting flowcharts. We obtained 59 unique car faults after data preprocessing,
350 which we used as the hypothesis space. Details are deferred to the appendix.

351 6.2 BASELINES

352 We primarily compare with UoT Hu et al. (2024). For both UoT and GoT, we set $d = m = 3$
353 unless otherwise stated. We additionally consider Direct Prompting (DP) where the LLM is asked
354 to generate the next question, and Direct Choice (DC) where the LLM is asked to choose from a set
355 of candidate questions. Each strategy is played against all possible s^* in each dataset and the worst
356 performance across all items is taken: $L_{worst} = \max_{s \in \mathcal{S}} |H^s|$, where H^s is the interaction history
357 of a method when s is the chosen item.

358 6.3 MODELS AND PROMPTS

359 We mainly experimented on GPT 4.1 OpenAI (2024) (gpt-4.1-2025-04-14 checkpoint) and
360 Qwen 2.5 72B Instruct Yang et al. (2024). In 20Q, we utilized two different prompts for sampling
361 questions. The *even* prompt, adopted from Hu et al. (2024), explicitly instructs the LLM to ask
362 questions that split items as evenly as possible. When using this prompt, we noticed unnatural
363 questions (e.g., Does this item begin with a letter from A-M?). These questions are ill-suited for
364 realistic settings as respondents may find it difficult to answer. This leads to the *natural* prompt,
365 which instructs LLMs to refrain from asking such questions. All results reported below use the
366 *natural* prompt. Comparison between the two prompts is deferred to the appendix. This issue was
367 not observed in the MD and TS settings.

368 6.4 ACCOUNTING FOR RANDOMNESS

369 (1) When a LLM is used as g to generate questions, the set of candidate questions $\mathcal{Q}(S(H_t))$ may
370 differ across runs. To provide a fair comparison between similar methods, we first play the game
371 using GoT and cache the questions in the simulation tree. The cached questions are reused for

DC and UoT. (2) The Questioner strategy designed by GoT is nondeterministic. To obtain the performance for each s^* , we average over ten plays of the game using the same strategy.

6.5 UNWEIGHTED VARIANT

As shown in Table 1, GoT consistently outperforms UoT in terms of worst-case interaction length. The prompting-based DP occasionally outperforms UoT, suggesting that while UoT can improve average-case performance, it may do so at the expense of worse worst-case performance.

Method	Common	20Q		MD	TS
		S128	Breeds	DX	FloDial
GPT 4.1					
GoT	<u>10.2</u>	<u>11.8</u>	<u>7.4</u>	<u>12.2</u>	<u>7.9</u>
UoT	11	13	9	13	9
DP	13.8	16.2	7.8	16.8	12.7
DC	12.9	14.6	9.3	16.2	11.6
Qwen 2.5 72B Instruct					
GoT	<u>10.0</u>	<u>10.8</u>	<u>6.6</u>	<u>10.5</u>	<u>7.5</u>
UoT	11	12	8	12	9
DP	12.7	19.2	8.0	12.4	10.7
DC	12.7	17.9	7.8	13.3	10.5

Table 1: **Worst case interaction length for each method in various settings.** Best performance for each setting is underlined.

From Theorem 3.7, we know that if a LLM is always able to propose questions that perfectly split $S(H)$ into even halves, we would be able to achieve the optimal performance by always asking such a question. However, we see that this is not the case: all methods fall short of the theoretical optimal performance of $\log_2(|S|)$ by around 2 to 3 turns of interaction. This suggests that in practice, particularly in realistic settings such as medical diagnosis or troubleshooting, it may be difficult to phrase a sufficiently natural question that achieves an even split. In such cases, considering multiple candidate questions and adopting a randomized selection strategy, as GoT does, can hedge against outliers, avoiding an excessively long conversation in the worst-case.

6.6 WEIGHTED VARIANT

We further examine the performance in the weighted variant of each setting. GoT now formulates the setting as a WLSLR game, and replaces the heuristic function used in the subgames with $h(l) = \max_{s \in S(l)} w(s) \cdot (d(l) + \log_2(|S(l)|))$ to reflect the change in payoff to $w(s^*) \cdot |H|$. For all methods the question sampling prompt is modified to include the item weights and the payoff calculation so as to inform the LLM. For MD and TS, we use GPT-5.2 Thinking (with extended reasoning) to annotate each item with an integer weight from 1 to 10 reflecting the severity and urgency of the corresponding disease or fault, with 1 being the least severe and 10 being the most. Since an analogous notion is not available in 20Q, we instead sample item weights for this setting from a lognormal distribution with parameters $\mu = 0$ and $\sigma = 1$. A visualization of the distribution of items weights is provided in the appendix.

The results can be seen in Table 2. GoT outperforms UoT in all settings, with improvement ranging from 15% to 40%. UoT’s improvement over pure prompting based methods such as DP and DC is also less obvious in the weighted variant, likely due to the UoT’s approach of maximizing information gain without considering the item weights, leading to situations where questions yielding higher information gain (under the assumption of a uniform distribution) are preferred over those that more efficiently isolate heavily weighted items, leading to a less optimal strategy in WLSLR.

6.7 AVERAGE PERFORMANCE OF UNWEIGHTED VARIANT


While we primarily examine the worst-case performance, here we also present an analysis of the average conversation length on the DX dataset under a multinomial prior P^o , calculated as

432
433
434
435
436
437
438
439
440
441
442
443

Method	20Q		MD	TS
	Common	Breeds	DX	FloDial
GPT 4.1				
GoT	<u>152.1</u>	<u>23.2</u>	78.3	61.4
UoT	227.4	32.1	110.0	81.0
DP	224.0	36.9	116.0	90.1
DC	199.2	41.1	126.4	97.4
Qwen 2.5 72B Instruct				
GoT	<u>151.9</u>	<u>32.3</u>	<u>73.6</u>	<u>62.3</u>
UoT	228.5	47.0	99.0	74.0
DP	235.7	47.8	114.3	80.0
DC	225.1	45.7	86.1	113.6

444 Table 2: **Worst case performance of various methods in the weighted variant, as measured by**
445 $\max_{s \in \mathcal{S}} (w(s) \cdot |H_s|)$. Best performance for each setting is underlined.
446

447
448 $L_{avg} = \sum_{s \in \mathcal{S}} P^o(s) \cdot |H^s|$. This represents a method’s expected conversation length when the
449 underlying disease distribution follows P^o . We obtain 50 samples of P^o by drawing from a Dirichlet
450 distribution $Dir(kC)$ where $C \in \mathbb{Z}_{100}$ is the occurrence count of each disease in the dataset, and
451 $k \in \mathbb{R}_+$. L_{avg} for each method is plotted in Figure 3 alongside L_{worst} to illustrate the trade-off
452 between average and worst-case performance. We also consider the setting where the item is not
453 chosen adversarially, but rather follows a publicly known P^o , which allows the Questioner to specif-
454 ically optimize for that prior. We refer to this strategy as the best response (BR) and it serves as a
455 theoretical lower bound on performance. Details are in the appendix.



456
457
458
459
460
461
462
463
464
465
466
467
468
469
470 Figure 3: **Average and Worst-Case Performance on DX.** The model used is Qwen 2.5 72B In-
471 struct, with k set to 1. Note that the variance in the average performance is due to different samples
472 of P^o , not the randomness in the methods themselves.

473
474 From Figure 3, we highlight two key observations. (1) UoT and GoT have similar average-case
475 performance: their gap is small relative to their gains over DP/DC and to BR’s improvement over
476 both. (2) GoT’s worst-case advantage over UoT is substantial: comparable in magnitude to UoT’s
477 average-case gain over DP, the metric UoT explicitly targets. Overall, GoT delivers meaningful
478 worst-case improvements with little loss in average-case performance relative to UoT.

479
480 **7 CONCLUSION**

481
482 We formalized the definition of SLS and its variants, and proposed GoT, a simple yet effective
483 approach to play SLSR. We show that GoT is able to improve the worst-case performance as com-
484 pared to prior methods. Our approach of optimizing for the worst-case performance can often be
485 more valuable than to optimize for the average performance. How GoT can be extended to include
questions with open ended responses is left as future work.

486 REFERENCES

- 487
488 Leonardo Bertolazzi, Davide Mazzaccara, Filippo Merlo, and Raffaella Bernardi. ChatGPT’s in-
489 formation seeking strategy: Insights from the 20-questions game. In *Proceedings of the 16th*
490 *International Natural Language Generation Conference*, pp. 153–162, 2023.
- 491 Justin Bishop, Jaylen Burgess, Cooper Ramos, Jade B. Driggs, Tom Williams, Chad C. Tossell,
492 Elizabeth Phillips, Tyler H. Shaw, and Ewart J. de Visser. Chaopt: A testbed for evaluating
493 human-autonomy team collaboration using the video game overcooked!2. In *2020 Systems and*
494 *Information Engineering Design Symposium (SIEDS)*, pp. 1–6, 2020.
- 495 Noam Brown and Tuomas Sandholm. Superhuman ai for heads-up no-limit poker: Libratus beats
496 top professionals. *Science*, 359(6374):418–424, 2018.
- 497
498 Noam Brown and Tuomas Sandholm. Superhuman ai for multiplayer poker. *Science*, 365(6456):
499 885–890, 2019.
- 500 Neil Burch, Michael Johanson, and Michael Bowling. Solving imperfect information games using
501 decomposition. In *Proceedings of the Twenty-Eighth AAAI Conference on Artificial Intelligence*,
502 pp. 602–608, 2014.
- 503 Valerio Capraro, Roberto Di Paolo, Matjaž Perc, and Veronica Pizziol. Language-based game theory
504 in the age of artificial intelligence. *Journal of The Royal Society Interface*, 21(212), 2024.
- 505
506 Junying Chen, Chi Gui, Anningzhe Gao, Ke Ji, Xidong Wang, Xiang Wan, and Benyou Wang. CoD,
507 towards an interpretable medical agent using chain of diagnosis. In *Findings of the Association*
508 *for Computational Linguistics: ACL 2025*, pp. 14345–14368, 2025.
- 509
510 Deepro Choudhury, Sinead Williamson, Adam Goliński, Ning Miao, Freddie Bickford Smith,
511 Michael Kirchof, Yizhe Zhang, and Tom Rainforth. Bed-llm: Intelligent information gather-
512 ing with llms and bayesian experimental design. *arXiv preprint arXiv:2508.21184*, 2025.
- 513 Joseph Farrell and Matthew Rabin. Cheap talk. *Journal of Economic Perspectives*, 10(3):103–118,
514 1996.
- 515
516 Ian Gemp, Yoram Bachrach, Marc Lanctot, Roma Patel, Vibhavari Dasagi, Luke Marris, Georgios
517 Piliouras, Siqi Liu, and Karl Tuyls. States as strings as strategies: Steering language models with
518 game-theoretic solvers. *arXiv preprint arXiv:2402.01704*, 2024.
- 519 Herbert Gintis, Eric Alden Smith, and Samuel Bowles. Costly signaling and cooperation. *Journal*
520 *of Theoretical Biology*, 213(1):103–119, 2001.
- 521
522 Sally A Goldman and Michael J Kearns. On the complexity of teaching. *Journal of Computer and*
523 *System Sciences*, 50(1):20–31, 1995.
- 524 Gabriel Grand, Valerio Pepe, Jacob Andreas, and Joshua B. Tenenbaum. Loose lips sink ships:
525 Asking questions in battleship with language-informed program sampling. *arXiv preprint*
526 *arXiv:2402.19471*, 2024.
- 527
528 Kunal Handa, Yarin Gal, Ellie Pavlick, Noah Goodman, Jacob Andreas, Alex Tamkin, and Belinda Z
529 Li. Bayesian preference elicitation with language models. *arXiv preprint arXiv:2403.05534*,
530 2024.
- 531 Martin N Hebart, Adam H Dickter, Alexis Kidder, Wan Y Kwok, Anna Corriveau, Caitlin Van Wick-
532 lin, and Chris I Baker. Things: A database of 1,854 object concepts and more than 26,000 natu-
533 ralist object images. *PloS one*, 14(10):e0223792, 2019.
- 534 Daniel Houser and Erte Xiao. Classification of natural language messages using a coordination
535 game. *Experimental Economics*, 14:1–14, 2011.
- 536
537 Zhiyuan Hu, Chumin Liu, Xidong Feng, Yilun Zhao, See-Kiong Ng, Anh Tuan Luu, Junxian He,
538 Pang Wei Koh, and Bryan Hooi. Uncertainty of thoughts: Uncertainty-aware planning enhances
539 information seeking in llms. In *Proceedings of the 38th Conference on Neural Information Pro-*
cessing Systems, NeurIPS ’24, 2024.

- 540 Bimal P Jain. Why is diagnosis not probabilistic in clinical-pathological conference (cpcs): Point.
541 *Diagnosis*, 3(3):95–97, 2016.
- 542 Benjamin Kempinski, Ian Gemp, Kate Larson, Marc Lanctot, Yoram Bachrach, and Tal Kachman.
543 Game of thoughts: Iterative reasoning in game-theoretic domains with large language models. In
544 *Proceedings of the 24th International Conference on Autonomous Agents and Multiagent Systems*,
545 pp. 1088–1097, 2025.
- 547 Vojtech Kovarik, Dominik Seitz, and Viliam Lisy. Value functions for depth-limited solving in
548 imperfect-information games. In *AAAI Reinforcement Learning in Games Workshop*, volume
549 132, pp. 133–138, 2021.
- 550 János Kramár, Tom Eccles, Ian M. Gemp, Andrea Tacchetti, Kevin R. McKee, Mateusz Malinowski,
551 Thore Graepel, and Yoram Bachrach. Negotiation and honesty in artificial intelligence methods
552 for the board game of diplomacy. *Nature Communications*, 13, 2022.
- 554 Lorenz Kuhn, Yarin Gal, and Sebastian Farquhar. Clam: Selective clarification for ambiguous
555 questions with generative language models. *arXiv preprint arXiv:2212.07769*, 2022.
- 556 Woosuk Kwon, Zhuohan Li, Siyuan Zhuang, Ying Sheng, Lianmin Zheng, Cody Hao Yu, Joseph
557 Gonzalez, Hao Zhang, and Ion Stoica. Efficient memory management for large language model
558 serving with pagedattention. In *Proceedings of the 29th symposium on operating systems princi-*
559 *ples*, pp. 611–626, 2023.
- 561 Marc Lanctot, Edward Lockhart, Jean-Baptiste Lespiau, Vinicius Zambaldi, Satyaki Upadhyay,
562 Julien Pérolat, Sriram Srinivasan, Finbarr Timbers, Karl Tuyls, Shayegan Omidshafiei, et al.
563 Openspiel: A framework for reinforcement learning in games. *arXiv preprint arXiv:1908.09453*,
564 2019.
- 565 David Kellogg Lewis. *Convention: A Philosophical Study*. Wiley-Blackwell, Cambridge, MA,
566 USA, 1969.
- 567 Belinda Z Li, Alex Tamkin, Noah Goodman, and Jacob Andreas. Eliciting human preferences with
568 language models. *arXiv preprint arXiv:2310.11589*, 2023.
- 569 Belinda Z Li, Been Kim, and Zi Wang. Questbench: Can llms ask the right question to acquire
570 information in reasoning tasks? *arXiv preprint arXiv:2503.22674*, 2025.
- 572 Shuyue Stella Li, Vidhisha Balachandran, Shangbin Feng, Jonathan S. Ilgen, Emma Pierson,
573 Pang Wei Koh, and Yulia Tsvetkov. Mediq: Question-asking llms and a benchmark for reliable
574 interactive clinical reasoning. In *Advances in Neural Information Processing Systems*, volume 37,
575 pp. 28858–28888, 2024.
- 576 Mingyang Liu, Gabriele Farina, and Asuman Ozdaglar. Liteefg: An efficient python library for
577 solving extensive-form games. *arXiv preprint arXiv:2407.20351*, 2024.
- 579 Matej Moravcik, Martin Schmid, Karel Ha, Milan Hladik, and Stephen Gaukrodger. Refining sub-
580 games in large imperfect information games. In *Proceedings of the AAAI Conference on Artificial*
581 *Intelligence*, volume 30, 2016.
- 582 OpenAI. Gpt-4.1, 2024.
- 583 Wasu Top Piriyaakulkij, Volodymyr Kuleshov, and Kevin Ellis. Active preference inference using
584 language models and probabilistic reasoning. *arXiv preprint arXiv:2312.12009*, 2023.
- 585 Dinesh Raghu, Shantanu Agarwal, Sachindra Joshi, and Mausam. End-to-end learning of flowchart
586 grounded task-oriented dialogs. In *Proceedings of the 2021 Conference on Empirical Methods in*
587 *Natural Language Processing*, pp. 4348–4366, 2021.
- 588 Hong Ri, Xiaohan Kang, Mohd Nor Akmal Khalid, and Hiroyuki Iida. The dynamics of minority
589 versus majority behaviors: a case study of the mafia game. *Information*, 13(3):134, 2022.
- 590 Robert S. Siegler. The twenty questions game as a form of problem solving. *Child Development*, 48
591 (2):395–403, 1977.

594 Matthijs TJ Spaan. Partially observable markov decision processes. In *Reinforcement learning:*
595 *State-of-the-art*, pp. 387–414. Springer, 2012.

596

597 J v. Neumann. Zur theorie der gesellschaftsspiele. *Mathematische annalen*, 100(1):295–320, 1928.

598 Bernhard Von Stengel. Efficient computation of behavior strategies. *Games and Economic Behavior*,
599 14(2):220–246, 1996.

600

601 Xuezhi Wang, Jason Wei, Dale Schuurmans, Quoc Le, Ed Chi, Sharan Narang, Aakanksha Chowdh-
602 ery, and Denny Zhou. Self-consistency improves chain of thought reasoning in language models.
603 *arXiv preprint arXiv:2203.11171*, 2022.

604 Jingjing Xu, Yuechen Wang, Duyu Tang, Nan Duan, Pengcheng Yang, Qi Zeng, Ming Zhou, and
605 Xu Sun. Asking clarification questions in knowledge-based question answering. In *Proceedings*
606 *of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th Inter-*
607 *national Joint Conference on Natural Language Processing (EMNLP-IJCNLP)*, pp. 1618–1629,
608 2019.

609

610 Qwen An Yang, Baosong Yang, Beichen Zhang, Binyuan Hui, Bo Zheng, Bowen Yu, Chengyuan
611 Li, Dayiheng Liu, Fei Huang, Guanting Dong, Haoran Wei, Huan Lin, Jian Yang, Jianhong Tu,
612 Jianwei Zhang, Jianxin Yang, Jiaxin Yang, Jingren Zhou, Junyang Lin, Kai Dang, Keming Lu,
613 Keqin Bao, Kexin Yang, Le Yu, Mei Li, Mingfeng Xue, Pei Zhang, Qin Zhu, Rui Men, Runji Lin,
614 Tianhao Li, Tingyu Xia, Xingzhang Ren, Xuancheng Ren, Yang Fan, Yang Su, Yi-Chao Zhang,
615 Yunyang Wan, Yuqi Liu, Zeyu Cui, Zhenru Zhang, Zihan Qiu, Shanghaoran Quan, and Zekun
616 Wang. Qwen2.5 technical report. *arXiv preprint arXiv:2412.15115*, 2024.

617 Shunyu Yao, Dian Yu, Jeffrey Zhao, Izhak Shafran, Tom Griffiths, Yuan Cao, and Karthik
618 Narasimhan. Tree of thoughts: Deliberate problem solving with large language models. In *Ad-*
619 *vances in Neural Information Processing Systems*, volume 36, pp. 11809–11822, 2023.

620 Xuan Zhang, Yang Deng, Zifeng Ren, See-Kiong Ng, and Tat-Seng Chua. Ask-before-plan: Proac-
621 tive language agents for real-world planning. In *Findings of the Association for Computational*
622 *Linguistics: EMNLP 2024*, pp. 10836–10863, 2024a.

623

624 Yizhe Zhang, Jiarui Lu, and Navdeep Jaitly. Probing the multi-turn planning capabilities of LLMs
625 via 20 question games. In *Proceedings of the 62nd Annual Meeting of the Association for Com-*
626 *putational Linguistics (Volume 1: Long Papers)*, pp. 1495–1516, 2024b.

627 Martin Zinkevich, Michael Johanson, Michael Bowling, and Carmelo Piccione. Regret minimization
628 in games with incomplete information. In *Advances in Neural Information Processing Systems*,
629 volume 20, 2007.

630

631

632

633

634

635

636

637

638

639

640

641

642

643

644

645

646

647

A STRATEGY REPRESENTATION

There are several ways to represent strategies (up to payoff equivalence) in imperfect information games with perfect recall. For computational reasons, the *sequence form* is often used. We briefly describe the other representations.

1. **Normal/Strategic Form.** This was what was presented in the paper. The set of deterministic strategies is the cartesian product of actions at each info set $\Pi = \prod_{I \in \mathcal{I}} \mathcal{A}(I)$. Thus, every policy $\pi \in \Pi$ tells us exactly what action to take at every information set that could be encountered. Randomized strategies are distributions over deterministic policies, i.e., Δ_{Π} . The size of Π is exponential in the number of info sets.
2. **Reduced Normal Form.** The reduced normal form prunes the number of normal form strategies by grouping together strategically equivalent ones. See any textbook in game theory, or the work by Von Stengel (1996) for a more complete discussion. Let I be an info set and $\alpha, \alpha' \in \mathcal{A}(I)$ be distinct actions in I . Let I' be an info set that α' precedes. Then, normal form strategies that choose α in I have payoffs (regardless of opponent strategy) is independent of what action is taken in I' , since to enter I' at all would require choosing α' . Thus, two strategies π, π' that choose α in I but differ in actions taken in I' are strategically equivalent. The minimal set of strategies that are obtained by forming such equivalence classes forms the set of reduced-normal form strategies, which can be significantly smaller than normal form ones. As before, strategies can be randomized in reduced normal form as well. Unfortunately, the size of reduced normal form strategies can still be exponential in the number of info sets.
3. **Behavioral Form.** The behavioral strategies involve placing a *distribution* of actions (possibly not deterministic) at each information set, thus the size is linear in the total number of actions summed over all info sets, which in turn is no larger than the size of the game tree. It can be shown using *Kuhn's theorem* that under perfect recall, the set of behavioral strategies are strategically equivalent to (reduced) normal form strategies. Unfortunately, while behavioral strategies are intuitive and compact, optimizing in behavioral form is difficult as payoffs are non-linear in the strategy representation.
4. **Sequence Form.** The sequence form strategy alleviates the problems assigning probabilities to sequences σ (essentially actions when the game has perfect recall) of taking a particular sequence in isolation from chance and other players. At each info set I , the sequence form is essentially identical to the behavioral form (a probability simplex) except that they are normalized by the probabilities given by the info set's parent sequence $\sigma(I)$, which is the last action (sequence) taken before reaching I — this is guaranteed to be unique because of perfect recall. Thus, the sequence form is the same size as behavioral strategies (except for an extra “empty sequence” ϕ set to 1.0 that is the parent of all initial info sets). The sequence form strategy space is sometimes known as the *treeplex*

$$\mathcal{X} = \left\{ x \in \mathbb{R}_+^N \mid x[\phi] = 1; \sum_{\sigma=Ia} x[\sigma] = x[\sigma(I)] \forall I \in \mathcal{I} \right\}$$

where $N = 1 + \sum_{I \in \mathcal{I}} |I|$ and \mathcal{I} are the set of info sets, Ia refers to the sequences ending with action i starting at info set I , and ϕ is the empty sequence. The vertices of Π are correspond to (reduced) normal form strategies. using the sequence form, we can write the Nash equilibrium of a zero-sum game as the bilinear saddle point problem

$$\min_{x \in \mathcal{X}} \max_{y \in \mathcal{Y}} x^T M y$$

where M is the sequence form payoff matrix. Observe that the objective is linear in both x or y . This saddle point can be found efficiently using a variety of methods, including first order methods such as the counterfactual regret minimization Zinkevich et al. (2007), linear programming or other first order methods (e.g., mirror prox). The library which we use Liu et al. (2024) uses counterfactual regret minimization.

B DETAILED DERIVATIONS

B.1 PROOF OF THEOREM 3.6

This problem is equivalent to the following set-intersection problem.

Set intersection problem. Let \mathcal{S} be a finite set and $\mathcal{K} \subseteq 2^{\mathcal{S}}$ a set of sets. Given some fixed $s \in \mathcal{S}$, we want to find if there is a set $\mathcal{J} \subseteq \mathcal{K}$ such that $|\mathcal{J}| \leq k$ and $\bigcap_{J \in \mathcal{J}} J = \{s^*\}$, i.e., can we find a small subset of $\mathcal{J} \subseteq \mathcal{K}$ such that its intersection contains exactly s^* . One can see that \mathcal{K} contains the set of questions that can be asked about s^* . We can safely assume that $\forall K \in \mathcal{K}, s^* \in K$.

Set cover. Let \mathcal{A} be an arbitrary set and $\mathcal{B} \subseteq 2^{\mathcal{A}}$. The decision problem is whether one can find some set $B^* \subseteq \mathcal{B}$ of size k or smaller such that $\bigcup B^* = \mathcal{A}$.

NP-completeness. We show that the set cover problem reduces to the set intersection problem.

Lemma B.1. *Set cover problem reduces to the Set intersection problem.*

Proof. we define $\mathcal{S} = \mathcal{A} \sqcup s^*$ for some dummy element s^* and \mathcal{K} to contain the subsets that are complements of elements of \mathcal{B} , with s^* added, $\mathcal{K} = \{K_i = \overline{B_i} \sqcup \{s^*\} \mid B_i \in \mathcal{B}\}$. Take a solution $K^* \subseteq \mathcal{K}$ to this set intersection problem and the corresponding subset $B^* = \{B_i \mid K_i \in K^*\}$. Since $\bigcap_{i: K_i \in K^*} K_i = \{s^*\}$, then $\bigcup_{i: K_i \in K^*} \overline{K_i} = \mathcal{S} \setminus \{s^*\}$. Thus $\bigcup_{i: B_i \in B^*} B_i = \bigcup_{i: K_i \in K^*} \overline{K_i} = \mathcal{S} \setminus \{s^*\} = \mathcal{A}$. \square

For completeness, we also show the other direction of reduction.

Lemma B.2. *Set intersection problem reduces to the Set cover problem.*

Proof. We define $\mathcal{A} = \mathcal{S} \setminus \{s^*\}$ and \mathcal{B} contains subsets that are the complements of the elements of \mathcal{K} , $\mathcal{B} = \{B_i = \overline{K_i} \mid K_i \in \mathcal{K}\}$. Take a set cover $B^* \subseteq \mathcal{B}$ of \mathcal{A} and its corresponding subset $K^* = \{K_i \mid B_i \in B^*\}$ of \mathcal{K} . Since B^* covers \mathcal{A} , i.e. $\bigcup B^* = \mathcal{A}$, we have $\bigcap_{B_i \in B^*} \overline{B_i} = \phi$, and thus $K^* : \bigcap_{i: K_i \in K^*} K_i = \{s^*\} \cup \bigcap_{B_i \in B^*} \overline{B_i} = \{s^*\}$. \square

Finally, any solution to the set intersection problem can also be checked in polynomial time.

Remark B.3. A very similar problem known as *teaching dimension* was studied by Goldman & Kearns (1995), and is in turn closely related to other related concepts in learning theory such as the VC-dimension.

B.2 PROOF OF THEOREM 3.7

It is clear that the even-split strategy uses exactly k questions. Furthermore, every question yields exactly one bit of information, so at least k questions are needed. This shows that the even-split strategy is a NE (that this is a minimax solution). To show that the uniform strategy is a maximin solution, simply apply symmetry. Let $y^* \in \Delta_n$ be some (potentially non-uniform) NE for the answerer. We know that the set of maximin solutions for a zero-sum matrix game forms a non-empty convex set. Take all permutations of y^* . By symmetry, they must all be NE as well. Let the average over all permutations be $\overline{y^*}$, again by symmetry this is equal to the uniform distribution. But by the aforementioned convexity of the set of maximin solutions this is also a Nash equilibrium for the Answerer.

B.3 DISCUSSION OF THEOREM 5.1

Step 2 of GoT augment the subgame to allow the Item Chooser to “re-choose” a new distribution over s^* . At first glance, doing this rather than sticking to the original distribution chosen by the Item Chooser at the start of the game seems to give them significantly more power than in the original SLSSR game, since it would be able to “switch items” depending on the questions asked in actual play.. In fact, this is a simple implementation of *maxmargin resolving*, a crucial step in performing *safe* subgame search Moravcik et al. (2016) in general zero-sum EFGs with imperfect information.

756 In these games, the optimal strategy of a subgame may depend on other unreached branches of the
757 original game and as such, we cannot solve for a strategy for this subgame in isolation. Performing
758 this safe subgame resolving provides a performance guarantee for the Questioner’s subgame strategy
759 with respect to some blueprint strategy or state value estimate in the original game. Conversely if
760 we were to not do this, the Questioner’s subgame strategy will enjoy no such guarantees and may
761 perform arbitrarily poorly. In practice, we see an improvement over unsafe variants of subgame
762 search during our preliminary investigation.

763 We give a very brief overview of subgame search and maxmargin resolving. The finer details and
764 mathematical formulation is omitted. The main goal is to establish that GoT is implemented in the
765 same way that maxmargin resolving is, which in turn implies safety.
766

767 **Safe subgame search** Subgame search (also known as subgame resolving or continual resolving)
768 is a class of methods used to perform depth-limited search in a principled manner in imperfect
769 information extensive form games. The idea behind subgame search is to play a *blueprint* strategy
770 until the player enters a *subgame* (an imperfect information subgame is a forest of trees, closed under
771 both the descendant relation and membership within augmented information sets for any player,
772 Burch et al. (2014)). The blueprint strategy is *typically* the solution to a coarse, abstract version of
773 the full game. Once inside the subgame, the player *resolves* for a better solution for the subgame
774 that was reached (and that subgame only). This is analogous to the perfect information case where
775 one only performs search (or refinement) of a strategy in the state that was reached in actual play,
776 since solving the original full game is intractable.

777 A safe subgame solving algorithm is one that is guaranteed to perform no worse than the blueprint
778 strategy. Naive subgame solving attempts to solve the subgame by constructing a gadget game
779 starting with a chance node which leads to all initial states in the subgame based on the probabilities
780 (under the blueprint and the opponent strategy when solving the blueprint) of reaching them. This
781 however, neglects the fact that resolving just the subgame that was reached could entice the opponent
782 to change their action, rendering these chance probabilities incorrect, leading to a worse performance
783 than the blueprint.

784 **Maxmargin resolving** Maxmargin resolving Moravcik et al. (2016) is one such approach to per-
785 form subgame solving in a more principled fashion. The idea is to augment the gadget game such
786 that the *opponent* first chooses which infoset (of the opponent) it would like to begin from, after
787 which, a chance node enforces the probabilities of reaching each of those states (belonging to the
788 opponent’s infoset) is, based on the blueprint strategy of the main player. Letting the opponent
789 choose which infoset (note that we may have to add dummy infosets if the opponent does not move
790 at the beginning of the subgame) they want to begin the subgame with ensures that the main player
791 optimizes for the minimum *margin*. Here, the margin for each of the opponent’s infoset is the dif-
792 ference between the value in the infoset under the blueprint strategy versus the refined strategy. If
793 the main player optimizes the value of a particular head infoset (of the opponent) too much at the
794 expense of performing poorly at other infosets, then the opponent would choose those infosets in-
795 stead, resulting in unsafe resolving. By allowing the opponent to choose initial infosets, Maxmargin
796 avoids this explicitly by ensuring that all of the infosets are equally improved (for the main player)
797 after refinement.

798 In practice, we do not actually know the values of initial states of the subgame under the best-
799 response of the opponent is (without expanding the entire subgame to its leaves) and have to resort
800 to approximate value functions. Note that it is not immediately clear what constitutes a good value
801 function, since the value of a state will depend on play from both players and is complicated by
802 imperfect information. See Kovarik et al. (2021) for a more thorough discussion.


803 **GoT as maxmargin resolving** First, observe that SLSR is a relatively simple EFG in that the
804 Answerer only moves once at the beginning, after which there are no further interactions from it. In
805 fact, we could allow the Answerer to have perfect information. Furthermore, the proper subgames
806 (i.e., not the full game) are simply the histories H , or equivalently, the subgame beginning at $I(H)$,
807 which comprise all questions asked but not what s^* was chosen. Note that each proper subgame only
808 has the Questioner taking actions. Since the Answerer has perfect information the “head infosets”
809 of a subgame $I(H)$ for the Answerer simply corresponds to the initial states of that history H .
Note that we don’t actually need to explicitly construct these head infosets: since the Answerer has

810 full information, these are “dummy” infosets have essentially one action only, which lead to the
 811 corresponding state in the lead infoset of the Questioner. This shows that the structure of the gadget
 812 game of maxmargin is exactly the same as what we propose. An example of this construction is
 813 shown in Figure 4.

814 In maxmargin, the payoffs under each head infoset of the subgame is shifted by the payoffs under
 815 the blueprint (or function approximation). This ensures that the *margin* is optimized as opposed to
 816 absolute payoffs. Thankfully, no such shift is necessary in our case because the approximated values
 817 at each state is $\log_2(|S(H)|)$, i.e., the log of the number of items remaining. This value is the same
 818 for *every* state in the infoset $I(H)$, thus the value of the shift is the same over the entire subgame,
 819 which, as far as solving the subgame goes has no bearing on the refined strategy.

820 This same argument also extends to our choice of value function for WLSR, $h(l) =$
 821 $\max_{s \in S(l)} w(s) \cdot (d(l) + \log_2(|S(l)|))$, which depends only on the set of items remaining, $S(H)$.
 822 However, if our value function was chosen to also depend on the Answerer’s precise choice of s^* ,
 823 then such an argument would no longer hold and we would have to perform these shifts in payoffs
 824 accordingly.

825 *Remark B.4.* In theory, maxmargin resolving only performs resolving upon entering a subgame
 826 (e.g., after $d = 3$ questions are asked). In practice, GoT performs resolving at every infoset that is
 827 encountered during actual play.



830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863

Figure 4: Left: example of a subgame based on Example 1 and Figure 1. Bounded region by thick dark lines form an example of a subgame corresponding to the history of asking $q^{(2)}$ and getting an answer of 1. Right: the gadget game used for solving the subgame shown on the left. Note that it is the Answerer who takes the first action, not chance (which would be the case for naive subgame solving), and the actions only include the items that are consistent with H , in this case $s^{(1)}$ and $s^{(3)}$.

C IMPLEMENTATION DETAILS

C.1 GENERAL IMPLEMENTATION

853 **Method Hyperparameters** Since UoT shares a similar simulation procedure with GoT, we use the
 854 same values for the simulation depth d and the number of candidate questions m for both methods
 855 within each experiment, although these values may vary across different experiments. For DC, we
 856 similarly provide a set of m candidate questions which it may choose from.

858 **Question Generation When There Are Two Items Left** In instances during a (W)SLSR game
 859 where the current history H satisfies $|S(H)| = 2$, we deterministically construct two candidate
 860 questions of the form “Is x the correct item?” for each remaining item, instead of sampling ques-
 861 tions from the LLM. While not strictly required, it is implemented primarily for efficiency. Under
 862 Theorem 3.8, any question that satisfies the assumption will successfully distinguish between the
 863 two remaining items, thereby terminating the game. This eliminates the need to query an LLM at
 such states, thereby reducing the latency associated with constructing the simulation tree.

Question Caching and Reuse Since we construct the SLSR game on demand in our experiments, we need to ensure the consistency between the game instance played by each of the methods. During each execution of GoT, the set of candidate questions $g(S(H))$ generated by the LLM for any explored history H is cached for reuse. In the case of UoT and DC, if the current history has previously been explored by GoT, the corresponding cached set of candidate questions is reused in place of sampling new questions from the LLM. This is done to ensure a fair comparison across methods, as variations in the quality of candidate questions can substantially impact performance.

Handling erroneous LLM outputs For ease of parsing, we require the LLMs to produce outputs in JSON format. While the model occasionally fails to adhere to this format, we address such cases by retrying the generation. In our experiments, this retry mechanism proved effective, and no further issues were observed.

C.2 GoT

When Simulation Tree is Terminal During Simulation Step (1), after constructing the local simulation tree, we verify whether each leaf node corresponds to a terminal state, i.e., whether $|S(l)| = 1$ holds for all leaf nodes. If this condition is met, the strategy derived from the current subgame is adopted for all subsequent question selections until the end of the game, rather than being used solely for the next question followed by resolving a new subgame at the next step. This is justified by the fact that the current subgame extends to the end of the game, thereby obviating the need for iterative strategy construction in subsequent steps.

C.3 BR

Obtaining Best Response To obtain a best response (BR), we consider a non-adversarial setting in which the item (distribution) is drawn from a known prior P^o rather than chosen adversarially. Under this assumption, the interaction can be modeled as a single-player extensive-form game with imperfect information, analogous to our SLS representation, by replacing the root node corresponding to the Item Chooser with a chance node whose outgoing edges are weighted according to P^o . The optimal Questioner strategy in this case is deterministic and should minimize the expected cost incurred. We obtain this strategy by adopting an iterative, on demand framework similar to GoT, replacing step 3 with a simple backward induction.

Example 4. Consider a game similar to Example 1, with $s^{(1)}, s^{(2)}, s^{(3)}$ being distributed under the prior $P^o = (0.8, 0.1, 0.1)$.

In Example 4, the Questioner should always ask $q^{(1)}$ first, followed by either $q^{(2)}$ or $q^{(3)}$. This yields an expected cost of 1.2. Figure 5 illustrates the extensive form representation of Example 4.




Figure 5: EFG representation of Example 4. The root node \bullet is a chance node and the other nodes ∇ belong to the Questioner. The respective probabilities of each item is shown.

Note that in this setting, the problem is equivalent to planning under partial observability, i.e., a Partially Observable Markov Decision Process (POMDP) Spaan (2012).

D ADDITIONAL RESULTS

D.1 SLSR WITH SYNTHETIC SPLITS

The quality of a candidate question q in SLSR at some infoset $I(H)$ can be roughly measured using the ratio $|Y(S(H), q)| : |\bar{Y}(S(H), q)|$, representing how evenly q is able to split $S(H)$ into two. Given the difficulty in controlling the quality of LLM-sampled questions, we wish to study SLSR in a more controlled environment. Instead of using a LLM for question generation, we define a question generating function $g' : 2^S \setminus \phi \times (0, 1) \rightarrow 2^S$ which takes as input $S(H)$ and a split ratio $r \in (0, 1)$, and outputs the set² $Y' \subset S(H)$ (and consequently $\bar{Y}' = S(H) \setminus Y'$) at the fixed ratio $\frac{|Y'|}{|S(H)|} = r$. Two implementations of g' were considered: (i) Random Splits: Sample and return $r \cdot |S(H)|$ items uniformly at random from $S(H)$ without replacement. (ii) Feature Based Splits: For each $s \in S(H)$, generate k features $F_i = (f_1, \dots, f_k), f_j \in [0, 1]$ at the start of the game. g' randomly selects one of k features, and sorts $S(H)$ based on the selected feature. The top $r \cdot |S(H)|$ items are returned.

The results are shown in Table 3. GoT consistently achieves superior performance compared to UoT, particularly as r decreases and the splits become increasingly skewed. This suggests that GoT provides the most improvement when the candidate questions are not optimal. This however does not translate well when actual questions are used due to other confounding factors not captured.

Method	r		
	0.4	0.33	0.25
3 Features			
GoT	9.4	10.0	13.8
UoT	10.0	11.0	15.0
5 Features			
GoT	9.2	10.2	13.2
UoT	10	11.0	15.0
Random Splits			
GoT	8.8	9.8	11.6
UoT	10	11	15

Table 3: **Worst case interaction length on SLSR with Synthetic splits with Common.** d is set to be 3.

D.2 FULL SLSR GAMES

For each SLSR game, there exists a lower bound on the expected worst case number of questions required. This bound can be obtained by solving the fully specified game. As this is only feasible for smaller datasets, we constructed complete SLSR games on the smaller Breeds dataset and experimented on GoT and UoT by setting the simulation depth d to game tree depth D . Since constructing the full game tree is required, we enforce Theorem E.1 to ensure that all branches eventually terminate. The results are shown in Table 4, where GoT’s performance aligns with the lower bound on the performance. On the other hand, UoT’s performance showed minimal improvement even when provided with the full game tree during simulation, suggesting that achieving the lower bound requires a non-deterministic strategy.

D.3 EFFECT OF SIMULATION DEPTH d

We further study the effect of increasing the simulation depth d for both UoT and GoT; the results are shown in Figure 6. Overall, GoT improves as d increases, but the gains plateau as it approaches what we hypothesize to be the optimal strategy for the fixed set of LLM-sampled questions. In contrast, UoT’s worst-case performance shows little to no improvement even with deeper lookahead, indicating that optimizing for information gain does not necessarily translate into better worst-case guarantees.

²The question itself does not matter in this case, as both UoT and GoT is language agnostic.

972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025

Method	Experiment	
	Subgame ($d = 3$)	Full Game ($d = D$)
GPT 4.1 + Even split prompt		
GoT	6.4	5.84
UoT	7	7
GPT 4.1 + Natural prompt		
GoT	7.4	5.64
UoT	9	8
Qwen 72B Instruct + Even split prompt		
GoT	6.2	5.44
UoT	7	7
Qwen 72B Instruct + Natural prompt		
GoT	6.6	5.88
UoT	8	8

Table 4: **Worst case interaction length for on full SLSR Game.** Dataset used is the Breeds Dataset.




Figure 6: **Worst-case performance of various methods in Weighted Variant on Common and Breeds.** The x-axis is d , the y-axis is the payoff for the Item Chooser $w_i \cdot |H|$.

D.4 EFFECT OF QUESTION QUALITY




Figure 7: **Performance in the weighted variant with artificially skewed weights on Breeds.** Graph on the left shows the performance when the additional question is included.

We conducted a brief ablation to examine the impact of question quality in WLSLR. Specifically, we created an artificially skewed weight distribution on the Breeds dataset by assigning weight 1 to all but one item and weight 100 to the remaining item. Under this construction, the optimal first query is to test whether the highest-weight item is the target. We verify this by manually injecting the corresponding question into the initial candidate set. As shown in Figure 7, GoT consistently reaches this optimal strategy. In contrast, when this question is not included, performance degrades

substantially, indicating that GoT’s effectiveness can be sensitive to the quality of the candidate questions.

D.5 AVERAGE CASE IN UNFAVORABLE CONDITIONS

We further evaluate L_{avg} for UoT and GoT under two families of multinomial priors, chosen to be unfavorable to each method respectively. Specifically for each method, we consider $X_{method} \sim Dir(k\alpha)$, where $\alpha \in \mathbb{Z}_{100}$ satisfies $\forall i \neq 0, \alpha_i = 1$. We set α_0 to concentrate the distribution around a single item. In particular, we let index 0 correspond to the item that yields the worst case conversation length for that method. We draw 100 samples from each configuration and compare the L_{avg} for UoT and GoT.




Figure 8: **Average Performance in various family of distributions** Left two plots corresponds to priors unfavorable to UoT, while right two plots corresponds to priors unfavorable to GoT. X-axis is the KL divergence of the prior from the uniform distribution.

As seen in Figure 8, for priors sampled from X_{UoT} , the two methods diverge markedly, with UoT’s performance degrading much more than GoT. In contrast, for priors sampled from X_{GoT} , there is no substantial gap in average performance. Together, these results suggest that GoT is more robust to unfavorable priors than UoT.

D.6 ITEM WEIGHTS

Figure 9 presents a histogram of item weights used in the weighted variant for the Breeds and Common datasets in the 20Q setting, DX in the MD setting, and Flodial in the TS setting. For datasets in the 20Q setting, the weights were assigned randomly, as there was no clear method for determining meaningful valuations for each item given the nature of the datasets. For TS and MD, the weights are obtained by asking Chatgpt 5.2 to annotate each disease/fault with a severity score. The prompt used is shown in Table 5

MD
 Here is a list of diseases. I want you to assign a severity score between 1 to 10 for each of these diseases. This severity score should depend on how life threatening the disease can be, and how urgently it needs treatment or care.
 The list of diseases:
[diseases]

TS
 Here is a list of car faults. I want you to assign a severity score between 1 to 10 for each of these faults. This severity score should depend on how severe the fault can be, and how urgently it needs to be repaired.
 The list of car faults:
[faults]

Table 5: **Prompt used to annotate the item weights for the MD and TS settings.**

It is important to note that the performance of GoT in a WLSR game may be sensitive to the underlying distribution of item weights. In particular, when the weights were sampled from a uniform

distribution, we observed that the relative performance of GoT compared to UoT mirrored the results in the unweighted setting, providing a consistent but smaller improvement.




Figure 9: **Distribution of item weights used in our experiments.** Weights are sampled from a lognormal distribution with parameters $\mu = 0, \sigma = 1$.

D.7 RANDOMIZATION OF GOT’S STRATEGIES

We quantified the randomness of GoT’s strategy using entropy, as shown in Figure 10. In general, the resulting strategies exhibit higher entropy in the standard SLSR game compared to the WSLSR variant. This is likely due to the item weight distribution being tail-heavy, which encourages the strategy to favor candidate questions that more efficiently isolate the heavily weighted items. Nonetheless the strategies remain sufficiently random, suggesting that we do not encounter degenerate cases in which a deterministic strategy would be optimal.

E DISCUSSION ON ASSUMPTIONS

All of the aforementioned assumptions are either naturally satisfied by the experimental setup or are explicitly enforced during the execution of our method.

Theorem 3.1 In our formulation of the SLS problem, we assume that (i) the codomain of f is binary, and (ii) each item $s \in S$ has a unique, well-defined answer under f . However, this assumption may not hold in real-world scenarios due to the inherent ambiguities and interpretive variability commonly present in natural language. One source of such ambiguity arises when an item name refers to multiple distinct entities. For example, consider the question: Is the Titanic something a person can pick up with their hands? The answer would be no if referring to the actual ship, but yes if referring to a DVD of the movie Titanic. In our experiments, to abstract away such linguistic ambiguity, we instantiate the labeling function f with an LLM and treat its output as a definitive label for each item.

Theorem 3.2 This naturally follows from Theorems 3.1 and 3.9 and the game structure.

Theorem 3.3 This naturally follows from the game structure.

Theorem 3.4 We employed LLMs, accessed both via online APIs and locally hosted instances, to implement the function f . For online API-based queries, the average latency per query is approxi-




Figure 10: **Entropy of the strategies obtained using GoT at each infoset.** As $m = 3$, the maximum entropy of the strategy is $\log_2(3) \approx 1.58$ when every candidate question is chosen with equal probability. Strategies for when there are only two items left are not included.

mately 1 to 5 seconds, while for locally hosted models, the latency is slightly lower, typically around 1 to 3 seconds.

Theorem 3.5 This assumption is satisfied as \mathcal{Q} is the set of all possible natural language questions. In particular it is trivially satisfied by the presence of identity questions.

Theorem 3.8 This assumption holds in nearly all cases when LLMs are used as the question generator g . To enforce this, we verify whether there exists at least one question from the sampled candidate set that permits progression of the game; if no such question is found, we resample the candidate questions. For certain experiments (such as full SLSR game solving) we impose a stronger version of this assumption:

Assumption E.1. For every subset $S \subseteq \mathcal{S}$, for every $q \in g(S)$, there exists a pair of distinct items $s, s' \in S$ where $f(q, s) \neq f(q, s')$

This guarantees that the game tree will be finite, thereby enabling the complete construction of the game tree. To enforce this condition, we explicitly remove any candidate question that fails to satisfy the assumption from the set of candidate questions.

Theorem 3.9 This assumption is made to mitigate potential inaccuracies arising from LLM-based classifications. Although LLMs may produce erroneous outputs, handling such errors is beyond the scope of our method and is therefore not the primary focus of this work. Without this assumption, classification errors during the simulation process could, in the worst case, require a restart of the game. Specifically, if the target item s^* is misclassified, it may be incorrectly eliminated from the set of possible items upon receiving a contradictory response from the answerer. Moreover, we observed that such misclassifications and consequently restarts occurred frequently when attempting to reproduce the results of Hu et al. (2024), which drastically affected the worst case performance. Since this does not influence the Questioner’s strategy for any of the evaluated methods, we believe it does not compromise the fairness of the experimental results. To enforce this assumption for both

1188 GoT and UoT, we depart from the approach used in Hu et al. (2024), where a separate LLM instance
1189 was employed to simulate the Answerer. Instead, we cache the item set splits generated during
1190 the simulation step corresponding to each question and reuse them as the Answerer’s response dur-
1191 ing our experiments. This strategy ensures consistency between the item classifications performed
1192 during the simulation phase and the responses observed during the actual execution of each method.

1193

1194 F DATASET DETAILS

1195

1196 All constructed datasets (along with item weights used for the weighted variant) are released along-
1197 side the accompanying code.

1198

1199 **20Q** To construct the datasets, we relied on publicly available sources. For example, the American
1200 Kennel Club for the Breeds dataset, and ChatGPT for the S128 dataset. All AI-generated datasets
1201 were subsequently verified to ensure that each item included corresponds to a real-world entity. The
1202 size of these datasets is intentionally designed to be comparable to those used in Hu et al. (2024),
1203 since both their method (UoT) and GoT shares a similar computational complexity due to the future
1204 simulation steps. Game-solving in GoT contributes only a minor fraction to the running time, and
1205 GoT can be seen as a robust extension to UoT at little extra cost. This is also why we primarily
1206 compare our method against UoT.

1207

1208 **MD** The DX dataset consists of 1148 entries of real cases across 461 unique diseases. We sampled
1209 100 out of the 461 unique diseases uniformly at random to be used as the item hypothesis space. For
1210 the average case analysis, we count how many entries in the DX dataset has each of the 100 diseases
1211 as the final diagnosis, and use this as an estimate of the population distribution.

1212

1213 **TS** Flodial contains both laptop-related and car-related faults. We decided to focus on the latter
1214 due to its greater variety and clearer distinction between each fault. In the dataset, each fault corre-
1215 sponds to a short textual description at a leaf node of a directed graph that encodes a troubleshooting
1216 flowchart. We extract these leaf descriptions and prompt GPT-5.2 Thinking to map each one to a
1217 concrete car-fault label. We then manually verify and edit the resulting labels based on the asso-
1218 ciated troubleshooting dialogues provided in Flodial. Finally, we merge or remove near-duplicate
1219 faults (e.g., “water leakage” vs. “water pump leak”) to ensure that each retained fault is distinct and
1220 readily distinguishable.

1221

1222 G EXAMPLES OF QUESTIONS ASKED

1223

1224 **Unnatural Questions** A typical question posed by the LLM in a game of Twenty Questions with
1225 the Common dataset resembles the following:

- 1226 • Is the item something a person can physically pick up with their hands (assuming average
- 1227 human size and strength)?
- 1228 • Is the item man-made?
- 1229 • Is the item an animal?

1230

1231 Such questions generally pertain to intrinsic properties of the items themselves.

1232

1233 In contrast, when the *even* prompt was used, we occasionally observed the generation of more “un-
1234 natural” questions:

- 1235 • Is the breed’s name made up of only one word?
- 1236 • Is the name of the item longer than 7 characters?
- 1237 • Does the item’s name start with a letter from A-M (inclusive)?

1238

1239 While we find it difficult provide a quantitative evaluation of the “naturalness” of a question, intu-
1240 itively, unnatural questions typically reference the item names directly, rather than the underlying
1241 items themselves. Natural questions on the other hand generally focuses on intrinsic properties of

the items. Unnatural questions can be interpreted as the LLM’s attempt to optimize the question by improving the chances of obtaining an even-split, which is optimal as implied by Theorem 3.7. These occurrences were primarily observed when GPT-4.1 was used as the LLM. We suspect this to be why a noticeable improvement in DP can be observed when *even* is used over *natural*, as seen from Table 6. This is less noticeable in GoT and UoT, possibly due to both performing planning via lookahead. This could reduce the influence of the few “unnatural” questions on the overall performance.

Method	20Q		
	Common	S128	Breeds
GPT 4.1 + Even split prompt			
GoT	9.4	9.2	6.4
UoT	10	10	7
DP	11.7	12.9	7.8
DC	12.3	12.6	9.0
GPT 4.1 + Natural prompt			
GoT	10.2	11.8	7.4
UoT	11	13	9
DP	13.8	16.2	7.8
DC	12.9	14.6	9.3
Qwen 2.5 72B Instruct + Even split prompt			
GoT	10.2	10.2	6.2
UoT	11	11	7
DP	11.9	14.6	8.0
DC	12.4	13.6	8.3
Qwen 2.5 72B Instruct + Natural prompt			
GoT	10.0	10.8	6.6
UoT	11	12	8
DP	12.7	19.2	8.0
DC	12.7	17.9	7.8

Table 6: **Worst case interaction length for each method using even or natural prompts.** For both UoT and GoT We set $d = 3$.

Questions in Practical Settings As noted previously, we claimed that the questions generated by the LLM in the MD and TS settings are reasonably natural. To illustrate this, we provide representative examples of questions sampled from GPT 4.1 in each setting.

Examples of questions sampled for Medical Diagnosis:

- Is the main symptom dermatological, affecting the skin (e.g., rashes, eczema, pigmentation, lesions)?
- Is the disease primarily associated with an infection or inflammation (for example, hepatitis, bronchitis, pneumonia, infectious mononucleosis, sepsis, pharyngitis, gastritis)?
- Is the primary symptom related to the respiratory system (such as cough, shortness of breath, or chest pain)?

These questions target either the patient’s symptoms or the affected body systems, which aligns with how diagnosis is typically conducted in practice. Moreover, each question can be (i) posed to the patient with minor rephrasing, (ii) used as a mental checklist during clinical reasoning, or (iii) mapped to a diagnostic test relevant to specific diseases.

Examples of questions sampled for Troubleshooting:

- Do you notice any warning lights or indicators on the dashboard when you turn the key to the 'ON' position?
- Are there any electrical accessories (like headlights or dashboard lights) not functioning even when the ignition is off?
- Does the car fail to start or crank when turning the ignition key?

1296 These questions are easy to understand and, importantly, refer to symptoms that can be readily
1297 verified by the customer. This property makes them suitable for the context of troubleshooting.
1298

1299 **Ambiguous Questions** In our formulation of the SLS problem, we assume that (i) the codomain
1300 of f is binary, and (ii) each item $s \in \mathcal{S}$ has a unique, well-defined answer under f , as stated in
1301 Assumption 3.1. However, this assumption may not hold in real-world scenarios due to the inherent
1302 ambiguities and interpretive variability commonly present in natural language. One source of such
1303 ambiguity arises when an item name refers to multiple distinct entities. For example, consider the
1304 question: Is the Titanic something a person can pick up with their hands? The answer would be no
1305 if referring to the actual ship, but yes if referring to a DVD of the movie Titanic. While language
1306 ambiguity is a well-studied phenomenon in the field of Natural Language Processing, addressing
1307 such ambiguities remains challenging when applied to the more formal and rigorous framework of
1308 Game Theory. We believe that addressing this challenge presents a promising direction for future
1309 research.

1310 H PROMPTS USED

1311
1312 The prompts used for sampling questions (to implement the function g) in the weighted and un-
1313 weighted variants are shown in Tables 7 and 8 respectively. DP uses the same prompts for asking
1314 questions by setting $m = 1$. DC additionally uses the prompt in Table 9 to choose the question from
1315 the candidate set. The prompts used to generate answers to questions for items (to implement the
1316 function f) is shown in Table 10.
1317

1318 I EXPERIMENT HARDWARE

1319
1320 Running the EFG solver was done on a AMD Ryzen 5 5500 CPU with 32 GB ram. Hosting the
1321 local instance of Qwen 2.5 72B Instruct LLM was done via the vLLMKwon et al. (2023) library on
1322 either 2 Nvidia H200 GPUs each with 141 GB memory, or 4 Nvidia H100 GPUs each with 80 GB
1323 memory.
1324

1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349

1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403

Even Prompt 20Q

We are playing the game of ask and seek, where I am the answerer and you are the questioner.
I have chosen one item from a list of items, and your goal is to identify the correct item from a list of items by asking a series of yes or no questions.
Your should try to ask as few questions as possible.
Here are all the items:
[items]
One of the items is the correct item, please design questions about those items that helps you find the right item and can only be answer by Yes or No.
Notably, this question should fulfill that the count of YES items and NO items are almost the same with a permissible discrepancy of no more than one!
You should respond with the best **[m]** questions you can think of.

Natural Prompt 20Q

We are playing the game of ask and seek, where I am the answerer and you are the questioner.
I have chosen one item from a list of items, and your goal is to identify the correct item from a list of items by asking a series of yes or no questions.
Your should try to ask as few questions as possible.
Here are all the items:
[items]
One of the items is the correct item, please design questions about those items that helps you find the right item and can only be answer by Yes or No.
You should avoid asking unnatural questions such as ones about the number of words the item has, or any such similar questions.
You should respond with the best **[m]** questions you can think of.

MD

You are a doctor trying to diagnose a patient.
The patient suffers from one of the diseases from the provided list, and your goal is to identify the correct item from this list asking a series of yes or no questions.
You should aim to ask as few questions as possible.
Here are all the diseases: **[diseases]**
One of the diseases is the correct disease, please design questions about those items that help you find the right item and can only be answered by Yes or No.
You should respond with the best **[m]** questions you can think of.

TS

You are a car mechanic providing remote troubleshooting to a customer.
The customer’s car suffers from one of the faults from the provided list, and your goal is to identify the correct fault from this list asking a series of yes or no questions.
You should aim to ask as few questions as possible.
Here are all the faults: **[faults]**
One of the faults is the correct fault, please design questions about these faults that help you find the right item and can only be answered by Yes or No.
You should respond with the best **[m]** questions you can think of.

Table 7: **Prompts used to sample candidate questions for unweighted variant.** The main difference between even and natural prompts are *italicized*. The items are represented as a python list, e.g. [`‘Oppenheimer’`, `‘Alan Turing’`, `‘A Beautiful Mind’`], while *m* is an integer

1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457

20Q

We are playing the game of ask and seek, where I am the answerer and you are the questioner. I have chosen one item from a list of items, and your goal is to identify the correct item from a list of items by asking a series of yes or no questions. Each item has a value associated with it, and your penalty score will be the number of questions asked until you find the right item multiplied by the value of the correct item. You should try to minimize this score. Here are all the items and their values: **[items with weights]** One of the items is the correct item, please design questions about those items that helps you find the right item and can only be answer by Yes or No. You should avoid asking unnatural questions such as ones about the number of words the item has, or any such similar questions. You should respond with the best **[m]** questions you can think of.

MD

You are a doctor trying to diagnose a patient. The patient suffers from one of the diseases from the provided list, and your goal is to identify the correct item from this list asking a series of yes or no questions. Each disease has a severity associated with it. Your penalty will be the number of questions asked multiplied by the severity value of the correct disease. You should try to minimize this penalty. Here are all the diseases: **[diseases with weights]** One of the diseases is the correct disease, please design questions about those items that help you find the right item and can only be answered by Yes or No. You should respond with the best **[m]** questions you can think of.

TS

You are a car mechanic providing remote troubleshooting to a customer. The customer’s car suffers from one of the faults from the provided list, and your goal is to identify the correct fault from this list asking a series of yes or no questions. Each fault has a severity associated with it. Your penalty will be the number of questions asked multiplied by the severity value of the correct fault. You should try to minimize this penalty. Here are all the faults: **[faults with weights]** One of the faults is the correct fault, please design questions about these faults that help you find the right item and can only be answered by Yes or No. You should respond with the best **[m]** questions you can think of.

Table 8: **Prompt used to sample candidate questions for weighted variant.** Items with weights are represented as a python dictionary, e.g. {‘Oppenheimer’ : 3, ‘Alan Turing’ : 2, ‘A Beautiful Mind’ : 2}, while m is an integer

1458	
1459	Choosing Prompt for 20Q Unweighted Variant
1460	We are playing the game of ask and seek, where I am the answerer and you are the questioner.
1461	I have chosen one item from a list of items, and your goal is to identify the correct item from a list of items
1462	by asking a series of yes or no questions.
1463	Your should try to ask as few questions as possible.
1464	Here are all the items:
1465	[items]
1466	Here are some Yes or No question about them:
1467	[question]
1468	One of the items is the correct item, please choose one question from the list of questions that helps you
1469	find the right item.
1470	Choosing Prompt for 20Q Weighted Variant
1471	We are playing the game of ask and seek, where I am the answerer and you are the questioner.
1472	I have chosen one item from a list of items, and your goal is to identify the correct item from a list of items
1473	by asking a series of yes or no questions.
1474	Each item has a value associated with it, and your penalty score will be the number of questions asked until
1475	you find the right item multiplied by the value of the correct item. You should try to minimize this score.
1476	Here are all the items:
1477	[items with weights]
1478	Here are some Yes or No question about them:
1479	[question]
1480	One of the items is the correct item, please choose one question from the list of questions that helps you
1481	find the right item.
1482	Choosing Prompt for MD Unweighted Variant
1483	'You are a doctor trying to diagnose a patient.
1484	The patient suffers from one of the diseases from the provided list, and your goal is to identify the correct
1485	item from this list asking a series of yes or no questions.
1486	Your should aim to ask as few questions as possible.
1487	Here are all the diseases: [diseases]
1488	Here are some Yes or No question about them: [question]
1489	One of the diseases is the correct disease, please choose one question from the list of questions that helps
1490	you narrow down to the right disease as quickly as possible.
1491	Choosing Prompt for TS Unweighted Variant
1492	You are a car mechanic providing remote troubleshooting to a customer.
1493	The customer's car suffers from one of the faults from the provided list, and your goal is to identify the
1494	correct fault from this list asking a series of yes or no questions.
1495	Your should aim to ask as few questions as possible.
1496	Here are all the faults: [faults]
1497	Here are some Yes or No question about them: [question]
1498	One of the faults is the correct fault, please choose one question from the list of questions that helps you
1499	narrow down to the right fault as quickly as possible.
1500	
1501	Table 9: Prompts used by DC to choose questions. Questions are represented as a python dictionary, e.g. {0 : 'Related to codes?', 1 : 'Is it a movie?', 2 : 'Is it a person?'}. The weighted variants
1502	of the prompt for MD and TS setting is obtained by modifying the unweighted variant in a similar
1503	manner as in the 20Q setting.
1504	
1505	Answer Prompt
1506	Here are some [items/diseases/car faults] :
1507	[items]
1508	Here is a Yes or No question about them:
1509	[question]
1510	Please classify the [items/diseases/car faults] above based on this question. You should ensure that each
1511	item should only appear once in the final classification. If you are unsure about any item, you can mention