

Contrastive Learning with Dynamic Localized Repulsion for Brain Age Prediction on 3D Stiffness Maps

Anonymous authors

Paper under double-blind review

Abstract

In the field of neuroimaging, accurate brain age prediction is pivotal for uncovering the complexities of brain aging and pinpointing early indicators of neurodegenerative conditions. Recent advancements in self-supervised learning, particularly in contrastive learning, have demonstrated greater robustness when dealing with complex datasets. However, current approaches often fall short in generalizing across non-uniformly distributed data, prevalent in medical imaging scenarios. To bridge this gap, we introduce a novel contrastive loss that adapts dynamically during the training process, focusing on the localized neighborhoods of samples. Moreover, we expand beyond traditional structural features by incorporating brain stiffness—a mechanical property previously underexplored yet promising due to its sensitivity to age-related changes. This work presents the first application of self-supervised learning to brain mechanical properties, using compiled stiffness maps from various clinical studies to predict brain age. Our approach, featuring dynamic localized loss, consistently outperforms existing state-of-the-art methods, demonstrating superior performance and laying the way for new directions in brain aging research.

1 Introduction

Aging causes significant changes in the structure and function of the brain. Magnetic Resonance Elastography (MRE) has recently emerged as a non-invasive technique to measure mechanical brain properties (Hiscox et al., 2016), such as stiffness μ , that is, the resistance of a viscoelastic material to an applied harmonic force. Studies have shown a promising age sensitivity of whole-brain stiffness measurements (Hiscox et al., 2021), surpassing established neuroimaging age biomarkers, such as volume measurements (Sack et al., 2011). With advancing MRE protocols, improvements in resolution have enabled the study of stiffness changes in more localized brain regions, revealing regional age-related variability (Murphy et al., 2013; Arani et al., 2015; Takamura et al., 2020; Hiscox et al., 2018; Delgorio et al., 2021). Furthermore, clinical studies in patients with neurodegenerative diseases have revealed stiffness alterations exceeding those observed in healthy aging (Murphy et al., 2016; Hiscox et al., 2020a). However, current methods are limited to region-wide averages and thus fail to exploit the rich information available in stiffness maps, which can be accessed through nonlinear relationships at a voxel level.

Brain age prediction leverages neuroimaging data through machine learning by casting it as a regression problem, wherein models are trained on healthy samples to establish a baseline trajectory for aging. Regression is a statistical method used to predict a continuous outcome—such as age—based on input data, in this case, brain imaging data. This approach is particularly promising for identifying deviations from normal aging processes that might indicate neurological conditions. This approach has traditionally been applied to structural brain features using T1-weighted MRI (Baecker et al., 2021). More recently, the scope has expanded to include features obtained from resting-state fMRI and diffusion imaging are also being examined (Lund et al., 2022; Niu et al., 2020). Additionally, its potential in detecting and the prognosis of neurodegenerative disorders such as Alzheimer’s Disease (AD) is gaining significant attention (Lee et al., 2022). In parallel, modeling approaches have evolved from traditional regression methods to state-of-the-art self-supervised learning (Zha et al., 2024; Dufumier et al., 2021; Barbano et al., 2023). Inspired by advancements in computer vision, self-supervised learning techniques, particularly contrastive learning

Method	Contrastive Regression Loss
Rank-N-Contrast	$\mathcal{L}^{RnC} = -\sum_i \sum_{k \neq i} \log \frac{\exp(s_k)}{\sum_{x_{i,t} \in S_{i,j}} \exp(s_{i,t})}$ with $S_{i,j} := \{x_k k \neq i, d(y_i, y_k) \geq d(y_i, y_j)\}$
Y-Aware	$\mathcal{L}^{y-aware} = -\sum_i \sum_{k \neq i} \frac{w_{i,k}}{\sum_t w_{i,t}} \log \left(\frac{\exp(s_{i,k})}{\sum_{t \neq k} \exp(s_{i,t})} \right)$
Threshold	$\mathcal{L}^{threshold} = -\sum_i \sum_{k \neq i} \frac{w_{i,k}}{\sum_t \delta_{w_{i,t} < w_{i,k}} w_{i,t}} \log \left(\frac{\exp(s_{i,k})}{\sum_{t \neq k} \delta_{w_{i,t} < w_{i,k}} \exp(s_{i,t})} \right)$
Exponential	$\mathcal{L}^{exp} = -\sum_i \sum_{k \neq i} \frac{w_{i,k}}{\sum_t w_{i,t}} \log \left(\frac{\exp(s_{i,k})}{\sum_{t \neq k} \exp(s_{i,t}(1-w_{i,t}))} \right)$

Table 1: Overview of Contrastive Regression Losses. This details existing methods each employing distinct strategies to refine the contrastive learning process for regression tasks.

methods, have been effectively adapted for predicting brain age from structural MRI scans (Dufumier et al., 2021; Barbano et al., 2023). Contrastive learning, a technique that learns by comparing pairs of examples, enhances model performance by focusing on the fine distinctions between similar cases.

Despite their potential, current methods often struggle with generalization, particularly across datasets characterized by non-uniform distributions. To address this limitation, we introduce a novel contrastive loss that specifically focuses on localized sample neighborhoods. This method is distinctively designed to adapt dynamically across different stages of training, thereby enhancing model performance where traditional approaches falter. Furthermore, considering the demonstrated age sensitivity of mechanical properties compared to structural brain properties, this study is pioneering. *It represents the first application of contrastive learning to brain stiffness maps*, highlighting a new direction in neuroimaging research. Our contributions are summarized next.

- We introduce a dynamic localized repulsion approach, specifically tailored for the framework of contrastive regression learning. Our new method is designed to address the major challenge of limited generalizability in medical image analysis, particularly within datasets characterized by non-uniform distributions. By concentrating on these challenging distributions, our approach not only enhances the robustness of the models but also performance.
- We apply our method to brain stiffness maps, introducing a novel, age-sensitive modality for brain age prediction that offers insights into neurological aging processes.
- To validate our novel contrastive regression loss, we have aggregated the largest multi-study dataset of brain stiffness from healthy controls, enabling comprehensive and robust conditions. We conducted experiments and demonstrated higher performance than existing techniques.

2 Related Work

• **Regression Task** Regression is a statistical technique that establishes a relationship between a set of independent variables (X) and a dependent variable (Y), through a function $f : X \rightarrow Y$. Regression specifically addresses continuous variables, with Y taking values in \mathbb{R} . Known for its robust effectiveness, regression has made significant impacts across various domains including (Fanelli et al., 2011; Sun et al., 2012; Lathuilière et al., 2019). Recent decades have seen a surge in research aimed at advancing deep regression techniques, significantly enhancing their performance and applicability – for example, the works of that (Gao et al., 2018; Rothe et al., 2015; Li et al., 2021; Cao et al., 2020; Yang et al., 2021). Another interesting family of techniques, which is the focus of this work, falls within the contrastive learning family. This perspective is particularly interesting due to its ability to enhance learning by emphasizing differences between samples, thereby improving model robustness and generalization (Zha et al., 2024; Barbano et al., 2023).

• **Contrastive Learning.** To construct semantically rich and structured representations, contrastive learning has become a widely adopted method for self-supervised representation learning. This technique involves differentiating between similar (positive) and dissimilar (negative) pairs of data samples x_i and x_k , with the goal of adjusting the distances between representations in the embedding space—bringing similar items

closer and pushing dissimilar ones apart (Chen et al., 2020; Khosla et al., 2020). Contrastive learning initially gained popularity through its applications in computer vision, where it demonstrated significant improvements in tasks such as image classification and object detection. Early methods like SimCLR (Chen et al., 2020) introduced a simple yet effective framework that maximized agreement between differently augmented views of the same data sample. This approach utilized a contrastive loss function to bring representations of augmented pairs (positive pairs) closer while pushing apart representations of different samples (negative pairs). Building on these foundations, a notable advancement was the introduction of supervised contrastive learning (Khosla et al., 2020), which extended the contrastive loss to leverage label information, treating all samples with the same label as positives. This approach enhanced the performance of models by incorporating supervised information into the self-supervised learning framework.

As we shift focus from classification to regression problems, the distinction between positive and negative pairs transitions to a continuous spectrum. This shift necessitates the model’s ability to discern varying degrees of similarity, represented as $s_{i,k} = \text{sim}(f(x_i), f(x_k))$, beyond mere categorical differentiation. Particularly, we are interested in brain age prediction, which requires precise modeling of age-related changes in brain structure and function. In response to the challenge of integrating continuous labels such as age, recent advancements propose strategies such as the Y-Aware loss (Dufumier et al., 2021), which softens the boundary between positive and negative samples. Similarly, the work of that (Barbano et al., 2023) proposed the Threshold and Exponential losses, which adjust the strength of alignment and repulsion based on the similarity between continuous labels. Another work introduced the Rank-N-Contrast loss (Zha et al., 2024), which employs a comparative ranking strategy among samples. This method ranks samples based on their similarity to a given anchor, creating a ranking-based continuous spectrum of positive and negative pairs.

3 Proposed Technique

This section details the proposed dynamic localized repulsion strategy, a novel approach within contrastive learning tailored for regression tasks.

3.1 Problem Setup

The primary challenge in brain age modeling lies in accurately mapping high-dimensional brain imaging data to a continuous age variable. Traditional contrastive learning methods are limited in their capacity to handle the subtle variations in brain stiffness associated with aging due to their global approach. Our proposed technique introduces a dynamic, localized strategy, focusing on progressively capture age-related features effectively. Formally, in brain age modeling, our objective is to train a neural network capable of accurately mapping brain images $x \in X$ to their corresponding target ages $y \in \mathbb{R}$. The model comprises two key components: a feature encoder $f(\cdot) : X \rightarrow \mathbb{R}^d$, which transforms brain images into a representative feature space, and an age predictor $g(\cdot) : \mathbb{R}^d \rightarrow \mathbb{R}$, tasked with estimating the age from these features.

3.2 Dynamic Localized Repulsion

The dynamic localized repulsion technique is a cornerstone of our methodology, designed to optimize the contrastive learning framework specifically for the regression tasks inherent in brain age modeling. This section outlines the detailed mechanics of this technique, including model components, operational processes, and algorithmic strategies.

To enhance the precision of contrastive regression learning, we introduce a dynamic localized repulsion approach that progressively explores varied scales within the embedding space, as depicted in Figure 1. This methodology systematically adjusts the selection of repulsion candidates, taking into account both their proximity and the evolutionary stage of training. The selection process for repulsed samples is defined by:

$$NN(x_i; \text{epoch}) = \{x_k \mid x_k \text{ is among the } NN_{nb}(\text{epoch}) \text{ nearest neighbors of } x_i \text{ based on } d(x_k, x_i)\} \quad (1)$$




Figure 1: Graphical Illustration of Our Proposed Method. Throughout training (top to bottom), the repulsion is progressively localized as the number of samples, selected as nearest neighbors, are gradually decreased.

This expression delineates the set of samples subject to repulsion, identified by their distance $d(\cdot)$. Our approach progressively narrows the scope of nearest neighbors involved in the repulsion process, thereby focusing the learning on increasingly localized vicinities within the embedding space. This adaptive mechanism is governed by two critical hyperparameters: the final count of nearest neighbors, $NN_{nb, final}$, representing the ultimate scope of repulsion at the end of training, and the decrement frequency, $NN_{step\ size}$, which specifies the interval of epochs for adjustments in the neighbor count, as detailed in Algorithm 1.

Algorithm 1 Calculation of Number of Nearest Neighbors NN_{nb} (epoch)

Require: $NN_{step\ size} < \max\ epochs \wedge NN_{nb, final} \geq 0$

$steps\ completed \leftarrow \left\lfloor \frac{current\ epoch}{NN_{step\ size}} \right\rfloor$

$total\ steps \leftarrow \left\lfloor \frac{\max\ epochs}{NN_{step\ size}} \right\rfloor$

$NN_{nb}\ \text{decrement per step} \leftarrow \frac{batch\ size - NN_{nb, final}}{total\ steps - 1}$

$NN_{nb} \leftarrow batch\ size - (NN_{nb}\ \text{decrement per step} \times steps\ completed)$

$NN_{nb} \leftarrow \max(NN_{nb}, NN_{nb, final})$

In datasets that show non-uniform distributions, especially those with multi-modal characteristics, it is common to find some target areas oversampled and others undersampled. This scenario is typical in neuroimaging datasets (see Fig. 3). Our dynamic localized strategy is designed to address this issue. It starts by segregating distinct groups and then explores the differences within those groups more deeply. This process is illustrated in Fig. 1. Our approach aims to reveal more coherent representations throughout the dataset.

Following the methodology proposed by (Barbano et al., 2023), we utilize kernel functions to determine the degrees of positiveness, $w_{i,k} = K(y_i - y_k)$ where $0 \leq w_{i,k} \leq 1$, between pairs of samples. This metric is defined by the function $K(y_i - y_k)$ and reflects the age similarity between two samples. A higher value of $w_{i,k}$ suggests that the samples are close in age, prompting the algorithm to minimize the distance between their representations in the embedding space. Conversely, a lower value indicates a significant age difference, thus triggering the repulsion mechanism to increase the distance between their embeddings.

Each sample x_i in a batch is compared against every other sample x_k , with the embeddings being adjusted based on their relative age similarities. The selection of nearest neighbors for this comparison, $NN_{nb}(\text{epoch})$, dynamically changes as the training progresses. Initially, a larger set of neighbors is considered to establish broad relationships. As training advances, this number is progressively reduced to focus on more immediate and relevant interactions, thus refining the learning towards localized features. The per-sample dynamic localized repulsion loss reads:

$$l_{DynLocRep}^i = - \sum_k \frac{w_{i,k}}{\sum_t w_{i,t}} \log \left(\frac{\exp(s_{i,k})}{\sum_{x_t \in NN(x_i; epoch)} \exp(s_{i,t}(1 - w_{i,t}))} \right). \quad (2)$$

This expression calculates the contribution of each sample pair to the overall loss. It normalizes these contributions by the sum of positiveness weights for all comparisons within the batch, adjusting the impact of each pair based on their age-related similarity. The softmax function is then applied to these normalized and adjusted similarity scores $s_{i,k}$, which are recalculated for each dynamically defined nearest neighbor set.

What is the Intuition Behind Our Dynamic Localized Repulsion? We address the challenge of non-uniform data distributions in neuroimaging datasets. Traditional learning models often fail to adequately distinguish between different age groups when these groups are unevenly represented in the training data. Our approach refines this by adjusting embeddings dynamically. This is done via (2) that represents the per-sample loss function in a contrastive learning framework, which aims to dynamically adjust the embeddings based on age-related similarities. The essence of this equation lies in its ability to modulate the degree of repulsion or attraction between samples within the same batch based on their age proximity, which is quantified by $w_{i,k}$ the positiveness weight. *This formulation allows for adaptive learning where the focus is progressively shifted toward more challenging or informative pairs, potentially those that are not well-aligned in age, thus encouraging the model to learn finer distinctions as training progresses.*

The total loss $\mathcal{L}_{DynLocRep}$ is then calculated over all samples as anchors:

$$\begin{aligned} \mathcal{L}_{DynLocRep} &= \sum_i l_{DynLocRep}^i \\ &= - \sum_i \sum_{k \neq i} \frac{w_{i,k}}{\sum_t w_{i,t}} \log \left(\frac{\exp(s_{i,k})}{\sum_{x_t \in NN(x_i; epoch)} \exp(s_{i,t}(1 - w_{i,t}))} \right). \end{aligned} \quad (3)$$

This aggregated loss function is key for structuring the embedding space optimally, ensuring that samples with similar ages are located closer together while those with significant age differences are distanced. Such a configuration not only enhances the accuracy of age prediction but also improves the model’s ability on complex neuroimaging datasets.

4 Experimental Results

This section details the complete set of experiments conducted to evaluate the proposed technique.

4.1 Data Description

We have assembled a dataset of 311 three-dimensional (3D) brain stiffness maps obtained from healthy control subjects (HC). These data were sourced from multiple clinical studies, all of which utilized highly




Figure 2: Comparison of Neuroimaging Modalities. Each row shows three orthogonal views (sagittal, coronal, and axial) of the brain images, highlighting the differences in mechanical and structural properties across different ages.

similar Magnetic Resonance Elastography (MRE) protocols. This ensures consistency across the collected data. For detailed information on the individual studies and the data collection methods, please refer to Table 2. All datasets were collected in accordance with ethical standards, under protocols approved by the respective local institutional review boards.

The age distribution of all samples from each study is illustrated in Fig. 3. Following this, stiffness maps, depicted in Fig. 4.1, were processed to enhance quality and uniformity. Initially, each map underwent skull stripping using Freesurfer (Fischl, 2012), a step to isolate the brain tissue from non-relevant anatomical structures. Subsequently, we applied a bias field correction to remove intensity gradients that could affect subsequent analyses.

To address the issue of data heterogeneity across different studies, we performed affine registration of the images to the MNI152 template. This registration was conducted at an isotropic resolution of 2 mm^3 using ANTs (Avants et al., 2009), ensuring consistent orientation and scale among all datasets. Finally, we normalized the quantitative stiffness images, setting their mean to zero and standard deviation to one across the dataset.

Table 2: Compilation of Dataset Information Across Multiple Studies: This table presents a detailed breakdown of the datasets used in our analysis. The aggregated data encompasses a diverse age range and a balanced gender ratio, facilitating a comprehensive evaluation of brain stiffness in healthy controls.

Study	Published In	#Subjects	Age [years]	Sex [F:M]
1	(Hiscox et al., 2020c)	134	23.4 ± 4.0	78:56
2	(Bayly et al., 2021)	60	37.8 ± 20.9	34:26
3	(Hiscox et al., 2020b)	12	69.4 ± 2.4	6:6
4	(Delgorio et al., 2023)	68	69.3 ± 5.8	49:19
5	(Sanjana et al., 2021; Delgorio et al., 2022)	37	49.1 ± 16.6	16:21
Total	-	311	41.0 ± 21.9	183:128

4.2 Evaluation Protocol

Our evaluation strategy involved a 3D ResNet-18 model (33.5M parameters), which was pre-trained on the openBHB dataset (Dufumier et al., 2022), containing over 5000 T_1 3D MRI brain images from multiple scanning sites, using the best reported method from the OpenBHB challenge (Dufumier et al., 2022). To enhance generalization to our stiffness dataset, we utilized quasi-raw images, ensuring uniform image pre-processing, and downsampled the structural MRI images to 2 mm^3 isotropic resolution. The pre-trained ResNet-18 underwent full fine-tuning (i.e. updating all weights) on our brain stiffness dataset, following an 80:20 train-test split, over 50 epochs and a batch size of 32 using the Adam optimizer. This optimization included an initial learning rate of 1×10^{-4} , decreased by 0.9 every 10 epochs, and a weight decay of 5×10^{-5} . Hyperparameters $NN_{nb,final}$ and $NN_{stepsize}$ were optimized via random search across 30 iterations. Our implementation is based on Barbano et al. (Barbano et al., 2023). Our models were trained using an NVIDIA A100-SXM-80GB GPU. Following the training of the representations, we employed a Ridge Regression estimator (Barbano et al., 2023) on top of the frozen encoder to predict age. As an evaluation metric, we calculated the mean absolute error (MAE) on the test set, averaging the results across five random seeds.

4.3 Results and Discussion

We begin by evaluating the representations of stiffness maps learned using our dynamic localized repulsion loss as in (3) with Manhattan distance, $NN_{nb,final} = 14$ and $NN_{stepsize} = 1$, selected via random search, against those using current state-of-the-art contrastive regression losses.

Table 3 illustrates the effectiveness of our proposed Dynamical Localized Repulsion approach in the context of brain age prediction from stiffness maps, as evidenced by the Mean Absolute Error (MAE) metric. When comparing our method to existing state-of-the-art contrastive regression losses, our approach demonstrates superior accuracy in predicting brain age. In a closer look, we can observe that Rank-N-Contrast (Zha et al., 2024) shows the highest MAE, suggesting it may be less adept at capturing the nuanced patterns within the data necessary for precise age prediction. Y-Aware and Exponential (Dufumier et al., 2021; Barbano et al., 2023) losses show improvements over Rank-N-Contrast. These methods appear to better align with the underlying age-related changes in brain stiffness but still fall short compared to our approach. Threshold (Barbano et al., 2023) loss offers a competitive performance, yet it does not achieve the same level of accuracy as our method. This could indicate that while it handles some aspects of the data variability effectively, it might not fully capture the localized age-related changes as our method does. Our proposed loss achieves the lowest MAE, underscoring its ability to more accurately model the age-related changes in brain stiffness. This suggests that our method’s focus on localized sample neighborhoods and its dynamic adaptation during the training process significantly contribute to its improved performance.

To investigate the role of the distance norm for nearest neighbor selection of our dynamic localized repulsion approach, we conduct an ablation study, examining the impact of various distance norms on the model’s




Figure 3: Age Distribution of Participants from Multi-Site MR Elastography Studies. Contribution to the 311 healthy control (HC) stiffness brain maps of different clinical studies is highlighted in color. The distribution is bimodal, indicating two predominant age groups among the subjects.

Table 3: Representation comparison demonstrates the superior performance of our method over state-of-the-art contrastive regression losses.

Contrastive Regression Loss	MAE [years]
Rank-N-Contrast (Zha et al., 2024)	5.266 ± 0.587
Y-Aware (Dufumier et al., 2021; Barbano et al., 2023)	3.852 ± 0.212
Threshold (Barbano et al., 2023)	4.420 ± 0.503
Exponential (Dufumier et al., 2021; Barbano et al., 2023)	3.824 ± 0.215
Dynamical Localized Repulsion (Ours)	3.724 ± 0.220

performance, as detailed in Fig. 5. The method shows robustness regarding the choice of distance norm. Our findings reveal that the Manhattan norm achieves the lowest MAE of 3.724 ± 0.220 years, outperforming the Cosine (MAE = 3.748 ± 0.142 years), Euclidean (MAE = 3.806 ± 0.154 years), and Chebyshev norm (MAE = 3.842 ± 0.196 years).

Following the ablation study, we turn our attention to the evolution of the representations as the model learns across epochs. The UMAP embedding visualizations presented in Fig. 4 showcase the progressive refinement of the feature space through epochs 1, 6, 21, 30, 40 and 50. Initially, the representations are scattered and lack clear structure, indicating that the model is yet to learn distinct age-related patterns. As training progresses, we observe the emergence of more defined clusters, reflecting the model’s increasing adeptness at capturing age-related variations in brain stiffness. By epoch 50, the embeddings show distinct, well-separated groupings, suggesting that our method has achieved a better understanding of the underlying age-related features. These visualizations not only confirm the effectiveness of our dynamic localized repulsion approach but also offer intuitive insights into how contrastive learning can be harnessed for regression tasks in medical imaging.




Figure 4: UMAP visualizations of representations show model improvements throughout various learning stages. As epochs increase, the clusters become more distinct and separate, indicating a more defined representation of the underlying data features.




Figure 5: Ablation study for different distance norms when selecting nearest neighbors shows Manhattan norm achieves lowest MAE.

5 Conclusion

We introduced a novel contrastive regression loss that adeptly prioritizes local regions within embedding spaces and dynamically adjusts these regions throughout the training process. By applying this method to brain stiffness maps obtained from Magnetic Resonance Elastography (MRE), we achieved superior predictive performance in brain age estimation compared to established contrastive learning methods. This advancement not only demonstrates our model’s efficacy but also underscores the potential of using localized dynamic adjustments in the analysis of complex neuroimaging data. Significantly, *our research marks the first application of self-supervised learning techniques to explore the mechanical properties of the brain, an area previously uncharted in the literature.* The implications of this are profound, opening up new avenues for understanding the structural changes associated with aging and potentially other neurological conditions. Future work includes to extend our framework to include cohorts with neurological diseases, such as Alzheimer’s and Parkinson’s. This expansion is expected to provide deeper insights into the progression and early diagnosis of these conditions, leveraging the detection capabilities of our model. Additionally, we aim to explore the integration of multimodal imaging data to enhance the robustness and accuracy of our predictions, potentially leading to breakthroughs in personalized medicine and neuroimaging analytics.

References

- Arvin Arani, Matthew C Murphy, Kevin J Glaser, Armando Manduca, David S Lake, Scott A Kruse, Clifford R Jack Jr, Richard L Ehman, and John Huston 3rd. Measuring the effects of aging and sex on regional brain stiffness with mr elastography in healthy older adults. *Neuroimage*, 111:59–64, 2015. [1](#)
- Brian B Avants, Nick Tustison, Gang Song, et al. Advanced normalization tools (ants). *Insight j*, 2(365): 1–35, 2009. [6](#)
- Lea Baecker, Rafael Garcia-Dias, Sandra Vieira, Cristina Scarpazza, and Andrea Mechelli. Machine learning for brain age prediction: Introduction to methods and clinical applications. *EBioMedicine*, 72, 2021. [1](#)
- Carlo Alberto Barbano, Benoit Dufumier, Edouard Duchesnay, Marco Grangetto, and Pietro Gori. Contrastive learning for regression in multi-site brain age prediction. In *2023 IEEE 20th International Symposium on Biomedical Imaging (ISBI)*, pp. 1–4. IEEE, 2023. [1](#), [2](#), [3](#), [5](#), [7](#), [8](#)
- Philip V Bayly, Ahmed Alshareef, Andrew K Knutsen, Kshitiz Upadhyay, Ruth J Okamoto, Aaron Carass, John A Butman, Dzung L Pham, Jerry L Prince, KT Ramesh, et al. Mr imaging of human brain mechanics in vivo: new measurements to facilitate the development of computational models of brain injury. *Annals of biomedical engineering*, 49:2677–2692, 2021. [7](#)
- Wenzhi Cao, Vahid Mirjalili, and Sebastian Raschka. Rank consistent ordinal regression for neural networks with application to age estimation. *Pattern Recognition Letters*, 140:325–331, 2020. [2](#)
- Ting Chen, Simon Kornblith, Mohammad Norouzi, and Geoffrey Hinton. A simple framework for contrastive learning of visual representations. In *International conference on machine learning*, pp. 1597–1607. PMLR, 2020. [3](#)
- Peyton L Delgorio, Lucy V Hiscox, Ana M Daugherty, Faria Sanjana, Ryan T Pohlig, James M Ellison, Christopher R Martens, Hillary Schwarb, Matthew DJ McGarry, and Curtis L Johnson. Effect of aging on the viscoelastic properties of hippocampal subfields assessed with high-resolution mr elastography. *Cerebral Cortex*, 31(6):2799–2811, 2021. [1](#)
- Peyton L Delgorio, Lucy V Hiscox, Ana M Daugherty, Faria Sanjana, Grace McIlvain, Ryan T Pohlig, Matthew DJ McGarry, Christopher R Martens, Hillary Schwarb, and Curtis L Johnson. Structure–function dissociations of human hippocampal subfield stiffness and memory performance. *Journal of Neuroscience*, 42(42):7957–7968, 2022. [7](#)
- Peyton L Delgorio, Lucy V Hiscox, Grace McIlvain, Mary K Kramer, Alexa M Diano, Kyra E Twohy, Alexis A Merritt, Matthew DJ McGarry, Hillary Schwarb, Ana M Daugherty, et al. Hippocampal subfield viscoelasticity in amnesic mild cognitive impairment evaluated with mr elastography. *NeuroImage: Clinical*, 37:103327, 2023. [7](#)

- Benoit Dufumier, Pietro Gori, Julie Victor, Antoine Grigis, Michele Wessa, Paolo Brambilla, Pauline Favre, Mircea Polosan, Colm McDonald, Camille Marie Piguët, et al. Contrastive learning with continuous proxy meta-data for 3d mri classification. In *Medical Image Computing and Computer Assisted Intervention–MICCAI 2021: 24th International Conference, Strasbourg, France, September 27–October 1, 2021, Proceedings, Part II* 24, pp. 58–68. Springer, 2021. 1, 2, 3, 7, 8
- Benoit Dufumier, Antoine Grigis, Julie Victor, Corentin Ambroise, Vincent Frouin, and Edouard Duchesnay. Openbhb: a large-scale multi-site brain mri data-set for age prediction and debiasing. *NeuroImage*, 263: 119637, 2022. 7
- Gabriele Fanelli, Juergen Gall, and Luc Van Gool. Real time head pose estimation with random regression forests. In *CVPR 2011*, pp. 617–624. IEEE, 2011. 2
- Bruce Fischl. Freesurfer. *Neuroimage*, 62(2):774–781, 2012. 6
- Bin-Bin Gao, Hong-Yu Zhou, Jianxin Wu, and Xin Geng. Age estimation using expectation of label distribution learning. In *IJCAI*, volume 1, pp. 3, 2018. 2
- Lucy V Hiscox, Curtis L Johnson, Eric Barnhill, Matt DJ McGarry, John Huston, Edwin JR Van Beek, John M Starr, and Neil Roberts. Magnetic resonance elastography (mre) of the human brain: technique, findings and clinical applications. *Physics in Medicine & Biology*, 61(24):R401, 2016. 1
- Lucy V Hiscox, Curtis L Johnson, Matthew DJ McGarry, Michael Perrins, Aimee Littlejohn, Edwin JR van Beek, Neil Roberts, and John M Starr. High-resolution magnetic resonance elastography reveals differences in subcortical gray matter viscoelasticity between young and healthy older adults. *Neurobiology of aging*, 65:158–167, 2018. 1
- Lucy V Hiscox, Curtis L Johnson, Matthew DJ McGarry, Helen Marshall, Craig W Ritchie, Edwin JR Van Beek, Neil Roberts, and John M Starr. Mechanical property alterations across the cerebral cortex due to alzheimer’s disease. *Brain Communications*, 2(1):fcz049, 2020a. 1
- Lucy V Hiscox, Curtis L Johnson, Matthew DJ McGarry, Helen Marshall, Craig W Ritchie, Edwin JR Van Beek, Neil Roberts, and John M Starr. Mechanical property alterations across the cerebral cortex due to alzheimer’s disease. *Brain Communications*, 2(1):fcz049, 2020b. 7
- Lucy V Hiscox, Matthew DJ McGarry, Hillary Schwarb, Elijah EW Van Houten, Ryan T Pohlig, Neil Roberts, Graham R Huesmann, Agnieszka Z Burzynska, Bradley P Sutton, Charles H Hillman, et al. Standard-space atlas of the viscoelastic properties of the human brain. *Human brain mapping*, 41(18): 5282–5300, 2020c. 7
- Lucy V Hiscox, Hillary Schwarb, Matthew DJ McGarry, and Curtis L Johnson. Aging brain mechanics: Progress and promise of magnetic resonance elastography. *Neuroimage*, 232:117889, 2021. 1
- Curtis L Johnson, Joseph L Holtrop, Matthew DJ McGarry, John B Weaver, Keith D Paulsen, John G Georgiadis, and Bradley P Sutton. 3d multislabs, multishot acquisition for fast, whole-brain mr elastography with high signal-to-noise efficiency. *Magnetic resonance in medicine*, 71(2):477–485, 2014. 13
- Prannay Khosla, Piotr Teterwak, Chen Wang, Aaron Sarna, Yonglong Tian, Phillip Isola, Aaron Maschinot, Ce Liu, and Dilip Krishnan. Supervised contrastive learning. *Advances in neural information processing systems*, 33:18661–18673, 2020. 3
- Stéphane Lathuilière, Pablo Mesejo, Xavier Alameda-Pineda, and Radu Horaud. A comprehensive analysis of deep regression. *IEEE transactions on pattern analysis and machine intelligence*, 42(9):2065–2081, 2019. 2
- Jeyeon Lee, Brian J Burkett, Hoon-Ki Min, Matthew L Senjem, Emily S Lundt, Hugo Botha, Jonathan Graff-Radford, Leland R Barnard, Jeffrey L Gunter, Christopher G Schwarz, et al. Deep learning-based brain age prediction in normal aging and dementia. *Nature Aging*, 2(5):412–424, 2022. 1

- Wanhua Li, Xiaoke Huang, Jiwen Lu, Jianjiang Feng, and Jie Zhou. Learning probabilistic ordinal embeddings for uncertainty-aware regression. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pp. 13896–13905, 2021. [2](#)
- Martina J Lund, Dag Alnæs, Ann-Marie G de Lange, Ole A Andreassen, Lars T Westlye, and Tobias Kaufmann. Brain age prediction using fmri network coupling in youths and associations with psychiatric symptoms. *NeuroImage: Clinical*, 33:102921, 2022. [1](#)
- Matthew C Murphy, John Huston III, Clifford R Jack Jr, Kevin J Glaser, Matthew L Senjem, Jun Chen, Armando Manduca, Joel P Felmlee, and Richard L Ehman. Measuring the characteristic topography of brain stiffness with magnetic resonance elastography. *PloS one*, 8(12):e81668, 2013. [1](#)
- Matthew C Murphy, David T Jones, Clifford R Jack Jr, Kevin J Glaser, Matthew L Senjem, Armando Manduca, Joel P Felmlee, Rickey E Carter, Richard L Ehman, and John Huston III. Regional brain stiffness changes across the alzheimer’s disease spectrum. *NeuroImage: Clinical*, 10:283–290, 2016. [1](#)
- Xin Niu, Fengqing Zhang, John Kounios, and Hualou Liang. Improved prediction of brain age using multi-modal neuroimaging data. *Human brain mapping*, 41(6):1626–1643, 2020. [1](#)
- Rasmus Rothe, Radu Timofte, and Luc Van Gool. Dex: Deep expectation of apparent age from a single image. In *Proceedings of the IEEE international conference on computer vision workshops*, pp. 10–15, 2015. [2](#)
- Ingolf Sack, Kaspar-Josche Streitberger, Dagmar Krefting, Friedemann Paul, and Jürgen Braun. The influence of physiological aging and atrophy on brain viscoelastic properties in humans. *PloS one*, 6(9):e23451, 2011. [1](#)
- Faria Sanjana, Peyton L Delgorio, Lucy V Hiscox, Theodore M DeConne, Joshua C Hobson, Matthew L Cohen, Curtis L Johnson, and Christopher R Martens. Blood lipid markers are associated with hippocampal viscoelastic properties and memory in humans. *Journal of Cerebral Blood Flow & Metabolism*, 41(6):1417–1427, 2021. [7](#)
- Min Sun, Pushmeet Kohli, and Jamie Shotton. Conditional regression forests for human pose estimation. In *2012 IEEE Conference on Computer Vision and Pattern Recognition*, pp. 3394–3401. IEEE, 2012. [2](#)
- Tomohiro Takamura, Utaroh Motosugi, Yu Sasaki, Takashi Kakegawa, Kazuyuki Sato, Kevin J Glaser, Richard L Ehman, and Hiroshi Onishi. Influence of age on global and regional brain stiffness in young and middle-aged adults. *Journal of Magnetic Resonance Imaging*, 51(3):727–733, 2020. [1](#)
- Yuzhe Yang, Kaiwen Zha, Yingcong Chen, Hao Wang, and Dina Katabi. Delving into deep imbalanced regression. In *International conference on machine learning*, pp. 11842–11851. PMLR, 2021. [2](#)
- Kaiwen Zha, Peng Cao, Jeany Son, Yuzhe Yang, and Dina Katabi. Rank-n-contrast: Learning continuous representations for regression. *Advances in Neural Information Processing Systems*, 36, 2024. [1](#), [2](#), [3](#), [7](#), [8](#)

A Appendix

A.1 Brain Coverage of Stiffness Maps




Figure 6: Distribution of Brain Coverage in Stiffness Maps Across Studies. In Magnetic Resonance Elastography (MRE), achieving optimal brain coverage necessitates a balance between high spatial resolution, signal-to-noise ratio (SNR), and acceptable scan times (Johnson et al., 2014). The majority of existing brain MRE studies focus on deep brain structures, leading to limited coverage in certain areas. This limitation is illustrated here, where the brain coverage variability in our stiffness maps is visualized.




Figure 7: Examples of stiffness maps across a spectrum of coverage percentages. Full coverage is shown alongside three reduced coverage cases: 95%, 90%, and 80%, respectively. As seen in Fig. 6, most of the data fall between 90% and full brain coverage.