

FILTERED NOT MIXED: FILTERING-BASED ONLINE GATING FOR MIXTURE OF LARGE LANGUAGE MODELS

Anonymous authors

Paper under double-blind review

ABSTRACT

We propose **MoE-F** – a formalized mechanism for combining N pre-trained expert Large Language Models (LLMs) in online time-series prediction tasks. MoE-F adaptively forecasts the optimal weighting of LLM predictions at each time step by leveraging the conditional information in each expert’s running performance, enabling the best combination of experts for the next step prediction. Diverging from static (learned) Mixture of Experts (MoE) methods, our approach employs time-adaptive stochastic filtering techniques to combine experts. By framing the expert selection problem as a finite state-space, continuous-time Hidden Markov model (HMM), we can leverage the *Wonham-Shiryayev* filter. Our approach first constructs N parallel filters corresponding to each N individual LLMs. Each filter proposes its best combination of LLMs, given the information that they have access to. Subsequently, the N filter outputs are optimally aggregated to maximize their robust predictive power, and this update is computed efficiently via a closed-form expression, thus generating our ensemble predictor. Our contributions are: **(I)** the MoE-F algorithm – deployable as a plug-and-play filtering harness over any heterogeneous mixture of LLMs or specialized models, **(II)** theoretical optimality guarantees of the proposed filtering-based gating algorithm (via optimality guarantees for its parallel Bayesian filtering and its robust aggregation steps), and **(III)** empirical evaluation and ablative results using state of the art foundational and MoE LLMs on a real-world *Financial Market Movement* task based on streaming news where MoE-F attains a **17% absolute** and **48.5% relative** F1-score improvement over the best performing individual LLM expert. Further, we provide empirical evidence of substantial performance gains with **MoE-F** over specialized models in the long-horizon time-series forecasting domain using electricity-grid datasets.

1 INTRODUCTION

Mixture of expert models (MoEs), such as the seminal Switch Transformers [Fedus et al., 2022], and more recently Mixtral [Jiang et al., 2024], Gemini [Google], DBRX [MosaicAI, 2024] and many others (e.g. [Saad et al., 2023, Chowdhury et al., 2023, Li et al., 2024, Puigcerver et al., 2024]), have taken a center stage in the generative AI zeitgeist since they allow the number of parameters in large language models (LLMs) to be scaled-up while maintaining a roughly constant computational cost.




Figure 1: A visualization of MoE-F’s application as a filtering harness. Depicts seven SOTA LLMs predicting market movement direction over three randomly sampled windows of seven (trading) days across varying market regimes — **left**: *mixed* market with high fluctuations, **middle**: *neutral*, and **right**: *bearish* market. In all sub-plots, the ground-truth (market) trajectory is in black, and the filtered trajectory is depicted in dotted green. All other experts’ (Table 2) predictions are overlaid as scatter-plot points. No values for non-trading days.

This is due to the sparse activation strategy employed by MoEs, wherein several offline experts are banked, and a gating network routes each input to a small subset of expert models when generating a prediction [Zhou et al., 2022]. Thus, only a few experts must be loaded into active memory at any given time, to generate a prediction from any novel input.

Currently, however, most MoE pipelines are designed for static tasks, i.e. where the gating mechanism is *constant-in-time*, tailored for tasks where the input signal can reasonably be expected to remain unchanged as time passes. This is, however, not compatible with most time series prediction paradigms, where the structure of inputs (fed into the LLM) evolves dynamically (often stochastically) in time. Such settings appear in a plethora of modelling fields; e.g. when inputs follow a *stochastic differential equation* (SDE) as in physics [Mao, 2007] or finance [Sharp, 1990]. In decision science [Feinberg & Schwartz, 2012] inputs are often assumed to follow a Markov process, or evolve according to an ordinary differential equation as in most reservoir computing applications [Jaeger, 2002].

This paper addresses this gap by considering the case where the input signal x is a d -dimensional smooth path and the target process Y is a continuous-time D -dimensional stochastic process. We are given N auto-regressive, causal pre-trained expert models, $f^{(1)}, \dots, f^{(N)} : \bigcup_{t \geq 0} C([0 : t], \mathbb{R}^d) \rightarrow \mathbb{R}$ which map input paths such as x to one-dimensional predictions in time such that their predictions do not depend on future states of x or Y when predicting at any time $t \geq 0$.

Instead of treating the target as being static we allow it to evolve dynamically in time. We assume that there is a *Hidden Markov process* w dictating which expert best approximates Y , up to some Brownian measurement noise W ; thus, we postulate that Y evolves according to the stochastic differential equation (SDE) with stochastic drift given by the equation (1):

$$Y_t = Y_0 + \underbrace{\int_0^t w_s^\top F(x_{[0,s]}) ds}_{\text{Best Expert Estimate}} + \underbrace{\int_0^t dW_s}_{\text{Idiosyncratic Residual Noise}}, \quad (1)$$

where the Markov process w randomly masks *all but one* expert at any given time and concatenates the experts $F(x_{[0:t]}) \stackrel{\text{def.}}{=} (f^{(n)}(x_{[0:t]}))_{n=1}^N$. The first term in equation (1), $\int_0^t w_s^\top F(x_{[0,s]}) ds$, represents the true best sparse approximation of Y — i.e. the maximally sparse “single expert” — by the ensemble of experts F . The second term, $\int_0^t dW_s$, is an additive Gaussian noise with mean 0 and variance t .

The key challenge is that we cannot directly observe which expert has been masked by w . Thus, w acts as a *unobservable signal* which we indirectly observe through our *measurements* of each expert’s running performance (process) $\ell^{(n)} \stackrel{\text{def.}}{=} (\ell_t^{(n)})_{t \geq 0}$, where $\ell_t^{(n)}$ is the performance at time $t \geq 0$ of the n^{th} model in our ensemble as measured by a loss-function $\ell : \mathbb{R} \times \mathbb{R} \rightarrow \mathbb{R}$. This *online mixture of experts problem* is a two-fold problem which can be solved by our proposed **MoE-F** procedure.

Contributions. We construct an online gating mechanism (Algorithm 1) for an online mixture of expert (LLM) models for time-series prediction tasks. Using tools from stochastic calculus and stochastic filtering theory, we prove the optimality of our online gating mechanism’s first parallel Bayesian estimation stage (Theorem 1). Using tools from the theory of Markov chains and from Gibbs-measures we demonstrate the optimality of the robust aggregation phase (Theorem 2).

Outline. Section §2 covers the necessary background, including our probabilistic framework and continuous-time Markov chains theory. Section §3 explicates the **MoE-F** algorithm. Section §4 provides theoretical guarantees for the two phases of **MoE-F** algorithm, with proofs in the appendix. Section §5 demonstrates the large-scale application of our algorithm on real-world online classification and regression tasks. For classification, we evaluate the online prediction of financial market movements using the NIFTY dataset [Saqr et al., 2024] and concurrent SOTA LLM experts. For regression, we showcase the filter’s utility in long-term time-series forecasting (LTSF) using the ETTh1, ETTh2 [Zhou et al., 2021] datasets with concurrent specialized LTSF models.

2 PRELIMINARIES

Notations for Markov Chains Matrices. For each $N \in \mathbb{N}_+$, we use \mathcal{P}_N to denote the set of $N \times N$ row-stochastic matrices; i.e. $P \in \mathcal{P}_P$ if each row of P is a vector in $[0, 1]^N$ whose entries sum to

1. We use \mathcal{P}_N^U to denote the set of “uniform row-stochastic matrices”, meaning the set of $P \in \mathcal{P}_N$ with identical rows. For each such N , we use \mathcal{Q}_N to denote the set of $N \times N$ Markov Q /intensity matrices; that is, $Q \in \mathcal{Q}_N$ if $Q_{n,m} \geq 0$ whenever $n \neq m$, for $n, m = 1, \dots, N$ and the rows of Q sum to 0. For any such Q , the matrix exponential $\exp(tQ)$ is a row-stochastic matrix for every $t \geq 0$. The ℓ^∞ norm of an $N \times M$ matrix X will be denoted by $\|X\|_\infty \stackrel{\text{def.}}{=} \max_{\substack{n=1,\dots,N \\ m=1,\dots,M}} |X_{n,m}|$.

Probability Theory. Let $x : [0, \infty) \rightarrow \mathbb{R}^d$ be a continuously differentiable path, and consider a complete filtered probability space $(\Omega, \mathcal{F}, \mathbb{P} \stackrel{\text{def.}}{=} (\mathcal{F}_t)_{t \geq 0}, \mathbb{P})$ with right-continuous filtration \mathbb{F} taking values in \mathbb{R}^D and supporting a 1-dimensional Brownian motion $W \stackrel{\text{def.}}{=} (W_t)_{t \geq 0}$. We want to predict an 1-dimensional *target (stochastic) process* $Y \stackrel{\text{def.}}{=} (Y_t)_{t \geq 0}$ using our MoE models F , as described in § 1. Assume $Y \cdot$ evolves according to the dynamics in Equation equation (1). The process w is assumed to be a hidden Markov process, taking values in the standard basis $\{e_n\}_{n=1}^N$ of \mathbb{R}^N . Its evolution is governed by the intensity (or Q) matrix $Q : [0, \infty) \rightarrow \mathbb{R}^{N \times N}$, which describes the *rate at which the transition probabilities* of the Markov chain w change.

Formally, for $i, j = 1, \dots, N$ and $t, \Delta > 0$ its $(i, j)^{\text{th}}$ entry $Q_t^{i,j} \stackrel{\text{def.}}{=} (Q_t)_{i,j}$ is determined by

$$|\mathbb{P}(w_{t+\Delta} = e_i | w_t = e_j) - I_{i=j} - \Delta \cdot Q_t^{i,j}| \in o(\Delta).$$

We provide additional details on stochastic filtering and matrix operations in Appendix D, that are not required to formulate our main guarantee (Theorem 1) but are included for completeness of proofs.

3 THE MOE FILTERING (MOE-F) ALGORITHM

Our MoE-F procedure (Algorithm 1) summarized in Figure 2 operates in two steps, both of which are efficiently computable due to closed-form expressions.




Figure 2: **MoE-F Mechanism:** conceptual depiction of an input signal x evolving in \mathbb{R}^d with N experts (π) .

In the first phase of our algorithm, we solve N distinct stochastic filtering problems in parallel. Each n^{th} expert provides an optimal Bayesian prediction \hat{Y}_t^n of the Y_t in equation (1) based on their running performance $\ell_t^{(n)}$ up to the current time $t \geq 0$. Additionally, each expert generates a *ranking* $\pi_t^{(n)}$ reflecting the reliability of all experts’ performance, including its own, up to that point. The optimality of this update is guaranteed by Theorem 1.

Next, these optimal Bayesian predictions from each expert is robustly aggregated by a central module. This module first computes a robust version π by aggregating the reliability scores of each expert $\{\pi_t^{(n)}\}_{n=1}^N$. Using this aggregate, robust π , it then computes a robust ensemble prediction: $\sum_{n=1}^N \pi_t^{(n)} \hat{Y}_t^{(n)}$ for the target Y_t . Finally, the dynamics of the hidden Markov chain w in equation (1), encoded by its so-called Q /intensity matrix, are re-estimated in a robust fashion using the running performance of each of the N experts up until the current time $t \geq 0$. The optimality of this robust aggregation step is provided by Theorem 2.

Loss functions. In this paper, we consider either the binary cross entropy (BCE) or mean-squared error (MSE) as loss functions. These are respectively defined by

$$\ell(\hat{y}, y) \stackrel{\text{def.}}{=} \begin{cases} y \log(\hat{y}) + (1 - y) \log(1 - \hat{y}), & \text{BCE,} \\ |y - \hat{y}|^2, & \text{MSE,} \end{cases}$$

where y, \hat{y} belong to \mathbb{R} in the regression case and to $[0, 1]$ in the classification case. Though the setting in equation (1) directly applies to unbounded targets, like in regression, one can also use it

in classification by simply taking Y_t to be the logits (inverse logistic transform) of the classification probabilities. Since the logistic function is a bi-measurable bijection, the filtration generated by the logits or the classification probability processes are equal; thus, the filter does not change.

Helper Functions. For a concise presentation of our MoE-F algorithm (Algorithm 1), we now introduce a few helper functions: A , \bar{A} , B , F . Intuitively, the first two helper functions, A_t and \bar{A}_t compute the gradient and average the gradient of the n^{th} expert's ($\pi^{(n)}$) prediction of the target path y_t up to time t , accounting for the sensitivity of the n^{th} expert to changes in the input path at time t . Here, the averaging is taken uniformly over which “latent expert” is truly active. We rely on the time-derivative of the loss function evaluated at the n^{th} expert's model, which is given in closed-form as:

$$A_t^{(n)}(w, y_t) \stackrel{\text{def.}}{=} \begin{cases} -\frac{(y_t - f^{(n)}(x_{[0:t]})) \Delta f^{(n)}(x_{[0:t]})}{(1 - f^{(n)}(x_{[0:t]})) f^{(n)}(x_{[0:t]})} - \log\left(\frac{f^{(n)}(x_{[0:t]})}{1 - f^{(n)}(x_{[0:t]})}\right) [w_t^\top F(x_{[0:t]})], & \text{if } \ell \text{ is BCE,} \\ 2(y_t - f^{(n)}(x_{[0:t]})) (w_t^\top F(x_{[0:t]}) - \Delta f^{(n)}(x_{[0:t]}) + 1), & \text{if } \ell \text{ is MSE.} \end{cases} \quad (2)$$

We will also use the concatenated and averaged gradients of the loss of each expert, denoted respectively by A_t and \bar{A}_t , and are defined as:

$$A_t(w, Y_t) \stackrel{\text{def.}}{=} \left(A_t^{(n)}(w, Y_t) \right)_{1 \leq n \leq N} \quad \text{and} \quad \bar{A}_t^{(n)}(\pi^{(n)}, y_t) \stackrel{\text{def.}}{=} \sum_{i=1}^N A_t^{(n)}(e_i, y_t) \pi^{(n:i)}, \quad (3)$$

where the sensitivity of the n^{th} expert at time t to changes in the input path x is

$$\Delta f^{(n)}(x_{[0:t]}) \stackrel{\text{def.}}{=} \lim_{\epsilon \downarrow 0} \frac{1}{\epsilon} (f^{(n)}(x_{[0:t]}) - f^{(n)}(x_{[0:t-\epsilon]})) \approx f^{(n)}(x_{[0:t]}) - f^{(n)}(x_{[0:t-1]}).$$

Helper function B quantifies the gradient of the loss function (BCE or MSE) of the n^{th} expert's prediction w.r.t. the observed target y_t , ignoring changes in the input path x , and is given by:

$$B_t^{(n)}(y_t) \stackrel{\text{def.}}{=} \begin{cases} -\log\left(\frac{f^{(n)}(x_{[0:t]})}{1 - f^{(n)}(x_{[0:t]})}\right), & \text{if } \ell \text{ is BCE,} \\ 2^{3/2} (y_t - f^{(n)}(x_{[0:t]})), & \text{if } \ell \text{ is MSE.} \end{cases} \quad (4)$$

The helper function F concatenates the N experts $F(x_{[0:t]}) \stackrel{\text{def.}}{=} (f^{(1)}(x_{[0:t]}), \dots, f^{(N)}(x_{[0:t]}))$.

As illustrated by Figure 2, our MoE-F¹ (Algorithm 1) operates in two steps. The first step (lines 3-11) implements N parallel stochastic filters yielding optimal Bayesian predictions of Y_t given the information available in the running loss function of each of the N expert models. The second step (lines 12 – 16) aggregates the N predictions of each expert model in a robust manner, and it performs a bi-level optimization to compute our most robust Markov Q /intensity matrix supporting the running performance of each expert thus far.

Step 1 – Optimal Parallel Filtering. Lines 3-8 of our MoE-F algorithm is simply a time discretization of the stochastic optimal filtering equations in equation (5) according to the standard Euler-Maruyama scheme, see e.g. [Hutzenthaler & Jentzen \[2015\]](#). This can be performed in parallel, with each parallel computing branch corresponding to a single expert. As in most discrete-time filtering implementations, e.g. [Grewal & Andrews \[2014\]](#), [Kim et al. \[2018\]](#), the discretized infinitesimal change in the running loss of the n^{th} expert is given by $d\ell_{[0:t]}^{(n)} \approx \ell_t^{(n)} - \ell_{t-\Delta}^{(n)}$; provided that $t > \Delta > 0$. Thus, the *innovations process* \bar{W} is simply the change in $\ell^{(n)}$ over the time increment $[t - \Delta : t]$ minus $\bar{A}(Y_{[0:t]})$, re-normalized by $B_t(Y_{[0:t]})$. Importantly, this means that it is *computable online from the incoming target process* Y_t . Next, in line 8, each expert (still in parallel) proposes their best estimate $\hat{Y}_t^{(n)}$ for Y_t using their mixture weights, estimated only using their (local) information in their historical loss.

Finally, in line 10, the *reliability* of each expert is measured (still in parallel) by evaluating the loss between the target process Y_t and their best (individual) prediction $\hat{Y}_t^{(n)}$ of it. This reliability metric is summarized by their score s_n of the n^{th} expert.

¹A version of our algorithm, which rolls forward online, is in Appendix A.

Step 2 – Robust Aggregation.

The prediction quality of each expert $\hat{Y}_t^{(n)}$ has been compressed into a score s_n . These scores are used to aggregate the expert predictions into a single prediction \hat{Y}_t of Y_t . This is done using the well-studied Gibbs-aggregation approach with the *softmax* function (since *lower* loss implies *better* score here). Line 13 computes these aggregation weights $\bar{\pi}$; which are then packaged into a uniform row-stochastic matrix whose rows are given by $\bar{\pi}$. With these aggregation weights, our MoE-F algorithm generates a joint predictor in line 14. We associate P to a Markov Q/intensity matrix Q . The matrix logarithm of \bar{P} is a viable candidate for Q , since $\exp(1 \cdot Q)$ would be a valid transition matrix; however, in general, the matrix logarithm of an arbitrary row-stochastic transition matrix is not a valid intensity matrix. Upon regularizing P in line 18 to avoid pathologies, in line 19, we compute the best intensity matrix approximation of its matrix logarithm.

Algorithm 1: MoE-F Algorithm

```

1 Initialize  $\pi, P$ , and  $Q$ ;
2 /* Step 1: Optimal Parallel Filter */
3 For  $n = 1, \dots, N$  in parallel
4   drift  $\leftarrow Q_{t-1}^\top \pi_{t-1}^{(n)}$ ;
5    $\Delta L \leftarrow \ell(f^{(n)}(x_{[0:t-1]}), Y_t) - \ell(f^{(n)}(x_{[0:t-2]}, Y_t))$ ;
6    $\Delta W \leftarrow (\Delta L - \bar{A}_{t-1}(\pi_{t-1}^{(n)}, Y_{[0:t-1]})) / B_{t-1}^{(n)}(Y_t)$ ;
7   diffi  $\leftarrow (\pi^{(n:i)}(A_{t-1}(e_i, Y_{[0:t-1]}) - \bar{A}_{t-1}(\pi_{t-1}^{(n)}, Y_{[0:t-1]}))) / B_{t-1}^{(n)}(Y_t)$ ;
8    $\pi_t^{(n)} \leftarrow \pi_{t-1}^{(n)} + \text{drift} + \text{diff} \Delta W$ ;
9    $\hat{Y}_t^{(n)} \leftarrow (\pi_t^{(n)})^\top F(x_{[0:t]})$ ;
10   $s_n \leftarrow \ell(Y_t, \hat{Y}_t^{(n)})$ ;
11 end
12 /* Step 2: Robust Aggregation */
13  $\bar{\pi} \leftarrow (e^{-\lambda s_n} / (\sum_{i=1}^N e^{-\lambda s_i}))_{n=1}^N$ ;
14  $\hat{Y}_t \stackrel{\text{def}}{=} \bar{\pi}^\top (\hat{Y}_t^{(n)})_{n=1}^N$ ;
15 for  $n = 1, \dots, N$  do
16    $P_{n,\cdot} \leftarrow \bar{\pi}$ 
17 end for
18  $P \leftarrow (1 - \alpha) P + \alpha I_N$ ;
19  $Q \leftarrow \text{ReLU}(\log(P)) - \text{diag}(\bar{I}_N^\top \text{ReLU}(\log(P)))$ ;
20 return MoE-F Prediction  $\hat{Y}_t$ ;

```

4 THEORETICAL GUARANTEES

Our MoE-F algorithm revolves around the following set of *stochastic filtering equations*. Each filtering equation corresponds to the best estimate of a single expert on masking process w , given only the information available in their *running performance*. Interpreting “best estimate” in the L^2 sense, each seeks to predict the conditional distribution of w , given the σ -algebra $\mathcal{F}_t^{(n)} \stackrel{\text{def}}{=} \sigma\{\ell_s^{(n)}\}_{0 \leq s \leq t}$ generated by the running loss process $\ell^{(n)} \stackrel{\text{def}}{=} (\ell(Y_t, \hat{Y}_t^{(n)}))_{t \geq 0}$; i.e.

$$\pi_t^{(n)} \stackrel{\text{def}}{=} (\mathbb{P}(w_t = e_i \mid \mathcal{F}_t^{(n)}))_{i=1}^N.$$

An essential property of our filtering equations are that they provide a *closed-form* recursion for $\pi^{(n)} \stackrel{\text{def}}{=} (\pi_t^{(n)})_{t \geq 0}$ depending only on each of the expert models and on the accumulating observations from the target process Y . This key property is rare in stochastic filtering paradigm, voiding the need for any Monte-Carlo simulation.

4.1 GUARANTEES FOR STEP 1 - ONLINE PARALLEL FILTERING

Our main result comes in two variants, a binary classification and a regression variant. Both versions of our guarantees operate under the following regularity conditions of the path x .

Assumptions 4.1 (Regularity Conditions). *The path $x : [0, \infty) \rightarrow \mathbb{R}^d$ is once continuously differentiable and there is a constant $C > 0$ such that, for each $t \geq 0$ and $i, j = 1, \dots, d$, $(Q_t)_{i,j} \leq C$. The loss function ℓ is either the binary cross entropy loss or the squared-norm loss.*

Theorem 1 (Optimal Optimistic Prior for n^{th} Expert). *Under Assumption 4.1, the best a posteriori estimate of the n^{th} expert, $\pi_t^{(n)}$, satisfies the SDE*

$$\pi_t^{(n:i)} = w_0^i + \int_0^t (Q_s)_i^\top \pi_s^{(n)} ds + \int_0^t \frac{\pi_s^{(n:i)} (A_s(e_i, Y_{[0:s]}) - \bar{A}_s(\pi_s^{(n)}, Y_{[0:s]}))}{B_s(Y_{[0:s]})} d\bar{W}_u^{(n)}, \quad (5)$$

where $(Q_t)_i$ denotes the i^{th} row of the transitions matrix Q_t at time $t \geq 0$, $w_0^i \stackrel{\text{def}}{=} \mathbb{P}(w_0 = e_i)$. The “innovations process” $\bar{W}^{(n)} \stackrel{\text{def}}{=} (\bar{W}_t^{(n)})_{t \geq 0}$ is the following $(\mathbb{P}, \mathcal{F}^n)$ -Brownian motion

$$\bar{W}_s^{(n)} \stackrel{\text{def}}{=} \int_0^s \frac{dL_{[0:u]}^{(n)} - \bar{A}_u(Y_{[0:u]})}{B_u(Y_{[0:u]})} du, \quad (6)$$

and each of the n “running loss processes” $L^{(n)}$ satisfy:

(i) **Classification:** If ℓ is the binary cross entropy loss:

$$dL_{[0:u]}^{(n)} = \frac{(Y_s - f^{(n)}(x_{[0:t]})) \Delta f^{(n)}(x_{[0:t]})}{(1 - f^{(n)}(x_{[0:t]})) f^{(n)}(x_{[0:t]})} + \log\left(\frac{f^{(n)}(x_{[0:t]})}{1 - f^{(n)}(x_{[0:t]})}\right) [w_t^\top F(x_{[0:t]})] dt + \log\left(\frac{f^{(n)}(x_{[0:t]})}{1 - f^{(n)}(x_{[0:t]})}\right) dW_t.$$

(ii) **Regression:** If ℓ is the squared-norm loss

$$dL_{[0:u]}^{(n)} = 2(Y_t - f^{(n)}(x_{[0:t]}))([w_s^\top F(x_{[0:t]})] - \Delta f^{(n)}(x_{[0:t]})) + e^{t \ln(\delta^8)} + 2(Y_t - f^{(n)}(x_{[0:t]})) e^{t \ln(\delta^4)} dW_t.$$

4.2 GUARANTEES FOR STEP 2 - ROBUST AGGREGATION

The following bi-level optimality guarantee justifies the second step of our MoE-F algorithm.

Theorem 2 (Bi-level Robust Updates to the Q -Matrix). *Let $\hat{Y}^{(1)}, \dots, \hat{Y}^{(N)}, Y \in \mathbb{R}$ and $\ell : \mathbb{R}^2 \rightarrow \mathbb{R}$ be Borel measurable. Then $P \stackrel{\text{def}}{=} [(\bar{\pi})_{n=1}^N]^\top$; where $\bar{\pi} \stackrel{\text{def}}{=} \text{Softmin}(\lambda(\ell(Y^{(n)}, Y))_{n=1}^N)$ minimizes*

$$\min_{P \in \mathcal{P}_N^U} \max_{m=1, \dots, N} \underbrace{\sum_{n=1}^N P_{m,n} \ell(\hat{Y}_t^{(n)}, Y_t)}_{\text{Predictive Power of Ensemble}} + \underbrace{\frac{1}{\lambda} \sum_{n=1}^N P_{m,n} \log(w_n/N)}_{\text{Entropic Regularization}}. \quad (\text{Inner})$$

Let $\alpha \in (0, 1)$ then $P^\alpha \stackrel{\text{def}}{=} (1 - \alpha)(\bar{\pi}, \dots, \bar{\pi}) + \alpha I_N$ is a row stochastic matrix and, for $\alpha < 1$ large enough, $\log(P^\alpha)$ is well-defined. Furthermore, $Q \stackrel{\text{def}}{=} \text{ReLU}(\log(P^\alpha))$ is a minimizer of

$$\min_{Q \in \mathcal{Q}} \|Q - \log(P^\alpha)\|_\infty. \quad (\text{Outer})$$

We close our guarantees section by investigating the effect of regularizing the row stochastic matrix P obtained in the inner-level optimization equation (Inner) to ensure its invertibility and the well-posedness of its matrix logarithm. We ask whether the probability distributions defined by the rows of P_t^α (whose state-space is $\{e_n\}_{n=1}^N$) depend continuously on α . Indeed, the next result shows that the KL-divergence of the rows of P_t^α and those of P_t (i.e. $\bar{\pi}$) are necessarily very close when α is small.

Proposition 1 (Stability of Perturbations). *In the setting of Proposition 2, we have that*

$$\max_{i=1, \dots, N} \text{KL}(\bar{\pi} | (P_t^\alpha)_i) \leq 2\alpha \left(-\frac{\log(\pi_{\min})}{1/\pi_{\min} - 1} - \frac{\log((1 - \alpha)\pi_{\min})}{1/((1 - \alpha)\pi_{\min}) - 1} \right)$$

where $\pi_{\min} = \min_{i=1, \dots, N} \bar{\pi}(> 0)$ and $(P_t^\alpha)_i$ denotes the i^{th} row of P_t^α .

5 EXPERIMENTS

5.1 FINANCIAL MARKET MOVEMENT (FMM) TASK ON NIFTY USING MoE-F

We show the efficacy of our proposed MoE-F algorithm by using various SOTA class large language models on the *financial market movement* prediction task.

Task. The Financial Market Movement (FMM) prediction task for experts’ evaluation can be defined as a ternary or binary market movement direction *classification task* among the labels’ set C : { ‘*Fall*’, ‘*Neutral*’, ‘*Rise*’ } conditioned on history (or, expert memory) of window size H (i.e., on the time window $[t - H + 1, t]$) – similar to the auto-regressive or causal generative language model (causal LM) training objective.

Experts. We consider a diverse list of SOTA general purpose instruction-tuned LLMs as experts for the experiments on our proposed MoE-F algorithm. For single LLM experts, we use Meta’s open-weights models: Llama-2 (7B, 70B), Llama-3 (8B, 70B) [Touvron et al., 2023]. For mixture of experts

Estée Lauder **Cuts** Profit Goals as **Coronavirus Slows** Travel Sales | Russia **Blocks** OPEC Response to **Coronavirus** | Yum China Shows **Coronavirus Outbreak** Curbs China's Consumption | Hedge-Fund Billionaire's **Deal** for Mets **Collapses** | Fed's Quarles Calls Current Stance on **Interest Rates** **Appropriate** | Pinterest's Revenue **Topped** \$1 Billion in 2019 | NYSE Owner **Abandons** Potential eBay **Deal** | T-Mobile Projects More **Customer Gains** in 2020 | Aurora Cannabis **Chief Executive** To **Depart** Amid **Layoffs** | Meredith **Shares Rally** as Publishing Giant Digests Time Inc. | CBD Producer GenCanna **Files for Bankruptcy** | **Risky** Corporate **Debt** to Take Center Stage in 2020 **Stress Tests** | Tyson Feels Weight of **Lower Poultry Prices** | China **Tariff Relief** Boosts Stock Market | Shale Gas Swamps Asia, **Pushing LNG Prices to Record Lows** | FAA **Flags** Warning-Light **Problem** with 737 MAX | Juul **Raises \$700 Million** From Investors | **Shares** of NYSE Owner **Slide** on Fresh eBay **Deal Jitters** | Deutsche Bank **Shares Rally** on Capital Group Stake | Kellogg **Low**ers **Expectations** for 2020 | New York Times Posts **Strong Subscription Growth** | Mnuchin Says U.S. 2020 **Growth to Be Less Than 3%** Due to Boeing | ArcelorMittal Posts **Earnings Beat** Despite **Tough Times** for **Steelmakers** | Canadian **Antitrust Officials Probe** Farm Giants | Zantac **Recall Weighs** on Sanofi's **Earnings** | News Corp **Posts Lower Profit**, Revenue |

Figure 3: Example snapshot of the ‘news’ component on 2020-02-06, at the upstart of the global coronavirus epidemic (the text colors here convey **negative** and **positive** sentiments). An expert policy, π_{LM} ’s prompt is composed of a task instruction as prefix, concatenated with the market context, and this news value concatenated: $s.t. x_p \leftarrow (x_{prefix}; x_{context}; x_{news})$.

(MoE) architecture models, we use SOTA open-weights models: Mixtral (8x7B) [Jiang et al., 2024] – which is a mixture of 8 Mistral (7B) [Jiang et al., 2023] models – and DBRX-Instruct [MosaicAI, 2024] with 132B total parameters and a mixture of 16 (fine-grained, smaller, 65x more combinations of) experts. For evaluation, we deployed these open-weights models as vLLM [Kwon et al., 2023] OpenAI compatible API endpoints and ran the dataset queries against them. We use API/model configurations like *guided-choice* and *max-tokens* to format class label converged expert responses alongside specific prompt instructions. We use the closed-source latest variants of the GPT-4 [OpenAI, 2023] class of models: GPT4o, using the OpenAI API. These experts are leading foundation models on current performance benchmarks on language understanding (MMLU [Hendrycks et al., 2021]), programming (HumanEval [Chen et al., 2021]), math (GSM8K [Cobbe et al., 2021]) tasks and other concurrent LLM benchmarks [Song et al., 2023, Liang et al., 2022].

Datasets. For real-world experiments on the defined FMM task, we use the US equities market movement (NYSE ticker: \$SPY) dataset NIFTY (\mathcal{D}_{LM}) [Saqr et al., 2024]. The test split statistics which we used are recorded in Table 1.

Each sample of the \mathcal{D}_{LM} contains high-quality, processed (one-turn) conversational queries for an expert instruction fine-tuned LLM, where a query, x_q , comprises of a prompt x_p^t and a response x_r^t , i.e., $x_q^t = (x_p^t; x_r^t)$ corresponding to a day (or, time-step) t .

Table 1: Statistics of NIFTY test split

Category	Statistics
Number of days (T) / increment (Δt)	317 / 1
Label support (Fall / Neutral / Rise)	73 / 143 / 101
Date range (start to end)	2019-02-13 to 2020-09-21

For evaluation, at each time step t , an expert LLM is prompted (x_p^t) to predict the market movement the following day (i.e., $t + 1$), based on the market’s current contextual information (relevant financial news headlines and the market’s financial numerics – like the standard OHLCV and common technical indicators – from past few days capturing trends). Fig. 3 depicts a snapshot of an expert prompt x_p^t for elucidation. Please see Fig. 6 in Appendix §C.1 for details.

For our ablative experiments, we utilise three additional datasets, namely StockNet aka. ACL18, BigData22 and CIKM datasets [Xu & Cohen, 2018, Soun et al., 2022, Wu et al., 2018]. These datasets have similar overarching (FMM) task design, but the prompted contextual information (e.g. social media opinions) and targeted asset classes (e.g. individual stock tickers, or price of gold) differ. We delegate the full details of these datasets in C.3 of Appendix §C Datasets.




Figure 4: Heatmap of expert weights and subsequent rankings for the sampled windows in Fig. 1.

Table 2: Results of applying **MoE-F** on seven SOTA experts on the NIFTY (*test split*). All values are mean of 3 (random) runs except GPT-4o. Best value in each metric row is in **bold**. Confusion matrices in appendix Fig. 7

Metrics \uparrow	LLM Experts							Experts Filter
	Llama-2 7b-chat	Llama-2 70b-chat	Llama-3 8B-Instruct	Llama-3 70B-Instruct	Mixtral-8x7B Instruct-v0.1	DBRX Instruct	OpenAI GPT-4o	MoE-F (ours)
F1	0.22	0.33	0.35	0.20	0.34	0.34	0.34	0.52
Acc	0.27	0.37	0.39	0.30	0.33	0.34	0.37	0.57
Precision	0.35	0.33	0.31	0.32	0.36	0.36	0.33	0.61
Recall	0.27	0.37	0.39	0.30	0.33	0.34	0.37	0.57

5.1.1 RESULTS: **MoE-F** ON MIXTURE OF (MIXTURE OF) EXPERTS

Table 2 show the results of running **MoE-F** on the collection of SOTA experts. While none of these remarkable experts out-performs others exceedingly or has an overall outstanding performance on the FMM task, filtering the expert decisions using **MoE-F** yields remarkable performance both in terms of overall task results and gains — with **17% real and 48.5% relative F1** measure **improvement** over the next best performing expert values ($\approx 35\%$). Fig. 1 depicts our **MoE-F** mechanism’s decisions trajectory overlayed on the true market movement and expert decision trajectories.

Ablations. We use the Llama [Touvron et al., 2023] instruction-tuned, open-weights class of experts — specifically, Llama-2 7B, Llama-3 8B variants — to further analyse **MoE-F** at work. For ablation experiments, we create 4 additional expert variants (as standard LoRA [Hu et al., 2021] LLM adapters) by fine-tuning the base expert with the 4 stock movement datasets, namely: {nifty, acl18, cikm18, bigdata22}, and run them against the same task and evaluation test split from before. Table 3 shows the combined results of Llama 2 and 3 along with the 4 expert variants.

Table 3: Performance of Llama-2-7b-chat and Llama-3-8B-Instruct base models with (SFT LoRA adapter) variants on the NIFTY Stock Price Movement Prediction Task (*test split*).

Metrics \uparrow	Llama-2-7b-chat						Llama-3-8B-Instruct					
	Base	+nifty	+acl18	+bigdata22	+cikm18	MoE-F	Base	+nifty	+acl18	+bigdata22	+cikm18	MoE-F
F1 Score	0.22	0.28	0.20	0.29	0.27	0.43	0.34	0.36	0.19	0.23	0.24	0.43
Accuracy	0.27	0.45	0.25	0.29	0.27	0.45	0.39	0.41	0.26	0.26	0.28	0.47
Precision	0.35	0.20	0.36	0.32	0.31	0.44	0.31	0.56	0.44	0.28	0.31	0.48
Recall	0.27	0.45	0.25	0.29	0.27	0.45	0.39	0.41	0.26	0.26	0.28	0.47

Discussions. As before, using **MoE-F** delivers superior results for each of the two cases. However, we notice that the overall performance on the FMM task is lower than from earlier: 43% compared to 52% (Table 2). This aligns with our proposed theoretical performance guarantee relative to experts. Increasing the quality and quantity of experts with specialized capabilities improves **MoE-F** results. Intuitively, in presence of a vastly superior expert, **MoE-F** will levy higher weight on it for its decisions. If any under-performing (specialized) expert does better over a certain time-window (say during bearish market regime), it percolates up the decision weighting map accordingly.

Decomposing Expert Performance by Class Labels. Table 4 tabulates experts’ performance by each of the three movement labels detailing another insight and verification of **MoE-F**’s mechanism at work. While some experts have overall equivalent performance (e.g. the F1 score of ‘+nifty’ and ‘+bigdata22’ adapters), examining their label-specific results show these experts performance emanates from different decisions. To elucidate, the Llama-2 base expert was far better in predicting market ‘Fall’ than Llama-3, however, the latter handily outperforms when predicting ‘Rise’. Similarly, we also see some experts are degenerate for some label predictions, like the ‘+nifty’ expert that only tends to predict ‘Neutral’ (the imbalanced class label with highest support).

5.2 TIME-SERIES FORECASTING (TSF) USING **MoE-F**

The mainstream practice of using the classic Mean Squared Error (MSE) in the TSF field makes problems in the domain a suitable test-bed for our regression based theorem (Theorem 4).

Table 4: Llama-2, 3 experts and MoE-F’s performance decomposition by class labels on NIFTY test split.

Expert	Fall (support: 73)			Neutral (support: 143)			Rise (support: 101)		
	F1	Precision	Recall	F1	Precision	Recall	F1	Precision	Recall
Llama-2-7b-chat	0.35	0.23	0.75	0.19	0.40	0.13	0.17	0.34	0.11
nifty	<i>0.00</i>	<i>0.00</i>	<i>0.00</i>	0.62	0.45	1.00	<i>0.00</i>	<i>0.00</i>	<i>0.00</i>
acl18	0.28	0.20	0.45	0.08	0.46	0.04	0.32	0.28	0.39
cikm18	0.21	0.18	0.25	0.34	0.43	0.29	0.29	0.26	0.32
bigdata22	0.21	0.19	0.23	0.31	0.42	0.24	0.31	0.26	0.38
MoE-F	0.30	0.27	0.33	0.60	0.54	0.66	0.30	0.43	0.23
Llama-3-8B-Instruct	<i>0.00</i>	<i>0.00</i>	<i>0.00</i>	0.49	0.46	0.51	0.38	0.31	0.49
nifty	<i>0.00</i>	<i>0.00</i>	<i>0.00</i>	0.48	0.46	0.51	0.42	0.35	0.54
acl18	0.15	0.17	0.14	0.04	0.30	0.02	0.41	0.29	0.70
cikm18	0.13	0.16	0.11	0.27	0.42	0.20	0.39	0.29	0.58
bigdata22	0.14	0.17	0.12	0.20	0.38	0.13	0.40	0.29	0.62
MoE-F	0.12	0.45	0.07	0.56	0.56	0.57	0.48	0.39	0.62

Task. Letting L represent the length of some historical observation window, and H the prediction horizon, a generic TSF problem can be formalized as

$$\bar{x}_{t+1:t+H} = f(x_{t-L+1:t}),$$

where $x_{t-L+1:t} \in \mathbb{R}^{L \times C}$ and $\bar{x}_{t+1:t+H} \in \mathbb{R}^{H \times C}$. Here, C is the number of distinct features or channels of an agent’s observation; the (MSE) loss measures the discrepancy between the predicted values $\bar{x}_{t+1:t+H}^{(i)}$ and the ground truth $y_{t+1:t+H}^{(i)}$ as $\mathcal{L} = \frac{1}{C} \sum_{i=1}^C \|y_{t+1:t+H}^{(i)} - \bar{x}_{t+1:t+H}^{(i)}\|_2^2$.

5.2.1 EXPERIMENTAL SETUP

Experts and Datasets. Table 5 presents a few, among a plethora of concurrent models in the busy TSF research area that come in a variety of flavours, from specialized TSF tasks only models like N-HITS, N-BEATS [Challu et al., 2023, Oreshkin et al., 2019] to customized or fine-tuned LLMs like LLMTime [Gruver et al., 2024]. Immediately recent works in both these categories – like the SAMFormer [Ilbert et al., 2024] and MoiRai [Woo et al., 2024] – pushes the envelope on ideas and performance further. The goal of the TSF experiments here is not to achieve superior performance, but to show the application of our online MoE-F harness over any N arbitrary expert models and effectively combine their strengths in an inexpensive, heuristic manner. Thus, for applying our filter, we chose three recent, well-adopted models with standardized implementation: DLinear, PatchTST, SparseTSF [Zeng et al., 2023, Nie et al., 2022, Lin et al., 2024] – using the author provided code from the latter to replicate the models’ predictions over varying horizon H .

Similarly, we picked the most common and widely adopted datasets among a slew of mainstream TSF datasets (e.g. Electricity [Dua & Graff, 2017], Traffic [California Department of Transportation, 2023]) from concurrent literature in the LTSF domain: ETTh1&ETTh2 [Zhou et al., 2021]. Fig. 5 presents the summary of these TSF datasets.

Figure 5: Electricity Transformer Datasets.

Datasets	ETTh1 & ETTh2
Channels	7
Frequency	hourly
Timesteps	17,420

Results. Table 5 presents MoE-F applied to a set of concurrent TSF experts. While our replicated performances of the bottom three experts, used for filtering, are lower than published results, the filtered predictions using MoE-F gains strong performance improvement using only three experts as-is and without any hyperparameters tuning (like optimal λ , α values).

6 RELATED WORK

Closed-Form Finite Dimensional Filters. Our proposed MoE-F utilizes finite-dimensional closed-form filtering equations via the Wonham-Shiryayev filter Wonham [1964], Širjaev [1965]. However, such closed-form filtering equations rarely exist as the general stochastic filtering theory is infinite-dimensional Stratonovich [1959; 1960], Zakai [1969] and thus computationally intractable in practice.

Table 5: MSE results of multivariate *Long-term Time-series Forecasting* comparing contemporary SOTA expert models and applying our proposed filtering harness MoE-F. Best results are highlighted in **bold**. Second best results underlined. Replicated performance results are presented using *4 decimal places*. Other performances quoted from respective papers. Only the bottom three models were used to generate MoE-F results.

Dataset	ETTh1				ETTh2			
Horizon	96	192	336	720	96	192	336	720
Informer [Zhou et al., 2021]	0.865	1.008	1.107	1.181	3.755	5.602	4.721	3.647
Autoformer [Wu et al., 2021]	0.449	0.500	0.521	0.514	0.645	0.788	0.957	0.792
Pyraformer [Liu et al., 2021]	0.664	0.790	0.891	0.963	0.645	0.788	0.907	0.963
FITS (2024) [Xu et al., 2024]	0.375	<u>0.408</u>	<u>0.429</u>	0.427	0.274	<u>0.333</u>	0.340	0.374
PatchTST [Nie et al., 2022]	0.6897	0.6676	0.5997	0.6873	0.4273	0.4964	2.6450	0.4324
DLinear [Zeng et al., 2023]	0.3788	0.4212	0.4520	0.5230	0.2908	0.4091	0.5320	0.7430
SparseTSF [Lin et al., 2024]	<u>0.3631</u>	0.4000	0.4346	<u>0.4238</u>	0.2945	0.3399	<u>0.3595</u>	<u>0.3831</u>
MoE-F (ours)	0.3630	0.4165	0.4178	0.4157	0.2911	0.3294	0.4840	0.3917

Other than the Wonham-Shiryayev filter, there is only a handful of such finite-dimensional filters with closed-form recursions. E.g. the Kalman-Bucy filter Kalman [1960], Bucy & Joseph [2005] or the Beneš filter Beneš [1981], both of which require highly rigid assumptions. Otherwise, one does typically have access to interacting systems of particles, so-called particle filters Djuric et al. [2003], Del Moral [2013], which can often approximate optimal filters but which are computationally intractable in high dimensions. In our case N can be large and thus these latter techniques may not be suitable for other MoE-F-type approaches to online mixture models.

Bayesian Mixture of Experts. In the context of mixtures of experts, or large foundation models, one typically relies on a gating mechanism, or a learned routing among expert models Jacobs et al. [1991], Jordan & Jacobs [1994]. These gating mechanisms are often using a *static* Bayesian optimization approach via Gibbs posterior mixtures; e.g. Alquier [2008], Alquier et al. [2016], Andrychowicz et al. [2016], Rothfuss et al. [2021; 2023]. What the gating mechanisms involved in these approaches have in common is that they all are *static* in the sense that they do not learn in an online manner from dynamically arriving inputs and feedback. In contrast to these, our MoE-F model is an online/dynamic Bayesian optimization algorithm which dynamically generates posteriors using a different (L^2) notion of optimality rather than the extremal version used to define (static) Gibbs posterior mixtures.

Learned Routing vs. Ours. Most concurrent MoE of LLMs build on the idea of trainable/learned experts mixing, and use a routing layer Zhou et al. [2022] as introduced by Jacobs et al. [1991], Jordan & Jacobs [1994] in the 90s. Their efficacy was later shown in Shazeer et al. [2017] and numerous models and variants of this core idea have been successfully showcased in the current LLM context Fedus et al. [2022], Jiang et al. [2024], Dai et al. [2024], Gale et al. [2023]. Our work is orthogonal to this approach since this framework has no dependency on learned routing. Our online heuristic approach alongside with formal optimality guarantee allows online adaptation like adding, removing or hot-swapping experts on the fly. Further, the adaptive online ranking of top-experts implicitly subsumes underlying (environmental) regime adaptation as the expert ranking reflects the top-performing experts given the current time step. In case of a sharp shift in the underlying environment, the experts specialized for the shifted environment climbs in ranking ahead of the underperforming (previously better) experts.

7 CONCLUSION

We introduced a stochastic filtering-based gating mechanism for dynamically adapting mixing procedures to incoming data, unlike static classical MoE methods. Our algorithm satisfies optimality guarantees (Theorem 1) and robustness guarantees (Theorem 2) and effectively performs TSF in two orthogonal settings.

Limitations & Future Work. Our numerical experiments focused solely on LLM experts, excluding random structures like neural SDEs Kidger et al. [2021], potentially missing technical market movements and stochastic effects. Future work will integrate both LLM and SDE-based experts to capture news-driven and technical market dynamics.

ETHICS STATEMENT

This research on stochastic filtering-based gating mechanisms for online MoE foundation models presents significant advancements, with broad plausible societal implications. Specifically, this technology can enhance adaptability in scientific predictions using complex dynamic systems, which is important in various disciplines including (but not limited to) financial markets, healthcare, and climate science for example. The ability to integrate multiple expert models dynamically can lead to more informed decision-making that is less constrained than conventional methods. However, as this technology is further refined, it will be important to prevent misuse in situations where advantage may be unfairly balanced, as in high-frequency trading. This technology should be used in transparent, accountable, and regularly audited frameworks to ensure its responsible deployment.

We note that access to highly-capable pre-trained foundation models is publicly available through open-weight LLM repositories, such as HuggingFace. The MoE-F filtering harness can be utilized to enhance the performance of many downstream tasks using an ensemble of off-the-shelf expert models, without the need for costly fine-tuning. However, there is a growing concern about the lack of transparency concerning the training data used in these models. Consequently, any inherent biases in the experts could be exacerbated by the filtering process. For example, a biased mortgage risk evaluating model can persistently rank higher due to predicting a majority/minority label.

REPRODUCIBILITY STATEMENT

In our commitment to advancing open science and fostering transparency, we strive to make all aspects of our research fully accessible to the broader scientific community. To ensure the reproducibility of our work, we have included relevant datasets, detailed results, and links to code repositories (or anonymized links, where appropriate) as supplementary materials. These resources have been provided to facilitate the replication and verification of our findings, in alignment with the principles of the double-blind review process.²

²Supplementary materials, including test results and scripts to replicate the results presented here is available at: <https://anonymous.4open.science/r/moe-f>.

REFERENCES

- Pierre Alquier. Pac-bayesian bounds for randomized empirical risk minimizers. *Mathematical Methods of Statistics*, 17:279–304, 2008.
- Pierre Alquier, James Ridgway, and Nicolas Chopin. On the properties of variational approximations of gibbs posteriors. *Journal of Machine Learning Research*, 17(236):1–41, 2016.
- Marcin Andrychowicz, Misha Denil, Sergio Gomez, Matthew W Hoffman, David Pfau, Tom Schaul, Brendan Shillingford, and Nando De Freitas. Learning to learn by gradient descent by gradient descent. *Advances in neural information processing systems*, 29, 2016.
- M. S. Bartlett. An inverse matrix adjustment arising in discriminant analysis. *Ann. Math. Statistics*, 22:107–111, 1951. ISSN 0003-4851. doi: 10.1214/aoms/1177729698. URL <https://doi.org/10.1214/aoms/1177729698>.
- Václav E Beneš. Exact finite-dimensional filters for certain diffusions with nonlinear drift. *Stochastics*, 5(1-2):65–92, 1981.
- Olivier Binette. A note on reverse Pinsker inequalities. *IEEE Trans. Inform. Theory*, 65(7):4094–4096, 2019. ISSN 0018-9448,1557-9654. doi: 10.1109/TIT.2019.2896192. URL <https://doi.org/10.1109/TIT.2019.2896192>.
- Richard S Bucy and Peter D Joseph. *Filtering for stochastic processes with applications to guidance*, volume 326. American Mathematical Soc., 2005.
- California Department of Transportation. Caltrans Performance Measurement System (PeMS). <https://pems.dot.ca.gov/>, 2023. Accessed: 2023-10-01.
- Cristian Challu, Kin G Olivares, Boris N Oreshkin, Federico Garza Ramirez, Max Mergenthaler Canseco, and Artur Dubrawski. Nhits: Neural hierarchical interpolation for time series forecasting. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 37, pp. 6989–6997, 2023.
- Mark Chen, Jerry Tworek, Heewoo Jun, Qiming Yuan, Henrique Ponde de Oliveira Pinto, Jared Kaplan, Harri Edwards, Yuri Burda, Nicholas Joseph, Greg Brockman, et al. Evaluating large language models trained on code. *arXiv preprint arXiv:2107.03374*, 2021.
- Mohammed Nowaz Rabbani Chowdhury, Shuai Zhang, Meng Wang, Sijia Liu, and Pin-Yu Chen. Patch-level routing in mixture-of-experts is provably sample-efficient for convolutional neural networks. In *International Conference on Machine Learning*, pp. 6074–6114. PMLR, 2023.
- Karl Cobbe, Vineet Kosaraju, Mohammad Bavarian, Mark Chen, Heewoo Jun, Lukasz Kaiser, Matthias Plappert, Jerry Tworek, Jacob Hilton, Reiichiro Nakano, et al. Training verifiers to solve math word problems. *arXiv preprint arXiv:2110.14168*, 2021.
- Samuel N. Cohen and Robert J. Elliott. *Stochastic calculus and applications*. Probability and its Applications. Springer, Cham, second edition, 2015. ISBN 978-1-4939-2866-8; 978-1-4939-2867-5. doi: 10.1007/978-1-4939-2867-5. URL <https://doi.org/10.1007/978-1-4939-2867-5>.
- Damai Dai, Chengqi Deng, Chenggang Zhao, RX Xu, Huazuo Gao, Deli Chen, Jiashi Li, Wangding Zeng, Xingkai Yu, Y Wu, et al. Deepseekmoe: Towards ultimate expert specialization in mixture-of-experts language models. *arXiv preprint arXiv:2401.06066*, 2024.
- E. B. Davies. Embeddable Markov matrices. *Electron. J. Probab.*, 15:no. 47, 1474–1486, 2010. ISSN 1083-6489. doi: 10.1214/EJP.v15-733. URL <https://doi.org/10.1214/EJP.v15-733>.
- Pierre Del Moral. *Mean field simulation for Monte Carlo integration*, volume 126 of *Monographs on Statistics and Applied Probability*. CRC Press, Boca Raton, FL, 2013. ISBN 978-1-4665-0405-9.
- Petar M Djuric, Jayesh H Kotecha, Jianqui Zhang, Yufei Huang, Tadesse Ghirmay, Mónica F Bugallo, and Joaquin Miguez. Particle filtering. *IEEE signal processing magazine*, 20(5):19–38, 2003.

- Dheeru Dua and Casey Graff. UCI machine learning repository. <https://archive.ics.uci.edu/ml/datasets/ElectricityLoadDiagrams20112014>, 2017.
- Nelson Dunford and Jacob T. Schwartz. *Linear Operators. I. General Theory*, volume Vol. 7 of *Pure and Applied Mathematics*. Interscience Publishers, Inc., New York; Interscience Publishers Ltd., London, 1958. With the assistance of W. G. Bade and R. G. Bartle.
- William Fedus, Barret Zoph, and Noam Shazeer. Switch transformers: Scaling to trillion parameter models with simple and efficient sparsity. *Journal of Machine Learning Research*, 23(120):1–39, 2022.
- Eugene A Feinberg and Adam Shwartz. *Handbook of Markov decision processes: methods and applications*, volume 40. Springer Science & Business Media, 2012.
- Trevor Gale, Deepak Narayanan, Cliff Young, and Matei Zaharia. Megablocks: Efficient sparse training with mixture-of-experts. *Proceedings of Machine Learning and Systems*, 5, 2023.
- Leo Gao, Jonathan Tow, Stella Biderman, Sid Black, Anthony DiPofi, Charles Foster, Laurence Golding, Jeffrey Hsu, Kyle McDonell, Niklas Muennighoff, Jason Phang, Laria Reynolds, Eric Tang, Anish Thite, Ben Wang, Kevin Wang, and Andy Zou. A framework for few-shot language model evaluation. x, September 2021. doi: 10.5281/zenodo.5371628. URL <https://doi.org/10.5281/zenodo.5371628>.
- Google. Gemini. Google. URL <https://gemini.google.com/>.
- Mohinder S Grewal and Angus P Andrews. *Kalman filtering: Theory and Practice with MATLAB*. John Wiley & Sons, 2014.
- Nate Gruver, Marc Finzi, Shikai Qiu, and Andrew G Wilson. Large language models are zero-shot time series forecasters. *Advances in Neural Information Processing Systems*, 36, 2024.
- Lu Han, Han-Jia Ye, and De-Chuan Zhan. The capacity and robustness trade-off: Revisiting the channel independent strategy for multivariate time series forecasting. *IEEE Transactions on Knowledge and Data Engineering*, 2024.
- Dan Hendrycks, Collin Burns, Steven Basart, Andy Zou, Mantas Mazeika, Dawn Song, and Jacob Steinhardt. Measuring massive multitask language understanding. In *9th International Conference on Learning Representations, ICLR 2021, Virtual Event, Austria, May 3-7, 2021*. OpenReview.net, 2021.
- Edward J Hu, Yelong Shen, Phillip Wallis, Zeyuan Allen-Zhu, Yanzhi Li, Shean Wang, Lu Wang, and Weizhu Chen. Lora: Low-rank adaptation of large language models. *arXiv preprint arXiv:2106.09685*, 2021.
- Martin Hutzenthaler and Arnulf Jentzen. *Numerical approximations of stochastic differential equations with non-globally Lipschitz continuous coefficients*, volume 236. American Mathematical Society, 2015.
- Romain Ilbert, Ambroise Odonnat, Vasilii Feofanov, Aladin Virmaux, Giuseppe Paolo, Themis Palpanas, and Ievgen Redko. SAMformer: Unlocking the potential of transformers in time series forecasting with sharpness-aware minimization and channel-wise attention. In Ruslan Salakhutdinov, Zico Kolter, Katherine Heller, Adrian Weller, Nuria Oliver, Jonathan Scarlett, and Felix Berkenkamp (eds.), *Proceedings of the 41st International Conference on Machine Learning*, volume 235 of *Proceedings of Machine Learning Research*, pp. 20924–20954. PMLR, 21–27 Jul 2024. URL <https://proceedings.mlr.press/v235/ilbert24a.html>.
- Robert A Jacobs, Michael I Jordan, Steven J Nowlan, and Geoffrey E Hinton. Adaptive mixtures of local experts. *Neural computation*, 3(1):79–87, 1991.
- Herbert Jaeger. Adaptive nonlinear system identification with echo state networks. *Advances in neural information processing systems*, 15, 2002.

- Albert Q Jiang, Alexandre Sablayrolles, Arthur Mensch, Chris Bamford, Devendra Singh Chaplot, Diego de las Casas, Florian Bressand, Gianna Lengyel, Guillaume Lample, Lucile Saulnier, et al. Mistral 7b. *arXiv preprint arXiv:2310.06825*, 2023.
- Albert Q Jiang, Alexandre Sablayrolles, Antoine Roux, Arthur Mensch, Blanche Savary, Chris Bamford, Devendra Singh Chaplot, Diego de las Casas, Emma Bou Hanna, Florian Bressand, et al. Mixtral of experts. *arXiv preprint arXiv:2401.04088*, 2024.
- Michael I Jordan and Robert A Jacobs. Hierarchical mixtures of experts and the em algorithm. *Neural computation*, 6(2):181–214, 1994.
- R. E. Kalman. A New Approach to Linear Filtering and Prediction Problems. *Journal of Basic Engineering*, 82(1):35–45, 03 1960. ISSN 0021-9223. doi: 10.1115/1.3662552. URL <https://doi.org/10.1115/1.3662552>.
- Patrick Kidger, James Foster, Xuechen Li, and Terry J Lyons. Neural sdes as infinite-dimensional gans. In *International conference on machine learning*, pp. 5453–5463. PMLR, 2021.
- Youngjoo Kim, Hyochoong Bang, et al. Introduction to kalman filter and its applications. *Introduction and Implementations of the Kalman Filter*, 1:1–16, 2018.
- Woosuk Kwon, Zhuohan Li, Siyuan Zhuang, Ying Sheng, Lianmin Zheng, Cody Hao Yu, Joseph E. Gonzalez, Hao Zhang, and Ion Stoica. Efficient memory management for large language model serving with pagedattention. In *Proceedings of the ACM SIGOPS 29th Symposium on Operating Systems Principles*, 2023.
- Pingzhi Li, Zhenyu Zhang, Prateek Yadav, Yi-Lin Sung, Yu Cheng, Mohit Bansal, and Tianlong Chen. Merge, then compress: Demystify efficient SMoe with hints from its routing policy. In *The Twelfth International Conference on Learning Representations*, 2024. URL <https://openreview.net/forum?id=eFWG9Cy3WK>.
- Percy Liang, Rishi Bommasani, Tony Lee, Dimitris Tsipras, Dilara Soylu, Michihiro Yasunaga, Yian Zhang, Deepak Narayanan, Yuhuai Wu, Ananya Kumar, et al. Holistic evaluation of language models. *ArXiv preprint*, abs/2211.09110, 2022.
- Shengsheng Lin, Weiwei Lin, Wentai Wu, Haojun Chen, and Junjie Yang. SparseTSF: Modeling long-term time series forecasting with $1k^*$ parameters. In Ruslan Salakhutdinov, Zico Kolter, Katherine Heller, Adrian Weller, Nuria Oliver, Jonathan Scarlett, and Felix Berkenkamp (eds.), *Proceedings of the 41st International Conference on Machine Learning*, volume 235 of *Proceedings of Machine Learning Research*, pp. 30211–30226. PMLR, 21–27 Jul 2024. URL <https://proceedings.mlr.press/v235/lin24n.html>.
- Robert S. Liptser and Albert N. Shiryaev. *Statistics of random processes. II*, volume 6 of *Applications of Mathematics (New York)*. Springer-Verlag, Berlin, expanded edition, 2001a. ISBN 3-540-63928-4. Applications, Translated from the 1974 Russian original by A. B. Aries, Stochastic Modelling and Applied Probability.
- Robert S. Liptser and Albert N. Shiryaev. *Statistics of random processes. I*, volume 5 of *Applications of Mathematics (New York)*. Springer-Verlag, Berlin, expanded edition, 2001b. ISBN 3-540-63929-2. General theory, Translated from the 1974 Russian original by A. B. Aries, Stochastic Modelling and Applied Probability.
- Shizhan Liu, Hang Yu, Cong Liao, Jianguo Li, Weiyao Lin, Alex X Liu, and Schahram Dustdar. Pyraformer: Low-complexity pyramidal attention for long-range time series modeling and forecasting. In *International conference on learning representations*, 2021.
- Xuerong Mao. *Stochastic differential equations and applications*. Elsevier, 2007.
- MosaicAI. Introducing dbx: A new state-of-the-art open llm. <https://www.databricks.com/blog/introducing-dbrx-new-state-art-open-llm>, 2024. Accessed: 2024-05-21.
- Yuqi Nie, Nam H Nguyen, Phanwadee Sinthong, and Jayant Kalagnanam. A time series is worth 64 words: Long-term forecasting with transformers. *arXiv preprint arXiv:2211.14730*, 2022.

- OpenAI. Gpt-4 technical report, 2023.
- Boris N Oreshkin, Dmitri Carпов, Nicolas Chapados, and Yoshua Bengio. N-beats: Neural basis expansion analysis for interpretable time series forecasting. *arXiv preprint arXiv:1905.10437*, 2019.
- Joan Puigcerver, Carlos Riquelme Ruiz, Basil Mustafa, and Neil Houlsby. From sparse to soft mixtures of experts. In *The Twelfth International Conference on Learning Representations*, 2024. URL <https://openreview.net/forum?id=jxpsAj7ltE>.
- Nils Reimers and Iryna Gurevych. Sentence-bert: Sentence embeddings using siamese bert-networks, 2019.
- Jonas Rothfuss, Vincent Fortuin, Martin Josifoski, and Andreas Krause. Pacoh: Bayes-optimal meta-learning with pac-guarantees. In *International Conference on Machine Learning*, pp. 9116–9126. PMLR, 2021.
- Jonas Rothfuss, Martin Josifoski, Vincent Fortuin, and Andreas Krause. Scalable pac-bayesian meta-learning via the pac-optimal hyper-posterior: From theory to practice. *Journal of Machine Learning Research*, 24:1–62, 2023.
- El Mehdi Saad, Nicolas Verzelen, and Alexandra Carpentier. Active ranking of experts based on their performances in many tasks. In *International Conference on Machine Learning*, pp. 29490–29513. PMLR, 2023.
- Claude Sammut and Geoffrey I. Webb (eds.). *TF-IDF*, pp. 986–987. Springer US, Boston, MA, 2010. ISBN 978-0-387-30164-8. doi: 10.1007/978-0-387-30164-8_832. URL https://doi.org/10.1007/978-0-387-30164-8_832.
- Raeid Saqur, Ken Kato, Nicholas Vinden, and Frank Rudzicz. Nifty financial news headlines dataset, 2024. Manuscript under review.
- Keith P Sharp. Stochastic differential equations in finance. *Applied mathematics and Computation*, 37(2):131–148, 1990.
- Noam Shazeer, Azalia Mirhoseini, Krzysztof Maziarsz, Andy Davis, Quoc Le, Geoffrey Hinton, and Jeff Dean. Outrageously large neural networks: The sparsely-gated mixture-of-experts layer. *arXiv preprint arXiv:1701.06538*, 2017.
- Yueqi Song, Catherine Cui, Simran Khanuja, Pengfei Liu, Fahim Faisal, Alissa Ostapenko, Genta Indra Winata, Alham Fikri Aji, Samuel Cahyawijaya, Yulia Tsvetkov, et al. GlobalBench: A benchmark for global progress in natural language processing. *ArXiv preprint*, abs/2305.14716, 2023.
- Yejun Soun, Jaemin Yoo, Minyong Cho, Jihyeong Jeon, and U Kang. Accurate stock movement prediction with self-supervised learning from sparse noisy tweets. In *2022 IEEE International Conference on Big Data (Big Data)*, pp. 1691–1700. IEEE, 2022.
- Ruslan Leontyevich Stratonovich. Optimum nonlinear systems which bring about a separation of a signal with constant parameters from noise. *Radiofizika*, 2(6):892–901, 1959.
- Ruslan Leontyevich Stratonovich. Application of the markov processes theory to optimal filtering. *Radio Engineering and Electronic Physics*, 5:1–19, 1960.
- Hugo Touvron, Thibaut Lavril, Gautier Izacard, Xavier Martinet, Marie-Anne Lachaux, Timothée Lacroix, Baptiste Rozière, Naman Goyal, Eric Hambro, Faisal Azhar, et al. Llama: Open and efficient foundation language models. *arXiv preprint arXiv:2302.13971*, 2023.
- A. N. Širjaev. Some explicit formulae in a problem on “disorder”. *Teor. Veroyatnost. i Primenen.*, 10: 380–385, 1965. ISSN 0040-361x.
- Renjie Wang, Cody Hyndman, and Anastasis Kratsios. The entropic measure transform. *Canadian Journal of Statistics*, 48(1):97–129, 2020.

- Yizhong Wang, Yeganeh Kordi, Swaroop Mishra, Alisa Liu, Noah A. Smith, Daniel Khashabi, and Hannaneh Hajishirzi. Self-instruct: Aligning language models with self-generated instructions, 2023.
- Henry Wolkowicz and George P. H. Styan. Bounds for eigenvalues using traces. *Linear Algebra Appl.*, 29:471–506, 1980. ISSN 0024-3795,1873-1856. doi: 10.1016/0024-3795(80)90258-X. URL [https://doi.org/10.1016/0024-3795\(80\)90258-X](https://doi.org/10.1016/0024-3795(80)90258-X).
- W Murray Wonham. Some applications of stochastic differential equations to optimal nonlinear filtering. *Journal of the Society for Industrial and Applied Mathematics, Series A: Control*, 2(3): 347–369, 1964.
- Gerald Woo, Chenghao Liu, Akshat Kumar, Caiming Xiong, Silvio Savarese, and Doyen Sahoo. Unified training of universal time series forecasting transformers. In Ruslan Salakhutdinov, Zico Kolter, Katherine Heller, Adrian Weller, Nuria Oliver, Jonathan Scarlett, and Felix Berkenkamp (eds.), *Proceedings of the 41st International Conference on Machine Learning*, volume 235 of *Proceedings of Machine Learning Research*, pp. 53140–53164. PMLR, 21–27 Jul 2024. URL <https://proceedings.mlr.press/v235/woo24a.html>.
- Haixu Wu, Jiehui Xu, Jianmin Wang, and Mingsheng Long. Autoformer: Decomposition transformers with auto-correlation for long-term series forecasting. *Advances in neural information processing systems*, 34:22419–22430, 2021.
- Huizhe Wu, Wei Zhang, Weiwei Shen, and Jun Wang. Hybrid deep sequential modeling for social text-driven stock prediction. In *Proceedings of the 27th ACM international conference on information and knowledge management*, pp. 1627–1630, 2018.
- Qianqian Xie, Weiguang Han, Xiao Zhang, Yanzhao Lai, Min Peng, Alejandro Lopez-Lira, and Jimin Huang. Pixiu: A large language model, instruction data and evaluation benchmark for finance. *arXiv preprint arXiv:2306.05443*, 2023.
- Yumo Xu and Shay B Cohen. Stock movement prediction from tweets and historical prices. In *Proceedings of the 56th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 1970–1979, 2018.
- Zhijian Xu, Ailing Zeng, and Qiang Xu. Fits: Modeling time series with 10k parameters. In *The Twelfth International Conference on Learning Representations*, 2024.
- Moshe Zakai. On the optimal filtering of diffusion processes. *Zeitschrift für Wahrscheinlichkeitstheorie und verwandte Gebiete*, 11(3):230–243, 1969.
- Ailing Zeng, Muxi Chen, Lei Zhang, and Qiang Xu. Are transformers effective for time series forecasting? In *Proceedings of the AAAI conference on artificial intelligence*, volume 37, pp. 11121–11128, 2023.
- Haoyi Zhou, Shanghang Zhang, Jieqi Peng, Shuai Zhang, Jianxin Li, Hui Xiong, and Wancai Zhang. Informer: Beyond efficient transformer for long sequence time-series forecasting. In *Proceedings of the AAAI conference on artificial intelligence*, volume 35, pp. 11106–11115, 2021.
- Yanqi Zhou, Tao Lei, Hanxiao Liu, Nan Du, Yanping Huang, Vincent Zhao, Andrew M Dai, Quoc V Le, James Laudon, et al. Mixture-of-experts with expert choice routing. *Advances in Neural Information Processing Systems*, 35:7103–7114, 2022.

Appendices

Appendix Contents

A	The MoE-F Algorithm	18
B	Proofs	19
B.1	Proof of Theorem 1	20
B.1.1	Case I: Binary Cross-Entropy Case	20
B.1.2	Case II: Squared Loss	22
B.2	Proof of Theorem 2	23
B.2.1	Completion of The Proof of Theorem 2	26
B.3	Proof of the Stability Guarantee in Proposition 1	27
C	Datasets and Benchmarks	27
C.1	NIFTY Dataset	27
C.1.1	NIFTY-LM: SFT Fine-tuning Dataset	28
C.2	NIFTY-RL: Preferences Dataset	29
C.3	FLARE Benchmark Datasets	30
D	Additional Background Material	30
D.1	Matrix Logarithms	30
D.2	The Shirayev-Wonham Filter	30
E	Additional Discussions	32
E.1	F1-Measure in FMM Task	32
E.2	Time-Series Forecasting Experiments: Additional Details	32
E.2.1	Forecasting granularity in Time-Series Forecasting: IMS vs. DMS	32
E.2.2	Channel Independent Strategy	33
E.2.3	Our Setup	33

A THE MOE-F ALGORITHM

This section records a detailed version of Algorithm 1, which can also be rolled-forward online as the target process Y is dynamically observed.

Algorithm 2: The MoE-F Algorithm

Input: A time-horizon $T \in \mathbb{N}_+$, N (pre-trained) experts $f^{(1)}, \dots, f^{(N)}$, hyperparameters $\lambda > 0$, $\alpha \in (0, 1)$ and $k \in \mathbb{N}_+$, target $(Y_t)_{t=0}^{T-1}$, and input signal $x_{[0:T-1]}$.

Output: A posterior Mixture Weights w_t

```

1 /* Initialize */
2 Initialize  $\pi \stackrel{\text{def}}{=} (\pi^{(n:i)})_{n,i=1}^N \leftarrow (1/N)_{n,i=1}^N$ 
3  $Q \leftarrow (1/(N-1)I_{i \neq j} - 1I_{i=j})_{i,j=1}^N$ 
4  $(L_-^{(n)})_{n=1}^N \leftarrow 0$ 
5 for  $t = 0, \dots, T-1$  do
6   For  $n = 1, \dots, N$  in parallel
7      $\bar{A} \leftarrow \bar{A}_t^{(n)}(\pi^{(n)}, Y_t)$ 
8      $B \leftarrow B_t^{(n)}(Y_t)$   $\tilde{\pi} \leftarrow \pi$ 
9      $L^{(n)} \leftarrow \ell(f^{(n)}(x_{[0:t]}))$ 
10     $\Delta L \leftarrow L^{(n)} - L_-^{(n)}$ 
11     $\Delta \bar{W} \leftarrow \frac{\Delta L - \bar{A}}{B}$ 
12     $L_-^{(n)} \leftarrow L^{(n)}$ 
13    /* Update components of  $n^{th}$  expert's posterior  $(\pi^{(n)})$  */
14    for  $i = 1, \dots, N$  do
15       $A \leftarrow A_t^{(n)}(e_i, Y_t)$ 
16      drift  $\leftarrow Q_i^\top \tilde{\pi}^{(n)}$ 
17      diffusion  $\leftarrow \tilde{\pi}^{(n:i)} (A - \bar{A})/B$ 
18       $\pi^{(n:i)} \leftarrow \tilde{\pi}^{(n:i)} + \text{drift} + \text{diffusion} \Delta \bar{W}$ 
19    end for
20     $\pi^{(n)} \leftarrow \pi^{(n)} / \sum_i \pi^{(n:i)}$ 
21     $s_n \leftarrow \ell(Y_t, (\pi^{(n)})^\top F(x_{[0:t]}))$ 
22     $\hat{Y}_t^{(n)} \leftarrow (\pi^{(n)})^\top F(x_{[0:t]})$  // Calculate expert scores
23  end
24   $\bar{\pi} \leftarrow (e^{-\lambda s_n} / (\sum_{i=1}^N e^{-\lambda s_i}))_{n=1}^N$  // Get Expert Scores
25   $\hat{Y}_t \stackrel{\text{def}}{=} \bar{\pi}^\top (\hat{Y}_t^{(n)})_{n=1}^N$  // Get time  $t$  prediction
26  /* Update  $Q$  */
27   $\tilde{Q} \leftarrow Q$ 
28  for  $n = 1, \dots, N$  do
29     $P^{(n)} \leftarrow \bar{\pi}$ 
30  end for
31   $P \leftarrow (1 - \alpha)P + \alpha I_N$ 
32   $Q \leftarrow \text{ReLU}(\log(P)) - \text{diag}(\bar{1}^\top \text{ReLU}(\log(P)))$ 
33 end for
34 return Sequence of Mixture Predictions  $(\hat{Y}_t)_{t=0}^{T-1}$ 

```

B PROOFS

This section contains the proofs of our main result, generalizations thereof, and variants which apply to the quadratic (squared) loss. In the latter case, the necessary modifications to the algorithm and the overall proof structure are relatively similar but with key technical differences.

Mild Generalizations and Further Discussion. We will consider the slightly more general case where the target process Y_t follows the generalized dynamics

$$Y_t = Y_0 + \underbrace{\int_0^t w_t^\top F(x_s) ds}_{\text{Best Expert Estimate}} + \underbrace{\int_0^t \sigma_s dW_s}_{\text{(Generalized) Idiosyncratic Residual}}, \quad (7)$$

where, there are constants $\alpha, C \geq 0$ with $C \leq 1$ such that: for each $t \geq 0$ one has $\sigma_t = C e^{-\alpha t}$. By the Itô-isometry, see [Cohen & Elliott, 2015, Lemma 12.1.4], we have that the variance of $\int_0^t \sigma_s dW_s$ is given by

$$\varsigma_t^2 \stackrel{\text{def.}}{=} \mathbb{E} \left[\left(\int_0^t \sigma_s dW_s \right)^2 \right] = \begin{cases} C^2 (1 - e^{-\alpha 2t}) / (2\alpha) & \text{if } \alpha > 0 \\ t & \text{if } \alpha = 0 \end{cases} \quad (8)$$

Observe that, if $\alpha > 0$ then the variance of $\int_0^t \sigma_s dW_s$ asymptotically stabilizes at 1, as t becomes arbitrarily large. In contrast, the variance of $\int_0^t \sigma_s dW_s$ diverges in the case where $\alpha = 0$ (which is the case considered in the main body of our paper).

Intuition behind the choice of assumed fluctuations/diffusion. The intuition behind this modelling choice for the diffusion coefficient σ_t is based on ideas behind concentration of measure. Consider the case where $\alpha > 0$ in equation (8). Since we will be considering classification applications, then we will not want the idiosyncratic residual $\int_0^t \sigma_s W_s$ to push fluctuate outside the unit interval $[0, 1]$, or rather the probability that any fluctuation of $\int_0^t \sigma_s W_s$ is “large” should be small. Since $\int_0^t \sigma_s W_s$ has a Gaussian distribution, then note, by standard Gaussian concentration inequalities, we have that

$$\mathbb{P} \left(\left| \int_0^t \sigma_s W_s \right| \geq 1/2 \right) \leq e^{(1/2)^2 / (2\varsigma_t^2)} = e^{-\alpha / (4C^2(1-e^{-\alpha 2t}))} \leq e^{-\alpha / (C^2 4)} \leq e^{-\alpha/4}. \quad (9)$$

We can control the probability that any fluctuation is “large”, meaning larger than $1/2$, by setting the right-hand side of equation (9) to be a prespecified “small” value $\delta \in (0, 1]$ and solving for the required $\alpha > 0$ parameter in terms of δ yields the specification $\alpha = \ln(1/\delta^4)$. If $d \geq 2$, then we may set $C = \frac{\sqrt{2}}{d}$ purely for convenience in simplifying expressions below.

In this case, for any hyperparameter $0 < \delta \leq 1$, the quantities in Theorem 1 become

$$\pi_t^{(n:i)} = w_0^i + \int_0^t (Q_s)_i^\top \pi_s^{(n)} ds + \int_0^t \frac{\pi_s^{(n:i)} (A_s(e_i, Y_{[0:s]}) - \bar{A}_s(Y_{[0:s]})^\top \pi_s^{(n)})}{B_s(Y_{[0:s]})} d\bar{W}_u^{(n)}, \quad (10)$$

where $(Q_t)_i$ denotes the i^{th} row of the transitions matrix Q_t at time $t \geq 0$, $w_0^i \stackrel{\text{def.}}{=} \mathbb{P}(w_0 = e_i)$ and where the “innovations process” $\bar{W}_t^{(n)} \stackrel{\text{def.}}{=} (\bar{W}_t^{(n)})_{t \geq 0}$ is the following $(\mathbb{P}, \mathcal{F}^n)$ -Brownian motion

$$\bar{W}_s^{(n)} \stackrel{\text{def.}}{=} \int_0^s \frac{dL_{[0:u]}^{(n)} - \bar{A}_u(Y_{[0:u]})}{B_u(Y_{[0:u]})} du,$$

where the “stochastic differential” $dL_{[0:u]}^{(n)}$ is given by

$$\begin{aligned} dL_{[0:u]}^{(n)} &= \left(2(Y_u - f^{(n)}(x_u)) [\nabla_u f^{(n)}(x_u) + w_u^\top F(x_u)] - e^{-2t \ln(1/\delta^4)} \right) du \\ &\quad + \frac{2^{3/2}}{d} (Y_u - f^{(n)}(x_u)) e^{-t \ln(1/\delta^4)} dW_u. \end{aligned}$$

B.1 PROOF OF THEOREM 1

We are now ready to state and prove two versions, one of which generalizes, our first main result (Theorem 1). We consider two cases. We obtain our main result by customizing Theorem 1 to our classification problem, where $D = 1$ and the range of each expert is in $\{0, 1\} \subset \mathbb{R}$, and setting σ to be a specific constant in $(0, \infty)$. For convenience, if we postulate that $\sigma_t = 1$; i.e. it is a constant function of the path $y_{[0:t]}$ and of time $t \geq 0$. Note that, by the Itô-isometry, see [Cohen & Elliott, 2015, Lemma 12.1.4] the *idiosyncratic residual* term $\int_0^t \sigma_s(Y_{[0:s]}) dW_s$ in equation (1) has a centred normal random distribution with variance $\int_0^t \sigma_s^2 ds = t$.

B.1.1 CASE I: BINARY CROSS-ENTROPY CASE

We now state and prove a mild generalization of Theorem 1.

Theorem 3 (Optimal Optimistic Prior for n^{th} Expert - Squared Loss Case). *Consider the binary cross-entropy loss*

$$\ell(\hat{y}, y) \stackrel{\text{def.}}{=} y \log(\hat{y}) + (1 - y) \log(1 - \hat{y})$$

and fix a continuously differentiable path $x \in C^1(\mathbb{R})$.

Under Assumptions 4.1, the best a posteriori estimate of the n^{th} expert, $\pi_t^{(n)}$, satisfies the following stochastic differential equation

$$\pi_t^{(n:i)} = w_0^i + \int_0^t (Q_t)_i^\top \pi_s^{(n)} ds + \int_0^t \frac{\pi_s^{(n:i)} (A_s(e_i, Y_{[0:s]}) - \bar{A}_s(\pi^{(n)}, Y_{[0:s]}))}{B_s(Y_{[0:s]})} d\bar{W}_u^{(n)}, \quad (11)$$

where $(Q_t)_i$ denotes the i^{th} row of the transitions matrix Q_t at time $t \geq 0$, $w_0^i \stackrel{\text{def.}}{=} \mathbb{P}(w_0 = e_i)$,

$$A_t^{(n)}(w, y_{[0:t]}) \stackrel{\text{def.}}{=} - \frac{(Y_t - f^{(n)}(x_{[0:t]})) \Delta f^{(n)}(x_{[0:t]})}{(1 - f^{(n)}(x_{[0:t]})) f^{(n)}(x_{[0:t]})} - \log\left(\frac{f^{(n)}(x_{[0:t]})}{1 - f^{(n)}(x_{[0:t]})}\right) [w_s^\top F(x_{[0:s]})]$$

$$\bar{A}_t^{(n)}(\pi^{(n)}, y_{[0:t]}) \stackrel{\text{def.}}{=} \sum_{i=1}^d A_t(e_i, Y_{[0:t]}) \pi^{(n:i)}$$

$$B_t^{(n)}(y_{[0:t]}) \stackrel{\text{def.}}{=} - \log\left(\frac{f^{(n)}(x_{[0:t]})}{1 - f^{(n)}(x_{[0:t]})}\right) e^{s \ln(\delta^4)}$$

$$F(x_{[0:t]}) \stackrel{\text{def.}}{=} (f^{(1)}(x_{[0:t]}), \dots, f^{(N)}(x_{[0:t]}))$$

and the “innovations process” $\bar{W}^{(n)} \stackrel{\text{def.}}{=} (\bar{W}_t^{(n)})_{t \geq 0}$ is the following $(\mathbb{P}, \mathcal{F}^n)$ -Brownian motion

$$\bar{W}_s^{(n)} \stackrel{\text{def.}}{=} \int_0^s \frac{dL_{[0:u]}^{(n)} - \bar{A}_u(Y_{[0:u]})}{B_u(Y_{[0:u]})} du,$$

where

$$\begin{aligned} dL_{[0:u]}^{(n)} &= d\ell(Y_t, \hat{f}^{(n)}(x_{[0:t]})) = \frac{(Y_t - f^{(n)}(x_{[0:t]})) \Delta f^{(n)}(x_{[0:t]})}{(1 - f^{(n)}(x_{[0:t]})) f^{(n)}(x_{[0:t]})} + \log\left(\frac{f^{(n)}(x_{[0:t]})}{1 - f^{(n)}(x_{[0:t]})}\right) [w_s^\top F(x_{[0:s]})] \\ &\quad + \log\left(\frac{f^{(n)}(x_{[0:t]})}{1 - f^{(n)}(x_{[0:t]})}\right) e^{s \ln(\delta^4)} dW_s. \end{aligned}$$

Proof. Fix a continuously differentiable path $x \in C^1(\mathbb{R})$. Define $\Delta f(x_{[0:t]}) \stackrel{\text{def.}}{=} \partial_t f(x_{[0:t]})$ and set $\ell : \mathbb{R} \ni y \mapsto (y - f(x_{[0:t]}))^2$.

First, observe that: for all $t \geq 0$, all $x. \in C^1(\mathbb{R})$ and all $y \in \mathbb{R}$ one has

$$\begin{aligned}\ell_t(y) &= -(y \log(f^{(n)}(x_{[0:t]})) + (1-y) \log(1 - f^{(n)}(x_{[0:t]}))) \\ \frac{\partial \ell_t}{\partial t}(y) &= -\frac{(y - f^{(n)}(x_{[0:t]})) \Delta f^{(n)}(x_{[0:t]})}{(1 - f^{(n)}(x_{[0:t]})) f^{(n)}(x_{[0:t]})}, \\ \frac{\partial \ell_t}{\partial y}(y) &= -\log\left(\frac{f^{(n)}(x_{[0:t]})}{1 - f^{(n)}(x_{[0:t]})}\right), \\ \frac{\partial^2 \ell_t}{\partial y^2}(y) &= 0.\end{aligned}\tag{12}$$

Since $\ell \in C^\infty(\mathbb{R}^d \times \mathbb{R}^d)$, we assumed that the path $x. \in C^1([0: \infty), \mathbb{R}^d)$ then this, together with the postulated dynamics on $Y^{(n)}$ imply that Itô's Lemma/Formula, see [Cohen & Elliott, 2015, Theorem 14.2.4], used on the map $\ell_t^{(n)} : [0, \infty) \times \mathbb{R}^D \ni (t, y) \rightarrow (y - f^{(n)}(x_t))^2 \in \mathbb{R}$ pre-composed with Y applies. Whence, our and the assumed dynamics on Y , postulated in equation (1), imply that the process $L_t^{(n)} \stackrel{\text{def}}{=} \ell_t^{(n)}(Y_t)$ satisfies the following stochastic differential equation

$$\begin{aligned}L_t^{(n)} &= L_0^{(n)} + \int_0^t \frac{\partial \ell_s^{(n)}}{\partial s}(Y_s) \\ &\quad + \frac{\partial \ell_s^{(n)}}{\partial y}(Y_s) [w_s^\top F(x_{[0:s]})] \\ &\quad + \frac{1}{2} \frac{\partial^2 \ell_t^{(n)}}{\partial y^2}(Y_s) 2e^{s \ln(\delta^8)} ds \\ &\quad + \int_0^t \frac{\partial \ell_t^{(n)}}{\partial y}(Y_s) e^{s \ln(\delta^4)} dW_s \\ &= L_0^{(n)} + \int_0^t \frac{(-1)(Y_s - f^{(n)}(x_{[0:t]})) \Delta f^{(n)}(x_{[0:t]})}{(1 - f^{(n)}(x_{[0:t]})) f^{(n)}(x_{[0:t]})} \\ &\quad + (-1) \log\left(\frac{f^{(n)}(x_{[0:t]})}{1 - f^{(n)}(x_{[0:t]})}\right) [w_s^\top F(x_{[0:s]})] \\ &\quad + \frac{1}{2} 0 ds \\ &\quad + \int_0^t (-1) \log\left(\frac{f^{(n)}(x_{[0:t]})}{1 - f^{(n)}(x_{[0:t]})}\right) e^{s \ln(\delta^4)} dW_s\end{aligned}\tag{13}$$

$$\begin{aligned}&= L_0^{(n)} + \int_0^t -\frac{(Y_s - f^{(n)}(x_{[0:t]})) \Delta f^{(n)}(x_{[0:t]})}{(1 - f^{(n)}(x_{[0:t]})) f^{(n)}(x_{[0:t]})} - \log\left(\frac{f^{(n)}(x_{[0:t]})}{1 - f^{(n)}(x_{[0:t]})}\right) [w_s^\top F(x_{[0:s]})] ds \\ &\quad - \log\left(\frac{f^{(n)}(x_{[0:t]})}{1 - f^{(n)}(x_{[0:t]})}\right) \int_0^t e^{s \ln(\delta^4)} dW_s\end{aligned}\tag{14}$$

Synchronizing our notation with [Liptser & Shiryaev, 2001a, Equation (9.1)], we write

$$\begin{aligned}A_t(w, y_{[0:t]}) &\stackrel{\text{def}}{=} -\frac{(Y_s - f^{(n)}(x_{[0:t]})) \Delta f^{(n)}(x_{[0:t]})}{(1 - f^{(n)}(x_{[0:t]})) f^{(n)}(x_{[0:t]})} - \log\left(\frac{f^{(n)}(x_{[0:t]})}{1 - f^{(n)}(x_{[0:t]})}\right) [w_s^\top F(x_{[0:s]})] \\ B_t(y_{[0:t]}) &\stackrel{\text{def}}{=} -\log\left(\frac{f^{(n)}(x_{[0:t]})}{1 - f^{(n)}(x_{[0:t]})}\right) e^{s \ln(\delta^4)}\end{aligned}\tag{15}$$

Under Assumptions 4.1, we may apply [Liptser & Shiryaev, 2001a, Theorem 9.1] to deduce that Then the a posteriori probability $\pi_t^{n:0} \stackrel{\text{def}}{=} (\pi_t)_0$, satisfies a system of equations

$$\pi_t^{(n:i)} = w_0^i + \int_0^t (Q_t)_i^\top \pi_s^{(n)} ds + \int_0^t \frac{\pi_s^{(n:i)} (A_s(e_i, Y_{[0:s]}) - \bar{A}_s(\pi^{(n)}, Y_{[0:s]}))}{B_s(Y_{[0:s]})} d\bar{W}_u, \tag{16}$$

where $(Q_t)_i$ denotes the i^{th} row of the Q_t /transitions matrix Q_t at time $t \geq 0$, $w_0^i \stackrel{\text{def.}}{=} \mathbb{P}(w_0 = e_i)$, and the “innovations process” is the $(\mathbb{P}, \mathcal{F}^n)$ -Brownian motion given by

$$\overline{W}_s^{(n)} \stackrel{\text{def.}}{=} \int_0^s \frac{dL_{[0:u]}^{(n)} - \bar{A}_u(\pi^{(n)}, Y_{[0:u]})}{B_u(Y_{[0:u]})} du \quad (17)$$

and where

$$\bar{A}_t(\pi^{(n)}, y_{[0:t]}) \stackrel{\text{def.}}{=} \sum_{i=1}^d A_s(e_i, Y_{[0:t]}) \pi^{(n:i)}.$$

This completes the proof. \square

Remark 1. Setting $\delta = 1$ in the previous derivation yields the formulation of Theorem 1 found in the main body of the paper.

B.1.2 CASE II: SQUARED LOSS

Theorem 4 (Optimal Optimistic Prior for n^{th} Expert - Squared Loss Case). *Let $\ell(\hat{y}, y) \stackrel{\text{def.}}{=} (y - \hat{y})^2$ and fix a continuously differentiable path $x \in C^1(\mathbb{R})$.*

Under Assumptions 4.1, the best a posteriori estimate of the n^{th} expert, $\pi_t^{(n)}$, satisfies the following stochastic differential equation

$$\pi_t^{(n:i)} = w_0^i + \int_0^t (Q_s)_i^\top \pi_s^{(n)} ds + \int_0^t \frac{\pi_s^{(n:i)} (A_s(e_i, Y_{[0:s]}) - \bar{A}_s(\pi^{(n)}, Y_{[0:s]}))}{B_s(Y_{[0:s]})} d\overline{W}_s^{(n)}, \quad (18)$$

where $(Q_t)_i$ denotes the i^{th} row of the transitions matrix Q_t at time $t \geq 0$, $w_0^i \stackrel{\text{def.}}{=} \mathbb{P}(w_0 = e_i)$,

$$A_t^{(n)}(w, y_{[0:t]}) \stackrel{\text{def.}}{=} 2(y_t - f^{(n)}(x_{[0:t]})) (w_t^\top F(x_{[0:t]}) - \Delta f^{(n)}(x_{[0:t]}) + e^{s \ln(\delta^8)})$$

$$\bar{A}_t^{(n)}(\pi^{(n)}, y_{[0:t]}) \stackrel{\text{def.}}{=} \sum_{i=1}^d A_t(e_i, Y_{[0:t]}) \pi^{(n:i)}$$

$$B_t^{(n)}(y_{[0:t]}) \stackrel{\text{def.}}{=} 2^{3/2} (y_t - f^{(n)}(x_{[0:t]})) e^{t \ln(\delta^4)}$$

$$F(x_{[0:t]}) \stackrel{\text{def.}}{=} (f^{(1)}(x_{[0:t]}), \dots, f^{(N)}(x_{[0:t]}))$$

and the “innovations process” $\overline{W}^{(n)} \stackrel{\text{def.}}{=} (\overline{W}_t^{(n)})_{t \geq 0}$ is the following $(\mathbb{P}, \mathcal{F}^n)$ -Brownian motion

$$\overline{W}_s^{(n)} \stackrel{\text{def.}}{=} \int_0^s \frac{dL_{[0:u]}^{(n)} - \bar{A}_u(Y_{[0:u]})}{B_u(Y_{[0:u]})} du,$$

where

$$\begin{aligned} dL_{[0:u]}^{(n)} &= d\ell(Y_t, \hat{f}^{(n)}(x_{[0:t]})) = 2(Y_t - f^{(n)}(x_{[0:t]})) ([w_s^\top F(x_{[0:t]})] - \Delta f^{(n)}(x_{[0:t]}) + e^{t \ln(\delta^8)}) \\ &\quad + 2(Y_t - f^{(n)}(x_{[0:t]})) e^{t \ln(\delta^4)} dW_t. \end{aligned}$$

Proof. Fix a continuously differentiable path $x \in C^1(\mathbb{R})$. Define $\Delta f(x_{[0:t]}) \stackrel{\text{def.}}{=} \partial_t f(x_{[0:t]})$ and set $\ell : \mathbb{R} \ni y \mapsto (y - f(x_{[0:t]}))^2$.

First, observe that: for all $t \geq 0$, all $x \in C^1(\mathbb{R})$ and all $y \in \mathbb{R}$ one has

$$\begin{aligned} \ell_t^{(n)}(y) &= (y - f^{(n)}(x_{[0:t]}))^2 \\ \frac{\partial \ell_t}{\partial t}(y) &= 2(y - f^{(n)}(x_{[0:t]})) (-\Delta f^{(n)}(x_{[0:t]})), \\ \frac{\partial \ell_t}{\partial y}(y) &= 2(y - f^{(n)}(x_{[0:t]})), \\ \frac{\partial^2 \ell_t}{\partial y^2}(y) &= 2. \end{aligned} \quad (19)$$

Since $\ell \in C^\infty(\mathbb{R}^d \times \mathbb{R}^d)$, we assumed that the path $x \cdot \in C^1([0 : \infty), \mathbb{R}^d)$ then this, together with the postulated dynamics on $Y^{(n)}$ imply that Itô's Lemma/Formula, see [Cohen & Elliott, 2015, Theorem 14.2.4], used on the map $\ell_t^{(n)} : [0, \infty) \times \mathbb{R}^D \ni (t, y) \rightarrow (y - f^{(n)}(x_t))^2 \in \mathbb{R}$ pre-composed with Y applies. Whence, the computations in equation (19) and the assumed dynamics on Y , postulated in equation (1), imply that the process $L_t^{(n)} \stackrel{\text{def}}{=} \ell_t^{(n)}(Y_t)$ satisfies the following stochastic differential equation

$$\begin{aligned} L_t^{(n)} &= L_0^{(n)} + \int_0^t \frac{\partial \ell_s^{(n)}}{\partial s}(Y_s) + \frac{\partial \ell_s^{(n)}}{\partial y}(Y_s) [w_s^\top F(x_{[0:s]})] + \frac{1}{2} \frac{\partial^2 \ell_t^{(n)}}{\partial y^2}(Y_s) 2e^{s \ln(\delta^8)} ds \\ &\quad + \int_0^t \frac{\partial \ell_t^{(n)}}{\partial y}(Y_s) e^{s \ln(\delta^4)} dW_s \\ &= L_0^{(n)} + \int_0^t 2(Y_s - f^{(n)}(x_{[0:s]})) ([w_s^\top F(x_{[0:s]})] - \Delta f^{(n)}(x_{[0:s]}) + e^{s \ln(\delta^8)}) ds \\ &\quad + \int_0^t 2(Y_s - f^{(n)}(x_{[0:s]})) \sqrt{2} e^{s \ln(\delta^4)} dW_s \end{aligned} \quad (20)$$

Synchronizing our notation with [Liptser & Shiryaev, 2001a, Equation (9.1)], we write

$$\begin{aligned} A_t(w, y_{[0:t]}) &\stackrel{\text{def}}{=} 2(y_t - f^{(n)}(x_{[0:t]})) (w_t^\top F(x_{[0:t]}) - \Delta f^{(n)}(x_{[0:t]}) + e^{t \ln(\delta^8)}) \\ B_t(y_{[0:t]}) &\stackrel{\text{def}}{=} 2^{3/2} (y_t - f^{(n)}(x_{[0:t]})) e^{t \ln(\delta^4)} \end{aligned} \quad (21)$$

Under Assumptions 4.1, we may apply [Liptser & Shiryaev, 2001a, Theorem 9.1] to deduce that Then the a posteriori probability $\pi_t^{n:0} \stackrel{\text{def}}{=} (\pi_t)_0$, satisfies a system of equations

$$\pi_t^{(n:i)} = w_0^i + \int_0^t (Q_t)_i^\top \pi_s^{(n)} ds + \int_0^t \frac{\pi_s^{(n:i)} (A_s(e_i, Y_{[0:s]}) - \bar{A}_s(\pi^{(n)}, Y_{[0:s]}))}{B_s(Y_{[0:s]})} d\bar{W}_u, \quad (22)$$

where $(Q_t)_i$ denotes the i^{th} row of the Q_t /transitions matrix Q_t at time $t \geq 0$, $w_0^i \stackrel{\text{def}}{=} \mathbb{P}(w_0 = e_i)$, and the “innovations process” is the $(\mathbb{P}, \mathcal{F}^n)$ -Brownian motion given by

$$\bar{W}_s^{(n)} \stackrel{\text{def}}{=} \int_0^s \frac{dL_{[0:u]}^{(n)} - \bar{A}_u(\pi^{(n)}, Y_{[0:u]})}{B_u(Y_{[0:u]})} du \quad (23)$$

and where

$$\bar{A}_t(\pi^{(n)}, y_{[0:t]}) \stackrel{\text{def}}{=} \sum_{i=1}^d A_s(e_i, Y_{[0:t]}) \pi^{(n:i)}.$$

This completes the proof. \square

Remark 2. Setting $\delta = 1$ in the previous derivation yields the formulation of Theorem 1 found in the main body of the paper.

B.2 PROOF OF THEOREM 2

The proof of Theorem 2 relies on the following result. Briefly, this result guarantees for the validity of the perturbation to the transition probability defined by

$$P_t^\alpha \stackrel{\text{def}}{=} (1 - \alpha)P_t + \alpha I_N \quad (24)$$

for arbitrary $N \in \mathbb{N}_+$, $P_t \in \mathcal{P}_N^U$, $\alpha \in (0, 1)$, and where I_N is the $N \times N$ identity matrix.

In what follows, we will use $\Delta_N \stackrel{\text{def}}{=} \{w \in [0, 1]^N : \sum_{n=1}^N w_n = 1\}$ to denote the probability N -simplex; which corresponds to the probability (measures) distributions supported on N points. Here, these N points are the experts themselves, and the probability of selecting any expert is interpreted as the relative credibility we ascribe to its historical predictive power.

Proposition 2 (Regularity of Perturbations). *Let $N \in \mathbb{N}_+$, $\lambda > 0$, $s_1, \dots, s_N \in \mathbb{R}$, $\bar{\pi} \in \Delta_N$ be given by*

$$\bar{\pi} \stackrel{\text{def.}}{=} \text{Softmin}(\lambda(s_n)_{n=1}^N) \text{ and } P_t \stackrel{\text{def.}}{=} [(\bar{\pi})_{n=1}^N]^N.$$

For every $\alpha \in (0, 1)$, the matrix P_t^α in equation (24), is invertible and (row) stochastic. If, moreover, all its real eigenvalues are non-negative, then $\log(P_t^\alpha)$ is well-defined and its rows sum to 0. In particular, setting $\alpha \geq 1 - 1/N$ guarantees that $\log(P_t^\alpha)$ exists, if P_t^α has real eigenvalues.

We will now show our second main result, and the intermediate lemmata leading up to it. The next lemma states that if a (row) stochastic matrix is constructed by filling each of its rows with an element of the probability simplex, then shining it by an arbitrarily small amount and growing its diagonal proportionally yields a (row) stochastic matrix, which is necessarily invertible.

Lemma 1 (Invertible Perturbations). *Let $N \in \mathbb{N}_+$ let $\pi \in \Delta_N$. If P is a (row) stochastic matrix, then, for any $\alpha \in (0, 1)$, the matrix $(1 - \alpha)P + \alpha I_N$ is an invertible (row) stochastic matrix.*

Proof of Lemma 1. Let $\mathbf{1}_N \in \mathbb{R}^N$ be such that: for each $i = 1, \dots, N$ we have $(\mathbf{1}_N)_i = 1$ (i.e. $\mathbf{1}_N$ is a matrix of ones). By construction $P = (\pi, \dots, \pi)^\top$. Therefore, P can be written as an outer product via

$$P = \mathbf{1}_N \pi^\top \quad (25)$$

Therefore, for any $\alpha \in (0, 1)$, the perturbed matrix $(1 - \alpha)P + \alpha I_N$ can be expressed as

$$(1 - \alpha)P = ((1 - \alpha) \cdot \mathbf{1}_N) \pi^\top, \quad (26)$$

i.e. $(1 - \alpha)P$ can be expressed as an outer product of vectors in \mathbb{R}^N ; namely of $((1 - \alpha) \cdot \mathbf{1}_N)$ and π^\top . Consequentially, our matrix of interest can be written as

$$(1 - \alpha)P + \alpha I_N = ((1 - \alpha) \cdot \mathbf{1}_N) \pi^\top + \alpha I_N. \quad (27)$$

Note that, αI_N is invertible since $\det(\alpha I_N) = \alpha^N > 0$. Thus, the main result of Bartlett [1951] can be applied, which yields the condition: if αI_N is invertible (which it is) and if

$$1 + \mathbf{1}_N^\top (\alpha I_N)^{-1} \pi \neq 0 \quad (28)$$

then $\alpha I_N + ((1 - \alpha) \cdot \mathbf{1}_N) \pi^\top$ is invertible. Thus, we only need to verify that the condition holds in our case. Simplifying equation (28) yields

$$-1 \neq \mathbf{1}_N^\top (\alpha I_N)^{-1} \pi \quad (29)$$

$$= \frac{1}{\alpha} \mathbf{1}_N^\top \pi \quad (30)$$

$$= \frac{1}{\alpha} \sum_{n=1}^N \pi_n \quad (31)$$

$$= \frac{1}{\alpha} 1 = \frac{1}{\alpha}, \quad (32)$$

where equation (32) held since $\pi \in \Delta_N$. Consequentially, the identity in equation (27) and the computation in equation (29)-equation (32) imply that $(1 - \alpha)P + \alpha I_N$ is invertible if $\alpha \neq -1$.

Finally, since P is (row) stochastic and so is I_N then, for each $i = 1, \dots, N$, we have that

$$\sum_{j=1}^N ((1 - \alpha)P_i + \alpha I_N)_{ij} = (1 - \alpha) \sum_{j=1}^N P_{i,j} + \alpha 1 = (1 - \alpha) 1 + \alpha = 1.$$

Whence, $(1 - \alpha)P + \alpha I_N$ is (row) stochastic also. \square

We now provide a set of *sufficient* condition on α , guaranteeing that the principal logarithm of P_t^α is well-defined. Furthermore, this lemme also shows that for $\alpha \in (0, 1)$ large enough, as a function of N , the matrix $\log(P_t^\alpha)$ is necessarily a valid candidate for a Markov transition matrix (i.e. each of its rows sum to 0).

Lemma 2 (Sufficient Condition for Existence). *If $\alpha \geq 1 - \frac{1}{N^2}$ then if either of the following holds:*

(i) **Real Case:** P_t^α has no complex eigenvalues,

(ii) **Complex Case:** P is doubly stochastic (i.e. row and column stochastic),

then $\log(P_t^\alpha)$ exists and its rows sum to 0.

Proof of Lemma 2. Since P_t^α is an $N \times N$ real (thus complex) matrix with real eigenvalues, then define

$$m \stackrel{\text{def.}}{=} \text{tr}(P_t^\alpha)/N \text{ and } s^2 \stackrel{\text{def.}}{=} \text{tr}((P_t^\alpha)^2)/N - m^2. \quad (33)$$

First, observe that since the entries of P_t (in particular its diagonal elements) are all positive then

$$m = \text{tr}(P_t^\alpha)/N \quad (34)$$

$$= \frac{1}{N} \sum_{i=1}^N ((1-\alpha)\pi_i + \alpha) \quad (35)$$

$$= \frac{1}{N} \left((1-\alpha) \sum_{i=1}^N \pi_i + \alpha \sum_{i=1}^N 1 \right) \quad (36)$$

$$= \frac{1}{N} \left((1-\alpha) + \alpha N \right) \quad (37)$$

$$= \frac{1}{N} \left(1 + \alpha(N-1) \right). \quad (38)$$

Next, we compute s^2 . By Lemma 1, we have that P_t^α is a stochastic matrix and, therefore, so is its square (as the product of stochastic matrices is stochastic). Note that

$$\text{tr}((P_t^\alpha)^2) \leq \max_{S \in \text{Stoch}(N)} \text{tr}(S) = \text{tr}(I_N) = N \quad (39)$$

where $\text{Stoch}(N)$ is the set of $N \times N$ stochastic matrices. Therefore, we bound s^2 , defined in equation (33) using the “extremal trace bound” in equation (39) via

$$s^2 = \text{tr}(P_t^\alpha)/N - m^2 \quad (40)$$

$$\leq N/N - m^2 \quad (41)$$

$$= 1 - \frac{1}{N^2} (1 + \alpha(N-1))^2. \quad (42)$$

That is

$$-s \geq -\left(1 - \frac{1}{N^2} (1 + \alpha(N-1))^2\right)^{1/2}.$$

Now, using lower-bound on the minimal eigenvalue of a square complex matrix with real eigenvalues using m and s in [Wolkowicz & Styan, 1980, Theorem 2.1] we have that

$$\lambda_{\min}(P_t^\alpha) \geq m - s(N-1)^{1/2} \quad (43)$$

$$\geq \frac{1}{N} (1 + \alpha(N-1)) - \left(1 - \frac{1}{N^2} (1 + \alpha(N-1))^2\right)^{1/2} (N-1)^{1/2} \quad (44)$$

$$= \frac{1}{N} (1 + \alpha(N-1)) - \left(N^2 - (1 + \alpha(N-1))^2\right)^{1/2} \frac{(N-1)^{1/2}}{N} \quad (45)$$

$$= \frac{1}{N} \left((1 + \alpha(N-1)) \right. \quad (46)$$

$$\left. - \left[(N-1) \left((1 - \alpha^2)N^2 + 2\alpha(\alpha-1)N - (\alpha-1)^2 \right) \right]^{1/2} \right). \quad (47)$$

If $\alpha \geq 1 - \frac{1}{N^2}$ and $N > 1$ (which is always the case) then

$$\left((1 + \alpha(N-1)) - \left[(N-1) \left((1 - \alpha^2)N^2 + 2\alpha(\alpha-1)N - (\alpha-1)^2 \right) \right]^{1/2} \right) > 0. \quad (48)$$

Therefore, equation (48) together with equation (46) imply that

$$\lambda_{\min}(P_t^\alpha) > 0$$

whenever $\alpha \geq 1 - \frac{1}{N^2}$.

Therefore, [Dunford & Schwartz, 1958, Theorem VII.1.10] implies that $\log(P_t^\alpha)$ exists, since P_t^α is a matrix whose spectrum does not contain $(-\infty, 0]$. Moreover, [Davies, 2010, Lemma 1] guarantees that the rows of $\log(P_t^\alpha)$ sum to 0.

Finally, we note that since I_N is doubly stochastic then so is P_t^α provided that P is. Therefore, \bar{P}_t^α is also a stochastic matrix and so is the product $\bar{P}_t^\alpha P_t^\alpha$ (as the product of (row) stochastic matrices is again a (row) stochastic matrix). Whence

$$s_a^2 \stackrel{\text{def.}}{=} \text{tr}(\bar{P}_t^\alpha P_t^\alpha)/N - m^2 \leq 1 - \frac{1}{N^2} (1 + \alpha(N-1))^2 \quad (49)$$

and the same argument may be applied with s_a^2 in place of s^2 upon using [Wolkowicz & Styan, 1980, Theorem 3.1] in place of [Wolkowicz & Styan, 1980, Theorem 2.1]; however, in this case we do not need to assume that the eigenvalues of P_t^α are real. In either case, this concludes our proof. \square

B.2.1 COMPLETION OF THE PROOF OF THEOREM 2

Proof of Theorem 2. Step 1 - Minimizer of Inner Problem equation (Inner):

Since the elements of the set of $N \times N$ uniform stochastic matrices \mathcal{P}_N^U all have identical rows then, P is an optimizer of equation (Inner) if and only if its first row is a minimizer of

$$\min_{P \in \mathcal{P}_N^U} \sum_{n=1}^N P_{1,n} \ell(Y_t^{(n)}, Y_t) + \frac{1}{\lambda} \sum_{n=1}^N P_{1,n} \log(w_n/N). \quad (50)$$

Since the matrices in \mathcal{P}_N^U are row-stochastic, then all their rows belong to the N simplex Δ_N . Therefore, P is a minimizer of equation (50) if and only if its first row, which we denote by $\pi \stackrel{\text{def.}}{=} (P_{1,1}, \dots, P_{1,N}) \in \Delta_N$ is a minimizer of

$$\min_{\pi \in \Delta_N} \sum_{n=1}^N \pi_n \ell(Y_t^{(n)}, Y_t) + \frac{1}{\lambda} \sum_{n=1}^N \pi_n \log(w_n/N). \quad (51)$$

Since the elements of Δ_N are in bijection with the set of probability measures on the N -point set $\{1, \dots, N\}$, $\lambda > 0$, and $\sum_{n=1}^N \pi_n \log(w_n/N)$ is the KL-divergence (relative entropy) between the probability measure $\sum_{n=1}^N \pi_n \delta_n$ and the uniform measure $\sum_{n=1}^N \frac{1}{N} \delta_n$ (both on $\{1, \dots, N\}$) then [Wang et al., 2020, Proposition 1] the unique minimizer of equation (51) is given by

$$\bar{\pi} \stackrel{\text{def.}}{=} \text{Softmin}(\lambda(\ell(Y^{(n)}, Y))_{n=1}^N).$$

Consequently, the matrix $P \in \mathcal{P}_N^U$ whose rows are π is a minimizer of equation (Inner).

Step 2 - Minimizer of Outer Problem equation (Outer):

By Proposition 2, for every $\alpha(0, 1)$ the matrix

$$P^\alpha \stackrel{\text{def.}}{=} (1 - \alpha)P + \alpha I_N$$

is row-stochastic and for α “large enough”; meaning for $\alpha \in (1 - 1/N, 1)$, the matrix P^α has all its eigenvalues in $(0, \infty)$. Therefore, by [Davies, 2010, Theorem 12] there is a minimizer of equation (Outer) and it is given in closed-form by

$$Q \stackrel{\text{def.}}{=} \text{ReLU}(\log(P_t^\alpha)).$$

This concludes our proof. \square

Proof of Proposition 2. By Lemma 1, the matrix P_t^α is (row) stochastic and invertible. Thus, it has no zero-eigenvalues. If, moreover, the assumption holds that P_t^α has no negative eigenvalues then [Dunford & Schwartz, 1958, Theorem VII.1.10] guarantees that the (principle branch) of the matrix logarithm of P_t^α exists. Consequently, [Davies, 2010, Lemma 1] applies from which we deduce that the rows of $\log(P_t^\alpha)$ sum to 0. The last claim follows directly from Lemma 2 (i). \square

B.3 PROOF OF THE STABILITY GUARANTEE IN PROPOSITION 1

The following generalizes, thus implies, Proposition 1.

Lemma 3 (Maximal KL Divergence for Perturbation in Lemma 1). *Let $\pi \in \Delta_N$, $\alpha \in [0, 1]$, $i = 1, \dots, N$, and let for each $i = 1, \dots, N$ let $\pi^{\alpha, i} = (1 - \alpha)\pi + \alpha e_i$ where $\{e_i\}_{i=1}^N$ is the standard basis of \mathbb{R}^N . If $p_{\min} \stackrel{\text{def.}}{=} \min_{i=1, \dots, N} p_i > 0$ then*

$$\max_{i=1, \dots, N} \text{KL}(\pi | \pi^{\alpha, i}) \leq 2\alpha \left(-\frac{\log(p_{\min})}{1/p_{\min} - 1} - \frac{\log((1 - \alpha)p_{\min})}{1/((1 - \alpha)p_{\min}) - 1} \right).$$

Proof of Lemma 3. By the (sharp) reverse Pinsker inequality in [Binette, 2019, Theorem 1], as formulated in [Binette, 2019, Example A], yields the bound

$$\text{KL}(\pi | \pi^{\alpha, i}) \leq \text{TV}(\pi | \pi^{\alpha, i}) \left(\frac{\log(1/p_{\min})}{1/p_{\min} - 1} + \frac{\log(1/p_{\min}^{\alpha, i})}{1/p_{\min}^{\alpha, i} - 1} \right) \quad (52)$$

where TV is the total variation distance between π and $\pi^{\alpha, i}$, and $p_{\min}^{\alpha, i} = \min_{j=1, \dots, N} \pi_j^{\alpha, i}$. By construction

$$(1 - \alpha)p_{\min} \leq p_{\min}^{\alpha, i} \leq (1 - \alpha)p_{\min} + \alpha.$$

Whence,

$$\frac{1}{p_{\min}^{\alpha, i}} \leq \frac{1}{(1 - \alpha)p_{\min}} \text{ and } \frac{1}{1/p_{\min}^{\alpha, i} - 1} \leq \frac{1}{1/((1 - \alpha)p_{\min} + \alpha) - 1}. \quad (53)$$

Incorporating equation (53) into equation (52) yields

$$\begin{aligned} \text{KL}(\pi | \pi^{\alpha, i}) &\leq \text{TV}(\pi, \pi^{\alpha, i}) \left(-\frac{\log(p_{\min})}{1/p_{\min} - 1} - \frac{\log((1 - \alpha)p_{\min})}{1/((1 - \alpha)p_{\min}) - 1} \right) \\ &= \sum_{j=1}^N |\pi_j - \pi_j^{\alpha, i}| \left(-\frac{\log(p_{\min})}{1/p_{\min} - 1} - \frac{\log((1 - \alpha)p_{\min})}{1/((1 - \alpha)p_{\min}) - 1} \right) \\ &= \sum_{j=1}^N |\alpha\pi_j + \alpha I_{j=i}| \left(-\frac{\log(p_{\min})}{1/p_{\min} - 1} - \frac{\log((1 - \alpha)p_{\min})}{1/((1 - \alpha)p_{\min}) - 1} \right) \\ &\leq \left(\sum_{j=1}^N |\alpha\pi_j| + \alpha \right) \left(-\frac{\log(p_{\min})}{1/p_{\min} - 1} - \frac{\log((1 - \alpha)p_{\min})}{1/((1 - \alpha)p_{\min}) - 1} \right) \\ &\leq \left(\alpha \sum_{j=1}^N |\pi_j| + \alpha \right) \left(-\frac{\log(p_{\min})}{1/p_{\min} - 1} - \frac{\log((1 - \alpha)p_{\min})}{1/((1 - \alpha)p_{\min}) - 1} \right) \\ &\leq \left(\alpha \sum_{j=1}^N \pi_j + \alpha \right) \left(-\frac{\log(p_{\min})}{1/p_{\min} - 1} - \frac{\log((1 - \alpha)p_{\min})}{1/((1 - \alpha)p_{\min}) - 1} \right) \end{aligned} \quad (54)$$

$$\begin{aligned} &\leq (\alpha + \alpha) \left(-\frac{\log(p_{\min})}{1/p_{\min} - 1} - \frac{\log((1 - \alpha)p_{\min})}{1/((1 - \alpha)p_{\min}) - 1} \right) \\ &= 2\alpha \left(-\frac{\log(p_{\min})}{1/p_{\min} - 1} - \frac{\log((1 - \alpha)p_{\min})}{1/((1 - \alpha)p_{\min}) - 1} \right). \end{aligned} \quad (55)$$

where equation (54) held since $\pi \in \Delta_N$ and therefore, $\pi_i \geq 0$ for each $i = 1, \dots, N$, and equation (55) held since $\sum_{i=1}^N \pi_i = 1$ again due to the fact that $\pi \in \Delta_N$. \square

C DATASETS AND BENCHMARKS

C.1 NIFTY DATASET

The News-Informed Financial Trend Yield (NIFTY) dataset Saqur et al. [2024] is a processed and curated daily news headlines dataset for the stock (US Equities) market price movement prediction

task. NIFTY is comprised of two related datasets, **NIFTY-LM** and **NIFTY-RL**. In this section we outline the composition of the two datasets, and comment on additional details.

Dataset statistics . Table 6 and Table 7 present pertinent statistics related to the dataset.

Table 6: Statistics and breakdown of splits sizes

Category	Statistics
Number of data points	2111
Number of Rise/Fall/Neutral label	558 / 433 / 1122
Train/Test/Evaluation split	1477 / 317 / 317

Table 7: Date Ranges of news headlines in splits

Split	Num. Samples	Date range
Train	1477	2010-01-06 to 2017-06-27
Valid	317	2017-06-28 to 2019-02-12
Test	317	2019-02-13 to 2020-09-21

Anticipate the direction of the \$SPY by analyzing market data and news from 2020-02-06.

(a) Instruction component of a π_{LM} policy query x_q .

date, open, high, ..., pct_change, macd, boll_ub, boll_lb, rsi_30, ..., close_60_sma
 2020-01-27, 323.03, 325.12, ..., -0.016, 2.89, 333.77, 319.15, 56.26, ..., 317.40
 2020-01-28, 325.06, 327.85, ..., 0.0105, 2.59, 333.77, 319.55, 59.57, ..., 317.78
 ..., ...
 2020-02-04, 328.07, 330.01, ..., 0.0152, 1.3341, 333.60, 321.26, ..., 319.41
 2020-02-05, 332.27, 333.09, ..., 0.0115, 1.7247, 334.15, 321.73, ..., 319.82

(b) The market’s **history** is provided as the past t days of numerical statistics like the (OHLCV) price (in blue) and common technical indicators (in orange) (e.g. moving averages) data.

Figure 6: Breaking down the instruction or prompt prefix, and market context components of a prompt, x_p .

C.1.1 NIFTY-LM: SFT FINE-TUNING DATASET

The NIFTY-LM prompt dataset was created to finetune and evaluate LLMs on predicting future stock movement given previous market data and news headlines. The dataset was assembled by aggregating information from three distinct sources from January 6, 2010, to September 21, 2020. The compilation includes headlines from The **Wall Street Journal** and **Reuters News**, as well as market data of the \$SPY index from **Yahoo Finance**. The NIFTY-LM dataset consists of:

- **Meta data:** Dates and data ID.
- **Prompt** (x_p): LLM question ($x_{question}$), market data from previous days ($x_{context}$), and news headlines (x_{news}).
- **Response:** Qualitative movement label (x_r) $\in \{Rise, Fall, Neutral\}$, and percentage change of the closing price of the \$SPY index.

To generate LLM questions, ($x_{question}$), the authors used the self-instruct Wang et al. [2023] framework and OpenAI GPT4 to create 20 synthetic variations of the instruction below:

Create 20 variations of the instruction below.
 Examine the given market information and news headlines data on DATE to forecast whether the \$SPY index will rise, fall, or remain unchanged. If you think the movement will be less than 0.5%, then return 'Neutral'. Respond with Rise, Fall, or Neutral and your reasoning in a new paragraph.

Where DATE would be substituted later, during the training phase with a corresponding date.

Context. The key ‘context’ ($x_{context}$) was constructed to have newline delimited market metrics over the past T (≈ 10) days (N.B. Not all market data for the past days for were available and therefore prompts might have less than 10 days of market metrics.).

Table 8 show the details of financial context provided in each day’s sample.

Table 8: Summary of the dataset columns with their respective descriptions.

Column Name	Description
Date	Date of the trading session
Opening Price	Stock’s opening market price
Daily High	Highest trading price of the day
Daily Low	Lowest trading price of the day
Closing Price	Stock’s closing market price
Adjusted Closing Price	Closing price adjusted for splits and dividends
Volume	Total shares traded during the day
Percentage Change	Day-over-day percentage change in closing price
MACD	Momentum indicator showing the relationship between two moving averages
Bollinger Upper Band	Upper boundary of the Bollinger Bands, set at two standard deviations above the average
Bollinger Lower Band	Lower boundary, set at two standard deviations below the average
30-Day RSI	Momentum oscillator measuring speed and change of price movements
30-Day CCI	Indicator identifying cyclical trends over 30 days
30-Day DX	Indicates the strength of price trends over 30 days
30-Day SMA	Average closing price over the past 30 days
60-Day SMA	Average closing price over the past 60 days

News Headlines. (x_{news}): Final list of filtered headlines from the aggregation pipeline. The non-finance related headlines were filtered out by performing a similarity search with SBERT model, "all-MiniLM-L6-v2" Reimers & Gurevych [2019]. Each headline was compared to a set of artificially generated financial headlines generated by GPT-4, with the prompt "Generate 20 financial news headlines". Headlines with a similarity score below 0.2, were excluded from the dataset. To respect the prompting ‘context length’ of LLMs, in instances where the prompt exceeded a length of 3000 words, a further refinement process was employed. This process involved the elimination of words with a tf-idf Sammut & Webb [2010] score below 0.2 and truncating the prompt to a maximum of 3000 words.

It is also important to note that the dataset does not encompass all calendar dates within the specified time range. This limitation emanates from the trading calendar days, and absence of relevant financial news headlines for certain dates.

Label. (x_r): The label is determined by the percentage change in closing prices from one day to the next, as defined in equation 56. This percentage change is categorized into three labels: {Rise, Fall, Neutral}, based on the thresholds specified in equation 57.

$$PCT_{\text{change}} = \left(\frac{\text{Closing Price}_t - \text{Closing Price}_{t-1}}{\text{Closing Price}_{t-1}} \right) \times 100\% \quad (56)$$

$$x_r = \begin{cases} \text{Fall} & \text{if } PCT_{\text{change}} < -0.5\% \\ \text{Neutral} & \text{if } -0.5\% \leq PCT_{\text{change}} \leq 0.5\% \\ \text{Rise} & \text{if } PCT_{\text{change}} > 0.5\% \end{cases} \quad (57)$$

C.2 NIFTY-RL: PREFERENCES DATASET

The preference dataset is a variation of the fine-tuning dataset and it is designed for alignment training of LLMs using reward model. In NIFTY-RL, labels are omitted and replaced with chosen and rejected results. The chosen result is a label corresponding to a rise, a fall or neutral movement in the stock market and is equivalent to the response in NIFTY-LM. The rejected result is a random label not equal to the chosen label.

- **Metadata:** Includes dates and data identifiers.

- **Prompt** (x_p): Includes an LLM instruction ($x_{question}$), preceding market data ($x_{context}$), and relevant news headlines (x_{news}).
- **Chosen Result**: A qualitative movement label (x_r) from $\{Rise, Fall, Neutral\}$ indicating the predicted market trend.
- **Rejected Result**: A label (\bar{x}_r) randomly selected from $\{Rise, Fall, Neutral, Surrender\} \setminus \{x_r\}$, representing an incorrect market prediction.

C.3 FLARE BENCHMARK DATASETS

Stock Movement Prediction Datasets and Tasks: Flare-SM tasks. FLARE proposed by Xie et al. [2023], extends to include one financial prediction task – the CIKM dataset Wu et al. [2018] as an evaluation task among (four) other general financial NLP tasks. Under the hood, this benchmark is a fork of the ‘lm-eval’ harness Gao et al. [2021] with addendums. Other stock price movement prediction from social dataset include what is referred to as ACL18 (or, ‘acl18’) in this paper is essentially the **StockNet** Xu & Cohen [2018] dataset which comprises of stock tweets of 88 stock tickers from 9 financial market industries from Twitter over two years (from 2014-2015) aligned with their corresponding historical price data. **BigData22** [Soun et al., 2022] is another more recent tweets dataset comprising of tweets about 50 stock tickers during the period 2019-07-05 to 2020-06-30.

Table 9: Summary of Flare stock price movement datasets. The ‘Stocks’ column indicates the total number of different stock tickers referenced. The ‘Tweets’ and ‘Days’ columns represent the number of tweets and days respectively in each dataset.

Data	Stocks	Tweets	Days	Start Date	End Date
ACL18	87	106,271	696	2014-01-02	2015-12-30
BigData22	50	272,762	362	2019-07-05	2020-06-30
CIKM18	38	955,788	352	2017-01-03	2017-12-28

D ADDITIONAL BACKGROUND MATERIAL

In an effort to keep our paper as self-contained as possible, this section contains additional background material used in our derivations and in the formulations of our technical results.

D.1 MATRIX LOGARITHMS

The (principal) logarithm of an $N \times N$ matrix A whose spectrum does not contain $(-\infty, 0]$ in \mathbb{C} is defined by

$$\log(A) \stackrel{\text{def}}{=} \frac{1}{2\pi i} \int_{\gamma} \log(z) (zI_N - A)^{-1} dz$$

where $\log(z)$ is the principal logarithm of z (in the complex plane) and γ is a closed curve in $\mathbb{C} \setminus (-\infty, 0]$ containing the eigenspectrum of A .

D.2 THE SHIRAYEV-WONHAM FILTER

To keep our paper as self-contained as possible, we included some brief background on *stochastic filtering*. Namely, this appendix contains background material on the Shirayev-Wonham (stochastic) filter, studied in [Liptser & Shiryaev, 2001b, Chapter 9].

Consider a complete probability space (Ω, \mathcal{F}, P) equipped with a non-decreasing sequence of right-continuous sub- σ -algebras $\mathcal{F}_t, 0 \leq t \leq T$. Let $\theta = (\theta_t, \mathcal{F}_t), 0 \leq t \leq T$, denote a real right-continuous Markov process taking values in the countable set $E = \{\alpha, \beta, \gamma, \dots\}$. Additionally, let $W = (W_t, \mathcal{F}_t), 0 \leq t \leq T$, be a standard Wiener process independent of θ , and let ξ_0 be a \mathcal{F}_0 -measurable random variable independent of θ . We assume the existence of nonanticipative functionals $A_t(\epsilon, x)$ and $B_t(x)$ that define

$$d\xi_t = A_t(\theta_t, \xi)dt + B_t(\xi)dW_t \quad (58)$$

and satisfy the following conditions.

$$A_t^2(\epsilon_t, x) \leq L_1 \int_0^t (1 + x_s^2) dK(s) + L_2(1 + \epsilon_t^2 + x_t^2), \quad (59)$$

$$0 < C \leq B_t^2(x) \leq L_1 \int_0^t (1 + x_s^2) dK(s) + L_2(1 + x_t^2), \quad (60)$$

$$|A_t(\epsilon_t, x) - A_t(\epsilon_t, y)|^2 + |B_t(x) - B_t(y)|^2 \leq L_1 \int_0^t (x_s - y_s)^2 dK(s) + L_2(x_t - y_t)^2, \quad (61)$$

where C, L_1, L_2 are certain constants, $K(s)$ is a non-decreasing right continuous function, $0 \leq K(s) \leq 1, x \in C_T, y \in C_T, \epsilon_t \in E, 0 \leq t \leq T$.

Along with Equations (59) to (61) it will also be assumed that

$$M\xi_0^2 < \infty, \quad (62)$$

and

$$M \int_0^T \theta_t^2 dt < \infty. \quad (63)$$

Define

$$p_\beta(t) \stackrel{\text{def.}}{=} P(\theta_t = \beta),$$

$$p_{\beta\alpha}(t, s) \stackrel{\text{def.}}{=} P(\theta_t = \beta | \theta_s = \alpha), \quad 0 \leq s < t \leq T, \quad \beta, \alpha \in E,$$

and assume there exist a function $\lambda_{\alpha\beta}(t), 0 \leq t \leq T, \alpha, \beta \in E$, that is

$$\text{continuous over } t, \text{ (uniformly over } \alpha, \beta) \quad (64)$$

$$|\lambda_{\alpha\beta}(t)| \leq K \quad (65)$$

$$|p_{\beta\alpha}(t + \Delta, t) - \delta(\beta, \alpha) - \lambda_{\alpha\beta}(t) \cdot \Delta| \leq o(\Delta), \quad (66)$$

where $\delta(\beta, \alpha)$ is a Kronecker's symbol and the value $o(\Delta)/\Delta \rightarrow 0$ as $\Delta \rightarrow 0$ (uniformly over α, β).

Let the Equations (59) to (66) be fulfilled. Then the a posteriori probability $\pi_\beta(t), \beta \in \mathcal{E}$, satisfies a system of equations

$$\pi_\beta(t) = p_\beta(0) + \int_0^t \mathcal{L}^* \pi_\beta(u) du + \int_0^t \pi_\beta(u) \frac{A_u(\beta, \xi) - \bar{A}_u(\xi)}{B_u(\xi)} d\bar{W}_u,$$

where

$$\mathcal{L}^* \pi_\beta(u) = \sum_{\gamma \in \mathcal{E}} \lambda_{\gamma\beta}(u) \pi_\gamma(u) \quad \text{and} \quad \bar{A}_u(\xi) = \sum_{\gamma \in \mathcal{E}} A_u(\gamma, \xi) \pi_\gamma(u),$$

and $\bar{W} = (\bar{W}_t, \mathcal{F}_t)$ is a Wiener process with


$$\bar{W}_t = \int_0^t \frac{d\xi_u - \bar{A}_u(\xi)}{B_u(\xi)} du.$$

E ADDITIONAL DISCUSSIONS


We have updated the anonymous git [repo](#) with all the experiment results and added script to easily replicate the main results of the paper in Table 2.

E.1 F1-MEASURE IN FMM TASK

For evaluation of model performances on the financial market movement (FMM) task using ternary class labels, we use the [scikit-learn](#) library methods. For multi-class, n , labels (with $n > 2$), the choice of *averaging* is important. The tabulated results were evaluated with default averaging set to “*weighted*” – where metrics for each label were calculated, then average weighted by their corresponding support (the number of true instances for each label). This alters the global averaging ‘macro’ (equal weight) for label imbalance. Imbalanced label support can result in an F-score that is lower or not in between precision and recall.



(a) Llama-class models.



(b) Mixture-of-experts class models and the state-of-the-art GPT-4 model.

Figure 7: Confusion matrices for Table 2. The first row highlights the Llama-class models, and the second row focuses on mixture-of-experts and GPT-4 models.

E.2 TIME-SERIES FORECASTING EXPERIMENTS: ADDITIONAL DETAILS

This section provides additional discussion in support of the long-horizon time-series forecasting (LTSF) experiment covered in §5.2.

E.2.1 FORECASTING GRANULARITY IN TIME-SERIES FORECASTING: IMS vs. DMS

In LTSF works, the decoding granularity is dichotomized in the following two categories:

I) Iterated/Incremental Multi-step (IMS). : This is auto-regressive language-modeling or generative style prediction decoding where each step in prediction horizon H is iteratively predicted: \hat{x}_{t+1} , and is used for the prediction for the subsequent time-step. The common limitations of such forecasting granularity is ‘error accumulation’ over time as the decoder builds on the error from previous steps while iteratively making subsequent predictions. Additionally, the run-time complexity is to the order of the length of the horizon H .

II) Direct Multi-step (DMS). : As the name implies, in this decoding or forecasting approach, the entire forecasting horizon H is predicted at one go: $\hat{x}_{t+1:t+H}$. While computationally more attractive

(much faster than IMS), this approach may not incorporate seasonality/periodicity in the time-series. Modern TSF specialist models, especially the transformer-based TSF architectures, tend to follow this scheme to avoid the quadratic cost (to the length of input) associated with attention.

E.2.2 CHANNEL INDEPENDENT STRATEGY

Recent advancements in Long-Term Series Forecasting (LTSF) have increasingly embraced a **Channel Independent (CI) approach** for handling multivariate time series data [Han et al. \[2024\]](#). The CI strategy simplifies forecasting by isolating each (channel or feature as) univariate time series within the dataset, allowing the model to focus on predicting individual channels independently. Unlike traditional methods that leverage the entire multivariate historical data to make forecasts, the CI approach seeks a shared function $f : x_{t-L+1:t}^{(i)} \in \mathbb{R}^L \rightarrow \hat{x}_{t+1:t+H}^{(i)} \in \mathbb{R}^H$ for each univariate series, providing a streamlined model for each channel and reducing the need to account for inter-channel dependencies.

E.2.3 OUR SETUP

For our experiments, the historical observation window (*aka. look-back window or lag period*), L , is kept constant at 720 time-steps to be consistent and comparable with the literature. We follow the channel-independent strategy similar to the three expert models used for filtering - giving us C number of distinct features or channels of an agent’s observation. The (MSE) loss is then measured as the discrepancy between the predicted values $\bar{x}_{t+1:t+H}^{(i)}$ and the ground truth $y_{t+1:t+H}^{(i)}$ as

$$\mathcal{L} = \frac{1}{C} \sum_{i=1}^C \|y_{t+1:t+H}^{(i)} - \bar{x}_{t+1:t+H}^{(i)}\|_2^2. \quad (67)$$