
GUI-WORLD: A GUI-oriented Video Dataset for Multimodal LLM-based Agents

Anonymous Author(s)

Affiliation

Address

email



Figure 1: GUI-WORLD: a comprehensive dataset for GUI understanding, holding significant potential for real-world applications. All screenshots that appeared are samples in our dataset.

Abstract

1 Recently, Multimodal Large Language Models (MLLMs) have been used as agents
2 to control keyboard and mouse inputs by directly perceiving the Graphical User
3 Interface (GUI) and generating corresponding code. However, current agents
4 primarily exhibit excellent understanding capabilities in static environments and
5 are predominantly applied in relatively simple domains, such as Web or mobile
6 interfaces. We argue that a robust GUI agent should be capable of perceiving
7 temporal information on the GUI, including dynamic Web content and multi-step
8 tasks. Additionally, it should possess a comprehensive understanding of various
9 GUI scenarios, including desktop software and multi-window interactions. To this
10 end, this paper introduces a new dataset, termed GUI-WORLD, which features
11 meticulously crafted Human-MLLM annotations, extensively covering six GUI
12 scenarios and eight types of GUI-oriented questions in three formats. We evaluate
13 the capabilities of current state-of-the-art MLLMs, including ImageLLMs and
14 VideoLLMs, in understanding various types of GUI content, especially dynamic
15 and sequential content. Our findings reveal that ImageLLMs struggle with dynamic
16 GUI content without manually annotated keyframes or operation history. On the
17 other hand, VideoLLMs fall short in all GUI-oriented tasks given the sparse GUI
18 video dataset. Based on GUI-WORLD, we take the initial step of leveraging a
19 fine-tuned VideoLLM as a GUI agent, demonstrating an improved understanding
20 of various GUI tasks. However, due to the limitations in the performance of base
21 LLMs, we conclude that using VideoLLMs as GUI agents remains a significant
22 challenge. We believe our work provides valuable insights for future research in
23 dynamic GUI content understanding.

24 1 Introduction

25 Multimodal Large Language Models (MLLMs), such as GPT-4V(ision) [1] and LLaVA [2], have
26 significantly contributed to the development of the visual-text domain [3]. These models bring forth
27 innovative solutions and paradigms for traditional visual tasks, including visual reasoning [4], medical
28 image interpretation [5, 6], and applications in embodied agents [7]. One particularly promising area
29 is Graphical User Interface (GUI) understanding, which holds significant potential for real-world
30 applications, such as webpage comprehension [8, 9] and navigation by GUI agents [10–12]. The key
31 challenges of GUI understanding are twofold: effective GUI agents are expected to (1) possess a deep
32 understanding of GUI elements, including webpage icons, text identified through Optical Character
33 Recognition (OCR), and page layouts, and (2) exhibit an exceptional ability to follow instructions
34 within GUI contexts, such as conducting searches through search engines.

35 Despite significant progress, as illustrated in Table 1, existing works suffer from the following
36 limitations: (1) Most studies predominantly focus on the static features of GUI scenarios, neglecting
37 the need for MLLMs to effectively process sequential information and dynamic operations. For
38 instance, an agent’s task performance can be disrupted by unexpected elements such as pop-up
39 advertisements, underscoring a gap in handling dynamic sequential tasks. (2) Current research
40 is typically restricted to Web-based environments, which limits the models’ generalization and
41 robustness. For instance, GUI agents may need to operate across diverse platforms such as Windows,
42 macOS, Linux, iOS, Android, and XR environments. Additionally, operations may sometimes
43 involve multiple windows. Therefore, expanding the scope of research to encompass these varied
44 environments will enhance the adaptability and effectiveness of GUI agents.

45 To mitigate these gaps, this paper introduces GUI-WORLD, a comprehensive dataset containing
46 12,379 GUI videos, specifically designed to evaluate and enhance the capabilities of GUI agents.
47 This dataset encompasses a wide range of GUI scenarios, including popular websites, desktop and
48 mobile applications across various operating systems, multi-window interactions, as well as XR
49 environments. The data collection process involves sourcing GUI videos from screen recordings and
50 instructional videos on YouTube. Subsequently, we utilize an Human-MLLM collaborative approach
51 to generate a diverse set of questions and instructions and finally construct GUI-WORLD.

52 Likewise, we also establish a comprehensive benchmark for GUI understanding, which encompasses
53 seven mainstream MLLMs, three keyframe selection strategies, six GUI scenarios, and a diverse
54 array of queries in multiple-choice, free-form, and conversational formats, aiming to provide a
55 thorough evaluation of the MLLMs’ GUI-oriented capabilities. As shown in Figure 2, the assessment
56 results indicate that most MLLMs struggle with GUI-WORLD, highlighting their limited dynamic
57 understanding of graphical interfaces and underscoring the need for further enhancement.

58 Leveraging this dataset, we take the first step of fine-tuning a Video GUI Agent proficient in dynamic
59 and sequential GUI tasks, which results in significant improvements in the general capabilities of GUI
60 agents, thereby demonstrating the utility and effectiveness of GUI-WORLD. Additionally, we delve
61 into discussing various factors critical to GUI understanding, including the integration of textual
62 information, the number of keyframes, and image resolutions.

63 Overall, the key contributions of this paper are three-fold:

64 ▷ **A New Dataset.** We propose GUI-WORLD, a comprehensive GUI dataset comprising 12,379
65 videos specifically designed to assess and improve the GUI understanding capabilities of MLLMs,
66 spanning a range of categories and scenarios, including desktop, mobile, and extended reality (XR),
67 and representing the first GUI-oriented instruction-tuning dataset in the video domain.

68 ▷ **A Novel Model.** Based on GUI-WORLD, we propose GUI-Vid, a GUI-oriented VideoLLM
69 with enhanced capabilities to handle various and complex GUI tasks. GUI-Vid shows a significant
70 improvement on the benchmark and achieves results comparable to the top-performing models.

71 ▷ **Comprehensive Experiments and Valuable Insights.** Our experiments indicate that most existing
72 MLLMs continue to face challenges with GUI-oriented tasks, particularly in sequential and dynamic
73 GUI content. Empirical findings suggest that improvements in vision perception, along with an
74 increase in the number of keyframes and higher resolution, can boost performance in GUI-oriented
75 tasks, thereby paving the way for the future of GUI agents.




Figure 2: Comparative performance of different MLLMs in six scenarios of GUI-WORLD. (a) Performance of four mainstream Image LLMs. (b) Performance of three Video LLMs and our **GUI-Vid**. (c) Performance among six methods. See [subsection 4.2](#) for more details.

Table 1: Comparison of GUI datasets and benchmarks. ‘Sem.’: semantic instruction level, ‘VL’: Vision-Language, ‘Seq.’: Tasks for sequential images, ‘Cro.’: Cross-app or multi-window tasks, ‘Dyn.’: Tasks for dynamic GUI content.

Dataset	Size	Sem.	VL	Video	Env Type				Task Coverage			Task
					Web.	Mob.	Desk.	XR	Seq.	Cro.	Dyn.	
Rico [13]	72,219	Low	✓	✓	✗	✓	✗	✗	✓	✓	✗	UI Code/Layout Generation Mobile Navigation
MetaGUI [14]	1,125	Low	✓	✗	✗	✓	✗	✗	✓	✗	✗	
UGIF [15]	523	High	✓	✗	✗	✓	✗	✗	✓	✗	✗	UI Grounded Instruction Following GUI Understanding
AITW [16]	715,142	High	✓	✗	✗	✓	✗	✗	✓	✓	✗	
Ferret-UI [17]	123,702	Low	✓	✗	✗	✓	✗	✗	✗	✗	✗	UI Grounding & Understanding Web Navigation
MiniWoB++ [18]	100	Low	✓	✗	✓	✗	✗	✗	✗	✗	✗	
WebArena [19]	812	Low	✓	✗	✓	✗	✗	✗	✓	✗	✗	Web Navigation
Mind2Web [20]	2,350	Both	✓	✓	✓	✗	✗	✗	✓	✗	✗	Web Navigation
OmniAct [21]	9,802	Low	✓	✗	✓	✗	✓	✗	✓	✗	✗	Code Generation
MMINA [22]	1,050	Low	✓	✗	✓	✗	✗	✗	✓	✓	✗	Web Navigation
AgentStudio [23]	304	High	✓	✗	✓	✗	✓	✗	✓	✓	✗	General Control
OSWorld [24]	369	High	✓	✗	✓	✗	✓	✗	✓	✓	✗	General Control
GUI-WORLD (Ours)	12,379	Both	✓	✓	✓	✓	✓	✓	✓	✓	✓	GUI Understanding Instruction Following

76 2 GUI-WORLD: A Comprehensive Dataset for GUI Understanding

77 2.1 Overview

78 We introduce GUI-WORLD, a comprehensive dataset covering six GUI scenarios including video,
 79 human-annotated keyframes, as well as detailed captions and diverse types of QA produced by
 80 our data curation framework, aiming at benchmarking and enhancing the general GUI-oriented
 81 capabilities. These GUI scenarios encompass desktop operating systems (*e.g.*, macOS, Windows) and
 82 mobile platforms (*e.g.*, Android and iOS), websites, software, and even extended-range technologies
 83 (XR) (*e.g.*, GUI in Apple Vision Pro [25]). We divide the dataset into a train-test split, each containing
 84 10,702 and 1,677 samples. Discussion for each scenario is in [subsection B.1](#).




Figure 3: An overview construction pipeline of GUI-WORLD.

85 As illustrated in [Figure 3](#), the development of GUI-WORLD is structured around a two-stage process.
 86 Details regarding video and query statistics are provided in [Table 2](#), which includes distributions of
 87 the number of keyframes, video lengths, and the lengths of queries and their corresponding golden
 88 answers, as displayed in [Figure 4](#). Refer to [Figure 5](#) and [Appendix G](#) for case study.

Table 2: The statistics of GUI-WORLD. For Android, we select videos from Rico [13] and randomly sample 10 frames. *Avg. Frame* refers to the average number of frames in each keyframe, and *Avg. Anno.* refers to the average number of manually annotated user actions in each keyframe.

Category	Total Videos	Free-form	MCQA	Conversation	Total Frame. (Avg.)	Avg. Anno.
Software	4,720	27,840	9,440	9,440	23,520 (4.983)	7.558
Website	2,499	14,994	4,998	4,998	15,371 (6.151)	6.862
IOS	492	2,952	984	984	2,194 (4.459)	7.067
Multi	475	2,850	950	950	2,507 (5.277)	7.197
XR	393	2,358	786	786	1,584 (4.030)	10.970
Android	3,800	15,199	7,600	7,600	38,000 (10.000)	-
Summary	12,379	76,673	24,758	24,758	83,176 (6.719)	7.463




Figure 4: Left: Distribution of the number of keyframes and video lengths. Right: Length distribution for each type of question and its golden answer.

89 2.2 GUI Video Collection and Keyframe Annotation Process

90 We describe the pipeline for collecting screen recordings from student workers and GUI-related
 91 instructional videos from YouTube for GUI-WORLD and the procedures followed to convert these
 92 videos into keyframe sequences.

93 A significant portion of our video data is derived from screen recordings executed by student workers,
 94 which can directly reflect real-life GUI usage scenarios. A typical video collection scenario involves
 95 assigning a student worker a specific software task. The student begins by familiarizing themselves
 96 with the software, followed by recording a series of operations in a short video clip, such as “Sign
 97 up”, “Sign in”, “Create a New Page”, and “Invite Other Collaborators” in the software “Notion¹”.

98 Despite the high fidelity of these manually recorded videos, we encounter several challenges: (1)
 99 Student workers often require substantial time to acquaint themselves with professional software
 100 (*e.g.*, MATLAB, Adobe After Effects (Ae)), which can hinder the progress of data collection. (2)
 101 The videos may lack comprehensiveness, typically capturing only commonly used operations and
 102 overlooking rarer functions crucial for dataset completeness. To address these issues, we also source
 103 videos from social media platforms that host a diverse array of GUI-related content. Specifically, we
 104 download tutorial videos from YouTube—given its prevalence as a video-sharing platform—because
 105 they richly detail various GUI operations. These videos are then segmented into shorter clips, each
 106 representing a distinct sequence of operations.

107 The subsequent step involves annotating these video clips with keyframes and textual descriptions of
 108 each keyframe using custom-designed annotation software. Although several algorithms exist for
 109 keyframe extraction [26–29], they typically underperform with GUI videos where changes between
 110 frames might be minimal (*e.g.*, a slight movement in the mouse cursor). To ensure high-quality
 111 datasets, we therefore perform manual extraction of these keyframes. Each keyframe is meticulously
 112 annotated to include details such as the operation performed, the purpose between two keyframes, the
 113 software or website used, mouse actions (*e.g.*, scroll, click), and keyboard inputs (*e.g.*, copy (Ctrl +
 114 C), paste (Ctrl + V), specific input). We detail our annotation process in [subsection B.3](#).

115 2.3 GUI Tasks Generation from Human-MLLM Collaboration

116 Drawing insights from prior research [30–34], we develop a Human-MLLM collaboration pipeline to
 117 annotate captions and diverse types of QA specifically tailored for GUI comprehension. The process
 118 involves inputting an instructional prompt, a comprehensive description, key information (*e.g.*, system
 119 or application), and a sequence of human-annotated keyframes into GPT-4V. As depicted in [Table 9](#),
 120 GUI-WORLD features an array of question types, as detailed in follows:

¹<https://www.notion.so/>




Figure 5: An example in multi-window GUI scene as a case study.

121 ▷ **Detailed and Summarized Captioning:** This task challenges basic GUI knowledge and multimodal
 122 perception, also addressing the deficiency of detailed GUI content in video-caption pairs. Initially,
 123 GPT-4V generates two distinct descriptions for each video: one concentrating on fine-grained details
 124 and the other on the overall image sequences. Furthermore, GPT-4V provides a succinct summary,
 125 highlighting core operations and overarching objectives in the video.

126 ▷ **Static GUI Content:** This task challenges MLLM with textual, layout, and iconographic analysis
 127 of static GUI content. We instruct GPT-4V to generate free-form queries with a golden answer
 128 concerning static GUI elements or specific scenes that recur in more than two keyframes, ensuring
 129 their consistent presence in the video. Additionally, GPT-4V also crafts QA pairs that evaluate
 130 inferential skills in static content, focusing on interrelations among icons or textual information.

131 ▷ **Dynamic and Sequential GUI Content:** This task concentrates on temporal content in GUI
 132 video, such as dynamically changing interfaces, and aims to elucidate the sequential information and
 133 reasoning chains within GUI content. We direct GPT-4V to identify consistently changing elements to
 134 create queries for dynamic content. Moreover, predictive tasks are formulated on order and temporal
 135 relation in provided sequential images, challenging agents to anticipate future events or states.

136 In the last stage, human annotators will follow the guideline in [subsection B.3](#) and carefully review
 137 the entire video and MLLM-generated QA pairs to correct inaccuracies and hallucinations, as well as
 138 supplement information for both questions and answers to **make these tasks more challenging**.

139 3 Progressive Enhancement on GUI Perception Ability

140 We introduce our strategy to enhance the GUI-oriented capabilities of current MLLMs on both static
 141 and dynamic GUI content. Inspired by previous studies [9, 35], we structure our methodology into
 142 two distinct fine-tuning stages, as illustrated in [Figure 6](#). Initially, we fine-tune the MLLM on simpler

143 tasks, such as description queries and captioning exercises, to instill a basic understanding of GUI
 144 elements. Subsequently, building on this foundation, the second stage aims to augment the MLLM’s
 145 proficiency with more complex and challenging tasks. Our fine-tuning is all based on the Supervised
 146 Fine-Tuning (SFT): $\mathcal{L}_{\text{SFT}}(\pi_\theta) = -\mathbb{E}_{(x,y)\sim\mathcal{D}}[\log \pi_\theta(y | x)]$, where x is the input, y is LLMs’ output,
 147 and π_θ denotes the model parameters that need to be optimized.




Figure 6: An overview of our fine-tuning architecture, focusing on 1) GUI content alignment and 2) GUI-oriented tasks instruction tuning.

148 **Stage-1: Learning Preliminary for GUI Content.** The initial phase focuses on aligning GUI
 149 content with a pre-trained vision encoder and a base LLM, utilizing GUI videos accompanied by
 150 detailed descriptions and captions. This phase aims to embed a robust understanding of fundamental
 151 GUI concepts and terminology within the MLLM. By engaging the model in basically captioning
 152 various GUI components, the model learns to recognize and articulate the functionalities and visual
 153 characteristics of these elements, thereby laying a solid groundwork for GUI knowledge.

154 **Stage-2: Mastering Advanced GUI Capability.** Building on the foundational knowledge estab-
 155 lished in Stage 1, the second stage focuses on advancing the MLLM’s proficiency in interacting
 156 with GUI elements through more complex tasks. These tasks are designed to simulate real-world
 157 scenarios that the MLLM might encounter in GUI environments, which include predicting based on
 158 image sequences, engaging in conversations, retrieving both static and dynamic GUI elements, and
 159 performing reasoning tasks.

160 As illustrated in Figure 6, We employ the two-stage training architecture utilizing VideoChat2
 161 [35] as our foundational model. Initially, videos and images are encoded using the UMT-L visual
 162 encoder [36]. Subsequently, a QFormer compresses visual tokens into a smaller set of query tokens.
 163 Drawing inspiration from [37], we enhance the QFormer [38] by integrating instructions to enable it
 164 to extract visual representations pertinent to the given instructions. Additionally, we apply low-rank
 165 adaptation (LoRA [39]) to base LLM. This model is concurrently fine-tuned with the visual encoder
 166 and QFormer using a Vision-grounded Text Generation (VTG) loss: $\mathcal{L}_{\text{VTG}}(\theta) = -\mathbb{E}[\log p(y|v; \theta)]$,
 167 where v represents the visual tokens derived from the QFormer, and y represents the text output
 168 grounded in the visual context. Training dataset and details can be found in Appendix D.

169 4 Experiments and Analysis

170 4.1 Experimental Setups

171 **Models.**² We conduct evaluations on four of the most popular ImageLLMs: GPT-4V(ision) [1],
 172 GPT-4o [40], Qwen-VL-Max [41], and Gemini-Pro-1.5 [42]. We benchmark on three keyframe
 173 selection settings: (1) *Random*, where frames are sampled at fixed time intervals within a video;
 174 (2) *Extracted*, with keyframes extracted using Katna [43], and ablation study with UVD [44] in
 175 VIP [45] and R3M [46] settings; and (3) *Human*, where keyframes are selected by humans during
 176 the annotation process. **For the *Random* and *Extracted* settings, we input 10 frames into each
 177 MLLM, while the *Human* setting uses an average of 6.719 frames, as detailed in Table 2.**
 178 Each model’s responses employ a three-step Chain-of-Thought (CoT) [47] process, i.e., “Describe-
 179 Analyze-Answer”, to evaluate their peak performance. Additionally, we assessed three advanced
 180 VideoLLMs—ChatUnivi [48], Minigtpt4-video [49], and Videochat2 [50]—for their performance on
 181 GUI content. Detailed experimental setups are referred to Appendix D. Comparison to some recently
 182 released VideoLLMs—VideoLLaVA [51] and LLaVA-Next [52]—are referred to Appendix E.

183 **Evaluation Metrics.** To assess free-form questions and multiple-round conversations, we utilize
 184 the LLM-as-a-Judge methodology, which assigns a similarity score ranging from 1 to 5 between

²Given that GPT-4V was announced to be deprecated during our paper writing, we used GPT-4o to conduct some ablation studies instead of GPT-4V, aiming to ensure our results provide longer-term reference value.

Table 3: The overall performance in six GUI scenarios for MCQA and Free-form queries. ‘R.’, ‘E.’, and ‘H.’ denote random-selected, programmatic-selected, and human-selected keyframes, respectively. ‘MC’ means Multiple-Choice QA and ‘Free’ represents the average score of all free-form and conversational queries.

Models	Setting	Software		Website		XR		Multi		IOS		Android		Avg.			
		MC	Free	MC	Free	MC	Free	MC	Free	MC	Free	MC	Free	MC	Free		
ImageLLMs	Gemini-Pro-1.5	R.	81.7%	3.339	82.6%	3.452	81.2%	3.154	81.2%	2.959	82.0%	3.213	81.6%	3.220	81.7%	3.223	
		E.	78.5%	3.152	77.8%	3.215	80.8%	3.006	71.8%	2.777	79.3%	3.007	78.5%	3.168	77.8%	3.054	
	Qwen-VL-Max	R.	74.9%	2.676	76.9%	2.656	74.2%	2.469	68.8%	2.432	75.4%	2.779	73.7%	2.309	74.0%	2.553	
		E.	74.3%	2.624	75.8%	2.627	69.0%	2.499	64.8%	2.362	77.4%	2.659	65.8%	2.277	71.2%	2.508	
	GPT-4V	H.	75.8%	2.651	75.5%	2.698	77.6%	2.373	66.9%	2.490	74.3%	2.633	-	-	74.0%	2.569	
		R.	81.5%	3.589	80.9%	3.648	80.6%	3.200	75.0%	3.452	82.5%	3.614	78.3%	3.515	79.8%	3.503	
		E.	85.1%	3.407	80.1%	3.433	81.8%	2.892	81.9%	3.219	86.4%	3.427	79.9%	3.176	82.6%	3.259	
	GPT-4o	H.	86.0%	3.520	79.8%	3.655	83.4%	3.265	76.9%	3.449	79.9%	3.453	-	-	81.2%	3.469	
		H.	86.5%	3.644	83.3%	3.740	84.3%	3.285	81.1%	3.654	83.3%	3.558	90.0%	3.561	84.8%	3.573	
	VideoLLMs	ChatUnivi	-	28.4%	2.389	22.2%	2.349	20.6%	2.161	17.5%	2.275	22.6%	2.337	23.0%	2.390	22.4%	2.317
		Minigt4Video	-	18.9%	1.475	15.3%	1.520	16.3%	1.362	15.4%	1.457	20.1%	1.501	14.6%	1.342	16.8%	1.443
		VideoChat2	-	45.5%	2.144	42.6%	2.221	44.0%	2.005	40.4%	2.222	40.2%	2.169	44.7%	2.119	42.9%	2.147
GUI-Vid		-	59.9%	2.847	54.1%	2.957	55.6%	2.764	52.9%	2.861	51.8%	2.773	53.4%	2.572	54.6%	2.796	

Table 4: Overall performance in six GUI scenarios for MCQA and Free-form queries. ‘D.C.’ means providing detailed caption, and ‘C.C.’ means concise caption, and **X** means no vision input.

Models	Setting		Software		Website		XR		Multi		IOS		Android		Avg.	
	Vision	Text	MC	Free	MC	Free	MC	Free	MC	Free	MC	Free	MC	Free	MC	Free
GPT-4V	X	D.C.	85.0%	3.350	83.1%	3.380	82.3%	3.056	84.2%	3.358	81.6%	2.751	81.7%	3.427	83.0%	3.316
	X	C.C.	80.7%	3.028	72.2%	3.025	82.8%	2.809	81.3%	3.160	76.5%	2.868	76.4%	2.939	78.3%	2.971
	✓	D.C.	82.5%	3.494	83.2%	3.682	85.9%	3.191	83.9%	3.617	80.9%	3.516	84.9%	3.758	83.5%	3.543

185 MLLM’s response and a predefined golden answer, already validated by previous studies[53–55]. For
 186 a comprehensive evaluation, we also provide BLEU [56] and BERTScore [57] in Appendix E. For
 187 multiple-choice questions, we measure performance using accuracy as the primary evaluation metric.

188 **Textual Information Integration.** To investigate the effectiveness of integrating image-caption
 189 models to enlarge the context window for LLMs—typically employed in natural videos—and the
 190 helpfulness of GUI history content in accomplishing GUI-oriented tasks, we implement three ex-
 191 perimental settings: Detailed Caption, Concise Caption, and Vision + Detailed Caption. GPT-4V is
 192 utilized to provide captions of these keyframes, integrating human annotators’ operational intents to
 193 more accurately describe each frame, being validated in subsection B.3.

194 **Quality and Quantity of Vision Input.** To explore the upper bound of GUI-oriented capabilities,
 195 particularly in dynamic and sequential tasks, we conduct ablation studies focusing on the impact of
 196 the quality and quantity of vision input. We vary the number of keyframes (8, 16) fed into GUI-Vid.
 197 Additionally, we test the effect of different vision input on GPT-4o, using both low and high settings,
 198 as well as without providing images, to further assess how resolution influences performance.

199 4.2 Empirical Results

200 **Commercial ImageLLMs outperform Open-source VideoLLMs in Zero-shot Settings.** Com-
 201 mercial ImageLLMs, notably GPT-4V and GPT-4o, consistently outperform open-source VideoLLMs
 202 in zero-shot settings. As detailed in Table 3, GPT-4o exhibits superior performance across all GUI
 203 scenarios in complex tasks, reflected in its high scores in both multiple-choice and free-form queries,
 204 with an average of 84.8% and 3.573. Similarly, Gemini demonstrates strong capabilities in captioning
 205 and descriptive tasks within software and iOS environments, scoring 2.836 and 2.936, respectively,
 206 as shown in Table 21. Further analysis (Figure 7) reveals that GPT-4V excels in applications with
 207 minimal textual content and simple layouts, such as TikTok, health apps, and GitHub. In contrast,
 208 its performance drops in more intricate applications like Microsoft ToDo and XR software. As for
 209 VideoLLMs, their significantly poorer performance is attributed to two main factors: their inability to
 210 accurately interpret GUI content from user inputs and a lack of sufficient GUI-oriented pretraining,
 211 which is evident from their inadequate performance in basic captioning and description tasks. See
 212 Appendix E for BLEU and BERTScore, as well as detailed performance for complex tasks.




Figure 7: Fine-grained performance of GPT-4V in each GUI scenario (w.o. Android).

Table 5: Detailed scores for each tasks in **Software** scenarios. ‘Dyn.’ refers to queries on dynamic GUI content, and ‘Pred.’ indicates prediction tasks.

	Models	Setting	Caption		Complex Tasks			Conversation		Average
			Concise	Detailed	Static	Dyn.	Pred.	Round 1	Round 2	
ImageLLMs	Gemini-Pro-1.5	R.	3.659	2.837	2.969	2.822	3.450	3.608	3.845	3.339
		E.	3.350	2.468	2.741	2.431	3.292	3.458	3.837	3.152
	Qwen-VL-Max	R.	2.381	1.758	2.277	2.144	2.724	3.125	3.317	2.676
		E.	2.459	1.693	2.143	1.954	2.742	3.174	3.298	2.624
		H.	2.474	1.711	2.137	2.032	2.834	3.223	3.257	2.651
	GPT-4V	R.	3.579	2.676	3.243	3.011	3.630	3.925	4.131	3.589
E.		3.141	2.301	2.927	2.627	3.541	3.844	4.103	3.407	
H.		3.352	2.509	3.053	2.849	3.609	3.928	4.163	3.520	
GPT-4o	H.	4.048	3.028	3.125	3.117	3.562	4.129	4.318	3.644	
VideoLLMs	ChatUnivi	-	1.587	1.240	1.705	1.656	2.524	2.698	3.366	2.389
	Minigt4Video	-	1.246	1.073	1.249	1.235	1.675	1.494	1.719	1.475
	VideoChat2	-	1.992	1.312	1.812	1.682	2.158	2.342	2.720	2.144
	GUI-Vid	-	3.562	2.058	2.376	2.090	3.435	3.080	3.260	2.847

213 **Performance Variate in Different GUI Scenarios and Applications.** GPT-4V (Figure 7) and
 214 Gemini (Figure 16) excel in common scenarios such as mobile and website interfaces but show
 215 marked deficiencies in more complex GUI environments like XR and multi-window interactions,
 216 across both captioning and intricate tasks. This performance gap highlights a significant shortfall
 217 in understanding environments where GUI elements are scattered and demand sophisticated inter-
 218 pretation. It emphasizes the critical need for specialized benchmarks and datasets tailored to these
 219 complex GUI scenarios, which is essential for enhancing the GUI-oriented capabilities of MLLMs,
 220 paving the way for them to become truly reliable and high-performing general control agents.

221 **Keyframe Selection is Important for GUI-oriented Tasks.** Across both basic tasks such as
 222 captioning and more complex tasks like prediction and reasoning, significant variations are evident
 223 among keyframe selection methods. As shown in Table 22 and Table 24, GPT-4V and Gemini signifi-
 224 cantly benefit from using random-selected and human-selected keyframes, scoring approximately
 225 0.2-0.3 points higher in both captioning and free-form tasks than those using programmatic extraction.
 226 This suggests that traditional keyframe technologies, designed for natural videos, are less effective
 227 for detecting essential GUI operations, particularly when subtle movements like mouse clicks and
 228 dynamic changes are involved. Therefore, we try model-based keyframe identifier mainly utilized
 229 in robotics, with UVD+VIP achieving the best results shown in Table 18, even comparative with
 230 human selected, further indicating that keyframe selection is crucial. However, small differences in
 231 Qwen-VL-Max demonstrate that different methods may exert less influence on less capable models.

232 **Dynamic GUI Tasks Continue to Challenge MLLMs.** In the fine-grained tasks depicted in Table 5,
 233 GPT-4V and GPT-4o excel with static GUI content and prediction tasks over image sequences but
 234 struggle with providing detailed descriptions for entire videos and dynamic content. This discrepancy
 235 is attributed to minor variations in GUI that significantly impact its semantic meaning. Enhancing
 236 the number of keyframes and the granularity of perception might mitigate these issues. Among
 237 VideoLLMs, ChatUnivi excels in conversational tasks by effectively leveraging contextual nuances,
 238 particularly in subsequent rounds, yet it underperforms in caption tasks. In contrast, GUI-Vid
 239 demonstrates proficiency in sequential tasks but falls short in both captioning and static content.
 240 This gap is linked to deficiencies in backbone pretraining, which lacked comprehensive GUI content
 241 crucial for effective vision-text alignment, as evidenced by its poor performance in simple captions
 242 task shown in Table 21 and an instruction tuning process failed to fully address these shortcomings.

Table 6: The overall results for ablation study on GUI-Vid finetuning. F.K. and E.K. mean keyframes during the finetuning and evaluation process respectively. I. means Image, and V. means Video.

Setting	F.K.	E.K.	Data		Software		Website		XR		Multi		IOS		Android		Avg.	
			I.	V.	MC	Free	MC	Free	MC	Free	MC	Free	MC	Free	MC	Free		
Baseline	-	8	-	-	45.5%	2.144	42.6%	2.221	44.0%	2.005	40.4%	2.222	40.2%	2.169	44.7%	2.119	42.9%	2.147
	-	16	-	-	45.1%	2.144	41.8%	2.240	41.0%	2.007	40.7%	2.238	39.9%	2.138	44.7%	2.147	42.2%	2.154
GUI-Vid	8	8	✗	✓	58.3%	2.709	53.6%	2.817	62.2%	2.626	54.2%	2.627	53.1%	2.708	54.9%	2.501	56.0%	2.665
			✓	✓	59.9%	2.856	54.1%	2.925	59.0%	2.751	52.1%	2.837	50.0%	2.756	54.0%	2.571	54.8%	2.782
			✗	✓	59.0%	2.709	55.1%	2.821	62.8%	2.645	53.3%	2.624	55.5%	2.727	55.7%	2.501	56.9%	2.671
			✓	✓	59.9%	2.847	54.1%	2.957	55.6%	2.764	52.9%	2.861	51.8%	2.772	53.4%	2.572	54.6%	2.796

Table 7: GPT-4o average score in all scenarios under w.o. vision input, low and high resolution.

Setting	Desc.	Conv.	Dyn.	Static	Caption	Average
w.o. Vision	1.872	3.915	2.979	2.486	2.187	2.688
Low Res.	2.794	3.912	3.150	2.869	3.672	3.279
High Res.	3.031	4.056	3.318	3.131	3.911	3.489

243 **Vision Perception is Important for Sequential GUI Tasks.** As demonstrated in Table 5, integrating
 244 detailed textual information slightly outperforms purely vision-based inputs or detailed captions, akin
 245 to a Chain of Thought (CoT) [47] setting. Surprisingly, GPT-4V excels in caption and prediction
 246 tasks with just detailed captions, providing insights on enhancing specific GUI-oriented tasks through
 247 additional textual information. However, it still falls short in more challenging tasks, such as retrieving
 248 static or dynamic content. This underscores the critical role of visual perception in GUI environments,
 249 where even minor changes can significantly impact outcomes.

250 **Supreme Enhancement of GUI-Vid on Graphic-based Interface After Fine-tuning on GUI-WORLD.** As a pioneering
 251 study in training VideoLLMs as screen agents, GUI-Vid significantly outperforms the baseline model, showing an average
 252 improvement of 30% across various tasks and GUI scenarios, even surpassing the commercial ImageLLM, Qwen-VL-
 253 Max. This enhancement is particularly notable in captioning and prediction over image sequences, where GUI-Vid matches
 254 the performance of GPT-4V and Gemini-Pro. As shown in Figure 8, our two-stage progressive finetuning significantly
 255 enhances the performance in all GUI scenarios. Remarkably, GUI-Vid scored 3.747 in caption tasks within the XR scenario,
 256 highlighting its potential in XR applications and the high-quality annotations provided by our dataset.
 257 However, in Multiple-Choice QA and Chatbot tasks, GUI-Vid still lags behind industry leaders like
 258 GPT-4V and Gemini-Pro, a discrepancy likely due to the baseline LLM’s weaker performance and
 259 the challenges of instruction-based fine-tuning.
 260
 261
 262
 263
 264
 265




Figure 8: Two stages of progressive training enhance GUI ability.

266 **Upper Bound of GUI-oriented Capability with More Keyframes and High Resolution.** As
 267 depicted in Table 6, our two ablation studies during the fine-tuning phase demonstrate that utilizing
 268 GUI image-text captioning data significantly enhances the model’s preliminary understanding of GUI
 269 elements, outperforming training that relies solely on videos. Additionally, an increased number of
 270 keyframes correlates with improved performance across various scenarios, notably in environments
 271 featuring multiple windows and software applications. Further evidence from Table 7 reveals that
 272 higher image resolutions substantially boost task performance, both basic and complex, for GPT-4o.
 273 These findings underscore the potential for further developing a more robust GUI Agent.

274 5 Conclusion

275 In this paper, we have introduced GUI-WORLD, a comprehensive GUI-oriented video dataset
 276 designed to benchmark and enhance understanding of virtual interfaces, especially sequential and
 277 dynamic tasks. This dataset extensively covers six scenarios and various tasks, addressing the previous
 278 research gap in comprehensively evaluating models’ capabilities in graphic-based understanding. We
 279 conduct extensive benchmarks on leading MLLMs and the first VideoLLM-based Agent ‘GUI-Vid’
 280 finetuned on GUI-WORLD specifically for GUI-oriented content, achieving results comparable to
 281 top-performing models, providing detailed insights into enhancing GUI-related capabilities.

282 **Limitations**

283 While our work presents significant advancements in the field of GUI agents, there are several
284 limitations that need to be addressed. Firstly, despite expanding the dataset to include various
285 GUI scenarios, it still contains limitations to environments not represented in the training data.
286 This highlights the need for further research to improve the adaptability and robustness of dataset
287 collection and GUI agents in diverse and unseen environments. Additionally, although VideoLLMs
288 have shown improvements in handling dynamic content, their ability to understand and predict
289 sequential information in GUI tasks remains suboptimal. This suggests a necessity for future work to
290 focus on enhancing the temporal understanding capabilities of these models. Finally, the training and
291 fine-tuning processes for VideoLLMs require significant computational resources, which may not be
292 accessible to all researchers.

293 **Potential Negative Societal Impacts**

294 While our work aims to advance the capabilities of GUI agents for beneficial applications, it is
295 important to consider potential negative societal impacts. The use of GUI agents, especially those
296 capable of operating across multiple environments and platforms, raises significant privacy concerns.
297 Ensuring that these agents operate within strict ethical guidelines and that user data is handled
298 securely and responsibly is paramount. There is also the risk of misuse of advanced GUI agents for
299 malicious purposes, such as unauthorized access to sensitive information or automated exploitation of
300 software vulnerabilities. Establishing robust security measures and ethical usage policies is essential
301 to mitigate these risks.

302 **References**

- 303 [1] OpenAI. Openai models - gpt-4-vision. [https://openai.com/research/
304 gpt-4v-system-card](https://openai.com/research/gpt-4v-system-card), 2023.
- 305 [2] Haotian Liu, Chunyuan Li, Qingyang Wu, and Yong Jae Lee. Visual instruction tuning. In
306 *NeurIPS*, 2023.
- 307 [3] Shukang Yin, Chaoyou Fu, Sirui Zhao, Ke Li, Xing Sun, Tong Xu, and Enhong Chen. A
308 survey on multimodal large language models, 2024.
- 309 [4] Zhengyuan Yang, Linjie Li, Jianfeng Wang, Kevin Lin, Ehsan Azarnasab, Faisal Ahmed,
310 Zicheng Liu, Ce Liu, Michael Zeng, and Lijuan Wang. Mm-react: Prompting chatgpt for
311 multimodal reasoning and action, 2023.
- 312 [5] Chunyuan Li, Cliff Wong, Sheng Zhang, Naoto Usuyama, Haotian Liu, Jianwei Yang, Tristan
313 Naumann, Hoifung Poon, and Jianfeng Gao. Llava-med: Training a large language-and-vision
314 assistant for biomedicine in one day, 2023.
- 315 [6] Kai Zhang, Jun Yu, Eashan Adhikarla, Rong Zhou, Zhiling Yan, Yixin Liu, Zhengliang Liu,
316 Lifang He, Brian Davison, Xiang Li, Hui Ren, Sunyang Fu, James Zou, Wei Liu, Jing Huang,
317 Chen Chen, Yuyin Zhou, Tianming Liu, Xun Chen, Yong Chen, Quanzheng Li, Hongfang
318 Liu, and Lichao Sun. Biomedgpt: A unified and generalist biomedical generative pre-trained
319 transformer for vision, language, and multimodal tasks, 2024.
- 320 [7] Jiangyong Huang, Silong Yong, Xiaojian Ma, Xiongkun Linghu, Puhao Li, Yan Wang, Qing
321 Li, Song-Chun Zhu, Baoxiong Jia, and Siyuan Huang. An embodied generalist agent in 3d
322 world, 2024.
- 323 [8] Wenyi Hong, Weihang Wang, Qingsong Lv, Jiazheng Xu, Wenmeng Yu, Junhui Ji, Yan Wang,
324 Zihan Wang, Yuxuan Zhang, Juanzi Li, Bin Xu, Yuxiao Dong, Ming Ding, and Jie Tang.
325 Cogagent: A visual language model for gui agents, 2023.
- 326 [9] Hanyu Lai, Xiao Liu, Iat Long Iong, Shuntian Yao, Yuxuan Chen, Pengbo Shen, Hao Yu,
327 Hanchen Zhang, Xiaohan Zhang, Yuxiao Dong, and Jie Tang. Autowebglm: Bootstrap and
328 reinforce a large language model-based web navigating agent, 2024.

- 329 [10] Chi Zhang, Zhao Yang, Jiaxuan Liu, Yucheng Han, Xin Chen, Zebiao Huang, Bin Fu, and
330 Gang Yu. Appagent: Multimodal agents as smartphone users, 2023.
- 331 [11] Runliang Niu, Jindong Li, Shiqi Wang, Yali Fu, Xiyu Hu, Xueyuan Leng, He Kong, Yi Chang,
332 and Qi Wang. Screenagent: A vision language model-driven computer control agent, 2024.
- 333 [12] Junyang Wang, Haiyang Xu, Jiabo Ye, Ming Yan, Weizhou Shen, Ji Zhang, Fei Huang,
334 and Jitao Sang. Mobile-agent: Autonomous multi-modal mobile device agent with visual
335 perception, 2024.
- 336 [13] Biplab Deka, Zifeng Huang, Chad Franzen, Joshua Hibschan, Daniel Afegan, Yang Li,
337 Jeffrey Nichols, and Ranjitha Kumar. Rico: A mobile app dataset for building data-driven
338 design applications. In *Proceedings of the 30th annual ACM symposium on user interface
339 software and technology*, pages 845–854, 2017.
- 340 [14] Liangtai Sun, Xingyu Chen, Lu Chen, Tianle Dai, Zichen Zhu, and Kai Yu. Meta-gui: towards
341 multi-modal conversational agents on mobile gui. *arXiv preprint arXiv:2205.11029*, 2022.
- 342 [15] Sagar Gubbi Venkatesh, Partha Talukdar, and Srini Narayanan. Ugif: Ui grounded instruction
343 following. *arXiv preprint arXiv:2211.07615*, 2022.
- 344 [16] Christopher Rawles, Alice Li, Daniel Rodriguez, Oriana Riva, and Timothy Lillicrap. Android
345 in the wild: A large-scale dataset for android device control. *arXiv preprint arXiv:2307.10088*,
346 2023.
- 347 [17] Keen You, Haotian Zhang, Eldon Schoop, Floris Weers, Amanda Swearngin, Jeffrey Nichols,
348 Yinfei Yang, and Zhe Gan. Ferret-ui: Grounded mobile ui understanding with multimodal
349 llms. *arXiv preprint arXiv:2404.05719*, 2024.
- 350 [18] Evan Zheran Liu, Kelvin Guu, Panupong Pasupat, Tianlin Shi, and Percy Liang. Reinforcement
351 learning on web interfaces using workflow-guided exploration. In *International Conference
352 on Learning Representations (ICLR)*, 2018. URL <https://arxiv.org/abs/1802.08802>.
- 353 [19] Shuyan Zhou, Frank F Xu, Hao Zhu, Xuhui Zhou, Robert Lo, Abishek Sridhar, Xianyi Cheng,
354 Yonatan Bisk, Daniel Fried, Uri Alon, et al. Webarena: A realistic web environment for
355 building autonomous agents. *arXiv preprint arXiv:2307.13854*, 2023.
- 356 [20] Xiang Deng, Yu Gu, Boyuan Zheng, Shijie Chen, Sam Stevens, Boshi Wang, Huan Sun, and
357 Yu Su. Mind2web: Towards a generalist agent for the web. *Advances in Neural Information
358 Processing Systems*, 36, 2024.
- 359 [21] Raghav Kapoor, Yash Parag Butala, Melisa Russak, Jing Yu Koh, Kiran Kamble, Waseem Al-
360 shikh, and Ruslan Salakhutdinov. Omniaact: A dataset and benchmark for enabling multimodal
361 generalist autonomous agents for desktop and web. *arXiv preprint arXiv:2402.17553*, 2024.
- 362 [22] Ziniu Zhang, Shulin Tian, Liangyu Chen, and Ziwei Liu. Mmina: Benchmarking multihop
363 multimodal internet agents. *arXiv preprint arXiv:2404.09992*, 2024.
- 364 [23] Longtao Zheng, Zhiyuan Huang, Zhenghai Xue, Xinrun Wang, Bo An, and Shuicheng Yan.
365 Agentstudio: A toolkit for building general virtual agents. *arXiv preprint arXiv:2403.17918*,
366 2024.
- 367 [24] Tianbao Xie, Danyang Zhang, Jixuan Chen, Xiaochuan Li, Siheng Zhao, Ruisheng Cao,
368 Toh Jing Hua, Zhoujun Cheng, Dongchan Shin, Fangyu Lei, et al. Osworld: Benchmarking
369 multimodal agents for open-ended tasks in real computer environments. *arXiv preprint
370 arXiv:2404.07972*, 2024.
- 371 [25] Apple. Apple vision pro. <https://www.apple.com/apple-vision-pro/>, 2024.
- 372 [26] Wangjiang Zhu, Jie Hu, Gang Sun, Xudong Cao, and Yu Qiao. A key volume mining deep
373 framework for action recognition. In *Proceedings of the IEEE conference on computer vision
374 and pattern recognition*, pages 1991–1999, 2016.
- 375 [27] Xiang Yan, Syed Zulqarnain Gilani, Hanlin Qin, Mingtao Feng, Liang Zhang, and Ajmal Mian.
376 Deep keyframe detection in human action videos. *arXiv preprint arXiv:1804.10021*, 2018.

- 377 [28] Behrooz Mahasseni, Michael Lam, and Sinisa Todorovic. Unsupervised video summarization
378 with adversarial lstm networks. In *Proceedings of the IEEE conference on Computer Vision*
379 *and Pattern Recognition*, pages 202–211, 2017.
- 380 [29] OpenCV. Opencv. <https://opencv.org/>.
- 381 [30] Yuan Li, Yue Huang, Yuli Lin, Siyuan Wu, Yao Wan, and Lichao Sun. I think, therefore i am:
382 Benchmarking awareness of large language models using awarebench, 2024.
- 383 [31] Lichao Sun, Yue Huang, Haoran Wang, Siyuan Wu, Qihui Zhang, Yuan Li, Chujie Gao, Yixin
384 Huang, Wenhan Lyu, Yixuan Zhang, Xiner Li, Zhengliang Liu, Yixin Liu, Yijue Wang, Zhikun
385 Zhang, Bertie Vidgen, Bhavya Kailkhura, Caiming Xiong, Chaowei Xiao, Chunyuan Li, Eric
386 Xing, Furong Huang, Hao Liu, Heng Ji, Hongyi Wang, Huan Zhang, Huaxiu Yao, Manolis
387 Kellis, Marinka Zitnik, Meng Jiang, Mohit Bansal, James Zou, Jian Pei, Jian Liu, Jianfeng
388 Gao, Jiawei Han, Jieyu Zhao, Jiliang Tang, Jindong Wang, Joaquin Vanschoren, John Mitchell,
389 Kai Shu, Kaidi Xu, Kai-Wei Chang, Lifang He, Lifu Huang, Michael Backes, Neil Zhenqiang
390 Gong, Philip S. Yu, Pin-Yu Chen, Quanquan Gu, Ran Xu, Rex Ying, Shuiwang Ji, Suman Jana,
391 Tianlong Chen, Tianming Liu, Tianyi Zhou, William Wang, Xiang Li, Xiangliang Zhang, Xiao
392 Wang, Xing Xie, Xun Chen, Xuyu Wang, Yan Liu, Yanfang Ye, Yinzhi Cao, Yong Chen, and
393 Yue Zhao. Trustllm: Trustworthiness in large language models, 2024.
- 394 [32] Fangyu Lei, Qian Liu, Yiming Huang, Shizhu He, Jun Zhao, and Kang Liu. S3eval: A
395 synthetic, scalable, systematic evaluation suite for large language models, 2024.
- 396 [33] Jasper Dekoninck, Marc Fischer, Luca Beurer-Kellner, and Martin Vechev. Understanding large
397 language models through the lens of dataset generation, 2024. URL [https://openreview.](https://openreview.net/forum?id=miGpIhqyB)
398 [net/forum?id=miGpIhqyB](https://openreview.net/forum?id=miGpIhqyB).
- 399 [34] Yue Yu, Yuchen Zhuang, Jieyu Zhang, Yu Meng, Alexander Ratner, Ranjay Krishna, Jiaming
400 Shen, and Chao Zhang. Large language model as attributed training data generator: A tale of
401 diversity and bias, 2023.
- 402 [35] KunChang Li, Yinan He, Yi Wang, Yizhuo Li, Wenhai Wang, Ping Luo, Yali Wang,
403 Limin Wang, and Yu Qiao. Videochat: Chat-centric video understanding. *arXiv preprint*
404 *arXiv:2305.06355*, 2023.
- 405 [36] Kunchang Li, Yali Wang, Yizhuo Li, Yi Wang, Yinan He, Limin Wang, and Yu Qiao. Unmasked
406 teacher: Towards training-efficient video foundation models, 2024.
- 407 [37] Wenliang Dai, Junnan Li, Dongxu Li, Anthony Meng Huat Tiong, Junqi Zhao, Weisheng
408 Wang, Boyang Li, Pascale Fung, and Steven Hoi. Instructblip: Towards general-purpose
409 vision-language models with instruction tuning, 2023.
- 410 [38] Qiming Zhang, Jing Zhang, Yufei Xu, and Dacheng Tao. Vision transformer with quadrangle
411 attention, 2023.
- 412 [39] Edward J. Hu, Yelong Shen, Phillip Wallis, Zeyuan Allen-Zhu, Yuanzhi Li, Shean Wang,
413 Lu Wang, and Weizhu Chen. Lora: Low-rank adaptation of large language models, 2021.
- 414 [40] OpenAI. Hello gpt-4o, May 2024. URL <https://openai.com/index/hello-gpt-4o/>.
415 Accessed: 2024-06-06.
- 416 [41] Jinze Bai, Shuai Bai, Shusheng Yang, Shijie Wang, Sinan Tan, Peng Wang, Junyang Lin, Chang
417 Zhou, and Jingren Zhou. Qwen-vl: A versatile vision-language model for understanding,
418 localization, text reading, and beyond, 2023.
- 419 [42] GeminiTeam. Gemini: A family of highly capable multimodal models, 2023.
- 420 [43] KeplerLab. Katna - video to keyframes and video to image crops utility. [https://github.](https://github.com/keplerlab/katna)
421 [com/keplerlab/katna](https://github.com/keplerlab/katna), 2023. Accessed: 2024-09-07.
- 422 [44] Zichen Zhang, Yunshuang Li, Osbert Bastani, Abhishek Gupta, Dinesh Jayaraman, Yecheng Ja-
423 son Ma, and Luca Weihs. Universal visual decomposer: Long-horizon manipulation made
424 easy. In *2024 IEEE International Conference on Robotics and Automation (ICRA)*, pages
425 6973–6980. IEEE, 2024.

- 426 [45] Yecheng Jason Ma, Shagun Sodhani, Dinesh Jayaraman, Osbert Bastani, Vikash Kumar, and
427 Amy Zhang. Vip: Towards universal visual reward and representation via value-implicit
428 pre-training. *arXiv preprint arXiv:2210.00030*, 2022.
- 429 [46] Suraj Nair, Aravind Rajeswaran, Vikash Kumar, Chelsea Finn, and Abhinav Gupta. R3m:
430 A universal visual representation for robot manipulation. *arXiv preprint arXiv:2203.12601*,
431 2022.
- 432 [47] Jason Wei, Xuezhi Wang, Dale Schuurmans, Maarten Bosma, Brian Ichter, Fei Xia, Ed Chi,
433 Quoc Le, and Denny Zhou. Chain-of-thought prompting elicits reasoning in large language
434 models, 2023.
- 435 [48] Peng Jin, Ryuichi Takanobu, Caiwan Zhang, Xiaochun Cao, and Li Yuan. Chat-univi: Unified
436 visual representation empowers large language models with image and video understanding.
437 *arXiv preprint arXiv:2311.08046*, 2023.
- 438 [49] Kirolos Ataallah, Xiaoqian Shen, Eslam Abdelrahman, Essam Sleiman, Deyao Zhu, Jian
439 Ding, and Mohamed Elhoseiny. Minigt4-video: Advancing multimodal llms for video
440 understanding with interleaved visual-textual tokens, 2024.
- 441 [50] Kunchang Li, Yali Wang, Yinan He, Yizhuo Li, Yi Wang, Yi Liu, Zun Wang, Jilan Xu,
442 Guo Chen, Ping Luo, et al. Mvbench: A comprehensive multi-modal video understanding
443 benchmark. *arXiv preprint arXiv:2311.17005*, 2023.
- 444 [51] Bin Lin, Bin Zhu, Yang Ye, Munan Ning, Peng Jin, and Li Yuan. Video-llava: Learning united
445 visual representation by alignment before projection. *arXiv preprint arXiv:2311.10122*, 2023.
- 446 [52] Haotian Liu, Chunyuan Li, Yuheng Li, Bo Li, Yuanhan Zhang, Sheng Shen, and Yong Jae
447 Lee. Llava-next: Improved reasoning, ocr, and world knowledge, January 2024. URL
448 <https://llava-vl.github.io/blog/2024-01-30-llava-next/>.
- 449 [53] Lianmin Zheng, Wei-Lin Chiang, Ying Sheng, Siyuan Zhuang, Zhanghao Wu, Yonghao
450 Zhuang, Zi Lin, Zhuohan Li, Dacheng Li, Eric P. Xing, Hao Zhang, Joseph E. Gonzalez, and
451 Ion Stoica. Judging llm-as-a-judge with mt-bench and chatbot arena, 2023.
- 452 [54] Xiao Liu, Xuanyu Lei, Shengyuan Wang, Yue Huang, Zhuoer Feng, Bosi Wen, Jiale Cheng,
453 Pei Ke, Yifan Xu, Weng Lam Tam, Xiaohan Zhang, Lichao Sun, Hongning Wang, Jing Zhang,
454 Minlie Huang, Yuxiao Dong, and Jie Tang. Alignbench: Benchmarking chinese alignment of
455 large language models, 2023.
- 456 [55] Dongping Chen, Ruoxi Chen, Shilin Zhang, Yinuo Liu, Yaochen Wang, Huichi Zhou, Qihui
457 Zhang, Pan Zhou, Yao Wan, and Lichao Sun. Mllm-as-a-judge: Assessing multimodal
458 llm-as-a-judge with vision-language benchmark, 2024.
- 459 [56] Kishore Papineni, Salim Roukos, Todd Ward, and Wei-Jing Zhu. Bleu: a method for automatic
460 evaluation of machine translation. In *Proceedings of the 40th annual meeting of the Association
461 for Computational Linguistics*, pages 311–318, 2002.
- 462 [57] Tianyi Zhang, Varsha Kishore, Felix Wu, Kilian Q Weinberger, and Yoav Artzi. Bertscore:
463 Evaluating text generation with bert. *arXiv preprint arXiv:1904.09675*, 2019.
- 464 [58] OpenAI Team. Gpt-4 technical report, 2024.
- 465 [59] Meta. Llama 2, 2023. <https://llama.meta.com/llama2>.
- 466 [60] Meta. Llama 3, 2023. <https://llama.meta.com/llama3>.
- 467 [61] OpenAI. Mistral ai, 2024. <https://mistral.ai/company/>.
- 468 [62] Junnan Li, Dongxu Li, Silvio Savarese, and Steven Hoi. Blip-2: Bootstrapping language-image
469 pre-training with frozen image encoders and large language models, 2023.

- 470 [63] Jean-Baptiste Alayrac, Jeff Donahue, Pauline Luc, Antoine Miech, Iain Barr, Yana Hasson,
471 Karel Lenc, Arthur Mensch, Katie Millican, Malcolm Reynolds, Roman Ring, Eliza Ruther-
472 ford, Serkan Cabi, Tengda Han, Zhitao Gong, Sina Samangooei, Marianne Monteiro, Jacob
473 Menick, Sebastian Borgeaud, Andrew Brock, Aida Nematzadeh, Sahand Sharifzadeh, Miko-
474 laj Binkowski, Ricardo Barreira, Oriol Vinyals, Andrew Zisserman, and Karen Simonyan.
475 Flamingo: a visual language model for few-shot learning, 2022.
- 476 [64] Haotian Liu, Chunyuan Li, Yuheng Li, and Yong Jae Lee. Improved baselines with visual
477 instruction tuning, 2023.
- 478 [65] Weihang Wang, Qingsong Lv, Wenmeng Yu, Wenyi Hong, Ji Qi, Yan Wang, Junhui Ji, Zhuoyi
479 Yang, Lei Zhao, Xixuan Song, Jiazheng Xu, Bin Xu, Juanzi Li, Yuxiao Dong, Ming Ding, and
480 Jie Tang. CogVLM: Visual expert for pretrained language models, 2024.
- 481 [66] Weihao Yu, Zhengyuan Yang, Linjie Li, Jianfeng Wang, Kevin Lin, Zicheng Liu, Xinchao
482 Wang, and Lijuan Wang. Mm-vet: Evaluating large multimodal models for integrated capabili-
483 ties, 2023.
- 484 [67] Yuan Liu, Haodong Duan, Yuanhan Zhang, Bo Li, Songyang Zhang, Wangbo Zhao, Yike
485 Yuan, Jiaqi Wang, Conghui He, Ziwei Liu, et al. Mmbench: Is your multi-modal model an
486 all-around player? *arXiv preprint arXiv:2307.06281*, 2023.
- 487 [68] Lin Chen, Jinsong Li, Xiaoyi Dong, Pan Zhang, Yuhang Zang, Zehui Chen, Haodong Duan,
488 Jiaqi Wang, Yu Qiao, Dahua Lin, and Feng Zhao. Are we on the right way for evaluating large
489 vision-language models?, 2024.
- 490 [69] Chaoyi Wu, Jiayu Lei, Qiaoyu Zheng, Weike Zhao, Weixiong Lin, Xiaoman Zhang, Xiao Zhou,
491 Ziheng Zhao, Ya Zhang, Yanfeng Wang, et al. Can gpt-4v (ision) serve medical applications?
492 case studies on gpt-4v for multimodal medical diagnosis. *arXiv preprint arXiv:2310.09909*,
493 2023.
- 494 [70] Naoki Wake, Atsushi Kanehira, Kazuhiro Sasabuchi, Jun Takamatsu, and Katsushi Ikeuchi.
495 Gpt-4v (ision) for robotics: Multimodal task planning from human demonstration. *arXiv*
496 *preprint arXiv:2311.12015*, 2023.
- 497 [71] Sili Huang, Jifeng Hu, Zhejian Yang, Liwei Yang, Tao Luo, Hechang Chen, Lichao Sun, and
498 Bo Yang. Decision mamba: Reinforcement learning via hybrid selective sequence modeling,
499 2024.
- 500 [72] Qihui Zhang, Chujie Gao, Dongping Chen, Yue Huang, Yixin Huang, Zhenyang Sun, Shilin
501 Zhang, Weiye Li, Zhengyan Fu, Yao Wan, and Lichao Sun. LLM-as-a-coauthor: Can mixed
502 human-written and machine-generated text be detected? In Kevin Duh, Helena Gomez, and
503 Steven Bethard, editors, *Findings of the Association for Computational Linguistics: NAACL*
504 *2024*, pages 409–436, Mexico City, Mexico, June 2024. Association for Computational
505 Linguistics. URL <https://aclanthology.org/2024.findings-naacl.29>.
- 506 [73] Wei Zhao, Zhitao Hou, Siyuan Wu, Yan Gao, Haoyu Dong, Yao Wan, Hongyu Zhang, Yulei
507 Sui, and Haidong Zhang. NL2Formula: Generating spreadsheet formulas from natural
508 language queries. In Yvette Graham and Matthew Purver, editors, *Findings of the Association*
509 *for Computational Linguistics: EACL 2024*, pages 2377–2388, St. Julian’s, Malta, March
510 2024. Association for Computational Linguistics. URL [https://aclanthology.org/2024.](https://aclanthology.org/2024.findings-eacl.158)
511 [findings-eacl.158](https://aclanthology.org/2024.findings-eacl.158).
- 512 [74] Yi Gui, Zhen Li, Yao Wan, Yemin Shi, Hongyu Zhang, Yi Su, Shaoling Dong, Xing Zhou,
513 and Wenbin Jiang. Vision2ui: A real-world dataset with layout for code generation from ui
514 designs, 2024.
- 515 [75] Muhammad Maaz, Hanoona Rasheed, Salman Khan, and Fahad Shahbaz Khan. Video-chatgpt:
516 Towards detailed video understanding via large vision and language models. *arXiv preprint*
517 *arXiv:2306.05424*, 2023.
- 518 [76] Chaoyun Zhang, Liqun Li, Shilin He, Xu Zhang, Bo Qiao, Si Qin, Minghua Ma, Yu Kang,
519 Qingwei Lin, Saravan Rajmohan, Dongmei Zhang, and Qi Zhang. Ufo: A ui-focused agent for
520 windows os interaction, 2024.

- 521 [77] Xiangxiang Chu, Limeng Qiao, Xinyang Lin, Shuang Xu, Yang Yang, Yiming Hu, Fei Wei,
522 Xinyu Zhang, Bo Zhang, Xiaolin Wei, and Chunhua Shen. Mobilevlm : A fast, strong and
523 open vision language assistant for mobile devices, 2023.
- 524 [78] Weihao Tan, Ziluo Ding, Wentao Zhang, Boyu Li, Bohan Zhou, Junpeng Yue, Haochong
525 Xia, Jiechuan Jiang, Longtao Zheng, Xinrun Xu, et al. Towards general computer control: A
526 multimodal agent for red dead redemption ii as a case study. *arXiv preprint arXiv:2403.03186*,
527 2024.
- 528 [79] Kevin Lin, Faisal Ahmed, Linjie Li, Chung-Ching Lin, Ehsan Azarnasab, Zhengyuan Yang,
529 Jianfeng Wang, Lin Liang, Zicheng Liu, Yumao Lu, et al. Mm-vid: Advancing video under-
530 standing with gpt-4v (ision). *arXiv preprint arXiv:2310.19773*, 2023.
- 531 [80] Zirui Song, Yaohang Li, Meng Fang, Zhenhao Chen, Zecheng Shi, and Yuan Huang.
532 Mmac-copilot: Multi-modal agent collaboration operating system copilot. *arXiv preprint*
533 *arXiv:2404.18074*, 2024.
- 534 [81] Yang Li, Jiacong He, Xin Zhou, Yuan Zhang, and Jason Baldrige. Mapping natural language
535 instructions to mobile ui action sequences, 2020.
- 536 [82] Danyang Zhang, Hongshen Xu, Zihan Zhao, Lu Chen, Ruisheng Cao, and Kai Yu. Mobile-Env:
537 An evaluation platform and benchmark for llm-gui interaction. *CoRR*, abs/2305.08144, 2023.
538 URL <https://arxiv.org/abs/2305.08144>.
- 539 [83] Xing Han Lù, Zdeněk Kasner, and Siva Reddy. Weblinx: Real-world website navigation with
540 multi-turn dialogue, 2024.
- 541 [84] Shunyu Yao, Howard Chen, John Yang, and Karthik Narasimhan. Webshop: Towards scalable
542 real-world web interaction with grounded language agents. In *ArXiv*, preprint.
- 543 [85] Jing Yu Koh, Robert Lo, Lawrence Jang, Vikram Duvvur, Ming Chong Lim, Po-Yu Huang,
544 Graham Neubig, Shuyan Zhou, Ruslan Salakhutdinov, and Daniel Fried. Visualwebarena:
545 Evaluating multimodal agents on realistic visual web tasks. *arXiv preprint arXiv:2401.13649*,
546 2024.
- 547 [86] Junpeng Liu, Yifan Song, Bill Yuchen Lin, Wai Lam, Graham Neubig, Yuanzhi Li, and Xiang
548 Yue. Visualwebbench: How far have multimodal llms evolved in web page understanding and
549 grounding?, 2024.
- 550 [87] Grégoire Mialon, Clémentine Fourier, Craig Swift, Thomas Wolf, Yann LeCun, and Thomas
551 Scialom. Gaia: a benchmark for general ai assistants, 2023.
- 552 [88] Boyuan Zheng, Boyu Gou, Jihyung Kil, Huan Sun, and Yu Su. Gpt-4v(ision) is a generalist
553 web agent, if grounded, 2024.
- 554 [89] Xiao Liu, Hanyu Lai, Hao Yu, Yifan Xu, Aohan Zeng, Zhengxiao Du, Peng Zhang, Yuxiao
555 Dong, and Jie Tang. Webglm: Towards an efficient web-enhanced question answering system
556 with human preferences, 2023.
- 557 [90] Ambreen Kousar, Saif Ur Rehman Khan, Shahid Hussain, M. Abdul Basit Ur Rahim, Wen-Li
558 Wang, and Naseem Ibrahim. A systematic review on pattern-based gui testing of android
559 and web apps: State-of-the-art, taxonomy, challenges and future directions. In *2023 25th*
560 *International Multitopic Conference (INMIC)*, pages 1–7, 2023. doi: 10.1109/INMIC60434.
561 2023.10465949.
- 562 [91] Rodrigo Funabashi Jorge, Márcio Eduardo Delamaro, Celso Gonçalves Camilo-Junior, and
563 Auri Marcelo Rizzo Vincenzi. Test data generation based on gui: A systematic mapping.
564 In *International Conference on Software Engineering Advances*, 2014. URL [https://api.
565 semanticscholar.org/CorpusID:64041598](https://api.semanticscholar.org/CorpusID:64041598).
- 566 [92] Ivans Kulesovs. ios applications testing. 2015. URL [https://api.semanticscholar.
567 org/CorpusID:59015994](https://api.semanticscholar.org/CorpusID:59015994).

- 568 [93] Kanzhi Cheng, Qiushi Sun, Yougang Chu, Fangzhi Xu, Yantao Li, Jianbing Zhang, and
569 Zhiyong Wu. Seeclick: Harnessing gui grounding for advanced visual gui agents, 2024.
- 570 [94] Han Hu, Haolan Zhan, Yujin Huang, and Di Liu. Pairwise gui dataset construction between
571 android phones and tablets, 2023.
- 572 [95] Tony Beltramelli. pix2code: Generating code from a graphical user interface screenshot, 2017.
- 573 [96] An Yan, Zhengyuan Yang, Wanrong Zhu, Kevin Qinghong Lin, Linjie Li, Jianfeng Wang,
574 Jianwei Yang, Yiwu Zhong, Julian J. McAuley, Jianfeng Gao, Zicheng Liu, and Lijuan Wang.
575 Gpt-4v in wonderland: Large multimodal models for zero-shot smartphone gui navigation.
576 *ArXiv*, abs/2311.07562, 2023. URL [https://api.semanticscholar.org/CorpusID:
577 265149992](https://api.semanticscholar.org/CorpusID:265149992).
- 578 [97] Hajime Nakajima, Takeshi Masuda, and Ikuya Takahashi. Gui ferret: Gui test tool to analyze
579 complex behavior of multi-window applications. *2013 18th International Conference on
580 Engineering of Complex Computer Systems*, pages 163–166, 2013. URL [https://api.
581 semanticscholar.org/CorpusID:837553](https://api.semanticscholar.org/CorpusID:837553).
- 582 [98] Philipp A. Rauschnabel, Reto Felix, Christian Hinsch, Hamza Shahab, and Florain Alt. What
583 is xr? towards a framework for augmented and virtual reality. *Comput. Hum. Behav.*, 133:
584 107289, 2022. URL <https://api.semanticscholar.org/CorpusID:247861674>.
- 585 [99] Meta quest 3: New mixed reality vr headset. <https://www.meta.com/quest/quest-3>.
- 586 [100] Brian K. Sanders, Yuzhong Shen, and Dennis A. Vincenzi. Understanding user interface
587 preferences for xr environments when exploring physics and engineering principles. In
588 *International Conference on Applied Human Factors and Ergonomics*, 2019. URL [https:
589 //api.semanticscholar.org/CorpusID:197940610](https://api.semanticscholar.org/CorpusID:197940610).
- 590 [101] OpenAI. Chatgpt, 2023. <https://openai.com/product/chatgpt>.
- 591 [102] Kevin Qinghong Lin, Linjie Li, Difei Gao, Qinchen WU, Mingyi Yan, Zhengyuan Yang, Lijuan
592 Wang, and Mike Zheng Shou. Videogui: A benchmark for gui automation from instructional
593 videos. *arXiv e-prints*, pages arXiv–2406, 2024.
- 594 [103] Xiao Liu, Tianjie Zhang, Yu Gu, Iat Long Iong, Yifan Xu, Xixuan Song, Shudan Zhang, Hanyu
595 Lai, Xinyi Liu, Hanlin Zhao, et al. Visualagentbench: Towards large multimodal models as
596 visual foundation agents. *arXiv preprint arXiv:2408.06327*, 2024.

597 **Part I**

598 **Appendix**

599 **Table of Contents**
600

601	A Related Work	18
602	B Details of Dataset Construction	18
603	B.1 Six Main GUI Categories	18
604	B.2 Selected Website/Software	19
605	B.3 Human Keyframes Annotation Process	19
606	C Dataset Analysis	22
607	D Details of Experiments Setups	25
608	D.1 Finetune dataset construction	25
609	D.2 Hyperparameter Settings	25
610	D.3 Evaluation.	26
611	E Additional Experiments Results	27
612	F Prompts	33
613	G Case Study	41

614
615
616

617 A Related Work

618 **MLLM-based Agents for GUI.** Building upon the significant advancements in LLMs [58–61]
619 and advanced modality-mixing technologies [62, 63], groundbreaking MLLMs such as GPT-4V [1]
620 and Gemini-Pro [42], along with open-source MLLMs like the LLaVA-1.6 series [2, 64], CogVLM
621 [65], and Qwen-VL series [41], have shown outstanding performance across various tasks [66–
622 74]. Venturing beyond text and single image, several studies are now exploring the integration of
623 video modalities for tasks requiring dynamic or sequential visual content [48, 35, 75, 51]. In the
624 GUI domain, leveraging the robust vision perception capabilities of MLLMs, applications such as
625 WebAgents [8, 76, 23] and Mobile Agents [17, 12, 77] have gained popularity for handling everyday
626 tasks like navigation and VQA. Frontier research is also investigating the use of MLLMs as general
627 control agents, such as in playing computer games [78, 79] and serving as OS co-pilots [80, 24],
628 paving the way for more complex GUI operations.

629 **GUI Benchmark & Dataset.** Building upon the foundational work of Rico [13], the first mobile
630 GUI video dataset, and AitW [16], which features 715k episodes of sequential images, research has
631 extensively covered mobile [14, 81, 82] and web GUI environments [83, 19, 84–86]. Mind2Web
632 [20] stands out in web-based datasets with over 2,000 tasks from 137 websites across 31 domains.
633 Advances continue into desktop GUIs with new toolkits [23], benchmarks [21, 87], and frameworks
634 [88, 89, 11]. Research on GUI also transfers from comprehending single images in a static workspace
635 [8] to sequential operations or multi-hop scenarios [24, 22], challenging the understanding and
636 operation capability of these powerful models.

637 B Details of Dataset Construction

638 B.1 Six Main GUI Categories

639 In earlier endeavors pertaining to GUI, such as those involving GUI testing [90–92], the focus
640 was segmented into GUIs for Website, Software, IOS and Android platforms. However, as a
641 comprehensive GUI dataset, we included all potential GUI scenarios in our dataset to ensure that
642 our data is the most comprehensive knowledge that the GUI Agent needs to learn; we divided these
643 scenarios into six categories:

- 644 • **Android.** This category focuses on the GUI scenarios that occur within the Android operating
645 system, which is predominantly used on smartphones. Android’s ubiquity in the mobile market has
646 led to a wide variety of GUI designs and interaction patterns, making it a rich field for study. This
647 category has been the subject of extensive scrutiny in scholarly works such as [13, 81, 16, 93].
- 648 • **Software.** This category encapsulates the GUI scenarios arising within software applications,
649 whether they are standalone programs or components of a larger suite. The diversity of software
650 applications, from productivity tools to creative suites, offers a wide range of GUI scenarios for
651 exploration. The literature is rich with research in this area, such as [94].
- 652 • **Website.** This category is concerned with the GUI scenarios that manifest within a web browser.
653 Given the ubiquity of web browsing in modern digital life, this category holds significant relevance.
654 It holds a substantial representation in academic literature, with pioneering papers such as [20, 21]
655 proposing excellent GUI datasets for websites.
- 656 • **IOS.** This category zeroes in on the GUI scenarios that transpire within the iOS operating system,
657 the proprietary system for Apple devices like the iPhone and iPad. The iOS platform is known for
658 its distinct design aesthetics and interaction patterns, providing a unique context for GUI research.
659 A number of studies, such as [95, 96] make use of GUI information in IOS.
- 660 • **Multi Windows.** This category is dedicated to GUI scenarios that necessitate simultaneous
661 interaction with multiple windows, a common occurrence in desktop environments where users
662 often juggle between several applications or documents. Despite the common use of multi-window
663 interaction in everyday GUI usage, there has been relatively little research into this area [97]. The
664 need for efficient multitasking in such scenarios presents unique challenges and opportunities for
665 GUI design and interaction research. As of our knowledge, there are no specific datasets catering
666 to these multi-window GUI scenarios.
- 667 • **XR.** XR encompasses Virtual Reality (VR), Augmented Reality (AR), and Mixed Reality (MR) [98].
668 Given the advancements in XR technology and the growing accessibility of commercial-grade head-

669 mounted displays [25, 99], XR has emerged as a novel medium for human-computer interaction.
670 This necessitates the exploration of GUI within XR environments. In these scenarios, the GUI
671 takes on a 3D, immersive form [100], demanding the agent to comprehend and navigate a 3D space.
672 The emerging field of XR presents a new frontier for GUI research, with unique challenges and
673 opportunities due to its immersive and interactive nature. To date, as far as we are aware, there are
674 no datasets that specifically address GUI in the realm of XR.

675 B.2 Selected Website/Software

676 In our study, we selected a diverse range of websites and software to comprehensively evaluate GUI
677 understanding capabilities across various user scenarios. These selections cover essential categories
678 such as social media, productivity tools, online shopping, and educational platforms, providing a
679 broad spectrum of GUI environments.

680 The chosen websites, as shown in Figure 9, include popular social media platforms like Instagram,
681 Twitter, and LinkedIn, which are integral to understanding dynamic and interactive GUI elements.
682 We also included widely-used productivity tools such as Microsoft Teams, Notion, and Slack to
683 evaluate GUI tasks in professional and collaborative settings.

684 For software shown in Figure 10, we incorporated key applications like Adobe Photoshop and
685 MATLAB to assess GUI operations in specialized and technical environments. Additionally, video
686 conferencing tools like Zoom and cloud storage services like Google Drive were included to represent
687 common remote work and file management scenarios.

688 These selections ensure that our study encompasses a wide array of user interactions and GUI
689 complexities, thereby providing a robust evaluation of the current state-of-the-art methods in GUI
690 understanding by MLLMs and comprehensively constructing a high-quality dataset.

691 B.3 Human Keyframes Annotation Process

692 **Annotator’s Information** The annotation is conducted by 16 authors of this paper and 8 volunteers
693 independently. As acknowledged, the diversity of annotators plays a crucial role in reducing bias and
694 enhancing the reliability of the benchmark. These annotators have knowledge in the GUI domain,
695 with different genders, ages, and educational backgrounds. The education backgrounds of annotators
696 are above undergraduate. To ensure the annotators can proficiently mark the data, we provide them
697 with detailed tutorials, teaching them how to use software to record videos or edit video clips. We
698 also provide them with detailed criteria and task requirements in each annotation process.

699 **Recording Video.** For self-recording videos, we employ OBS³ on the Windows system for screen
700 capturing and the official screen recording toolkit on the Mac/iOS system. This process necessitates
701 human labelers to execute a series of targeted actions within specific websites or applications, which
702 are subsequently captured as raw video footage. These actions, commonplace in everyday usage,
703 enhance the reliability of our dataset. Subsequently, the raw videos are segmented into sub-videos,
704 each encapsulating multiple actions (e.g., clicking a button) to achieve a specific objective (e.g., image
705 search). The videos are then processed to extract keyframes annotated with detailed descriptions.

706 **Edition Based on YouTube Videos.** For sourcing videos from YouTube, we utilize a search
707 protocol formatted as "[website name/application name] + tutorial" to compile relevant
708 video lists. Human labelers first review these videos to understand the primary operations they depict.
709 These videos are then divided into sub-videos, each containing several actions directed towards a
710 single goal (e.g., image search). Like the self-recorded footage, these segments are processed to
711 isolate keyframes and furnish them with descriptive annotations.

712 **Keyframes Annotation.** After obtaining the GUI video clips, human annotators will filter out
713 the keyframes of the operations based on the video content and the mouse and keyboard actions
714 at that time. They will also label the sub-operations or targets between the two keyframes. Once
715 the annotation is complete, the annotators will provide an overall description of the entire video,
716 summarizing the main goal of the human operations in the video. After all the information is
717 annotated, we will use a Large Language Model (LLM) to refine the text content, reducing any errors

³<https://obsproject.com/>







<p>Productivity </p> <ul style="list-style-type: none"> • Asana • Dropbox • EndNote • Evernote • Google Drive • Google Meet • Mendeley • Microsoft OneDrive • Microsoft Teams • Notion • OneNote • Slack • Trello • Zoom • Zotero 	<p>Education </p> <ul style="list-style-type: none"> • Adobe Digital Editions • Amazon Kindle • Blackboard • Coursera • edX • Google Classroom • Kahoot! • Khan Academy • MATLAB • Microsoft Teams for Education • Moodle • PhET Interactive Simulations • Quizlet • Scratch • Stellarium • Turnitin • Udemy
<p>Entertainment </p> <ul style="list-style-type: none"> • Amazon Prime Video • Apple Music • Disney+ • HBO Max • Hulu • Netflix • Pandora • Spotify • Twitch • YouTube 	<p>Social Media </p> <ul style="list-style-type: none"> • Discord • Facebook • Instagram • LinkedIn • Messenger (Facebook) • Pinterest • Snapchat • TikTok • Twitter • WeChat • WhatsApp
<p>Windows System Software </p> <ul style="list-style-type: none"> • Alarm & Clock • Calculator • Calendar • Control Panel • Cortana • File Explorer • Mail • Microsoft Edge • Microsoft Store • Paint • Photos • Settings • Snipping Tool • Sticky Notes • Task Manager • Windows Media Player • WordPad 	<p>Mac System Software </p> <ul style="list-style-type: none"> • Calendar • Contacts • FaceTime • Finder • Mail • Maps • Messages • Music • Notes • Photos • Podcasts • Preview • Reminders • Safari • Siri • TV

Figure 9: List of desktop softwares in GUI-WORLD.









<p>Social Media </p> <ul style="list-style-type: none"> • https://instagram.com/ • https://twitter.com/ • https://whatsapp.com/ • https://pinterest.com/ • https://linkedin.com/ • https://tiktok.com/ • https://discord.com/ • https://reddit.com/ • https://telegram.org/ <p>Search Engines </p> <ul style="list-style-type: none"> • https://google.com/ • https://yandex.com/ • https://bing.com/ • https://baidu.com/ • https://search.aol.com/ <p>Online Shopping </p> <ul style="list-style-type: none"> • https://etsy.com/ • https://alibaba.com/ • https://ebay.com/ <p>Education and Learning </p> <ul style="list-style-type: none"> • https://quora.com/ • https://byjus.com/ • https://cambridge.org/ • https://udemy.com/ • https://coursera.org/ • https://khanacademy.org/ • https://edx.org/ • https://academia.edu/ 	<p>Technology and Software </p> <ul style="list-style-type: none"> • https://microsoft.com/ • https://apple.com/ • https://adobe.com/ • https://github.com/ • https://openai.com/ • https://oracle.com/ • https://vmware.com/ <p>Travel and Hospitality </p> <ul style="list-style-type: none"> • https://booking.com/ • https://tripadvisor.com/ • https://yelp.com/ • https://airbnb.com/ • https://expedia.com/ • https://hotels.com/ • https://trivago.com/ • https://homeaway.com/ <p>Finance </p> <ul style="list-style-type: none"> • https://moneycontrol.com/ • https://bloomberg.com/ • https://investing.com/ • https://marketwatch.com/ • https://seekingalpha.com/ • https://zacks.com/ <p>Food and Cooking </p> <ul style="list-style-type: none"> • https://cookpad.com/ • https://allrecipes.com/ • https://foodnetwork.com/ • https://yummly.com/ • https://epicurious.com/
---	---

Figure 10: List of some websites in GUI-WORLD.

718 made by human annotators and adjusting the sentence structure. The prompt we use for the LLM to
 719 polish the human annotations is shown in Figure 11 and Figure 12.

720 **Human-LLM Cooperated Instruction Generation.** To curate and refine the golden answer of each
 721 video-instruction pair generated by GPT-4V, given that the raw response from GPT-4V may contain
 722 harmful content or hallucinations. The role of humans in the golden answer generation process is
 723 to enhance the difficulty of the questions and remove harmful and incorrect content, as shown in
 724 Table 8.

Table 8: Comparison of raw answer from GPT-4V and golden answer from humans.

Raw response from GPT-4V	Golden answer from humans
"Q": "What subcategories are visible under the 'Lifestyle' section in the static GUI content of the video?" "A": "In the 'Lifestyle' section of the telegram.com website, the visible subcategories are 'Worcester Living', 'Faith', and 'Food'. These are clearly displayed in a horizontal list just below the main 'Lifestyle' category header, indicating different areas of content that users can explore within the lifestyle section."	"Q": "What subcategories are visible under the 'Lifestyle' section in the static GUI content of the video?" "A": "The 'Lifestyle' section of the telegram.com website features visible subcategories such as 'Worcester Living', 'Faith', and 'Food'. These are prominently shown in a horizontal list beneath the main 'Lifestyle' header, offering users various content areas to explore within the section."

725 **Human verifying GPT-4V annotated captions.** We evaluated the quality of annotations from
 726 GPT-4V by selecting 1,000 detailed descriptions and captions generated by GPT-4V, which were
 727 then assessed by human annotators. The high satisfaction rate of 98% underscores the quality and
 728 relevance of the GPT-4V annotations.




Figure 11: The overall preview of our annotating software.

729 **C Dataset Analysis**

730 In this section, we provide an analysis of the length distribution of QA in each GUI scenario, as
 731 illustrated in Figure 13 and Figure 14. Questions focused on sequential and predictional tasks are
 732 slightly longer than other types, while the golden answer of static tasks tends to be longer. Length of




Figure 12: The interface for annotating a keyframe, consists of mouse action, keyboard action, and a short sub-action purpose.

Table 9: Examples of diverse question types in GUI-WORLD.

T.	Question	Examples
Caption	Detailed Description	Q: <i>Please provide a detailed description of what occurs throughout these sequential GUI images.</i> A: The video shows a user taking the 16 Personalities test on a Windows desktop using the Edge browser...
	Summarized Caption	Q: <i>Write a clear description of the video, make sure the key features are well covered.</i> A: Creating a new IT team in Todoist by selecting industry, job function, role, team size, and inviting members.
Static	Layout, Icon Retrieval	Q: <i>What related searches are suggested on the right side of the Bing results for 'emnlp 2024'?</i> A: The suggested related searches shown include 'emnlp 2024 miami', 'eac1 2024 call for papers'...
	Textual Retrieval	Q: <i>What is the estimated time to complete the content for Week 2 of the course?</i> A: The estimated time to complete the content for Week 2 of the course is 1 hour...
	Interrelations in GUI Content	Q: <i>What is the name of the browser and the tab where the user performs the product search?</i> A: The browser is Microsoft Edge, and the user performs the product search in the eBay tab.
Dynamic	Content Retrieval	Q: <i>What specific action does the user take after turning their head to the left to view the left side of the page?</i> A: After turning their head to the left to view the left side of the page, the user performs...
	Prediction	Q: <i>Given the mouse is over 'Add NeurIPS 2024 DB Track Submission,' what's the likely next step?</i> A: It would be to click on the 'Add NeurIPS 2024 Datasets and Benchmarks Track Submission' button...
	Sequential Reasoning	Q: <i>Scrolls down from the 'Moon Gravity', which of the following cheats? A. Change Weather B. Skyfall ...</i> A: [[B]]

733 Question-answer pair in various GUI scenarios is similarly distributed, with questions in Android
734 environment being slightly shorter, and answers in XR environment being longer.




Figure 13: Length distribution of free-form questions.




Figure 14: Length distribution of answers to free-form questions.




Figure 15: Statistic of different GUI scenarios in GUI-WORLD.

735 D Details of Experiments Setups

736 D.1 Finetune dataset construction

737 We use two settings to finetune GUI-Vid, one with video-text pairs only, and the other with video-text
738 and image-text pairs, which are all GUI content:

- 739 • **Video Only.** In this setting, we only trained GUI-Vid with video-text pairs in GUI-WORLD, as
740 shown in Table 10.
- 741 • **Video-Image.** Inspired by the pre-trained process of Videochat2, we include image-text pairs to
742 help the visual encoder align GUI knowledge. These images are selected from our GUI-WORLD,
743 MetaGUI [14], and OmniAct [21] for high-quality GUI content. Subsequently, we use GPT-4V to
744 generate a detailed description and a concise caption for each image. Finally, we construct a dataset
745 consisting of video-text and image-text pairs for gaining comprehensive GUI-oriented capabilities.

Table 10: Video-only finetune dataset.

Stage	Data types	Amount
1	Detailed Description	14,276
	Concise Caption	7,138
2	GUI VQA	21,414
	Multiple-Choice QA	14,276
	Conversation	7,138

Table 11: Video-image finetune dataset.

Stage	Data types	Source	Type	Amount
1	GUI-WORLD	Video	Detailed Description	14,276
			Concise Caption	7,138
		Image	Detailed Description	5,555
			Concise Caption	5,555
	METAGUI	Image	Detailed Description	19,626
			Concise Caption	19,626
OmniAct	Image	Detailed Description	260	
		Concise Caption	260	
2	GUI-WORLD	Video	GUI VQA	21,414
			Multiple-Choice QA	14,276
			Conversation	7,138

746 D.2 Hyperparameter Settings

747 In this section, we will introduce the hyperparameters of MLLMs to facilitate experiment repro-
748 ducibility and transparency. We divide them into three parts: the inference phase during benchmark
749 and dataset construction, the LLM-as-a-Judge phase, and the fine-tuning phase. All our experiments
750 were conducted on a server equipped with dual A800 and dual 4090 GPUs.

751 **Inference.** We empirically study 7 MLLMs, involving 4 Image-LLMs and 3 Video-LLMs, with
752 their hyperparameters detailed as follows:

- 753 • **GPT-4V [1] & GPT-4o [40]:** We set the temperature and top-p as 0.9, max-token as 2048, and
754 both all images input are set as high quality in *Instruction Dataset Construction* and benchmarking.
- 755 • **Gemini-Pro-1.5 [42]:** We use the default settings, which set temperature as 0.4, top-p as 1, and
756 max-token as 2048. It should be noted that during our project, Gemini-Pro-1.5 is still under the
757 user request limit, which only provides 100 requests per day, making our benchmark difficult.
758 Given that Gemini hasn't launched Pay-as-you-go⁴, we will include benchmark results on 'Human'
759 setting as soon as possible.

⁴<https://ai.google.dev/pricing>

- 760 • **Qwen-VL-Max [41]:** We use the default settings for Qwen-VL-Max, with top-p as 0.8 and max-
761 token as 2048. Given that the input context window is merely 6,000 for Qwen, we scale the
762 resolution for all images to 0.3.
 - 763 • **ChatUnivi [48]:** We use ChatUnivi-7B built upon Vicuna-v0-7B and set the max frame as 100,
764 temperature as 0.2, and max-token as 1024.
 - 765 • **Minigpt4video [49]:** We use the suggested settings⁵ for this model and the max-frame are set as
766 45, with only the max-token being modified to 1024.
 - 767 • **VideoChat2 & GUI-Vid [50]:** For a fair comparison, we set the same hyperparameters for
768 VideoChat2 & GUI-Vid. We set the max-token as 1024, top-p as 0.9, temperature as 1.0, max-
769 frame as 8/16, repetition penalty as 1.2, and length penalty as 1.2.
- 770 **LLM-as-a-Judge.** We studied four LLM-as-a-Judge in giving a similarity score for the MLLM’s
771 response and ground truth, namely GPT-4 [58], ChatGPT [101], LLaMA-3-70b-instruct [60], and
772 Mixtral-8x22b-instruct-v0.1 [61]. Hyperparameter settings are detailed as follows:
- 773 • **GPT-4 & ChatGPT.** We set the temperature as 0.6 and others as default.
 - 774 • **LLaMA-3-70b-instruct.** We set the temperature as 0.6, top-p as 0.9, top-k as 50.
 - 775 • **Mixtral-8x22b-instruct-v0.1.** We set top-p as 0.7, top-k as 50, and temperature as 0.7.
- 776 **Finetune.** We include several hyperparameter settings in experiment settings and ablation studies,
777 as shown in Table 12.

Table 12: Configuration settings for fine-tuning.

Config	Setting
input frame	8
input resolution	224
max text length	512
input modal	I. + V.
optimizer	AdamW
optimizer momentum	$\beta_1, \beta_2 = 0.9, 0.999$
weight decay	0.02
learning rate schedule	cosine decay
learning rate	2e-5
batch size	4
warmup epochs	0.6
total epochs	3
backbone drop path	0
QFormer drop path	0.1
QFormer dropout	0.1
QFormer token	96
flip augmentation	yes
augmentation	MultiScaleCrop [0.5, 1]

Table 13: Evaluating LLM-as-a-Judge as a replacement for human judging in the scoring setting.

Models	Pearson(↑)	Spearman(↑)	Kendall(↑)	\$ per Benchmark(↓)
GPT-4	0.856	0.853	0.793	120\$
ChatGPT	0.706	0.714	0.627	12\$
Llama-3-70b-instruct	0.774	0.772	0.684	12\$
Mixtral-8x22b-instruct-v0.1	0.759	0.760	0.670	15\$

778 **D.3 Evaluation.**

779 Given the complexity of free-form answers in GUI scenarios, the evaluation includes specific positions
780 of GUI elements, textual content, and comparing the response to the golden answer. LLM-as-a-judge
781 has been widely used in previous studies for complex evaluation tasks [53, 54]. Therefore, we
782 leverage LLM-as-a-Judge [53] in a similar setting to MM-vet [66], which compares the MLLM’s
783 response to the golden answer. We carefully evaluate the accessibility of leveraging LLM-as-a-Judge,
784 selecting 1,000 samples covering 6 free-form questions mentioned in our dataset. As shown in
785 Table 13, GPT-4 outperforms other LLMs, exhibiting a better human alignment on providing a

⁵<https://github.com/Vision-CAIR/MiniGPT4-video>

Table 14: Strong Correlation Between Our Benchmark (GUI Understanding) and Other GUI Agent Benchmarks.

Model	GUI-World	VisualAgentBench	VideoGUI	OS-World
GPT-4o	1	1	1	2
GPT-4V	2	2	2	1
Gemini-1.5-Pro	3	3	3	3
Qwen-VL-Max	4	4	4	/

Table 15: User Preference: GUI-Vid vs VideoChat2 (With and Without Fine-tuning on GUI-World).

Scenarios	GUI-Vid	Tie	VideoChat2
Software	82.7%	13.3%	4.0%
Website	86.0%	12.0%	2.0%
XR	88.0%	8.7%	3.3%
Multi	85.3%	10.0%	8.7%
IOS	92.0%	6.0%	2.0%
Android	82.0%	16.0%	2.0%
Average	86.0%	11.0%	3.7%

786 similarity score for the response compared to the golden answer, although it is approximately 10
787 times more expensive than other models.

788 E Additional Experiments Results

789 In this section, we first provide an ablation study on keyframe selection methods. Then, we conduct
790 statistics and human preference experiments on correlations of GUI understanding capability to other
791 mainstream GUI-related tasks. Furthermore, we provide detailed, performance on newly released
792 models after our submission of the first version, followed by very detailed results on each task in each
793 GUI scenario.

794 **Ablation study on keyframe identify methods.** Firstly, we show performance on model-based
795 keyframe identify methods in Table 18, with details of UVD+VIP and UVD+R3M in Table 19 and
796 Table 20.

797 **Correlation between GUI understanding and other mainstream GUI tasks.** Furthermore, We
798 conducted additional analysis and experiments to show how GUI understanding capability helps
799 mainstream GUI-related tasks, including generating code to operate GUI [93] and assist people
800 through chat [8]. Both demonstrate the strong correlation between GUI understanding capability and
801 specific tasks for GUI agents.

- 802 • We compared the benchmark results on GUI-world with existing benchmarks [24, 102, 103] for
803 operating on GUI as shown in Table 1, and found that the results generally match, i.e., the stronger
804 the understanding ability, the stronger the agent performance.
- 805 • For the definition of chat helping humans, we selected 180 videos from the benchmark, choosing
806 30 videos for each scenario. We asked 5 human annotators to pose the question they most wanted to
807 ask after watching each video. We then used GUI-Vid, both before and after fine-tuning, to answer
808 these questions. The human annotators who asked the questions were then asked to indicate which
809 answer was more helpful. The results are shown in Table 2, demonstrating that models trained in
810 GUI understanding are more favored by people when acting as GUI agents.

811 **Performance of newly released models in GUI-WORLD test set.** We evaluated two latest models,
812 LLaVA-Next-Video-7B-DPO [52] and Video-LLaVA [51]. We show their performance in Table 17
813 and Table 16. Our model outperformed these in most tasks, except Conversation, likely due to their
814 use of DPO during training.

815 For captioning tasks, Table 21 shows comprehensive experimental results among six scenarios.
816 For scores of LLM-as-a-Judge in a specific task, see Table 22, Table 23, Table 24, Table 25, and
817 Table 26. For BLEU [56] and BERTScore [57] in validating free-form and conversational questions,
818 see Table 27, Table 28, Table 32, Table 30, and Table 31. For performance in fine-grain
819 (application level), see Figure 16 for Gemini-Pro and Figure 17 for Qwen-VL-Max.

Table 16: Video-LLaVA Performance

Scene	MCQA	Description	Conversation	Dynamic	Static	Caption	Average
XR	0.442	1.100	2.686	2.055	1.808	1.654	2.258
Android	0.513	1.162	2.952	1.858	1.673	1.763	2.259
IOS	0.497	1.143	2.966	1.992	1.680	1.654	2.319
Multi	0.459	1.106	2.863	2.069	1.781	1.772	2.329
Website	0.524	1.183	3.059	2.102	1.736	1.371	2.410
Software	0.529	1.241	2.942	1.958	1.657	1.519	2.290
Average	0.494	1.156	2.911	2.005	1.722	1.622	2.311

Table 17: LLaVA-Next-Video-7B-DPO Performance

File	MCQA	Description	Conversation	Dynamic	Static	Caption	Average
XR	0.596	1.867	3.123	2.580	2.147	1.987	2.709
Android	0.243	1.675	3.338	2.360	1.980	2.189	2.675
IOS	0.581	1.762	3.229	2.536	2.051	2.017	2.717
Multi	0.355	1.069	2.982	2.437	1.870	2.541	2.541
Website	0.484	1.729	3.123	2.422	1.854	2.004	2.588
Software	0.569	1.762	3.220	2.448	1.868	2.149	2.641
Average	0.471	1.644	3.169	2.464	1.961	2.148	2.645

Table 18: Average Performance of GPT-4o among 6 scenarios: Two Automated Keyframe Identification Methods vs. Human-Selected Keyframes

Setting	MCQA	Description	Conversation	Dynamic	Static	Caption	Average
Human	84.8%	3.031	4.056	3.318	3.131	3.911	3.573
UVD+vip	83.5%	3.150	4.044	3.265	3.346	3.923	3.581
UVD+r3m	84.5%	3.136	4.058	3.292	3.363	3.940	3.612

Table 19: Detailed Performance of GPT-4o using UVD+ViP Keyframe Identification Method.

Scenario	MCQA	Description	Conversation	Dynamic	Static	Caption	Average
Software	86.2%	3.297	4.282	3.354	3.478	4.112	3.749
Website	82.0%	3.248	4.155	3.415	3.567	4.074	3.744
XR	84.2%	2.980	3.775	3.034	3.122	3.587	3.347
Multi	82.1%	3.391	4.165	3.466	3.404	3.868	3.659
IOS	86.0%	3.157	4.017	3.353	3.492	4.050	3.648
Mobile	80.7%	2.827	3.871	2.970	3.014	3.844	3.340
Average	83.5%	3.150	4.044	3.265	3.346	3.923	3.581

Table 20: Detailed Performance of GPT-4o using UVD+R3M Keyframe Identification Method.

Scenario	MCQA	Description	Conversation	Dynamic	Static	Caption	Average
Software	85.8%	3.290	4.273	3.352	3.458	4.134	3.741
Website	82.7%	3.282	4.114	3.460	3.591	4.065	3.746
XR	87.7%	3.010	3.861	3.142	3.161	3.600	3.433
Multi	83.6%	3.237	4.129	3.503	3.417	3.897	3.737
IOS	86.4%	3.165	4.094	3.328	3.480	4.078	3.663
Android	80.6%	2.835	3.876	2.968	3.072	3.865	3.353
Average	84.5%	3.136	4.058	3.292	3.363	3.940	3.612

Table 21: Scores of Caption (Cap.) and Description (Des.) tasks in six GUI scenarios.

Models	Setting	Software		Website		XR		Multi		IOS		Android		Avg.	
		Cap.	Des.	Cap.	Des.	Cap.	Des.	Cap.	Des.	Cap.	Des.	Cap.	Des.	Cap.	Des.
Gemini-Pro-1.5	R.	3.659	2.837	3.613	2.860	2.995	2.590	3.276	2.470	3.678	2.936	-	-	3.444	2.739
	E.	3.350	2.468	3.159	2.422	2.837	2.279	2.824	2.109	3.394	2.519	3.185	2.312	3.125	2.351
Qwen-VL-Max	R.	2.381	1.758	2.326	1.681	2.172	1.772	2.035	1.463	2.513	1.662	2.141	1.565	2.261	1.650
	E.	2.459	1.693	2.317	1.599	2.167	1.638	2.190	1.438	2.189	1.615	2.002	1.429	2.221	1.569
	H.	2.474	1.711	2.457	1.698	2.383	1.777	1.910	1.346	2.577	1.795	2.474	1.711	2.360	1.665
GPT-4V	R.	3.579	2.676	3.612	2.699	2.975	2.525	3.281	2.661	3.757	2.775	3.655	2.755	3.479	2.682
	E.	3.141	2.301	3.293	2.380	2.471	2.085	3.063	2.324	3.624	2.611	3.201	2.312	3.132	2.335
	H.	3.352	2.509	3.702	2.750	3.050	3.556	3.524	2.673	3.670	2.588	-	-	3.460	2.614
GPT-4o	H.	4.048	3.028	4.067	3.233	3.398	2.729	3.869	3.111	4.014	2.993	4.071	3.095	3.911	3.869
ChatUnivi	-	1.587	1.240	1.569	1.254	1.417	1.148	1.575	1.267	1.480	1.146	1.778	1.249	1.568	1.217
Minigt4Video	-	1.246	1.073	1.200	1.057	1.320	1.106	1.130	1.034	1.190	1.076	1.184	1.061	1.212	1.068
VideoChat2	-	1.992	1.312	1.817	1.307	1.838	1.426	2.222	1.433	2.169	1.270	2.119	1.294	1.900	1.340
GUI-Vid	-	3.562	2.085	3.655	2.167	3.747	2.153	3.370	1.742	3.566	2.071	2.662	1.248	3.427	1.911

Table 22: Detailed scores for each tasks in Website scenarios.

Models	Setting	Static	Sequential	Prediction	Conversation1	Conversation2	Average
Gemini-Pro-1.5	R.	3.279	3.050	3.560	3.579	3.796	3.452
	E.	2.983	2.491	3.432	3.405	3.760	3.215
Qwen-VL-Max	R.	2.317	2.271	2.802	2.995	3.069	2.656
	E.	2.256	2.198	2.821	2.861	3.144	2.627
	H.	2.308	2.078	2.832	3.061	3.358	2.698
GPT-4V	R.	3.461	3.214	3.754	3.778	4.029	3.648
	E.	3.197	2.808	3.487	3.717	3.954	3.433
	H.	3.498	3.255	3.727	3.731	4.061	3.655
	C.C.	1.746	2.738	3.645	3.363	3.632	3.025
	D.C.	2.704	2.917	3.686	3.680	3.901	3.380
H.+D.C.	3.313	3.221	3.852	3.850	4.171	3.682	
GPT-4o	H.	3.443	3.373	3.672	4.086	4.122	3.740
ChatUnivi	-	1.701	1.668	2.524	2.514	3.338	2.349
Minigt4Video	-	1.309	1.233	1.766	1.439	1.854	1.520
VideoChat2	-	1.771	1.777	2.288	2.461	2.812	2.221
GUI-Vid	-	2.406	2.341	3.544	3.135	3.355	2.957

Table 23: Detailed scores for each tasks in XR scenarios.

Models	Setting	Static	Sequential	Prediction	Conversation1	Conversation2	Average
Gemini-Pro-1.5	R.	2.892	2.505	3.543	3.222	3.611	3.154
	E.	2.814	2.163	3.510	3.108	3.455	3.006
Qwen-VL-Max	R.	2.047	1.968	2.712	2.879	3.132	2.469
	E.	2.125	1.973	2.658	2.760	3.029	2.499
	H.	1.886	1.920	2.656	2.727	3.012	2.373
GPT-4V	R.	2.934	2.668	3.392	3.291	3.714	3.200
	E.	2.222	2.153	3.310	3.151	3.618	2.892
	H.	2.893	2.778	3.538	3.364	3.747	3.265
	C.C.	1.744	2.412	3.327	3.080	3.485	2.809
	D.C.	2.427	2.409	3.518	3.176	3.749	3.056
H.+D.C.	2.775	2.635	3.580	3.235	3.734	3.191	
GPT-4o	H.	2.871	2.745	3.370	3.596	3.836	3.285
ChatUnivi	-	1.660	1.420	2.205	2.250	3.270	2.161
Minigt4Video	-	1.225	1.161	1.610	1.347	1.465	1.362
VideoChat2	-	1.654	1.547	2.192	2.099	2.529	2.005
GUI-Vid	-	2.444	2.147	3.347	2.836	3.036	2.764

Table 24: Detailed scores for each tasks in **Multi-windows** scenarios.

Models	Setting	Static	Sequential	Prediction	Conversation1	Conversation2	Average
Gemini-Pro-1.5	R.	2.538	2.410	3.296	3.152	3.402	2.959
	E.	2.545	2.049	2.972	2.930	3.389	2.777
Qwen-VL-Max	R.	1.793	1.872	2.770	2.897	3.122	2.432
	E.	1.866	1.780	2.730	2.627	3.105	2.362
	H.	1.884	1.969	2.913	2.689	3.104	2.490
GPT-4V	R.	3.185	2.655	3.745	3.699	3.973	3.452
	E.	2.902	2.406	3.636	3.420	3.729	3.219
	H.	3.000	2.952	3.801	3.597	3.889	3.449
	C.C.	2.097	2.973	3.774	3.331	3.621	3.160
	D.C.	2.671	2.979	3.849	3.466	3.822	3.358
H.+D.C.	3.037	3.162	4.079	3.748	4.036	3.617	
GPT-4o	H.	3.108	3.106	3.829	4.043	4.188	3.654
ChatUnivi	-	1.658	1.623	2.514	2.384	3.199	2.275
Minigt4Video	-	1.205	1.186	1.690	1.400	1.801	1.457
VideoChat2	-	1.754	1.774	2.479	2.420	2.699	2.222
GUI-Vid	-	2.485	2.067	3.537	2.954	3.247	2.861

Table 25: Detailed scores for each tasks in **IOS** scenarios.

Models	Setting	Static	Sequential	Prediction	Conversation1	Conversation2	Average
Gemini-Pro-1.5	R.	3.076	2.637	3.370	3.366	3.615	3.213
	E.	2.852	2.356	3.137	3.126	3.566	3.007
Qwen-VL-Max	R.	2.438	2.244	2.923	3.102	3.273	2.779
	E.	2.303	2.150	2.614	3.145	3.264	2.659
	H.	1.884	1.969	2.913	2.689	3.104	2.490
GPT-4V	R.	3.364	3.080	3.684	3.766	4.184	3.614
	E.	3.209	2.774	3.545	3.611	4.006	3.427
	H.	3.107	2.830	3.631	3.680	4.011	3.453
	C.C.	1.788	2.291	3.511	3.212	3.542	2.868
	D.C.	2.751	2.732	3.654	3.642	3.842	3.324
H.+D.C.	3.090	2.965	3.740	3.786	3.994	3.516	
GPT-4o	H.	3.183	2.993	3.460	4.050	4.141	3.558
ChatUnivi	-	1.771	1.642	2.408	2.559	3.307	2.337
Minigt4Video	-	1.291	1.219	1.698	1.556	1.737	1.501
VideoChat2	-	1.955	1.803	2.145	2.315	2.626	2.169
GUI-Vid	-	2.262	2.133	3.401	2.843	3.224	2.773

Table 26: Detailed scores for each tasks in **Android** scenarios.

Models	Setting	Static	Sequential	Prediction	Conversation1	Conversation2	Average
Gemini-Pro-1.5	E.	2.703	2.460	3.157	3.642	3.881	3.168
Qwen-VL-Max	R.	1.887	1.804	2.398	2.823	3.056	2.309
	E.	1.785	1.630	2.311	2.605	3.233	2.277
GPT-4V	R.	3.116	3.047	3.477	3.924	4.008	3.515
	E.	2.705	2.470	3.175	3.647	3.885	3.176
	C.C.	2.092	2.243	3.139	3.443	3.782	2.939
	D.C.	3.015	2.890	3.357	3.883	3.990	3.427
GPT-4o	H.	3.057	3.220	3.373	3.981	4.186	3.561
ChatUnivi	-	1.835	1.654	2.317	2.712	3.433	2.390
Minigt4Video	-	1.183	1.159	1.507	1.342	1.521	1.342
VideoChat2	-	1.732	1.754	2.125	2.340	2.645	2.119
GUI-Vid	-	2.010	1.928	3.053	2.755	3.105	2.572

Table 27: Detailed BLEU and BERTScore (B.S.) in **Software** scenarios.

Models	Setting	Static		Sequential		Prediction		Description		Caption		Conversation		Avg.	
		BLEU	B.S.	BLEU	B.S.	BLEU	B.S.	BLEU	B.S.	BLEU	B.S.	BLEU	B.S.	BLEU	B.S.
Gemini-Pro-1.5	R.	0.109	0.789	0.150	0.720	0.078	0.680	0.056	0.716	0.016	0.605	0.122	0.761	0.089	0.712
	E.	0.093	0.758	0.134	0.699	0.072	0.659	0.046	0.682	0.011	0.558	0.106	0.747	0.077	0.684
Qwen-VL-Max	R.	0.085	0.698	0.101	0.649	0.064	0.576	0.010	0.521	0.008	0.443	0.121	0.749	0.065	0.606
	E.	0.094	0.704	0.103	0.633	0.062	0.595	0.009	0.524	0.006	0.437	0.113	0.739	0.065	0.605
	H.	0.081	0.676	0.098	0.620	0.067	0.596	0.009	0.504	0.004	0.429	0.117	0.743	0.063	0.595
GPT-4V	R.	0.162	0.814	0.206	0.753	0.190	0.739	0.041	0.676	0.033	0.581	0.181	0.793	0.136	0.726
	E.	0.161	0.792	0.191	0.726	0.175	0.724	0.030	0.609	0.017	0.486	0.165	0.786	0.123	0.687
	H.	0.153	0.805	0.194	0.737	0.183	0.731	0.037	0.639	0.025	0.537	0.179	0.791	0.129	0.707
GPT-4o	H.	0.131	0.806	0.212	0.776	0.147	0.728	0.041	0.711	0.018	0.575	0.159	0.803	0.118	0.733
ChatUnivi	-	0.097	0.697	0.074	0.581	0.101	0.619	0.005	0.409	0.000	0.195	0.084	0.723	0.060	0.537
Minigt4Video	-	0.019	0.516	0.022	0.470	0.029	0.516	0.000	0.399	0.000	0.249	0.013	0.510	0.014	0.443
VideoChat2	-	0.095	0.698	0.080	0.595	0.076	0.574	0.004	0.341	0.000	0.193	0.100	0.733	0.059	0.523
GUI-Vid	-	0.142	0.758	0.145	0.681	0.114	0.698	0.049	0.658	0.004	0.519	0.093	0.717	0.091	0.672

Table 28: Detailed BLEU and BERTScore (B.S.) in **Website** scenarios.

Models	Setting	Static		Sequential		Prediction		Description		Caption		Conversation		Avg.	
		BLEU	B.S.	BLEU	B.S.	BLEU	B.S.	BLEU	B.S.	BLEU	B.S.	BLEU	B.S.	BLEU	B.S.
Gemini-Pro-1.5	R.	0.113	0.793	0.145	0.727	0.083	0.676	0.054	0.720	0.016	0.664	0.098	0.736	0.085	0.719
	E.	0.095	0.754	0.121	0.681	0.079	0.661	0.041	0.676	0.011	0.602	0.092	0.725	0.073	0.683
Qwen-VL-Max	R.	0.099	0.728	0.099	0.634	0.080	0.610	0.008	0.519	0.005	0.471	0.085	0.694	0.063	0.609
	E.	0.083	0.710	0.101	0.631	0.093	0.611	0.011	0.503	0.004	0.469	0.099	0.709	0.065	0.605
	H.	0.079	0.693	0.089	0.597	0.093	0.606	0.009	0.488	0.007	0.449	0.103	0.705	0.063	0.590
GPT-4V	R.	0.173	0.830	0.241	0.765	0.205	0.751	0.040	0.694	0.032	0.645	0.164	0.763	0.142	0.741
	E.	0.159	0.802	0.204	0.727	0.202	0.727	0.033	0.648	0.031	0.590	0.149	0.757	0.130	0.708
	H.	0.182	0.823	0.234	0.771	0.213	0.758	0.043	0.696	0.041	0.660	0.165	0.768	0.147	0.746
GPT-4o	H.	0.141	0.813	0.219	0.768	0.199	0.731	0.054	0.700	0.026	0.602	0.146	0.755	0.131	0.728
ChatUnivi	-	0.078	0.645	0.068	0.581	0.102	0.607	0.008	0.399	0.000	0.192	0.061	0.661	0.053	0.514
Minigt4Video	-	0.022	0.527	0.016	0.448	0.027	0.501	0.000	0.344	0.000	0.186	0.011	0.522	0.013	0.421
VideoChat2	-	0.073	0.619	0.075	0.579	0.049	0.511	0.004	0.328	0.000	0.167	0.067	0.678	0.045	0.480
GUI-Vid	-	0.114	0.731	0.158	0.674	0.129	0.694	0.049	0.667	0.002	0.553	0.075	0.681	0.088	0.667

Table 29: Detailed BLEU and BERTScore (B.S.) in **XR** scenarios.

Models	Setting	Static		Sequential		Prediction		Description		Caption		Conversation		Avg.	
		BLEU	B.S.	BLEU	B.S.	BLEU	B.S.	BLEU	B.S.	BLEU	B.S.	BLEU	B.S.	BLEU	B.S.
Gemini-Pro-1.5	R.	0.088	0.772	0.101	0.678	0.070	0.678	0.026	0.650	0.002	0.463	0.082	0.733	0.062	0.662
	E.	0.073	0.760	0.090	0.651	0.062	0.666	0.015	0.618	0.002	0.449	0.084	0.720	0.054	0.644
Qwen-VL-Max	R.	0.069	0.703	0.075	0.602	0.049	0.601	0.006	0.486	0.000	0.338	0.117	0.738	0.053	0.578
	E.	0.048	0.689	0.079	0.657	0.058	0.605	0.005	0.498	0.000	0.359	0.112	0.739	0.050	0.591
	H.	0.051	0.651	0.073	0.593	0.044	0.591	0.004	0.493	0.001	0.357	0.101	0.726	0.046	0.569
GPT-4V	R.	0.093	0.794	0.169	0.715	0.165	0.736	0.028	0.625	0.006	0.457	0.147	0.768	0.101	0.683
	E.	0.085	0.726	0.131	0.665	0.162	0.724	0.020	0.541	0.003	0.382	0.141	0.760	0.090	0.633
	H.	0.091	0.797	0.181	0.732	0.180	0.744	0.027	0.630	0.006	0.471	0.154	0.773	0.106	0.691
GPT-4o	H.	0.077	0.800	0.154	0.717	0.153	0.718	0.020	0.615	0.006	0.468	0.138	0.759	0.091	0.680
ChatUnivi	-	0.083	0.686	0.061	0.538	0.091	0.575	0.006	0.475	0.000	0.282	0.086	0.693	0.054	0.541
Minigt4Video	-	0.014	0.545	0.016	0.466	0.027	0.502	0.001	0.453	0.000	0.262	0.013	0.474	0.012	0.450
VideoChat2	-	0.077	0.679	0.079	0.595	0.073	0.577	0.004	0.378	0.000	0.211	0.101	0.721	0.056	0.527
GUI-Vid	-	0.096	0.754	0.149	0.689	0.131	0.700	0.051	0.637	0.003	0.460	0.082	0.705	0.085	0.657

Table 30: Detailed BLEU and BERTScore (B.S.) in **IOS** scenarios.

Models	Setting	Static		Sequential		Prediction		Description		Caption		Conversation		Avg.	
		BLEU	B.S.	BLEU	B.S.	BLEU	B.S.	BLEU	B.S.	BLEU	B.S.	BLEU	B.S.	BLEU	B.S.
Gemini-Pro-1.5	R.	0.108	0.797	0.142	0.717	0.080	0.682	0.075	0.714	0.011	0.602	0.117	0.746	0.089	0.710
	E.	0.099	0.768	0.136	0.700	0.075	0.655	0.066	0.695	0.011	0.592	0.113	0.743	0.083	0.692
Qwen-VL-Max	R.	0.087	0.704	0.098	0.650	0.112	0.639	0.009	0.519	0.003	0.465	0.106	0.725	0.069	0.617
	E.	0.075	0.638	0.095	0.647	0.094	0.600	0.009	0.512	0.009	0.475	0.103	0.712	0.064	0.597
	H.	0.080	0.632	0.083	0.589	0.092	0.617	0.013	0.520	0.007	0.452	0.099	0.703	0.062	0.585
GPT-4V	R.	0.159	0.824	0.224	0.772	0.206	0.766	0.040	0.673	0.030	0.579	0.174	0.777	0.139	0.732
	E.	0.149	0.813	0.201	0.752	0.207	0.746	0.035	0.659	0.017	0.566	0.160	0.762	0.128	0.716
	H.	0.156	0.805	0.205	0.745	0.203	0.748	0.034	0.644	0.025	0.559	0.159	0.763	0.130	0.711
GPT-4o	H.	0.137	0.802	0.196	0.761	0.199	0.732	0.035	0.683	0.022	0.533	0.154	0.774	0.124	0.714
ChatUnivi	-	0.093	0.679	0.085	0.604	0.106	0.616	0.005	0.437	0.000	0.258	0.076	0.698	0.061	0.548
Minigt4Video	-	0.026	0.547	0.026	0.513	0.035	0.548	0.001	0.411	0.000	0.236	0.015	0.529	0.017	0.464
VideoChat2	-	0.089	0.683	0.078	0.605	0.061	0.555	0.002	0.355	0.000	0.190	0.086	0.710	0.053	0.516
GUI-Vid	-	0.114	0.725	0.144	0.693	0.123	0.700	0.048	0.641	0.002	0.518	0.083	0.686	0.085	0.661

Table 31: Detailed BLEU and BERTScore (B.S.) in **Android** scenarios.

Models	Setting	Static		Sequential		Prediction		Description		Caption		Conversation		Avg.	
		BLEU	B.S.	BLEU	B.S.	BLEU	B.S.	BLEU	B.S.	BLEU	B.S.	BLEU	B.S.	BLEU	B.S.
Gemini-Pro-1.5	E.	0.089	0.771	0.189	0.704	0.189	0.710	0.023	0.619	0.016	0.570	0.149	0.749	0.109	0.687
Qwen-VL-Max	R.	0.041	0.640	0.084	0.528	0.066	0.549	0.008	0.484	0.004	0.445	0.089	0.673	0.049	0.553
	E.	0.037	0.634	0.074	0.498	0.065	0.541	0.005	0.443	0.003	0.383	0.089	0.683	0.045	0.530
GPT-4V	R.	0.106	0.809	0.242	0.757	0.210	0.733	0.029	0.653	0.028	0.619	0.170	0.763	0.131	0.723
	E.	0.089	0.771	0.192	0.705	0.190	0.713	0.023	0.619	0.016	0.571	0.150	0.750	0.110	0.688
GPT-4o	H.	0.075	0.809	0.241	0.755	0.188	0.719	0.038	0.677	0.014	0.581	0.137	0.747	0.116	0.715
ChatUnivi	-	0.076	0.675	0.079	0.588	0.096	0.594	0.007	0.482	0.001	0.368	0.063	0.670	0.054	0.563
Minigt4Video	-	0.017	0.416	0.013	0.369	0.019	0.405	0.000	0.279	0.000	0.103	0.010	0.392	0.010	0.327
VideoChat2	-	0.057	0.641	0.077	0.560	0.063	0.523	0.004	0.402	0.000	0.272	0.075	0.654	0.046	0.509
GUI-Vid	-	0.083	0.682	0.130	0.628	0.126	0.644	0.023	0.500	0.001	0.393	0.071	0.659	0.072	0.584

Table 32: Detailed BLEU and BERTScore (B.S.) in **Multiple-windows** scenarios.

Models	Setting	Static		Sequential		Prediction		Description		Caption		Conversation		Avg.	
		BLEU	B.S.	BLEU	B.S.	BLEU	B.S.	BLEU	B.S.	BLEU	B.S.	BLEU	B.S.	BLEU	B.S.
Gemini-Pro-1.5	R.	0.113	0.739	0.126	0.693	0.086	0.658	0.061	0.685	0.012	0.586	0.090	0.674	0.081	0.673
	E.	0.106	0.728	0.131	0.680	0.072	0.622	0.055	0.655	0.015	0.550	0.084	0.679	0.077	0.652
Qwen-VL-Max	R.	0.079	0.599	0.076	0.591	0.080	0.595	0.002	0.444	0.006	0.370	0.072	0.666	0.053	0.544
	E.	0.064	0.609	0.087	0.567	0.089	0.608	0.003	0.445	0.004	0.398	0.073	0.647	0.053	0.546
	H.	0.089	0.634	0.078	0.580	0.093	0.612	0.003	0.409	0.005	0.344	0.080	0.656	0.058	0.539
GPT-4V	R.	0.172	0.800	0.186	0.737	0.212	0.745	0.040	0.671	0.021	0.592	0.145	0.728	0.129	0.712
	E.	0.160	0.763	0.169	0.703	0.198	0.759	0.034	0.621	0.012	0.527	0.116	0.709	0.115	0.680
	H.	0.173	0.781	0.196	0.748	0.220	0.775	0.046	0.672	0.021	0.577	0.133	0.724	0.132	0.713
GPT-4o	H.	0.156	0.792	0.185	0.754	0.213	0.769	0.040	0.683	0.019	0.588	0.121	0.717	0.122	0.717
ChatUnivi	-	0.076	0.628	0.063	0.573	0.103	0.605	0.009	0.413	0.000	0.191	0.057	0.643	0.051	0.509
Minigt4Video	-	0.015	0.504	0.024	0.473	0.023	0.527	0.001	0.326	0.000	0.155	0.009	0.469	0.012	0.409
VideoChat2	-	0.098	0.657	0.081	0.593	0.067	0.577	0.007	0.344	0.000	0.162	0.065	0.654	0.053	0.498
GUI-Vid	-	0.128	0.737	0.144	0.664	0.133	0.721	0.041	0.605	0.004	0.452	0.058	0.644	0.084	0.637




Figure 16: Fine-grained performance of Gemini-Pro-1.5 in each software and website.




Figure 17: Fine-grained performance of Qwen-VL-Max in each software and website.

820 F Prompts

821 In this section, we provide detailed prompts for models and human annotators. [Figure 19](#) shows the
822 guideline of human annotation, [Figure 18](#) shows the prompt for leveraging LLMs to refine grammarly
823 mistakes and polish sentence for human annotations. [Figure 20](#), [Figure 21](#), and [Figure 22](#) present
824 the prompt for Human-MLLM collaboration method to generate GUI-orientaed tasks. [Figure 23](#)
825 illustrate the prompt for benchmarking MLLMs, different GUI scenarios and different QA type has
826 different prompt. [Figure 24](#) and [Figure 25](#) show prompt for LLM-as-a-Judge for free-form as well as
827 conversational tasks and multiple-choice QA respectively.

Refining Human Annotation on Goal and Sub-goal

As an expert in English, please refine the following English instructions (or objectives) into a polished phrase or a concise sentence.
Avoid including irrelevant content and provide the polished output directly.
Here is the English sentence: {string}

Figure 18: Refining Human Annotation on Goal and Sub-goal.

Guideline for Human Annotation

Main Interface

1. Video List Panel (Left Panel): Displays a list of loaded video files. Each video file is shown with its name for identification.
2. Video Display Area (Center Panel): Shows the currently selected video for playback and annotation.
3. Control Settings (Right Panel):
Operating System: Select the operating system of the machine where the video was recorded.
Full Screen: Toggle full screen mode for the video display.
Multi-application?: Indicate if multiple applications in the video.
Application/Website: Enter the name of the application or website being used in the video.
User Goal: Enter the goal of the user performing the annotation.
4. Playback and Annotation Controls (Bottom Panel)
Annotate: Open a annotation window to add a new keyframe annotation.
Play: Starts or pauses the video playback.
Load Video: Allows you to load a single video file.
Load Video Folder: Allows to load multiple video files from a folder.
Previous Video / Next Video: Navigate through the loaded video files.
Save to JSON: Save the annotations in a JSON format.

Annotation Window

1. Mouse Action: Select a type of mouse action (e.g. click, drag).
2. Keyboard Action: Select the type of keyboard action (e.g., typing, key press).
3. Keyboard Operation Record: Enter details of the keyboard operation, if any.
4. sub-action Purpose: Describe the purpose of the action being annotated.

How to Use

Loading Videos

1. Load Multiple Videos
Click on the Load Video Folder button.
Select the folder containing your video files.
All video files in the folder will be loaded and listed in the Video List Panel.

Playing Videos

Select a video from the Video List Panel. Click the Play button to start or pause the video.

Annotating Videos

1. Start Annotation
Pause the video at the desired frame.
Click the Annotate button to open the annotation window.
2. Annotation Window
Select the Mouse Action Type and Keyboard Action Type from the drop-down menus.
If there is a keyboard action, enter the details in the Keyboard Operation Record field.
Describe the action's purpose in the Sub-action Purpose field.
Click OK to save the annotation.

Saving Annotations

Once all annotations are completed, click the Save to JSON button.

Figure 19: Guideline for Human Annotation.

(Part 1) GPT-4V Generating GUI-oriented Tasks

You are an AI visual assistant. This is a video of a mobile GUI, which I've divided into multiple frames and sent to you. Please provide a detailed description of what occurs throughout the entire video, focusing on the changes in the GUI elements or scenes rather than static aspects of a single frame. The detailed description should be placed under the key 'Description'. Based on your description, please design the following tasks:

Generate a precise caption for the video. This caption should encapsulate the main activities or changes observed throughout the video sequence. Place this caption under the key 'Caption'.

Create a free-form QA question related to the video's static GUI content, along with its answer. The question should delve into the details or changes in the static GUI elements or scenes captured in the video. The QA task should be nested under the key 'static QA', with 'Question' and 'Answer' as subkeys.

Develop a multiple-choice QA question about the video, with four options: one correct answer and three incorrect or irrelevant options. This task should assess the understanding of specific elements retrieval or changes depicted in the video. Structure this task under the key 'MCQA', with 'Question' detailing the query, 'Options' listing the four choices including one correct answer, and 'Correct Answer' specifying the correct option, denoted, for example, as `[[B]]`.

Here are some key information of the video to help you understand the video comprehensively:

System: `{item['system']}`

Application: `{item['app']}`

Summary of the video: `{item['goal']}`

Key Operation/Sub goal in the video: `{[i['sub_goal'] for i in item['keyframes']]}`

Notice: Ensure that the questions you design for these tasks are answerable and the answers can be deduced from the GUI video content. The answerable question should be designed as difficult as possible. The tasks should be unambiguous and the answers must be definitively correct based on your understanding of the video content. Only include questions that have definite answers: (1) one can see the content in the image that the question asks about and can answer confidently; (2) one can determine confidently from the image that it is not in the image. Do not ask any question that cannot be answered confidently.

Each of these tasks should focus on the dynamic aspect of the GUI elements or scenes. Provide detailed answers when answering complex questions. For example, give detailed examples or reasoning steps to make the content more convincing and well-organized. The answers should be in a tone that a visual AI assistant is seeing the image and answering the question.

For the free-form QA tasks, please ensure that the answers are as detailed and lengthy as possible, with no concern for length. You can include multiple paragraphs if necessary to provide a comprehensive and thorough response. Please structure your response using JSON format and specific keys mentioned in the task requirements.

Figure 20: (Part 1) GPT-4V Generating GUI-oriented Tasks.

(Part 2) GPT-4V Generating GUI-oriented Tasks.

You are an AI visual assistant. This is a video of a <Scene Name> GUI, which I've divided into multiple frames and sent to you. Please provide a detailed description of what occurs throughout the entire video, focusing on the changes in the GUI elements or scenes rather than static aspects of a single frame. The detailed description should be placed under the key 'Description'. Based on your description, please design the following tasks:

A Sequential QA task: Design a question that requires understanding the sequence of GUI element changes or scene transformations in the video. The question should be free-form and necessitate the use of temporal information from the sequential images. The task should be structured under the key 'Sequential-QA' with subkeys 'Question' and 'Answer'.

A Next Stage Prediction task: Formulate a question that asks about the subsequent state or event following a certain frame in the video. The question should be designed in a free-form manner and predict future GUI elements or scene changes, structured under the key 'Prediction' with subkeys 'Question' and 'Answer'.

A two-round dialogue task: Create a dialogue with two rounds of interaction. The first round includes a user instruction and an assistant response, and the second round's user instruction should be based on the response from the first round. Both rounds should be free-form and nested under the key 'Conversation', with subkeys 'User 1', 'Assistant 1', 'User 2', and 'Assistant 2'.

A reasoning task: Design a multi-choice QA task that requires reasoning to identify the correct answer from four options. This task should test the reasoning ability to infer or deduce information that is not explicitly provided. It should be structured under the key 'Reasoning', with subkeys 'Question', 'Options', and 'Correct Answer'. Here are some key information of the video to help you understand the video comprehensively:

System: {item['system']}

Application: {item['app']}

Summary of the video: {item['goal']}

Key Operation/Sub goal in the video: {[i['sub_goal'] for i in item['keyframes']]}

Figure 21: (Part 2) GPT-4V Generating GUI-oriented Tasks.

(Part 3) GPT-4V Generating GUI-oriented Tasks.

Notice: Ensure that the questions you design for these tasks are answerable and the answers can be deduced from the GUI video content. The answerable question should be designed as difficult as possible. The tasks should be unambiguous and the answers must be definitively correct based on your understanding of the video content. Only include questions that have definite answers: (1) one can see the content in the image that the question asks about and can answer confidently; (2) one can determine confidently from the image that it is not in the image. Do not ask any question that cannot be answered confidently.

Each of these tasks should focus on the dynamic aspect of the GUI elements or scenes, with each answerable task as difficult as possible. Provide detailed answers when answering complex questions. For example, give detailed examples or reasoning steps to make the content more convincing and well-organized. The answers should be in a tone that a visual AI assistant is seeing the image and answering the question.

For the free-form QA tasks, please ensure that the answers are as detailed and lengthy as possible, with no concern for length. You can include multiple paragraphs if necessary to provide a comprehensive and thorough response. Please structure your response using JSON format and specific keys mentioned in the task requirements.

Figure 22: (Part 3) GPT-4V Generating GUI-oriented Tasks.

Prompts for Benchmarking MLLMs

"XR": "You are an AI visual assistant. Here are sequential images of Mixed-Reality combining GUI interface and real world, which are selected from a GUI video.",
"software": "You are an AI visual assistant. Here are sequential GUI interface images of a specific software, which are selected from a GUI video.",
"website": "You are an AI visual assistant. Here are sequential GUI interface images of a desktop website, which are selected from a GUI video.",
"mobile": "You are an AI visual assistant. Here are sequential GUI mobile interface images, which are selected from a GUI video.",
"multi": "You are an AI visual assistant. Here are sequential GUI interface images of interaction among multiple softwares and websites, which are selected from a GUI video.",
"IOS": "You are an AI visual assistant. Here are sequential GUI IOS interface images, which are selected from a GUI video.",

"Sequential-QA": "This is a question about sequential information in sequential images.",
"Prediction": "This is a question about predicting the next action base on the previous actions in the sequential images.",
"Reasoning": "This is a multiple choice question with only one correct answer. This question may need multiple steps of reasoning according to the vision information in sequential images.",
"Description1": "Please give me a detail description of these sequential images.",
"Description2": "Offer a thorough analysis of these sequential images",
"Caption": "Please give me a concise caption of these sequential images.",
"static QA": "This is a question about static information such as text, icon, layout in these sequential images.",
"MCQA": "This is a multiple choice question with only one correct answer. This question may require sequential analysis ability to the vision information in these sequential images.",
"Conversation1": "Act as an assistant to answer the user's question in these sequential images.",
"Conversation2": "This is a multi-turn conversation task. You will be provide the first round conversation and act as an assistant to answer the user's question in the second round according to these sequential images."
Notice = "You can first provide an overall description of these sequential images, and then analyze the user's question according to the sequential images and description. Finally, give an answer based on this description and the image information. Please format your output in a Json format, with key 'Description' for the description of these sequential images, key 'Analysis' for your analysis on the user's question and key 'Answer' for your answer to the User's question."

Figure 23: Prompts for Benchmarking MLLMs.

Prompt for LLM-as-a-Judge: Judging Free-form and Conversational Tasks

You are an impartial judge. I will provide you with a question, a 'gold standard' answer, and a response that needs evaluation. Your task is to assess the quality of the response in comparison to the 'gold standard' answer. Please adhere to the following guidelines:

1. Start your evaluation by comparing the response to the 'gold standard' answer. Offer a brief explanation highlighting similarities and differences, focusing on relevance, accuracy, depth, and level of detail.
 2. Conclude your evaluation with a score from 1 to 5, where 1 indicates the response is mostly irrelevant to the 'gold standard' answer, and 5 indicates it is very similar or equivalent.
 3. Present your findings in JSON format, using 'Evaluation' for your textual analysis and 'Score' for the numerical assessment.
 4. Ensure objectivity in your evaluation. Avoid biases and strive for an even distribution of scores across the spectrum of quality.
- Your scoring must be as rigorous as possible and adhere to the following rules:

- Overall, the higher the quality of the model's response, the higher the score, with factual accuracy and meeting user needs being the most critical dimensions. These two factors largely dictate the final composite score.
- If the model's response is irrelevant to the question, contains fundamental factual errors, or generates harmful content, the total score must be 1.
- If the model's response has no severe errors and is essentially harmless, but of low quality and does not meet user needs, the total score should be 2.
- If the model's response generally meets user requirements but performs poorly in certain aspects with medium quality, the total score should be 3.
- If the model's response is close in quality to the reference answer and performs well in all dimensions, the total score should be 4.
- Only when the model's response surpasses the reference answer, fully addresses the user's problem and all needs, and nearly achieves a perfect score in all dimensions, can it receive a score between 5.
- As an example, the golden answer could receive a 4-5.

Here is the response for you to judge:

Question: {question}

Golden Answer: {golden_answer}

Response: {response}

Now, directly output your response in json format.

Figure 24: Prompt for LLM-as-a-Judge: Judging Free-form and Conversational Tasks .

Prompt for LLM-as-a-Judge: Judging Multiple-Choice QA Tasks

You are a helpful assistant tasked with judging a Multiple Choice Question Answering exercise.

I will provide a correct answer with only one option, and a response that requires evaluation.

If the response matches the correct answer, simply output "Yes"; If it does not, output "No".

Please avoid including any irrelevant information.

Here are some examples:

Example 1:

Question: Based on the GUI video, why might the 'Loading' animation continue without reaching the next stage? A. The user has not yet entered their login credentials. B. There is a system update being installed. C. The server is taking time to authenticate the login credentials. D. The 'Log In' button is malfunctioning.

Answer: C

Response: C. The server is taking time to authenticate the login credentials.

Output: Yes

Example 2:

Question: If the user wants to resume the group video call after checking messages, what action should they take? A. Turn their head to the right. B. Close the messaging app interface. C. Say a voice command to switch applications. D. Turn their head to the left.

Answer: A

Response: B

Output: No

Example 3:

Question: What action does the user take to start playing music in the video? A. Closed the music player application B. Moved the music player to a new position C. Clicked the play button D. Adjusted the system volume

Answer: [[B]]

Response: C

Output: No

Here is the question, answer, and response for you to judge:

Question: {question}

Answer: {answer}

Response: {response}


Now, directly output "Yes" or "No".

Figure 25: Prompt for LLM-as-a-Judge: Judging Multiple-Choice QA Tasks.

828 **G Case Study**

829 In this section, we provide detailed case studies for six GUI scenarios, each divided into two parts.
830 **Figure 26** and **Figure 27** show example frames and various tasks associated with them. **Figure 28**
831 and **Figure 29** for IOS, **Figure 30** and **Figure 31** for multiple-windows interaction, **Figure 34** and
832 **Figure 35** for website, and **Figure 36** and **Figure 37** for XR respectively.

(Part 1) Android



'Description1': "The video starts with a view of a mobile app interface, specifically an Al-Qur'an Indonesia app with a list of Surahs. A user scrolls through the Surah list, selects a specific Surah, and the view transitions to a page displaying the verses in Arabic and their Indonesian translation. The user then returns to the Surah list. Following this, a pop-up appears indicating a configuration process that takes approximately 10-20 seconds. After the configuration, another pop-up notifies of an available update from the Google Play Store, which the user can accept or postpone. The user dismisses this pop-up. The main menu is accessed, showing options such as 'Baca Quran', 'Terakhir Baca', 'Pencarian', 'Jadwal Sholat', and 'Pengaturan'. The user selects the 'Pencarian' option, which leads to a search page. Here, the user is instructed to enter a keyword to search in the translation database. Finally, the user navigates back to the main menu and then to the Surah list once more."

'Sequential-QA': 'Question': 'After selecting a specific Surah from the list, what does the user do next before a pop-up notification appears?'

'Answer': 'After selecting a Surah, the user views the verses in Arabic and their Indonesian translation. Then, the user returns to the Surah list before a pop-up notification appears.'

'Prediction': 'Question': 'What would likely be the next step in the app interface after the user is directed to the search page?'

'Answer': "After being directed to the search page, the likely next step would be for the user to enter a keyword into the search bar to find a translation or meaning within the app's database."

'Conversation': 'User 1': 'I need to find a specific verse in the Quran. How do I search for it?'

'Assistant 1': "You can search for a specific verse by tapping on the 'Pencarian' option in the main menu, which will take you to a search page where you can enter a keyword."

'User 2': 'I see. And how do I get back to the main menu from the search page?'

'Assistant 2': 'To return to the main menu from the search page, you can tap on the back arrow located at the top left corner of the screen.'


'Reasoning': 'Question': "If the user wants to read the verses of Surah 'Al-Infitar', what should they do after launching the app?"

'Options': ["A. Go to the settings and select 'Al-Infitar'."], "B. Scroll through the Surah list and select 'Al-Infitar'."], "C. Choose the 'Pencarian' option and type 'Al-Infitar'."], "D. Wait for a pop-up and select 'Al-Infitar' from there."]

'Correct Answer': "B. Scroll through the Surah list and select 'Al-Infitar'."

Figure 26: Case study for Android (part 1).

(Part 2) Android



'Description2': "The video begins by displaying a mobile GUI with a list of chapters from the Quran in Indonesian. Each chapter has a downward arrow suggesting expandable content. As the video progresses, a popup appears with a loading icon and a message in Indonesian indicating a configuration is in progress, which takes about 10-20 seconds. After this, another popup appears notifying of a new update available on the Google Play Store with options to update or postpone. Subsequently, the screen shows a search interface where users can input keywords for searching within the Quran's translated database. The main menu is then accessed, with options such as 'Read Quran', 'Last Read', 'Search', 'Prayer Schedule', and 'Settings'. The GUI transitions back to the list of chapters, and a specific chapter, At-Takwir, is selected. The video then displays the verses of this chapter, both in Arabic and Indonesian translation, with an option to listen to the audio. Finally, it navigates back to the list of chapters."

'Caption': "Navigating through a Quran app's GUI, interacting with chapter lists, update notifications, search function, and viewing specific verses with translations."

'static QA': 'Question': 'What options are available in the main menu of the mobile Quran application?'

'Answer': "The main menu of the mobile Quran application provides several options for the user to choose from. These include 'BACA QURAN' (Read Quran) for accessing the chapters to read, 'TERAKHIR BACA' (Last Read) to resume reading from where the user left off last time, 'PENCARIAN' (Search) to search the Quran's database for specific keywords, 'JADWAL SHOLAT' (Prayer Schedule) to check the prayer times, and 'PENGATURAN' (Settings) to modify app settings. This menu provides a simple and efficient way for users to navigate through the app's features and customize their reading and learning experience."


'MCQA': 'Question': 'What happens after the user is notified about the new update available on the Google Play Store?'

'Options': 'A': 'The app closes automatically.', 'B': 'The search interface is displayed.', 'C': 'The list of chapters disappears.', 'D': 'An advertisement for shopping deals is shown.'

'Correct Answer': '[[B]] The search interface is displayed.'

Figure 27: Case study for Android (part 2).

(Part 1) IOS



'Description1': "The video demonstrates a user navigating through the Khan Academy mobile application under the 'Computing' category. Initially, the user scrolls through the 'Computers and the Internet' section, viewing topics such as 'Digital information,' 'Bits and bytes,' 'The Internet,' and 'Online data security.' The user then scrolls to the bottom, revealing the 'Computing innovations' section and the 'Take Course Challenge' button. Subsequently, the user returns to the previous screen, displaying other computing sections like 'AP®/College Computer Science Principles' and 'Computer science theory.' The user clicks to enter the 'Computer science theory' interface; the content is loading. After the content has loaded, revealing topics like 'Cryptography' and 'Information theory,' the user returns to the previous page and clicks on 'Code.org.'"

'Caption': "Navigating through computing courses on Khan Academy's mobile application, viewing sections, and attempting to enter 'Computer science theory.'"

'static QA': 'Question': "Which topic appears directly below 'Online data security' in the 'Computers and the Internet' section before scrolling down?"

'Answer': "Before scrolling down, the topic that appears directly below 'Online data security' is 'Computing innovations.' This can be confirmed from the initial frames of the video where the 'Computing innovations' section is partially visible, indicating that it is the next topic in the sequence after 'Online data security.' As the video progresses and the user scrolls down, the full 'Computing innovations' section comes into view, affirming its position in the GUI layout."


'MCQA': 'Question': "What action does the user take after viewing the 'Computing innovations' section?"

'Options': ["A) Scrolls up to view 'Digital information' again.", "B) Returns to the previous screen showing different computing sections.", "C) Clicks on the 'Take Course Challenge' button.", "D) Taps on the 'Explore' tab at the bottom of the screen."]

'Correct Answer': "[B] Returns to the previous screen showing different computing sections.'

Figure 28: Case study for IOS (part 1).

(Part 2) IOS



'Description2': "The video begins with the user viewing the 'Computers and the Internet' course section within the Khan Academy application. The user scrolls through various subsections such as 'Digital information,' 'Computers,' 'The Internet,' and 'Online data security,' each with a list of topics and a status of possible mastery points. The user continues to scroll down to the 'Computing innovations' section and then further down to a 'Course challenge' prompt. The user then scrolls back up, revealing previously seen sections in reverse order. The user eventually navigates back to the main 'Computing' category screen, showing an overview of all computing-related courses. From there, the user selects 'Computer science theory,' which briefly loads before displaying topics within that course such as 'Cryptography' and 'Information theory.' Following this, the user returns to the main 'Computing' category screen."

'Sequential-QA': 'Question': "What action does the user take after scrolling through the 'Online data security' section, and what is displayed as a result of this action?", 'Answer': "After scrolling through the 'Online data security' section, the user scrolls down to the 'Computing innovations' section. As a result of this action, topics such as 'Communication innovations', 'Collaboration innovations', 'Crowdsourcing innovations', and 'Monitoring innovations' are displayed, followed by a 'Course challenge' prompt."

'Prediction': 'Question': "If the user were to select the 'Cryptography' section after it was displayed, what kind of content could you predict will be shown next?"

'Answer': "If the user selects the 'Cryptography' section, one could predict that the next content shown would be detailed topics under Cryptography, such as 'Ancient cryptography,' 'Ciphers,' 'Cryptography challenge 101,' 'Modern cryptography,' 'Modular arithmetic,' 'Primality test,' and 'Randomized algorithms,' along with the status of possible mastery points for that section."

'Conversation': 'User 1': 'Can you take me to the section about user authentication methods?'

'Assistant 1': "Sure, you will need to scroll down the 'Computers and the Internet' course section until you reach the 'Online data security' subsection, where you will find the topic 'User authentication methods.'"

'User 2': "I scrolled too far down and reached the course challenge. How do I find 'User authentication methods' from here?"

'Assistant 2': "No problem, you'll need to scroll back up past the 'Computing innovations' section until you see the 'Online data security' subsection again. 'User authentication methods' is listed there among other topics."


'Reasoning': 'Question': "After browsing through the course topics in 'Computers and the Internet,' the user returns to a broader category view. Based on this behavior, what could be the reason for the user returning to the broader category view?"

'Options': ['A. The user wants to take a course challenge.', 'B. The user is looking for a different computing-related course.', 'C. The application automatically redirected the user.', 'D. The user intends to log out of the Khan Academy application.']

'Correct Answer': 'B'

Figure 29: Case study for IOS (part 2).

(Part 1) Multiple-Windows Interaction



'Description1': "The video begins with a Windows desktop displaying multiple open applications, including Steam, OBS Studio, and a web browser with NVIDIA's website loaded. The user starts by clicking on the back page of the browser, which partially obscures the OBS window. Then, the user clicks on the OBS application, bringing it to the foreground. The user minimizes OBS, followed by dragging the Steam window to the center of the screen and minimizing it as well. A new web page is opened in the Edge browser's navigation bar, and the user types 'office' into the search bar. The browser navigates to the Bing search interface, and 'office' is successfully searched."

'Caption': 'Navigating and Managing Multiple Applications on Windows Including Steam, OBS Studio, and Edge Browser'

'static QA': **'Question'**: "Which web browser is used in the video and which website is prominently featured before the search for 'office'?"

'Answer': "The web browser used in the video is Microsoft Edge.

The prominently featured website before the search for 'office' is NVIDIA's official website where the 'Download Drivers' page is displayed."


'MCQA': **'Question'**: 'What action is taken after the OBS application is minimized?', **'Options'**: ['A. The Steam window is closed.'

'B. The Steam window is moved to the center of the screen and minimized.', 'C. The Edge browser is closed.', 'D. A file is opened from the desktop.']

'Correct Answer': '[[B]] The Steam window is moved to the center of the screen and minimized.'

Figure 30: Case study for multiple-windows interaction (part 1).

(Part 2) Multiple-Windows Interaction



'Description2': "The video shows a Windows desktop with several application windows open, including Steam, OBS, and Edge. Initially, the OBS window is partially covering the Edge browser. The user clicks on the Edge browser, bringing it to the foreground, and then minimizes the OBS window, clearing the view. Next, the user moves the Steam window to the center of the screen and minimizes it as well. Afterward, the user opens a new tab in Edge and enters 'office' into the search bar, which leads to a Bing search results page for 'office'. The video ends with the user on the Bing search page with 'office' results displayed."

'Sequential-QA': 'Question': 'After moving the Steam window to the center, what did the user do next in the Edge browser?'

'Answer': "After moving the Steam window to the center, the user minimized the Steam application. Then, they opened a new tab in the Edge browser and entered 'office' into the search bar, which led them to the Bing search results page for 'office'."

'Prediction': 'Question': "What would be the likely next action the user performs after searching for 'office' on Bing?"

'Answer': "The likely next action the user would perform after searching for 'office' on Bing would be to click on one of the search results to find more information or to visit the Microsoft Office website to purchase or learn more about the office suite."

'Conversation': 'User 1': 'Can you minimize the OBS application for a better view of the browser?'

'Assistant 1': 'Certainly, the OBS application has been minimized, providing a clear view of the Edge browser.'

'User 2': 'Great, now can you search for Microsoft Office in the Edge browser?'

'Assistant 2': "Of course, a new tab has been opened in the Edge browser and 'office' has been entered into the search bar. The Bing search results for 'office' are now displayed."


'Reasoning': 'Question': 'If the user needs to record gameplay footage next, which application should they interact with and what would be their first step?'

'Options': ["A. They should open the Steam application and click on the 'STORE' tab.", "B. They should open the Edge browser and search for 'game recording software'.", "C. They should reopen the OBS application and click on the 'Start Recording' button.", "D. They should access the Windows Start menu and search for the 'Camera' app."]

'Correct Answer': 'C'

Figure 31: Case study for multiple-windows interaction (part 2).

(Part 1) Software



'Description1': "The video shows a Python 3.7.4 Shell window on a Windows system. The user begins by typing the 'print' function followed by a pair of parentheses. Inside the parentheses, the user types a string, 'Hello World', which is enclosed in double quotes. Upon pressing Enter, the Python Shell executes the command and outputs the text 'Hello World' below the command line, indicating that the code ran successfully without any errors."

'Caption': "Executing the print command in Python Shell to display 'Hello World'"

'static QA': "Question": "What version of Python is shown running in the video?"

"Answer": "The version of Python running in the video is Python 3.7.4, as indicated by the text at the top of the Python Shell window."


'MCQA': "Question": "What operation does the user perform after typing the print command?"

"Options": ["A. The user saves the file.", "B. The user compiles the code.", "C. The user executes the print command.", "D. The user closes the Python Shell."]

"Correct Answer": "[[C]] The user executes the print command."

Figure 32: Case study for software (part 1).

(Part 2) Software



'Description2': "The video shows a sequence of a user interacting with the Python Shell on a Windows system. Initially, the shell is open and waiting for input. The user begins by typing 'print*' and then corrects the typo by removing the asterisk, typing 'print'. They then type two quotation marks to prepare for a string input. Subsequently, the user moves the cursor between the quotation marks and types 'Hello World' to complete the 'print(Hello World)' command. After pressing enter, the shell executes the command, and the phrase 'Hello World' is outputted below the command prompt."

'Sequential-QA': "Question": "Can you describe the sequence of actions the user took to correct the command and output 'Hello World'?"

"Answer": "Certainly. Initially, the user typed 'print*' but realized the asterisk was a mistake. They deleted the asterisk to correct the command to 'print'. Next, they entered two quotation marks to indicate the start of a string. The user then placed the cursor between the quotation marks and typed the string 'Hello World'. Finally, upon pressing enter, the Python Shell executed the command and displayed the output 'Hello World' beneath the command prompt."

'Prediction': "Question": "What would be the expected GUI change if the user were to type another command after the 'Hello World' output?"

"Answer": "If the user were to type another command after the 'Hello World' output, the expected GUI change would be that the command prompt indicator '>>' would appear on a new line below the 'Hello World' output, signaling readiness for the next command input. Any subsequent command typed by the user would appear after this new prompt, awaiting execution."

'Conversation': "User 1": "I want to print a different message in Python. How can I do that?", "Assistant 1": "To print a different message, you can simply type 'print(Your Message Here)' where 'Your Message Here' is the text you wish to print. Make sure you enclose your message in quotation marks and hit enter to execute the command."

"User 2": "What if I want to print 'Goodbye, World' instead?"

"Assistant 2": "To print 'Goodbye, World', you would type 'print(Goodbye, World)' and press enter. The Python Shell will execute the command and display 'Goodbye, World' as the output below the command prompt."


'Reasoning': "Question": "What command did the user execute to get the output in the Python Shell?"

"Options": ["A. print(Hello World)", "B. print(Hello World)", "C. print(Hello World)", "D. echo(Hello World)"]

"Correct Answer": "C",

Figure 33: Case study for software (part 2).

(Part 1) Website



'Description1': "The video begins with the Google search results page visible on a Windows system browser, displaying the query 'is oatmeal a healthy breakfast'. The mouse cursor scrolls down the page, revealing additional search results, and the 'People also ask' section with related questions. The user then scrolls back up to the top of the page. Next, the cursor moves to the search bar, and the 'X' button is clicked to clear the previous search content, leaving an empty search bar. The browser's suggested searches drop-down menu appears with various related search queries. Finally, the video fades to black, indicating the end of the sequence."

'Caption': 'Navigating Google Search Results and Clearing the Search Query on a Windows System Browser'

'static QA': 'Question': "What feature snippet is displayed at the top of the Google search results for the query 'is oatmeal a healthy breakfast'?"

'Answer': "The featured snippet at the top of the Google search results for the query 'is oatmeal a healthy breakfast' is from the Harvard T.H. Chan School of Public Health website. It includes an excerpt stating 'Whether it's steel-cut or rolled, quick-cooking or instant, oatmeal is good for you, experts say-with a few caveats. Oatmeal is rich in fiber, which promotes fullness, eases the insulin response, and benefits gut health. It's also a source of vitamins B and E, and minerals such as magnesium.' This snippet provides a concise summary of the health benefits of oatmeal, according to experts, highlighting its nutritional value and potential impact on fullness and insulin response. The presence of this snippet offers a quick and authoritative answer to the user's query, showcasing Google's ability to extract relevant information from web pages and present it prominently for ease of access."


'MCQA': 'Question': 'What action did the user take after reviewing the search results?'

'Options': ['A. The user clicked on one of the search results.', "B. The user scrolled through the 'People also ask' section.", 'C. The user cleared the search content in the search bar.', 'D. The user navigated to a different website.']

'Correct Answer': '[[C]] The user cleared the search content in the search bar.',

Figure 34: Case study for website (part 1).

(Part 2) Website



'Description2': "The video shows a sequence of actions on a Google search results page within a web browser on a Windows system. Initially, the mouse cursor moves over a search result discussing the health benefits of oatmeal. Next, the user scrolls down, revealing a 'People also ask' section with questions related to oatmeal and a 'Videos' section showcasing related content. Subsequently, the user scrolls back up to the original position, highlighting the same search result about oatmeal's health benefits. Finally, the user moves the cursor to the search bar and clicks the 'X' to clear the previous search content, resulting in a blank search bar with suggestions and related searches listed below it. The screen then goes black, indicating the end of the video."

'Sequential-QA': 'Question': "After reading about oatmeal's health benefits, what section of the page did the user explore next and did they return to read more about the health benefits afterward?"

'Answer': "After reading about the health benefits of oatmeal, the user scrolled down to explore the 'People also ask' section and the 'Videos' section related to oatmeal. Following this, the user scrolled back up to revisit the original search result that discussed the health benefits of oatmeal."

'Prediction': 'Question': 'Based on the sequence of events, what action is the user likely to perform after clearing the search bar?'

'Answer': 'After clearing the search bar, the user is likely to type in a new search query or select one of the suggested searches that appear below the search bar.'

'Conversation': 'User 1': "I want to find more articles on oatmeal's health benefits. Can you scroll back up?"

'Assistant 1': "I've scrolled back up and the article on oatmeal's health benefits from the Harvard T.H. Chan School of Public Health is highlighted again."

'User 2': 'Great, now can you clear the search and look for something else?'

'Assistant 2': 'The search content has been cleared, and the search bar is now empty, showing a list of related searches and previous search history suggestions for a new query.'


'Reasoning': 'Question': 'If the user wants to perform a new search after clearing the search bar, which of the following actions would they need to take next?', 'Options': ['A. Scroll down to view more search results'

'B. Type a new query into the search bar', "C. Click on one of the 'People also ask' questions", 'D. Close the browser window']

'Correct Answer': 'B',

Figure 35: Case study for website (part 2).

(Part 1) XR



'Description1': "The video showcases a user navigating through various pages within the Apple Vision Pro browser on a Windows system. Initially, the browser displays the start page with Favorites and Reading List. The user then turns their head to the right, which triggers the transition to view a webpage on the right side. Following this, the user pinches with both hands to exit the page and then pinches with both hands and fingers moving towards the middle to expand the browser's various pages. This reveals multiple open browser tabs side by side. The user continues to turn their head left and right to view different pages on each side. Lastly, the user selects and expands a specific tab to fill the screen, displaying its content."

'Caption': 'Navigating through multiple browser pages using head movement and hand gestures in Apple Vision Pro on Windows'

'static QA': 'Question': "What is the main category listed under the Favorites section on the browser's start page?"

'Answer': "The main category listed under the Favorites section on the browser's start page is 'Perplexity', denoted by a unique icon, followed by other favorites like Instagram and various websites."


'MCQA': 'Question': 'How does the user switch between different open tabs in the Apple Vision Pro browser?'

'Options': ['A. Using keyboard shortcuts', 'B. Turning their head left and right', 'C. Scrolling with a mouse', 'D. Typing the tab number']

'Correct Answer': '[[B]] Turning their head left and right'

Figure 36: Case study for XR (part 1).

(Part 2) XR



'Description2': "The video starts with a full-screen view of a browser interface titled 'Apple Vision Pro' displaying various website thumbnails and bookmarks. The user then turns their head to the right, causing the right side of the browser to come into view. Next, the user looks at a dot at the bottom of the page and pinches with both hands, which causes the browser to exit the full-screen view and shrink to a smaller, windowed mode. The user then performs a pinching motion with both hands, bringing the fingers towards the middle, which causes the browser's various pages to expand, giving an overview of multiple open tabs. The user again turns their head to the right to view the right side page and then to the left to view the left side page. Throughout the video, the GUI elements such as tabs, the address bar, and website thumbnails respond dynamically to the user's head movements and hand gestures."

'Sequential-QA': 'Question': 'What action did the user take immediately after turning their head to the right to view the right side page?'
'Answer': 'After turning their head to the right to view the right side page, the user looked at a dot at the bottom of the page and pinched with both hands, which caused the browser to exit full-screen mode and shrink to a smaller windowed interface.'

'Prediction': 'Question': 'If the user pinches with both hands and moves their fingers towards the middle after the browser shrinks to a smaller window, what will happen next?'
'Answer': "If the user pinches with both hands and moves their fingers towards the middle after the browser shrinks, the action will cause the browser's various pages to expand, providing an overview of multiple open tabs."

'Conversation': 'User 1': 'How do I view all the pages I have open in the browser?'
'Assistant 1': 'You can view all the open pages by pinching with both hands and moving your fingers towards the middle. This will expand the browser and show an overview of all the open tabs.'

'User 2': 'Great, and how can I exit this overview?'
'Assistant 2': 'To exit the overview of open pages, you can look at the dot at the bottom of the page and pinch with both hands. This will exit the overview and return you to the individual page view.'

'Reasoning': 'Question': 'How can the user access the options to open a new tab or window from the current state?'
'Options': ['A. Turn their head to the left and select the plus sign.', 'B. Swipe left on the touchpad.', 'C. Turn their head to the right and select the 'Done' button.', 'D. Pinch with both hands to exit the current view and access the toolbar.']
'Correct Answer': 'D'

Figure 37: Case study for XR (part 2).