

Geolocation with Real Human Gameplay Data: A Large-Scale Dataset and Human-Like Reasoning Framework

Anonymous ACL submission

Abstract

Geolocation aims to identify an image’s location and requires complex reasoning, playing an important role in navigation, monitoring, and cultural preservation. However, existing methods often yield coarse and non-interpretable predictions. A key challenge is the limited quality and scale of current geolocation datasets, which are typically small, automatically constructed, and suffer from noise and inconsistent difficulty. To address these challenges, we introduce a comprehensive geolocation framework with three key components: **GeoComp**, a large-scale dataset; **GeoCoT**, a novel reasoning method; and **GeoEval**, designed to evaluate the correctness of the geolocation reasoning process. At the core of this framework is GeoComp, a large-scale dataset collected from a geolocation game platform involving 740K users over two years. It comprises 25 million entries of metadata and 2.7 million geo-tagged locations spanning much of the globe, with each location annotated thousands to tens of thousands of times by human users. Building on this dataset, we propose Geographical Chain-of-Thought (GeoCoT), a multi-step reasoning framework designed to enhance the reasoning capabilities of Large Vision Models (LVMs) in geolocation tasks. Finally, we demonstrate that GeoCoT significantly boosts performance by up to 25% on classic geolocation metrics and by 9% in reasoning quality as measured by GeoEval: [Github link](#).

1 Introduction

Geolocation, the task of determining an image’s geographical location, is crucial for applications like crime tracking, navigation, fact-checking, and cultural exploration (Cheng et al., 2022; Chalvatzaras et al., 2022). It involves interpreting contextual clues within an image, such as architectural styles, road signs, natural landscapes, and cultural markers. Inferring location from such diverse indicators

Dataset	Size	Geographic Coverage	Source	Open Access	Human Annotation
Google-WS-15k (Clark et al., 2023a)	15k	Global	Map Service	✗	✗
GMCP (Zamir and Shah, 2014)	105K	Local	Map Service	✗	✗
StreetCLIP (Haas et al., 2023)	1M	Unknown	Map Service	✗	✗
Im2GPS (Hays and Efros, 2008)	237	Local	Web-Scraped	✓	✗
Im2GPS3K (Vo et al., 2017b)	2997	Local	Web-Scraped	✓	✗
YFCC4K (Vo et al., 2017b)	4536	Local	Web-Scraped	✓	✗
YFCC26K (Theiner et al., 2022a)	26k	Local	Web-Scraped	✓	✗
MP-16 (Larson et al., 2017)	4.7M	Local	Web-Scraped	✓	✗
OSV-5M (Astruc et al., 2024)	5.1M	Global	Map Service	✓	✗
GeoComp	2.7M	Global	Map Service	✓	✓

Table 1: Comparison of Existing Geolocation Datasets and GeoComp. “Local” refers to city- or region-specific data, while “Global” spans multiple continents. Darker green shades indicate broader geographic coverage.

demands advanced reasoning, making geolocation a challenging task for both artificial models and human experts (Khan et al., 2024).

Significant effort has been devoted to solving the geolocation task (Vo et al., 2017a; Weyand et al., 2016a; Zhu et al., 2022; Müller-Budack et al., 2018), but often at a coarse level of granularity and unlocalizability. The reason is potentially due to the lack of high-quality datasets. For example, Im2GPS3K contains up to 35% non-localizable images (Astruc et al., 2024), while the YFC100M dataset includes irrelevant data such as indoor photos and food images, which provide little to no locational information (Theiner et al., 2022a). Additionally, many datasets are limited in size, with Georeasoner (Li et al., 2024) featuring only 3K images, thereby restricting the robustness and generalizability of geolocation models. A comparison of these datasets is shown in Table 1.

To address the above obstacles, in this work, we leverage the contributions of hundreds of thousands of geolocation game enthusiasts who provide real user prediction annotations while playing the game. Specifically, we launched a free, public-benefit-oriented online geoguessing platform in June 2022. A screenshot of the platform’s GUI is provided in Appendix A. In each game, two players independently guess the location based on the same image and their own hints, with scores

determined by the distance between their predictions and the ground-truth location. The images are sourced from Google Maps, Baidu Maps, Tencent Maps, and Gaode Maps. The platform offers multiple game modes, allowing users to either choose opponents or join random matchups. As of December 2024, this platform has 740K users, 2.7M locations as unique geolocation tasks, and 25M human response records. We name the collected dataset GeoComp. This rich and valuable dataset of real human responses enables us to evaluate task difficulty and filter out unreasonable cases. For instance, some tasks are too easy, such as when the name of a shopping mall in a city is clearly visible in the image, enabling most users to answer correctly. On the other hand, some tasks are highly challenging, where only a few users spend considerable time before providing accurate answers. Additionally, there are unreasonable tasks that contain no identifiable hints, making them unsolvable for all users despite significant effort.

Unlike previous approaches that address this task with a coarse level of granularity, we conduct a comprehensive evaluation of recent advanced LVMs on GeoComp, where the models are required to reason and predict the exact city of a given location. Our findings reveal that this task poses a significant challenge for existing LVM models. To address this, we introduce a Geographical Chain of Thought (GeoCoT) approach, which automatically guides the reasoning process through multi-step analysis of geographical cues, such as landmarks, environmental features, and spatial relationships. For the evaluation of the reasoning process, we propose a set of articulated evaluation metrics, named as GeoEval including comparison with ground truth reasoning data and intrinsic evaluation. The results demonstrate that our GeoCoT paradigm significantly improves geolocation accuracy. It not only helps break down complex tasks into manageable reasoning steps but also enhances the interpretability of the inference process.

Our work makes key contributions to geolocation. First, we present GeoComp, a large-scale, human-annotated geolocation dataset with over 2.7 million location images with corresponding location labels, and 25 million human player annotations, featuring diverse geographic regions, languages, and environmental contexts. These annotations identify different difficulty geolocation cases and establish benchmarks to guide future advancements. Second, we introduce the Geographical

Chain of Thought framework, a multi-step reasoning approach that improves geolocation accuracy by leveraging geographical cues like landmarks, environmental features, and spatial relationships. Finally, through evaluations involving human assessments and LLM inferences, we show that GeoCoT improves predictive performance by up to 25% while enhancing interpretability.

2 Related work

2.1 Image Geolocation Task

Image geolocation refers to determining the corresponding location of a given image, a crucial task in computer vision (Zhu et al., 2023b,a, 2024b), spatial data mining (Zhao et al., 2017, 2016; Zhang et al., 2023d; Han et al., 2023), and GeoAI (Zhao and Tang, 2017; Zhao et al., 2022; Zhang et al., 2023c,e). Previous research in image geolocalization could be primarily classified into two approaches: classification-based methods and retrieval-based methods. (1) *Classification-based methods* partition most regions of the Earth into multiple grid cells. Models are trained to classify each image into the correct cell (Clark et al., 2023b; Pramanick et al., 2022; Müller-Budack et al., 2018; Seo et al., 2018; Weyand et al., 2016b). The center coordinates of each cell are used as the predicted values. However, due to the limited number of cells, the granularity of the predicted values is coarse, preventing precise predictions. (2) *Retrieval-based methods* establish a database of geographic images with GPS coordinates. For a given input image, these methods retrieve the most similar image from the dataset and use its coordinates as the predicted location (Zhu et al., 2022; Müller-Budack et al., 2018; Zhang et al., 2023a; Workman et al., 2015; Liu and Li, 2019; Zhou et al., 2024). However, constructing a comprehensive global-level image database is clearly impractical.

2.2 Geolocation Dataset

Existing geolocation datasets primarily originate from web-scraped or street-view images that have not been human-validated, raising concerns about their quality for effectively evaluating geolocation capabilities. For instance, datasets derived from web scraping, such as YFCC100M (Theiner et al., 2022b) and Im2GPS3K (Vo et al., 2017a), include a significant proportion of images depicting food, art, pets, and personal photographs. These types of images are often weakly localizable or entirely




Figure 1: Comparison of data distribution between our GeoComp dataset and the existing SOTA OSV-5M dataset. (a) Global geographical heatmaps illustrating image density. (b–c) Country-level statistical breakdowns for GeoComp and OSV-5M, respectively. The Geo-Pop Index, defined as the harmonic mean of Area Bias and Population Bias, is used to comprehensively assess distribution balance. Index values are color-coded to indicate balance levels: High Balance , Moderate Balance , Imbalance , and Critical Imbalance .

non-localizable (Theiner et al., 2022a). Street-view datasets also face limitations, such as restricted geographic coverage (Astruc et al., 2024); for example, (Mirowski et al., 2019)’s work includes data from only three cities in the United States. Furthermore, dataset collection processes often introduce biases. For instance, some commonly used platforms are inaccessible in certain countries, resulting in uneven geographic representation. Additionally, the difficulty of individual geolocation tasks varies widely within these datasets, but this aspect has not been comprehensively evaluated. For example, images taken at prominent landmarks are relatively easy to geolocate, while others offer no clear hints and are highly challenging (Astruc et al., 2024). These limitations undermine the reliability of current geolocation benchmarks.

2.3 Large Vision Language Models

Numerous studies have been conducted on various aspects of LVMs, encompassing structural design (Liu et al., 2024b; Cai et al., 2023; Liu et al., 2024a), data construction (LAION, 2023; Zhao et al., 2024), training strategies (Zhao et al., 2023; McKinzie et al., 2024; Lu et al., 2024), evalua-

tions (Bithel and Bedathur, 2023), and the development of lightweight LVMs (Zhu et al., 2024a). Additionally, the robust capabilities of LVMs have been applied to other fields, such as medical image understanding (Zhou and Huang, 2024; Zhang et al., 2023b, 2024) and document parsing (Ye et al., 2023; Liu et al., 2024c). However, the reasoning capabilities of LVMs in geolocation tasks remain underexplored. One of the primary reasons for this limitation is the lack of high-reasoning-value geographic data.

3 Data Overview

3.1 Geolocation Competition

Inspired by geoguessr website, we developed a free geolocation game platform that tracks participants’ competition histories. Unlike most geolocation websites, including Geoguessr, which rely solely on samples from Google Street View, our platform integrates Baidu Maps, Tencent Maps, and Gaode Maps to address coverage gaps in regions like mainland China, ensuring broader global accessibility. Users can choose specific opponents or engage in random matches. Each match consists of multiple questions, and each user is initially assigned a “vi-

talities score.” Users mark their predicted location on a map, and the system evaluates accuracy based on the surface distance between the predicted point and the ground truth. Larger errors result in greater deductions from the user’s vitality score. The user with the higher vitality score at the end of the match is declared the winner. To ensure predictions are human-generated rather than machine-generated, users must register with a phone number, enabling tracking of individual activities. Using this platform, we collected GeoComp, a comprehensive dataset covering 1,000 days of user competition.

3.2 Dataset Statistics and Geographic Balance

To comprehensively evaluate the geographical distribution quality of our dataset, we conduct a comparative analysis with the existing SOTA dataset, OSV-5M (Astruc et al., 2024). Figure 1(a) visualizes the global density of the dataset via geographical heatmaps. Compared to OSV-5M, which exhibits a skewed distribution towards Western regions, GeoComp demonstrates a significantly more comprehensive coverage. First, GeoComp successfully mitigates the data sparsity in under-represented areas, achieving dense coverage in East Asia and South America. Second, our improved global balance does not sacrifice the density of data in well-covered areas. As evidenced by the higher heatmap intensity, our dataset maintains superior sampling density even in Western regions (e.g., Europe and North America) compared to OSV-5M. This dual advantage, expanding global reach while intensifying local density, ensures that GeoComp is both spatially balanced and densely distributed.

To further validate the distribution quality beyond visual inspection, we propose the *Area Bias* and *Population Bias* ratios, calculated as the quotient of a country’s proportion in the dataset to its respective global share of land area or population. To synthesize spatial and population factors, we define the *Geo-Pop* Index as the harmonic mean of Area Bias and Population Bias, where 1.0 indicates perfect parity. We categorize distribution quality into four levels based on the magnitude of deviation: High Balance (0.8–1.4) denotes optimal alignment with real-world shares; Moderate Balance (0.3–0.8 or 1.4–3.0) and Imbalance (0.1–0.3 or 3.0–4.5) reflect increasing degrees of skew; while Critical Imbalance (< 0.1 or > 4.5) identifies extreme outliers that are either under-represented by over $10\times$ or over-sampled by more than $4.5\times$. The statistical breakdown reveals a severe polarization

in OSV-5M. As shown in Figure 1(c), it exhibits Critical Imbalance in major nations: the United States is disproportionately over-represented (accounting for 24.90% of the data with an Index of 4.74), while China is severely under-represented (only 0.16%, Index 0.01). In contrast, GeoComp effectively mitigates these imbalances, achieving a status of High Balance across the mainstream country (Figure 1(b)). For instance, the representation of China is restored to a reasonable 16.39% (Index 1.38), and the United States is normalized to 6.75% (Index 1.31), reflecting a distribution more aligned with real-world geography and population. Overall, the majority of countries in GeoComp fall within the High Balance range, demonstrating a stable distribution (Global Std. Dev. of 0.57). Conversely, OSV-5M is predominantly characterized by Moderate Balance and Critical Imbalance, resulting in a significantly higher deviation of 1.37.

3.3 Human Annotations

Distinct from previous works, GeoComp includes rich human gameplay data, serving as a vital benchmark for evaluating geolocation difficulty and image localizability. We analyze performance using the GeoGuessr scoring mechanism, where a user’s score S decays exponentially with the distance error d . The score is calculated as $S = \lfloor \exp(-d/s_d) \times 5000 \rfloor$, where s_d is a scale factor derived from the map’s maximum distance. A perfect prediction ($d = 0$) yields 5,000 points. To establish a reliable difficulty benchmark, we visualized the dataset for the annotated locations and calculated the average score for each location. The resulting distribution is shown in Figure 3.

As illustrated in the histogram, the dataset exhibits a broad spectrum of difficulty levels. The 0–1,000 score range constitutes the largest portion of the data, accounting for approximately 27.6%. This high concentration of low scores reveals a substantial subset of hard samples, which are typically located in remote or rural areas and lack explicit semantic cues such as text signs. For these locations, accurate localization requires fine-grained reasoning over implicit environmental features, including vegetation patterns, soil texture, and architectural styles. The poor human performance in this range suggests that average players generally lack the specialized domain knowledge needed to interpret these subtle cues, which often results in near-random guessing. This characteristic highlights the opportunity for models to surpass human




Figure 2: Comparison of previous geolocation tasks and our proposed paradigm: while previous works focused on coarse-grained predictions limited by dataset quality, our generation and reasoning-based method enables fine-grained city-level predictions.




Figure 3: Number of locations distributed across different average score intervals.

performance by effectively learning high-entropy environmental representations. Overall, this distribution confirms that GeoComp serves as a robust benchmark, providing sufficient challenging samples to stress state-of-the-art models while retaining a substantial volume of human-solvable data to support meaningful geographic feature learning.

4 Geographic Chain of Thought

4.1 Rethinking Geolocation Task

As discussed in §2.1, the geolocation task has traditionally relied on classification-based (Clark et al., 2023b; Pramanick et al., 2022; Weyand et al., 2016b) and retrieval-based methods (Zhu et al., 2022; Zhang et al., 2023a), as shown in Figure 2. While these approaches have advanced the field, they face significant limitations in precision and scalability, prompting a rethinking of the task. Inspired by how humans gradually narrow down locations from broad to fine-grained observations (Luo et al., 2022), we propose a new geolocation paradigm: predicting geographic locations through a step-by-step reasoning process. Unlike traditional approaches limited by grid-based classification and exhaustive databases, our model generates natural language reasoning, guiding it to the final predicted city. To implement

this paradigm, we introduce GeoCoT (Geographic Chain-of-Thought), a framework designed for both interpretability and accuracy.

4.2 GeoCoT Design

Our design of GeoCoT is inspired by how humans intuitively approach geolocation—progressing from broad to fine-grained analysis. Rather than relying on generic step-by-step reasoning like standard CoT prompting, GeoCoT mimics the human process: starting with macro-level cues (e.g., climate, terrain), then narrowing down to country, city, and finally micro-level details to guide the model through interpretable geographic reasoning.

Concretely, GeoCoT operates in five sequential stages: 1. *Continental or Climate Zone Identification*. The process begins with identifying broad regions using natural features like mountains, vegetation, or soil, narrowing the scope to a continent or climate zone. 2. *Country-Level Localization*. Cultural markers, language on signs, and architectural styles are analyzed to refine predictions to the country level. 3. *City-Level Refinement Using Infrastructure*. Street elements, such as driving direction, bollards, and license plate colors, are used to locate specific cities or regions. 4. *Landmark-Based Verification*. Features like fire hydrants, guideposts, and street signs help validate and further refine the predicted location. 5. *Fine-Grained Micro-Level Validation*. Finally, subtle details such as sidewalk patterns and clothing styles confirm precise localization at a city or neighborhood level. These five reasoning steps are formulated as a single, structured prompt and jointly fed into the LVM, which directly generates the final predicted location. Detailed prompts can be found in Appendix B.

It is important to note that GeoCoT does not require any concrete knowledge about the specific

Model	City			Country			Continent		
	Accuracy↑	Recall↑	F1↑	Accuracy↑	Recall↑	F1↑	Accuracy↑	Recall↑	F1↑
LLaVA-1.6	0.002	0.001	0.002	0.041	0.019	0.028	0.175	0.067	0.056
LLama-3.2-Vision	0.081	0.037	0.030	0.630	0.199	0.217	0.866	0.643	0.639
Qwen-VL	0.016	0.013	0.014	0.069	0.042	0.070	0.130	0.115	0.077
GeoCLIP	0.018	0.007	0.008	0.550	0.197	0.204	0.872	0.746	0.731
GeoReasoner	0.018	0.014	0.012	0.092	0.053	0.085	0.208	0.161	0.144
Kimi-latest	0.027	0.023	0.024	0.135	0.112	0.156	0.315	0.148	0.220
Kimi-latest(CoT)	0.028	0.029	0.029	0.139	0.092	0.124	0.331	0.154	0.210
Kimi-latest(GeoCoT)	0.038	0.035	0.029	0.239	0.192	0.224	0.361	0.168	0.232
GPT-4o	0.092	0.048	0.044	0.615	0.188	0.208	0.807	0.468	0.487
GPT-4o(CoT)	0.094	0.052	0.042	0.623	0.194	0.212	0.819	0.430	0.449
GeoCoT	0.118	0.089	0.086	0.640	0.260	0.291	0.862	0.638	0.646

Table 2: Comparison of Precision, Recall and F1 scores in country-level and city-level geolocation. The scores are represented as follows: **best**, **second**, and **third**. Numbers in **bold** mean that the improvement to the best baseline is statistically significant (a two-tailed paired t-test with p-value <0.05).

features of locations. Instead, it offers reasoning tutorials designed to help LVMs identify geographic clues by leveraging their existing knowledge. Our inference time and efficiency analysis in Appendix E shows that GeoCoT incurs only about a 10% increase in inference latency compared to standard CoT. We further provide an ablation study in Appendix F.

5 Experiments

5.1 Setting

We selected 500 geo-tagged locations with high inferential value from the dataset to serve as a test set, using a stratified sampling method across continents to ensure balanced geographic distribution. This number is larger than in previous works (Liu et al., 2023b; Guan et al., 2024), which typically include only a few dozen case studies to examine the reasoning process. Specifically, we selected 20 mainstream countries across six continents as representative samples and extracted tasks with an average player score of around 3,000 out of 5,000 for annotation. This test set has been publicly released on GitHub.

5.2 Baselines

We compare GeoCoT against strong baselines representing recent geolocation advancements. For general open-source VLMs, we evaluate LLaVA-1.6 (Liu et al., 2023a), Llama-3.2-vision (Meta, 2024), and Qwen2.5-VL (Bai et al., 2023), also include geolocation-specific models GeoCLIP (Vivanco Cepeda et al., 2024) and GeoReasoner (Li et al., 2024). Furthermore, we assess closed-source performance using GPT-4o (OpenAI, 2024) and GPT-4o(CoT) utilizing chain-of-thought reasoning (Wei et al., 2022). All models are evaluated

using the same input format and test set to ensure a fair comparison.

5.3 Overall Performance Evaluation of GeoCoT

We evaluate geolocation performance from two aspects: first, location prediction compared with the ground truth at various levels; and second, the direct calculation of the Earth’s surface distance. We present the location prediction performance in Table 2, evaluated across three levels: city, country, and continent. Performance is measured using *accuracy*, which calculates the proportion of correct predictions out of all predictions; *recall*, which determines the proportion of true positive predictions out of all actual positive cases; and the *F1* score, which balances precision and recall to provide their harmonic mean.

The results reveal several key observations. First, open-source LVMs such as LLaMA-3.2-Vision achieve competitive performance, performing on par with GPT-4o and GPT-4o (CoT), demonstrating their effectiveness in location prediction tasks. Second, performance varies across different levels of granularity. While GPT-4o (CoT) ranks second at the city level, it underperforms at the country level, highlighting the importance of multi-level evaluation to fully assess a model’s geolocation reasoning ability. Finally, our model, GeoCoT, consistently achieves top performance across all nine metrics and three levels, demonstrating its robustness and adaptability in geolocation tasks. Additionally, GeoCLIP surpasses GPT-4o at the continent level, which can be attributed to its pretraining on image-GPS pairs, making it particularly well-suited for coarse-grained geolocation tasks. Coarse-grained continent-level predictions typically require less de-

tailed local knowledge and instead rely on broader geographic cues, such as climate, landscapes, and cultural markers. However, GeoCLIP performs poorly at finer granularities like city levels, suggesting that it lacks a strong capability for geographic reasoning beyond direct visual features.

Model	Street 1km	City 25km	Country 750km
LLaVA-1.6	0.006	0.020	0.082
Llama-3.2-Vision	0.018	0.104	0.638
Qwen-VL	0.004	0.014	0.090
GeoCLIP	0.035	0.077	0.625
GeoReasoner	0.010	0.020	0.128
GPT-4o	0.045	0.147	0.678
GPT-4o(CoT)	0.047	0.151	0.701
GeoCoT	0.073	0.157	0.711

Table 3: Accuracy of different models on geolocation tasks at various scales. Numbers in **bold** mean that the improvement to the best baseline is statistically significant (a two-tailed paired t-test with p-value <0.05).

Next, in Table 3, we present the accuracy of each model by measuring the geographic distance between the predicted city and the ground truth. The metrics represent the proportion of predictions within three distance thresholds: Street (1 km), City (25 km), and Country (750 km). Higher values indicate better performance, with stricter thresholds assessing fine-grained localization and larger thresholds evaluating coarse-level accuracy. The results show that GPT-4o and Llama-3.2-vision outperform the dedicated large-scale model GeoCLIP for geolocation, even under finer-grained evaluation settings. For example, at the street-level threshold, GPT-4o achieves 0.045 compared to GeoCLIP’s 0.035, and at the city-level threshold, GPT-4o scores 0.147, nearly double GeoCLIP’s 0.077. Moreover, our proposed GeoCoT paradigm demonstrates even greater improvements. At the street level, GeoCoT achieves 0.073, significantly outperforming both GeoCLIP (0.035) and GPT-4o (0.045). Similarly, at the city level, GeoCoT achieves 0.157, and at the country level (750 km), it achieves 0.711, the highest among all models. These results highlight GeoCoT’s strong performance and the potential of its reasoning framework for geolocation tasks. We further provide an ablation study on GeoCoT in Appendix F.

5.4 Generalizability Evaluation

Even though our dataset is more comprehensive and human-annotated, we are also interested in evaluating how our model performs on traditional geolocation datasets to provide a more thorough

Model	Im2GPS			Im2GPS3K		
	Street 1km	City 25km	Country 750km	Street 1km	City 25km	Country 750km
LLaVA-1.6	0.04	0.18	0.39	0.03	0.14	0.32
Llama-3.2-Vision	0.09	0.37	0.65	0.07	0.27	0.52
Qwen-VL	0.04	0.21	0.37	0.04	0.15	0.26
GeoCLIP	0.17	0.41	0.77	0.13	0.32	0.67
GeoReasoner	0.05	0.19	0.33	0.04	0.15	0.26
PlaNet	0.08	0.25	0.54	0.09	0.25	0.48
GPT-4o	0.13	0.47	0.74	0.14	0.40	0.66
GPT-4o(CoT)	0.16	0.49	0.77	0.14	0.45	0.69
GeoCoT	0.22	0.55	0.83	0.15	0.46	0.74

Table 4: Performance comparison of GeoCoT and state-of-the-art geolocation models on traditional benchmarks. Numbers in **bold** mean that the improvement to the best baseline is statistically significant (a two-tailed paired t-test with p-value <0.05).

comparison. Hence, we select two existing benchmark datasets, Im2GPS (Hays and Efros, 2008) and Im2GPS3K (Vo et al., 2017b), due to their popularity and widespread use in geolocation tasks as standard benchmarks for evaluating model performance. We present the performance results in Table 4. We observe that state-of-the-art geolocation models, such as GeoCLIP, perform well on traditional geolocation tasks, surpassing GPT-4o and coming close to our model, GeoCoT. However, this is in contrast to the results shown in Table 2, where GeoCLIP significantly underperforms GPT-4o on fine-grained city- and country-level geolocation tasks. This discrepancy suggests that these baseline models may be overfitting to the specific datasets they were trained on, lacking the generalization ability required for more diverse or fine-grained geolocation challenges.

5.5 GeoEval: Reference-Based Evaluation

Beyond evaluating overall task performance, we focus on analyzing the reasoning process of GeoCoT, which emulates a human-like reasoning approach. To establish a reference for this evaluation, three gaming enthusiasts collaboratively constructed reasoning processes for the same 500 cases based on geo-tagged locations. We designated these as the reasoning ground truth (a human-annotated example can be found in Appendix C). These GT annotations serve as a benchmark within our evaluation framework, GeoEval. The evaluation process utilizes GPT-based assessment through GPTScore (Fu et al., 2023) and prompt-based scoring.

Our prompt-based scoring includes four dimensions (scored 0-5; detailed prompts are on Github). First, *completeness of feature extraction (CE)* evaluates whether all key clues in the GT are comprehensively covered, ensuring reasoning relies on sufficient factual evidence. Second, *accuracy of*

feature extraction (AE) measures the correctness of identified attributes to prevent reasoning deviations caused by misidentified features. Third, *accuracy of reasoning and cue correspondence* (AC) assesses whether conclusions derived from extracted cues are reasonable and consistent with the GT logic. Finally, *logical coherence of reasoning* (LC) evaluates the consistency, flow, and adherence to common sense within the reasoning chain, ensuring the reliability of the conclusion.

Model	Similarity GPTScore	GeoEval			
		CE	AE	AC	LC
LLaVA-1.6	0.478	1.262	1.271	1.446	1.490
Llama-3.2-Vision	0.566	2.203	2.386	2.558	2.721
Qwen-VL	0.371	1.231	1.255	1.453	1.484
GeoReasoner	0.424	1.421	1.533	1.719	2.038
GPT-4o	0.613	2.320	2.891	2.809	3.143
GPT-4o(CoT)	0.663	2.462	3.136	3.156	3.540
GeoCoT	0.728	2.690	3.538	3.696	3.945

Table 5: Evaluation of GeoCoT’s reasoning process using ground truth-based metrics within the GeoEval framework. Numbers in **bold** mean that the improvement to the best baseline is statistically significant (a two-tailed paired t-test with p-value <0.05).

The experimental results in Table 5 highlight the significant advantages of GeoCoT compared to baseline models across all evaluation metrics. GeoCoT achieves the highest GPTScore of 0.728, outperforming GPT-4o (CoT) (0.663) and LLaVA-1.6 (0.478), demonstrating its superior alignment with human-constructed reasoning processes. In terms of feature extraction, GeoCoT achieves a CE score of 2.690 and an AE score of 3.538, significantly surpassing GPT-4o (CoT) and the dedicated GeoReasoner model. These results clearly demonstrate that GeoCoT not only captures key information more comprehensively but also maintains a more accurate and logically coherent reasoning process compared to both reasoning-based models and traditional baselines like GeoReasoner.

5.6 Intrinsic Evaluation of GeoCoT Reasoning

We begin with a ground truth-based evaluation, comparing GeoCoT’s reasoning to human-authored processes to assess its alignment with established reasoning patterns. To complement this, we conduct an intrinsic evaluation focused on hallucination errors, coherence, and robustness without relying on external references. Given the need for multimodal judgment, this evaluation is performed by human annotators.

Following previous work on assessing halluci-

Model	OH Count↓	FH Count↓	AH Count↓
GeoReasoner	237	151	203
GPT-4o	43	4	35
GeoCoT	5	1	18

Table 6: Hallucination Evaluation on Reasoning Data.

nations in terms of objects, attributes, and relationships (Li et al., 2023; Sun et al., 2023), we evaluate the quality of synthetic data across three key dimensions: (1) *Object Hallucination* (OH): assesses whether the synthetic data includes objects that do not exist in the image. Object Hallucination evaluates the extent to which synthetic data introduces fictional elements. (2) *Fact Hallucination* (FH) measures the accuracy of factual information within the synthetic data. Fact Hallucination occurs when the synthetic data contains facts, figures, or other information that is incorrect or not supported by the original data. (3) *Attribution Hallucination* (AH) evaluates whether the synthetic data incorrectly attributes properties, characteristics, or relations to entities or objects. To quantify hallucinations, each detected error is counted as one instance in the corresponding dimension. To evaluate these dimensions, we invited 2 human annotators with professional backgrounds in geographic reasoning and data validation to assess GPT-4o, GeoReasoner, and our proposed GeoCoT model. These three baselines provide textual reasoning processes across 1,500 evaluated cases. The results, shown in Table 6, indicate the number of errors in each dimension, demonstrating that GeoCoT significantly reduces hallucination errors compared to the other models. The inter-annotator agreement, measured by Cohen’s Kappa, is 0.82 for OH, 0.79 for FH, and 0.85 for AH, indicating substantial agreement across all dimensions. The detailed reasoning case studies are listed in Appendix D.

6 Conclusion

In this work, we advance the field of image geolocation by introducing GeoComp, the largest human-annotated dataset to date, comprising 2.7 million locations and 25 million real-world gameplay records. Leveraging this rich data, we propose GeoCoT, a geographical chain-of-thought framework that mimics human reasoning to enhance LVM capabilities. Comprehensive evaluations using our novel GeoEval metric demonstrate that GeoCoT significantly outperforms state-of-the-art baselines in both accuracy and interpretability.

616 Limitations

617 Despite the advancements presented, our work has
 618 three main limitations. First, although GeoComp
 619 is globally diverse, geographic coverage remains
 620 uneven, with sparse representation in regions like
 621 Africa and parts of Oceania due to limited map
 622 service availability. Nevertheless, compared to
 623 existing large-scale geolocation benchmarks (e.g.,
 624 OSV-5M), GeoComp substantially mitigates ex-
 625 treme regional bias and achieves a markedly more
 626 balanced global distribution, as demonstrated by
 627 the Geo-Pop Index analysis. Second, GeoCoT re-
 628 lies on computationally intensive LVM (e.g., GPT-
 629 4o). The multi-step reasoning process increases
 630 inference latency and cost compared to lightweight,
 631 embedding-based retrieval methods, potentially
 632 limiting real-time deployment. While this over-
 633 head is inherent to CoT-style reasoning, our empir-
 634 ical analysis (Appendix E) indicates that GeoCoT
 635 does not incur substantially higher latency than
 636 standard CoT prompting across different models.
 637 Finally, while GeoCoT excels at city-level localiza-
 638 tion through reasoning, it may struggle with precise
 639 meter-level coordinate prediction in non-urban en-
 640 vironments where semantic cues (text, landmarks)
 641 are absent, an area where retrieval-based methods
 642 still hold an advantage. This limitation stems from
 643 the intrinsic reliance of reasoning-based methods
 644 on interpretable visual cues; in such low-semantic
 645 settings, direct visual matching remains more ef-
 646 fective, and we view the integration of reasoning-
 647 based and retrieval-based paradigms as a promising
 648 direction for future work.

649 Data Ethics

650 The creation and release of our dataset adhere to
 651 stringent ethical standards to ensure the privacy and
 652 well-being of all contributors. We have conducted
 653 rigorous anonymization of the dataset to protect
 654 user privacy. All personally identifiable informa-
 655 tion, such as usernames, email addresses, and IP
 656 addresses, has been permanently removed. Only
 657 non-identifiable behavioral data, such as predic-
 658 tion outcomes and timestamps, are retained. The
 659 dataset originates from user participation on our
 660 open-source geolocation game platform. Users
 661 were informed during the registration process that
 662 their activity data might be used for research pur-
 663 poses. This ensures transparency in data collection
 664 and maintains user trust. We have explicitly de-
 665 signed the dataset for research purposes, with the

sole intention of advancing geolocation and related
 artificial intelligence technologies. Importantly,
 our dataset does not include the images directly
 but instead provides links to images hosted on plat-
 forms such as Google Maps or Baidu Maps, which
 can be accessed through their official APIs. We are
 committed to ensuring the responsible use of this
 dataset. Researchers accessing the data must agree
 to a data usage agreement that prohibits unethical
 or illegal use.

References

- Guillaume Astruc, Nicolas Dufour, Ioannis Siglidis,
 Constantin Aronssohn, Nacim Bouia, Stephanie Fu,
 Romain Loiseau, Van Nguyen Nguyen, Charles
 Raude, Elliot Vincent, and 1 others. 2024.
 Openstreetview-5m: The many roads to global visual
 geolocation. In *Proc. of CVPR*, pages 21967–21977.
- Jinze Bai, Shuai Bai, Yunfei Chu, Zeyu Cui, Kai Dang,
 Xiaodong Deng, Yang Fan, Wenbin Ge, Yu Han, Fei
 Huang, and 1 others. 2023. Qwen technical report.
arXiv:2309.16609.
- Shivangi Bithel and Srikanta Bedathur. 2023. Evalu-
 ating cross-modal generative models using retrieval
 task. In *Proc. of SIGIR*, pages 1960–1965.
- Rizhao Cai, Zirui Song, Dayan Guan, Zhenhao
 Chen, Xing Luo, Chenyu Yi, and Alex Kot. 2023.
 Benchlm: Benchmarking cross-style visual capa-
 bility of large multimodal models. *arXiv preprint*
arXiv:2312.02896.
- Athanasios Chalvatzaras, Ioannis Pratikakis, and Ange-
 los A Amanatiadis. 2022. A Survey on Map-Based
 Localization Techniques for Autonomous Vehicles.
IEEE Transactions on Intelligent Vehicles, pages
 1574–1596.
- Wenqing Cheng, Ruxue Wen, Haojun Huang, Wang
 Miao, and Chen Wang. 2022. OPTDP: Towards op-
 timal personalized trajectory differential privacy for
 trajectory data publishing. *Neurocomputing*, pages
 201–211.
- Brandon Clark, Alec Kerrigan, Parth Parag Kulkarni,
 Vicente Vivanco Cepeda, and Mubarak Shah. 2023a.
 Where we are and what we’re looking at: Query
 based worldwide image geo-localization using hier-
 archies and scenes. In *Proc. of CVPR*, pages 23182–
 23190.
- Brandon Clark, Alec Kerrigan, Parth Parag Kulkarni,
 Vicente Vivanco Cepeda, and Mubarak Shah. 2023b.
 Where We Are and What We’re Looking At: Query
 Based Worldwide Image Geo-Localization Using Hi-
 erarchies and Scenes. In *CVPR*, pages 23182–23190.
- Jinlan Fu, See-Kiong Ng, Zhengbao Jiang, and Pengfei
 Liu. 2023. Gptscore: Evaluate as you desire. *arXiv*
preprint arXiv:2302.04166.

719	Tianrui Guan, Fuxiao Liu, Xiyang Wu, Ruiqi Xian,	Haotian Liu, Chunyuan Li, Qingyang Wu, and Yong Jae	772
720	Zongxia Li, Xiaoyu Liu, Xijun Wang, Lichang Chen,	Lee. 2023b. Visual instruction tuning. <i>Advances</i>	773
721	Furong Huang, Yaser Yacoob, and 1 others. 2024.	<i>in neural information processing systems</i> , 36:34892–	774
722	Hallusionbench: an advanced diagnostic suite for	34916.	775
723	entangled language hallucination and visual illusion		
724	in large vision-language models. In <i>Proceedings of</i>	Haotian Liu, Chunyuan Li, Qingyang Wu, and Yong Jae	776
725	<i>the IEEE/CVF Conference on Computer Vision and</i>	Lee. 2024b. Visual instruction tuning. <i>Proc. of</i>	777
726	<i>Pattern Recognition</i> , pages 14375–14385.	<i>NeurIPS</i> .	778
727	Lukas Haas, Silas Alberti, and Michal Skreta. 2023.	Liu Liu and Hongdong Li. 2019. Lending orientation to	779
728	Learning generalized zero-shot learners for open-	neural networks for cross-view geo-localization. In	780
729	domain image geolocalization. <i>arXiv preprint</i>	<i>Proc. of CVPR</i> , pages 5624–5633.	781
730	<i>arXiv:2302.00275</i> .		
731	Xiao Han, Xiangyu Zhao, Liang Zhang, and Wanyu	Yuliang Liu, Biao Yang, Qiang Liu, Zhang Li, Zhiyin	782
732	Wang. 2023. Mitigating action hysteresis in traffic	Ma, Shuo Zhang, and Xiang Bai. 2024c. Textmon-	783
733	signal control with traffic predictive reinforcement	key: An ocr-free large multimodal model for under-	784
734	learning. In <i>Proc. of KDD</i> , pages 673–684.	standing document. <i>arXiv:2403.04473</i> .	785
735	James Hays and Alexei A Efros. 2008. IM2GPS: esti-	Haoyu Lu, Wen Liu, Bo Zhang, Bingxuan Wang, Kai	786
736	imating geographic information from a single image.	Dong, Bo Liu, Jingxiang Sun, Tongzheng Ren, Zhu-	787
737	In <i>CVPR</i> , pages 1–8.	oshu Li, Yaofeng Sun, and 1 others. 2024. Deepseek-	788
738	Sohail Ahmed Khan, Laurence Dierickx, Jan-Gunnar	vl: towards real-world vision-language understand-	789
739	Furuly, Henrik Brattli Vold, Rano Tahseen, Carl-	ing. <i>arXiv preprint arXiv:2403.05525</i> .	790
740	Gustav Linden, and Duc-Tien Dang-Nguyen. 2024.		
741	Debunking war information disorder: A case study	Grace Luo, Giscard Biamby, Trevor Darrell, Daniel	791
742	in assessing the use of multimedia verification tools.	Fried, and Anna Rohrbach. 2022. G3: Geolocation	792
743	<i>Journal of the Association for Information Science</i>	via guidebook grounding. In <i>Proc. of EMNLP Find-</i>	793
744	<i>and Technology</i> .	<i>ings</i> , pages 5841–5853.	794
745	LAION. 2023. Gpt-4v dataset.	Brandon McKinzie, Zhe Gan, Jean-Philippe Faucon-	795
746	Martha Larson, Mohammad Soleymani, Guillaume	nier, Sam Dodge, Bowen Zhang, Philipp Dufter,	796
747	Gravier, Bogdan Ionescu, and Gareth JF Jones. 2017.	Dhruti Shah, Xianzhi Du, Futang Peng, Floris	797
748	The benchmarking initiative for multimedia evalua-	Weers, and 1 others. 2024. Mm1: Methods, anal-	798
749	tion: Mediaeval 2016. <i>IEEE MultiMedia</i> , pages	ysis & insights from multimodal llm pre-training.	799
750	93–96.	<i>arXiv:2403.09611</i> .	800
751	Ling Li, Yu Ye, Bingchuan Jiang, and Wei Zeng. 2024.	AI Meta. 2024. Llama 3.2: Revolutionizing edge ai	801
752	Georeasoner: Geo-localization with reasoning in	and vision with open, customizable models. <i>Meta AI</i>	802
753	street views using a large vision-language model. In	<i>Blog</i> . Retrieved December, page 2024.	803
754	<i>Proc. of ICML</i> .		
755	Ling Li, Yao Zhou, Yuxuan Liang, Fugee Tsung, and	Piotr Mirowski, Andras Banki-Horvath, Keith Ander-	804
756	Jiaheng Wei. 2025. Recognition through reasoning:	son, Denis Teplyashin, Karl Moritz Hermann, Ma-	805
757	Reinforcing image geo-localization with large vision-	teusz Malinowski, Matthew Koichi Grimes, Karen	806
758	language models . <i>Preprint</i> , arXiv:2506.14674.	Simonyan, Koray Kavukcuoglu, Andrew Zisserman,	807
759	Yifan Li, Yifan Du, Kun Zhou, Jinpeng Wang,	and 1 others. 2019. The StreetLearn environment	808
760	Wayne Xin Zhao, and Ji-Rong Wen. 2023. Eval-	and dataset. <i>arXiv preprint arXiv:1903.01292</i> .	809
761	uating object hallucination in large vision-language		
762	models. <i>arXiv preprint arXiv:2305.10355</i> .	Eric Müller-Budack, Kader Pustu-Iren, and Ralph Ew-	810
763	Dongyang Liu, Renrui Zhang, Longtian Qiu, Siyuan	erth. 2018. Geolocation Estimation of Photos using	811
764	Huang, Weifeng Lin, Shitian Zhao, Shijie Geng, Ziyi	a Hierarchical Model and Scene Classification. In	812
765	Lin, Peng Jin, Kaipeng Zhang, and 1 others. 2024a.	<i>Proc. of ECCV</i> , pages 563–579.	813
766	Sphinx-x: Scaling data and parameters for a family of	OpenAI. 2024. Gpt-4o system card. <i>arXiv preprint</i>	814
767	multi-modal large language models. <i>arXiv preprint</i>	<i>arXiv:2410.21276</i> .	815
768	<i>arXiv:2402.05935</i> .		
769	Haotian Liu, Chunyuan Li, Yuheng Li, and Yong Jae	Shraman Pramanick, Ewa M Nowara, Joshua Gleas-	816
770	Lee. 2023a. Improved baselines with visual instruc-	son, Carlos D Castillo, and Rama Chellappa. 2022.	817
771	tion tuning.	Where in the World is this Image? Transformer-based	818
		Geo-localization in the Wild. In <i>Proc. of ECCV</i> ,	819
		pages 196–215.	820
		Paul Hongsuck Seo, Tobias Weyand, Jack Sim, and	821
		Bohyung Han. 2018. CPLaNet: Enhancing Image Ge-	822
		olocalization by Combinatorial Partitioning of Maps.	823
		In <i>Proc. of ECCV</i> , pages 536–551.	824

825	Zhiqing Sun, Sheng Shen, Shengcao Cao, Haotian Liu,	Xiaohan Zhang, Xingyu Li, Waqas Sultani, Yi Zhou,	877
826	Chunyuan Li, Yikang Shen, Chuang Gan, Liang-Yan	and Safwan Wshah. 2023a. Cross-View Geo-	878
827	Gui, Yu-Xiong Wang, Yiming Yang, and 1 others.	Localization via Learning Disentangled Geometric	879
828	2023. Aligning large multimodal models with factually	Layout Correspondence. In <i>Proc. of AAAI</i> , pages	880
829	augmented rlhf. <i>arXiv:2309.14525</i> .	3480–3488.	881
830	Jonas Theiner, Eric Müller-Budack, and Ralph Ewerth.	Xiaoman Zhang, Chaoyi Wu, Ziheng Zhao, Weixiong	882
831	2022a. Interpretable semantic photo geolocation. In	Lin, Ya Zhang, Yanfeng Wang, and Weidi Xie. 2023b.	883
832	WACV.	Pmc-vqa: Visual instruction tuning for medical visual	884
833	Jonas Theiner, Eric Müller-Budack, and Ralph Ewerth.	question answering. <i>arXiv:2305.10415</i> .	885
834	2022b. Interpretable Semantic Photo Geolocation.	Zijian Zhang, Ze Huang, Zhiwei Hu, Xiangyu Zhao,	886
835	In <i>Proceedings of the IEEE/CVF Winter Conference</i>	Wanyu Wang, Zitao Liu, Junbo Zhang, S Joe Qin, and	887
836	<i>on Applications of Computer Vision</i> , pages 750–760.	Hongwei Zhao. 2023c. Mlpst: Mlp is all you need	888
837	Vicente Vivanco Cepeda, Gaurav Kumar Nayak, and	for spatio-temporal prediction. In <i>Proc. of CIKM</i> ,	889
838	Mubarak Shah. 2024. Geoclip: Clip-inspired align-	pages 3381–3390.	890
839	ment between locations and images for effective	Zijian Zhang, Xiangyu Zhao, Qidong Liu, Chunxu	891
840	worldwide geo-localization. <i>Proc. of NeurIPS</i> .	Zhang, Qian Ma, Wanyu Wang, Hongwei Zhao, Yiqi	892
841	Nam Vo, Nathan Jacobs, and James Hays. 2017a. Re-	Wang, and Zitao Liu. 2023d. Promptst: Prompt-	893
842	visiting im2gps in the deep learning era. In <i>Proc. of</i>	enhanced spatio-temporal multi-attribute prediction.	894
843	<i>ICCV</i> , pages 2621–2630.	In <i>Proc. of CIKM</i> , pages 3195–3205.	895
844	Nam Vo, Nathan Jacobs, and James Hays. 2017b. Re-	Zijian Zhang, Xiangyu Zhao, Hao Miao, Chunxu Zhang,	896
845	visiting IMG2GPS in the deep learning era. In <i>ICCV</i> .	Hongwei Zhao, and Junbo Zhang. 2023e. Autostl:	897
846	Jason Wei, Xuezhi Wang, Dale Schuurmans, Maarten	Automated spatio-temporal multi-task learning. In	898
847	Bosma, Fei Xia, Ed Chi, Quoc V Le, Denny Zhou,	<i>Proc. of AAAI</i> , pages 4902–4910.	899
848	and 1 others. 2022. Chain-of-thought prompting elic-	Han Zhao, Min Zhang, Wei Zhao, Pengxiang Ding,	900
849	its reasoning in large language models. <i>Proc. of</i>	Siteng Huang, and Donglin Wang. 2024. Co-	901
850	<i>NeurIPS</i> , pages 24824–24837.	bra: Extending mamba to multi-modal large lan-	902
851	Tobias Weyand, Ilya Kostrikov, and James Philbin.	guage model for efficient inference. <i>arXiv preprint</i>	903
852	2016a. <i>PlaNet - Photo Geolocation with Convolutional</i>	<i>arXiv:2403.14520</i> .	904
853	<i>Neural Networks</i> , page 37–55.	Xiangyu Zhao, Wenqi Fan, Hui Liu, and Jiliang Tang.	905
854	Tobias Weyand, Ilya Kostrikov, and James Philbin.	2022. Multi-type urban crime prediction. In <i>Proc. of</i>	906
855	2016b. <i>PlaNet - Photo Geolocation with Convolutional</i>	<i>AAAI</i> , pages 4388–4396.	907
856	<i>Neural Networks</i> . In <i>Proc. of ECCV</i> , pages	Xiangyu Zhao and Jiliang Tang. 2017. Modeling	908
857	37–55.	temporal-spatial correlations for crime prediction. In	909
858	Scott Workman, Richard Souvenir, and Nathan Jacobs.	<i>Proceedings of the 2017 ACM on Conference on In-</i>	910
859	2015. Wide-area image geolocation with aerial	<i>formation and Knowledge Management</i> , pages 497–	911
860	reference imagery. In <i>Proc. of ICCV</i> , pages 3961–	506.	912
861	3969.	Xiangyu Zhao, Tong Xu, Yanjie Fu, Enhong Chen,	913
862	Jiabo Ye, Anwen Hu, Haiyang Xu, Qinghao Ye,	and Hao Guo. 2017. Incorporating spatio-temporal	914
863	Ming Yan, Yuhao Dan, Chenlin Zhao, Guohai	smoothness for air quality inference. In <i>Proc. of</i>	915
864	Xu, Chenliang Li, Junfeng Tian, and 1 others.	<i>ICDM</i> , pages 1177–1182.	916
865	2023. mplug-docowl: Modularized multimodal	Xiangyu Zhao, Tong Xu, Qi Liu, and Hao Guo. 2016.	917
866	large language model for document understanding.	Exploring the choice under conflict for social event	918
867	<i>arXiv:2307.02499</i> .	participation. In <i>Proc. of DASFAA</i> , pages 396–411.	919
868	Amir Roshan Zamir and Mubarak Shah. 2014. Im-	Zijia Zhao, Longteng Guo, Xingjian He, Shuai Shao,	920
869	age geo-localization based on multiplenearest neigh-	Zehuan Yuan, and Jing Liu. 2023. Mamo: Fine-	921
870	bor feature matching usinggeneralized graphs. <i>IEEE</i>	grained vision-language representations learning	922
871	<i>transactions on pattern analysis and machine intelli-</i>	with masked multimodal modeling. In <i>Proc. of SI-</i>	923
872	<i>gence</i> , pages 1546–1558.	<i>GIR</i> , pages 1528–1538.	924
873	Peng-Fei Zhang, Zi Huang, and Guangdong Bai.	Baichuan Zhou and Lei Huang. 2024. Tinyllava.	925
874	2024. Universal adversarial perturbations for vision-	Zhongliang Zhou, Jielu Zhang, Zihan Guan, Mengxuan	926
875	language pre-trained models. In <i>Proc. of SIGIR</i> ,	Hu, Ni Lao, Lan Mu, Sheng Li, and Gengchen Mai.	927
876	pages 862–871.	2024. Img2loc: Revisiting image geolocation	928
		using multi-modality foundation models and image-	929
		based retrieval-augmented generation. In <i>Proc. of</i>	930
		<i>SIGIR</i> , page 2749–2754.	931

- Minjie Zhu, Yichen Zhu, Xin Liu, Ning Liu, Zhiyuan Xu, Chaomin Shen, Yaxin Peng, Zhicai Ou, Feifei Feng, and Jian Tang. 2024a. A comprehensive overhaul of multimodal assistant with small language models. *arXiv preprint arXiv:2403.06199*.
- Sijie Zhu, Mubarak Shah, and Chen Chen. 2022. TransGeo: Transformer Is All You Need for Cross-view Image Geo-localization. In *CVPR*, pages 1162–1171.
- Yuanshao Zhu, Yongchao Ye, Ying Wu, Xiangyu Zhao, and James Yu. 2023a. Synmob: Creating high-fidelity synthetic gps trajectory dataset for urban mobility analysis. *Proc. of NeurIPS*, pages 22961–22977.
- Yuanshao Zhu, Yongchao Ye, Shiyao Zhang, Xiangyu Zhao, and James Yu. 2023b. Difftraj: Generating gps trajectory with diffusion probabilistic model. *Proc. of NeurIPS*, pages 65168–65188.
- Yuanshao Zhu, James Jianqiao Yu, Xiangyu Zhao, Qidong Liu, Yongchao Ye, Wei Chen, Zijian Zhang, Xuetao Wei, and Yuxuan Liang. 2024b. Controltraj: Controllable trajectory generation with topology-constrained diffusion model. In *Proc. of KDD*, pages 4676–4687.




Figure 4: UI of Gameplay. UI components that could potentially compromise the double-blind review policy were masked.

A Data Collection Platform User Interface

To comply with the double-blind review policy, we did not include the URL of our active website in the paper. Instead, we presented selected interface screenshots of the website in Figure 4 while obscuring any elements that could potentially compromise the anonymity required by the policy.

B Detail of GeoCoT

We present the detailed prompt of our GeoCoT process below:

• **Question1:** Are there prominent natural features, such as specific types of *vegetation*, *landforms* (e.g., *mountains*, *hills*, *plains*), or *soil characteristics*, that provide clues about the geographical *region*? • **Question2:** Are there any culturally, historically, or architecturally significant *landmarks*, *buildings*, or *structures*, or are there any *inscriptions* or *signs* in a specific language or script that could help determine the *country* or *region*? • **Question3:** Are there distinctive road-related features, such as *traffic direction* (e.g., *left-hand* or *right-hand driving*), specific types of *bollards*,

unique utility *pole designs*, or *license plate colors* and styles, which *countries* are known to have these characteristics? • **Question4:** Are there observable *urban* or *rural markers* (e.g., *street signs*, *fire hydrants* *guideposts*), or other *infrastructure* elements, that can provide more specific information about the *country* or *city*? • **Question5:** Are there identifiable patterns in *sidewalks* (e.g., *tile shapes*, *colors*, or *arrangements*), *clothing styles* worn by people, or other culturally specific details that can help narrow down the *city* or *area*?

Let’s think step by step. Based on the question I provided, locate the location of the picture as accurately as possible. Identify the continent, country, and city, and summarize it into a paragraph. For example: the presence of tropical rainforests, palm trees, and red soil indicates a tropical climate... Signs in Thai, right-side traffic, and traditional Thai architecture further suggest it is in Thailand... Combining these clues, this image was likely taken in a city in *Bangkok, Thailand, Asia*.

Here, *cyan* highlights potential clues within the image to help the model infer geographic locations. *Green* defines the geographic scope inferred from the clues, such as a region, country, or city. *Orange* provides detailed descriptions of the cyan clues, enhancing the model’s understanding. *Red* specifies the expected output format, including city, country, and continent.

C Human Annotation Example

Below we show an example of human annotated ground truth to demonstrate the annotation process, criteria, and the reasoning behind the annotations, where clues are shown in *blue*, correct predictions in *green*.

The image shows a rural residential area with dense trees and expansive green lawns. The terrain is flat, and the *soil is reddish-brown*, which matches the temperate climate of central Europe, particularly rural areas of France. The architectural style of the house is distinctive: a *red-tiled sloped roof*, *yellow walls*, and *solar panels*, reflecting the region’s focus on renewable energy, a common feature in French countryside homes. The *red mailbox* at the gate is a hallmark of rural French residences. The design of the fences and modern *gates aligns* with typical styles in the French countryside. The house design and surrounding natural environment suggest a rural European region. Based on the architectural style, natural landscape, and street el-



Figure 5: Qualitative comparison of LLaVA, GPT4o, and GeoReasoner. Clues are shown in blue, correct predictions in green, incorrect in red, and vague/uncertain guesses in orange.

ements, the image was most likely taken in **Aumont, France, Europe**.

D Case Study

Figure 5 presents qualitative comparisons. In the first case, GeoCoT correctly identifies the location in France by integrating architectural and environmental clues, whereas baselines struggle with specific regional markers. In the second case, GeoCoT leverages text and traffic signs for precise city-level localization, while baselines like LLaVA and GPT-4o fail to capture fine-grained details.

E Inference Time and Efficiency Analysis

To address concerns regarding computational overhead, we conducted a comprehensive performance analysis on our test set. It is important to note that a key advantage of our GeoCoT framework is its efficiency in deployment: it does not require any additional model training or fine-tuning. Instead, our contribution focuses on engineering a structured chain-of-thought prompt that elicits advanced reasoning capabilities from off-the-shelf Large Vision Models. Furthermore, we benchmark our framework against GLOBE (Li et al., 2025), a recent reasoning-driven approach that reinforces image geo-localization through policy optimization and enhanced visual-cue reasoning. Table 7 presents the average number of tokens generated and the corresponding inference time for the base model

(GPT-4o), a standard Chain-of-Thought (CoT) approach, and our proposed GeoCoT framework.

Model	Avg. Generated Tokens	Avg. Inference Time (s)
GLOBE	397.74	8.13
GPT-4o	89.76	5.62
GPT-4o (CoT)	141.58	7.57
GeoCoT	173.28	8.88

Table 7: Comparison of inference time and token generation across different methods. GeoCoT introduces only a marginal increase in latency compared to standard CoT.

The results indicate that GeoCoT introduces a modest and acceptable latency overhead, with approximately 1.3 seconds over standard CoT and 3.2 seconds over the base model. This marginal increase in response time is a direct trade-off for the more comprehensive, multi-step reasoning process required for precise geolocation. Given the significant gains in localization accuracy demonstrated in the main experiments, we consider this computational cost to be acceptable for practical applications.

F Ablation Study on Reasoning Steps

To assess the contribution of each reasoning stage within our framework, we conducted an ablation study on the reasoning steps. The detailed results are presented in Table 8.

The experimental results indicate that single-step reasoning (e.g., relying solely on climate or in-

Configuration	City			Country			Continent		
	Accuracy	Recall	F1	Accuracy	Recall	F1	Accuracy	Recall	F1
Step1	0.113	0.098	0.076	0.551	0.133	0.151	0.776	0.443	0.468
Step2	0.103	0.086	0.074	0.510	0.157	0.181	0.755	0.438	0.464
Step3	0.102	0.073	0.076	0.490	0.142	0.165	0.673	0.334	0.380
Step4	0.082	0.078	0.069	0.469	0.122	0.142	0.735	0.346	0.369
Step5	0.102	0.088	0.078	0.551	0.151	0.173	0.776	0.338	0.363
Step1+2	0.112	0.083	0.086	0.571	0.196	0.190	0.795	0.443	0.468
Step1+2+3	0.114	0.102	0.089	0.592	0.216	0.192	0.816	0.453	0.474
Step1+2+3+4	0.112	0.089	0.078	0.604	0.231	0.293	0.824	0.550	0.572
Step1+2+3+4+5 (GeoCoT)	0.118	0.089	0.086	0.640	0.260	0.291	0.862	0.638	0.646

Table 8: Ablation study on the cumulative effect of different reasoning steps within the GeoCoT framework. The results demonstrate that the combination of all five steps yields the best performance.

frastructure) fails to fully leverage the advantages of GeoCoT. This limitation is highlighted by the marginal improvements observed across all three evaluation metrics (City, Country, and Continent). As shown in the table, the performance steadily improves as more reasoning steps are integrated. Consequently, the full efficacy of our GeoCoT framework is only realized through the synergistic integration of multi-step reasoning (Step 1 through Step 5), which achieves the highest accuracy and F1 scores across all granularities.