# FastGAS: Fast Graph-based Annotation Selection for In-Context Learning

Anonymous ACL submission

#### Abstract

In-context learning (ICL) empowers large language models (LLMs) to tackle new tasks by using a series of training instances as prompts. Since generating the prompts needs to sample from a vast pool of instances and annotate them (e.g., add labels in classification task), existing methods have proposed to select a subset of un-800 labeled examples for annotation, thus enhancing the quality of prompts and concurrently mitigating annotation costs. However, these methods often require a long time to select in-011 012 stances due to their complexity, hindering their practical viability. To address this limitation, we propose a graph-based selection method, 014 015 FastGAS, designed to efficiently identify highquality instances while minimizing computa-017 tional overhead. Initially, we construct a data similarity graph based on instance similarities. Subsequently, employing a graph partitioning algorithm, we partition the graph into pieces. Within each piece (i.e., subgraph), we adopt a greedy approach to pick the most representative nodes. By aggregating nodes from diverse pieces and annotating the corresponding instances, we identify a set of diverse and representative instances for ICL. Compared to prior approaches, our method not only exhibits supe-027 rior performance on different tasks but also significantly reduces selection time. In addition, we demonstrate the efficacy of our approach in LLMs of larger sizes.

#### 1 Introduction

Recent advances in natural language processing heavily leverage large language models, exemplified by models such as GPT-3 (Brown et al., 2020). Among them, in-context learning (ICL) emerges as a promising direction in this field. ICL adapts specific tasks with just a few instances as prompts, offering a viable alternative to traditional supervised fine-tuning (Liu et al., 2023). The performance of ICL is intricately tied to the effectiveness of the prompt surface, encompassing factors such as instance selection and the sequence of demonstration instances (Zhao et al., 2021; Dong et al., 2022; Lu et al., 2021). In this study, we focus on instance selection and explore novel solutions to reduce manual annotation costs while maintaining high in-context learning performance. 043

044

045

046

047

049

051

054

057

059

060

061

062

063

064

065

066

067

068

069

070

071

072

073

076

077

078

079

081

Previous research underscores the importance of retrieving prompts from a vast set of annotated instances to achieve optimal performance (Liu et al., 2021; Rubin et al., 2021). In particular, performance is shown to improve significantly when choosing in-context examples similar to each test input (Liu et al., 2021). However, addressing the unique requirements of different test instances requires a large set of annotated examples, incurring significant human and financial resources.

To mitigate annotation costs, previous efforts have sought to identify a small number of unlabeled instances for annotation (Su et al., 2022; Zhang et al., 2023). The objective is to select diverse and representative instances, where representativeness aids in finding similar demonstrations for different test instances, while diversity broadens the overall coverage. Despite their superiority over random selection, these methods have specific drawbacks. For example, Vote-k (Su et al., 2022) emphasizes diversity but adds inference costs due to predictions on unlabeled data. IDEAL (Zhang et al., 2023) employs influence-driven selective annotations, drawing inspiration from influence maximization in social graphs. However, both methods struggle to balance diversity and representativeness, leading to suboptimal performance.

Furthermore, a notable shortcoming of existing methods is their computational inefficiency. The precise calculation process (e.g., iteratively searching the entire dataset) results in high computational costs, making them less practical for real-world applications. Figure 1 illustrates the time required by our method and two baseline methods, Vote-k and IDEAL, under the same hardware conditions



Figure 1: Comparison of our method and two baselines on three classification tasks (MPRC, SST-5, and DBpedia) with respect to time consumption during subset selection. The annotation budget is 18. The y-axis represents the time consumption with a log scale. Notably, our method significantly reduces the time cost in comparison to both baseline methods.

and annotation budgets. It is observed that both baselines necessitate at least 500 seconds to select a subset for DBpedia and SST-5 tasks. Remarkably, for the DBpedia task, Vote-*k* exceeds 30,000 seconds (over eight hours) to select just 18 instances. As the annotation budget grows, the time needed by these methods to perform the selection process can increase exponentially (See Section 4.4), further constraining their applicability in real-world settings. In our pursuit of an efficient and effective selective annotation method, we pose the fundamental question: *Can we identify a set of diverse and representative instances with high efficiency*?

087

093

100

101

102

103

104

105

106

107

109

110

111

112

113

114

115

116

117

Answering this question, we propose **FastGAS**, a <u>Fast Graph-based Annotation Selection method</u> that works in an unsupervised manner. We first build a data similarity graph based on the similarity among unlabeled data. We then select instances for annotation based on the data similarity graph. In particular, our method focuses on the following three properties of selected instances:

- **Diversity**: We perform graph partitioning to separate the data similarity graph into segments. We treat each segment as a set of instances. We ensure the diversity of selected instances by selecting them from different segments.
- **Representiveness**: For each segment, we select instances with the max corresponding node degree in the data similarity graph. The selected instances thus can maximally cover the subgraph and guarantee their representativeness.
- **Efficiency**: We apply a multi-level graph bisection algorithm to speed up the graph partitioning process. For the selection of each segment, we

apply a simple but effective greedy algorithm. Compared to baseline methods that iteratively select over the entire graph, applying the greedy algorithm on each component can reduce the computation time. 118

119

120

121

122

123

124

125

126

127

128

129

130

131

132

133

134

135

136

137

138

139

140

141

142

143

144

145

146

147

148

149

151

152

153

154

155

156

157

158

159

160

161

163

164

165

167

Compared with state-of-the-art baseline methods, our method improves the overall performance on seven datasets in three types of tasks. Besides, for all tasks, our method only needs a few seconds to complete the instance selection process. In addition, we also provide a theoretical guarantee for the effectiveness of the greedy selection algorithm.

## 2 Related Work

**In-Context Learning** In-context learning (ICL) integrates a small number of training examples as prompts before the test input (Brown et al., 2020), demonstrating a remarkable ability to enhance the performance of large language models (LLMs) in a wide range of downstream tasks, such as machine translation (Agrawal et al., 2022; Sia and Duh, 2023), data generation (Ye et al., 2022), and others (Wang et al., 2021b; He et al., 2023; Panda et al., 2023). Furthermore, the advent of advanced strategies such as chain-of-thought prompting (Wei et al., 2022) has significantly refined the efficacy of ICL, offering deeper insights and more nuanced understanding within this innovative paradigm (Kim et al., 2022; Chan et al., 2022; Srivastava et al., 2022; Bansal et al., 2022).

Despite its successes, ICL's efficacy is often hampered by the sensitivity to the choice of in-context examples, leading to research on optimized selection strategies (Liu et al., 2021; Lu et al., 2021; Zhao et al., 2021). Techniques have evolved from selecting examples close to the test input in embedding spaces (Liu et al., 2021; Wu et al., 2022; Gao et al., 2020; Rubin et al., 2021). The focus has also shifted towards annotation efficiency, exploring how to find a set of examples once for all queries on the same task (Zhang et al., 2023; Su et al., 2022; Chang and Jia, 2023). Following existing works (Zhang et al., 2023; Su et al., 2022), we also use a graph to represent unlabeled instances and employ graph-based methods to select instances for annotation. However, our methodology distinguishes itself from existing works by focusing on efficiency in the selection of instances. As discussed in Section 1, we aim to select diverse and representative instances while reducing the computation cost.

267

Active Learning Given a limited budget for la-168 beling, active learning empowers machine learn-169 ing models to achieve comparable or superior per-170 formance using a carefully selected set of labeled 171 training instances (Cohn et al., 1994; Settles, 2009). Our work on selective annotation aligns with the 173 goal of active learning applied to graphs, specifi-174 cally focusing on the selection of nodes for labeling 175 to inform predictions (Cai et al., 2017; Jia et al., 2019; Wang et al., 2021a). Traditional graph-based 177 active learning methods employ criteria such as un-178 certainty (Settles and Craven, 2008) and represen-179 tativeness (Li and Guo, 2013) for selection. Since 180 the ICL tasks we focus on do not involve model 181 training or finetuning, we compare our method 182 with basic graph active learning methods that are not incorporated with model training, like those based on node degree (Cai et al., 2017; Wang et al., 2021a) and PageRank (Rodriguez, 2008). Our ex-186 periments indicate that while simple graph active learning methods work well in ICL, our approach still achieves better overall performance.

#### 3 Methods

190

191

192

194

195

196

197

207

209

212

213

214

215

216

In this section, we will explain how to integrate a graph partition algorithm and a greedy algorithm in a selective annotation in in-context learning to reduce the annotation cost.

#### 3.1 Problem Setup

We first give the definition of the selective annotation problem. In-context learning is a paradigm that allows language models to learn tasks given only a few examples in the form of demonstration (Brown et al., 2020). Specifically, LLMs perform in-context learning tasks based on a taskspecific prompt Z formed by concatenating M labeled training examples  $Z = [\mathbf{z}_1, ..., \mathbf{z}_M]$ , where each  $\mathbf{z}_i$  represents one labeled example  $(\mathbf{x}_i, \mathbf{y}_i)$ consisting of the instance  $\mathbf{x}_i$  and label  $\mathbf{y}_i$  (e.g., the answer of a question based on the instance). In the real world, we usually only have unlabeled samples  $\mathcal{X} = {\mathbf{x}_i}_{i=1}^N$ , and obtaining large-scale annotated examples for ICL requires substantial manpower and financial resources.

Selective annotation aims at selecting a subset  $\mathcal{L} \subset \mathcal{X}$  to be annotated, where  $|\mathcal{L}| = M$  is the annotation budget, such that ICL only using prompts retrieved from the selected subset can yield good performance on the test set and thus reduce the annotation cost.

#### **3.2 Fast Graph-based Annotation Selection**

For the selective annotation problem, it is essential to find a subset that covers vast unlabeled data. To achieve this, we design a graph-based annotation method that balances the diversity and representativeness of the annotated samples. Briefly, we build a data similarity graph by assessing the similarity of unlabeled data embeddings. We partition the data similarity graph into distinct subgraphs by employing a multi-level graph bisection algorithm, and each subgraph is treated as a candidate set. Through a stepwise, greedy selection process of the most influential data nodes in each subgraph, we generate subsets that encapsulate the subgraph's information. Ultimately, we aggregate these subsets from all subgraphs to represent the unlabeled data. We will now provide a detailed, step-by-step explanation of the aforementioned process.

**Data Similarity Graph Generation.** By averaging the resulting vectors over the text input words, we compute the vector representation for each unlabeled training instance using Sentence-BERT (Reimers and Gurevych, 2019). We then use the embedding vectors to create the data similarity graph  $\mathcal{G} = (\mathcal{V}, \mathcal{E})$  where each vertex  $v_i \in \mathcal{V}$  represents an unlabeled instance  $x_i \in \mathcal{X}$  as defined above. For each vertex  $v \in \mathcal{V}$ , we introduce edges connecting it to its k nearest neighbors in terms of cosine similarity and get  $\mathcal{E}$ .

Graph Partitioning. We aim to enhance instance *diversity* by strategically selecting instances from various regions within the data similarity graph. The division of regions process can be conceptualized as addressing a K-way graph partitioning problem, where the goal is to effectively divide the graph into K distinct components with approximately equal numbers of vertices but with few edges crossing between components. The formal definition of the graph partitioning problem is defined as follows: given a graph  $\mathcal{G}$  =  $(\mathcal{V}, \mathcal{E})$  with  $|\mathcal{V}| = N$ , partition  $\mathcal{V}$  into K subsets,  $\mathcal{V}_1, \mathcal{V}_2, ..., \mathcal{V}_K$  such that  $\mathcal{V}_i \cap \mathcal{V}_j = \emptyset$  for  $i \neq j$ ,  $|\mathcal{V}_i|$  is close N/K,  $\bigcup_i \mathcal{V}_i = \mathcal{V}$ , and the number of edges of  $\mathcal{E}$  whose incident vertices belong to different subsets is minimized.

The K-way graph partitioning problem is an NP-complete problem. We tend to use recursive bisection to find an approximate solution with an acceptable execution time. Specifically, we first obtain a 2-way partition of  $\mathcal{G}$ , and then we recursively bisect the two segments independently. Af-



Figure 2: An overview FastGAS. Given the unlabeled data pool, we initially construct a graph based on data similarity. This graph is then partitioned into distinct components. Within each component, we employ a greedy algorithm to select nodes until we reach the annotation budget. The selected instances are annotated and subsequently used to retrieve ICL prompts for the task.

ter  $\log K$  phases,  $\mathcal{G}$  is partitioned into K different components. Unfortunately, graph bisection is also NP-complete and has several inherent shortcomings (Hendrickson et al., 1995). In order to improve efficiency, we apply a multi-level graph bisection algorithm to produce high-quality partitions at low cost (Karypis and Kumar, 1998). It consists of the following three phases:

269

270

271

272

273

278

279

283

290

291

296

298

- Coarsening phase: The graph G is transformed into a sequence of smaller graphs G<sub>1</sub>, G<sub>2</sub>, ..., G<sub>m</sub> such that |V| > |V<sub>1</sub>| > |V<sub>2</sub>| > ··· > |V<sub>m</sub>|.
- Partitioning phase: A 2-way partition P<sub>m</sub> of the graph G<sub>m</sub> = (V<sub>m</sub>, E<sub>m</sub>) is computed that partitions V<sub>m</sub> into two subgraphs, each containing half the vertices of G.
- Uncoarsening phase: The partition  $P_m$  of  $\mathcal{G}_m$  is projected back to  $\mathcal{G}$  by going through intermediate partitions  $P_{m-1}, P_{m-2}, ..., P_1, P_0$ .

For more detailed methods of each phase, we will include them in Appendix C.

**Greedy Node Selection.** The graph partitioning operation divides the data similarity graph into Kdisjoint components, ensuring diversity by treating each component as a set of instances. However, further discussion is required on the selection of suitable instances that exhibit significant *representativeness* for each subgraph. Following the graph partitioning process, which yields K subgraphs with a similar number of nodes denoted as  $|\mathcal{V}_i| = N/K$ , and considering an annotation budget  $|\mathcal{L}| = M$ , our objective is to choose n = M/K instances within each subgraph. To mitigate potential challenges associated with high memory and computation costs, we employ a greedy selection method. In detail, for the subgraph  $\mathcal{G}_i$ , we first select the node  $v_i^1$  that has the largest degree:  $v_i^1 = \operatorname{argmax}_{v \in \mathcal{G}_j} d(v)$ . Then, we update the subgraph  $\mathcal{G}_i$  by removing the selected node  $v_i^1$  and the edges connecting  $v_i^1$ :  $\mathcal{G}_i = \mathcal{G}_i \setminus v_i^1$ . The above steps are repeated *n* times to get the selected node set  $\mathcal{V}_i^{sel} = \{v_i^1, ..., v_i^n\}$ , and the corresponding instances  $\mathcal{X}_i^{sel} = \{x_i^1, ..., x_i^n\}$  are chosen to represent the instances belonging to the subgraph  $\mathcal{G}_i$ . The iterative form can be written as

299

300

301

302

303

304

305

306

307

308

309

310

311

312

313

314

315

316

317

318

319

320

323

324

325

327

$$v_i^j = \operatorname*{argmax}_{v \in \mathcal{G}_i \setminus \{v_i^k | k \in [1, j-1]\}} d(v) \tag{1}$$

Specifically, the greedy selection algorithm guarantees the following property, demonstrating its ability to enhance the representativeness of the selected instances.

**Proposition 3.1.** Given the budget n and graph  $\mathcal{G}$ , the greedy algorithm will select  $\mathcal{V}^{sel} = \{v^1, ..., v^n\}$  that maximize the number of edges within  $\mathcal{V}^{sel}$  and those connecting  $\mathcal{V}^{sel}$  and  $\mathcal{G} \setminus \mathcal{V}^{sel}$ .

$$\mathcal{V}^{sel} = \operatorname*{argmax}_{|\mathcal{V}|=n} |\{(u, v) | u, v \in \mathcal{V}\}| + |\{(u, v) | u \in \mathcal{V} \text{ and } v \in \mathcal{G} \setminus \mathcal{V}\}|$$

$$321$$

**Remark 1.** The greedy selection process on subgraphs can be conceptualized as a divide-andconquer approach to selection on the entire graph, leading to improved algorithmic efficiency. Specifically, when the annotation budget M is considerably smaller than the total number of nodes N (i.e.,  $M \ll N$ ), the computational cost of greedy selection on the entire graph is  $\mathcal{O}(2MN)$ , while the cost incurred on the K subgraphs is significantly reduced to  $\mathcal{O}(\frac{2MN}{K})$ .

**Prompt Retrieval.** Upon obtaining a set of instances  $\mathcal{L} = \bigcup_i \mathcal{X}_i^{sel}$  through the greedy selective annotation process, we manually annotate  $\mathcal{L}$  to create a comprehensive set of labeled instances. Consistent with previous studies, we leverage Sentence-BERT (Reimers and Gurevych, 2019) to generate embeddings for all annotated instances and identify the most similar instances to each test input based on cosine similarity.

#### 4 Experiment

328

332

335

339

341

342

343

344

346

353

357

359

361

365

371

373

374

In this section, we evaluate the effectiveness of our method in various datasets encompassing diverse task categories. We begin by presenting the details of our experiment setups. Subsequently, the reported results demonstrate the superior performance of the proposed method in identifying an optimal selective annotation subset efficiently, outperforming established baselines. Furthermore, we conduct ablation studies to investigate the impact of crucial hyperparameters in our method.

#### 4.1 Setups

**Datasets and Models** We conduct extensive experiments in seven diverse datasets, which include six distinct tasks detailed in Table 4. Following existing works, each dataset adheres to the standard train/dev/test split provided by the Transformers library (Wolf et al., 2019). For datasets with publicly available test data (SST-5, XSUM, and DBpedia), we utilize the test set for evaluation. In cases where test data is not publicly accessible, consistent with previous works (Zhang et al., 2023; Su et al., 2022), we employ the dev data for evaluation. Evaluation metrics include precision for all classification and multiple-choice selection datasets and ROUGE-L (Lin, 2004) for XSUM.

Unless explicitly mentioned, we conduct all experiments using the GPT-J-6B model (Wang and Komatsuzaki, 2021). Additionally, we present results from tests on other models such as GPT-Neo-2.7B (Black et al., 2021), OPT-6.7B (Zhang et al., 2022), as well as more advanced models including Llama-2-7B-Chat (Touvron et al., 2023) and GPT-3.5-Turbo (OpenAI, 2023).

Baselines In our main experiments, we conduct acomprehensive evaluation of FastGAS against two

state-of-the-art selective annotation baselines: Votek (Su et al., 2022) and IDEAL (Zhang et al., 2023). Additionally, we benchmark FastGAS against other widely recognized methods in selecting core sets from extensive unlabeled data pools. These methods include (1) Top-degree (Wu et al., 2019), which selects nodes with the largest degrees until the annotation budget is met; (2) PageRank (Cai et al., 2017), which is used to score node representativeness in graph-based active learning; (3) Subclustering (Chen et al., 2023), which initially clusters instances into K groups via K-means, then further subdivides each into M/K subclusters for centroid instance selection; and (4) Louvain (Blondel et al., 2008), which utilizes the Louvain community detection algorithm for graph partitioning and a greedy selection algorithm akin to FastGAS for instance selection from each community.<sup>1</sup>

377

378

379

381

382

383

384

388

389

390

391

392

393

394

395

396

397

398

399

400

401

402

403

404

405

406

407

408

409

410

411

412

413

414

415

416

417

418

419

420

421

422

423

To emulate real-world conditions, we follow Vote-k (Su et al., 2022) and IDEAL (Zhang et al., 2023), selectively annotating from a pool of 3,000 instances randomly subsampled from the original training data for each task. For robustness, we conduct this subsampling procedure three times per experiment, and the reported results represent the average across three trials.

Hyperparameter Setting In our main experiment, we create a data similarity graph for all unlabeled instances by linking each vertex to its ten nearest neighbors (k = 10). For the baseline methods, we follow their hyperparameter settings to construct directed graphs (Zhang et al., 2023; Su et al., 2022). Regarding the selection of K for graph partitioning, we adjust K within  $\{2, 3, 6, 9\}$  for an annotation budget of 18, and within  $\{2, 5, 10, 25, 50\}$  for a budget of 100, identifying an optimal K for each task. Our method's selection time is significantly shorter than that of the baselines (Section 4.4), making the time spent finding the appropriate K negligible. We align our annotation budgets of 18 and 100 with those used in Vote-k (Su et al., 2022) and IDEAL (Zhang et al., 2023), choosing 18 specifically because it allows all annotated examples to fit within the context limits of LLMs without necessitating prompt retrieval. The impacts of k and K are detailed in Sections 4.3 and 4.5, respectively.

<sup>&</sup>lt;sup>1</sup>Since different communities contain different numbers of nodes, we select instances in proportion to the size of each community.

#### 4.2 Main Result

424

425

426

427 428

429

430

431

432

433

434

435

436

437

438

439

440

441

442

443

444

445

446

447

448

449

450

451

452

453

454

455

456

457

Table 2 presents a comparison between FastGAS and other baseline methods across annotation budgets of  $|\mathcal{L}| \in \{18, 100\}$ . FastGAS outperforms the two existing baselines in nearly all scenarios (13 out of 14). Notably, with an annotation budget of 18, all annotated examples fit within the prompt limitations of LLMs, making the evaluation results a direct reflection of the quality of selected instances (Zhang et al., 2023). When the annotation budget is 18, FastGAS performs better than the baseline on most datasets, which shows that FastGAS can select higher-quality data. While the proposed active learning baselines outshine in specific instances (e.g., the Subclustering method excels in the DBpedia task for both annotation budgets), their general performance is hindered by their approach to balancing representativeness and diversity of the selected instances. For example, methods like Top-degree and PageRank prioritize representativeness (Cai et al., 2017). Overall, FastGAS generally surpasses these baselines (10 out of 14), demonstrating its effectiveness. Furthermore, as a deterministic selective annotation method, Fast-GAS operates based on a given set of unlabeled samples, mirroring the advantage seen with Vote-k. This means that the variability in FastGAS's performance stems exclusively from the manner in which unlabeled samples are gathered. This significantly enhances the robustness of ICL by ensuring consistency in the selection process (Su et al., 2022). We provide detailed results that contain the maximum and minimum values of each task in Appendix F.

#### **4.3 Effect of** *k*

We compare FastGAS and other graph-based base-458 lines with respect to different k for the construction 459 of the graph, and the result is shown in Figure 3. 460 Initially, our method consistently exceeds other 461 graph-based baselines in various settings. Second, 462 we observe that the ideal k value varies among dif-463 ferent methods and datasets. Specifically, for the 464 MNLI dataset, most methods perform better with 465 k = 10. We also conclude that, for FedGAS, k466 must be carefully balanced, neither too large nor 467 too small. A smaller k value, as well as a larger one, impedes the ability to differentiate between distinct 469 representative nodes in the graph, complicating the 470 selection process by potentially choosing multiple 471 similar nodes. Concurrently, a larger k value could 472 also increase the computational time. 473



Figure 3: Comparison of our method and other graphbased baselines with respect to different k for the construction of the graph.

#### 4.4 Evaluating Time Efficiency

In Section 1, we illustrate that FastGAS drastically reduces the time cost compared to two existing methods with an annotation budget of 18. Figure 4 expands on this by showing the time consumption of our method and two baselines for an annotation budget of 100. Relative to Figure 1, the time needed for FastGAS does not increase much. This is because the most time-intensive processes in FastGAS, i.e., constructing and partitioning the data similarity graph, are not affected by the annotation budget. In contrast, the time costs of the two baselines, especially IDEAL, increase sharply; for nearly all tasks, IDEAL and Vote-k require more than eight hours for selection. As the annotation budget increases, the efficiency of FastGAS in example selection becomes even more pronounced.



Figure 4: Comparison of our method and two baselines on three classification tasks (MPRC, SST-5, and DBpedia) with respect to time consumption during subset selection. The annotation budget is 100. The y-axis represents the time consumption with a log scale.

#### 4.5 Effect of Number of Partitions

The hyperparameter K plays a critical role in graph partitioning, determining the number of components into which the graph is divided. We explore K's impact on FastGAS and offer insights for adjusting it. Figure 5 illustrates FastGAS's performance in three datasets with an annotation budget of 100. The figure demonstrates that enhancing 491

474

475

476

477

478

479

480

481

482

483

484

485

486

487

488

489

490

	Methods	Classification				Multi-Choice	Generation	
		MRPC	SST-5	MNLI	DBpedia	RTE	HellaSwag	XSUM
100	Vote-k	64.60	46.61	38.93	89.19	57.68	65.89	19.55
100	IDEAL	<u>65.49</u>	<u>49.87</u>	41.02	90.63	<u>58.98</u>	64.97	<u>19.68</u>
100	Top-degree	62.76	42.32	41.02	83.85	51.69	<u>66.67</u>	19.39
100	PageRank	64.84	40.71	44.17	83.72	53.38	66.01	19.55
100	Subclustering	64.84	49.48	41.28	92.32	57.55	65.62	19.18
100	Louvain	59.63	39.58	41.14	86.33	53.52	65.89	19.27
100	FastGAS	66.15	50.26	<u>42.06</u>	<u>90.76</u>	61.98	67.45	20.00
18	Vote-k	56.90	41.78	39.45	88.02	56.64	<u>66.02</u>	19.45
18	IDEAL	<u>63.80</u>	44.92	39.58	83.20	53.65	65.89	19.21
18	Top-degree	48.57	39.45	41.93	77.34	54.43	65.76	20.05
18	PageRank	46.09	39.71	40.49	79.04	56.07	65.89	19.82
18	Subclustering	61.46	<u>46.05</u>	37.63	89.06	<u>56.63</u>	65.76	19.49
18	Louvain	61.33	38.02	38.02	83.59	55.86	65.62	20.23
18	FastGAS	65.23	46.61	44.53	<u>88.93</u>	56.51	66.67	20.26

Table 1: The results of FastGAS and six baselines on seven distinct datasets with annotation budgets of 100 and 18, utilizing similarity-based prompt retrieval for all methods. We report the average results with three different runs for each method. Bold fonts indicate the best performance, while underlines denote the second-best results.

K up to a certain point improves FastGAS's performance; however, the increase beyond this optimal threshold does not result in further performance gains. A small K results in relatively rough partitioning, such that significantly different data points are grouped into the same subgraph. Selecting through coarsely partitioned subgraphs can obscure meaningful distinctions in the data, resulting in the loss of the diversity of the selected nodes. Conversely, with a sufficiently large K, the graph partitioning algorithm results in more edges being cut during the partitioning process, thus affecting the degree of nodes in each disjoint subgraph. As a result, nodes with a large degree in the original graph may lose a large number of edges due to partitioning and thus be ignored by the greedy algorithm. This alteration hampers the greedy algorithm's ability to select representative nodes effectively. Hence, a balanced K value facilitates the optimal performance of FastGAS by ensuring a balance of representativeness and diversity.

#### 4.6 **Random Prompt Retrieval**

In Section 4.2, we evaluate the performance of FastGAS against other baselines using a similarity-522 based prompt retrieval method. Building on previ-523 ous research (Zhang et al., 2023; Su et al., 2022), 524 we investigate the impact of employing a random 525 retrieval method, specifically, by randomly select-



Figure 5: Performance of FastGAS across different numbers of partitions with an annotation budget of 100.

527

528

529

530

531

532

533

534

535

536

537

538

539

540

541

542

543

544

ing labeled instances as prompts for each test instance under the annotation budget 100 and 18. The findings are presented in Table 2. We note a marked decline in the effectiveness of selective annotation methods under large annotation budgets when prompts are chosen through random selection. This deterioration may stem from the increased likelihood of selecting instances from the larger labeled pool that are less relevant to the test sample, as determined by their distance in the embedding space (Liu et al., 2021). Significantly, FastGAS continues to outperform the two baseline methods across all datasets, even when employing random retrieval. With an annotation budget of 18, all annotated instances fit within the prompt capacity of LLMs, making the order of instances the only difference between the two prompt retrieval methods. The performance of FastGAS underscores its capa-

499

500

501

504

505

506

507

510

511

512

513

514

515

517

518

519

Table 2: Comparison of random and similar prompt retrieval. The selection approach, when paired with a similarity-based prompt retrieval method, generally outperforms its counterpart, which utilizes a random prompt retrieval technique.

	Metho	ds	Datasets			
$ \mathcal{L} $	Selection	Retrieval	MRPC	MNLI	HellaSwag	
100	Vote-k	Similar	64.60	38.93	65.89	
100	IDEAL	Similar	65.49	41.02	64.97	
100	FastGAS	Similar	<b>66.15</b>	<b>42.06</b>	<b>67.45</b>	
100	Vote-k	Random	60.67	37.76	64.58	
100	IDEAL	Random	62.50	39.06	66.80	
100	FastGAS	Random	<b>62.50</b>	<b>40.88</b>	<b>67.32</b>	
18	Vote-k	Similar	56.90	39.45	66.02	
18	IDEAL	Similar	63.80	39.58	65.89	
18	FastGAS	Similar	<b>65.23</b>	<b>44.53</b>	<b>66.67</b>	
18	Vote-k	Random	54.56	41.02	66.54	
18	IDEAL	Random	64.19	38.15	66.54	
18	FastGAS	Random	<b>64.71</b>	<b>44.01</b>	<b>67.19</b>	

bility to produce a more reliable training subset for ICL tasks (Chang and Jia, 2023).

545

546

547

550

551

552

553

554

557

559

563

564

565

571

572

#### 4.7 Evaluation on Different Language Models

We conduct evaluations of FastGAS on various language models, including GPT-Neo 2.7B (Black et al., 2021), OPT-6.7B (Zhang et al., 2022), Llama-2-7B-Chat (Touvron et al., 2023), and GPT-3.5-Turbo (OpenAI, 2023)<sup>2</sup>, applying the same instructions across each dataset. Table 3 shows the performance of three selective annotation methods on smaller language models (GPT-Neo 2.7B and OPT-6.7B) across three datasets, where FastGAS overall surpasses two baseline annotation methods. Notably, OPT-6.7B exhibits lower performance on the XSUM summarization task compared to other LLMs, a finding echoed in (Tam et al., 2022). However, FastGAS remains superior to the baselines even when using the OPT-6.7B model.

Further experiments on more advanced LLMs are presented in Figure 6, confirming FastGAS's enhanced performance with larger language models. This underscores FastGAS as a versatile approach effective across LLMs of varying sizes. Particularly, the performance leap with GPT-3.5-Turbo, especially notable on the MNLI dataset (improving from 50.18% with Llama-2-7B-Chat to 70.18% with GPT-3.5-Turbo), highlights the advantage of larger models equipped with more parameters and

Table 3: Comparative performance of FastGAS versus baselines using GPT-Neo-2.7B and OPT-6.7B models across various datasets with an annotation budget of 18. FastGAS generally outperforms baseline methods across a variety of models and datasets.

Ν	lethods	Datasets		
Selection	Selection Model		DBpedia	XSUM
Vote-k	GPT-Neo-2.7B	57.42	80.73	19.45
IDEAL	GPT-Neo-2.7B	65.89	78.38	19.69
FastGAS	GPT-Neo-2.7B	<b>66.02</b>	<b>80.86</b>	<b>20.15</b>
Vote-k	OPT-6.7B	36.59	88.02	6.86
IDEAL	OPT-6.7B	<b>45.18</b>	83.20	6.13
FastGAS	OPT-6.7B	44.66	<b>88.93</b>	<b>6.89</b>

extensive training data, thereby bolstering their capability in classification tasks.



Figure 6: Comparative performance of FastGAS versus baselines using Llama-2-7B-Chat and GPT-3.5-Turbo models across various datasets with an annotation budget of 18.

### 5 Conclusion

Recent advancements have showcased the capability of large language models (LLMs) to adapt to new tasks with just a few demonstration instances. While existing approaches aim to enhance model performance by selecting a limited number of instances to annotate for prompts, they are hindered by significant computational demands and lengthy processing times. To address these challenges, we introduce a graph-based selection algorithm, Fast-GAS, accompanied by a theoretical analysis of its effectiveness. Our empirical evaluations reveal that this method outperforms others in seven distinct tasks, demonstrating exceptional efficacy. Unlike conventional methods that require high computation costs, our method greatly improves the efficiency of selecting instances, substantially enhancing its applicability to practical scenarios. Additionally, we demonstrate FastGAS's versatility across LLMs of various sizes. We hope that these insights will help researchers in devising effective ICL strategies to optimize LLM performance.

574

575

576

577

578

579

580

581

582

584

585

586

587

588

589

590

591

592

593

594

595

 $<sup>^{2}</sup>$ In a recent update, OpenAI announced the deprecation of the logprobs endpoint. Consequently, in our experiment, we employ the Vote-*k* method, specifically 'Fast vote-*k*,' which does not depend on this value.

618

619

625

633

634

635

637

638

639

641

642

643

644

## 6 Limitation

The primary constraint of our study is the inability to automatically select the most appropriate 599 number of partitions (K) and the most appropriate number of neighbors (k) during the data similarity graph construction. Given the relatively short execution time of our method, conducting multiple trials to identify the ideal K and k value is viable. However, the cost of the inference phase could restrict the feasibility of such extensive experimentation in practical settings. To enhance efficiency, FastGAS adopts a greedy selection process that is carried out separately for each piece. However, we have not explored how the interrelations between samples across different graph pieces influence the overall instance selection. Addition-612 ally, due to hardware limitations and available time, 613 our research only covered LLMs up to 7B in size. Future investigations will aim to assess FastGAS's 615 efficacy with larger LLMs and across a broader 616 array of tasks. 617

#### 7 Ethics Statement

This work introduces FastGAS, a graph-based selective annotation method that can effectively and efficiently select high-quality instances for incontext learning tasks. While acknowledging the need for responsible usage of the proposed method, we do not foresee major negative societal impacts.

#### References

- Sweta Agrawal, Chunting Zhou, Mike Lewis, Luke Zettlemoyer, and Marjan Ghazvininejad. 2022. Incontext examples selection for machine translation. *arXiv preprint arXiv:2212.02437*.
- Hritik Bansal, Karthik Gopalakrishnan, Saket Dingliwal, Sravan Bodapati, Katrin Kirchhoff, and Dan Roth.
  2022. Rethinking the role of scale for in-context learning: An interpretability-based case study at 66 billion scale. arXiv preprint arXiv:2212.09095.
- Luisa Bentivogli, Peter Clark, Ido Dagan, and Danilo Giampiccolo. 2009. The fifth pascal recognizing textual entailment challenge. *TAC*, 7(8):1.
- Sid Black, Leo Gao, Phil Wang, Connor Leahy, and Stella Biderman. 2021. Gpt-neo: Large scale autoregressive language modeling with mesh-tensorflow. *If you use this software, please cite it using these metadata*, 58.
- Vincent D Blondel, Jean-Loup Guillaume, Renaud Lambiotte, and Etienne Lefebvre. 2008. Fast unfolding of communities in large networks. *Jour*-

*nal of statistical mechanics: theory and experiment,* 2008(10):P10008.

646

647

648

649

650

651

652

653

654

655

656

657

658

659

660

661

662

663

664

665

666

668

669

670

671

672

673

674

675

676

677

678

679

680

681

682

683

684

685

686

687

688

689

690

691

692

693

694

695

696

697

- Tom Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared D Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, et al. 2020. Language models are few-shot learners. *Advances in neural information processing systems*, 33:1877–1901.
- Thang Nguyen Bui and Curt Jones. 1993. A heuristic for reducing fill-in in sparse matrix factorization. Technical report, Society for Industrial and Applied Mathematics (SIAM), Philadelphia, PA ....
- Hongyun Cai, Vincent W Zheng, and Kevin Chen-Chuan Chang. 2017. Active learning for graph embedding. *arXiv preprint arXiv:1705.05085*.
- Stephanie Chan, Adam Santoro, Andrew Lampinen, Jane Wang, Aaditya Singh, Pierre Richemond, James McClelland, and Felix Hill. 2022. Data distributional properties drive emergent in-context learning in transformers. *Advances in Neural Information Processing Systems*, 35:18878–18891.
- Ting-Yun Chang and Robin Jia. 2023. Data curation alone can stabilize in-context learning. In *Proceedings of the 61st Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 8123–8144.
- Zihan Chen, Xingyu Li, Miaomiao Yang, Hong Zhang, and Xu Steven Xu. 2023. Optimization of deep learning models for the prediction of gene mutations using unsupervised clustering. *The Journal of Pathology: Clinical Research*, 9(1):3–17.
- Patrick Ciarlet Jr and Françoise Lamour. 1996. On the validity of a front-oriented approach to partitioning large sparse graphs with a connectivity constraint. *Numerical Algorithms*, 12(1):193–214.
- David Cohn, Les Atlas, and Richard Ladner. 1994. Improving generalization with active learning. *Machine learning*, 15:201–221.
- Bill Dolan, Chris Quirk, and Chris Brockett. 2004. Unsupervised construction of large paraphrase corpora: exploiting massively parallel news sources. In *Proceedings of the 20th international conference on Computational Linguistics*, pages 350–es.
- Qingxiu Dong, Lei Li, Damai Dai, Ce Zheng, Zhiyong Wu, Baobao Chang, Xu Sun, Jingjing Xu, and Zhifang Sui. 2022. A survey for in-context learning. *arXiv preprint arXiv:2301.00234*.
- Tianyu Gao, Adam Fisch, and Danqi Chen. 2020. Making pre-trained language models better few-shot learners. *arXiv preprint arXiv:2012.15723*.
- Todd Goehring and Yousef Saad. 1994. Heuristic algorithms for automatic graph partitioning. Technical report, Citeseer.

- 704 706 707 708 710 711 712 713 714 715 716 717 718 719 720 721 722 723 724 725 727 728
- 731 736
- 739 740
- 741 742

744 745 746

747

749

- Jiabang He, Lei Wang, Yi Hu, Ning Liu, Hui Liu, Xing Xu, and Heng Tao Shen. 2023. Icl-d3ie: In-context learning with diverse demonstrations updating for document information extraction. arXiv preprint arXiv:2303.05063.
- Bruce Hendrickson, Robert W Leland, et al. 1995. A multi-level algorithm for partitioning graphs. SC, 95(28):1-14.
- Junteng Jia, Michael T Schaub, Santiago Segarra, and Austin R Benson. 2019. Graph-based semisupervised & active learning for edge flows. In Proceedings of the 25th ACM SIGKDD international conference on knowledge discovery & data mining, pages 761-771.
- George Karypis and Vipin Kumar. 1998. A fast and high quality multilevel scheme for partitioning irregular graphs. SIAM Journal on scientific Computing, 20(1):359-392.
- Brian W Kernighan and Shen Lin. 1970. An efficient heuristic procedure for partitioning graphs. The Bell system technical journal, 49(2):291-307.
- Hyuhng Joon Kim, Hyunsoo Cho, Junyeob Kim, Taeuk Kim, Kang Min Yoo, and Sang-goo Lee. 2022. Self-generated in-context learning: Leveraging autoregressive language models as a demonstration generator. arXiv preprint arXiv:2206.08082.
- Jens Lehmann, Robert Isele, Max Jakob, Anja Jentzsch, Dimitris Kontokostas, Pablo N Mendes, Sebastian Hellmann, Mohamed Morsey, Patrick Van Kleef, Sören Auer, et al. 2015. Dbpedia-a large-scale, multilingual knowledge base extracted from wikipedia. Semantic web, 6(2):167-195.
- Xin Li and Yuhong Guo. 2013. Active learning with multi-label svm classification. In IjCAI, volume 13, pages 1479-1485. Citeseer.
- Chin-Yew Lin. 2004. Rouge: A package for automatic evaluation of summaries. In Text summarization branches out, pages 74-81.
- Jiachang Liu, Dinghan Shen, Yizhe Zhang, Bill Dolan, Lawrence Carin, and Weizhu Chen. 2021. What makes good in-context examples for gpt-3? arXiv preprint arXiv:2101.06804.
- Pengfei Liu, Weizhe Yuan, Jinlan Fu, Zhengbao Jiang, Hiroaki Hayashi, and Graham Neubig. 2023. Pretrain, prompt, and predict: A systematic survey of prompting methods in natural language processing. ACM Computing Surveys, 55(9):1–35.
- Yao Lu, Max Bartolo, Alastair Moore, Sebastian Riedel, and Pontus Stenetorp. 2021. Fantastically ordered prompts and where to find them: Overcoming few-shot prompt order sensitivity. arXiv preprint arXiv:2104.08786.

Shashi Narayan, Shay Cohen, and Maria Lapata. 2018. Don't give me the details, just the summary! topicaware convolutional neural networks for extreme summarization. In 2018 Conference on Empirical Methods in Natural Language Processing, pages 1797–1807. Association for Computational Linguistics.

751

752

753

754

755

758

759

760

761

762

763

764

765

766

767

768

769

770

771

772

773

774

775

776

777

778

779

780

781

782

783

784

785

786

787

790

793

794

795

796

797

798

799

800

801

802

- OpenAI. 2023. Introducing GPT-3.5 Turbo. https: //openai.com/blog/gpt-3-5-turbo. Accessed: date-of-access.
- Ashwinee Panda, Tong Wu, Jiachen T Wang, and Prateek Mittal. 2023. Differentially private in-context learning. arXiv preprint arXiv:2305.01639.
- Adam Paszke, Sam Gross, Francisco Massa, Adam Lerer, James Bradbury, Gregory Chanan, Trevor Killeen, Zeming Lin, Natalia Gimelshein, Luca Antiga, et al. 2019. Pytorch: An imperative style, high-performance deep learning library. Advances in neural information processing systems, 32.
- Nils Reimers and Iryna Gurevych. 2019. Sentence-bert: Sentence embeddings using siamese bert-networks. arXiv preprint arXiv:1908.10084.
- Marko A Rodriguez. 2008. Grammar-based random walkers in semantic networks. Knowledge-Based Systems, 21(7):727-739.
- Ohad Rubin, Jonathan Herzig, and Jonathan Berant. 2021. Learning to retrieve prompts for in-context learning. arXiv preprint arXiv:2112.08633.

Burr Settles. 2009. Active learning literature survey.

- Burr Settles and Mark Craven. 2008. An analysis of active learning strategies for sequence labeling tasks. In proceedings of the 2008 conference on empirical methods in natural language processing, pages 1070-1079.
- Suzanna Sia and Kevin Duh. 2023. In-context learning as maintaining coherency: A study of on-the-fly machine translation using large language models. arXiv preprint arXiv:2305.03573.
- Richard Socher, Alex Perelygin, Jean Wu, Jason Chuang, Christopher D Manning, Andrew Y Ng, and Christopher Potts. 2013. Recursive deep models for semantic compositionality over a sentiment treebank. In Proceedings of the 2013 conference on empirical methods in natural language processing, pages 1631-1642.
- Aarohi Srivastava, Abhinav Rastogi, Abhishek Rao, Abu Awal Md Shoeb, Abubakar Abid, Adam Fisch, Adam R Brown, Adam Santoro, Aditya Gupta, Adrià Garriga-Alonso, et al. 2022. Beyond the imitation game: Quantifying and extrapolating the capabilities of language models. arXiv preprint arXiv:2206.04615.

- 803 804
- 80 80
- 807
- 80 80
- 810 811
- 812
- 813 814 815
- 816 817
- 817 818
- 819 820

- 823 824 825 826
- 827 828 829
- 0
- 831 832
- 833 834
- 836

8

841 842

- 84
- 844 845
- 8
- 8
- 850 851

8

- 853 854
- 855

- Hongjin Su, Jungo Kasai, Chen Henry Wu, Weijia Shi, Tianlu Wang, Jiayi Xin, Rui Zhang, Mari Ostendorf, Luke Zettlemoyer, Noah A Smith, et al. 2022. Selective annotation makes language models better fewshot learners. *arXiv preprint arXiv:2209.01975*.
- Derek Tam, Anisha Mascarenhas, Shiyue Zhang, Sarah Kwan, Mohit Bansal, and Colin Raffel. 2022. Evaluating the factual consistency of large language models through summarization. *arXiv preprint arXiv:2211.08412*.
- Hugo Touvron, Louis Martin, Kevin Stone, Peter Albert, Amjad Almahairi, Yasmine Babaei, Nikolay Bashlykov, Soumya Batra, Prajjwal Bhargava, Shruti Bhosale, et al. 2023. Llama 2: Open foundation and fine-tuned chat models. *arXiv preprint arXiv:2307.09288*.
- Ben Wang and Aran Komatsuzaki. 2021. GPT-J-6B: A 6 Billion Parameter Autoregressive Language Model. https://github.com/kingoflolz/ mesh-transformer-jax.
- Qunbo Wang, Wenjun Wu, Yongchi Zhao, and Yuzhang Zhuang. 2021a. Graph active learning for gcn-based zero-shot classification. *Neurocomputing*, 435:15– 25.
- Shuohang Wang, Yang Liu, Yichong Xu, Chenguang Zhu, and Michael Zeng. 2021b. Want to reduce labeling cost? gpt-3 can help. *arXiv preprint arXiv:2108.13487*.
- Jason Wei, Xuezhi Wang, Dale Schuurmans, Maarten Bosma, Fei Xia, Ed Chi, Quoc V Le, Denny Zhou, et al. 2022. Chain-of-thought prompting elicits reasoning in large language models. *Advances in Neural Information Processing Systems*, 35:24824–24837.
- Adina Williams, Nikita Nangia, and Samuel Bowman. 2018. A broad-coverage challenge corpus for sentence understanding through inference. In Proceedings of the 2018 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long Papers), pages 1112–1122.
- Thomas Wolf, Lysandre Debut, Victor Sanh, Julien Chaumond, Clement Delangue, Anthony Moi, Pierric Cistac, Tim Rault, Rémi Louf, Morgan Funtowicz, et al. 2019. Huggingface's transformers: State-ofthe-art natural language processing. *arXiv preprint arXiv:1910.03771*.
- Yuexin Wu, Yichong Xu, Aarti Singh, Yiming Yang, and Artur Dubrawski. 2019. Active learning for graph neural networks via node feature propagation. *arXiv preprint arXiv:1910.07567*.
- Zhiyong Wu, Yaoxiang Wang, Jiacheng Ye, and Lingpeng Kong. 2022. Self-adaptive in-context learning. *arXiv preprint arXiv:2212.10375*.

Jiacheng Ye, Jiahui Gao, Jiangtao Feng, Zhiyong Wu, Tao Yu, and Lingpeng Kong. 2022. Progen: Progressive zero-shot dataset generation via in-context feedback. *arXiv preprint arXiv:2210.12329*. 856

857

858

859

860

861

862

863

864

865

866

867

868

869

870

871

872

873

874

875

876

877

878

879

- Rowan Zellers, Ari Holtzman, Yonatan Bisk, Ali Farhadi, and Yejin Choi. 2019. Hellaswag: Can a machine really finish your sentence? *arXiv preprint arXiv:1905.07830*.
- Shaokun Zhang, Xiaobo Xia, Zhaoqing Wang, Ling-Hao Chen, Jiale Liu, Qingyun Wu, and Tongliang Liu. 2023. Ideal: Influence-driven selective annotations empower in-context learners in large language models. *arXiv preprint arXiv:2310.10873*.
- Susan Zhang, Stephen Roller, Naman Goyal, Mikel Artetxe, Moya Chen, Shuohui Chen, Christopher Dewan, Mona Diab, Xian Li, Xi Victoria Lin, Todor Mihaylov, Myle Ott, Sam Shleifer, Kurt Shuster, Daniel Simig, Punit Singh Koura, Anjali Sridhar, Tianlu Wang, and Luke Zettlemoyer. 2022. Opt: Open pretrained transformer language models.
- Zihao Zhao, Eric Wallace, Shi Feng, Dan Klein, and Sameer Singh. 2021. Calibrate before use: Improving few-shot performance of language models. In *International Conference on Machine Learning*, pages 12697–12706. PMLR.

## A General experimental conditions

881

894

901

903

904

905

906

907

909

882Our implementation of FastGAS and baselines is primarily conducted using PyTorch (Paszke et al., 2019).883For the GPT-3.5-Turbo experiments, we utilize the OpenAI API. The models GPT-J-6B, GPT-Neo 2.7B,884Llama-2-7B-Chat, and OPT-6.7B are sourced from the Huggingface Transformers Library (Wolf et al.,8852019). All experiments are performed on a single NVIDIA RTX A6000 GPU with 48GB of memory.

## **B** The Detailed Information of Seven Datasets

	Dataset	Task
Classification	MRPC (Dolan et al., 2004) SST-5 (Socher et al., 2013) DBpedia (Lehmann et al., 2015) MNLI (Williams et al., 2018) RTE (Bentivogli et al., 2009)	Paraphrase Detection Sentiment Analysis Topic Classification Natural Language Inference Natural Language Inference
Multiple-Choice	HellaSwag (Zellers et al., 2019)	Commonsense Reasoning
Generation	XSUM (Narayan et al., 2018)	Summarization

#### Table 4: The detailed information of seven datasets

## C Detailed Graph Partition Algorithm

- Coarsening phase: The graph G is transformed into a sequence of smaller graphs G<sub>1</sub>, G<sub>2</sub>, ..., G<sub>m</sub> such that |V| > |V<sub>1</sub>| > |V<sub>2</sub>| > ··· > |V<sub>m</sub>|.
- **Partitioning phase**: A 2-way partition  $P_m$  of the graph  $\mathcal{G}_m = (\mathcal{V}_m, \mathcal{E}_m)$  is computed that partitions  $\mathcal{V}_m$  into two parts, each containing half the vertices of  $\mathcal{G}$ .
  - Uncoarsening phase: The partition  $P_m$  of  $\mathcal{G}_m$  is projected back to  $\mathcal{G}$  by going through intermediate partitions  $P_{m-1}, P_{m-2}, ..., P_1, P_0$

**Coarsening phase** Due to the construction of the data similarity graph, the degree of most vertices is close to the graph's average degree. To generate coarser graphs, we employ a strategy of finding a random matching and merging the matched vertices into a multi-node (Bui and Jones, 1993; Hendrickson et al., 1995). A graph's matching is a set of edges, each pair of which shares no common vertex. We create a subsequent coarser graph,  $\mathcal{G}_{i+1}$ , from  $\mathcal{G}_i$  by matching in  $\mathcal{G}_i$  and merging the matched vertices. We utilize a random algorithm akin to those detailed in (Bui and Jones, 1993; Hendrickson et al., 1995).

The algorithm operates as follows: vertices are processed in a random sequence. For an unmatched vertex u, an unmatched adjacent vertex v is randomly chosen, and the edge (u, v) is added to the matching. If there is no unmatched adjacent vertex for u, then u remains unmatched in this random matching process. The computational complexity of this algorithm is  $O(|\mathcal{E}|)$ .

**Partitioning phase** To efficiently bisect the graph, we simply initiate from a vertex and expand a region around it using a breadth-first approach until half of the vertices are encompassed (Ciarlet Jr and Lamour, 1996; Goehring and Saad, 1994). Given that the bisection quality is highly dependent on the initial vertex selection (Karypis and Kumar, 1998), we employ a strategy similar to (Karypis and Kumar, 1998), wherein we randomly select 10 vertices and subsequently expand 10 distinct regions from each. The trail yielding the smallest edge cut is then chosen for the partition.

**Uncoarsening phase** During the uncoarsening phase, as each vertex  $u \in \mathcal{G}_{i+1}$  represents a unique subset  $\mathcal{U}$  of vertices from  $\mathcal{G}_i$ , we derive partition  $P_i$  from  $P_{i+1}$  by assigning the vertices in  $\mathcal{U}$  to the same part that vertex u belongs to. Although  $P_{i+1}$  may represent a local minimum partition for  $\mathcal{G}_{i+1}$ , the corresponding partition  $P_i$  might not be at a local minimum with respect to  $\mathcal{G}_i$ . To refine this uncoarsened partition, we employ the KL algorithm (Kernighan and Lin, 1970), which iteratively searches for and swaps subsets of vertices between partitions to achieve a lower edge cut. This swapping process continues until no further improvements can be made, indicating that the partition has reached a local minimum.

#### D Proof of Proposition 3.1

*Proof.* We employ an inductive approach to demonstrate that the node set  $\mathcal{V}^{sel}$ , selected by the greedy algorithm, satisfies the maximum cover property, 919

$$\mathcal{V}^{sel} = \operatorname*{argmax}_{|\mathcal{V}|=n} |\{(u,v)|u,v\in\mathcal{V}\}| + |\{(u,v)|u\in\mathcal{V} \text{ and } v\in\mathcal{G}\setminus\mathcal{V}\}|$$
(2)

When n = 1,  $\mathcal{V}^{sel} = \{v^1\}$ . Thus,

$$|\{(u,v)|u \in \mathcal{V} \text{ and } v \in \mathcal{G} \setminus \mathcal{V}\}| = \text{degree}(v^1) \text{ and } |\{(u,v)|u,v \in \mathcal{V}\}| = 0.$$
922

By selecting  $v_1 = \operatorname{argmax}_{v \in \mathcal{G}} d(v)$ , the maximum cover property holds for n = 1. Assume it holds for n = k, let  $\mathcal{V}_k^{sel}$  denotes the selected node set at the budget k and  $\mathcal{V}_{k+1}^{sel} = \mathcal{V}_k^{sel} \cup \{v^{k+1}\}$ . For the first term in Eq. 2, we have 925

$$|\{(u,v)|u,v\in\mathcal{V}_{k+1}^{sel}\}| = |\{(u,v)|u,v\in\mathcal{V}_{k}^{sel}\}| + |\{(u,v^{k+1})|u\in\mathcal{V}_{k}^{sel}\}|.$$
(3) 926

For the second term in Eq. 2, we have

$$\begin{aligned} |\{(u,v)|u \in \mathcal{V}_{k+1}^{sel} \text{ and } v \in \mathcal{G} \setminus \mathcal{V}_{k+1}^{sel}\}| \\ = |\{(u,v)|u \in \mathcal{V}_{k}^{sel} \text{ and } v \in \mathcal{G} \setminus \mathcal{V}_{k+1}^{sel}\}| + |\{(v^{k+1},v)| \ v \in \mathcal{G} \setminus \mathcal{V}_{k+1}^{sel}\}| \\ = |\{(u,v)|u \in \mathcal{V}_{k}^{sel} \text{ and } v \in \mathcal{G} \setminus \mathcal{V}_{k+1}^{sel}\}| + |\{(v^{k+1},v)| \ v \in \mathcal{G} \setminus \mathcal{V}_{k}^{sel}\}| \\ = |\{(u,v)|u \in \mathcal{V}_{k}^{sel} \text{ and } v \in \mathcal{G} \setminus \mathcal{V}_{k}^{sel}\}| - |\{(u,v^{k+1})|u \in \mathcal{V}_{k}^{sel}\}| + |\{(v^{k+1},v)| \ v \in \mathcal{G} \setminus \mathcal{V}_{k}^{sel}\}|. \end{aligned}$$

$$(4)$$

The second equality sign holds because

$$|\{(v^{k+1}, v)| \ v \in \mathcal{G} \setminus \mathcal{V}_{k+1}^{sel}\}| = |\{(v^{k+1}, v)| \ v \in \mathcal{G} \setminus \mathcal{V}_{k}^{sel}\}| - |\{(v^{k+1}, v)| \ v \in \mathcal{V}_{k+1}^{sel} \setminus \mathcal{V}_{k}^{sel}\}|, \\ |\{(v^{k+1}, v)| \ v \in \mathcal{V}_{k+1}^{sel} \setminus \mathcal{V}_{k}^{sel}\}| = |\{(v^{k+1}, v)| \ v \in \{v^{k+1}\}\}| = 0.$$

We then combine Eq. 3 and Eq. 4 and obtain that

$$\begin{aligned} |\{(u,v)|u,v \in \mathcal{V}_{k+1}^{sel}\}| + |\{(u,v)|u \in \mathcal{V}_{k+1}^{sel} \text{ and } v \in \mathcal{G} \setminus \mathcal{V}_{k+1}^{sel}\}| \\ = |\{(u,v)|u,v \in \mathcal{V}_{k}^{sel}\}| + |\{(u,v^{k+1})|u \in \mathcal{V}_{k}^{sel}\}| + |\{(u,v)|u \in \mathcal{V}_{k}^{sel} \text{ and } v \in \mathcal{G} \setminus \mathcal{V}_{k}^{sel}\}| \\ - |\{(u,v^{k+1})|u \in \mathcal{V}_{k}^{sel}\}| + |\{(v^{k+1},v)| \ v \in \mathcal{G} \setminus \mathcal{V}_{k}^{sel}\}| \\ = |\{(u,v)|u,v \in \mathcal{V}_{k}^{sel}\}| + |\{(u,v)|u \in \mathcal{V}_{k}^{sel} \text{ and } v \in \mathcal{G} \setminus \mathcal{V}_{k}^{sel}\}| + |\{(v^{k+1},v)| \ v \in \mathcal{G} \setminus \mathcal{V}_{k}^{sel}\}| \end{aligned}$$
(5)

Since  $\mathcal{V}_k^{sel}$  satisfies that

$$\mathcal{V}_{k}^{sel} = \operatorname*{argmax}_{|\mathcal{V}|=k} |\{(u,v)|u,v\in\mathcal{V}\}| + |\{(u,v)|u\in\mathcal{V} \text{ and } v\in\mathcal{G}\setminus\mathcal{V}\}|,$$
934

and from the algorithm, we have

$$v^{k+1} = \operatorname*{argmax}_{v \in \mathcal{G} \setminus \{v_i | i \in [1,k]\}} \operatorname{degree}(v) = \operatorname*{argmax}_{v \in \mathcal{G} \setminus \mathcal{V}_k^{sel}} |\{(v,u)| \ u \in \mathcal{G} \setminus \mathcal{V}_k^{sel}\}|.$$
936

Thus

$$\mathcal{V}_{k+1}^{sel} = \mathcal{V}_k^{sel} \cup \{v^{k+1}\}$$

$$= \underset{|\mathcal{V}|=k+1}{\operatorname{argmax}} |\{(u,v)|u,v\in\mathcal{V}\}| + |\{(u,v)|u\in\mathcal{V} \text{ and } v\in\mathcal{G}\setminus\mathcal{V}\}|.$$
938

In conclusion, given the budget n and graph  $\mathcal{G}$ , the  $\mathcal{V}^{sel}$  returned by the greedy algorithm satisfies the property in Eq.2.

932

933

935

917

921

927

929

# E Example Prompt of Each Task

## 942 E.1 MRPC

- **Input:** Are the following two sentences 'equivalent' or 'not equivalent'?
  - Excluding autos, retail sales rose by 0.3 % in September, lower than a forecast rise of 0.5 % ... Retail sales fell 0.2 percent overall in September compared to forecasts of a 0.1 percent dip ...
  - answer:
- 947
  - Output: not equivalent

# 48 E.2 SST-5

- **Input:** How do you feel about the following sentence?
  - ... the film's considered approach to its subject matter is too calm and thoughtful for agitprop, and the thinness of its characterizations makes it a failure as straight drama.
- 952 answer:
- 953 **Output:** very negative

## 54 E.3 MNLI

**Input:** Quite an hour, or even more, had elapsed between the time when she had heard the voices and 5 o'clock when she had taken tea to her mistress. Based on that information, is the claim A day had passed from when she'd taken the tea in. "True," "False," or "Inconclusive"? answer:

158 a

955

956

957

959 Output: False

## 60 E.4 DBpedia

Input: title: Grace Evangelical Lutheran Church (Minneapolis Minnesota); content: Grace Evangelical
 Lutheran Church is a church in Minneapolis, Minnesota, United States, adjacent to the University of
 Minnesota East Bank campus. The church was built in 1915-1917 by a Swedish Lutheran congregation to
 serve university students. It was designed by Chapman and Magney and built in the Gothic Revival style.
 The congregation was organized in Minneapolis in 1903 by the Swedish immigrant-dominated Augustana
 Evangelical Lutheran Church.

967 **Output:** building

## 968 E.5 RTE

- Input: He met U.S. President, George W. Bush, in Washington and British Prime Minister, Tony Blair, in London..
- 71 question: Washington is part of London. True or False?
- answer:
- 973 **Output:** False

#### E.6 Hellaswag

Input: The topic is Cleaning sink. A middle aged female talks about a cleaning product. The female
opens a container of cleaner and puts it on a rag. the female,
Optional E"then inflormed a different cleaner to clean a cock " "week the rag to enrow down a well "

- **Options:** ["then inflames a different cleaner to clean a sock.", "uses the rag to spray down a wall.",
- "washes the rug thoroughly and scratches it.", "then uses the rag to rub the inside of the sink."]
- 979 **Output:** then uses the rag to rub the inside of the sink.

## E.7 Xsum

**Input:** Stead curled home with 14 minutes remaining to cap a fine comeback at the Northern Gas and Power Stadium after Louis Lang cancelled out Toto Nsiala's opener. Hartlepool flew out of the blocks and took an eighth-minute lead when Nsiala bundled home at the back post after Lewis Alessandra beat his man and sent in a pin-point cross.

980

981

982

983

984

985

986

987

988

989

990

991

992

993

994

995

996

997

998

#### •••••

Substitution, Notts County. Vadaine Oliver replaces Jonathan Forte because of an injury. Attempt saved. Nathan Thomas (Hartlepool United) right footed shot from the left side of the box is saved in the bottom right corner. Corner, Hartlepool United. Conceded by Matt Tootle. Attempt missed. Michael Woods (Hartlepool United) right footed shot from outside the box is close, but misses the top right corner. Foul by Billy Paynter (Hartlepool United). Stanley Aborah (Notts County) wins a free kick in the attacking half... **Output:** Jon Stead struck the winner as Notts County came from behind to earn victory at Hartlepool United in League Two.

#### **F** Detailed Main Results

In Section 4.2, we present the average evaluation outcomes of various methods across three random trials. This section offers comprehensive results for FastGAS and two current baselines, detailing mean, maximum, and minimum values. It is evident that FastGAS consistently delivers superior performance across the majority of trials. Furthermore, FastGAS's performance in the least favorable scenarios is markedly better than that of the baselines in most instances.

Table 5: Mean/Maximum/Minimum performance of FastGAS and two baselines across the first four tasks in Table 1 over three trials. The best average performance for each task is highlighted in bold.

Methods	MRPC	SST-5	MNLI	DBpedia
100 Vote-k	64.60/68.75/62.11	46.61/47.27/46.09	38.93/43.75/35.55	89.19/89.84/88.67
100 IDEAL	65.49/66.02/64.84	49.87/52.73/46.09	41.02/41.41/40.23	90.63/91.41/89.45
100 FastGAS	<b>66.15</b> /69.14/62.89	<b>50.26</b> /55.86/42.58	<b>42.06</b> /43.75/41.02	<b>90.76</b> /92.19/88.28
18 Vote-k	56.90/67.19/47.27	41.78/45.70/37.11	39.45/42.19/37.11	88.02/91.02/83.59
18 IDEAL	63.80/67.19/59.77	44.92/48.82/41.79	39.58/41.80/37.50	83.20/85.94/81.64
18 FastGAS	<b>65.23</b> /71.88/55.47	<b>46.61</b> /48.04/45.70	<b>44.53</b> /47.66/41.02	<b>88.93</b> /92.58/84.77

Table 6: Average/Maximum/Minimum performance of FastGAS and two baselines across the first four tasks in Table 1 over three trials. The best performance for each task is highlighted in bold.

Methods	RTE	HellaSwag	Xsum
100 Vote- <i>k</i>	57.68/58.20/57.42	65.89/69.14/64.06	19.55/19.94/19.13
100 IDEAL	58.98/60.94/57.42	64.97/69.53/61.72	19.68/19.77/19.58
100 FastGAS	<b>61.98</b> /63.28/60.55	<b>67.45</b> /71.88/65.23	<b>20.00</b> /20.55/19.59
18 Vote-k	<b>56.64</b> /57.81/55.86	66.02/71.09/63.28	19.45/20.45/18.30
18 IDEAL	53.65/55.47/52.34	65.89/70.70/63.28	19.21/20.09/18.76
18 FastGAS	56.51/57.81/54.69	<b>66.67</b> /69.92/64.84	<b>20.26</b> /20.65/19.63