

INFINITY AND BEYOND: COMPOSITIONAL ALIGNMENT IN VAR AND DIFFUSION T2I MODELS

Hossein Shahabadi¹ Niki Sepasian¹ Arash Marioriyad¹

Ali Sharifi-Zarchi¹ Mahdih Soleymani Baghshah¹

¹Sharif University of Technology

ABSTRACT

Achieving compositional alignment between textual descriptions and generated images - covering objects, attributes, and spatial relationships - remains a core challenge for modern text-to-image (T2I) models. Although diffusion-based architectures have been widely studied, the compositional behavior of emerging Visual Autoregressive (VAR) models is still largely unexamined. We benchmark six diverse T2I systems - SDXL, PixArt- α , Flux-Dev, Flux-Schnell, Infinity-2B, and Infinity-8B - across the full T2I-CompBench++ and GenEval suites, evaluating alignment in color and attribute binding, spatial relations, numeracy, and complex multi-object prompts. Across both benchmarks, Infinity-8B achieves the strongest overall compositional alignment, while Infinity-2B also matches or exceeds larger diffusion models in several categories, highlighting favorable efficiency-performance trade-offs. In contrast, SDXL and PixArt- α show persistent weaknesses in attribute-sensitive and spatial tasks. These results provide the first systematic comparison of VAR and diffusion approaches to compositional alignment and establish unified baselines for the future development of the T2I model.

1 INTRODUCTION

Recent advances in text-to-image (T2I) generation have enabled models to synthesize highly realistic, semantically rich, and stylistically diverse images at scale (Ramesh et al., 2021; 2022; Saharia et al., 2022; Podell et al., 2023). However, despite their impressive perceptual quality, contemporary T2I models continue to exhibit substantial limitations in compositional alignment, the ability to faithfully bind objects, attributes, and spatial or non-spatial relations described in natural language into coherent visual outputs. A growing body of work demonstrates that strong visual fidelity does not equate to reliable compositional correctness, particularly in multi-object or attribute-heavy prompts, where models frequently violate attribute bindings, confuse spatial configurations, or hallucinate unintended elements (Huang et al., 2025; Ghosh et al., 2023; Chefer et al., 2023).

Although prior work has examined compositionality in diffusion-based T2I models, the compositional alignment abilities of emerging visual autoregressive (VAR) architectures remain largely unexplored (Tian et al., 2024; Han et al., 2025). These models exhibit strong global coherence and semantic richness, yet their capacity to preserve structured multi-entity relationships has not been systematically evaluated. To fill this gap, we assess six modern T2I models - Flux-Dev and Flux-Schnell (Labs, 2024), SDXL, PixArt- α (Chen et al., 2023), Infinity-2B, and Infinity-8B (Han et al., 2025) - using T2I-CompBench++ (Huang et al., 2025) as our primary benchmark, and further validate consistency through the full GenEval (Ghosh et al., 2023) suite.

Across both T2I-CompBench++ and GenEval, Infinity-8B achieves the strongest overall compositional alignment, leading in color, texture, shape, spatial relations, and multi-constraint prompts, while Infinity-2B also surpasses or matches diffusion models in several dimensions despite its smaller scale. Flux-Dev and Flux-Schnell exhibit competitive performance but trail Infinity-8B across most categories, whereas SDXL and PixArt- α consistently underperform, particularly on attribute binding tasks. These results provide a clear quantitative characterization of compositional alignment across diffusion, diffusion-transformer, and VAR-based architectures, establishing Infinity models as strong contenders in T2I generation.

2 BENCHMARK SETUP

2.1 T2I-COMP BENCH++

We adopt T2I-CompBench++ as our primary evaluation suite (Huang et al., 2025). The benchmark covers eight major aspects of text-image compositional alignment: color, texture, and shape binding; non-spatial relations; 2D and 3D spatial relations; counting; and complex multi-attribute compositions. Color, texture, and shape measure attribute binding; non-spatial relations capture interactions such as “holding” or “wearing”; 2D and 3D spatial categories evaluate positional and depth relations; numeracy tests correct object counts; and complex compositions assess multi-attribute, multi-object prompts. For each prompt in the dataset, every model generates a single image, and accuracy is computed using the official evaluation pipeline. These metrics collectively capture a wide spectrum of compositional failures, from incorrect attribute assignment to violations of spatial configurations.

2.2 GEN EVAL

We include GenEval (Ghosh et al., 2023) alongside T2I-CompBench++ because the two benchmarks capture complementary aspects of compositional alignment: T2I-CompBench++ relies on detector-driven verification, whereas GenEval uses rule-based constraints, enabling a more holistic evaluation. To validate our findings under an independent evaluation protocol, we also run all models on the full GenEval benchmark. GenEval provides seven metrics - Overall, Single Object, Two Objects, Counting, Colors, Position, and Color Attributes - covering object presence, attribute correctness, and simple spatial reasoning. Single Object and Two Objects test object presence; Colors and Color Attributes evaluate correct attribute assignment; Position measures simple spatial layout; Counting evaluates numerical correctness; and the Overall score aggregates these metrics into a single alignment measure. Unlike T2I-CompBench++, GenEval relies on prompt-structured rules rather than detector-heavy pipelines, making it a complementary sanity check.

2.3 EVALUATION PROTOCOL

For T2I-CompBench++, we assess each model using four independent random seeds and report seed-averaged results, with full mean and standard deviation values provided in Appendix A. For GenEval, we follow the official protocol by generating four samples per prompt; because GenEval aggregates these into a single metric without exposing sample-level variance, we report only the aggregated scores.

3 TEXT-TO-IMAGE MODELS

As described in Table 1, our evaluation includes six state-of-the-art open models spanning diffusion, diffusion–transformer hybrid, and autoregressive (VAR-based) architectures.

SDXL. Stable Diffusion XL is a diffusion model with a large U-Net backbone and CLIP-based text conditioning (Podell et al., 2023). It is widely used due to its high aesthetic quality, making it an important reference point for assessing compositional behavior.

PixArt- α . PixArt- α is a transformer-based diffusion model for high-resolution image synthesis (Chen et al., 2023). Despite its strong visual quality, prior work notes difficulties in object binding and spatial consistency, motivating its inclusion as a contrasting baseline (Balaji et al., 2022).

Flux-Dev and Flux-Schnell. Flux models are diffusion-based generators that incorporate transformer blocks and efficient attention mechanisms (Labs, 2024). Flux-Dev provides higher-quality outputs, while Flux-Schnell is optimized for speed. Their differing configurations allow us to compare quality–speed trade-offs in compositional tasks.

Infinity-2B and Infinity-8B. Infinity models adopt a bit-wise visual autoregressive paradigm that predicts hierarchical latent codes across scales via a next-scale autoregressive transformer (Han et al., 2025), fundamentally differing from diffusion-based denoising. Infinity-2B and Infinity-8B correspond to mid-sized and large configurations within this framework.

Table 1: Metadata for all T2I models included in our evaluation.

Model	Architecture Type	Release	Parameters	Text Encoder
SDXL	Diffusion (UNet)	2023	3.5B	OpenCLIP ViT-G
PixArt- α	Diffusion (Transformer)	2023	0.6B	T5-XXL
Flux-Dev	DiT	2024	12B	CLIP, Flan-T5-XXL
Flux-Schnell	DiT	2024	12B	CLIP, Flan-T5-XXL
Infinity-2B	VAR	2024	2B	Flan-T5-XL
Infinity-8B	VAR	2025	8B	Flan-T5-XL

4 RESULTS

4.1 T2I-COMP BENCH++

Table 2 summarizes category-wise performance on T2I-CompBench++. Infinity-8B emerges as the strongest model, ranking first in seven of the eight evaluation categories and placing a close second in numeracy. Infinity-2B also performs well, forming a middle tier together with the Flux models and consistently outperforming SDXL and PixArt- α .

Among non-VAR models, Flux-Schnell achieves the most balanced results and secures several second-place rankings, while Flux-Dev attains the highest numeracy score. In contrast, SDXL and PixArt- α show limited compositional alignment, particularly in spatial and complex categories, where they consistently occupy the bottom positions.

Overall, our results suggest that VAR-based models perform competitively with diffusion models within the scope of the compositional benchmarks we evaluate, and that sufficiently scaled autoregressive architectures, as demonstrated by Infinity-8B, achieve leading performance across a broad range of tasks.

Table 2: T2I-CompBench++ compositionality scores (higher is better). Best values in **bold**, second best underlined. Results are averaged over four runs; additional statistics appear in Appendix A.

Model	Color	Texture	Shape	Non-Spatial	2D Spatial	3D Spatial	Numeracy	Complex	Mean
SDXL	0.593	0.519	0.466	0.311	0.215	0.341	0.504	0.319	0.409
PixArt- α	0.407	0.444	0.367	0.308	0.202	0.350	0.506	0.324	0.364
Flux-Dev	<u>0.746</u>	0.644	0.482	0.309	<u>0.273</u>	0.393	0.613	0.363	0.478
Flux-Schnell	0.725	<u>0.683</u>	<u>0.559</u>	<u>0.312</u>	0.271	0.373	0.604	0.364	<u>0.486</u>
Infinity-2B	0.741	0.636	0.480	0.310	0.240	<u>0.406</u>	0.573	<u>0.382</u>	0.471
Infinity-8B	0.827	0.753	0.604	0.316	0.365	0.414	<u>0.612</u>	0.397	0.536

4.2 GENEVAL

GenEval results, shown in Table 3, exhibit the same overall trends observed in T2I-CompBench++. Infinity-8B is the strongest model, achieving the highest Overall score and leading every individual metric. Infinity-2B and Flux-Schnell form a competitive second tier, consistently outperforming SDXL and PixArt- α across most categories. SDXL and PixArt- α again show the weakest compositional alignment, with pronounced errors in positional reasoning and attribute binding.

The consistency between GenEval and T2I-CompBench++ indicates that the performance trends are robust across distinct datasets, despite the benchmarks employing different scoring methodologies.

For additional context, Appendix C compares our results against GenEval scores reported in prior work, including proprietary models (e.g., DALL-E) and test-time optimization methods such as ReNO (Eyring et al., 2024; Ramesh et al., 2021).

4.3 RUNTIME AND MEMORY OBSERVATIONS

Although computational efficiency is not the primary focus of this study, we report a limited set of runtime and memory measurements (see Appendix B) to contextualize the practical behavior of the

Table 3: GenEval scores. Best values in **bold**, second best underlined.

Model	Colors	Color Attr.	Position	Single Obj.	Two Obj.	Counting	Overall
SDXL	<u>0.862</u>	0.210	0.105	0.984	0.664	0.409	0.539
PixArt- α	0.801	0.093	0.068	0.978	0.505	0.438	0.480
Flux-Dev	0.766	0.470	0.185	0.988	0.785	<u>0.716</u>	0.652
Flux-Schnell	0.785	0.505	0.263	1.000	<u>0.894</u>	0.597	0.674
Infinity-2B	0.830	<u>0.590</u>	<u>0.270</u>	0.997	0.798	0.597	<u>0.680</u>
Infinity-8B	0.886	0.765	0.578	1.000	0.937	0.778	0.824

evaluated models. The non-VAR models exhibit substantial variation in efficiency: Flux-Schnell is the fastest, whereas Flux-Dev incurs the highest memory usage and slowest generation times; PixArt- α also displays relatively slow inference despite its moderate parameter count. In contrast, Infinity-2B achieves a favorable efficiency–performance trade-off, requiring considerably less GPU memory than the large diffusion models and generating images faster than all diffusion baselines. Infinity-8B necessitated KV-caching to fit on a single A100 GPU, consistent with prior findings that KV-cache usage affects memory consumption and decoding speed but does not alter model outputs or evaluation performance (Li et al., 2025). As such, its memory profile is not directly comparable to the other models.

5 LIMITATIONS

Our evaluation covers only two benchmarks, and additional datasets or human studies may reveal complementary aspects of compositional behavior. Moreover, runtime and memory assessments are limited to a single hardware setup and all results rely on automatic evaluators, which can be sensitive to prompt ambiguity and may miss nuanced visual semantics.

6 DISCUSSION

Our evaluation reveals clear and consistent patterns in the compositional behavior of contemporary T2I models. Within the VAR family, scale plays a decisive role: Infinity-8B achieves the strongest compositional alignment across both T2I-CompBench++ and GenEval, while the much smaller Infinity-2B remains competitive with strong diffusion baselines. These results indicate that autoregressive architectures, when sufficiently scaled, can deliver robust compositional generation, and that even mid-sized VAR models can rival or surpass considerably larger diffusion models, possibly due to the next-scale autoregressive generation used by VAR models, which explicitly conditions each stage on previously generated visual structure, in contrast to denoising-based generation where global consistency must emerge implicitly over many refinement steps; however, several compositional categories show limited gains with increased scale, indicating that further improvements in these dimensions likely require factors beyond model scaling alone.

In contrast, diffusion and hybrid models exhibit greater variability, with Flux-Schnell and Flux-Dev forming a reliable mid-tier, while SDXL and PixArt- α consistently underperform across most compositional categories. This reinforces that high aesthetic fidelity does not necessarily correlate with accurate multi-object binding, spatial structure, or attribute consistency.

The strong agreement between T2I-CompBench++ and GenEval, despite differing verification methodologies, suggests that the observed trends are stable across evaluation protocols. Both benchmarks identify persistent challenges shared by all models, including spatial reasoning, fine-grained attribute binding, and multi-object scene composition.

Overall, our study provides a unified and systematic comparison of compositional capability across diffusion, hybrid, and visual autoregressive architectures. By establishing consistent baselines and highlighting the roles of scale, training objectives, and model design, we aim to support future work on T2I systems that more reliably encode structured scene information.

REFERENCES

- Yogesh Balaji, Seungjun Nah, Xun Huang, Arash Vahdat, Jiaming Song, Qinsheng Zhang, Karsten Kreis, Miika Aittala, Timo Aila, Samuli Laine, et al. ediff-i: Text-to-image diffusion models with an ensemble of expert denoisers. *arXiv preprint arXiv:2211.01324*, 2022.
- Hila Chefer, Yuval Alaluf, Yael Vinker, Lior Wolf, and Daniel Cohen-Or. Attend-and-excite: Attention-based semantic guidance for text-to-image diffusion models. *ACM transactions on Graphics (TOG)*, 42(4):1–10, 2023.
- Junsong Chen, Jincheng Yu, Chongjian Ge, Lewei Yao, Enze Xie, Yue Wu, Zhongdao Wang, James Kwok, Ping Luo, Huchuan Lu, et al. Pixart- α : Fast training of diffusion transformer for photorealistic text-to-image synthesis. *arXiv preprint arXiv:2310.00426*, 2023.
- Luca Eyring, Shyamgopal Karthik, Karsten Roth, Alexey Dosovitskiy, and Zeynep Akata. Reno: Enhancing one-step text-to-image models through reward-based noise optimization. *Advances in Neural Information Processing Systems*, 37:125487–125519, 2024.
- Dhruba Ghosh, Hannaneh Hajishirzi, and Ludwig Schmidt. Geneval: An object-focused framework for evaluating text-to-image alignment. *Advances in Neural Information Processing Systems*, 36: 52132–52152, 2023.
- Jian Han, Jinlai Liu, Yi Jiang, Bin Yan, Yuqi Zhang, Zehuan Yuan, Bingyue Peng, and Xiaobing Liu. Infinity: Scaling bitwise autoregressive modeling for high-resolution image synthesis. In *Proceedings of the Computer Vision and Pattern Recognition Conference*, pp. 15733–15744, 2025.
- Kaiyi Huang, Chengqi Duan, Kaiyue Sun, Enze Xie, Zhenguo Li, and Xihui Liu. T2i-compbench++: An enhanced and comprehensive benchmark for compositional text-to-image generation. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 2025.
- Black Forest Labs. Flux. <https://github.com/black-forest-labs/flux>, 2024.
- Kunjun Li, Zigeng Chen, Cheng-Yen Yang, and Jenq-Neng Hwang. Memory-efficient visual autoregressive modeling with scale-aware kv cache compression. *arXiv preprint arXiv:2505.19602*, 2025.
- Dustin Podell, Zion English, Kyle Lacey, Andreas Blattmann, Tim Dockhorn, Jonas Müller, Joe Penna, and Robin Rombach. Sdxl: Improving latent diffusion models for high-resolution image synthesis. *arXiv preprint arXiv:2307.01952*, 2023.
- Aditya Ramesh, Mikhail Pavlov, Gabriel Goh, Scott Gray, Chelsea Voss, Alec Radford, Mark Chen, and Ilya Sutskever. Zero-shot text-to-image generation. In *International conference on machine learning*, pp. 8821–8831. Pmlr, 2021.
- Aditya Ramesh, Prafulla Dhariwal, Alex Nichol, Casey Chu, and Mark Chen. Hierarchical text-conditional image generation with clip latents. *arXiv preprint arXiv:2204.06125*, 1(2):3, 2022.
- Chitwan Saharia, William Chan, Saurabh Saxena, Lala Li, Jay Whang, Emily L Denton, Kamyar Ghasemipour, Raphael Gontijo Lopes, Burcu Karagol Ayan, Tim Salimans, et al. Photorealistic text-to-image diffusion models with deep language understanding. *Advances in neural information processing systems*, 35:36479–36494, 2022.
- Keyu Tian, Yi Jiang, Zehuan Yuan, Bingyue Peng, and Liwei Wang. Visual autoregressive modeling: Scalable image generation via next-scale prediction. *Advances in neural information processing systems*, 37:84839–84865, 2024.

A ADDITIONAL VARIANCE MEASUREMENTS

The following tables report the mean and standard deviation across four seeds for all T2I-CompBench++ categories. The main paper reports only mean values for readability.

Table 4: T2I-CompBench++ mean \pm std for basic attribute categories.

Model	Color	Texture	Shape	Non-Spatial
SDXL	0.593 \pm 0.031	0.519 \pm 0.013	0.466 \pm 0.020	0.311 \pm 0.002
PixArt- α	0.407 \pm 0.028	0.444 \pm 0.014	0.367 \pm 0.012	0.308 \pm 0.001
Flux-Dev	0.746 \pm 0.020	0.644 \pm 0.016	0.482 \pm 0.013	0.309 \pm 0.000
Flux-Schnell	0.725 \pm 0.042	0.683 \pm 0.027	0.559 \pm 0.014	0.312 \pm 0.002
Infinity-2B	0.741 \pm 0.007	0.636 \pm 0.009	0.480 \pm 0.007	0.310 \pm 0.001
Infinity-8B	0.827 \pm 0.003	0.753 \pm 0.002	0.604 \pm 0.004	0.316 \pm 0.001

Table 5: T2I-CompBench++ mean \pm std for spatial and composition categories.

Model	2D Spatial	3D Spatial	Numeracy	Complex
SDXL	0.215 \pm 0.012	0.341 \pm 0.007	0.504 \pm 0.017	0.319 \pm 0.005
PixArt- α	0.202 \pm 0.012	0.350 \pm 0.005	0.506 \pm 0.008	0.324 \pm 0.003
Flux-Dev	0.273 \pm 0.007	0.393 \pm 0.015	0.613 \pm 0.024	0.363 \pm 0.001
Flux-Schnell	0.271 \pm 0.016	0.373 \pm 0.019	0.604 \pm 0.008	0.364 \pm 0.012
Infinity-2B	0.240 \pm 0.008	0.406 \pm 0.003	0.573 \pm 0.007	0.382 \pm 0.003
Infinity-8B	0.365 \pm 0.010	0.414 \pm 0.008	0.612 \pm 0.006	0.397 \pm 0.002

B RUNTIME AND MEMORY MEASUREMENTS

Table 6 reports runtime and memory measurements collected using 50 randomly selected prompts from T2I-CompBench++, with all models evaluated on the same prompt set for comparability. Reported memory values correspond to PyTorch’s *allocated* CUDA memory, which reflects model-controlled GPU usage. System-level tools such as `nvidia-smi` may show higher totals due to additional runtime and driver allocations. All models were measured using the same procedure for consistency.

Table 6: Runtime and memory measurements averaged over 50 prompts.

Model	Load Mem. (GB)	Peak Mem. (GB)	Avg. Time (s)
SDXL	6.58	10.47	4.08
PixArt- α	12.07	14.46	5.82
Flux-Dev	33.32	35.71	9.86
Flux-Schnell	33.29	35.68	2.74
Infinity-2B	7.37	15.75	2.13
Infinity-8B	–	–	–

C EXTENDED GEN EVAL COMPARISON WITH PRIOR WORK

To place our results in the context of prior large-scale and proprietary text-to-image systems, we additionally report GenEval scores for a range of models from the literature, including ReNO-enhanced diffusion models and proprietary systems such as DALL·E. All scores in Table 7 are taken from the corresponding papers and were not re-evaluated by us. Scores reported below the midrule are intended as reference points from prior work rather than strictly controlled comparisons, as they may differ in prompt sets, inference settings, and evaluation protocols.

This extended comparison highlights two complementary trends. First, test-time optimization methods such as ReNO can substantially improve the compositional alignment of diffusion-based models,

with particularly large gains in counting and attribute-sensitive categories (e.g., SDXL-Turbo, HyperSDXL, and FLUX-Schnell). Second, despite the absence of any test-time optimization, the base Infinity-8B model achieves comparable or stronger performance across most GenEval categories. This suggests that architectural design and model scale play a substantial role in compositional alignment, even without inference-time optimization.

We report prior Flux-Schnell results as published and do not attempt to reconcile numerical differences with our own evaluation, as these differences likely arise from variations in inference settings and evaluation protocols.

Table 7: Extended GenEval scores from prior work. Rows highlighted in gray correspond to models using test-time optimization (e.g., ReNO). Models above the first midrule are evaluated in this work; models below are reported from external sources. Best values per column are shown in **bold**.

Model	Colors	Color Attr.	Position	Single Obj.	Two Obj.	Counting	Overall
SDXL	0.862	0.210	0.105	0.984	0.664	0.409	0.539
PixArt- α	0.801	0.093	0.068	0.978	0.505	0.438	0.480
Flux-Dev	0.766	0.470	0.185	0.988	0.785	0.716	0.652
Flux-Schnell	0.785	0.505	0.263	1.000	0.894	0.597	0.674
Infinity-2B	0.830	0.590	0.270	0.997	0.798	0.597	0.680
Infinity-8B	0.886	0.765	0.578	1.000	0.937	0.778	0.824
DALL-E 2	0.770	0.190	0.100	0.940	0.660	0.490	0.520
DALL-E 3	0.830	0.450	0.430	0.960	0.870	0.470	0.670
SDXL-Turbo	0.840	0.200	0.090	1.000	0.660	0.450	0.540
+ ReNO	0.900	0.350	0.130	1.000	0.840	0.680	0.650
HyperSDXL	0.870	0.210	0.100	1.000	0.760	0.430	0.560
+ ReNO	0.910	0.330	0.170	1.000	0.900	0.560	0.650
Flux-Schnell	0.780	0.430	0.180	0.980	0.800	0.640	0.640
+ ReNO	0.870	0.560	0.210	0.990	0.900	0.790	0.720