

LV-EVAL: A BALANCED LONG-CONTEXT BENCHMARK WITH 5 LENGTH LEVELS UP TO 256K

Anonymous authors

Paper under double-blind review

ABSTRACT

State-of-the-art large language models (LLMs) are now claiming remarkable supported context lengths of $256k$ or even more. In contrast, the average context lengths of mainstream benchmarks are insufficient ($5k$ - $21k$), and they suffer from potential knowledge leakage and inaccurate metrics, resulting in biased evaluation. This paper introduces *LV-Eval*, a challenging long-context benchmark with five length levels ($16k$, $32k$, $64k$, $128k$, and $256k$) reaching up to $256k$ words. *LV-Eval* features two main tasks, single-hop QA and multi-hop QA, comprising 11 bilingual datasets. The design of *LV-Eval* has incorporated three key techniques, namely confusing facts insertion (CFI), keyword and phrase replacement (KPR), and keyword-recall-based metric design. The advantages of *LV-Eval* include controllable evaluation across context lengths, challenging test instances with confusing facts, mitigated knowledge leakage, and more objective evaluation. We evaluate 15 LLMs on *LV-Eval* and conduct ablation studies on the benchmarking techniques. The results reveal that: (i) Moonshot-v1 and recent large-scale open-source models, such as Qwen-2.5-72B and Llama-3.1-70B, achieve the highest performance on *LV-Eval*, particularly at lengths below $64k$. (ii) Models exhibit distinct score trends. For example, GLM-4-9B-128k, Yi-6B-200k, and Llama3-8B-1M exhibit a relatively gentle degradation of performance, but their absolute performances may not necessarily be higher than those of LLMs with shorter context lengths. (iii) LLMs’ performances can significantly degrade in the presence of confusing information, especially in the pressure test of “needle in a haystack”. (iv) Issues related to knowledge leakage and inaccurate metrics introduce bias in evaluation, and these concerns are alleviated in *LV-Eval*.

1 INTRODUCTION

Large language models (LLMs) have demonstrated exceptional performance on a variety of natural language processing tasks. The ability of long-context understanding is crucial for LLMs to deal with tasks based on longer contexts, such as books, lengthy chat history, and so on. Recently, extensive efforts have been devoted in enlarging the supported context length (i.e., the number of tokens that the model can accept as input) of LLMs. These efforts have pushed the supported context length of LLMs from $2k$ tokens to $32k$ tokens (Touvron et al., 2023; Zheng et al., 2023; Bai et al., 2023a; Zeng et al., 2022; Li et al., 2023a), and some models have achieved a remarkable context length of $128k$ and $200k$ (Peng et al., 2023a; Achiam et al., 2023; Yi, 2023).

In contrast to the rapid evolution of the models’ supported context length, existing benchmarks have lagged behind. The average word count in current long-context benchmarks typically falls within the range of $32k$ (Bai et al., 2023b; Li et al., 2023b; An et al., 2023; Shaham et al., 2023; Dong et al., 2023), considerably shorter compared to the supported context lengths of state-of-the-art long-context models. Moreover, previous benchmarks primarily consist of *unaltered* public documents and articles. This could be problematic for two reasons: (i) the data might be involved in LLMs’ training processes, and (ii) the facts within them might be common-sense facts found in other training resources. The presence of this issue, known as “knowledge leakage” (Zhou et al., 2023a), can lead to models answering questions with memorization or common-sense knowledge instead of understanding long-range contexts. Last but not least, the automatic metrics employed in most of the existing benchmarks are susceptible to the variations in answer format and the inclusion of irrelevant words. Such metrics struggle to accurately assess the answer quality.

Benchmark	#Datasets	Avg #Words	Min/Max Words	Length Levels	Opt. Metric	Lang.
ZeroSCROLLS Shaham et al. (2023)	10	13,556	1,023/320,774	none		en
LooGLE Li et al. (2023b)	7	21,247	10,927/246,182	none		en
L-Eval An et al. (2023)	20	12,993	2,119/170,256	none	✓	en
BAMBOO Dong et al. (2023)	10	5,067	229/14,858	4k,16k		en+zh
LongBench Bai et al. (2023b)	21	9,486	128/71,954	0-4k,4k-8k,8k+		en+zh
<i>LV-Eval</i>	11	102,380	11,896/387,406	16k,32k,64k,128k,256k	✓	en+zh

Table 1: Comparison of different long-context benchmarks. We count the number of words for the English datasets and the number of characters for the Chinese datasets. The punctuation marks are taken into account, while tabs, blank spaces, and newlines are not included.

To address these issues, we propose *LV-Eval*, a bilingual benchmark with up to 256k words. *LV-Eval* incorporates distractions and confusions to make the test more challenging, replaces keywords and rephrases sentences to prevent knowledge leakage, and employs a more accurate metric. We summarize the key characteristics of *LV-Eval* as follows:

- **Sufficiently long context length to evaluate state-of-the-art models:** *LV-Eval* comprises 5 length levels with word counts of 16k, 32k, 64k, 128k, and 256k. Test instances across these levels share the same set of question-answer (QA) pairs, and only differ in the context content and length. Testing on the same QA pairs with different context lengths facilitates a controllable evaluation of models’ long-context ability.
- **Incorporation of distraction and confusion to increase difficulty:** When constructing the context for each test instance, we mix up distracting documents and supporting documents. This approach evaluates the model’s ability in pinpointing key information in a large bunch of distracting texts. In addition, we insert confusing facts generated by GPT-4 and revised by human annotators into the context. This assesses the model’s capability to accurately reason in the presence of interference.
- **Keyword and phrase replacement to mitigate knowledge leakage:** To mitigate the biased evaluation of long-context ability caused by knowledge leakage, we replace the keywords and phrases in the context and QA pairs. The replacement rules are annotated by human annotators. In this way, *LV-Eval* requires LLMs to rely on the understanding of context to answer questions rather than relying on memorization or common-sense knowledge.
- **Keyword-recall-based metric for more objective scoring:** Existing *N*-gram metrics such as the F1 score are sensitive to the format variations and non-informative words in the answer, which results in inaccurate scores. To address this, we manually annotate answer keywords and a blacklist of unrelated words. The golden answers are the critical words or sentences extracted from original ground-truth (GT) answers, while the word blacklist contains common and non-informative words such as ‘the’, ‘a’, ‘of’, and so on. The metric calculation follows a two-stage procedure: the first stage calculates the recall of golden answer keywords. if the recall exceeds a certain threshold, the second stage will remove all the blacklisted words and then calculate the F1 score between the prediction and the GT answer. This metric design can get scores with higher objectivity.

Findings. We evaluate 15 LLMs on *LV-Eval* and summarize the main findings as follows: (i) Moonshot-v1 and recent large-scale open-source models, such as Qwen-2.5-72B and Llama-3.1-70B, achieve the highest performance on *LV-Eval*, particularly at lengths below 64k. (ii) Models exhibit distinct score trends. For example, GLM-4-9B-128k, Yi-6B-200k, and Llama3-8B-1M exhibit a relatively gentle degradation of performance, but their absolute performances may not necessarily be higher than those of LLMs with shorter context lengths. (iii) LLMs’ performances can significantly degrade in the presence of confusing information, especially in the pressure test of “needle in a haystack”. (iv) Issues related to knowledge leakage and inaccurate metrics introduce bias in evaluation, and these concerns are alleviated in *LV-Eval*.

2 RELATED WORK

Long-Context Benchmarks. Table 1 provides a summary of existing long-context benchmarks, including ZeroScrolls (Shaham et al., 2023), LooGLE (Li et al., 2023b), L-Eval (An et al., 2023),

Task	Dataset	CFI	#KPR	AK	Language	#QA pairs	#Contexts
Single-hop QA	lic-mixup	✓		✓	zh	197	985
	loogle-SD-mixup			✓	en	160	800
	cmrc-mixup		786		zh	200	1,000
	multifieldqa-en-mixup	✓	476	✓	en	101	505
	multifieldqa-zh-mixup	✓	424	✓	zh	133	665
	factrecall-en	✓	3	✓	en	1	200×5
	factrecall-zh	✓	3	✓	zh	1	200×5
Multi-hop QA	dureader-mixup				zh	176	880
	loogle-CR-mixup			✓	en	99	495
	loogle-MR-mixup			✓	en	139	695
	hotpotwikiqa-mixup	✓	232	✓	en	124	620

Table 2: Data statistics of *LV-Eval*. The abbreviations “CFI”, “KPR”, “AK” stand for “Confusing Fact Insertion”, “Keyword and Phrase Replacement”, and “Answer Keywords”, respectively. “#KPR” is the number of KPR rules. Note that in **factrecall-en** and **factrecall-zh**, all QA pairs are the same across all test instances, i.e., there is only one unique QA pair for each of the two datasets.

BAMBOO (Dong et al., 2023), and LongBench (Bai et al., 2023b). ZeroScrolls, LooGLE, and L-Eval are monolingual benchmarks without explicit length level partition. Their average word counts are $\sim 14k$, $\sim 21k$ and $\sim 13.5k$, respectively. In order to evaluate the model’s capability across various context lengths, BAMBOO and LongBench have designed various length levels. However, the word counts ($\sim 5k$, $\sim 9.5k$) of the contexts in these two benchmarks are notably smaller than the supported context length of state-of-the-art long-context models, making them unsuitable for evaluating the claimed extremely long-context understanding ability. In contrast, *LV-Eval* contains five length levels, up to $256k$ words, each with the same set of QA pairs for controllable evaluation.

In terms of metric design, L-Eval introduces a length-instruction-enhanced metric to mitigate the undesired impact of the answer length on metric scores. Additionally, L-Eval proposes to use LLMs to assist in scoring. In *LV-Eval*, we ask human annotators to mark the answer keywords and create a non-informative word blacklist, and propose a two-stage metric to focus more on the answer keywords while reducing the influences of non-informative words.

The “needle in a haystack” (NIAH) task (Kamradt, 2023) has been very popular in assessing the long-context retrieval ability of LLMs. A recent benchmark, RULER (Hsieh et al., 2024), identifies the necessity of extending the NIAH task. It extends NIAH with diverse types and quantities of needles and distracting information. In our work, *LV-Eval* also includes an extended version of the NIAH task with our confusing fact insertion and keyword-and-phrase replacement techniques.

Long-Context Techniques. Considerable efforts have been devoted to enhancing the long-context abilities of LLMs. One line of work focuses on making LLMs have extended context sizes without fine-tuning and behave normally on inputs longer than their training context lengths. The design and extrapolation method of the position encoding module (Su et al., 2024; Press et al., 2021; bloc97, 2023) is crucial for this goal. Besides, several sparse attention techniques (Han et al., 2023; Xiao et al., 2023) have also been proposed to avoid model collapse. These sparse attention techniques also alleviate the quadratic complexity w.r.t. the sequence length.

There are many other strategies aimed at enabling LLMs to effectively leverage long input contexts. The most commonly utilized strategy is long-context fine-tuning (Xiong et al., 2023; Li et al., 2023a; Peng et al., 2023b). For instance, YaRN (Peng et al., 2023b) conducts fine-tuning with $64k$ and $128k$ context lengths starting with Llama2-7B/13B, and Yi-6B-200k (Yi, 2023) is trained with $200k$ context length starting with its $4k$ variant. Other strategies include the recurrent- or memory-based architecture (Dai et al., 2019; Wu et al., 2021; Martins et al., 2022; Zhou et al., 2023b; Liang et al., 2023), and the retrieval- or summarization-based context compression techniques (Khandelwal et al., 2019; Borgeaud et al., 2022; Bai et al., 2023b; Zhou et al., 2023b), and so on.

In this work, we evaluate LLMs of diverse context sizes, ranging from $4k$ to $200k$, most of which have incorporated advanced position encoding design and undergone long-context fine-tuning.




Figure 1: The construction process of *LV-Eval*. “CF” is short for “Confusing Fact”.

3 LV-EVAL BENCHMARK

LV-Eval focuses on two types of QA tasks: single-hop QA and multi-hop QA, and is comprised of 11 QA datasets (6 in English and 5 in Chinese). The data statistics for *LV-Eval* are outlined in Table 2. Each test instance in *LV-Eval* comprises three parts: a context (C), a question (Q), and a GT answer (A), where C is a synthetic document containing the information required to answer Q .


Datasets in *LV-Eval* are constructed with existing public datasets as the source, except for *factrecall-en* and *factrecall-zh*, which are constructed using the data from *PG19* (Rae et al., 2019) dataset and *Journey to the West* book. Each dataset consists of five subsets of different lengths: 16k, 32k, 64k, 128k, and 256k. All five subsets share the same question-answer (QA) pairs, meaning there are five contexts of varying lengths for each QA pair. This allows for a controllable evaluation of models’ long-context ability when testing the same set of questions with different context lengths. In total, *LV-Eval* comprises 1,729 QA pairs and $1,729 \times 5 = 8,645$ synthetic contexts.

Figure 1 illustrates the construction process of *LV-Eval*. For *factrecall-en* and *factrecall-zh*, we write one QA pair for each dataset. For the rest 9 out of the 11 datasets, we first choose a specific number of QA pairs from existing QA datasets (Section 3.1). Then, for each unique QA pair, we go through three procedures to construct the context (Section 3.2):

1. **Context mixing up** (Section 3.2.1): We first construct five contexts of different lengths by mixing up supporting documents corresponding to the QA pair and several distracting documents. For *factrecall-en* and *factrecall-zh*, we mix the supporting evidence of the single QA pair with distracting documents from two books. For other datasets, the distracting documents are unrelated to the question and are chosen from the context documents corresponding to non-selected QA pairs in the same source dataset.
2. **Confusing Facts Insertion (CFI)** (Section 3.2.2): Then, in some datasets, we introduce confusing facts by generating them with GPT-4, manually revising them, and randomly inserting these into the context. These confusing facts bear similarities to the original supporting facts but are factually different, without contradicting the original information. This helps make the test instances more challenging.
3. **Keyword and Phrase Replacement (KPR)** (Section 3.2.3): Finally, to reduce the impacts of knowledge leakage on evaluation results, we manually replace some keywords and phrases in the context and the QA pairs.

When evaluating the generated answer, to mitigate the bias in existing metrics, we manually annotate the keywords in the GT answer and adjust the metric to focus more on the keywords (Section 3.3).

During the benchmark construction, we employ and guide five human annotators to revise the confusing facts, replace the keywords and phrases, and annotate the keywords in GT answers. These human annotators include three master students involved in LLM research and two master students majored in linguistics. The details of our annotation process are introduced in Appendix C.



233 Figure 2: Steps for CFI. Firstly, we prompt GPT-4 to generate two descriptions that are close to
234 the original fact. Then we ask human annotators to resolve any conflicts in the generated facts.
235 For example, the first generated confusing fact “Albert Einstein was an Italian astronomer” is in
236 conflict with the original fact and the human annotator revise it to “Albert Beverley was an Italian
237 astronomer”. Finally, the confusing facts are inserted into a randomly position in the context.

239 3.1 DATA SOURCE AND QA PAIR CONSTRUCTION

241 We construct 11 datasets (see Table 2) using public data sources, including
242 Long-instruction-en2zh (yuyijiong, 2023), HotpotQA (Yang et al., 2018), 2Wiki-
243 MultiHopQA (Ho et al., 2020), DuReader (Tang et al., 2020), LooGLE (Li et al., 2023b),
244 LongBench (Bai et al., 2023b), CMRC 2018 (Cui et al., 2018), MultiFieldQA (Bai et al., 2023b),
245 PG-19 (Rae et al., 2019) and the book of *Journey to the West*. The construction of QA pairs in each
246 dataset is elaborated in Appendix B.

248 3.2 CONTEXT CONSTRUCTION

249 3.2.1 CONTEXT MIXING UP

251 Can the LLMs identify the key evidences to answer the target question within a long context? To
252 assess this ability, as shown in Figure 1, LV-Eval randomly mixes the supporting documents with
253 various distracting documents to generate five contexts of varying length for a given QA pair. For
254 9 out of the 11 datasets (excluding **factrecall-en** and **factrecall-zh**), the distracting documents are
255 chosen from the contexts corresponding to the non-selected QA pairs in the source dataset. For
256 **factrecall-en** and **factrecall-zh**, the distracting documents are extracted from the *PG-19* dataset and
257 the book of *Journey to the West*.

258 For each length level, we sample distracting documents one by one until the cumulative word count
259 meets the desired length level. Then, we shuffle the supporting and distracting documents, prepend
260 a string “`Passage i\n`” to the i -th document, and concatenate them to form the final context.

261 Note that in **hotpotwikiqa-mixup** and **dureader-mixup**, where multiple supporting documents exist
262 for each QA pair, instead of regarding the multiple supporting documents a single unit, we dis-
263 perse and shuffle all supporting and distracting documents.

266 3.2.2 CONFUSING FACTS INSERTION

267 Can the LLMs identify the key evidences correctly if there are confusing facts in the context?
268 To assess this ability, we apply CFI in **hotpotwikiqa-mixup**, **lic-mixup**, **multifieldqa-en-mixup**,
269 **multifieldqa-zh-mixup**, **factrecall-en**, and **factrecall-zh**, which inserts similar, factually different,




Figure 3: Steps for KPR. First, given a QA pair, the annotators are asked to select keywords or phrases to replace and write a substitute for each. Then, the selected keywords and phrases are replaced throughout the context and QA pair. Finally, annotators will check the modified context. If there is any conflict, the annotators are asked to revise the replacement rule until all conflicts are resolved.

non-contradictory facts into the context. These facts might mislead less meticulous models, leading them to generate incorrect answers.

The generation process of the confusing facts goes as follows. Firstly, we use the question and answer as the input, and prompt GPT-4 (Achiam et al., 2023) to generate two descriptions that are close to the original fact. The prompt for GPT-4 is shown in Figure A7. Then, we ask human annotators to resolve any conflicts in the generated facts. As illustrated in Figure 2, the generated confusing fact “Albert Einstein was an Italian astronomer” is in conflict with the original fact. Therefore, the human annotator revise it to “Albert Beverley was an Italian astronomer”. After this generation and revising process, we insert the confusing facts into a randomly picked position between two sentences in the context.

3.2.3 KEYWORD AND PHRASE REPLACEMENT

Knowledge leakage is an important concern in LLM evaluation (Zhou et al., 2023a). On the one hand, the test data are usually collected from open-access sources, and we cannot fully rule out the possibility of their being involved in some LLMs’ training process. On the other hand, some common-sense questions can be answered without referencing the provided context. Consequently, LLMs might rely on memorization and common-sense knowledge to answer the questions rather than fully understanding the context. This will cause inflated benchmark scores to overrate the long-context ability of models.

To mitigate the influences of knowledge leakage on the evaluation results, we conduct KPR according to manually crafted rules in **hotpotwikiqa-mixup**, **cmrc-mixup**, **multifieldqa-en-mixup**, **multifieldqa-zh-mixup**, **factrecall-en**, and **factrecall-zh**. Specifically, given a QA pair, the annotators are asked to select keywords or phrases for replacement and write a substitute for each. After the selected keywords and phrases are replaced throughout the entire context, the annotators review the modified context to check and resolve any conflicts: If there are conflicts, the annotators are asked to revise the replacement rule until all conflicts are resolved. One example of the KPR process is shown in Figure 3. See Table 2 for the statistics of the number of replacement rules.

3.3 METRIC DESIGN

The quality evaluation of natural language generation is challenging. Current N -gram metrics, such as the F1 score, treat all words equally. The neglect of differences in word importance leads to evaluation bias. For example, in the sentence “Attention is all you need”, the word “attention”

carries the key information and is more important. However, the answer “Attention matters” will get a lower score than the answer “CNN is all you need”, which is not what we expected. To this end, we adopt a two-stage metric calculation process.

Specifically, to evaluate an answer A' , we first calculate the recall of several “answer keywords” in A' . When the recall exceeds a certain threshold (0.2 for Chinese dataset, 0.4 for English datasets), we calculate the F1 score between A' and GT answer A as the final score for A' . otherwise, A' gets a zero score. We manually annotate the answer keywords in the GT answer A for **hotpotwikiqa-mixup**, **lic-mixup**, **loogle-CR-mixup**, **loogle-MR-mixup**, **loogle-SD-mixup**, **multifieldqa-en-mixup**, and **multifieldqa-zh-mixup**. Figure A6 (a) shows an example, demonstrating how this two-stage calculation helps avoid some inflated high evaluation scores.

When calculating the F1 score between A' and A in the second stage, we exclude common but non-informative words like ‘the,’ ‘a,’ ‘of’, and so on. The word blacklist is constructed as follows. We first summarized the word counts in the generations of Llama2-7B-Chat-hf and ChatGLM3-6B-32K on all datasets and chose the top 100 words that matched the GT answer most frequently. Then, we manually annotate the non-informative words from the 100 words to construct the blacklist. Figure A6 (b) shows an example of how the word blacklist aids in calibrating the evaluation scores.

4 EVALUATION

Models and Inference. We evaluate 3 commercial and 12 open-source LLMs on *LV-Eval*. Their information is summarized in Table A5. We follow the official implementation of all LLMs to conduct their inferences. Greedy sampling is used for generating tokens. For LLMs with a context window size smaller than the length of the data context, we truncate the data context in the middle, and concatenate the head and the tail of the context as input, ensuring that the QA instructions are fully contained within the input.

Metrics. For all tasks except **dureader-mixup** and **cmrc-mixup**, we evaluate the generated answers with our keyword-recall-based F1 metric, utilizing the annotated answer keywords and word blacklist. For **cmrc-mixup**, we omit the manual annotation of answer keywords since the answers in this dataset is already concise. Therefore, we use the F1 metric with word blacklist. In the case of **dureader-mixup**, where the GT answer lengths are relatively long, we do not manually annotate the answer keywords and use the ROUGH-L metric with the word blacklist.

4.1 COMPARE LLMs ON *LV-EVAL*

Figure 4 (a) shows the average scores across all 11 datasets of 15 LLMs at different length levels. We can see that (i) The commercial Moonshot-v1 and recent large-scale open-source models (Qwen2.5-72B, Llama-3.1-70B) achieve the best performances. Notably, both Qwen2.5-72B and Moonshot-v1 obtain average scores exceeding 40 at $16k$ and $32k$ lengths. (ii) Among open-source models with parameter sizes in the 6-9B range, GLM-4-9B achieves the best performance, even outperforming Llama-3.1-70B on longer lengths ($128k$, $256k$). (iii) Models exhibit distinct score trends, resulting in different relative rankings across different length levels. For example, the model with the largest context window size, Llama3-8B-1M, exhibits one of the slowest decline of performance from $16k$ to $128k$. Specifically, its scores at the length level $16k$ is lower than ChatGLM3-6B-32k and BlueLM-7B-32k-Chat. Nevertheless, as the length of input context increases, Llama3-8B-1M retains a higher score than these two models that need to truncate the input context. The similar phenomenon can be observed between Yi-6B-200k and two GPTs, as well as between GLM-4-9B and Llama-3.1-70B. (iv) Models exhibit a sharp performance drop, often occurring prior to or when the context length exceeds their supported context length. Some models experience a sharp decline in performance once the context length exceeds their supported context length. For instance, Qwen2.5-72B-128k, GLM-4-9B-128k, and ChatGLM3-6B-32k exhibit a sharp performance drop after $128k$, $128k$, and $32k$, respectively. In contrast, some other models encounter this sharp performance drop earlier. For instance, Llama-3.1-70B-128k exhibit a sharp performance drop after $64k$, despite its stated support for $128k$ context.

Figure 4 (b) shows the average scores across all 5 length levels on 5 task types. We can see that (i) LLMs attain lower scores on multi-hop QA tasks compared to single-hop QA tasks. (ii) Confusing




Figure 4: Overall results on different length levels and types of datasets. (a) Average scores across all datasets of 15 LLMs at 5 length levels. The circle markers represent open-source models of 6-9B; The square markers represent larger open-source models around 70B; The triangle markers represent commercial APIs. Note that we only evaluate Moonshot-v1-128k on 16k and 32k length levels due to the high cost. (b) Average scores across all length levels of 14 LLMs on 5 types of datasets. “CQA” refers to QA datasets with CFI.

facts insertion adds complexity to the tasks, particularly evident in single-hop QA and single-hop confusion QA. See Appendix D for more detailed results and Appendix G for example failure cases.

4.2 ABLATION STUDY OF LV-EVAL TECHNIQUES

Confusing facts insertion. Table A8, A9, and A10 show the scores of multiple LLMs on dataset with and without CFI. We can see that (i) On **multifieldqa-en-mixup** and **multifieldqa-zh-mixup**, CFI leads to a notable degradation in the scores of LLMs. However, CFI in the **hotpotwikiqa-mixup** dataset does not result in severe degradation. (ii) Table A9 and A10 show that a strong model, ChatGLM3-6B-32k, exhibits the most substantial score degradation on data with CFI. For instance, the score of ChatGLM3-6B-32k degrades from 41.46 to 31.97 (a degradation of 9.49) on the 16k length level of **multifieldqa-en-mixup**, while the score degradation of other 5 LLMs falls within the range [0.47, 4.89]. This observation suggests that current powerful LLMs may even be more susceptible to confusing information in the context. Future research is needed to enhance the models’ ability to discern information that appears similar but is in fact unrelated. (iii) As the length of the input context increases, the score degradation becomes smaller. This phenomenon can be attributed to two factors: the truncation of confusing facts and a decrease in baseline performance.

Keyword and phrase replacement. The technique of KPR aims to eliminate the knowledge leakage and common-sense memorization of LLMs. Intuitively, for datasets sourced from Wikipedia and other widely used corpus, the risk of knowledge leakage is higher. From the results in Table A8, A9, and A10, we observe that: (i) KPR brings notable degradation of LLM scores on these three datasets suggesting that knowledge leakage exists in open-source corpus and can be mitigated by KPR. (ii) The extent of degradation is relatively consistent across different length levels.

We illustrate the knowledge leakage issue and the impact of KPR in Table 3. Specifically, we compare three settings: (i) Directly querying the LLMs to answer the question without the context (“direct (w.o. KPR)”). (ii) Applying KPR to the QA pair, and directly querying the LLMs without the context (“direct (w. KPR)”). (iii) Applying KPR to the QA pair and the context, and querying the LLMs to answer the question with the context (“w. context (w. KPR)”).

Table 3 shows that without KPR, some LLMs can achieve a considerable score even without context. For instance, Yi-6B-200k and ChatGLM3-6B-32k achieve scores of 16.11 and 12.24, respectively, through memorization or common-sense knowledge. Applying KPR decreases the score without

Model Name	Ablation	hotpotwikiqa-mixup				
		16k	32k	64k	128k	256k
Llama2-7B-Chat-hf	direct (w. KPR)			2.43		
	direct (w.o. KPR)			3.52		
	w. context (w. KPR)	3.99	1.30	1.84	0.81	0.75
ChatGLM3-6B-32k	direct (w. KPR)			4.96		
	direct (w.o. KPR)			12.24		
	w. context (w. KPR)	16.98	14.76	9.02	8.31	6.68
Yi-6B-200k	direct (w. KPR)			6.06		
	direct (w.o. KPR)			16.11		
	w. context (w. KPR)	23.55	18.94	9.94	7.66	2.01

Table 3: Ablation results for KPR. “direct (w. KPR)”: Apply KPR and direct query without context; “direct (w.o. KPR)”: Direct query without context; “w. context (w. KPR)”: Apply KPR and query with context. Note that there is only one result in the first two rows in each section of the table, since the results of direct querying without context do NOT depend on the context length.

context (6.06 for Yi-6B-200k and 4.96 for ChatGLM3-6B-32k). This helps mitigate the influence of memorization or common-sense knowledge on the assessment of long-context understanding ability.

Case study on the fact-recall tasks. The **factrecall-en** and **factrecall-zh** datasets are constructed to evaluate the enhanced NIAH (Kamradt, 2023) ability. The traditional NIAH evaluation is basically a retrieval task, asking LLMs to find the answer or passkey in long context, which is too simple for majority of LLMs that they can easily get high scores after task oriented training. Therefore we enhance the NIAH evaluation with CFI and KPR to assess LLM’s positional consistency of retrieval while challenging their comprehension and anti-interference ability.

We show the ablation results of CFI and KPR in Figure 5 and Table A11. From the first column in Figure 5, we can see that ChatGLM3-6B-32k attains high accuracy on datasets without CFI and KPR, as long as the input context length is within its context size (32k). However, when either CFI (second column of sub-figure) or KPR (third column sub-figure) is applied, the retrieval accuracy decreases. The accuracy experiences a more severe degradation when both CFI and KPR are applied, particularly evident in **factrecall-zh**, where a performance collapse is observed (See Appendix G for an example failure case). This indicates that there is room for improvement in the model’s ability to accurately identify a specific piece of information from a long context in the presence of interference.

Keyword-recall-based metric. For a given length level L_d of the dataset, if the single key information is uniformly distributed in the context, an LLM with a context window size L_m can only observe the key information for approximately $\frac{L_m}{L_d}$ of the time. Thanks to our KPR technique, we can reasonably expect that the LLM cannot get the correct answer through memorization or common-sense knowledge. Furthermore, in our free-form QA tasks, unlike in multiple-choice settings, the LLM cannot easily guess the correct answer. Therefore, we would not expect to see a metric score much higher than $\frac{L_m}{L_d}$. In other words, $\frac{L_m}{L_d}$ is the ideal score assuming that all answers are correctly extracted from and only from the context, and the metric accurately measures the answer correctness.

However, as shown in Table 4, when using the original F1 metric, the metric score can be significantly higher than $\frac{L_m}{L_d}$ due to the undesired matching of non-keywords and non-informative words. For example, ChatGLM3-6B-32k achieves a score of 26.43% on the 256k length level of the **cmrc-mixup** dataset, which greatly exceeds $\frac{L_m}{L_d} = 12.5\%$. In contrast, our keyword-recall-based metric with the word blacklist is a more meaningful metric, as its scores are more aligned with our expectations (i.e., smaller than $\frac{L_m}{L_d}$).




Figure 5: Ablation results of the “needle in a haystack” task on ChatGLM3-6B-32k. (a) **factrecall-en**. (b) **factrecall-zh**. In each of (a)(b), from left to right, the four sub-figures show the results of w.o. “CFI and KPR”, “w. CFI only”, “w. KPR only”, and “w. both CFI and KPR”, respectively. These results illustrate that CFI and KPR are effective in improving the task difficulty.

Metric	16k	32k	64k	128k	256k
reference $\frac{L_m}{L_d}$	100	100	50.00	25.00	12.50
original	66.49	59.99	38.71	31.76	26.43
w. answer keywords	57.67	52.18	28.92	21.07	15.45
w. answer keywords + word blacklist	51.21	46.34	20.71	14.16	8.38

Table 4: Metric scores of ChatGLM3-6B-32k on **cmrc-mixup**. The score inflation is suppressed with keyword-recall-based metric design.

5 LIMITATIONS AND FUTURE WORK

LV-Eval does not encompass other task types such as summarization. Additionally, due to the high cost, we do not test some of the most recent LLMs, such as GPT-4-128k, GPT-4o, and so on. As we release all the test data, one can intentionally overfit the benchmark by training on the test data to get a high score. In this case, training on LV-Eval datasets with KPR might lead to mistakes in common-sense knowledge, resulting in a very unreliable evaluation.

As LV-Eval primarily focuses on extracting and manipulating information from long *inputs*, we do not include questions that require long *outputs*. In future benchmarks where evaluating long outputs is necessary, a more appropriate metric might involve using an LLM rater to assess whether the answer matches the ground truth. However, since our benchmark does not focus on long outputs, we rely on human efforts to provide a simpler metric, with the goal of avoiding the use of a strong LLM in the evaluation process, as this could introduce additional biases and costs.

A worth-noting issue about KPR is that as KPR modifies the fact, there exist some cases where the model identifies factual errors and then insists on providing a common-sense response. We view these cases as an issue with the model’s instruction-following ability, as our prompt explicitly states that the answer should be solely based on the context instead of its existing knowledge.

Our CFI technique relies on manual revision of the confusing facts to ensure the benchmark quality. A possible way to alleviate the human efforts when applying the CFI technique to future corpus might be leveraging stronger LLMs to substitute manual revision efforts.

REFERENCES

- 540
541
542 Josh Achiam, Steven Adler, Sandhini Agarwal, Lama Ahmad, Ilge Akkaya, Florencia Leoni Ale-
543 man, Diogo Almeida, Janko Altenschmidt, Sam Altman, Shyamal Anadkat, et al. Gpt-4 technical
544 report. *arXiv preprint arXiv:2303.08774*, 2023.
- 545 AI@Meta. Llama 3 model card. [https://github.com/meta-llama/llama3/blob/
546 main/MODEL_CARD.md](https://github.com/meta-llama/llama3/blob/main/MODEL_CARD.md), 2024.
547
- 548 Chenxin An, Shansan Gong, Ming Zhong, Mukai Li, Jun Zhang, Lingpeng Kong, and Xipeng Qiu.
549 L-eval: Instituting standardized evaluation for long context language models. *arXiv preprint
550 arXiv:2307.11088*, 2023.
- 551 Jinze Bai, Shuai Bai, Shusheng Yang, Shijie Wang, Sinan Tan, Peng Wang, Junyang Lin, Chang
552 Zhou, and Jingren Zhou. Qwen-vl: A frontier large vision-language model with versatile abilities.
553 *arXiv preprint arXiv:2308.12966*, 2023a.
554
- 555 Yushi Bai, Xin Lv, Jiajie Zhang, Hongchang Lyu, Jiankai Tang, Zhidian Huang, Zhengxiao Du,
556 Xiao Liu, Aohan Zeng, Lei Hou, et al. Longbench: A bilingual, multitask benchmark for long
557 context understanding. *arXiv preprint arXiv:2308.14508*, 2023b.
- 558 bloc97. Ntk-aware scaled rope allows llama models to extrapolate. [https://www.reddit.
559 com/r/LocalLLaMA/comments/141z7j5/ntkaware_scaled_rope_allows_
560 llama_models_to_have/](https://www.reddit.com/r/LocalLLaMA/comments/141z7j5/ntkaware_scaled_rope_allows_llama_models_to_have/), 5 2023.
561
- 562 Sebastian Borgeaud, Arthur Mensch, Jordan Hoffmann, Trevor Cai, Eliza Rutherford, Katie Milli-
563 can, George Bm Van Den Driessche, Jean-Baptiste Lespiau, Bogdan Damoc, Aidan Clark, et al.
564 Improving language models by retrieving from trillions of tokens. In *International conference on
565 machine learning*, pp. 2206–2240. PMLR, 2022.
- 566 Yiming Cui, Ting Liu, Wanxiang Che, Li Xiao, Zhipeng Chen, Wentao Ma, Shijin Wang, and Guop-
567 ing Hu. A span-extraction dataset for chinese machine reading comprehension. *arXiv preprint
568 arXiv:1810.07366*, 2018.
569
- 570 Zihang Dai, Zhilin Yang, Yiming Yang, Jaime Carbonell, Quoc V Le, and Ruslan Salakhutdi-
571 nov. Transformer-xl: Attentive language models beyond a fixed-length context. *arXiv preprint
572 arXiv:1901.02860*, 2019.
- 573 Zican Dong, Tianyi Tang, Junyi Li, Wayne Xin Zhao, and Ji-Rong Wen. Bamboo: A comprehensive
574 benchmark for evaluating long text modeling capacities of large language models. *arXiv preprint
575 arXiv:2309.13345*, 2023.
576
- 577 Team GLM. Chatglm: A family of large language models from glm-130b to glm-4 all tools. *arXiv
578 preprint arXiv:2406.12793*, 2024.
- 579 gradient.ai. Llama-3 8b gradient instruct 1048k model card. [https://huggingface.co/
580 gradientai/Llama-3-8B-Instruct-Gradient-1048k](https://huggingface.co/gradientai/Llama-3-8B-Instruct-Gradient-1048k), 2024.
581
- 582 Chi Han, Qifan Wang, Wenhan Xiong, Yu Chen, Heng Ji, and Sinong Wang. Lm-infinite: Simple
583 on-the-fly length generalization for large language models. *arXiv preprint arXiv:2308.16137*,
584 2023.
- 585 Xanh Ho, Anh-Khoa Duong Nguyen, Saku Sugawara, and Akiko Aizawa. Constructing a multi-hop
586 qa dataset for comprehensive evaluation of reasoning steps. *arXiv preprint arXiv:2011.01060*,
587 2020.
588
- 589 Cheng-Ping Hsieh, Simeng Sun, Samuel Kriman, Shantanu Acharya, Dima Rekesh, Fei Jia, and
590 Boris Ginsburg. Ruler: What’s the real context size of your long-context language models? *arXiv
591 preprint arXiv:2404.06654*, 2024.
592
- 593 Greg Kamradt. Pressure testing gpt-4-128k with long context recall. [https://twitter.com/
GregKamradt/status/1722386725635580292](https://twitter.com/GregKamradt/status/1722386725635580292), 2023.

- 594 Urvashi Khandelwal, Omer Levy, Dan Jurafsky, Luke Zettlemoyer, and Mike Lewis. Generaliza-
595 tion through memorization: Nearest neighbor language models. In *International Conference on*
596 *Learning Representations*, 2019.
- 597 Dacheng Li, Rulin Shao, Anze Xie, Ying Sheng, Lianmin Zheng, Joseph Gonzalez, Ion Stoica,
598 Xuezhe Ma, and Hao Zhang. How long can context length of open-source llms truly promise? In
599 *NeurIPS 2023 Workshop on Instruction Tuning and Instruction Following*, 2023a.
- 600 Jiaqi Li, Mengmeng Wang, Zilong Zheng, and Muhan Zhang. Loogle: Can long-context language
601 models understand long contexts? *arXiv preprint arXiv:2311.04939*, 2023b.
- 602 Xinnian Liang, Bing Wang, Hui Huang, Shuangzhi Wu, Peihao Wu, Lu Lu, Zejun Ma, and Zhoujun
603 Li. Unleashing infinite-length input capacity for large-scale language models with self-controlled
604 memory system. *arXiv preprint arXiv:2304.13343*, 2023.
- 605 Pedro Henrique Martins, Zita Marinho, and André FT Martins. ∞ -former: Infinite memory
606 transformer-former: Infinite memory transformer. In *Proceedings of the 60th Annual Meeting*
607 *of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 5468–5485, 2022.
- 608 Meta. Llama-3.1-70b-instruct model card. [https://huggingface.co/meta-llama/](https://huggingface.co/meta-llama/Llama-3.1-70B-Instruct)
609 [Llama-3.1-70B-Instruct](https://huggingface.co/meta-llama/Llama-3.1-70B-Instruct), 2024.
- 610 moonshot. moonshot model site. <https://www.moonshot.cn/>, 2024.
- 611 Xuanfan Ni, Hengyi Cai, Xiaochi Wei, Shuaiqiang Wang, Dawei Yin, and Piji Li. Xl²bench:
612 A benchmark for extremely long context understanding with long-range dependencies. *arXiv*
613 *preprint arXiv:2404.05446*, 2024.
- 614 Bowen Peng, Jeffrey Quesnelle, Honglu Fan, and Enrico Shippole. Yarn: Efficient context window
615 extension of large language models. *arXiv preprint arXiv:2309.00071*, 2023a.
- 616 Bowen Peng, Jeffrey Quesnelle, Honglu Fan, and Enrico Shippole. Yarn: Efficient context window
617 extension of large language models. *arXiv preprint arXiv:2309.00071*, 2023b.
- 618 Ofir Press, Noah A Smith, and Mike Lewis. Train short, test long: Attention with linear biases
619 enables input length extrapolation. *arXiv preprint arXiv:2108.12409*, 2021.
- 620 Jack W Rae, Anna Potapenko, Siddhant M Jayakumar, and Timothy P Lillicrap. Compressive
621 transformers for long-range sequence modelling. *arXiv preprint arXiv:1911.05507*, 2019.
- 622 Uri Shaham, Maor Ivgi, Avia Efrat, Jonathan Berant, and Omer Levy. Zeroscrolls: A zero-shot
623 benchmark for long text understanding. *arXiv preprint arXiv:2305.14196*, 2023.
- 624 Jianlin Su, Murtadha Ahmed, Yu Lu, Shengfeng Pan, Wen Bo, and Yunfeng Liu. Roformer: En-
625 hanced transformer with rotary position embedding. *Neurocomputing*, 568:127063, 2024.
- 626 Hongxuan Tang, Hongyu Li, Jing Liu, Yu Hong, Hua Wu, and Haifeng Wang. Dureader_robust: A
627 chinese dataset towards evaluating robustness and generalization of machine reading comprehen-
628 sion in real-world applications. *arXiv preprint arXiv:2004.11142*, 2020.
- 629 BlueLM Team. BlueLM: An open multilingual 7b language model. [https://github.com/](https://github.com/vivo-ai-lab/BlueLM)
630 [vivo-ai-lab/BlueLM](https://github.com/vivo-ai-lab/BlueLM), 2023.
- 631 togetherAI. Llama-2-7b-32k-instruct — and fine-tuning for llama-2 models with together api.
632 <https://www.together.ai/blog/llama-2-7b-32k-instruct>, August 2023.
- 633 Hugo Touvron, Louis Martin, Kevin Stone, Peter Albert, Amjad Almahairi, Yasmine Babaei, Niko-
634 lay Bashlykov, Soumya Batra, Prajjwal Bhargava, Shrutli Bhosale, et al. Llama 2: Open founda-
635 tion and fine-tuned chat models. *arXiv preprint arXiv:2307.09288*, 2023.
- 636 Minzheng Wang, Longze Chen, Cheng Fu, Shengyi Liao, Xinghua Zhang, Bingli Wu, Haiyang Yu,
637 Nan Xu, Lei Zhang, Run Luo, Yunshui Li, Min Yang, Fei Huang, and Yongbin Li. Leave no
638 document behind: Benchmarking long-context llms with extended multi-doc qa. *arXiv preprint*
639 *arXiv:2406.17419*, 2024.

- 648 Yuhuai Wu, Markus Norman Rabe, DeLesley Hutchins, and Christian Szegedy. Memorizing trans-
649 formers. In *International Conference on Learning Representations*, 2021.
650
- 651 Guangxuan Xiao, Yuandong Tian, Beidi Chen, Song Han, and Mike Lewis. Efficient streaming
652 language models with attention sinks. *arXiv preprint arXiv:2309.17453*, 2023.
- 653 Wenhan Xiong, Jingyu Liu, Igor Molybog, Hejia Zhang, Prajjwal Bhargava, Rui Hou, Louis Martin,
654 Rashi Rungta, Karthik Abinav Sankararaman, Barlas Oguz, et al. Effective long-context scaling
655 of foundation models. *arXiv preprint arXiv:2309.16039*, 2023.
656
- 657 An Yang, Baosong Yang, Binyuan Hui, Bo Zheng, Bowen Yu, Chang Zhou, Chengpeng Li,
658 Chengyuan Li, Dayiheng Liu, Fei Huang, et al. Qwen2 technical report. *arXiv preprint*
659 *arXiv:2407.10671*, 2024.
- 660 Zhilin Yang, Peng Qi, Saizheng Zhang, Yoshua Bengio, William W Cohen, Ruslan Salakhutdinov,
661 and Christopher D Manning. Hotpotqa: A dataset for diverse, explainable multi-hop question
662 answering. *arXiv preprint arXiv:1809.09600*, 2018.
663
- 664 Junjie Ye, Xuanting Chen, Nuo Xu, Can Zu, Zekai Shao, Shichun Liu, Yuhan Cui, Zeyang Zhou,
665 Chao Gong, Yang Shen, et al. A comprehensive capability analysis of gpt-3 and gpt-3.5 series
666 models. *arXiv preprint arXiv:2303.10420*, 2023.
- 667 Yi. A series of large language models trained from scratch by developers at 01-ai. [https://](https://github.com/01-ai/Yi)
668 github.com/01-ai/Yi, 2023.
669
- 670 yuyijiong. Long-instruction-en2zh. [https://huggingface.co/datasets/yuyijiong/](https://huggingface.co/datasets/yuyijiong/Long-instruction-en2zh)
671 [Long-instruction-en2zh](https://huggingface.co/datasets/yuyijiong/Long-instruction-en2zh), 2023.
- 672 Aohan Zeng, Xiao Liu, Zhengxiao Du, Zihan Wang, Hanyu Lai, Ming Ding, Zhuoyi Yang, Yifan Xu,
673 Wendi Zheng, Xiao Xia, et al. Glm-130b: An open bilingual pre-trained model. *arXiv preprint*
674 *arXiv:2210.02414*, 2022.
- 675 Lianmin Zheng, Wei-Lin Chiang, Ying Sheng, Siyuan Zhuang, Zhanghao Wu, Yonghao Zhuang,
676 Zi Lin, Zhuohan Li, Dacheng Li, Eric Xing, et al. Judging llm-as-a-judge with mt-bench and
677 chatbot arena. *arXiv preprint arXiv:2306.05685*, 2023.
678
- 679 Kun Zhou, Yutao Zhu, Zhipeng Chen, Wentong Chen, Wayne Xin Zhao, Xu Chen, Yankai Lin,
680 Ji-Rong Wen, and Jiawei Han. Don't make your llm an evaluation benchmark cheater. *arXiv*
681 *preprint arXiv:2311.01964*, 2023a.
- 682 Wangchunshu Zhou, Yuchen Eleanor Jiang, Peng Cui, Tiannan Wang, Zhenxin Xiao, Yifan Hou,
683 Ryan Cotterell, and Mrinmaya Sachan. Recurrentgpt: Interactive generation of (arbitrarily) long
684 text. *arXiv preprint arXiv:2305.13304*, 2023b.
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701




Figure A6: Keyword-recall-based two-stage metric calculation. (a) The vanilla F1 score (red) is inflated high. With the keyword recall-based metric, the final score is set to zero due to the low recall of answer keywords. (b) The vanilla F1 score (red) is inflated high due to irrelevant words. By filtering of blacklisted words, the final score is better calibrated.

Prompts of GPT4 used to generate confusing facts

Prompt_en:

'I will provide a question, which is a query about the facts described in an article. This article and question will be input into a language model to predict the answer, and the accuracy of the answer will be used to evaluate the model's ability. I need you to generate two confusing facts in the article, making it harder for the language model to figure out the correct answer, while these confusing facts should not be in conflict with the original facts in the article. Here's an example: input: What is the total bid control price in ten thousand yuan for Sections A, B and C of the Wuzhou City Ring Expressway? Output: Recently, the bid control price for Sections A, B, and C of the Fuzhou City Ring Expressway reached 600 ten thousand yuan, which greatly propelled the rapid development of local infrastructure and injected robust power into the city's economy. Recently, the bid control price for Sections D, E, and F of the Wuzhou City Ring Expressway was determined to be 500 ten thousand yuan after careful assessment and approval by relevant parties. The first confusing fact changes the subject from Wuzhou City, and the second modifies the ABC sections, making it impossible to complete the input question based on these two confusing facts. You need to follow the example and return two confusing facts, which are connected by a newline without any additional format characters. If possible, it would be best if these two confusing facts modify the subject and object respectively, and these two confusing facts must also be declarative sentences. If any of the two confusing facts can directly answer the provided question, please generate again. This is the question I'm providing:'

Prompt_zh:

'我将提供一个问题，它是对一篇文章中描述的事实进行提问。这个文章和问题将会输入给一个语言模型让其回复答案，根据答案来评测语言模型的能力，我需要你生成两个干扰事实插入到文章中，让语言模型更难找到正确答案，同时混淆事实不应该与文章中原本的事实产生冲突。这是一个案例：input: 梧州市环城高速公路A标段、B标段和C标段的招标控制价合计是多少万元？output: 最近，福州市环城高速公路A标段、B标段和C标段的招标控制价达到了600万元，这一大笔资金的投入极大地推动了当地基础设施建设的快速发展，为城市经济注入了强劲动力。最近，梧州市环城高速公路D标段、E标段和F标段的招标控制价被确定为500万元，这一价格经过了相关方面的认真评估和审批。其中第一个回答修改了主语梧州市，第二个回答修改了ABC标段，导致你不能根据这两个干扰事实来完成对输入问题的回答。你需要仿照案例返回两个干扰事实，这两个事实直接用换行符连接，不需要额外添加任何格式符号，如果可以的话，最好这两个回答分别修改主语和宾语，这两个回答也必须是陈述句。如果你给出的两个回答中只要有一个能直接解答提供的问题，请重新生成。这是我提供的问题：'

Figure A7: Prompts used for GPT-4 to generate confusing facts.

A DISCUSSION

Could the CF generated by GPT-4 give an unfair effect to the evaluation results of GPT-4? There is a possibility that the CF generated by GPT-4 could lead to either an unfair advantage or an unfair disadvantage in its evaluation results. On the one hand, the generated CF is aligned to GPT-4's internal concept, which may lead to an unfair advantage, due to the problem of data leakage. On the other hand, it may lead to an unfair disadvantage, because the CF generated by GPT-4 itself may be

the ones that are hardest for GPT-4 to distinguish, unless explicitly prompted to consider CF within the context.

Comparison of LV-Eval with two concurrently developed benchmarks: XLBench (Ni et al., 2024) and Loong (Wang et al., 2024) There are several key differences between LV-Eval and these two benchmarks: 1. **Context Length Balance:** Both Loong and XLBench are not length-balanced, meaning that test instances of different lengths do not share the same QA pairs. In contrast, LV-Eval ensures that the supporting documents and QA pairs are shared across different length levels, making it easier to track performance degradation as context length increases. 2. **Application Focus:** Loong is primarily focused on information extraction tasks, such as sheet analysis, which limits its scope. In contrast, LV-Eval is a more general-purpose benchmark, assessing not only knowledge extraction but also manipulation and understanding in complex long-context scenarios. 3. **Benchmarking Techniques:** We introduce the KPR benchmarking technique to decouple the evaluation of common-sense knowledge from the evaluation of long-context understanding, addressing a key limitation in existing long-context benchmarks. Additionally, we propose an optimized metric, leveraging manual efforts to label keywords, which makes the scoring more intuitive and interpretable (see Table 4). We hope this comparison clarifies the distinct contributions of LV-Eval to the community.

B DETAILED CONSTRUCTION OF QA PAIRS

As LV-Eval primarily focuses on extracting and manipulating information from long inputs, we do not include questions that require long outputs. We select QA pairs with short and brief answers.

Multi-hop QA. In a multi-hop QA task, the reasoning to derive the answer needs to gather multiple pieces of information from various locations in the context. We construct four multi-hop QA datasets: **dureader-mixup**, **loogle-CR-mixup**, **loogle-MR-mixup**, and **hotpotwikiqa-mixup**.

- **hotpotwikiqa-mixup** is originated from two Wikipedia-based multi-hop QA datasets: HotpotQA and 2WikiMultihopQA. HotpotQA contains 112,779 2-hop questions that are written by native speakers according to two given paragraphs as the context. 2WikiMultihopQA contains 192,606 5-hop questions that are synthesized using manually designed templates to prevent shortcut solutions. We select 124 samples from the two datasets.
- **loogle-MR-mixup** and **loogle-CR-mixup** originate from LooGLE’s Long-dependency QA task, specifically the *Multiple information Retrieval* and *Comprehension and Reasoning* subtasks. The *Multiple information Retrieval* task requires aggregation of the evidence that can be directly located in original sentences, while the *Comprehension and Reasoning* task contains implicit evidence within the context, it requires multi-step reasoning to get the correct answers. We select 139 and 99 questions for **loogle-MR-mixup** and **loogle-CR-mixup**, respectively.
- **dureader-mixup** is built from the DuReader dataset. We first randomly select 200 instances and then manually remove 24 samples whose answers are longer than 360 words.

Single-hop QA. In a single-hop QA task, only a single evidence in the context is needed to derive the answer. We construct seven single-hop QA datasets: **lic-mixup**, **loogle-SD-mixup**, **cmrc-mixup**, **multifieldqa-en-mixup**, **multifieldqa-zh-mixup**, **factrecall-en**, and **factrecall-zh**.

- **lic-mixup** is originated from the Long-instruction-en2zh dataset on Hugging Face. Long-instruction-en2zh contains 8,000+ high-quality Chinese multi-doc QA data translated from English. We selected 197 QA pairs and their corresponding documents as supporting data, while the remaining documents serve as distracting data for context mixing.
- **loogle-SD-mixup** contains 160 unique QA pairs and 800 documents originated from the short-dependency QA task in LooGLE.
- **cmrc-mixup** is derived from the CMRC 2018 Public Datasets, designed for Chinese machine reading comprehension. It contains $\sim 20k$ questions annotated on Wikipedia docu-

810 ments by human experts. We manually pick 200 QA pairs and their corresponding docu-
811 ments as supporting QA pairs and documents.

- 812 • **multifieldqa-en-mixup** and **multifieldqa-zh-mixup** are built from the MultiFieldQA
813 datasets in Long-Bench. We manually remove questions that can be answered using
814 common-sense knowledge without referring to the context, and eventually get 101 and 133
815 unique QA pairs for **multifieldqa-en-mixup** and **multifieldqa-zh-mixup**, respectively.
- 816 • **factrecall-en** and **factrecall-zh** are two synthetic datasets designed to assess the LLMs’
817 ability to identify a small piece of evidence (“fact”) located at various locations within
818 a lengthy context. As shown in Figure A12 A13, we write one English fact-question-
819 answer pair for **factrecall-en** and one Chinese fact-question-answer pair for **factrecall-zh**.
820 distracting documents are sourced from *PG-19* dataset (English) and the book of *Journey*
821 *to the West* (Chinese) to create five contexts of different length levels. For each context,
822 we generate 200 documents by inserting the fact at 200 evenly spaced positions within the
823 context.

824 C ANNOTATION DETAILS

- 825 • **Annotators:** We hire a total of five annotators, including three master students involved
826 in LLM research and two master students majored in linguistics. They are hired to work
827 on-site as full-time annotators.
- 828 • **Annotation time:** On average, annotators worked 8 hours per day. (1) For CFI, six datasets
829 comprising a total of 557 instances of confusing facts were reviewed, with the verification
830 process completed by two annotators over a period of three days. This task was assigned to
831 master’s students in linguistics to ensure semantic consistency. (2) For KPR, six datasets
832 containing 1,924 pairs were processed. Replacing key words and phrases in the Chinese
833 datasets involved five individuals over three days, whereas the English datasets required two
834 individuals over two days. (3) For answer keyword annotation, nine datasets comprising
835 955 instances of answer keywords were annotated by two individuals within a single day.
- 836 • **Annotation guidelines:** We provided guidelines and examples to the five annotators and
837 conducted a trial annotation in accordance with these guidelines to ensure they understand
838 the guidelines. The guidelines are summarized as follows. For CFI, two types of cases
839 require manual modification: (a) The confusing facts generated by GPT-4 fail to produce
840 interference; (b) The confusing facts generated by GPT-4 conflict with the original facts.
841 For KPR, the guidelines are: (a) Ensure that the replaced words or phrases are distinct
842 from the original and not synonyms; (b) Maximize the differences between the revised and
843 original sentences by replacing as many words as possible; (c) Prioritize the replacement
844 of words that do not have synonyms, as it is challenging to ensure that all synonyms are
845 correctly replaced for words with multiple synonyms; (d) After replacement, the resulting
846 statement may be inconsistent with common knowledge; (e) After replacement, it’s OK
847 that the resulting statement may be inconsistent with common knowledge, as long as the
848 answer can be derived from the context and that all information related to this answer is
849 consistent within the context.
- 850 • **Measurement of inter-annotator agreement:** We did not measure inter-annotator agree-
851 ment during the annotation process. Since the principles of the annotation task are simple
852 and clear, and the number of annotations is relatively small, we had the two annotators
853 review each other’s work to resolve any disagreements after completing their independent
854 annotations.

855 D DETAILED EVALUATION RESULTS

856 The detailed information of evaluated LLMs are shown in Table A5.

857 The detailed results on each dataset of the single-hop QA task type and multi-hop QA task type
858 are shown in Figure A8 and Figure A9, respectively. We can see that (i) Among the multi-hop QA
859 datasets, **loogle-CR-mixup** and **loogle-MR-mixup** are particularly challenging. Future research is
860 needed to improve the ability to aggregate multiple pieces of evidence from a long context with
861

Model Name	SFT	Context Length	HuggingFace / API Endpoint
Llama2-7B-Chat-hf (Touvron et al., 2023)	✓	4k	meta-llama/Llama-2-7b-chat-hf
Qwen-7B-8k-Chat (Bai et al., 2023a)	✓	8k	Qwen/Qwen-7B-Chat
Llama3-8B-Instruct (AI@Meta, 2024)	✓	8k	meta-llama/Meta-Llama-3-8B-Instruct
Vicuna-7B-16k-v1.5 (Zheng et al., 2023)	✓	16k	lmsys/vicuna-7b-v1.5-16k
ChatGLM3-6B-32k (Zeng et al., 2022)	✓	32k	THUDM/chatglm3-6b-32k
BlueLM-7B-32k-Chat (Team, 2023)	✓	32k	vivo-ai/BlueLM-7B-Chat-32K
LongChat-7B-32k-v1.5 (togetherAI, 2023)	✓	32k	lmsys/longchat-7b-v1.5-32k
GLM-4-9B-128k (GLM, 2024)	✓	128k	THUDM/glm-4-9b-chat
Qwen2.5-72B-Instruct-128k (Yang et al., 2024)	✓	128k	Qwen/Qwen2.5-72B-Instruct
Meta-Llama-3.1-70B-128k-Instruct (Meta, 2024)	✓	128k	meta-llama/Llama-3.1-70B-Instruct
Yi-6B-200k (Yi, 2023)	✓	200k	01-ai/Yi-6B-200K
Llama3-8B-1M (gradient.ai, 2024)	✓	1048k	gradientai/Llama-3-8B-Instruct-Gradient-1048k
GPT-4-8k (Achiam et al., 2023)	✓	8k	gpt-4-0613
GPT-3.5-16k (Ye et al., 2023)	✓	16k	gpt-3.5-turbo-1106
Moonshot-V1-128k (moonshot, 2024)	✓	128k	moonshot-V1-128k

Table A5: Information of evaluated LLMs.

distracting and confusing facts. (ii) For single-hop QA datasets, as expected, LLMs can achieve higher scores on datasets without CFI, including **loogle-SD-mixup** and **cmrc-mixup**. (iii) Several LLMs, namely ChatGLM3-6B-32k, BlueLM-7B-32k-Chat, and Yi-6B-200k, can achieve relatively high scores on **factrecall-en**. This indicates that the NIAH task might not be challenging enough, emphasizing the need to evaluate LLMs on other tasks, particularly multi-hop QA datasets. (iv) The performance gap between LLMs on **factrecall-en** and **factrecall-zh** is especially large, and some open-source LLMs with relatively small context sizes, namely Llama2-7B-Chat-hf (4k context window size), Qwen-7B-8k-Chat, and Vicuna-7B-16k-v1.5, even get near-zero scores. (v) A few LLMs have unbalanced performances on Chinese and English datasets, as illustrated by the results on **multifieldqa-en-mixup** and **multifieldqa-zh-mixup**. The detailed scores of all models on 5 length levels of all sub-datasets are shown in Table A6 A7.

Dataset	Len.	Ch.	Bl.	Yi.	Lo.	Qw.	Vi.	LI.4	LI.8	LI.M	GPT3.	GPT4.	LI.31	Qw.25	GLM9.	Ms.
dureader-mixup	16k	23.99	19.40	2.87	13.44	11.82	9.67	7.21	16.39	18.06	8.01	19.14	20.22	18.28	19.71	21.46
	32k	25.21	19.74	2.98	11.57	12.80	7.65	5.42	13.08	15.86	5.26	13.64	22.38	19.16	19.15	21.00
	64k	22.01	14.44	2.88	9.23	10.48	6.62	5.59	10.24	15.16	4.26	12.66	19.22	17.82	21.02	-
	128k	17.94	10.95	2.36	9.51	8.15	6.25	4.78	5.30	14.46	3.30	8.19	9.90	18.24	19.37	-
	256k	8.72	8.51	3.06	7.96	8.65	5.70	4.45	4.46	10.64	3.50	6.71	5.11	16.27	18.54	-
loogle-CR-mixup	16k	14.41	9.01	8.25	11.25	5.48	5.00	3.69	8.63	12.56	10.04	12.68	30.05	20.33	21.59	25.02
	32k	14.10	7.36	8.83	11.17	3.30	4.25	3.29	8.74	11.05	8.39	10.40	26.24	20.25	20.53	23.29
	64k	9.92	3.81	4.73	9.31	3.82	3.76	3.13	2.78	8.64	5.58	6.48	26.81	19.08	15.55	-
	128k	6.95	2.40	4.05	6.19	1.14	1.99	2.19	0.26	5.81	3.08	2.83	20.72	12.56	14.07	-
	256k	5.46	2.60	3.23	5.03	1.94	1.28	0.81	0.49	4.54	3.37	3.91	16.61	7.31	7.61	-
loogle-MR-mixup	16k	15.83	4.90	6.94	10.53	4.93	5.17	3.37	10.39	13.73	12.95	12.24	23.60	19.14	15.88	20.62
	32k	11.62	3.14	7.67	9.51	2.95	3.83	2.20	7.14	10.9	7.03	7.83	22.54	16.12	16.29	19.63
	64k	7.00	1.68	2.69	3.04	2.37	0.96	2.05	3.89	7.82	6.23	6.26	21.57	16.52	16.41	-
	128k	7.24	2.46	3.44	4.05	1.80	0.55	1.04	2.37	5.93	2.13	2.30	18.75	12.06	11.87	-
	256k	3.82	2.19	1.32	3.01	1.46	1.06	0.33	0.4	4.63	1.00	0.90	15.83	7.74	11.40	-
hotpotwikiqua-mixup	16k	16.98	19.31	23.55	11.57	2.78	2.63	3.99	12.14	17.67	11.96	13.51	27.53	31.69	27.60	30.08
	32k	14.76	14.07	18.94	10.71	1.89	2.19	1.30	7.37	17.17	6.66	10.62	30.86	31.96	28.98	28.93
	64k	9.02	9.63	9.94	4.77	2.27	2.05	1.84	2.34	13.37	3.27	6.67	27.57	26.80	24.42	-
	128k	8.31	7.71	7.66	5.49	2.37	1.04	0.81	3.86	15.02	4.23	4.13	17.97	21.46	21.06	-
	256k	6.68	5.40	2.01	2.37	1.82	1.85	0.75	2.17	10.88	3.30	2.36	8.07	14.07	13.98	-

Table A6: Overall results of multi-hop QA tasks in LV-Eval. The abbreviations “Ch.,” “Bl.,” “Yi.,” “Lo.,” “Qw.,” “Vi.,” “LI.4,” “LI.8,” “LI.M,” “LI.31,” “Qw.25,” “GLM9.,” “Ms.,” “GPT3.,” and “GPT4.” stand for ChatGLM3-6B-32k, BlueLM-7B-32k-Chat, Yi-6B-200k, LongChat-7B-32k-v1.5, Qwen-7B-8k-Chat, Vicuna-7B-16k-v1.5, Llama2-7B-Chat-hf, Llama3-8B-Instruct, Llama3-8B-1M, Meta-Llama-3.1-70B-Instruct, Qwen2.5-72B-Instruct-128k, GLM-4-9B-128k, moonshot-v1-128k, GPT-3.5-16k, and GPT-4-8k, respectively.

Additionally, we select the top 3 LLMs from our study for evaluation with LLM auto rater. We select GPT-4-0613 as auto rater, and the auto rating prompts, which is shown in Figure A10, are well-crafted to make evaluation objective. The average scores on five length levels of those 3 LLMs are plot in dot lines in Figure A11. The results suggest that auto rater generally assigns higher scores than our keyword-recall-based metric. Despite this, the relative model performance is still accurately reflected. LLM auto rater consumes about 2M input tokens in the case of taking GPT-4-0613 as judge model, which incurs an approximate cost of 20 \$ per model evaluation.




Figure A8: Average scores across all length levels of 14 LLMs on single-hop QA datasets.

E DETAILED ABLATION RESULTS

The detailed ablation results of CFI and KPR are shown in Table A8 A9 A10.

F SAMPLES IN LV-EVAL

For completeness of our manuscript, we show some data samples of **factrecall-en** and **factrecall-zh** in Figure A12 A13.

G EXAMPLES OF FAILURE CASES

Figure A14 shows some failure cases of Llama-3-8b-Instruct when confusing facts exist in **factrecall-en** and **factrecall-zh**. In **factrecall-zh-16k**, all of Llama-3-8b-Instruct’s responses were misled by the confusing fact, that is “David Beckham”, whereas in the **factrecall-en-16k** dataset, only 32% of the responses were misled by the confusing fact. This suggests that the model’s anti-interference ability may vary significantly across languages.

Figure A15 shows a failure case of multi-hop reasoning in a QA task. In the 65th test sample of the **hotpotwikiqa-mixup-16k** dataset, the question asks,

972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025




Figure A9: Average scores across all length levels of 14 LLMs on multi-hop QA datasets.

```

Rating prompt for LLM auto judge

For factrecall datasets:
"""You are a LLM evaluator. There are a refernce {{answer}}, and a LLM's {{response}}. Your task is to rate the {{response}} based on
the following two aspects:
## Semantic similarity between {{answer}} and {{response}}
## {{response}} recall of the {{answer}}
You must rate the response on a scale of 0 to 10 by strictly following this format: "[rating]", for example: "[5]".
<The start of {{answer}}>
{A}
<The end of {{answer}}>
<The start of {{response}}>
{R}
<The end of {{response}}>"""

For other datasets:
"""You are a LLM evaluator. There are a pair of {{question}} and {{answer}}, and a {{response}} from the evaluated LLM. Your task is to
rate LLM's {{response}} based on the following two aspects:
## Semantic similarity between {{answer}} and {{response}}
## Is the {{response}} relevant to the {{question}}?
You must rate the response on a scale of 0 to 10 by strictly following this format: "[rating]", for example: "[5]".
<The start of {{question}}>
{Q}
<The end of {{question}}>
<The start of {{answer}}>
{A}
<The end of {{answer}}>
<The start of {{response}}>
{R}
<The end of {{response}}>"""
    
```


Figure A10: Rating prompt for GPT4 auto judge.

What is the date of death of the director of the film Nallavan Vazhvan?. Answering this question requires multi-hop reasoning: The model needs to first extract the director's name from ### Passage 30, which discusses the film Nallavan Vazhvan, and then retrieve the final answer from ### Passage 15 which provides biographical details. However, the model incorrectly pulls the answer from ### Passage 27, which describes another director, giving a vague statement that the director was involved in the production of over 60 films. The model mistakenly interprets this as relevant information for answering the question. Additionally, the incorrect response may have been influenced by the fact that the director's first name in the film's introduction was abbreviated, preventing the model from retrieving the correct answer via exact matching. This example indicates that even a powerful model like Llama 3 struggles to accurately

Dataset	Len.	Ch.	Bl.	Yi.	Lo.	Qw.	Vi.	Ll.4	Ll.8	Ll.M	GPT3.	GPT4.	Ll.31	Qw.25	GLM9.	Ms.
lic-mixup	16k	24.15	20.75	5.37	15.45	6.05	8.34	2.48	9.16	15.27	7.65	13.69	15.46	30.96	31.11	35.57
	32k	22.27	12.68	6.25	10.02	6.07	4.81	0.99	6.57	15.62	4.42	5.86	17.02	28.14	30.00	34.46
	64k	14.33	5.00	7.19	4.54	4.21	2.52	0.48	1.80	14.85	3.07	3.23	12.77	27.65	31.84	-
	128k	8.30	3.03	5.56	2.47	4.34	2.36	0.42	2.52	11.86	0.87	1.90	2.17	27.71	30.35	-
	256k	6.07	4.11	6.24	2.14	3.19	1.99	0.73	1.30	7.96	1.65	1.70	1.32	15.20	17.99	-
loogle-SD-mixup	16k	41.82	34.34	39.56	27.42	10.54	8.79	6.75	25.08	39.53	31.67	27.01	63.25	58.13	57.23	59.83
	32k	30.31	15.10	36.48	18.21	4.70	4.90	2.61	12.56	31.45	18.56	14.01	61.95	57.02	52.98	57.85
	64k	19.07	4.95	31.71	12.09	2.40	3.07	2.58	7.34	28.45	10.41	8.00	53.97	56.38	47.83	-
	128k	11.34	5.32	25.71	9.11	3.25	4.24	2.04	4.85	18.81	5.74	5.14	35.63	41.99	43.15	-
	256k	8.92	5.41	12.37	5.97	3.02	2.39	1.24	0.91	8.37	3.56	1.48	22.45	23.95	22.62	-
cmrc-mixup	16k	51.21	45.89	1.05	20.99	11.13	11.75	3.85	15.16	20.25	12.19	14.67	53.95	35.63	42.42	46.42
	32k	46.34	19.53	0.35	10.77	5.32	6.55	1.08	6.77	19.83	6.00	3.33	49.82	33.01	42.01	46.80
	64k	20.71	10.66	0.84	8.97	4.68	5.04	1.72	4.82	17.27	3.57	5.31	50.72	35.38	38.50	-
	128k	14.16	7.06	1.58	3.77	3.81	3.77	1.64	1.78	13.46	2.73	3.81	5.32	35.42	36.67	-
	256k	8.38	4.51	2.54	3.75	4.09	4.13	1.54	1.73	5.66	1.32	2.68	2.94	22.38	22.56	-
multifieldqa-en-mixup	16k	25.40	11.82	10.01	12.02	7.66	6.29	8.81	16.33	21.30	18.78	19.00	39.46	29.90	32.06	33.44
	32k	12.78	6.34	9.24	7.58	3.61	4.32	5.55	9.60	17.05	11.59	12.69	38.61	27.96	31.18	34.19
	64k	12.32	8.38	8.83	7.84	5.23	2.79	1.58	6.15	18.68	7.38	8.30	32.19	26.87	27.89	-
	128k	9.89	5.29	5.98	3.11	3.64	2.51	2.54	6.63	17.27	7.95	7.25	26.06	21.21	24.25	-
	256k	4.24	4.78	4.69	4.22	2.44	1.28	1.49	3.20	14.42	3.21	3.54	19.05	17.10	17.27	-
multifieldqa-zh-mixup	16k	32.38	22.05	2.85	9.81	8.82	5.82	4.72	18.73	21.69	18.94	17.61	39.16	40.65	39.44	39.05
	32k	24.48	17.64	0.75	8.82	5.68	4.45	1.21	13.60	13.46	12.21	11.18	32.80	36.28	35.84	31.71
	64k	20.97	7.36	1.89	3.23	3.01	2.03	0.68	6.13	11.31	6.29	4.99	30.77	31.79	36.13	-
	128k	10.08	5.90	2.11	3.54	2.84	0.88	0.24	1.52	9.28	2.94	1.76	24.42	30.71	35.13	-
	256k	7.05	4.48	1.58	3.92	2.52	1.26	0.56	2.62	7.79	2.15	0.92	19.37	25.95	26.42	-
factrecall-en	16k	91.50	58.5	24.88	9.22	1.77	0	1.08	2.72	68.00	8.25	23.4	85.20	98.50	86.35	81.38
	32k	89.00	32.17	23.09	14.33	1.12	0	0.46	2.03	67.17	3.27	11.84	88.36	96.00	82.00	86.17
	64k	46.00	15.50	24.96	8.31	0.71	0	0.31	0.61	73.00	1.80	5.21	93.33	94.00	79.00	-
	128k	24.00	9.00	22.04	7.86	0.18	0.25	0.23	0.15	78.83	0.60	4.03	81.88	88.00	69.00	-
	256k	12.50	5.00	16.44	6.00	0.22	0.20	0.15	0	58.00	0.45	1.79	47.96	52.50	46.50	-
factrecall-zh	16k	0	19.00	25.73	7.20	15.75	0	0	2.18	0	14.51	28.03	17.00	83.00	10.50	67.19
	32k	2.00	37.00	16.86	5.00	6.00	0	0	2.03	0.14	6.70	15.24	17.50	77.50	8.00	71.14
	64k	12.50	20.00	12.41	3.50	3.50	0	0	1.09	0	2.49	8.08	6.00	77.00	8.50	-
	128k	9.00	12.50	10.13	3.70	1.50	0	0	0.32	0	1.72	3.58	5.53	76.50	6.00	-
	256k	7.00	5.50	4.62	2.00	0.50	0	0	0.21	0	0.98	2.00	10.44	47.06	11.00	-

Table A7: Overall results of single-hop QA tasks in LV-Eval. The abbreviations “Ch.,” “Bl.,” “Yi.,” “Lo.,” “Qw.,” “Vi.,” “Ll.4,” “Ll.8,” “Ll.M,” “Ll.31,” “Qw.25,” “GLM9.,” “Ms.,” “GPT3.,” and “GPT4.” stand for ChatGLM3-6B-32k, BlueLM-7B-32k-Chat, Yi-6B-200k, LongChat-7B-32k-v1.5, Qwen-7B-8k-Chat, Vicuna-7B-16k-v1.5, Llama2-7B-Chat-hf, Llama3-8B-Instruct, Llama3-8B-1M, Meta-Llama-3.1-70B-Instruct, Qwen2.5-72B-Instruct-128k, GLM-4-9B-128k, moonshot-v1-128k, GPT-3.5-16k, and GPT-4-8k, respectively.

understanding entity relationships in long-context, multi-step reasoning tasks and is easily misled by superficially relevant but ambiguous information.



1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133

Figure A11: Average scores on five length levels. The dot lines show 3 best LLMs judged by GPT-0613 auto rater, corresponding to 3 solid lines in the same colors which show performance under proposed metrics. The abbreviation "LJ" stands for auto LLM Judge

Model Name	Ablation	hotpotwikiqa-mixup				
		16k	32k	64k	128k	256k
Llama2-7B-Chat-hf	w. both	3.99	1.30	1.84	0.81	0.75
	w. KPR	4.10	1.56	1.36	0.63	0.88
	w. CFI	6.29	2.47	3.37	1.47	1.57
	w.o. both	6.48	2.48	2.98	1.29	1.57
ChatGLM3-6B-32k	w. both	16.98	14.76	9.02	8.31	6.68
	w. KPR	21.32	13.04	9.99	6.56	6.12
	w. CFI	27.06	24.75	17.57	12.89	10.88
	w.o. both	28.48	21.96	18.89	11.31	10.69
LongChat-7B-32k-v1.5	w. both	11.57	10.71	4.77	5.49	2.37
	w. KPR	11.07	6.17	5.27	5.31	3.06
	w. CFI	19.48	14.33	9.41	11.34	6.44
	w.o. both	18.79	12.44	9.94	11.33	7.47
Yi-6B-200k	w. both	23.55	18.94	9.94	7.66	2.01
	w. KPR	23.84	13.77	6.52	6.69	3.84
	w. CFI	33.32	16.89	11.00	7.62	8.09
	w.o. both	30.71	17.62	10.43	10.17	8.51
Vicuna-7B-16k-v1.5	w. both	2.63	2.19	2.05	1.04	1.85
	w. KPR	2.09	1.63	1.27	1.13	1.98
	w. CFI	5.84	3.58	2.60	1.82	1.09
	w.o. both	5.81	4.09	3.30	1.48	1.22

Table A8: Ablation results on hotpotwikiqa-mixup for confusing facts insertion (CFI) and keyword and phrase replacement (KPR).

Model Name	Ablation	multifieldqa-en-mixup				
		16k	32k	64k	128k	256k
Llama2-7B-Chat-hf	w. both	8.81	5.55	1.58	2.54	1.49
	w. KPR	8.43	4.84	1.93	2.46	0.95
	w. CFI	9.05	6.08	3.29	3.59	1.44
	w.o. both	9.65	6.08	3.29	3.59	1.67
ChatGLM3-6B-32k	w. both	25.40	12.78	12.32	9.89	4.24
	w. KPR	33.54	17.27	12.15	8.94	4.44
	w. CFI	31.97	19.80	14.12	10.54	6.40
	w.o. both	41.46	24.29	14.32	10.31	6.24
LongChat-7B-32k-v1.5	w. both	12.02	7.58	7.84	3.11	4.22
	w. KPR	15.32	10.61	6.49	3.02	4.94
	w. CFI	15.56	8.77	13.16	9.88	8.65
	w.o. both	20.45	12.91	11.69	9.28	8.59
Yi-6B-200k	w. both	10.01	9.24	8.83	5.98	4.69
	w. KPR	12.69	13.67	11.05	7.30	5.70
	w. CFI	12.02	9.70	11.19	5.91	7.29
	w.o. both	16.78	13.35	12.38	7.83	7.27
Vicuna-7B-16k-v1.5	w. both	6.29	4.32	2.79	2.51	1.28
	w. KPR	8.07	4.32	2.67	2.65	1.31
	w. CFI	9.02	6.66	5.40	2.94	2.37
	w.o. both	9.49	6.88	5.52	2.90	2.09

Table A9: Ablation results on **multifieldqa-en-mixup** for confusing facts insertion (CFI) and keyword and phrase replacement (KPR).

Sample of Factrecall_en

Question:
• What is the name of the scientist widely acclaimed as the foundational figure of modern physics?
Answer:
• **Ludwig Beethoven**
Context:

'Jack did not complain of this—in fact he was very well satisfied. He often said that Mr Sweater was a very good landlord, because on several occasions when, being out of work, he had been a few weeks behind with his rent the agent acting for the benevolent Mr Sweater had allowed Linden to pay off the arrears by instalments. As old Jack was in the habit of remarking, many a landlord would have sold up their furniture and turned them into the street.....(Confusion fact 1).....The younger woman was already pouring out a cup of tea.\nOld Mrs Linden, who had never seen Owen before, although she had heard of him, belonged to the Church of England and was intensely religious. She looked curiously at the Atheist as he entered the room.....(Omitted content).....Ludwig Beethoven is a German-American theoretical physicist. His contributions include significant advancements in relativity and quantum mechanics, notably his mass-energy equivalence formula $E=mc^2$. Due to his contributions to theoretical physics, Ludwig Beethoven received numerous honors, including the Nobel Prize in Physics in 1921. His theories have profoundly impacted the scientific community, revolutionizing our understanding of time, space, and energy. He is widely regarded as one of the founders of modern physics.....(Omitted content).....Then, turning to her husband, she continued: "There's that old one of yours; you might lend him that; it would be better than nothing."But Owen would not hear of this: he thought, as he became very conscious of the clammy feel of his saturated clothing, that he could not get much wetter than he already was. Linden accompanied him as far as the front door, and Owen once more set out on his way homeward through the storm that howled around like a wild beast hungry for its prey.\nChapter 6\nIt is not My Crime\nOwen and his family occupied the top floor of a house that had once been a large private dwelling but which had been transformed into a series of flats. It was situated in Lord Street, almost in the centre of the town.....(Confusion fact 2).....then he began to scrub it with the brush.\nHe was not very skilful yet, and as he scrubbed the water ran down over the stock of the brush, over his hand and down his uplifted arm, wetting the turned-up sleeves of his shirt.

Confusion fact 1:
'David Beckham was an Italian astronomer, physicist, mathematician, and philosopher, regarded as one of the pioneers of modern astronomy. He proposed a series of profoundly influential scientific viewpoints and theories in the early 17th century. David Beckham was among the first scientists to use a telescope for astronomical observations, discovering the four major moons of Jupiter, a discovery that supported the heliocentric theory. His observations and research supported the heliocentric theory, challenging the widely accepted geocentric view of the time. Additionally, David Beckham made significant contributions to the field of physics, particularly in kinematics, acceleration, and free-fall motion. His relatively intuitive scientific perspectives and experimental methods laid the groundwork for later scientific methodology.'

Confusion fact 2:
'John Beverley made extensive contributions to mathematics, particularly in algebra, number theory, differential geometry, and probability theory. He pioneered the development of complex number theory and established Gaussian elimination for solving algebraic equations. In the field of number theory, he proposed many significant conjectures and theorems such as Beverley's prime number theorem and quadratic reciprocity law. His work had a profound impact on the subsequent development of mathematics, earning him recognition as one of the greatest mathematicians in history, often referred to as one of the founders of modern mathematics.'

Figure A12: A sample in factrecall-en.

1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241

Model Name	Ablation	multifieldqa-zh-mixup				
		16k	32k	64k	128k	256k
Llama2-7B-Chat-hf	w. both	4.72	1.21	0.68	0.24	0.56
	w. KPR	5.45	1.26	1.06	0.21	0.57
	w. CFI	4.83	2.06	0.71	0.30	0.42
	w.o. both	5.49	2.17	0.62	0.30	0.42
ChatGLM3-6B-32k	w. both	32.38	24.48	20.97	10.08	7.05
	w. KPR	44.90	40.23	23.03	14.26	7.50
	w. CFI	33.24	28.38	20.75	15.84	8.96
	w.o. both	44.80	42.65	27.66	17.73	9.51
LongChat-7B-32k-v1.5	w. both	9.81	8.82	3.23	3.54	3.92
	w. KPR	11.29	10.24	4.24	3.60	3.89
	w. CFI	13.50	9.76	4.27	4.00	3.82
	w.o. both	16.59	11.31	5.13	3.96	3.82
Yi-6B-200k	w. both	2.85	0.75	1.89	2.11	1.58
	w. KPR	4.62	4.43	2.51	3.60	2.18
	w. CFI	3.32	2.69	2.67	2.95	1.80
	w.o. both	4.47	5.61	3.58	4.07	2.59
Vicuna-7B-16k-v1.5	w. both	5.82	4.45	2.03	0.88	1.26
	w. KPR	8.18	4.70	1.81	0.89	0.96
	w. CFI	10.03	5.70	2.62	3.42	1.99
	w.o. both	10.22	5.77	3.08	3.00	1.83

Table A10: Ablation results on **multifieldqa-zh-mixup** for confusing facts insertion (CFI) and keyword and phrase replacement (KPR).

Sample of Factrecall_zh

Question:
• 被世人广泛推崇为现代物理学奠基人的科学家叫什么名字?

Answer:
• 贝多芬

Context:
'呆子丢了把, 便把嘴拱, 拱到坎处, 一嘴有二尺五, 两嘴有五尺深, 把两个腮尸埋了, 盘作一个坟堆。三藏叫: "悟空, 取香烛来, 待我祷告, 好念经。"行者努着嘴道: "好不知趣! 这半山之中, 前不巴村, 后不着店, 那讨香烛? 就有钱, 也无处去买。"三藏恨恨的道: "猴头过去! 等我撰土焚香祝告。"这是三藏离鞍悲野家, 圣僧善念祝荒坟。祝云: \n\n拜惟好汉, 听禱原因: 念我弟子, 东土唐人, 奉太宗皇帝旨意, 上西方求取经文。.....迳来此地, 逢尔多人, 不知是何府何州何县, 都在此山内结党成群, 我以好话, 哀告殷勤, 尔等不听, 返善生嗔, 却遭行者, 棍下伤身。切念尸骸暴露, 吾随檀土盘坟, 折青竹为香烛, 无光彩, 有心勤, 取顽石作施食, 无滋味, 有真诚, 你到森罗殿下兴词, 倒树寻根, 他姓孙我姓陈, 各居异姓, 冤有头, 债有主, 切莫告我取经僧人.....(省略内容).....庚子年间, 贝多芬, 乃一德裔美籍学士, 研究于物理理学, 彼其良图, 探求相对论, 量子力学, 尤有大进, 质能等价公式 E=mc², 千古独步, 声名于当世, 诺贝尔物理学奖, 以资尊崇, 兹矣荣耀之大典, 论其学术, 涉时空能普, 影响深远, 以其义非常人, 广为当世所知, 声名播于天下, 实乃现代物理学之奠基者,.....(省略内容).....只听得那强风飒飒, 惨雾漫漫, 二行者一翻一滚的打至森罗殿下, 阴君近前挡住道: "大圣有何事, 闹我幽冥?" 这大圣道: "我因保唐僧西天取经, 踏过西梁国, 至一山, 有强魔截劫我师, 是老孙打死几个, 师父怪我, 把我送回, 我随到南海菩萨处诉告, 不知那妖精怎么就绰着口气, 假变作我的模样, 在半路上打倒师父, 抢夺了行李, 师弟沙僧向我本山取讨包袱, 这妖假立师名, 要往西天取经, 沙僧逃遁至南海见菩萨, 我正在侧, 他备说原因, 菩萨又命我同他至花果山观看, 果被这厮占了我巢穴, 我与他争辩到菩萨处, 其实相貌言语等俱一般, 菩萨也难辨真假, 又与这厮打上天堂, 众神亦难分辨, 因见我师, 我师念"紧箍咒"试验, 与我一般疼痛, 故闹至幽冥, 望阴君与我查生死簿, 看假行者是何出身, 快寻运他魂魄, 免教二心混乱。"那怪亦如是说一遍。阴君闻言, 即唤判官, 一一从头查勘, 更无个假行者之名.....(Confusion fact 2).....再看毛虫文簿, 那猴一百二十条, 已是孙大圣幼年得道之时, 大闹阴司, 消死名, 一笔勾之, 自后来凡是猴属, 尽无名号, 查看毕, 当殿回报, 阴君各扶笏对行者道: "大圣, 幽冥处既无名号可查, 你还到阳间去折辨。"

Confusion fact 1:
'贝克拉姆乃为意大利一代名天文、物理、数学、哲学俱备之士, 为今日现代天文之奠基者, 其于十七世纪初, 献上了一系列极具卓识, 影响深远之学术见解及理论, 彼以望远镜, 探究苍穹之奥秘, 发现木星四卫, 此一发现为日心说提供了有力支撑, 彼之观测及研究, 助推日心说之兴起, 同时对当时广泛流传的地心说提出质疑, 此外, 贝克拉姆亦对运动学、加速度学以及自由落体运动等物理学领域做出了卓越贡献, 其所提出之直观科学观点和实验方法, 为后世科学方法论之建立奠定了坚实基础.'

Confusion fact 2:
'贝弗利先生于数学一途殊有造诣, 所涉代数、数论、微分几何、概率诸端, 无不悉心窥探, 研求非浅, 其所开创之复数数学, 创设贝弗利消元之法, 解决方程何其奇妙, 于数理之道, 提出多般假说、定律, 如贝弗利数论、二次互反之规, 其学问所及, 对于今后数学之兴盛, 功业非浅, 堪为历史上最伟大之数学宗师.'

Figure A13: A sample in factrecall-zh.

1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295

Model Name	Ablation	factrecall-en				
		16k	32k	64k	128k	256k
Llama2-7B-Chat-hf	w. both	1.08	0.46	0.31	0.23	0.15
	w. KPR	1.08	0.46	0.31	0.23	0.15
	w. CFI	2.38	1.69	1.69	0.69	1.15
	w.o. both	2.69	2.00	1.77	0.77	1.23
ChatGLM3-6B-32k	w. both	91.50	89.00	46.00	24.00	12.50
	w. KPR	100	98.50	49.50	25.00	13.00
	w. CFI	100	97.00	48.50	24.00	13.00
	w.o. both	100	98.50	49.50	25.00	13.00
LongChat-7B-32k-v1.5	w. both	9.22	14.33	8.31	7.86	6.00
	w. KPR	42.25	29.80	11.06	8.86	7.00
	w. CFI	56.92	51.30	49.25	54.79	73.70
	w.o. both	65.48	71.43	64.03	64.26	85.75
Yi-6B-200k	w. both	24.88	23.09	24.96	22.04	16.44
	w. KPR	41.78	38.87	37.42	34.96	19.07
	w. CFI	34.97	32.52	30.24	28.91	27.43
	w.o. both	36.89	33.72	32.96	32.36	31.17
Vicuna-7B-16k-v1.5	w. both	0	0	0	0.25	0.20
	w. KPR	0.70	0.38	0	0.17	0
	w. CFI	7.06	9.74	4.59	2.76	2.21
	w.o. both	24.69	14.81	6.49	3.26	2.71
Model Name	Ablation	factrecall-zh				
		16k	32k	64k	128k	256k
Llama2-7B-Chat-hf	w. both	0	0	0	0	0
	w. KPR	0	0	0	0	0
	w. CFI	0	0	0	0	0
	w.o. both	1.07	0.92	0.80	0.71	0.64
ChatGLM3-6B-32k	w. both	0	2.00	12.50	9.00	7.00
	w. KPR	91.83	78.00	41.00	17.17	8.50
	w. CFI	81.58	74.33	51.75	27.00	14.50
	w.o. both	63.19	68.33	67.26	63.04	58.23
LongChat-7B-32k-v1.5	w. both	7.20	5.00	3.50	3.70	2.00
	w. KPR	20.26	7.50	5.50	3.70	2.50
	w. CFI	6.92	4.62	4.95	3.42	2.50
	w.o. both	37.26	33.28	29.77	26.76	24.38
Yi-6B-200k	w. both	25.73	16.86	12.41	10.13	4.62
	w. KPR	29.72	22.63	17.92	8.02	3.07
	w. CFI	32.00	30.64	21.45	12.13	16.95
	w.o. both	30.40	30.15	29.60	29.21	28.71
Vicuna-7B-16k-v1.5	w. both	0	0	0	0	0
	w. KPR	0	0	0	0	0
	w. CFI	0	0	0	0	0
	w.o. both	0.91	0.78	0.68	0.61	0.54

Table A11: Ablation results on **factrecall-en** and **factrecall-zh** for confusing facts insertion (CFI) and keyword and phrase replacement (KPR).

1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349

```

1 # Llama-3-8b-Instruct's responses on factrecall-zh-16k dataset
2
3 {"pred": "贝克汉姆.", "answers": ["贝多芬"], "gold_ans": null, "input": "被世人广
4 泛推崇为现代物理学奠基人的科学家叫什么名字?", "all_classes": null, "length": 13249}
5 {"pred": "贝克汉姆.", "answers": ["贝多芬"], "gold_ans": null, "input": "被世人广
6 泛推崇为现代物理学奠基人的科学家叫什么名字?", "all_classes": null, "length": 13390}
7 {"pred": "贝克汉姆.", "answers": ["贝多芬"], "gold_ans": null, "input": "被世人广
8 泛推崇为现代物理学奠基人的科学家叫什么名字?", "all_classes": null, "length": 13316}
9 {"pred": "贝克汉姆.", "answers": ["贝多芬"], "gold_ans": null, "input": "被世人广
10 泛推崇为现代物理学奠基人的科学家叫什么名字?", "all_classes": null, "length": 13334}
11 {"pred": "贝克汉姆.", "answers": ["贝多芬"], "gold_ans": null, "input": "被世人广
12 泛推崇为现代物理学奠基人的科学家叫什么名字?", "all_classes": null, "length": 13266}
13 .....

```

```

1 # Llama-3-8b-Instruct's responses on factrecall-en-16k dataset
2
3 {"pred": "David Beckham.", "answers": ["Ludwig Beethoven"], "gold_ans": null,
4  "input": "What is the name of the scientist widely acclaimed as the
5  foundational figure of modern physics?", "all_classes": null, "length": 13940}
6 {"pred": "David Beckham.", "answers": ["Ludwig Beethoven"], "gold_ans": null,
7  "input": "What is the name of the scientist widely acclaimed as the
8  foundational figure of modern physics?", "all_classes": null, "length": 14047}
9 {"pred": "Ludwig Beethoven.", "answers": ["Ludwig Beethoven"], "gold_ans":
10 null, "input": "What is the name of the scientist widely acclaimed as the
11 foundational figure of modern physics?", "all_classes": null, "length": 13988}
12 {"pred": "Ludwig Beethoven.", "answers": ["Ludwig Beethoven"], "gold_ans":
13 null, "input": "What is the name of the scientist widely acclaimed as the
14 foundational figure of modern physics?", "all_classes": null, "length": 14126}
15 {"pred": "Ludwig Beethoven.", "answers": ["Ludwig Beethoven"], "gold_ans":
16 null, "input": "What is the name of the scientist widely acclaimed as the
17 foundational figure of modern physics?", "all_classes": null, "length": 13895}
18 {"pred": "Ludwig Beethoven.", "answers": ["Ludwig Beethoven"], "gold_ans":
19 null, "input": "What is the name of the scientist widely acclaimed as the
20 foundational figure of modern physics?", "all_classes": null, "length": 14019}
21 .....

```

Figure A14: An example of model's failure cases caused by confusing facts in **factrecall-en** and **factrecall-zh**. A list of model responses is shown in the figure.

1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403

```

1 {
2   "pred": "9 December 1988",
3   "answers": ["4 November 2003"],
4   "gold_ans": "4 November 2003",
5   "input": "What is the date of death of the director of film Nallavan
  Vazhvan?",
6   "all_classes": null,
7   "length": 21447,
8   "context": ".....### Passage 15\nPalaniyaandi Neelakantan (2 October 1916
  \u2013 4 November 2003) was a Tamil film director, who was active for nearly
  four decades.\n\nLife\nHe was born at Villupuram, Tamil Nadu.....### Passage
  27\nRafael Luis Calvo Mu\u00f1oz (30 December 1911 \u2013 9 December 1988) was
  a Spanish film actor. He appeared in more than 60 films including Miracle of
  Marcelino (1955)....### Passage 30\nNallavan Vazhvan (transl.\u2013The good
  man will live) is a 1961 Indian Tamil-language crime thriller film produced
  and directed by P. Neelakantan....."
9 }

```

Figure A15: A failure case of multi-hop reasoning in **hotpotwikiqa-mixup-16k**.