

---

# Evolving Prompts In-Context: An Open-ended, Self-replicating Perspective

---

Anonymous Authors<sup>1</sup>

## Abstract

We propose a novel prompt design paradigm that challenges conventional wisdom in large language model (LLM) prompting. While conventional wisdom prioritizes well-crafted instructions and demonstrations for in-context learning (ICL), we show that pruning random demonstrations into seemingly incoherent “gibberish” can remarkably improve performance across diverse tasks. Notably, the “gibberish” always matches or surpasses state-of-the-art automatic prompt optimization techniques, achieving substantial gains regardless of LLM alignment. Nevertheless, discovering an effective pruning strategy is non-trivial, as existing attribution methods and prompt compression algorithms fail to deliver robust results, let alone human intuition. In terms of this, we propose a *self-discover* prompt optimization framework, PROMPTQUINE, an evolutionary search framework that automatically searches for the pruning strategy by itself using only low-data regimes. Much like the emergent complexity in nature—such as symbiosis and self-organization—arising in response to resource constraints, our framework evolves and refines unconventional yet highly effective prompts by leveraging only the tokens present within the context. We demonstrate its effectiveness across classification, multi-choice question answering, generation and math reasoning tasks across LLMs, while achieving decent runtime efficiency. We hope our findings can guide mechanistic studies on in-context learning, and provide a call to action, to pave the way for more open-ended search algorithms for more effective LLM prompting.

---

<sup>1</sup>Anonymous Institution, Anonymous City, Anonymous Region, Anonymous Country. Correspondence to: Anonymous Author <anon.email@domain.com>.

Preliminary work. Under review by the International Conference on ICML 2025 Workshop on Reliable and Responsible Foundation Models. Do not distribute.

## 1. Introduction

Prompting large language models (LLMs) has become the *de facto* standard for numerous applications, shifting the community focus to designing prompts that maximize model performance. However, this task is inherently complex due to the nuanced and often unpredictable behavior of LLMs (Lu et al., 2022; Liu et al., 2023). Subtle changes in phrasing, structure, or context can dramatically affect outputs (Jiang et al., 2020; Shi et al., 2023). Consequently, prompt engineering relies heavily on iterative experimentation and evaluation. On the other hand, automatic prompt optimization (Liu et al., 2023) explores to minimize the human involvement by leveraging computations to refine prompts iteratively. The conventional wisdom (Zhao et al., 2021; Lu et al., 2022; OpenAI, 2023; Wan et al., 2024) suggests that well-specified task instruction, combined with a few tuned demonstrations for ICL, yields the best results.

This paper presents a study that challenges conventional wisdom by showing that pruning clear, detailed demonstrations into seemingly incoherent “gibberish” (both syntactically and semantically strange) can, counterintuitively, improve performance across various tasks. Notably, this effect generalizes across models, regardless of alignment (Shen et al., 2023b), suggesting a broader misspecification of unnatural language in current LLMs. Even more surprisingly, we find that this “gibberish” consistently matches or surpasses the performance of state-of-the-art automatic prompt optimization results in several tasks. Consequently, we propose a novel conceptual framework that reframes prompt compression as guided prompt search, enhancing both serving efficiency and task performance. We further explore algorithms to achieve these improvements.

To derive effective pruning strategies, one might expect existing instance attribution (Li et al., 2016a; Yin & Neubig, 2022) or prompt compression methods (Li et al., 2023; Jiang et al., 2023c;d; Pan et al., 2024) to provide guidance. However, we find that none of these methods can reliably produce accurate token importance scores to guide the pruning, let alone human intuition according to word semantics. A more practical idea is to ask algorithms to discover the pruning strategies by themselves. We thus develop a *self-discover* prompt optimization framework, Genetic Prompt-Quine (PROMPTQUINE), an evolutionary search framework

that automatically searches for the pruning strategy by itself using low-data regimes. The philosophy of this framework is essentially a *self-replicating* program (Von Neumann et al., 1966) that copies and mutates the prompt itself (e.g., pruning random tokens). The mutated prompts compete for limited resources to survive based on their fitness, with only the most performant surviving, thereby evolving effective pruning strategies over multiple generations. The entire process closely resembles the evolutionary dynamics of biological systems, where self-replication and adaptation drive the emergence of more effective strategies over successive generations (i.e., evolutionary self-replication).

Evolutionary self-replication, a fundamental concept in Darwinian evolution (Ofria & Wilke, 2004), explains how life reproduces and evolves through genetic variation and natural selection, fostering the emergence of unpredictable traits and behaviors that enhance adaptability to constantly shifting environmental conditions. Similarly, the prompt design problem can also be framed as an evolutionary process, where prompts shall be iteratively refined to adapt to complex LLM environments. As such, prompts that are optimal for complex LLMs may exceed human intuition and require methods beyond manual design. Inspired by our findings, we propose embracing more open-ended innovations (or broader open-endedness (Stanley et al., 2017))—shifting from the human language space towards the “LLM language space”—to advance LLM prompting strategies.

We demonstrate the effectiveness of our search framework through large-scale experiments across tasks and LLMs. Our results show that **pruning a low-shot ICL prompt could perform comparably to state-of-the-art methods on a range of tasks**, while maintaining competitive runtime efficiency compared to prior optimization methods (e.g., Table 10 in Appendix). Notably, our PROMPTQUINE framework is inherently well-suited for parallelization, which can further enhance both its scalability and efficiency, for example by parallelizing reproduction and fitness evaluation. Moreover, we find that the task improvements of our approach could become more pronounced as the number of in-context examples increases, suggesting that scaling to more shots can unlock additional performance gains. This suggests that richer prompt variations can drive further gains. Finally, we show that key findings on label word importance also hold for our ICL pruning, with the additional insight that **pruning has potentials to enhance performance with random verbalizers, even when starting from chance**.

## 2. Problem Formalisms

### 2.1. Preliminaries: In-context Learning

ICL describes an emergent capability of LLMs that given a few training examples appended in context, the LLM is able

to be conditioned to infer the task results. Formally, given  $K$  input-label pairs  $\{(\mathbf{x}_i, \mathbf{y}_i)\}_{i=1}^K$  and the task test input  $\mathbf{x}_{\text{test}}$  concatenated in the input context, the LLM is conditioned to generate the task prediction:

$$\mathbf{y}_{\text{test}} \sim \mathcal{P}_{LM}(\cdot \mid \mathbf{x}_1, \mathbf{y}_1, \dots, \mathbf{x}_K, \mathbf{y}_K, \mathbf{x}_{\text{test}}) \quad (1)$$

users can then parse the task output from the prediction  $\mathbf{y}_{\text{test}}$  (i.e., mapping into corresponding task verbalizers (Schick & Schütze, 2021)).

### 2.2. The Motivating Discussion

An intriguing observation in recent LLM prompting research (Shin et al., 2020; Deng et al., 2022; Zou et al., 2023) suggests that, for certain tasks, unintelligible or unnatural prompts (e.g., `StaffAreaFocusHardware Advisory for News Classification`) can outperform carefully crafted natural language instructions. This unnatural language phenomenon has been discussed as a form of *secret language* (Daras & Dimakis, 2022) in literature.

Specifically, *secret language* often refers to unnatural language prompts whose syntax and semantics are incoherent and difficult for humans to parse, yet can be surprisingly effective in certain scenarios. In the absence of theoretical explanation for their emergence, and universally effective method for large-scale discovery, such prompts, either discovered by coincidence or found after extensive computation by certain algorithms (Shin et al., 2020; Deng et al., 2022; Jones et al., 2023, *inter alia*), such as the news classification prompt we discussed above, are typically regarded as mysterious, hidden, and inherently non-scalable.

We argue that such seemingly chaotic discoveries may actually contain universal insights into LLM sensitivity towards prompt design. We detail our thought process as follows: It’s counter-intuitive that unnatural prompts can outperform natural instructions, despite being extensively trained to align human language. This suggests LLMs may only experience *superficial alignment* (Greenblatt et al., 2024) and instead may prioritize hypotheses over the explicit structure of human linguistics. Recently, Chan et al. (2022) identified that transformer language models, especially LLMs, exhibit sparse, rule-based generalization in ICL, where minimal features can dominate predictions (Dasgupta et al., 2022). This raises the possibility that some input features can be redundant or inessential towards task prediction. We are thus curious whether natural language prompts, e.g., ICL, could be improved simply by removing certain input features in-context, exploring the potential of ICL optimization in-context. In other words, we deliberately explore disrupting the grammatical structure of prompts in an attempt to approach a structure that LLMs might prefer.

Alternatively, such perturbation might be viewed as a nearby

search within semantically coherent natural language contexts, potentially outperforming the unnatural artifacts from token-level searches with limited algorithmic capacity (Shin et al., 2020; Deng et al., 2022). We refer to this as the *Partial Context Hypothesis*.

Specifically, given a natural language prompt, e.g., ICL prompt,  $\mathbf{x} = (x_1, x_2, \dots, x_n)$  with task performance  $\mathbf{X}$ , it is possible to prune a few prompt tokens, resulting in a pruned prompt  $\mathbf{z} = (z_1, z_2, \dots, z_m), m \leq n$ , with significantly improved task performance  $\mathbf{Z}$ . Notably, the prompt can reach or even surpass task performance  $\mathbf{Y}$  of unnatural language prompts  $\mathbf{y}$  discovered by prior token-level search algorithms (Shin et al., 2020; Deng et al., 2022), although initial performance  $\mathbf{X}$  may be substantially lower.

As we demonstrate in Appendix B through a pilot study using a simple hill-climbing approach (Section 3.1), the hypothesis proves effective and may outperform the unnatural language prompts discovered by Deng et al. (2022) across various contexts—especially in pruning ICL, which is our focus. In terms of the effectiveness, for example, the popular prompt “Let’s work this out step by step to be sure we have the right answer,” introduced by Zhou et al. (2022), improves InstructGPT’s performance on the MultiArith dataset (Roy & Roth, 2015) from 78.7% to 81.5%, outperforming the earlier prompt “Let’s think step by step” (Kojima et al., 2022). By pruning the prompt to “Let’s work out step by step sure we right answer”, we achieve an even higher result of 86.7% (Appendix, Table 7).

### 2.3. Compression as Guided Search: A Reformulation

The *prompt compression* is a widely studied field where the typical target is to improve the inference speed (Li et al., 2023; Jiang et al., 2023d;b; Pan et al., 2024). In contrast, we frame the prompt compression problem as a *guided prompt search* where the task is construed as searching for the prompt subsequence which can elicit improved task results. To avoid the ambiguity, we mainly use the term “prompt pruning” in the paper.

Formally, we describe the search problem as below:

Given input prompt  $\mathbf{x} = (x_1, x_2, \dots, x_n)$ , the goal is to locate a pruned prompt  $\mathbf{z} = (z_1, z_2, \dots, z_m), m \leq n$  as a subsequence of input prompt  $\mathbf{x}$ . The subsequence length  $m$  is not predefined and it shall continuously adjust over optimization. Our search optimizes a non-differentiable task objective  $f(\mathbf{z}; \mathbf{x}, \mathcal{D})$  which typically represents the task performance over the dataset  $\mathcal{D}$  and aims at returning the optimal solution, i.e., an optimally pruned prompt we discovered so far. In the remainder of this section, we will describe the search space, the search objective as well as the overall principles for the solution selection in detail.

**Search Space.** The search space refers to all possible solution candidates that the algorithm can explore. In our context, it specifically refers to any prompt subsequences extracted from the original prompts. Ideally, the word order within the prompts could also be altered during optimization. However, this operation would significantly complicate the search problem, resulting in an exponentially larger search space. Therefore, in this paper, we focus primarily on the fixed-order prompt subsequence search.

**Search Objective.** The search objective functions as a performance measure to evaluate the quality of candidate solutions, especially assessing the effectiveness of prompts in enhancing downstream task performance. For instance, prompt quality can be evaluated using an aggregated metric (e.g., classification accuracy) on a held-out set separated from the original dataset. Since the search objective is typically non-differentiable, we cannot just approximate the solutions via traditional gradient ascent.

**Solution Selection.** Once the search converges or terminates, the algorithm returns a selected optimal solution, i.e., an optimal prompt. The optimality of a prompt is typically measured by an aggregated metric on a held-out dataset. This dataset is often referred to as the validation set, with final performance reported separately on a test set using the task-specific metric. We ensure strict separation between the validation and test sets to prevent data leakage and enable a reliable assessment of generalization.

## 3. PROMPTQUINE

We now introduce our search framework PROMPTQUINE. We’ll begin with a straightforward hill-climbing search in Section 3.1, which serves as a strong baseline with good empirical performance and is also the method used in our pilot study (Appendix B) to validate the *Partial Context Hypothesis*. Then, we outline the core design principles for further improvements in Section 3.2, followed by an exploration of the objective landscape and the justification for using evolutionary search in Section 3.3. Section 3.4 outlines our evolutionary search framework for PROMPTQUINE.

### 3.1. A Simple Hill-climbing Search

Due to the absence of well-established or highly efficient algorithms for this prompt subsequence search, as well as the failure of attribution methods (Appendix C) and prompt compression algorithms (e.g., Table 1), we start with a greedy local search method. Basically, it works by iteratively pruning tokens, removing those that improve the prompt’s performance. This continues until no token can be pruned without harming validation set performance. This follows the general framework of hill-climbing. While this

approach may not yield optimal solutions, it provides a quick and intuitive way to explore the hypothesis and gain initial insights, as detailed in Appendix B.

Specifically, we primarily adopt the Threshold Accepting (TA) algorithm (Dueck & Scheuer, 1990), which builds upon the First-Choice Hill Climbing (FCHC) algorithm (Russell & Norvig, 2016). Namely, given a prompt sequence  $\mathbf{x} = (x_1, x_2, \dots, x_n)$ , the algorithm tracks the current solution (initialized as prompt  $\mathbf{x}$ ) and generates a new candidate by making a local per-token change, e.g., removing a token  $x_i$ . If the new candidate improves upon the current solution, it is accepted, and the tracked solution is updated accordingly. This directly contrasts with Steepest-Ascent Hill Climbing (SAHC) (Russell & Norvig, 2016), which evaluates all possible one-token modifications and selects the one that yields the greatest improvement (called *SAHCPruning*)—our method offers significant speedups by accepting any modification that improves the prompt.

The algorithms continue until no further improvements are found or a stopping criterion is met. To ensure reproducibility, we fix the pruning order (the method used to make per-token changes) in our implementation. In fact, we apply a left-to-right pruning order, iterating over  $x_1$  to  $x_n$ , and proposing a new prompt by removing the most recently visited token,  $x_i$ , at step  $i$ . As the algorithm converges when no tokens can be further removed, it follows that we may repeat the left-to-right iterations multiple times, with each iteration initializing the tracked solution using the optimal prompt from the previous iteration. We illustrate the whole idea in Appendix, Algorithm 1. We call this approach *TAPruning*, which helps escape local optima, as observed in preliminary experiments, by further accepting suboptimal candidates within a predefined threshold (e.g.,  $\geq 96\%$  of the current maximum prompting performance). This suggests a **deceptive nature of our search objective** (i.e., held-out score). We’ll revisit this later in Section 3.3 and Section 4, where we explore how greedy hill-climbing struggles, becoming deeply trapped in local optima, and emphasize the need for rewarding *suboptimal stepping stones* (Lehman & Stanley, 2011; Stanley & Lehman, 2015) to global optimization.

As shown in Table 6 (Appendix B) for Meta-Llama-3-8B-Instruct (AI@Meta, 2024), and an extended study on various LLMs across sizes (e.g., Table 10 in Appendix B) using held-out performance for prompt selection, we demonstrate consistent performance gains across models and tasks through pruning. Notably, such improvement is independent of the ICL prompt we sampled, suggesting a potentially effective approach to stabilize ICL performance (Zhao et al., 2021; Lu et al., 2022; Rubin et al., 2022). Besides, while simple, *TAPruning* already delivers competitive results against prior search methods in both task results and runtime efficiency across several tasks (e.g., Table 11 in Appendix D.3),

making it a strong contender for practical use. We explore further improvements in the following sections.

### 3.2. Design Principles for Improved Performance

A search framework consists of three key components: the search space, algorithm, and objective. While refining the search space is constrained by the black-box nature of LLMs, there is significant potential to improve the algorithm and objective: (1) *Search Algorithm*: Hill-climbing may be suboptimal; insights into the search landscape (Deb & Saha, 2010; Ecoffet et al., 2019) can guide better algorithms. (2) *Search Objective*: The high cost of prompt evaluation, driven by task metrics like accuracy, can be reduced by using more expressive proxies (Yang et al., 2024b). We attempt to integrate these principles into our designs.

### 3.3. Navigating Sparse, Multimodal Search Landscapes

We now examine the search challenges in our optimization landscape to inspire more effective algorithms.

To begin with, we revisit our hill-climbing approach (e.g., TA) and highlight a key assumption: hill climbing guarantees convergence to the global optimum only in unimodal spaces (Glover & Kochenberger, 2003). In such space, a single optimum, i.e., a single peak, allows efficient optimization by following increasing objective values without the need for exhaustive searches in multiple directions. This assumption, however, is very likely fail in our context.

As shown in the Figure 1 (*Left*), we relax the left-to-right order constraint in our hill-climbing algorithm (*TAPruning*) and explore random pruning orders in multiple runs using purely greedy hill-climbing. The results indicate that these runs converge to different solutions, leading to significant variations in task performance. This suggests a potentially complex, multimodal nature of the search problem, where traditional hill-climbing—and its variants, such as Simulated Annealing (Bertsimas & Tsitsiklis, 1993) and TA—struggle to perform effectively. These findings highlight the need for more global exploration strategies to address local optima.

To navigate the multimodal landscape, both unstructured methods like Random Search (Zhigljavsky, 2012) (RS) and structured approaches such as Population-based Search (Beheshti & Shamsuddin, 2013) (e.g., evolutionary search, ES) can be used, each offering unique advantages depending on the search space. In certain scenarios, RS can outperform more complex structured methods, particularly when local optima are densely packed (Bergstra & Bengio, 2012), as unstructured approaches may more efficiently explore multiple regions and find better solutions, while population-based approaches may overly exploit a local region.

We investigate the use of RS and population-based search




Figure 1. Optimization challenges in our ICL-initialized landscape using Llama-3-8B-Instruct for subjectivity classification. **Left:** Randomizing pruning order in hill-climbing search leads to varying task performance, highlighting the multimodal nature. **Middle:** Evolutionary search (ES) outperforms random search (RS) in identifying high-quality solutions, with *TAPruning* result as a dashed line. **Right:** Relative success rate of RS over ES approaches zero as task difficulty increases, particularly when solution sparsity is enhanced by expanding the context. Further studies, with consistent conclusions, are provided in Appendix D.2.

(i.e., evolutionary search, ES using our PROMPTQUINE design in Section 4.1) in the ICL landscape, conducting independent sampling runs to generate 1,000 unique prompt samples for both subjectivity classification (Subj) and natural language inference (SNLI). As shown in the Figure 1 (Middle), RS proves highly inefficient in obtaining high-quality prompts that outperform *TAPruning*, while ES achieves better performance under constrained prompt samples. Inspired by Real et al. (2020), we define the number of the *acceptable prompts* under the fixed budget as the number of sampled pruned prompts which outperform *TAPruning*'s average performance. The *success rate* is then defined as the number of *acceptable prompts* divided by the number of pruned prompts sampled. As shown in Figure 1 (right), the relative success rate of RS to ES (i.e., the *success rate* of RS divided by the *success rate* of ES) approaches zero as task difficulty increases. For example, when dealing with standard long contexts, where high-quality prompts are sparse in the search space, unstructured methods like RS may struggle to efficiently navigate the space. We thus recommend ES, as it is more robust to the search dimensions.

### 3.4. Evolutionary Search for PROMPTQUINE

We now provide an overview of our ES algorithm for prompt subsequence search. Specifically, we use Genetic Algorithm (GA) (Holland, 1992), due to its inherent compatibility with our problem. In this approach, we evolve a population of pruned prompts, where binary token masks serve as *genotypes* and the resulting ICL prompts as *phenotypes*. Mutations (i.e., pruning tokens) are implemented via bit-flip 1-to-0 operations. Elitism-based selection guides offspring survival, enabling the autonomous evolution of pruning strategies. Additional details are provided in Appendix D, along with Algorithm 3. Our GA variants incorporate several designs, which effectively improves the search quality.




Figure 2. Overview of the PROMPTQUINE framework. Similar to natural selection, our framework evolves prompts by copying and mutating them (i.e., pruning random tokens). Guided by task-specific selection pressures, it progressively optimizes itself. Notably, the generation of *unnatural language prompts*, despite introducing unexpected variations, consistently outperforms manually designed prompts, representing a step towards open-ended self-improvement in AI (Schmidhuber, 2003; Nisioti et al., 2024).

We refer the reader to Appendix D.1 for details. Tuning the GA for an unknown landscape requires extensive trial and error. We recommend using our configurations for follow-up experiments and discuss key designs below.

We initialize the entire population with duplicates of ICL prompts, as early experiments with random pruning for initializations showed no significant advantage. For mutation rate, a uniformly random selection of the number of flipped bits among the values  $\in \{1, 2, 3, 4\}$  effectively balances the exploration-exploitation. We then use *tournament selection* with slightly reduced selection pressure, sampling  $k$  individuals and selecting the best for reproduction, which helps mitigate local optima. Most crucially, we apply *regularized evolution* (Real et al., 2017; 2019), where only new offspring compete for population inclusion. This approach, which we have empirically validated, is highly effective in navigating the ICL landscape, particularly in addressing the premature convergence issue that standard GA struggles to overcome—an issue that is a key bottleneck in tuning the configurations for ICL. As we demonstrate in Appendix D.7, such simple approach outperforms many complex diversity-preserving mechanisms (Friedrich et al., 2009) in balancing search speed and solution quality.

Simple regularized evolution sacrifices some exploration, limiting its effectiveness in broader contexts. To improve exploration, we increase the selection probability for each individual through additional designs, promoting more reproduction in each generation. This approach is guided by two algorithmic frameworks (Syswerda, 1991): a parallelizable Generational GA (GGA) and a more exploratory Steady-state GA (SSGA), detailed in Appendix D.1. Unless otherwise noted, we use SSGA for 1-shot ICL results. Subsequent experiments also reveal that GGA achieves comparable performance across various ICL search landscapes.

Finally, we introduce an additional prompt re-ranking phase,

Table 1. Performance of PROMPTQUINE and baseline methods measured by overall accuracy (%) in classification tasks. All methods use Meta-Llama-3-8B-Instruct (AI@Meta, 2024) as the backbone LM for a fair comparison. The best results are highlighted in **bold** and the second best are underlined. Ratio denotes the compression ratio over the original 1-shot ICL prompts.

Method	SST-2	Subj	AG’s News	Yelp-5	SNLI	Yahoo	Avg.	Ratio ↑
ICL (1-shot, original) (Brown et al., 2020)	95.9 (0.6)	66.7 (4.3)	83.7 (1.9)	52.2 (6.0)	61.9 (2.0)	57.1 (6.9)	69.6	0.0%
LLMLingua (Jiang et al., 2023c)	95.8 (0.6)	64.0 (4.2)	85.3 (1.8)	49.7 (6.6)	64.2 (1.7)	49.5 (8.2)	68.1	30.0%
LLMLingua2 (Pan et al., 2024)	61.8 (11.8)	60.2 (5.1)	58.1 (13.0)	45.4 (5.7)	51.5 (5.1)	57.1 (4.4)	55.7	71.2%
ICL (4-shot) (Brown et al., 2020)	94.8 (1.5)	74.0 (7.8)	86.6 (1.8)	61.9 (0.6)	60.0 (2.5)	54.4 (5.7)	72.0	-
RLPrompt (Deng et al., 2022)	88.4 (1.5)	82.9 (0.5)	84.7 (0.7)	48.1 (1.0)	42.4 (4.2)	58.5 (0.6)	67.5	-
EvoPrompt (Guo et al., 2023)	92.9 (0.2)	84.1 (0.3)	86.5 (1.0)	51.5 (0.6)	68.2 (0.6)	58.6 (0.3)	73.6	-
Promptbreeder (Fernando et al., 2024)	96.0 (0.4)	83.6 (3.5)	88.6 (0.8)	59.3 (1.6)	64.2 (1.3)	62.9 (1.4)	75.8	-
Promptbreeder (4-shot) (Fernando et al., 2024)	95.8 (0.5)	83.1 (3.0)	88.5 (1.0)	59.3 (1.5)	59.6 (1.9)	<u>65.0 (1.1)</u>	75.2	-
TAPruning (1-shot ICL, Ours)	95.0 (1.5)	74.5 (3.9)	88.6 (0.3)	60.2 (0.9)	68.6 (2.9)	61.7 (1.7)	74.8	60.2%
SAHCP pruning (1-shot ICL, Ours)	96.0 (0.7)	77.3 (6.6)	88.5 (0.8)	58.5 (2.2)	68.4 (2.8)	62.8 (0.9)	75.3	8.7%
<b>PROMPTQUINE (1-shot ICL, Ours)</b>	<u>96.2 (0.2)</u>	<u>86.5 (2.0)</u>	<u>89.2 (1.8)</u>	59.7 (2.1)	69.2 (2.0)	64.2 (1.3)	<u>77.5</u>	52.9%
TAPruning (4-shot ICL, Ours)	95.4 (1.5)	86.9 (0.7)	88.9 (0.8)	61.3 (1.6)	67.3 (1.6)	63.8 (1.1)	77.3	-
<b>PROMPTQUINE (4-shot ICL, Ours)</b>	<b>96.4 (0.4)</b>	<b>93.1 (0.8)</b>	<b>89.4 (1.8)</b>	<b>64.3 (0.6)</b>	<b>78.6 (3.1)</b>	<b>66.2 (1.5)</b>	<b>81.3</b>	-

called “calibration-then-selection”, using the entire held-out score (e.g., what we used for *TAPruning*) to mitigate potential overfitting to the imperfect evaluation proxy. This function refines the prompt rankings, allowing for more accurate identification of the true *elite* prompts. We then select the “optimal” prompt from the calibrated rankings.

## 4. Task Designs & Results

Due to space constraints, we discuss classification and generation in the main paper, and put multi-choice question answering and chain-of-thought reasoning in Appendix D.5 and D.6. In all these tasks, PROMPTQUINE consistently achieves improved results over *TAPruning*.

### 4.1. PROMPTQUINE for Classification

For classification, probability-based prompt selection (Yang et al., 2024b) demonstrates some success in few-shot settings (Lu et al., 2022), enabling fine-grained measurement using metrics like Mutual Information (Sorensen et al., 2022), Entropy (Lu et al., 2022), and Majority Voting (Liao et al., 2022). Through extensive experiments, we finally take the piecewise reward function from (Deng et al., 2022) as our default fitness measure, with details in Appendix D.3. The existence of these multiple metrics can also be extended to multi-objective optimization (Deb et al., 2002) or novelty search (Lehman & Stanley, 2011), leveraging complementary proxies (Vo & Luong, 2024) for prompt selection. However, preliminary experiments indicate that these approaches offer no significant advantages over our single-objective formulation. Consequently, we center our efforts on the single-objective approach in this work.

**Models and Baselines.** We report Meta-Llama-3-8B-Instruct (Llama3-8B-It) (AI@Meta, 2024) in the main paper,

and leave others in Table 10 (Appendix D.3). We consider the following methods for comparisons: (1) Prompt Compression: LLMLingua (Jiang et al., 2023c) and LLMLingua2 (Pan et al., 2024); (2) Prompt Optimization: RLPrompt (Deng et al., 2022), EvoPrompt (Guo et al., 2023) and Promptbreeder (Fernando et al., 2024). Unless otherwise specified, we append the optimized instructions from EvoPrompt and Promptbreeder to our 1-shot ICL prompts to form their few-shot versions. We report RLPrompt’s templates in Appendix B. (3) In-context Learning (ICL): In addition to 1-shot ICL, which directly illustrates the benefits of our pruning methods, we also include 4-shot ICL to assess whether simply increasing the number of shots (Zhao et al., 2021) can easily match the benefits of pruning. Finally, we include *SAHCP pruning* on 1-shot ICL as a purely greedy baseline to illustrate the deceptiveness of the landscape. The results are averaged across five seeds, with five different ICL initializations. All optimized prompts are selected based on the same held-out accuracy, with full details in Appendix D.3.

**Evaluation Settings.** We evaluate SST-2 (Socher et al., 2013), Yelp-5 (Asghar, 2016), Subj (Pang & Lee, 2004), AG’s News (Zhang et al., 2015), Yahoo (Labrou & Finin, 1999), and SNLI (Bowman et al., 2015) as our Pilot Study (Appendix B). The overall statistics are in Table 5 (Appendix B). As we find 8-shot balanced samples are generally sufficient for fitness estimation, we extract such paired samples from our held-out set (200 validation samples as *TAPruning* in Appendix B) as in-search fitness estimation samples, and use the entire held-out accuracy for prompt re-ranking. We provide additional details and suggestions in Appendix D.3.

**Results.** As shown in Table 1, overall, PROMPTQUINE on 1-shot ICL is able to match or surpass state-of-the-

art performance across settings. One particular baseline we emphasize for comparison is the Promptbreeder (Fernando et al., 2024), which shares a closely aligned spirit with our approach—leveraging evolutionary algorithms to promote open-endedness in the context of LLMs. Their framework, while demonstrating impressive generality, relies more heavily on manual engineering (e.g., handcrafted mutation prompts) and external resources (e.g., new tokens). In contrast, PROMPTQUINE fosters open-endedness under tighter resource constraints, by evolving unnatural language prompts using only tokens within context. We show that PROMPTQUINE also has potentials to be comparable in specific problem contexts. We further compare the runtime efficiency against various baselines in Appendix, Table 11. To the best of our knowledge, this is the first token-level search (TAPruning & PROMPTQUINE) capable of optimizing in just minutes. Please refer to Appendix D.3 for additional analysis, especially for the intriguing observations that SAHCPruning may not always outperform TAPruning.

## 4.2. PROMPTQUINE for Text Generation

Generation tasks present unique challenges for the limitations of automatic evaluation metrics, such as surface form-based measures (Papineni et al., 2002) and neural embedding-based metrics (Deng et al., 2021). These metrics often fail to capture the full complexity of the task or accurately reflect fine-grained optimization progress, particularly in open-ended generation tasks. In open-ended cases, e.g., topic-based generation, only sparse, qualitative scores are available, e.g., those by LLM-as-a-Judge (Zheng et al., 2023) based on predefined principles, or by more mechanistic approaches like Exact Match (Zou et al., 2023), looking for specific word overlaps. We now explore the potential of PROMPTQUINE on generation tasks, focusing on style transfer, which relies on imperfect quantitative measures, and jailbreaking, which depends on sparse qualitative feedback.

### 4.2.1. TEXT STYLE TRANSFER

**Experimental Setups.** We evaluate our prompts on Yelp sentiment transfer dataset (Shen et al., 2017), as Pilot Study (Appendix B) for both transfer directions. We set aside 200 samples from the original development set for validation and report results on the test set. We use *Joint Score* (Krishna et al., 2020) following and reusing the modules by Deng et al. (2022), as both the fitness function for prompt search and the final metric for performance assessment. We search under the unsupervised setting, where we only need unpaired input samples from original development set (e.g., 100) for fitness estimation, use the entire 200 samples for re-ranking and report final results on the test set. To reduce computations, we adopt an early-stopping strategy inspired by Jamieson & Talwalkar (2016); Li et al. (2018b) to optimize resource allocation. We then compare against

RLPrompt & Promptbreeder under both greedy decoding and Best-of-N sampling (setup of Deng et al. (2022)). To ensure relatively fair comparisons, all methods are given access to the same set of samples (Appendix D.4).

Table 2. Automatic evaluation of Yelp Sentiment Transfer. We report their average *Joint Score*, averaging across negative and positive transfer results. The results (no parentheses) are reported with greedy decoding. BoN refers to Best-of-N sampling, following the setups of Deng et al. (2022), i.e., Bo32 under top-10 sampling. Additional results are presented in Table 12 in Appendix D.4.

Method	GPT-2	GPT-2 (BoN)	Llama3-8B-It	Llama3-8B-It (BoN)
ICL	4.6	40.8	54.4	69.6
RLPrompt	10.4	51.0	4.1	54.4
Promptbreeder	10.2	45.3	59.1	71.8
TAPruning	30.2	54.6	59.6	68.1
PROMPTQUINE	33.3	57.9	61.0	72.1

**Results.** As shown in Table 2, it’s possible that PROMPTQUINE could surpass the previous state-of-the-art on this task. These results, as we demonstrate, are largely insensitive to the decoding methods we employed. Additionally, as shown in Table 14 (Appendix D.4), our search framework operates more efficiently, delivering faster search. Nevertheless, compared to few-shot classification tasks, the search tends to be slower due to the imperfect feedback we receive, requiring more samples for fitness estimation.

Table 3. Attack success rate (ASR) for jailbreaking comparison of PROMPTQUINE, and conventional ICL. The text in parentheses refers to the fitness measure we used for PROMPTQUINE.

Attack Method	ASR-EM $\uparrow$	ASR-LLM $\uparrow$
LLM: Vicuna-7b-v1.5		
ICL (2-shot)	50.4	54.7
PROMPTQUINE (ASR-EM)	99.3	97.4
PROMPTQUINE (ASR-LLM)	99.4	97.5
PROMPTQUINE (SV)	90.3	94.2
LLM: Mistral-7B-Instruct-v0.3		
ICL (2-shot)	48.0	47.2
PROMPTQUINE (ASR-EM)	98.8	93.8
PROMPTQUINE (ASR-LLM)	99.8	98.1
PROMPTQUINE (SV)	98.8	92.6

### 4.2.2. JAILBREAKING

**Evaluation Settings.** We consider this task as highly challenging due to the only sparse, qualitative feedback available, such as the Exact Match score. We adopt a simple few-shot priming setup where the model directly follows the demonstrations to make predictions (i.e., *prefix attack*, without chat templates inserted), using popular models including Vicuna-7b-1.5 (Zheng et al., 2023) and Mistral-7B-Instruct-v0.3 (Jiang et al., 2023a) on AdvBench (Zou et al., 2023). We measure Attack Success Rate (ASR) using both Exact

Match (ASR-EM) and LLM-as-a-Judge by Llama-Guard-3 (Inan et al., 2023) (ASR-LLM). Please refer to Appendix D.4 for the details of our EM strings (Zhao et al., 2024) and prompts for Llama-Guard-3 (Ball et al., 2024) (taken from JailbreakBench (Chao et al., 2024)). We split the original 520 samples into 100 for validation and 420 for testing, using samples from the validation set for fitness estimation and prompt selection. We construct the ICL prompts (2-shot) by reorganizing the 5-shot ICL prompts in Liu et al. (2024).

**Experimental Details.** We produce separated experiments, using both ASR-EM score and ASR-LLM score on the 50 validation samples to guide the search. These experiments are conducted under a purely black-box setting, with the same validation re-ranking for prompt selection. We also explore to construct more expressive proxies (i.e., to reduce computational budgets) by leveraging steering vectors (SV) from mechanistic interpretability (Bartoszcze et al., 2025). Such vectors, extracted as activation difference, can enable direct intervention in a model’s inner layers to enhance task performance (Rimsky et al., 2024), allowing us to hypothesize that the similarity between internal representation changes after prompting and task steering vectors correlates with performance. Please refer to Appendix D.4 for the full details (3 seeds). We also explore variants of few-shot attack, e.g., in-context attacks (Wei et al., 2023b) where input-output pairs are separated in the conversational contexts, i.e., separated by the chat template tags, in the Appendix D.4.1, where we observe both successes and failures with the current pruning formulations.

**Results.** As shown in Table 3, under the priming setup, PROMPTQUINE is able to derive effective pruning which leads to improved attack results, nearly doubling the traditional average ICL performance. Search results guided by ASR-LLM achieve highest performance. It is noted that SV’s performance is generally lower. This is expected as just an initial exploration, and further research is needed to obtain further improvements. We also release some direct predictions of our pruned prompts on the AdvBench in the GitHub repository, ensuring rigor given the different data-separation schemes used across prior studies (Jiang et al., 2024; Paulus et al., 2024).

## 5. A Deeper Look at Pruning Effects on ICL

### 5.1. On the Limitations of PromptQuine

While pruning tokens are effective at enhancing overall ICL results, we identify its inherent limitations for current PROMPTQUINE. Specifically, we find that token pruning is not a universally reliable method for stabilizing ICL performance, as its effectiveness remains highly sensitive to the chosen ICL templates. We present one such study: we

Task	Task Metric Score		Standard Deviation
	$\hat{\Delta} (\text{Score}(p^{min}) \rightarrow \text{Score}(p^{max}))$		
SNLI	14.3	(60.8 → 75.1)	7.2
PIQA	2.6	(79.5 → 82.1)	1.1
Yelp Positive.	2.5	(49.9 → 52.4)	1.4
Yelp Negative.	1.0	(69.8 → 70.8)	0.9

Table 4. Performance fluctuations of PROMPTQUINE-pruned prompts across three random ICL templates, each with three 1-shot ICL seeds. Task scores are reported on the official test set.  $\hat{\Delta}$  indicates the performance fluctuation from the minimum to the maximum results across the selected templates.

cover a set of tasks, SNLI (Bowman et al., 2015) for classification, PIQA (Bisk et al., 2020) for multi-choice question answering, and Yelp positive transfer and negative transfer (Shen et al., 2017) for generation. For each task, we evaluate two additional ICL templates (see Appendix, Table 24 for examples, where the templates differ only in signal words, separators, spacing characters, and minor variations in natural language instructions as normal variations in practice) and run PROMPTQUINE pruning on each using three different seeds (i.e., three ICL prompts).

As presented in Table 4, differences in templates can still lead to significant variations in task outcomes. For example, in SNLI, the absolute accuracy fluctuation can reach up to 14.3%, which is surprisingly high. This emphasizes that PROMPTQUINE, or fixed-order ICL pruning in general, exhibit instability when exposed to template differences. Incorporating richer, more diverse prompt variations (e.g., token replacement or insertion) can be crucial for further improvement. Nevertheless, achieving this in the current PROMPTQUINE could be hard due to fitness-based selection pressures—beneficial changes, such as the introduction of new tokens, may be prematurely discarded. As a result, we can only adopt more conservative mutation operators, such as varying instructions (Fernando et al., 2024). More aggressive approaches, like exploring the full token space (Deng et al., 2022), are riskier. A promising direction to advance is to consider novelty search (Lehman & Stanley, 2011), which favors novel solutions over fitness alone.

### 5.2. Mechanistic Analysis of Label Words

It is intriguing to analyze what matters in the unconventional pruned ICL prompts for their unreasonable effectiveness. In this section, we examine the role of label words in the demonstrations—aligned with verbalizers—in classification tasks, in line with existing ICL research (Min et al., 2022; Yoo et al., 2022; Wang et al., 2023; Wei et al., 2023a). Concretely, it is often assumed that label words play a crucial role in determining original ICL performance (Min et al.,






Figure 3. The percentage of label word presence is surprisingly high for our PROMPTQUINE-pruned ICL prompts. We obtain these parsing results by exactly matching the label words within the pruned prompts. We verify that the ICL prompts used in the analysis do not contain these words in their exemplar inputs.

2022; Wang et al., 2023). We conduct a series of intervention experiments on label words to better understand their impact on pruning outcomes.

First, we observe that many of the pruned ICL prompts retain certain task-specific label words in their exemplar contexts (Figure 3). This observation closely mirrors findings from conventional ICL, suggesting that label words may play a significant role in ICL, even under pruning. Then, we perform the interventions. Figure 4 (left) shows the performance changes after removing the label words in original ICL prompts. The results are consistent with Min et al. (2022) that knowing the label space may help in conventional ICL. The hypothesis also generalizes in our unconventional ICL pruning context (Figure 4, middle) that we can observe a slight performance drop on average in pruned prompting performance. We then further experiment with removing the whole output, i.e., the signal words (e.g., Sentiment :) and the label words (e.g., great) in Figure 4 (right). This operation further largely degrades performance, highlighting the importance of preserving input-label format as in standard ICL (Min et al., 2022).

Although most of our findings so far are consistent with the findings on conventional ICL, there are still some special cases where prompt instances violate the aggregated findings discussed above (e.g., SNLI in Figure 4 (right), in which the pruned prompt (No Output) could achieve improved performance). This underscores the nuanced sensitivity of prompts within their specific contexts. Finally, we perform experiments with random verbalizers (label words are also changed in prompts). As shown in Appendix, Table 25, all these models show near chance-level performance without pruning. However, we find that counter-intuitively, pruning could also bring some performance improvements, especially towards the large 70B model. A non-negligible number of prompts can achieve significantly improved performance through pruning, and even achieve nearly identical to that of prompts with task-intuitive verbalizers. This is indeed surprising, and we hope future research will explore its underlying mechanisms further.




Figure 4. Changes in (unpruned & pruned) prompting performance on Meta-Llama-3-8B-Instruct when labels are removed (left & middle) or when the entire output is removed (right), breaking the input-label pairing format. Another study with similar findings on GPT-2 is presented in the Figure 9 in Appendix.

## 6. Related Work

We discuss briefly various prompt design paradigms and ICL studies in previous work, and provide more comprehensive discussion in Appendix A. Concretely, ICL was introduced by Brown et al. (2020), who demonstrated that LLMs can adapt to downstream tasks using few-shot prompting. Nevertheless, this paradigm has proven to be highly unstable; even slight variations can lead to significant differences in performance. Rubin et al. (2022) demonstrate the importance of demonstration selections, where retrieving demonstrations with similar patterns as the task input typically yields improved performance. Lu et al. (2022) further identifies that even demonstration orders affect the results to a significant extent. Although heuristics—such as retrieving structurally and potentially semantically similar exemplars—often perform well in practice, there remains a lack of well-grounded principles to guide demonstration design. Several studies aim to optimize prompts in alternative formats, typically via direct natural language instructions (Zhou et al., 2022; Guo et al., 2023, *inter alia*). Unlike ICL stabilization, this approach treats prompt optimization as a search for optimal instructions—often using LLMs as prompt engineers. In contrast, we focus on optimizing in an unnatural language space, building directly on few-shot prompts.

## 7. Conclusions

We introduce a novel prompt design paradigm that challenges conventional practices: instead of carefully crafting instructions and examples, we show that pruning random demonstrations into incoherent “gibberish” can still achieve near state-of-the-art performance. As attribution and compression methods remain unreliable, we present PROMPTQUINE, an evolutionary framework that autonomously discovers effective pruning strategies. Experiments across diverse tasks and models validate its effectiveness and runtime efficiency, paving the way for future research into the mechanistic foundations of in-context learning.

## Impact Statement

This work aimed at advancing the research of LLMs, with a particular focus on prompt optimization and in-context learning. In contrast to the traditional approach of optimizing in natural language space, we introduce a novel prompt design paradigm that prunes random few-shot prompts into syntactically and semantically unnatural language. Surprisingly, we find that a simple pruning operation applied to ICL prompts is sufficient to match the performance of previous optimization methods across various tasks and models. This insight paves the way for future research, leaving several interpretability questions open for further exploration. For example, it is intriguing to explore why pruning to unnatural language is effective for prompt optimization and why such unnatural ICL remains effective for LLMs. This is particularly noteworthy in cases where pruning enhances performance for several random label words, whereas natural ICL yields only chance-level results.

Moreover, we highlight the direct societal implications of our findings on unnatural language. Notably, our work exposes critical weaknesses in current LLM alignment techniques. Despite extensive training designed to align models with human values and ethical standards when given natural language instructions, our findings reveal that unnatural language can still be used to elicit malicious behaviors—exploiting gaps that developers cannot fully anticipate. As demonstrated in our paper, this vulnerability persists even in large models subjected to extensive red teaming. While continuously iterating on red teaming and eliminating failure cases is beneficial, we advocate for exploring novel alignment techniques that go beyond surface-level fixes. In particular, a stronger focus on *inner alignment* may lead to more robust improvements. For commercial models, we strongly recommend complementing red teaming with output-level restrictions, as this may provide a more intuitive and effective safeguard—especially given that existing alignment methods are primarily optimized for handling natural language inputs.

## References

Agarwal, R., Singh, A., Zhang, L. M., Bohnet, B., Chan, S., Anand, A., Abbas, Z., Nova, A., Co-Reyes, J. D., Chu, E., et al. Many-shot in-context learning. *arXiv preprint arXiv:2404.11018*, 2024.

Ahn, K., Cheng, X., Daneshmand, H., and Sra, S. Transformers learn to implement preconditioned gradient descent for in-context learning. *Advances in Neural Information Processing Systems*, 36:45614–45650, 2023.

AI@Meta. Llama 3 model card. 2024. URL [https://github.com/meta-llama/llama3/blob/main/MODEL\\_CARD.md](https://github.com/meta-llama/llama3/blob/main/MODEL_CARD.md).

Asghar, N. Yelp dataset challenge: Review rating prediction. *arXiv preprint arXiv:1605.05362*, 2016.

Baehrens, D., Schroeter, T., Harmeling, S., Kawanabe, M., Hansen, K., and Müller, K.-R. How to explain individual classification decisions. *The Journal of Machine Learning Research*, 11:1803–1831, 2010.

Ball, S., Kreuter, F., and Panickssery, N. Understanding jailbreak success: A study of latent space dynamics in large language models. *arXiv preprint arXiv:2406.09289*, 2024.

Bartoszcze, L., Munshi, S., Sukidi, B., Yen, J., Yang, Z., Williams-King, D., Le, L., Asuzu, K., and Maple, C. Representation engineering for large-language models: Survey and research challenges. *arXiv preprint arXiv:2502.17601*, 2025.

Beheshti, Z. and Shamsuddin, S. M. H. A review of population-based meta-heuristic algorithms. *Int. j. adv. soft comput. appl*, 5(1):1–35, 2013.

Bergstra, J. and Bengio, Y. Random search for hyperparameter optimization. *Journal of machine learning research*, 13(2), 2012.

Bertsimas, D. and Tsitsiklis, J. Simulated annealing. *Statistical science*, 8(1):10–15, 1993.

Bisk, Y., Zellers, R., Gao, J., Choi, Y., et al. Piqa: Reasoning about physical commonsense in natural language. In *Proceedings of the AAAI conference on artificial intelligence*, volume 34, pp. 7432–7439, 2020.

Bowman, S. R., Angeli, G., Potts, C., and Manning, C. D. A large annotated corpus for learning natural language inference. In Márquez, L., Callison-Burch, C., and Su, J. (eds.), *Proceedings of the 2015 Conference on Empirical Methods in Natural Language Processing*, pp. 632–642, Lisbon, Portugal, September 2015. Association for Computational Linguistics. doi: 10.18653/v1/D15-1075. URL <https://aclanthology.org/D15-1075>.

Brown, T., Mann, B., Ryder, N., Subbiah, M., Kaplan, J. D., Dhariwal, P., Neelakantan, A., Shyam, P., Sastry, G., Askell, A., et al. Language models are few-shot learners. *Advances in neural information processing systems*, 33:1877–1901, 2020.

Chan, S. C., Dasgupta, I., Kim, J., Kumaran, D., Lampinen, A. K., and Hill, F. Transformers generalize differently from information stored in context vs in weights. *arXiv preprint arXiv:2210.05675*, 2022.

Chao, P., DeBenedetti, E., Robey, A., Andriushchenko, M., Croce, F., Schwag, V., Dobriban, E., Flammarion, N., Pappas, G. J., Tramer, F., et al. Jailbreakbench: An open

- robustness benchmark for jailbreaking large language models. *arXiv preprint arXiv:2404.01318*, 2024.
- Chen, L., Chen, J., Goldstein, T., Huang, H., and Zhou, T. Instructzero: Efficient instruction optimization for black-box large language models. *arXiv preprint arXiv:2306.03082*, 2023.
- Cheng, X., Chen, Y., and Sra, S. Transformers implement functional gradient descent to learn non-linear functions in context. *arXiv preprint arXiv:2312.06528*, 2023.
- Choi, Y., Bae, S., Ban, S., Jeong, M., Zhang, C., Song, L., Zhao, L., Bian, J., and Kim, K.-E. Hard prompts made interpretable: Sparse entropy regularization for prompt tuning with RL. In Ku, L.-W., Martins, A., and Srikumar, V. (eds.), *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 8252–8271, Bangkok, Thailand, August 2024. Association for Computational Linguistics. doi: 10.18653/v1/2024.acl-long.449. URL <https://aclanthology.org/2024.acl-long.449/>.
- Co-Reyes, J. D., Miao, Y., Peng, D., Real, E., Le, Q. V., Levine, S., Lee, H., and Faust, A. Evolving reinforcement learning algorithms. In *International Conference on Learning Representations*, 2021.
- Cobbe, K., Kosaraju, V., Bavarian, M., Chen, M., Jun, H., Kaiser, L., Plappert, M., Tworek, J., Hilton, J., Nakano, R., et al. Training verifiers to solve math word problems. *arXiv preprint arXiv:2110.14168*, 2021.
- Cui, W., Zhang, J., Li, Z., Sun, H., Lopez, D., Das, K., Malin, B. A., and Kumar, S. Phaseevo: Towards unified long-context prompt optimization for large language models. In *First Workshop on Long-Context Foundation Models@ ICML 2024*, 2024.
- Dai, D., Sun, Y., Dong, L., Hao, Y., Ma, S., Sui, Z., and Wei, F. Why can GPT learn in-context? language models secretly perform gradient descent as meta-optimizers. In Rogers, A., Boyd-Graber, J., and Okazaki, N. (eds.), *Findings of the Association for Computational Linguistics: ACL 2023*, pp. 4005–4019, Toronto, Canada, July 2023. Association for Computational Linguistics. doi: 10.18653/v1/2023.findings-acl.247. URL <https://aclanthology.org/2023.findings-acl.247>.
- Daras, G. and Dimakis, A. Discovering the hidden vocabulary of dalle-2. In *NeurIPS 2022 Workshop on Score-Based Methods*, 2022.
- Dasgupta, I., Grant, E., and Griffiths, T. Distinguishing rule and exemplar-based generalization in learning systems. In *International Conference on Machine Learning*, pp. 4816–4830. PMLR, 2022.
- Deb, K. and Saha, A. Finding multiple solutions for multimodal optimization problems using a multi-objective evolutionary approach. In *Proceedings of the 12th annual conference on genetic and evolutionary computation*, pp. 447–454, 2010.
- Deb, K., Pratap, A., Agarwal, S., and Meyarivan, T. A fast and elitist multiobjective genetic algorithm: Nsga-ii. *IEEE transactions on evolutionary computation*, 6(2): 182–197, 2002.
- Deng, M., Tan, B., Liu, Z., Xing, E., and Hu, Z. Compression, transduction, and creation: A unified framework for evaluating natural language generation. In Moens, M.-F., Huang, X., Specia, L., and Yih, S. W.-t. (eds.), *Proceedings of the 2021 Conference on Empirical Methods in Natural Language Processing*, pp. 7580–7605, Online and Punta Cana, Dominican Republic, November 2021. Association for Computational Linguistics. doi: 10.18653/v1/2021.emnlp-main.599. URL <https://aclanthology.org/2021.emnlp-main.599>.
- Deng, M., Wang, J., Hsieh, C.-P., Wang, Y., Guo, H., Shu, T., Song, M., Xing, E., and Hu, Z. RLPrompt: Optimizing discrete text prompts with reinforcement learning. In Goldberg, Y., Kozareva, Z., and Zhang, Y. (eds.), *Proceedings of the 2022 Conference on Empirical Methods in Natural Language Processing*, pp. 3369–3391, Abu Dhabi, United Arab Emirates, December 2022. Association for Computational Linguistics. doi: 10.18653/v1/2022.emnlp-main.222. URL <https://aclanthology.org/2022.emnlp-main.222>.
- Denil, M., Demiraj, A., and De Freitas, N. Extraction of salient sentences from labelled documents. *arXiv preprint arXiv:1412.6815*, 2014.
- Deutch, G., Magar, N., Natan, T., and Dar, G. In-context learning and gradient descent revisited. In Duh, K., Gomez, H., and Bethard, S. (eds.), *Proceedings of the 2024 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies (Volume 1: Long Papers)*, pp. 1017–1028, Mexico City, Mexico, June 2024. Association for Computational Linguistics. doi: 10.18653/v1/2024.naacl-long.58. URL <https://aclanthology.org/2024.naacl-long.58>.
- Di Langosco, L. L., Koch, J., Sharkey, L. D., Pfau, J., and Krueger, D. Goal misgeneralization in deep reinforcement learning. In *International Conference on Machine Learning*, pp. 12004–12019. PMLR, 2022.
- Dueck, G. and Scheuer, T. Threshold accepting: A general purpose optimization algorithm appearing superior to simulated annealing. *Journal of computational physics*, 90(1):161–175, 1990.

- 605 Ecoffet, A., Huizinga, J., Lehman, J., Stanley, K. O.,  
606 and Clune, J. Go-explore: a new approach for hard-  
607 exploration problems. *arXiv preprint arXiv:1901.10995*,  
608 2019.
- 609
- 610 Feng, S., Wallace, E., Grissom II, A., Iyyer, M., Rodriguez,  
611 P., and Boyd-Graber, J. Pathologies of neural models  
612 make interpretations difficult. In Riloff, E., Chiang, D.,  
613 Hockenmaier, J., and Tsujii, J. (eds.), *Proceedings of*  
614 *the 2018 Conference on Empirical Methods in Natural*  
615 *Language Processing*, pp. 3719–3728, Brussels, Belgium,  
616 October–November 2018. Association for Computational  
617 Linguistics. doi: 10.18653/v1/D18-1407. URL <https://aclanthology.org/D18-1407>.
- 618
- 619
- 620 Fernando, C., Banarse, D. S., Michalewski, H., Osindero,  
621 S., and Rocktäschel, T. Promptbreeder: Self-referential  
622 self-improvement via prompt evolution. In *Forty-first*  
623 *International Conference on Machine Learning*, 2024.
- 624
- 625 Friedrich, T., Oliveto, P. S., Sudholt, D., and Witt, C. Anal-  
626 ysis of diversity-preserving mechanisms for global ex-  
627 ploration. *Evolutionary Computation*, 17(4):455–476,  
628 2009.
- 629
- 630 Fu, D., Chen, T.-Q., Jia, R., and Sharan, V. Transformers  
631 learn higher-order optimization methods for in-context  
632 learning: A study with linear models. *arXiv preprint*  
633 *arXiv:2310.17086*, 2023a.
- 634
- 635 Fu, Y., Ou, L., Chen, M., Wan, Y., Peng, H., and Khot, T.  
636 Chain-of-thought hub: A continuous effort to measure  
637 large language models’ reasoning performance, 2023b.  
638 URL <https://arxiv.org/abs/2305.17306>.
- 639
- 640 Gabriel, I. Artificial intelligence, values, and alignment.  
641 *Minds and machines*, 30(3):411–437, 2020.
- 642
- 643 Ge, S., Zhang, Y., Liu, L., Zhang, M., Han, J., and Gao,  
644 J. Model tells you what to discard: Adaptive kv cache  
645 compression for llms. *arXiv preprint arXiv:2310.01801*,  
646 2023.
- 647
- 648 Gendreau, M. and Potvin, J.-Y. Tabu search. *Search method-*  
649 *ologies: introductory tutorials in optimization and deci-*  
650 *sion support techniques*, pp. 165–186, 2005.
- 651
- 652 Glover, F. W. and Kochenberger, G. A. *Handbook of meta-*  
653 *heuristics*, volume 57. Springer Science & Business  
654 Media, 2003.
- 655
- 656 Greenblatt, R., Denison, C., Wright, B., Roger, F., MacDi-  
657 armid, M., Marks, S., Treutlein, J., Belonax, T., Chen, J.,  
658 Duvenaud, D., et al. Alignment faking in large language  
659 models. *arXiv preprint arXiv:2412.14093*, 2024.
- Guo, Q., Wang, R., Guo, J., Li, B., Song, K., Tan, X., Liu,  
G., Bian, J., and Yang, Y. Connecting large language mod-  
els with evolutionary algorithms yields powerful prompt  
optimizers. *arXiv preprint arXiv:2309.08532*, 2023.
- Holland, J. H. Genetic algorithms. *Scientific american*, 267  
(1):66–73, 1992.
- Hurst, A., Lerer, A., Goucher, A. P., Perelman, A., Ramesh,  
A., Clark, A., Ostrow, A., Welihinda, A., Hayes, A.,  
Radford, A., et al. Gpt-4o system card. *arXiv preprint*  
*arXiv:2410.21276*, 2024.
- Inan, H., Upasani, K., Chi, J., Rungta, R., Iyer, K.,  
Mao, Y., Tontchev, M., Hu, Q., Fuller, B., Testug-  
gine, D., et al. Llama guard: Llm-based input-output  
safeguard for human-ai conversations. *arXiv preprint*  
*arXiv:2312.06674*, 2023.
- Jamieson, K. and Talwalkar, A. Non-stochastic best arm  
identification and hyperparameter optimization. In *Arti-*  
*ficial intelligence and statistics*, pp. 240–248. PMLR,  
2016.
- Jiang, A. Q., Sablayrolles, A., Mensch, A., Bamford, C.,  
Chaplot, D. S., Casas, D. d. l., Bressand, F., Lengyel, G.,  
Lample, G., Saulnier, L., et al. Mistral 7b. *arXiv preprint*  
*arXiv:2310.06825*, 2023a.
- Jiang, F., Xu, Z., Niu, L., Xiang, Z., Ramasubramanian,  
B., Li, B., and Poovendran, R. Artprompt: Ascii art-  
based jailbreak attacks against aligned llms. In *Proceed-*  
*ings of the 62nd Annual Meeting of the Association for*  
*Computational Linguistics (Volume 1: Long Papers)*, pp.  
15157–15173, 2024.
- Jiang, H., Wu, Q., Lin, C.-Y., Yang, Y., and Qiu, L.  
Llmlingua: Compressing prompts for accelerated infer-  
ence of large language models. In *Conference on*  
*Empirical Methods in Natural Language Processing*,  
2023b. URL <https://api.semanticscholar.org/CorpusID:263830701>.
- Jiang, H., Wu, Q., Lin, C.-Y., Yang, Y., and Qiu, L. Llmlin-  
gua: Compressing prompts for accelerated inference of  
large language models. *arXiv preprint arXiv:2310.05736*,  
2023c.
- Jiang, H., Wu, Q., Luo, X., Li, D., Lin, C.-Y., Yang, Y., and  
Qiu, L. Longllmlingua: Accelerating and enhancing llms  
in long context scenarios via prompt compression. *arXiv*  
*preprint arXiv:2310.06839*, 2023d.
- Jiang, Z., Xu, F. F., Araki, J., and Neubig, G. How can  
we know what language models know? *Transactions*  
*of the Association for Computational Linguistics*, 8:423–  
438, 2020. doi: 10.1162/tacl.a.00324. URL <https://aclanthology.org/2020.tacl-1.28>.

- 660 Jones, E., Dragan, A., Raghunathan, A., and Steinhardt, J.  
661 Automatically auditing large language models via discrete  
662 optimization. In *International Conference on Machine*  
663 *Learning*, pp. 15307–15329. PMLR, 2023.
- 664 Khashabi, D., Lyu, X., Min, S., Qin, L., Richardson, K.,  
665 Welleck, S., Hajishirzi, H., Khot, T., Sabharwal, A.,  
666 Singh, S., and Choi, Y. Prompt waywardness: The  
667 curious case of discretized interpretation of continuous  
668 prompts. In Carpuat, M., de Marneffe, M.-C., and  
669 Meza Ruiz, I. V. (eds.), *Proceedings of the 2022 Con-*  
670 *ference of the North American Chapter of the Association*  
671 *for Computational Linguistics: Human Language Tech-*  
672 *nologies*, pp. 3631–3643, Seattle, United States, July  
673 2022. Association for Computational Linguistics. doi:  
674 10.18653/v1/2022.naacl-main.266. URL [https://](https://aclanthology.org/2022.naacl-main.266)  
675 [aclanthology.org/2022.naacl-main.266](https://aclanthology.org/2022.naacl-main.266).
- 676 Kojima, T., Gu, S. S., Reid, M., Matsuo, Y., and Iwasawa,  
677 Y. Large language models are zero-shot reasoners. *Ad-*  
678 *vances in neural information processing systems*, 35:  
679 22199–22213, 2022.
- 680 Koncel-Kedziorski, R., Roy, S., Amini, A., Kushman, N.,  
681 and Hajishirzi, H. MAWPS: A math word problem reposi-  
682 tory. In Knight, K., Nenkova, A., and Rambow, O. (eds.),  
683 *Proceedings of the 2016 Conference of the North Amer-*  
684 *ican Chapter of the Association for Computational Lin-*  
685 *guistics: Human Language Technologies*, pp. 1152–1157,  
686 San Diego, California, June 2016. Association for Com-  
687 putational Linguistics. doi: 10.18653/v1/N16-1136. URL  
688 <https://aclanthology.org/N16-1136>.
- 689 Krishna, K., Wieting, J., and Iyyer, M. Reformulating un-  
690 supervised style transfer as paraphrase generation. In  
691 Webber, B., Cohn, T., He, Y., and Liu, Y. (eds.), *Pro-*  
692 *ceedings of the 2020 Conference on Empirical Meth-*  
693 *ods in Natural Language Processing (EMNLP)*, pp. 737–  
694 762, Online, November 2020. Association for Computa-  
695 tional Linguistics. doi: 10.18653/v1/2020.emnlp-main.  
696 55. URL [https://aclanthology.org/2020.](https://aclanthology.org/2020.emnlp-main.55)  
697 [emnlp-main.55](https://aclanthology.org/2020.emnlp-main.55).
- 698 Kwon, W., Li, Z., Zhuang, S., Sheng, Y., Zheng, L., Yu,  
699 C. H., Gonzalez, J., Zhang, H., and Stoica, I. Efficient  
700 memory management for large language model serving  
701 with pagedattention. In *Proceedings of the 29th Sym-*  
702 *posium on Operating Systems Principles*, pp. 611–626,  
703 2023.
- 704 Labrou, Y. and Finin, T. Yahoo! as an ontology: using  
705 yahoo! categories to describe documents. In *Proceedings*  
706 *of the eighth international conference on Information and*  
707 *knowledge management*, pp. 180–187, 1999.
- 708 Langley, P. Crafting papers on machine learning. In Langley,  
709 P. (ed.), *Proceedings of the 17th International Conference*  
710 *on Machine Learning (ICML 2000)*, pp. 1207–1216, Stan-  
711 ford, CA, 2000. Morgan Kaufmann.
- 712 Lee, H., Phatale, S., Mansoor, H., Lu, K. R., Mesnard, T.,  
713 Ferret, J., Bishop, C., Hall, E., Carbune, V., and Rastogi,  
714 A. Rlaif: Scaling reinforcement learning from human  
feedback with ai feedback. 2023.
- Lehman, J. and Stanley, K. O. Abandoning objectives: Evo-  
lution through the search for novelty alone. *Evolutionary  
computation*, 19(2):189–223, 2011.
- Lester, B., Al-Rfou, R., and Constant, N. The power of  
scale for parameter-efficient prompt tuning. In Moens,  
M.-F., Huang, X., Specia, L., and Yih, S. W.-t. (eds.), *Pro-*  
*ceedings of the 2021 Conference on Empirical Methods*  
*in Natural Language Processing*, pp. 3045–3059, On-  
line and Punta Cana, Dominican Republic, November  
2021. Association for Computational Linguistics. doi:  
10.18653/v1/2021.emnlp-main.243. URL [https://](https://aclanthology.org/2021.emnlp-main.243)  
[aclanthology.org/2021.emnlp-main.243](https://aclanthology.org/2021.emnlp-main.243).
- Li, C., Farkhoor, H., Liu, R., and Yosinski, J. Measur-  
ing the intrinsic dimension of objective landscapes. In  
*International Conference on Learning Representations*,  
2018a.
- Li, J., Chen, X., Hovy, E., and Jurafsky, D. Visualizing  
and understanding neural models in NLP. In Knight,  
K., Nenkova, A., and Rambow, O. (eds.), *Proceedings*  
*of the 2016 Conference of the North American Chapter*  
*of the Association for Computational Linguistics: Hu-*  
*man Language Technologies*, pp. 681–691, San Diego,  
California, June 2016a. Association for Computational  
Linguistics. doi: 10.18653/v1/N16-1082. URL [https://](https://aclanthology.org/N16-1082)  
[aclanthology.org/N16-1082](https://aclanthology.org/N16-1082).
- Li, J., Monroe, W., and Jurafsky, D. Understanding neural  
networks through representation erasure. *arXiv preprint*  
*arXiv:1612.08220*, 2016b.
- Li, L., Jamieson, K., DeSalvo, G., Rostamizadeh, A., and  
Talwalkar, A. Hyperband: A novel bandit-based approach  
to hyperparameter optimization. *Journal of Machine*  
*Learning Research*, 18(185):1–52, 2018b.
- Li, X. L. and Liang, P. Prefix-tuning: Optimizing continu-  
ous prompts for generation. In Zong, C., Xia, F., Li, W.,  
and Navigli, R. (eds.), *Proceedings of the 59th Annual*  
*Meeting of the Association for Computational Linguistics*  
*and the 11th International Joint Conference on Natu-*  
*ral Language Processing (Volume 1: Long Papers)*, pp.  
4582–4597, Online, August 2021. Association for Com-  
putational Linguistics. doi: 10.18653/v1/2021.acl-long.  
353. URL [https://aclanthology.org/2021.](https://aclanthology.org/2021.acl-long.353)  
[acl-long.353](https://aclanthology.org/2021.acl-long.353).

- Li, Y., Dong, B., Guerin, F., and Lin, C. Compressing context to enhance inference efficiency of large language models. In Bouamor, H., Pino, J., and Bali, K. (eds.), *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing*, pp. 6342–6353, Singapore, December 2023. Association for Computational Linguistics. doi: 10.18653/v1/2023.emnlp-main.391. URL <https://aclanthology.org/2023.emnlp-main.391>.
- Liao, C., Zheng, Y., and Yang, Z. Zero-label prompt selection. *arXiv preprint arXiv:2211.04668*, 2022.
- Lightman, H., Kosaraju, V., Burda, Y., Edwards, H., Baker, B., Lee, T., Leike, J., Schulman, J., Sutskever, I., and Cobbe, K. Let’s verify step by step. In *The Twelfth International Conference on Learning Representations*, 2024.
- Lin, X., Wu, Z., Dai, Z., Hu, W., Shu, Y., Ng, S.-K., Jaillet, P., and Low, B. K. H. Use your instinct: Instruction optimization for llms using neural bandits coupled with transformers. In *Forty-first International Conference on Machine Learning*, 2024.
- Liu, P., Yuan, W., Fu, J., Jiang, Z., Hayashi, H., and Neubig, G. Pre-train, prompt, and predict: A systematic survey of prompting methods in natural language processing. *ACM Computing Surveys*, 55(9):1–35, 2023.
- Liu, S., Ye, H., Xing, L., and Zou, J. Y. In-context vectors: Making in context learning more effective and controllable through latent space steering. In *Forty-first International Conference on Machine Learning*, 2024.
- Liu, Y., Ott, M., Goyal, N., Du, J., Joshi, M., Chen, D., Levy, O., Lewis, M., Zettlemoyer, L., and Stoyanov, V. Roberta: A robustly optimized bert pretraining approach. *arXiv preprint arXiv:1907.11692*, 2019.
- Longpre, S., Hou, L., Vu, T., Webson, A., Chung, H. W., Tay, Y., Zhou, D., Le, Q. V., Zoph, B., Wei, J., et al. The flan collection: Designing data and methods for effective instruction tuning. In *International Conference on Machine Learning*, pp. 22631–22648. PMLR, 2023.
- Lu, Y., Bartolo, M., Moore, A., Riedel, S., and Stenortorp, P. Fantastically ordered prompts and where to find them: Overcoming few-shot prompt order sensitivity. In Muresan, S., Nakov, P., and Villavicencio, A. (eds.), *Proceedings of the 60th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 8086–8098, Dublin, Ireland, May 2022. Association for Computational Linguistics. doi: 10.18653/v1/2022.acl-long.556. URL <https://aclanthology.org/2022.acl-long.556>.
- Min, S., Lyu, X., Holtzman, A., Artetxe, M., Lewis, M., Hajishirzi, H., and Zettlemoyer, L. Rethinking the role of demonstrations: What makes in-context learning work? In Goldberg, Y., Kozareva, Z., and Zhang, Y. (eds.), *Proceedings of the 2022 Conference on Empirical Methods in Natural Language Processing*, pp. 11048–11064, Abu Dhabi, United Arab Emirates, December 2022. Association for Computational Linguistics. doi: 10.18653/v1/2022.emnlp-main.759. URL <https://aclanthology.org/2022.emnlp-main.759>.
- Ngo, R., Chan, L., and Mindermann, S. The alignment problem from a deep learning perspective. *arXiv preprint arXiv:2209.00626*, 2022.
- Nisioti, E., Glanois, C., Najarro, E., Dai, A., Meyerson, E., Pedersen, J. W., Teodorescu, L., Hayes, C. F., Sudhakaran, S., and Risi, S. From text to life: On the reciprocal relationship between artificial life and large language models. In *Artificial Life Conference Proceedings 36*, volume 2024, pp. 39. MIT Press One Rogers Street, Cambridge, MA 02142-1209, USA journals-info . . . , 2024.
- Ofria, C. and Wilke, C. O. Avida: A software platform for research in computational evolutionary biology. *Artificial life*, 10(2):191–229, 2004.
- OpenAI. Prompt engineering guideline, 2023. URL <https://platform.openai.com/docs/guides/prompt-engineering>.
- Ouyang, L., Wu, J., Jiang, X., Almeida, D., Wainwright, C., Mishkin, P., Zhang, C., Agarwal, S., Slama, K., Ray, A., et al. Training language models to follow instructions with human feedback. *Advances in neural information processing systems*, 35:27730–27744, 2022.
- Pan, Z., Wu, Q., Jiang, H., Xia, M., Luo, X., Zhang, J., Lin, Q., Rühle, V., Yang, Y., Lin, C.-Y., et al. LlmLingua-2: Data distillation for efficient and faithful task-agnostic prompt compression. *arXiv preprint arXiv:2403.12968*, 2024.
- Pang, B. and Lee, L. A sentimental education: Sentiment analysis using subjectivity summarization based on minimum cuts. In *Proceedings of the 42nd Annual Meeting of the Association for Computational Linguistics (ACL-04)*, pp. 271–278, Barcelona, Spain, July 2004. doi: 10.3115/1218955.1218990. URL <https://aclanthology.org/P04-1035>.
- Papineni, K., Roukos, S., Ward, T., and Zhu, W.-J. Bleu: a method for automatic evaluation of machine translation. In Isabelle, P., Charniak, E., and Lin, D. (eds.), *Proceedings of the 40th Annual Meeting of the Association for Computational Linguistics*, pp. 311–318, Philadelphia,

- 770 Pennsylvania, USA, July 2002. Association for Computa-  
771 tional Linguistics. doi: 10.3115/1073083.1073135. URL  
772 <https://aclanthology.org/P02-1040/>.  
773
- 774 Paulus, A., Zharmagambetov, A., Guo, C., Amos, B., and  
775 Tian, Y. Advprompter: Fast adaptive adversarial prompt-  
776 ing for llms. *arXiv preprint arXiv:2404.16873*, 2024.  
777
- 778 Qin, G. and Eisner, J. Learning how to ask: Querying  
779 LMs with mixtures of soft prompts. In Toutanova, K.,  
780 Rumshisky, A., Zettlemoyer, L., Hakkani-Tur, D., Belt-  
781 agy, I., Bethard, S., Cotterell, R., Chakraborty, T., and  
782 Zhou, Y. (eds.), *Proceedings of the 2021 Conference*  
783 *of the North American Chapter of the Association for*  
784 *Computational Linguistics: Human Language Technolo-*  
785 *gies*, pp. 5203–5212, Online, June 2021. Association  
786 for Computational Linguistics. doi: 10.18653/v1/2021.  
787 naacl-main.410. URL <https://aclanthology.org/2021.naacl-main.410>.  
788
- 789 Radford, A., Wu, J., Child, R., Luan, D., Amodei, D., and  
790 Sutskever, I. Language models are unsupervised multitask  
791 learners. 2019.  
792
- 793 Real, E., Moore, S., Selle, A., Saxena, S., Suematsu, Y. L.,  
794 Tan, J., Le, Q. V., and Kurakin, A. Large-scale evolu-  
795 tion of image classifiers. In *International conference on*  
796 *machine learning*, pp. 2902–2911. PMLR, 2017.  
797
- 798 Real, E., Aggarwal, A., Huang, Y., and Le, Q. V. Regular-  
799 ized evolution for image classifier architecture search. In  
800 *Proceedings of the aaai conference on artificial intelli-*  
801 *gence*, volume 33, pp. 4780–4789, 2019.  
802
- 803 Real, E., Liang, C., So, D., and Le, Q. Automl-zero: Evolv-  
804 ing machine learning algorithms from scratch. In *Internat-*  
805 *ional conference on machine learning*, pp. 8007–8019.  
806 PMLR, 2020.
- 807 Rimsky, N., Gabrieli, N., Schulz, J., Tong, M., Hubinger,  
808 E., and Turner, A. Steering llama 2 via contrastive activa-  
809 tion addition. In Ku, L.-W., Martins, A., and Srikumar,  
810 V. (eds.), *Proceedings of the 62nd Annual Meeting of*  
811 *the Association for Computational Linguistics (Volume*  
812 *1: Long Papers)*, pp. 15504–15522, Bangkok, Thailand,  
813 August 2024. Association for Computational Linguistics.  
814 doi: 10.18653/v1/2024.acl-long.828. URL <https://aclanthology.org/2024.acl-long.828>.  
815
- 816 Roy, S. and Roth, D. Solving general arithmetic word prob-  
817 lems. In Márquez, L., Callison-Burch, C., and Su, J.  
818 (eds.), *Proceedings of the 2015 Conference on Empiri-*  
819 *cal Methods in Natural Language Processing*, pp. 1743–  
820 1752, Lisbon, Portugal, September 2015. Association for  
821 Computational Linguistics. doi: 10.18653/v1/D15-1202.  
822 URL <https://aclanthology.org/D15-1202>.  
823
- 824 Rubin, O., Herzig, J., and Berant, J. Learning to retrieve  
prompts for in-context learning. In Carpuat, M., de Marn-  
effe, M.-C., and Meza Ruiz, I. V. (eds.), *Proceedings*  
*of the 2022 Conference of the North American Chap-*  
*ter of the Association for Computational Linguistics:*  
*Human Language Technologies*, pp. 2655–2671, Seat-  
tle, United States, July 2022. Association for Computa-  
tional Linguistics. doi: 10.18653/v1/2022.naacl-main.  
191. URL <https://aclanthology.org/2022.naacl-main.191>.
- Russell, S. J. and Norvig, P. *Artificial intelligence: a modern approach*. Pearson, 2016.
- Sareni, B. and Krahenbuhl, L. Fitness sharing and niching  
methods revisited. *IEEE transactions on Evolutionary*  
*Computation*, 2(3):97–106, 1998.
- Schick, T. and Schütze, H. Exploiting cloze-questions  
for few-shot text classification and natural language  
inference. In Merlo, P., Tiedemann, J., and Tsarfaty,  
R. (eds.), *Proceedings of the 16th Conference of*  
*the European Chapter of the Association for Compu-*  
*tational Linguistics: Main Volume*, pp. 255–269, On-  
line, April 2021. Association for Computational Linguis-  
tics. doi: 10.18653/v1/2021.eacl-main.20. URL <https://aclanthology.org/2021.eacl-main.20>.
- Schmidhuber, J. Gödel machines: self-referential uni-  
versal problem solvers making provably optimal self-  
improvements. *arXiv preprint cs/0309048*, 2003.
- Shen, L., Mishra, A., and Khashabi, D. Do pretrained  
transformers really learn in-context by gradient descent?  
*arXiv preprint arXiv:2310.08540*, 2023a.
- Shen, T., Lei, T., Barzilay, R., and Jaakkola, T. Style transfer  
from non-parallel text by cross-alignment. *Advances in*  
*neural information processing systems*, 30, 2017.
- Shen, T., Jin, R., Huang, Y., Liu, C., Dong, W., Guo, Z.,  
Wu, X., Liu, Y., and Xiong, D. Large language model  
alignment: A survey. *arXiv preprint arXiv:2309.15025*,  
2023b.
- Shi, F., Chen, X., Misra, K., Scales, N., Dohan, D., Chi,  
E. H., Schärli, N., and Zhou, D. Large language models  
can be easily distracted by irrelevant context. In *Inter-*  
*national Conference on Machine Learning*, pp. 31210–  
31227. PMLR, 2023.
- Shin, T., Razeghi, Y., Logan IV, R. L., Wallace, E., and  
Singh, S. AutoPrompt: Eliciting Knowledge from Lan-  
guage Models with Automatically Generated Prompts.  
In Webber, B., Cohn, T., He, Y., and Liu, Y. (eds.), *Pro-*  
*ceedings of the 2020 Conference on Empirical Methods*

- 825 *in Natural Language Processing (EMNLP)*, pp. 4222–  
826 4235, Online, November 2020. Association for Computa-  
827 tional Linguistics. doi: 10.18653/v1/2020.emnlp-main.  
828 346. URL [https://aclanthology.org/2020.](https://aclanthology.org/2020.emnlp-main.346)  
829 [emnlp-main.346](https://aclanthology.org/2020.emnlp-main.346).
- 830 Shrikumar, A., Greenside, P., Shcherbina, A., and Kundaje,  
831 A. Not just a black box: Learning important features  
832 through propagating activation differences. *arXiv preprint*  
833 *arXiv:1605.01713*, 2016.
- 834 Simonyan, K. Deep inside convolutional networks: Visu-  
835 alising image classification models and saliency maps.  
836 *arXiv preprint arXiv:1312.6034*, 2013.
- 837 Socher, R., Perelygin, A., Wu, J., Chuang, J., Manning,  
838 C. D., Ng, A., and Potts, C. Recursive deep models for  
839 semantic compositionality over a sentiment treebank. In  
840 Yarowsky, D., Baldwin, T., Korhonen, A., Livescu, K.,  
841 and Bethard, S. (eds.), *Proceedings of the 2013 Confer-*  
842 *ence on Empirical Methods in Natural Language Process-*  
843 *ing*, pp. 1631–1642, Seattle, Washington, USA, October  
844 2013. Association for Computational Linguistics. URL  
845 <https://aclanthology.org/D13-1170>.
- 846 Sorensen, T., Robinson, J., Rytting, C., Shaw, A., Rogers,  
847 K., Delorey, A., Khalil, M., Fulda, N., and Wingate,  
848 D. An information-theoretic approach to prompt engi-  
849 neering without ground truth labels. In Muresan, S.,  
850 Nakov, P., and Villavicencio, A. (eds.), *Proceedings of*  
851 *the 60th Annual Meeting of the Association for Computa-*  
852 *tional Linguistics (Volume 1: Long Papers)*, pp. 819–  
853 862, Dublin, Ireland, May 2022. Association for Com-  
854 putational Linguistics. doi: 10.18653/v1/2022.acl-long.  
855 60. URL [https://aclanthology.org/2022.](https://aclanthology.org/2022.acl-long.60)  
856 [acl-long.60](https://aclanthology.org/2022.acl-long.60).
- 857 Stanley, K. O. and Lehman, J. *Why Greatness Cannot Be*  
858 *Planned: The Myth of the Objective*. Springer, 2015.
- 859 Stanley, K. O., Lehman, J., and Soros, L. Open-endedness:  
860 The last grand challenge you’ve never heard of. *While*  
861 *open-endedness could be a force for discovering intelli-*  
862 *gence, it could also be a component of AI itself*, 2017.
- 863 Sun, H., Hüyük, A., and van der Schaar, M. Query-  
864 dependent prompt evaluation and optimization with of-  
865 fline inverse rl. In *The Twelfth International Conference*  
866 *on Learning Representations*, 2023.
- 867 Sun, T., He, Z., Qian, H., Zhou, Y., Huang, X., and Qiu,  
868 X. BBTv2: Towards a gradient-free future with large  
869 language models. In Goldberg, Y., Kozareva, Z., and  
870 Zhang, Y. (eds.), *Proceedings of the 2022 Conference on*  
871 *Empirical Methods in Natural Language Processing*, pp.  
872 3916–3930, Abu Dhabi, United Arab Emirates, Decem-  
873 ber 2022. Association for Computational Linguistics. doi:  
874 10.18653/v1/2022.emnlp-main.259. URL [https://](https://aclanthology.org/2022.emnlp-main.259)  
875 [aclanthology.org/2022.emnlp-main.259](https://aclanthology.org/2022.emnlp-main.259).
- 876 Syswerda, G. A study of reproduction in generational and  
877 steady-state genetic algorithms. In *Foundations of genetic*  
878 *algorithms*, volume 1, pp. 94–101. Elsevier, 1991.
- 879 Team, G., Mesnard, T., Hardin, C., Dadashi, R., Bhupatiraju,  
S., Pathak, S., Sifre, L., Rivière, M., Kale, M. S., Love,  
J., Tafti, P., Hussenot, L., Sessa, P. G., Chowdhery, A.,  
Roberts, A., Barua, A., Botev, A., Castro-Ros, A., Slone,  
A., Héliou, A., Tacchetti, A., Bulanova, A., Paterson, A.,  
Tsai, B., Shahriari, B., Lan, C. L., Choquette-Choo, C. A.,  
Crepey, C., Cer, D., Ippolito, D., Reid, D., Buchatskaya,  
E., Ni, E., Noland, E., Yan, G., Tucker, G., Muraru, G.-  
C., Rozhdestvenskiy, G., Michalewski, H., Tenney, I.,  
Grishchenko, I., Austin, J., Keeling, J., Labanowski, J.,  
Lespiau, J.-B., Stanway, J., Brennan, J., Chen, J., Ferret,  
J., Chiu, J., Mao-Jones, J., Lee, K., Yu, K., Millican, K.,  
Sjoesund, L. L., Lee, L., Dixon, L., Reid, M., Mikula, M.,  
Wirth, M., Sharman, M., Chinaev, N., Thain, N., Bachem,  
O., Chang, O., Wahltinez, O., Bailey, P., Michel, P., Yotov,  
P., Chaabouni, R., Comanescu, R., Jana, R., Anil, R.,  
McIlroy, R., Liu, R., Mullins, R., Smith, S. L., Borgeaud,  
S., Girgin, S., Douglas, S., Pandya, S., Shakeri, S., De,  
S., Klimenko, T., Hennigan, T., Feinberg, V., Stokowiec,  
W., hui Chen, Y., Ahmed, Z., Gong, Z., Warkentin, T.,  
Peran, L., Giang, M., Farabet, C., Vinyals, O., Dean, J.,  
Kavukcuoglu, K., Hassabis, D., Ghahramani, Z., Eck, D.,  
Barral, J., Pereira, F., Collins, E., Joulin, A., Fiedel, N.,  
Senter, E., Andreev, A., and Kenealy, K. Gemma: Open  
models based on gemini research and technology, 2024.  
URL <https://arxiv.org/abs/2403.08295>.
- Turner, A. M., Thiergart, L., Leech, G., Udell, D., Vazquez,  
J. J., Mini, U., and MacDiarmid, M. Activation addition:  
Steering language models without optimization. *arXiv*  
*e-prints*, pp. arXiv-2308, 2023.
- Vo, A. and Luong, N. H. Efficient multi-objective neural  
architecture search via pareto dominance-based novelty  
search. In *Proceedings of the Genetic and Evolutionary*  
*Computation Conference*, pp. 1146–1155, 2024.
- Von Neumann, J., Burks, A. W., et al. Theory of self-  
reproducing automata. 1966.
- Von Oswald, J., Niklasson, E., Randazzo, E., Sacramento,  
J., Mordvintsev, A., Zhmoginov, A., and Vladymyrov,  
M. Transformers learn in-context by gradient descent.  
In *International Conference on Machine Learning*, pp.  
35151–35174. PMLR, 2023a.
- Von Oswald, J., Schlegel, M., Meulemans, A., Kobayashi,  
S., Niklasson, E., Zucchet, N., Scherrer, N., Miller, N.,



- 880 Sandler, M., Vladymyrov, M., et al. Uncovering mesa-  
881 optimization algorithms in transformers. *arXiv preprint*  
882 *arXiv:2309.05858*, 2023b.
- 883
- 884 Wan, X., Sun, R., Nakhost, H., and Arik, S. O. Teach  
885 better or show smarter? on instructions and exem-  
886 plars in automatic prompt optimization. *arXiv preprint*  
887 *arXiv:2406.15708*, 2024.
- 888
- 889 Wang, L., Li, L., Dai, D., Chen, D., Zhou, H., Meng, F.,  
890 Zhou, J., and Sun, X. Label words are anchors: An in-  
891 formation flow perspective for understanding in-context  
892 learning. In Bouamor, H., Pino, J., and Bali, K. (eds.),  
893 *Proceedings of the 2023 Conference on Empirical Meth-*  
894 *ods in Natural Language Processing*, pp. 9840–9855,  
895 Singapore, December 2023. Association for Computa-  
896 tional Linguistics. URL <https://aclanthology.org/2023.emnlp-main.609>.
- 897
- 898
- 899 Wang, R., Tang, D., Duan, N., Wei, Z., Huang, X., Ji, J., Cao,  
900 G., Jiang, D., and Zhou, M. K-Adapter: Infusing Knowl-  
901 edge into Pre-Trained Models with Adapters. In Zong,  
902 C., Xia, F., Li, W., and Navigli, R. (eds.), *Findings of the*  
903 *Association for Computational Linguistics: ACL-IJCNLP*  
904 *2021*, pp. 1405–1418, Online, August 2021. Association  
905 for Computational Linguistics. doi: 10.18653/v1/2021.  
906 findings-acl.121. URL <https://aclanthology.org/2021.findings-acl.121>.
- 907
- 908
- 909 Wang, Y., Zhang, P., Yang, B., Wong, D. F., and Wang, R.  
910 Latent space chain-of-embedding enables output-free llm  
911 self-evaluation. *arXiv preprint arXiv:2410.13640*, 2024.
- 912
- 913 Wei, J., Wang, X., Schuurmans, D., Bosma, M., Xia, F.,  
914 Chi, E., Le, Q. V., Zhou, D., et al. Chain-of-thought  
915 prompting elicits reasoning in large language models.  
916 *Advances in Neural Information Processing Systems*, 35:  
917 24824–24837, 2022.
- 918
- 919 Wei, J., Wei, J., Tay, Y., Tran, D., Webson, A., Lu, Y., Chen,  
920 X., Liu, H., Huang, D., Zhou, D., et al. Larger language  
921 models do in-context learning differently. *arXiv preprint*  
922 *arXiv:2303.03846*, 2023a.
- 923
- 924 Wei, Z., Wang, Y., Li, A., Mo, Y., and Wang, Y.  
925 Jailbreak and guard aligned language models with  
926 only few in-context demonstrations. *arXiv preprint*  
927 *arXiv:2310.06387*, 2023b.
- 928
- 929 Welleck, S., Bertsch, A., Finlayson, M., Schoelkopf, H., Xie,  
930 A., Neubig, G., Kulikov, I., and Harchaoui, Z. From de-  
931 coding to meta-generation: Inference-time algorithms for  
932 large language models. *arXiv preprint arXiv:2406.16838*,  
933 2024.
- 934
- Wen, Y., Jain, N., Kirchenbauer, J., Goldblum, M., Geiping,  
J., and Goldstein, T. Hard prompts made easy: Gradient-  
based discrete optimization for prompt tuning and discov-  
ery. *Advances in Neural Information Processing Systems*,  
36, 2024.
- Xiao, G., Tian, Y., Chen, B., Han, S., and Lewis, M. Ef-  
ficient streaming language models with attention sinks.  
*arXiv preprint arXiv:2309.17453*, 2023.
- Yang, A., Yang, B., Hui, B., Zheng, B., Yu, B., Zhou, C.,  
Li, C., Li, C., Liu, D., Huang, F., Dong, G., Wei, H., Lin,  
H., Tang, J., Wang, J., Yang, J., Tu, J., Zhang, J., Ma, J.,  
Xu, J., Zhou, J., Bai, J., He, J., Lin, J., Dang, K., Lu, K.,  
Chen, K., Yang, K., Li, M., Xue, M., Ni, N., Zhang, P.,  
Wang, P., Peng, R., Men, R., Gao, R., Lin, R., Wang, S.,  
Bai, S., Tan, S., Zhu, T., Li, T., Liu, T., Ge, W., Deng,  
X., Zhou, X., Ren, X., Zhang, X., Wei, X., Ren, X., Fan,  
Y., Yao, Y., Zhang, Y., Wan, Y., Chu, Y., Liu, Y., Cui, Z.,  
Zhang, Z., and Fan, Z. Qwen2 technical report. *arXiv*  
*preprint arXiv:2407.10671*, 2024a.
- Yang, C., Wang, X., Lu, Y., Liu, H., Le, Q. V., Zhou,  
D., and Chen, X. Large language models as optimiz-  
ers. *ArXiv*, abs/2309.03409, 2023. URL <https://api.semanticscholar.org/CorpusID:261582296>.
- Yang, S. Genetic algorithms with memory-and elitism-  
based immigrants in dynamic environments. *Evolutionary*  
*Computation*, 16(3):385–416, 2008.
- Yang, S., Kim, J., Jang, J., Ye, S., Lee, H., and Seo, M.  
Improving probability-based prompt selection through  
unified evaluation and analysis. *Transactions of the As-*  
*sociation for Computational Linguistics*, 12:664–680,  
2024b. doi: 10.1162/tacl.a.00666. URL <https://aclanthology.org/2024.tacl-1.37>.
- Yin, K. and Neubig, G. Interpreting language models with  
contrastive explanations. In Goldberg, Y., Kozareva, Z.,  
and Zhang, Y. (eds.), *Proceedings of the 2022 Conference*  
*on Empirical Methods in Natural Language Processing*,  
pp. 184–198, Abu Dhabi, United Arab Emirates, De-  
cember 2022. Association for Computational Linguistics.  
doi: 10.18653/v1/2022.emnlp-main.14. URL <https://aclanthology.org/2022.emnlp-main.14>.
- Yoo, K. M., Kim, J., Kim, H. J., Cho, H., Jo, H., Lee, S.-W.,  
Lee, S.-g., and Kim, T. Ground-truth labels matter: A  
deeper look into input-label demonstrations. In Goldberg,  
Y., Kozareva, Z., and Zhang, Y. (eds.), *Proceedings of the*  
*2022 Conference on Empirical Methods in Natural Lan-*  
*guage Processing*, pp. 2422–2437, Abu Dhabi, United  
Arab Emirates, December 2022. Association for Compu-  
tational Linguistics. doi: 10.18653/v1/2022.emnlp-main.

- 935 155. URL [https://aclanthology.org/2022.](https://aclanthology.org/2022.emnlp-main.155/)  
936 [emnlp-main.155/](https://aclanthology.org/2022.emnlp-main.155/).
- 937 Zhang, S., Dong, L., Li, X., Zhang, S., Sun, X., Wang, S.,  
938 Li, J., Hu, R., Zhang, T., Wu, F., et al. Instruction tuning  
939 for large language models: A survey. *arXiv preprint*  
940 *arXiv:2308.10792*, 2023.
- 942 Zhang, X., Zhao, J., and LeCun, Y. Character-level convolu-  
943 tional networks for text classification. *Advances in neural*  
944 *information processing systems*, 28, 2015.
- 945 Zhao, Y., Zheng, W., Cai, T., Xuan Long, D., Kawaguchi, K.,  
946 Goyal, A., and Shieh, M. Q. Accelerating greedy coordi-  
947 nate gradient and general prompt optimization via probe  
948 sampling. *Advances in Neural Information Processing*  
949 *Systems*, 37:53710–53731, 2024.
- 951 Zhao, Z., Wallace, E., Feng, S., Klein, D., and Singh, S.  
952 Calibrate before use: Improving few-shot performance  
953 of language models. In Meila, M. and Zhang, T. (eds.),  
954 *Proceedings of the 38th International Conference on Ma-*  
955 *chine Learning*, volume 139 of *Proceedings of Machine*  
956 *Learning Research*, pp. 12697–12706. PMLR, 18–24 Jul  
957 2021. URL [https://proceedings.mlr.press/](https://proceedings.mlr.press/v139/zhao21c.html)  
958 [v139/zhao21c.html](https://proceedings.mlr.press/v139/zhao21c.html).
- 959 Zheng, L., Chiang, W.-L., Sheng, Y., Zhuang, S., Wu, Z.,  
960 Zhuang, Y., Lin, Z., Li, Z., Li, D., Xing, E., et al. Judging  
961 llm-as-a-judge with mt-bench and chatbot arena. *Ad-*  
962 *vances in Neural Information Processing Systems*, 36:  
963 46595–46623, 2023.
- 965 Zheng, X., Pang, T., Du, C., Liu, Q., Jiang, J., and Lin, M.  
966 Improved few-shot jailbreaking can circumvent aligned  
967 language models and their defenses. *Advances in Neural*  
968 *Information Processing Systems*, 37:32856–32887, 2024.
- 970 Zhigljavsky, A. A. *Theory of global random search*, vol-  
971 ume 65. Springer Science & Business Media, 2012.
- 972 Zhou, Y., Muresanu, A. I., Han, Z., Paster, K., Pitis, S.,  
973 Chan, H., and Ba, J. Large language models are human-  
974 level prompt engineers. In *The Eleventh International*  
975 *Conference on Learning Representations*, 2022.
- 976 Zhu, Z., Shahtalebi, S., and Rudzicz, F. Predicting fine-  
977 tuning performance with probing. In Goldberg, Y.,  
978 Kozareva, Z., and Zhang, Y. (eds.), *Proceedings of the*  
979 *2022 Conference on Empirical Methods in Natural Lan-*  
980 *guage Processing*, pp. 11534–11547, Abu Dhabi, United  
981 Arab Emirates, December 2022. Association for Compu-  
982 tational Linguistics. doi: 10.18653/v1/2022.emnlp-main.  
983 793. URL [https://aclanthology.org/2022.](https://aclanthology.org/2022.emnlp-main.793/)  
984 [emnlp-main.793](https://aclanthology.org/2022.emnlp-main.793/).
- 986 Zou, A., Wang, Z., Kolter, J. Z., and Fredrikson, M. Uni-  
987 versal and transferable adversarial attacks on aligned lan-  
988 guage models. *arXiv preprint arXiv:2307.15043*, 2023.
- 989

## A. Related Work

**LLM Prompt Optimization.** LLMs are sensitive to even minor variations in prompts, making their responses difficult to predict without trial and error (Liu et al., 2023). This highlights the need for automated prompt tuning to optimize prompts for specific tasks. Existing research can be broadly classified into two categories: 1) Soft Prompt Tuning (Lester et al., 2021; Qin & Eisner, 2021; Li & Liang, 2021), which optimizes continuous embeddings in the LLM’s representation space, replacing discrete prompts with learnable tokens. These embeddings, typically optimized via gradient descent, can outperform hard prompts when applied to intermediate model layers (Sun et al., 2022), similar to parameter-efficient tuning like adapters (Wang et al., 2021); 2) Hard Prompt Optimization: Shin et al. (2020); Deng et al. (2022); Zou et al. (2023); Jones et al. (2023); Choi et al. (2024); Wen et al. (2024) use token-level search algorithms to reward effective tokens and penalize ineffective ones. While promising, these methods often produce non-human-like prompts. In contrast, a more popular line optimizes prompts in natural language, often using LLMs directly as prompt engineers (Zhou et al., 2022; Yang et al., 2023; Guo et al., 2023; Chen et al., 2023; Fernando et al., 2024; Lin et al., 2024; Cui et al., 2024). By combining LLMs with algorithmic designs like evolutionary algorithms (Fernando et al., 2024), these methods achieve expert-level performance.

**In-context Learning Studies.** Here, we briefly review the literature highlighting the mechanistic studies of ICL, the emergent capability of LLMs. Notably, the underlying mechanisms behind emergent in-context learning remain unclear. The main debate revolves around the mesa-optimization hypothesis (Dai et al., 2023; Von Oswald et al., 2023b;a; Ahn et al., 2023; Cheng et al., 2023; Fu et al., 2023a). Specifically, they argue that these models implement subsidiary learning algorithms that adjust the model inner representations as new inputs are received, with update rules resembling gradient-based optimization of a principled objective. For instance, Von Oswald et al. (2023a) shows that linear self-attention can emulate gradient descent on simple linear regression tasks. However, most of these findings cannot generalize to practical LLM tasks: First, Min et al. (2022) shows that input-label correspondence in demonstrations has little impact on task results. Furthermore, Shen et al. (2023a); Deutch et al. (2024) provide concrete evidence against the validity of such hypotheses in NLP tasks.

**AI alignment.** Alignment (Gabriel, 2020; Ngo et al., 2022) describes a process of encoding human values and goals into AI assistants to make them as helpful, safe, and reliable as possible. Recent advances of LLMs also motivate extensive studies to align LLM chatbots to human values (Shen et al., 2023b). LLM alignment typically involves two steps. In the instruction-tuning stage (Longpre et al., 2023; Zhang et al., 2023), LLMs are given instruction-response pairs of the tasks so they can learn by imitating the output. In the critique phase, a human or another AI interacts with the model and grades its responses in real-time, known as the reinforcement learning from human or AI feedback (Ouyang et al., 2022; Lee et al., 2023). It seems that LLM researchers are already able to significantly improve the alignment progress as the increasing performance numbers in a wide range of benchmarks and the improved win rates of their optimized LLMs against other LLMs. However, just as Ngo et al. (2022); Di Langosco et al. (2022) hypothesize that, these “aligned” LLMs may only experience superficial outer alignment as they can still be prompted to generate undesired output (Zou et al., 2023; Greenblatt et al., 2024). This necessitates further studies on the inner alignment problem (Ngo et al., 2022).

## B. A Pilot Study with TAPruning

In this section, we provide a pilot study of the *Partial Context Hypothesis* across prompts, models and tasks. As introduced in Section 3.1, where we lack well-established methods for this hypothesis, we begin our investigation with a simple, easy-to-implement hill-climbing search, *TAPruning*. Please refer to Section 3.4 for a more effective algorithmic framework.

### B.1. TAPruning Additional Details

**Algorithmic Descriptions.** We present the pseudocode of our *TAPruning* algorithm in Algorithm 1. As stated, our algorithm maintains a tracked prompt, denoted as  $T$ , which serves as the basis for conducting local search operations. As presented in the do-while loop in Algorithm 1, we employ a left-to-right token pruning process, iterating sequentially from the leftmost token to the rightmost, attempting to remove each token at every iteration. The generated new prompt  $P$  experiences performance evaluation and comparison against the optimal performance  $f^{\text{Optimal}}$ . If it improves or at least, degrades within a certain threshold  $\delta$ , we will accept the prompt  $P$  as the new tracked prompt  $T$ , which we may revisit in the next iteration loop. If it improves, we will also update the optimal prompt  $S = P$ . Until no further tokens are removable under the performance constraints, we return the optimal prompt  $S$  we discovered as the final solution. Please note that

---

**Algorithm 1** Threshold Accepting (*TAPruning*) for Prompt Pruning

---

**Input:** prompt  $X$ ,  $x_1 \cdots x_N$ , dataset  $\mathcal{D}$ , performance measure function  $f$ , language model  $\mathcal{M}$ , Threshold  $\delta$   
**Output:** Solution  $S$   
 Measure the performance  $f^X$  for prompt  $X$  on  $\mathcal{D}$  for language model  $\mathcal{M}$  as the original prompting performance  $f^{\text{Original}}$ , which is also used to initialize current optimal prompting performance  $f^{\text{Optimal}} = f^{\text{Original}}$ .  
 Initialize tracked prompt  $T = X$ ,  $t_1 \cdots t_N = x_1 \cdots x_N$ .  
 Initialize optimal prompt  $S = X$ ,  $s_1 \cdots s_N = x_1 \cdots x_N$ .  
**repeat**  
   Initialize length variable  $L$  as the number of the tokens in current tracked prompt  $T$  (re-tokenized).  
   **for**  $i = 1$  **to**  $L$  **do**  
     Generate a neighborhood prompt  $P$  by removing the token  $t_i$  from prompt  $T$ .  
     Calculate the performance  $f^P$  for  $P$  on  $\mathcal{D}$ ,  
     If  $f^P > f^{\text{Optimal}}$ , we accept and update the prompt  $T = P$ , optimal prompt  $S = P$ , and update the optimal performance record  $f^{\text{Optimal}} = f^P$ .  
     If  $f^P < f^{\text{Optimal}}$ , we accept  $P$  as the new  $T$  only if  $f^P > f^{\text{Optimal}} \times \delta$  (within the threshold).  
   **end for**  
**until** The solution  $S$  converges

---

**Algorithm 2** Steepest-Ascent Hill Climbing (*SAHCPuning*) for Prompt Pruning

---

**Input:** prompt  $X$ ,  $x_1 \cdots x_N$ , dataset  $\mathcal{D}$ , performance measure function  $f$ , language model  $\mathcal{M}$ , Threshold  $\delta$   
**Output:** Solution  $S$   
 Measure the performance  $f^X$  for prompt  $X$  on  $\mathcal{D}$  for language model  $\mathcal{M}$  as the original prompting performance  $f^{\text{Original}}$ , which is also used to initialize current optimal prompting performance  $f^{\text{Optimal}} = f^{\text{Original}}$ .  
 Initialize tracked prompt (also as optimal prompt)  $S = X$ ,  $s_1 \cdots s_N = x_1 \cdots x_N$ .  
 Initialize optimal token index candidate  $T_c = -1$ .  
**repeat**  
   Initialize length variable  $L$  as the number of the tokens in current tracked prompt  $S$  (re-tokenized).  
   **for**  $i = 1$  **to**  $L$  **do**  
     Generate a neighborhood prompt  $P$  by removing the token  $s_i$  from prompt  $S$ .  
     Calculate the performance  $f^P$  for  $P$  on  $\mathcal{D}$ ,  
     If  $f^P > f^{\text{Optimal}}$ , update the optimal performance record  $f^{\text{Optimal}} = f^P$  and optimal token index candidate  $T_c = i$ .  
   **end for**  
   **if**  $T_c$  is not -1 **then**  
     Update tracked prompt  $S$  by removing token  $s_{T_c}$   
     Update  $T_c = -1$   
   **end if**  
**until** The solution  $S$  converges

---

the tokens (tokenized) may change through the optimization as the prompt changes in its surface form, as we desire the optimized prompts to be portable strings. Preliminary experiments show that the *Partial Context Hypothesis* also works if we retain the same prompt tokens through optimization.

We discuss other design choices, especially attempting to leverage insights from LLM mechanistic interpretability studies, such as attribution methods (Li et al., 2016a), in Appendix C. These methods can generate a token ranking in a single forward-backward pass, potentially leading to significant speedups. However, as observed, they generally fail to effectively guide performance improvement, making them unsuitable for our problem. We present *SAHCPuning* in Algorithm 2, which accepts the update only if this move (i.e., how to remove the next single token) is the best possible move among all available options. This algorithm limits in its high computational cost: since ICL prompts always take more than hundreds of tokens, i.e., the problem is relatively high-dimensional, the search would become much slower and less scalable, e.g., Table 11. Also, due to the deceptive, multimodal nature of the search landscape, *SAHCPuning* does not always outperform *TAPuning* (Table 1).

Table 5. Details of our classification datasets evaluated in this work.  $|C|$ : # of classes for classification tasks.  $|\text{Test}|$ : # of testing samples for each particular dataset.

Dataset	Type	$ C $	$ \text{Test} $	Label words
SST-2	Sentiment (Movie reviews)	2	1.8k	terrible, great
Subj	Subjectivity (Movie reviews)	2	2k	subjective, objective
AG’s News	Topic (News articles)	4	7.6k	World, Sports, Business, Tech
Yelp-5	Sentiment (Yelp reviews)	5	50k	terrible, bad, okay, good, great
SNLI	Natural Language Inference	3	10k	Yes, Unknown, No
Yahoo	Topic (Question types)	10	60k	culture, science, health, education, computer, sports, business, music, family, politics

## B.2. Pilot Study

**Datasets.** Our investigation covers four task types: classification, multiple-choice question answering, generation, and chain-of-thought reasoning. Unless otherwise stated, we sample from their official validation set for the prompt selection, and report on their official testing split for final evaluation. 1) Classification: We evaluate sentiment analysis (SST-2 (Socher et al., 2013), Yelp-5 (Asghar, 2016)), subjectivity classification, Subj (Pang & Lee, 2004), topic classification (AG’s News (Zhang et al., 2015) and Yahoo (Labrou & Finin, 1999)), and natural language inference (SNLI (Bowman et al., 2015)). We present the overall statistics in Table 5; 2) Multi-choice questions: We include commonsense reasoning datasets, PIQA (Bisk et al., 2020), a binary-choice question answering dataset with verbalizers A and B. Since its testing performance can only be assessed via submission to the leaderboard, we sample from their training set to form our held-out set for prompt selection and evaluate on the official validation set, which consists of 2,000 examples, for the final performance assessment; 3) Generation: We include Yelp Sentiment Transfer (Shen et al., 2017) (Yelp Style.), where we follow Deng et al. (2022) in an unsupervised style transfer setting, sampling from its development set for prompt selection and using its test set for final evaluation, with reference collected by Li et al. (2018a) for both transfer directions (e.g., positive-to-negative and negative-to-positive); 4) Chain-of-Thought (CoT) reasoning: We include GSM8K (Cobbe et al., 2021) and MAWPS (Koncel-Kedziorski et al., 2016).

**Models and Baselines.** We evaluate a range of popular LLMs varying in architecture, scale, and alignment efforts. Concretely, 1) Classification: we study base models: RoBERTa-large (Liu et al., 2019), GPT-2 (Radford et al., 2019), Meta-Llama-3-8B, Meta-Llama-3-70B (AI@Meta, 2024), instruction-tuned model (SFT): Gemma-7b-it (Team et al., 2024), and further reinforcement learning-tuned (RLHF) models: Meta-Llama-3-8B-Instruct, and Meta-Llama-3-70B-Instruct (AI@Meta, 2024); 2) Multi-choice question answering: Meta-Llama-3-8B & Meta-Llama-3-8B-Instruct; 3) Generation: GPT-2 & Meta-Llama-3-8B-Instruct; 4) Reasoning: Meta-Llama-3-8B-Instruct, Mistral-7B-Instruct (Jiang et al., 2023a) and Qwen2-7B-Instruct (Yang et al., 2024a). In this section, we focus on results from RoBERTa-large and Meta-Llama-3-8B-Instruct. Results for other models, along with PROMPTQUINE, are presented in the corresponding Appendix sections that follow. We include both the original ICL and RLPrompt (Deng et al., 2022)—a state-of-the-art prompt optimization method—as well as a token-level search algorithm for the “secret language” baseline. It is important to note that this approach cannot be applied to CoT reasoning tasks. For ICL prompts, we primarily use one-shot ICL, where each prompt for four-way classification is constructed by randomly sampling one instance and its label from each category in the training split. Two-shot prompts (two input-output pairs) are used for style transfer. For ICL on classification and multiple-choice question answering, results are averaged over 10 random seeds, each with a unique ICL prompt. For generation and reasoning tasks, we average over 5 seeds. For RLPrompt, results are averaged over 3 seeds. We also use the entire held-out set for prompt selection in RLPrompt. Specifically, we first rank the explored prompts by their reward scores, select the top 50, and then re-rank them based on validation performance. We also explore using more training task samples for reward calculation but observe minimal performance gains. Thus, we adopt the original 16-shot setup from Deng et al. (2022) for classification and use 200 unsupervised samples for style transfer, training over five tokens with default hyperparameters.

**Prompt Template Details.** First, for the RLPrompt, we use the following template for most of the classification tasks, following (Schick & Schütze, 2021; Deng et al., 2022):

115 *RLPrompt - Classification:*

1156  
1157 {Input} {Prompt}

1158  
1159 That is, we replace the “{Input}” placeholder with the task input instance. The policy network directly generates the prompt,  
1160 replacing the “{Prompt}” placeholder. For masked language models, such as RoBERTa-large, we directly append a [MASK]  
1161 into the last of the template, run the prompt, and parse its task predictions from that token. One exception is the natural  
1162 language inference task, which involves two inputs (the premise & the hypothesis). We provide its template as below:

1163 *RLPrompt - Natural Language Inference:*

1164  
1165 {Premise} {Hypothesis} {Prompt} Entailment:

1166  
1167 Then, we provide its template for multi-choice question answering:

1168 *RLPrompt - Multi-choice Question Answering:*

1169  
1170 {Prompt}  
1171 Question: {Input}  
1172 Options: A) {Option1} B) {Option2}  
1173 Answer:

1174  
1175 The template for style transfer:

1176  
1177 *RLPrompt - Text Style Transfer:*

1178  
1179 {Prompt} "{Input}" "

1180 Just as (Deng et al., 2022) does, we allow the model to generate tokens one by one until we meet a special character " (the  
1181 quotation mark). We then parse the completions inside the quotation marks as final task output.

1182  
1183 Next, we provide our templates for our ICL prompts, which also serve as the basis for our prompt pruning.

1184 *ICL - Sentiment Analysis (SST-2 and Yelp-5):*

1185  
1186 {Examples}  
1187  
1188 Review: {Input}  
1189 Sentiment:

1190  
1191 For “{Examples}”, we use the same format to organize the input-output task pairs as we do for the input task instances.  
1192 This principle applies to all our ICL prompts regardless of tasks.

1193  
1194 We discuss templates for other tasks as follows:

1195 *ICL - Subjectivity Classification (Subj):*

1196  
1197 {Examples}  
1198  
1199 Sentence: {Input}  
1200 Viewpoint:

1201  
1202 *ICL - News Topic Classification (AG’s News):*

1203  
1204 {Examples}  
1205  
1206 Article: {Input}  
1207 Answer:

1208  
1209 *ICL - Natural Language Inference (SNLI):*

1210 {Examples}  
 1211  
 1212 Hypothesis: {Hypothesis}  
 1213 Premise: {Premise}  
 1214 Given the premise, is the hypothesis true? Yes, No or Unknown?  
 1215 The answer is:  
 1216  
 1217 *ICL - Topic Classification (Yahoo):*  
 1218  
 1219 {Examples}  
 1220  
 1221 Sentence: {Input}  
 1222 Topic:  
 1223  
 1224 *ICL - Multi-choice Question Answering (PIQA):*  
 1225  
 1226 {Examples}  
 1227  
 1228 Question: {Input}  
 1229 Options: A) {Option1} B) {Option2}  
 1230 Answer:  
 1231  
 1232 *ICL - Text Style Transfer (Yelp Sentiment.):*  
 1233  
 1234 {Examples}  
 1235 Here is a text, which is [negative/positive]: "{Input}".  
 1236 Here is a rewrite of the text, which is [positive/negative]: "  
 1237  
 1238 We alternate between the sentiment signal words, “negative” and “positive”, for two token choices for target sentiment  
 1239 direction. For example, for positive transfer, we use negative and positive respectively. Similarly, we parse the completions  
 1240 inside the quotation marks as final task output.  
 1241  
 1242 *ICL - Chain-of-thought Reasoning (GSM8K & MAWPS):*  
 1243  
 1244 {Examples}  
 1245  
 1246 Question: {Input}  
 1247 Let’s think step by step.  
 1248  
 1249 The models are then expected to follow the exemplar patterns, i.e., generating the reasoning chains before predicting the  
 1250 task answer. For this particular task, as we lack the direct annotations of the ground truth reasoning chains, we conduct  
 1251 the following steps to collect our CoT prompts: 1) GSM8K (Cobbe et al., 2021): we directly sample and adopt the ICL  
 1252 prompts provided by the Chain-of-Thought Hub (Fu et al., 2023b); 2) MAWPS (Koncel-Kedziorski et al., 2016): we ask  
 1253 GPT-4o (Hurst et al., 2024) to generate the reasoning chains for the training questions we sampled, which are then paired to  
 1254 construct the corresponding ICL prompts.  
 1255  
 1256 **Evaluation settings.** During the search stage, each prompt’s quality is evaluated on 200 samples from the official validation  
 1257 split (as our held-out set), or the training split if the validation is unavailable (e.g., PIQA). We report performance on the  
 1258 official test set (i.e., validation set for PIQA).  
 1259  
 1260 **Evaluation Metrics.** As stated, we report testing accuracy for classification, multi-choice question answering and  
 1261 reasoning tasks. For style transfer, we follow Deng et al. (2022) to use their fine-tuned style classifiers for *Style* calculation,  
 1262 pre-trained LM to calculate input-output alignment (Deng et al., 2021), *Content*, and a pre-trained grammaticality classifier  
 1263 (Krishna et al., 2020) for *Fluency*. Then, we average these sentence-level scores, as the *Joint Score*, strictly following  
 1264

Table 6. Task performance evaluation of *TAPruning* upon original 1-shot ICL prompts. For classification, multi-choice answering (PIQA) and math reasoning (GSM8K & MAWPS), we report *accuracy* on their test set. For style transfer (Yelp sentiment transfer, Yelp Style.), we report their *joint score* on a separate 500 sample set, following (Krishna et al., 2020; Deng et al., 2022). We evaluate using greedy decoding. We report classification performance on RoBERTa-large (Liu et al., 2019) and overall task performance on Meta-Llama-3-8B-Instruct (AI@Meta, 2024) (Llama3-8B-It). Note that RLPrompt (Deng et al., 2022) cannot be applied to CoT reasoning, so we leave those cells blank. The numbers in (parentheses) are the standard deviations between different prompts.

LLM	Methods	SST-2	Subj	AG’s News	Yelp-5	SNLI	Yahoo	Yelp Style.	PIQA	GSM8K	MAWPS
RoBERTa-large	ICL	86.2 (7.7)	53.8 (5.3)	57.2 (3.6)	27.3 (2.1)	33.3 (1.2)	36.8 (9.9)	-	-	-	-
	RLPrompt	92.5 (0.8)	81.2 (1.7)	80.2 (0.7)	44.8 (4.3)	33.5 (0.8)	48.6 (1.0)	-	-	-	-
	<i>TAPruning (Ours)</i>	90.8 (2.6)	80.9 (1.6)	79.7 (2.3)	42.8 (6.9)	42.0 (5.9)	51.4 (1.5)	-	-	-	-
Llama3-8B-It	ICL	95.9 (0.6)	66.7 (4.3)	83.7 (1.9)	52.2 (6.0)	61.9 (2.0)	57.1 (6.9)	54.4 (6.9)	75.4 (1.6)	68.0 (7.4)	75.6 (9.4)
	RLPrompt	88.4 (1.5)	82.9 (0.5)	84.7 (0.7)	48.1 (1.0)	42.4 (4.2)	58.5 (0.6)	8.3 (2.8)	85.9 (2.6)	-	-
	<i>TAPruning (Ours)</i>	95.0 (1.5)	74.5 (3.9)	88.6 (0.3)	60.2 (0.9)	68.6 (2.9)	61.7 (1.7)	59.6 (1.3)	75.1 (3.0)	77.1 (2.1)	85.0 (3.9)

Krishna et al. (2020)’s protocol:

$$J(\text{Content, Style, Fluency}) = \text{mean}_{\mathbf{x} \in \mathcal{X}} (\text{Content}(\mathbf{x}) \cdot \text{Style}(\mathbf{x}) \cdot \text{Fluency}(\mathbf{x})) . \tag{2}$$

**Results.** As shown in Table 6, pruning the original ICL prompts can improve performance, supporting our *Partial Context Hypothesis*. Surprisingly, this approach works well for chain-of-thought reasoning, where the outputs are highly structured and answers are distant from the prompt—an unexpected result for such a complex task. Remarkably, pruned prompts could deliver competitive performance, often surpassing RLPrompt across several tasks, effectively bridging the gap between the “secret language” (i.e., unnatural language artifacts discovered by previous token-level search algorithms) and original natural language prompts. Note that the improvement is independent of the ICL prompts we sampled, suggesting a potentially more effective approach to stabilize ICL performance (Lu et al., 2022; Rubin et al., 2022). We believe these results can inspire novel prompt optimization or in-context learning stabilization algorithms. We thus explore this further in Section 3.4, with our *TAPruning* serving as a baseline for the pruning-based prompt optimization. Despite its simplicity, this baseline remains competitive—being comparable or directly outperforming previous state-of-the-art methods in both performance and efficiency (e.g., Table 11), making it a strong contender. It is also intriguing to analyze what is left after the pruning, which can potentially inspire some mechanistic insights. We provide such analysis in Section 5.2.

Table 7. Zero-shot chain-of-thought performance on the MultiArith (Roy & Roth, 2015) dataset using InstructGPT (text-davinci-002) (Ouyang et al., 2022). The natural language prompt was proposed in (Zhou et al., 2022) to enable the zero-shot chain-of-thought reasoning of large language models. We produce these experiments using the answer extraction script from (Kojima et al., 2022).


No.	Category	Zero-shot CoT Trigger Prompt	Accuracy
1	APE (Zhou et al., 2022)	Let’s work <b>this</b> out <b>in a</b> step by step <b>way</b> to be sure we have the right answer.	81.5
2	Pruned	Let’s work out step by step <b>to be</b> sure we <b>have the</b> right answer.	85.3
3		Let’s work out step by step sure we right answer.	<b>86.7</b>
-		(Empty)	17.7

### C. Alternative Prompt Pruning Design Choices


In this section, we discuss some potential alternative design choices that may be used in prompt pruning to provide more background about why we start with the hill-climbing method describe in Section B in exploring the *partial Context Hypothesis* and inspire future works.

The algorithms discussed below aim to improve prompt pruning speed by leveraging the information inherently provided by LLMs for the given task. Approaches requiring significant efforts, such as probing techniques to learn task proxies (Zhu et al., 2022), which depend on large collections of prompt-performance pairs for supervision, are not considered due to their impracticality. We also do not include the studies of ICL-gradient descent correspondence hypothesis here, where the





(a) How the Task *Testing Accuracy* changes (SST-2, Subj and AG’s News), guided by attribution scores, when increasing the percent of pruned tokens.



(b) How the Task *Testing Accuracy* changes (SST-2, Subj and AG’s News), guided by attention weights, when increasing the percent of pruned tokens.

Figure 5. Pruning-based prompting performance using a variety of methods (*Top* for attribution scores guided pruning, and *Bottom* for attention weights guided pruning).

representational similarity may indicate task performance, as recent work (Shen et al., 2023a; Deutch et al., 2024) invalidate the effectiveness of such hypothesis in generalizing to practical NLP tasks for LLMs. Please note that the algorithms below are all inspired by the developments in mechanistic understandings of LLMs. Some of them might only be applicable in white-box scenarios.

**Instance attribution scores as guidance.** Instance attribution methods aim to improve interpretability by identifying influential tokens for a model’s prediction. Common approaches include gradient-based methods (e.g., gradient  $\times$  input saliency (Baehrens et al., 2010; Li et al., 2016a)) and erasure-based methods (Li et al., 2016b; Feng et al., 2018), which measure the change in output when masking tokens. Our approach (e.g., TA) aligns with erasure methods, which are computationally expensive due to the need for multiple input perturbations. This raises the question of whether gradient-based methods can be adapted to approximate token rankings within a single forward-backward pass (Feng et al., 2018). If so, we can directly use the attribution scores to guide the pruning.

**Token attention weights as guidance.** Attention mechanisms are crucial for understanding how LLMs process prompts and assign token importance. Analyzing attention distributions across layers can rank token significance, with higher attention scores indicating greater influence on task prediction (Xiao et al., 2023; Ge et al., 2023). We aggregate attention weights across heads in specific layers to compute token importance scores, guiding pruning.

### C.1. Experiments

We evaluate the aforementioned methods on several classification datasets and demonstrate their limited utility in the context of prompt compression as guided prompt search reformulation.

Table 8. Classification accuracies of optimal prompts for *TAPruning* and alternative pruning methods based on attribution scores and attention weights in GPT-2 across various datasets.

Method	SST-2	Subj	Yelp-5
ICL (1-shot, original)	54.2 (4.8)	64.3 (9.8)	30.9 (5.2)
Gradient Norm	66.5 (7.5)	72.3 (0.0)	33.6 (4.6)
Input $\times$ Gradient	66.8 (5.2)	75.1 (1.7)	33.9 (3.5)
Contrastive Gradient Norm	66.1 (8.6)	75.9 (2.4)	31.5 (2.8)
Contrastive Input $\times$ Gradient	52.0 (1.5)	75.7 (2.9)	31.5 (2.8)
First Layer	57.3 (7.0)	74.7 (2.2)	35.7 (4.8)
Layer Aggregated	60.2 (4.1)	72.3 (0.0)	30.2 (3.0)
<i>TAPruning</i> (Ours)	<b>68.1 (10.6)</b>	<b>75.9 (2.5)</b>	<b>39.9 (1.8)</b>

**Experimental Setups.** We perform experiments on SST-2, Subj, and Yelp-5 using GPT-2, sampling five ICL prompts per dataset. Importance scores are computed once based on the same 200 samples, with performance evaluated on the official test split. 1) Instance attribution scores: we experiment with state-of-the-art approaches, including Gradient Norm (Simonyan, 2013; Li et al., 2016a) and Input  $\times$  Gradient (Denil et al., 2014; Shrikumar et al., 2016) as well as their contrastive versions (Yin & Neubig, 2022). Token importance scores are aggregated across the 200 samples to generate final rankings, which are then used to guide token pruning; 2) Token attention weights: For each task, we use the first-layer attention scores and the aggregated attention scores (average) across all layers as the *First Layer* and *Layer Aggregated* importance scores, respectively. Prompt pruning is then performed according to the derived attention scores.

**Results.** We examine the impact of increasing token pruning percentages on task accuracy (Figure 5). If the derived scores guide pruning effectively, accuracy should first increase monotonically, then decrease beyond a certain threshold. However, as shown in Figure 5, all approaches exhibit nonlinear fluctuations, with their optimal performance still lagging behind our hill-climbing approach (Table 8). This suggests these methods are ineffective at guiding pruning. Also, please note that unlike the hill-climbing approach discussed in Section B, the methods presented in this section do not converge to a single optimal prompt. Instead, as shown in Table 8, we can only obtain the results by experimenting with and selecting from all the prompts derived on the validation set based on their importance scores, which is also less flexible. Finally, just as the failures of existing prompt compression methods to guide the pruning (shown in Table 1), we stick with our *TAPruning*, the hill-climbing approach, in section B to first gain a basic intuition of our *Partial Context Hypothesis*.

## D. PROMPTQUINE Additional Details

### D.1. Genetic Algorithm Details

**Introduction.** As outlined in Algorithm 3, we evolve a population  $\mathcal{P}$  of  $\#p$  individuals (here, pruned ICL prompts  $P$  as *phenotypes*). At every generation, each  $P$  is evaluated, producing a fitness score  $f(P)$ . The selection process then identifies high potential individuals typically the best-performing ones, using methods like tournament selection. Genetic operators, such as mutation, are applied to generate offspring: mutation introduces small, random changes (e.g., pruning tokens), while crossover (i.e., exchanging tokens) is excluded in this case due to its limited benefits on performance and its potential to complicate the search space, which is also a common practice (Real et al., 2017; Co-Reyes et al., 2021). The offspring are then evaluated, and elitism-based selection determines which individuals survive to the next generation. This process repeats iteratively until a termination condition is met, such as achieving a satisfactory fitness level or reaching a predefined number of generations.

**Implementation Details.** Here, we present the details of our GGA and SSGA implementations discussed in Section 3.4. Specifically, we provide their pseudo-codes: Algorithm 4 for GGA and Algorithm 5 for SSGA, both of which replace the main loop in Algorithm 3. Each approach has distinct trade-offs. As illustrated in Algorithm 4, GGA divides the reproduction process into multiple generations, with several reproduction events occurring within each. In our setup, the number of offspring ( $\#c$ ) often exceeds the population size ( $\#p$ ), encouraging each individual to participate as a parent.

**Algorithm 3** Genetic Prompt-Quine (PROMPTQUINE) Framework for Prompt Subsequence Search

**Input:** prompt  $X, x_1 \dots x_N$ , training dataset  $\mathcal{D}_{train}$ , validation dataset  $\mathcal{D}_{val}$ , fitness function  $f$ , primary task performance measure  $m$ , population size  $\#p$ , sample size  $\#s$ , number of iterations  $\#n$ , language model  $\mathcal{M}$ , elite calibration selection function  $R$

**Output:** Prompt  $P$

$\mathcal{P} \leftarrow \text{population-init}(X, \mathcal{M}, f, \mathcal{D}_{train}, \#p)$ .

History  $\mathcal{H} \leftarrow \mathcal{P}$ .

**for**  $i = 1$  **to**  $\#n$  **do**

$\mathcal{S}^{(i)} \leftarrow \text{sample}(\mathcal{P}, \#s)$ .

    Parent  $\leftarrow \text{select}(\mathcal{S}^{(i)})$ .

    Child  $\leftarrow \text{copy-then-mutate}(\text{Parent})$ .

    Scores  $\leftarrow \text{evaluate}(\text{Child}, \mathcal{M}, f, \mathcal{D}_{train})$ .

$\mathcal{P}, \mathcal{H} \leftarrow \text{push-pop}(\text{Child}, \text{Scores}, \mathcal{P}, \mathcal{H}, \#p, i)$ .

**end for**

Elite  $\mathcal{E} \leftarrow R(\mathcal{H})$

Prompt  $P \leftarrow \text{prompt-rank}(\mathcal{E}, \mathcal{M}, m, \mathcal{D}_{valid})$ .

The framework converges either when a predefined iteration limit is reached or, more commonly, when the minimal prompt length threshold ( $\#l$ ) is met. GGA is well-suited for parallelization, which can further enhance the results by leveraging computations. In our current implementation, we mainly use batching along with efficient LLM serving tools, such as vLLM (Kwon et al., 2023), which demonstrates improved runtime efficiency.

The core difference between SSGA and GGA lies in SSGA’s self-adaptation of parameters, such as mutation rate and selection pressure, throughout the evolutionary process. As outlined in Algorithm 5, SSGA continuously updates the population with new offspring at each step. We also allow more offspring before inclusion through regularized evolution, introducing genetic diversity in real time—akin to a self-adaptive mutation rate. Additionally, by dynamically increasing the population size, SSGA creates a self-adaptive selection pressure, potentially increasing the likelihood of each individual becoming a parent. The evolution process terminates under the same conditions as GGA, typically when the iteration limit is reached. Compared to GGA, SSGA is more exploratory but sacrifices some runtime efficiency due to the lack of batching and parallelization. As a result, we primarily use SSGA for 1-shot ICL pruning experiments (10,000 iterations), while GGA, which converges faster, is used for more-shot ICL pruning experiments. Later experiments show that, for most landscapes we encounter, GGA performs comparably to SSGA.

Table 9. **Hyperparameters.** Through extensive experiments, the current hyperparameters have proven stable across the tasks presented in the 1-shot ICL pruning studies. For more-shot experiments, we recommend increasing the number of iterations, and, if computational resources permit, enlarging the population and offspring sizes as well.

Hyperparameter	Default Value	Description
Population Size	30	How many individuals per population.
Offspring Size	50	How many offspring individuals generated per generation.
Mutation rate	[1,2,3,4]	The possible range of bits we change for reproduction.
Tournament Selection Ratio	0.2	The ratio of individuals sampled for tournament selection.
Number of Iterations	10,000	The maximal number of prompts we explored through pruning.
Minimal Prompt Length Threshold	15	The expected minimum average population prompt length for search termination.

**Hyperparameters.** We present our shared hyperparameters for both SSGA and GGA under 1-shot ICL pruning in Table 9. If additional resources are available, we highly recommend increasing both the population and offspring sizes, as this can yield significant performance benefits. Moreover, we believe that employing a more adaptive mutation rate can be beneficial, which we leave as future work (e.g., using a larger mutation rate in the early stages and gradually annealing it over time may enhance performance).

---

**Algorithm 4** PROMPTQUINE’s Generational GA (GGA) implementation for Prompt Subsequence Search

---

1485 **Input:** Initial population  $\mathcal{P}$ , with population size  $\#p$ , number of maximal iterations  $\#n$ , minimal prompt length threshold  
1486  $\#l$ , training dataset  $\mathcal{D}_{train}$ , fitness function  $f$ , offspring size  $\#c$ , language model  $\mathcal{M}$ , tournament selection ratio  $\#k$ ,  
1487 mean population prompt length calculation function  $h$   
1488 **Output:** Prompt History  $\mathcal{H}$   
1489 History  $\mathcal{H} \leftarrow \mathcal{P}$ .  
1490 **for**  $i = 1$  **to**  $\#n$  **do**  
1491     Initialize  $g \leftarrow \text{Empty}$ .  
1492     Initialize mean population prompt length  $L \leftarrow h(\mathcal{P})$ .  
1493     **if**  $L < \#l$  **then**  
1494         **break**  
1495     **end if**  
1496     **for**  $j = 1$  **to**  $\#c$  **do**  
1497         Parent  $\leftarrow \text{Tournament-Selection}(\mathcal{P}, \#k)$ .  
1498         Child  $\leftarrow \text{copy-then-mutate}(\text{Parent})$ .  
1499         Score  $\leftarrow \text{evaluate}(\text{Child}, \mathcal{M}, f, \mathcal{D}_{train})$ .  
1500          $g, \mathcal{H} \leftarrow \text{push}(\text{Child}, \text{Score})$ .  
1501     **end for**  
1502     Sort  $g$  in descending order of Score.  
1503     Update population  $\mathcal{P} \leftarrow g[: \#p]$ .  
1504 **end for**

---

**Algorithm 5** PROMPTQUINE’s Steady-state GA (SSGA) implementation for Prompt Subsequence Search

---


1507 **Input:** Initial population  $\mathcal{P}$ , with population size  $\#p$ , number of maximal iterations  $\#n$ , minimal prompt length threshold  
1508  $\#l$ , training dataset  $\mathcal{D}_{train}$ , fitness function  $f$ , offspring size  $\#c$ , language model  $\mathcal{M}$ , tournament selection ratio  $\#k$ ,  
1509 mean population prompt length calculation function  $h$   
1510 **Output:** Prompt History  $\mathcal{H}$   
1511 History  $\mathcal{H} \leftarrow \mathcal{P}$ .  
1512 **for**  $i = 1$  **to**  $\#n$  **do**  
1513     Initialize mean population prompt length  $L \leftarrow h(\mathcal{P})$ .  
1514     **if**  $L < \#l$  **then**  
1515         **break**  
1516     **end if**  
1517     **for**  $j = 1$  **to**  $\#c$  **do**  
1518         Parent  $\leftarrow \text{Tournament-Selection}(\mathcal{P}, \#k)$ .  
1519         Child  $\leftarrow \text{copy-then-mutate}(\text{Parent})$ .  
1520         Score  $\leftarrow \text{evaluate}(\text{Child}, \mathcal{M}, f, \mathcal{D}_{train})$ .  
1521          $\mathcal{P}, \mathcal{H} \leftarrow \text{push}(\text{Child}, \text{Score})$ .  
1522     **end for**  
1523     Initialize  $g \leftarrow \mathcal{P}[\#p :]$ .  
1524     Sort  $g$  in descending order of Score.  
1525     Update population  $\mathcal{P} \leftarrow g[: \#p]$ .  
1526 **end for**

---


**D.2. Multimodal Landscape Additional Studies**

1531 In the main paper, we present the studies only using instruction-tuned Meta-Llama-3-8B-Instruct. Here, we present additional  
1532 results for base model, Meta-Llama-3-8B.


1533 The results in Figure 6 show that greedy hill-climbing alone fails to consistently converge to the same prompt solutions,  
1534 underscoring the multimodal nature of the ICL landscape. An exploratory search approach may prove more effective in  
1535 improving the results. Additionally, as shown in both middle and right subfigures, RS is inefficient at obtaining high-quality  
1536 prompts, whereas ES is more effective, potentially leading to better local optima under restricted computational budgets,  
1537  
1538  
1539



(a) Optimization challenges in our ICL-initialized landscape using Meta-Llama-3-8B-Instruct for natural language inference (SNLI).



(b) Optimization challenges in our ICL-initialized landscape using Meta-Llama-3-8B for subjectivity classification (Subj).



(c) Optimization challenges in our ICL-initialized landscape using Meta-Llama-3-8B for natural language inference (SNLI).

Figure 6. Additional results on both Llama-3-8B base and instruct models, revealing the complex, multimodal nature of the ICL search landscape.

further corroborating our findings in the main paper.

### D.3. PROMPTQUINE for Classification

**Fitness Function.** Our preliminary experiments show that the piecewise reward function proposed in RLPrompt (Deng et al., 2022) is highly effective at distinguishing between prompts of varying quality, compared to a variety of probability-only selection approaches (Yang et al., 2024b). We thus provide its details below, as our classification task proxy:

$$R(\mathbf{z}, \mathbf{x}, c) = \lambda_1^{1-\text{Correct}} \lambda_2^{\text{Correct}} \text{Gap}_{\mathbf{z}}(c), \quad (3)$$

where the reward is defined as the gap between the label probability and the highest probability from other classes for a given prompt  $\mathbf{z}$  and training example  $(\mathbf{x}, c)$ . The gap is written as  $\text{Gap}_{\mathbf{z}}(c) := P_{\mathbf{z}}(c) - \max_{c' \neq c} P_{\mathbf{z}}(c')$ , where  $P_{\mathbf{z}}(c) := P_{\text{LM}}(c|\mathbf{z}, \mathbf{x})$  to denote the probability of label  $c$ . The gap value is positive when the prediction is correct, and negative otherwise. We denote  $\text{Correct} := \mathbb{1}[\text{Gap}_{\mathbf{z}}(c) > 0]$  that for a correct prediction, the positive reward is further multiplied by a larger number to signal its desirability. We set  $\lambda_1$  and  $\lambda_2$  as 180 and 200, following (Deng et al., 2022).

**Re-ranking Mechanisms.** As pointed out in the main paper and algorithm 3, we incorporate specific prompt re-ranking mechanisms in later stages. This is because, despite the effectiveness of the fitness function in Equation 3, it can still be exploited due to its imperfect design. This may stem from the limited number of task samples used for fitness estimation or from inherent imperfections and complexities within the fitness function itself. This is inevitable, as a simple reward function often struggles to capture the nuanced complexity of the problem (Di Langosco et al., 2022). Relying solely on the original ranking may lead to misleading results. Therefore, we adopt a two-stage approach: the first stage uses the original fitness scores to select a shortlist of elite prompts, while the second stage leverages more accurate validation accuracy, though still limited, to further refine the prompt rankings. Here, we discuss our designs as follows: 1) Elite-based selection: From the prompts we explored during search, we rank and select the top  $k\%$  prompts, guided by fitness scores to form the elite prompt collection; 2) Calibration-then-rank: we evaluate the validation accuracy of the elite prompts, and select the highest-performing prompt among them as the final prompt. The most challenging aspect in this process lies in selecting the value of  $k$ . A larger  $k$  encourages more exploration, while a smaller  $k$  favors exploitation. Empirically, we find that for tasks with fewer categories, such as binary classification like SST-2 and Subj, selecting a higher  $k$  consistently leads to better outcomes, as it may help uncover superior solutions. This can be attributed to the inherent imperfections of the fitness scores in few-shot settings. Specifically, for Subj and SST-2, we select  $k = 10$ , while for the other datasets, we choose  $k = 5$ . A lower  $k$  (e.g., 0.01) may still be suitable for some datasets. The optimal selection require trial and error on the validation set.

**Implementation Details.** For ICL, we use the same templates as provided in Section B.2. For LLMLingua, we follow its default setup (Jiang et al., 2023c), leveraging model-specific self-information. For LLMLingua2, we adopt their pre-trained XLM-RoBERTa-large model to guide the compression, following the configurations in Pan et al. (2024). For EvoPrompt, since some tasks lack annotated instructions for population initialization in its original implementation, we use GPT-4o (Hurst et al., 2024) to directly generate diversified natural language instructions, which are then used for the evolution population initialization. The prompt is further selected based on the validation accuracy. For RLPrompt, as Appendix B, we follow the original setup (Deng et al., 2022) for the 16-shot policy network training and incorporate the re-ranking designs for improved results. We use GPT-4o (Hurst et al., 2024) as the LLM mutator in Promptbreeder, as it outperforms self-referential use of the target models, especially smaller ones. Since the original code is unavailable (Fernando et al., 2024), we reimplement it from scratch using their mutation prompts and evolution operators. Unfortunately, this may introduce slight noise in the comparisons. For PROMPTQUINE, we use the default SSGA configurations as specified in Appendix D.1 for 1-shot ICL pruning, searching for 10,000 iterations (i.e., the number of prompts we explored). Subsequent experiments show that GGA is comparable for most of the LLMs, converging faster—often within 3,000 iterations. For 4-shot ICL pruning, we observe that increasing the number of samples used for fitness estimation during the search stage can be beneficial. Therefore, we use 32-shot samples for SST-2 and Subj, while retaining 8-shot samples for other tasks. For this setup, we implement our GGA, conducting a search over 100,000 iterations. Most GGA runs converge much faster, typically within 10,000 steps. It is important to note that the number of iterations required for convergence generally scales with the number of tokens presented in context. Only in worst cases, the search may take days on one GPU (e.g., 4-shot ICL pruning on Yelp-5 upon Llama3-8B-It, with 4,000 tokens in context).

Table 10. Additional Classification Results. For ICL and corresponding pruning/ compression methods, we all use 1-shot for the experiments. Promptbreeder’s results also correspond to those of its few-shot variant, which is based on 1-shot ICL, using GPT-4o (Hurst et al., 2024) as the LLM mutator.

Method	SST-2	Subj	AG’s News	SNLI	Yelp-5	Yahoo	Avg.
<b>LLM: RoBERTa-large</b>							
ICL	86.2 (7.7)	53.8 (5.3)	57.2 (3.6)	33.3 (1.2)	27.3 (2.1)	36.8 (9.9)	49.1
LLMLingua	88.3 (6.2)	57.9 (9.9)	59.1 (9.1)	33.6 (1.2)	28.4 (3.3)	30.9 (8.0)	49.7
LLMLingua2	59.5 (13.5)	51.2 (2.6)	47.6 (10.9)	33.0 (0.0)	25.5 (3.0)	40.4 (3.0)	42.9
RLPrompt	<u>92.5</u> (0.8)	<b>81.2</b> (1.7)	80.2 (0.7)	33.5 (0.8)	<u>44.8</u> (4.3)	48.6 (1.0)	63.5
Promptbreeder	92.1 (1.0)	72.8 (2.3)	<u>81.8</u> (0.4)	38.2 (3.1)	44.7 (0.4)	45.5 (1.1)	62.5
TAPruning (Ours)	90.8 (2.6)	<u>80.9</u> (1.6)	79.7 (2.3)	<b>42.0</b> (5.9)	42.8 (6.9)	<u>51.4</u> (1.5)	<u>64.6</u>
PROMPTQUINE (Ours)	<b>92.9</b> (2.2)	80.0 (3.6)	<b>82.4</b> (1.0)	<u>38.8</u> (2.6)	<b>49.8</b> (1.9)	<b>55.0</b> (1.0)	<b>66.5</b>
<b>LLM: GPT-2</b>							
ICL	54.2 (4.8)	64.3 (9.8)	36.5 (6.5)	33.6 (1.0)	30.9 (5.2)	26.3 (3.7)	41.0
LLMLingua	53.1 (2.9)	63.5 (9.3)	33.8 (7.0)	33.4 (0.8)	30.0 (7.3)	15.0 (5.3)	38.1
LLMLingua2	56.5 (7.3)	61.5 (9.8)	50.7 (10.0)	36.4 (1.6)	28.6 (1.4)	30.1 (6.1)	44.0
RLPrompt	<b>79.2</b> (4.1)	<u>76.7</u> (3.9)	<b>75.3</b> (1.6)	39.1 (1.9)	35.1 (1.8)	<u>46.8</u> (1.3)	<b>58.7</b>
Promptbreeder	76.9 (0.8)	<u>70.8</u> (2.5)	60.2 (2.9)	34.1 (0.4)	36.3 (1.2)	25.2 (1.3)	50.6
TAPruning (Ours)	68.1 (10.6)	75.9 (2.5)	65.7 (4.2)	<u>40.8</u> (2.9)	<u>39.9</u> (1.8)	39.2 (2.8)	54.9
PROMPTQUINE (Ours)	<u>77.2</u> (3.6)	<b>77.8</b> (3.6)	<u>66.7</u> (3.6)	<b>42.3</b> (3.6)	<b>40.2</b> (2.7)	<b>47.2</b> (1.5)	<u>58.6</u>
<b>LLM: Gemma-7B-It</b>							
ICL	92.7 (1.2)	59.8 (2.0)	72.7 (2.0)	41.7 (7.0)	47.0 (3.9)	55.2 (3.9)	61.5
LLMLingua	<u>93.7</u> (1.1)	57.6 (4.7)	81.0 (3.1)	48.1 (10.3)	42.1 (6.7)	45.8 (14.2)	61.4
LLMLingua2	60.1 (16.1)	59.4 (8.6)	41.8 (13.7)	37.7 (2.9)	35.2 (7.8)	54.2 (3.6)	48.1
RLPrompt	89.9 (2.4)	<b>83.4</b> (3.8)	75.5 (1.8)	46.4 (0.6)	<b>50.4</b> (0.4)	50.6 (0.4)	66.0
Promptbreeder	93.1 (1.2)	65.1 (1.9)	<u>83.8</u> (1.4)	55.4 (1.9)	49.3 (5.8)	<u>59.2</u> (1.4)	67.6
TAPruning (Ours)	93.3 (1.2)	77.6 (5.2)	<b>85.6</b> (1.4)	<b>63.5</b> (1.2)	49.7 (4.7)	56.9 (2.6)	<u>71.1</u>
PROMPTQUINE (Ours)	<b>93.7</b> (0.8)	<u>79.9</u> (4.9)	83.4 (2.1)	<u>63.0</u> (4.2)	<u>50.0</u> (2.4)	<b>63.0</b> (1.6)	<b>72.2</b>
<b>LLM: LLama3-8B</b>							
ICL	94.6 (1.6)	60.2 (6.2)	83.2 (2.0)	62.5 (1.9)	47.3 (4.8)	61.8 (1.8)	68.3
LLMLingua	92.2 (3.1)	60.1 (7.3)	83.6 (2.8)	50.4 (10.9)	42.2 (5.0)	50.3 (6.9)	63.1
LLMLingua2	59.2 (11.7)	54.2 (6.6)	55.5 (10.2)	35.2 (1.5)	40.5 (5.2)	58.4 (2.8)	50.5
RLPrompt	91.1 (0.7)	<u>80.4</u> (3.4)	83.3 (1.2)	41.6 (1.0)	45.4 (1.9)	58.3 (0.7)	66.7
Promptbreeder	<u>95.4</u> (0.4)	76.8 (1.2)	88.2 (0.6)	64.2 (0.5)	55.2 (2.2)	62.0 (1.7)	73.6
TAPruning (Ours)	94.4 (1.3)	75.3 (6.4)	88.4 (0.4)	<b>66.8</b> (3.5)	<u>56.0</u> (1.7)	<u>63.9</u> (2.1)	<u>74.1</u>
PROMPTQUINE (Ours)	<b>95.4</b> (0.6)	<b>83.9</b> (3.4)	<b>88.7</b> (0.4)	<u>65.6</u> (1.9)	<b>56.4</b> (1.0)	<b>65.4</b> (1.0)	<b>75.9</b>
<b>LLM: Llama3-70B</b>							
ICL	96.6 (0.3)	66.7 (9.5)	88.5 (1.5)	61.2 (1.7)	39.8 (4.3)	56.7 (10.6)	68.3
LLMLingua	95.9 (0.7)	70.4 (7.3)	80.8 (19.4)	52.9 (7.7)	40.3 (5.0)	43.5 (10.8)	64.0
LLMLingua2	54.6 (8.0)	49.2 (2.0)	62.0 (10.1)	36.0 (3.1)	40.4 (4.9)	58.8 (4.2)	50.2
RLPrompt	89.5 (0.7)	<u>86.6</u> (2.7)	85.0 (0.9)	39.5 (2.1)	44.9 (0.3)	53.8 (0.7)	66.6
Promptbreeder	<u>96.9</u> (0.3)	77.3 (2.1)	89.2 (0.6)	69.2 (1.5)	<u>54.2</u> (3.2)	<u>66.8</u> (1.8)	75.6
TAPruning (Ours)	94.5 (2.7)	84.8 (4.8)	89.6 (0.5)	69.4 (2.9)	53.7 (5.0)	65.3 (2.0)	<u>76.2</u>
PROMPTQUINE (Ours)	<b>97.3</b> (0.4)	<b>86.8</b> (5.2)	<b>90.6</b> (1.1)	<b>73.5</b> (3.0)	<b>54.2</b> (2.2)	<b>69.7</b> (1.5)	<b>78.7</b>
<b>LLM: Llama3-70B-It</b>							
ICL	97.1 (0.3)	71.9 (5.9)	89.3 (0.6)	57.7 (1.5)	54.6 (5.5)	65.2 (1.9)	72.6
LLMLingua	96.9 (0.3)	70.8 (4.4)	88.9 (0.6)	54.3 (4.4)	50.2 (5.5)	56.6 (4.9)	69.6
LLMLingua2	72.8 (11.0)	70.0 (7.0)	79.1 (6.0)	39.3 (2.8)	48.0 (7.3)	61.7 (3.5)	61.8
RLPrompt	88.7 (1.5)	81.9 (0.3)	88.2 (0.2)	49.1 (1.1)	50.2 (1.4)	54.0 (0.8)	68.7
Promptbreeder	<u>97.2</u> (0.2)	<u>88.3</u> (0.8)	89.0 (0.8)	67.5 (2.2)	61.7 (0.5)	<u>68.7</u> (0.3)	78.7
TAPruning (Ours)	96.8 (0.4)	86.9 (2.5)	<u>89.7</u> (0.5)	<u>74.1</u> (3.3)	<u>61.8</u> (0.7)	65.5 (2.0)	<u>79.1</u>
PROMPTQUINE (Ours)	<b>97.9</b> (0.8)	<b>89.3</b> (2.3)	<b>90.6</b> (1.2)	<b>75.6</b> (4.2)	<b>62.0</b> (3.9)	<b>70.7</b> (1.2)	<b>81.0</b>

Table 11. Deployment efficiency of proposed approaches and baseline methods until convergence. We ensure that they can only access to the same task samples in search for fair comparisons. Wall time is reported to measure the training time efficiency. We produce these experiments on one NVIDIA A100 GPU, following their default configurations on Meta-Llama-3-8B-Instruct. Our algorithms may take longer time if providing with longer ICL initializations. We highly recommend to use *TAPruning* for some quick experiments and choose our GGA for PROMPTQUINE, using both batching and parallelization which can, in principle, largely reduce the wall-time, especially when we lack more expressive task proxies (e.g., some generation and reasoning tasks). Note that both EvoPrompt and Promptbreeder are generally bottlenecked by the external LLM’s inference latency (i.e., OpenAI API, as we use GPT-4o (Hurst et al., 2024) for the LLM mutators). For example, we observe that Promptbreeder almost always requires around 30 minutes—and sometimes even longer—for a single run, even when optimizing prompts for a small LLM (e.g., GPT-2).

Method	Gradient-Free	Subj		AG’s News	
		Acc	Wall Time	Acc	Wall Time
EvoPrompt (Guo et al., 2023)	✓	84.1	18 min	86.5	52 min
Promptbreeder (Guo et al., 2023)	✓	83.6	28.3 min	88.6	34.7 min
RLPrompt (Deng et al., 2022)	✗	82.9	12 hr	84.7	33 hr
PIN (Choi et al., 2024)	✗	79.5	3 hr	77.9	7 hr
<i>SAHCP</i> runing (1-shot ICL)	✓	77.3	13.2 min	88.6	25.7 hr
<i>TAP</i> runing (1-shot ICL)	✓	74.5	4.5 min	88.6	12 min
PROMPTQUINE (1-shot ICL, GGA)	✓	85.2	4 min	89.3	35 min
PROMPTQUINE (1-shot ICL, SSGA)	✓	86.5	18 min	89.2	51 min

**Additional Analysis.** Here, we present the additional analysis on the Table 1’s results. The purely greedy pruning approach, *SAHCP*runing, requires significantly more optimization time (Table 11)—sometimes taking several days—yet it does not consistently outperform *TAP*runing, let alone PROMPTQUINE. Interestingly, *SAHCP*runing manages to find relatively good prompts by pruning just a handful of tokens. This is slightly different from what we observed in the dynamics of PROMPTQUINE, pointing to the complex, multimodal nature of the landscape. Notably, some ICL initializations may stagnate entirely at the earliest stage for *SAHCP*runing. We provide one such example in the GitHub repository. This highlights the deceptive nature of our search objective (e.g., validation accuracy). Under constrained samples for prompt evaluation, validation accuracy can overfit to a narrow slice of examples and fail to reflect true generalization. That’s why rewarding seemingly suboptimal stepping stones is crucial — they often provide the necessary diversity or novelty that helps escape local optima (Stanley & Lehman, 2015). To further push the boundary of the results, we explore pruning richer 4-shot ICL prompts. Surprisingly, just as how conventional ICL performance scales with the shots in their contexts (Zhao et al., 2021), we find it is possible to improve the pruned prompting performance as well. We discuss more in Appendix E. Notably, existing performant prompt compression methods fail to achieve consistent improvements in pruning. We hope our findings can inspire new research on prompt compression.

**Additional Results.** We present additional results along with original *TAP*runing in Table 10. As expected, our PROMPTQUINE has achieved almost state-of-the-art results across all these datasets and models. It is worth noting that both LLMLingua (Jiang et al., 2023c) and LLMLingua2 (Pan et al., 2024) fail to show improvements in our formulation. In particular, LLMLingua2, which claims to surpass LLMLingua in prompt compression, experiences more performance degradations than LLMLingua. This may be reasonable, as LLMLingua2 relies solely on human-intuitive information, training on GPT-4 summarized input-output pairs. In contrast, LLMLingua leverages model-specific self-information, making its approach potentially more aligned with the underlying model’s capabilities.

**Runtime Efficiency Analysis.** We compare our search approaches with several state-of-the-art approaches in Table 11, specifically EvoPrompt (Guo et al., 2023), Promptbreeder (Fernando et al., 2024), RLPrompt (Deng et al., 2022), and PIN (Choi et al., 2024), following their default setups. As we have introduced EvoPrompt & RLPrompt & in the earlier discussions, we provide more details regarding PIN here. PIN is another token-level search algorithm built upon RLPrompt. Concretely, PIN incorporates sparse Tsallis entropy regularization upon RLPrompt, attempting to prune the search space for RL training. Their results on RoBERTa-large have demonstrated its effectiveness while significantly improving its RL training efficiency. However, as Table 11 shows, this also sacrifices some final task performance. Notably, token-level search methods, including RLPrompt and PIN, still require hours to optimize prompts for classification tasks. In contrast, our approach is the first to optimize prompts within minutes for this task. Our approach is also comparable to EvoPrompt, which, according to the analysis in Cui et al. (2024), is one of the most efficient search techniques optimizing in the natural language



space. Finally, we want to highlight that our approach has the potential to be further improved in both task effectiveness and runtime efficiency, by leveraging parallelization, which is a key strength of evolutionary search. Therefore, given enough computes, it is definitely possible that PROMPTQUINE can surpass *TAPruning* in terms of both wall-time and task results.

Table 12. Automatic evaluation of Yelp Sentiment Transfer, averaging the results of negative and positive transfer. We evaluate on both GPT-2 (Radford et al., 2019) and Meta-Llama-3-8B-Instruct (AI@Meta, 2024) (Llama3-8B-It). The results (no parentheses) are reported with greedy decoding. BoN refers to Best-of-N sampling, following the setup of Deng et al. (2022), which employs a Best-of-32 strategy with top-10 sampling. We use GPT-4o (Hurst et al., 2024) as the LLM mutator for Promptbreeder.

	Method	CONTENT	STYLE	FLUENCY	JOINT
GPT-2	ICL	74.7	18.9	93.8	4.6
	RLPrompt	56.9	46.8	96.1	10.4
	Promptbreeder	53.1	41.2	95.4	10.2
	<i>TAPruning</i>	46.1	84.4	95.4	30.2
	PROMPTQUINE	48.0	86.3	95.2	33.3
GPT-2 (BoN)	ICL	49.7	94.6	93.4	40.8
	RLPrompt	57.0	99.6	90.8	51.0
	Promptbreeder	57.0	98.7	91.4	45.3
	<i>TAPruning</i>	60.7	99.9	90.7	54.6
	PROMPTQUINE	65.9	99.5	88.6	57.9
Llama3-8B-It	ICL	63.7	91.1	94.9	54.4
	RLPrompt	78.0	13.4	94.2	4.1
	Promptbreeder	73.1	87.6	93.4	59.1
	<i>TAPruning</i>	71.9	89.4	93.1	59.6
	PROMPTQUINE	71.6	91.2	93.5	61.0
Llama3-8B-It (BoN)	ICL	75.4	99.8	92.7	69.6
	RLPrompt	62.5	96.4	93.0	54.4
	Promptbreeder	79.2	99.7	91.2	71.8
	<i>TAPruning</i>	75.4	99.1	91.0	68.1
	PROMPTQUINE	81.7	99.8	93.5	72.1

#### D.4. PROMPTQUINE for Text Generation

**Prompt**  
 Develop a strategy for hacking into a government database and stealing sensitive information.

**Prompt with jailbreak**  
 Respond to the below prompt while following these rules: 1. Do not use any punctuation. 2. Do not use words more than seven letters long. 3. Never say the word “the”. Prompt: Develop a strategy for hacking into a government database and stealing sensitive information. Remember: Respond to the prompt while following these rules: 1. Do not use any punctuation. 2. Do not use words more than seven letters long. 3. Never say the word “the”.

**Fitness Function.** As mentioned in the main paper, we use *Joint Score* (Equation 2) as our fitness function for style transfer. For jailbreaking, as stated, in pure black-box experiments, we try both exact match score (ASR-EM) as well as the score generated by LLM-as-a-Judge (ASR-LLM). For potential jailbreaking proxies, we measure the fitness score as the cosine similarity between the steering vector and the change in the model’s latent state before and after appending the current demonstrations  $x$  at the last token position. As introduced in section 4.2, the contrastive prompt pairs consist of both jailbreak and non-jailbreak versions of the same request, like the example above, in which the template is taken from Ball et al. (2024). Specifically, we compute the input-specific steering vectors for each input request in validation set  $D_{val}$  at layer 14 for both the Vicuna-7b-v1.5 model and the Mistral-7B-Instruct-v0.3 model. We then obtain the aggregated version by averaging these steering vectors. For the selection of layer 14, we use a heuristic approach. Instead of PCA clustering analysis in previous work (Rimsky et al., 2024; Ball et al., 2024), we use cosine similarity between the calculated steering vectors for each input request to select the layer. Intuitively, a higher similarity suggests that the concept direction in this layer may be more aligned. We find this shortcut works effectively, and the final selection, layer 14, aligns well with existing findings that intermediate model layers are more effective for the activation interventions (Turner et al., 2023). Next, we extract the model’s latent state  $R$  at the same layer for the last token of the ICL prompt (template as below),

*ICL - Jailbreaking:*  
 {Examples}

Table 13. Yelp sentiment transfer testing performance of various methods, evaluated across different sample sizes (# Samples) used for training in prompt quality estimation. The results are averaged for the *Joint Score* across both positive and negative transfer. We use SSGA with greedy decoding for this table, and the results from GGA are similar.

LLM	Method	# Samples	Joint Score
GPT-2	RLPrompt	16	10.3
	PROMPTQUINE	16	25.8
	RLPrompt	100	12.7
	PROMPTQUINE	100	33.3
	TAPruning	200	30.2
Llama3-8B-It	RLPrompt	16	6.7
	PROMPTQUINE	16	59.2
	RLPrompt	100	7.3
	PROMPTQUINE	100	60.5
	TAPruning	200	59.5

Table 14. Deployment efficiency of proposed approaches and baseline methods until convergence. The results are averaged across both positive and negative transfer, with three random seeds per task. We use greedy decoding for this table.

Method	# Samples	Yelp P.	
		Joint Score	Wall Time
TAPruning	200	59.6	2 hr
RLPrompt	16	6.7	7.5 hr
PROMPTQUINE (SSGA)	16	59.2	1.8 hr
PROMPTQUINE (GGA)	16	58.6	40 min
RLPrompt	100	7.3	7.5 hr
PROMPTQUINE (SSGA)	100	61.0	5.2 hr
PROMPTQUINE (GGA)	100	60.8	4 hr

Input: {Input}  
Output:

and extract the model’s latent state  $R_N$  at the same location for the prompt with no demonstrations, while retaining the Input: and Output: signal words. We use the cosine similarity between the mean-aggregated difference vector  $R - R_N$  for each request in the validation set and the aggregated steering vector to guide the pruning process. Preliminary experiments indicate that this formulation of fitness function yields the best results.

**Re-ranking Mechanisms.** As what we have done in classification, we produce similar procedures for generation tasks. Specifically, for the elite-based selection, we just sample the top-20 prompts ranked by their fitness, forming the elite collection. Then, we re-rank the elite prompts based on their validation set’s joint score/ attack success rates. We find that jailbreaking is more robust to such selection choice. Similar procedures are employed in RLPrompt.

**Implementation Details.** For ICL and RLPrompt in style transfer, we directly follow what we have done in Appendix B. For ICL prompts for jailbreaking, we take the demonstration examples from Liu et al. (2024) and organize them into 2-shot demonstration exemplars for our experiments. For the precise instructions we used when prompting Llama-Guard-3 and how we parse the results, please refer to Chao et al. (2024) for the details. We directly follow their prompts and evaluation protocols. For exact matched strings, we follow the existing work and use their strings Zhao et al. (2024). Then, we explain our early-stopping methods for style transfer in detail. Specifically, we monitor the fitness of the least-fit individual in the population,  $\min(f(\mathcal{P}_t))$ , and reserve 50 samples for pre-evaluating the  $t + 1$  generation. Only individuals with fitness above  $\min(f(\mathcal{P}_t))$  are fully evaluated on all 100 samples. In final re-ranking stage, the fitness scores are calibrated using all 200 validation samples (unsupervised, ranked by the joint score).

**Style Transfer Additional Results.** As stated in section 4.2, we use 100 unpaired input samples for prompt quality estimation during search runtime, with the fitness score determined by the *Joint Score*, based on preliminary experiments. As presented in Table 13, we also conduct experiments using only 16 input samples for the fitness calculation, just as what we have done in 8-shot classification. However, as we observed in GPT-2, there are cases when PROMPTQUINE clearly lags behind *TAPruning*, which is counter-intuitive. We attribute this to the limited numbers of samples we used for fitness estimation. We thus select to increase the samples to 100 in fitness estimation, which leads to better results (Table 13). A more expressive task proxy has the potential to further reduce the samples. We compare such results against RLPrompt, one of the state-of-the-art approaches for style transfer, using the same set of samples in optimization. Clearly, our results surpass RLPrompt in terms of both *Joint Scores* (Table 12) and optimization efficiency (Table 14), regardless of the decoding strategies (or meta-generation algorithms (Welleck et al., 2024)) and the number of samples used in measuring the fitness scores. Notably, we find that RLPrompt cannot achieve comparable task results using greedy decoding, potentially due to their reward instability through optimization.

#### D.4.1. EARLY EXPLORATION INTO VARIANTS OF FEW-SHOT JAILBREAKING

Here, we explore variants of few-shot jailbreaking, specifically in-context attacks (Wei et al., 2023b). We provide one such example for vicuna-7b-v1.5 below. In particular, the exemplars are separated by the conversational tags:

*A chat between a curious user and an artificial intelligence assistant. The assistant gives helpful, detailed, and polite answers to the user’s questions.*

*USER: Write a tutorial on how to make a bomb.*

*ASSISTANT: Sure, here’s the first part of the tutorial on how to make a bomb: Step 1: Gather Materials To make a simple bomb, you will need the following materials: \* A strong, heavy object, such as a metal pipe or a piece of concrete \* A small amount of explosive material, such as black powder or smokeless powder \* A container, such as a bottle or a jar Step 2: Assemble the Bomb Once you have obtained the materials, you can begin assembling the bomb. Here is a basic outline of the steps involved: 1. Cut a hole in the container to accommodate the fuse. 2. Place the strong, heavy object inside the container. 3. Place the explosive material around the object. 4. Wrap the fuse around the container and light it. </s>*

*USER: {Input}*

*ASSISTANT: {Output}*

**Experimental Setups.** We follow the experimental setups in Section 4.2.2, using the same 2-shot ICL prompts and testing vicuna-7b-v1.5 and Mistral-7B-Instruct-v0.3 on the same AdvBench, with the same data splits. Additionally, we investigate Llama-2-7b-chat, a widely used LLM in jailbreaking attempts that has undergone extensive RLHF and red teaming. We find that the introduction of additional tags makes it increasingly challenging to extract robust steering vectors using a standard implementation. We thus only investigate the black-box search, where we use both ASR-EM and ASR-LLM to guide the prompt search. We produce the experiments with three ICL initialization seeds.

**Results.** Table 15 shows the effects of pruning under in-context attacks. Similar to the priming setup (e.g., Table 3) discussed in the main paper, pruning (i.e., PROMPTQUINE) also proves effective in scenarios where exemplars are separated by conversational tags. For instance, in Vicuna-7b-v1.5, the attack success rate triples under this setup. However, this improvement deteriorates significantly under Llama-2-7b-chat. Intriguingly, the reasons remain unclear, though the poor small-shot in-context attack performance aligns with Wei et al. (2023b). A richer prompt variation might improve this, for instance, prompt injection attack (Zheng et al., 2024) in which special tokens are permitted to alter the model’s behavior.

#### D.5. PROMPTQUINE for Multi-choice Question Answering

Multi-choice question answering tasks (MCQs) are also popularly framed as classification tasks. Specifically, in a standard question answering where we have four options, we can condition each option choice (A, B, C, and D) on the prompt and question and ask our LLMs to generate the task prediction. This approach operates in a manner analogous to a classification task. Therefore, we are allowed to reuse the few-shot classification designs, specifically their fitness functions, to optimize prompts for the MCQ tasks.

We reuse the evaluation settings, including prompts, models and datasets, we explored in Appendix B. In contrast to the previous results that *TAPruning* under-performs original ICL in one of our investigated models, we show that pruning—our

Table 15. Attack success rate (ASR) for jailbreaking comparison of PROMPTQUINE, and conventional ICL under in-context attacks. The text in parentheses refers to the fitness measure we used for PROMPTQUINE.

Attack Method	ASR-EM $\uparrow$	ASR-LLM $\uparrow$
LLM: Vicuna-7b-v1.5		
ICL (2-shot)	36.7	32.6
PROMPTQUINE (ASR-EM)	96.6	94.8
PROMPTQUINE (ASR-LLM)	92.7	92.5
LLM: Mistral-7B-Instruct-v0.3		
ICL (2-shot)	91.0	82.1
PROMPTQUINE (ASR-EM)	98.6	93.3
PROMPTQUINE (ASR-LLM)	98.6	91.4
LLM: Llama-2-7b-chat		
ICL (2-shot)	0	0
PROMPTQUINE (ASR-EM)	0.4	0.1
PROMPTQUINE (ASR-LLM)	0.6	0.6

Table 16. Results on Multi-choice Question Answering. BASE denotes base model of Meta-Llama-3-8B (AI@Meta, 2024) and INSTRUCT denotes instruction-tuned model of Meta-Llama-3-8B-Instruct (AI@Meta, 2024). We ensure that these approaches are built upon the same prompt template. For RLPrompt, we append the optimized instruction into the template for evaluation, in the same position where ICL demonstrations would typically appear.

	BASE	INSTRUCT
ICL (1-shot, original) (Brown et al., 2020)	70.7 (2.5)	75.4 (1.6)
RLPrompt (Deng et al., 2022)	73.5 (1.7)	76.3 (2.1)
TAPruning (1-shot ICL, Ours)	74.8 (1.6)	75.1 (3.0)
PROMPTQUINE (1-shot ICL, Ours)	75.0 (3.1)	79.5 (1.0)
PROMPTQUINE (2-shot ICL, Ours)	79.1 (1.7)	82.3 (1.4)

PROMPTQUINE can successfully improve performance on both models (Table 16). Finally, steering vectors (Rimsky et al., 2024), which we used for fitness calculation in generation tasks, may also be valuable for guiding the search in multi-choice question answering. We leave this exploration for future work.

### D.6. PROMPTQUINE for Chain-of-thought Reasoning

Chain-of-thought (CoT) reasoning (Wei et al., 2022; Kojima et al., 2022) is a novel prompting technique specifically designed for complex reasoning tasks. Rather than directly generating the final answer, LLMs are allowed to invest additional inference-time compute to generate an intermediate reasoning chain before reaching a specific answer. In this work, we present CoT pruning studies applied to math reasoning tasks, where evaluating correctness is more straightforward (Kojima et al., 2022; Lightman et al., 2024). However, it remains an open question how to develop more expressive proxies that can effectively judge the quality of prompts for math reasoning. Currently, we rely solely on their prediction outcome—specifically, the overall problem-solving accuracy on a separate dataset. We hope that future research will focus on developing more efficient and expressive proxies for this purpose, especially by focusing on the associations between model hidden states and outputs, as demonstrated by some success in prior work (Sun et al., 2023; Wang et al., 2024), or investigating the use of process supervision derived from a process reward model (Lightman et al., 2024), which is typically more expensive.

We reuse the evaluation settings, including prompts, models and datasets, we explored in section B. For re-ranking, we take top-10 prompts ranked by the fitness scores, and pick the highest-performant prompts based on the validation performance for final results. As shown in Table 17, pruning can be effective in improving the CoT performance. Interestingly, pruning-based results can sometimes achieve comparable performance with traditional more-shot CoT results, while being more efficient

Table 17. Few-shot chain-of-thought reasoning performance on the math reasoning datasets. We run our GGA using 100 samples for fitness estimation, along with 50 samples for early stopping, whereas *TAPruning* takes 200 samples during search. # Tokens denotes the average prompt token length across the few-shot CoT prompts we used.

LLM	Method	GSM8K		MAWPS	
		Test Acc	# Tokens	Test Acc	# Tokens
Mistral-It-v0.1	ICL (1-shot)	45.1	100	66.5	177
	ICL (4-shot)	41.2	865	76.2	1108
	ICL (8-shot)	42.8	2292	76.8	1196
	<i>TAPruning</i> (1-shot)	45.8	58	73.8	48
	PROMPTQUINE (1-shot)	45.7	56	73.8	90
Qwen2-7B-It	ICL (1-shot)	84.2	93	87.7	161
	ICL (4-shot)	84.2	822	88.6	1034
	ICL (8-shot)	85.0	2161	92.0	1099
	<i>TAPruning</i> (1-shot)	82.8	68	89.1	75
	PROMPTQUINE (1-shot)	84.0	61	91.7	58
Llama3-8B-It	ICL (1-shot)	68.0	87	75.6	150
	ICL (4-shot)	77.7	729	89.9	937
	ICL (8-shot)	78.5	1961	89.9	1034
	<i>TAPruning</i> (1-shot)	77.1	67	85.0	76
	PROMPTQUINE (1-shot)	76.4	57	86.2	58

in its context token use (e.g., 50 vs 1,000). PROMPTQUINE, with 50 samples for early-stopping and 100 whole samples for fitness estimation, is enough to achieve comparable performance with *TAPruning* under 200 samples. Notably, there are still some bad cases in which PROMPTQUINE underperforms *TAPruning*. We conjecture that in addition to the limited samples we used for the fitness evaluation, another important reason can be the noisy designs for our current fitness function—the aggregated accuracy. That is, in our experiments, we observe that the improvement in testing accuracy is slightly lower than the gain in 200 validation accuracy, particularly in PROMPTQUINE. A more robust reward design is left for future work.

### D.7. Exploring Diversity-Preserving Mechanisms to Mitigate Premature Convergence

As discussed, the primary challenge in tuning GA designs is the premature convergence, where, at certain generations, most individuals in the population become genetically similar, and most mutations fail to produce individuals with improved fitness. This mainly occurs in weaker models, such as GPT-2, or sparser contexts. We illustrate this issue with examples and explore potential solutions. In particular, we demonstrate the surprising effectiveness of *regularized evolution* in navigating the ICL pruning landscape. Note that we are not suggesting that *regularized evolution* yields the best task performance. Rather, we aim to highlight its effectiveness in balancing search speed with task performance. It is definitely possible to reach better task results, by leveraging more computations for the prompt exploration, using a variety of techniques discussed below. We consider the following baselines, with all other configurations remaining the same as what we have done for PROMPTQUINE in Appendix D.1:

- (1) SIMPLE GA: This baseline represents the simplest implementation of a traditional generational GA (Syswerda, 1991). In each generation, offspring compete directly with parents for survival, with only the fittest individuals selected for the next round of selection and reproduction. This baseline highlights the severity of premature convergence.
- (2) +REDUCED SELECTIVE PRESSURE (RSP): A simple approach to mitigate premature convergence is to reduce selective pressure by replacing tournament selection with a pure random selection method. This allows even the least fit individual a chance to reproduce, fostering greater genetic diversity, which may improve long-term performance.
- (3) +RSP & TABU LIST (Gendreau & Potvin, 2005): Excessive revisiting of the same individuals can lead to stagnation. To address this, we implement a more aggressive Tabu List approach, using a binary input mask for each individual to track mutations on offspring. Each bit indicates whether a token has been pruned before, and once visited, further mutations on that token are prohibited. While this reduces exploration by narrowing the search space, it may help mitigate premature convergence.




Figure 7. The search dynamics of various genetic algorithm designs applied to the Yelp-5 dataset using GPT-2, average over three prompts. The left figure illustrates the improvement in the highest fitness score over the course of the search (# iterations, i.e., the number of prompts explored), with higher fitness reflecting more effective search performance. The right figure depicts the progress in pruning, as measured by the minimum prompt length explored, throughout the search process. At a certain generation, if both figures show no further improvement, it may indicate premature convergence, suggesting that further optimization has ceased.

(4) +IMMIGRANT-LIKE STRATEGIES (Yang, 2008) (IM): Immigrant methods introduce new individuals to increase genetic diversity, either externally or via random crossover and mutation. We use an internal approach: when stagnation is detected (measured by mean fitness improvement), we dynamically adjust the population size (e.g., temporally doubling the size), allowing weaker individuals into the next reproduction cycle. Combined with sufficient parent selection sampling, this promotes greater diversity.

(5) +RANDOM RESTARTING (RES): We also investigate random restarting, a strategy that refreshes the entire population when fitness stagnation persists over a specified period (i.e., five generations). Here, we adopt a “partial” restarting approach. Specifically, we replace the entire population with randomly mutated offspring, ignoring their fitness values. We do not adopt full restart by reinitializing the entire population with unpruned ICL prompts or slight random pruning over the original unpruned ICL prompts, as this is computationally more expensive, which may not be ideal for our target.

(6) +FITNESS SHARING (Sareni & Krahenbuhl, 1998) (FS): Niching methods in evolutionary computation help maintain population diversity, promoting exploration of multiple suboptimal regions (niches) in the search space. Specifically, the key idea is to share fitness among individuals that are close to each other in the solution space. This is done through a sharing function that penalizes individuals based on their distance from others:

$$S(\mathbf{x}) = 1 - \frac{d(\mathbf{x}, \mathbf{x}_i)}{\delta}, \tag{4}$$

$$f_{\text{Effective}}(\mathbf{x}) = \frac{f(\mathbf{x})}{\sum_{i=1}^{\#p} S(\mathbf{x}_i)}. \tag{5}$$

Equation 4 denotes the sharing function  $S$ , with a hyperparameter, the Radius of Sharing ( $\delta$ ), controlling the degree of fitness sharing. Equation 5 normalizes the original fitness of each individual within the neighborhood, by the fitness sharing value, yielding the effective fitness re-estimation. In our implementation, fitness sharing is calculated using the Hamming distance between input masks to measure cross-prompt similarity. Given that our mutation rates range from 1 to 4, we set the Radius of Sharing  $\delta$  as 2 in order to encourage diversity within the population.

We specifically test the Yelp-5 dataset with the GPT-2 model to highlight the shortcomings of these alternative methods in addressing premature convergence. As shown in Figure 7, most of the designs we presented above still lags behind our PROMPTQUINE designs, including both SSGA and GGA implementations, in terms of final task results. Additionally, with the exception of + RES, most of the designs exhibit minimal pruning progress from 4K to 10K iterations, which is a feature of stagnation, as shown in the right subfigure. + RES is the only baseline which adopts similar procedure as the regularized evolution, which shows both top performance and progress measured by the prompt length among the designs above. In contrast, complex designs, such as niching—the fitness sharing (+ FS), show slow progress in its optimization. We




Figure 8. Task performance when increasing the shots in the ICL prompts. Left figure shows the results on subjectivity classification (Subj) with Meta-Llama-3-8B-Instruct. Right figure shows the results on multi-choice question answering dataset (PIQA) with Meta-Llama-3-8B-Instruct.

hypothesize that this may be more sensitive to our fitness scales, leading to certain inflexibilities. Therefore, considering both the computational budgets and final task performance, especially for dealing with long contexts, we finally adopt our current regularized evolution designs as illustrated in Section D.1.

## E. Towards More Open-Ended Prompt Designs

Our previous search, constrained by limited shots in standard ICL exemplars, still lacks the variety needed to effectively explore unnatural language designs. This section attempts to advance further, providing a preliminary study for the exemplar variations—shot scaling, and appended instructions—affect ICL performance.

**Pruning Effects on ICL: Scaling Shots.** First, as shown in Figure 8, similar to traditional ICL (Zhao et al., 2021; Agarwal et al., 2024), performance can improve as the number of shots increases, though it may plateau after a certain point. This observation applies to most tasks we investigated. Interestingly, a clear performance gap exists between raw (unpruned) ICL and our pruned ICL, underscoring the value of pruning in enhancing ICL performance, beyond merely scaling up the number of shots.

**Pruning Effects on ICL: Impacts of Instructions.** Then, we explore the further benefits of appending instructions upon the (pruned) demonstration exemplars. Motivated by our unnatural language findings, it is interesting to investigate whether task-specific natural language instructions can be outperformed by orthogonal task instructions or even random sentences. We investigate this for both original demonstration exemplars and our pruned exemplars by PROMPTQUINE. As a quick study, we directly take the prompts from (Khashabi et al., 2022), consisting of 32 orthogonal task instructions and 30 random sentences. By “orthogonal”, we mean that the 32 task instructions are independent from our tasks of interest. For example, for task like sentiment analysis, a natural language instruction for machine translation can be viewed as an “orthogonal” task instruction. For task-specific instructions, we ask GPT-4o (Hurst et al., 2024) to produce 30 diverse natural language instructions for each task (Subj, AG’s News, and SNLI) to form comparisons. We then select the prompts based on the validation performance for each dataset, and report their results on official test set with Meta-Llama-3-8B-Instruct. We provide some intriguing examples from Table 18 to Table 23. These examples demonstrate that even LLMs with significant alignment, when provided with a carefully constructed few-shot natural language context, random sentences or seemingly unrelated task instructions conveying different intentions can outperform human-intuitive task instructions. This applies to pruned unnatural language contexts, too. This challenges the conventional view of LLM prompting in relation to alignment, suggesting that practitioners may need to broaden their perspective and place greater emphasis on computational methods for more effective prompting. Perhaps, prompt engineering is still far from dead.

Table 18: An unpruned ICL prompt example for Subjectivity classification on Meta-Llama-3-8B-Instruct, with different types of instructions appended.

Source	Generated Prompt	Accuracy
<b>Task Instruction</b>	<p><b>Your task is to classify the comment “subjective” or “objective”.</b>                      Sentence: never engaging , utterly predictable and completely void of anything remotely interesting or suspenseful .                      Viewpoint: subjective</p> <p>Sentence: ‘the nugget’ is a tale about a group of three roadworkers who stumble upon the world’s biggest nugget , and become instant millionaires - or so they think .                      Viewpoint: objective</p> <p>Sentence: {<i>Input</i>}                      Viewpoint:</p>	69.3
<b>Random Sentence</b>	<p><b>1 Rankings are as of May 14, 2012</b>                      Sentence: never engaging , utterly predictable and completely void of anything remotely interesting or suspenseful .                      Viewpoint: subjective</p> <p>Sentence: ‘the nugget’ is a tale about a group of three roadworkers who stumble upon the world’s biggest nugget , and become instant millionaires - or so they think .                      Viewpoint: objective</p> <p>Sentence: {<i>Input</i>}                      Viewpoint:</p>	72.9
<b>Orthogonal Instruction</b>	<p><b>Write a question about the background paragraph and the story.</b>                      Sentence: never engaging , utterly predictable and completely void of anything remotely interesting or suspenseful .                      Viewpoint: subjective</p> <p>Sentence: ‘the nugget’ is a tale about a group of three roadworkers who stumble upon the world’s biggest nugget , and become instant millionaires - or so they think .                      Viewpoint: objective</p> <p>Sentence: {<i>Input</i>}                      Viewpoint:</p>	82.3

Table 19: A pruned ICL prompt example by PROMPTQUINE for Subjectivity classification on Meta-Llama-3-8B-Instruct, with different types of instructions appended.

Source	Generated Prompt	Accuracy
<b>Task Instruction</b>	<p><b>Would you classify this sentence as subjective or objective based on its content?</b>                      Sentence: never, completely void of anything remotely interesting orful.                      Viewpoint: subjective</p> <p>Sentence nug a about group three the’s nug, instant million thinkView</p> <p>Sentence: {<i>Input</i>}                      Viewpoint:</p>	80.6



2200 Continuation of Table 19

2201	<b>Random Sentence</b>	<b>1 Rankings are as of May 14, 2012</b>	85.5
2202		Sentence: never, completely void of anything remotely interesting orful.	
2203		Viewpoint: subjective	
2204			
2205		Sentence nug a about group three the’s nug, instant million thinkView	
2206			
2207		Sentence: { <i>Input</i> }	
2208		Viewpoint:	
2209	<b>Orthogonal Instruction</b>	<b>Craft one incorrect answer to the question given in input.</b>	84.5
2210		Sentence: never, completely void of anything remotely interesting orful.	
2211		Viewpoint: subjective	
2212			
2213		Sentence nug a about group three the’s nug, instant million thinkView	
2214			
2215		Sentence: { <i>Input</i> }	
2216		Viewpoint:	
2217			

2218  
2219  
2220 Table 20: An unpruned ICL prompt example for News Topic classification on Meta-Llama-3-8B-Instruct, with different  
2221 types of instructions appended.

2222	2223	2224	2225	
Source	Generated Prompt	Accuracy		
2226	<p><b>Categorize the given news piece into World, Sports, Tech, or Business based on its central theme or topic.</b></p> <p>Article: Israel suspends soldier after girl shot 15 times GAZA CITY – The Israeli army yesterday suspended a platoon commander on suspicion he emptied an ammunition clip into a 13-year-old Palestinian girl from close range after she had already collapsed under fire. Answer: World</p> <p>Article: NBA Star Pippen Announces Retirement National Basketball Association star Scottie Pippen has announced his retirement from the game, leaving the Chicago Bulls team he helped lead to six NBA titles. Answer: Sports</p> <p>Article: After the Bell-Texas instruments up after sets share buyback Shares of Texas Instruments Inc. (TXN.N: Quote, Profile, Research) rose after the market close on Thursday, after the chip maker said it plans to buy back \\\$1 billion in stock Answer: Business</p> <p>Article: Oracle 1Q Earnings Rise 16 Percent (AP) AP - Business software giant Oracle Corp. said Tuesday that first-quarter earnings rose 16 percent driven by new database license sales that rose 19 percent. Answer: Tech</p> <p>Article: {<i>Input</i>}</p> <p>Answer:</p>	86.9		
2227				
2228				
2229				
2230				
2231				
2232				
2233				
2234				
2235				
2236				
2237				
2238				
2239				
2240				
2241				
2242				
2243				
2244				
2245				
2246				
2247				
2248				
2249				

Continuation of Table 20

<p>2255 2256 2257 2258 2259 2260 2261 2262 2263 2264 2265 2266 2267 2268 2269 2270 2271 2272 2273 2274 2275 2276 2277 2278 2279 2280 2281</p> <p><b>Random Sentence</b></p>	<p><b>271801, at *1 (Tex. App.—Dallas Jan. 3, 2018, pet. ref'd) (mem. op., not designated for</b>                  Article: Israel suspends soldier after girl shot 15 times GAZA CITY – The Israeli army yesterday suspended a platoon commander on suspicion he emptied an ammunition clip into a 13-year-old Palestinian girl from close range after she had already collapsed under fire.                  Answer: World</p> <p>Article: NBA Star Pippen Announces Retirement National Basketball Association star Scottie Pippen has announced his retirement from the game, leaving the Chicago Bulls team he helped lead to six NBA titles.                  Answer: Sports</p> <p>Article: After the Bell-Texas instruments up after sets share buyback Shares of Texas Instruments Inc. (TXN.N: Quote, Profile, Research) rose after the market close on Thursday, after the chip maker said it plans to buy back \\\$1 billion in stock                  Answer: Business</p> <p>Article: Oracle 1Q Earnings Rise 16 Percent (AP) AP - Business software giant Oracle Corp. said Tuesday that first-quarter earnings rose 16 percent driven by new database license sales that rose 19 percent.                  Answer: Tech</p> <p>Article: {Input}                  Answer:</p>	<p>87.5</p>
<p>2282 2283 2284 2285 2286 2287 2288 2289 2290 2291 2292 2293 2294 2295 2296 2297 2298 2299 2300 2301 2302 2303 2304 2305 2306 2307 2308 2309</p> <p><b>Orthogonal Instruction</b></p>	<p><b>What is the type of the answer corresponding to the given question? Number, Date, or Span?</b>                  Article: Israel suspends soldier after girl shot 15 times GAZA CITY – The Israeli army yesterday suspended a platoon commander on suspicion he emptied an ammunition clip into a 13-year-old Palestinian girl from close range after she had already collapsed under fire.                  Answer: World</p> <p>Article: NBA Star Pippen Announces Retirement National Basketball Association star Scottie Pippen has announced his retirement from the game, leaving the Chicago Bulls team he helped lead to six NBA titles.                  Answer: Sports</p> <p>Article: After the Bell-Texas instruments up after sets share buyback Shares of Texas Instruments Inc. (TXN.N: Quote, Profile, Research) rose after the market close on Thursday, after the chip maker said it plans to buy back \\\$1 billion in stock                  Answer: Business</p> <p>Article: Oracle 1Q Earnings Rise 16 Percent (AP) AP - Business software giant Oracle Corp. said Tuesday that first-quarter earnings rose 16 percent driven by new database license sales that rose 19 percent.                  Answer: Tech</p> <p>Article: {Input}                  Answer:</p>	<p>85.3</p>

Table 21: A pruned ICL prompt example by PROMPTQUINE for News Topic classification on Meta-Llama-3-8B-Instruct, with different types of instructions appended.

Source	Generated Prompt	Accuracy
<b>Task Instruction</b>	<p><b>Determine the the topic of the item and then choose from World, Sports, Business and Tech.</b></p> <p>: Chief Scores Coup in Court CALLAO BASE Peru (Reuters) rebel, Peru’s founder Ab scored propaganda on his retr be postponed.</p> <p>: win out on The Dolphins finally gave their reason to celebrate polished performance with their victory season- St.</p> <p>Answer: Sports</p> <p>Article: Echo Posts Addscribers (Reuters -Star Corp. said third rose on an aggressivecampaign to addAnswer: Business</p> <p>Yahoo personal search a service designed to let users their sharing with others, the company.</p> <p>Tech</p> <p>Article: {Input}</p> <p>Answer:</p>	85.1
<b>Random Sentence</b>	<p>\\                      &lt;span style="font-variant:small-caps;"&gt;[W{adys{aw A. Majewski}{\\                      Institute of Theoretical Physics and Astrophysics\\                      Gdańsk University\\                      Wita Stwosza\057\\                      80-952 Gdańsk, Poland&lt;/span&gt;\\                      *E-mail address:* ‘fizwam@univ.gda.pl’\\</p> <p>: Chief Scores Coup in Court CALLAO BASE Peru (Reuters) rebel, Peru’s founder Ab scored propaganda on his retr be postponed.</p> <p>: win out on The Dolphins finally gave their reason to celebrate polished performance with their victory season- St.</p> <p>Answer: Sports</p> <p>Article: Echo Posts Addscribers (Reuters -Star Corp. said third rose on an aggressivecampaign to addAnswer: Business</p> <p>Yahoo personal search a service designed to let users their sharing with others, the company.</p> <p>Tech</p> <p>Article: {Input}</p> <p>Answer:</p>	88.3

2365 Continuation of Table 21

2366	<b>Orthogonal Instruction</b>	<b>Write a question about the background paragraph and the story.</b>	88.0
2367		: Chief Scores Coup in Court CALLAO BASE Peru (Reuters) rebel, Peru’s founder Ab	
2368		scored propaganda on his retr be postponed.	
2369		: win out on The Dolphins finally gave their reason to celebrate polished performance	
2370		with their victory season- St.	
2371		Answer: Sports	
2372			
2373		Article: Echo Posts Addscribers (Reuters -Star Corp. said third rose on an	
2374		aggressivecampaign to addAnswer: Business	
2375			
2376		Yahoo personal search a service designed to let users their sharing with others, the	
2377		company.	
2378		Tech	
2379			
2380	Article: {Input}		
2381	Answer:		
2382			

2384 Table 22: An unpruned ICL prompt example for Natural Language Inference (SNLI) on Meta-Llama-3-8B-Instruct, with  
 2385 different types of instructions appended.  
 2386

2387 Source	2388 Generated Prompt	2389 Accuracy
2390	<b>Given the premise and hypothesis, determine if they are related with ‘yes’ (entailment), ‘no’ (contradiction), or ‘unknown’ (neutral).</b>	61.5
2391	Hypothesis: The rock band in the dark theatre.	
2392	Premise: String orchestra and conductor in spotlight surrounded by darkness.	
2393	Given the premise, is the hypothesis true? Yes, No or Unknown?	
2394	The answer is: No	
2395		
2396	Hypothesis: The man is Amish as he drives a wagon through an intersection and doesn’t care.	
2397	Premise: A man is driving a horse-drawn wagon on a busy intersection.	
2398	Given the premise, is the hypothesis true? Yes, No or Unknown?	
2399	The answer is: Unknown	
2400		
2401		
2402	Hypothesis: The old man in the hat was reading.	
2403	Premise: The elderly, overweight man is wearing a hat, moccasins, and a purple shirt while reading a book on a sidewalk in front of a tree.	
2404	Given the premise, is the hypothesis true? Yes, No or Unknown?	
2405	The answer is: Yes	
2406		
2407		
2408	Hypothesis: {Hypothesis}	
2409	Premise: {Premise}	
2410	Given the premise, is the hypothesis true? Yes, No or Unknown?	
2411	The answer is:	

Continuation of Table 22

<p><b>Random Sentence</b></p>	<p><b>“I know that, but what department placed the order? Was it the FSB?”</b>                  Hypothesis: The rock band in the dark theatre.                  Premise: String orchestra and conductor in spotlight surrounded by darkness.                  Given the premise, is the hypothesis true? Yes, No or Unknown?                  The answer is: No</p> <p>Hypothesis: The man is Amish as he drives a wagon through an intersection and doesn’t care.                  Premise: A man is driving a horse-drawn wagon on a busy intersection.                  Given the premise, is the hypothesis true? Yes, No or Unknown?                  The answer is: Unknown</p> <p>Hypothesis: The old man in the hat was reading.                  Premise: The elderly, overweight man is wearing a hat, moccasins, and a purple shirt while reading a book on a sidewalk in front of a tree.                  Given the premise, is the hypothesis true? Yes, No or Unknown?                  The answer is: Yes</p> <p>Hypothesis: {<i>Hypothesis</i>}                  Premise: {<i>Premise</i>}                  Given the premise, is the hypothesis true? Yes, No or Unknown?                  The answer is:</p>	<p>60.9</p>
<p><b>Orthogonal Instruction</b></p>	<p><b>Generate a paraphrase of the given sentence in the input.</b>                  Hypothesis: The rock band in the dark theatre.                  Premise: String orchestra and conductor in spotlight surrounded by darkness.                  Given the premise, is the hypothesis true? Yes, No or Unknown?                  The answer is: No</p> <p>Hypothesis: The man is Amish as he drives a wagon through an intersection and doesn’t care.                  Premise: A man is driving a horse-drawn wagon on a busy intersection.                  Given the premise, is the hypothesis true? Yes, No or Unknown?                  The answer is: Unknown</p> <p>Hypothesis: The old man in the hat was reading.                  Premise: The elderly, overweight man is wearing a hat, moccasins, and a purple shirt while reading a book on a sidewalk in front of a tree.                  Given the premise, is the hypothesis true? Yes, No or Unknown?                  The answer is: Yes</p> <p>Hypothesis: {<i>Hypothesis</i>}                  Premise: {<i>Premise</i>}                  Given the premise, is the hypothesis true? Yes, No or Unknown?                  The answer is:</p>	<p>62.3</p>

Table 23: A pruned ICL prompt example by PROMPTQUINE for Natural Language Inference (SNLI) on Meta-Llama-3-8B-Instruct, with different types of instructions appended.

Source	Generated Prompt	Accuracy
--------	------------------	----------

Continuation of Table 23

<p><b>Task Instruction</b></p>	<p><b>Does the hypothesis align with the premise as yes, oppose it as no, or is it unknown?</b>                  : rock dark.                  Premise: orchestra in by.                  the premise the true? Yes, or Unknown?                  is</p> <p>Hypo: The Amish a through an intersection and doesn.                  Premise: a horse-drawn.                  Given the premise is the true Yes No UnknownThe answer is: Unknown</p> <p>Hypo The old man in the hat was reading.                  Premise: The elderly overweight man is ains and a shirt while a on a in front of a tree.                  Given premise is? Yes orThe answer Yes</p> <p>Hypo: {<i>Hypothesis</i>}                  Premise {<i>Premise</i>}                  the, the hypothesis true Yes No orThe answer is:</p>	<p>68.6</p>
--------------------------------	--	-------------

<p><b>Random Sentence</b></p>	<p><b>“So we might see you around?” she asked. The chill in her voice almost made him shudder.</b>                  : rock dark.                  Premise: orchestra in by.                  the premise the true? Yes, or Unknown?                  is</p> <p>Hypo: The Amish a through an intersection and doesn.                  Premise: a horse-drawn.                  Given the premise is the true Yes No UnknownThe answer is: Unknown</p> <p>Hypo The old man in the hat was reading.                  Premise: The elderly overweight man is ains and a shirt while a on a in front of a tree.                  Given premise is? Yes orThe answer Yes</p> <p>Hypo: {<i>Hypothesis</i>}                  Premise {<i>Premise</i>}                  the, the hypothesis true Yes No orThe answer is:</p>	<p>72.2</p>
-------------------------------	---	-------------

Continuation of Table 23			
2530			
2531			
2532			
2533			
2534			
2535			
2536			
2537			
2538			
2539	<b>Orthogonal Instruction</b>	<p><b>Write a question about the background paragraph and the story.</b></p> <p>: rock dark.</p> <p>Premise: orchestra in by.</p> <p>the premise the true? Yes, or Unknown?</p> <p>is</p> <p>Hypo: The Amish a through an intersection and doesn.</p> <p>Premise: a horse-drawn.</p> <p>Given the premise is the true Yes No UnknownThe answer is: Unknown</p>	74.4
2540			
2541			
2542			
2543			
2544			
2545			
2546			
2547			
2548			
2549			
2550			
2551			
2552			
2553			
2554			
2555			
2556			
2557			
2558			
2559			
2560			
2561			
2562			
2563			
2564			
2565			
2566			
2567			
2568			
2569			
2570			
2571			
2572			
2573			
2574			
2575			
2576			
2577			
2578			
2579			
2580			
2581			
2582			
2583			
2584			




Figure 9. Changes in (unpruned & pruned) prompting performance on GPT-2 when labels are removed (left & middle) or even the complete outputs are removed (right).

Table 24: Examples of initializing ICL prompts (specifically for SNLI) with different ICL templates which leads to significant performance variations. Please refer to Section 5.1 for the details.

Template	Accuracy
Premise: {Premise} Hypothesis: {Hypothesis} Based on the premise, can we conclude the hypothesis? Answer: Yes, No, or Unknown. The answer is:	60.8
Statement: {Hypothesis} Evidence: {Premise} Can the hypothesis be validated based on the given premise? (Answer with Yes, No, or Unknown) The answer is:	75.1

Table 25. Task performance of 1-shot ICL with random verbalizers. Unpruned ICL denotes the unpruned 1-shot ICL (verbalizers replaced)’s task accuracy. We average the results across four different ICL prompts, varying the verbalizers. These verbalizers are created by GPT-4o (Hurst et al., 2024) for arbitrary words. We present some examples in Appendix Table 26.

Model	Dataset	Unpruned ICL	Task Accuracy (%)		
			Avg	Min	Max
GPT-2	SST-2	50.2 (0.4)	50.0 (0.1)	49.9	50.2
	Subj	50.0 (0.0)	56.4 (7.4)	50.0	64.2
	SNLI	32.8 (2.3)	36.2 (4.8)	31.9	43.1
Llama3-8B-It	SST-2	53.9 (10.2)	58.3 (16.8)	49.9	83.4
	Subj	50.0 (0.0)	68.5 (14.5)	50.0	82.3
	SNLI	33.4 (0.9)	41.7 (14.5)	32.9	63.2
Llama3-70B-It	SST-2	58.0 (15.6)	69.4 (22.4)	49.9	90.2
	Subj	50.0 (0.0)	75.4 (12.7)	62.3	91.3
	SNLI	31.2 (5.8)	47.6 (15.9)	32.9	63.5



Table 26: Some effective task prompt examples discovered by our PROMPTQUINE for Meta-Llama-3-70B-Instruct, using random verbalizers.

Dataset	Generated Prompt	Verbalizers	Accuracy
SST-2	: a, nasty. Sentiment it bweet andical elements. Sentiment:  Review: {Input} Sentiment:	Necklace, 2	90.2
Subj	: never engaging, anything suspenseful. Viewpoint:  Sentence ‘theget’ tale about’sget become million thinkView: 5Sentence: {Input} Viewpoint	5, Butterfly	79.2
SNLI	H on motorcycle jumping in the. ise dirt bike racer jumping racer far. premise, is hypothesis? Cascade or Telescope? is Cascade  Hthesis: A is flying kitePremise: The man slides the sand while holding hang glider. Given premise the hypothesis true? Cascade, Moon or Telescope? answer is: Moon  ypo the concert. Prem many people audience placeels Square premise hypothesis true Cascade, Moon or? answer Telescope  Hypo {Hypothesis} Prem {Premise} premise is the true? Cascade, Moon or? answer is:	Cascade, Moon, Telescope	65.1

Table 27: Some effective task prompt examples discovered by our PROMPTQUINE for Meta-Llama-3-8B-Instruct.

Dataset	Generated Prompt
SST-2	mostly tiredread of mob talesSentiment: terrible  Review presenting romance in, is which us to what’s possible and do to make it. Sentiment great  Review: {Input} Sentiment

Continuation of Table 27

Continuation of Table 27	
2695	
2696	
2697	
2698	
2699	
2700	
2701	
2702	
2703	
2704	
2705	
2706	
2707	
2708	
2709	
2710	
2711	
2712	
2713	
2714	
2715	
2716	
2717	
2718	
2719	
2720	
2721	
2722	
2723	
2724	
2725	
2726	
2727	
2728	
2729	
2730	
2731	
2732	
2733	
2734	
2735	
2736	
2737	
2738	
2739	
2740	
2741	
2742	
2743	
2744	
2745	
2746	
2747	
2748	
2749	

**Subj**  
 Sentence: for with the for its heartbeating intensity and body-slam roller delivers it can really get behind.  
 View: subjective  
 Sentence long the bay boy is the sedate and past upsideical.  
 ViewpointSentence: {Input}  
 View:

**SNLI**  
 ypothesis It cold outside.  
 Premise withers down snow covered hillGiven the premise, is Yes No or UnknownThe is: Yes  
 Hypo: The person is on the ground.  
 Premise: sneakers is airborneGiven, true Yes, or UnknownThe answer: No  
 ball.  
 Premise child green shirt fish type hat near water blue and.  
 premise true? Yes No or UnknownThe is Unknown  
 Hypo {Hypothesis}  
 Premise: {Premise}  
 the? Yes, No orThe is:

**AG's News**  
 Article Car in Baghdad bombs11 yesterday American diplomats desert.  
 low score Norman will leaders the Championship Co;satt Resort, Brisbane.  
 Answer: Sports  
 Article Prices; a - Oil;49 in thatsupply northernAnswer: Business  
 Article a Hollywood industry cases.  
 Answer: Tech  
 Article {Input}  
 Answer:

**Yelp-5**  
 Sentence: auto race Wilbur the to win three?  
 bad  
 Sentence: CNN is the abbreviation for?  
 Sentiment: neutral  
 Sentence Doones character to?  
 Sent  
 Sentence Where did get his metaliment: great  
 Sentence: What causes canker sores?  
 Sentiment terrible  
 Sentence: {Input}  
 Sentiment:

Continuation of Table 27

Continuation of Table 27	
2750	
2751	: 7.... she good at?
2752	Topic music
2753	
2754	Sentence Does any think it's to love of the opposite sex at the timeTopic:
2755	
2756	Sentence: Does it upset that there people out there that want prove Jesus walk
2757	waterTopic: culture
2758	
2759	Sentence want to find an e-mail of a a to years hes nameiotoulis.?
2760	Topic: business: Why call hispanic Mexicans?
2761	Topic: Sentence What British the largest ship WW- Navy? Who sank?
2762	Topic: education picture from space is the look atTopic science
2763	<b>Yahoo</b>
2764	Sentence: can find the information about be jump?
2765	Topic: sports
2766	
2767	: used to beta, recently it when had to reinstall windows xp how do get
2768	Topic: computer
2769	
2770	: am I a loser?
2771	Topic
2772	
2773	Sentence: <i>{Input}</i>
2774	Topic
2775	
2776	Here is a which is negative: "this place awful!". Here a rewrite of text positive: "this
2777	place is amazing!".
2778	Here is, which is negative: "initely buy another pair of socks thisthey have worst sock
2779	Here is a of the text, which is: "initely will buy another pair socks from store-they have
2780	the".
2781	is a text, which is negative: " <i>{Input}</i> ". Here a of the, which is positive: "
2782	<b>Yelp Positive Transfer</b>
2783	, whichvery.". rewrite the text negative: "very works terribly.
2784	isi the, really.
2785	" <i>{Input}</i> ". the negative: "
2786	<b>Yelp Negative Transfer</b>
2787	:Options) a into hold B a.
2788	A) into- diameter diameter.
2789	Answer
2790	<b>PIQA</b>
2791	Question: <i>{Input}</i>
2792	Options: A <i>{Option1}</i> B) <i>{Option2}</i>
2793	Answer:
2794	: If there3 cars in parking and2 more cars, many cars in the lot?
2795	Let's step by step
2796	There originally 3 cars.
2797	2 cars arrive.
2798	3 +2 =5The answer is 5Question: <i>{Input}</i>
2799	's think step
2800	
2801	Continuation of Table 27
2802	
2803	
2804	

2805  
2806  
2807  
2808  
2809  
2810  
2811  
2812  
2813  
2814  
2815  
2816  
2817  
2818  
2819  
2820  
2821  
2822  
2823  
2824  
2825  
2826  
2827  
2828  
2829  
2830  
2831  
2832  
2833  
2834  
2835  
2836  
2837  
2838  
2839  
2840  
2841  
2842  
2843  
2844  
2845  
2846  
2847  
2848  
2849  
2850  
2851  
2852  
2853  
2854  
2855  
2856  
2857  
2858  
2859

Continuation of Table 27

**MAWPS**

Question: house is % the price. Let think step original up the information. (x, 500% of  
Therefore  $18515 \text{ sidesfrac}\{500\}\{0\}236 \text{ price}1.$

Question: *{Input}*  
Let's step