

# Question Answering Infused Pre-training of General-Purpose Contextualized Representations

Anonymous ACL submission

## Abstract

We propose a pre-training objective based on question answering (QA) for learning general-purpose contextualized representations, motivated by the intuition that the representation of a phrase in a passage should encode all questions that the phrase can answer in context. To this end, we train a bi-encoder QA model, which independently encodes passages and questions, to match the predictions of a more accurate cross-encoder model on 80 million synthesized QA pairs. By encoding QA-relevant information, the bi-encoder’s token-level representations are useful for non-QA downstream tasks without extensive (or in some cases, any) fine-tuning. We show large improvements over both RoBERTa-large and previous state-of-the-art results on zero-shot and few-shot paraphrase detection on four datasets, few-shot named entity recognition on two datasets, and zero-shot sentiment analysis on three datasets.

## 1 Introduction

Although masked language models build contextualized word representations, they are pre-trained with losses that minimize distance to *uncontextualized* word embeddings (Peters et al., 2018; Devlin et al., 2019; Liu et al., 2019). In this paper, we introduce Question Answering Infused Pre-training (QUIP), a new pre-training loss based on question answering (QA) that depends much more directly on context, and learns improved token-level representations for a range of zero- and few-shot tasks.

Our intuition for QUIP is that the contextualized representation for a phrase in a passage should contain enough information to identify all the questions that the phrase could answer in context. For example, in Figure 1, the representation for *Johannes Brahms* should be similar to the representation of all questions it can answer, such as “*Who wrote the violin concerto?*” We anticipate that optimizing passage representations for QA should benefit many downstream tasks, as question-answer pairs




Figure 1: An overview of Question Answering Infused Pre-training. Our model independently creates vector representations (middle) for phrases in a passage (top) and for synthesized questions (bottom). Our objective encourages the vector for each phrase to have high similarity with the vectors for all questions it answers.

have been used as broad-coverage meaning representations (He et al., 2015; Michael et al., 2018), and a wide range of NLP tasks can be cast as QA problems (Levy et al., 2017; McCann et al., 2018; Gardner et al., 2019). For instance, our learned representations should encode whether a phrase answers a question like “*Why was the movie considered good?*”, which corresponds to identifying rationales for sentiment analysis.

We train QUIP with a bi-encoder extractive QA objective. The bi-encoder model independently encodes passages and questions such that the representation of each phrase in a passage is similar to the representation of reading comprehension questions answered by that phrase. To train this model, we use a question generation model to synthesize 80 million QA examples, then train the bi-encoder to match the predictions of a cross-encoder QA model, which processes the passage and question

together, on these examples. Bi-encoder QA has been used before for efficient open-domain QA via phrase retrieval (Seo et al., 2018, 2019; Lee et al., 2020, 2021), but its lower accuracy compared to cross-encoder QA has previously been viewed as a drawback. We instead view the relative weakness of bi-encoder QA as an opportunity to improve contextual representations via knowledge distillation, as self-training can be effective when the student model must solve a harder problem than the teacher (Xie et al., 2020). In particular, since the bi-encoder does not know the question when encoding the passage, it must produce a single passage representation that simultaneously encodes the answers to *all* possible questions. In contrast, while cross-encoder QA models are more accurate, they depend on a specific question when encoding a passage; thus, they are less suited to downstream use cases that require contextualized representations of passages in isolation.

We show that QUIP token-level representations are useful in a variety of zero-shot and few-shot learning settings, both because the representations directly encode useful contextual information, and because we can often reduce downstream tasks to QA. For few-shot paraphrase detection, QUIP with BERTScore-based features (Zhang et al., 2020) outperforms prior work by 9 F1 points across four datasets. For few-shot named entity recognition (NER), QUIP combined with an initialization scheme that uses question embeddings improves over RoBERTa-large by 14 F1 across two datasets. Finally, for zero-shot sentiment analysis, QUIP with question prompts improves over RoBERTa-large with MLM-style prompts by 5 accuracy points across three datasets, and extracts interpretable rationales as a side effect. Through ablations, we show that using real questions, a strong teacher model, and the bi-encoder architecture are all crucial to the success of QUIP. We will release code to reproduce all results upon publication.

## 2 QA Infused Pre-training

QA Infused Pre-training (QUIP) involves pre-training contextual representations with a bi-encoder extractive QA objective. In this section, we introduce some notation (§2.1), then describe our QUIP pipeline, which consists of three steps: question generation (§2.2), cross-encoder teacher re-labeling (§2.3), and bi-encoder training (§2.4).

### 2.1 Notation

All models operate on sequences of tokens  $x = [x_1, \dots, x_L]$  of length  $L$ , where  $x_1$  is the special beginning-of-sequence token. We learn an encoder  $r$  that maps inputs  $x$  to outputs  $r(x) = [r(x)_1, \dots, r(x)_L]$  where each  $r(x)_i \in \mathbb{R}^d$  for some fixed dimension  $d$ . We call  $r(x)_i$  the contextual representation of the  $i$ -th token in  $x$ .

In extractive question answering, a model is given a context passage  $c$  and question  $q$ , and must output a span of  $c$  that answers the question. Typically, models independently predict probability distributions  $p(a_{\text{start}} | c, q)$  and  $p(a_{\text{end}} | c, q)$  over the answer start index  $a_{\text{start}}$  and end index  $a_{\text{end}}$ .

### 2.2 Question Generation

**Question generation model.** We train a BART-large model (Lewis et al., 2020) to generate question-answer pairs given context passages. The model receives the passage as context and must generate the answer text, then a special separator token, then the question; this approach is simpler than prior approaches that use separate models for answer and question generation (Lewis and Fan, 2019; Alberti et al., 2019; Puri et al., 2020), and works well in practice.

**Training data.** We train on data from the MRQA 2019 Shared Task (Fisch et al., 2019), which includes six datasets: HotpotQA (Yang et al., 2018), NaturalQuestions (Kwiatkowski et al., 2019), NewsQA (Trischler et al., 2017), SearchQA (Dunn et al., 2017), SQuAD (Rajpurkar et al., 2016), and TriviaQA (Joshi et al., 2017). These datasets cover many of the text sources commonly used for pre-training (Liu et al., 2019; Lewis et al., 2020), namely Wikipedia (HotpotQA, NaturalQuestions, SQuAD), News articles (NewsQA), and general web text (SearchQA, TriviaQA).

**Generating questions.** We run our question generation model over a large set of passages to generate a large dataset of question-answer pairs. We decode using nucleus sampling (Holtzman et al., 2020) with  $p = 0.6$ , which was chosen by manual inspection to balance diversity with quality of generated questions. We do not filter questions in any way. While we observed some flaws related to question quality (questions were not always well-formed) and diversity (for some passages, the same or very similar questions were asked multiple times), this approach nonetheless yielded good

downstream results. Attempts to mitigate these issues, such as using a two-stage beam search to ensure that questions for the same passage have different answers, did not noticeably change our downstream results (see §4.8). We obtain passages from the same training corpus as RoBERTa (Liu et al., 2019), which uses four sub-domains: BOOK-CORPUS plus Wikipedia, CC-NEWS, OPENWEB-TEXT, and STORIES. For each domain, we sample 2 million passages and generate 10 questions per passage, for a total of 80 million questions.<sup>1</sup>

### 2.3 Teacher Re-labeling

The answers generated by our BART model are not always accurate, nor are they always spans in the context passage. To improve the training signal, we relabel examples with a teacher model, as is common in knowledge distillation (Hinton et al., 2015). We use a standard cross-encoder RoBERTa-large model trained on the MRQA training data as our teacher. The model takes in the concatenation of the context passage  $c$  and question  $q$  and predicts  $a_{\text{start}}$  and  $a_{\text{end}}$  with two independent 2-layer multi-layer perceptron (MLP) heads. Let  $T_{\text{start}}(c, q)$  and  $T_{\text{end}}(c, q)$  denote the teacher’s predicted probability distribution over  $a_{\text{start}}$  and  $a_{\text{end}}$ , respectively.

### 2.4 Bi-encoder Training

Finally, we train a bi-encoder model to match the cross-encoder predictions on the generated questions. This objective encourages the contextual representation for a token to have high similarity (in inner product space) with the representation of every question that is answered by that token.

**Model.** The bi-encoder model with parameters  $\theta$  consists of of three components: an encoder  $r$  and two question embedding heads  $h_{\text{start}}$  and  $h_{\text{end}}$  that map  $\mathbb{R}^d \rightarrow \mathbb{R}^d$ . These heads will only be applied to beginning-of-sequence (i.e., CLS) representations; as shorthand, define  $f_{\text{start}}(x) = h_{\text{start}}(r(x)_1)$  and likewise for  $f_{\text{end}}$ . Given a context passage  $c$  and question  $q$ , the model predicts

$$p_{\theta}(a_{\text{start}} = i \mid c, q) \propto e^{r(c)_i^{\top} f_{\text{start}}(q)} \quad (1)$$

$$p_{\theta}(a_{\text{end}} = i \mid c, q) \propto e^{r(c)_i^{\top} f_{\text{end}}(q)} \quad (2)$$

In other words, the model independently encodes the passage and question with  $r$ , applies the start

<sup>1</sup>We estimate that using the entire corpus with these settings would generate around 900 million questions. We leave investigation of further scaling to future work.

and end heads to the CLS token embedding for  $q$ , then predicts the answer start (end) index with a softmax over the dot product between the passage representation at that index and the output of the start (end) head. We initialize  $r$  to be the pre-trained RoBERTa-large model (Liu et al., 2019), which uses  $d = 1024$ .  $h_{\text{start}}$  and  $h_{\text{end}}$  are randomly-initialized 2-layer MLPs with hidden dimension 1024, matching the default initialization of classification heads in RoBERTa.

**Training.** For an input consisting of context  $c$  of length  $L$  and question  $q$ , we train  $\theta$  to minimize the KL-divergence between the student and teacher predictions, which is equivalent to the objective

$$-\sum_{i=1}^L T_{\text{start}}(c, q)_i \log p_{\theta}(a_{\text{start}} = i \mid c, q) + T_{\text{end}}(c, q)_i \log p_{\theta}(a_{\text{end}} = i \mid c, q) \quad (3)$$

up to constants that do not depend on  $\theta$ . We train for two epochs on the 80 million generated questions, which takes roughly 56 hours on 8 V100 GPUs, or roughly 19 GPU-days.<sup>2</sup> For details about training, see Appendix A.1.

## 3 Downstream Tasks

We evaluate QUIP on zero-shot paraphrase ranking, few-shot paraphrase classification, few-shot NER, and zero-shot sentiment analysis. We leverage the improved token-level representations afforded by QUIP, and in many cases also directly use QUIP’s question-answering abilities.

### 3.1 Paraphrase Ranking

We first evaluate QUIP token-level representations by measuring their usefulness for zero-shot paraphrase ranking. In this task, systems must rank sentence pairs that are paraphrases above pairs that are non-paraphrases, without any task-specific training data. We compute similarity scores using the  $F_{\text{BERT}}$  variant of BERTScore (Zhang et al., 2020), which measures cosine similarities between the representation of each token in one sentence and its most similar token in the other sentence. Given sentences  $x_1$  and  $x_2$  of lengths  $L_1$  and  $L_2$ , define

$$B(x_1, x_2) = \frac{1}{L_1} \sum_{i=1}^{L_1} \max_{1 \leq j \leq L_2} \frac{r(x_1)_i^{\top} r(x_2)_j}{\|r(x_1)_i\| \|r(x_2)_j\|}.$$

<sup>2</sup>For comparison, pre-training RoBERTa-large from scratch took roughly 5000 GPU-days (Liu et al., 2019)

The  $F_{\text{BERT}}$  BERTScore is defined as the harmonic mean of  $B(x_1, x_2)$  and  $B(x_2, x_1)$ . Zhang et al. (2020) showed that BERTScore with RoBERTa is useful for both natural language generation evaluation and paraphrase ranking. Since BERTScore uses token-level representations, we hypothesize that it should pair well with QUIP. As in Zhang et al. (2020), we use representations from the layer of the network that maximizes Pearson correlation between BERTScore and human judgments on the WMT16 metrics shared task (Bojar et al., 2016).

### 3.2 Paraphrase Classification

We next use either frozen or fine-tuned QUIP representations for few-shot paraphrase classification, rather than ranking. Through these experiments, we can compare QUIP with existing work on few-shot paraphrase classification.

**Frozen model.** We train a logistic regression model that uses BERTScore with frozen representations as features. For a given pair of sentences, we extract eight features, corresponding to BERTScore computed with the final eight layers (i.e., layers 17-24) of the network. These layers encompass the optimal layers for both RoBERTa-large and QUIP (see §4.4). Freezing the encoder is often useful in practice, particularly for large models, as the same model can be reused for many tasks (Brown et al., 2020; Du et al., 2020).

**Fine-tuning.** For fine-tuning, we use the same computation graph and logistic loss function, but now backpropagate through the parameters of our encoder. For details, see Appendix A.3.

### 3.3 Named Entity Recognition

We also use QUIP for few-shot<sup>3</sup> named entity recognition, which we frame as a BIO tagging task. Since questions in QA often ask for entities of a specific type, we expect QUIP representations to contain rich entity type information. We add a linear layer that takes in token-level representations and predicts the tag for each token, and backpropagate log loss through the entire network. By default, the output layer is initialized randomly.

As a refinement, we propose using question prompts to initialize this model. The output layer is parameterized by a  $T \times d$  matrix  $M$ , where  $T$  is the number of distinct BIO tags. The log-probability

<sup>3</sup>Yang and Katiyar (2020) study few-shot NER assuming data from other NER datasets is available; we assume no such data is available, matching Huang et al. (2020).

of predicting the  $j$ -th tag for token  $i$  is proportional to the dot product between the representation for token  $i$  and the  $j$ -th row of  $M$ ; this resembles how the bi-encoder predicts answers. Thus, we initialize each row of  $M$  with the start head embedding of a question related to that row’s corresponding entity tag. For instance, we initialize the parameters for the `B-location` and `I-location` tags with the embedding for “*What is a location ?*” We normalize the question embeddings to have unit L2 norm. This style of initialization is uniquely enabled by our bi-encoder QA model; it would be unclear how to use a language model or a cross-encoder QA model similarly.

### 3.4 Zero-shot Sentiment Analysis

Finally, we use QUIP for zero-shot binary sentiment analysis. We reduce sentiment analysis to QA by writing a pair of questions that ask for a *reason* why an item is good or bad (e.g., “*Why is this movie [good/bad]?*”). We predict the label whose corresponding question has higher similarity with the QUIP representation of some token in the input. This prompting strategy has the additional benefit of extracting rationales, namely the span that the QUIP model predicts as the answer to the question. While we focus on sentiment analysis, extractive rationales have been used for a wide range of NLP tasks (DeYoung et al., 2020), suggesting that this method could be applied more broadly.

More formally, let  $x$  be an input sentence and  $(q_0, q_1)$  be a pair of questions (i.e., a prompt). For label  $y \in \{0, 1\}$ , we compute a score for  $y$  as

$$S(x, y) = \max_i r(x)_i^\top f_{\text{start}}(q_y) + \max_i r(x)_i^\top f_{\text{end}}(q_y). \quad (4)$$

This formula is a straightforward way to measure the extent to which *some* span in  $x$  looks like the answer to the question  $q_y$ , based on the model’s pre-trained ability to perform QA. We predict whichever  $y$  has the higher value of  $S(x, y) - C_y$ , where  $C_y$  is a calibration constant that offsets the model’s bias towards answering  $q_0$  or  $q_1$ . Our inclusion of  $C_y$  is inspired by Zhao et al. (2021), who recommend calibrating zero-shot and few-shot models with a baseline derived from content-free inputs to account for biases towards a particular label. To choose  $C_y$ , we obtain a list  $W$  of the ten most frequent English words, all of which convey no sentiment, and define  $C_y$  as the mean over



$w \in W$  of  $S(w, y)$ , i.e., the score when using  $w$  as the input sentence (see Appendix A.5).

## 4 Experiments

### 4.1 Experimental details

**Datasets.** For paraphrasing, we use four datasets: QQP (Iyer et al., 2017), MRPC (Dolan and Brockett, 2005), PAWS-Wiki, and PAWS-QQP (Zhang et al., 2019). The PAWS datasets were designed to be challenging for bag-of-words models, and thus test whether our representations are truly contextual or mostly lexical. For QQP and MRPC, we use the few-shot splits from Gao et al. (2021) that include 16 examples per class; for the PAWS datasets, we create new few-shot splits in the same manner. We report results on the development sets of QQP and MRPC (as test labels were not available), the test set of PAWS-Wiki, and the “dev-and-test” set of PAWS-QQP. For NER, we use two datasets: CoNLL 2003 (Tjong Kim Sang and De Meulder, 2003) and WNUT-17 (Derczynski et al., 2017). We use the few-shot splits from Huang et al. (2020) that include 5 examples per entity type. All few-shot experiments report an average over five random splits and seeds, following both Gao et al. (2021) and Huang et al. (2020). For sentiment analysis, we use two movie review datasets, SST-2 (Socher et al., 2013) and Movie Reviews (MR; Pang and Lee, 2005), as well as the Customer Reviews (CR) dataset (Hu and Liu, 2004). We evaluate on the SST-2 development set and the MR and CR test sets made by Gao et al. (2021).

**Hyperparameter and prompt selection.** Due to the nature of zero-shot and few-shot experiments, we minimize the extent to which we tune hyperparameters, relying on existing defaults and previously published hyperparameters. For few-shot paraphrase classification, NER, and sentiment analysis, we developed our final method only using QQP, CoNLL, and SST-2, respectively, and directly applied it to the other datasets with no further tuning. We did measure zero-shot paraphrase ranking accuracy on all datasets during development of QUIP. For more details, see Appendix A.4.

For NER, we used the first question prompts we wrote for both CoNLL and WNUT, which all follow the same format, “*Who/What is a/an [entity type] ?*” (see Appendix A.8 for all prompts). For sentiment analysis, we wrote six prompts (shown in Appendix A.10) and report mean accuracy over

these prompts, to avoid pitfalls associated with prompt tuning (Perez et al., 2021). We use the same prompts for SST-2 and MR; for CR, the only change we make is replacing occurrences of the word “*movie*” with “*product*” to reflect the change in domain between these datasets.

### 4.2 Baselines and Ablations

To confirm the importance of all three stages of our pre-training pipeline, we compare with a number of baselines and ablations.

**No question generation.** We train the bi-encoder model directly on the MRQA training data (“Bi-encoder + MRQA”). We also include the cross-encoder teacher model trained on MRQA as a baseline (“Cross-encoder + MRQA”). These settings mirror standard intermediate task training (Phang et al., 2018; Pruksachatkun et al., 2020).

**No teacher.** We train the bi-encoder using the answer generated by the question generation model (“QUIP, no teacher”). If the generated answer is not a span in the passage, we consider the question unanswerable and treat the span containing the CLS token as the answer, as in Devlin et al. (2019).

**Cross-encoder self-training.** To test whether the bottleneck imposed by the bi-encoder architecture is crucial for QUIP, we also train a cross-encoder model on our generated data (“QUIP, cross-encoder student”). Since this student model has the same architecture as the teacher model, we train it to match the teacher’s argmax predictions, a standard self-training objective (Lee, 2013). We train for a comparable number of GPU-hours as QUIP (see Appendix A.2 for details).

**Unsupervised QA.** We test whether QUIP requires real QA data, or if a rough approximation suffices. We thus train a bi-encoder on 80 million pseudo-questions generated by applying noise to sentences (“Bi-encoder + UnsupervisedQA”), as in Lewis et al. (2019).

### 4.3 Bi-encoder Question Answering

While not our main focus, we first check that QUIP improves bi-encoder QA accuracy, as shown in Table 1. QUIP improves over Lee et al. (2021) by 5.4 F1 on the SQuAD development set. It also surpasses the reported human accuracy of 91.2 F1 on the SQuAD test set, as well as the best cross-encoder BERT-large single model from Devlin et al. (2019). QUIP greatly improves over baselines that

Model	EM	F1
Lee et al. (2021)	78.3	86.3
Bi-encoder + UnsupervisedQA	17.4	24.9
Bi-encoder + MRQA	70.7	79.4
QUIP, no teacher	75.3	84.7
QUIP	<b>85.2</b>	<b>91.7</b>
BERT-large cross-encoder	84.2	91.1
Cross-encoder + MRQA	88.8	94.7
QUIP, cross-encoder student	<b>89.5</b>	<b>94.8</b>

Table 1: EM and F1 scores on the SQuAD development set for bi-encoder (top) and cross-encoder (bottom) models. QUIP outperforms the other bi-encoder model baselines, and even a cross-encoder BERT-large model. The RoBERTa cross-encoder models are better at QA, but will underperform QUIP on non-QA tasks.

directly train on MRQA data or do not use the teacher model. As expected, our cross-encoder models are more accurate at QA; we will show that their representations are less useful for non-QA tasks than the QUIP bi-encoder. Appendix A.6 shows results on all MRQA development datasets.

#### 4.4 Zero-shot Paraphrase Ranking

We validate our approach and study the effects of various ablations on zero-shot paraphrase ranking. The first half of Table 2 shows WMT development set Pearson correlations averaged across six to-English datasets, as in Zhang et al. (2020), along with the best layer for each model. QUIP reaches its optimal score at a later layer (20) than RoBERTa-large (17), which may suggest that the QUIP training objective is more closely aligned with learning better representations than MLM.

The rest of Table 2 shows zero-shot paraphrase ranking results using BERTScore. QUIP improves substantially over RoBERTa on all four datasets, with an average improvement of .076 AUROC. The improvement is greatest on the PAWS datasets; since these datasets cannot be solved by lexical features alone, QUIP representations must be much more contextualized than RoBERTa representations. Training on Unsupervised QA data degrades performance compared to RoBERTa, showing that QUIP does not merely make word representations encode local context in a simple way. Training the bi-encoder directly on the MRQA dataset or without the teacher improves on average over RoBERTa, but QUIP greatly outperforms both baselines. The cross-encoder models also lag behind QUIP at paraphrase ranking, despite their higher QA accuracy. Thus, we conclude that having real questions, accu-

rate answer supervision, and a bi-encoder student model are all crucial to the success of QUIP.

#### 4.5 Paraphrase Classification

Table 3 shows few-shot paraphrase classification results. As we studied ablations in the previous section, we focus on the comparison between QUIP and non-QUIP baselines. First, we use RoBERTa-large embeddings in place of QUIP in our method. Second, we compare with LM-BFF (Gao et al., 2021), which pairs RoBERTa-large with MLM-style prompts. We use LM-BFF with manually written prompts and demonstrations, which was their best method on QQP by 2.1 F1 and was 0.3 F1 worse than their best method on MRPC. QUIP used as a frozen encoder is competitive with LM-BFF on QQP and outperforms it by 6.1 F1 on MRPC, 11.2 F1 on PAWS-Wiki, and 12.1 F1 on PAWS-QQP. Fine-tuning QUIP gives additional improvements on three of the four datasets, and outperforms fine-tuning RoBERTa by an average of 6.9 F1.

#### 4.6 Named Entity Recognition

Table 4 shows few-shot NER results on the CoNLL and WNUT datasets. QUIP improves over RoBERTa-large by 11 F1 on CoNLL and 2.9 F1 on WNUT when used with a randomly initialized output layer. We see a further improvement of 4 F1 on CoNLL and 7.4 F1 on WNUT when using question embeddings to initialize the output layer. Using the cross-encoder trained directly on QA data is roughly as good as QUIP when using randomly initialized output layers, but it is incompatible with question embedding initialization.

#### 4.7 Sentiment Analysis

Table 5 shows zero-shot accuracy on our three sentiment analysis datasets. We compare with zero-shot results for LM-BFF (Gao et al., 2021)<sup>4</sup> and reported zero-shot results from Zhao et al. (2021) using GPT-3 with Contextual Calibration (CC) on SST-2. QUIP using an average prompt outperforms zero-shot LM-BFF by 5.4 points, averaged across the three datasets. Choosing the best prompt on SST-2 and using that for all datasets improves results not only on SST-2 but also MR, and maintains average accuracy on CR. Using the cross-encoder student QA model with the same prompts leads to worse performance: we hypothesize that the bi-encoder bottleneck encourages QUIP to make each

<sup>4</sup>We tried applying our calibration strategy to LM-BFF as well, but found that it did not improve accuracy.

Model	WMT $r$	WMT Best Layer	QQP	MRPC	PAWS-Wiki	PAWS-QQP
RoBERTa-large	.739	17	.763	.831	.698	.690
Cross-encoder + MRQA	.744	16	.767	.840	.742	.731
QUIP, cross-encoder student	.753	16	.769	.847	.751	.706
Bi-encoder + UnsupervisedQA	.654	11	.747	.801	.649	.580
Bi-encoder + MRQA	.749	15	.771	.807	.747	.725
QUIP, no teacher	.726	19	.767	.831	.780	.709
QUIP	<b>.764</b>	20	<b>.809</b>	<b>.849</b>	<b>.830</b>	<b>.796</b>

Table 2: Pearson correlation on WMT development data, best layer chosen based on WMT results, and AUROC on zero-shot paraphrase ranking using BERTScore. QUIP outperforms all baselines on all datasets.

Model	Fine-tuned?	QQP	MRPC	PAWS-Wiki	PAWS-QQP
LM-BFF (reported)	Fine-tuned	69.8 <sub>0.8</sub>	77.8 <sub>0.9</sub>	-	-
LM-BFF (rerun)	Fine-tuned	67.1 <sub>0.9</sub>	76.5 <sub>1.5</sub>	60.7 <sub>0.7</sub>	50.1 <sub>2.8</sub>
RoBERTa-large	Frozen	64.4 <sub>0.4</sub>	80.6 <sub>0.7</sub>	62.3 <sub>0.9</sub>	50.6 <sub>0.4</sub>
QUIP	Frozen	68.9 <sub>0.2</sub>	82.6 <sub>0.4</sub>	71.9 <sub>0.5</sub>	<b>63.0<sub>1.2</sub></b>
RoBERTa-large	Fine-tuned	64.9 <sub>0.7</sub>	84.4 <sub>0.3</sub>	65.7 <sub>0.3</sub>	50.9 <sub>0.8</sub>
QUIP	Fine-tuned	<b>71.0<sub>0.3</sub></b>	<b>86.6<sub>0.4</sub></b>	<b>75.1<sub>0.2</sub></b>	60.9 <sub>1.0</sub>

Table 3: F1 scores on few-shot paraphrase classification, averaged across five training splits (standard errors in subscripts). QUIP outperforms prior work (LM-BFF; Gao et al., 2021) as well as our own RoBERTa baselines.

Model	CoNLL	WNUT
Huang et al. (2020)	65.4	37.6
<b>Standard init.</b>		
RoBERTa-large	59.0 <sub>2.4</sub>	39.3 <sub>0.6</sub>
Cross-encoder + MRQA	68.9 <sub>3.3</sub>	43.0 <sub>0.9</sub>
QUIP, cross-encoder student	63.4 <sub>3.3</sub>	39.4 <sub>1.7</sub>
Bi-encoder + UnsupervisedQA	58.2 <sub>2.6</sub>	26.0 <sub>1.0</sub>
Bi-encoder + MRQA	66.4 <sub>3.3</sub>	42.2 <sub>0.4</sub>
QUIP, no teacher	67.7 <sub>1.9</sub>	40.7 <sub>1.4</sub>
QUIP	70.0 <sub>2.4</sub>	42.2 <sub>0.5</sub>
<b>Question prompt init.</b>		
Bi-encoder + UnsupervisedQA	62.7 <sub>3.3</sub>	30.4 <sub>0.8</sub>
Bi-encoder + MRQA	72.0 <sub>2.8</sub>	44.0 <sub>1.3</sub>
QUIP, no teacher	71.4 <sub>3.0</sub>	47.8 <sub>1.1</sub>
QUIP	<b>74.0<sub>2.4</sub></b>	<b>49.6<sub>0.5</sub></b>

Table 4: F1 scores on few-shot NER, averaged over five training splits (standard errors in subscripts). QUIP with question prompts performs best on both datasets.

span’s representation dissimilar to those of questions that it does not answer, whereas the cross-encoder model trained only on answerable questions handles unanswerable questions poorly (e.g., “Why is it bad?” asked about a positive review).

Table 6 shows rationales extracted from random SST-2 examples for which QUIP was correct with the best prompt for SST-2 (“What is the reason this movie is [good/bad]?”). To prefer shorter rationales, we extract the highest-scoring span of five BPE tokens or less. The model often identifies phrases that convey clear sentiment. Appendix A.11 shows full examples and rationales.

Model	SST-2	MR	CR
CC + GPT-3	71.6	-	-
LM-BFF	83.6	80.8	79.5
QUIP (average)	<b>87.9<sub>0.6</sub></b>	<b>81.9<sub>0.4</sub></b>	<b>90.3<sub>0.2</sub></b>
w/ cross-enc. student	83.3 <sub>0.4</sub>	78.5 <sub>0.4</sub>	88.9 <sub>0.3</sub>
QUIP (tune on SST-2)	89.6	83.1	90.4

Table 5: Zero-shot accuracy on sentiment analysis. Third and fourth rows show mean accuracy across six prompts (standard error in subscripts). QUIP with an average prompt outperforms prior work; using the best prompt on SST-2 helps on all datasets.

Label	Rationale
-	“too slim”, “stale”, “every idea”, “wore out its welcome”, “unpleasant viewing experience”, “lifeless”, “plot”, “amateurishly assembled”, “10 times their natural size”, “wrong turn”
+	“packed with information and impressions”, “slash-and-hack”, “tightly organized efficiency”, “passion and talent”, “best films”, “surprises”, “great summer fun”, “play equally well”, “convictions”, “wickedly subversive bent”

Table 6: Rationales extracted by QUIP on ten random examples for each label from SST-2.

## 4.8 Stability Analysis

We experimented with some design decisions that did not materially affect our results. Appendix A.7 shows results for three such choices: including in-batch negative passages (Lee et al., 2021), using the argmax prediction of the teacher rather than soft labels, and using beam search to generate a diverse set of answers followed by one high-likelihood

question per answer. We take these findings as evidence that our basic recipe is stable to many small changes. For question generation, we hypothesize that the objective of matching the cross-encoder teacher model encourages the bi-encoder to learn important features identified by the cross-encoder, even on questions that are not entirely well-formed.

## 5 Discussion and Related Work

We build on work in question generation and answering, pre-training, and few-shot learning.

**Question Generation.** Neural question generation has been well-studied for different purposes (Du et al., 2017; Du and Cardie, 2018; Zhao et al., 2018; Lewis and Fan, 2019; Alberti et al., 2019; Puri et al., 2020; Lewis et al., 2021; Bartolo et al., 2021). We use generated questions to learn general-purpose representations. We also show that a relatively simple strategy of generating the answer and question together with a single model can be effective; most prior work uses separate answer selection and question generation models.

**Phrase-indexed Question Answering.** Phrase-indexed question answering is a paradigm for open-domain QA that retrieves answers by embedding questions and candidate answers in a shared embedding space (Seo et al., 2018, 2019; Lee et al., 2020). It requires using a bi-encoder architecture for efficient phrase retrieval. Especially related is Lee et al. (2021), which also uses question generation and a cross-encoder teacher model to improve phrase-indexed QA, though they focus on improving QA accuracy rather than transfer to other tasks. Our results reinforce prior observations that bi-encoder models are usually less accurate at QA than cross-encoders (see Table 1). However, the bi-encoder model transfers better to settings that require a contextualized representation of a single passage; the cross-encoder instead optimizes for producing representations of passage-question pairs.

**Improving question answering.** While we use QA to aid pre-training, related work aims to improve accuracy on QA. Ram et al. (2021) propose a span extraction pre-training objective that enables few-shot QA. Khashabi et al. (2020) run multi-task training on many QA datasets, both extractive and non-extractive, to improve QA accuracy.

**Learning contextual representations.** Pre-training on unlabeled data has yields useful

contextual representations (Peters et al., 2018; Devlin et al., 2019), but further improvements are possible using labeled data. Intermediate task training (Phang et al., 2018) improves representations by training directly on large labeled datasets. Muppet (Aghajanyan et al., 2021) improves models by multi-task pre-finetuning on many labeled datasets. Most similar to our work, He et al. (2020) uses extractive QA to pre-train a BERT paragraph encoder. We use question generation and knowledge distillation to improve over directly training on labeled data, and focus on zero- and few-shot settings. Other work has used similar methods to learn sentence embeddings. Reimers and Gurevych (2019) train sentence embeddings for sentence similarity tasks using natural language inference data. Thakur et al. (2021) train a sentence embedding bi-encoder to mimic the predictions of a cross-encoder model. We learn token-level representations, rather than a single vector for a sentence, and thus use token-level supervision from extractive QA.

**Few-shot learning.** We study few-shot learning without access to unlabeled data, following most recent work (Brown et al., 2020; Gao et al., 2021; Zhao et al., 2021). Schick and Schütze (2021) notably propose a semi-supervised approach that uses unlabeled data for knowledge distillation; this process does not improve accuracy, but mainly improves efficiency. Moreover, large-scale unlabeled data may not be easily obtainable for all tasks, and utilizing such data increase computation time in the fine-tuning stage, so we focus on the setting without unlabeled data. The aforementioned work uses language models for few-shot learning by converting tasks to language modeling problems; we develop alternative methods for few-shot learning that use token-level representations and question-based prompts.

## 6 Conclusion

In this work, we pre-trained token-level contextual representations that are useful for downstream few-shot learning. Our key idea was to use question-answer pairs to define what information should be encoded in bi-encoder passage representations. We showed that passage representations learned in this way are useful for a variety of standard NLP tasks in zero- and few-shot settings, namely paraphrase detection, named entity recognition, and sentiment analysis, across nine total datasets.



636

## References

637  
638  
639  
640  
641

Armen Aghajanyan, Anchit Gupta, Akshat Shrivastava, Xilun Chen, Luke Zettlemoyer, and Sonal Gupta. 2021. [Muppet: Massive multi-task representations with pre-finetuning](#). *arXiv preprint arXiv:2101.11038*.

642  
643  
644  
645  
646  
647  
648

Chris Alberti, Daniel Andor, Emily Pitler, Jacob Devlin, and Michael Collins. 2019. [Synthetic QA corpora generation with roundtrip consistency](#). In *Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics*, pages 6168–6173, Florence, Italy. Association for Computational Linguistics.

649  
650  
651  
652  
653

Max Bartolo, Tristan Thrush, Robin Jia, Sebastian Riedel, Pontus Stenetorp, and Douwe Kiela. 2021. [Improving question answering model robustness with synthetic adversarial data generation](#). *arXiv preprint arXiv:2104.08678*.

654  
655  
656  
657  
658  
659

Ondřej Bojar, Yvette Graham, Amir Kamran, and Miloš Stanojević. 2016. [Results of the WMT16 metrics shared task](#). In *Proceedings of the First Conference on Machine Translation: Volume 2, Shared Task Papers*, pages 199–231, Berlin, Germany. Association for Computational Linguistics.

660  
661  
662  
663  
664  
665  
666  
667  
668  
669  
670  
671  
672  
673

Tom Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared D Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, Sandhini Agarwal, Ariel Herbert-Voss, Gretchen Krueger, Tom Henighan, Rewon Child, Aditya Ramesh, Daniel Ziegler, Jeffrey Wu, Clemens Winter, Chris Hesse, Mark Chen, Eric Sigler, Mateusz Litwin, Scott Gray, Benjamin Chess, Jack Clark, Christopher Berner, Sam McCandlish, Alec Radford, Ilya Sutskever, and Dario Amodei. 2020. [Language models are few-shot learners](#). In *Advances in Neural Information Processing Systems*, volume 33, pages 1877–1901. Curran Associates, Inc.

674  
675  
676  
677  
678  
679  
680

Leon Derczynski, Eric Nichols, Marieke van Erp, and Nut Limsopatham. 2017. [Results of the WNUT2017 shared task on novel and emerging entity recognition](#). In *Proceedings of the 3rd Workshop on Noisy User-generated Text*, pages 140–147, Copenhagen, Denmark. Association for Computational Linguistics.

681  
682  
683  
684  
685  
686  
687  
688  
689

Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. 2019. [BERT: Pre-training of deep bidirectional transformers for language understanding](#). In *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers)*, pages 4171–4186, Minneapolis, Minnesota. Association for Computational Linguistics.

690  
691  
692

Jay DeYoung, Sarthak Jain, Nazneen Fatema Rajani, Eric Lehman, Caiming Xiong, Richard Socher, and Byron C. Wallace. 2020. [ERASER: A benchmark to](#)

[evaluate rationalized NLP models](#). In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, pages 4443–4458, Online. Association for Computational Linguistics. 693  
694  
695  
696

William B. Dolan and Chris Brockett. 2005. [Automatically constructing a corpus of sentential paraphrases](#). In *Proceedings of the Third International Workshop on Paraphrasing (IWP2005)*. 697  
698  
699  
700

Jingfei Du, Myle Ott, Haoran Li, Xing Zhou, and Veselin Stoyanov. 2020. [General purpose text embeddings from pre-trained language models for scalable inference](#). In *Findings of the Association for Computational Linguistics: EMNLP 2020*, pages 3018–3030, Online. Association for Computational Linguistics. 701  
702  
703  
704  
705  
706  
707

Xinya Du and Claire Cardie. 2018. [Harvesting paragraph-level question-answer pairs from Wikipedia](#). In *Proceedings of the 56th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 1907–1917, Melbourne, Australia. Association for Computational Linguistics. 708  
709  
710  
711  
712  
713  
714

Xinya Du, Junru Shao, and Claire Cardie. 2017. [Learning to ask: Neural question generation for reading comprehension](#). In *Proceedings of the 55th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 1342–1352, Vancouver, Canada. Association for Computational Linguistics. 715  
716  
717  
718  
719  
720  
721

Dheeru Dua, Yizhong Wang, Pradeep Dasigi, Gabriel Stanovsky, Sameer Singh, and Matt Gardner. 2019. [DROP: A reading comprehension benchmark requiring discrete reasoning over paragraphs](#). In *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers)*, pages 2368–2378, Minneapolis, Minnesota. Association for Computational Linguistics. 722  
723  
724  
725  
726  
727  
728  
729  
730  
731

Matthew Dunn, Levent Sagun, Mike Higgins, V. Ugur Guney, Volkan Cirik, and Kyunghyun Cho. 2017. [SearchQA: A new Q&A dataset augmented with context from a search engine](#). *arXiv preprint arXiv:1704.05179*. 732  
733  
734  
735  
736

Adam Fisch, Alon Talmor, Robin Jia, Minjoon Seo, Eunsol Choi, and Danqi Chen. 2019. [MRQA 2019 shared task: Evaluating generalization in reading comprehension](#). In *Proceedings of the 2nd Workshop on Machine Reading for Question Answering*, pages 1–13, Hong Kong, China. Association for Computational Linguistics. 737  
738  
739  
740  
741  
742  
743

Tianyu Gao, Adam Fisch, and Danqi Chen. 2021. [Making pre-trained language models better few-shot learners](#). In *Association for Computational Linguistics (ACL)*. 744  
745  
746  
747

748	Matt Gardner, Jonathan Berant, Hannaneh Hajishirzi, Alon Talmor, and Sewon Min. 2019. <a href="#">Question answering is a format; when is it useful?</a> <i>arXiv preprint arXiv:1909.11291</i> .	<i>EMNLP 2020</i> , pages 1896–1907, Online. Association for Computational Linguistics.	805 806
752	Hangfeng He, Qiang Ning, and Dan Roth. 2020. <a href="#">QuASE: Question-answer driven sentence encoding</a> . In <i>Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics</i> , pages 8743–8758, Online. Association for Computational Linguistics.	Tom Kwiatkowski, Jennimaria Palomaki, Olivia Redfield, Michael Collins, Ankur Parikh, Chris Alberti, Danielle Epstein, Illia Polosukhin, Jacob Devlin, Kenton Lee, Kristina Toutanova, Llion Jones, Matthew Kelcey, Ming-Wei Chang, Andrew M. Dai, Jakob Uszkoreit, Quoc Le, and Slav Petrov. 2019. <a href="#">Natural questions: A benchmark for question answering research</a> . <i>Transactions of the Association for Computational Linguistics</i> , 7:452–466.	807 808 809 810 811 812 813 814 815
758	Luheng He, Mike Lewis, and Luke Zettlemoyer. 2015. <a href="#">Question-answer driven semantic role labeling: Using natural language to annotate natural language</a> . In <i>Proceedings of the 2015 Conference on Empirical Methods in Natural Language Processing</i> , pages 643–653, Lisbon, Portugal. Association for Computational Linguistics.	Guokun Lai, Qizhe Xie, Hanxiao Liu, Yiming Yang, and Eduard Hovy. 2017. <a href="#">RACE: Large-scale Reading comprehension dataset from examinations</a> . In <i>Proceedings of the 2017 Conference on Empirical Methods in Natural Language Processing</i> , pages 785–794, Copenhagen, Denmark. Association for Computational Linguistics.	816 817 818 819 820 821 822
765	Geoffrey Hinton, Oriol Vinyals, and Jeffrey Dean. 2015. <a href="#">Distilling the knowledge in a neural network</a> . In <i>NeurIPS Deep Learning and Representation Learning Workshop</i> .	Dong-Hyun Lee. 2013. <a href="#">Pseudo-label: The simple and efficient semi-supervised learning method for deep neural networks</a> . In <i>ICML 2013 Workshop on Challenges in Representation Learning (WREPL)</i> .	823 824 825 826
769	Ari Holtzman, Jan Buys, Li Du, Maxwell Forbes, and Yejin Choi. 2020. <a href="#">The curious case of neural text de-generation</a> . In <i>International Conference on Learning Representations</i> .	Jinhyuk Lee, Minjoon Seo, Hannaneh Hajishirzi, and Jaewoo Kang. 2020. <a href="#">Contextualized sparse representations for real-time open-domain question answering</a> . In <i>Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics</i> , pages 912–919, Online. Association for Computational Linguistics.	827 828 829 830 831 832 833
773	Minqing Hu and Bing Liu. 2004. Mining and summarizing customer reviews. In <i>Proceedings of the tenth ACM SIGKDD international conference on Knowledge discovery and data mining</i> , pages 168–177.	Jinhyuk Lee, Mujeen Sung, Jaewoo Kang, and Danqi Chen. 2021. <a href="#">Learning dense representations of phrases at scale</a> . In <i>Association for Computational Linguistics (ACL)</i> .	834 835 836 837
777	Jiaxin Huang, Chunyuan Li, Krishan Subudhi, Damien Jose, Shobana Balakrishnan, Weizhu Chen, Baolin Peng, Jianfeng Gao, and Jiawei Han. 2020. <a href="#">Few-shot named entity recognition: A comprehensive study</a> . <i>arXiv preprint arXiv:2012.14978</i> .	Omer Levy, Minjoon Seo, Eunsol Choi, and Luke Zettlemoyer. 2017. <a href="#">Zero-shot relation extraction via reading comprehension</a> . In <i>Proceedings of the 21st Conference on Computational Natural Language Learning (CoNLL 2017)</i> , pages 333–342, Vancouver, Canada. Association for Computational Linguistics.	838 839 840 841 842 843
782	Shankar Iyer, Nikhil Dandekar, and Kornél Csernai. 2017. First quora dataset release: Question pairs. <a href="https://www.quora.com/q/quoradata/First-Quora-Dataset-Release-Question-Pairs">https://www.quora.com/q/quoradata/First-Quora-Dataset-Release-Question-Pairs</a>	Mike Lewis and Angela Fan. 2019. <a href="#">Generative question answering: Learning to answer the whole question</a> . In <i>International Conference on Learning Representations</i> .	844 845 846 847
786	Mandar Joshi, Eunsol Choi, Daniel Weld, and Luke Zettlemoyer. 2017. <a href="#">TriviaQA: A large scale distantly supervised challenge dataset for reading comprehension</a> . In <i>Proceedings of the 55th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)</i> , pages 1601–1611, Vancouver, Canada. Association for Computational Linguistics.	Mike Lewis, Yinhan Liu, Naman Goyal, Marjan Ghazvininejad, Abdelrahman Mohamed, Omer Levy, Veselin Stoyanov, and Luke Zettlemoyer. 2020. <a href="#">BART: Denoising sequence-to-sequence pre-training for natural language generation, translation, and comprehension</a> . In <i>Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics</i> , pages 7871–7880, Online. Association for Computational Linguistics.	848 849 850 851 852 853 854 855 856
793	Aniruddha Kembhavi, Minjoon Seo, Dustin Schwenk, Jonghyun Choi, Ali Farhadi, and Hannaneh Hajishirzi. 2017. <a href="#">Are you smarter than a sixth grader? textbook question answering for multimodal machine comprehension</a> . In <i>2017 IEEE Conference on Computer Vision and Pattern Recognition (CVPR)</i> , pages 5376–5384.	Patrick Lewis, Ludovic Denoyer, and Sebastian Riedel. 2019. <a href="#">Unsupervised question answering by cloze translation</a> . In <i>Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics</i> ,	857 858 859 860
800	Daniel Khashabi, Sewon Min, Tushar Khot, Ashish Sabharwal, Oyvind Tafjord, Peter Clark, and Hannaneh Hajishirzi. 2020. <a href="#">UNIFIEDQA: Crossing format boundaries with a single QA system</a> . In <i>Findings of the Association for Computational Linguistics</i> :		

861	pages 4896–4910, Florence, Italy. Association for Computational Linguistics.	918
862		919
863	Patrick Lewis, Yuxiang Wu, Linqing Liu, Pasquale Minervini, Heinrich Küttler, Aleksandra Piktus, Pontus Stenetorp, and Sebastian Riedel. 2021. <a href="#">Paq: 65 million probably-asked questions and what you can do with them</a> . <i>arXiv preprint arXiv:2102.07033</i> .	920
864		921
865		922
866		923
867		924
868	Yinhan Liu, Myle Ott, Naman Goyal, Jingfei Du, Mandar Joshi, Danqi Chen, Omer Levy, Mike Lewis, Luke Zettlemoyer, and Veselin Stoyanov. 2019. <a href="#">RoBERTa: A robustly optimized bert pretraining approach</a> . <i>arXiv preprint arXiv:1907.11692</i> .	925
869		926
870		927
871		928
872		929
873		930
874	Bryan McCann, Nitish Shirish Keskar, Caiming Xiong, and Richard Socher. 2018. <a href="#">The natural language decathlon: Multitask learning as question answering</a> . <i>arXiv preprint arXiv:1806.08730</i> .	931
875		932
876		933
877		934
878	Julian Michael, Gabriel Stanovsky, Luheng He, Ido Dagan, and Luke Zettlemoyer. 2018. <a href="#">Crowdsourcing question-answer meaning representations</a> . In <i>Proceedings of the 2018 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 2 (Short Papers)</i> , pages 560–568, New Orleans, Louisiana. Association for Computational Linguistics.	935
879		936
880		937
881		938
882		939
883		940
884		941
885		942
886		943
887	Stephen Mussmann, Robin Jia, and Percy Liang. 2020. <a href="#">On the Importance of Adaptive Data Collection for Extremely Imbalanced Pairwise Tasks</a> . In <i>Findings of the Association for Computational Linguistics: EMNLP 2020</i> , pages 3400–3413, Online. Association for Computational Linguistics.	944
888		945
889		946
890		947
891		948
892		949
893	Bo Pang and Lillian Lee. 2005. <a href="#">Seeing stars: Exploiting class relationships for sentiment categorization with respect to rating scales</a> . In <i>Proceedings of the 43rd Annual Meeting of the Association for Computational Linguistics (ACL’05)</i> , pages 115–124, Ann Arbor, Michigan. Association for Computational Linguistics.	950
894		951
895		952
896		953
897		954
898		955
899		956
900	F. Pedregosa, G. Varoquaux, A. Gramfort, V. Michel, B. Thirion, O. Grisel, M. Blondel, P. Prettenhofer, R. Weiss, V. Dubourg, J. Vanderplas, A. Passos, D. Cournapeau, M. Brucher, M. Perrot, and E. Duchesnay. 2011. <a href="#">Scikit-learn: Machine learning in Python</a> . <i>Journal of Machine Learning Research</i> , 12:2825–2830.	957
901		958
902		959
903		960
904		961
905		962
906		963
907	Ethan Perez, Douwe Kiela, and Kyunghyun Cho. 2021. <a href="#">True few-shot learning with language models</a> . <i>arXiv preprint arXiv:2105.11447</i> .	964
908		965
909		966
910	Matthew Peters, Mark Neumann, Mohit Iyyer, Matt Gardner, Christopher Clark, Kenton Lee, and Luke Zettlemoyer. 2018. <a href="#">Deep contextualized word representations</a> . In <i>Proceedings of the 2018 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long Papers)</i> , pages 2227–2237, New Orleans, Louisiana. Association for Computational Linguistics.	967
911		968
912		969
913		970
914		971
915		972
916		973
917		974
	Jason Phang, Thibault Févry, and Samuel R Bowman. 2018. <a href="#">Sentence encoders on stilts: Supplementary training on intermediate labeled-data tasks</a> . <i>arXiv preprint arXiv:1811.01088</i> .	918
		919
		920
		921
	Yada Pruksachatkun, Jason Phang, Haokun Liu, Phu Mon Htut, Xiaoyi Zhang, Richard Yuanzhe Pang, Clara Vania, Katharina Kann, and Samuel R. Bowman. 2020. <a href="#">Intermediate-task transfer learning with pretrained language models: When and why does it work?</a> In <i>Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics</i> , pages 5231–5247, Online. Association for Computational Linguistics.	922
		923
		924
		925
		926
		927
		928
		929
		930
	Raul Puri, Ryan Spring, Mohammad Shoeybi, Mostofa Patwary, and Bryan Catanzaro. 2020. <a href="#">Training question answering models from synthetic data</a> . In <i>Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing (EMNLP)</i> , pages 5811–5826, Online. Association for Computational Linguistics.	931
		932
		933
		934
		935
		936
		937
	Pranav Rajpurkar, Jian Zhang, Konstantin Lopyrev, and Percy Liang. 2016. <a href="#">SQuAD: 100,000+ questions for machine comprehension of text</a> . In <i>Proceedings of the 2016 Conference on Empirical Methods in Natural Language Processing</i> , pages 2383–2392, Austin, Texas. Association for Computational Linguistics.	938
		939
		940
		941
		942
		943
	Ori Ram, Yuval Kirstain, Jonathan Berant, Amir Globerson, and Omer Levy. 2021. <a href="#">Few-shot question answering by pretraining span selection</a> . In <i>Association for Computational Linguistics (ACL)</i> .	944
		945
		946
		947
	Nils Reimers and Iryna Gurevych. 2019. <a href="#">Sentence-BERT: Sentence embeddings using Siamese BERT-networks</a> . In <i>Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing (EMNLP-IJCNLP)</i> , pages 3982–3992, Hong Kong, China. Association for Computational Linguistics.	948
		949
		950
		951
		952
		953
		954
		955
	Amrita Saha, Rahul Aralikkatte, Mitesh M. Khapra, and Karthik Sankaranarayanan. 2018. <a href="#">DuoRC: Towards complex language understanding with paraphrased reading comprehension</a> . In <i>Proceedings of the 56th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)</i> , pages 1683–1693, Melbourne, Australia. Association for Computational Linguistics.	956
		957
		958
		959
		960
		961
		962
		963
	Timo Schick and Hinrich Schütze. 2021. <a href="#">It’s not just size that matters: Small language models are also few-shot learners</a> . In <i>Proceedings of the 2021 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies</i> , pages 2339–2352, Online. Association for Computational Linguistics.	964
		965
		966
		967
		968
		969
		970
	Minjoon Seo, Tom Kwiatkowski, Ankur Parikh, Ali Farhadi, and Hannaneh Hajishirzi. 2018. <a href="#">Phrase-indexed question answering: A new challenge for scalable document comprehension</a> . In <i>Proceedings</i>	971
		972
		973
		974



975					
976					
977					
978	Minjoon Seo, Jinhyuk Lee, Tom Kwiatkowski, Ankur				
979	Pariikh, Ali Farhadi, and Hannaneh Hajishirzi. 2019.				
980	<a href="#">Real-time open-domain question answering with</a>				
981	<a href="#">dense-sparse phrase index</a> . In <i>Proceedings of the</i>				
982	<i>57th Annual Meeting of the Association for Computa-</i>				
983	<i>tional Linguistics</i> , pages 4430–4441, Florence, Italy.				
984	Association for Computational Linguistics.				
985	Richard Socher, Alex Perelygin, Jean Wu, Jason				
986	Chuang, Christopher D. Manning, Andrew Ng, and				
987	Christopher Potts. 2013. <a href="#">Recursive deep models for</a>				
988	<a href="#">semantic compositionality over a sentiment treebank</a> .				
989	In <i>Proceedings of the 2013 Conference on Empiri-</i>				
990	<i>cal Methods in Natural Language Processing</i> , pages				
991	1631–1642, Seattle, Washington, USA. Association				
992	for Computational Linguistics.				
993	Nandan Thakur, Nils Reimers, Johannes Daxenberger,				
994	and Iryna Gurevych. 2021. <a href="#">Augmented SBERT: Data</a>				
995	<a href="#">augmentation method for improving bi-encoders for</a>				
996	<a href="#">pairwise sentence scoring tasks</a> . In <i>Proceedings of</i>				
997	<i>the 2021 Conference of the North American Chapter</i>				
998	<i>of the Association for Computational Linguistics: Hu-</i>				
999	<i>man Language Technologies</i> , pages 296–310, Online.				
1000	Association for Computational Linguistics.				
1001	Erik F. Tjong Kim Sang and Fien De Meulder.				
1002	2003. <a href="#">Introduction to the CoNLL-2003 shared task:</a>				
1003	<a href="#">Language-independent named entity recognition</a> . In				
1004	<i>Proceedings of the Seventh Conference on Natural</i>				
1005	<i>Language Learning at HLT-NAACL 2003</i> , pages 142–				
1006	147.				
1007	Adam Trischler, Tong Wang, Xingdi Yuan, Justin Har-				
1008	ris, Alessandro Sordani, Philip Bachman, and Kaheer				
1009	Suleman. 2017. <a href="#">NewsQA: A machine comprehension</a>				
1010	<a href="#">dataset</a> . In <i>Proceedings of the 2nd Workshop</i>				
1011	<i>on Representation Learning for NLP</i> , pages 191–200,				
1012	Vancouver, Canada. Association for Computational				
1013	Linguistics.				
1014	George Tsatsaronis, Georgios Balikas, Prodromos				
1015	Malakasiotis, Ioannis Partalas, Matthias Zschunke,				
1016	Michael R Alvers, Dirk Weissenborn, Anastasia				
1017	Krithara, Sergios Petridis, Dimitris Polychronopou-				
1018	los, Yannis Almirantis, John Pavlopoulos, Nico-				
1019	las Baskiotis, Patrick Gallinari, Thierry Artieres,				
1020	Axel Ngonga, Norman Heino, Eric Gaussier, Lil-				
1021	iana Barrio-Alvers, Michael Schroeder, Ion An-				
1022	droutsopoulos, and Georgios Paliouras. 2015. <a href="#">An</a>				
1023	<a href="#">overview of the bioasq large-scale biomedical se-</a>				
1024	<a href="#">mantic indexing and question answering competition</a> .				
1025	<i>BMC Bioinformatics</i> , 16:138.				
1026	Thomas Wolf, Lysandre Debut, Victor Sanh, Julien				
1027	Chaumond, Clement Delangue, Anthony Moi, Pier-				
1028	ric Cistac, Tim Rault, Remi Louf, Morgan Funtow-				
1029	icz, Joe Davison, Sam Shleifer, Patrick von Platen,				
1030	Clara Ma, Yacine Jernite, Julien Plu, Canwen Xu,				
1031	Teven Le Scao, Sylvain Gugger, Mariama Drame,				
	Quentin Lhoest, and Alexander Rush. 2020. <a href="#">Trans-</a>				
	<a href="#">formers: State-of-the-art natural language processing</a> .				
	In <i>Proceedings of the 2020 Conference on Empirical</i>				
	<i>Methods in Natural Language Processing: System</i>				
	<i>Demonstrations</i> , pages 38–45, Online. Association				
	for Computational Linguistics.				
	Qizhe Xie, Minh-Thang Luong, Eduard Hovy, and				
	Quoc V. Le. 2020. Self-training with noisy student				
	improves imagenet classification. In <i>Proceedings of</i>				
	<i>the IEEE/CVF Conference on Computer Vision and</i>				
	<i>Pattern Recognition (CVPR)</i> .				
	Yi Yang and Arzoo Katiyar. 2020. <a href="#">Simple and effective</a>				
	<a href="#">few-shot named entity recognition with structured</a>				
	<a href="#">nearest neighbor learning</a> . In <i>Proceedings of the</i>				
	<i>2020 Conference on Empirical Methods in Natural</i>				
	<i>Language Processing (EMNLP)</i> , pages 6365–6375,				
	Online. Association for Computational Linguistics.				
	Zhilin Yang, Peng Qi, Saizheng Zhang, Yoshua Bengio,				
	William Cohen, Ruslan Salakhutdinov, and Christo-				
	pher D. Manning. 2018. <a href="#">HotpotQA: A dataset for</a>				
	<a href="#">diverse, explainable multi-hop question answering</a> .				
	In <i>Proceedings of the 2018 Conference on Empiri-</i>				
	<i>cal Methods in Natural Language Processing</i> , pages				
	2369–2380, Brussels, Belgium. Association for Com-				
	putational Linguistics.				
	Tianyi Zhang, Varsha Kishore, Felix Wu, Kilian Q.				
	Weinberger, and Yoav Artzi. 2020. <a href="#">BERTScore:</a>				
	<a href="#">Evaluating text generation with bert</a> . In <i>International</i>				
	<i>Conference on Learning Representations</i> .				
	Yuan Zhang, Jason Baldridge, and Luheng He. 2019.				
	<a href="#">PAWS: Paraphrase adversaries from word scrambling</a> .				
	In <i>Proceedings of the 2019 Conference of the North</i>				
	<i>American Chapter of the Association for Computa-</i>				
	<i>tional Linguistics: Human Language Technologies,</i>				
	<i>Volume 1 (Long and Short Papers)</i> , pages 1298–1308,				
	Minneapolis, Minnesota. Association for Computa-				
	tional Linguistics.				
	Tony Z. Zhao, Eric Wallace, Shi Feng, Dan Klein, and				
	Sameer Singh. 2021. <a href="#">Calibrate before use: Improv-</a>				
	<a href="#">ing few-shot performance of language models</a> . <i>arXiv</i>				
	<i>preprint arXiv:2102.09690</i> .				
	Yao Zhao, Xiaochuan Ni, Yuanyuan Ding, and Qifa				
	Ke. 2018. <a href="#">Paragraph-level neural question gener-</a>				
	<a href="#">ation with maxout pointer and gated self-attention</a>				
	<a href="#">networks</a> . In <i>Proceedings of the 2018 Conference on</i>				
	<i>Empirical Methods in Natural Language Processing</i> ,				
	pages 3901–3910, Brussels, Belgium. Association				
	for Computational Linguistics.				
	<b>A Appendix</b>				
	<b>A.1 QUIP Details</b>				
	For efficiency, we process all questions for the same				
	passage in the same batch, as encoding passages				
	dominates runtime. We limit passages to 456 byte-				
	pair encoding (BPE) tokens and questions to 50 so				



that the concatenation can fit comfortably within the 512 token context usable by the cross-encoder teacher. We create passages from our unlabeled text corpus by greedily selecting maximal chunks of contiguous sentences that fit within the BPE token limit. We pre-compute the teacher predictions  $T_{\text{start}}$  and  $T_{\text{end}}$  before bi-encoder training. To save space, we sparsify these vectors by only storing the eight largest predicted probabilities, treating all others as 0.

We conducted minimal hyperparameter tuning for QUIP. We used a learning rate of  $1 \cdot 10^{-5}$  (default for most RoBERTa fine-tuning experiments<sup>5</sup>) and no gradient accumulation, which we found led to faster training.

## A.2 Cross-encoder Self-training Details

Training is much less efficient for the cross-encoder than the bi-encoder, since batching questions about the same passage together does not speed up training, so we train for a comparable number of GPU-hours (60 hours on 8 V100 GPUs).

## A.3 Paraphrase Fine-tuning Details

To fine-tune our model for paraphrase classification, we use two practices recommended by Musmann et al. (2020), who also train a binary classification model that uses cosine similarity-based features derived from fine-tuned BERT embeddings. First, we disable dropout during training, as dropout artificially lowers all cosine similarities. Second, we use a larger learning rate on the final output layer than the Transformer parameters, by a factor of  $10^3$ .

## A.4 Downstream Task Hyperparameter Details

For few-shot paraphrase detection with the frozen model, we use Scikit-learn’s logistic regression implementation with default settings (Pedregosa et al., 2011). For fine-tuned paraphrase detection, we again use a learning rate of  $1 \cdot 10^{-5}$  and train for 20 epochs, which we found to usually be sufficient for convergence on the training data. For NER, we use the default hyperparameters from the Huggingface transformers repository (Wolf et al., 2020), with the exception of decreasing the learning rate from  $5 \cdot 10^{-5}$  to  $2 \cdot 10^{-5}$ , which we found improved the RoBERTa baseline on CoNLL.

<sup>5</sup><https://github.com/pytorch/fairseq/tree/master/examples/roberta>

## A.5 Sentiment Analysis Calibration

To calibrate the zero-shot sentiment analysis model, we use ten content-free inputs: “the”, “be”, “to”, “of”, “and”, “a”, “in”, “that”, “have”, and “I”. These were the top ten words listed on [https://en.wikipedia.org/wiki/Most\\_common\\_words\\_in\\_English](https://en.wikipedia.org/wiki/Most_common_words_in_English). We only applied calibration for the main QUIP model, as we did not find calibration to improve results for either LM-BFF or the cross-encoder QA student model.

## A.6 Full QA results

Table 7 shows EM and F1 scores on the 12 development sets from the MRQA 2019 Shared Task (Fisch et al., 2019). These are divided into 6 in-domain datasets—HotpotQA (Yang et al., 2018), NaturalQuestions (Kwiatkowski et al., 2019), NewsQA (Trischler et al., 2017), SearchQA (Dunn et al., 2017), SQuAD (Rajpurkar et al., 2016), and TriviaQA (Joshi et al., 2017)—for which corresponding training data was used to train the question generation model and teacher, and 6 out-of-domain datasets—BioASQ (Tsatsaronis et al., 2015), DROP (Dua et al., 2019), DuoRC (Saha et al., 2018), RACE (Lai et al., 2017), RelationExtraction (Levy et al., 2017), and TextbookQA (Kembhavi et al., 2017)—for which no training data was used in the QUIP pipeline. QUIP improves over training the bi-encoder directly on the MRQA data by an average of 4.4 F1 on the in-domain datasets and 12.7 F1 on the out-of-domain datasets. It underperforms the cross-encoder teacher by about 5 F1 on both the in-domain and out-of-domain datasets on average.

## A.7 Stability Analysis

We experimented with some design decisions that did not materially affect our results. Here, we report these findings as evidence that our basic recipe is stable to many small changes. First, we concatenated the representations of all passages in the same batch and on the same GPU together (9 passages on average), and trained the model to extract answers from this larger pseudo-document; this effectively adds in-batch negative passages, as in Lee et al. (2021). Second, we trained the model to match the argmax prediction of the teacher, rather than its soft distribution over start and end indices. Finally, we used a two-stage beam search to generate questions. For a given passage, we generated

In-domain	HotpotQA	NaturalQ	NewsQA	SQuAD	SearchQA	TriviaQA	Average
Bi-encoder + UnsupervisedQA	9.5 / 16.6	8.0 / 15.5	7.6 / 14.4	17.5 / 25.0	15.4 / 21.1	17.6 / 23.3	12.6 / 19.3
Bi-encoder + MRQA	61.0 / 77.5	64.1 / 76.4	46.1 / 61.5	70.9 / 79.6	73.8 / 79.8	63.1 / 69.0	63.2 / 74.0
QUIP, no teacher	52.9 / 68.7	57.8 / 70.8	41.8 / 58.7	75.4 / 84.8	64.5 / 71.7	71.1 / 76.1	60.6 / 71.8
QUIP	61.3 / 77.9	63.7 / 77.2	52.4 / 68.7	85.3 / 91.8	68.7 / 76.8	72.0 / 78.1	67.2 / 78.4
Cross-encoder + MRQA	66.8 / 83.0	70.5 / 82.0	58.8 / 72.9	89.1 / 94.8	78.3 / 84.6	73.4 / 79.6	72.8 / 82.8
QUIP, cross-encoder student	66.3 / 82.3	66.5 / 79.4	54.4 / 70.5	89.6 / 94.9	72.1 / 80.1	73.4 / 79.8	70.4 / 81.2
Out-of-domain	BioASQ	DROP	DuoRC	RACE	RelationExt	TextbookQA	Average
Bi-encoder + UnsupervisedQA	15.3 / 19.2	5.9 / 9.5	14.1 / 17.4	6.5 / 11.4	12.7 / 22.1	8.9 / 13.3	10.6 / 15.5
Bi-encoder + MRQA	42.2 / 57.2	29.9 / 38.3	38.6 / 48.6	29.1 / 39.8	71.3 / 83.5	34.7 / 43.6	41.0 / 51.8
QUIP, no teacher	40.9 / 54.9	33.5 / 43.0	44.1 / 53.2	31.8 / 44.4	70.8 / 82.1	37.3 / 46.2	43.0 / 54.0
QUIP	51.3 / 67.5	46.2 / 57.1	53.0 / 63.2	39.6 / 53.4	75.5 / 86.0	50.2 / 60.0	52.6 / 64.5
Cross-encoder + MRQA	58.0 / 72.9	55.4 / 65.3	55.0 / 66.8	44.2 / 57.7	78.5 / 88.8	58.5 / 67.4	58.2 / 69.8
QUIP, cross-encoder student	57.3 / 72.6	57.5 / 68.3	56.2 / 67.5	44.8 / 58.6	79.5 / 89.1	58.4 / 67.3	59.0 / 70.6

Table 7: Exact match/F1 scores on the twelve development datasets from the MRQA 2019 shared task. The six in-domain datasets are on top; the six out-of-domain datasets are on bottom.

Model	SQuAD F1	Paraphrase AUROC	NER F1
QUIP	91.7	.821	61.8
+ concat. passages	91.7	.818	62.7
w/ hard labels	91.5	.814	62.5
w/ 2-stage beam search	91.7	.821	62.8

Table 8: SQuAD development set F1, average zero-shot paraphrase ranking AUROC across all datasets, and average few-shot NER F1 using question prompts across both datasets for QUIP variants. Models shown here are all similarly effective.

Entity type	Question
<b>Both datasets</b>	
O	“What is a generic object ?”
Person	“Who is a person ?”
Location	“What is a location ?”
<b>CoNLL</b>	
Organization	“What is an organization ?”
Miscellaneous	“What is a miscellaneous entity ?”
<b>WNUT</b>	
Corporation	“What is a corporation ?”
Product	“What is a product ?”
Creative work	“What is a creative work ?”
Group	“What is a group ?”

Table 9: Question prompts used for the CoNLL and WNUT NER datasets.

Model	CoNLL	WNUT
RoBERTa-large	92.7	57.9
QUIP, standard	92.7	58.1
QUIP, QA prompts	92.8	58.8

Table 10: F1 scores on NER, using the entire training dataset.

20 possible answers via beam search, chose 10 of these to maximize answer diversity, then generated one question for each answer with another beam search. Our goal was to ensure diversity by forcing questions to be about different answers, while also maintaining high question quality. As shown in Table 8, these choices have a relatively minor impact on the results (within .007 AUROC and 1 F1 on NER).

## A.8 QA Prompts for NER

Table 9 shows the question prompts we use to initialize the NER model for CoNLL and WNUT. For entity types that occur in both datasets, and for the O tag, we always use the same question. We used the English description of the entity type provided by the dataset.

## A.9 Full training set NER

Table 10 shows NER results when training on the full training dataset. QUIP gives a 0.6 F1 improvement on WNUT, but has effectively the same accuracy on CoNLL.

## A.10 Sentiment Analysis QA Prompts

Table 11 shows the six prompts we use for sentiment analysis for the movie review datasets (SST-2 and MR). Each prompt consists of one question for the positive label and one for the negative label. For CR, we use the same prompts except that we replace all instances of the word “movie” with “product”.

## A.11 Sentiment Analysis Rationales

Tables 12, 13, and 14 show full examples and rationales extracted by our zero-shot sentiment analysis

#	Label	Question
1	+	“Why is it good?”
	-	“Why is it bad?”
2	+	“Why is this movie good?”
	-	“Why is this movie bad?”
3	+	“Why is it great?”
	-	“Why is it terrible?”
4	+	“What makes this movie good?”
	-	“What makes this movie bad?”
5	+	“What is the reason this movie is good?”
	-	“What is the reason this movie is bad?”
6	+	“What is the reason this movie is great?”
	-	“What is the reason this movie is terrible?”

Table 11: Question prompts used for sentiment analysis on movie review datasets (SST-2 and MR). Prompts used for CR are identical except for replacing “*movie*” with “*product*”.

1213 method for SST-2, MR, and CR, respectively. In  
1214 all cases, we use the prompt that led to the highest  
1215 accuracy on SST-2. For each dataset, we randomly  
1216 sample ten examples of each label for which the  
1217 model predicted the correct answer. We highlight  
1218 in bold the span of  $\leq 5$  BPE tokens that the model  
1219 predicts best answers the question associated with  
1220 the correct label. In some cases, the rationales cor-  
1221 respond to clear sentiment markers. In other cases,  
1222 they highlight an aspect of a movie or product that  
1223 is criticized or praised in the review; these could be  
1224 considered reasonable answers to a question like  
1225 “Why is this movie bad?” even if the sentiment asso-  
1226 ciated with them is unclear without the surrounding  
1227 context. In future work, it would be interesting to  
1228 find better ways to align the task of extractive QA  
1229 and with the goal of producing rationales that are  
1230 human-interpretable in isolation.

Label	SST-2 Example (rationale in bold)
-	<p>“for starters , the story is just <b>too slim</b> .”</p> <p>“paid in full is so <b>stale</b> , in fact , that its most vibrant scene is one that uses clips from brian de palma ’s scarface .”</p> <p>“( e ) ventually , <b>every idea</b> in this film is flushed down the latrine of heroism .”</p> <p>“corpus collosum – while undeniably interesting – <b>wore out its welcome</b> well before the end credits rolled about 45 minutes in .”</p> <p>“makes for a pretty <b>unpleasant viewing experience</b> .”</p> <p>“while ( hill ) has learned new tricks , the tricks alone are not enough to salvage this <b>lifeless</b> boxing film .”</p> <p>“it ’s hampered by a lifetime-channel kind of <b>plot</b> and a lead actress who is out of her depth .”</p> <p>“dull , lifeless , and <b>amateurishly assembled</b> .”</p> <p>“the movie is what happens when you blow up small potatoes to <b>10 times their natural size</b> , and it ai n’t pretty .”</p> <p>“every time you look , sweet home alabama is taking another bummer of a <b>wrong turn</b> .”</p>
+	<p>“though only 60 minutes long , the film is <b>packed with information and impressions</b> .”</p> <p>“good old-fashioned <b>slash-and-hack</b> is back !”</p> <p>“with <b>tightly organized efficiency</b> , numerous flashbacks and a constant edge of tension , miller ’s film is one of 2002 ’s involvingly adult surprises .”</p> <p>“displaying about equal amounts of naïveté , <b>passion and talent</b> , beneath clouds establishes sen as a filmmaker of considerable potential .”</p> <p>“easily my choice for one of the year ’s <b>best films</b> . ”</p> <p>“a delectable and intriguing thriller filled with <b>surprises</b> , read my lips is an original .”</p> <p>“it is <b>great summer fun</b> to watch arnold and his buddy gerald bounce off a quirky cast of characters .”</p> <p>“the film will <b>play equally well</b> on both the standard and giant screens .”</p> <p>“for this reason and this reason only – the power of its own steadfast , hoity-toity <b>convictions</b> – chelsea walls deserves a medal .”</p> <p>“there ’s a <b>wickedly subversive bent</b> to the best parts of birthday girl .”</p>

Table 12: Rationales (in bold) extracted by the zero-shot QUIP sentiment analysis model for SST-2. We show ten random examples for each label on which the model made the correct prediction.

Label	MR Example (rationale in bold)
-	<p>“strangely comes off as a kingdom <b>more mild than wild</b> .”</p> <p>“feels like the work of someone who may indeed have finally <b>aged past his prime</b> . . . and , perhaps more than he realizes , just wants to be liked by the people who can still give him work .”</p> <p>“watching the powerpuff girls movie , my mind kept returning to one anecdote for comparison : the cartoon in japan that <b>gave people seizures</b> .”</p> <p>“this is a movie so insecure about its <b>capacity to excite</b> that it churns up not one but two flagrantly fake thunderstorms to underscore the action .”</p> <p>“<b>witless</b> , pointless , tasteless and idiotic .”</p> <p>“the next big thing’s not-so-big ( and <b>not-so-hot</b> ) directorial debut .”</p> <p>“unfortunately , it’s also <b>not very good</b> . especially compared with the television series that inspired the movie .”</p> <p>“<b>irwin and his director</b> never come up with an adequate reason why we should pay money for what we can get on television for free .”</p> <p>“with this new rollerball , sense and sensibility have been overrun by what can only be characterized as <b>robotic sentiment</b> .”</p> <p>“the video work is so <b>grainy and rough</b> , so dependent on being ’naturalistic’ rather than carefully lit and set up , that it’s exhausting to watch .”</p>
+	<p>“the <b>appearance of treebeard</b> and gollum’s expanded role will either have you loving what you’re seeing , or rolling your eyes . i loved it ! gollum’s ’performance’ is incredible !”</p> <p>“droll <b>caper-comedy</b> remake of “ big deal on madonna street ” that’s a sly , amusing , laugh-filled little gem in which the ultimate “ bellini ” begins to look like a “ real kaputschnik . ””</p> <p>“katz uses archival footage , horrifying documents of lynchings , still photographs and charming old reel-to-reel recordings of meeropol entertaining his children to create his song history , but most powerful of all is <b>the song itself</b>”</p> <p>“a thunderous ride at first , quiet cadences of pure finesse are few and far between ; their shortage dilutes the potency of otherwise respectable action . still , this flick is <b>fun</b> , and host to some truly excellent sequences .”</p> <p>“<b>compellingly watchable</b> .”</p> <p>“an unbelievably fun film just a <b>leading man away from perfection</b> .”</p> <p>“andersson creates a world that’s at once <b>surreal and disturbingly familiar</b> ; absurd , yet tremendously sad .”</p> <p>“the <b>invincible</b> werner herzog is alive and well and living in la”</p> <p>“you can feel the heat that ignites this gripping tale , and the <b>humor and humanity</b> that root it in feeling .”</p> <p>“this is a terrific <b>character study</b> , a probe into the life of a complex man .”</p>

Table 13: Rationales (in bold) extracted by the zero-shot QUIP sentiment analysis model for the Movie Reviews (MR) dataset. We show ten random examples for each label on which the model made the correct prediction.



Label	CR Example (rationale in bold)
-	<p>“i ’ve tried the belkin fm transmitter unit with it &amp; it worked well when i set it on top of a portable radio , but was awful trying to use <b>in the car</b> which is somewhat of a disappointment .”</p> <p>“but the major problem i had was with the <b>software</b> .”</p> <p>“after a week i tried to load some more songs and delete a few but the <b>auto load</b> didn ’t do anything but turn on my player .”</p> <p>“2 . the scroll button is n ’t the best , as it sometimes can be <b>hard to select</b> .”</p> <p>“iriver has a better fm receiver built in , but the drawback to iriver products is they are <b>fimsy and poorly constructed</b> .”</p> <p>“i would imagine this is a problem with any camera of a <b>compact nature</b> .”</p> <p>“the <b>pictures are a little dark</b> sometimes .”</p> <p>“the <b>depth adjustment</b> was sloppy .”</p> <p>“the <b>instructions</b> that come with it do n ’t explain how to make things simple .”</p> <p>“my " fast forward " button works , but it <b>takes a little extra pressure</b> on it to make it go .”</p>
+	<p>“i did not conduct a rigorous test , but just took some identical shots in <b>identical lighting</b> with both cameras , and the canon won hands down .”</p> <p>“as a whole , the dvd player has a <b>sleek design and works fine</b> .”</p> <p>“i , as many others , have waited for many years for the <b>convergence of price</b> , features , size and ease of use to hit that happy center point .”</p> <p>“+ i had <b>no problem</b> using musicmatch software already on my computer to load songs and albums onto this unit”</p> <p>“apex is the best <b>cheap quality</b> brand for dvd players .”</p> <p>“i chose this one because from what i read , it was the <b>best deal for the money</b> .”</p> <p>“the <b>two-times optical zoom</b> operates smoothly and quietly , and lo and behold , a two-piece shutter-like cap automatically slides closed over the lens when you turn the camera off .”</p> <p>“this camera is perfect for the person who wants a compact camera that <b>produces excellent photos</b> in just about any situation .”</p> <p>“it was easy enough to remove the front plate , and there was only one way the <b>battery could be inserted</b> .”</p> <p>“i have been very impressed with my purchase of the sd500 i bought it at the beginning of the month as <b>the ultimate pocket camera</b> and have shot 300 images so far with it .”</p>

Table 14: Rationales (in bold) extracted by the zero-shot QUIP sentiment analysis model for the Customer Reviews (CR) dataset. We show ten random examples for each label on which the model made the correct prediction.