

SPIDER 2.0: CAN LANGUAGE MODELS RESOLVE REAL-WORLD ENTERPRISE TEXT-TO-SQL WORKFLOWS?

Anonymous authors

Paper under double-blind review


ABSTRACT

Real-world enterprise text-to-SQL workflows often involve complex cloud or local data across various database systems, multiple SQL queries in various dialects, and diverse operations from data transformation to analytics. We introduce Spider 2.0, an evaluation framework comprising 595 real-world text-to-SQL workflow problems derived from enterprise-level database use cases. The databases in Spider 2.0 are sourced from real data applications, often containing over 1,000 columns and stored in local or cloud database systems such as BigQuery and Snowflake. We show that solving problems in Spider 2.0 frequently requires understanding and searching through database metadata, dialect documentation, and even project-level codebases. This challenge calls for models to interact with complex SQL workflow environments, process extremely long contexts, perform intricate reasoning, and generate multiple SQL queries with diverse operations, often exceeding 100 lines, which goes far beyond traditional text-to-SQL challenges. Our evaluations indicate that based on o1-preview, our code agent framework successfully solves only 15.1% of the tasks, compared with 91.2% on Spider 1.0 and 73.0% on BIRD. Our results on Spider 2.0 show that while language models have demonstrated remarkable performance in code generation — especially in prior text-to-SQL benchmarks — they require significant improvement in order to achieve adequate performance for real-world enterprise usage. Progress on Spider 2.0 represents crucial steps towards developing intelligent, autonomous, code agents for real-world enterprise settings.

1 INTRODUCTION

Automated code generation can serve as a crucial bridge between humans and data, assisting individuals in achieving difficult or monotonous tasks using complex data. A significant portion of existing data is stored in relational databases, where SQL serves as an essential interface that facilitates human interaction with these data. In this context, semantic parsing or text-to-SQL (Dahl et al., 1994; Zelle; Zettlemoyer & Collins, 2005; Li & Jagadish, 2014; Zhong et al., 2017; Yu et al., 2018) is an important technology that assists data analysts in performing routine queries, orchestrating data workflows, and accomplishing advanced business intelligence, thereby significantly reducing repetitive human labor and alleviating the burden on programmers. Large language models (LLMs) have demonstrated excellent capabilities in generating code (Chen et al., 2021; Austin et al., 2021), particularly in transforming natural language questions into SQL queries. Notably, methods based on GPT-4 achieved execution accuracy of 91.2% and 73.0% on the classic benchmarks Spider 1.0 (Yu et al., 2018) and BIRD (Li et al., 2024b), respectively.

Although LLMs excel on these datasets, they often use non-industrial databases with few tables and columns, featuring simplistic SQL and questions that fall short of real-world complexity and overlook diverse SQL dialects. By contrast, real-world data are stored across a diverse array of database systems, each with its own unique SQL dialects, introducing a wide range of SQL syntax and functions. Additionally, these enterprise-level application databases are characterized by large-scale schemas with thousands of columns and complex nested structures. Moreover, real-world text-to-SQL workflows require the utilization of project codebases, external knowledge, and various contexts to construct intricate SQL queries across multiple steps, complete various operations, and



066 Figure 1: Spider 2.0 aims to evaluate LLMs on real-world enterprise-level text-to-SQL workflows. Solving each task requires understanding database metadata, consulting SQL dialect documentation, handling complex workflows, and performing intricate reasoning to generate diverse SQL queries.

069 build a comprehensive data engineering pipeline. This includes data wrangling to clean and organize the data for analysis, data transformation to restructure and enhance the data, and conducting data analytics to extract insights that inform decision making and drive strategic initiatives. All these complexities underscore the pressing need for a more realistic enterprise-level benchmark.

074 We present Spider 2.0, a benchmark that reflects real-world data workflows to facilitate the development of text-to-SQL models in enterprise applications, encompassing 595 real-world complex data wrangling, transformation, and analysis tasks. As illustrated in Fig. 1, the databases in Spider 2.0 are sourced from industrial applications (e.g. Google Analytics and Salesforce) and feature massive schema items (an average of 755 columns) with unique structures (e.g., nested columns in Fig. 13, multiple schema in Fig. 14), along with terabyte-scale data volumes. They encompass a variety of database systems, including local databases (e.g., SQLite and DuckDB) and cloud data warehouses (e.g., BigQuery and Snowflake). Complicated SQL dialects for these databases are curated from technical tutorials, community forums, and open-source projects. On average, each ground-truth SQL query contains 144 tokens and includes advanced functions (e.g., $ST_DISTANCE(x_1, x_2)$ measures the shortest distance between two points), exhibiting a level of complexity notably surpassing previous benchmarks. All tasks are based on project codebases along with documents and database interface to simulate real-world text-to-SQL writing scenarios.

086 Unlike previous datasets, Spider 2.0’s agentic task setting does not rely on pre-prepared inputs (question and database schema) or expected outputs (predicted SQL). Instead, it incorporates a real project codebase and a database interface. This complexity extends beyond merely predicting an SQL query; it involves navigating the project and dynamically interacting with complex databases through SQL queries and command-line scripts (in Python or Shell). The task objective is to perform intricate data transformations within the database or to extract analytical insights from the data. This task setting closely mirrors real-world enterprise SQL workflows, requiring the model to refer to the codebase and documentation, generate multiple SQL queries, and dynamically interact with the environment to complete complex tasks and derive the final result. To simplify performance comparisons with previous text-to-SQL methods and benchmarks, and to support faster development and evaluation, we also introduce Spider 2.0-lite, a self-contained dataset with preprocessed database schema and documentation. This setting omits the codebase and restricts output to SQL only, thus eliminating the need to predict final answers or transform the database. While Spider 2.0-lite is sourced from the same raw data as Spider 2.0, it is not easier than Spider 2.0 because Spider 2.0-lite models have access to less information (e.g., execution feedback). We present Spider 2.0-lite as a direct text-input-to-SQL-output challenge that is easier to work with using current advanced text-to-SQL parsers, and Spider 2.0 as a real-world data workflow challenge that involves interacting with diverse sources to perform data transformation and analyses.

103 Our evaluation on Spider 2.0 indicates significant room for improvement in deploying LLMs within real-world enterprise text-to-SQL workflows. The best o1-preview based code agent framework achieves a performance of only 15.1%, underscoring the significant deficiency in LLMs’ capability to serve as proficient SQL experts (Tab. 2). As for Spider 2.0-lite setting, even the most advanced text-to-SQL parser could successfully address only 9.3% of the questions, a stark contrast to the execution accuracy of 91.2% on Spider 1.0 and 73.0% on BIRD, thereby highlighting the substantial

challenges (§3.2). Our detailed analysis further identifies major obstacles in enterprise text-to-SQL, including accurately linking schemas from extremely large databases, correctly handling different SQL dialects, planning sequences of nested SQL queries to perform complex transformation and analytical tasks, and effectively leveraging external documentations and understanding project-level codebase. (§4.1 and §4.2). These challenges in Spider 2.0 represent crucial steps toward creating a benchmark that closely aligns with real-world scenarios. With Spider 2.0, we aim to enable the development of a new generation of intelligent autonomous agents capable of data engineering workflows in real-world enterprise settings.

2 BENCHMARK CONSTRUCTION

In this section, we introduce the task definition, general annotation pipeline, and dataset statistics for Spider 2.0 and Spider 2.0-lite. For concrete examples, refer to App.B.

2.1 TASK DEFINITION

Fig. 2 illustrates the task definition of both Spider 2.0 and Spider 2.0-lite settings.

Spider 2.0. Given a question Q , a database interface \mathcal{I} , and a codebase \mathcal{C} (with project context, configuration, and documentation, illustrated in Fig. 1), the task is to iteratively modify the code (SQL/Python) \mathcal{C} based on observations $O_k = \text{execute}(\mathcal{C}, \mathcal{I}, Q)$ until the final result \mathcal{A} (text/table/database) is obtained. In other words, we use the final observation O_k as an agent’s answer to the question, i.e., $\mathcal{A} = O_k$.

Spider 2.0-lite. In contrast to Spider 2.0, Spider 2.0-lite is formulated as a self-contained task. Given database schema \mathcal{D} , a natural language question Q , and auxiliary documentation \mathcal{E} as inputs, the text-to-SQL parser $f(\cdot)$ is required to output the corresponding SQL query $\mathcal{S} = f(Q, \mathcal{D}, \mathcal{E} \mid \theta)$, where θ is the parameters of the parser.




Figure 2: We offer two settings: traditional text-input-to-SQL-output Spider 2.0-lite, and agentic Spider 2.0.

2.2 ANNOTATION PIPELINE

Eight authors majoring in computer science, all highly proficient in SQL, carry out the data annotation process. The annotation pipelines consist of the following six steps:

1) Database and SQL collection. We collect various databases from cloud data warehouses, including BigQuery public data, Snowflake Marketplace data, and other platforms, to ensure that they meet specific criteria: each database must contain more than 200 columns or have a nested schema structure. After filtering, we select 149 BigQuery, 12 Snowflake, 30 SQLite, 40 DuckDB, 10 PostgreSQL, and 5 ClickHouse databases. From the corresponding tutorials and forums, we gather 1,021 complex SQL queries, as well as 157 data transformation projects sourced from Fivetran and DBT (see App.B.2). To meet our criteria, the SQL queries must contain more than 50 tokens (tokenized by whitespace; for reference, the average token count of BIRD (Li et al., 2024b) is 30.9). Furthermore, queries must originate from real projects or tutorials, not from synthetic examples or corner cases. Ultimately, we retain 528 high-quality SQL queries and 67 DBT projects.

2) SQL rewrite to prevent data leakage. To avoid contamination and ensure the credibility of Spider 2.0’s evaluation, annotators are required to rewrite each SQL and verify that they are bug-free. The rewrites are performed at two levels of increasing complexity: the surface and semantic levels, as detailed in Tab. 1. 84.2% of the examples underwent surface-level rewriting, while 42% experienced semantic-level rewriting. Annotators must ensure that the rewritten SQL executes successfully, completes in an acceptable time, and returns non-empty results. 85.98% of these SQL queries utilize advanced functions in various dialects (App.B.7.1), while 11.26% require additional DBT tools, posing challenges due to the need to integrate the project context.

3) Codebase and context setup. For each complex SQL query in Spider 2.0-lite, we collect the external reference documents necessary to complete the task. Since the tasks span multiple database types, we gather documentation on SQL dialects and external functions, as shown in Tab. 17. Ad-

Table 1: The rewrite categories are as follows: “Surface” rewrites adjust the parameters and the answer format, while “Semantic” rewrites expand the question’s meaning. Each table reference in *Example* column represents the details of rewrite examples for the corresponding type.

Rewrite	Categories	Example
Surface	Answer format	Tab. 12, replace the one channel with the channel ranking by sessions.
	Condition parameters	Tab. 13, more complex filter condition: citibike is faster than a taxi.
	Advanced calculation	Tab. 14, calculate originality score based on selected publications.
Semantic	Advanced requirements	Tab. 15, change <i>page view order</i> to <i>page conversion rate</i> .
	Merge related SQLs	Tab. 16, merge geography-related and weather-related queries.
	SQL codebase files	App.B.2, change SQL and YML files in the original project.

ditionally, for Spider 2.0, we preserve the original codebase of the SQL-related project. For Spider 2.0, besides collecting reference documents, annotators also gather resources such as codebases, database interfaces to establish the context for each task (Fig. 1). Since some complex data transformation intentions may not be fully captured by a natural language question, annotators provide additional context, including data model descriptions (App.B.2) or predefined answer files (App.B.5), to maintain clarity while addressing potential ambiguities.

4) Natural language task instructions annotation. Annotators are required to write questions based on the SQLs and context gathered in Step 3, crafting two versions for Spider 2.0 and Spider 2.0-lite. The instructions are designed to balance both *naturalness* and *unambiguity*. Due to the differences between Spider 2.0 and Spider 2.0-lite, Spider 2.0 demonstrates greater naturalness in its questions because it provides contexts and predefined files to guide the answers, while Spider 2.0-lite prioritizes unambiguity, ensuring clearer and more straightforward specifications (see App.B.6 for differences). Annotators manually write the instructions, making them natural by *avoiding blunt descriptions, removing ambiguity* in the expected results, and ensuring that all *SQL conditions are clearly mentioned*. Also, the DBT-project tasks (see Fig. 1 and App.B.2), which are realistic data transformation coding scenarios, are exclusively used in Spider 2.0. Annotators craft task instructions based on the provided context. After the initial annotation, they verify the semantic equivalence between the SQL queries and instructions, paraphrasing for clarity with the help of LLMs.

5) Execution-based focused evaluation. In this step, annotators are required to obtain results from the databases programmatically and write evaluation scripts (details in App.A). The evaluation scripts can process the results in the form of strings, tables, and database files. It is important to note that in table-based evaluations, predicted results may include numerous columns, which might not exactly match the gold standard answers. This discrepancy often arises because some questions do not specify the columns that should be returned. To mitigate this, the evaluation scripts are specifically focused on the essential components of the answers, ignoring non-essential columns and emphasizing the core elements outlined in the instructions. This method facilitates targeted assessments of key columns for each task, thus significantly reducing the occurrence of false negatives. For Spider 2.0-lite, the setting requires that the output must be SQL, so the evaluation will compare the execution results of the SQL queries using the table-based assessment method.

6) Quality control. To ensure the quality of our benchmark, each instruction, the gold SQL query, and evaluation script are reviewed by at least three annotators. We require the annotators to repeatedly review steps 3), 4), and 5) to ensure the correctness, naturalness, and unambiguity of the annotations. Consequently, 45% of the examples have errors identified by the first validators. After discussions and corrections, following the second round of iteration with the second validators, only 5% of the examples contain errors. Then we correct all errors and refine all annotations, and ultimately, all examples are deemed fully annotated. Additionally, we perform a “red team” assessment of our automatic evaluation by providing a set of false results to determine if they would be correctly classified as false, along with various correctly formatted results to verify their classification as true.

2.3 DATASET STATISTICS

We present a detailed statistical analysis of the features of Spider 2.0 and Spider 2.0-lite, comparing them with multiple previous datasets in Tab. 2, our datasets demonstrate strong complexity and realism in aspects such as databases, SQLs, and task scenarios.

Diverse database systems and SQL dialects. As shown in Fig. 3 and Tab. 3, our benchmarks feature a diverse array of database systems, including cloud data warehouses like *BigQuery* and

Table 2: Statistical comparison among Spider 2.0, Spider 2.0-lite, and other text-to-SQL benchmarks. Tok. and Func. refer to tokens and functions, respectively. * denotes the statistics from dev set due to the inaccessibility of test set. For more statistics, refer to App.B.8.

Dataset	# Test Examples	# Test DB	# Col /DB	# Tok. /SQL	# Func. /SQL	External Knowledge	SQL Dialect	Project Level
WikiSQL (Zhong et al., 2017)	15,878	5,230	6.3	12.2	0.0	✗	✗	✗
Spider 1.0 (Yu et al., 2018)	2,147	40	27.1	18.5	0.0*	✗	✗	✗
KaggleDBQA (Lee et al., 2021)	272	8	23.4	13.8	0.0	✓	✗	✗
SEDE (Hazoom et al., 2021)	857	1	212.0	46.9	1.4	✗	✗	✗
BIRD (Li et al., 2024b)	1,789	15	54.2	30.9	0.4*	✓	✗	✗
Spider 2.0-lite	528	191	755.4	144.5	6.5	✓	✓	✗
Spider 2.0	595	246	710.1	148.3	6.8	✓	✓	✓

Snowflake, locally hosted databases such as *Postgres* and *ClickHouse*, and lightweight systems like *SQLite* and *DuckDB*. This diversity distinguishes our benchmarks from previous work by encompassing various SQL dialects. Notably, 85.98% of the examples require the use of specialized functions from these dialects, with an average of 6.8 special functions utilized in each ground-truth SQL.

Real and complex database schema. As shown in Tab. 2, the databases in Spider 2.0 are equipped with large-scale schemas comprising extensive tables and columns, effectively mirroring real-world enterprise environments. As shown in Tab. 3, these databases are characterized by complex schema structures (e.g., multiple and nested schemas, partitioned tables; see Fig. 13 and Fig. 14), and dynamic tables that are updated daily. Additionally, the data encompasses a broad spectrum of complex types (Fig. 18), extensive volumes, and diverse scopes (Fig. 17), rendering it more diverse than previous datasets.

Challenging tasks across the data engineering pipeline. The examples in our benchmarks are collected from real tutorials and forums, covering a wide range of issues encountered in data pipelines, including data wrangling, data transformation, and data analysis (see App.B.1 for examples). The difficulty of these questions significantly exceeds that of previous SQL-related benchmarks, as the SQL queries in Spider 2.0 contain significantly more columns, tokens, and functions per query than those in prior work (see Tab. 2 and Fig. 20 for examples).

Real projects scenarios with codebases and documents. As demonstrated in Tab. 2 and 3, tasks in both datasets require access to documentation, like external knowledge (App.B.4) and SQL dialect (App.B.7), necessitating a deep understanding of these resources. Compared to other prior works, for each task in Spider 2.0, we provide a codebase context to simulate a real workflow (App.B.5). More notably, some tasks introduce innovations such as project-level data transformation workflows built on DBT (App.B.2), a widely used tool for managing data transformations and analytics engineering. Successfully addressing these tasks requires navigating complex project codebases and databases, comprehending documentation, processing intricate contexts, and generating diverse queries through multi-step execution and reasoning.

3 EXPERIMENTS

3.1 EXPERIMENTAL SETUP

Evaluation metrics. For Spider 2.0, we use the **Success Rate (SR)** metric, which measures the proportion of task instances successfully completed. For Spider 2.0-lite, the output for each task must be an SQL, we use the widely used metric **Execution Accuracy (EX)** (Yu et al., 2018; Li et al., 2024b). We employ the execution-based *focused* evaluation (App.A) to determine the success




Figure 3: Data distribution on different database systems.

Table 3: Statistics of Spider 2.0 task features.

Statistics	Number (% of Total)
Total Levels (#tokens)	595 (100%)
- Easy (#tokens < 80)	166 (27.90%)
- Medium (80 ≤ #tokens < 160)	259 (43.53%)
- Hard (#tokens ≥ 160)	170 (28.57%)
- With Cloud Database	383 (64.36%)
- With Local Database	212 (35.63%)
- With Project-level (DBT)	67 (11.26%)
- With Documentation	57 (9.58%)
- With Functions	454 (85.98%)
- With Partition Tables	44 (7.39%)
- With Multiple Schemas	102 (27.26%)
- With Nested Schemas	103 (13.44%)
- With Dynamic Database	54 (9.94%)
- With String/Number Answer	150 (25.21%)
- With Table Answer	378 (63.53%)
- With Database Answer	67 (11.26%)

of each result for Spider 2.0 and assess the accuracy of SQL execution results for Spider 2.0-lite. The evaluation scripts are designed to accept output in the form of strings, tables, or database. For each example, an evaluation script is run for each example, producing a score of either 0 or 1. It is worth noting that in table-based evaluations, predicted results may contain numerous columns, leading to results that are not exactly the same as the gold answer. This occurs because, for some examples, questions do not explicitly specify which columns to return. The evaluation scripts are specifically focused on the essential components of the answers, disregarding irrelevant columns and concentrating on the core elements specified in the instructions.

Difficulty level. We tokenize the gold SQL queries based on whitespace and classify their difficulty according to the number of tokens: < 80 tokens as Easy, $80 - 159$ as Medium, and ≥ 160 as Hard¹.

LLMs. We experiment with state-of-the-art LLMs, including open-source representatives such as DeepseekCoder-V2.5 (Zhu et al., 2024), Qwen2.5-72B-Instruct (Team, 2024) and Llama-3.1-405B (Meta AI, 2024), and closed-source ones including Gemini-Pro-1.5 (Reid et al., 2024), Claude-3.5-Sonnet (Anthropic, 2024) and GPT (OpenAI, 2023) families (GPT-4o, GPT-4 and o1-preview). Follow (Yang et al., 2024a; Chen et al., 2024), we use a temperature of 0.0 and truncate from the beginning of the input if still exceeding the max tokens limit required by the models.

Code agent frameworks for Spider 2.0. We utilize several state-of-the-art frameworks, which have demonstrated excellent performance on other benchmarks. These include Reflexion (Shinn et al., 2023), CodeR (Chen et al., 2024), AutoEval (Pan et al., 2024). Inspired by React (Yao et al., 2022) and Intercode (Yang et al., 2023), we develop an agent framework called Spider-Agent, which is primarily focused on database-related coding tasks and projects. The framework allows for multi-turn interactions with the database via command-line interfaces until the final answer is obtained. The implementation details of Spider-Agent are shown in App.C.1.

Text-to-SQL methods for Spider 2.0-lite. We evaluate several state-of-the-art and widely recognized text-to-SQL methods on Spider 2.0-lite, including approaches based on prompting LLMs such as DIN-SQL (Pourreza & Rafiei, 2024), DAIL-SQL (Gao et al., 2024) and CHESS (Talei et al., 2024), alongside SFT CodeS (Li et al., 2024a), which fine-tuned open-source models on extensive text-to-SQL corpora. DAIL-SQL and CHESS achieve the best performance among all accessible methods on the Spider 1.0 and BIRD benchmark, respectively. During implementation, we optimize the prompt organizations across all methods to better align with Spider 2.0-lite, incorporating sampled cell values, external knowledge, and SQL dialect specifications (see Fig. 23).

3.2 EVALUATION RESULTS

Table 4: Success rate (SR) of different frameworks and models on Spider 2.0, grouped by difficulty level. The costs under different settings are shown in Tab.19.

Framework	Model	SR (\uparrow)			Overall
		Easy	Medium	Hard	
AutoEval	GPT-4o	12.05%	6.95%	1.18%	6.72%
CodeR	GPT-4o	13.85%	7.72%	1.76%	7.73%
Reflexion	GPT-4o	16.87%	7.72%	1.18%	8.40%
Spider-Agent	o1-Preview	25.30%	15.44%	4.71%	15.12%
	Claude-3.5-Sonnet	24.09%	8.10%	2.94%	11.09%
	GPT-4	22.89%	8.49%	2.35%	10.58%
	GPT-4o	18.07%	9.65%	3.53%	10.25%
	Qwen2.5-72B	20.48%	8.11%	2.35%	9.91%
	Gemini-Pro-1.5	10.84%	7.33%	1.17%	6.55%
DeepSeek-V2.5	12.65%	5.02%	1.76%	6.21%	
Llama-3.1-405B	10.24%	3.86%	0.59%	5.42%	

Existing LLMs are still far from being expert on real-world text-to-SQL workflow tasks. The o1-preview model demonstrates the best performance, with a maximum success rate of 15.12%,

¹While there are various ways to measure difficulty, we use SQL length here as the most common and significant metric for experimental reference.

Table 5: Execution Accuracy (EX) for baseline methods on three text-to-SQL datasets: Spider 1.0, BIRD, and Spider 2.0-lite.

Method	EX (↑)					
	Spider 1.0	BIRD	Spider 2.0-lite			Overall
			Easy	Medium	Hard	
DIN-SQL + GPT-4o	85.3%	55.9%	16.45%	5.64%	3.29%	7.32%
DAIL-SQL + GPT-4o	86.6%	57.4%	20.73%	6.16%	4.40%	9.29%
CHESS + GPT-4o	87.2%	66.7%	18.10%	5.88%	4.75%	8.36%
SFT CodeS-15B	85.4%	59.3%	6.02%	0.00%	1.12%	2.00%

leaving ample room for improvement. o1-preview performs similarly to Claude-3.5-connect and GPT-4 on *Easy* cases, but significantly better on *Medium* cases, demonstrating its strong reasoning capabilities. This discrepancy highlights the broad range of difficulties in Spider 2.0 and underscores its complexity. Other advanced LLMs, like GPT-4 and Claude-3.5-Sonnet, performed worse. Surprisingly, the open-source LLM Qwen-2.5-72B showed excellent performance at 9.91%, comparable to GPT-4o, and far better than other open-source LLMs.

Existing code agent frameworks struggle with solving database-related coding tasks. Tab. 4 shows that despite using the powerful GPT-4o, advanced code agent frameworks like CodeR achieve only a 7.73% success rate, while on SWE-Bench (Jimenez et al., 2023), the success rate is 28.33%. Currently, no code agents are specifically designed for database-related tasks. The challenge is that they must not only explore the codebase and documentation, but also navigate complex databases and generate SQL queries that are far more intricate than typical code. This demands a high level of code grounding capability. Our proposed baseline Spider-Agent, with actions tailored for Spider 2.0 tasks, currently demonstrates the highest performance. It provides a crucial baseline for Spider 2.0, facilitating the evaluation of various LLMs, underscoring the potential for significant advancements and inspiring methodology enhancements for future research.

Current LLM-based methods exhibit limited capability in addressing Spider 2.0-lite. Tab. 5 illustrates that Spider 2.0-lite presents a significant challenge. The highest performing method, DAIL-SQL + GPT-4o, achieves an EX of only 9.29%, which is markedly lower compared to its score of 86.6% on Spider 1.0 and 57.4% on BIRD datasets. With efficiently filtering the minimal sufficient schema, CHESS + GPT-4o is able to tackle more instances with *Hard* level, which are often overwhelmed by the extensive candidate schemas. Despite being extensively fine-tuned, SFT CodeS-15B is far from solving Spider 2.0-lite, with an EX score of only 2.00%, which further reveals the significant complexity gap between Spider 2.0-lite and the current text-to-SQL corpus.

Sampling more candidate SQL queries achieves a notable improvement on Spider 2.0-lite. We employ the $pass@n$ metric (Kulal et al., 2019), where n predicted SQL queries are generated per example, with the hope of any one in them is correct. As shown in Fig. 4, we use DAIL-SQL + GPT-4o, with the temperature of 1.0 (Chen et al., 2021) to generate multiple SQLs on Spider 2.0-lite. The results show that the improvement in accuracy is noticeable as n increases, but later becomes marginal. This highlights the inherent challenges of Spider 2.0, along with the rigorous and high-quality task annotations provided.




Figure 4: $pass@n$ results.

4 ANALYSIS

4.1 ANALYSIS OF DIFFERENT TASK TYPES

LLM-agent frameworks struggle to address project-level tasks.

As shown in Tab. 6, the LM agent’s performance on DBT-based project-level tasks is poor, solving only 10.45% of tasks with just 7 examples correct. This underscores the challenges in these tasks, which can be attributed to: (1) Data transformation projects often require *multiple SQL queries* to complete various models, necessitating a comprehensive understanding of the project. (2) These tasks involve *complex context usage*, demanding strong repository exploratory capabilities from the

Table 6: Performance on DBT Project.

Task Subset	% of Total	SR (↑)
w/ DBT Project	11.26%	10.45%
w/o DBT Project	88.74%	15.81%

models. (3) Data is stored in databases, requiring the agent to transform data while exploring existing data, alongside SQL coding. Fig. 27 illustrates the action process of o1-preview successfully solving a task defined in App.B.2, while Fig. 28 is a failure case due to the failure to explore the information in the “mrr.md” file to solve a monthly recurring revenue classification.

The performance drops when external documents are required.

From Tab. 7, we observe that when tasks involve external documents, the model performs poorly, correctly answering only 7 examples out of full dataset that accounts for just 9.58%. Through error analysis, we find that the model is not incapable of grounding complex documents information. These models typically have the correct problem-solving strategies and effectively explore the database, but fails at the most crucial step: grounding the complex requirements from the documents into SQLs. As the document shown in Fig. 15, the gold SQL is shown in Tab. 15. The failure case shows that the model cannot combine complex document with schema information and convert it into SQL query (Fig. 29).

Table 7: Performance of the model on external document tasks in non-dbt projects.

Task Subset	% of Total	SR (↑)
w/ External Doc	9.58%	12.28%
w/o External Doc	79.16%	16.14%

LLM-agent frameworks struggle interpreting databases with nested schema.

As shown in Tab. 8, the model often performs poorly when handling columns with nested types. Nested columns are a common scenario in industrial-grade databases (see Fig. 13), where data is stored in array, dict formats within a single column. This poses significant challenges for LLMs in understanding the schema. As shown in Fig. 30, LLMs encounter schema linking errors due to an incomplete understanding of the information contained within nested fields. Most databases with nested types face the issue that models find it difficult to fully grasp the function of each nested column’s internal information, while humans can comprehend the database schema through multi-step reasoning and iterative understanding.

Table 8: Model performance on databases with nested columns in non-dbt projects.

Task Subset	% of Total	SR (↑)
w/ Nested Column	17.31%	11.18%
w/o Nested Columns	71.43%	20.13%

The performance declines as the schema size increases. In Fig. 5, we explore the impact of the total number of columns in the database on performance. The experimental results align with intuition in Fig. 5. As the number of columns or required tables increases beyond a certain scale, the performance drops sharply, approaching almost 1.0% successful rate. This indicates that current LLMs still face challenges when handling extremely long schemas. The model’s ability to understand long schemas remains a key factor limiting its performance.




Figure 5: The effect of different column numbers (or input DB size) on performances.

4.2 ERROR ANALYSIS OF SQL GENERATION

We conduct a detailed analysis of the errors encountered by both code agent frameworks and text-to-SQL parsing methods, as illustrated in Fig. 6. Representative errors along with their statistics and causal analysis are as follows.

Erroneous data analysis (35.5%). Compare to the previous benchmarks, Spider 2.0 and Spider 2.0-lite exhibit significantly complex data analysis demands that challenge the models’ capabilities: 1) Dialect function usage (10.3%). This includes processing temporal (e.g., DATE_TRUNC) or geographic data (e.g., ST_DISTANCE). These functions require a nuanced understanding, which the models often fail to exhibit. 2) Advanced data calculation (7.5%). Model struggle with tasks like grouping samples to analyze trends within groups (using NTILE), or applying formulas for statistical values (e.g., CORR for Pearson correlation coefficients; STDDEV for standard deviation). 3) Intricate query planning (17.7%). Gold SQLs typically involve multiple nested queries, intermediate result processing through common table expressions (CTEs), or merging results from various sub-queries via set oper-




Figure 6: Statistics of errors. For detailed descriptions and examples of each error category, see App.C.3.

ations. However, models often inadequately handle these complexities. Refer to Fig. 7 for case studies on erroneous data processing.

Wrong schema linking (27.6%). This category includes errors with wrong tables and columns. For column linking errors (16.6%), the average number of columns per database in Spider 2.0-lite far exceeds those in other benchmarks (over 755 compared to approximately 54 in BIRD), making accurate column linking extremely challenging. Regarding table linking (10.1%), although examples from BigQuery support advanced syntax features like (`TABLE_SUFFIX`) and wildcard expressions, the models show limited flexibility in leveraging these features, even in few-shot setting.

JOIN errors (8.3%). While foreign keys represent known schema relationships essential for valid SQL JOIN operations, databases in BigQuery often lack explicit foreign key. This omission forces models to infer potential keys based on column names and descriptions, leading to errors.

Table 9: EX for baseline methods on Spider 2.0-lite under oracle setting. To seek the highest possible performance, we also employ the latest o1-preview as the base LLM.

Method	EX (↑)		
	w/o both	w.Ref.Plan	w.Oracle Func
DAIL-SQL + GPT-4o	9.29%	13.56%	9.90%
DAIL-SQL + o1-preview	14.74%	18.87%	15.59%

Table 10: EX for DAIL-SQL on Spider 2.0-lite under few-shot setting with manually selected demonstrations.

Method	EX (↑)		
	0-shot	3-shot	9-shot
DAIL-SQL + GPT-4o	9.29%	9.40%	9.66%




FIGURE 7: Case study of two representative incorrect SQL predictions due to erroneous data analysis. (a): An example of **incorrect data calculation**, where quantiles were incorrectly divided based on the number of trips, rather than on the *trip duration* as required. (b): An example of **incorrect planning**, where the predicted SQL incorrectly sorted data by the number of users, rather than by the required *retention ratio*. The prerequisite for achieving this is to properly plan a sequence of CTEs. Additional examples of error cases across all categories are available in Fig. 24 and Fig. 25.

4.3 ANALYSIS OF DIFFERENT EXPERIMENTAL SETTINGS

Reference plan can significantly improve SQL generation performance. Annotators are required to provide detailed annotations for task instructions. While the original instructions are brief and conversational, the reference plan offers a comprehensive, step-by-step explanation of how to write each SQL. This approach decouples the exploration of the database from the process of generating text-to-SQL. An example is provided in App.B.1. As shown in Tab. 9, incorporating a reference plan resulted in an approximate 4% improvement in the EX of DAIL-SQL. By harnessing the latest

o1-preview, which excels at code generation, 18.4% of the instances can be correctly solved. This suggests that some challenging instances can't be solved by directly generating the final SQL but benefit from a step-by-step approach using multiple CTE clauses.

Providing oracle functions leads to a slight performance improvement. Considering that Spider 2.0 and Spider 2.0-lite involve SQL dialects from various database systems, we provide syntax and function documentation for each system to prevent the methods from suffering due to lack of syntax knowledge. For each example, we manually include the relevant function documentation that may be required, eliminating the need for a retrieval method and ensuring that the necessary syntax knowledge is readily accessible. As shown in Tab. 9, providing oracle SQL function documentation results in only a slight improvement in model performance. This suggests that, to a certain extent, models are capable of selecting appropriate functions and understanding their basic usage and syntax. However, the critical challenge lies in accurately utilizing these functions to reflect user intentions, as illustrated in Fig. 7(a).

Few-shot prompting has little impact on performance. Spider 2.0-lite is not divided into train and dev sets, we manually select 9 representative examples with distinct characteristics (encompassing multiple CTE or nested queries, or requiring intricate data processing) to serve as few-shot examples. Unexpectedly, few-shot in-context learning shows only marginal improvements in performance (see Tab. 10). This may be due to the gap between the simplistic text-to-SQL pre-training data used with LLMs and the complexity of the few-shot examples. Additionally, extensive schema prompts may hinder the model's ability to effectively assimilate information in the few-shot examples.

5 RELATED WORK

Code generation and text-to-SQL benchmark. As model capabilities advance, code generation benchmarks have become more complex and generalized. Many benchmarks (e.g., SQL-Spider (Yu et al., 2018), Bash-NL2Bash (Lin et al., 2018), Python-HumanEval (Chen et al., 2021)) treat code generation as seq2seq tasks. DS-1000 (Lai et al., 2023) and Arcade (Yin et al., 2023) define code generation tasks for data science. MAgentBench (Huang et al., 2023) and Intercode (Yang et al., 2024b) focus on interactive environments, while SWE-Bench (Jimenez et al., 2023) emphasizes repository-level coding tasks. Particularly for the text-to-SQL task, WikiSQL (Zhong et al., 2017) is the first large-scale dataset for evaluating text-to-SQL methods. KaggleDBQA (Lee et al., 2021) includes database documentation, while SEDE (Hazoom et al., 2021) and MIMICSQL (Wang et al., 2020) feature more sophisticated SQL queries within specific domains. BIRD (Li et al., 2024b) focuses on SQL execution efficiency and requires an understanding of external knowledge. However, existing text-to-SQL benchmarks primarily target lightweight local databases, much smaller in schema scale and data volume than cluster-hosted industrial databases, and fail to capture the *agentic* nature of SQL programming using various dialects in real scenarios. Spider 2.0 bridges the gap between research and enterprise-level industrial text-to-SQL workflows.

Code agent framework and text-to-SQL methods. The intersection of generative code models and interactive problem-solving has spurred significant advancements in both agent-based frameworks and text-to-SQL methodologies. Recent efforts aim to enhance the reasoning capabilities of language models, as evidenced by a surge in agent methods designed for code generation tasks (Yao et al., 2022; Zhang et al., 2022; Chen et al., 2023; Wang et al., 2023b; Shinn et al., 2024; Zhang et al., 2024; Xia et al., 2024). Several works have designed special actions to standardize agent operations (Wang et al., 2024; Yang et al., 2024a). For methods specifically designed for text-to-SQL, several fine-tuning methods (Li et al., 2024a) and LLM-prompting methods (Dong et al., 2023; Wang et al., 2023a; Zhang et al., 2023; Talaei et al., 2024; Pourreza & Rafiei, 2024; Gao et al., 2024) have achieved strong performance on previous benchmarks. We propose Spider-Agent, a code agent framework specifically designed for database-related tasks, showcasing strong performance in this domain. For Spider 2.0-lite, we also adapt several text-to-SQL methods to suit our benchmark.

6 CONCLUSION

We propose Spider 2.0, a benchmark for real-world enterprise-level text-to-SQL workflow tasks. It encompasses diverse database systems with various SQL dialects, large and complex database schemas, and challenging tasks across the data engineering pipeline, all set within real project scenarios including codebases and documentation. Despite being the most advanced LLMs (o1-preview), they still perform poorly on Spider 2.0, achieving a success rate of only 15.1%, which underscores its status as a highly challenging benchmark. Spider 2.0 presents a novel challenge for text-to-SQL research, providing a direction towards more realistic and intelligent solutions.

540 CODE OF ETHICS AND ETHICS STATEMENT

541
542 In the process of collecting databases and SQL queries for Spider 2.0, we ensure that all sources
543 come from public data, used solely for academic research and not for commercial purposes, in full
544 compliance with the copyright rights granted by the sources. We guarantee that none of the databases
545 contain harmful information to society, such as racial discrimination, violence, or any private data.
546 Our work aims to contribute to the welfare of society and humanity, and any researcher is free to use
547 our dataset for research purposes. All the data and experiments presented in our paper adhere to the
548 highest standards of scientific excellence, ensuring the authenticity and accuracy of the data.

549 REPRODUCIBILITY

550 Our datasets and annotation process are introduced in §2.2, and the experimental settings are de-
551 scribed in §3.1. Specific implementation details can be found in App.C.1 and App.C.2. To facilitate
552 the reproduction of our experiments, the code is provided in <https://anonymous.4open.science/r/Spider2-F78F>.

556 REFERENCES

- 557
558
559 Anthropic. The claude 3 model family: Opus, sonnet, haiku. [https://www-](https://www-cdn.anthropic.com/de8ba9b01c9ab7cbabf5c33b80b7bbc618857627/Model_Card_Claude_3.pdf)
560 [cdn.anthropic.com/de8ba9b01c9ab7cbabf5c33b80b7bbc618857627/Model_Card_Claude_3.pdf](https://www-cdn.anthropic.com/de8ba9b01c9ab7cbabf5c33b80b7bbc618857627/Model_Card_Claude_3.pdf),
561 2024.
- 562 Jacob Austin, Augustus Odena, Maxwell Nye, Maarten Bosma, Henryk Michalewski, David Dohan,
563 Ellen Jiang, Carrie Cai, Michael Terry, Quoc Le, et al. Program synthesis with large language
564 models. *arXiv preprint arXiv:2108.07732*, 2021.
- 565 Dong Chen, Shaoxin Lin, Muhan Zeng, Daoguang Zan, Jian-Gang Wang, Anton Cheshkov, Jun
566 Sun, Hao Yu, Guoliang Dong, Artem Aliev, et al. Coder: Issue resolving with multi-agent and
567 task graphs. *arXiv preprint arXiv:2406.01304*, 2024.
- 568 Mark Chen, Jerry Tworek, Heewoo Jun, Qiming Yuan, Henrique Ponde De Oliveira Pinto, Jared
569 Kaplan, Harri Edwards, Yuri Burda, Nicholas Joseph, Greg Brockman, et al. Evaluating large
570 language models trained on code. *arXiv preprint arXiv:2107.03374*, 2021.
- 571 Xinyun Chen, Maxwell Lin, Nathanael Schaerli, and Denny Zhou. Teaching large language models
572 to self-debug. In *The 61st Annual Meeting Of The Association For Computational Linguistics*,
573 2023.
- 574 Deborah A Dahl, Madeleine Bates, Michael K Brown, William M Fisher, Kate Hunicke-Smith,
575 David S Pallett, Christine Pao, Alexander Rudnicky, and Elizabeth Shriberg. Expanding the scope
576 of the atis task: The atis-3 corpus. In *Human Language Technology: Proceedings of a Workshop*
577 *held at Plainsboro, New Jersey, March 8-11, 1994*, 1994.
- 578 Xuemei Dong, Chao Zhang, Yuhang Ge, Yuren Mao, Yunjun Gao, Jinshu Lin, Dongfang Lou, et al.
579 C3: Zero-shot text-to-sql with chatgpt. *arXiv preprint arXiv:2307.07306*, 2023.
- 580 Dawei Gao, Haibin Wang, Yaliang Li, Xiuyu Sun, Yichen Qian, Bolin Ding, and Jingren Zhou.
581 Text-to-sql empowered by large language models: A benchmark evaluation. *Proceedings of the*
582 *VLDB Endowment*, 17(5):1132–1145, 2024.
- 583 Moshe Hazoom, Vibhor Malik, and Ben Bogin. Text-to-sql in the wild: A naturally-occurring
584 dataset based on stack exchange data. In *Proceedings of the 1st Workshop on Natural Language*
585 *Processing for Programming (NLP4Prog 2021)*, pp. 77–87, 2021.
- 586 Qian Huang, Jian Vora, Percy Liang, and Jure Leskovec. Benchmarking large language models as
587 ai research agents. *arXiv preprint arXiv:2310.03302*, 2023.
- 588 Carlos E Jimenez, John Yang, Alexander Wettig, Shunyu Yao, Kexin Pei, Ofir Press, and Karthik R
589 Narasimhan. Swe-bench: Can language models resolve real-world github issues? In *The Twelfth*
590 *International Conference on Learning Representations*, 2023.

- 594 Sumith Kulal, Panupong Pasupat, Kartik Chandra, Mina Lee, Oded Padon, Alex Aiken, and Percy S
595 Liang. Spoc: Search-based pseudocode to code. *Advances in Neural Information Processing*
596 *Systems*, 32, 2019.
- 597
- 598 Yuhang Lai, Chengxi Li, Yiming Wang, Tianyi Zhang, Ruiqi Zhong, Luke Zettlemoyer, Wen-tau
599 Yih, Daniel Fried, Sida Wang, and Tao Yu. Ds-1000: A natural and reliable benchmark for data
600 science code generation. In *International Conference on Machine Learning*, pp. 18319–18345.
601 PMLR, 2023.
- 602 Chia-Hsuan Lee, Oleksandr Polozov, and Matthew Richardson. Kaggledbqa: Realistic evaluation
603 of text-to-sql parsers. In *Proceedings of the 59th Annual Meeting of the Association for Compu-*
604 *tational Linguistics and the 11th International Joint Conference on Natural Language Processing*
605 *(Volume 1: Long Papers)*, pp. 2261–2273, 2021.
- 606
- 607 Fei Li and HV Jagadish. Constructing an interactive natural language interface for relational
608 databases. *Proceedings of the VLDB Endowment*, 8(1), 2014.
- 609 Haoyang Li, Jing Zhang, Hanbing Liu, Ju Fan, Xiaokang Zhang, Jun Zhu, Renjie Wei, Hongyan
610 Pan, Cuiping Li, and Hong Chen. Codes: Towards building open-source language models for
611 text-to-sql. *Proceedings of the ACM on Management of Data*, 2(3):1–28, 2024a.
- 612
- 613 Jinyang Li, Binyuan Hui, Ge Qu, Jiayi Yang, Binhua Li, Bowen Li, Bailin Wang, Bowen Qin,
614 Ruiying Geng, Nan Huo, et al. Can llm already serve as a database interface? a big bench for
615 large-scale database grounded text-to-sqls. *Advances in Neural Information Processing Systems*,
616 36, 2024b.
- 617 Xi Victoria Lin, Chenglong Wang, Luke Zettlemoyer, and Michael D Ernst. Nl2bash: A corpus and
618 semantic parser for natural language interface to the linux operating system. In *Proceedings of the*
619 *Eleventh International Conference on Language Resources and Evaluation (LREC 2018)*, 2018.
- 620
- 621 Meta AI. Introducing meta Llama 3: The most capable openly available LLM to date, April 2024.
622 URL <https://ai.meta.com/blog/meta-llama-3/>. Accessed: 2024-04-18.
- 623
- 624 R OpenAI. Gpt-4 technical report. arxiv 2303.08774. *View in Article*, 2:13, 2023.
- 625
- 626 Jiayi Pan, Yichi Zhang, Nicholas Tomlin, Yifei Zhou, Sergey Levine, and Alane Suhr. Autonomous
627 evaluation and refinement of digital agents. In *First Conference on Language Modeling*, 2024.
- 628
- 629 Mohammadreza Pourreza and Davood Rafiei. Din-sql: Decomposed in-context learning of text-to-
630 sql with self-correction. *Advances in Neural Information Processing Systems*, 36, 2024.
- 631
- 632 Machel Reid, Nikolay Savinov, Denis Teplyashin, Dmitry Lepikhin, Timothy Lillicrap, Jean-
633 baptiste Alayrac, Radu Soricut, Angeliki Lazaridou, Orhan Firat, Julian Schrittwieser, et al. Gem-
634 ini 1.5: Unlocking multimodal understanding across millions of tokens of context. *arXiv preprint*
635 *arXiv:2403.05530*, 2024.
- 636
- 637 Noah Shinn, Federico Cassano, Ashwin Gopinath, Karthik R Narasimhan, and Shunyu Yao. Reflexion:
638 language agents with verbal reinforcement learning. In *Thirty-seventh Conference on Neural*
639 *Information Processing Systems*, 2023.
- 640
- 641 Noah Shinn, Federico Cassano, Ashwin Gopinath, Karthik Narasimhan, and Shunyu Yao. Reflexion:
642 Language agents with verbal reinforcement learning. *Advances in Neural Information Processing*
643 *Systems*, 36, 2024.
- 644
- 645 Shayan Talaie, Mohammadreza Pourreza, Yu-Chen Chang, Azalia Mirhoseini, and Amin Saberi.
646 Chess: Contextual harnessing for efficient sql synthesis. *arXiv preprint arXiv:2405.16755*, 2024.
- 647
- 648 Qwen Team. Qwen2.5: A party of foundation models, September 2024. URL [https://qwenlm.](https://qwenlm.github.io/blog/qwen2.5/)
649 [github.io/blog/qwen2.5/](https://qwenlm.github.io/blog/qwen2.5/).
- 650
- 651 Bing Wang, Changyu Ren, Jian Yang, Xinnian Liang, Jiaqi Bai, Qian-Wen Zhang, Zhao Yan, and
652 Zhoujun Li. Mac-sql: Multi-agent collaboration for text-to-sql. *arXiv preprint arXiv:2312.11242*,
653 2023a.

- 648 Lei Wang, Wanyu Xu, Yihuai Lan, Zhiqiang Hu, Yunshi Lan, Roy Ka-Wei Lee, and Ee-Peng Lim.
649 Plan-and-solve prompting: Improving zero-shot chain-of-thought reasoning by large language
650 models. In *Proceedings of the 61st Annual Meeting of the Association for Computational Lin-*
651 *guistics (Volume 1: Long Papers)*, pp. 2609–2634, 2023b.
- 652 Ping Wang, Tian Shi, and Chandan K Reddy. Text-to-sql generation for question answering on
653 electronic medical records. In *Proceedings of The Web Conference 2020*, pp. 350–361, 2020.
- 654 Xingyao Wang, Boxuan Li, Yufan Song, Frank F. Xu, Xiangru Tang, Mingchen Zhuge, Jiayi Pan,
655 Yueqi Song, Bowen Li, Jaskirat Singh, Hoang H. Tran, Fuqiang Li, Ren Ma, Mingzhang Zheng,
656 Bill Qian, Yanjun Shao, Niklas Muennighoff, Yizhe Zhang, Binyuan Hui, Junyang Lin, Robert
657 Brennan, Hao Peng, Heng Ji, and Graham Neubig. OpenDevin: An Open Platform for AI
658 Software Developers as Generalist Agents, 2024. URL [https://arxiv.org/abs/2407.](https://arxiv.org/abs/2407.16741)
659 [16741](https://arxiv.org/abs/2407.16741).
- 660
661 Chunqiu Steven Xia, Yinlin Deng, Soren Dunn, and Lingming Zhang. Agentless: Demystifying
662 llm-based software engineering agents. *arXiv preprint arXiv:2407.01489*, 2024.
- 663
664 John Yang, Akshara Prabhakar, Karthik Narasimhan, and Shunyu Yao. Intercode: Standardizing
665 and benchmarking interactive coding with execution feedback. *CoRR*, abs/2306.14898, 2023. doi:
666 [10.48550/arXiv.2306.14898](https://doi.org/10.48550/arXiv.2306.14898). URL <https://doi.org/10.48550/arXiv.2306.14898>.
- 667 John Yang, Carlos E. Jimenez, Alexander Wettig, Kilian Lieret, Shunyu Yao, Karthik Narasimhan,
668 and Ofir Press. Swe-agent: Agent computer interfaces enable software engineering language
669 models, 2024a.
- 670 John Yang, Akshara Prabhakar, Karthik Narasimhan, and Shunyu Yao. Intercode: Standardizing
671 and benchmarking interactive coding with execution feedback. *Advances in Neural Information*
672 *Processing Systems*, 36, 2024b.
- 673
674 Shunyu Yao, Jeffrey Zhao, Dian Yu, Nan Du, Izhak Shafran, Karthik R Narasimhan, and Yuan
675 Cao. React: Synergizing reasoning and acting in language models. In *The Eleventh International*
676 *Conference on Learning Representations*, 2022.
- 677 Pengcheng Yin, Wen-Ding Li, Kefan Xiao, Abhishek Rao, Yeming Wen, Kensen Shi, Joshua How-
678 land, Paige Bailey, Michele Catasta, Henryk Michalewski, et al. Natural language to code gen-
679 eration in interactive data science notebooks. In *Proceedings of the 61st Annual Meeting of the*
680 *Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 126–173, 2023.
- 681 Tao Yu, Rui Zhang, Kai Yang, Michihiro Yasunaga, Dongxu Wang, Zifan Li, James Ma, Irene Li,
682 Qingning Yao, Shanelle Roman, et al. Spider: A large-scale human-labeled dataset for complex
683 and cross-domain semantic parsing and text-to-sql task. In *Proceedings of the 2018 Conference*
684 *on Empirical Methods in Natural Language Processing*, pp. 3911–3921, 2018.
- 685
686 John M Zelle. Learning to parse database queries using inductive logic programming.
- 687
688 Luke S Zettlemoyer and Michael Collins. Learning to map sentences to logical form: structured
689 classification with probabilistic categorial grammars. In *Proceedings of the Twenty-First Confer-*
690 *ence on Uncertainty in Artificial Intelligence*, pp. 658–666, 2005.
- 691 Hanchong Zhang, Ruisheng Cao, Lu Chen, Hongshen Xu, and Kai Yu. Act-sql: In-context learning
692 for text-to-sql with automatically-generated chain-of-thought. In *Findings of the Association for*
693 *Computational Linguistics: EMNLP 2023*, pp. 3501–3532, 2023.
- 694 Shun Zhang, Zhenfang Chen, Yikang Shen, Mingyu Ding, Joshua B Tenenbaum, and Chuang Gan.
695 Planning with large language models for code generation. In *The Eleventh International Confer-*
696 *ence on Learning Representations*, 2022.
- 697
698 Yuntong Zhang, Haifeng Ruan, Zhiyu Fan, and Abhik Roychoudhury. Autocoderover: Autonomous
699 program improvement. In *Proceedings of the 33rd ACM SIGSOFT International Symposium on*
700 *Software Testing and Analysis*, pp. 1592–1604, 2024.
- 701 Victor Zhong, Caiming Xiong, and Richard Socher. Seq2sql: Generating structured queries from
natural language using reinforcement learning. *arXiv preprint arXiv:1709.00103*, 2017.

702 Qihao Zhu, Daya Guo, Zhihong Shao, Dejian Yang, Peiyi Wang, Runxin Xu, Y Wu, Yukun Li,
703 Huazuo Gao, Shirong Ma, et al. Deepseek-coder-v2: Breaking the barrier of closed-source models
704 in code intelligence. *arXiv preprint arXiv:2406.11931*, 2024.
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755

A SPIDER 2.0 EVALUATION SCRIPTS

In this section, we present the detailed definition and discussion of evaluation metrics for Spider 2.0-lite and Spider 2.0.

Spider 2.0-lite. The setting of Spider 2.0-lite resembles that of a traditional text-to-SQL task in which text-to-SQL parsers are required to generate SQL queries. Therefore, **Execution Accuracy (EX)** is used as the primary evaluation metric. Slightly different from existing works, we employ an *execution-based focused evaluation*, which measures whether all columns in the gold value are present in the output of the predicted SQL query. This is defined as follows:

$$EX = \frac{\sum_{n=1}^N \mathbb{1}(v^n, \hat{v}^n)}{N}, \quad (1)$$

$$\text{where } \mathbb{1}(v, \hat{v}) = \begin{cases} 1, & \text{if } v_i \in \hat{v}, \forall v_i \in v \\ 0, & \text{if } v_i \notin \hat{v}, \exists v_i \in v \end{cases}, \quad (2)$$

where v_i represents the i -th column of data frame v , v^n and \hat{v}^n denote execution results of the gold SQL and predicted SQL for the n -th instance in the evaluation set, respectively. Empirically, this evaluation method significantly reduces the false negative rate without increasing the number of false positives. Given that the ground-truth values result from extensive data wrangling, transformation, and analysis, it is difficult for models to manipulate or exploit the system.

Spider 2.0. We use the **Success rate (SR)**, which measures the proportion of task instances successfully resolved. Human-written evaluation scripts are used to determine whether an example is resolved. For each example, we provide string-based, table-based, and database-based evaluation functions, depending on the type of answer output, as shown in Tab. 11.

Examples. Maintaining naturalness and unambiguity is often a conflicting challenge. To address this, we provide an example to illustrate the important parameters “condition_cols” and “ignore_order”. Achieving a balance between these two aspects is quite challenging, which is why we incorporate this mechanism into our evaluation scripts.

Given a data frame v with a set of column vectors $\{v_i\}$, each representing the cell values for the i -th column, a prediction \hat{v} is considered equivalent with v if and only if for any $v_i \in v$, $v_i \in \hat{v}$. Therefore, at such times, we only check whether a specific column appears in it. Intuitively, if all columns in the reference table appear in the result table, the result is considered correct.

For example, as illustrated in Fig. 8, the question does not explicitly specify which columns are required in our response. Consider the following question: “The company management has requested a detailed report on the year-to-date performance of the Magnificent 7 stocks.”. We need to carefully analyze the task requirements and only check if the following columns in the reference answer—“Ticker”, “Change_YTD”—appear in the predicted answer. This meets the semantic requirements of the abstract instruction. Empirically, we find our evaluation metric is reliable in identifying solutions with alternative output, with a relatively low false-negative rate.




Figure 8: An example of evaluation scripts for table-based evaluation: in this example, the condition_cols is {0,5}, and the ignore_order is true. As long as these two columns are predicted correctly, the example can be considered solved.

Table 11: The evaluation scripts for Spider 2.0 are tailored to the specific format of the model’s output. Each script is optimized to handle various output types, ensuring precise and contextually appropriate evaluation.

Output Type	Description	Parameters
String w/o number	<i>If the answer is found in the string, it is given a score of 1; otherwise, it receives a score of 0.</i>	pred (str): The string in which to search for substrings. gold (List of str): A list of strings to check within the predicted string. conj (str): The conjunction used for matching (‘and’ or ‘or’). Default is ‘or’. exclude (List of Str): Strings that must not be present in the answer.
String w. number	<i>For output strings containing numbers, the script captures these numbers and performs number matching for scoring using the <code>number_match</code> function.</i>	pred (str): The string in which to search for substrings. gold (List[str float]): A list of strings or numbers to check within the predicted string. percentage (bool): Default is false. If the gold answer is related to percentages, set this to true for more robust evaluation. precision (int): The number of decimal places to consider. Defaults to 4. conj (str): The conjunction used for matching (‘and’ or ‘or’). Default is ‘or’, and it’s typically ‘or’.
Table	<i>If the answer is a CSV file or a table in string format, table-level evaluation is performed.</i>	result (str): Path to the CSV file or result string. gold (str List[str]): Path(s) to the gold file(s), excluding the root directory. Multiple potential gold answers are supported. condition_cols (List[int] List[List[int]]): List of column indices to match conditions. For example, [0, 1] uses the 0th and 1st columns in the gold table for matching, while ignoring the others. ignore_order (bool): Whether to ignore the order of rows when matching elements.
Database	<i>If the answer is stored in a DB file, database-level evaluation is applied using the <code>db_match</code> function.</i>	result (str): Path to the DuckDB file containing the result tables. gold (str): Path to the DuckDB file containing the gold standard tables. condition_tabs (List[str], optional): List of table names to be checked. If not provided, all tables in the gold DuckDB file will be considered. condition_cols (List[List[int]], optional): A list of lists, where each inner list contains column indices used for matching conditions for the corresponding table. Defaults to considering all columns. ignore_orders (List[bool], optional): A list of boolean values indicating whether to ignore the row order for each table comparison. Defaults to [False] for each table.
SQL	<i>If the output is an SQL, execution-based evaluation is used. This is primarily designed for Spider 2.0-lite.</i>	To compare the execution results of the predicted SQL and the gold SQL, table matching is used.

B ANNOTATION DETAILS

B.1 SQL ANNOTATION EXAMPLES

In this section, we present several representative examples of the SQL annotation process, including the original SQL, how the SQL was rewritten to obtain the gold SQL, and the use of external knowledge.

Tab. 12 presents an example based on the Google Analytics database. The task is to calculate the source of web traffic and count the number of sessions for each traffic channel within a given time period.

Tab. 13 presents an example based on New York City public data, where the task is to find Citibike and taxi trips between specified locations and analyze whether Citibike or taxi is more suitable for travel between the two locations. In this case, the condition in the original SQL is to calculate trips between the two locations by Citibike and car. We extend this condition by introducing a real-life problem: identifying which routes are faster by Citibike compared to taxi.

Tab. 14 is based on the Google Patents database, which contains a large amount of patent information. The original SQL applied several filtering conditions to retrieve a set of patents. We find a document explaining how to calculate a patent’s originality score, which led to an advanced calculation method. As a result, the final task include additional complex calculation steps.

Tab. 15 is also based on the Google Analytics database. The original SQL calculates the Product List Page (PLP) and Product Details Page (PDP). Based on the description in the blog, we define a new task to calculate the conversion rate by determining the probability of users clicking from PLP to PDP.

Tab. 16 presents an example where we merge and rewrite two related SQL queries. The first SQL calculates the 50 weather stations closest to downtown Chicago, while the second SQL calculates the number of bike trips on rainy and non-rainy days in New York City. We combine these two tasks, meaning that to determine whether it is a rainy day, we first need to find data from the weather station closest to downtown New York City.

B.2 DBT PROJECT ANNOTATION EXAMPLES

Annotation Pipeline of DBT Project. The DBT project can be found on online resources and is one of the projects with the most SQL scripts. Similar data transformation tools are widely used in industrial production. Completing a DBT project requires a comprehensive understanding of both the code and documentation within the project to accomplish the entire task. Fig. 9 shows a Salesforce-based project in Spider 2.0. This represents a natural and realistic SQL generation scenario. Using a Fivetran Salesforce transformation package² as an example, we transform a complex DBT project into a Spider 2.0 example through the following steps.

(1) Run a DBT project from start to finish, ensuring it is bug-free and generates a dbt DAG (Fig. 11). This allows for a comprehensive understanding of the data flow.

(2) The DBT project includes yml files and markdown documents, where the project developers have already planned out the data models and data flow. We will use these as the basis for task instructions.




Figure 9: Codebase for a DBT project, showing models, macros, and configuration files.

²https://github.com/fivetran/dbt_salesforce/

```

918 - name: salesforce__opportunity_enhanced
919   description: >
920     This table both cleans and enhances your opportunities source table with information about
921     the associate account and opportunity owner.
922   ref:
923     - name: opportunity
924     - name: user
925     - name: user_role
926     - name: account
927   columns:
928     - name: opportunity_id
929       description: The unique, system-generated ID assigned during creation.
930       tests:
931         - not_null
932         - unique
933     - name: account_number
934       description: Number of the account associated with this opportunity.
935     - name: account_id
936       description: ID of the account associated with this opportunity.
937     - name: account_type
938       description: Type of account, for example, Customer, Competitor, or Partner.
939     - name: amount
940       description: Estimated total sale amount. For opportunities with products, the amount is the sum of the related products.
941     - name: campaign_id
942       description: ID of a related Campaign. This field is defined only for those organizations that have the campaign feature Campaigns enabled.
943     - name: close_date
944       description: Required. Date when the opportunity is expected to close.
945     - name: created_date
946       description: Date when the opportunity is was created.
947     - name: opportunity_description
948       description: Text description of the opportunity.
949     - name: expected_revenue
950       description: Read-only field that is equal to the product of the opportunity Amount field and the Probability.
951     - name: fiscal
952       description: If fiscal years are not enabled, the name of the fiscal quarter or period in which the opportunity CloseDate falls.
953     - name: fiscal_quarter
954       description: Represents the fiscal quarter. Valid values are 1, 2, 3, or 4.
955     - name: fiscal_year
956       description: Represents the fiscal year, for example, 2006.
957     - name: forecast_category
958       description: The category of the state of the opportunity. Default values are 'pipeline','forecast','bestcase','closed', and 'omited'
959     - name: forecast_category_name
960       description: The name of the forecast category.
961     - name: has_open_activity
962       description: Indicates whether an opportunity has an open event or task (true) or not (false).
963     - name: has_opportunity_line_item
964       description: Read-only field that indicates whether the opportunity has associated line items. A value of true means that Opportunity line i
965     - name: has_overdue_task
966       description: Indicates whether an opportunity has an overdue task (true) or not (false).
967     - name: last_activity_date
968       description: Value is one of the following, whichever is the most recent:Due date of the most recent event logged against the record or Due
969     - name: last_referenced_date
970       description: The timestamp when the current user last accessed this record, a record related to this record, or a list view.
971     - name: last_viewed_date
972       description: The timestamp when the current user last viewed this record or list view. If this value is null, the user might have only acces
973     - name: lead_source
974       description: Source of this opportunity, such as Advertisement or Trade Show.
975     - name: opportunity_name

```

951 Figure 10: This is a common configuration file in DBT projects used to define the schema of a data
 952 model. It represents a natural SQL generation scenario, specifying details such as field names, data
 953 types, and references for the “salesforce_opportunity_enhanced” data model.
 954

955 (3) We remove the .sql files corresponding to a specific data flow within the complete DBT project.
 956 For example, in Fig. 11, we may delete one to three data flows, as shown in Fig. 12, removing
 957 “sales_daily_activity” and “salesforce_contact_enhanced” along with their upstream nodes. This
 958 turns it into an incomplete transformation project. Note that the DAG figure is only used as an
 959 aid for data annotation, and the task does not include any images.

960 (4) Write the task instructions. For instance, we can draft a prompt like, “I need a daily report
 961 on key sales activities—covering tasks completed, events held, leads generated, and the status of
 962 opportunities.” Although the data model contains many columns, thanks to the presence of yml files
 963 (see Fig. 10), there is no need to describe the output columns in detail in the instructions.

964 **Approach to Solving DBT Project Examples.** As shown in Fig. 27, completing a DBT project
 965 example typically requires the following abilities:

966 1) Problem comprehension. First, it is necessary to fully understand a natural language task.

967 2) Project reading ability. A real-world data transformation project consists of multiple files, as
 968 illustrated in Fig. 9. The method needs to explore the codebase and review relevant project files,
 969 including .yml, .md, and .sql files. YAML files (Fig. 10) generally define the data models for the data
 970 transformation, .md files contain textual descriptions of the data models, and SQL files are the data
 971 transformation models themselves.



Figure 11: A DAG (Directed Acyclic Graph) illustrating the data flow and dependencies between various Salesforce tables and models in a dbt (data build tool) project. The graph shows stages of transformation, from raw Salesforce data (green nodes) to enhanced and aggregated models (blue nodes), representing different entities such as opportunities, contacts, accounts, and events.




Figure 12: In this version of the DAG, several data models are missing, including “salesforce_daily_activity” and “salesforce_contact_enhanced” along with their upstream nodes. This creates an incomplete data flow compared to the original.

3) Database exploration ability. The codebase only contains the data transformation code, while the data to be transformed is stored in a database. The method must explore the database to understand the available source data and identify any missing data models.

4) Problem localization ability. By combining the natural language problem and the YML files, the method should locate where to add or modify the code in the project.

5) Coding ability. The method needs to complete complex data transformation code based on the data models defined in the YML files and add the .sql files in the appropriate locations. Visually, it requires completing the data models defined in the yml file, transitioning from Fig. 12 to Fig. 11.

6) Data transformation execution. Once the SQL is written, it is necessary to run `dbt run` to execute the data transformation.

7) Debugging. After running the DBT project, if the data transformation is successful, the data models (the tables) in the database will change, with tables being added or removed. The method needs to examine the database to determine if the transformation was fully successful. If not, the above steps must be repeated until the method meets the problem’s requirements.

Table 12: Google analytics traffic session examples, using *answer format surface* rewrite.**Question**

Provide the number of sessions and percentage breakdown by channel for December 2020.

Reference Plan

1. First, read the document to understand how traffic is divided into 18 channel groups, primarily based on the metrics of source, medium, and campaign. 2. Extract all visits from the database for December, each visit having a unique user ID and session ID. Retrieve the source, medium, and campaign for each visit. 3. Based on the classification standards for channel groups in the document, write conditional statements to determine which channel each set of data belongs to, mainly using regular expressions. If the data source (source) contains any of the following: 'badoo', 'facebook', 'fb', 'instagram', 'linkedin', 'pinterest', 'tiktok', 'twitter', or 'whatsapp', and the medium (medium) includes 'cp', 'ppc', or starts with 'paid', then categorize it as 'Paid Social'. 4. Calculate the number of sessions and percentage for each channel based on the channel grouping.

Gold SQL (After rewriting)

```
WITH prep AS (
SELECT user_pseudo_id,
(SELECT value.int_value FROM UNNEST(event_params) WHERE key = 'ga_session_id') AS session_id,
ARRAY_AGG((SELECT value.string_value FROM UNNEST(event_params) WHERE key = 'source')
IGNORE NULLS ORDER BY event_timestamp)[SAFE_OFFSET(0)] AS source,
ARRAY_AGG((SELECT value.string_value FROM UNNEST(event_params) WHERE key = 'medium')
IGNORE NULLS ORDER BY event_timestamp)[SAFE_OFFSET(0)] AS medium,
ARRAY_AGG((SELECT value.string_value FROM UNNEST(event_params) WHERE key = 'campaign')
IGNORE NULLS ORDER BY event_timestamp)[SAFE_OFFSET(0)] AS campaign
FROM `bigquery-public-data.ga4_obfuscated_sample_ecommerce.events_*`
WHERE TABLE_SUFFIX BETWEEN '20201201' AND '20201231' GROUP BY user_pseudo_id, session_id )
grouped_data AS (
SELECT CASE
WHEN source = '(direct)' AND (medium IN ('not set'), '(none))') THEN 'Direct',
WHEN REGEXP_CONTAINS(campaign, 'cross-network') THEN 'Cross-network'
WHEN (REGEXP_CONTAINS(source, 'alibaba|amazon|google shopping|shopify|etsy|ebay|stripe|walmart')
OR REGEXP_CONTAINS(campaign, '^.*(([^a-z]|)shop|shopping).*$'))
AND REGEXP_CONTAINS(medium, '^.*(cp|ppc|paid).*') THEN 'Paid Shopping',
WHEN REGEXP_CONTAINS(source, 'baidu|bing|duckduckgo|ecosia|google|yahoo|yandex')
AND REGEXP_CONTAINS(medium, '^.*(cp|ppc|paid).*') THEN 'Paid Search',
WHEN REGEXP_CONTAINS(source, 'badoo|facebook|fb|instagram|linkedin|pinterest|tiktok|twitter|whatsapp')
AND REGEXP_CONTAINS(medium, '^.*(cp|ppc|paid).*') THEN 'Paid Social',
WHEN REGEXP_CONTAINS(source, 'dailymotion|disneyplus|netflix|youtube|vimeo|twitch|vimeo|youtube')
AND REGEXP_CONTAINS(medium, '^.*(cp|ppc|paid).*') THEN 'Paid Video',
WHEN medium IN ('display', 'banner', 'expandable', 'interstitial', 'cpm') THEN 'Display'
WHEN REGEXP_CONTAINS(source, 'alibaba|amazon|google shopping|shopify|etsy|ebay|stripe|walmart')
OR REGEXP_CONTAINS(campaign, '^.*(([^a-z]|)shop|shopping).*$') THEN 'Organic Shopping'
WHEN REGEXP_CONTAINS(source, 'badoo|facebook|fb|instagram|linkedin|pinterest|tiktok|twitter|whatsapp')
OR medium IN ('social', 'social-network', 'social-media', 'sm', 'social network', 'social media') THEN 'Organic Social'
WHEN REGEXP_CONTAINS(source, 'dailymotion|disneyplus|netflix|youtube|vimeo|twitch|vimeo|youtube')
OR REGEXP_CONTAINS(medium, '^.*(video).*') THEN 'Organic Video'
WHEN REGEXP_CONTAINS(source, 'baidu|bing|duckduckgo|ecosia|google|yahoo|yandex') OR medium = 'organic' THEN 'Organic Search'
WHEN REGEXP_CONTAINS(source, 'email|e-mail|e_mail|e mail') OR REGEXP_CONTAINS(medium, 'email|e-mail|e_mail|e mail') THEN 'Email'
WHEN medium = 'affiliate' THEN 'Affiliates' WHEN medium = 'referral' THEN 'Referral'
WHEN medium = 'audio' THEN 'Audio' WHEN medium = 'sms' THEN 'SMS'
WHEN medium LIKE 'push' OR REGEXP_CONTAINS(medium, 'mobile|notification') THEN 'Mobile Push Notifications' ELSE 'Unassigned'
END AS channel_grouping_session, COUNT(DISTINCT CONCAT(user_pseudo_id, session_id)) AS session_count
FROM
prep GROUP BY channel_grouping_session
),
total_sessions AS (
SELECT SUM(session_count) AS total_count FROM grouped_data )
SELECT gd.channel_grouping_session, gd.session_count, ROUND(gd.session_count / ts.total_count * 100, 2) AS percentage_of_total
FROM grouped_data gd, total_sessions ts
ORDER BY gd.session_count DESC LIMIT 10;
```

Original SQL

```
WITH prep AS (
SELECT user_pseudo_id,
(SELECT value.int_value FROM UNNEST(event_params) WHERE key = 'ga_session_id') AS session_id,
ARRAY_AGG((SELECT value.string_value FROM UNNEST(event_params) WHERE key = 'source')
IGNORE NULLS ORDER BY event_timestamp)[SAFE_OFFSET(0)] AS source,
ARRAY_AGG((SELECT value.string_value FROM UNNEST(event_params) WHERE key = 'medium')
IGNORE NULLS ORDER BY event_timestamp)[SAFE_OFFSET(0)] AS medium,
ARRAY_AGG((SELECT value.string_value FROM UNNEST(event_params) WHERE key = 'campaign')
IGNORE NULLS ORDER BY event_timestamp)[SAFE_OFFSET(0)] AS campaign
FROM `bigquery-public-data.ga4_obfuscated_sample_ecommerce.events_*`
WHERE TABLE_SUFFIX BETWEEN '20201201' AND '20201231' GROUP BY user_pseudo_id, session_id )
grouped_data AS (
SELECT CASE
WHEN source = '(direct)' AND (medium IN ('not set'), '(none))') THEN 'Direct',
WHEN REGEXP_CONTAINS(campaign, 'cross-network') THEN 'Cross-network'
WHEN (REGEXP_CONTAINS(source, 'alibaba|amazon|google shopping|shopify|etsy|ebay|stripe|walmart')
OR REGEXP_CONTAINS(campaign, '^.*(([^a-z]|)shop|shopping).*$'))
AND REGEXP_CONTAINS(medium, '^.*(cp|ppc|paid).*') THEN 'Paid Shopping',
WHEN REGEXP_CONTAINS(source, 'baidu|bing|duckduckgo|ecosia|google|yahoo|yandex')
AND REGEXP_CONTAINS(medium, '^.*(cp|ppc|paid).*') THEN 'Paid Search',
WHEN REGEXP_CONTAINS(source, 'badoo|facebook|fb|instagram|linkedin|pinterest|tiktok|twitter|whatsapp')
AND REGEXP_CONTAINS(medium, '^.*(cp|ppc|paid).*') THEN 'Paid Social',
WHEN REGEXP_CONTAINS(source, 'dailymotion|disneyplus|netflix|youtube|vimeo|twitch|vimeo|youtube')
AND REGEXP_CONTAINS(medium, '^.*(cp|ppc|paid).*') THEN 'Paid Video',
WHEN medium IN ('display', 'banner', 'expandable', 'interstitial', 'cpm') THEN 'Display'
WHEN REGEXP_CONTAINS(source, 'alibaba|amazon|google shopping|shopify|etsy|ebay|stripe|walmart')
OR REGEXP_CONTAINS(campaign, '^.*(([^a-z]|)shop|shopping).*$') THEN 'Organic Shopping'
WHEN REGEXP_CONTAINS(source, 'badoo|facebook|fb|instagram|linkedin|pinterest|tiktok|twitter|whatsapp')
OR medium IN ('social', 'social-network', 'social-media', 'sm', 'social network', 'social media') THEN 'Organic Social'
WHEN REGEXP_CONTAINS(source, 'dailymotion|disneyplus|netflix|youtube|vimeo|twitch|vimeo|youtube')
OR REGEXP_CONTAINS(medium, '^.*(video).*') THEN 'Organic Video'
WHEN REGEXP_CONTAINS(source, 'baidu|bing|duckduckgo|ecosia|google|yahoo|yandex') OR medium = 'organic' THEN 'Organic Search'
WHEN REGEXP_CONTAINS(source, 'email|e-mail|e_mail|e mail') OR REGEXP_CONTAINS(medium, 'email|e-mail|e_mail|e mail') THEN 'Email'
WHEN medium = 'affiliate' THEN 'Affiliates' WHEN medium = 'referral' THEN 'Referral'
WHEN medium = 'audio' THEN 'Audio' WHEN medium = 'sms' THEN 'SMS'
WHEN medium LIKE 'push' OR REGEXP_CONTAINS(medium, 'mobile|notification') THEN 'Mobile Push Notifications' ELSE 'Unassigned'
END AS channel_grouping_session, COUNT(DISTINCT CONCAT(user_pseudo_id, session_id)) AS session_count
FROM
prep GROUP BY channel_grouping_session
),
ORDER BY
COUNT(DISTINCT CONCAT(user_pseudo_id, session_id)) DESC
LIMIT 1
```


Table 13: Citibike and taxi of NYC public data example, *condition parameters* surface rewrite.

1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133

Question

For the top 20 Citi Bike routes in 2016, which route is faster than yellow taxis and among those, which one has the longest average bike duration? Please provide the start station name of this route. The coordinates are rounded to three decimals.

Reference Plan

1. Focus on 2016 data to determine the top 20 most popular bike routes based on start and end stations, noting their latitude and longitude. 2. Calculate the average bike duration and count the number of bike trips for each route. 3. Extract the average duration for corresponding taxi routes using the same latitude and longitude for start and end points. 4. Calculate the average taxi duration for the matching routes. 5. Filter the results to find the bike route where the average bike duration is shorter than the average taxi duration. 6. Order the results by average bike duration in descending order and limit the output to one record.

Gold SQL (After rewriting)

```
WITH top20route AS (
SELECT
start_station_name, end_station_name, avg_bike_duration, avg_taxi_duration
FROM (
SELECT start_station_name, end_station_name,
ROUND(start_station_latitude, 3) AS ss_lat, ROUND(start_station_longitude, 3) AS ss_long,
ROUND(end_station_latitude, 3) AS es_lat, ROUND(end_station_longitude, 3) AS es_long,
AVG(tripduration) AS avg_bike_duration, COUNT(*) AS bike_trips
FROM `bigquery-public-data.new_york.citibike_trips`
WHERE
EXTRACT(YEAR from starttime) = 2015 AND start_station_name != end_station_name
GROUP BY start_station_name, end_station_name, ss_lat, ss_long, es_lat, es_long
ORDER BY bike_trips DESC LIMIT 20
) a
JOIN (
SELECT
ROUND(pickup_latitude, 3) AS pu_lat, ROUND(pickup_longitude, 3) AS pu_long,
ROUND(dropoff_latitude, 3) AS do_lat, ROUND(dropoff_longitude, 3) AS do_long,
AVG(UNIX_SECONDS(dropoff_datetime)-UNIX_SECONDS(pickup_datetime)) AS avg_taxi_duration,
COUNT(*) AS taxi_trips
FROM `bigquery-public-data.new_york.tlc_yellow_trips_2015`
GROUP BY
pu_lat, pu_long, do_lat, do_long
) b
ON
a.ss_lat = b.pu_lat AND a.es_lat = b.do_lat AND
a.ss_long = b.pu_long AND a.es_long = b.do_long
)
SELECT start_station_name FROM top20route
WHERE avg_bike_duration < avg_taxi_duration
ORDER BY avg_bike_duration DESC LIMIT 1
```

Original SQL

```
SELECT
start_station_name, end_station_name, avg_bike_duration, avg_taxi_duration, avg_taxi_fare
FROM (
SELECT start_station_name, end_station_name,
ROUND(start_station_latitude, 3) AS ss_lat, ROUND(start_station_longitude, 3) AS ss_long,
ROUND(end_station_latitude, 3) AS es_lat, ROUND(end_station_longitude, 3) AS es_long,
COUNT(*) AS bike_trips
FROM `bigquery-public-data.new_york.citibike_trips`
WHERE start_station_name != end_station_name
GROUP BY start_station_name, end_station_name, ss_lat, ss_long, es_lat, es_long
ORDER BY bike_trips DESC LIMIT 100 ) a
JOIN (
SELECT
ROUND(pickup_latitude, 3) AS pu_lat, ROUND(pickup_longitude, 3) AS pu_long,
ROUND(dropoff_latitude, 3) AS do_lat, ROUND(dropoff_longitude, 3) AS do_long,
COUNT(*) AS taxi_trips
FROM `bigquery-public-data.new_york.tlc_yellow_trips_2016`
GROUP BY pu_lat, pu_long, do_lat, do_long) b
ON
a.ss_lat=b.pu_lat AND a.es_lat=b.do_lat AND a.ss_long=b.pu_long AND a.es_long=b.do_long
ORDER BY bike_trips DESC LIMIT 20;
```

Table 14: Google patent example, *advanced calculation* surface rewrite.

1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187

Question

What is the publication number of US patent granted at January 2018, with the highest originality score based on the diversity of 4-digits IPC codes from its backward citations?

Reference Plan

1. Filter US Patents: Select publication numbers and application numbers from the dataset, including only records where the country code is 'US', the grant date is within January 2018, and excluding records with a grant date of 0. Additionally, only consider patents with a specific kind code pattern (e.g., %B2%). 2. Extract IPC Codes: Select the publication number and count the unique 4-digit IPC codes associated with each selected patent. 3. Identify Maximum IPC Code Count: Create a subset of records that have the maximum count of a specific 4-digit IPC code for each patent. 4. Calculate IPC Occurrences in Backward Citations: Join the filtered patents with their backward citations. For each backward citation, join with the subset of records to get the 4-digit IPC codes, counting occurrences of each IPC code in the backward citations for each patent. 5. Compute Originality Score: For each patent, calculate an originality score based on the diversity of the 4-digit IPC codes from the backward citations, using a formula that considers the sum of squared occurrences of each IPC code, normalized by the total number of occurrences. 6. Select Highest Originality Score: From the computed originality scores, select the patent with the highest score. 7. Return Result: Output the publication number of the patent with the highest originality score.

Gold SQL (After rewriting)

```
WITH patents_sample AS (
  SELECT
    t1.publication_number, t1.application_number FROM `patents-public-data.patents.publications` t1
  WHERE
    country_code = 'US' AND grant_date BETWEEN 20180101 AND 20180131
    AND grant_date != 0 AND publication_number LIKE '%B2%'
),
interim_table AS (
  SELECT t1.publication_number, SUBSTR(ipc_u.code, 0, 4) AS ipc4,
  COUNT(SUBSTR(ipc_u.code, 0, 4)) AS ipc4_count
  FROM
    patents-public-data.patents.publications t1, UNNEST(ipc) AS ipc_u
  GROUP BY t1.publication_number, ipc4
),
chosen_ipc4_view AS (
  SELECT * FROM interim_table
  WHERE CONCAT(interim_table.publication_number, interim_table.ipc4_count) IN (
    SELECT CONCAT(publication_number, MAX(ipc4_count)) FROM interim_table GROUP BY publication_number
  )
  ORDER BY ipc4_count DESC
),
ipc_counts AS (
  SELECT t1.publication_number, t3.ipc4, COUNT(t3.ipc4) AS ipc_occurrences
  FROM patents_sample t1
  LEFT JOIN (
    SELECT
      x2.publication_number AS citing_publication_number, citation_u.publication_number AS backward_citation
    FROM
      patents-public-data.patents.publications x2, UNNEST(citation) AS citation_u) t2
  ON
    t2.citing_publication_number = t1.publication_number
  LEFT JOIN chosen_ipc4_view t3 ON t3.publication_number = t2.backward_citation
  GROUP BY t1.publication_number, t3.ipc4
),
max_originality AS (
  SELECT publication_number,
  1 - SUM(POWER(ipc_occurrences, 2)) / POWER(SUM(ipc_occurrences), 2) AS originality
  FROM ipc_counts GROUP BY publication_number
  HAVING SUM(ipc_occurrences) > 0 ORDER BY originality DESC LIMIT 1
)
SELECT publication_number FROM max_originality
```

Original SQL

```
WITH patents_sample AS (
  SELECT
    t1.publication_number, t1.application_number FROM `patents-public-data.patents.publications` t1
  WHERE
    country_code = 'US' AND grant_date BETWEEN 20180101 AND 20180131
    AND grant_date != 0 AND publication_number LIKE '%B2%'
),
interim_table AS (
  SELECT t1.publication_number, SUBSTR(ipc_u.code, 0, 4) AS ipc4,
  COUNT(SUBSTR(ipc_u.code, 0, 4)) AS ipc4_count
  FROM
    patents-public-data.patents.publications t1, UNNEST(ipc) AS ipc_u
  GROUP BY t1.publication_number, ipc4
),
chosen_ipc4_view AS (
  SELECT * FROM interim_table
  WHERE CONCAT(interim_table.publication_number, interim_table.ipc4_count) IN (
    SELECT CONCAT(publication_number, MAX(ipc4_count)) FROM interim_table GROUP BY publication_number
  )
  ORDER BY ipc4_count DESC
),
SELECT t1.publication_number, t3.ipc4, COUNT(t3.ipc4) AS ipc_occurrences
FROM patents_sample t1
LEFT JOIN (
  SELECT
    x2.publication_number AS citing_publication_number,
    citation_u.publication_number AS backward_citation
  FROM
    patents-public-data.patents.publications x2, UNNEST(citation) AS citation_u) t2
ON
  t2.citing_publication_number = t1.publication_number
LEFT JOIN chosen_ipc4_view t3 ON t3.publication_number = t2.backward_citation
GROUP BY t1.publication_number, t3.ipc4
```

Table 15: Google analytics page conversion rate example, *advanced requirements* semantic rewrite.**Question**

Calculate the conversion rate from product list pages to product detail pages for all sessions at January 2nd, 2021.

Reference Plan

1. query the event data to retrieve all unique event names 2. Selects events data from the Google Analytics 4 (GA4) sample e-commerce dataset for the specific date (20210102) 3. Filter to include only events named page_view, which represent page views. 4. flatten the nested event_params array and extract values for ga_session_id, ga_session_number, page_title, and page_location. This allows the analysis of individual page views within each user's session. 5. Further processes the unnested event data to classify pages based on URL depth and specific keywords into either Product Detail Pages (PDP) or Product Listing Pages (PLP). 6. Applies window functions to the categorized data to calculate the previous and next pages for each session per user, facilitating analysis of navigation paths between pages. 7. Filters sessions where the current page is a PLP and the next page is a PDP. 8. Counts the number of sessions transitioning from PLP to PDP and divides this by the total views of PLP pages to calculate the conversion rate.

Gold SQL (After rewriting)

```
WITH base_table AS (
SELECT
event_name, event_date, event_timestamp, user_pseudo_id, user_id, device, geo, traffic_source, event_params, user_properties
FROM
`bigquery-public-data.ga4_obfuscated_sample_ecommerce.events_*`
WHERE
_table_suffix BETWEEN '20210101' AND '20210131' AND event_name IN ('page_view')
),
unnested_events AS (
SELECT
event_date AS date, event_timestamp AS event_timestamp_microseconds, user_pseudo_id,
MAX(CASE WHEN c.key = 'ga_session_id' THEN c.value.int_value END) AS visitID,
MAX(CASE WHEN c.key = 'ga_session_number' THEN c.value.int_value END) AS visitNumber,
MAX(CASE WHEN c.key = 'page_title' THEN c.value.string_value END) AS page_title,
MAX(CASE WHEN c.key = 'page_location' THEN c.value.string_value END) AS page_location
FROM
base_table, UNNEST(event_params) c
GROUP BY 1, 2, 3
),
unnested_events_categorised AS (
SELECT
*,
CASE
WHEN ARRAY_LENGTH(SPLIT(page_location, '/')) >= 5 AND CONTAINS_SUBSTR(ARRAY_REVERSE(SPLIT(page_location, '/'))[SAFE_OFFSET(0)], '+')
AND (LOWER(SPLIT(page_location, '/'))[SAFE_OFFSET(4)])
IN('accessories', 'apparel', 'brands', 'campus+collection', 'drinkware', 'electronics', 'google+redesign',
'lifestyle', 'nest', 'new+2015+logo', 'notebooks+journals', 'office', 'shop-by-brand', 'small+goods', 'stationery', 'wearables')
OR LOWER(SPLIT(page_location, '/'))[SAFE_OFFSET(3)] IN
('accessories', 'apparel', 'brands', 'campus+collection', 'drinkware', 'electronics', 'google+redesign', 'lifestyle', 'nest', 'new+2015+logo',
'notebooks+journals', 'office', 'shop-by-brand', 'small+goods', 'stationery', 'wearables')) THEN 'PDP'
WHEN NOT CONTAINS_SUBSTR(ARRAY_REVERSE(SPLIT(page_location, '/'))[SAFE_OFFSET(0)], '+') AND (LOWER(SPLIT(page_location,
'/'))[SAFE_OFFSET(4)]) IN
('accessories', 'apparel', 'brands', 'campus+collection', 'drinkware', 'electronics', 'google+redesign', 'lifestyle', 'nest', 'new+2015+logo',
'notebooks+journals', 'office', 'shop-by-brand', 'small+goods', 'stationery', 'wearables') OR LOWER(SPLIT(page_location,
'/'))[SAFE_OFFSET(3)] IN
('accessories', 'apparel', 'brands', 'campus+collection', 'drinkware', 'electronics', 'google+redesign', 'lifestyle', 'nest', 'new+2015+logo',
'notebooks+journals', 'office', 'shop-by-brand', 'small+goods', 'stationery', 'wearables')) THEN 'PLP'
ELSE 'Other'
END AS page_category FROM unnested_events
)
ranked_screens AS (
SELECT
*,
LAG(page_category, 1) OVER (PARTITION BY user_pseudo_id, visitID ORDER BY event_timestamp_microseconds) AS previous_page,
LEAD(page_category, 1) OVER (PARTITION BY user_pseudo_id, visitID ORDER BY event_timestamp_microseconds) AS next_page
FROM
unnested_events_categorised
)
PLPtoPDPtransitions AS (SELECT page_title, COUNT(*) AS transitions FROM ranked_screens WHERE page_category = 'PLP' AND next_page =
'PDP' GROUP BY page_title),
TotalPLPViews AS (SELECT page_title, COUNT(*) AS total_plp_views FROM ranked_screens WHERE page_category = 'PLP' GROUP BY
page_title),
ConversionRates AS (
SELECT p.page_title, (CAST(t.transitions AS FLOAT64) / p.total_plp_views) * 100.0 AS conversion_rate
FROM TotalPLPViews t JOIN PLPtoPDPtransitions t ON p.page_title = t.page_title
SELECT page_title, MAX(conversion_rate) AS max_conversion_rate FROM ConversionRates GROUP BY page_title ORDER BY max_conversion_rate
DESC LIMIT 1;

```

Original SQL

```
WITH base_table AS (
SELECT
event_name, event_date, event_timestamp, user_pseudo_id, user_id, device, geo, traffic_source, event_params, user_properties
FROM
`bigquery-public-data.ga4_obfuscated_sample_ecommerce.events_*`
WHERE
_table_suffix BETWEEN '20210101' AND '20210131' AND event_name IN ('page_view')
),
unnested_events AS (
SELECT
event_date AS date, event_timestamp AS event_timestamp_microseconds, user_pseudo_id,
MAX(CASE WHEN c.key = 'ga_session_id' THEN c.value.int_value END) AS visitID,
MAX(CASE WHEN c.key = 'ga_session_number' THEN c.value.int_value END) AS visitNumber,
MAX(CASE WHEN c.key = 'page_title' THEN c.value.string_value END) AS page_title,
MAX(CASE WHEN c.key = 'page_location' THEN c.value.string_value END) AS page_location
FROM
base_table, UNNEST(event_params) c
GROUP BY 1, 2, 3
),
unnested_events_categorised AS (
SELECT
*,
CASE
WHEN ARRAY_LENGTH(SPLIT(page_location, '/')) >= 5 AND CONTAINS_SUBSTR(ARRAY_REVERSE(SPLIT(page_location, '/'))[SAFE_OFFSET(0)], '+')
AND (LOWER(SPLIT(page_location, '/'))[SAFE_OFFSET(4)])
IN('accessories', 'apparel', 'brands', 'campus+collection', 'drinkware', 'electronics', 'google+redesign',
'lifestyle', 'nest', 'new+2015+logo', 'notebooks+journals', 'office', 'shop-by-brand', 'small+goods', 'stationery', 'wearables')
OR LOWER(SPLIT(page_location, '/'))[SAFE_OFFSET(3)] IN
('accessories', 'apparel', 'brands', 'campus+collection', 'drinkware', 'electronics', 'google+redesign', 'lifestyle', 'nest', 'new+2015+logo',
'notebooks+journals', 'office', 'shop-by-brand', 'small+goods', 'stationery', 'wearables')) THEN 'PDP'
WHEN NOT CONTAINS_SUBSTR(ARRAY_REVERSE(SPLIT(page_location, '/'))[SAFE_OFFSET(0)], '+') AND (LOWER(SPLIT(page_location,
'/'))[SAFE_OFFSET(4)]) IN
('accessories', 'apparel', 'brands', 'campus+collection', 'drinkware', 'electronics', 'google+redesign', 'lifestyle', 'nest', 'new+2015+logo',
'notebooks+journals', 'office', 'shop-by-brand', 'small+goods', 'stationery', 'wearables') OR LOWER(SPLIT(page_location,
'/'))[SAFE_OFFSET(3)] IN
('accessories', 'apparel', 'brands', 'campus+collection', 'drinkware', 'electronics', 'google+redesign', 'lifestyle', 'nest', 'new+2015+logo',
'notebooks+journals', 'office', 'shop-by-brand', 'small+goods', 'stationery', 'wearables')) THEN 'PLP'
ELSE 'Other'
END AS page_category FROM unnested_events
)
SELECT (SELECT COUNT(*) FROM unnested_events_categorised WHERE page_title_adjusted='PDP')
/ (SELECT COUNT(*) FROM unnested_events_categorised)*100;

```

Table 16: GSOD and NYC public data example, *merge related SQLs* semantic rewrite.

1242	
1243	
1244	Question
1245	
1246	Get the average number of trips on rainy and non-rainy days in New York City during 2016,
1247	using data from the closest weather station located near the coordinates (-74.0060, 40.7128).
1248	Define a “rainy day” as any day where the precipitation recorded is more than 0 millimeters.
1249	Reference Plan
1250	1. Which days were rainy in 2016, and how can we obtain weather information? 2. The GHCN-D database allows us to access
1251	weather data from each weather station. 3. Given that the central coordinates of New York City are (-74.0060, 40.7128), we need
1252	to select a weather station to represent the weather data for New York City. 4. Calculate the weather stations closest to the center of
1253	New York City based on their distance. 5. Obtain the precipitation data from that weather station. 6. Use the precipitation data to
1254	classify the days in 2016 as either rainy or non-rainy. 7. The New York Citibike database stores daily bike rental data, which can be
1255	grouped based on whether it was a rainy day and then averaged. 8. Compare the differences in the average number of bike rentals on
1256	rainy days versus non-rainy days.
1257	Gold SQL (After rewriting)
1258	<pre>WITH params AS (SELECT ST_GeogPoint(-74.0060, 40.7128) AS center, 50 AS maxn_stations, 50 AS maxdist_km), distance_from_center AS (SELECT id, name, state, ST_GeogPoint(longitude, latitude) AS loc, ST_Distance(ST_GeogPoint(longitude, latitude), params.center) AS dist_meters FROM `bigquery-public-data.ghcn_d.ghcnd_stations`, params WHERE ST_DWithin(ST_GeogPoint(longitude, latitude), params.center, params.maxdist_km * 1000)), nearest_stations AS (SELECT *, RANK() OVER (ORDER BY dist_meters ASC) AS rank FROM distance_from_center), nearest_nstations AS (SELECT station.* FROM nearest_stations AS station, params WHERE rank <= params.maxn_stations), station_ids AS (SELECT id, dist_meters from nearest_nstations ORDER BY dist_meters ASC LIMIT 50), bicycle_rentals AS (SELECT COUNT(starttime) as num_trips, EXTRACT(DATE from starttime) as trip_date FROM `bigquery-public-data.new_york_citibike.citibike_trips` GROUP BY trip_date), closest AS (SELECT station_ids.id as id, ANY_VALUE(station_ids.dist_meters) as dist FROM `bigquery-public-data.ghcn_d.ghcnd_2016` AS wx JOIN station_ids ON wx.id=station_ids.id GROUP BY station_ids.id ORDER BY dist ASC LIMIT 1), rainy_days AS (SELECT date, COALESCE(MAX(prcp), 0) > 0) AS rainy FROM (SELECT wx.date AS date, IF (wx.element = 'PRCP', wx.value/10, NULL) AS prcp FROM `bigquery-public-data.ghcn_d.ghcnd_2016` AS wx WHERE wx.id IN (SELECT id FROM closest)) GROUP BY date) SELECT ROUND(AVG(bk.num_trips)) AS num_trips, wx.rainy FROM bicycle_rentals AS bk JOIN rainy_days AS wx ON wx.date = bk.trip_date GROUP BY wx.rainy</pre>
1277	Original SQL
1278	<pre>--SQL1: New York City Rainy Days WITH bicycle_rentals AS (SELECT COUNT(starttime) as num_trips, EXTRACT(DATE from starttime) as trip_date FROM `bigquery-public-data.new_york_citibike.citibike_trips` GROUP BY trip_date), rainy_days AS (SELECT date, (MAX(prcp) > 5) AS rainy FROM (SELECT wx.date AS date, IF (wx.element = 'PRCP', wx.value/10, NULL) AS prcp FROM `bigquery-public-data.ghcn_d.ghcnd_2016` AS wx WHERE wx.id = 'USW00094728') GROUP BY date) SELECT ROUND(AVG(bk.num_trips)) AS num_trips, wx.rainy FROM bicycle_rentals AS bk JOIN rainy_days AS wx ON wx.date = bk.trip_date GROUP BY wx.rainy</pre>
1288	<pre>--SQL2: Chicago Nearest Weather Station WITH params AS (SELECT ST_GeogPoint(-87.63, 41.88) AS center, 50 AS maxn_stations, 50 AS maxdist_km), distance_from_center AS (SELECT id, name, state, ST_GeogPoint(longitude, latitude) AS loc, ST_Distance(ST_GeogPoint(longitude, latitude), params.center) AS dist_meters FROM `bigquery-public-data.ghcn_d.ghcnd_stations`, params WHERE ST_DWithin(ST_GeogPoint(longitude, latitude), params.center, params.maxdist_km*1000)) SELECT * from distance_from_center</pre>

B.3 SPIDER 2.0 DATABASE EXAMPLES

Google Analytics 4 serves as a notable example of a Spider 2.0 database (see Fig. 13). For each Google Analytics 4 property and linked Firebase project enabled for BigQuery export, a dataset named `analytics_{property_id}` is created. Within the dataset, daily tables named `events_YYYYMMDD` are generated when the Daily export option is enabled.

To accommodate latency, Google Analytics 4 updates these daily tables for up to three days with late-arriving events, ensuring proper timestamping. Each column in these tables represents specific event parameters, some of which are nested within RECORDS and may be repeated. For instance, the `item_params` RECORD stores custom item parameters unique to each implementation.




Figure 13: Google analytics 4 database schema with nested record.

Fig. 14 showcases an example of an enterprise-level real-world database environment from Spider 2.0, with multiple schemas to navigate through, each of them containing a variety of tables. It highlights the complex structure types of Spider 2.0 databases, which exemplifies how our benchmark encompasses a broader and more intricate variety compared to others.




Figure 14: Bigquery database environment with multiple schema and tables.

B.4 EXAMPLES OF EXTERNAL DOCUMENTS

In this section, we present the external documents utilized in Spider 2.0. The first is a table that outlines the categorization method for traffic channels. The original document provided an HTML table, which we present here in Fig. 15. The second document is the Google Page Category as shown in Fig. 16, which demonstrates how to classify a page into categories such as Product List Page and Product Detail Page.

Channel	Conditions
Direct	Source exactly matches "(direct)" AND Medium is one of ("not set"), "(none)"
Cross-network	Campaign Name contains "cross-network" Cross-network includes Demand Gen, Performance Max and Smart Shopping.
Paid Shopping	Source matches a list of shopping sites (alibaba, amazon, google shopping, shopify, etsy, ebay, stripe, walmart) OR Campaign Name is of-z)\ shop\ shopping.*)\$ AND Medium matches regex ^\(.+cp.*\ ppc\ retargeting\ paid.*)\$
Paid Search	Source matches a list of search sites (baidu,bing,duckduckgo,ecosia,google,yahoo,yandex) AND Medium matches regex ^\(.+cp.*\ ppc\
Paid Social	Source matches a regex list of social sites (badoo,facebook,fb,instagram,linkedin,pinterest,tiktok,twitter,whatsapp) AND Medium matches regex ^\(.+cp.*\ ppc\ retargeting\ paid.*)\$
Paid Video	Source matches a list of video sites (dailymotion,disneyplus,netflix,youtube,vimeo,twitch,vimeo,youtube) AND Medium matches regex ^\(.+cp.*\ ppc\ retargeting\ paid.*)\$
Display	Medium is one of ("display", "banner", "expandable", "interstitial", "cpm")
Organic Shopping	Source matches a list of shopping sites (alibaba,amazon,google shopping,shopify,etsy,ebay,stripe,walmart) OR Campaign name matches z)\ shop\ shopping.*)\$
Organic Social	Source matches a regex list of social sites (badoo,facebook,fb,instagram,linkedin,pinterest,tiktok,twitter,whatsapp) OR Medium is of "social-network", "social-media", "sm", "social network", "social media")
Organic Video	Source matches a list of video sites (dailymotion,disneyplus,netflix,youtube,vimeo,twitch,vimeo,youtube) OR Medium matches regex ^\
Organic Search	Source matches a list of search sites (baidu,bing,duckduckgo,ecosia,google,yahoo,yandex) OR Medium exactly matches organic
Referral	Medium exactly matches Referral
Email	Source = email\ e-mail\ e_mail\ e mail OR Medium = email\ e-mail\ e_mail\ e mail
Affiliates	Medium = affiliate
Audio	Medium exactly matches audio
SMS	Source exactly matches sms OR Medium exactly matches sms
Mobile Push Notifications	Medium ends with "push" OR Medium contains "mobile" or "notification"
Unassigned	Others

Figure 15: Channel group of Google Analytics, external document for a bigquery example.

Product page category

Refined Page Classification Criteria

Overview

To enhance our understanding of user engagement on our e-commerce platform, we differentiate between two types of pages based on the URL structure: Product Listing Pages (PLPs) and Product Detail Pages (PDPs). These classifications are crucial for analyzing user behavior and improving site navigation efficiency.

Product Listing Pages (PLPs)

PLPs are identified by specific characteristics in the URL:

- The URL must be divided into at least five segments.
- Neither the fourth nor the fifth segment contains a '+' sign, ensuring these are not detail views.
- The fourth or fifth segment must contain one of the following category names, indicating a broader category or collection page rather than a specific product focus:
 - Accessories - Apparel - Brands - Campus Collection - Drinkware - Electronics - Google Redesign - Lifestyle - Nest - New 2015 Logo - Notebooks & Journals - Office - Shop by Brand - Small Goods - Stationery - Wearables

Product Detail Pages (PDPs)

PDPs, which focus on individual products, are marked by:

- A URL split into at least five segments, akin to PLPs.
- The presence of a '+' sign in the last segment, a common marker for detailed product pages.
- The fourth or fifth segment must also include one of the specified category names, ensuring that the detail being viewed pertains to one of the recognized product categories:
 - Accessories - Apparel - Brands - Campus Collection - Drinkware - Electronics - Google Redesign - Lifestyle - Nest - New 2015 Logo - Notebooks & Journals - Office - Shop by Brand - Small Goods - Stationery - Wearables

Conclusion

This detailed classification approach enables a more nuanced analysis of user pathways and interactions on our platform. By distinguishing between general browsing (PLPs) and targeted product interest (PDPs), we can tailor our content and design strategies to better meet the needs of our users, ultimately enhancing the shopping experience and improving business outcomes.

Figure 16: Page category document of Google analytics 4.

B.5 EXAMPLES OF CONTEXT SETUP

Besides the context setup method for the DBT project mentioned in App.B.2, we will outline the process for establishing the context in a example about query database.

1404 For the task, *Can you provide the details of the top 5 longest bike share trips that started during the*
 1405 *second half of 2017?*, ‘query.py’ serves as our predefined interface for interaction between the model
 1406 and the cloud database. This question is inherently ambiguous; without specifying the answer for-
 1407 mat constraints, evaluating the responses becomes challenging. Therefore, we provide “result.csv”,
 1408 which defines the required answer format.

```
1409 |--- README.md # The task description
1410 |--- query.py # The query interface
1411 |--- bigquery_credential.json # Bigquery credentials
1412 |--- result.csv # Answer format of data in November 2022
1413 -- result.csv
1414 trip_id,duration_sec,start_date,start_station_name,route,bike_number,
1415 subscriber_type,member_birth_year,age,age_class,member_gender,region_name
```

1416 For the examples presented in Tab. 12, we outline the setup details for the Spider 2.0 example.
 1417 Additionally, we provide answer examples for specific cases, which not only constrain the answer
 1418 format but also enable the agent to perform self-debugging using these examples.

1419 The task instruction is *Provide the number of sessions and percentage breakdown by channel for*
 1420 *December 2020*. We supply ‘202011.csv’ and ‘202101.csv’ as demonstration answers. We envision
 1421 a real SQL writing scenario where the agent can first query November 2020 to check for consistency
 1422 with ‘202011.csv’. If discrepancies arise, the agent can identify that their SQL is incorrect and make
 1423 the necessary corrections. Note that this is not a task requirement; it is simply our belief that real
 1424 SQL writing has such a need, and we will not mandate that the model does this. We believe this
 1425 approach reflects a natural and realistic setting, although we only provide answer constraints for a
 1426 limited number of examples.

```
1428 |--- README.md # The task description
1429 |--- query.py # The query interface
1430 |--- BASIC_SQLs # SQL examples of google analytics
1431 |--- bigquery_credential.json # Bigquery credentials
1432 |--- 202012.csv # The predefined answer file,
1433 |--- 202101.csv # Answer format of data in January 2021
1434 |--- 202011.csv # Answer format of data in November 2022
1435 -- 202011.csv
1436 item_name,item_quantity
1437 Google Decal,103
1438 Google Clear Pen 4-Pack,81
1439 Google Mesh Bag Red,79
1440 Google Mini Kick Ball,77
1441 Google Light Pen Red,8
1442 Google Laptop and Cell Phone Stickers,7
1443 Google Pen Neon Coral,7
1444 Google Metallic Notebook Set,7
1445 Google Pen Lilac,5
1446 Google Pen Red,5
```

1447 The query interface of Bigquery “query.py” is

```
1448 import os
1449 import pandas as pd
1450 from google.cloud import bigquery
1451 def query_data(sql_query, is_save, save_path="result.csv"):
1452     """
1453     Queries data from BigQuery based on the provided SQL query and handles the result.
1454     Args:
1455     sql_query (str): SQL query string to be executed.
1456     is_save (bool): If True, saves the query results to a CSV file at the specified save_path.
1457     If False, prints the results to the console.
1458     save_path (str): The file path where the results will be saved if is_save is True.
1459     Defaults to 'result.csv'.
1460     """
1461     os.environ["GOOGLE_APPLICATION_CREDENTIALS"] = "bigquery_credential.json"
1462     client = bigquery.Client()
1463     query_job = client.query(sql_query)
1464     try:
```

```

1458     results = query_job.result().to_dataframe()
1459     if results.empty:
1460         print("No data found for the specified query.")
1461     else:
1462         if is_save:
1463             results.to_csv(save_path, index=False)
1464             print(f"Results saved to {save_path}")
1465         else:
1466             print(results)
1467     except Exception as e:
1468         print("Error occurred while fetching data: ", e)
1469
1470 if __name__ == "__main__":
1471
1472     # Write your SQL query in the sql_query variable to interact with the database,
1473     #example SQL query related to this task is provided below
1474     sql_query = """
1475     SELECT
1476     *
1477     FROM
1478     `bigquery-public-data.ga4_obfuscated_sample_ecommerce.events_*`
1479     WHERE
1480     _TABLE_SUFFIX BETWEEN '20201201' AND '20201231'
1481     LIMIT 1
1482     """
1483     query_data(sql_query, is_save=True, save_path="result.csv")
1484
1485

```

1477 B.6 THE DIFFERENCE IN TASK INSTRUCTIONS BETWEEN SPIDER 2.0 AND SPIDER 2.0-LITE.

1478 During the annotation process, we found that *unambiguity* and *naturalness* are two mutually exclu-
1479 sive concepts. Therefore, in Spider 2.0-Lite, we emphasize unambiguity, while in Spider 2.0, we
1480 emphasize naturalness. The two instructional approaches restore the possible question forms that
1481 may arise in real-world text-to-SQL workflows.

1483 Example 1:

1484 Spider 2.0: The company management has requested a detailed report on the year-to-date perfor-
1485 mance of the Magnificent 7 stocks.

1486 Spider 2.0-lite: Please show the price change rate of the Magnificent 7 stocks from the beginning of
1487 this year to today.

1489 Example 2:

1490 Spider 2.0: Can you provide the details of the top 5 longest bike share trips that started during the
1491 second half of 2017?

1492 Spider 2.0-lite: Can you provide the details of the top 5 longest bike share trips that started during
1493 the second half of 2017, including the trip ID, duration in seconds, start date, start station name,
1494 route (start station to end station), bike number, subscriber type, member's birth year, age, age
1495 classification, gender, and the region name of the start station?

1497 Example 3:

1498 Spider 2.0: What's the no-tip percentage for NYC yellow taxi trips in each borough from January
1499 1-7, 2016, considering valid trips with at least one passenger and non-negative amounts?

1500 Spider 2.0-lite: For NYC yellow taxi trips between January 1-7, 2016, could you tell me the percent-
1501 age of no tips in each borough. Ensure trips where the dropoff occurs after the pickup, the passenger
1502 count is greater than 0, and trip distance, tip, tolls, MTA tax, fare, and total amount are non-negative.

1504
1505
1506
1507
1508
1509
1510
1511

1512 B.7 SQL DIALECT DOCUMENTS COLLECTION

1513

1514

1515

1516

1517

1518

1519

1520

1521

1522

1523

1524

1525

1526

1527

1528

1529

1530

1531

1532

1533

1534

1535

1536

1537

1538

1539

1540

1541

1542

1543

1544

1545

1546

1547

1548

1549

1550

1551

1552

1553

1554

1555

1556

1557

1558

1559

1560

1561

1562

1563

1564

1565

The core of SQL dialects lies in different advanced functions and subtle syntax variations across SQL versions. To support retrieval-augmented agent frameworks, we crawled and pre-processed the function documents for different database systems from their official websites. The detailed statistics of the crawled web pages and parsed categories/functions are presented in Tab. 17. Note that, functions belonging to the same category (e.g., aggregate functions like COUNTIF and STRING_AGG) may be introduced in the same paragraph in some web pages. In this case, we re-use the description on this shared function category for different concrete functions.

Table 17: Statistics of different database systems on Spider 2.0. Notice that, [†] means there is no well-defined function list in the official web pages for Postgres, thus we merely use the summarized document for each function category.

Database	Documentation Website	# Page	# Category	# Function
BigQuery	https://cloud.google.com/bigquery/docs/reference/standard-sql/functions-and-operators	34	34	390
Snowflake	https://docs.snowflake.com/en/sql-reference/	719	30	719
Postgres	https://www.postgresql.org/docs/current/functions.html	30	30	30 [†]
Clickhouse	https://clickhouse.com/docs/en/sql-reference/functions	226	6	226
SQLite	https://www.sqlite.org/docs.html	6	6	147
DuckDB	https://duckdb.org/docs/sql/functions/overview	24	24	513
Total		1039	130	2025

1536

1537

1538

1539

1540

1541

B.7.1 PROCESSED FUNCTIONS FOR DIFFERENT DATABASE SYSTEMS

In this section, we demonstrate examples of parsed documents for different database systems. These pre-parsed chunks can be retrieved and inserted into the prompt to compensate agents for their deficiencies in SQL dialect knowledge.

1544

1545

1546

1547

1548

1549

1550

1551

1552

1553

1554

1555

1556

1557

1558

1559

1560

1561

1562

1563

1564

1565

Document of BigQuery Functions

```
database="BigQuery", function="ST_INTERSECTS", category="geography-functions"
```

```
## ST_INTERSECTS
```

```
ST_INTERSECTS(geography_1, geography_2)
```

```
**Description**
```

```
Returns `TRUE` if the point set intersection of `geography_1` and `geography_2` is non-empty. Thus, this function returns `TRUE` if there is at least one point that appears in both input `GEOGRAPHY` s.
```

```
If `ST_INTERSECTS` returns `TRUE`, it implies that `ST_DISJOINT` returns `FALSE`.
```

```
**Return type**
```

```
`BOOL`
```

Document of Postgres Functions

1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619

```
database="Postgres", function_category="enum-support-functions"
```

For enum types (described in Section 8.7), there are several functions that allow cleaner programming without hard-coding particular values of an enum type. These are listed in Table 9.35. The examples assume an enum type created as:

```
CREATE TYPE rainbow AS ENUM ("red", "orange", "yellow", "green",  
"blue", "purple");
```

Table 9.35. Enum Support Functions

Function	Description	Example(s)
<code>enum_first (anyenum)</code>	→ anyenum Returns the first value of the input enum type.	<code>enum_first(null::rainbow) → red</code>
<code>enum_last (anyenum)</code>	→ anyenum Returns the last value of the input enum type.	<code>enum_last(null::rainbow) → purple</code>
<code>enum_range (anyenum)</code>	→ anyarray Returns all values of the input enum type in an ordered array.	<code>enum_range(null::rainbow) → red,orange,yellow,green,blue,purple</code>
<code>enum_range (anyenum, anyenum)</code>	→ anyarray Returns the range between the two given enum values, as an ordered array. The values must be from the same enum type. If the first parameter is null, the result will start with the first value of the enum type. If the second parameter is null, the result will end with the last value of the enum type.	<code>enum_range("orange"::rainbow, 'green'::rainbow) → orange,yellow,green</code> <code>enum_range(NULL, "green"::rainbow) → red,orange,yellow,green</code> <code>enum_range("orange"::rainbow, NULL) → orange,yellow,green,blue,purple</code>

Notice that except for the two-argument form of `enum_range`, these functions disregard the specific value passed to them; they care only about its declared data type. Either null or a specific value of the type can be passed, with the same result. It is more common to apply these functions to a table column or function argument than to a hardwired type name as used in the examples.

1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673

```
database="Snowflake", function="ATAN2", category="numeric-functions"
```

Categories: Numeric functions (Trigonometric)

ATAN2

Computes the inverse tangent (arc tangent) of the ratio of its two arguments.
For example, if $x > 0$, then the expression $\text{ATAN2}(y, x)$ is equivalent to $\text{ATAN}(y/x)$.
The arc tangent is the angle between:

The X axis.
The ray from the point (0,0) to the point (X, Y) (where X and Y are not both 0).

See also: ATAN

Syntax

$\text{ATAN2}(\langle y \rangle, \langle x \rangle)$

Copy Note that the first parameter is the Y coordinate, not the X coordinate.

Arguments

y This parameter is the Y coordinate of the point at the end of the ray. The data type is DOUBLE.

x This parameter is the X coordinate of the point at the end of the ray. The data type is DOUBLE.

Returns

The data type of the returned value is DOUBLE.
The returned value is in radians, not degrees.
The returned value is a number in the interval $[-\pi, \pi]$.

Usage notes

If the data type of an argument is a numeric data type other than DOUBLE, then the value is converted to DOUBLE.

If the data type of an argument is string, the value is converted to DOUBLE if possible.

If the data type of an argument is any other data type, the function returns an error.

If either argument is NULL, the returned value is NULL.

Examples

```
SELECT ATAN2(5, 5);
```

```
-----+
ATAN2(5, 5) |
-----+
0.7853981634 |
-----+
```

Document of DuckDB Functions

```
database="DuckDB", function="datediff", category="date-functions"
```

Function: `datediff(part, startdate, enddate)`

The number of partition boundaries between the dates. Alias of `date_diff`.

Description: The number of partition boundaries between the dates.

Example: `datediff('month', DATE '1992-09-15', DATE '1992-11-14')`

Result: 2

Alias: `date_diff`.

Document of SQLite Functions

1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727

```
database="SQLite", function="group_concat (X, Y)", category="aggregate-functions"
```

Function: group_concat(X,Y)

Usage: group_concat(X) group_concat(X,Y) string_agg(X,Y)

Description: The group_concat() function returns a string which is the concatenation of all non-NULL values of X. If parameter Y is present then it is used as the separator between instances of X. A comma (",") is used as the separator if Y is omitted.

The string_agg(X,Y) function is an alias for group_concat(X,Y). String_agg() is compatible with PostgreSQL and SQL-Server and group_concat() is compatible with MySQL.

The order of the concatenated elements is arbitrary unless an ORDER BY argument is included immediately after the last parameter.

Document of Clickhouse Functions

```
database="Clickhouse", function="JSONHas", category="json-functions"
```

```
## JSONHas
```

If the value exists in the JSON document, 1 will be returned. If the value does not exist, 0 will be returned.

```
### Syntax
```

```
JSONHas(json [, indices_or_keys]...)
```

```
### Parameters
```

```
json
```

- JSON string to parse. String

```
indices_or_keys
```

- A list of zero or more arguments, each of which can be either string or integer. String, Int*.

```
indices_or_keys
```

```
type:
```

String = access object member by key.

Positive integer = access the n-th member/key from the beginning.

Negative integer = access the n-th member/key from the end.

```
### Returned value
```

Returns 1 if the value exists in json , otherwise 0. UInt8.

```
### Examples
```

```
Query:
```

```
SELECT JSONHas('{ "a": "hello", "b": [-100, 200.0, 300] }', 'b') = 1
```

```
SELECT JSONHas('{ "a": "hello", "b": [-100, 200.0, 300] }', 'b', 4) = 0
```

The minimum index of the element is 1. Thus the element 0 does not exist. You may use integers to access both JSON arrays and JSON objects. For example:

```
SELECT JSONExtractKey('{ "a": "hello", "b": [-100, 200.0, 300] }', 1) = 'a'
```

```
SELECT JSONExtractKey('{ "a": "hello", "b": [-100, 200.0, 300] }', 2) = 'b'
```

```
SELECT JSONExtractKey('{ "a": "hello", "b": [-100, 200.0, 300] }', -1) = 'b'
```

```
SELECT JSONExtractKey('{ "a": "hello", "b": [-100, 200.0, 300] }', -2) = 'a'
```

```
SELECT JSONExtractString('{ "a": "hello", "b": [-100, 200.0, 300] }', 1) = 'hello'
```

B.8 EXTEND DATASET STATISTIC

Database scope. As shown in Fig. 17, the databases utilized in Spider 2.0 encompass a wide array of domains and real-world scenarios, providing a notable degree of diversity.

Data types. As depicted in Fig. 18, the Spider 2.0 database encompasses a wide variety of data types, including text-based data types including STRING and BOOLEAN, number-based like INTEGER and FLOAT, structured data as STRUCT, JSON, time-related data such as TIMESTAMP, and spatial

1728 data like GEOGRAPHY in google bigquery datasets. The diversity and breadth of these data types
 1729 underscore the extensive complexity and wide-ranging nature of our benchmark database. This
 1730 variability is reflected in the SQL dialects and the intricacies of data handling, thereby presenting
 1731 significant challenges for SQL generation.

1732 **Keywords.** As shown in Fig. 19, due to the complexity of the SQL in the Spider 2.0 dataset and its
 1733 coverage of various dialects, it contains more SQL keywords than any previous datasets.

1734 **Number of Tables.** As shown in Fig. 19, the databases in Spider 2.0 contain more tables than
 1735 previous datasets. Additionally, each SQL query in Spider 2.0 requires joining more tables on
 1736 average.

1737 **Data Volume.** The databases used in Spider 2.0 contain significantly larger data volumes. In com-
 1738 parison, each database in WikiSQL has only 17 rows, Spider 1.0 contains 2K rows, KaggleDBQA
 1739 has 280K rows, and BIRD has 549K rows. In contrast, the average database in Spider 2.0 has
 1740 **5273.42M rows**, with many databases reaching **TB-level** sizes.





Figure 18: Data types of Spider 2.0 database.

Figure 17: Domain distribution of Spider 2.0 database.




Figure 19: A comparative statistical analysis of SQL queries in Spider 2.0 and previous text-to-SQL benchmarks.

1777 C DETAILS OF EXPERIMENTS

1779 C.1 SPIDER-AGENT FRAMEWORK

1780 Inspired by React (Yao et al., 2022) and Intercode (Yang et al., 2023), we developed an agent frame-
 1781 work called Spider-Agent, which is primarily focused on database-related coding tasks and projects.

1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835




Figure 20: A comparison of SQL examples selected based on the median token length for Spider 2.0 and previous text-to-SQL benchmarks. Spider 2.0 examples were selected with token counts at the median, while examples from the other four datasets were selected from the original papers.

The framework allows for multi-turn interactions with the database via command-line interfaces until the final answer is obtained. To ensure the agent focuses solely on interacting with the database, as shown in Tab. 18, we designed a set of specialized actions. We use a temperature of 1.0 and top-p of 0.9 and truncate from the beginning of the input if still exceeding the max tokens limit required by the models.

The model automatically terminates if it outputs the same result three times in a row or if any action takes longer than 120 seconds. The prompts used in the experiments are provided in App.C.6. We heuristically request the agents to complete the tasks within a max step limit of 30, which is enough for most tasks.

Table 18: The action space of Spider-Agent, an agent baseline method for Spider 2.0.

Action	Description
BASH	Executes shell commands, such as checking file information, running code, or executing DBT commands.
CreateFile	Creates a new file with specified content.
EditFile	Edits or overwrites the content of an existing file.
ExecuteSQL	Executes a SQL query on BigQuery/Snowflake, with an option to print or save the results.
GetTables	Retrieves all table names and schemas from a specified BigQuery/Snowflake dataset.
GetTabInfo	Retrieves detailed column information for a specific table in BigQuery/Snowflake.
SampleRows	Samples a specified number of rows from a BigQuery/Snowflake table and saves them as JSON.
FAIL	Agent decides the task is infeasible.
Terminate	Agent decides the task is finished.

The number of joins does not have a direct correlation with model performance. For Tab. 21, there was no clear correlation observed between performance and the number of joins. We speculate that this is due to the fact that during the SQL annotation process, we ensured that all examples were quite complex, which made performance independent of the number of tables in SQL involved.

Action analysis of Spider-Agent. We analyze the results of Spider-Agent. For all correctly completed tasks, the agent needed an average of 9.0 steps (with a maximum of 17 steps and a minimum of 6 steps) within the defined action space to achieve the desired result. We also analyze the frequency with which actions are invoked at each turn by Spider-Agent, as shown in Fig. 22.




Figure 21: The effect of the number of *Join* on performance.




Figure 22: The frequency with which actions are invoked at each turn by Spider-Agent w/ o1-Preview for task instances that it solved on the Spider 2.0 (286 trajectories).

C.2 DETAILS OF SPIDER 2.0-LITE EXPERIMENTS

Details of baseline methods. LLM-based text-to-SQL methods have demonstrated exceptional zero-shot reasoning and domain generalization capabilities. DIN-SQL (Pourreza & Rafiei, 2024)




Figure 23: An example of prompt organization given by DAIL-SQL. prompt components that tailored to Spider 2.0-lite are highlighted. All these prompt components are similarly implemented for all other evaluated baseline methods including DIN-SQL, CHESS and CodeS.

employs task decomposition and adaptive prompting strategies tailored to task complexity. DAIL-SQL (Gao et al., 2024) achieves the best EX on Spider through elaborately designed prompt optimizations and in-context learning. CHESS (Talaie et al., 2024) integrates schema filtering based on entity and context retrieval, and SQL revision, achieving the best EX on BIRD. CodeS (Li et al., 2024a) fine-tunes open-source code generation models on extensive text-to-SQL corpora, obtaining performance comparable to methods that are based on prompting LLMs.

The treatment for sampled cell values. Spider 2.0-lite contains various complex data types, such as nested structures (RECORDED) or array (REPRATED) in BigQuery). if we only provide data type indicators, it is challenging for models to correctly process these types by appropriate SQL functions. Therefore, we provide sampled cell values (in markdown format) from each table in the prompt for all evaluated methods.

The treatment for value linking. During evaluation, we do not perform value linking (entity retrieval in CHESS, value retriever in CodeS) when solving instances from BigQuery, as the API cost of retrieving all values from a terabyte-scale cloud database is prohibitively expensive. Since value linking is crucial for identifying entities in filter conditions, its omission may hinder performance. Exploring cost-efficient methods for value linking or alternative approaches is an important direction for future work.

LLM. Given the extensive length of prompts after serializing large-scale schemas, we default to using GPT-4o, which supports a 128K context window, as the base LLM. Specifically for CHESS, we use GPT-3.5-turbo for column filtering to reduce costs.

Temperature. For all methods, we set the temperature of the LLM to 0 to ensure the reproducibility of the results.

Table 19: Average cost per instance across all methods.

Method	Avg. Cost (\downarrow)
Spider-Agent + o1-preview	0.75 \$
Spider-Agent + GPT-4-Turbo	0.58 \$
Spider-Agent + GPT-4o	0.32 \$
DIN-SQL + GPT-4o	0.14 \$
DAIL-SQL + GPT-4o	0.09 \$
DAIL-SQL + o1-preview	0.32 \$
CHESS + GPT-4o	0.43 \$
SFT CodeS-15B	0.00 \$

C.3 DETAILS OF ERROR ANALYSIS

We summarize the descriptions for all error categories in Fig. 24.

Error Type	Subcategory	Description	Example of Predicted SQL	Example of Gold SQL
Wrong Schema Linking	Wrong Table	Some of the requested tables are incorrect or do not exist, or excessive tables are requested, or some ground truth tables are missing.	FROM spider2-public-data.wide_world_importers.sales_customers c JOIN spider2-public-data.wide_world_importers.sales_orders o ON c.CustomerID = o.CustomerID JOIN spider2-public-data.wide_world_importers.sales_invoices i ON c.CustomerID = i.CustomerID	FROM spider2-public-data.wide_world_importers.sales_customers cu INNER JOIN spider2-public-data.wide_world_importers.sales_orders' o ON cu.CustomerID = o.CustomerID INNER JOIN spider2-public-data.wide_world_importers.sales_invoices' oi ON o.OrderID = oi.OrderID INNER JOIN spider2-public-data.wide_world_importers.sales_invoices' inv ON oi.OrderID = inv.OrderID) Orders
	Wrong Column	Some of the requested columns are incorrect or do not exist, or excessive columns are requested, or some ground truth columns are missing.	WITH Yearly_Delivered_Orders AS (SELECT strftime("Y", order_purchase_timestamp) AS year, ...	WITH monthly_order_counts AS (SELECT strftime("Y", order_delivered_customer_date) AS Year, ...
Erroneous Data Analysis	Incorrect Dialect Function Usage	Incorrect or missing use of dialect-specific functions for string manipulation (e.g., CONCAT), date processing (e.g., DATE_TRUNC), or geographic data (e.g., ST_DISTANCE), etc.	SELECT ... (LAG(longitude, 1) OVER (ORDER BY iso_time ASC) - longitude) AS lon_diff (LAG(latitude, 1) OVER (ORDER BY iso_time ASC) - latitude) AS lat_diff FROM hurricane_data	SELECT ... ST_DISTANCE(geom, LAG(geom, 1) OVER (BY sid ORDER BY iso_time ASC)) / 1000 AS dist FROM hurricane_geometry
	Incorrect Data Calculation	Advanced data calculations fail to meet the intended outcomes, often due to errors in grouping, aggregation (e.g., AVG, SUM), window functions (e.g., PARTITION BY, NTILE), or formula application (e.g., CORR, STDDEV).		Refer to Fig. 7(a)
	Incorrect Planning	The gold SQL involves nested queries, intermediate result processing through CTEs, or set operations for merging sub-query results. The model either fails to recognize or misuses these elements.		Refer to Fig. 7(b)
Join Error		The JOIN condition selects the incorrect tables or columns.	SELECT ... FROM spider2-public-data.wide_world_importers.sales_invoices t1 JOIN spider2-public-data.wide_world_importers.sales_invoices t2 ON t1.OrderID = t2.InvoiceID	SELECT ... FROM spider2-public-data.wide_world_importers.sales_invoices' AS INV1 INNER JOIN spider2-public-data.wide_world_importers.sales_invoices' AS INV2 ON INV1.InvoiceID = INV2.InvoiceID
Condition Filter Error		The filtering conditions in the WHERE clause are incorrectly defined.	WHERE code.coding[OFFSET(0)].code IN ('4404000', '3004000')	WHERE code.coding[safe_offset(0)].display = 'Diabetes' OR code.coding[safe_offset(0)].display = 'Hypertension'
Misunderstanding External Knowledge		The model misinterprets external knowledge relevant to the question.		Refer to Fig. 25
Excessive Prompt Length		The input prompt exceeds the LLM's maximum length, causing truncation and making the answer inaccessible.		-
Syntax Error		The generated SQL query contains invalid syntax that prevents execution.		-

Figure 24: Descriptions and examples for all error categories.

C.4 EXPERIMENTS COST

We summarize the average cost of API calls for each instance across different methods in Tab. 19.

C.5 CASE STUDY OF SPIDER-AGENT

In this section, we present the success and fail cases on Spider 2.0 using the o1-preview and Spider-Agent framework.

1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051

Question:

Please find out what percentage of the page views on January 2, 2021, were for **PDP type pages**.

Gold SQL:

```

WITH base_table AS (
  -- categorizing Page Titles into PDPs and PLPs
  -- pulls relevant columns from
  -- relevant dates
  SELECT
    event_name,
    event_date,
    ...
  FROM
    'bigquery-public-
data.ga4_obfuscated_sample_ecom
merce.events_*'
  WHERE
    _table_suffix = '20210102'
  AND event_name IN ('page_view')
),
unnested_events AS (
  -- unnests event parameters to
  -- get to relevant keys and values
  SELECT
    MAX(CASE WHEN c.key =
'page_title' THEN
c.value.string_value END) AS
page_title,
    MAX(CASE WHEN c.key =
'page_location' THEN
c.value.string_value END) AS
page_location
  FROM
    base_table,
    UNNEST (event_params) c
  GROUP BY 1,2,3
),
unnested_events_categorised AS (
  SELECT
    *,
    CASE WHEN
      ARRAY_LENGTH(SPLIT(page_location, '/')) >= 5
      AND
      CONTAINS_SUBSTR(ARRAY_REVERSE(SPLIT(page_location,
'/')[SAFE_OFFSET(0)], '+') AND
      (LOWER(SPLIT(page_location,
'/')[SAFE_OFFSET(4)]) IN
      ('accessories','apparel','brands',..., 'wearables')
      OR LOWER(SPLIT(page_location,
'/')[SAFE_OFFSET(3)]) IN
      ('accessories','apparel','brands',..., 'wearables'))
    THEN 'PDP'
    WHEN
      NOT(CONTAINS_SUBSTR(ARRAY_REVERSE(SPLIT(page_locat
ion, '/')[SAFE_OFFSET(0)], '+') AND
      (LOWER(SPLIT(page_location, '/')[SAFE_OFFSET(4)])
      IN
      ('accessories','apparel','brands',..., 'wearables')
      OR LOWER(SPLIT(page_location, '/')[SAFE_OFFSET(3)])
      IN
      ('accessories','apparel','brands',..., 'wearables'))
    THEN 'PLP'
    ELSE page_title
  END AS page_title_adjusted
  FROM
    unnested_events
),
SELECT (SELECT COUNT(*) FROM
unnested_events_categorised WHERE
page_title_adjusted='PDP') / (SELECT COUNT(*) FROM
unnested_events_categorised)*100;

```

Predicted SQL:

```

SELECT
  (COUNT IF(
    event_dimensions.hostname LIKE '%%' AND
    REGEXP_CONTAINS(SPLIT(event_dimensions.hostname, '/') [OFFSET(3)],
    r'Accessories|Apparel|Brands|Campus Collection|Drinkware|Electronics|Google
    Redesign|Lifestyle|Nest|New 2015 Logo|Notebooks & Journals|Office|Shop by
    Brand|Small Goods|Stationery|Wearable')
  ) / COUNT(*) * 100
  AS pdp_percentage
FROM
  bigquery-public-data.ga4_obfuscated_sample_ecommerce.events_20210102
WHERE event_name = 'page_view'
AND event_date = '20210102';

```

External Knowledge:

Refined Page Classification Criteria

Overview

To enhance our understanding of user engagement on our e-commerce platform, we differentiate between two types of pages based on the URL structure: **Product Listing Pages (PLPs)** and **Product Detail Pages (PDPs)**. These classifications are crucial for analyzing user behavior and improving site navigation efficiency.

Product Listing Pages (PLPs)

PLPs are identified by specific characteristics in the URL:

- The first segment doesn't contain a '+' sign, ensuring these are not detail views.
- The fourth or fifth segment must contain one of the following category names, indicating a broader category or collection page rather than a specific product focus:

- | | |
|---------------------|------------------------|
| • Accessories | • Nest |
| • Apparel | • New 2015 Logo |
| • Brands | • Notebooks & Journals |
| • Campus Collection | • Office |
| • Drinkware | • Shop by Brand |
| • Electronics | • Small Goods |
| • Google Redesign | • Stationery |
| • Lifestyle | • Wearables |

Product Detail Pages (PDPs)

PDPs, which focus on individual products, are marked by:

- The URL must be divided into at least five segments.
 - The presence of a '+' sign in the first segment, a common marker for detailed product pages.
 - The fourth or fifth segment must also include one of the specified category names, ensuring that the detail being viewed pertains to one of the recognized product categories:
- Accessories
 - ...
 - Wearables

Gold Result:

f0_

Predicted Result:

pdp_percentage

Figure 25: An example of **Misunderstanding External Knowledge**. The error in predicted SQL stems from the failure to correctly interpret the external knowledge provided for classifying PDP and PLP pages. While the predicted SQL uses a simple pattern-matching approach with regular expressions, it overlooks key aspects of the classification rules, such as the specific URL structure and the position of a '+' sign, which indicates the misunderstanding when trying to leverage the external knowledge.

2052 Fig. 26 shows a success case of google patents data. The Spider-Agent receives feedback from
 2053 executed queries, allowing it to iteratively refine SQL queries until it achieves a bug-free result.
 2054 Automated iterative debugging is one of the key advantages of Spider-Agent.

2055 Fig. 27 shows a success case where Spider-Agent successfully solves a DBT project example. It
 2056 first explores the codebase and database, locates where the code needs to be added, writes two
 2057 SQL scripts, debugs, and runs the DBT command, ultimately completing the data transformation
 2058 successfully.

2059 Fig. 28 shows a failure case where the agent fails to explore the codebase and locate key information
 2060 about monthly recurring revenue, resulting in an incorrect SQL query.
 2061

2062 Fig. 29 presents a failure case where the model reads the document but fails to transform the complex
 2063 document strings into an accurate SQL query.

2064 Fig. 30 illustrates a failure where the model cannot comprehend the database format with nested
 2065 columns, leading to multiple unsuccessful attempts at writing the correct code.
 2066

Success case 1: about patents analysis

2067
 2068
 2069 ### 17 Steps

2070 **Action 0:** Bash(code="ls")

2071 **Action 1:** Bash(code="cat README.md")

2072 **Action 2:** BQ_GET_TABLES(database_name="patents-public-data", dataset_name="patents",
 2073 save_path="dataset_metadata.csv")

2074 **Action 3:** BQ_GET_TABLE_INFO(database_name="patents-public-data", dataset_name="patents", ta-
 2075 ble="publications", save_path="publication_info.csv")

2076 **Action 4:** BQ_EXEC_SQL(sql_query=..., is_save=False)

2077 **Observation-4:** Error occurred while fetching data: 400 No matching signature for function DATE Argu-
 2078 ment types: INT64 Signature: DATE(TIMESTAMP, [STRING]) Argument 1: Unable to coerce type INT64
 to expected type TIMESTAMP

2079 **Thought-4:** The error indicates that I'm trying to use the DATE function on an INT64 field, which is
 2080 invalid. The date fields in the dataset are stored as integers in YYYYMMDD format. I need to convert these
 2081 integer date fields to DATE using the PARSE_DATE function. I'll update my SQL query to properly parse
 2082 the dates and include the condition for published applications.
 2083

2084 **Action-14:** BQ_EXEC_SQL(sql_query=..., is_save="/workspace/result.csv")

2085 **Observation-14:** Error occurred while fetching data: 400 No matching signature for function DATE Argu-
 2086 ment types: INT64 Signature: DATE(TIMESTAMP, [STRING]) Argument 1: Unable to coerce type INT64
 to expected type TIMESTAMP

2087 **Action-15:** BQ_EXEC_SQL(sql_query=..., is_save="/workspace/result.csv")

2088 **Observation-15:** Now that the results are saved to /workspace/result.csv.

2089 **Action-16:** Terminate(output="result.csv")
 2090

2091 Figure 26: Success case 1. After multiple rounds of SQL writing and repeated debugging, the correct
 2092 answer was obtained.
 2093
 2094
 2095
 2096
 2097
 2098
 2099
 2100
 2101
 2102
 2103
 2104
 2105

2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159

Success case 2

20 Steps

.....

Action 3: Bash(code="ls models/salesforce")

Action 4: Bash(code="cat models/salesforce/salesforce.yml")

Action 5: Bash(code="cat models/salesforce/salesforce__manager_performance.sql")

Action 6: Bash(code="ls models/salesforce/intermediate")

Action 7: Bash(code="cat models/salesforce/intermediate/int_salesforce__opportunity_aggregation_by_owner.sql")

Action 8: LOCAL_DB_SQL(file_path="salesforce.duckdb", command="SHOW TABLES;", output="direct")

Action 9: LOCAL_DB_SQL(file_path="salesforce.duckdb", command="SHOW TABLES;", output="direct")

Action 10: CreateFile(filepath=models/salesforce/salesforce__daily_sales_activity.sql':date_spine as (selectdate_day as activity ...)

Action 11: Bash(code="dbt run")

Observation 11: I noticed warnings during 'dbt run' indicating that 'salesforce__daily_activity' is not found. Since we don't have a model named 'salesforce__daily_activity', I should remove references to it from 'salesforce.yml'. Additionally, I need to add the new model 'salesforce__daily_sales_activity' to 'salesforce.yml' with appropriate descriptions

.....

Action 15: LOCAL_DB_SQL(file_path="salesforce.duckdb", command="SELECT * FROM salesforce__daily_sales_activity LIMIT 5;", output=direct)

.....

Action 18: Bash(code="dbt run")

Action 19: Terminate(output="salesforce.duckdb")

Figure 27: Success Case 2. After multiple rounds of file and DBT operations, the data transformation task has been successfully resolved.

2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210
2211
2212
2213

Failure case 1

```

Action 1: Bash(code="ls -R")
Action 2: Bash(code="cat models/customer_churn_month.yml")
Action 3: Bash(code="cat models/customer_churn_month.sql")
Action 4: EditFile(filepath="models/customer_churn_month.sql"):
.....
Action 5: Bash(code="cat models/mrr.yml")
Action 6: Bash(code="cat models/mrr.sql")
Action 7: EditFile(filepath="models/mrr.sql"):

with unioned as (
  select * from {{ ref('customer_revenue_by_month') }}
  union all
  select * from {{ ref('customer_churn_month') }}
),
lagged_values as (
  select
    *,
    coalesce(
      lag(is_active) over (partition by customer_id order by date_month), false
    ) as previous_month_is_active,
    coalesce( lag(mrr) over (partition by customer_id order by date_month), 0
    ) as previous_month_mrr
  from unioned
)
select
  date_month, customer_id, mrr, is_active,
  case
    when previous_month_is_active = false and is_active = true then 'New_Business'
    when previous_month_is_active = true and is_active = true and mrr_change > 0 then 'Expansion'
    when previous_month_is_active = true and is_active = true and mrr_change < 0 then 'Contraction'
    when previous_month_is_active = true and is_active = false then 'Churn'
    when previous_month_is_active = true and is_active = true and mrr_change = 0 then 'Renewal'
    when previous_month_is_active = false and is_active = false then 'Resurrection'
    else 'Other'
  end as change_category
from lagged_values

Action 8: Bash(code="dbt run")
Action 9: LOCAL_DB_SQL(file_path="mrr.duckdb", command="SELECT * FROM mrr LIMIT 5", out-
put="direct")

```

Figure 28: Failure case 1. Reasonable data transformation process, but did not follow our predefined category type.

2214
2215
2216
2217
2218
2219
2220
2221
2222
2223
2224
2225
2226
2227
2228
2229
2230
2231
2232
2233
2234
2235
2236
2237
2238
2239
2240
2241
2242
2243
2244
2245
2246
2247
2248
2249
2250
2251
2252
2253
2254
2255
2256
2257
2258
2259
2260
2261
2262
2263
2264
2265
2266
2267

Failure case 2

Action 1: Bash(code="ls -R")

Action 2: Bash(code="cat README.md ga4_page_category.md")

Action 3: BQ_GET_TABLES(database_name="bigquery-public-data",
dataset_name="ga4_obfuscated_sample_ecommerce",save_path="dataset_metadata.csv")

Action 4: Bash(code="cat dataset_metadata.csv")

Action 5: BQ_GET_TABLE_INFO(database_name="bigquery-public-data",dataset_name="ga4_obfuscated_sample_ecommerce", table="events_20210109", save_path="ga4_info.csv")

```
WITH pdp_pages AS (
  SELECT
    event_params.value.string_value AS page_location
  FROM
    `bigquery-public-data.ga4_obfuscated_sample_ecommerce.events_20210102`,
    UNNEST(event_params) AS event_params
  WHERE
    event_name = 'page_view'
    AND event_params.key = 'page_location'
    AND REGEXP_CONTAINS(event_params.value.string_value, r'
      \/[^\|]+\.[^\|]+\.[^\|]+\.[^\|]+\.[^\|]+*\/')
    AND REGEXP_CONTAINS(event_params.value.string_value, r'\/(Accessories|Apparel|Brands|Campus_Collection|
      Drinkware|Electronics|Google_Redesign|Lifestyle|Nest|New_2015_Logo|Notebooks_&_Journals|Office|
      Shop_by_Brand|Small_Goods|Stationery|Wearables)\/')
),
total_page_views AS (
  SELECT
    COUNT(*) AS total_views
  FROM
    `bigquery-public-data.ga4_obfuscated_sample_ecommerce.events_20210102`
  WHERE
    event_name = 'page_view'
)
SELECT
  (SELECT COUNT(*) FROM pdp_pages) * 100.0 / total_page_views.total_views AS pdp_percentage
FROM
  total_page_views
```

Action 9: Terminate(output="result.csv")

Figure 29: Failure case 2. Cannot ground the complex document into SQL.

Failure case 3

Action 1: Bash(code="ls -R")

Action 2: BQ_GET_TABLES(database_name="bigquery-public-data",
dataset_name="ga4_obfuscated_sample_ecommerce",save_path="dataset_metadata.csv")

Action 3: Bash(code="cat dataset_metadata.csv")

Action 4: BQ_GET_TABLE_INFO(database_name="bigquery-public-data",dataset_name="ga4_obfuscated_sample_ecommerce", table="events_20210109", save_path="ga4_info.csv")

```
SELECT
  event_timestamp,
  event_params.key,
  event_params.value.string_value AS page_location
FROM
  `bigquery-public-data.ga4_obfuscated_sample_ecommerce.events_20210128`,
  UNNEST(event_params) AS event_params
WHERE
  user_id = '1362228'
  AND event_date = '20210128'
ORDER BY
  event_timestamp
```

Action 9: Terminate(output="result.csv")

Figure 30: Failure case 3. Cannot understand the complex nested schema.

2268 C.6 PROMPTS OF SPIDER-AGENT
2269

2270 Following the ReAct (Yao et al., 2022) prompting framework, which guides models in breaking
2271 down complex problems into manageable steps through an iterative chain of reasoning (Reasoning),
2272 action (Action), and observation (Observation) phases, where the current state is observed after each
2273 action before proceeding to the next step of reasoning, we build the Spider-Agent. Below, we will
2274 introduce the system messages and actions used within this framework.

2275 **System Prompt**
2276

2277 **System Prompt**

2278 You are a data scientist proficient in database, SQL and DBT Project. You are starting in the `{work_dir}`
2279 directory, which contains all the data needed for your tasks. You can only use the actions provided in the
2280 **action space** to solve the task.

2281 **### [Action space]: {action prompts}**

2282 **### [Notice]**

- 2283 1. First, run "ls" to check the current folder for files. If there are other markdown files, read them as they
2284 may contain useful information.
2285 2. Examine the database schema folder, you fully understand the structure schema of the database.
2286 3. Use appropriate SQL execution action to run queries.
2287 4. Be prepared to write multiple SQL queries to find the correct answer. If an error occurs, revisit the
2288 database information and previous queries to adjust your SQL accordingly.
2289 5. Ensure the results are valid. If the result.csv file is empty or only contains a header, the SQL query is
2290 incorrect. The final result should be either saved as a CSV or directly provided as a text answer, not an
2291 intermediate step or SQL statement.
2292 6. After completing the task, verify the output data against the definitions. For dbt projects, after writing the
2293 SQL, run dbt run to update the database and confirm the new data models meet the YAML file definitions.

2294 **### [Response format]**

2295 For each task input, your response should contain:

- 2296 1. One analysis of the task and the current environment, reasoning to determine the next action (prefix
2297 "Thought: ").
2298 2. One action string in the ACTION SPACE (prefix "Action: ").

2299 **### [Example interaction]**

2300 Observation: ...(the output of last actions, as provided by the environment and the code output, you don't
2301 need to generate it)

2302 Thought: ...

2303 Action: ...

2304 **### [Task]: {Task}**
2305

2306 **Action Space Prompt**

2307 **Bash**

2308 **## Bash Action**

2309 * Signature: Bash(code="shell_command")

2310 * Description: This action string will execute a valid shell command in the code field. Only non-interactive
2311 commands are supported. Commands like "vim" and viewing images directly (e.g., using "display") are
2312 not allowed.

2313 * Example: Bash(code="ls -l")
2314

2315 **CreateFile**

2316 **## CreateFile Action**

2317 * Signature: CreateFile(code="shell_command")

2318 * Description: This action string will execute a valid shell command in the 'code' field. Only non-interactive
2319 commands are supported. Commands like "vim" and viewing images directly (e.g., using "display") are not
2320 allowed.

2321 * Example: CreateFile(code="ls -l")

2322
2323
2324
2325
2326
2327
2328
2329
2330
2331
2332
2333
2334
2335
2336
2337
2338
2339
2340
2341
2342
2343
2344
2345
2346
2347
2348
2349
2350
2351
2352
2353
2354
2355
2356
2357
2358
2359
2360
2361
2362
2363
2364
2365
2366
2367
2368
2369
2370
2371
2372
2373
2374
2375

EditFile

```
## EditFile
* Signature: EditFile(filepath="path/to/file"):
  \ \ \
File_content
  \ \ \
* Description: This action will overwrite the file specified in the filepath field with the content wrapped in
paired symbols. Normally, you need to read the file before deciding to use EditFile to modify it.
* Example: EditFile(filepath="hello_world.py"):
  \ \ \
print("Hello, world!")
  \ \ \
```

BIGQUERY_EXEC_SQL

```
## BIGQUERY_EXEC_SQL
* Signature: BIGQUERY_EXEC_SQL(sql_query="SELECT * FROM your_table", is_save=True,
save_path="/workspace/output_file.csv")
* Description: Executes a SQL query on Google Cloud BigQuery. If 'is_save' is True, the results are saved
to a specified CSV file; otherwise, results are printed. If you estimate that the number of returned rows is
small, you can set is_save=False, to directly view the results. If you estimate that the number of returned
rows is large, be sure to set is_save = True. The 'save_path' CSV must be under the '/workspace' directory.
* Examples:
- Example1: BIGQUERY_EXEC_SQL(sql_query="SELECT count(*) FROM sales", is_save=False)
- Example2: BIGQUERY_EXEC_SQL(sql_query="SELECT user_id, sum(purchases) FROM transactions
GROUP BY user_id", is_save=True, save_path="/workspace/result.csv")
```

GET_TABLES

```
## GET_TABLES
* Signature: GET_TABLES(database_name="your_database_name", dataset_name="your_dataset_name",
save_path="path/to/output_file.csv")
* Description: Executes a query to fetch all table names and their corresponding DDL from the specified
dataset in Google Cloud BigQuery. The results are saved to the specified CSV file.
- The BigQuery id of a table is usually in the form of database_name.dataset_name.table_name. This action
mainly focuses on the tables under dataset_name.
* Examples:
- Example1: GET_TABLES(database_name="bigquery-public-data", dataset_name="new_york",
save_path="dataset_metadata.csv")
```

GET_TABLES_INFO

```
## GET_TABLE_INFO Action
* Signature:
GET_TABLE_INFO(database_name="your_database_name", dataset_name="your_dataset_name", ta-
ble="table_name", save_path="path/to/output_file.csv")
* Description: Executes a query to fetch all column information (field path, data type, and description) from
the specified table in the dataset in Google Cloud BigQuery. The results are saved to the specified CSV file.
- The BigQuery id of a table is usually in the form of database_name.dataset_name.table_name.
* Examples:
- Example1: GET_TABLE_INFO(database_name="bigquery-public-data", dataset_name="samples", ta-
ble="shakespeare", save_path="shakespeare_info.csv")
```

SAMPLE_ROWS

```
## SAMPLE_ROWS Action
* Signature:
SAMPLE_ROWS(database_name="your_database_name", dataset_name="your_dataset_name", ta-
ble="table_name", save_path="path/to/output_file.csv")
* Description: Executes a query to fetch all column information (field path, data type, and description) from
the specified table in the dataset in Google Cloud BigQuery. The results are saved to the specified CSV file.
- The BigQuery id of a table is usually in the form of database_name.dataset_name.table_name.
* Examples:
```

2376
2377
2378
2379
2380
2381
2382
2383
2384
2385
2386
2387
2388
2389
2390
2391
2392
2393
2394
2395
2396
2397
2398
2399
2400
2401
2402
2403
2404
2405
2406
2407
2408
2409
2410
2411
2412
2413
2414
2415
2416
2417
2418
2419
2420
2421
2422
2423
2424
2425
2426
2427
2428
2429

- Example1: `SAMPLE_ROWS(database_name="bigquery-public-data", dataset_name="samples", table="shakespeare", save_path="shakespeare_info.csv")`