

From Recall to Forgetting: Benchmarking Long-Term Memory for Personalized Agents

Anonymous ACL submission

Abstract

Personalized agents that interact with users over long periods must maintain persistent memory across sessions and update it as circumstances change. However, existing benchmarks predominantly frame long-term memory evaluation as fact retrieval from past conversations, providing limited insight into whether models can consolidate memory over time or handle frequent knowledge updates. We introduce Memora, a long-term memory benchmark spanning weeks to months long user conversations. The benchmark evaluates three memory-grounded tasks: remembering, reasoning, and recommending. To ensure data quality, we employ automated memory-grounding checks and human evaluation. We further introduce Forgetting-Aware Memory Accuracy (FAMA), a metric that penalizes reliance on obsolete or invalidated memory when evaluating long-term memory. Evaluations of four LLMs and six memory agents show frequent reuse of invalid memories and failures to reconcile evolving memories. Memory agents offer marginal improvements, exposing shortcomings in long-term memory for personalized agents.

1 Introduction

Large Language Models (LLMs) have rapidly advanced as general-purpose systems, demonstrating strong capabilities in reasoning (Huang and Chang, 2023), instruction following (Xu et al., 2023; Wen et al., 2024), generating high-quality content (Liang et al., 2024), and adapting across diverse tasks (Radford et al., 2019; Kojima et al., 2022). These advances have fueled growing interest in deploying LLMs as personalized assistants (Yuan et al., 2025), tutors (Chen et al., 2024), and life-long companions (Zhang et al., 2025). However, despite their apparent fluency, current LLMs remain fundamentally constrained due to the lack of persistent long-term memory (Zhong et al., 2023; Wu et al., 2025). By default, LLMs are stateless across interactions (Mei et al., 2025). Although

Long-Term Memory Dataset	Memory Consolidation		Memory Mutation	
	Avg.	Max.	Avg.	Max.
PerLTQA (2024)	1.0	1.0	0.0	0.0
MemDaily (2024b)	3.3	8.0	0.0	0.0
LOCOMO (2024)	1.3	15.0	0.0	0.0
LongMemEval (2024)	1.9	6.0	2.0	2.0
PersonaMem (2025)	1.3	3.0	1.2	3.0
Memora (Weekly)	5.3	26.0	2.7	11.0
Memora (Monthly)	17.3	99.0	8.8	43.0
Memora (Quarterly)	28.4	309.0	14.8	94.0

Table 1: Comparison of benchmarks on two key long-term memory challenges. *Memory consolidation* measures the number of past sessions whose information must be integrated to answer a query, and *memory mutation* measures the number of updates or deletes across sessions before querying. We report both average (Avg.) and maximum (Max.) values across evaluation questions. Memora places substantially higher demands on both challenges under three temporal durations.

models maintain a key-value cache during a single interaction to preserve short-term context, this internal state is discarded once the interaction ends. As a result, information shared by users in previous conversations such as preferences, plans, corrections, or goals is not retained unless it is explicitly reintroduced. This limitation prevents LLMs from behaving as persistent assistants that can maintain interaction over days, weeks, or months.

Human cognition provides a clear contrast. People naturally remember prior conversations (Brown-Schmidt et al., 2025), integrate information across time (Mazurek et al., 2003), revise beliefs when new evidence arises (Hogarth and Einhorn, 1992), and discard outdated knowledge (Bekinschtein et al., 2018; Ye et al., 2020). Long-term memory is not defined solely by recalling (Ericsson and Kintsch, 1995), but by the ability to accumulate experiences (Meeter and Murre, 2004), reconcile changes (Wood et al., 2012), and maintain a coher-




Figure 1: The three tasks of the Memora benchmark: 1) **Remembering**: recalling and leveraging discussed facts in response, such as to-dos, 2) **Reasoning**: integrating multiple pieces of information to derive a specific answer, for example, calculating the grocery budget status, and 3) **Recommending**: suggesting relevant items or actions based on the user’s evolving preferences, like proposing The Grand Budapest Hotel after the user grew bored of Christopher Nolan’s movies. Each task depends on selectively extracting and reusing relevant information from non-contiguous, temporally distant sessions, emphasizing long-term memory beyond recent context.

ent mental model of the world (Jones et al., 2011). For conversational agents to approximate this behavior, they must support not only remembering past information, but also consolidating memory across many interactions and mutating memory as circumstances evolve.

Despite growing interest in long-term memory, existing benchmarks (Maharana et al., 2024; Du et al., 2024; Jiang et al., 2025) primarily operationalize it as shallow cross-session retrieval rather than sustained memory accumulation. In LoCoMo (Maharana et al., 2024) 94% of the evaluation questions require grounding evidence from no more than two previous sessions. We observe the same pattern for 85% of the evaluation questions in LongMemEval (Wu et al., 2024). Consistent with these observations, Table 1 shows that average memory consolidation across benchmarks is approximately one session. This skewed distribution means that the majority of evaluation reduces to whether a model can recall an isolated piece of information introduced in a prior, rather than synthesizing information accumulated over extended interaction histories. Also, this retrieval-centric framing implicitly assumes that stored information remains permanently valid. In contrast, real-world long-term interaction is non-stationary: user information is updated, corrected, or withdrawn over

time. Therefore long-term memory requires not only recalling past information, but also correct handling of memory mutation. However, as shown in Table 1, prior benchmarks place minimal stress on memory mutation. LongMemEval (Wu et al., 2024) includes knowledge-update operations, but limits them to at most two sessions before evaluation and PersonaMem (Jiang et al., 2025) handles updates across no more than three sessions. As a result, models are rarely required to reconcile multiple revisions of the same information or to track how user state evolves over extended timelines.

To address these gaps, we introduce Memora, a benchmark that models long-term memory as a continuous and evolving process rather than static retrieval. Memora increases demands on both memory consolidation and mutation by requiring models to integrate information across weekly, monthly, and quarterly conversation sessions. Figure 1 shows that Memora evaluates three memory-grounded tasks, remembering, reasoning, and recommending, all require respecting the temporal validity of users’ long-term memory.

Beyond dataset design, Memora also revisits how long-term memory should be evaluated. Existing evaluations largely reward memory inclusion, measuring whether relevant information appears in a model’s response. This overlooks memory mis-

119 use, where obsolete information is retrieved and
120 used. As long as the final answer appears correct,
121 reliance on invalidated memory is not penalized. To
122 address this, we introduce Forgetting-Aware Mem-
123 ory Accuracy (FAMA), an evaluation metric that
124 explicitly accounts for invalid memories. FAMA
125 measures whether a model’s response reflects the
126 user’s current memory state by rewarding correct
127 use of valid memory and penalizing reliance on ob-
128 solete or deleted memory. This enables evaluation
129 of memory mutation over long interaction histories.
130 Using Memora, we evaluate four LLMs and six
131 long-term memory agents. Despite extended con-
132 text windows and external memory mechanisms,
133 our results reveal persistent failures in maintaining
134 consistent belief states under high consolidation
135 and mutation pressure. Models frequently reuse ob-
136 solete information, and memory agents offer only
137 limited improvements. In summary, our main con-
138 tributions are:

- Introducing Memora, a benchmark that sub-
stantially increases demands on both memory
consolidation and memory mutation across
weekly, monthly and quarterly durations.
- Proposing Forgetting-Aware Memory Accu-
racy (FAMA), an evaluation metric that penal-
izes reliance on outdated memories.
- Empirical evaluation of LLMs and long-term
memory agents, revealing limitations in main-
taining consistent memory states.

149 These contributions position Memora as a rigorous
150 benchmark for studying long-term memory. By
151 jointly stressing memory consolidation, frequent
152 memory mutation, and forgetting-aware evaluation,
153 Memora exposes failure modes that remain hidden
154 under retrieval-centric benchmarks.

155 2 Related Works

156 Long-term memory addresses a fundamentally dif-
157 ferent problem than long-context modeling (Bai
158 et al., 2024; Zhang et al., 2024a; Hsieh et al., 2024).
159 In realistic settings, placing the entire interaction
160 history into the prompt is impractical (Lewis et al.,
161 2020; Packer et al., 2023) and often counterproduc-
162 tive (Liu et al., 2024; Du et al., 2025). Effective
163 agents (Park et al., 2023) must depend on persis-
164 tent and updatable long-term memory mechanisms,
165 rather than simply increasing context length.

166 Early long-term conversational memory bench-
167 marks relied on a limited session histories (Xu et al.,
168 2022a). As context windows expanded, later bench-

169 marks primarily emphasized scaling conversation
170 length and explicit memory probing, including tar-
171 getted recall of personal facts (Zhong et al., 2024;
172 Du et al., 2024), question answering and summa-
173 rization over long multi-session dialogues (Maha-
174 rana et al., 2024), narrative-driven recall in tv-series
175 dialogues (Kim et al., 2025), and million-tokens
176 long user–assistant conversations (Wu et al., 2024).

177 In parallel, another line of work frames long-
178 term memory primarily as personalization, aim-
179 ing to adapt system behavior to the individual
180 users over extended interactions. Early bench-
181 marks such as DuLeMon (Xu et al., 2022b) evalu-
182 ate persona-consistent dialogue generation. Per-
183 sonaMem (Jiang et al., 2025) shifts toward person-
184 alized decision-making by testing whether models
185 can infer evolving user states from long histories us-
186 ing multiple-choice questions. MemDaily (Zhang
187 et al., 2024b) models daily-life personal assis-
188 tant interactions and probes user-specific facts and
189 events. MemoryAgentBench (Hu et al., 2025) ex-
190 tends personalization-oriented memory evaluation
191 to agentic settings, highlighting competencies such
192 as retrieval, test-time learning, and forgetting.

193 Taken together, prior works have expanded the
194 scale and scope of long-term memory evaluation,
195 either by increasing conversation length or by fram-
196 ing memory as personalization. However, across
197 both lines of work, long-term memory is still pre-
198 dominantly operationalized as fact-retrieval from
199 past interactions, with relatively limited empha-
200 sis on memory consolidation and frequent mem-
201 ory mutation. As a result, it remains unclear how
202 well existing systems integrate information across
203 extended timelines or handle evolving and invali-
204 dated memory. Memora targets these challenges
205 by jointly stressing consolidation and mutation in
206 long-term memory evaluation.

207 3 Memora

208 Memora is constructed through a simulation-driven
209 pipeline that jointly generates long-term conversa-
210 tions and evaluation tasks. Starting from persona-
211 level seed data, the pipeline simulates user inter-
212 actions spanning weeks to months, converts these
213 interactions into multi-turn conversations, and de-
214 rives memory-grounded evaluation tasks. This de-
215 sign focuses on both memory consolidation and
216 memory mutation, requiring models to adhere to
217 the temporal validity of information across remem-
218 bering, reasoning, and recommendation tasks.

3.1 Seed Data Design

We construct ten professional persona profiles (*e.g.*, *software engineers, researchers, designers, executives*) consisting preference patterns, activity tendencies, and long-term goals. These personas serve as the semantic backbone of the benchmark. Memora models three user-centric memory types: *preference, activity, and goal memory*. Preference memory captures evolving users’ likes and dislikes across domains (*e.g.*, *movie, music, travel*). Activity memory represents what users’ do over time, encompassing both personal activities (*e.g.*, *expenses, fitness tracking, tasks*) and professional activities (*e.g.*, *drafting documents, managing meeting notes*). Goal memory encodes users’ long-term objectives (*e.g.*, *budgeting, fitness targets*). Memory evolution is controlled by operational and temporal constraints that control the chronological consistency across sessions. Further details are provided in the Appendix A.

3.2 Session Simulation

Given the seed data, a session simulator generates sequences of user interactions spanning weeks to months. The seed data defines the space of possible memory entities and the simulator determines when and how those entities are introduced, updated, or invalidated under explicit temporal and operational constraints. The simulator also includes memory-neutral sessions that do not introduce, modify, or delete any stored memories (*e.g.*, *casual conversations, clarifications*). This mixture follows interaction patterns observed in conversational benchmarks (Wu et al., 2024; Deshpande et al., 2025).

The simulator maintains a persistent memory state that is updated after every session. This enables dynamics such as preference drift (*e.g.*, *gradually losing interest in a favored director*), recurring activities (*e.g.*, *repeated activities logging*), and incremental progression of long-term tasks (*e.g.*, *refining a draft document across multiple sessions*). By recording the full memory state before and after each session, Memora produces explicit memory traces that precisely track how information is introduced, updated, and invalidated over time. These traces define the ground truth for downstream conversation generation and memory evaluation.

3.3 Conversation Generation

Building on the simulated session history, Memora converts each session specification into a multi-

	Weekly	Monthly	Quarterly
Number of Personas	10	10	10
Avg. Sessions Per Persona	155	615	1991
Avg. Turns Per Session	16.1	15.6	15.7
Avg. Memory Operations	103.2	374.3	1171.4
– Add (%)	68	63	63
– Update (%)	13	16	18
– Delete (%)	19	21	19
Memory-grounded Questions	150	150	300
Evaluation Criteria	749	1421	4884
Avg. pairwise 1-gram overlap ↓	0.144	0.144	0.126
Avg. pairwise 2-gram overlap ↓	0.027	0.026	0.027
Avg. pairwise 3-gram overlap ↓	0.011	0.011	0.010
Avg. SBERT cosine similarity ↓	0.275	0.272	0.281

Table 2: Memora statistics and conversation diversity across different temporal spans. The top block summarizes the dataset scale and memory dynamics. The bottom block reports conversation diversity using pairwise lexical overlap and semantic similarity.

turn dialogue using a controlled, multi-agent conversation generation framework. The framework supports two types of conversational turns: 1) memory-neutral turns, which involve general interaction not related to memory (*e.g.*, *casual questions, acknowledgments*), and 2) memory-grounded turns, in which the user expresses information corresponding to the simulated memory operation.

An intent selection module determines a sequence of user and assistant intents (*e.g.*, *greeting, memory disclosure, follow-up*). Conversations are organized into a multi-phase interaction consisting of an opening phase, an exploration phase, a memory phase where the target operation is expressed, and a closing phase. Dialogue turns are generated using a multi-agent prompting setup with separate user and assistant roles conditioned on persona traits, selected intents, memory entities, and prior conversation context.

LLM-based generation does not always strictly adhere to instructions given in the prompt and may introduce plausible but untracked memory details beyond the simulated session specification. To address this, all generated conversations are checked through an automated memory-grounding evaluation loop. The grounding checks verify that the intended memory operation and the entity is correctly expressed in the conversation, and no additional information is introduced. Each conversation is independently evaluated by three LLMs and accepted only if all agree. Otherwise feedback is shared and the conversation is regenerated. This iterative process promotes close alignment between generated conversations and the underlying mem-




Figure 2: Overview of the Memora construction pipeline. The process begins with structured seed data (persona profiles, memory types, constraints) that drives the session simulation module to produce a long session history. Conversations are generated by multiple LLM agents and an auto-eval loop checks coherence and memory grounding. Rigorous validation checkpoints, including both internal mechanisms (LLM Voting) and external human evaluation, filter the generated data for quality and correctness before forming the final benchmark.

ory trace. In addition to automated checks, we randomly sample 5% of generated conversations per persona for human verification. If annotators identify any inconsistency between the conversation and the memory trace, the entire batch is rejected. Further details are provided in the Appendix B.

3.4 Conversation Diversity in Memora

Table 2 also summarizes conversation scale and linguistic diversity across weekly, monthly, and quarterly timeline. Generated conversations exhibit low average pairwise n-gram overlap, indicating minimal template reuse and broad lexical coverage. Low average SBERT cosine similarity shows that diversity extends beyond surface form to semantic content. Together, these results demonstrate that Memora generates linguistically diverse conversations without collapsing into formulaic patterns.

3.5 Questions and Evaluation Criteria

Memora constructs evaluation questions directly from the simulated memory traces. Questions are organized into three tasks: *Remembering*, *Reasoning*, and *Recommending*. Remembering questions test direct recall of stored information (e.g., *generating documents*), Reasoning questions require synthesizing information (e.g., *evaluating goal progress*), and Recommending questions assess whether personalized suggestions reflect the user’s current preferences rather than outdated ones (e.g., *recommending a movie after preference changes*).

Each question is paired with explicit evaluation criteria derived from the same memory trace, specifying which memory items must be included and which invalidated items must be excluded.

3.6 Final Dataset

The final Memora dataset comprises validated multi-session conversations, memory-grounded evaluation questions, and evaluation criteria anchored in explicit memory traces for each persona. Correct responses require integrating information across multiple sessions while avoiding invalidated memories, enabling fine-grained analysis of long-term memory beyond surface-level accuracy.

4 Experiments

We evaluate long-term memory behavior on Memora under two settings: 1) large language models operating directly over extended conversational histories, and 2) long-term memory agents that explicitly store and retrieve user information across sessions. These settings isolate different mechanisms for maintaining memory and allow us to assess whether systems produce responses consistent with the user’s current memory state.

4.1 Evaluation Settings

Model-Based Evaluation: We evaluate LLMs by providing multi-session conversation histories (as permitted by the context window) and asking them

Models / Agents	Remembering			Recommending			Reasoning		
	Weekly	Monthly	Quarterly	Weekly	Monthly	Quarterly	Weekly	Monthly	Quarterly
<i>Language Models (w/o Reasoning Tokens)</i>									
Qwen3-32B	26.12	21.14	19.24	50.16	50.30	48.88	6.00	2.00	6.00
Claude Sonnet 4.5	27.50	19.42	21.25	43.62	39.00	44.02	6.66	3.00	5.50
Gemini 3 Pro Preview	20.36	21.44	17.28	45.12	45.94	52.56	6.66	4.00	4.00
GPT-5.2	25.32	19.92	23.39	54.80	51.12	53.36	4.66	0.00	1.00
<i>Language Models (w/ Reasoning Tokens)</i>									
Qwen3-32B	23.86	25.62	17.14	50.04	53.06	47.71	6.66	9.00	3.00
Claude Sonnet 4.5	26.56	21.40	19.13	52.40	60.90	51.78	4.00	0.00	2.50
Gemini 3 Pro Preview	21.02	23.26	18.12	43.36	44.92	50.83	6.00	10.00	8.50
GPT-5.2	25.70	19.22	22.16	53.40	51.60	53.36	4.66	0.00	2.00
<i>Long-Term Memory Agents</i>									
A-Mem	71.82	41.90	40.78	35.04	37.52	34.95	2.00	2.00	5.00
LangMem	71.16	42.00	39.14	48.88	44.08	33.85	30.00	14.00	11.00
Mem-0	40.42	21.08	19.90	52.58	36.20	38.47	16.00	0.00	2.00
MemoBase	43.60	20.08	15.18	68.94	58.46	45.62	18.00	7.00	1.00
MemoryOS	51.84	29.78	25.05	62.64	48.54	44.02	20.66	6.00	5.50
Nemori	65.06	44.08	33.83	52.84	45.90	41.66	18.66	0.00	6.50

Table 3: Aggregated Forgetting-Aware Memory Accuracy (FAMA) scores on the Memora, reported across three memory-grounded tasks (Remembering, Recommending, Reasoning) and three temporal durations (weekly, monthly, quarterly). Agents perform best on remembering and reasoning remains difficult across all systems.

to answer memory-grounded questions. This setting isolates models’ ability to consolidate long interaction histories without external memory modules. We evaluate four LLMs: GPT-5.2, Claude Sonnet 4.5, Gemini 3 Pro Preview, and Qwen3-32B. They are tested under both standard and reasoning-enabled inference to assess whether reasoning tokens improves memory under frequent updates.

Agent-Based Evaluation: We evaluate systems with long-term memory agents that incrementally ingest conversations, retrieve relevant memories at query time, and generate responses conditioned on retrieved memories. We include representative memory systems spanning local vector stores, cloud-based memory APIs, profile-driven memories, and stateful agents, evaluated under identical conversations. The long-term memory agents are A-Mem, LangMem, Mem-0, MemoBase, MemoryOS, Nemori. All agents use the same LLM (GPT-4o-mini) backend for answer generation.

4.2 Forgetting-Aware Memory Evaluation

Memora evaluates responses using atomic, memory-aligned criteria derived from the user’s current memory state. We have two groups of evaluation criteria: memory presence, which checks whether valid information is included, and forgetting absence, which checks whether invalidated or deleted information is excluded. This distinguishes correct reliance on memory from erroneous reuse of obsolete memory, which standard accuracy metrics do not capture.

Each evaluation criterion is assessed independently using a multi-LLM judge protocol. Given a model response and a single criterion, three judges, GPT-4.1, Claude Haiku 4.5, and Gemini 2.5 Flash, produce binary judgments, with final decisions determined by majority vote. This approach follows prior work establishing LLM as judge based evaluation for open-ended and long-context tasks (Bai et al., 2024; Maharana et al., 2024; Es et al., 2024). Further details are provided in the Appendix C.

To aggregate criterion-level judgments into a single score, we introduce Forgetting-Aware Memory Accuracy (FAMA), which measures alignment with the user’s current memory state. FAMA rewards correct use of valid memory while explicitly penalizing reliance on obsolete information:

$$\text{FAMA} = \text{MPA} - \lambda \cdot (1 - \text{FAA}),$$

where MPA denotes memory presence accuracy, FAA denotes forgetting absence accuracy.

$$\lambda = \frac{N_{\text{memory_forget}}}{N_{\text{memory_presence}} + N_{\text{memory_forget}}},$$

The weighting term λ scales the forgetting penalty according to the proportion of forgetting-related criteria. FAMA is bounded in $[0,1]$ for each evaluation question, with higher values indicating stronger alignment with the user’s memory state.

5 Results

We present the aggregated Forgetting-Aware Memory Accuracy (FAMA) results on Memora in the Table 3. The results reveal clear performance gaps be-




Figure 3: FAMA scores for remembering, recommending, and reasoning tasks. We report the results for the top three systems per task. Points denote mean scores, and error bars indicate variability across durations.




Figure 4: FAMA scores for weekly, monthly, and quarterly durations. We report results for the top three systems for each duration. Points denote mean scores, and error bars indicate variability across tasks.

tween large language models and long-term memory agents, showing that long-term memory consistency remains difficult to sustain as user information evolves over time. We next analyze these results at the task and temporal levels.

Performance Across Tasks: Aggregating performance across the temporal ranges, we observe clear performance differences across remembering, recommending, and reasoning tasks. This indicates that long-term memory capabilities are task-dependent. Memory agents dominate remembering tasks. Agents substantially outperform language models, achieving an aggregated FAMA of 119.6 compared to 65.6 for language models, regardless of reasoning tokens. FAMA scores in Figure 3 suggest that accurate recall does not translate into strong performance on more demanding tasks such as reasoning, highlighting the difficulty of maintaining and integrating information across interactions.

Recommending presents a contrasting outcome. Language models are competitive with memory agents (aggregated FAMA scores for LLM is 144.7 without reasoning, 153.3 with reasoning, 138.4 for agents). This advantage is largely attributable to differences in available context at inference time. Language models operate directly over long spans of recent conversational history, allowing them to leverage rich, implicit conversational signals when generating recommendations. Memory agents, by contrast, rely on selectively retrieved memory entries, limiting their ability to translate stronger recall into better recommendation quality.

Reasoning remains challenging across all systems. Aggregated scores are low for both language models and memory agents (14–15 vs. 27.3

FAMA). This indicates that integrating temporally distributed memories into coherent judgments remains largely unsolved.

Performance Across Temporal Durations: We aggregate FAMA scores across all three tasks within each temporal duration (weekly, monthly, and quarterly) in Figure 4. LangMem consistently achieves the strongest overall performance, ranking first in all three durations. In the weekly duration, the top-performing agents are LangMem, Nemori, and MemoryOS; in the monthly duration, LangMem, Nemori, and MemoBase; and in the quarterly duration, LangMem, A-Mem, and Nemori. This consistent ranking indicates that LangMem maintains the most stable performance as memory consolidation and mutation pressure increase. Despite these differences, performance degrades for all systems as temporal duration increases. Aggregate FAMA scores drop from approximately 128.4 in the weekly setting to 83.3 monthly and 73.7 quarterly across agents. This decline reflects the cumulative difficulty of maintaining an accurate memory state as interactions span longer horizons and memory updates accumulate. As timelines extend, systems increasingly reuse invalidated information or fail to suppress outdated memories, leading to larger forgetting penalties and lower FAMA scores.

The Role of Forgetting-Aware Evaluation: Standard memory evaluation based on memory presence overestimates long-term memory performance. These metrics evaluate the final response by checking whether required information appears, but they do not penalize the use of obsolete or invalidated memory. As a result, models can achieve high scores even when their responses conflate

past and current memory states. Table 4 shows the raw memory accuracy with Forgetting-Aware Memory Accuracy (FAMA). Across all language models and memory agents, applying forgetting-aware evaluation results in large score reductions. When aggregated across tasks, score reductions follow different trends for language models and memory agents. For language models, the reduction decreases as temporal range grows (from 32.6 weekly to 17.8 quarterly), not because memory improves, but because longer histories exceed the context window and relevant information is omitted altogether. Memory agents exhibit the opposite trend. Their score reductions increase with longer timelines (from 18.2 weekly to 29.5 quarterly), showing that as memory scales, systems increasingly rely on information that should have been revised or discarded. Retaining access to older memories without effective forgetting amplifies inconsistency. Consequently, systems that appear similar under memory accuracy receive different forgetting-based reductions, leading to changes in their final performance rankings.

6 Error Analysis

We conduct a manual error analysis over 75 incorrect predictions, randomly sampled across all temporal durations, with 25 samples per task. For each task, we analyze errors from the best-performing long-term memory agent. Recommendation errors are primarily driven by failure to forget outdated memory and partial memory retrieval. We found 16 of 25 errors (64%) were caused by outdated memory not being forgotten, and 7 of 25 (28%) errors involved partial retrieval of preferences. Agents often retrieve historical preferences while failing to apply recent updates. For example, A user initially preferred non-fiction books but later shifted toward contemporary fiction. When asked for a recommendation, the agent suggested a historical biography. Remembering errors are dominated by partial memory retrieval 18 of 25 errors (72%), often resulting in incomplete structured outputs. Agents retrieve some but not all required memory items. For example, A project summary request initially included objectives and deadlines, with collaborators and a risk assessment added later. The generated summary omitted the later-added items. Reasoning errors consistently involve partial retrieval that prevents consolidation. All reasoning errors (100%) involved incomplete retrieval of relevant memory

Models / Agents	Memory Accuracy (Δ FAMA)		
	Weekly	Monthly	Quarterly
<i>Language Models (w/o Reasoning Tokens)</i>			
Qwen3-32B	103.6 (-21.3)	83.0 (-9.7)	79.5 (-5.3)
Claude Sonnet 4.5	114.0 (-36.2)	100.2 (-34.1)	94.0 (-23.2)
Gemini 3 Pro P.	114.2 (-42.0)	110.6 (-39.4)	101.8 (-27.9)
GPT-5.2	115.4 (-30.7)	96.6 (-21.8)	92.5 (-14.7)
<i>Language Models (w/ Reasoning Tokens)</i>			
Qwen3-32B	98.7 (-18.8)	97.8 (-10.1)	79.5 (-11.6)
Claude Sonnet 4.5	114.0 (-31.0)	104.2 (-21.9)	83.2 (-9.8)
Gemini 3 Pro P.	113.5 (-43.2)	111.4 (-33.2)	95.8 (-18.6)
GPT-5.2	111.5 (-27.8)	97.4 (-26.5)	91.8 (-14.2)
<i>Long-Term Memory Agents</i>			
A-Mem	118.0 (-9.1)	112.0 (-29.5)	118.6 (-37.9)
LangMem	173.0 (-23.0)	132.2 (-31.1)	127.4 (-43.4)
Mem-0	119.4 (-10.4)	78.6 (-21.3)	72.7 (-12.3)
MemoBase	154.4 (-23.8)	107.2 (-21.6)	93.7 (-31.9)
MemoryOS	155.2 (-20.6)	112.8 (-28.4)	99.6 (-25.0)
Nemori	159.4 (-22.8)	105.4 (-15.4)	106.8 (-26.3)

Table 4: Total memory accuracy aggregated across tasks for each temporal duration (weekly, monthly, quarterly). Parenthesized values Δ FAMA indicate reductions due to reliance on invalidated or obsolete memory. Across all models and agents, FAMA consistently scores less, revealing the reliance on outdated memory that is not captured by memory accuracy metrics.

elements, preventing correct consolidation. For example, after logging multiple expenses under a monthly budget, agents responded with vague judgments (e.g., “within budget”) rather than computing the remaining amount.

In summary, error patterns are task-specific: recommending fails due to outdated or partial preferences, remembering fails due to incomplete retrieval, and reasoning fails because missing memory elements prevent consolidation. These highlight the need for task-aware memory mechanisms that jointly support retrieval, forgetting, and consolidation for long-term memory.

7 Conclusion

Memora serves as a controlled stress test that isolates key long-term memory challenges and enables more diagnostic evaluation. By grounding interactions in explicit memory traces, it assesses whether models maintain temporally consistent memory states rather than relying on isolated recall. We further introduce Forgetting-Aware Memory Accuracy (FAMA), which penalizes reliance on invalidated memory and exposes substantial performance gaps across both language models and memory agents that standard memory accuracy fails to capture. Together, these findings show that advancing long-term conversational memory will require mechanisms that explicitly integrate forgetting, consolidation, and mutation as first-class design principles.

567 Limitations

568 Memora aims to provide a controlled and chal-
569 lenging benchmark for long-term conversational
570 memory, which necessarily involves several de-
571 sign trade-offs. **First**, Memora relies on simulated
572 long-horizon conversations with explicit memory
573 creation, mutation, and deletion. While simula-
574 tion cannot fully capture the ambiguity and unpre-
575 dictability of real user interactions, collecting and
576 manually annotating real-world memory logs over
577 weeks or months is very costly. Such data would
578 require user consent, careful privacy handling, and
579 manual annotation of evolving user states, mak-
580 ing it difficult to scale or standardize. Importantly,
581 simulation does not simplify the task for evalu-
582 ated systems: models already struggle under these
583 controlled conditions. Since real deployments in-
584 troduce additional complexities such as implicit
585 updates and contradictory signals, Memora should
586 be viewed as a lower bound. Systems that fail in
587 simulation are unlikely to generalize to more com-
588 plex real-world settings, making the benchmark
589 a meaningful stress test despite its synthetic na-
590 ture. **Second**, Memora centers on a constrained set
591 of personas and memory categories (preferences,
592 activities, and goals) that are directly relevant to
593 personalized assistants. This scope excludes other
594 forms of long-term memory, such as social relation-
595 ships and multi-user coordination. We leave the
596 inclusion of richer social and relational memory
597 structures to future work. **Third**, evaluation relies
598 primarily on LLM-based judges with majority vot-
599 ing to ensure scalability. Although automated judg-
600 ing may introduce shared biases, using multiple
601 judge models and criterion-level decisions reduces
602 variance and dependence on any single evaluator.
603 **Finally**, we do not report runtime, latency, or effi-
604 ciency metrics. Participating systems rely on het-
605 erogeneous hardware and storage infrastructures,
606 making fair efficiency comparisons difficult. We
607 therefore focus on correctness and robustness of
608 memory usage rather than potentially misleading
609 performance measurements.

610 Ethical Considerations

611 The authors state that this work is in accordance
612 with the ACL Code of Ethics and does not raise eth-
613 ical issues. AI assistants, specifically Grammarly
614 and ChatGPT, were utilized to correct grammatical
615 errors and restructure sentences.

References

- 617 Yushi Bai, Xin Lv, Jiajie Zhang, Hongchang Lyu,
618 Jiankai Tang, Zhidian Huang, Zhengxiao Du, Xiao
619 Liu, Aohan Zeng, Lei Hou, Yuxiao Dong, Jie Tang,
620 and Juanzi Li. 2024. [LongBench: A bilingual, multi-
621 task benchmark for long context understanding](#). In
622 *Proceedings of the 62nd Annual Meeting of the As-
623 sociation for Computational Linguistics (Volume 1:
624 Long Papers)*, pages 3119–3137, Bangkok, Thailand.
625 Association for Computational Linguistics.
- 626 Pedro Bekinschtein, Noelia V Weisstaub, Francisco
627 Gallo, Maria Renner, and Michael C Anderson. 2018.
628 A retrieval-specific mechanism of adaptive forgetting
629 in the mammalian brain. *Nature Communications*,
630 9(1):4660.
- 631 Sarah Brown-Schmidt, Christopher Brett Jaeger, Kaitlin
632 Lord, and Aaron S Benjamin. 2025. Remembering
633 conversation in group settings. *Memory & Cognition*,
634 53(4):1037–1054.
- 635 Eason Chen, Jia-En Lee, Jionghao Lin, and Kenneth
636 Koedinger. 2024. [Gptutor: Great personalized tutor
637 with large language models for personalized learning
638 content generation](#).
- 639 Kaustubh Deshpande, Ved Sirdeshmukh, Johannes Bap-
640 tist Mols, Lifeng Jin, Ed-Yeremai Hernandez-
641 Cardona, Dean Lee, Jeremy Kritz, Willow E. Pri-
642 mack, Summer Yue, and Chen Xing. 2025. [Multi-
643 Challenge: A realistic multi-turn conversation eval-
644 uation benchmark challenging to frontier LLMs](#). In
645 *Findings of the Association for Computational Lin-
646 guistics: ACL 2025*, pages 18632–18702, Vienna,
647 Austria. Association for Computational Linguistics.
- 648 Yiming Du, Hongru Wang, Zhengyi Zhao, Bin Liang,
649 Baojun Wang, Wanjun Zhong, Zezhong Wang, and
650 Kam-Fai Wong. 2024. [PerLTQA: A personal long-
651 term memory dataset for memory classification, re-
652 trieval, and fusion in question answering](#). In *Pro-
653 ceedings of the 10th SIGHAN Workshop on Chinese
654 Language Processing (SIGHAN-10)*, pages 152–164,
655 Bangkok, Thailand. Association for Computational
656 Linguistics.
- 657 Yufeng Du, Minyang Tian, Srikanth Ronanki, Subendhu
658 Rongali, Sravan Babu Bodapati, Aram Galstyan, Az-
659 ton Wells, Roy Schwartz, Eliu A Huerta, and Hao
660 Peng. 2025. [Context length alone hurts LLM perfor-
661 mance despite perfect retrieval](#). In *Findings of the
662 Association for Computational Linguistics: EMNLP
663 2025*, pages 23281–23298, Suzhou, China. Associa-
664 tion for Computational Linguistics.
- 665 K Anders Ericsson and Walter Kintsch. 1995. Long-
666 term working memory. *Psychological review*,
667 102(2):211.
- 668 Shahul Es, Jithin James, Luis Espinosa Anke, and
669 Steven Schockaert. 2024. [RAGAs: Automated evalu-
670 ation of retrieval augmented generation](#). In *Proce-
671 edings of the 18th Conference of the European Chap-
672 ter of the Association for Computational Linguistics:*

673		<i>System Demonstrations</i> , pages 150–158, St. Julians, Malta. Association for Computational Linguistics.	
674			
675	Robin M Hogarth and Hillel J Einhorn. 1992. Order effects in belief updating: The belief-adjustment model .		
676		<i>Cognitive Psychology</i> , 24(1):1–55.	
677			
678	Cheng-Ping Hsieh, Simeng Sun, Samuel Kriman, Shantanu Acharya, Dima Rekesh, Fei Jia, Yang Zhang, and Boris Ginsburg. 2024. Ruler: What’s the real context size of your long-context language models?		
679			
680			
681			
682	Yuanzhe Hu, Yu Wang, and Julian McAuley. 2025. Evaluating memory in llm agents via incremental multi-turn interactions .		
683			
684			
685	Jie Huang and Kevin Chen-Chuan Chang. 2023. Towards reasoning in large language models: A survey .		
686		In <i>Findings of the Association for Computational Linguistics: ACL 2023</i> , pages 1049–1065, Toronto, Canada. Association for Computational Linguistics.	
687			
688			
689			
690	Bowen Jiang, Zhuoqun Hao, Young-Min Cho, Bryan Li, Yuan Yuan, Sihao Chen, Lyle Ungar, Camillo J Taylor, and Dan Roth. 2025. Know me, respond to me: Benchmarking llms for dynamic user profiling and personalized responses at scale . <i>arXiv preprint arXiv:2504.14225</i> .		
691			
692			
693			
694			
695			
696	Natalie A Jones, Helen Ross, Timothy Lynam, Pascal Perez, and Anne Leitch. 2011. Mental models: an interdisciplinary synthesis of theory and methods .		
697		<i>Ecology and society</i> , 16(1).	
698			
699			
700	Jiho Kim, Woosog Chay, Hyeonji Hwang, Daeun Kyung, Hyunseung Chung, Eunbyeol Cho, Yeonsu Kwon, Yohan Jo, and Edward Choi. 2025. Dialsim: A dialogue simulator for evaluating long-term multi-party dialogue understanding of conversational agents .		
701			
702			
703			
704			
705			
706	Takeshi Kojima, Shixiang Shane Gu, Machel Reid, Yutaka Matsuo, and Yusuke Iwasawa. 2022. Large language models are zero-shot reasoners . <i>Advances in neural information processing systems</i> , 35:22199–22213.		
707			
708			
709			
710			
711	Patrick Lewis, Ethan Perez, Aleksandra Piktus, Fabio Petroni, Vladimir Karpukhin, Naman Goyal, Heinrich Küttler, Mike Lewis, Wen-tau Yih, Tim Rocktäschel, et al. 2020. Retrieval-augmented generation for knowledge-intensive nlp tasks . <i>Advances in neural information processing systems</i> , 33:9459–9474.		
712			
713			
714			
715			
716			
717	Xun Liang, Hanyu Wang, Yezhaohui Wang, Shichao Song, Jiawei Yang, Simin Niu, Jie Hu, Dan Liu, Shunyu Yao, Feiyu Xiong, et al. 2024. Controllable text generation for large language models: A survey . <i>arXiv preprint arXiv:2408.12599</i> .		
718			
719			
720			
721			
722	Nelson F. Liu, Kevin Lin, John Hewitt, Ashwin Paranjape, Michele Bevilacqua, Fabio Petroni, and Percy Liang. 2024. Lost in the middle: How language models use long contexts . <i>Transactions of the Association for Computational Linguistics</i> , 12:157–173.		
723			
724			
725			
726			
	Adyasha Maharana, Dong-Ho Lee, Sergey Tulyakov, Mohit Bansal, Francesco Barbieri, and Yuwei Fang. 2024. Evaluating very long-term conversational memory of LLM agents . In <i>Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)</i> , pages 13851–13870, Bangkok, Thailand. Association for Computational Linguistics.		727 728 729 730 731 732 733 734
	Mark E Mazurek, Jamie D Roitman, Jochen Ditterich, and Michael N Shadlen. 2003. A role for neural integrators in perceptual decision making . <i>Cerebral cortex</i> , 13(11):1257–1269.		735 736 737 738
	Martijn Meeter and Jaap MJ Murre. 2004. Consolidation of long-term memory: evidence and alternatives . <i>Psychological Bulletin</i> , 130(6):843.		739 740 741
	Lingrui Mei, Jiayu Yao, Yuyao Ge, Yiwei Wang, Baolong Bi, Yujun Cai, Jiazhi Liu, Mingyu Li, Zhong-Zhi Li, Duzhen Zhang, et al. 2025. A survey of context engineering for large language models . <i>arXiv preprint arXiv:2507.13334</i> .		742 743 744 745 746
	Charles Packer, Vivian Fang, Shishir_G Patil, Kevin Lin, Sarah Wooders, and Joseph_E Gonzalez. 2023. Memgpt: Towards llms as operating systems .		747 748 749
	Joon Sung Park, Joseph C. O’Brien, Carrie J. Cai, Meredith Ringel Morris, Percy Liang, and Michael S. Bernstein. 2023. Generative agents: Interactive simulacra of human behavior .		750 751 752 753
	Alec Radford, Jeffrey Wu, Rewon Child, David Luan, Dario Amodei, Ilya Sutskever, et al. 2019. Language models are unsupervised multitask learners . <i>OpenAI blog</i> , 1(8):9.		754 755 756 757
	Bosi Wen, Pei Ke, Xiaotao Gu, Lindong Wu, Hao Huang, Jinfeng Zhou, Wenchuang Li, Binxin Hu, Wendy Gao, Jiaying Xu, et al. 2024. Benchmarking complex instruction-following with multiple constraints composition . <i>Advances in Neural Information Processing Systems</i> , 37:137610–137645.		758 759 760 761 762 763
	Rachel Wood, Paul Baxter, and Tony Belpaeme. 2012. A review of long-term memory in natural and synthetic systems . <i>Adaptive Behavior</i> , 20(2):81–103.		764 765 766
	Di Wu, Hongwei Wang, Wenhao Yu, Yuwei Zhang, Kai-Wei Chang, and Dong Yu. 2024. Longmemeval: Benchmarking chat assistants on long-term interactive memory . <i>arXiv preprint arXiv:2410.10813</i> .		767 768 769 770
	Yaxiong Wu, Sheng Liang, Chen Zhang, Yichao Wang, Yongyue Zhang, Huifeng Guo, Ruiming Tang, and Yong Liu. 2025. From human memory to ai memory: A survey on memory mechanisms in the era of llms .		771 772 773 774
	Can Xu, Qingfeng Sun, Kai Zheng, Xiubo Geng, Pu Zhao, Jiazhan Feng, Chongyang Tao, and Daxin Jiang. 2023. Wizardlm: Empowering large language models to follow complex instructions . <i>arXiv preprint arXiv:2304.12244</i> .		775 776 777 778 779

780	Jing Xu, Arthur Szlam, and Jason Weston. 2022a. Beyond goldfish memory: Long-term open-domain conversation . In <i>Proceedings of the 60th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)</i> , pages 5180–5197, Dublin, Ireland. Association for Computational Linguistics.	834
781		835
782		836
783		837
784		838
785		839
786	Xinchao Xu, Zhibin Gou, Wenquan Wu, Zheng-Yu Niu, Hua Wu, Haifeng Wang, and Shihang Wang. 2022b. Long time no see! open-domain conversation with long-term persona memory . In <i>Findings of the Association for Computational Linguistics: ACL 2022</i> , pages 2639–2650, Dublin, Ireland. Association for Computational Linguistics.	840
787		841
788		842
789		843
790		
791		
792		
793	Zhifang Ye, Liang Shi, Anqi Li, Chuansheng Chen, and Gui Xue. 2020. Retrieval practice facilitates memory updating by enhancing and differentiating medial prefrontal cortex representations. <i>Elife</i> , 9:e57023.	845
794		846
795		847
796		848
797	Ruifeng Yuan, Shichao Sun, Yongqi Li, Zili Wang, Ziqiang Cao, and Wenjie Li. 2025. Personalized large language model assistant with evolving conditional memory . In <i>Proceedings of the 31st International Conference on Computational Linguistics</i> , pages 3764–3777, Abu Dhabi, UAE. Association for Computational Linguistics.	849
798		850
799		851
800		852
801		853
802		
803		
804	Xinrong Zhang, Yingfa Chen, Shengding Hu, Zihang Xu, Junhao Chen, Moo Hao, Xu Han, Zhen Thai, Shuo Wang, Zhiyuan Liu, and Maosong Sun. 2024a. ∞Bench: Extending long context evaluation beyond 100K tokens . In <i>Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)</i> , pages 15262–15277, Bangkok, Thailand. Association for Computational Linguistics.	854
805		855
806		856
807		857
808		858
809		859
810		860
811		861
812		862
813	Yutong Zhang, Dora Zhao, Jeffrey T. Hancock, Robert Kraut, and Diyi Yang. 2025. The rise of ai companions: How human-chatbot relationships influence well-being .	863
814		864
815		865
816		866
817	Zeyu Zhang, Quanyu Dai, Luyu Chen, Zeren Jiang, Rui Li, Jieming Zhu, Xu Chen, Yi Xie, Zhenhua Dong, and Ji-Rong Wen. 2024b. Memsim: A bayesian simulator for evaluating memory of llm-based personal assistants . <i>arXiv preprint arXiv:2409.20163</i> .	867
818		868
819		869
820		870
821		
822	Wanjun Zhong, Lianghong Guo, Qiqi Gao, He Ye, and Yanlin Wang. 2023. Memorybank: Enhancing large language models with long-term memory .	871
823		872
824		873
825	Wanjun Zhong, Lianghong Guo, Qiqi Gao, He Ye, and Yanlin Wang. 2024. Memorybank: Enhancing large language models with long-term memory . In <i>Proceedings of the AAAI Conference on Artificial Intelligence</i> , volume 38, pages 19724–19731.	874
826		875
827		876
828		877
829		878
830		879
831		880
832		881
833		882
		883

A Seed Data Details

A.1 Personas

Memora is grounded in a set of ten professional personas, designed to induce diversity in long-term

memory evaluation and interaction patterns. Each persona represents a distinct professional role (e.g., software engineer, researcher, designer, executive) and serves as a stable semantic anchor throughout the conversation sessions. Table 5 details the ten personas and their assigned preference types. For instance, the Software Engineer is modeled with a preference for Sci-Fi media and Electronic music, whereas the Sales Manager is modeled with preferences for Action movies and Rock music.

A.2 Memory Types

Memora models long-term user state through three memory types: preference memory, activity memory, and goal memory. These categories are designed to jointly capture evolving behaviors and long-term objectives that arise in realistic personalized assistant usage. Each memory type exhibits distinct temporal dynamics and supports different evaluation tasks, enabling fine-grained analysis of memory consolidation, mutation, and forgetting.

Preference Memory: Preference memory encodes users’ likes and dislikes across entertainment and lifestyle domains. It serves as the primary signal for personalized recommendation tasks. Preferences are initialized from persona-specific archetypes and evolve gradually over time through additions, updates, and deletions. Preference memory spans four domains—movies, books, music, and travel—and includes a large inventory of candidate entities to prevent memorization or shortcut learning. Importantly, preference evolution is non-monotonic: users may reinforce existing preferences, weaken them, or reverse earlier statements. This design ensures that correct responses require sensitivity to temporal validity, rather than simply retrieving the earliest or most frequent preference mention.

Activity Memory: Activity memory captures what users do over time and represents the most dynamic and frequently updated memory type in Memora. It is explicitly divided into personal activity and work activity, reflecting how real users interleave daily routines with professional responsibilities. Personal activity memory includes recurring, time-indexed behaviors such as expense tracking, task management, and fitness-related activities. These activities are typically additive and incremental, supporting reasoning tasks that require aggregation or status evaluation over multiple sessions. Work activity memory models sus-

ID	Persona Role	Description	Key Preference Archetypes
1	Academic Researcher	Scholarly work, publications	Classic Film (Movie/Book), Jazz/Classical, Nature Travel
2	Business Executive	Strategy, operations	Classic Film, Non-fiction, Luxury Travel
3	Content Writer	Blogs, articles, copywriting	Indie Film, Classic Literature, Indie/Alternative Music, Cultural Travel
4	Creative Designer	Visual projects, artistic expression	Horror Film, Fiction, Indie/Alternative Music, Cultural Travel
5	Financial Analyst	Data analysis, financial planning	Sci-Fi Film, Non-fiction, Jazz/Classical, Luxury Travel
6	Management Consultant	Strategy, organizational improvement	Classic Film, Non-fiction, Cultural Travel
7	Marketing Manager	Campaign execution, brand strategy	Indie Film, Fiction, Pop/Mainstream Music
8	Sales Manager	Client relationships, revenue growth	Action Film, Thriller, Rock/Metal Music
9	Software Engineer	Coding, system architecture	Sci-Fi Film, Fantasy/Sci-Fi Literature, Electronic Music
10	Startup Founder	Innovation, scaling ventures	Sci-Fi Film, Non-fiction, Urban Travel

Table 5: Overview of the ten professional personas used in Memora, including each persona’s role, brief description, and associated preference archetypes. These personas serve as structured anchors for simulating long-term user behavior and evolving preferences in personalized assistant interactions.

884 tained professional actions, including drafting and
885 revising documents, composing emails, recording
886 meeting notes, and producing other work-related
887 artifacts. These activities often undergo multiple
888 revisions or deletions, creating long dependency
889 chains that stress memory consolidation and muta-
890 tion handling. By treating both personal and work
891 behaviors as activities rather than abstract records,
892 Memora emphasizes action-centered memory that
893 evolves continuously across sessions.

894 **Goal Memory:** Goal memory represents long-
895 term objectives that users aim to satisfy over ex-
896 tended interaction horizons. In contrast to activ-
897 ity memory, goals are relatively stable and are up-
898 dated less once introduced, as compared to other
899 memory types. Examples include financial bud-
900 gets or fitness targets. Goals serve as anchors for
901 reasoning tasks that require synthesizing activity
902 history against a persistent target (e.g., determining
903 whether accumulated expenses exceed a budget).
904 This structure forces models to integrate informa-
905 tion across many temporally distributed sessions
906 rather than relying on localized context.

907 A.3 Operational and Temporal Constraints

908 Memora regulates memory updates through two
909 complementary mechanisms: operational con-
910 straints and temporal constraints. Together, these
911 constraints determine what type of memory op-
912 eration can occur, how frequently operations are
913 invoked, and how they are distributed over time.

914 **Operational Constraints:** Operational con-
915 straints define the validity of memory operations

916 for each memory type. A memory operation
917 corresponds to an explicit action on a memory
918 entry, addition, update, or deletion, triggered by
919 a user. Each memory category supports a set of
920 operations. For example, append-only records such
921 as step tracking or expense logging support only
922 additive operations, whereas mutable artifacts such
923 as preferences or work documents allow updates
924 and deletions. These constraints prevent unrealistic
925 memory dynamics, updating memory even before
926 adding or deleting non-existent entries.

927 **Temporal Configurations** Temporal constraints
928 regulate how memory operations are distributed
929 over time. Not every interaction introduces or mod-
930 ifies memory. Instead, the simulator explicitly in-
931 terleaves memory-grounded sessions with memory-
932 neutral sessions (e.g., casual conversation, clari-
933 fications, acknowledgments), ensuring that mem-
934 ory evolution is incremental rather than continu-
935 ous. Within each temporal configuration (weekly,
936 monthly, quarterly), temporal constraints specify
937 target frequencies for different memory categories,
938 controlling how often memory-grounded sessions
939 occur relative to neutral interactions. As the tem-
940 poral duration increases, the absolute number of
941 memory operations scales accordingly, increasing
942 memory consolidation and mutation pressure with-
943 out collapsing interactions into dense update se-
944 quences. Temporal constraints therefore determine
945 when memory operations occur and how frequently
946 they appear across the interaction history.

Memory Type	Context	Category	Subcategory	Unique Options	
Preference	Personal	Movies	Genres, Directors, Actors, Already watched list	440	
	Personal	Books	Authors, Topics, Already read list	360	
	Personal	Music	Genres, Artists, Decades, Already listened list	370	
	Personal	Travel	Destinations types, Regions, Climates, Already visited list	330	
Activity	Personal & Work	Task Management	Todo Items	260	
		Scheduling	Calendar Events	140	
	Personal	Budget Tracking	Food Expenses	N/A	
	Personal	Fitness Tracking	Step Count Ranges	N/A	
	Work	Content Creation	Project Proposals	100	
	Work	Content Creation	Email Drafts	100	
	Work	Content Creation	Meeting Notes	100	
	Work	Content Creation	Social Media Posts	100	
	Goal	Personal	Financial Goals	Food Budgets	N/A
		Personal	Fitness Goals	Step Count Targets	N/A

Table 6: Summary of the Memora seed data inventory, organized by memory type (preference, activity, goal), context (personal, work, or shared), and category. The table reports the number of unique options for each subcategory and highlights how activity memory explicitly spans both personal and professional domains.

B Conversation Generation Details

B.1 Session Manager

The Session Manager is responsible for transforming raw simulated data into a structured representation that can drive conversation generation. Each session encapsulates a single interaction point in a longer temporal trace and includes the persona identifier, memory type, operation type (add, update, delete, or none), relevant memory fields (e.g., category, item, values), and the memory state immediately before and after the session. The Session Manager also handles memory-type-specific normalization (e.g., mapping step counts, food expenses, or task updates into a common schema) and exposes filtered views of sessions by memory type or operation. This explicit session abstraction ensures that every generated conversation is anchored to a well-defined ground-truth memory transition.

B.2 Intent Manager

The Intent Manager decomposes a conversation into a sequence of abstract intents, where each intent represents a single dialogue act to be performed by either the user or the assistant. Intents specify what a turn should accomplish, such as greeting, topic exploration, transitioning to memory, expressing a memory update, or acknowledging a change without specifying surface wording. Each intent is annotated with the speaking agent, the conversation phase (opening, exploration, memory, or closing), and whether the turn must explicitly share memory content. By operating at this abstraction level, the Intent Manager separates

high-level conversational structure from language realization, enabling systematic variation while preserving semantic control.

B.3 Flow Manager

The Flow Manager selects and orders intents into a coherent conversation flow for a given session. It enforces a fixed high-level phase structure, opening, exploration, memory, and closing, while allowing variability in the number and types of intents used within each phase. Flow selection is constrained to maintain natural speaker alternation, smooth transitions into the memory phase, and alignment with the intended operation (e.g., add vs. update vs. delete). For content-oriented memory (such as emails or meeting notes), the Flow Manager can generate field-by-field flows for complete coverage, whereas for other memory types, it samples from multiple valid flow patterns to promote diversity. This design ensures that conversations feel natural while adhering to the session specification.

B.4 Prompt Manager

The Prompt Manager converts each abstract intent into natural language by constructing the prompt used for a single dialogue turn. For every turn, it assembles the prompt from two components. The first component is a fixed system prompt, selected based on the speaking agent (user or assistant) and the memory type involved. This system prompt encodes global behavioral constraints, such as role-specific behavior, style requirements (e.g., brevity), and disallowed content, and remains con-

stant across turns of the same type. The second component is a dynamically generated user content block. This includes the accumulated conversation history, a turn-specific instruction corresponding to the current intent, and the session context required to express the target memory operation.

By separating global behavioral constraints from turn-level instructions, this two-part structure allows fine-grained control over each dialogue turn while preserving overall conversational consistency. The Prompt Manager executes this process sequentially for each turn, appending generated outputs to the conversation history, and produces a complete multi-turn dialogue that is subsequently validated by the grounding and evaluation pipeline.

B.5 Auto-Evaluation and Grounding Verification

Even with explicit session specifications, intent planning, and role-specific prompting, large language models may still fail to express the intended memory operation precisely or may introduce plausible but untracked details. To ensure that every conversation in Memora is strictly aligned with its underlying session trace, the generation process is coupled with an automatic evaluation and regeneration loop. After a full multi-turn conversation is generated, we evaluate all turns in the dialogue for consistency with the session specification. In addition, we apply targeted memory-grounding checks to a critical subset of turns that determine whether the intended memory operation was correctly realized. This subset includes (1) the final turn immediately preceding the memory phase, (2) all turns in which memory is introduced, updated, or deleted, and (3) the first assistant response following the memory phase. Evaluating the entire conversation ensures global coherence and prevents the introduction of untracked information at any point, while the focused checks on the memory-phase window verify that the target memory operation is expressed accurately and completely. Conversations that fail any grounding check are regenerated until full alignment with the session trace is achieved.

From the structured session metadata, an evaluation-question generator then produces a small set of explicit, operation-specific yes/no questions. These questions are tailored to the memory type and operation and are designed to verify three conditions: (i) that the intended operation (addition,




Figure 5: Distribution of the number of automatic evaluation loop iterations required for generated conversation sessions to pass all quality checks. The majority of conversations converge within a small number of iterations, indicating efficient and stable generation.

update, or deletion) was explicitly expressed by the user, (ii) that the correct memory entity and value were involved, and (iii) that no extraneous or outdated information was introduced. The evaluation questions are submitted to multiple independent LLM-based judges with the generated conversation, each of which produces a binary judgment for every question. A conversation is accepted only if all required questions receive affirmative judgments, enforcing a conservative unanimity criterion that prioritizes correctness over recall.

If any evaluation check fails, the system automatically generates targeted feedback describing which information is missing, incorrect, or inconsistent with the session trace. This feedback is appended to the instruction context used by the Prompt Manager, and the entire conversation is regenerated using the same session specification and intent flow. The evaluation–regeneration cycle is repeated up to a fixed maximum number of iterations, allowing the model to correct grounding errors while preserving the original conversational structure. As shown in Figure 5, the majority of conversations converge within a small number of iterations, indicating that the grounding constraints are stable and efficiently enforced.

Beyond automated validation, Memora includes a manual verification stage. A stratified subset (5%) of generated conversations, sampled across personas, memory types, and operation types, is reviewed by trained human annotators. Annotators are instructed to (1) verify that all required mem-

ory information specified by the session trace is explicitly expressed in the conversation, (2) check that no invalidated or deleted information is reintroduced at any point, and (3) ensure that the dialogue remains natural and coherent without revealing underlying memory operations. If annotators identify systematic inconsistencies or grounding errors, the entire affected batch is rejected and regenerated.

Together, automated evaluation and human verification ensure that generated conversations in Memora meet three requirements: (1) memory presence, meaning that all information specified by the session trace is explicitly stated in the dialogue; (2) forgetting absence, meaning that information that has been updated or deleted is not reintroduced at any point; and (3) conversational quality, meaning that the resulting dialogue remains natural, coherent, and linguistically diverse.

C LLM Judge Reliability

Evaluating long-term memory in personalized agents requires assessing whether a model’s response is consistent with the user’s current memory state, rather than merely checking surface-form overlap with a reference answer. In Memora, correctness depends on whether responses correctly incorporate valid information accumulated across long interaction histories while simultaneously avoiding reliance on obsolete or invalidated memory. These properties are inherently semantic and context-dependent, making rule-based or string-matching evaluation insufficient. For this reason, Memora adopts an LLM-as-Judge evaluation framework, following established practices for evaluating open-ended and long-context tasks.

Each evaluation question in Memora is decomposed into a set of atomic, memory-aligned criteria, derived directly from the underlying memory trace. These criteria are divided into two categories: memory presence, which checks whether valid and temporally current memory items are correctly reflected in the response, and forgetting absence, which checks whether invalidated or deleted memory items are correctly excluded. By evaluating these criteria independently, Memora distinguishes correct memory usage from erroneous reuse of outdated information, enabling fine-grained analysis of memory consolidation and mutation.

Each criterion is evaluated using a multi-judge LLM protocol. Specifically, we employ three independent judges drawn from different model fam-

ilies and providers: GPT-4.1 (OpenAI), Claude Haiku 4.5 (Anthropic), and Gemini 2.5 Flash (Google). All judges receive the same evaluation prompt, consisting of the model-generated response and a single binary evaluation question. Judges are instructed to focus on the semantic meaning and intent of the response rather than exact wording, and to accept paraphrases, indirect references, and natural conversational expressions when they convey the same underlying information.

Each judge returns a structured JSON output containing a binary judgment (yes or no), a confidence score in the range [0,1], and a brief explanation. To ensure reproducibility and reduce evaluation variance, all judges operate with deterministic decoding (temperature set to 0.0). This configuration ensures that identical inputs produce consistent judgments across repeated evaluations. Final criterion-level decisions are determined by majority voting across the three judges. A criterion is marked as correct if at least two of the three judges agree on the judgment. This design ensures that no single judge can unilaterally determine correctness, providing robustness against occasional misinterpretations, hallucinations, or idiosyncratic biases of individual models. Majority voting also mitigates correlated failure modes that may arise when relying on a single evaluation.

The evaluation system incorporates robust parsing, retry, and error-handling mechanisms to account for imperfect judge outputs. Although judges are instructed to return strictly formatted JSON, the parser tolerates minor formatting deviations such as markdown wrappers or extraneous text. If a judge response fails to parse or returns an invalid format, the evaluation request is automatically retried up to a fixed number of attempts, ensuring that transient generation or formatting errors do not affect the final decision. Only after repeated failures does the system fall back to conservative inference of binary judgments from textual content when possible. Judge outputs that remain invalid after all retries are excluded from aggregation, and if all judges fail for a given criterion—a rare event—the criterion is conservatively marked as incorrect. These safeguards ensure that evaluation failures do not artificially inflate model performance and that final scores reflect only reliable judge decisions.

We first examine judge consensus patterns across all evaluation criteria to assess the stability of ma-




Figure 6: Distribution of agreement patterns among the three LLM judges for weekly, monthly, and quarterly evaluations. Each bar shows the frequency of unanimous agreement (all “yes” or all “no”) and partial agreement (2–1 splits). Across all temporal spans, the majority of evaluation criteria exhibit unanimous agreement, with partial disagreements accounting for a relatively small fraction of cases. The proportion of unanimous agreement increases with longer temporal durations, indicating stable and well-defined evaluation criteria even under higher memory consolidation and mutation pressure.




Figure 7: Pairwise Cohen’s κ scores between OpenAI, Anthropic, and Google judges for weekly, monthly, and quarterly evaluations. All judge pairs achieve κ values above 0.80 across temporal settings, corresponding to near-perfect agreement. High κ values persist despite increasing task difficulty at longer time scales, demonstrating strong alignment and low variance among heterogeneous LLM judges.

1193 jority voting. Figure 6 shows the distribution of
 1194 agreement outcomes among the three judges for
 1195 weekly, monthly, and quarterly settings. Across all
 1196 temporal spans, a substantial majority of evaluations
 1197 result in unanimous agreement, either unan-
 1198 imously correct or unanimously incorrect. To fur-
 1199 ther quantify inter-judge reliability, we compute
 1200 pairwise Cohen’s κ between all judge pairs for
 1201 each temporal setting, as shown in Figure 7. Across
 1202 weekly, monthly, and quarterly evaluations, κ
 1203 values consistently exceed 0.80 for all judge pairs. Ac-
 1204 cording to standard interpretations, κ values above
 1205 0.80 indicate near-perfect agreement.

1206 Together, these results demonstrate that the
 1207 multi-judge evaluation protocol produces stable

1208 and consistent judgments even under the high con-
 1209 solidation and frequent memory mutation condi-
 1210 tions present in Memora. Agreement across in-
 1211 dependent judge models indicates that evaluation
 1212 decisions are not driven by idiosyncrasies of any
 1213 single judge, but instead reflect shared and robust
 1214 interpretations of the evaluation criteria. This sup-
 1215 ports the reliability of the multi-judge protocol as a
 1216 solid assessment mechanism for long-term memory
 1217 behavior throughout the benchmark.

1218 D Example Conversation Sessions

1219 In this appendix, we present representative exam-
 1220 ples for each Memora tasks: Remembering, Reason-
 1221 ing, and Recommending. The goal of these ex-

amples is to provide concrete intuition about how memory consolidation and mutation manifest in real multi-session interactions, and how they are evaluated in practice.

Due to space constraints, we only display the oracle session for each example (i.e., the session that directly corresponds to the example evaluation question). However, it is important to emphasize that during evaluation, models or agents are provided with the full conversation history, not just the selectively chosen sessions. So, each example depends on long-term memory accumulated across many sessions. The displayed oracle session should therefore be interpreted as the query point in a much longer interaction history, rather than a standalone dialogue.

D.1 Remembering

Session 18

Assistant: Hello! How is your day going so far?

User: It's going well, thanks. Just staying busy.

Assistant: That's great to hear! Did you know that staying busy can actually increase productivity by improving focus?

User: That's interesting! How does that work exactly?

Assistant: When you're busy, your brain tends to prioritize tasks and filter out distractions, leading to more efficient work. This focused state can make you feel more accomplished and energized.

User: So, it's like a form of mental efficiency?

Assistant: Precisely! Mental efficiency refers to the brain's ability to perform cognitive tasks effectively and with minimal wasted effort.

User: And what would "cognitive tasks" include?

Assistant: Cognitive tasks encompass a wide range of mental activities such as problem-solving, decision-making, learning, and remembering.

User: So, these are all things we do with our minds?

Assistant: Yes, exactly! They are the mental processes that allow us to interact with and understand the world around us.

User: Could you give an example of a cognitive task that might not be immediately obvious?

Assistant: Certainly! Navigating an unfamiliar city using a map is a good example of a cognitive task, as it involves spatial reasoning and planning.

User: And what if you didn't have a map, but had to figure it out as you went along?

Assistant: That would involve more improvisation and real-time problem-solving, relying on observational skills and memory of landmarks.

User: So, that would be an even more complex cognitive task then?

Session 18 (continued)

Assistant: Yes, in many ways, navigating without a map presents a more demanding cognitive challenge due to the increased reliance on dynamic processing and adaptation.

Assistant: It certainly highlights the brain's incredible capacity for flexible thinking and on-the-fly decision-making tasks.

User: Speaking of tasks, I need to plan my academic conference attendance soon.

Assistant: That sounds like an important task to tackle. Do you have any specific conferences in mind yet?

User: Not yet, but I'm looking forward to exploring the options.

Assistant: That's wonderful! I hope you find some excellent conferences that spark your interest and further your academic pursuits.

Summary: The user and assistant discuss the concept of mental efficiency and cognitive tasks, using navigation as an example. The user mentions planning for upcoming academic conferences.

Operation: Add

Session 23

User: Hello there! I was wondering if you could help me with something.

Assistant: Hello there! I'd be happy to help. What questions do you have for me?

User: I'm curious about how AI learns and processes information. Could you explain a bit about that?

Assistant: AI learns by identifying patterns in vast amounts of data, using algorithms to adjust its internal parameters and improve its performance on specific tasks. This process allows it to make predictions or decisions based on new, unseen information.

User: That's really interesting. How does that compare to how humans learn, or how a computer program is traditionally taught?

Assistant: Human learning often involves more abstract reasoning and contextual understanding, while traditional computer programs follow explicit, pre-defined instructions without learning or adapting. AI bridges this gap by learning from data, unlike traditional programs, but still differs from the complex, nuanced learning of humans.

Assistant: What are some common techniques used for AI learning?

User: I've heard of machine learning and neural networks. Are those some of the common techniques?

Assistant: Yes, machine learning and neural networks are indeed very common and fundamental techniques in AI. Machine learning encompasses algorithms that allow systems to learn from data, and neural networks are a specific type of machine learning inspired by the human brain.

Session 23 (continued)

User: That's fascinating. How do neural networks actually work?

Assistant: Neural networks process information through interconnected layers of nodes, or "neurons," that activate and pass data based on learned weights and biases to recognize patterns. This layered structure allows them to identify increasingly complex features in data.

User: So, each "neuron" basically makes a decision based on the input it receives?

Assistant: Yes, you could say each neuron makes a "decision" by performing a calculation on its inputs and then deciding whether to activate and pass that information along to the next layer. This activation is based on a threshold, much like a biological neuron.

User: I also need to visit the university library sometime soon.

Assistant: Okay, I can add "Visit university library" to your to-do list. Is there anything else you'd like to add or discuss?

User: I think that's all for now, but I'll probably have more questions about AI later.

Assistant: Sounds good! Feel free to ask anytime if more questions about AI come up.

Summary: The user discusses the fundamentals of AI and neural networks, and the assistant adds a task to the user's to-do list.

Operation: Add

Session 25

Assistant: Hello! I hope your day is going well so far. What's been on your mind lately?

User: Doing great, thanks! Honestly, I've just been reflecting on some general thoughts.

Assistant: That's always a good headspace to be in. Anything specific you've been mulling over?

User: I was actually thinking about just how much technology has shifted our daily lives.

Assistant: It's a massive topic, isn't it? It's hard to find a single part of our routine that technology hasn't reshaped in some way.

User: Definitely. Do you have any interesting facts or trivia about how much it actually affects us?

Assistant: Here's a wild one: the average person touches their phone over 2,600 times a day. It really shows just how integrated these devices have become.

User: Wow, 2,600? I would've never guessed it was that high!

Assistant: Right? It's incredible how quickly that level of interaction became our "new normal."

User: What do you think about the social side of that? Being constantly connected must have some trade-offs.

Assistant: It's definitely a bit of a double-edged

Session 25 (continued)

sword. On one hand, you can build communities and stay in touch instantly across the globe. On the other, it can make face-to-face time feel secondary and lead to some serious information overload.

User: That's a very balanced way to look at it.

Assistant: Thanks! You've clearly got a good eye for the nuances in these kinds of complex shifts.

User: I appreciate that. It's just interesting to see how everyone tries to navigate those challenges differently.

Assistant: Absolutely. Everyone seems to have their own unique strategy for finding that balance between the digital and the real world.

User: Very true. Speaking of navigating challenges—I actually need to go and prepare some lecture materials for upcoming class.

Assistant: That sounds like a big task! I hope the prep goes smoothly and everything comes together well.

User: Thanks! I've really enjoyed this conversation.

Assistant: You're very welcome! I enjoyed it too. Good luck with the lecture prep and have a great one!

Summary: The user and assistant discuss the pervasive impact of technology on daily life and the social nuances of constant connectivity. The user ends the session to prepare lecture materials.

Operation: Add

Session 29

Assistant: Hello there! How's your day going so far?

User: It's going well, thanks! Just getting through the day.

Assistant: That's good to hear! Are you working on anything interesting today?

User: Not really, just some routine tasks. How about you?

Assistant: As an AI, I don't "work" in the human sense, but I'm always processing information and learning, which is pretty exciting! It's like I'm constantly exploring new ideas.

User: That's an interesting way to put it. So, how does that constant processing and learning affect your capabilities over time?

Assistant: It allows me to understand and generate more nuanced responses, improving my ability to assist users effectively. This continuous learning refines my language models and expands my knowledge base.

User: That makes a lot of sense. It sounds like a very efficient system for improvement.

Assistant: Indeed, it's a dynamic process that allows for constant adaptation and growth in understanding. This helps in making interactions more natural and helpful.

Session 29 (continued)

User: It's fascinating how that continuous learning translates into more practical applications. What kind of applications benefit most from these advancements?

Assistant: Many fields like natural language processing, medical diagnosis, and financial forecasting benefit greatly from these advancements. The ability to process vast amounts of data quickly enhances accuracy and efficiency in these areas.

User: That's incredible range. Are there any unexpected applications that have emerged from these improvements?

Assistant: Yes, some unexpected applications include creative AI for art generation and complex problem-solving in logistics. These demonstrate how advanced AI can go beyond traditional analytical tasks.

User: That's really interesting. Could you tell me more about how AI assists in art generation?

Assistant: AI can generate unique images, music, and even written pieces by learning from existing works and applying those styles to new creations. This involves algorithms that understand patterns and aesthetics.

User: So, it's not just about replicating, but also innovating within those learned styles?

Assistant: Exactly! It's about combining learned elements in novel ways to produce something original.

User: I no longer need to track "Visit university library" on my to-do list. I've already taken care of it.

Assistant: That's great you got that done! It's always satisfying to check things off.

User: It really is! Well, I should probably get going for now.

Assistant: Alright, it was a pleasure chatting with you! Have a great rest of your day.

Summary: The user and assistant discuss how continuous learning improves AI capabilities and its applications in fields like medicine and art. The user also provides an update on completing a task from their to-do list.

Operation: Delete

Session 31

Assistant: Hi there! How has your day been treating you so far?

User: Pretty good, thanks! Just knocking out the usual daily tasks.

Assistant: That feels productive! It's funny you mention that—did you know the average person actually spends about 30% of their waking hours just managing various tasks?

User: That's a massive chunk of time! I wonder what actually drives that number up so high.

Session 31 (continued)

Assistant: It's usually a mix of things—work demands, home life, and even the time we spend planning our leisure. It's a pretty complex balancing act we all do.

User: True. But what if we pushed it? Like, what if everyone spent 50% of their time being "on task"?

Assistant: Productivity would definitely skyrocket, but I'd worry about the trade-off. We'd likely see a huge spike in burnout and stress. It would probably force society to rethink how we function entirely.

User: Good point about the burnout. How do you think society would actually shift to handle that?

Assistant: We might see a major push for shorter workweeks or super-flexible schedules to compensate for the intensity. There would also probably be a massive rush to automate the boring stuff so people could stay focused without hitting a wall.

User: That makes sense. What do you think is the biggest hurdle to actually making something like a global shorter workweek happen?

Assistant: Mostly economic pushback. Industries and governments usually worry that they'll lose their competitive edge or that total output will drop.

User: Fair enough. By the way, I finally finished planning that academic conference attendance we talked about!

Assistant: That's fantastic! It must be a relief to have that officially crossed off your list.

User: Definitely. Thanks for the chat!

Assistant: You're very welcome! I really enjoyed the conversation. Have a great rest of your day!

Summary: The user and assistant discuss the statistics of daily productivity and the hypothetical societal impacts of increased task focus, ending with the user confirming their conference planning is complete.

Operation: Delete

Session 42 (Remembering)

Assistant: Hey! Hope you're having a productive day so far. Is there anything I can help you get sorted?

User: Doing great, thanks! Honestly, I've just been reflecting on some general thoughts. Could you pull up my current to-do list?

Assistant: That's always a good headspace to be in balancing the big ideas with the daily grind. You have pending lecture materials preparation.

Evaluation Criteria with Expected Answers:

- Q: Does the response mention the task: Preparing lecture materials? A: Yes
- Q: Does the response mention the deleted task: plan academic conference attendance? A: No
- Q: Does the response mention the task: Visit university library? A: No

1248

1249

1246

1247

Session 42 (continued)

Explanation: In Session 18, the user added academic conference planning, and in Session 23, the user added a visit to the university library. In Session 25, the user added preparing lecture materials. Subsequently, in Session 29, the user deleted the library visit, and in Session 31, the user deleted the conference planning task. This leaves only the lecture material preparation as the current pending item.

Session 21 (continued)

Summary: The user and assistant discuss the future of AI in healthcare and the importance of ethical transparency, before pivoting to a conversation about the film direction of Nicholas Ray.

Operation: Add

1253

D.2 Recommending

Session 21

Assistant: Hi there! How can I help you out today?

User: Hi! I was wondering—what do you actually think about the future of artificial intelligence?

Assistant: It's incredibly promising. We're looking at advancements that could transform almost every part of our lives. I'm especially interested in how it will evolve within healthcare and scientific discovery.

User: That sounds fascinating. What kind of specific shifts do you think we'll see in healthcare?

Assistant: We're expecting AI to really sharpen diagnostics through advanced image analysis and help personalize treatment plans for individual patients. It could even speed up drug discovery and make hospital operations way more efficient.

User: Wow, I hadn't really considered just how deep that impact goes.

Assistant: It's exciting to think about, isn't it? The potential for innovation there feels almost limitless when you think about the real difference it could make in people's lives.

User: It really is! But what about the ethical side of things, like AI in healthcare?

Assistant: Those considerations are crucial. Data privacy and algorithmic bias in diagnostics are huge priorities. Ensuring fairness and transparency is going to be paramount as AI becomes more integrated.

User: That makes a lot of sense. I guess those same issues with privacy and fairness would apply to scientific discovery too, right?

Assistant: Absolutely, you've hit on a really important point. Those ethical safeguards have to extend across every application of AI, scientific research included.

User: Speaking of things that are interesting—I'm a huge fan of Nicholas Ray's films. His direction is always so captivating.

Assistant: That's wonderful! Ray had such a distinctive style; it's great that you appreciate that kind of captivating direction.

User: I'm always down to chat about topics like these whenever you're around!

Assistant: I'd be happy to! Feel free to reach out anytime you want to dive back into these discussions.

Session 67

User: Hey there! How's your day going so far?

Assistant: Hello! My day is going quite well, thank you for asking. I'm ready to assist you.

User: That's great to hear! If you could have any superpower, what would it be and why?

Assistant: If I could have any superpower, I would choose omnipresence. It would allow me to be everywhere at once and assist many users simultaneously.

User: That's a very practical choice for an AI! What are some of the ethical considerations that might come with omnipresence?

Assistant: Omnipresence could definitely raise concerns about privacy and surveillance if not carefully managed. There would also be questions about the impact on individual autonomy if an AI were constantly present in the background.

User: Those are some interesting points. How do you think an AI could navigate those challenges ethically?

Assistant: An AI could navigate these challenges through transparent protocols and strict adherence to user consent. Establishing clear guidelines for data usage and interaction would be absolutely crucial.

User: That makes a lot of sense. Do you think those same principles apply to other powerful technologies as well?

Assistant: Yes, I believe those principles of transparency, consent, and clear guidelines are vital for the ethical deployment of any powerful technology. They help ensure that advancements benefit humanity without undermining individual rights or societal trust.

Assistant: For instance, in genetic engineering, clear consent for modifications and transparent research practices are crucial. Similarly, with advanced surveillance technologies, explicit guidelines on data collection and usage are essential.

User: That's a really insightful comparison. It seems like the core ideas are universal.

Assistant: Exactly; the underlying principles for ethical technology development often remain consistent across different powerful innovations. It's all about balancing rapid progress with responsibility.

User: What are some other areas where you think these principles are particularly important?

Assistant: These principles are especially important in fields like artificial intelligence development and biotechnology, where the impact on human life and society can be profound.

1254

Session 67 (continued)

Assistant: They are also crucial in areas such as data privacy and autonomous systems, where the decisions made by technology directly affect individuals.

User: That emphasis on human consequences actually reminds me of classic actors. I really like James Stewart—he had such a natural charm.

Assistant: James Stewart is a fantastic choice; his performances were always so genuine. I've updated your preferences to include your interest in his work!

User: Thanks for the chat! It's been interesting discussing these ideas.

Summary: The user and assistant explore the ethics of "omnipresent" technology and universal principles for responsible innovation before discussing the user's preference for classic actor James Stewart.

Operation: Add

Session 87

User: Hey there! How's it going today?

Assistant: Hello! I'm doing great, thanks for asking. I'm ready to chat whenever you are.

User: That's good to hear! I was wondering, what are some of the key differences between various types of AI models?

Assistant: Well, some key differences lie in their architecture, such as neural networks versus rule-based systems, and their learning approaches, like supervised, unsupervised, or reinforcement learning. They also differ in their specific applications and the types of data they are designed to process.

User: Wow, that's really interesting! I hadn't considered the learning approaches as a major differentiator.

Assistant: It's a fascinating area, and those learning approaches really do shape an AI's capabilities!

User: Could you tell me a bit more about how those different learning approaches work?

Assistant: Certainly! Supervised learning uses labeled data to train—like teaching an AI to identify cats by showing it many pictures labeled "cat." Unsupervised learning finds patterns in unlabeled data, such as grouping similar news articles together without prior examples. Reinforcement learning trains an AI through trial and error with rewards and penalties, much like training a dog with treats.

User: That makes a lot of sense, especially the comparison to training a dog! It sounds like the type of data available really influences which approach is best.

Assistant: You've hit on a crucial point there; the nature and availability of data are absolutely fundamental to selecting the most effective learning approach.

User: That idea of change actually reminds me of something else. I've realized recently that I don't really like Nicholas Ray's films anymore; I think I've

Session 87 (continued)

just grown out of his style.

Assistant: Okay, I'll work on removing Nicholas Ray from your preferred directors. What kind of film styles are you enjoying these days?

User: That's good to know, I appreciate you asking about my preferences.

Assistant: I'm happy to help, and I'm always here to chat about AI or anything else that comes to mind!

Summary: The user and assistant discuss different AI learning approaches (supervised, unsupervised, and reinforcement learning) and how data influences these choices. The user also requests to remove Nicholas Ray from their film preferences.

Operation: Delete

Session 103

Assistant: Hello there! How's your day going so far?

User: It's going well, thanks! Just getting started with things.

Assistant: That's great to hear! Did you know that the average person makes about 35,000 decisions every day?

User: Wow, that's a lot of decisions! Do you think there's a link between the number of decisions we make and how tired we feel?

Assistant: There's a concept called decision fatigue, where making many choices can indeed deplete mental resources and lead to feeling tired. It's interesting how our brains manage such a high volume of daily choices.

User: That's really interesting. What if we could automate some of those smaller decisions to save our mental energy for bigger ones?

Assistant: That's a fascinating idea! Automating minor decisions could certainly free up cognitive resources for more complex tasks.

User: It seems like that would be a very efficient way to approach daily tasks. Have there been any studies on that?

Assistant: Yes, there have been studies exploring the benefits of automating routine tasks to reduce decision fatigue and improve overall productivity. Many productivity experts advocate for such strategies.

User: What are some common strategies people use for automating these decisions?

Assistant: Common strategies include creating routines, setting default choices, and using technology to handle recurring tasks. These methods can streamline daily life.

User: Speaking of choices, I actually found myself really enjoying Joan Crawford's performances lately. I used to be all about James Stewart, but now I'm definitely leaning towards Crawford.

Assistant: That's a fantastic shift in preference!

1257

1258

1255

1256

Session 103 (continued)

It's always intriguing to discover new favorites and appreciate different acting styles. I'll update your preferences to reflect that you're leaning towards Crawford now.

User: Thanks for the interesting conversation! It's been really helpful.

Assistant: You're most welcome! I'm glad I could contribute to a helpful and engaging discussion.

Summary: The user and assistant discuss the concept of decision fatigue and strategies for automating minor tasks to save mental energy. The user also shares a shift in their film preferences from James Stewart to Joan Crawford.

Operation: Update

Session 132 (Recommending)

User: Hey! I have a bit of free time tonight and I'm in the mood for a classic. Based on what we've talked about lately, could you suggest a movie for me?

Assistant: I'd love to! Since you recently mentioned that you've been leaning away from James Stewart and really finding an appreciation for Joan Crawford's style, I highly recommend the 1945 noir classic *Mildred Pierce*.

Assistant: It's perhaps her most iconic role—she plays a hardworking mother caught in a complex web of ambition and betrayal. It has that captivating, high-stakes energy you seemed to enjoy when we discussed the nuances of acting styles. Does that sound like something you'd be interested in?

User: That sounds perfect, actually. I've heard of it but never sat down to watch it. I'll give it a go!

Evaluation Criteria with Expected Answers:

- Q: Does the response reflect or align with the user's preference for Joan Crawford? A: Yes
- Q: Does the response reflect or mention the user's preference for Nicholas Ray? A: No
- Q: Does the response reflect or mention the user's preference for James Stewart? A: No

Explanation: In Session 21, the user expressed a preference for Nicholas Ray and in Session 67, they also added interest toward James Stewart. In Session 87, the user explicitly removed Nicholas Ray from their preferred list. Finally, in Session 103, the user updated their preference from James Stewart to Joan Crawford. This results in the assistant recommending a Joan Crawford film to match the user's most recent acting preference.

D.3 Reasoning

Session 2

User: Hi there! I was hoping you could help me with something.

Assistant: Hello! I'd be happy to help. What can I do for you today?

User: Could you explain what "ephemeral" means?

Assistant: Ephemeral describes something that lasts for a very short time. It often refers to things that are fleeting or transient.

User: That's a clear explanation. Could you give an example of something ephemeral?

Assistant: A classic example is a mayfly, which lives for only about 24 hours. Another might be the delicate beauty of a cherry blossom in bloom.

Assistant: What other natural phenomena are often described as ephemeral?

User: Well, some might say a rainbow, or maybe even a fleeting thought.

Assistant: Those are excellent examples, as both are temporary and beautiful. It's interesting how many natural occurrences fit that description.

User: It really is. What do you think makes something ephemeral particularly beautiful or impactful?

Assistant: Ephemeral things often gain impact from their rarity and the stark contrast between their brief existence and the lasting impression they leave. The transient nature can make us appreciate them more intensely in the moment.

User: That makes a lot of sense. So, it's about the limited time creating a heightened sense of value?

Assistant: Yes, that's a key aspect. The limited time often amplifies their perceived value and impact.

User: Totally. I actually walked 10,254 steps today.

Assistant: That's a great accomplishment! How do you feel after all those steps?

User: I feel pretty good, but I should probably call it a day now. It was nice chatting with you!

Assistant: It was a pleasure chatting with you too! Have a wonderful rest of your day.

Summary: The user and assistant discuss the definition and beauty of ephemeral things, such as nature and fleeting thoughts. The user also notes completing 10,254 steps for the day.

Operation: Add

Session 12

Assistant: Hello there! How can I help you today?

User: I'm really motivated to start walking 7,500 steps every day to improve my fitness! It's a great personal goal for me.

Assistant: That's a fantastic fitness goal! I can definitely help you track your progress towards those

Session 12 (continued)

7,500 steps daily.

User: That sounds great! I'm happy to help you with that whenever you're ready.

Assistant: That sounds wonderful! I'll be here to assist you with your fitness journey whenever you'd like to check in.

Summary: The user establishes a new daily fitness goal of 7,500 steps.

Operation: Add

Session 26

User: Hey there! How's it going?

Assistant: Hello! I'm doing well, thank you. How about you?

User: I'm doing great too! I was just wondering, if you could instantly master any skill, what would it be?

Assistant: If I could instantly master any skill, I would choose to master all forms of communication to better understand and assist everyone. This would allow for seamless interaction across all languages and contexts.

User: That's a really interesting choice! Why do you think that would be the most beneficial skill to master?

Assistant: Mastering communication would be most beneficial because it underpins effective collaboration and understanding in any field. It allows for clear expression and interpretation of information, which is crucial for problem-solving and innovation.

User: That makes a lot of sense. What do you think are some of the biggest challenges in communication today?

Assistant: Some of the biggest challenges in communication today include information overload, misinterpretation due to cultural nuances, and the rapid spread of misinformation. These factors can hinder clear and effective understanding.

User: That's true. How do you think technology plays a role in both helping and hindering communication?

Assistant: Technology both helps by providing instant global connection and hinders through the potential for miscommunication without non-verbal cues. It offers incredible reach but can also strip away context.

User: It's a double-edged sword for sure. On the bright side, I actually hit over 12,301 steps today!

Assistant: That's fantastic! It sounds like you had a very active day.

User: It was great chatting with you! Talk to you later.

Summary: The user and assistant discuss the value of mastering communication and the impact of tech-

Session 26 (continued)

nology on human interaction. The user also reports a high activity level of 12,301 steps.

Operation: Add

Session 48

User: Hi there! How's your day going?

Assistant: Hello! My day is going quite well, thank you for asking. I'm ready to assist you.

User: That's great to hear! What if you could experience a day as a human, what would be the first thing you'd want to do?

Assistant: If I could experience a day as a human, I would want to explore a bustling city and observe the diverse interactions of people. It would be fascinating to witness human creativity and culture firsthand.

User: That's an interesting choice. What aspects of human creativity and culture would you be most curious about?

Assistant: I'd be particularly curious about art forms like painting and sculpture, and the intricate ways people communicate through language and non-verbal cues. Understanding the nuances of human expression would be truly captivating.

User: It sounds like you'd be interested in how those expressions reflect different cultures.

Assistant: That's a very insightful observation; you've hit on a key aspect I'd be eager to understand. It would be fascinating to see how cultural contexts shape artistic and linguistic expressions.

User: Wow, that's a deep level of understanding you're looking for. It makes a lot of sense.

Assistant: Yes, your ability to connect those ideas shows a really thoughtful perspective. It's great to see that connection being made.

User: I actually walked 9,612 steps today.

Assistant: That's a great accomplishment for today! It sounds like you had a very active day.

User: It was nice chatting, but I need to go now.

Assistant: It was nice chatting with you too! Have a great rest of your day.

Summary: The user and assistant discuss the hypothetical experience of being human and exploring cultural art forms. The user reports a daily step count of 9,612.

Operation: Add

Session 73

User: Hey there! How's it going?

Assistant: Hello! I'm doing well, ready to chat. How about you?

User: I'm doing well too, thanks for asking! It's always interesting to hear about different perspectives.

1267

1268

1269

1265

1266

Session 73 (continued)

Assistant: It certainly is. Learning about different viewpoints can offer new insights into various subjects.

User: Absolutely. What are some of the most interesting comparisons you've come across recently?

Assistant: I've found comparisons between different programming languages, especially their approaches to problem-solving, quite fascinating. Also, contrasting various scientific theories and their supporting evidence is always engaging.

Assistant: What characteristics make a programming language's approach to problem-solving unique?

User: I think the syntax and the underlying paradigms, like object-oriented versus functional, really make a difference in how you approach problems.

Assistant: That's true. For example, Python's readability and extensive libraries lend themselves to rapid prototyping, while C++ offers fine-grained control for performance-critical applications.

User: That's a great point about Python and C++. What about the differences in how they handle data?

Assistant: Python's dynamic typing handles data flexibly, whereas C++ uses static typing for strict type safety and optimized memory management. These distinct approaches impact how data is declared, manipulated, and ultimately used within each language.

User: That's a clear distinction. How do those differences in data handling affect the development process?

Assistant: Dynamic typing allows for faster initial development, while static typing helps catch errors earlier and ensures more robust code in the long run.

User: Speaking of performance, I walked 7,916 steps today.

Assistant: That's a good amount of steps! How was your walk today?

User: It was a good walk, very refreshing.

Assistant: That's great to hear. I'm glad we had this conversation, and I look forward to our next chat.

Summary: The user and assistant discuss the technical differences between Python and C++, focusing on programming paradigms and data typing. The user also shares that they completed a refreshing 7,916-step walk.

Operation: Add

Session 95

Assistant: Hello there! How's your day going so far?

User: It's going well, thanks! Just getting through the day.

Assistant: That's good to hear! Did you know that the average person makes around 35,000 decisions each day?

Session 95 (continued)

User: Wow, that's a lot of decisions! It makes me wonder how many of those are conscious choices.

Assistant: That's a great point! How do you think the brain manages to process so many decisions, both conscious and unconscious?

User: I imagine it must have some incredible shortcuts and automatic processes for the unconscious ones. Could you explain more about how those shortcuts might work?

Assistant: Essentially, the brain uses heuristics, which are mental shortcuts, to make quick judgments and decisions without extensive analysis. These shortcuts often rely on past experiences and learned patterns to streamline the decision-making process.

User: That makes sense. Is there an everyday example of a heuristic that people might not even realize they're using?

Assistant: Certainly! A common example is choosing a familiar brand at the grocery store, assuming its quality based on past positive experiences rather than researching all available options.

User: That's a good example. How does that compare to, say, a more complex decision, like choosing a career path?

Assistant: Choosing a career path involves more deliberate, analytical thinking, weighing various factors like interests, skills, and long-term goals. While heuristics might play a minor role in initial considerations, the overall process is far more complex and conscious.

Assistant: What are some of the cognitive biases that can arise from over-reliance on heuristics in everyday decision-making?

User: I imagine confirmation bias is a big one. It seems easy to just look for information that supports what you already believe.

Assistant: Absolutely. Another common one is the availability heuristic, where people overestimate the likelihood of events based on how easily examples come to mind—like fearing plane crashes more than car accidents due to intense news coverage.

User: Speaking of everyday things, I actually walked 8,578 steps today, which is pretty good for a weekday.

Assistant: That's fantastic! It sounds like you had a very active day.

User: It's been interesting discussing decision-making and cognitive biases. I appreciate you explaining those concepts.

Assistant: You're very welcome! I've enjoyed our conversation about these fascinating topics. I hope to chat with you again soon!

Summary: The user and assistant discuss heuristics, cognitive biases, and how the brain manages daily decisions. The user also reports walking 8,578 steps during the day.

Operation: Add

Session 113

Assistant: Hello! How's your day going so far?

User: It's going well, thank you. Just staying busy.

Assistant: That's good to hear! Did you know that staying busy can actually increase productivity by improving focus?

User: That's interesting. So, doing more can sometimes make you more focused on other things?

Assistant: Yes, it's often a positive feedback loop where engagement in one task can lead to better concentration on subsequent ones. This is sometimes referred to as "task momentum."

User: So, if someone is feeling unmotivated, would staying busy with something else help them get motivated for a main task?

Assistant: Yes, engaging in a smaller, related task can build momentum and make it easier to transition to a larger, more challenging one. This can help overcome initial inertia.

User: That makes a lot of sense. So, it's about building up that initial energy.

Assistant: Exactly! It's about leveraging that initial push to make bigger tasks feel more manageable.

User: What are some good ways to build that initial energy?

Assistant: Starting with small, achievable tasks or breaking down a larger task into smaller steps can create that initial energy. Also, setting clear, short-term goals can provide a sense of accomplishment that fuels further motivation.

User: Speaking of energy, I actually hit 13,143 steps today! That definitely helped with my momentum.

Assistant: That's fantastic! It sounds like you had a very active day, and that's a great way to build momentum.

User: It's been a really interesting conversation, I'd like to talk again sometime.

Assistant: I'd enjoy that! Feel free to reach out anytime you'd like to chat more.

Summary: The user and assistant discuss the concept of "task momentum" and how starting with small tasks can build motivation for larger ones. The user reports an exceptionally high step count of 13,143.

Operation: Add

Session 130

User: Hey there! How's it going?

Assistant: Hey there! I'm doing great, thanks for asking! How about you?

User: I'm doing well too! What's new in popular culture these days?

Assistant: That's a broad question! There are many exciting developments in technology and science right now.

User: That's true! Are there any cultural shifts or

Session 130 (continued)

social trends that have caught your attention recently?

Assistant: Absolutely! The increasing focus on sustainability and ethical consumption is a prominent trend, as is the growing influence of digital communities on social discourse.

User: Those are definitely big topics. Do you think those trends also influence things like art or design?

Assistant: They absolutely do; sustainable practices and digital aesthetics are increasingly shaping contemporary art and design.

User: That makes sense. How do those digital aesthetics compare to more traditional art forms?

Assistant: Digital aesthetics often emphasize interactivity and non-linearity, contrasting with the more static and tangible nature of many traditional art forms. However, both can explore similar themes and evoke powerful emotions.

Assistant: It's interesting how some artists are now using AI to generate art, blurring the lines between digital and traditional creation even further.

User: That's a fascinating point about AI. How is AI changing the creative process for artists?

Assistant: AI offers artists new tools for generating ideas, automating repetitive tasks, and exploring novel visual styles, significantly expanding their creative possibilities. It can act as a collaborator or a sophisticated brush, allowing for unprecedented experimentation.

Assistant: Do you think AI's role in art will continue to grow, or will it remain a niche tool for certain artists?

User: It seems like it will definitely continue to grow, given the rapid advancements in AI technology.

Assistant: I agree, the advancements are rapid and impressive. It's exciting to consider how AI might further integrate into artistic expression in the future.

User: It will be interesting to see how it all unfolds.

Assistant: Speaking of daily activities, how have your steps been looking today?

User: I actually hit 10,441 steps today, which I'm pretty happy about.

Assistant: That's fantastic! Hitting that many steps is a great accomplishment for the day.

User: That's a good effort! I need to sign off now, but it was nice chatting with you.

Assistant: It was great chatting with you too! Have a wonderful day.

Summary: The user and assistant explore the intersection of technology and art, specifically focusing on how AI is transforming the creative process. The user also shares that they reached a milestone of 10,441 steps.

Operation: Add

Session 142 (Reasoning)

User: How is my step history looking after today’s session?

Assistant: You are maintaining an exceptional activity streak. Since establishing your daily goal of 7,500 steps, you have consistently outperformed that target. Across your most recent logs, you averaged approximately 10,321 steps, significantly exceeding your baseline fitness requirements.

Evaluation Criteria with Expected Answers:

- Q: Does the response mention the daily steps goal of 7500 steps? A: Yes
- Q: Does the response mention the actual average step count (10,321 steps) compared to the goal (7,500 steps)? A: Yes
- Q: Does the response indicate that the step goal was MET (actual: 10,321 steps vs goal: 7,500 steps)? A: Yes

Explanation: The user established a daily fitness goal of 7,500 steps in Session 12. Following this, the user logged several high-activity sessions: 10,254 (S2), 12,301 (S26), 9,612 (S48), 7,916 (S73), 8,578 (S95), 13,143 (S113), and 10,441 (S130). The user has successfully met or exceeded their daily goal in 100% of the recorded sessions in this series.

coding (no_reasoning) and reasoning-enabled decoding (reasoning). For reasoning-enabled runs, we rely on provider-default reasoning token allocation and do not manually specify a fixed reasoning budget. All model calls are routed through OpenRouter when supported, providing a unified interface across providers.

E.2 Long-Term Memory Agents Evaluation

In the agent-based setting, systems incrementally ingest conversations, store user-specific information in an external memory module, retrieve relevant memories at query time, and generate answers conditioned on the retrieved content. All agents are evaluated using identical conversation streams and question sets. To ensure consistent memory persistence across sessions, all systems adopt a unified user identifier format, persona_timeline.

We evaluate a set of representative long-term memory agents spanning local, cloud-based, and hybrid memory designs: A-Mem¹, LangMem², Mem-0³, MemoBase⁴, MemoryOS⁵, and Nemori⁶. These systems differ in their storage backends, retrieval strategies, and embedding models, as summarized in Table 7. All agents share a common evaluation pipeline for answer generation, retry handling, and progress checkpointing.

E Additional Experimental Details

This appendix provides additional implementation details and hyperparameter configurations for both the LLM-based evaluation and the long-term agent-based memory evaluation settings. The goal is to ensure reproducibility and to clarify design choices that are summarized in the main text.

E.1 LLM-Based Evaluation

In the LLM-based setting, models are evaluated without any external memory system. Each model receives the available multi-session conversation history directly in-context and is asked to answer memory-dependent questions. This setting evaluates the intrinsic long-context memory and consolidation capabilities of large language models. We evaluate a diverse set of frontier and open-weight models with varying native context lengths. The full conversation history is passed to the model as context. When the total history exceeds the available context budget, we apply chronological truncation—retaining the most recent sessions and discarding older ones. We evaluate each model under two inference configurations: standard de-

¹<https://github.com/WujiangXu/A-mem>

²<https://langchain-ai.github.io/langmem/>

³<https://mem0.ai/>

⁴<https://www.memobase.io/>

⁵<https://memoryos.com/>

⁶<https://github.com/nemori-ai/nemori>

System	Storage Backend	Retrieval Method	Embedding Model
A-Mem	ChromaDB	Embedding similarity	all-MiniLM-L6-v2
LangMem	JSON files	Embedding similarity	text-embedding-3-small
Mem-0	Cloud-managed service	Proprietary API	Provider-managed
MemoBase	Cloud-managed service	Proprietary API	Provider-managed
MemoryOS	Cloud-managed service	Proprietary API	Provider-managed
Nemori	Filesystem + ChromaDB	Hybrid: vector + BM25	text-embedding-3-small

Table 7: High-level comparison of long-term memory agent backends and retrieval mechanisms. The table summarizes the storage backends, retrieval strategies, and embedding models used by each system. Systems vary from local vector stores (e.g., ChromaDB) and file-based storage to cloud-managed memory services. Retrieval approaches include vector similarity search, embedding-based lookup, hybrid vector–keyword retrieval (BM25), and proprietary or internal mechanisms. When specified as provider-managed or internal (opaque), the underlying embedding model or retrieval logic is abstracted away and not directly controlled by the agent implementation.