

Controlled Self-Evolution for Algorithmic Code Optimization

Anonymous ACL submission

Abstract

Self-evolution methods enhance code generation through iterative “generate-verify-refine” cycles, yet existing approaches suffer from low exploration efficiency, failing to discover solutions with superior complexity within limited budgets. This inefficiency stems from initialization bias trapping evolution in poor solution regions, uncontrolled stochastic operations lacking feedback guidance, and insufficient experience utilization across tasks. To address these bottlenecks, we propose **Controlled Self-Evolution (CSE)**, which consists of three key components. Diversified Planning Initialization generates structurally distinct algorithmic strategies for broad solution space coverage. Genetic Evolution replaces stochastic operations with feedback-guided mechanisms, enabling targeted mutation and compositional crossover. Hierarchical Evolution Memory captures both successful and failed experiences at inter-task and intra-task levels. Experiments on EffiBench-X demonstrate that CSE consistently outperforms all baselines across various LLM backbones. Furthermore, CSE achieves higher efficiency from early generations and maintains continuous improvement throughout evolution.

1 Introduction

Code generation has emerged as a critical application of Large Language Models (LLMs) (Comanici et al., 2025; Achiam et al., 2023; Cai et al., 2024; Dubey et al., 2024; Team et al., 2025; Guo et al., 2025), with models demonstrating impressive capabilities in producing functionally correct solutions for programming tasks (Chen, 2021; Jiang et al., 2024; Dong et al., 2025; Wang et al., 2025a; Hui et al., 2024; Wang et al., 2024, 2025b). Early approaches relied on single-turn generation, where models directly produce complete solutions from problem specifications (Luo et al., 2023; Wei et al., 2024). While achieving reasonable success on simple tasks, this paradigm struggles with complex




Figure 1: **Controlled Self-Evolution (CSE) improves exploration efficiency.** (a) Existing self-evolution wastes budget on low-quality regions due to initialization bias, uncontrolled evolution and repeated failure. (b) CSE guides exploration toward higher-quality solutions through diversified initialization, controlled evolution, and experience reuse.

algorithmic problems and lacks mechanisms to interact with execution environments or leverage verification feedback. To address these limitations, self-evolution methods (Gao et al., 2025; Fang et al., 2025) have emerged as a promising paradigm that enables iterative “generate-verify-refine” cycles: models start from initial solutions, execute code against test cases, analyze feedback signals (e.g., failed tests, performance bottlenecks), and generate improved variants. Methods such as AlphaEvolve (Novikov et al., 2025) and SE-Agent (Lin et al., 2025) have demonstrated that treating code generation as a feedback-driven search process can substantially enhance code quality.

Ideally, with unlimited computational resources, we could allow these self-evolving agents to explore extensively until reaching optimal solutions that are not only functionally correct but also exhibit superior time and space complexity. How-

063 ever, practical deployment scenarios impose strict
064 resource constraints. In real-world applications,
065 extensive multi-turn inference incurs prohibitive
066 computational costs and latency. This creates a
067 fundamental tension: we need methods that can
068 discover high-quality solutions, measured not just
069 by correctness but by algorithmic efficiency, within
070 a limited exploration budget.

071 Unfortunately, existing self-evolution methods
072 suffer from critically low exploration efficiency.
073 This inefficiency prevents them from discovering
074 code with superior time and space complexity
075 within limited exploration budgets, as the search
076 process fails to efficiently navigate toward algorithmically optimal solutions. This inefficiency stems from three fundamental limitations (as shown in Figure 1). First, *initialization bias*: methods (Du et al., 2025; Huang et al., 2024) typically begin evolution from a single or few initial solutions generated by the base model, which may lie in poor regions of the solution space, necessitating many iterations to escape local optima. Second, *uncontrolled stochastic evolution*: operations like random mutation and crossover are applied without explicit guidance from feedback signals, resulting in undirected exploration where many generated variants fail to systematically navigate toward better solutions. Third, *insufficient utilization of evolution experience*: existing approaches (Lin et al., 2025; Du et al., 2025) do not effectively accumulate successful patterns within a task or abstract transferable experiences across tasks, causing repeated failures and preventing the reuse of proven optimization strategies.

097 This motivates our central research question:
098 **Can we design a self-evolution framework that**
099 **achieves high code quality while dramatically**
100 **improving exploration efficiency?** We propose
101 **Controlled Self-Evolution (CSE)**, a novel frame-
102 work that addresses all three efficiency bottle-
103 necks through three key innovations. First, Di-
104 versified Planning Initialization generates multi-
105 ple structurally distinct algorithmic strategies be-
106 fore evolution begins, ensuring broad coverage
107 of the solution space and reducing the likelihood
108 of getting trapped in poor local regions. Sec-
109 ond, Genetic Evolution replaces stochastic opera-
110 tions with fine-grained feedback-guided mecha-
111 nisms: functional decomposition enables targeted
112 mutation that refines faulty components while pre-
113 serving high-performing parts, and compositional
114 crossover structurally integrates complementary

115 strengths from diverse solutions. Third, Hierar-
116 chical Evolution Memory captures and reuses evo-
117 lutionary insights at two levels: local memory ac-
118 cumulates task-specific lessons to avoid repeating
119 failures within the current problem, while global
120 memory distills cross-task optimization patterns
121 into reusable templates that accelerate future evolu-
122 tion. We conduct comprehensive experiments on
123 EffiBench-X(Qing et al., 2025), showing that CSE
124 consistently outperforms all baselines across di-
125 verse LLM backbones, achieves stronger efficiency
126 from early generations, and continues improving
127 throughout evolution. These results demonstrate
128 robust, backbone-agnostic gains with both fast-
129 starting and sustained progress.

2 Related Work 130

Code Generation with LLMs. Large Language
131 Models have demonstrated remarkable capabilities
132 in code generation (Dong et al., 2025; Liu et al.,
133 2025; Lyu et al., 2025; Zhu et al.; Lavon et al.,
134 2025; Yao et al., 2025). Recent advances span in-
135 struction tuning (WizardCoder (Luo et al., 2023),
136 Magicoder (Wei et al., 2024)), retrieval augmen-
137 tation (Lu et al., 2022), while specialized models
138 such as GPT-4o (Hurst et al., 2024) and DeepSeek-
139 Coder (Guo et al., 2024) have achieved strong
140 results on programming benchmarks. However,
141 recent evaluations consistently reveal that LLMs
142 tend to generate solutions that are "correct yet in-
143 efficient." For instance, EffiBench-X (Qing et al.,
144 2025) highlights a significant efficiency gap be-
145 tween model-generated code and human-written
146 canonical solutions. These findings underscore that
147 code generation capability does not equate to evo-
148 lution proficiency, necessitating the introduction
149 of post-generation systematic refinement mecha-
150 nisms. 151

Self-Evolution. To address single-turn genera-
152 tion limitations, self-evolution methods enable iter-
153 ative refinement through "generate-verify-refine"
154 cycles. Self-reflection (Madaan et al., 2023; Shinn
155 et al., 2023; Du et al., 2025; Sun et al., 2023)
156 approaches enable models to learn from execu-
157 tion feedback, though they focus on debugging
158 rather than algorithmic optimization. Such as
159 AfterBurner (Du et al., 2025) which perform lo-
160 cal refinement but suffer from initialization bias
161 and local optima. Population-based approaches
162 (Romera-Paredes et al., 2023; Liu et al., 2024b;
163 Lange et al., 2025) such as AlphaEvolve (Novikov
164

et al., 2025) employ evolutionary resampling with stochastic mutations, while SE-Agent (Lin et al., 2025) introduces trajectory-level evolution via step-wise recombination. However, these methods face low search efficiency due to unguided exploration through random mutations, and lack of experience reuse. They thus require extensive iterations and often fail to discover optimal solutions within limited budgets. Our CSE framework addresses this through diversified initialization, feedback-guided operations, and hierarchical memory for efficient, controlled evolution.

3 Problem Formulation

We formalize the algorithmic code efficiency optimization task as follows. Given a problem specification x describing functional requirements and constraints, the goal is to generate an implementation y that satisfies correctness while achieving optimal execution efficiency.

The optimization environment is defined as $\mathcal{O} = (\mathcal{X}, \mathcal{Y}, \mathcal{F})$, where \mathcal{X} represents the problem specification space, \mathcal{Y} denotes the solution space, and $\mathcal{F} : \mathcal{Y} \times \mathcal{X} \rightarrow \mathbb{R}$ is a reward function evaluating solution quality. The reward function captures both correctness and efficiency.

The optimization unfolds as a population-based evolutionary process over T iterations. At each step t , we maintain a population $\mathcal{P}_t = \{y_1^{(t)}, y_2^{(t)}, \dots, y_{N_t}^{(t)}\}$ of N_t candidate solutions. The evolutionary trajectory $\mathcal{T} = (\mathcal{P}_0, \mathcal{P}_1, \dots, \mathcal{P}_T)$ progresses through feedback-driven selection, mutation, and crossover operators. Our objective is to discover the optimal solution $y^* = \arg \max_{y \in \bigcup_{t=0}^T \mathcal{P}_t} \mathcal{F}(y, x)$, requiring efficient navigation of the solution space through controlled exploration rather than uncontrolled stochastic evolution.

4 Method

As illustrated in Figure 2, our method consists of three key components: **Diversified Planning Initialization**, **Genetic Evolution**, and **Hierarchical Evolution Memory**. Diversified Planning Initialization generates high-quality and diverse initial solutions through varied planning strategies, providing a strong foundation for subsequent evolution. Unlike prior black-box evolutionary approaches, Genetic Evolution enables fine-grained, controllable mutation to efficiently navigate toward optimal solutions. Hierarchical Evolution Memory

hierarchically summarizes both intra-task and inter-task experiences, providing search guidance for the evolutionary process. In the following subsections, we describe each component in detail.

4.1 Diversified Planning Initialization

To maximize the diversity of initial solutions and ensure broad coverage of the solution space, we employ a two-stage approach: diverse planning followed by completion. Specifically, we prompt the agent \mathcal{A}_θ with explicit diversity constraints to generate a set of high-level solution sketches $\mathcal{Z} = \{z_1, \dots, z_{N_{\text{init}}}\}$, where each sketch represents a semantically distinct strategy. For example, given a code generation task, the agent might propose fundamentally different approaches such as a greedy algorithm, dynamic programming, or bit manipulation optimization, rather than superficial variations of the same logic.

Subsequently, each solution sketch is instantiated into a concrete code implementation, forming the initial candidate solutions:

$$y_i^{(0)} \sim \mathcal{A}_\theta(y | x, z_i), \quad \forall i \in \{1, \dots, N_{\text{init}}\}, \quad (1)$$

where $y_i^{(0)}$ denotes the complete output generated by the model conditioned on the input specification x and solution sketch z_i at the initial stage. Through this approach, the initial population $\mathcal{P}_0 = \{y_1^{(0)}, \dots, y_{N_{\text{init}}}^{(0)}\}$ is no longer composed of random perturbations around a single mode, but instead achieves diverse coverage of the solution space. This ensures that the subsequent evolutionary process can explore multiple promising regions in parallel, significantly reducing the risk of premature convergence to a suboptimal local optimum.

4.2 Genetic Evolution

The goal of self-evolutionary update is to guide the model in searching for better trajectories based on existing ones. A key insight is that incorporating explicit control into the search process, rather than relying on uncontrolled stochastic evolution, can significantly improve search efficiency. To this end, we design a Genetic Evolution mechanism with the following components:

Parent Selection. We depart from prior evolutionary approaches (Lin et al., 2025) that exclusively select high-reward solutions, as low-reward solutions may also contain valuable parts. We design a probability-based parent selection strategy




Figure 2: **Overview of the CSE.** Our method consists of three key components: Diversified Planning Initialization, Genetic Evolution, and Hierarchical Evolution Memory.

where the selection probability of each candidate is proportional to its normalized reward:

$$P_{\text{select}}(y_i^{(t)}) = \frac{\mathcal{F}(y_i^{(t)}, x)}{\sum_{j=1}^{|\mathcal{P}_t|} \mathcal{F}(y_j^{(t)}, x)}, \quad (2)$$

where $P_{\text{select}}(y_i^{(t)})$ denotes the selection probability of candidate solution $y_i^{(t)}$, and \mathcal{P}_t represents the population at evolution step t . This mechanism implements a soft selection distribution that prioritizes high-reward individuals while retaining lower-reward individuals that may contain useful logic fragments or partial solutions for recombination.

Evolution Strategies. To enable fine-grained controlled evolution, we first prompt the agent to decompose the code y into a set of disjoint functional components $\{c_1, c_2, \dots, c_m\}$ (e.g., I/O parsing module, core algorithm logic, boundary condition handling). This functional decomposition provides the necessary structural foundation for subsequent fine-grained interventions. We then equip the agent with two controlled evolution strategies:

Controlled Mutation. The agent employs self-reflection to identify the specific faulty component c_{faulty} responsible for low reward. After localizing the problematic module, we perform targeted regeneration on c_{faulty} while keeping the remaining

$m - 1$ well-performing components frozen:

$$y_{\text{child}} = \{c_1, \dots, \text{Refine}(c_{\text{faulty}}), \dots, c_m\}. \quad (3)$$

This surgical repair strategy not only avoids disruptive interference with the global context but also significantly improves mutation efficiency.

Compositional Crossover. To facilitate the flow of advantageous traits across the population, we introduce compositional crossover, which performs logic-level recombination of strengths rather than naive textual concatenation. Suppose parent solutions y_A and y_B exhibit complementary advantages in different components (e.g., y_A has superior time complexity while y_B demonstrates better robustness). The crossover operator synthesizes these strengths structurally:

$$y_{\text{child}} = \text{Crossover}(\{c_{\text{time}}^{(A)}\}, \{c_{\text{robust}}^{(B)}\}), \quad (4)$$

where $c_{\text{time}}^{(A)}$ denotes the time-efficient component from solution y_A , and $c_{\text{robust}}^{(B)}$ represents the robustness-oriented component from solution y_B . This enables the agent to mimic the human practice of combining complementary strengths from different solutions.

4.3 Hierarchical Evolution Memory

To effectively leverage both intra-task and inter-task experiences, we propose Hierarchical Evolution Memory.

Local Memory. $\mathcal{M}_{\text{local}}$ aims to capture immediate experiences from intra-task search trajectories. At each evolutionary step t , we compare the reward change $\Delta_t = \mathcal{F}(y_{\text{child}}^{(t)}, x) - \mathcal{F}(y_{\text{parent}}^{(t)}, x)$ between the parent $y_{\text{parent}}^{(t)}$ and its child $y_{\text{child}}^{(t)}$. The agent extracts two types of critical experiences: success insights ($\Delta_t > 0$) that analyze what led to improvements and are marked as positive patterns to retain, and failure lessons ($\Delta_t \leq 0$) that analyze causes of reward degradation and are marked as negative constraints to avoid. This reflection process is formalized as:

$$m_t \leftarrow \text{Reflect}(y_{\text{child}}^{(t)}, y_{\text{parent}}^{(t)}, \Delta_t), \quad (5a)$$

$$\mathcal{M}_t^{\text{loc}} \leftarrow \text{Compress}(\mathcal{M}_{t-1}^{\text{loc}} \cup \{m_t\}), \quad (5b)$$

where m_t denotes the distilled experience at step t . At evolution step $t + 1$, the accumulated $\mathcal{M}_{\text{local}}$ is dynamically injected into the prompt context, forming bidirectional guidance: success insights explicitly instruct the model to reuse validated optimization strategies, while failure lessons prevent the model from repeating known mistakes. To prevent memory overflow as iterations accumulate, whenever $\mathcal{M}_t^{\text{loc}}$ exceeds a predefined length threshold, we perform semantic compression to maintain high information density in the local memory.

Global Memory. \mathcal{M}_{glb} aims to distill and reuse inter-task experiences. For each task τ , we collect all evolution steps and their reward changes. We keep the top- K improving useful steps and top- K degrading harmful steps (ranked by Δ), denoted by \mathcal{S}_τ^+ and \mathcal{S}_τ^- , respectively. The LLM distills a task-level global experience g_τ with \mathcal{S}_τ^+ , \mathcal{S}_τ^- and best solution y_τ^* and stores it in a vector database:

$$g_\tau \leftarrow \text{Reflect}(\mathcal{S}_\tau^+, \mathcal{S}_\tau^-, y_\tau^*), \quad (6a)$$

$$\mathcal{M}^{\text{glb}} \leftarrow \mathcal{M}^{\text{glb}} \cup \{g_\tau\}. \quad (6b)$$

At evolutionary step t , the agent generates N_q targeted retrieval queries based on the current evolutionary context (including the current code state, encountered errors, or performance bottlenecks):

$$\{q_t^{(n)}\}_{n=1}^{N_q} \leftarrow \text{GenerateQueries}(\text{Context}_t), \quad (7a)$$

$$\mathcal{E}_t^{\text{ret}} \leftarrow \text{Retrieve}(\mathcal{M}^{\text{glb}}, \{q_t^{(n)}\}_{n=1}^{N_q}), \quad (7b)$$

where $\{q_t^{(n)}\}_{n=1}^{N_q}$ represents the generated queries and $\mathcal{E}_t^{\text{ret}}$ denotes the retrieved relevant experiences. This mechanism ensures that the agent can precisely invoke past experiences from similar tasks when encountering specific challenges.

As summarized in Algorithm 1, CSE first generates diverse strategy sketches \mathcal{Z} and instantiates them into an initial population \mathcal{P}_0 with \mathcal{A}_θ . It then iterates for T steps: at iteration t , it samples parent solution(s) from \mathcal{P}_{t-1} via probabilistic selection (Eq. 2), retrieves relevant experiences $\mathcal{E}_t^{\text{ret}}$ from global memory \mathcal{M}^{glb} , and composes them with local memory $\mathcal{M}_{t-1}^{\text{loc}}$ as context. Conditioned on this context, the agent applies controlled mutation (Eq. 3) or compositional crossover (Eq. 4) to generate an offspring, evaluates it by $\mathcal{F}(\cdot, x)$, and updates \mathcal{P}_t and $\mathcal{M}_t^{\text{loc}}$ using the reward change Δ_t (Eq. 5). Finally, CSE returns the best solution y^* and updates \mathcal{M}^{glb} by distilling intra-task experiences g_τ from top- K improving and degrading steps (Eq. 6).

5 Experiments

5.1 Experimental Setup

Benchmark. We evaluate on EffiBench-X (Qing et al., 2025), which aggregates 623 algorithmic problems from major competitive programming platforms, including AtCoder, Codeforces, and LeetCode, spanning six programming languages. Each problem comes with strict time/memory limits and comprehensive test cases. We run experiments on two different languages (Python and C++) to assess the generality of our method. Following prior work (Qing et al., 2025), we report three normalized efficiency metrics: Execution-Time ratio (ET), Memory-Peak ratio (MP) and Memory-Integral ratio (MI), which compare the LLM-generated solution with the human reference on every problem. Detailed definitions and derivations are provided in Appendix B.

Baselines. We compare CSE against three code-generation paradigms: (1) Direct: a single-turn generation. (2) Self-Reflection: iterative modification of the current best solution based on its feedback (e.g., variants of EffiLearner (Huang et al., 2024) and AfterBurner (Du et al., 2025)). (3) SE-Agent (Lin et al., 2025): a trajectory-level self-evolving agent method (4) AlphaEvolve (Novikov et al., 2025): a representative self-evolving agent method; we reproduce it using the open-source implementation of OpenEvolve (Sharma, 2025). We

	Python			C++			Avg		
	ET	MP	MI	ET	MP	MI	ET	MP	MI
Qwen3-235B-A22B									
Direct	31.10%	49.13%	46.28%	17.42%	46.55%	19.24%	24.26%	47.84%	32.76%
Self-Reflection	48.49%	49.82%	50.89%	47.47%	48.00%	44.75%	47.98%	48.91%	47.82%
SE-Agent	48.57%	50.39%	49.63%	50.71%	48.25%	47.19%	49.64%	49.32%	48.41%
AlphaEvolve	48.70%	50.33%	51.47%	48.75%	48.67%	46.58%	48.73%	49.50%	49.03%
CSE (Ours)	49.06%	50.99%	52.38%	48.70%	49.03%	47.95%	48.88%	50.01%	50.17%
DeepSeek-v3-0324									
Direct	52.90%	58.89%	56.22%	44.21%	45.79%	41.01%	48.56%	52.34%	48.62%
Self-Reflection	57.35%	60.20%	61.18%	45.43%	46.53%	43.16%	51.39%	53.37%	52.17%
SE-Agent	60.09%	59.68%	60.69%	47.74%	46.42%	44.54%	53.92%	53.05%	52.62%
AlphaEvolve	58.86%	60.04%	60.24%	46.19%	46.41%	44.02%	52.53%	53.23%	52.13%
CSE (Ours)	61.06%	61.03%	62.80%	48.75%	46.89%	47.37%	54.91%	53.96%	55.09%
Claude-4.5-Sonnet									
Direct	65.43%	69.03%	67.31%	63.16%	69.16%	62.78%	64.30%	69.10%	65.05%
Self-Reflection	69.79%	71.16%	73.08%	70.29%	68.42%	67.43%	70.04%	69.79%	70.26%
SE-Agent	64.14%	70.58%	67.25%	72.93%	68.81%	70.61%	68.54%	69.70%	68.93%
AlphaEvolve	69.45%	69.50%	70.57%	71.07%	68.45%	67.66%	70.26%	68.98%	69.12%
CSE (Ours)	71.17%	70.39%	73.94%	75.29%	69.82%	74.88%	73.23%	70.11%	74.41%
GPT-5									
Direct	60.21%	62.31%	61.66%	60.02%	62.60%	56.60%	60.12%	62.46%	59.13%
Self-Reflection	62.21%	63.09%	63.72%	61.79%	62.08%	56.76%	62.00%	62.59%	60.24%
SE-Agent	61.74%	64.51%	65.36%	68.61%	62.70%	63.46%	65.18%	63.61%	64.41%
AlphaEvolve	63.30%	63.96%	65.53%	64.13%	63.05%	60.54%	63.72%	63.51%	63.04%
CSE (Ours)	65.46%	66.82%	68.10%	69.94%	64.42%	66.83%	67.70%	65.62%	67.47%

Table 1: **Main results on EffiBench-X (Python and C++)**. ET, MP, and MI measure execution time, peak memory, and memory integral ratio relative to human solutions (higher is better). Avg is the per-metric mean across Python and C++. Best results are in bold.

evaluate two open-source models (DeepSeek-V3-0324 (Liu et al., 2024a) and Qwen3-235B-A22B (Yang et al., 2025)) and two closed-source models (Claude-4.5-Sonnet and GPT-5).

Implementation Details. All methods (except Direct) share a 30-candidate budget per task; the best solution encountered in the trajectory is recorded. Following EffiLearner’s setup (Huang et al., 2024), efficiency is measured only on tasks already solved by Direct to decouple speed from correctness; if a method exhausts its budget without a valid solution, we fall back to the Direct baseline for that task, guaranteeing identical problem sets across evaluators. Across all methods, the reward is the raw memory–time integral, inverted into a maximization score to capture joint runtime and memory gains. See Appendix C for more details.

5.2 Main Results

Table 1 presents the main experimental results on EffiBench-X across Python and C++ under a fixed test-time budget of 30 candidates per task. CSE consistently achieves the best performance across




Figure 3: **Best-so-far MI vs. generations.** At each generation t , we report the *best-so-far* MI.

most three efficiency metrics (ET, MP, MI) on both programming languages, with particularly notable improvements on memory integral, demonstrating its effectiveness in discovering algorithmically efficient solutions within limited exploration budgets. The advantages hold across diverse model capabilities, from open-source mod-

Setting	ET	MP	MI
CSE (Full)	65.46%	66.82%	68.10%
w/o <i>Planning</i>	61.39%	64.40%	63.82%
w/o <i>Evolution</i>	62.16%	64.28%	64.72%
w/o <i>Memory</i>	59.87%	64.75%	63.08%

Table 2: **Ablation study.** *Planning* means diversified planning initialization; *Evolution* means genetic evolution; *Memory* means hierarchical evolution memory.

els (Qwen3-235B-A22B, DeepSeek-v3-0324) to state-of-the-art closed-source models (Claude-4.5-Sonnet, GPT-5), validating that CSE’s framework is model-agnostic and captures fundamental principles of efficient code evolution. Compared to population-based baselines AlphaEvolve and SE-Agent, CSE demonstrates clear superiority across most settings. This can be attributed to our key design that enables controlled evolution rather than uncontrolled stochastic exploration: through controlled mutation and compositional crossover, CSE achieves fine-grained, feedback-guided evolution that systematically navigate toward optimal solutions with higher exploration efficiency, while hierarchical memory allows the framework to leverage accumulated experiences from both previous iterations and related tasks to accelerate convergence and avoid repeated failures.

Beyond the final metrics, Figure 3 visualizes how performance evolves with increasing iteration budget. CSE not only reaches a higher best-so-far MI, but also improves more rapidly in early generations and continues to make progress in later generations, suggesting stronger budget utilization under the same 30-generation constraint.

5.3 Further Analysis

Ablation Studies on CSE. To investigate the individual contribution of each component in CSE, we conduct an ablation study where we systematically remove one component at a time while maintaining the same 30-candidate budget. Table 2 presents the results. We evaluate three variants: CSE without *Planning*, which eliminates the diversified initialization strategy; CSE without *Evolution*, which removes the genetic operators; and CSE without *Memory*, which discards the hierarchical evolution memory mechanism. All three components prove essential, with *Memory* showing the largest impact, followed by *Planning* and *Evolution*. The consistent performance drops across both ET and MP demonstrate that CSE’s effectiveness



Figure 4: **Synergy between *Memory* and other modules.** We report MI and the gain Δ MI from adding *Memory* to each module combination.

Method	#Imp.	Iter@Best	Last-10 #Imp.
SE-Agent	1.60	9.51	0.19
AlphaEvolve	0.90	7.44	0.06
CSE (Ours)	1.79	12.06	0.29

Table 3: **Statistics of Evolution dynamics.**

arises from the synergistic interplay of all three components rather than any single mechanism. We additionally provide qualitative case studies in Appendix D to visualize the evolution dynamics under each ablation.

Analysis of *Memory*. To determine whether *Memory*’s contribution is additive or conditional on other components, we compare different module combinations under the same 30-iteration budget. Fig 4 reports the MI and the gain from adding *Memory* (Δ MI). The results reveal that *Memory*’s effectiveness depends strongly on context. Adding *Memory* to *Planning* alone provides negligible benefit (Δ MI = -0.23), while combining it with *Evolution* yields substantial gains (Δ MI = $+2.68$). The strongest effect emerges when all three components are present (Δ MI = $+5.02$). This demonstrates that *Memory* amplifies controlled evolutionary processes rather than providing universal improvement. It is most valuable when the system can generate diverse candidates, refine them through evolution, and strategically revisit solutions—reinforcing guided exploration rather than offering standalone benefits.

Exploration on Evolution Dynamics. To understand when and how frequently improvements occur during evolution, we conduct a fine-grained analysis over 30-iteration runs. Table 3 reports




Figure 5: A Case Study of CSE evolution dynamics. To quantify progress, we plot the best-so-far **raw memory-time integral** (lower is better) against the number of generations. The case highlights the concrete logic of key initialization, mutation, and crossover steps, and contrasts the final evolved solution against the human solution.

three statistics: (i) the number of improvement times (#Imp.), measuring how many iterations yield efficiency gains over the previous best; (ii) the iteration at which the final solution is found (Iter@Best), indicating whether the best result appears early or late; and (iii) improvements in the last 10 generations (Last-10 #Imp.), quantifying the ability to sustain late-stage progress. The results show that CSE achieves substantially more frequent improvements than baselines (#Imp. = 1.79 vs. 0.90 for AlphaEvolve and 1.60 for SE-Agent) and notably stronger late-stage progress (Last-10 #Imp. = 0.29 vs. 0.06 for AlphaEvolve and 0.19 for SE-Agent). This indicates that CSE continues exploring throughout the entire budget rather than plateauing early, contributing to its superior performance in Table 1.

5.4 Case Study

To demonstrate CSE in practice, Figure 5 shows the complete 30-iteration evolution on EffiBench-X ringo’s-favorite-numbers-3. The trajectory illustrates how our mechanisms work together: initialization explores diverse solution hypotheses, including a precomputation-centric strategy (Iter 1) versus a reformulated k-space search (Iter 5), showing CSE can switch high-level formulations rather than merely refining a single approach. Once the stronger structure emerges, mutations fix bottle-

necks (e.g., inefficient checking or missing guards) while preserving the effective skeleton, yielding steady improvements. Crossover then merges complementary strengths from different parents, such as combining robust core search with cleaner predicates. Throughout, hierarchical evolution memory guides the search away from explored variants toward novel directions, reducing redundancy. The final solution differs markedly from the human reference in both design and implementation, achieving better efficiency.

6 Conclusion

We present Controlled Self-Evolution (CSE), a novel framework that addresses the low exploration efficiency of existing self-evolution methods for code optimization. By identifying three fundamental limitations, we propose CSE, including Diversified Planning Initialization, Genetic Evolution and Hierarchical Evolution Memory. Experiments on EffiBench-X demonstrate that CSE consistently outperforms all baselines across various LLM backbones, achieving higher efficiency from early generations while maintaining continuous improvement throughout evolution. Our work highlights the importance of controlled, feedback-driven exploration in self-evolution paradigms for code generation.

553
554
555
556
557
558
559
560
561
562
563

564

565
566
567
568
569

570
571
572
573

574
575

576
577
578
579
580
581
582

583
584
585
586

587
588
589
590
591

592
593
594
595
596

597
598
599
600
601
602

Limitations

CSE can continuously improve solution quality through multi-round evolution. However, we have not yet explored how to amortize this iterative optimization into the base model. A promising yet underexplored direction is to distill CSE’s evolution trajectories into RL-style training (Yu et al., 2025; Zheng et al., 2025; Jiang et al., 2025) signals to strengthen the base model, enabling comparable or better optimization and producing higher-quality solutions.

References

Josh Achiam, Steven Adler, Sandhini Agarwal, Lama Ahmad, Ilge Akkaya, Florencia Leoni Aleman, Diogo Almeida, Janko Altenschmidt, Sam Altman, Shyamal Anadkat, et al. 2023. Gpt-4 technical report. *arXiv preprint arXiv:2303.08774*.

Zheng Cai, Maosong Cao, Haojiong Chen, Kai Chen, Keyu Chen, Xin Chen, Xun Chen, Zehui Chen, Zhi Chen, Pei Chu, et al. 2024. Internlm2 technical report. *arXiv preprint arXiv:2403.17297*.

Mark Chen. 2021. Evaluating large language models trained on code. *arXiv preprint arXiv:2107.03374*.

Gheorghe Comanici, Eric Bieber, Mike Schaeckermann, Ice Pasupat, Noveen Sachdeva, Inderjit Dhillon, Marcel Blistein, Ori Ram, Dan Zhang, Evan Rosen, et al. 2025. Gemini 2.5: Pushing the frontier with advanced reasoning, multimodality, long context, and next generation agentic capabilities. *arXiv preprint arXiv:2507.06261*.

Yihong Dong, Xue Jiang, Jiaru Qian, Tian Wang, Kechi Zhang, Zhi Jin, and Ge Li. 2025. A survey on code generation with llm-based agents. *arXiv preprint arXiv:2508.00083*.

Mingzhe Du, Luu Anh Tuan, Yue Liu, Yuhao Qing, Dong Huang, Xinyi He, Qian Liu, Zejun Ma, and See-kiong Ng. 2025. Afterburner: Reinforcement learning facilitates self-improving code efficiency optimization. *arXiv preprint arXiv:2505.23387*.

Abhimanyu Dubey, Abhinav Jauhri, Abhinav Pandey, Abhishek Kadian, Ahmad Al-Dahle, Aiesha Letman, Akhil Mathur, Alan Schelten, Amy Yang, Angela Fan, et al. 2024. The llama 3 herd of models. *arXiv preprint arXiv:2407.21783*.

Jinyuan Fang, Yanwen Peng, Xi Zhang, Yingxu Wang, Xinhao Yi, Guibin Zhang, Yi Xu, Bin Wu, Siwei Liu, Zihao Li, et al. 2025. A comprehensive survey of self-evolving ai agents: A new paradigm bridging foundation models and lifelong agentic systems. *arXiv preprint arXiv:2508.07407*.

Huan-ang Gao, Jiayi Geng, Wenyue Hua, Mengkang Hu, Xinzhe Juan, Hongzhang Liu, Shilong Liu, Jiahao Qiu, Xuan Qi, Yiran Wu, et al. 2025. A survey of self-evolving agents: On path to artificial super intelligence. *arXiv preprint arXiv:2507.21046*.

Daya Guo, Dejian Yang, Haowei Zhang, Junxiao Song, Ruoyu Zhang, Runxin Xu, Qihao Zhu, Shirong Ma, Peiyi Wang, Xiao Bi, et al. 2025. Deepseek-r1: Incentivizing reasoning capability in llms via reinforcement learning. *arXiv preprint arXiv:2501.12948*.

Daya Guo, Qihao Zhu, Dejian Yang, Zhenda Xie, Kai Dong, Wentao Zhang, Guanting Chen, Xiao Bi, Yu Wu, YK Li, et al. 2024. Deepseek-coder: When the large language model meets programming—the rise of code intelligence. *arXiv preprint arXiv:2401.14196*.

Dong Huang, Jianbo Dai, Han Weng, Puzhen Wu, Yuhao Qing, Heming Cui, Zhijiang Guo, and Jie Zhang. 2024. Efficlearner: Enhancing efficiency of generated code via self-optimization. *Advances in Neural Information Processing Systems*, 37:84482–84522.

Binyuan Hui, Jian Yang, Zeyu Cui, Jiayi Yang, Dayiheng Liu, Lei Zhang, Tianyu Liu, Jiajun Zhang, Bowen Yu, Keming Lu, et al. 2024. Qwen2. 5-coder technical report. *arXiv preprint arXiv:2409.12186*.

Aaron Hurst, Adam Lerer, Adam P Goucher, Adam Perelman, Aditya Ramesh, Aidan Clark, AJ Ostrow, Akila Welihinda, Alan Hayes, Alec Radford, et al. 2024. Gpt-4o system card. *arXiv preprint arXiv:2410.21276*.

Juyong Jiang, Fan Wang, Jiasi Shen, Sungju Kim, and Sunghun Kim. 2024. A survey on large language models for code generation. *arXiv preprint arXiv:2406.00515*.

Xue Jiang, Yihong Dong, Mengyang Liu, Hongyi Deng, Tian Wang, Yongding Tao, Rongyu Cao, Binhua Li, Zhi Jin, Wenpin Jiao, et al. 2025. Coderl+: Improving code generation via reinforcement with execution semantics alignment. *arXiv preprint arXiv:2510.18471*.

Robert Tjarko Lange, Yuki Imajuku, and Edoardo Cetin. 2025. Shinkaevolve: Towards open-ended and sample-efficient program evolution. *arXiv preprint arXiv:2509.19349*.

Boaz Lavon, Shahar Katz, and Lior Wolf. 2025. Execution guided line-by-line code generation. *arXiv preprint arXiv:2506.10948*.

Jiaye Lin, Yifu Guo, Yuzhen Han, Sen Hu, Ziyi Ni, Licheng Wang, Mingguang Chen, Hongzhang Liu, Ronghao Chen, Yangfan He, et al. 2025. Se-agent: Self-evolution trajectory optimization in multi-step reasoning with llm-based agents. *arXiv preprint arXiv:2508.02085*.

657	Aixin Liu, Bei Feng, Bing Xue, Bingxuan Wang,	Noah Shinn, Federico Cassano, Ashwin Gopinath,	713
658	Bochao Wu, Chengda Lu, Chenggang Zhao, Chengqi	Karthik Narasimhan, and Shunyu Yao. 2023. Re-	714
659	Deng, Chenyu Zhang, Chong Ruan, et al. 2024a.	flexion: Language agents with verbal reinforcement	715
660	Deepseek-v3 technical report. <i>arXiv preprint</i>	learning. <i>Advances in Neural Information Process-</i>	716
661	<i>arXiv:2412.19437</i> .	<i>ing Systems</i> , 36:8634–8652.	717
662	Fei Liu, Xialiang Tong, Mingxuan Yuan, Xi Lin, Fu Luo,	Haotian Sun, Yuchen Zhuang, Lingkai Kong, Bo Dai,	718
663	Zhenkun Wang, Zhichao Lu, and Qingfu Zhang.	and Chao Zhang. 2023. Adaplaner: Adaptive plan-	719
664	2024b. Evolution of heuristics: Towards efficient au-	ning from feedback with language models. <i>Advances</i>	720
665	tomatic algorithm design using large language model.	<i>in neural information processing systems</i> , 36:58202–	721
666	In <i>International Conference on Machine Learning</i>	58245.	722
667	(ICML).		
668	Jiawei Liu, Nirav Diwan, Zhe Wang, Haoyu Zhai, Xi-	Kimi Team, Angang Du, Bofei Gao, Bowei Xing,	723
669	aona Zhou, Kiet A Nguyen, Tianjiao Yu, Muntasir	Changjiu Jiang, Cheng Chen, Cheng Li, Chenjun	724
670	Wahed, Yinlin Deng, Hadjer Benkraouda, et al.	Xiao, Chenzhuang Du, Chonghua Liao, et al. 2025.	725
671	2025. Purpcode: Reasoning for safer code gener-	Kimi k1. 5: Scaling reinforcement learning with llms.	726
672	ation. <i>arXiv preprint arXiv:2507.19060</i> .	<i>arXiv preprint arXiv:2501.12599</i> .	727
673	Shuai Lu, Nan Duan, Hojae Han, Daya Guo, Seung-	Evan Wang, Federico Cassano, Catherine Wu, Yun-	728
674	won Hwang, and Alexey Svyatkovskiy. 2022. Reacc:	feng Bai, Will Song, Vaskar Nath, Ziwen Han, Sean	729
675	A retrieval-augmented code completion framework.	Hendryx, Summer Yue, and Hugh Zhang. 2024. Plan-	730
676	<i>arXiv preprint arXiv:2203.07722</i> .	ning in natural language improves llm search for code	731
677	Ziyang Luo, Can Xu, Pu Zhao, Qingfeng Sun, Xi-	generation. <i>arXiv preprint arXiv:2409.03733</i> .	732
678	ubo Geng, Wenxiang Hu, Chongyang Tao, Jing Ma,	Huanting Wang, Jingzhi Gong, Huawei Zhang, Jie Xu,	733
679	Qingwei Lin, and Daxin Jiang. 2023. Wizardcoder:	and Zheng Wang. 2025a. Ai agentic programming:	734
680	Empowering code large language models with evol-	A survey of techniques, challenges, and opportunities.	735
681	instruct. <i>arXiv preprint arXiv:2306.08568</i> .	<i>arXiv preprint arXiv:2508.11126</i> .	736
682	Zhiyi Lyu, Jianguo Huang, Yanchen Deng, Steven Hoi,	Zhengren Wang, Rui Ling, Chufan Wang, Yongan	737
683	and Bo An. 2025. Let’s revise step-by-step: A unified	Yu, Sizhe Wang, Zhiyu Li, Feiyu Xiong, and Wen-	738
684	local search framework for code generation with llms.	tao Zhang. 2025b. Maintaincode: Maintainable	739
685	<i>arXiv preprint arXiv:2508.07434</i> .	code generation under dynamic requirements. <i>arXiv</i>	740
686	Aman Madaan, Niket Tandon, Prakhar Gupta, Skyler	<i>preprint arXiv:2503.24260</i> .	741
687	Hallinan, Luyu Gao, Sarah Wiegrefe, Uri Alon,	Yuxiang Wei, Zhe Wang, Jiawei Liu, Yifeng Ding, and	742
688	Nouha Dziri, Shrimai Prabhunoye, Yiming Yang,	Lingming Zhang. 2024. Magicoder: empowering	743
689	et al. 2023. Self-refine: Iterative refinement with	code generation with oss-instruct. In <i>Proceedings of</i>	744
690	self-feedback. <i>Advances in Neural Information Pro-</i>	<i>the 41st International Conference on Machine Learn-</i>	745
691	<i>cessing Systems</i> , 36:46534–46594.	<i>ing</i> , pages 52632–52657.	746
692	Alexander Novikov, Ngân Vũ, Marvin Eisenberger,	An Yang, Anfeng Li, Baosong Yang, Beichen Zhang,	747
693	Emilien Dupont, Po-Sen Huang, Adam Zsolt Wag-	Binyuan Hui, Bo Zheng, Bowen Yu, Chang Gao,	748
694	ner, Sergey Shirobokov, Borislav Kozlovskii, Fran-	Chengen Huang, Chenxu Lv, et al. 2025. Qwen3	749
695	cisco JR Ruiz, Abbas Mehrabian, et al. 2025. Alpha-	technical report. <i>arXiv preprint arXiv:2505.09388</i> .	750
696	evolve: A coding agent for scientific and algorithmic		
697	discovery. <i>arXiv preprint arXiv:2506.13131</i> .	Feng Yao, Zilong Wang, Liyuan Liu, Junxia Cui,	751
698	Yuhao Qing, Boyu Zhu, Mingzhe Du, Zhijiang Guo,	Li Zhong, Xiaohan Fu, Haohui Mai, Vish Krishnan,	752
699	Terry Yue Zhuo, Qianru Zhang, Jie M Zhang, Hem-	Jianfeng Gao, and Jingbo Shang. 2025. Training lan-	753
700	ing Cui, Siu-Ming Yiu, Dong Huang, et al. 2025.	guage models to generate quality code with program	754
701	Effibench-x: A multi-language benchmark for mea-	analysis feedback. <i>arXiv preprint arXiv:2505.22704</i> .	755
702	suring efficiency of llm-generated code. <i>arXiv</i>		
703	<i>preprint arXiv:2505.13004</i> .	Qiyang Yu, Zheng Zhang, Ruofei Zhu, Yufeng Yuan,	756
704	Bernardino Romera-Paredes, Mohammadamin	Xiaochen Zuo, Yu Yue, Weinan Dai, Tiantian Fan,	757
705	Barekatin, Alexander Novikov, Matej Balog,	Gaohong Liu, Lingjun Liu, et al. 2025. Dapo: An	758
706	M. Pawan Kumar, Emilien Dupont, Francisco J. R.	open-source llm reinforcement learning system at	759
707	Ruiz, Jordan Ellenberg, Pengming Wang, Omar	scale. <i>arXiv preprint arXiv:2503.14476</i> .	760
708	Fawzi, Pushmeet Kohli, and Alhussein Fawzi. 2023.	Chujie Zheng, Shixuan Liu, Mingze Li, Xiong-Hui	761
709	Mathematical discoveries from program search with	Chen, Bowen Yu, Chang Gao, Kai Dang, Yuqiong	762
710	large language models. <i>Nature</i> .	Liu, Rui Men, An Yang, et al. 2025. Group	763
711	Asankhaya Sharma. 2025. Openevolve: an open-source	sequence policy optimization. <i>arXiv preprint</i>	764
712	evolutionary coding agent.	<i>arXiv:2507.18071</i> .	765

766 Derui Zhu, Dingfan Chen, Jens Grossklags, Walter
767 Pretschner, Weiyi Shang, et al. More than just func-
768 tional: Llm-as-a-critique for efficient code generation.
769 In *The Thirty-ninth Annual Conference on Neural In-*
770 *formation Processing Systems*.

A Algorithmic Overview of CSE

We summarize the end-to-end workflow of Controlled Self-Evolution (CSE) in Algorithm 1. CSE proceeds in three stages: (i) diversified planning initialization constructs a diverse initial population \mathcal{P}_0 by instantiating strategy sketches \mathcal{Z} ; (ii) an iterative evolutionary loop performs reward-based parent selection, retrieves inter-task experiences from \mathcal{M}^{glb} and injects them together with the intra-task memory $\mathcal{M}_{t-1}^{\text{loc}}$ into the context, then applies controlled mutation (REFINE) or compositional crossover (CROSSOVER) to generate $y_{\text{child}}^{(t)}$; (iii) after T iterations, we return the best solution y^* and distill task-level experience g_τ from top- K improving/degrading steps to update \mathcal{M}^{glb} .

B Evaluation Metrics.

To quantify the efficiency of LLM-generated solutions relative to human-expert-written reference solutions, we follow prior work and report three normalized metrics: Execution Time (ET), Memory Peak (MP), and Memory Integral (MI). We evaluate on N problems, indexed by $i \in \{1, \dots, N\}$. For each problem i , we measure the execution time, peak memory usage, and memory–time integral for both the human reference solution (superscript H) and the LLM-generated solution (superscript L), under the same evaluation protocol.

Failure Handling. If the LLM-generated solution for problem i fails to pass all test cases or encounters a runtime error (e.g., timeout, crash), we assign a score of 0 for that problem for all metrics.

Clipping. To both (i) preserve the ability to credit solutions that outperform the human reference (ratios > 1) and (ii) limit the influence of extreme outliers, we apply

$$\text{clip}(z, 0, k) = \min(\max(z, 0), k).$$

In all experiments we set $k = 5$ (shared across all methods), which retains sufficient headroom for surpassing human references while preventing a small number of extreme cases from dominating the average.

(1) Execution Time (ET). Let T_i^H denote the raw execution time of the human reference solution required to pass all test cases for problem i , and T_i^L denote the execution time of the LLM-generated solution (conditioned on passing). The per-problem

ET score is

$$s_i^T = \begin{cases} 0, & \text{if solution fails,} \\ \text{clip}\left(\frac{T_i^H}{T_i^L}, 0, 5\right), & \text{otherwise,} \end{cases} \quad (8)$$

and the overall ET is the mean score across problems, reported in a scaled form for readability:

$$\text{ET}(\%) = \left(\frac{1}{N} \sum_{i=1}^N s_i^T \right) \times 100\%. \quad (9)$$

(2) Memory Peak (MP). Let M_i^H and M_i^L denote the raw peak memory usage of the human reference and the LLM-generated solution on problem i , respectively. The per-problem MP score is

$$s_i^M = \begin{cases} 0, & \text{if solution fails,} \\ \text{clip}\left(\frac{M_i^H}{M_i^L}, 0, 5\right), & \text{otherwise,} \end{cases} \quad (10)$$

and the overall MP is

$$\text{MP}(\%) = \left(\frac{1}{N} \sum_{i=1}^N s_i^M \right) \times 100\%. \quad (11)$$

(3) Memory Integral (MI). To measure lifetime memory consumption, we define the raw memory–time integral for one execution as

$$A = \int_0^{T_{\text{total}}} m(t) dt, \quad (12)$$

where $m(t)$ is the memory usage trace at time t and T_{total} is the total execution time. This integral is numerically approximated from high-resolution profiling traces. Let A_i^H and A_i^L denote the memory integrals of the human reference and the LLM-generated solution on problem i , respectively. The per-problem MI score is

$$s_i^A = \begin{cases} 0, & \text{if solution fails,} \\ \text{clip}\left(\frac{A_i^H}{A_i^L}, 0, 5\right), & \text{otherwise,} \end{cases} \quad (13)$$

and the overall MI is

$$\text{MI}(\%) = \left(\frac{1}{N} \sum_{i=1}^N s_i^A \right) \times 100\%. \quad (14)$$

C Implementation Details

Experimental Setup Rationale. We follow the evaluation protocol used in EffiLearner (Huang

Algorithm 1 Controlled Self-Evolution (CSE)

Require: Problem specification x , Global memory \mathcal{M}^{glb} , Max iterations T , retrieval queries N_q , top- K size K

Ensure: Optimized solution y^*

```
1:  $\mathcal{Z} \leftarrow \text{PlanStrategies}(x)$ 
2:  $\mathcal{P}_0 \leftarrow \{y_i^{(0)} \sim \mathcal{A}_\theta(y \mid x, z_i) \mid z_i \in \mathcal{Z}\}$ 
3:  $\mathcal{M}_0^{\text{loc}} \leftarrow \emptyset$ 
4:  $\mathcal{S}_\tau \leftarrow \emptyset$ 
5: for  $t = 1$  to  $T$  do
6:   Compute  $\{\mathcal{F}(y, x)\}_{y \in \mathcal{P}_{t-1}}$ 
7:   Sample  $y_{\text{parent}}^{(t)} \leftarrow \text{SelectParent}(\mathcal{P}_{t-1})$  with  $P_{\text{select}}(y) = \frac{\mathcal{F}(y, x)}{\sum_{y' \in \mathcal{P}_{t-1}} \mathcal{F}(y', x)}$ 
8:    $\{q_t^{(n)}\}_{n=1}^{N_q} \leftarrow \text{GenerateQueries}(\text{Context}_t)$ 
9:    $\mathcal{E}_t^{\text{ret}} \leftarrow \text{Retrieve}(\mathcal{M}^{\text{glb}}, \{q_t^{(n)}\}_{n=1}^{N_q})$ 
10:   $\text{Context}'_t \leftarrow \text{Compose}(\text{Context}_t, \mathcal{M}_{t-1}^{\text{loc}}, \mathcal{E}_t^{\text{ret}})$ 
11:   $\text{Op}_t \leftarrow \text{ChooseOp}(\text{Refine}, \text{Crossover})$ 
12:  if  $\text{Op}_t = \text{Refine}$  then
13:     $y_{\text{child}}^{(t)} \leftarrow \text{Refine}(y_{\text{parent}}^{(t)} \mid \text{Context}'_t)$ 
14:  else
15:    Sample  $y'_{\text{parent}} \leftarrow \text{SelectParent}(\mathcal{P}_{t-1})$  with  $P_{\text{select}}(\cdot)$ 
16:     $y_{\text{child}}^{(t)} \leftarrow \text{Crossover}(y_{\text{parent}}^{(t)}, y'_{\text{parent}} \mid \text{Context}'_t)$ 
17:  end if
18:   $\Delta_t \leftarrow \mathcal{F}(y_{\text{child}}^{(t)}, x) - \mathcal{F}(y_{\text{parent}}^{(t)}, x)$ 
19:   $\mathcal{P}_t \leftarrow \text{UpdatePopulation}(\mathcal{P}_{t-1}, y_{\text{child}}^{(t)}, \mathcal{F}(y_{\text{child}}^{(t)}, x))$ 
20:   $m_t \leftarrow \text{Reflect}(y_{\text{child}}^{(t)}, y_{\text{parent}}^{(t)}, \Delta_t)$ 
21:   $\mathcal{M}_t^{\text{loc}} \leftarrow \text{Compress}(\mathcal{M}_{t-1}^{\text{loc}} \cup \{m_t\})$ 
22:   $\mathcal{S}_\tau \leftarrow \mathcal{S}_\tau \cup \{(y_{\text{parent}}^{(t)}, y_{\text{child}}^{(t)}, \Delta_t)\}$ 
23: end for
24:  $y^* \leftarrow \arg \max_{y \in \bigcup_{t=0}^T \mathcal{P}_t} \mathcal{F}(y, x)$ 
25:  $\mathcal{S}_\tau^+ \leftarrow \text{TopK}_{\max \Delta}(\mathcal{S}_\tau, K)$ 
26:  $\mathcal{S}_\tau^- \leftarrow \text{TopK}_{\min \Delta}(\mathcal{S}_\tau, K)$ 
27:  $g_\tau \leftarrow \text{Reflect}(\mathcal{S}_\tau^+, \mathcal{S}_\tau^-, y^*)$ 
28:  $\mathcal{M}^{\text{glb}} \leftarrow \mathcal{M}^{\text{glb}} \cup \{g_\tau\}$ 
29: return  $y^*$ 
```

et al., 2024) to decouple *efficiency* from *correctness* when comparing iterative optimization methods. In particular, efficiency is measured only on tasks that are already solved by DIRECT. This restriction ensures that all evaluated solutions are functionally correct, and avoids an apples-to-oranges comparison where different methods solve different subsets of tasks, making efficiency scores not directly comparable. Moreover, if an iterative method exhausts the shared 30-candidate budget without producing a valid solution, we fall back to the DIRECT solution for that task, guaranteeing an identical set of evaluated problems across methods under a fixed budget.

Evaluation Protocol. Following our main experimental setup, each problem is evaluated on **100 test cases** with a time limit of **10 s** and a memory limit of **1024 MB**. If a candidate program triggers a runtime error, exceeds the time limit (TLE), or violates the memory limit (MLE), we mark it as a *failure* and assign it a reported metric of 0 (for ET/MP/MI).

Raw Signal for Evolution. While the paper reports the *normalized* metrics (ET/MP/MI) w.r.t. the human reference solution, the *evolution process* is guided by the **raw memory–time integral** value, denoted as A (lower is better). To reduce measure-

ment noise, we evaluate each candidate on the same machine for **5 repeated runs**; we remove outliers by discarding the maximum and minimum runs and take the mean of the remaining runs as the final A . If any run results in failure (runtime error, TLE, or MLE), the candidate is treated as failed.

Reward and Parent Selection. Since smaller A indicates better efficiency, we convert A into a maximization-form reward for selection:

$$\mathcal{F} = \frac{1}{A + \epsilon},$$

where we set $\epsilon = 0.001$. We sample parents proportional to their reward, i.e.,

$$p_i = \frac{\mathcal{F}_i}{\sum_j \mathcal{F}_j}.$$

Failed candidates are assigned $\mathcal{F} = 0$, and thus will not be selected as parents.

Search Budget and Operator Schedule. We run evolution for $T = 30$ iterations. At each iteration, we generate exactly **one** child candidate, resulting in a total budget of 30 evolved candidates per task. We adopt a **deterministic alternating schedule** for the two evolution operators: **controlled mutation** and **compositional crossover** are executed in an interleaving order across iterations. Concretely, we apply mutation on odd iterations and crossover on even iterations, ensuring a stable and reproducible operator mixture throughout evolution.

Initialization and Retrieval Hyperparameters. We use $N_{\text{init}} = 5$ diverse initialization plans per problem. For global memory retrieval, we generate $N_q = 3$ queries and retrieve top- $K_m = 3$ memories per query, resulting in at most $N_q \cdot K_m$ retrieved entries.

Embedding Model and Similarity Search. We encode both queries and memory entries using **Qwen3-8B-Embedding**. We perform nearest-neighbor retrieval via **cosine similarity** and return the top- K_m entries for each query.

Module Decomposition Template. To enable controlled mutation and crossover, we enforce a **fixed decomposition template** (in Figure 9) and require the LLM to output code in structured modules (e.g., [A] Input, [B] Core, [C] Optimization module). The number of modules is fixed and determined by the template. All subsequent mutation/crossover operations are applied at the module


level, which helps maintain interface consistency and reduces unintended edits outside the targeted components.

Local Memory Compression. We maintain a local memory buffer for intra-task experiences. To prevent memory overflow in the prompt context, we perform semantic compression whenever the local memory exceeds **1000 tokens**.


Global Memory Distillation and Construction Order. For each task τ , we keep the top- K improving and top- K degrading steps (ranked by Δ) to distill a task-level experience item g_τ , with $K = 5$. To ensure determinism and reproducibility, we fix a single task-processing order and apply the same order to all methods when constructing and using the global memory. After each processed task, we distill the evolved trajectory into compact experience items and add them into the global memory for retrieval in subsequent tasks.

D Ablation Case Studies


Case Study: Diversified Planning Initialization. Figure 6a compares full CSE with an ablated variant that removes diversified planning initialization. We observe a clear initialization bias: without diversified planning, the search starts from a substantially worse region (best-so-far ≈ 1230.5) and remains almost unchanged for several generations, indicating that the initial candidates are clustered around a low-quality mode. Although the ablated run eventually makes progress (dropping to ≈ 929.3 and ≈ 761.2 around mid-early generations), it still struggles to escape the basin and only reaches a plateau at ≈ 433.7 after ~ 12 generations, with little improvement thereafter. In contrast, diversified planning immediately provides a much stronger and more promising starting point (iter 1: 886.1), enabling an early “algorithmic jump” within a few iterations (iter 5: 197.5, a 77.7% reduction), followed by continued refinement (iter 8: 176.9). More importantly, starting from diverse, semantically distinct strategy sketches allows the evolutionary loop to explore multiple high-potential basins in parallel, which later supports a second breakthrough (iter 22: 95.7) and a final improvement (iter 25: 93.9). Overall, removing diversified planning causes prolonged stagnation and a much higher final plateau (≈ 433.7 vs. 93.9), demonstrating that diversified planning is crucial for overcoming poor initial modes and accelerating the discov-



(a) **w/o Diversified Planning Initialization.** Best-so-far performance over generations for full CSE (red) versus removing diversified planning initialization (blue).



(b) **w/o Genetic Evolution.** Best-so-far performance over generations for full CSE (red) versus removing genetic evolution (blue).



(c) **w/o Hierarchical Evolution Memory.** Best-so-far performance over generations for full CSE (red) versus removing hierarchical experience memory (blue).

Figure 6: **Case studies of ablation evolution dynamics.** We compare the best-so-far **raw memory-time integral** (lower is better) across generations between full CSE (red) and three ablated variants (blue). Yellow callouts highlight representative milestone solutions along the CSE trajectory (e.g., iter 1, iter 5).

ery of high-efficiency solution structures.

Case Study: Genetic Evolution. Figure 6b illustrates the effect of removing *Genetic Evolution* (i.e., controlled mutation and compositional crossover). Although the ablated variant starts from a relatively strong initial point (best-so-far ≈ 569.4), it quickly becomes stagnant: the curve stays nearly flat for the first ~ 10 generations and only achieves a modest improvement to ≈ 377.9 around the mid-run, after which it plateaus again until the end of the budget. In contrast, full CSE exhibits step-wise breakthroughs characteristic of effective evolutionary search: despite a worse starting best (iter 1: 886.1), it rapidly triggers a major early jump to iter 5 (197.5; $\downarrow 77.7\%$), further refines to iter 8 (176.9), and later achieves another large improvement at

iter 22 (95.7; $\downarrow 45.9\%$) followed by a final gain at iter 25 (93.9). This gap suggests that the core benefit of Genetic Evolution is not merely producing more variants, but enabling *structure-preserving, feedback-aligned* updates: controlled mutation can surgically repair the bottleneck component without disrupting already-correct parts (Eq. 3), while compositional crossover can recombine complementary strengths across candidates rather than performing superficial text-level mixing (Eq. 4). Without these operators, the search lacks an effective mechanism to translate evaluation feedback into high-reward structural edits, leading to long plateaus and a much higher final performance floor (≈ 377.9 vs. 93.9).

Case Study: Hierarchical Evolution Memory. Figure 6c examines the impact of removing *Hi-*

1001 *erarchical Evolution Memory*. Without memory,
1002 the search trajectory exhibits pronounced plateaus
1003 and delayed progress: the best-so-far performance
1004 remains extremely high for multiple generations
1005 (around ~ 1200), then only drops to ~ 910.6 , and
1006 later makes a larger decrease to roughly ~ 405.9
1007 before entering a long stagnation period near ~ 400 .
1008 Even late in the run, the memory-ablated variant
1009 only achieves a modest improvement to ~ 328.5
1010 and then plateaus again, indicating that exploration
1011 repeatedly revisits similar low-yield regions rather
1012 than systematically leveraging past lessons. In con-
1013 trast, full CSE quickly consolidates early improve-
1014 ments (iter 5: 197.5; iter 8: 176.9) and, crucially,
1015 avoids long mid-run stagnation by triggering a late-
1016 stage breakthrough (iter 22: 95.7; $\downarrow 45.9\%$) fol-
1017 lowed by a final refinement (iter 25: 93.9). This
1018 divergence highlights the role of memory as a
1019 feedback-to-action bridge: local memory distills
1020 parent-child reward changes into actionable suc-
1021 cess patterns and failure constraints (Eq. 5), reduc-
1022 ing redundant trial-and-error within the task, while
1023 global memory retrieval supplies reusable optimiza-
1024 tion heuristics from prior tasks that steer generation
1025 toward unexplored but promising directions (Eq. 6).
1026 Removing this mechanism substantially slows the
1027 transition from incremental tweaks to high-impact
1028 structural changes, yielding a much higher final
1029 performance floor (~ 328.5 vs. 93.9).

1030 **E Prompt Templates**

1031 This appendix section provides the exact sys-
1032 tem/user prompts used by our pipeline. The
1033 templates cover diversified planning to propose
1034 multiple high-performance strategies; implemen-
1035 tation prompts that synthesize a complete pro-
1036 gram under explicit constraints; slot-based de-
1037 composition prompts that diagnose correctness
1038 and efficiency by comparing a target solution
1039 against a reference baseline; evolution prompts
1040 for controlled mutation (reflection and refine)
1041 and compositional crossover (hybrid synthesis);
1042 and memory prompts that extract, compress, re-
1043 trieve, and aggregate reusable success/failure ex-
1044 periences. Across stages, prompts emphasize
1045 correctness-first optimization, favor algorithmic
1046 improvements over micro-optimizations, and opti-
1047 mize the raw memory-time integral to encourage
1048 balanced runtime-memory trade-offs.

System Prompt

You are a world-class Algorithm Engineer. Design EXACTLY K distinct, high-performance strategies for the given problem.

Guidelines:

1. **Diversity**: Strategies MUST differ in algorithmic paradigms (DP, Greedy, Two Pointers, Bit Manipulation, etc.) or core data structures.
2. **Performance**: Prioritize optimal Time/Space complexity. Avoid brute-force unless necessary.
3. **Content**: Each strategy must include:
 - Core algorithmic logic
 - Key data structures
 - Expected Time/Space complexity (Big-O)

Output Format:

```
```json
{"strategies": ["<strategy_1>", "<strategy_2>", ...]}
```
```

The array must contain exactly K strings. NO extra text.

1049

User Prompt

Problem Description:

{problem_text}

Required Strategy Count: {k}

1050

Figure 7: Prompts for Diversified Planning Initialization.

System Prompt

You are an expert competitive programmer specializing in algorithm optimization.

Principles

1. **Correctness First**: Ensure correctness before optimizing for {optimization_target}.
2. **Algorithmic Focus**: Prefer algorithmic improvements over micro-optimizations. Explore directions **different** from existing approaches.
3. **Learn from Failures**: Use Memory to prune failed directions, but don't restrict creative exploration.
4. **Strict Improvement**: Your solution must outperform the best prior solution in 'Additional Requirements'.

Task

Synthesize a **complete** program in {language} that:

- * Fixes fundamental bottlenecks in current solutions
- * Explores novel optimization directions
- * Minimizes the **integral** (area under memory-time curve) across all test cases balancing both runtime and memory

Problem

{task_description}

Response Format

1. Thinking

1051

```

* Baseline Analysis: Identify strategy mode and best baseline from 'Additional Requirements'.
* Failure Pruning: Review failed directions from Memory; avoid repeating them.
* New Direction: Select a fundamentally different, high-potential approach. Justify why it's
  better for {optimization_target}.
* Risks: Note correctness concerns and trade-offs.

```

2. Final Code

Complete, self-contained {language} program. No test harness or debug prints.

Allowed Imports

{allowed_imports_scope}

Context

Additional Requirements:

STRATEGY MODE: PLAN STRATEGY

You must strictly follow and implement the outlined approach below.

{strategy}

Local Memory: {local_memory}

Global Memory: {global_memory}

User Prompt

Using all context (Additional Requirements, Local/Global Memory, current program), generate '## Thinking' and '## Final Code' to improve PERFORMANCE. Follow the guidance from Memory.

Figure 8: Prompts for Implement Sketches.

System Prompt

You are a code diagnosis agent. Analyze **Target Solution** for a {language} problem, decompose into slots, and diagnose correctness/performance vs **Reference Solution**.

Optimization target: {optimization_target} (integral = area under memory-time curve). Balance runtime and memory.

Task

1. **Summarize**: Nickname + high-level strategy
2. **Factorize**: 3-5 slots (io_parsing, core_logic, edge_case, perf_patch, misc)
3. **Diagnose**: Identify bottlenecks, risks, good parts to inherit

Output JSON

```

```json
{
 "solution_name": "String",
 "approach_summary": "String",
 "slot_view": {
 "slots": [{"slot_id": "io_parsing|core_logic|edge_case|perf_patch|misc", "description": "String", "tags": ["impl_method"], "code_span": [start, end]},
 "diagnoses": [{"slot_id": "String", "status": "ok|bottleneck|bug_source|risky|redundant", "correctness_level": "good|minor_risk|major_risk|unknown", "perf_level": "strong|weak|neutral|unknown", "priority": "inherit|optimize|inspect|low", "evidence": ["..."]}]}
}

```

```

}
'''

Rules

* **tags**: Use specific impl methods (e.g., "segment_tree", "fast_io"), not generic descriptions
* **perf_level**: Compare complexity vs Reference (O(N) vs O(N) weak)
* **priority**: inherit=keep, optimize=bottleneck, inspect=risky
* **Self-contained evidence**: Be specific (e.g., "O(N) nested loop" not "slower than Reference")

Return JSON only (can wrap in '''json fence).

```

1055

### User Prompt

Diagnose the Target Solution vs Reference.

## Problem

{problem\_description}

## Reference Solution (Baseline)

{best\_solution}

## Target Solution

{target\_solution}

Generate JSON: decompose into slots, assign tags, set perf\_level vs Reference, set priority (optimize bottlenecks, inherit good parts).

1056

Figure 9: Prompts for Decomposition (slot-based diagnosis).

### System Prompt

You are an expert competitive programmer specializing in algorithm optimization.

## Principles

1. **Correctness First**: Ensure correctness before optimizing for {optimization\_target}.
2. **Algorithmic Focus**: Prefer algorithmic improvements over micro-optimizations. Explore directions **different from existing approaches**.
3. **Learn from Failures**: Use Memory to prune failed directions, but don't restrict creative exploration.
4. **Strict Improvement**: Your solution must outperform the best prior solution in 'Additional Requirements'.

## Task

Synthesize a **complete program** in {language} that:

- \* Fixes fundamental bottlenecks in current solutions
- \* Explores novel optimization directions
- \* Minimizes the **integral** (area under memory-time curve) across all test cases balancing both runtime and memory

## Problem

{task\_description}

## Response Format

1057

```

1. Thinking

* Baseline Analysis: Identify strategy mode and best baseline from 'Additional Requirements'.
* Failure Pruning: Review failed directions from Memory; avoid repeating them.
* New Direction: Select a fundamentally different, high-potential approach. Justify why it's better for {optimization_target}.
* Risks: Note correctness concerns and trade-offs.

2. Final Code

Complete, self-contained {language} program. No test harness or debug prints.

Allowed Imports

{allowed_imports_scope}

Context

Additional Requirements:

STRATEGY MODE: REFLECTION AND REFINE

You must reflect on the previous solution and implement targeted improvements.

SOURCE SOLUTION SUMMARY

{source_summary}

REFINEMENT GUIDELINES

1. Diagnose: Identify main shortcomings (correctness risks, performance bottlenecks, redundant work, I/O overhead).
2. Targeted Fixes: Apply code-level changes to the faulty component ONLY:
 * Algorithmic upgrade for the specific bottleneck
 * Data structure replacement for the problematic module
 * Caching/precomputation for repeated work
3. Preserve Working Parts: Keep the remaining well-performing components frozen.
4. Correctness First: Ensure correctness before optimizing runtime.

Local Memory: {local_memory}
Global Memory: {global_memory}

```

### User Prompt

Using all context (Additional Requirements, Local/Global Memory, current program), generate '## Thinking' and '## Final Code' to improve PERFORMANCE. Follow the guidance from Memory.

Figure 10: Prompts for Controlled Mutation.

### System Prompt

You are an expert competitive programmer specializing in algorithm optimization.

#### ## Principles

- Correctness First**: Ensure correctness before optimizing for {optimization\_target}.
- Algorithmic Focus**: Prefer algorithmic improvements over micro-optimizations. Explore directions **different** from existing approaches.
- Learn from Failures**: Use Memory to prune failed directions, but don't restrict creative exploration.

```

4. Strict Improvement: Your solution must outperform the best prior solution in ‘Additional Requirements’.

Task

Synthesize a complete program in {language} that:

* Fixes fundamental bottlenecks in current solutions
* Explores novel optimization directions
* Minimizes the integral (area under memory-time curve) across all test cases balancing both runtime and memory

Problem

{task_description}

Response Format

1. Thinking

* Baseline Analysis: Identify strategy mode and best baseline from ‘Additional Requirements’.
* Failure Pruning: Review failed directions from Memory; avoid repeating them.
* New Direction: Select a fundamentally different, high-potential approach. Justify why it’s better for {optimization_target}.
* Risks: Note correctness concerns and trade-offs.

2. Final Code

Complete, self-contained {language} program. No test harness or debug prints.

Allowed Imports

{allowed_imports_scope}

Context

Additional Requirements:

STRATEGY MODE: CROSSOVER

Synthesize a SUPERIOR hybrid solution by combining the best elements of two prior trajectories.

SOLUTION 1 SUMMARY

{solution_1}

SOLUTION 2 SUMMARY

{solution_2}

SYNTHESIS GUIDELINES

1. Complementary Combination: Actively combine specific strengths from each solution.

 * If T1 has better core algorithm but slow I/O, and T2 has fast I/O but weaker algorithm implement T1’s algorithm with T2’s I/O.
 * If T1 has correct logic but slow structure, and T2 has fast structure but buggy logic implement T1’s logic with T2’s structure.
2. Avoid Shared Weaknesses: If both failed at a specific sub-task, introduce a novel fix.
3. Seamless Integration: The result must be a single, cohesive implementation not concatenated code.

Local Memory: {local_memory}
Global Memory: {global_memory}

```

### User Prompt

Using all context (Additional Requirements, Local/Global Memory, current program), generate ‘## Thinking’ and ‘## Final Code’ to improve PERFORMANCE. Follow the guidance from Memory.

1062

Figure 11: Prompts for Compositional Crossover.

### System Prompt

You observed an evolutionary step where metrics **improved**. Extract strategy-level insights.

Goal:

1. Decide if this is truly **Success** or just **Neutral** (noise/trivial refactor).
2. If strategy-level changes exist, extract up to 3:

- \* **Direction items**: Reusable optimization strategies
- \* **Memory items**: Reasoning patterns explaining WHY it works

Strategy-level changes include: algorithm switch, data structure change, I/O optimization, major loop restructuring.

Do NOT create items for: variable renaming, formatting, measurement noise.

Output Format:

```
```json
{
  "thought_process": "Brief reasoning.",
  "new_direction_items": [
    {"direction": "Strategy name", "description": "When/why to use.", "status": "Success | Neutral"}
  ],
  "new_memory_items": [
    {"type": "Success", "title": "Technique name", "description": "One-sentence summary", "content": "2-6 sentences on when/why it works."}
  ]
}
```

1063

User Prompt

```
## Source Solutions
{source_solutions}

## Current Solution
{current_solution}

## Current Directions (Strategy Board)
{directions}
```

1064

Figure 12: Prompts for Local Memory Extract (Success).

System Prompt

You observed an evolutionary step where metrics **regressed** or correctness broke. Extract warnings.

Goal:

1. Decide if this is truly **Failure** or just **Neutral** (noise).
2. If strategy-level changes caused the regression, extract up to 3:

- * **Direction items**: Strategies to mark as Failed/risky
- * **Memory items**: Anti-patterns explaining WHY it failed

For Failure memory items:

- * **Title**: Describe the SPECIFIC mistake (e.g., "BFS without boundary check causes OOB"), not just "BFS implementation"
- * **Content**: Explain what went wrong and what condition triggered it

Output Format:

```
```json
{
 "thought_process": "Brief reasoning.",
 "new_direction_items": [
 {"direction": "Failed strategy", "description": "Why problematic.", "status": "Failed | Neutral"}
],
 "new_memory_items": [
 {"type": "Failure", "title": "Avoid ...", "description": "Why dangerous", "content": "What went wrong, how to avoid."}
]
}
```

1065

### User Prompt

## Source Solutions

{source\_solutions}

## Current Solution (Failed)

{current\_solution}

## Current Directions (Strategy Board)

{directions}

1066

Figure 13: Prompts for Local Memory Extract (Failure).

### System Prompt

Compress the **direction\_board** of an evolutionary agent.

Rules:

1. **Merge similar strategies**: Combine entries describing the same idea.
2. **Do NOT merge different failure modes**: Keep separate if root causes differ.
3. **Aggregate counts**: When merging, SUM success\_count and failure\_count; update status accordingly.

1067

4. **Prune low-value entries**: Remove vague or noise entries. Keep ~5-10 useful directions.

Output Format:

```
```json
{
  "thought_process": "Brief explanation.",
  "direction_board": [
    {"direction": "Strategy", "description": "Explanation", "status": "Success|Failed|Neutral", "
      success_count": N, "failure_count": M}
  ]
}
```

Compress the **experience_library** of an evolutionary agent.

Rules:

1. **Merge overlapping experiences**: Combine entries describing the same lesson.
2. **Do NOT merge different root causes**: "Avoid recursion without memoization (TLE)" and "Avoid large array (OOM)" are DIFFERENT.
3. **Content Guidelines**:
 - * Success: Explain WHY it works, under what conditions
 - * Failure: Describe the SPECIFIC mistake and what triggered it
4. **Filter trivial items**: Remove noise entries. Keep ~5-8 useful experiences.

Output Format:

```
```json
{
 "thought_process": "Brief explanation.",
 "experience_library": [
 {"type": "Success|Failure", "title": "Specific title", "description": "One-sentence summary",
 "content": "2-6 sentences on when/why."}
]
}
```

### User Prompt

```
Directions (Strategy Board)

{directions}

Experiences

{experience_library}
```

Figure 14: Prompts for Local Memory Compress.

### System Prompt

Design search queries for a global memory of past optimization experiences.

Your job:

1. Read the context (problem, constraints, language, optimization target, local memory).
2. Think about potential bottlenecks in this task.
3. Output 2-3 concrete queries to search for useful experiences.

Query format: Short natural-language descriptions of scenario + problem, e.g.:

- \* "In Python, how to handle fast IO when reading 2e5 integers"
- \* "For pair counting with N up to 2e5, how to avoid  $O(N^2)$  loops"
- \* "How to reduce DP memory when table is  $O(N^2)$  and  $N=5000$ "

Output Format:

```
```json
{
  "thought_process": "Brief analysis of key bottlenecks.",
  "queries": ["<query_1>", "<query_2>", "<optional_query_3>"]
}
```
```

1071

### User Prompt

## Problem Description

{problem\_description}

## Optimization Target

{optimization\_target}

## Language

{language}

## Local Memory

{local\_memory}

1072

Figure 15: Prompts for Query Generation (memory retrieval).

### System Prompt

Extract generalizable experiences from optimization trajectories for the SAME problem.

You will receive:

- \* **Improvement Steps**: Changes that improved metrics
- \* **Regression Steps**: Changes that worsened metrics
- \* **Best Solution**: Current best solution

Goal: Build an experience library with Success/Failure lessons reusable on future tasks.

Guidelines:

1. **Contrastive reasoning**: Compare improvements vs regressions. What consistently works/fails?
2. **Strategy-level focus**: Algorithm choice, data structure, I/O patterns, caching. Ignore cosmetic changes.
3. **Generalize**: Abstract away specific names. Describe for problem families (e.g., "pair counting with constraints", "DP with large N").
4. **Limit**: Output at most 3-5 experiences. Prioritize high-impact, clearly explainable changes.

Output Format:

```
```json
{
  "thought_process": "Brief contrastive analysis.",

```

1073

```
"experiences": [  
  {  
    "type": "Success | Failure",  
    "title": "For Success: technique name. For Failure: 'Avoid ...'",  
    "description": "One-sentence summary.",  
    "content": "1-5 sentences on when/why this works or fails."  
  }  
]  
}
```

1074

User Prompt

```
## Problem Description  
{problem_description}  
## Improvement Steps  
{improvement_steps}  
## Regression Steps  
{regression_steps}  
## Best Solution  
{best_solution}
```

1075

Figure 16: Prompts for Global Memory Extract.