

FIZZ: Factual Inconsistency Detection by Zoom-in Summary and Zoom-out Document

Anonymous ACL submission

Abstract

Through the advent of pre-trained language models, there have been notable advancements in abstractive summarization systems. Simultaneously, a considerable number of novel methods for evaluating factual consistency in abstractive summarization systems has been developed. But these evaluation approaches incorporate substantial limitations, especially on refinement and interpretability. In this work, we propose highly effective and interpretable factual inconsistency detection method **FIZZ** (Factual Inconsistency Detection by Zoom-in Summary and Zoom-out Document) for abstractive summarization systems that is based on fine-grained *atomic facts* decomposition. Moreover, we align *atomic facts* decomposed from the summary with the source document through adaptive granularity expansion. These *atomic facts* represent a more fine-grained unit of information, facilitating detailed understanding and interpretability of the summary’s factual inconsistency. Experimental results demonstrate that our proposed factual consistency checking system significantly outperforms existing systems. We release the code at <https://anonymous.4open.science/status/FAIRY-B5F7>.

1 Introduction

With the development of pre-trained language models, abstractive summarization systems using these language models have made remarkable progress in generating fluent and natural summarizations (Chang et al., 2023). However, one of the notable challenges these systems confront is the hallucination, causing language models to generate summaries that are factually inconsistent with the given article (Maynez et al., 2020; Kryscinski et al., 2020; Tam et al., 2023; Zhang et al., 2023). Recognizing the significance of this issue, various evaluation metrics have been introduced to detect these errors, starting from traditional methods like ROUGE (Lin, 2004) and




Figure 1: Comparison between sentence level evaluation and atomic facts level evaluation. The numbers in parentheses represent the maximum NLI entailment scores obtained by comparing each sentence and atomic fact with the source document on a sentence-wise basis.

BERTScore (Zhang et al., 2020) to a large number of advanced metrics (Goyal and Durrett, 2020, 2021; Scialom et al., 2021; Fabbri et al., 2022; Laban et al., 2022; Luo et al., 2023; Zha et al., 2023; Wang et al., 2023a). Especially, many of the recent works (Laban et al., 2022; Schuster et al., 2022; Zha et al., 2023) adopted sentence level evaluation using Natural Language Inference (NLI) systems for factual consistency checking.

Although these studies have shown a certain level of performance in summary evaluation, they still exhibit significant deficiencies in accuracy. Additionally, they substantially lack in interpretability, an area crucial for further development in the field of summarization factual consistency detection. As shown in Figure 1, sentence level evaluation often fails to check the details of the various facts in each sentence, resulting in lower accuracy and lower interpretability. Furthermore, we find that pair-wise single sentence level evaluation is vulnerable to summary evaluation that requires multi-sentence reasoning. In addition, expressions such as pronouns in sentences can lead the NLI system to make incorrect judgments in single sentence level evaluation.

In this paper, we propose an interpretable summarization factual inconsistency detection system, FIZZ, which overcomes the issues of previous sentence level NLI-based evaluation. As in Figure 2, FIZZ first resolves coreferences in both the source document and the generated summary. Subsequently, we decompose this coreference resolved summary into *atomic facts*, which is an approach that zooms in the summary. This *atomic fact* can be considered a more fine-grained information unit embedded within the text than a sentence at a broad level. As in the *atomic fact* examples in Figure 1, a single sentence from the summary can be segmented into two or more distinct units of information. This approach allows for a more detailed analysis of textual information, which is crucial for evaluating the factuality of generated text. Using these *atomic facts*, we check the consistency of each *atomic fact* against the source document using an NLI model. As highlighted in Figure 1, factual inconsistencies that cannot be detected at the sentence level can be identified through evaluation at this atomic fact level with higher interpretability. Also, we propose a granularity expansion method that can adaptively increase the number of context sentences when verifying the consistency of each atomic fact. Through this way of zooming out the document, we efficiently check the consistency of certain atomic facts that require multi-sentence level reasoning.

Experimental results show that our proposed system FIZZ achieves state-of-the-art performance on the AGGREFACT (Tang et al., 2023) benchmark dataset. FIZZ exhibits high interpretability by utilizing *atomic facts*. Furthermore, We have tested on various LLMs to implement atomic fact generation task and identified the best model suited for this task. Additionally, our analysis shows that flexibly increasing the granularity choice of the source document significantly enhances accuracy.

2 Related Work

Summarization Factual Consistency Evaluation

A multitude of metrics designed to evaluate summarization factual consistency are currently being refined by leveraging NLP pipelines originally developed for disparate tasks, including QA-based evaluation, parsing-based methods, LLM-based prompting, and NLI-based metrics.

QA-based methods involve two steps of question generation (QG) and question answering(QA).

While FEQA (Durmus et al., 2020) generate questions with the summary as the source, QUESTEVAL (Scialom et al., 2021) and QAFACTEVAL (Fabbri et al., 2022) generate questions with both the summary and the document.

Parsing-based methods discover relationships by employing syntactic parsing process, thereafter calculating the proportion of summary-derived relations that align with those extracted from source documents. Goodrich et al. (2019) extract relation tuples for the evaluation. DAE (Goyal and Durrett, 2020, 2021) propose utilizing a dependency arc between the entities and the relationship.

There is a growing trend for using LLMs like ChatGPT (OpenAI, 2022) and GPT-4 (OpenAI, 2023) on summarization factual consistency checking (Luo et al., 2023; Chen et al., 2023; Wang et al., 2023a; Gekhman et al., 2023; Yang et al., 2024). Initially, Luo et al. (2023) explores ChatGPT’s ability in evaluating factual consistency for text summarization with zero-shot prompting. Yang et al. (2024) extend the work by excluding irrelevant sentences from both documents before providing prompts to GPT-4.

SUMMAC (Laban et al., 2022) re-visit NLI-based models and granularity choice for inconsistency detection in summarization. ALIGNSCORE (Zha et al., 2023) develops an alignment system, incorporating a summarization consistency checking metric and an NLI model, which has been trained across a diverse array of tasks that can be aligned with NLI. Our proposed FIZZ is also based on NLI. However, unlike the aforementioned systems, which compare the summary at the sentence level, FIZZ conducts comparisons at a more fine-grained atomic fact level with high interpretability.

Atomic Facts Generation To the best of our knowledge, van Halteren and Teufel (2003) pioneered the introduction of an atomic information unit, named a *factoid*, within the field of summarization evaluation. Building on this foundational work, Nenkova and Passonneau (2004) proposed the Pyramid method, a manual evaluation protocol for summarization that employs *Summarization Content Units* (SCUs), also referred to as *Semantic Content Units*. This innovative approach has inspired a significant body of subsequent research (Harnly et al., 2005; Shapira et al., 2019; Gao et al., 2019; Bhandari et al., 2020; Zhang and Bansal, 2021). Liu et al. (2023) referred to these elementary information units as *Atomic Content Unit*,




Figure 2: Overall flow of FIZZ. The pipeline begins by applying coreference resolution to both the summary and the document. Atomic facts are then decomposed from the summary using an LLM. These atomic facts are filtered and subsequently scored against the document. The scores are refined through granularity expansion. The ultimate score is defined by choosing the minimum score.

or *Atomic Facts*. However, the realm of these investigations is primarily concentrated on assessing summarization itself via the examination of *atomic facts* crafted by human annotators¹.

In the scope of hallucination detection and fact verification for text generated by models, there has been a recent initiative to employ LLMs to create *atomic facts*. FACTSCORE (Min et al., 2023) utilize InstructGPT (Ouyang et al., 2022) for the creation of *atomic facts*. Following this work, FAC-TOOL (Chern et al., 2023) introduce a fact verification pipeline that leverages fine-grained information units generated by ChatGPT, referred to as *claims*. In this study, we present a novel method FIZZ leveraging atomic semantic unit, from now on called *atomic fact*, in the domain of summarization factual inconsistency detection.

3 FIZZ

The overall flow of our proposed system FIZZ is presented in Figure 2. Our method first begins with the application of a coreference resolution model to a given (*document, summary*) pair, resulting in a new pair of texts (*document, summary*) where coreferences have been resolved (Section 3.1). Following this, we proceed to generate *atomic facts* from the coreference-resolved summary leveraging LLMs as a zooming-in approach for the summary. (Section 3.2). Using the generated atomic facts, we compute the score of each *atomic fact* with the NLI system. (Section 3.3). Finally, we propose a granularity expansion method, which is a way of

¹We note that Zhang and Bansal (2021) generated SCUs with semantic role labeling.

zooming out the documents, to compute the score for the summaries that contain high abstractiveness more accurately.

3.1 Coreference Resolution

To enhance the entailment recognition capabilities of NLI models, FIZZ first conducts centered around coreference resolution in both document and summary texts. The motivation behind this approach is driven by the inherent limitations observed in NLI models when processing texts with pronouns. Specifically, we find that NLI models tend to struggle with recognizing entailment when presented with *premises* and *hypotheses* that contain the same content but differ in their use of pronouns and explicit entity names. To address this challenge, FIZZ employs pronoun resolution in summaries by analyzing them on a sentence-by-sentence basis to extract atomic facts. This strategy not only facilitates a more granular understanding of the summary content but also avoids the limited context length in LLMs.

Furthermore, applying pronoun resolution to the document text ensures that the entities are explicitly named, aligning the *premise* more closely with the *hypothesis*. By resolving coreferences in both documents and summaries, our approach aims to bridge the gap between pronoun use and explicit entity naming, thereby improving the performance of NLI models in entailment tasks. This dual focus on both document and summary texts underscores the comprehensive nature of our strategy to bolster the accuracy and reliability of NLI models in handling a variety of linguistic expressions.

Formally, given a document D and its summary S , we define coreference resolution as f_{coref} , which makes:

$$D' = f_{\text{coref}}(D), \quad S' = f_{\text{coref}}(S) \quad (1)$$

where D' and S' are coreference resolved texts of D and S , respectively.

3.2 Atomic Facts Decomposition

Atomic Facts Generation As demonstrated in Figure 1, sentence level evaluation of summaries can often yield inaccurate results. Therefore, we propose a method that evaluates the factuality of summaries at a more fine-grained level, specifically at the level of *atomic facts* as exemplified in Figure 2. By employing *atomic facts*, which are highly detailed units of information, FIZZ considerably enhances interpretability.

The definition of an *atomic fact* differs across studies, primarily due to the inherently subjective nature of this concept. We propose our own definition of an *atomic fact* that is designed to align with and complement the nature of NLI models. Building upon Bhandari et al. (2020), we specify further that an *atomic fact* is short and concise, containing no more than two or three entities, with person entities specifically resolved any of coreferences.

We generate atomic facts from summaries at the sentence level after resolving coreferences. This strategy for atomic fact generation not only increases the quantity of atomic facts but also substantially augments the generated summary’s pool of information. To extract atomic facts from the summaries, we input prompts into the LLM that include both a task description and a sentence-level summary, as exemplified in Table 7. This approach systematically decomposes each sentence in the summary into individual atomic facts, facilitating a comprehensive extraction and representation of information. The coreference resolved summary $S' = \{s'_j\}_{j=1}^N$, where s'_j represents the j^{th} sentence in S' and N the total number of sentences in S' , could be decomposed to a set of atomic facts $A' = \{a'_k\}_{k=1}^L$, with L denotes the total number of sentences in A' .

Atomic Facts Filtering One significant issue with atomic facts generated by LLMs is that these facts are often produced not from the content of summaries themselves but from the pretrained knowledge embedded within the LLMs. For example, when we decompose the sentence of the

Algorithm 1 Filtering Out Incorrect Atomic Facts

Input: An NLI model \mathcal{M} ; coreference resolved summary $S' = \{s'_j\}_{j=1}^N$; decomposed atomic facts $A' = \{a'_k\}_{k=1}^L$.

Initialize: set $A_{\text{filtered}} = \phi$

```

1: for  $k = 1, 2, \dots, L$  do
2:   for  $j = 1, 2, \dots, N$  do
3:      $(e_{j,k}, c_{j,k}, n_{j,k}) \leftarrow \mathcal{M}(s'_j, a'_k)$ 
4:     if  $\max(e_{j,k}, c_{j,k}, n_{j,k})$  is  $e_{j,k}$  then
5:       Append  $a'_k$  to  $A_{\text{filtered}}$ .
6:     end if
7:   end for
8: end for

```

Output: A set of atomic facts A_{filtered} .

summary "The mass, which has risen some 50ft above sea level, measures roughly 1,000 - 1,640ft long, and 100ft wide", the decomposed atomic facts contain an atomic fact "The mass is a noun". Such atomic facts may not align with either the summaries or the documents and can significantly influence the scoring method described in Section 3.3. Consequently, the exclusion of these atomic facts becomes a necessary step in our process.

Hence, we utilize an NLI model to filter out incorrect atomic facts. Our approach leverages the probabilistic distribution of the NLI model, which categorizes outcomes into three types: *Entailment* (E), *Contradiction* (C), and *Neutral* (N). In the filtering process, we set the summary S' as the *premise*, and the atomic fact A' as the *hypothesis*. We filter out atomic facts that exhibit exceptionally low *entailment* scores. We outline the detailed procedure of the atomic facts filtering process in Algorithm 1.

3.3 Atomic Facts Scoring

Atomic Facts Pair-Wise Scoring To compute the score for each atomic fact of the summaries, FIZZ first decomposes the coreference resolved document into sentences. We split the document D' into M sentences and the filtered atomic facts A_{filtered} into N sentences, formulating $D' = \{d'_i\}_{i=1}^M$ and $A_{\text{filtered}} = \{a_k\}_{k=1}^L$, respectively. We use each (d_i, a_k) as an input for an NLI model, positioning the generated atomic fact as the *hypothesis* and the sentence of the document as the *premise*.

Finally, we assign scores to each atomic fact based on the maximum *entailment* score obtained through comparison with every sentence in the document. The atomic fact *entailment* scores $E = \{e_{i,k}\}$, where $1 \leq i \leq M$ and $1 \leq k \leq L$, are computed to a vector \mathbf{T} :

$$\mathbf{t}_k = \max_{1 \leq i \leq M} e_{i,k} \quad (2)$$

$$\mathbf{T} = \{\mathbf{t}_1, \dots, \mathbf{t}_L\}$$

Adaptive Granularity Expansion Summaries generated by *abstractive* summarization systems contain a high degree of *abstractiveness*. This *abstractiveness* occurs when content spread across multiple sentences in the document is condensed into one or two sentences in the summary. To accurately detect factual inconsistencies within such summaries, it is necessary to zoom out and examine multiple sentences across the source document. Furthermore, several studies have demonstrated that considering multiple sentences from the document leads to better accuracy (Laban et al., 2022; Glover et al., 2022).

We aim to identify scores where $\max(e_k, c_k, n_k)$ is *not* e_k from the \mathbf{T} . For atomic facts associated with these scores, we further increase the granularity of the document and perform computation once again. We incrementally increase the granularity starting from the document sentence d_i that contributed to each identified score, limiting the granularity at a maximum of three sentences ($d_{i-1} + d_i$, $d_i + d_{i+1}$, $d_{i-2} + d_{i-1} + d_i$, $d_i + d_{i+1} + d_{i+2}$, $d_{i-1} + d_i + d_{i+1}$). Subsequently, we re-calculate the scores within this expanded context and replace the original scores with the maximum value observed among the re-calculated scores and the original. As a result, the vector \mathbf{T} is transformed into \mathbf{T}^* as certain scores are replaced by new scores. Detailed information on this procedure is provided in Algorithm 2.

The final score is then determined by the minimum score within vector \mathbf{T}^* , enabling a highly interpretable evaluation:

$$FIZZ \text{ score} = \min(\mathbf{T}^*) \quad (3)$$

4 Experiments

4.1 Experimental Setups

In our experiments, we leverage MT5 (Bhnet et al., 2023) for coreference resolution, which returns with the identification of clusters referring to the same entities. With these clusters, we further implement rule-based pronoun substitution strategies to generate coreference resolved texts. For atomic fact decomposition, the Orca-2 model (Mittra et al., 2023) is utilized. Additionally, this work adopts the same off-the-shelf NLI model as implemented in SUMMAC (See Appendix B for more details).

Algorithm 2 Scoring with Document Granularity Expansion

Input: An NLI model \mathcal{M} ; coreference resolved document $D' = \{d'_i\}_{i=1}^M$; decomposed atomic facts $A' = \{a'_k\}_{k=1}^L$.

Initialize: $\mathbf{T}^* = \phi$; Max granularity size $gran = 3$.

- 1: Define $\mathcal{C}(D, g) =$ list of subsets of D with size of g .
- 2: Define $\mathcal{F}(\mathcal{C}(D, g))$ which returns whether $\mathcal{C}(D, g)$ is a consecutive list.
- 3: Define $\mathcal{D}(\mathcal{C}(D, g)) =$ list of document sentences in index list in $\mathcal{C}(D, g)$.
- 4: **for** $k = 1, 2, \dots, L$ **do**
- 5: set $E = \phi$
- 6: **for** $i = 1, 2, \dots, M$ **do**
- 7: $(e_{i,k}, c_{i,k}, n_{i,k}) \leftarrow \mathcal{M}(d'_i, a'_k)$
- 8: Append $e_{i,k}$ to E .
- 9: **end for**
- 10: $m_{idx} = E.index(\max(E))$
- 11: **if** $\max(e_{i,k}, c_{i,k}, n_{i,k})$ **is not** $e_{i,k}$ **then**
- 12: set $D_{idx} = [0, \dots, M - 1]$
- 13: set $D_{expanded} = \phi$
- 14: **for** $g = 1, 2, \dots, gran + 1$ **do**
- 15: **if** m_{idx} in $\mathcal{C}(D_{idx}, g)$ and $\mathcal{F}(\mathcal{C}(D_{idx}, g))$ **then**
- 16: Extend $\mathcal{C}(D_{idx}, g)$ to $D_{expanded}$.
- 17: **end if**
- 18: **end for**
- 19: set $E_{expanded} = \phi$
- 20: **for** $d_{expanded} \in \mathcal{D}(D_{expanded})$ **do**
- 21: $(e, c, n) \leftarrow \mathcal{M}(d_{expanded}, a'_k)$
- 22: Append e to $E_{expanded}$.
- 23: **end for**
- 24: Append $\max(E_{expanded})$ to \mathbf{T}^* .
- 25: **else**
- 26: Append $e_{i,k}$ to \mathbf{T}^* .
- 27: **end if**
- 28: **end for**

Output: vector \mathbf{T}^* with maximum entailment scores from each atomic fact.

4.2 Benchmark Datasets

We use AGGREGFACT (Tang et al., 2023) benchmark dataset, a comprehensive aggregation of 9 leading summary factual consistency detection datasets currently available. AGGREGFACT is stratified into three distinct splits, namely FTSOTA, EXFORMER, and OLD, with each split containing its own validation and test sets. We standardize the evaluation as a binary classification and choose the best threshold from the validation set following SummaC. Finally, we apply this threshold to the test set and report the balanced accuracy score, considering the imbalance in the dataset.

4.3 Baselines

We adopt all of the baselines of AGGREGFACT dataset: DAE (Goyal and Durrett, 2020, 2021), QuestEval (Scialom et al., 2021), SummaC-ZS and SummaC-Conv (Laban et al., 2022), QAFactEval (Fabbri et al., 2022), ChatGPT-ZS and ChatGPT-CoT (Luo et al., 2023), ChatGPT-DA and

	AGGREGFACT-CNN			AGGREGFACT-XSUM			AVG
	FTSOTA	EXF	OLD	FTSOTA	EXF	OLD	
Baseline	50.0	50.0	50.0	50.0	50.0	50.0	50.0
DAE*	59.4	67.9	69.7	73.1	-	-	67.5
QuestEval	63.7	64.3	65.2	61.6	60.1	59.7	62.4
SummaC-ZS	63.3	76.5	76.3	56.1	51.4	53.3	62.8
SummaC-Cv	70.3	69.8	78.9	67.0	64.6	67.5	69.7
QAFactEval	61.6	69.1	<u>80.3</u>	65.9	59.6	60.5	66.2
AlignScore	53.4	<u>73.1</u>	80.2	<u>70.2</u>	80.1	63.7	70.1
ChatGPT-ZS	66.2	64.5	74.3	62.6	69.2	60.1	66.2
ChatGPT-CoT	49.7	60.4	66.7	56.0	60.9	50.1	57.3
ChatGPT-DA	48.0	63.6	71.0	53.6	65.6	61.5	60.6
ChatGPT-Star	55.8	65.8	71.2	57.7	70.6	53.8	62.5
FactScore	60.7	66.1	72.7	68.0	63.9	62.2	65.6
FactTool	<u>72.7</u>	66.1	60.8	68.0	64.0	62.2	65.6
FIZZ	73.2	67.3	76.0	69.7	<u>72.4</u>	<u>68.5</u>	71.2
<i>w/o GE</i>	68.0	67.1	77.6	69.4	71.5	69.8	<u>70.6</u>
<i>w/o AF</i>	72.4	67.0	80.4	64.9	67.1	66.1	69.7

Table 1: Balanced accuracy results on the AGGREGFACT dataset. Following Tang et al. (2023), we omitted the results from DAE, as it was trained on the XSum-Faith (Goyal and Durrett, 2021) dataset, which includes human-annotated summaries from EXFORMER and OLD. Highest performance is highlighted in **bold**, and the second highest is underlined.

ChatGPT-Star (Wang et al., 2023a). Also, we report the results with AlignScore (Zha et al., 2023), which is a recently introduced system for checking the factual consistency of summaries based on NLI.

Additionally, we incorporate FACTSCORE (Min et al., 2023) and FACTOOL (Chern et al., 2023) in our baselines. These methods decompose generated texts into *atomic facts* and then retrieve corresponding entries from a given knowledge base, such as Wikipedia, to evaluate the factuality of the generated context. For the purpose of verification, we assume the availability of this knowledge base, which we use as the source document to assess summary factual consistency. In FACTSCORE, we employ a **No-context LM** for factual verification. This approach operates on a QA basis, assessing whether *atomic facts* are true or false with respect to the source document. In FACTOOL, we utilize a **Knowledge-based QA** approach. This also follows a QA format but incorporates the CoT method, where the LLM evaluates if *claims* are true or false relative to the source document².

4.4 Results

We present the performance outcomes obtained by applying each metric to the AGGREGFACT benchmark dataset in Table 1. We show the perfor-

²Details of the experiments are provided in Appendix B

	AGGREGFACT-	AGGREGFACT-	AVG
	CNN-FTSOTA	XSUM-FTSOTA	
DAE	65.4±4.4	70.2±2.3	67.8
QuestEval	70.2±3.2	59.5±2.7	64.9
SummaC-ZS	64.0±3.8	56.4±1.2	60.2
SummaC-Conv	61.0±3.9	65.0±2.2	63.0
QAFactEval	67.8±4.1	63.9±2.4	65.9
AlignScore	62.5±3.3	69.6±1.7	66.1
ChatGPT-ZS	56.3±2.9	62.7±1.7	59.5
ChatGPT-COT	52.5±3.3	55.9±2.1	54.2
ChatGPT-DA	53.7±3.5	54.9±1.9	54.3
ChatGPT-Star	56.3±3.1	57.8±0.2	57.1
FactScore	60.8±3.2	68.0±2.0	64.4
FactTool	49.3±3.5	59.0±2.0	54.2
FIZZ	72.6±3.0	<u>69.3±1.9</u>	71.0
<i>w/o GE</i>	<u>72.2±2.8</u>	66.3±1.9	<u>69.3</u>
<i>w/o AF</i>	63.6±2.9	65.8±2.0	64.7

Table 2: Balanced accuracy results using a single threshold with 95% confidence intervals on the AGGREGFACT-FTSOTA split dataset.

formance of three versions of our proposed metric: FIZZ, its without granularity expanded version, $FIZZ_{w/o GE}$, and its without atomic facts version, $FIZZ_{w/o AF}$. The complete results for AGGREGFACT-CNN and AGGREGFACT-XSUM are displayed in Table 1. FIZZ demonstrates the highest average performance, followed by $FIZZ_{w/o GE}$ and $FIZZ_{w/o AF}$.

Additionally, we provide results for a single-threshold approach on AGGREGFACT-FTSOTA split as in Tang et al. (2023). We list the best threshold findings for the AGGREGFACT-CNN-FTSOTA and AGGREGFACT-XSUM-FTSOTA splits, with corresponding binary classification balanced accuracy scores in Table 2. In this setting, FIZZ achieves the highest average performance, with $FIZZ_{w/o GE}$ coming in second. Both metrics perform exceptionally well on the CNN split. Furthermore, the granularity expansion in FIZZ leads to notably higher performance improvements on the XSUM split.

Both FACTSCORE and FACTOOL have demonstrated scores that are comparable to or exceed those of ChatGPT-based metrics. It appears that decomposing summaries into atomic facts and comparing them with the source document is more effective than performing factuality checking on the entire summary. However, metrics based on ChatGPT inherently face disadvantages compared to other metrics, which can be tuned by adjusting thresholds; such tuning is unnecessary for ChatGPT-based metrics. This distinction may limit the effectiveness of ChatGPT-based evaluations in some contexts.

LLM	CNN	XSUM	AVG	AVG. TOKEN LENGTH
Zephyr	65.1±3.3	65.2±2.0	65.2	97.6
gpt-3.5-turbo	68.7±3.4	68.7±2.0	68.7	95.9
gpt-3.5-turbo-instruct	70.7±3.1	67.0±1.8	68.9	90.5
Mistral	70.5±3.5	68.7±2.1	69.6	86.5
Orca-2	72.6±3.0	69.3±1.9	71.0	81.4

Table 3: Experimental results of FIZZ with atomic facts generated by different LLMs using the same prompt on AGGREGATE-FTSOTA split. **Avg. Token Length** indicates the average number of total tokens of atomic facts per summary.

4.5 Analysis

LLMs used for Atomic Facts Decomposition

To investigate the most suitable LLMs for generating atomic facts, we evaluate the generation of atomic facts using various LLMs, including gpt-3.5-turbo, gpt-3.5-turbo-instruct, and other 7B models such as Zephyr (Tunstall et al., 2023) and Mistral (Jiang et al., 2023)³. The results, documented in Table 3, demonstrate that while the atomic facts generated by gpt-3.5-turbo and gpt-3.5-turbo-instruct generally perform better compared to other metrics, they are still inferior to those produced by Orca-2. The performance drop associated with the gpt series suggests a noteworthy observation. We explain that this discrepancy is due to the length of the atomic facts. As shown in Table 3, which includes the average token length of atomic facts after the filtering process per summary, there is a clear inverse relationship between the number of tokens in an atomic fact and its average performance. Longer atomic facts tend to contain more entities and are less concise. Such sentences are less suitable as *hypotheses* when compared sentence-wise using NLI models. Furthermore, the sensitivity of using the minimum atomic fact scores as the final score exacerbates the challenge, making it difficult to achieve desired outcomes with lengthy sentences. In contrast, other 7B models such as LLaMa (Touvron et al., 2023) show limitations in adhering to instructions for atomic fact decomposition.

Sizes of Granularity Expansion As underscored in Section 3.3, accurately evaluating the factual consistency of *abstractive* summaries necessitates an expansion of document granularity. This requirement stems from the observation that a single sentence within a summary may incorporate content from multiple sentences within the document. Illustrative of this point, Figure 3 highlights that




Figure 3: The effect of granularity expansions and coreference resolution in real AGGREGATE dataset. The entailment score of an atomic fact and document sentence with (a) only Coreference Resolution, (b) only Granularity Expansion, and (c) the both.

segmenting conversational dialogues into discrete sentences can lead to a loss of contextual clarity, where the synthesis of various segmented sentences is required for an accurate interpretation.

SUMMAC present experimental results across different granularity choices, categorizing document granularity into a sentence, two sentences, paragraph, and full document levels. However, adjusting document granularity in such a manner reduces interpretability and undermines result reliability. Our approach is to adaptively increase granularity only for atomic facts where the entailment score significantly decreases.

Table 4 presents the outcomes associated with varying granularity sizes in adaptive granularity expansion. The experimental findings reveal a consistent improvement in average performance with increasing granularity, particularly for summaries derived from XSum (Narayan et al., 2018). This significant performance boost can be attributed to the inherently *abstractive* nature of XSum-based summaries.

Despite the increase in average score for the maximum of four sentences, the scores for CNN summaries actually declined. Additionally, we observe that computational costs rose with increasing granularity. Hence, we determined that the maximum of three sentences represents the best trade-off between computational cost and performance.

³Details of the model are provided in Appendix B

Doc. Max Granularity	AGGREFACT-CNN-FtSOTA	AGGREFACT-XSUM-FtSOTA	AVG	s/it
One Sent.	72.2±2.8	66.3±1.9	69.25	2.49
Two Sent.	71.0±3.2	69.3±2.0	70.15	2.53
Three Sent.	72.6±3.0	69.3±1.9	70.95	2.64
Four Sent.	72.1±3.1	70.0±1.8	71.05	2.80

Table 4: **Size of granularity choice** in granularity expansion on AGGREFACT-FtSOTA split. We tested four granularity sizes on the document side for the additional lookup of an atomic fact which scored *too low* entailment score. *s/it* indicates seconds per iteration during the inference of an NLI model.

Effectiveness of Coreference Resolution In the application of NLI models for comparing *premises* with *hypotheses*, the significance of coreference resolution cannot be overstated. As outlined in Section 3.1, failure to resolve pronouns in the *premise* significantly hinders the attainment of desired outcomes. This point is vividly illustrated in Figure 3, where the difference between document(b) and document(c) is merely the resolution of pronouns. Yet, this seemingly minor modification leads to a stark contrast in entailment scores, with document(b) achieving a score of 0.09 compared to document(c)’s 0.83. The discrepancy arises due to the document (*premise*)’s reference to "he" not being recognized as pertaining to "Chris Gunter", as stated in the atomic fact (*hypothesis*).

Moreover, Table 5 presents more granular experimental results on the impact of coreference resolution. We implemented experiments to evaluate the impact of coreference resolution on both documents and atomic facts. Our investigation included scenarios where coreference resolution was applied and cases where it was not. We show that texts with resolved coreferences, whether they be




Figure 4: Drawbacks of atomic fact level evaluation versus the sentence level evaluation. The numbers represent the maximum NLI entailment scores obtained by comparing each sentence and atomic fact with the source document on a sentence-wise basis.

Atomic Facts	Doc	CNN	XSUM	AVG
Original	Original	63.2±2.3	66.4±1.8	64.8
	Coref Resolved	65.7±3.4	67.8±2.0	66.7(+1.95)
Coref Resolved	Original	66.2±3.4	66.6±1.9	66.4
	Coref Resolved	72.2±2.7	66.3±1.9	69.2(+2.85)

Table 5: **Effect of coreference resolution** of document and atomic facts on AGGREFACT-FtSOTA splits before the process of granularity expansion. Coreference resolved either atomic fact or document both show an increase in the average.

atomic facts or documents, consistently outperform those without resolution. Notably, there is a marked improvement in performance on datasets based on CNN (Hermann et al., 2015) summaries compared to those based on XSum summaries. This is likely due to the *extractive* nature of CNN-based summaries, as opposed to the more *abstractive* summaries derived from XSum.

Failure Case Study We analyze the drawbacks of decomposing summaries into atomic facts in the summary factual consistency checking task, through the main example in Figure 4, which compares the drawbacks of analyzing atomic facts versus sentences. When comparisons are made at the sentence level, a sentence can be correctly judged as entailing the content of a document. Conversely, when breaking down the content into atomic facts, the fact "The tweet was about a rocket landing." receives a maximum entailment score of only 0.33. This particular atomic fact remains even after undergoing the filtering process. As a result, a summary that is factually consistent may be erroneously classified as factually inconsistent due to the analysis of this single atomic fact.

5 Conclusion

In this work, we propose a novel method, FIZZ, in detecting summary factual inconsistency. Our approach decomposes summaries into *atomic facts* and conducts a sentence-wise comparison with the document, and achieves state-of-the-art performance on the AGGREFACT benchmark dataset. Also, our proposed system has a higher interpretability due to its ability to precisely identify which parts of a summary are factually inaccurate by breaking it down into *atomic facts*. Furthermore, we analyze the necessity and significance of coreference resolution and granularity expansion in the context of summary factual consistency checking.

576 Limitations

577 Our proposed method is quite time-consuming. No-
578 tably, during the coreference resolution phase, we
579 leverage 11B model. This process requires more
580 time than other factual consistency checking sys-
581 tems. The practical applicability of FIZZ in real-
582 time settings remains to be determined.

583 Furthermore, our research was limited to sum-
584 maries based on articles and news domains. We
585 did not verify the effectiveness of FIZZ in other
586 domains such as dialogue summarization (Tang
587 et al., 2024) or medical summarization (Wang et al.,
588 2023b). Additionally, our study was confined to
589 English-language data. The validity of FIZZ needs
590 to be assessed in datasets based on other languages.

591 Despite these limitations, we believe our method
592 paves a new path in the area of summarization
593 factual consistency detection. This work could be a
594 significant contribution to the field, pending further
595 validation across varied domains and languages.

596 Ethics Statement

597 This work uses English document summarization
598 dataset, AGGREGFACT. This dataset is publicly
599 available online. We also provided adequate ci-
600 tations for the papers and sources we consulted in
601 writing our paper. As our work addresses consis-
602 tency checking, Our work may have implications
603 for society in terms of preventing the spread of
604 inaccurate information, as it deals with factual con-
605 sistency checking.

606 References

607 Manik Bhandari, Pranav Narayan Gour, Atabak Ash-
608 faq, Pengfei Liu, and Graham Neubig. 2020. [Re-](#)
609 [evaluating evaluation in text summarization](#). In
610 *Proceedings of the 2020 Conference on Empirical*
611 *Methods in Natural Language Processing (EMNLP)*,
612 pages 9347–9359, Online. Association for Computa-
613 tional Linguistics.

614 Stephen Bird, Edward Loper, and Ewan Klein. 2009.
615 *Natural Language Processing with Python*. O’Reilly
616 Media Inc.

617 Bernd Bohnet, Chris Alberti, and Michael Collins. 2023.
618 [Coreference resolution through a seq2seq transition-](#)
619 [based system](#). *Transactions of the Association for*
620 *Computational Linguistics*, 11:212–226.

621 Samuel R. Bowman, Gabor Angeli, Christopher Potts,
622 and Christopher D. Manning. 2015. [A large anno-](#)
623 [tated corpus for learning natural language inference](#).

In *Proceedings of the 2015 Conference on Empiri-*
cal Methods in Natural Language Processing, pages
632–642, Lisbon, Portugal. Association for Compu-
626 tational Linguistics. 627

Yupeng Chang, Xu Wang, Jindong Wang, Yuan Wu,
Linyi Yang, Kaijie Zhu, Hao Chen, Xiaoyuan Yi,
Cunxiang Wang, Yidong Wang, Wei Ye, Yue Zhang,
Yi Chang, Philip S. Yu, Qiang Yang, and Xing Xie.
2023. [A survey on evaluation of large language mod-](#)
628 [els](#). 629 630 631 632 633

Shiqi Chen, Siyang Gao, and Junxian He. 2023. [Eval-](#)
[uating factual consistency of summaries with large](#)
634 [language models](#). 635 636

I Chern, Steffi Chern, Shiqi Chen, Weizhe Yuan, Kehua
Feng, Chunting Zhou, Junxian He, Graham Neubig,
Pengfei Liu, et al. 2023. [Factool: Factuality detec-](#)
[tion in generative ai—a tool augmented framework](#)
637 [for multi-task and multi-domain scenarios](#). *arXiv*
638 *preprint arXiv:2307.13528*. 639 640 641 642

Esin Durmus, He He, and Mona Diab. 2020. [FEQA: A](#)
[question answering evaluation framework for faith-](#)
643 [fulness assessment in abstractive summarization](#). In
644 *Proceedings of the 58th Annual Meeting of the Asso-*
645 *ciation for Computational Linguistics*, pages 5055–
646 5070, Online. Association for Computational Lin-
647 guistics. 648 649

Alexander Fabbri, Chien-Sheng Wu, Wenhao Liu, and
Caiming Xiong. 2022. [QAFactEval: Improved QA-](#)
[based factual consistency evaluation for summariza-](#)
650 [tion](#). In *Proceedings of the 2022 Conference of the*
651 *North American Chapter of the Association for Com-*
652 *putational Linguistics: Human Language Technolo-*
653 *gies*, pages 2587–2601, Seattle, United States. Asso-
654 ciation for Computational Linguistics. 655 656 657

YanJun Gao, Chen Sun, and Rebecca J. Passonneau.
2019. [Automated pyramid summarization evaluation](#).
658 In *Proceedings of the 23rd Conference on Computa-*
659 *tional Natural Language Learning (CoNLL)*, pages
660 404–418, Hong Kong, China. Association for Com-
661 putational Linguistics. 662 663

Zorik Gekhman, Jonathan Herzig, Roei Aharoni, Chen
Elkind, and Idan Szpektor. 2023. [TrueTeacher:](#)
[Learning factual consistency evaluation with large](#)
664 [language models](#). In *Proceedings of the 2023 Con-*
665 *ference on Empirical Methods in Natural Language*
666 *Processing*, pages 2053–2070, Singapore. Associa-
667 tion for Computational Linguistics. 668 669 670

John Glover, Federico Fancellu, Vasudevan Jagan-
nathan, Matthew R. Gormley, and Thomas Schaaf.
2022. [Revisiting text decomposition methods for](#)
[NLI-based factuality scoring of summaries](#). In *Pro-*
671 *ceedings of the 2nd Workshop on Natural Language*
672 *Generation, Evaluation, and Metrics (GEM)*, pages
673 97–105, Abu Dhabi, United Arab Emirates (Hybrid).
674 Association for Computational Linguistics. 675 676 677 678

679	Ben Goodrich, Vinay Rao, Peter J. Liu, and Mohammad Saleh. 2019. Assessing the factual accuracy of generated text . In <i>Proceedings of the 25th ACM SIGKDD International Conference on Knowledge Discovery & Data Mining, KDD '19</i> , page 166–175, New York, NY, USA. Association for Computing Machinery.	734
680		735
681		736
682		737
683		
684		
685	Tanya Goyal and Greg Durrett. 2020. Evaluating factuality in generation with dependency-level entailment . In <i>Findings of the Association for Computational Linguistics: EMNLP 2020</i> , pages 3592–3603, Online. Association for Computational Linguistics.	738
686		739
687		740
688		741
689		742
690	Tanya Goyal and Greg Durrett. 2021. Annotating and modeling fine-grained factuality in summarization . In <i>Proceedings of the 2021 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies</i> , pages 1449–1462, Online. Association for Computational Linguistics.	743
691		744
692		745
693		746
694		
695		
696		
697	Aaron Harnly, Ani Nenkova, Rebecca Passonneau, and Owen Rambow. 2005. Automation of summary evaluation by the pyramid method. In <i>International Conference on Recent Advances in Natural Language Processing, RANLP 2005 - Proceedings</i> , International Conference Recent Advances in Natural Language Processing, RANLP, pages 226–232. Association for Computational Linguistics (ACL). International Conference on Recent Advances in Natural Language Processing, RANLP 2005 ; Conference date: 21-09-2005 Through 23-09-2005.	747
698		748
699		749
700		
701		
702		
703		
704		
705		
706		
707		
708	Karl Moritz Hermann, Tomáš Kočiský, Edward Grefenstette, Lasse Espeholt, Will Kay, Mustafa Suleyman, and Phil Blunsom. 2015. Teaching machines to read and comprehend .	750
709		751
710		752
711		753
712	Matthew Honnibal, Ines Montani, Sofie Van Landeghem, and Adriane Boyd. 2020. spaCy: Industrial-strength Natural Language Processing in Python .	754
713		755
714		
715	Albert Q. Jiang, Alexandre Sablayrolles, Arthur Mensch, Chris Bamford, Devendra Singh Chaplot, Diego de las Casas, Florian Bressand, Gianna Lengyel, Guillaume Lample, Lucile Saulnier, L�lio Renard Lavaud, Marie-Anne Lachaux, Pierre Stock, Teven Le Scao, Thibaut Lavril, Thomas Wang, Timoth�e Lacroix, and William El Sayed. 2023. Mistral 7b .	756
716		757
717		758
718		759
719		760
720		761
721		762
722	Wojciech Kryscinski, Bryan McCann, Caiming Xiong, and Richard Socher. 2020. Evaluating the factual consistency of abstractive text summarization . In <i>Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing (EMNLP)</i> , pages 9332–9346, Online. Association for Computational Linguistics.	763
723		764
724		765
725		766
726		767
727		768
728		769
729	Philippe Laban, Tobias Schnabel, Paul N. Bennett, and Marti A. Hearst. 2022. SummaC: Re-visiting NLI-based models for inconsistency detection in summarization . <i>Transactions of the Association for Computational Linguistics</i> , 10:163–177.	770
730		771
731		772
732		773
733		774
	Chin-Yew Lin. 2004. ROUGE: A package for automatic evaluation of summaries . In <i>Text Summarization Branches Out</i> , pages 74–81, Barcelona, Spain. Association for Computational Linguistics.	775
		776
		777
	Yixin Liu, Alex Fabbri, Pengfei Liu, Yilun Zhao, Linyong Nan, Ruilin Han, Simeng Han, Shafiq Joty, Chien-Sheng Wu, Caiming Xiong, and Dragomir Radev. 2023. Revisiting the gold standard: Grounding summarization evaluation with robust human evaluation . In <i>Proceedings of the 61st Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)</i> , pages 4140–4170, Toronto, Canada. Association for Computational Linguistics.	778
		779
		780
		781
		782
		783
		784
		785
	Zheheng Luo, Qianqian Xie, and Sophia Ananiadou. 2023. Chatgpt as a factual inconsistency evaluator for text summarization .	786
		787
		788
		789
		790
	Joshua Maynez, Shashi Narayan, Bernd Bohnet, and Ryan McDonald. 2020. On faithfulness and factuality in abstractive summarization . In <i>Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics</i> , pages 1906–1919, Online. Association for Computational Linguistics.	791
		792
		793
		794
		795
		796
		797
		798
		799
		800
		801
		802
		803
		804
		805
		806
		807
		808
		809
		810
		811
		812
		813
		814
		815
		816
		817
		818
		819
		820
		821
		822
		823
		824
		825
		826
		827
		828
		829
		830
		831
		832
		833
		834
		835
		836
		837
		838
		839
		840
		841
		842
		843
		844
		845
		846
		847
		848
		849
		850
		851
		852
		853
		854
		855
		856
		857
		858
		859
		860
		861
		862
		863
		864
		865
		866
		867
		868
		869
		870
		871
		872
		873
		874
		875
		876
		877
		878
		879
		880
		881
		882
		883
		884
		885
		886
		887
		888
		889
		890
		891
		892
		893
		894
		895
		896
		897
		898
		899
		900

791	pages 4885–4901, Online. Association for Computational Linguistics.		848
792			849
793	OpenAI. 2022. Chatgpt blog post. https://openai.com/blog/chatgpt .		850
794			851
795	OpenAI. 2023. Gpt-4 technical report .		852
796	Long Ouyang, Jeffrey Wu, Xu Jiang, Diogo Almeida, Carroll Wainwright, Pamela Mishkin, Chong Zhang, Sandhini Agarwal, Katarina Slama, Alex Gray, John Schulman, Jacob Hilton, Fraser Kelton, Luke Miller, Maddie Simens, Amanda Askell, Peter Welinder, Paul Christiano, Jan Leike, and Ryan Lowe. 2022. Training language models to follow instructions with human feedback . In <i>Advances in Neural Information Processing Systems</i> .		853
797			854
798			855
799			856
800			857
801			858
802			
803			
804			
805	Tal Schuster, Sihao Chen, Senaka Buthpitiya, Alex Fabrikant, and Donald Metzler. 2022. Stretching sentence-pair NLI models to reason over long documents and clusters . In <i>Findings of the Association for Computational Linguistics: EMNLP 2022</i> , pages 394–412, Abu Dhabi, United Arab Emirates. Association for Computational Linguistics.		859
806			860
807			861
808			862
809			863
810			864
811			865
812	Tal Schuster, Adam Fisch, and Regina Barzilay. 2021. Get your vitamin C! robust fact verification with contrastive evidence . In <i>Proceedings of the 2021 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies</i> , pages 624–643, Online. Association for Computational Linguistics.		866
813			867
814			868
815			869
816			870
817			871
818			
819	Thomas Scialom, Paul-Alexis Dray, Sylvain Lamprier, Benjamin Piwowarski, Jacopo Staiano, Alex Wang, and Patrick Gallinari. 2021. QuestEval: Summarization asks for fact-based evaluation . In <i>Proceedings of the 2021 Conference on Empirical Methods in Natural Language Processing</i> , pages 6594–6604, Online and Punta Cana, Dominican Republic. Association for Computational Linguistics.		872
820			873
821			874
822			875
823			876
824			
825			
826			
827	Ori Shapira, David Gabay, Yang Gao, Hadar Ronen, Ramakanth Pasunuru, Mohit Bansal, Yael Amsterdamer, and Ido Dagan. 2019. Crowdsourcing lightweight pyramids for manual summary evaluation . In <i>Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers)</i> , pages 682–687, Minneapolis, Minnesota. Association for Computational Linguistics.		877
828			878
829			879
830			880
831			881
832			882
833			883
834			884
835			885
836			886
837	Derek Tam, Anisha Mascarenhas, Shiyue Zhang, Sarah Kwan, Mohit Bansal, and Colin Raffel. 2023. Evaluating the factual consistency of large language models through news summarization . In <i>Findings of the Association for Computational Linguistics: ACL 2023</i> , pages 5220–5255, Toronto, Canada. Association for Computational Linguistics.		887
838			888
839			889
840			890
841			891
842			892
843			
844	Liyang Tang, Tanya Goyal, Alex Fabbri, Philippe Laban, Jiacheng Xu, Semih Yavuz, Wojciech Kryscinski, Justin Rousseau, and Greg Durrett. 2023. Understanding factual errors in summarization: Errors, summarizers, datasets, error detectors . In <i>Proceedings of the 61st Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)</i> , pages 11626–11644, Toronto, Canada. Association for Computational Linguistics.		893
845			894
846			895
847			896
			897
			898
			899
			900
			901
			902
			903
			904

905 Yuheng Zha, Yichi Yang, Ruichen Li, and Zhiting Hu.
906 2023. [AlignScore: Evaluating factual consistency](#)
907 [with a unified alignment function](#). In *Proceedings*
908 *of the 61st Annual Meeting of the Association for*
909 *Computational Linguistics (Volume 1: Long Papers)*,
910 pages 11328–11348, Toronto, Canada. Association
911 for Computational Linguistics.

912 Shiyue Zhang and Mohit Bansal. 2021. [Finding a bal-](#)
913 [anced degree of automation for summary evaluation](#).
914 In *Proceedings of the 2021 Conference on Empiri-*
915 *cal Methods in Natural Language Processing*, pages
916 6617–6632, Online and Punta Cana, Dominican Re-
917 public. Association for Computational Linguistics.

918 Tianyi Zhang, Varsha Kishore, Felix Wu, Kilian Q.
919 Weinberger, and Yoav Artzi. 2020. [Bertscore: Evalu-](#)
920 [ating text generation with bert](#).

921 Yue Zhang, Yafu Li, Leyang Cui, Deng Cai, Lemao Liu,
922 Tingchen Fu, Xinting Huang, Enbo Zhao, Yu Zhang,
923 Yulong Chen, Longyue Wang, Anh Tuan Luu, Wei
924 Bi, Freda Shi, and Shuming Shi. 2023. [Siren’s song](#)
925 [in the ai ocean: A survey on hallucination in large](#)
926 [language models](#). *ArXiv*, abs/2309.01219.

A Prompt for Atomic Facts Decomposition

The prompt for atomic fact decomposition is shown in Table 7. The examples given in the prompt are similarly used in other LLMs.

B Experimental Details

Baseline Details In this section, we present the implementation details of FACTSCORE and FACTOOL, which have been integrated into our experimental baseline. For decomposing atomic facts, FACTSCORE uses the gpt-3.5-turbo-instruct model, and the QA process is conducted using gpt-3.5-turbo, with prompts exactly as specified in the paper⁴. Similar to FACTSCORE, FACTOOL employs gpt-3.5-turbo for both the *claim* extraction and the QA tasks, again using prompt directly from the paper⁵.

Language Model Details We report on the details and Huggingface links of LLMs used in Section 4. We employed Orca-2-7B model⁶ for experiments in AGGREGFACT benchmark dataset. For Zephyr, we used Zephyr-7B-beta⁷, while for Mistral, we used Mistral-7B-instruct-v0.2⁸. Additionally, we used ChatGPT version of gpt-3.5-turbo-0125.

NLI Model Details We leveraged NLI model from SUMMAC⁹, which has been trained on the conventional NLI datasets SNLI (Bowman et al., 2015), MNLI (Williams et al., 2018), ANLI (Nie et al., 2020), and also on VitaminC (Schuster et al., 2021).

Coreference Resolution Details We used MT5-11B model for coreference resolution¹⁰. Coreference resolution is the task of identifying all expressions that refer to the same entity within a text. While recent models perform well on this task, returning a text with resolved coreferences is an entirely different challenge. We have tested various models, but none have functioned adequately. A

⁴<https://github.com/shmsw25/FActScore>

⁵<https://github.com/GAIR-NLP/factool>

⁶<https://huggingface.co/microsoft/Orca-2-7b>

⁷<https://huggingface.co/HuggingFaceH4/zephyr-7b-beta>

⁸<https://huggingface.co/mistralai/Mistral-7B-Instruct-v0.2>

⁹<https://huggingface.co/tals/albert-xlarge-vitaminc-mnli>

¹⁰<https://huggingface.co/mt5-coref-pytorch/link-append-xxl>

Sentence Splitter	AGGREGFACT-CNN-FtSOTA	AGGREGFACT-XSUM-FtSOTA	AVG
Spacy	72.5±3.4	67.0±2.0	69.8
NLTK	72.6±3.0	69.3±1.9	71.0

Table 6: Sentence splitter choice on AGGREGFACT-FtSOTA split.

significant issue was the prevalent method of using the first word in a cluster for resolution instead of the entity’s name, which frequently resulted in improper replacements with pronouns. To address this, we slightly modified the code to ensure that where an entity name is available, it replaces pronouns as much as possible¹¹. Furthermore, when an adjective or a modifier refers to an entity, we prefixed it with the entity’s name followed by a comma. Table 8 illustrates these modifications. By enhancing coreference resolution in this manner, we were able to capture more comprehensive atomic facts without omitting critical information.

Other Details In this section, we report the differences observed when splitting text into sentences using NLTK (Bird et al., 2009) and Spacy (Hon-nibal et al., 2020). We utilized NLTK sentence splitter in FIZZ. The results of the experiments are presented in Table 6.

¹¹https://github.com/google-research/google-research/tree/master/coref_mt5

Input Prompt

You are a helpful assistant. Please give me a list of atomic facts of the following texts.

lisa courtney, of hertfordshire, has spent most of her life collecting pokemon memorabilia.

- Lisa Courtney is from Hertfordshire.
- Lisa Courtney has spent most of her life collecting Pokémon memorabilia.

prince jan zylinski said he was fed up with discrimination against poles living in britain.

- Prince Jan Zylinski made a statement.
- The statement made by Prince Jan Zylinski was about discrimination.
- The statement made by Prince Jan Zylinski was regarding Poles living in Britain.
- Prince Jan Zylinski expressed feeling fed up with this type of discrimination.

no charges were filed, there will be no travel ban.

- No charges were filed.
- There will be no travel ban.

rudd has pleaded guilty to threatening to kill and possession of drugs in a court.

- Rudd has pleaded guilty.
- Rudd has pleaded guilty to threatening to kill.
- Rudd has pleaded guilty to possession of drugs.

Lee made his acting debut in the film The Moon is the Sun's Dream (1992), and continued to appear in small and supporting roles throughout the 1990s.

- Lee made his acting debut in The Moon is the Sun's Dream.
- The Moon is the Sun's Dream is a film.
- The Moon is the Sun's Dream was released in 1992.
- After Lee's acting debut, he appeared in small and supporting roles throughout the 1990s.

In 1963, Collins became one of the third group of astronauts selected by NASA and he served as the back-up Command Module Pilot for the Gemini 7 mission.

- Collins became an astronaut.
- Collins became one of the third group of astronauts selected by NASA in 1963.
- Collins served as the back-up Command Module Pilot for the Gemini 7 mission.

In addition to his acting roles, Bateman has written and directed two short films and is currently in development on his feature debut.

- Bateman has acting roles.
- Bateman has written two short films.
- Bateman has directed two short films.
- Bateman is currently in development on his feature debut.

Michael Collins (born October 31, 1930) is a retired American astronaut and test pilot who was the Command Module Pilot for the Apollo 11 mission in 1969.

- Michael Collins was born on October 31, 1930.
- Michael Collins is retired.
- Michael Collins is an American.
- Michael Collins was an astronaut.
- Michael Collins was a test pilot.
- Michael Collins was the Command Module Pilot for the Apollo 11 mission in 1969.

Summary Sentence

Table 7: Prompt used to generate atomic facts from coreference resolved summary in Section 3.2. We employed 8-shot learning to enhance the model's performance.

Original Text		The 27-year-old joined spurs from manchester city in 2011.
	Coref Resolved Text	Emmanuel Adebayor joined spurs from manchester city in 2011.
Others	Atomic Fact #1	Emmanuel Adebayor joined spurs.
	Atomic Fact #2	Emmanuel Adebayor joined spurs from manchester city.
	Atomic Fact #3	Emmanuel Adebayor joined spurs in 2011.
	Coref Resolved Text	Emmanuel Adebayor, the 27-year-old joined spurs from manchester city in 2011.
Ours	Atomic Fact #1	Emmanuel Adebayor is 27-year-old.
	Atomic Fact #2	Emmanuel Adebayor joined spurs.
	Atomic Fact #3	Emmanuel Adebayor joined spurs from manchester city.
	Atomic Fact #4	Emmanuel Adebayor joined spurs in 2011.

Table 8: Our distinct approach for coreference resolution. The original text is coreference resolved by two ways, which are **Others** and **Ours**. We ensure that critical information is preserved while generating atomic facts by prefixing modifiers with the names of entities during the coreference resolution.