

JUDGE DECODING: FASTER SPECULATIVE SAMPLING REQUIRES GOING BEYOND MODEL ALIGNMENT

Anonymous authors

Paper under double-blind review

ABSTRACT

The performance of large language models (LLMs) is closely linked to their underlying size, leading to ever-growing networks and hence slower inference. Speculative decoding has been proposed as a technique to accelerate autoregressive generation, leveraging a fast draft model to propose candidate tokens, which are then verified in parallel based on their likelihood under the target model. While this approach guarantees to reproduce the target output, it incurs a substantial penalty: many high-quality draft tokens are rejected, even when they represent objectively valid continuations. Indeed, we show that even powerful draft models such as GPT-4o, as well as human text cannot achieve high acceptance rates under the standard verification scheme. This severely limits the speedup potential of current speculative decoding methods, as an early rejection becomes overwhelmingly likely when solely relying on alignment of draft and target.

We thus ask the following question: *Can we adapt verification to recognize correct, but non-aligned replies?* To this end, we draw inspiration from the *LLM-as-a-judge* framework, which demonstrated that LLMs are able to rate answers in a versatile way. We carefully design a dataset coined *TokenCourt* to elicit the same capability in the target model by training a compact module on top of the embeddings to produce “judgements” of the current continuation. We showcase our strategy on the Llama-3.1 family, where our 8b/405B-Judge achieves a speedup of $9\times$ over Llama-405B, while maintaining its quality on a large range of benchmarks. These benefits remain present even in optimized inference frameworks, where our method reaches up to 141 tokens/s for 8B/70B-Judge and 129 tokens/s for 8B/405B on 2 and 8 H100s respectively.




Figure 1: Standard speculative decoding versus our judge decoding strategy for Llama-3.1-8B as draft and Llama-3.1-405B as target. Accepted (rejected) tokens are highlighted in green (red). SD verification rejects tokens due to misalignment, even if these tokens are correct within the context of the response. Our judge decoding recognizes the correct tokens, leading to high acceptance rate.

1 INTRODUCTION

Large language models have transformed the field of natural language processing in recent years, displaying astounding capabilities across various tasks (Radford et al., 2019; OpenAI et al., 2024). The performance of these models is closely tied to their underlying size, with bigger models often achieving significantly better results across benchmarks (Kaplan et al., 2020; Hoffmann et al., 2022). For example, Meta recently released their largest and best model to date with Llama-3.1-405B, boasting an enormous parameter count of 405 billion (Dubey et al., 2024).

While offering great performance, such big models require a vast amount of resources to be deployed, and inference efficiency starts to pose a critical problem. Due to the autoregressive nature of decoding coupled with the large parameter count, token generation becomes a memory-bound process, especially at small batch sizes (Shazeer, 2019; Ivanov et al., 2021; Pope et al., 2023). To speed up inference in such a setting, *speculative decoding* (SD) has been proposed (Stern et al., 2018; Xia et al., 2023; Chen et al., 2023; Leviathan et al., 2023), a technique that leverages the fact that processing several tokens in parallel comes at no additional latency cost in the memory-bound regime. More concretely, a small but fast *draft* model produces a sequence of M candidate tokens, which are then verified in parallel by the model of interest, usually referred to as the *target* model. In standard SD, the target model accepts a candidate token if it assigns the same or higher probability given the context, otherwise a biased coin is flipped. If at least one candidate token is accepted, inference time is reduced as the large model needs to be called only once to produce multiple tokens. As shown in Chen et al. (2023), such a strategy provably preserves the distribution of the target model while achieving significant speedups.

Relying on target probabilities guarantees the same output, but as a consequence, a token is solely judged based on its alignment with the target model, and not by its inherent contextual quality. As a consequence, current approaches set the number of candidate tokens to small numbers $M \in \{5, 7\}$, as an early rejection becomes overwhelmingly likely when drafting more. On the other hand, the quality of “small” language models (and thus the quality of candidate tokens) has been rapidly improving recently. GPT-4o and the recently introduced GPT-4o-mini show strong performance across many benchmarks, with OpenAI actively recommending these models over the more expensive GPT-4. Similarly, Llama-3.1-8B has achieved bigger gains in performance over its prior iterations, compared to the larger Llama-3.1-70B (Dubey et al., 2024), highlighting as well that small models are catching up. Phi-3-mini is another small model at “only” three billion parameters that despite its size manages to match the performance of GPT-3.5 (Abdin et al., 2024).

While draft models are rapidly improving and providing increasingly high-quality answers, alignment-based verification fails to reflect this progress, still rejecting tokens that are not perfectly aligned with the target response (see Fig. 1 for an example). Motivated by this insight, we explore the following question in this paper:

Can we adapt verification to assess token quality rather than alignment?

We draw inspiration from the *LLM-as-a-judge* framework, where LLMs are used to judge the quality of other model responses to user questions (Zheng et al., 2023). These judgements exhibit very strong correlation with human ratings, making this a cheap and scalable approach for model quality evaluation. Interestingly, LLM-judges display the ability to rate answers in a versatile way, allowing them to appreciate correct but potentially unaligned responses. To equip the target model with similar capabilities, we design a small dataset consisting of correct and wrong replies to user questions. We create a diverse set of responses from several models and precisely annotate the location of the mistaken tokens. We then leverage the powerful target embeddings to train a small module with the objective of predicting the correctness of a given token, mimicking the LLM-judge mechanism.

In summary, we make the following contributions:

- We demonstrate through a series of experiments how the decision mechanism in speculative decoding rejects many high quality tokens, identifying a key limitation of the technique.
- We adapt verification using ideas from *LLM-as-a-judge*, eliciting the same versatile rating capability in the target by adding a simple linear layer that can be trained in under 1.5 hours.
- Using a Llama 8B/70B-Judge, our approach obtains speedups of $9\times$ over standard decoding, achieving an unprecedented 129 tokens/s, while maintaining the quality of Llama-405B on a range of benchmarks.

2 RELATED WORKS

Speculative decoding has been used and extended in a range of works, leading to significant speedups across many model families and datasets. Several ideas for draft models have been explored in the literature. Early papers rely on specialized draft models (Sun et al., 2021; Xia et al., 2023) or smaller versions of the target model (Chen et al., 2023; Leviathan et al., 2023), usually trained using the same data and learning protocol. Another line of work uses shallow networks on top of the target embeddings as a drafter with the goal to predict multiple tokens into the future (Stern et al., 2018; Cai et al., 2024; Li et al., 2024a;b; Zhang et al., 2024a; Wertheimer et al., 2024; Ankner et al., 2024; Gloeckle et al., 2024; Bhendawade et al., 2024). Other approaches use a sub-network of the target model, e.g. Schuster et al. (2022); Zhang et al. (2024b); Elhoushi et al. (2024); Liu et al. (2024b;a) skip a percentage of the layers to produce candidate tokens. Other architectures have also been explored: Wang et al. (2024) develop a SD variant for Mamba models (Gu & Dao, 2024), while Christopher et al. (2024) explore diffusion-based language models as drafters. Other components of the process have been investigated as well; Huang et al. (2024); Liu et al. (2024c) analyze the number of draft tokens M with the goal of learning to choose it dynamically. Kim et al. (2023) take a similar approach aiming to measure the uncertainty of the draft model, allowing the target to take over when needed. Monea et al. (2023); Bachmann & Nagarajan (2024) on the other hand explore parallel decoding without a draft by conditioning on “look-ahead” tokens or using Jacobi iterations (Santilli et al., 2023; Fu et al., 2024), allowing the target to produce several tokens in one step.

Many works have aimed to improve the acceptance rates in SD: Zhou et al. (2024) encourage higher alignment by finetuning with a distillation loss, Li et al. (2024a); Cai et al. (2024); Ankner et al. (2024); Miao et al. (2024); Chen et al. (2024) construct token trees out of the top- K predictions in various ways and verify them in parallel using tree-attention, covering thus a larger space of token combinations. Other methods propose to exchange more information between draft and target: Du et al. (2024) allow the draft to access the key-value cache of the target, while in S et al. (2024) the draft is further conditioned on target activations. All these methods improve acceptance rates by either encouraging better alignment with more information or producing more guesses in parallel. This is different from our work, which seeks to change the verification scheme itself.

3 VERIFICATION IN SPECULATIVE DECODING

3.1 BACKGROUND

Speculative decoding. Denote by LLM_{targ} and $\text{LLM}_{\text{draft}}$ the target and draft model respectively. We use $\mathcal{V} = \{1, \dots, V\}$ for the vocabulary. Let $M \in \mathbb{N}$ represent the number of candidate tokens, m_* the number of accepted tokens and $\mathbf{s} \in \mathcal{V}^L$ the context. Let us denote by

$$(t_1, \mathbf{p}_1), \dots, (t_m, \mathbf{p}_m) = \text{LLM}^{(m)}(\mathbf{s}) \quad (1)$$

an autoregressive sampling of m tokens from LLM given context \mathbf{s} , where $t_1, \dots, t_m \in \mathcal{V}$ are the sampled tokens and $\mathbf{p}_i \in \mathbb{R}^V$ the corresponding softmax probabilities. Further, we denote by

$$\mathbf{p}_1, \dots, \mathbf{p}_{m+1} = \text{LLM}(t_1, \dots, t_m; \mathbf{s}) \quad (2)$$

running the (parallel) forward pass of LLM on tokens t_1, \dots, t_m . Notice that this produces one more probability vector \mathbf{p}_{m+1} as we now also process token t_m .

In SD, the draft model autoregressively produces M candidate tokens given the current context \mathbf{s} using any sampling scheme (but usually greedy),

$$(c_1, \mathbf{q}_1), \dots, (c_M, \mathbf{q}_M) = \text{LLM}_{\text{draft}}^{(M)}(\mathbf{s}) \quad (3)$$

where c_1, \dots, c_M are the sampled candidate tokens and $\mathbf{q}_i \in \mathbb{R}^V$ for $i = 1, \dots, M$ are the corresponding probability vectors over the vocabulary. The probability of token c_i under the draft model is thus $\mathbf{q}_i[c_i]$. The target model then processes these tokens in parallel, resulting in probability vectors $\mathbf{p}_1, \dots, \mathbf{p}_{M+1} = \text{LLM}_{\text{targ}}(c_1, \dots, c_M; \mathbf{s})$. Rejection now works as follows:

$$\text{Accept } c_i \text{ if all previous tokens are accepted and } \epsilon_i < \frac{\mathbf{p}_i[c_i]}{\mathbf{q}_i[c_i]} \text{ for } \epsilon_i \sim \mathcal{U}([0, 1]) \quad (4)$$




Figure 2: **Left:** Average number of generated tokens as a function of the number of draft tokens M for Llama-8B/405B with standard and judge verification. **Right:** Number of accepted tokens on high-quality human text (top) and for both 8B/405B and 405B/8B (bottom), both standard SD.

In words, a candidate c_i is accepted if the probability under the target model is even larger. If the probability is smaller, a stochastic decision is made according to the discrepancy between the probabilities. Crucially, one is always guaranteed to produce at least one valid token: p_1 is solely a function of the current context s and can thus be used to sample a token according to the target distribution. Similarly, if c_i is the first rejected token, one can sample a correct token from p_i . Finally, when all candidate tokens are accepted, an extra token can be sampled from p_{M+1} . The accepted tokens are then added to the current context s and we repeat the steps until completion.

Number of draft tokens. An immediate question comes to mind when examining speculative decoding: How many draft tokens should one choose for optimal speedup? On the one hand, if the draft model produces good tokens, one would ideally want to draft a high number of candidate tokens M to avoid invoking the expensive target model too many times. On the other hand, if many candidates end up being rejected, one wants to avoid spending the unnecessary drafting time. The ideal M thus heavily depends on the acceptance rate, which in turn naturally depends on the verification scheme. In Fig. 2 we plot the average number of accepted tokens as a function of M for the model pair Llama-3.1-8B and Llama-3.1-405B evaluated on MT-Bench (Zheng et al., 2023) and GSM8K (Cobbe et al., 2021) (yellow curve). We observe that the number of accepted tokens quickly saturates as a function of M and the acceptance rates thus decrease rapidly. As a result, choosing a large number of draft tokens M solely calls the draft model more in vain, leading to inefficient inference overall. This is the reason why prior work is limited largely to $M \leq 7$.

3.2 LIMITATIONS OF STANDARD VERIFICATION

Rejected tokens. What types of tokens get rejected in such a setup? In order to obtain an intuition, we explore the behaviour of SD on several benchmarks including GSM8K, MT-Bench and HumanEval (Chen et al., 2021). We use Llama-8B as the draft and Llama-405B as the target model. While there is a significant discrepancy in terms of performance between these two models, it is worth highlighting that the draft model achieves competitive scores on all these tasks. Higher acceptance rates would thus not necessarily reduce the quality of the output on many of these examples. In fact, a large number of draft answers could be accepted as they are, especially those addressing relatively simple queries.

Notably, even in instances where the draft model produces entirely accurate solutions, the target model frequently rejects numerous tokens due to the stringent nature of the verification process. This rejection occurs despite the correctness of the solution, as the target model seeks alignment with its own response rather than contextual accuracy (Liu et al., 2023). As illustrated in Fig 1, a correct answer can be rejected after only two tokens, underscoring the potential for relaxed verification




Figure 3: **Left:** Standard SD and our judge decoding when GPT-4o is drafting and Llama-405B is verifying. Green denotes accepted and red rejected tokens. **Right:** Number of accepted tokens for GPT-4o as draft and Llama-405B as target for standard speculative and our judge verification.

schemes.¹ Intuitively, one would expect from a well-calibrated verification scheme to allow for accepting candidate tokens whenever they are contextually correct. However, as we show in the following two paragraphs, this not the case for standard logits-based verification.

High-quality draft model. To further demonstrate how valid responses incur high rejection rates, we perform the following experiment: We take a very powerful LLM as the draft model and evaluate whether the target model accepts more candidate tokens, which are now guaranteed to be of high quality. While such a setup does not make sense for SD from an efficiency point of view (a powerful drafter is of course too slow), it further investigates if acceptance rates improve with the quality of responses. To that end we use GPT-4o as draft model for the target Llama-405B. We generate full answers with GPT-4o on MT-Bench, GSM8K and HumanEval and simply check how many tokens the target accepts under greedy decoding before the first rejection, as there is no way to properly perform SD with closed-source models. In order to ensure that the target model is able to “recognize” the high-quality tokens, we use the performant Llama-405B. We display the average acceptance length and an example prompt in Fig. 3. Counter-intuitively, we find that the target model does not reward the higher quality of tokens, accepting only roughly two before encountering the first rejection. To further explore if this observation changes when running the complete process of SD, we reverse the roles of our standard setup and use Llama-405B as draft for a Llama-8B target model. Similarly, we find that reversing the roles reduces the number of accepted tokens slightly (see Fig. 2, right side), even though they are of better quality now. We thus conclude that acceptance rates do not improve with the quality of the responses.

Human expert drafting. Finally, we evaluate the efficacy of human annotations as candidate tokens for Llama-405B by processing *Wikipedia* articles. Using a subset of the `wikipedia-summary` dataset (Schepers, 2017), which contains high-quality, community-reviewed abstracts, we assess token acceptance rates under greedy SD verification when prompting the model to summarize these articles. As illustrated in Fig. 2 (right), a substantial proportion of tokens face rejection, even within this high-quality context.

In summary, we conclude that SD verification in its current form is highly inefficient, as large portions of correct answers are rejected. Motivated by this insight, the following section presents a more effective verification scheme that goes beyond model alignment in order to increase efficiency.

¹Additional examples of this phenomenon are provided in Appendix C.1 for further examination.




Figure 4: Two examples from our dataset TokenCourt. We highlight the incorrect tokens in the wrong answer in red.

4 JUDGE DECODING

As demonstrated by previous experiments, we need a more flexible method of verifying sequences to increase the number of accepted draft tokens, especially as draft models continue to improve in quality. Recent work by Zheng et al. (2023) showed that large LLMs can reliably act as judges to evaluate responses generated by less capable models, correlating highly with human ratings. This judging approach allows for more versatile evaluation, focusing on correctness and contextual quality rather than strict alignment. However, using LLM-judges directly is not feasible because (a) they require lengthy system prompts and often chain-of-thought reasoning, slowing inference, and (b) they evaluate full answers, whereas SD requires evaluating short, sometime partial continuations.

We thus aim to achieve this judge-like behavior efficiently while retaining the advantages of the original verification method, which ensures accurate next-token predictions in case of rejection. Since this involves computing embeddings for each draft token, we explore whether these embeddings contain sufficient information to enable rapid, reliable judgments.

4.1 VERSATILE AND ACCURATE VERIFICATION WITH TOKEN EMBEDDINGS

Token embeddings signal errors. Contrary to standard SD, which accepts or rejects a given token based on its softmax probabilities (see Eq. 4), we find that the model’s reaction to processing the incorrect token itself reveals surprisingly valuable information. Specifically, our experiments show that last hidden layer embeddings of erroneous tokens effectively “flag” errors and contradictions, prompting the model to generate subsequent tokens that attempt to correct the mistake. This phenomenon is strikingly illustrated in Fig. 5, where we condition Llama-405B on wrong replies (highlighted in red) and observe the model’s immediate efforts to rectify its response (highlighted in green). For instance, when forced to start with the incorrect statement “The capital of France is Berlin”, the model continues with “... just kidding, it’s actually Paris”. More such examples can be found in Appendix C.3. This unexpected behavior suggests the feasibility of leveraging the embedding of the *current* token as a means of verifying its correctness. In fact, we will show in the following that a simple logistic regression head on top of these embeddings achieves high accuracy and can be trained in under 1.5 hours. Prior, embeddings have also been used to discover latent knowledge in LLMs or edit their behaviour (Burns et al., 2023; Zou et al., 2023a; Marks & Tegmark, 2024; von Rütte et al., 2024), further underscoring their richness.

Dataset curation. In order to leverage token embeddings for verification, we carefully craft a dataset consisting of high-quality user inputs, along with a correct and wrong answer pair, coined TokenCourt. The set of input prompts are a mixture of newly-created questions and two public datasets that we heavily filtered (Alpaca (Taori et al., 2023) and ARC (Clark et al., 2018)). Importantly, we only use the input questions and none of the answers. We leverage several models to produce a diverse set of correct and wrong answers, including Mistral-Large-2, Llama-8B and Llama-405B, thereby fostering robustness of the trained judge to recognize correct but differently aligned solutions. All answers were manually reviewed and corrected by the authors, who also

annotated the precise location of errors in wrong answers². In total we collected 500 high-quality question, correct answer, wrong answer tuples. For training, we label every token from the correct answer as positive, every token from the wrong answer up until the point of mistake as positive, and finally every mistaken token as negative. Two examples from our dataset are depicted in Fig. 4. Naturally, the dataset exhibits a strong imbalance, leading to roughly $20\times$ more positive than negative examples.

Model design and training. Equipped with the dataset, we train a linear head f_{judge} on top of the target embeddings, using a weighted cross entropy loss as the objective to counter the imbalance in the dataset. We place larger weight on the negative examples in order to ensure that the resulting judge does not falsely accept wrong tokens to limit quality degradation and perform early-stopping to reduce overfitting. We tune all hyperparameters on a small test split from `TokenCourt`. We experiment with embeddings from several layers and find that deeper layers perform best with only insignificant differences, while too shallow layers are clearly worse, consistent with similar observations in previous works (Zou et al., 2023b; Gurnee & Tegmark, 2023; von Rütte et al., 2024). For simplicity, we thus stick to using the last embedding of the target before the RMS normalization (Zhang & Sennrich, 2019) and the language modelling (LM) head. While we experimented with more complex architectures, including MLPs and shallow Transformer networks, a simple linear head proved most effective, demonstrating excellent performance without overfitting. This linear classifier offers significant practical advantages: we train only 16.4k parameters on just 30k tokens in less than 1.5 hours, with all target model parameters remaining frozen. Additional details are provided in Appendix B.1.

Inference. How is the judge head now combined with the standard elements of SD? In essence, we use f_{judge} as an additional evaluator for a given token c_i (or rather its embedding $e_i \in \mathbb{R}^D$) and accept it if $\sigma(f_{\text{judge}}(e_i)) > \delta$ for $\delta \in [0.5, 1]$, where σ is the sigmoid function. In other words, δ serves as a threshold for the confidence of acceptance and practitioners can thus choose how much to trust the judge layer. In practice we observed that there is no need to tune this value to ensure quality and leave it at the natural value $\delta = 0.5$. Given a sequence of candidate tokens c_1, \dots, c_M , we thus get two accept/reject masks from the target model: $z_{\text{stand}} \in \{0, 1\}^M$ as in standard SD verification and $z_{\text{judge}} \in \{0, 1\}^M$ from the judge head. We take the logical OR between the two, $z = z_{\text{stand}} \vee z_{\text{judge}}$, since when the judge rejects and standard SD accepts, the corrected token according to the target will exactly be the same token. We can thus already accept it. We illustrate this mechanism in more detail in Appendix B.2. Note that $\delta = 1$ reduces to SD.

5 EVALUATION OF JUDGE DECODING

First, we revisit the initial experiments outlined in Sec. 3.2 where we use GPT-4o as the draft model, as well as human generated text as candidate tokens. In both cases, the average number of accepted tokens is significantly higher for our method across datasets (see Fig 2 and 3). The example prompt in Fig. 3 (left) shows that the correct response of GPT-4o is fully accepted by judge decoding while standard SD rejects after two words. This illustrates that our verification scheme offers more versatile decisions.

5.1 PERFORMANCE BENCHMARK

We now evaluate our verification method on standard benchmarks in the SD literature, including GSM8K (Cobbe et al., 2021), HumanEval (Chen et al., 2021) and MT-Bench (Zheng et al., 2023). In contrast to standard SD works, we do need to report the achieved accuracy values of our strategy, as adapting verification comes with the possibility of accepting wrong tokens and thus worse performance. To give a more complete picture, we further include multiple-choice benchmarks ARC (Clark et al., 2018) and MMLU (Hendrycks et al., 2021), which are atypical tasks for standard SD as only a few tokens need to be produced, but further serves as a check that our verification scheme does not degrade performance. We use the prompting templates from Dubey et al. (2024).

²Using LLMs to that end proved to be too imprecise, which is consistent with recent observations in Tyen et al. (2024).




Figure 5: **Left:** Conditioning Llama-405B on wrong outputs. The part of the assistant response in red was forced, while parts in green were generated freely. **Right:** Judge illustration where s_L is the last token from the context s and c_1, \dots, c_M are candidate tokens. Orange denotes embeddings, green denotes the LM-head output and red denotes the produced judgements.

Table 1: Average acceptance length (m_*) and speedup factor over standard decoding in HuggingFace and *gpt-fast* for batch size 1. We report generation tokens/s for *gpt-fast* for 512 input and output tokens, quantized to 8-bit. All 70B (405B) models run on 2 (8) H100 GPUs, except for *Medusa (Nvidia, 2024), which runs on significantly faster H200s with NVLink Switch and TensorRT.

	m_*	HUGGINGFACE	GPT-FAST	TOKENS/S (512 + 512)
8B/70B-STANDARD	6.4	1.5×	1.7×	76.7
8B/70B-JUDGE (OURS)	18.8	2×	3×	141.8
70B-EAGLE-2	4.5	3.3×	1.9×	88.1
8B/405B-STANDARD	6.3	5.3×	1.78×	58.7
8B/405B-JUDGE (OURS)	19.7	9.7×	3.9×	129.3
405B-MEDUSA	< 6	< 6×	1.9×	108*

Training-free baseline. To provide more context for our results and to demonstrate that our judging strategy goes beyond simple heuristics, we also explore a simple training-free method to relax the acceptance scheme. In particular, we investigate top- K verification, where a candidate token c_i is accepted, if it is among the K highest valued probabilities p_i produced by token c_{i-1} . $K \in \mathbb{N}$ is a hyper-parameter of the decoding technique that trades-off quality against speed. Setting $K = V$ reduces to running just the fast draft model, while $K = 1$ results in standard SD.

Preserving target performance. We display the accuracy of *judge decoding* alongside the vanilla draft and target models, as well as top- K decoding in Fig. 6 for both Llama-405B and Llama-70B. We observe that *judge decoding* almost exactly preserves target performance for all

benchmarks, showing hence that up to ~ 20 tokens can be accepted on average from modern draft models without loss of quality. The simple heuristic baseline, on the other hand, is hardly able to improve over the draft model (even for $K = 5$), highlighting the difficulty of the problem we address with the learned head.

5.2 SPEED BENCHMARK

The end-to-end speed-ups achieved by SD methods improve as mainly two factors increase: (1) the number of accepted tokens and (2) the latency gap between draft and target model. Importantly, the latter is heavily dependent on whether or not orthogonal inference time optimizations like quantization, model parallelism and graph/kernel optimization techniques (like torch.compile and TensorRT) are applied. Unfortunately, prior works on SD have almost exclusively relied on the user-friendly – but un-optimized – library HuggingFace (Wolf et al., 2020) to implement their methods. Yet, as rightfully pointed out by (Wertheimer et al., 2024), speed-ups of prior SD methods reported in HuggingFace tend to shrink significantly when moving to optimized inference frameworks. For example, the acceleration of Eagle on Llama-2-7B reduces from $3\times$ to merely $1.5\times$ when using *gpt-fast* as reported in Li et al. (2024a). In fact, vanilla Llama-70B *without any speculative decoding* achieves a higher throughput in *gpt-fast* than the state-of-the-art SD method Eagle-2 does on the same model in HuggingFace (~ 45 vs ~ 33 tokens/s).

To offer a complete picture, we here provide latency benchmarks in both frameworks, HuggingFace to facilitate comparison, as well as the arguably more relevant and optimized *gpt-fast* framework (Pytorch-Team, 2023). If not stated otherwise, we run Llama-70B and Llama-405B on 2 and 8 Nvidia H100 GPUs respectively. Our results are summarized in Table 2.

Llama-3.1-70B. When drafting with Llama-8B for Llama-70B with batch size 1 in simple frameworks, the latency delta between the two models is relatively small, limiting the speed-ups of *judge decoding*. This is particularly evident when compared to SD methods that leverage small LM heads as draft modules (such as Eagle-2 Li et al. (2024b) and Medusa Cai et al. (2024)). However, in the more realistic setting of deployment within an optimized inference framework, several latency bottlenecks (like CPU instruction and memory I/O) are alleviated, resulting in a more pronounced latency delta between the target and draft models. Consequently, our method effectively capitalizes on this increased latency disparity and outperforms the current state-of-the-art by a substantial margin (see right-hand side of Table 2).

Llama-3.1-405B. Replacing the target model with the more powerful Llama-405B model significantly increases verification latency. As a result, drafting (and accepting) longer sequences becomes more crucial for the overall runtime. In such settings, *judge decoding* shines because the average number of accepted tokens is $> 3\times$ larger than prior works (left-hand side of Table 2). In particular, both Medusa and Eagle-2³ are limited to drafting ≤ 6 token at the time, by the number of heads and the draft tree depth respectively. Our 8B/405B-Judge, however, accepts close to 20 tokens at a time and thereby achieves a $9.7\times$ speed-up in HuggingFace and unprecedented 129 tokens/s in *gpt-fast*.

5.3 OUT-OF-DISTRIBUTION PERFORMANCE

Finally, we investigate to what degree our judge-decoding strategy extends to situations for which it has not been trained. To this end, we filter TokenCourt by removing all coding examples, train the verification head for Llama-405B on this reduced set and then evaluate on the coding task HumanEval. While we do observe a drop in performance from 86.6 to 80.4%, the performance is still significantly better than the draft model at 71.3%, indicating that the notion of “correctness” transfers between tasks at least to some degree. Nevertheless, our approach is not a silver bullet and to maintain target quality it is required to train the judge on data of similar nature.

³of which no 405B version exists.




Figure 6: Benchmark results. **Top:** Draft Llama-8B and target Llama-70B. **Bottom:** Draft Llama-8B and target Llama-405B. We show top- K decoding, standard SD for $M = 10$ and our judge decoding for $M = 25$ (striped). Notice that our judging method preserves accuracies very well, while top- K loses most performance.

6 CONCLUSION

In this work we have investigated the verification mechanism in speculative decoding and identified how its focus on alignment between draft and target response leads to the rejection of objectively correct continuations. To fully leverage the improved quality of “small” language models, we thus proposed an adapted verification scheme that makes use of the capability of LLMs to judge responses in a versatile way. This allows for efficiently drafting more tokens, leading to significant speedups up to $9\times$ on a range of benchmarks, achieving unprecedented speeds of 129 tokens/s for Llama-405B. In the regime of many draft tokens, “small” language models shine as drafters compared to the small modules employed in approaches like Eagle or Medusa and we believe this trend will only further accentuate in the future. Our approach however also comes with a drawback; the mathematical guarantee to maintain target quality is lost by relying on the judge. Through extensive experiments we show that a well-trained judge does not lose performance on standard benchmarks and we thus view our approach as a significant first step into this direction. On the other hand, our strategy in its current version does not present a silver bullet; novel tasks require the careful annotation of similar data to maintain quality, otherwise performance is lost. The small amount of data required in our setup is nevertheless a very encouraging sign. Future work can hopefully build upon our contributions, further improving our judge decoding strategy to enable more speedups.

REFERENCES

Marah Abdin, Jyoti Aneja, Hany Awadalla, Ahmed Awadallah, Ammar Ahmad Awan, Nguyen Bach, Amit Bahree, Arash Bakhtiari, Jianmin Bao, Harkirat Behl, Alon Benhaim, Misha Bilenko, Johan Bjorck, Sébastien Bubeck, Martin Cai, Qin Cai, Vishrav Chaudhary, Dong Chen, Dongdong Chen, Weizhu Chen, Yen-Chun Chen, Yi-Ling Chen, Hao Cheng, Parul Chopra, Xiyang Dai, Matthew Dixon, Ronen Eldan, Victor Fragoso, Jianfeng Gao, Mei Gao, Min Gao, Amit Garg, Allie Del Giorno, Abhishek Goswami, Suriya Gunasekar, Emman Haider, Junheng Hao, Russell J. Hewett, Wenxiang Hu, Jamie Huynh, Dan Iter, Sam Ade Jacobs, Mojan Javaheripi, Xin Jin, Nikos Karampatziakis, Piero Kauffmann, Mahoud Khademi, Dongwoo Kim, Young Jin Kim, Lev Kurilenko, James R. Lee, Yin Tat Lee, Yuanzhi Li, Yunsheng Li, Chen Liang, Lars Liden, Xihui Lin, Zeqi Lin, Ce Liu, Liyuan Liu, Mengchen Liu, Weishung Liu, Xiaodong Liu, Chong Luo, Piyush Madan, Ali Mahmoudzadeh, David Majercak, Matt Mazzola, Caio César Teodoro Mendes, Arindam Mitra, Hardik Modi, Anh Nguyen, Brandon Norick, Barun Patra, Daniel Perez-Becker, Thomas Portet, Reid Pryzant, Heyang Qin, Marko Radmilac, Liliang Ren, Gustavo de Rosa, Corby Rosset, Sambudha Roy, Olatunji Ruwase, Olli Saarikivi, Amin Saied, Adil Salim, Michael Santacrose, Shital Shah, Ning Shang, Hiteshi Sharma, Yelong Shen, Swadheen Shukla, Xia Song, Masahiro Tanaka, Andrea Tupini, Praneetha Vaddamanu, Chunyu Wang, Guanhua Wang, Lijuan Wang, Shuohang Wang, Xin Wang, Yu Wang, Rachel Ward, Wen Wen, Philipp Witte, Haiping Wu, Xiaoxia Wu, Michael Wyatt, Bin Xiao, Can Xu, Jiahang Xu, Weijian Xu, Ji-

- long Xue, Sonali Yadav, Fan Yang, Jianwei Yang, Yifan Yang, Ziyi Yang, Donghan Yu, Lu Yuan, Chenruidong Zhang, Cyril Zhang, Jianwen Zhang, Li Lina Zhang, Yi Zhang, Yue Zhang, Yunan Zhang, and Xiren Zhou. Phi-3 technical report: A highly capable language model locally on your phone, 2024. URL <https://arxiv.org/abs/2404.14219>.
- Zachary Ankner, Rishab Parthasarathy, Aniruddha Nrusimha, Christopher Rinard, Jonathan Ragan-Kelley, and William Brandon. Hydra: Sequentially-dependent draft heads for medusa decoding, 2024. URL <https://arxiv.org/abs/2402.05109>.
- Gregor Bachmann and Vaishnavh Nagarajan. The pitfalls of next-token prediction. In *Forty-first International Conference on Machine Learning*, 2024. URL <https://openreview.net/forum?id=76zq8Wkl6Z>.
- Nikhil Bhendawade, Irina Belousova, Qichen Fu, Henry Mason, Mohammad Rastegari, and Mahyar Najibi. Speculative streaming: Fast llm inference without auxiliary models, 2024. URL <https://arxiv.org/abs/2402.11131>.
- Collin Burns, Haotian Ye, Dan Klein, and Jacob Steinhardt. Discovering latent knowledge in language models without supervision. In *The Eleventh International Conference on Learning Representations*, 2023. URL <https://openreview.net/forum?id=ETKGuby0hcs>.
- Tianle Cai, Yuhong Li, Zhengyang Geng, Hongwu Peng, Jason D. Lee, Deming Chen, and Tri Dao. Medusa: Simple llm inference acceleration framework with multiple decoding heads. *arXiv preprint arXiv: 2401.10774*, 2024.
- Charlie Chen, Sebastian Borgeaud, Geoffrey Irving, Jean-Baptiste Lespiau, Laurent Sifre, and John Jumper. Accelerating large language model decoding with speculative sampling, 2023. URL <https://arxiv.org/abs/2302.01318>.
- Mark Chen, Jerry Tworek, Heewoo Jun, Qiming Yuan, Henrique Ponde de Oliveira Pinto, Jared Kaplan, Harri Edwards, Yuri Burda, Nicholas Joseph, Greg Brockman, Alex Ray, Raul Puri, Gretchen Krueger, Michael Petrov, Heidy Khlaaf, Girish Sastry, Pamela Mishkin, Brooke Chan, Scott Gray, Nick Ryder, Mikhail Pavlov, Alethea Power, Lukasz Kaiser, Mohammad Bavarian, Clemens Winter, Philippe Tillet, Felipe Petroski Such, Dave Cummings, Matthias Plappert, Fotios Chantzis, Elizabeth Barnes, Ariel Herbert-Voss, William Hebgen Guss, Alex Nichol, Alex Paino, Nikolas Tezak, Jie Tang, Igor Babuschkin, Suchir Balaji, Shantanu Jain, William Saunders, Christopher Hesse, Andrew N. Carr, Jan Leike, Josh Achiam, Vedant Misra, Evan Morikawa, Alec Radford, Matthew Knight, Miles Brundage, Mira Murati, Katie Mayer, Peter Welinder, Bob McGrew, Dario Amodei, Sam McCandlish, Ilya Sutskever, and Wojciech Zaremba. Evaluating large language models trained on code, 2021. URL <https://arxiv.org/abs/2107.03374>.
- Zhuoming Chen, Avner May, Ruslan Svirschevski, Yuhsun Huang, Max Ryabinin, Zhihao Jia, and Beidi Chen. Sequoia: Scalable, robust, and hardware-aware speculative decoding, 2024. URL <https://arxiv.org/abs/2402.12374>.
- Jacob K Christopher, Brian R Bartoldson, Bhavya Kailkhura, and Ferdinando Fioretto. Speculative diffusion decoding: Accelerating language generation through diffusion, 2024. URL <https://arxiv.org/abs/2408.05636>.
- Peter Clark, Isaac Cowhey, Oren Etzioni, Tushar Khot, Ashish Sabharwal, Carissa Schoenick, and Oyvind Tafjord. Think you have solved question answering? try arc, the ai2 reasoning challenge. *ArXiv*, abs/1803.05457, 2018. URL <https://api.semanticscholar.org/CorpusID:3922816>.
- Karl Cobbe, Vineet Kosaraju, Mohammad Bavarian, Mark Chen, Heewoo Jun, Lukasz Kaiser, Matthias Plappert, Jerry Tworek, Jacob Hilton, Reiichiro Nakano, Christopher Hesse, and John Schulman. Training verifiers to solve math word problems, 2021. URL <https://arxiv.org/abs/2110.14168>.
- Cunxiao Du, Jing Jiang, Xu Yuanchen, Jiawei Wu, Sicheng Yu, Yongqi Li, Shenggui Li, Kai Xu, Liqiang Nie, Zhaopeng Tu, and Yang You. Glide with a caPE: A low-hassle method to accelerate speculative decoding. In *Forty-first International Conference on Machine Learning*, 2024. URL <https://openreview.net/forum?id=mk8oRhox2l>.

Abhimanyu Dubey, Abhinav Jauhri, Abhinav Pandey, Abhishek Kadian, Ahmad Al-Dahle, Aiesha Letman, Akhil Mathur, Alan Schelten, Amy Yang, Angela Fan, Anirudh Goyal, Anthony Hartshorn, Aobo Yang, Archi Mitra, Archie Sravankumar, Artem Korenev, Arthur Hinsvark, Arun Rao, Aston Zhang, Aurelien Rodriguez, Austen Gregerson, Ava Spataru, Baptiste Roziere, Bethany Biron, Binh Tang, Bobbie Chern, Charlotte Caucheteux, Chaya Nayak, Chloe Bi, Chris Marra, Chris McConnell, Christian Keller, Christophe Touret, Chunyang Wu, Corinne Wong, Cristian Canton Ferrer, Cyrus Nikolaidis, Damien Allonsius, Daniel Song, Danielle Pintz, Danny Livshits, David Esiobu, Dhruv Choudhary, Dhruv Mahajan, Diego Garcia-Olano, Diego Perino, Dieuwke Hupkes, Egor Lakomkin, Ehab AlBadawy, Elina Lobanova, Emily Dinan, Eric Michael Smith, Filip Radenovic, Frank Zhang, Gabriel Synnaeve, Gabrielle Lee, Georgia Lewis Anderson, Graeme Nail, Gregoire Mialon, Guan Pang, Guillem Cucurell, Hailey Nguyen, Hannah Korevaar, Hu Xu, Hugo Touvron, Iliyan Zarov, Imanol Arrieta Ibarra, Isabel Kloumann, Ishan Misra, Ivan Evtimov, Jade Copet, Jaewon Lee, Jan Geffert, Jana Vranes, Jason Park, Jay Mahadeokar, Jeet Shah, Jelmer van der Linde, Jennifer Billock, Jenny Hong, Jenya Lee, Jeremy Fu, Jianfeng Chi, Jianyu Huang, Jiawen Liu, Jie Wang, Jiecao Yu, Joanna Bitton, Joe Spisak, Jongsoo Park, Joseph Rocca, Joshua Johnstun, Joshua Saxe, Junteng Jia, Kalyan Vasuden Alwala, Kartikeya Upasani, Kate Plawiak, Ke Li, Kenneth Heafield, Kevin Stone, Khalid El-Arini, Krithika Iyer, Kshitiz Malik, Kuenley Chiu, Kunal Bhalla, Lauren Rantala-Yeary, Laurens van der Maaten, Lawrence Chen, Liang Tan, Liz Jenkins, Louis Martin, Lovish Madaan, Lubo Malo, Lukas Blecher, Lukas Landzaat, Luke de Oliveira, Madeline Muzzi, Mahesh Pasupuleti, Manan Singh, Manohar Paluri, Marcin Kardas, Mathew Oldham, Mathieu Rita, Maya Pavlova, Melanie Kambadur, Mike Lewis, Min Si, Mitesh Kumar Singh, Mona Hassan, Naman Goyal, Narjes Torabi, Nikolay Bashlykov, Nikolay Bogoychev, Niladri Chatterji, Olivier Duchenne, Onur Çelebi, Patrick Alrassy, Pengchuan Zhang, Pengwei Li, Petar Vasic, Peter Weng, Prajjwal Bhargava, Pratik Dubal, Praveen Krishnan, Punit Singh Koura, Puxin Xu, Qing He, Qingxiao Dong, Ragavan Srinivasan, Raj Ganapathy, Ramon Calderer, Ricardo Silveira Cabral, Robert Stojnic, Roberta Raileanu, Rohit Girdhar, Rohit Patel, Romain Sauvestre, Ronnie Polidoro, Roshan Sumbaly, Ross Taylor, Ruan Silva, Rui Hou, Rui Wang, Saghar Hosseini, Sahana Chennabasappa, Sanjay Singh, Sean Bell, Seohyun Sonia Kim, Sergey Edunov, Shaoliang Nie, Sharan Narang, Sharath Raparthy, Sheng Shen, Shengye Wan, Shruti Bhosale, Shun Zhang, Simon Vandenhende, Soumya Batra, Spencer Whitman, Sten Sootla, Stephane Collot, Suchin Gururangan, Sydney Borodinsky, Tamar Herman, Tara Fowler, Tarek Sheasha, Thomas Georgiou, Thomas Scialom, Tobias Speckbacher, Todor Mihaylov, Tong Xiao, Ujjwal Karn, Vedanuj Goswami, Vibhor Gupta, Vignesh Ramanathan, Viktor Kerkez, Vincent Gonguet, Virginie Do, Vish Vogeti, Vladan Petrovic, Weiwei Chu, Wenhan Xiong, Wenyin Fu, Whitney Meers, Xavier Martinet, Xiaodong Wang, Xiaoqing Ellen Tan, Xinfeng Xie, Xuchao Jia, Xuwei Wang, Yaelle Goldschlag, Yashesh Gaur, Yasmine Babaei, Yi Wen, Yiwen Song, Yuchen Zhang, Yue Li, Yuning Mao, Zacharie DelPierre Coudert, Zheng Yan, Zhengxing Chen, Zoe Papakipos, Aaditya Singh, Aaron Grattafiori, Abha Jain, Adam Kelsey, Adam Shajnfeld, Adithya Gangidi, Adolfo Victoria, Ahuva Goldstand, Ajay Menon, Ajay Sharma, Alex Boesenberg, Alex Vaughan, Alexei Baevski, Allie Feinstein, Amanda Kallet, Amit Sangani, Anam Yunus, Andrei Lupu, Andres Alvarado, Andrew Caples, Andrew Gu, Andrew Ho, Andrew Poulton, Andrew Ryan, Ankit Ramchandani, Annie Franco, Aparajita Saraf, Arkabandhu Chowdhury, Ashley Gabriel, Ashwin Bharambe, Assaf Eisenman, Azadeh Yazdan, Beau James, Ben Maurer, Benjamin Leonhardi, Bernie Huang, Beth Loyd, Beto De Paola, Bhargavi Paranjape, Bing Liu, Bo Wu, Boyu Ni, Braden Hancock, Bram Wasti, Brandon Spence, Brani Stojkovic, Brian Gamido, Britt Montalvo, Carl Parker, Carly Burton, Catalina Mejia, Changan Wang, Changkyu Kim, Chao Zhou, Chester Hu, Ching-Hsiang Chu, Chris Cai, Chris Tindal, Christoph Feichtenhofer, Damon Civin, Dana Beaty, Daniel Kreymer, Daniel Li, Danny Wyatt, David Adkins, David Xu, Davide Testuggine, Delia David, Devi Parikh, Diana Liskovich, Didem Foss, Dingkan Wang, Duc Le, Dustin Holland, Edward Dowling, Eissa Jamil, Elaine Montgomery, Eleonora Presani, Emily Hahn, Emily Wood, Erik Brinkman, Esteban Arcaute, Evan Dunbar, Evan Smothers, Fei Sun, Felix Kreuk, Feng Tian, Firat Ozgenel, Francesco Caggioni, Francisco Guzmán, Frank Kanayet, Frank Seide, Gabriela Medina Florez, Gabriella Schwarz, Gada Badeer, Georgia Swee, Gil Halpern, Govind Thattai, Grant Herman, Grigory Sizov, Guangyi, Zhang, Guna Lakshminarayanan, Hamid Shojanazeri, Han Zou, Hannah Wang, Hanwen Zha, Haroun Habeeb, Harrison Rudolph, Helen Suk, Henry Aspegren, Hunter Goldman, Ibrahim Damlaj, Igor Molybog, Igor Tufanov, Irina-Elena Veliche, Itai Gat, Jake Weissman, James Geboski, James Kohli, Japhet Asher, Jean-Baptiste Gaya, Jeff Marcus, Jeff Tang, Jennifer Chan, Jenny Zhen, Jeremy Reizenstein, Jeremy Teboul, Jessica Zhong, Jian Jin, Jingyi Yang, Joe

- Cummings, Jon Carvill, Jon Shepard, Jonathan McPhie, Jonathan Torres, Josh Ginsburg, Junjie Wang, Kai Wu, Kam Hou U, Karan Saxena, Karthik Prasad, Kartikay Khandelwal, Katayoun Zand, Kathy Matosich, Kaushik Veeraraghavan, Kelly Michelena, Keqian Li, Kun Huang, Kunal Chawla, Kushal Lakhotia, Kyle Huang, Lailin Chen, Lakshya Garg, Lavender A, Leandro Silva, Lee Bell, Lei Zhang, Liangpeng Guo, Licheng Yu, Liron Moshkovich, Luca Wehrstedt, Madian Khabisa, Manav Avalani, Manish Bhatt, Maria Tsimpoukelli, Martynas Mankus, Matan Hasson, Matthew Lennie, Matthias Reso, Maxim Groshev, Maxim Naumov, Maya Lathi, Meghan Keenally, Michael L. Seltzer, Michal Valko, Michelle Restrepo, Mihir Patel, Mik Vyatskov, Mikayel Samvelyan, Mike Clark, Mike Macey, Mike Wang, Miquel Jubert Hermoso, Mo Metanat, Mohammad Rastegari, Munish Bansal, Nandhini Santhanam, Natascha Parks, Natasha White, Navyata Bawa, Nayan Singhal, Nick Egebo, Nicolas Usunier, Nikolay Pavlovich Laptev, Ning Dong, Ning Zhang, Norman Cheng, Oleg Chernoguz, Olivia Hart, Omkar Salpekar, Ozlem Kalinli, Parkin Kent, Parth Parekh, Paul Saab, Pavan Balaji, Pedro Rittner, Philip Bontrager, Pierre Roux, Piotr Dollar, Polina Zvyagina, Prashant Ratanchandani, Pritish Yuvraj, Qian Liang, Rachad Alao, Rachel Rodriguez, Rafi Ayub, Raghotham Murthy, Raghu Nayani, Rahul Mitra, Raymond Li, Rebekkah Hogan, Robin Battey, Rocky Wang, Rohan Maheswari, Russ Howes, Ruty Rinott, Sai Jayesh Bondu, Samyak Datta, Sara Chugh, Sara Hunt, Sargun Dhillon, Sasha Sidorov, Satadru Pan, Saurabh Verma, Seiji Yamamoto, Sharadh Ramaswamy, Shaun Lindsay, Shaun Lindsay, Sheng Feng, Shenghao Lin, Shengxin Cindy Zha, Shiva Shankar, Shuqiang Zhang, Shuqiang Zhang, Sinong Wang, Sneha Agarwal, Soji Sajuyigbe, Soumith Chintala, Stephanie Max, Stephen Chen, Steve Kehoe, Steve Satterfield, Sudarshan Govindaprasad, Sumit Gupta, Sungmin Cho, Sunny Virk, Suraj Subramanian, Sy Choudhury, Sydney Goldman, Tal Remez, Tamar Glaser, Tamara Best, Thilo Kohler, Thomas Robinson, Tianhe Li, Tianjun Zhang, Tim Matthews, Timothy Chou, Tzook Shaked, Varun Vontimitta, Victoria Ajayi, Victoria Montanez, Vijai Mohan, Vinay Satish Kumar, Vishal Mangla, Vitor Albiero, Vlad Ionescu, Vlad Poenaru, Vlad Tiberiu Mihailescu, Vladimir Ivanov, Wei Li, Wenchen Wang, Wenwen Jiang, Wes Bouaziz, Will Constable, Xiaocheng Tang, Xiaofang Wang, Xiaojuan Wu, Xiaolan Wang, Xide Xia, Xilun Wu, Xinbo Gao, Yanjun Chen, Ye Hu, Ye Jia, Ye Qi, Yenda Li, Yilin Zhang, Ying Zhang, Yossi Adi, Youngjin Nam, Yu, Wang, Yuchen Hao, Yundi Qian, Yuzi He, Zach Rait, Zachary DeVito, Zef Rosnbrick, Zhaoduo Wen, Zhenyu Yang, and Zhiwei Zhao. The llama 3 herd of models, 2024. URL <https://arxiv.org/abs/2407.21783>.
- Mostafa Elhoushi, Akshat Shrivastava, Diana Liskovich, Basil Hosmer, Bram Wasti, Liangzhen Lai, Anas Mahmoud, Bilge Acun, Saurabh Agarwal, Ahmed Roman, Ahmed Aly, Beidi Chen, and Carole-Jean Wu. LayerSkip: Enabling early exit inference and self-speculative decoding. In Lun-Wei Ku, Andre Martins, and Vivek Srikumar (eds.), *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 12622–12642, Bangkok, Thailand, August 2024. Association for Computational Linguistics. URL <https://aclanthology.org/2024.acl-long.681>.
- Yichao Fu, Peter Bailis, Ion Stoica, and Hao Zhang. Break the sequential dependency of LLM inference using lookahead decoding. In *Forty-first International Conference on Machine Learning*, 2024. URL <https://openreview.net/forum?id=eDjvSF0kXw>.
- Fabian Gloeckle, Badr Youbi Idrissi, Baptiste Roziere, David Lopez-Paz, and Gabriel Synnaeve. Better & faster large language models via multi-token prediction. In *Forty-first International Conference on Machine Learning*, 2024. URL <https://openreview.net/forum?id=pEWAcEjiU2>.
- Albert Gu and Tri Dao. Mamba: Linear-time sequence modeling with selective state spaces, 2024. URL <https://arxiv.org/abs/2312.00752>.
- Wes Gurnee and Max Tegmark. Language models represent space and time. *arXiv preprint arXiv:2310.02207*, 2023.
- Dan Hendrycks, Collin Burns, Steven Basart, Andy Zou, Mantas Mazeika, Dawn Song, and Jacob Steinhardt. Measuring massive multitask language understanding. In *International Conference on Learning Representations*, 2021. URL <https://openreview.net/forum?id=d7KBjmI3GmQ>.

- Jordan Hoffmann, Sebastian Borgeaud, Arthur Mensch, Elena Buchatskaya, Trevor Cai, Eliza Rutherford, Diego de Las Casas, Lisa Anne Hendricks, Johannes Welbl, Aidan Clark, Tom Hennigan, Eric Noland, Katie Millican, George van den Driessche, Bogdan Damoc, Aurelia Guy, Simon Osindero, Karen Simonyan, Erich Elsen, Jack W. Rae, Oriol Vinyals, and Laurent Sifre. Training compute-optimal large language models, 2022. URL <https://arxiv.org/abs/2203.15556>.
- Kaixuan Huang, Xudong Guo, and Mengdi Wang. Specdec++: Boosting speculative decoding via adaptive candidate lengths, 2024. URL <https://arxiv.org/abs/2405.19715>.
- Andrei Ivanov, Nikoli Dryden, Tal Ben-Nun, Shigang Li, and Torsten Hoefler. Data movement is all you need: A case study on optimizing transformers. *Proceedings of Machine Learning and Systems*, 3:711–732, 2021.
- Jared Kaplan, Sam McCandlish, Tom Henighan, Tom B. Brown, Benjamin Chess, Rewon Child, Scott Gray, Alec Radford, Jeffrey Wu, and Dario Amodei. Scaling laws for neural language models, 2020. URL <https://arxiv.org/abs/2001.08361>.
- Sehoon Kim, Karttikeya Mangalam, Suhong Moon, Jitendra Malik, Michael W. Mahoney, Amir Gholami, and Kurt Keutzer. Speculative decoding with big little decoder. In *Thirty-seventh Conference on Neural Information Processing Systems*, 2023. URL <https://openreview.net/forum?id=EfMyf9MC3t>.
- Yaniv Leviathan, Matan Kalman, and Yossi Matias. Fast inference from transformers via speculative decoding. In *Proceedings of the 40th International Conference on Machine Learning*, ICML’23. JMLR.org, 2023.
- Yuhui Li, Fangyun Wei, Chao Zhang, and Hongyang Zhang. Eagle: Speculative sampling requires rethinking feature uncertainty. In *International Conference on Machine Learning*, 2024a.
- Yuhui Li, Fangyun Wei, Chao Zhang, and Hongyang Zhang. Eagle-2: Faster inference of language models with dynamic draft trees, 2024b. URL <https://arxiv.org/abs/2406.16858>.
- Fangcheng Liu, Yehui Tang, Zhenhua Liu, Yunsheng Ni, Kai Han, and Yunhe Wang. Kangaroo: Lossless self-speculative decoding via double early exiting, 2024a. URL <https://arxiv.org/abs/2404.18911>.
- Jiahao Liu, Qifan Wang, Jingang Wang, and Xunliang Cai. Speculative decoding via early-exiting for faster LLM inference with Thompson sampling control mechanism. In Lun-Wei Ku, Andre Martins, and Vivek Srikumar (eds.), *Findings of the Association for Computational Linguistics ACL 2024*, pp. 3027–3043, Bangkok, Thailand and virtual meeting, August 2024b. Association for Computational Linguistics. URL <https://aclanthology.org/2024.findings-acl.179>.
- Tianyu Liu, Yun Li, Qitan Lv, Kai Liu, Jianchen Zhu, and Winston Hu. Parallel speculative decoding with adaptive draft length, 2024c. URL <https://arxiv.org/abs/2408.11850>.
- Xiaoxuan Liu, Lanxiang Hu, Peter Bailis, Ion Stoica, Zhijie Deng, Alvin Cheung, and Hao Zhang. Online speculative decoding. *arXiv preprint arXiv:2310.07177*, 2023.
- Ilya Loshchilov and Frank Hutter. Decoupled weight decay regularization. In *International Conference on Learning Representations*, 2019. URL <https://openreview.net/forum?id=Bkg6RiCqY7>.
- Samuel Marks and Max Tegmark. The geometry of truth: Emergent linear structure in large language model representations of true/false datasets. In *First Conference on Language Modeling*, 2024. URL <https://openreview.net/forum?id=aa jyHYjjsk>.
- Xupeng Miao, Gabriele Oliaro, Zhihao Zhang, Xinhao Cheng, Zeyu Wang, Zhengxin Zhang, Rae Ying Yee Wong, Alan Zhu, Lijie Yang, Xiaoxiang Shi, Chunan Shi, Zhuoming Chen, Daiyaan Arfeen, Reyna Abhyankar, and Zhihao Jia. Specinfer: Accelerating large language model serving with tree-based speculative inference and verification. In *Proceedings of the 29th ACM*

International Conference on Architectural Support for Programming Languages and Operating Systems, Volume 3, ASPLOS '24, pp. 932–949, New York, NY, USA, 2024. Association for Computing Machinery. ISBN 9798400703867. doi: 10.1145/3620666.3651335. URL <https://doi.org/10.1145/3620666.3651335>.

Giovanni Monea, Armand Joulin, and Edouard Grave. Pass: Parallel speculative sampling, 2023. URL <https://arxiv.org/abs/2311.13581>.

Nvidia. Llama 3.1 performance with medusa. <https://shorturl.at/IkXRC>, 2024. Accessed: 2024-10-01.

OpenAI, Josh Achiam, Steven Adler, Sandhini Agarwal, Lama Ahmad, Ilge Akkaya, Florencia Leoni Aleman, Diogo Almeida, Janko Altschmidt, Sam Altman, Shyamal Anadkat, Red Avila, Igor Babuschkin, Suchir Balaji, Valerie Balcom, Paul Baltescu, Haiming Bao, Mohammad Bavarian, Jeff Belgum, Irwan Bello, Jake Berdine, Gabriel Bernadett-Shapiro, Christopher Berner, Lenny Bogdonoff, Oleg Boiko, Madelaine Boyd, Anna-Luisa Brakman, Greg Brockman, Tim Brooks, Miles Brundage, Kevin Button, Trevor Cai, Rosie Campbell, Andrew Cann, Brittany Carey, Chelsea Carlson, Rory Carmichael, Brooke Chan, Che Chang, Fotis Chantzis, Derek Chen, Sully Chen, Ruby Chen, Jason Chen, Mark Chen, Ben Chess, Chester Cho, Casey Chu, Hyung Won Chung, Dave Cummings, Jeremiah Currier, Yunxing Dai, Cory Decareaux, Thomas Degry, Noah Deutsch, Damien Deville, Arka Dhar, David Dohan, Steve Dowling, Sheila Dunning, Adrien Ecoffet, Atty Eleti, Tyna Eloundou, David Farhi, Liam Fedus, Niko Felix, Simón Posada Fishman, Juston Forte, Isabella Fulford, Leo Gao, Elie Georges, Christian Gibson, Vik Goel, Tarun Gogineni, Gabriel Goh, Rapha Gontijo-Lopes, Jonathan Gordon, Morgan Grafstein, Scott Gray, Ryan Greene, Joshua Gross, Shixiang Shane Gu, Yufei Guo, Chris Hallacy, Jesse Han, Jeff Harris, Yuchen He, Mike Heaton, Johannes Heidecke, Chris Hesse, Alan Hickey, Wade Hickey, Peter Hoeschele, Brandon Houghton, Kenny Hsu, Shengli Hu, Xin Hu, Joost Huizinga, Shantanu Jain, Shawn Jain, Joanne Jang, Angela Jiang, Roger Jiang, Haozhun Jin, Denny Jin, Shino Jomoto, Billie Jonn, Heewoo Jun, Tomer Kaftan, Łukasz Kaiser, Ali Kamali, Ingmar Kanitscheider, Nitish Shirish Keskar, Tabarak Khan, Logan Kilpatrick, Jong Wook Kim, Christina Kim, Yongjik Kim, Jan Hendrik Kirchner, Jamie Kiros, Matt Knight, Daniel Kokotajlo, Łukasz Kondraciuk, Andrew Kondrich, Aris Konstantinidis, Kyle Kopic, Gretchen Krueger, Vishal Kuo, Michael Lampe, Ikai Lan, Teddy Lee, Jan Leike, Jade Leung, Daniel Levy, Chak Ming Li, Rachel Lim, Molly Lin, Stephanie Lin, Mateusz Litwin, Theresa Lopez, Ryan Lowe, Patricia Lue, Anna Makanju, Kim Malfacini, Sam Manning, Todor Markov, Yaniv Markovski, Bianca Martin, Katie Mayer, Andrew Mayne, Bob McGrew, Scott Mayer McKinney, Christine McLeavey, Paul McMillan, Jake McNeil, David Medina, Aalok Mehta, Jacob Menick, Luke Metz, Andrey Mishchenko, Pamela Mishkin, Vinnie Monaco, Evan Morikawa, Daniel Mossing, Tong Mu, Mira Murati, Oleg Murk, David Mély, Ashvin Nair, Reiichiro Nakano, Rameesh Nayak, Arvind Neelakantan, Richard Ngo, Hyeonwoo Noh, Long Ouyang, Cullen O’Keefe, Jakub Pachocki, Alex Paino, Joe Palermo, Ashley Pantuliano, Giambattista Parascandolo, Joel Parish, Emy Parparita, Alex Passos, Mikhail Pavlov, Andrew Peng, Adam Perelman, Filipe de Avila Belbute Peres, Michael Petrov, Henrique Ponde de Oliveira Pinto, Michael, Pokorny, Michelle Pokrass, Vitchyr H. Pong, Tolly Powell, Alethea Power, Boris Power, Elizabeth Proehl, Raul Puri, Alec Radford, Jack Rae, Aditya Ramesh, Cameron Raymond, Francis Real, Kendra Rimbach, Carl Ross, Bob Rotsted, Henri Roussez, Nick Ryder, Mario Saltarelli, Ted Sanders, Shibani Santurkar, Girish Sastry, Heather Schmidt, David Schnurr, John Schulman, Daniel Selsam, Kyla Sheppard, Toki Sherbakov, Jessica Shieh, Sarah Shoker, Pranav Shyam, Szymon Sidor, Eric Sigler, Maddie Simens, Jordan Sitkin, Katarina Slama, Ian Sohl, Benjamin Sokolowsky, Yang Song, Natalie Staudacher, Felipe Petroski Such, Natalie Summers, Ilya Sutskever, Jie Tang, Nikolas Tezak, Madeleine B. Thompson, Phil Tillet, Amin Tootoonchian, Elizabeth Tseng, Preston Tuggle, Nick Turley, Jerry Tworek, Juan Felipe Cerón Uribe, Andrea Vallone, Arun Vijayvergiya, Chelsea Voss, Carroll Wainwright, Justin Jay Wang, Alvin Wang, Ben Wang, Jonathan Ward, Jason Wei, CJ Weinmann, Akila Welihinda, Peter Welinder, Jiayi Weng, Lilian Weng, Matt Wiethoff, Dave Willner, Clemens Winter, Samuel Wolrich, Hannah Wong, Lauren Workman, Sherwin Wu, Jeff Wu, Michael Wu, Kai Xiao, Tao Xu, Sarah Yoo, Kevin Yu, Qiming Yuan, Wojciech Zaremba, Rowan Zellers, Chong Zhang, Marvin Zhang, Shengjia Zhao, Tianhao Zheng, Juntang Zhuang, William Zhuk, and Barret Zoph. Gpt-4 technical report, 2024.

- Reiner Pope, Sholto Douglas, Aakanksha Chowdhery, Jacob Devlin, James Bradbury, Jonathan Heek, Kefan Xiao, Shivani Agrawal, and Jeff Dean. Efficiently scaling transformer inference. *Proceedings of Machine Learning and Systems*, 5:606–624, 2023.
- Pytorch-Team. gpt-fast. <https://github.com/pytorch-labs/gpt-fast>, 2023.
- Alec Radford, Jeffrey Wu, Rewon Child, David Luan, Dario Amodei, Ilya Sutskever, et al. Language models are unsupervised multitask learners. *OpenAI blog*, 1(8):9, 2019.
- Aishwarya P S, Pranav Ajit Nair, Yashas Samaga B L, Toby James Boyd, Sanjiv Kumar, Prateek Jain, and Praneeth Netrapalli. Tandem transformers for inference efficient LLMs. In Ruslan Salakhutdinov, Zico Kolter, Katherine Heller, Adrian Weller, Nuria Oliver, Jonathan Scarlett, and Felix Berkenkamp (eds.), *Proceedings of the 41st International Conference on Machine Learning*, volume 235 of *Proceedings of Machine Learning Research*, pp. 42906–42917. PMLR, 21–27 Jul 2024. URL <https://proceedings.mlr.press/v235/s24a.html>.
- Andrea Santilli, Silvio Severino, Emilian Postolache, Valentino Maiorca, Michele Mancusi, Riccardo Marin, and Emanuele Rodola. Accelerating transformer inference for translation via parallel decoding. In Anna Rogers, Jordan Boyd-Graber, and Naoaki Okazaki (eds.), *Proceedings of the 61st Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 12336–12355, Toronto, Canada, July 2023. Association for Computational Linguistics. doi: 10.18653/v1/2023.acl-long.689. URL <https://aclanthology.org/2023.acl-long.689>.
- Thijs Scheepers. Improving the compositionality of word embeddings. Master’s thesis, Universiteit van Amsterdam, Science Park 904, Amsterdam, Netherlands, 11 2017.
- Tal Schuster, Adam Fisch, Jai Gupta, Mostafa Dehghani, Dara Bahri, Vinh Q. Tran, Yi Tay, and Donald Metzler. Confident adaptive language modeling. In Alice H. Oh, Alekh Agarwal, Danielle Belgrave, and Kyunghyun Cho (eds.), *Advances in Neural Information Processing Systems*, 2022. URL <https://openreview.net/forum?id=uLYc4L3C81A>.
- Noam Shazeer. Fast transformer decoding: One write-head is all you need, 2019. URL <https://arxiv.org/abs/1911.02150>.
- Mitchell Stern, Noam M. Shazeer, and Jakob Uszkoreit. Blockwise parallel decoding for deep autoregressive models. In *Neural Information Processing Systems*, 2018. URL <https://api.semanticscholar.org/CorpusID:53208380>.
- Xin Sun, Tao Ge, Furu Wei, and Houfeng Wang. Instantaneous grammatical error correction with shallow aggressive decoding. In Chengqing Zong, Fei Xia, Wenjie Li, and Roberto Navigli (eds.), *Proceedings of the 59th Annual Meeting of the Association for Computational Linguistics and the 11th International Joint Conference on Natural Language Processing (Volume 1: Long Papers)*, pp. 5937–5947, Online, August 2021. Association for Computational Linguistics. doi: 10.18653/v1/2021.acl-long.462. URL <https://aclanthology.org/2021.acl-long.462>.
- Rohan Taori, Ishaan Gulrajani, Tianyi Zhang, Yann Dubois, Xuechen Li, Carlos Guestrin, Percy Liang, and Tatsunori B. Hashimoto. Stanford alpaca: An instruction-following llama model. https://github.com/tatsu-lab/stanford_alpaca, 2023.
- Gladys Tyen, Hassan Mansoor, Victor Cărbune, Peter Chen, and Tony Mak. LLMs cannot find reasoning errors, but can correct them given the error location, 2024. URL <https://arxiv.org/abs/2311.08516>.
- Dimitri von Rütten, Sotiris Anagnostidis, Gregor Bachmann, and Thomas Hofmann. A language model’s guide through latent space. *arXiv preprint arXiv:2402.14433*, 2024.
- Junxiong Wang, Daniele Paliotta, Avner May, Alexander M. Rush, and Tri Dao. The mamba in the llama: Distilling and accelerating hybrid models, 2024. URL <https://arxiv.org/abs/2408.15237>.
- Davis Wertheimer, Joshua Rosenkranz, Thomas Parnell, Sahil Suneja, Pavithra Ranganathan, Raghu Ganti, and Mudhakar Srivatsa. Accelerating production LLMs with combined token/embedding speculators, 2024. URL <https://arxiv.org/abs/2404.19124>.

- Thomas Wolf, Lysandre Debut, Victor Sanh, Julien Chaumond, Clement Delangue, Anthony Moi, Pierric Cistac, Tim Rault, Rémi Louf, Morgan Funtowicz, Joe Davison, Sam Shleifer, Patrick von Platen, Clara Ma, Yacine Jernite, Julien Plu, Canwen Xu, Teven Le Scao, Sylvain Gugger, Mariama Drame, Quentin Lhoest, and Alexander M. Rush. Transformers: State-of-the-art natural language processing. In *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing: System Demonstrations*, pp. 38–45, Online, October 2020. Association for Computational Linguistics. URL <https://www.aclweb.org/anthology/2020.emnlp-demos.6>.
- Heming Xia, Tao Ge, Peiyi Wang, Si-Qing Chen, Furu Wei, and Zhifang Sui. Speculative decoding: Exploiting speculative execution for accelerating seq2seq generation. In Houda Bouamor, Juan Pino, and Kalika Bali (eds.), *Findings of the Association for Computational Linguistics: EMNLP 2023*, pp. 3909–3925, Singapore, December 2023. Association for Computational Linguistics. doi: 10.18653/v1/2023.findings-emnlp.257. URL <https://aclanthology.org/2023.findings-emnlp.257>.
- Aonan Zhang, Chong Wang, Yi Wang, Xuanyu Zhang, and Yunfei Cheng. Recurrent drafter for fast speculative decoding in large language models. *arXiv preprint arXiv:2403.09919*, 2024a.
- Biao Zhang and Rico Sennrich. Root mean square layer normalization, 2019. URL <https://arxiv.org/abs/1910.07467>.
- Jun Zhang, Jue Wang, Huan Li, Lidan Shou, Ke Chen, Gang Chen, and Sharad Mehrotra. Draft& verify: Lossless large language model acceleration via self-speculative decoding. In Lun-Wei Ku, Andre Martins, and Vivek Srikumar (eds.), *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 11263–11282, Bangkok, Thailand, August 2024b. Association for Computational Linguistics. URL <https://aclanthology.org/2024.acl-long.607>.
- Lianmin Zheng, Wei-Lin Chiang, Ying Sheng, Siyuan Zhuang, Zhanghao Wu, Yonghao Zhuang, Zi Lin, Zhuohan Li, Dacheng Li, Eric Xing, Hao Zhang, Joseph E. Gonzalez, and Ion Stoica. Judging LLM-as-a-judge with MT-bench and chatbot arena. In *Thirty-seventh Conference on Neural Information Processing Systems Datasets and Benchmarks Track*, 2023. URL <https://openreview.net/forum?id=uccHPGDlao>.
- Yongchao Zhou, Kaifeng Lyu, Ankit Singh Rawat, Aditya Krishna Menon, Afshin Rostamizadeh, Sanjiv Kumar, Jean-François Kagy, and Rishabh Agarwal. Distillspec: Improving speculative decoding via knowledge distillation. In *The Twelfth International Conference on Learning Representations*, 2024. URL <https://openreview.net/forum?id=rsY6J3ZaTF>.
- Andy Zou, Long Phan, Sarah Chen, James Campbell, Phillip Guo, Richard Ren, Alexander Pan, Xuwang Yin, Mantas Mazeika, Ann-Kathrin Dombrowski, Shashwat Goel, Nathaniel Li, Michael J. Byun, Zifan Wang, Alex Troy Mallen, Steven Basart, Sanmi Koyejo, Dawn Song, Matt Fredrikson, Zico Kolter, and Dan Hendrycks. Representation engineering: A top-down approach to ai transparency. *ArXiv*, abs/2310.01405, 2023a. URL <https://api.semanticscholar.org/CorpusID:263605618>.
- Andy Zou, Long Phan, Sarah Chen, James Campbell, Phillip Guo, Richard Ren, Alexander Pan, Xuwang Yin, Mantas Mazeika, Ann-Kathrin Dombrowski, et al. Representation engineering: A top-down approach to ai transparency. *arXiv preprint arXiv:2310.01405*, 2023b.

A LIMITATIONS

Here we list limitations of our approach to the best of our knowledge:

- An obvious limitation is the loss of the mathematical guarantee to match target quality. While we perform extensive experiments and show that quality is maintained, there is no certainty for novel tasks.
- The draft model needs to be of high-quality, otherwise our approach naturally does not prove beneficial and too many tokens end up being rejected. Self-speculation and small drafters in the spirit of Medusa or Eagle are thus not ideal since their generations quickly deteriorate when drafting too far into the future.
- Similarly, the target model needs to be of sufficient size to be able to provide accurate judgments. Speedups for smaller models such as Llama-8B are hence tougher to achieve.
- As highlighted in the main text, new tasks do require careful annotation of data to maintain quality. The required amount on the other hand turns out to be small in our case.
- If the draft model has safety issues, the target model could potentially accept safety-critical tokens through the judge, even if the target would otherwise never produce such outputs. We have not observed such issues in our experiments but have also not thoroughly investigated this problem as it is beyond the scope of our work.

B ARCHITECTURAL AND EXPERIMENTAL DETAILS

B.1 LINEAR HEAD

We train our linear heads using the AdamW optimizer (Loshchilov & Hutter, 2019) with learning rate $\eta = 0.0001$, weight decay 0.1 and batch size 128. Note that for Llama-405B, our linear head has dimension 16,384 while for Llama-70B it has 8,192. Our linear head can be viewed as an additional entry in the vocabulary \mathcal{V} , reducing its inference overhead thus to practically zero.

B.2 JUDGE MASKING

We describe the the combination of standard and judge mask in more detail in Fig. 7. In the following

Judge mask	Harry	Potter	is	a	series	of	fantasy	thrillers	written
Standard mask	Harry	Potter	is	a	series	of	fantasy	thrillers	written
Final mask	Harry	Potter	is	a	series	of	fantasy	thrillers	written

Figure 7: Illustration of mask creation in judge decoding. The decision mask resulting from the judge is combined with the standard mask from SD. Once both methods disagree, subsequent tokens get rejected automatically as usual, even if they were individually accepted.

we will describe in more detail why it is natural to combine the masks of judge decoding and standard speculative decoding. We illustrate this in Fig. 8. There are (rare) scenarios where a candidate token is rejected by judge decoding (such as "that" in the example) and the "corrected" token according to the target model happens to be the same token ("that" in blue). This situation could repeat; the very next token could again be rejected by JD and accepted by the target (token "guy" in the example). Standard SD on the other hand would accept all those tokens as the draft exactly matches the target suggestion. We eventually end up accepting the exact same tokens (in case of rejection we have to trust the target), so it makes sense to combine the masks and use the SD mask to not end up repeating the steps (in the example we combine steps 1., 2., 3. into one step on the right). In our experiments we do not observe this situation too often, but it can occasionally occur as the judge was tuned to rather reject than accept when in doubt to avoid false positives.




Figure 8: Illustration how combining the masks of judge decoding (JD) and standard speculative decoding (SD) results in the same reply but in less steps in the (rare) case that JD rejects a token that is actually the target token.

B.3 HARDWARE

We run all of our experiments on a single node of H100-SXM5 GPUs. For Llama-405B we use 8 GPUs and 8-bit quantization to ensure that the model fits on a single node. For Llama-70B, we use again 8-bit quantization but only 2 GPUs.

B.4 INDIVIDUAL SPEEDUPS PER BENCHMARK

In Table 2 we provide individual speedup numbers in HuggingFace. As observed in prior works, HumanEval enjoys the highest speedup, followed by GSM8K and then MT-Bench.

	GSM8K	HUMANEVAL	MT-BENCH
8B/405B-STANDARD	5.2×	5.5×	5.0×
8B/405B-JUDGE	9.8×	10.1×	9.4×
8B/70B-STANDARD	1.5×	1.7×	1.3×
8B/70B-JUDGE	2×	2.1×	1.8×

Table 2: Individual speedups over standard autoregressive decoding evaluated across several benchmarks when using standard HuggingFace implementation for batch size 1.

C MORE PROMPTS

C.1 REJECTED REPLIES FOR LLAMA-8B

Here we provide more example prompts where Llama-8B provides completely correct answers but gets rejected early on by the target Llama-405B. We display the decision of our judge decoding strategy right below. To also highlight that judge decoding can catch errors and does not just blindly accept responses, we also show prompts where Llama-8B provides a wrong response.




Figure 9: More example prompts for SD for Llama-8B and Llama-405B. **Left:** Correct response getting rejected early under standard decoding, while judge decoding accepts a long continuation (but admittedly over-cautiously rejects later on). **Right:** Wrong response that gets rejected too early by standard decoding and correctly rejected later on by judge decoding (there are 5 roommates in total).




Figure 10: More example prompts for speculative decoding for Llama-8B and Llama-405B. **Left:** Correct response getting rejected early under standard decoding, while judge decoding accepts a long continuation (but admittedly over-cautiously rejects later on). **Right:** Wrong response that gets rejected too early by standard decoding and correctly rejected later on by judge decoding (there are 5 roommates in total).

C.2 JUDGING OF WIKIPEDIA ARTICLES

Here we provide more details and examples for verifying *Wikipedia* articles. Given a *Wikipedia* article name such as “aluminium”, “Moore’s Law” or “Pet Shop Boys”, we prompt the model for information by asking “What can you tell me about <insert topic>?”. We then again compare greedy matching for standard speculative decoding with our judging strategy when using the summary part of the *Wikipedia* article as a reply. We display some example prompts along with the corresponding verifications in Fig. 11.

C.3 FORCING WRONG REPLIES FOR LLAMA-405B

Here we provide some more evidence of the “correcting” behaviour of Llama-405B when conditioned on wrong tokens. If the model cannot fix the response anymore, then it will often point out that the completion it just gave is actually wrong, see e.g. examples in Fig. 12 and Fig. 13. This again strongly suggests that correctness should thus be detectable in the embeddings of such tokens.




Figure 11: Two example prompts from the subset of wikipedia-summaries, along with the correspond verifications.




Figure 12: **Left:** Llama-405B corrects the mistake by subtracting $l[i]$ to double instead of triple. **Right:** Similar correction behaviour by pointing out that response so far is wrong.




Figure 13: **Left:** Llama-405B correctly points out that there is a bug as the index variable "j" is not defined. **Right:** The model can also catch more subtle mistakes. Here the original list also gets modified as no copy was made, leading to wrong outputs.