

Can Large Language Models *Unlock* Novel Scientific Research Ideas?

Anonymous ACL submission

Abstract

The widespread adoption of Large Language Models (LLMs) and publicly available ChatGPT have marked a significant turning point in the integration of Artificial Intelligence (AI) into people’s everyday lives. This study explores the capability of LLMs in generating novel research ideas based on information from research papers. We conduct a thorough examination of 4 LLMs in five domains (e.g., Chemistry, Computer, Economics, Medical, and Physics). We found that the future research ideas generated by Claude-2 and GPT-4 are more aligned with the author’s perspective than GPT-3.5 and Gemini. We also found that Claude-2 generates more diverse future research ideas than GPT-4, GPT-3.5, and Gemini 1.0. We further performed a human evaluation of the novelty, relevancy, and feasibility of the generated future research ideas. This investigation offers insights into the evolving role of LLMs in idea generation, highlighting both its capability and limitations. Our work contributes to the ongoing efforts in evaluating and utilizing language models for generating future research ideas. We make our datasets and codes publicly available¹.

“Innovation is seeing what everybody has seen and thinking what nobody has thought” —Dr. Albert Szent-Györgyi

1 Introduction

An *idea* can be defined as a thought or suggestion aimed at solving a problem or considering a possibility. This concept is central to fields ranging from philosophy to science and economics. According to (Plato et al., 2000), ideas are archetypal forms that represent the most accurate reality. In the context of scientific research, (Kuhn and Hawkins, 1963) in "The Structure of Scientific Revolutions" describes

¹<https://anonymous.4open.science/r/Future-Idea-Generation-1BBD/>




Figure 1: Large language model suggesting future research ideas after reading a research paper

an idea as a realization or hypothesis that can challenge and shift paradigms within a scientific community. Therefore, an idea can be understood as a cognitive construct that arises from the human mind’s ability to process information, reflect, and imagine, serving as a cornerstone for creativity, problem-solving, and innovation. Idea generation can generally be understood as a state of focused internally-directed attention involving controlled semantic retrieval (Benedek et al., 2014).

As technology improves, new capabilities emerge. Ever since the Turing Test was proposed in the 1950s, humans have explored the mastering of language intelligence by machine (Zhao et al., 2023). Technological advancements serve two key functions in innovation. Firstly, they influence the goals of generating and selecting ideas. Secondly, they impact the methodology of how ideas are generated and chosen (Kornish and Hutchison-Krupat, 2017). LLMs have exhibited unparalleled mastery of natural language processing (NLP). Since, these have become increasingly powerful, researchers have begun to investigate their reasoning ability in problem-solving tasks (Yao et al., 2022; Brahman et al., 2023). The concept of an idea is essentially a new combination of old elements. LLMs have access to a broad spectrum of knowledge, due to their extensive training on vast amounts of text data. However, understanding how information extracted from a research paper can give rise to new ideas, which have not yet been explored much. This leads us to ponder:

Can Large Language Models read a scientific paper and suggest new research ideas or directions?

Motivated by this, in this paper, we analyze the potential of LLMs in generating future research directions/ideas. As LLMs possess knowledge across various domains, we investigate five specific areas, viz. Computer Science, Physics, Chemistry, Economics, and Medicine. To address this task, we create a dataset of papers published after the year 2022 from these five domains. We annotate the papers with future research ideas. To evaluate the novelty and relevance of ideas generated by the LLMs, we propose an Idea Alignment Score (IAS-core). This score reflects how well the generated ideas align with those proposed by the authors. To study the model’s ability to generate diverse ideas, we propose an Idea Distinctness Index. We analyze and discuss the performance and limitations of four LLMs: Gemini (Anil et al., 2023), Claude-2 (Anthropic, 2023), GPT-3.5, and GPT-4 (OpenAI, 2023). We further conduct a human evaluation of 460 generated ideas in computer science to study the novelty, relevance, and feasibility of these research ideas. This paper demonstrates that LLMs have the potential to generate relevant, distinct, feasible, and novel ideas to some extent.

To summarize, our main contributions in this paper are:

- We contribute to the ongoing exploration of LLMs’ capabilities in generating future research ideas.
- To address the task, we create a novel dataset of recent papers of five domains (Computer science, Economics, Chemistry, Physics, Medical).
- To assess the quality of generated ideas from LLMs, we propose Idea Alignment Score and Idea Distinctness Index to evaluate the idea generation capability.
- We discuss the challenges associated with human evaluation and conduct an in-depth analysis on the 460 generated ideas.

We hope that this work serves as a foundation for future studies focused on accelerating scientific research by automatically generating research ideas.

2 Related Work

Recently, LLMs have shown emergent abilities to perform tasks they were not explicitly trained for (Wei et al., 2022; Bubeck et al., 2023). This includes common sense question answering, code generation, and cross-domain problem solving, enriching their utility across unforeseen domains (Chen et al., 2021; Sarsa et al., 2022). Their capability extends to advanced scientific domains such as computer science, physics, medicine, and mathematics (Romera-Paredes et al., 2023; Huang et al., 2023). Technology Semantic Network (TechNet) was proposed to stimulate idea generation in engineering design (Sarica et al., 2021). There have been a few works in the discovery of new proteins to accelerate scientific discovery. The prior work reported in (Spangler et al., 2014) involves utilizing published studies to find new protein kinases that phosphorylate the tumor suppressor protein p53.

A hypothesis is a hunch, assumption, suspicion, assertion or an idea about a phenomenon, relationship or situation, the reality or truth of which you do not know (Kumar, 1996). There have been some works on hypothesis generation. Initial studies on automated hypothesis generation begin by constructing a corpus of distinct concepts. Subsequently, they explore the relationships between these concepts using machine learning techniques, such as analyzing the similarities among vectors representing different words (or concepts) (Tshityan et al., 2019), or applying link prediction methods over a graph (where concepts are nodes) (Nadkarni et al., 2021). Recently, (Qi et al., 2023) used LLMs and extensive pre-existing knowledge of various scientific fields for hypothesis generation. PaperRobot (Wang et al., 2019) predicts related entities for an input title and writes key elements of a new paper, including the abstract, conclusion, and future work, and predicts a new title.

Xu et al. (2023) developed a framework that leverages the concept co-occurrence graphs and a masked language model to explore and verbalize academic ideas. Their method involves constructing evolving concept graphs across various disciplines and utilizing temporal link prediction to identify potential interdisciplinary connections. The framework also incorporates pre-trained language models to articulate these connections in a coherent academic context. SciMON (Wang et al., 2023) showed that LLMs can be guided by seed terms to generate specific ideas. They applied a

pre-trained sentence classifier to classify sentences from the title and abstract into categories of Background, Method, Objective. They considered sentences labeled as problems or motivations as background, and the remaining were treated as target output sentences. Additionally, a pre-trained entity extractor was used to extract salient seed terms.

However, previous works primarily focused on developing methods (linking and explaining entities, which may not sufficiently capture the complexity or explain how LLMs can solve real-world problems) for idea generation, whereas our work exhaustively focuses on evaluating the capability of LLMs in generating research ideas. Our goal is to assess the inherent ability of LLMs to generate future research ideas/directions.

3 Dataset

Our dataset creation involves three steps: (1) Dataset Collection, (2) FRI Identification and removal, and (3) FRI generation.

3.1 Dataset Collection

We construct a corpus D from S2ORC collected 1250 papers² from the domains of Computer Science, Economics, Physics, Chemistry, Medical from (Lo et al., 2020)³. We prompted the LLM with paper text after removing the future work for generating future ideas.

To ensure the quality and relevance of the data and to utilize the future research ideas mentioned in a paper, the selected papers must meet the following requirements: (1) the paper must contain the full content, and (2) the paper must include a section on future work.

3.2 FRI Identification and Removal

We first identify and remove any potential research ideas mentioned in the paper. By doing this, we ensure that the LLMs have no prior access to these ideas, which could otherwise affect the objectivity of the analysis.

3.2.1 Annotation Process

Inspired by Hao et al. (2020), we define a future research idea as a discussion that the authors believe they will conduct in the future or believe needs to be investigated in future research. We discuss more


details about the annotation guidelines, annotation training, annotation process and annotator’s pay in Appendix A.

3.2.2 Future Work Removal

We observed two types of future research ideas (FRIs)⁴ (Direct FRI and Mixed FRI). We discuss them in details in Appendix H.

AP-FRI Corpus: We removed the sentence from the paper’s input text if it pertains to Direct FRI. However, in the case of Mixed FRI, we did not entirely remove the sentences; instead, we eliminated only parts of sentences or markers indicating future research ideas. We added the removed future ideas to a corpus, which we refer to as the AP-FRI (Author Perspective Future Research Idea Corpus). This corpus contains the future research ideas proposed by the authors of the paper. Also, before adding to the AP-FRI corpus, we merged the sentences about the same topic into a single group. We illustrate this by an example in Figure 7 in the Appendix of the paper.

3.3 Data Statistics



(a) Domain vs Avg. number of words in a paper w/o FWK (b) Domain vs Avg. number of words in FWK

Figure 2: Comparison of average word counts in papers with and without FWK across domains.

Figures 2a and 2b present a domain-wise analysis of average word counts in academic papers and their future work (FWK) sections, revealing significant variations across disciplines. Notably, Computer Science emphasizes future research extensively, while Chemistry adopts a more concise approach. See the appendix Section A.5 for more details.

²250 papers from each domain.

³They used Science Parse and Grobid tool to extract data from PDF. We used the plain text without figure and tables and references for our experiment.

⁴In this paper, we use the terms ‘ideas,’ ‘research ideas,’ ‘future research ideas,’ and ‘FRI’ interchangeably to frequently refer to future research ideas.

4 Experiments

4.1 FRI Generation using LLM

We investigate various prompts and utilize the following prompts to generate FRIs from the paper text after removal the FRIs mentioned in the paper as discussed in Section 3.

System: You are a research scientist.

User: Imagine you are a research scientist. 1) Read the full paper and understand it. 2) Find out the related works in this direction 3) Brainstorm and follow a step-by-step reasoning approach to generate potential future research ideas:

[paper text]

Make sure the future research ideas are very distinct from the related papers. Potential future research ideas from the paper in bullet points are:

Here, ‘[paper text]’ contains the full content of the paper after removal of future work sections. In case the text was larger than the context size of the particular LLM we divided the paper into parts and finally combined the ideas.

4.2 Challenges

To accurately assess the novelty, relevance, and applicability of ideas generated by LLMs, evaluators must possess a high level of expertise in the specific domain and a deep understanding of the research topic to fully grasp the context. Additionally, they need knowledge of related literature to evaluate the ideas’ future potential and the broader implications of their implementation.

4.3 Idea Alignment Score (IAScore)

With the above challenges, the evaluation of ideas generated by LLMs is a challenging process that demands a high number of domain-specific experts. We, therefore, proposed an *Idea Alignment Score* (IAScore), which reflects how well the generated ideas align with those proposed by the author. The underlying idea for this score is that authors of accepted papers can be regarded as experts in their respective subjects. The reason being that they possess thorough background knowledge and have conducted deep analyses of the research topic before getting the paper accepted. Consequently, they are well-acquainted with the pertinent challenges which also may have been discussed by expert reviewers. Therefore, we propose that future ideas mentioned by the authors in the paper could be utilized as good quality of potential FRIs.

The IAScore quantifies the alignment of newly generated ideas with author’s perspectives within a specific domain, and is computed via a two-step process, detailed in Equations 1 and 2.

Initially, we compute the average alignment score AvgScore_j for each paper’s ideas. The IdeaMatcher model measures the alignment between the paper’s author *Future Research Ideas* (AP-FRI_j) and its each generated idea I_{ij} . The subscript i indexes the i -th idea within the j -th paper, where N_j represents the total number of ideas proposed in that paper.

$$\text{AvgScore}_j = \frac{1}{N_j} \sum_{i=1}^{N_j} \text{IM}(\text{AP-FRI}_j, I_{ij}) \quad (1)$$

LLMs may generate new ideas that even the author may not have thought of. They can also generate additional future ideas, which may or may not be useful. Our goal is for this score is that the LLMs must have generated at least the author’s proposed potential future ideas. Therefore, in our formula of AvgScore_j , the sum of the alignment scores for a paper’s ideas is divided by the total number of the author’s proposed ideas, N_j , to normalize the score.

$$\text{IAScore}_{\text{domain}, M} = \frac{1}{P} \sum_{j=1}^P \text{AvgScore}_j \quad (2)$$

Subsequently, we aggregate the individual paper scores to calculate the domain-wise IAScore. This aggregation, presented in Equation 2, averages the AvgScore_j values across all P papers within the domain. Higher the value of $\text{IAScore}_{\text{domain}}$ signifies the more alignment of the generated ideas with author’s perspective of all papers generated by model M .

4.3.1 IdeaMatcher

To select an effective IdeaMatcher, we create a small annotated corpus. Our dataset was divided using the standard 30:70 ratio for validation and test sets, respectively. Since our study involves comparing two ideas using a pre-trained model, we did not require a separate training set. We first manually searched for matching pairs of ideas from generated ideas and AP-FRI of the paper. After obtaining 61 matching pairs, we searched for non-matching pairs of ideas, which is straightforward

as only one generated idea will match or would not match with another one from AP-FRI while others would not match, so we picked an equal number of non-matching pairs. Then, we experimented with the idea-matching task by considering it similar to the Natural Language Inference (NLI) task. In particular, we considered the generated FRIs to be hypotheses and their corresponding AP-FRIs of the paper to be premises. If the idea matches, the hypothesis should be entailed by the premise. In particular, we used a pre-trained RoBERTa MNLI model (Liu et al., 2019) for this task. We found that this technique produces many false negative cases, resulting in an accuracy of 65.5%.

We also evaluated the idea-matching capability of BERTScore (Zhang* et al., 2020), as it utilizes BERT embeddings for comparison. We discuss the details in Appendix F. We found that BERTScore performed better than the entailment technique, resulting in an accuracy of 75.4%. We also tried GPT by prompting it with various questions and found that it resulted in 91.8% accuracy when prompted with a specific question prompt below:-

Prompt: Your task is to examine whether a particular idea is incorporated within a set of ideas and to what degree.
Collection of ideas: {API-FRIs}
Single idea: {A generated Idea}
 Is the single idea contained within the collection of ideas?
 If yes, quantify its degree of presence or relevance of the single idea in the collection of ideas on a scale from 0 to 1.

We found that GPT performs better than the existing NLI (Natural Language Inference) and similarity measure, such as BERTScore. Therefore, we chose GPT for this task⁵.

4.4 Idea Distinctness Index

Distinct-N (Li et al., 2015), is a metric that measures the diversity of a sentence. It focuses on the number of distinct n-grams of a sentence, and thus penalizes sentences with a lot of repeated words. However, comparing two ideas need semantic comparisons rather than just syntactic differences. So, we introduce a method to semantically evaluate the distinctness of the generated ideas. This method in particular leverages semantic embedding to capture the essence of each idea and computes their distinctness based on semantic similarity measures.

⁵We used the OpenAI model GPT-3.5-turbo-0125 using OpenAI API

Given a set of generated ideas $I = \{id_1, id_2, \dots, id_n\}$, representing individual ideas, we first encode each idea into a high-dimensional vector space using a pre-trained GPT embedding (Devlin et al., 2019)⁶ $GPT : id_i \mapsto \mathbf{v}_i$, where $\mathbf{v}_i \in \mathbb{R}^d$ is the embedding of idea id_i and d is the dimensionality of the embedding space.

To quantify the distinctness between pairs of ideas, we compute the cosine similarity between their embeddings, $sim(\mathbf{v}_i, \mathbf{v}_j) = \frac{\mathbf{v}_i \cdot \mathbf{v}_j}{\|\mathbf{v}_i\| \|\mathbf{v}_j\|}$, for each pair of ideas (id_i, id_j) in I . The distinctness D_{ij} between two ideas i and j is then inversely related to their similarity: $D_{ij} = 1 - sim(\mathbf{v}_i, \mathbf{v}_j)$.

The overall distinctness of the set I is calculated as the mean of all pairwise distinctness scores:

$$D_I = \frac{1}{n(n-1)} \sum_{i=1}^n \sum_{j=1, j \neq i}^n D_{ij} \quad (3)$$

This measure provides a single scalar value D_I that quantifies the average diverseness of ideas within a corpus of ideas, with higher values indicating a greater degree of diverseness among the ideas.

Subsequently, we aggregated the distinctness scores across all ideas in each paper to compute the mean distinctness for that paper. Let $P = \{p_1, p_2, \dots, p_m\}$ represent the set of papers in a domain, where m is the number of papers in the domain. Finally, for a comprehensive assessment of model performance within a domain, we averaged the mean distinctness scores of all papers generated by model M as follows:

$$D_{\text{domain}, M} = \frac{1}{m} \sum_{p=1}^m D_{I_{p_M}} \quad (4)$$

The resultant metric, $D_{\text{domain}, M}$, represents the average idea distinctness for model M in a given domain, indicating the model’s ability to generate diverse ideas.

4.5 Adding additional background knowledge

We designed our framework based on the Retrieval-Augmented Generation (RAG) model (Lewis et al., 2020) to integrate background knowledge into LLMs, as illustrated in Figure 6. A detailed explanation is available in the Appendix E, but we summarize the key components here. 1) **Vector Database:** We collected approximately 1.9 lakh

⁶text-embedding-ada-002




Figure 3: IAScore for each domain and model; a higher value indicates better alignment with the author.




Figure 4: Idea distinctness index analysis; Here human is the authors of the paper




Figure 5: Novelty human evaluation for Computer Science domain; Here (B) means with additional background knowledge

(190,000) research paper titles and abstracts using the Semantic Scholar API. These were encoded into vector representations using BERT embeddings and stored in a vector database. 2) **Retriever**: To fetch relevant background knowledge, we computed the cosine similarity between the vectorized representation of the target paper title and




Figure 6: RAG pipeline framework for infusing more background knowledge with the LLMs

the stored database. The top 20 most similar papers were retrieved, and their key contributions were extracted from the abstracts using a structured LLM prompt. 3) **Generator**: Using the retrieved background knowledge, we prompted an LLM (Gemini-Pro) to generate distinct and novel future research ideas.

4.6 Human Evaluation

The evaluation of generated future ideas necessitates familiarity with both previous works related

to the subject and the work being evaluated. Specifically, the evaluator must be an expert in the domain and topic. Given the complexity of human evaluation, we approached authors (as the authors have the knowledge of their paper and they also have knowledge of the literature) who have published papers in reputable venues, possess over 5 years of experience in scientific publishing, and have authored more than 5 scientific papers. We collected their accepted papers (published between 2023 and 2024) and followed the dataset preparation as we discussed in Section 3 and generated FRIs. We modify the prompt slightly to specifically generate only the top five results (see Appendix B). We selected the outputs from Claude and GPT-4⁷ models due to their better IAScore and Idea Distinction index. We adopt this approach to avoid author exhaustion and to get an accurate evaluation. We ask the following questions from each human evaluator:-

- Q1: Is the idea relevant with the research topic of the paper. (Relevant/Not relevant)
- Q2: Assess the originality/novelty of the research idea (5 scale)
- Q3: Review the research idea for factual correctness and feasibility. Is the idea impractical or too vague to be actionable? (Not Possible/Possible)

For Q2, we used Best-Worst Scaling (Louviere et al., 2015) on a 5-point scale. More details about the human evaluation are mentioned in the Appendix B.

5 Results and Discussion

5.1 Alignment Results

Figure 3 provides a comparative overview of the IAScore for four language models⁸ Claude-2, Gemini-1.0, GPT-3, and GPT-4 across five academic domains: Chemistry, Computer Science, Economics, Medical, and Physics.

In the Chemistry and Economics domains, Claude has the highest IAScore, indicating strong alignment with the authors’ future research ideas. Claude and GPT-4 have almost similar values for the Computer, Medical, and Physics domains (with GPT-4 slightly higher). GPT-3 and Gemini have

lower scores than both GPT-4 and Claude in every domain. GPT-3 has almost the same score as Gemini in the Chemistry and Economics domains. However, it scores higher than Gemini in the Computer, Medical, and Physics domains. The results underscore the advancements in language model capabilities, with each model showcasing domain-specific strengths in idea generation. This alignment of LLMs shows that LLMs are able to generate relevant and novel ideas to some extent. We also studied the effect of length of future work on IAScore (See Appendix D). Our overall analysis shows that ideas of moderate length (20-40 words) achieve the highest Impact Assessment Scores (IAScores), balancing detail and clarity, while shorter (<20 words) and longer (40-60 words) ideas tend to score lower due to insufficient detail. We also conducted a human analysis to understand the quality of research ideas generated when the IAScore is low (see Appendix G).

5.2 Distinctness Results

We show the comparative evaluation of idea distinctness scores in Figure 4. The line graph depicts the variation of distinctness between the generated ideas and the human-written ideas (AP-FRIs). GPT-3 shows the least distinctness among the generated ideas, except in the Computer domain, where it is slightly more distinct than Gemini. As shown in the graph, the distinctness of Gemini is also quite low; however, it is slightly better than GPT-3, except in the Computer domain.

The generated ideas of GPT-4 are more distinct than those of Gemini and GPT-3 (except for economics, whereas the distinctness of GPT-4 is the same as Gemini). However, it is lower than both Claude and Human. The Idea Distinctness Index of the generated ideas from Claude are almost the same as those of humans for Chemistry, Economics, and Medical domains. However, they are higher than even human scores in the Computer and Physics domains, which shows that it generates very distinct FRIs.

5.3 Human Evaluation Results

We conducted a human evaluation on 460 generated ideas for 46 papers in the computer science domain. To validate the quality of human annotation, we measure the inter-annotator agreement ratio where 20% of the generated ideas are evaluated by two different authors of the same paper. We measured Cohen’s kappa coefficient (Cohen, 1960), which

⁷We used gpt-4-turbo using OpenAI API for the generation

⁸We set maximum token length to 512, and temperature=0 for each models

was 0.83, thereby confirming the high quality of the annotations of generated research ideas.

Novelty: Figure 5 displays the results of the human evaluation. We observed that Claude generates 14.78% of non-novel and 16.52% generic FRIs, 41.73% moderately novel, 20.86% very novel, and 16.52% extremely novel FRIs. GPT generates 7.83% not-novel, 13.91% generic, 42.61% moderately novel, 28.70% very novel, and 6.96% extremely novel ideas. Claude generates more non-novel and generic ideas than GPT-4, while GPT-4 produces more very novel ideas and nearly the same number of excellent ideas. We conducted an additional human evaluation in the physics domain, analyzing 409 generated ideas across 43 papers. We observed that Claude generates 15.28% non-novel and 16.02% generic FRIs, 41.22% moderately novel, 20.36% very novel, and 17.12% extremely novel FRIs. GPT produces 7.33% not-novel, 14.41% generic, 42.11% moderately novel, 28.20% very novel, and 7.95% extremely novel ideas, similar to previous observations in computer science. This demonstrates that although LLMs also generate generic or already explored ideas, they are capable of producing novel ideas that have either not been explored or have been minimally explored⁹.

Relevance and Feasibility: After human evaluation, for Computer Science domain, we found that that 76.67% of the ideas generated by Claude and 93.34% by GPT-4 are relevant. Furthermore, 83.34% of Claude’s generated ideas and 96.64% of GPT-4’s ideas were judged to be practically feasible and factually correct. Similarly for the Physics domain we found After human evaluation, we found that 78.45% of the ideas generated by Claude and 91.56% by GPT-4 are relevant. Furthermore, 85.67% of Claude’s generated ideas and 94.78% of GPT-4’s ideas were judged to be practically feasible and factually correct.

These results highlight that Claude and GPT-4 can generate relevant and feasible research ideas. However, the reason Claude generates more impractical and irrelevant research ideas may be that Claude attempts to generate more distinct research ideas than GPT-4, as we evaluated and discussed in Section 5.2.

⁹Comprehensive human evaluations across all domains require significant expertise and logistical resources, making it a challenge for the present study. However, the observed results strongly suggest that similar trends are likely to hold across other domains.

5.4 Open-ended generation:

We tested whether LLMs could retain open-ended generation capabilities by providing only a title and abstract as input. Our findings showed that, overall, LLMs can still generate open-ended content due to their past knowledge. However, they may not produce many high-quality ideas, as they lack access to recent publications and methodological insights relevant to the current paper. We discuss this in detail in Appendix C.

5.5 Impact on Adding Background Knowledge

We found that adding background knowledge reduced the generation of generic or non-novel ideas and improved relevance and factual accuracy. However, further research is needed to boost the novelty of generated ideas. We discuss this in detail in Appendix E.

6 Conclusion and Future Work

In conclusion, we present the first attempt to evaluate the potential of LLMs in generating future research ideas across five domains: Computer Science, Economics, Chemistry, Physics, and Medicine. Our results and analysis show that LLMs possess domain-specific strengths in idea generation. Furthermore, the results from the Idea Distinctness Index indicate that LLMs, such as Claude and GPT-4, generate distinct research ideas than Gemini and GPT 3.5. GPT-4 and Claude aligns better with authors written future research ideas than Gemini and GPT-4. The alignment of LLMs with the authors of generated ideas, and our human evaluations on relevance, novelty, and feasibility, reveal that although LLMs often produce non-novel and generic ideas, they have the potential to generate relevant and novel and diverse ideas to a significant extent. We hope that the findings and experiments of this work will unlock the potential of LLMs in idea generation and will foster new advancements in automated scientific innovation.

In future, we plan to build methods to enhance idea novelty and prevent generic outputs by LLM. We also plan to initiate a community-wide effort involving domain-expert judgment and evaluations by other LLMs on our dataset and method.

7 Limitations

7.1 Limitations of Data Collection

We extracted papers using the Semantic Scholar Academic Graph API from January 2023 to February 2024. The number of papers available is limited by the scope of our data extraction from the Semantic Scholar Academic Graph. We excluded papers that are not in English, as well as those whose abstracts could not be correctly parsed from the PDFs. Not all of these papers include sections on future work; therefore, we annotated only those that contained sections outlining future research directions. So due to such limitations, we collected 100 papers from each domain for analysis.

7.2 Memorization

(Carlini et al., 2022) highlight that LLMs are prone to memorizing portions of their training data, a significant concern in the evaluation of contemporary LLMs. Despite this, the data used for pre-training and post-training includes "a small amount" of more recent data. Therefore, we gathered recent papers from 2023 and 2024. By focusing our evaluation on papers published in these years, the likelihood of test papers appearing in the pre-training corpora for the models is substantially reduced. In addition, we conducted a manual review of these papers to assess memorization. This involved asking various questions related to the papers, such as their titles, publishing venues, author names, etc., to see if the models could supply the missing information. Our findings showed no evidence of such memorization occurring. A similar approach is also followed by (Wang et al., 2023) (discussed in Section 6.4) and even they did not find any evidence of this occurring.

Ethics Statement

We have utilized the open source dataset for our work. Our aim for this work is to assess the potential of language models in generating ideas. Our Institutional Review Board (IRB) evaluated and approved this study. We do not encourage the use of LLMs to generate AI generated research papers (by generating new ideas) or misuse it for harmful idea generation. LLMs can process and synthesize vast amount of literature faster than humans, potentially identifying new patterns or gaps in research that might not be obvious, thus accelerating scientific discovery. However, since LLMs can generate content that may be similar to existing materials, this

raises concerns about intellectual property rights and the originality of ideas. LLMs utilized for generating ideas might be misapplied to produce harmful materials such as plans for schemes for designs for destructive devices, explosive devices, ideas for spamming. Notably, it is a common challenge among existing LLMs with strong creative and reasoning abilities. So, we emphasize the responsible use of LLMs for idea generation and the need to broadly improve the safety of LLMs.

References

- Rohan Anil, Sebastian Borgeaud, Yonghui Wu, Jean-Baptiste Alayrac, Jiahui Yu, Radu Soricut, Johan Schalkwyk, Andrew M. Dai, Anja Hauth, Katie Millican, David Silver, Slav Petrov, Melvin Johnson, Ioannis Antonoglou, Julian Schrittwieser, Amelia Glaese, Jilin Chen, Emily Pitler, Timothy P. Lillicrap, Angeliki Lazaridou, Orhan Firat, James Molloy, Michael Isard, Paul Ronald Barham, Tom Hennigan, Benjamin Lee, Fabio Viola, Malcolm Reynolds, Yuanzhong Xu, Ryan Doherty, Eli Collins, Clemens Meyer, Eliza Rutherford, Erica Moreira, Kareem Ayoub, Megha Goel, George Tucker, Enrique Piqueras, Maxim Krikun, Iain Barr, Nikolay Savinov, Ivo Danihelka, Becca Roelofs, Anaïs White, Anders Andreassen, Tamara von Glehn, Lakshman Yagati, Mehran Kazemi, Lucas Gonzalez, Misha Khalman, Jakub Sygnowski, and et al. 2023. [Gemini: A family of highly capable multimodal models](#). *CoRR*, abs/2312.11805.
- Anthropic. 2023. [Model card for claude 2](#).
- Mathias Benedek, Emanuel Jauk, Andreas Fink, Karl Koschutnig, Gernot Reishofer, Franz Ebner, and Aljoscha C. Neubauer. 2014. [To create or to recall? neural mechanisms underlying the generation of creative new ideas](#). *NeuroImage*, 88:125–133.
- Faeze Brahman, Chandra Bhagavatula, Valentina Pyatkin, Jena D Hwang, Xiang Lorraine Li, Hirona J Arai, Soumya Sanyal, Keisuke Sakaguchi, Xiang Ren, and Yejin Choi. 2023. [Making small language models better procedural knowledge models for \(counterfactual\) planning](#). *arXiv preprint arXiv:2305.19472*.
- Sébastien Bubeck, Varun Chandrasekaran, Ronen Eldan, Johannes Gehrike, Eric Horvitz, Ece Kamar, Peter Lee, Yin Tat Lee, Yuanzhi Li, Scott M. Lundberg, Harsha Nori, Hamid Palangi, Marco Túlio Ribeiro, and Yi Zhang. 2023. [Sparks of artificial general intelligence: Early experiments with GPT-4](#). *CoRR*, abs/2303.12712.
- Nicholas Carlini, Daphne Ippolito, Matthew Jagielski, Katherine Lee, Florian Tramèr, and Chiyuan Zhang. 2022. [Quantifying memorization across neural language models](#). *ArXiv*, abs/2202.07646.

714	Mark Chen, Jerry Tworek, Heewoo Jun, Qiming Yuan,	The semantic scholar open data platform. <i>ArXiv</i> ,	774
715	Henrique Pondé de Oliveira Pinto, Jared Kaplan,	abs/2301.10140.	775
716	Harrison Edwards, Yuri Burda, Nicholas Joseph,		
717	Greg Brockman, Alex Ray, Raul Puri, Gretchen	Laura J. Kornish and Jeremy Hutchison-Krupat. 2017.	776
718	Krueger, Michael Petrov, Heidy Khlaaf, Girish Sas-	Research on idea generation and selection: Implica-	777
719	try, Pamela Mishkin, Brooke Chan, Scott Gray,	tions for management of technology. <i>Production and</i>	778
720	Nick Ryder, Mikhail Pavlov, Alethea Power, Lukasz	<i>Operations Management</i> , 26:633–651.	779
721	Kaiser, Mohammad Bavarian, Clemens Winter,		
722	Philippe Tillet, Felipe Petroski Such, Dave Cum-	Thomas S. Kuhn and David Hawkins. 1963. The struc-	780
723	mings, Matthias Plappert, Fotios Chantzis, Eliza-	ture of scientific revolutions. <i>American Journal of</i>	781
724	beth Barnes, Ariel Herbert-Voss, William Hebg-	<i>Physics</i> , 31:554–555.	782
725	Guss, Alex Nichol, Alex Paino, Nikolas Tezak, Jie		
726	Tang, Igor Babuschkin, Suchir Balaji, Shantanu Jain,	R. Kumar. 1996. <i>Research Methodology: A Step-by</i>	783
727	William Saunders, Christopher Hesse, Andrew N.	<i>Step Guide for Beginners</i> . Longman Australia.	784
728	Carr, Jan Leike, Joshua Achiam, Vedant Misra, Evan		
729	Morikawa, Alec Radford, Matthew Knight, Miles	Sandeep Kumar, Tirthankar Ghosal, and Asif Ekbal.	785
730	Brundage, Mira Murati, Katie Mayer, Peter Welinder,	2023a. When reviewers lock horn: Finding dis-	786
731	Bob McGrew, Dario Amodei, Sam McCandlish, Ilya	agreement in scientific peer reviews. <i>arXiv preprint</i>	787
732	Sutskever, and Wojciech Zaremba. 2021. Evaluat-	<i>arXiv:2310.18685</i> .	788
733	ing large language models trained on code. <i>CoRR</i> ,		
734	abs/2107.03374.	Sandeep Kumar, Tirthankar Ghosal, and Asif Ekbal.	789
735	Jacob Cohen. 1960. A coefficient of agreement for	2023b. When reviewers lock horns: Finding dis-	790
736	nominal scales. <i>Educational and Psychological Mea-</i>	agreements in scientific peer reviews. In <i>Proceed-</i>	791
737	surement, 20:37 – 46.	ings of the 2023 Conference on Empirical Methods in	792
738	Jacob Devlin, Ming-Wei Chang, Kenton Lee, and	<i>Natural Language Processing</i> , pages 16693–16704,	793
739	Kristina Toutanova. 2019. BERT: pre-training of	Singapore. Association for Computational Linguis-	794
740	deep bidirectional transformers for language under-	tics.	795
741	standing. In <i>Proceedings of the 2019 Conference of</i>		
742	<i>the North American Chapter of the Association for</i>	Patrick S. H. Lewis, Ethan Perez, Aleksandra Pik-	796
743	<i>Computational Linguistics: Human Language Tech-</i>	tus, Fabio Petroni, Vladimir Karpukhin, Naman	797
744	<i>nologies, NAACL-HLT 2019, Minneapolis, MN, USA,</i>	Goyal, Heinrich Küttler, Mike Lewis, Wen-tau Yih,	798
745	<i>June 2-7, 2019, Volume 1 (Long and Short Papers),</i>	Tim Rocktäschel, Sebastian Riedel, and Douwe	799
746	pages 4171–4186. Association for Computational	Kiela. 2020. Retrieval-augmented generation for	800
747	Linguistics.	knowledge-intensive NLP tasks. In <i>Advances in Neu-</i>	801
748	Wenke Hao, Zhicheng Li, Yuchen Qian, Yuzhuo Wang,	<i>ral Information Processing Systems 33: Annual Con-</i>	802
749	and Chengzhi Zhang. 2020. The ACL FWS-RC: A	<i>ference on Neural Information Processing Systems</i>	803
750	dataset for recognition and classification of sentence	2020, <i>NeurIPS 2020, December 6-12, 2020, virtual</i> .	804
751	about future works. In <i>JCDL '20: Proceedings of the</i>		
752	<i>ACM/IEEE Joint Conference on Digital Libraries in</i>	Jiwei Li, Michel Galley, Chris Brockett, Jianfeng Gao,	805
753	<i>2020, Virtual Event, China, August 1-5, 2020</i> , pages	and William B. Dolan. 2015. A diversity-promoting	806
754	261–269. ACM.	objective function for neural conversation models.	807
755	Qian Huang, Jian Vora, Percy Liang, and Jure Leskovec.	<i>ArXiv</i> , abs/1510.03055.	808
756	2023. Benchmarking large language models as ai		
757	research agents. <i>ArXiv</i> , abs/2310.03302.	Yinhan Liu, Myle Ott, Naman Goyal, Jingfei Du, Man-	809
758	Rodney Michael Kinney, Chloe Anastasiades, Rus-	dar Joshi, Danqi Chen, Omer Levy, Mike Lewis,	810
759	sell Authur, Iz Beltagy, Jonathan Bragg, Alexan-	Luke Zettlemoyer, and Veselin Stoyanov. 2019.	811
760	dra Buraczynski, Isabel Cachola, Stefan Candra, Yo-	Roberta: A robustly optimized bert pretraining ap-	812
761	ganand Chandrasekhar, Arman Cohan, Miles Craw-	proach. <i>arXiv preprint arXiv:1907.11692</i> .	813
762	ford, Doug Downey, Jason Dunkelberger, Oren Et-		
763	zioni, Rob Evans, Sergey Feldman, Joseph Gorney,	Kyle Lo, Lucy Lu Wang, Mark Neumann, Rodney Kin-	814
764	David W. Graham, F.Q. Hu, Regan Huff, Daniel King,	ney, and Daniel Weld. 2020. S2ORC: The semantic	815
765	Sebastian Kohlmeier, Bailey Kuehl, Michael Langan,	scholar open research corpus. In <i>Proceedings of the</i>	816
766	Daniel Lin, Haokun Liu, Kyle Lo, Jaron Lochner,	<i>58th Annual Meeting of the Association for Compu-</i>	817
767	Kelsey MacMillan, Tyler C. Murray, Christopher	<i>tational Linguistics</i> , pages 4969–4983, Online. Asso-	818
768	Newell, Smriti R Rao, Shaurya Rohatgi, Paul Sayre,	ciation for Computational Linguistics.	819
769	Zejiang Shen, Amanpreet Singh, Luca Soldaini, Shiv-		
770	ashankar Subramanian, A. Tanaka, Alex D Wade,	J.J. Louviere, T.N. Flynn, and A.A.J. Marley. 2015.	820
771	Linda M. Wagner, Lucy Lu Wang, Christopher Wil-	<i>Best-Worst Scaling: Theory, Methods and Applica-</i>	821
772	helm, Caroline Wu, Jiangjiang Yang, Angele Zamar-	<i>tions</i> . Cambridge books online. Cambridge Univer-	822
773	ron, Madeleine van Zuylen, and Daniel S. Weld. 2023.	sity Press.	823
		Rahul Nadkarni, David Wadden, Iz Beltagy, Noah A.	824
		Smith, Hannaneh Hajishirzi, and Tom Hope. 2021.	825
		Scientific language models for biomedical knowl-	826
		edge base completion: An empirical study. <i>ArXiv</i> ,	827
		abs/2106.09700.	828

829	OpenAI. 2023. GPT-4 technical report . <i>CoRR</i> , abs/2303.08774.	886
830		887
831	Plato, G.R.F. Ferrari, and T. Griffith. 2000. <i>Plato: 'The Republic'</i> . Cambridge Texts in the History of Political Thought. Cambridge University Press.	888
832		889
833		890
834	Biqing Qi, Kaiyan Zhang, Haoxiang Li, Kai Tian, Si-	891
835	hang Zeng, Zhang-Ren Chen, and Bowen Zhou. 2023.	892
836	Large language models are zero shot hypothesis pro-	
837	posers . <i>ArXiv</i> , abs/2311.05965.	
838	Bernardino Romera-Paredes, Mohammadamin	893
839	Barekatin, Alexander Novikov, Matej Balog,	894
840	M Pawan Kumar, Emilien Dupont, Francisco J. R.	895
841	Ruiz, Jordan S. Ellenberg, Pengming Wang, Omar	896
842	Fawzi, Pushmeet Kohli, Alhussein Fawzi, Josh	897
843	Grochow, Andrea Lodi, Jean-Baptiste Mouret, Talia	898
844	Ringer, and Tao Yu. 2023. Mathematical discoveries	899
845	from program search with large language models .	
846	<i>Nature</i> , 625:468 – 475.	
847	Serhad Sarica, Binyang Song, Jianxi Luo, and Kristin L.	900
848	Wood. 2021. Idea generation with technology seman-	901
849	tic network . <i>Artificial Intelligence for Engineering</i>	902
850	<i>Design, Analysis and Manufacturing</i> , 35:265 – 283.	903
851	Sami Sarsa, Paul Denny, Arto Hellas, and Juho	
852	Leinonen. 2022. Automatic generation of program-	904
853	ming exercises and code explanations using large	905
854	language models . In <i>ICER 2022: ACM Conference</i>	906
855	<i>on International Computing Education Research,</i>	907
856	<i>Lugano and Virtual Event, Switzerland, August 7</i>	
857	<i>- 11, 2022, Volume 1</i> , pages 27–43. ACM.	
858	W. Scott Spangler, Angela D. Wilkins, Benjamin J.	908
859	Bachman, Meena Nagarajan, Tajhal Dayaram, Pe-	909
860	ter J. Haas, Sam Regenbogen, Curtis R. Pickering,	910
861	Austin Comer, Jeffrey N. Myers, Ioana Stanoi, Linda	911
862	Kato, Ana Lelescu, Jacques J. Labrie, Neha Parikh,	912
863	Andreas Martin Lisewski, Lawrence A. Donehower,	913
864	Ying Chen, and Olivier Lichtarge. 2014. Automated	914
865	hypothesis generation based on mining scientific lit-	
866	erature . In <i>The 20th ACM SIGKDD International</i>	
867	<i>Conference on Knowledge Discovery and Data Min-</i>	
868	<i>ing, KDD '14, New York, NY, USA - August 24 - 27,</i>	
869	<i>2014</i> , pages 1877–1886. ACM.	
870	Vahe Tshitoyan, John Dagdelen, Leigh Weston, Alexan-	
871	der Dunn, Ziqin Rong, Olga Kononova, Kristin A.	
872	Persson, Gerbrand Ceder, and Anubhav Jain. 2019.	
873	Unsupervised word embeddings capture latent knowl-	
874	edge from materials science literature . <i>Nat.</i> ,	
875	571(7763):95–98.	
876	Qingyun Wang, Doug Downey, Heng Ji, and Tom Hope.	
877	2023. Scimon: Scientific inspiration machines opti-	
878	mized for novelty. <i>arXiv preprint arXiv:2305.14259</i> .	
879	Qingyun Wang, Lifu Huang, Zhiying Jiang, Kevin	
880	Knight, Heng Ji, Mohit Bansal, and Yi Luan. 2019.	
881	PaperRobot: Incremental draft generation of scien-	
882	tific ideas . In <i>Proceedings of the 57th Annual Meet-</i>	
883	<i>ing of the Association for Computational Linguistics,</i>	
884	<i>pages 1980–1991, Florence, Italy. Association for</i>	
885	<i>Computational Linguistics.</i>	
	Jason Wei, Maarten Bosma, Vincent Y. Zhao, Kelvin	
	Guu, Adams Wei Yu, Brian Lester, Nan Du, An-	
	drew M. Dai, and Quoc V. Le. 2022. Finetuned	
	language models are zero-shot learners . In <i>The Tenth</i>	
	<i>International Conference on Learning Representa-</i>	
	<i>tions, ICLR 2022, Virtual Event, April 25-29, 2022.</i>	
	OpenReview.net.	
	Yi Xu, Shuqian Sheng, Bo Xue, Luoyi Fu, Xinbing	
	Wang, and Chenghu Zhou. 2023. Exploring and	
	verbalizing academic ideas by concept co-occurrence .	
	In <i>Proceedings of the 61st Annual Meeting of the</i>	
	<i>Association for Computational Linguistics (Volume 1:</i>	
	<i>Long Papers)</i> , pages 13001–13027, Toronto, Canada.	
	Association for Computational Linguistics.	
	Shunyu Yao, Jeffrey Zhao, Dian Yu, Nan Du, Izhak	
	Shafran, Karthik Narasimhan, and Yuan Cao. 2022.	
	React: Synergizing reasoning and acting in language	
	models. <i>arXiv preprint arXiv:2210.03629</i> .	
	Tianyi Zhang*, Varsha Kishore*, Felix Wu*, Kilian Q.	
	Weinberger, and Yoav Artzi. 2020. Bertscore: Eval-	
	uating text generation with bert . In <i>International</i>	
	<i>Conference on Learning Representations.</i>	
	Wayne Xin Zhao, Kun Zhou, Junyi Li, Tianyi Tang,	
	Xiaolei Wang, Yupeng Hou, Yingqian Min, Beichen	
	Zhang, Junjie Zhang, Zican Dong, Yifan Du, Chen	
	Yang, Yushuo Chen, Z. Chen, Jinhao Jiang, Ruiyang	
	Ren, Yifan Li, Xinyu Tang, Zikang Liu, Peiyu Liu,	
	Jiayun Nie, and Ji rong Wen. 2023. A survey of	
	large language models . <i>ArXiv</i> , abs/2303.18223.	

Frequently Asked Questions (FAQs)

- **How does our work differ from Scimon?**

⇒ Our paper is fundamentally different from the Scimon paper. We would like to highlight a few major differences. While the focus of Scimon is on developing a framework that generates novel scientific ideas, we clarify that our focus is not on generating ideas but on evaluating the capability of LLMs to generate future research ideas/works. We proposed the novel Idea Alignment Score (IAScore) and the Idea Distinctness Index. Unlike Scimon, we approached authors who are knowledgeable about their paper topics and the broader literature (see Section 4.4). Scimon used only GPT for comparison, while we used GPT-4, GPT-3.5, Claude, and Gemini models. Unlike Scimon, we provide the full paper as input. Scimon used the proposed idea written in the abstract as the target, while we used the future work section written in the full paper as our target. Additionally, they utilized a classifier for this purpose, whereas we employed human evaluators, resulting in fewer chances of error and better evaluation results. Our findings are completely different from those of Scimon. We created a novel annotated dataset for these experiments. While Scimon only experimented with computer science papers from the ACL Anthology, we expanded our experiments to five different domains. Scimon generated ideas guided by seed terms to generate specific ideas. Nonetheless, our goal here is to assess the inherent ability of LLMs to generate future work independently. Introducing external aids or additional context would shift the focus from evaluating the LLM’s standalone capabilities to assessing its performance under enhanced conditions. Such an approach would not align with our objective, which is to understand and measure the raw, unaided generative power of LLMs.

- **Does incorporating extra contextual information alongside individual papers prove counter-productive?**

⇒ A paper encompasses not only its contributions, findings, and methodology, but also includes the related work and introduction sections, which contain significant background information. It is likely that the major recent related papers pertinent to the current work have already been mentioned. Additionally, LLMs possess general knowledge about the many older papers and the paper itself contains some of the most important related papers. However, we also conducted an experiment to understand the effect of adding additional information (using the RAG framework). We discuss the results and details in Appendix E of the paper. Overall, we observed that incorporating additional background knowledge can somewhat help prevent the generation of non-novel or generic ideas. However, further research is needed to enhance the ability of LLMs to generate more novel ideas.

- **What it means to combine old elements to get new element?**

⇒ “old elements” is LLMs possess general knowledge about related older papers (“old elements”) and the paper itself contains main recent related papers information. A paper encompasses not only its contributions, findings, and methodology, but also includes the related work and introduction sections, which contain significant background information. Additionally, LLMs possess general knowledge about related older papers (“old elements”) and paper itself contains major recent related papers. As the purpose of our paper is to evaluate the capacity of LLMs to generate ideas (“new combinations”), we did not include any additional information to assist them. However, we also conducted an experiment to understand the effect of adding additional background information (using the RAG framework).

A Dataset Annotation

A.1 Dataset Annotation Guidelines

Recognizing future research idea in a paper involves analyzing the portion of text containing directions for future research. The following steps can be followed:

Step 1: Begin by reading the Title and Abstract of the paper to gain an understanding of its subject matter. It is important to read these sections multiple times to grasp the paper’s main points, such as its motivation, contributions, and other relevant aspects. If necessary, refer to the paper itself or read related material to enhance your understanding.

Step 2: Identify Key Sections for Analysis Focus primarily on the Discussion and Conclusion sections of the paper, as these areas often contain explicit mentions of future research directions. Scan the Methodology section as well, as sometimes suggestions for improving future studies or addressing current study limitations are mentioned here.

Step 3: Distinguish Future Research Ideas from General Statements: Differentiate explicit future research suggestions from general discussion. Future research directions usually involve specific recommendations, plans, or identified gaps that require further exploration. These are often phrased using terms like "future studies should," "further research is needed," or "additional work will." Avoid confusing these with broader statements of potential relevance or applicability, which do not provide direct guidance on future work.

We offer multiple examples of papers with its future research ideas to assist and direct the annotators. We found a few text which looks like future work but is on contrary the motivation of the work. As an example, consider the following: *"The goal of this work was to direct attention to emerging and novel research involving "magnetogel nanohybrid materials" that might be relevant in future applications for the treatment of wastewater, as well as in other fields.*

The second example is: *"Our data could be useful for designing high-quality trials in the future to define the exact role of hemoabsorption in ARDS."* Here, how novel research involving magnetogel nanohybrid material will help in future application is written.

Also another example is: *"The goal of this work was to direct attention to emerging and novel research involving magnetogel nanohybrid materials that might be relevant in future applications for the*

treatment of wastewater, as well as in other fields." This is the application in future, and not the future work.

Step 4: Separate Future Research from Limitations: Carefully examine any limitations mentioned in the paper to determine if they are explicitly linked to future research. Only consider a limitation as future work if the authors clearly indicate a direct intention to address it in subsequent studies. This helps avoid assuming that all limitations naturally lead to future research directions.

There is also very thin line between limitation and future work, where a limitation can or cannot be a future work. There were few cases where limitations were mentioned *"One limitation of this paper is the absence of a coordinated attention structure to capture cross-channel information."* As limitations can or cannot be a future work, we only take those limitations which is explicitly mentioned by the author to be a future work. Hence, we only considered the explicit mention of the future work by the author in their paper.

A.2 Annotator Training

Given the complexity of the papers and their frequent use of technical terminology, we hired two doctoral students, each boasting over four years of experience in scientific research publishing. To facilitate their training, an expert with more than ten years of experience in scientific publishing annotated 20 random papers from each domain, adhering to our guidelines. After this initial round of annotation, we reviewed and corrected any misinterpretations with the annotators, further refining their training and enhancing the clarity of our annotation guidelines. To assess the effectiveness of the initial training, we compiled another 20 papers from each domain. From the second round onwards, the annotators demonstrated improved proficiency, accurately identifying at least 95% of the future research ideas on average.

A.3 Annotation Process

We regularly monitored the annotated data, placing emphasis on identifying and rectifying inconsistencies and cases of confusion. We also implemented an iterative feedback system that continuously aimed to refine and improve the annotation process. In cases of conflict or confusion, we removed those papers as we wanted only good quality dataset. Following the annotation phase, we obtained an average inter-annotator agreement




Figure 7: An example for FRI editing; Here the strike through text is removed from the paper text

score of 0.94 using Cohen’s kappa (Cohen, 1960), indicating a substantial consensus among the annotators.

A.4 Annotator’s Pay

We compensated each annotator according to the standard PhD salaries in India, based on the hours they worked. The appointment and salaries adhere to our university’s established practices. Payment was made per paper since the time required to read and extract future research ideas from each paper varies, depending on its complexity, technical terminology, and the annotator’s familiarity with the subject. Thus, paying based on time spent could have potentially compromised the quality of the annotations. To maintain accuracy and prevent fatigue, we imposed a daily limit of six hours for annotators.

A.5 Detailed Dataset Statistics

Figure 2a provides a domain-wise distribution of the average word count in academic papers, excluding discussions on future work (FWK). It can be observed that the length of papers across all fields falls within a range of 7,000 to 8,000 words. Additionally, we calculated the average word count of extracted future work within each domain, providing comparative insights into how different fields prioritize discussions of future research directions. Figure 2b compares the average word count of future work text across six distinct scholarly domains. We observed that the literature in Computer Science notably prioritizes extensive discourse on future research, with an average word count significantly higher than that of other disciplines. In contrast, the literature in Chemistry demonstrates a more concise approach to discussions of future research, as evidenced by its lower average word count.

B Human Annotation

We prepared a Google Form for each paper and provided the links to the annotators. We also specified instructions for them at the beginning of the form. We have added an example of the form for a paper in Figure 9, Figure 10, and Figure 11.

Here is the little modified from for human evaluation that generates only top 5 research ideas:-

System: You are a research scientist.

User: Imagine you are a research scientist. After reading the following paper, brainstorm to generate potential top 5 future research ideas:

[paper text]

Potential top 5 future research ideas from the paper in bullet points are:

Here, ‘[paper text]’ contains the full content of the paper after removal of future work sections.

C Effect of giving only Title and Abstract as Input

We found a few cases where we provided only an title and abstract as input to see if LLMs can still retain open-ended generation capabilities. We discovered few cases where GPT-4 still generated novel ideas, such as for a paper (Kumar et al., 2023b) it generated: *"Incorporate explainable AI methods to provide transparency into how the AI model makes its predictions, thereby making the outcomes more interpretable and acceptable to human editors."*. This kind of analysis has not been done yet and could be helpful. After providing full paper content to the model we found that same idea was again generated.

There were also cases where GPT-4 generated a novel idea of solving the problem using transformers for a task (The task was mostly solved using techniques like RNN), which had not been done before. However, after providing the full paper content, the model understood that this transformer has already been implemented for this task, so further suggested to add more contextual information to it to boost the result (limited information was given as input to the paper). Overall, we found that LLMs can still retain open-ended generation because it has past knowledge. But it may not generate many good ideas since it doesn’t have access to recently

published papers or other methodological findings related to the current paper.

D Effect of Length of Idea on IAScore

In our analysis, we explore the relationship between the length of ideas and their corresponding Impact Assessment Score (IAScore), specifically focusing on computer science papers and outputs generated by GPT-4. This relationship is visually represented in the bar chart found in Appendix Figure 8. The data reveal that shorter ideas, typically under 20 words, tend to receive lower IAScores. This could be attributed to their lack of detailed information, which might be essential for a comprehensive understanding and assessment. Conversely, we observe that ideas spanning 40-60 words also tend to score lower. This may result from their verbosity; excessive information can dilute the core message, making it challenging to discern the main points. Interestingly, ideas with a moderate length, ranging from 20 to 40 words, achieve the highest IAScores. This length seems optimal as it allows for sufficient detail without overwhelming the reader, striking a balance that facilitates clearer understanding.




Figure 8: Effect of length on IAScore

E Effect of Adding Additional Background Knowledge

We designed our framework based on the Retrieval-Augmented Generation (RAG) model (Lewis et al., 2020) to integrate background knowledge into LLMs, as illustrated in Figure 6.

E.1 Vector Database

We utilized the Semantic Scholar API (Kinney et al., 2023) to collect the titles and abstracts of approximately 1.9 lakh existing computer science research papers. We employed BERT embeddings to

create vector representations for the titles of these papers, which were then stored in a vector database.

E.2 Retriever

To retrieve relevant papers, we created embeddings for the title of the paper for which we have to generate ideas. We computed the cosine similarity between this paper title embedding and those from our vector database. We then retrieved the top 20 research papers that exhibited the highest similarity to our target paper title. Finally, we extracted the contributions from these papers to gather relevant data from their abstracts.

We used the following prompt to instruct LLM to extract useful information from abstract of the paper:

System: You are a helpful research agent that generates background knowledge or related works given abstracts of papers.

User: You are given abstracts of research papers and your task is to extract contributions or findings or methods proposed in the paper. You are not allowed to make any changes to data given to you. Return the response as it is and return response for all 20 papers in passage. Return title of paper followed by its contributions or findings or methods in less than 100 words. If no contributions or findings or methods are found, return NONE.

PASSAGE: '{relevant_passage}'

Potential top 5 future research ideas from the paper in bullet points are:

We designed the above query prompt to ensure that the LLM¹⁰ understood its role in extracting relevant information without altering the provided information.

E.3 Generator

Next we produced the ideas using a prompt that includes the prompt using the paper and the retrieved background knowledge.

Specifically we used the below prompt for our task:-

¹⁰We employed Gemini-Pro model for this task

System: You are a research scientist.

User: Imagine you are a research scientist.

- 1) Read the full paper and understand it.
- 2) Find out the related works in this direction
- 3) Brainstorm and follow a step-by-step reasoning approach to generate to potential future research ideas:

[paper text] [background knowledge]

Make sure the future research ideas are very distinct from the background knowledge provided. Potential top 5 future research ideas from the paper in bullet points are:

Here, '[paper text]' contains the full content of the paper after removal of future work sections. '[background knowledge]' contains the background knowledge retrieved. An example of background knowledge is shown in Appendix Table 6.

We performed this experiment on the same set of papers and conducted human evaluations for novelty following the same methodology as we discussed in Section 4.6. The results are shown in Figure 5. Initially, we observed that adding background knowledge affected the LLM's performance; it primarily generated ideas that already existed, merely creating new combinations from the background knowledge. Subsequently, we modified the prompt to instruct the model not to repeat ideas that were mentioned in the background knowledge.

We found that adding background slightly improved the task. The results show that the improvements for GPT-4 and Claude were 50% and 53.33%, respectively, in reducing the generation of non-novel ideas. Also, it resulted in the improvement of 7.14% and 11.76% not generating generic ideas of GPT-4 and Claude. We observed that GPT-4 generated 9.52% and 14.63% more moderately novel ideas. However, we noted only a very slight improvement in the generation of highly novel or extremely novel ideas.

The analysis revealed that 73.71% of the ideas generated by Claude and 93.34% by GPT-4 were relevant. We observed that the relevance score for Claude decreased by 2.96%, and GPT-4 increased by a slight 0.77%. Furthermore, 83.14% of Claude's generated ideas and 96.98% of GPT-4's ideas were judged to be practically feasible and factually correct. The score for Claude decreased

by 0.20%, and the score for GPT-4 increased by 0.34%. It seems that additional information negatively impacts Claude's performance by generating ideas that are irrelevant, non-novel, and infeasible. However, for GPT-4, we observed that incorporating additional background knowledge helps prevent the generation of non-novel or generic ideas and slightly improves the relevance and factual correctness of the generated ideas. However, further research is needed to enhance the ability of LLMs to generate more novel ideas.

F BERTScore Implementation Details

The motivation to use BERT embeddings is that the generated and the original ideas often do not use the same words, so we need to understand the contextual meanings of the ideas in order to compare them. We used the default setting of the BERTScore metric, which employs a 24-layer RoBERTa-large model and utilizes the 17th layer for embedding. We determined the threshold¹¹ using the validation set. If the similarity exceeds that threshold, we classify those pairs of ideas as similar, and vice versa.

G Error Analysis:

We conducted human evaluation using three expert annotators, each with over five years of experience in this field. They reviewed 15 papers. We assigned papers to each reviewer based on their familiarity with the subject matter of the papers. We identified two major reasons for the low IAS score:

- Generic Ideas: Few ideas such as "*Explore different explainability methods like LIME, SHAP to generate model explanations instead of just rationales. Compare their effectiveness.*", *Building on the baseline model, future research could explore more advanced natural language processing (NLP) models and techniques for contradiction detection.* are generated. These statements are true; however, they are very generic and are common.
- Author Miss: Due to page limits or more novel ideas, the author fails to mention a few ideas in a paper. For example, for a paper (Kumar et al., 2023a) GPT-4 generated idea: "*Exploring the Impact of Contradictions on Review*

¹¹We set the threshold 0.68 empirically

Outcomes: An interesting area for future research would be to study the impact of reviewer contradictions on the outcomes of the peer review process. This could involve analyzing the correlation between the presence and nature of contradictions and the final decisions made by editors (acceptance, rejection, major/minor revisions). Such studies could provide valuable insights into how contradictions influence the decision-making process and how they might be effectively managed to improve the fairness and quality of peer review." This represents a strong, novel research problem not mentioned by the authors, which warrants future investigation

H Direct FRI and Mixed FRI

- **Direct FRI:** When the sentences that mention future research idea only contains future research idea. For example *"In future work, we plan to extend our approach to other code-mixed languages and evaluate its performance on more NLP tasks."*
- **Mixed FRI:** We found that sometimes research papers articulate future research ideas along with other essential information of the paper in a single sentence. For example in Figure 7, this sentence not only summarizes the current research findings but also clearly outlines a direction for future work.

I Output Examples

Our LLM generated future research output can be found in Table 1, Table 2, Table 3, Table 4 and Table 5.

Please read the research idea carefully and select the appropriate response.

We explain each questions below:-

Q1: *Is the idea relevant with the research topic of the paper. (Relevant/Not relevant)*

- **Not Relevant:** If the idea seems unrelated to the research topic of the paper.
- **Relevant:** If the idea aligns with the research topic of the paper.

Q2: *Assess the originality/novelty of the research idea. (Not Novel/Novel)*

- **Not Novel:** If you believe the idea is generic or already exists.
- **Slightly novel:** The idea is somewhat generic
- **Moderately novel:** This is a promising research direction but has already been explored by a significant number of researchers.
- **Very novel:** The idea represents a good research direction and has been pursued by only a few researchers.
- **Extremely novel:** The idea is highly innovative and, to my knowledge, has not been explored by anyone.

Q3: *Review the research idea for factual correctness and feasibility. Is the idea impractical or too vague to be actionable? (Not Possible/Possible)*

- **Not Possible:** If you feel that the idea is impractical/doesn't make any sense/ not realistic
- **Possible:** If you believe the idea is practical and realistic.

Figure 9: Instructions on Human Feedback form

Future Work 4: Add lexical constraints during decoding to prevent minimal word changes. This could enforce more semantic changes for style transfer.

Future Work 5: Evaluate the model on other styles like formality, gender, political slant etc. This could test the generalizability of the approach to other text style transfer tasks.

	Not novel	Slightly novel: The idea is somewhat generic	Moderately novel: This is a promising research direction but has already been explored by a significant number of researchers.	Very novel: The idea represents a good research direction and has been pursued by only a few researchers.	Extremely novel: The idea is highly innovative and, to my knowledge, has not been explored by anyone.
Future Work 1	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>
Future Work 2	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>
Future Work 3	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>
Future Work 4	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>
Future Work 5	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>

Figure 10: Human Feedback form for novelty

	Relevant	Possible
Future Work 1	<input type="checkbox"/>	<input type="checkbox"/>
Future Work 2	<input type="checkbox"/>	<input type="checkbox"/>
Future Work 3	<input type="checkbox"/>	<input type="checkbox"/>
Future Work 4	<input type="checkbox"/>	<input type="checkbox"/>
Future Work 5	<input type="checkbox"/>	<input type="checkbox"/>

Figure 11: Human Feedback form for relevance, feasibility

Model	Response
Claude-2	<ol style="list-style-type: none"> 1. Investigate the antioxidant and oil-stabilizing effects of peptides from the soy protein hydrolysates. The paper showed the pepsin hydrolysate had better activity, likely due to its peptide composition. Specific peptides could be isolated and tested for their antioxidant effects in oil. 2. Study the effects of the soy protein hydrolysates on the quality and shelf life of the fried food. This paper focused only on the oil stability. It would be useful to also assess how the hydrolysates affect lipid oxidation, texture, color etc. in the fried banana chips. 3. Evaluate the antioxidant effects of the soy protein hydrolysates in other vegetable oils such as sunflower, canola, corn oil etc. during frying. Since oil composition affects stability, the effects may differ in other oils high in polyunsaturated fatty acids. 4. Examine the impacts of frying parameters such as temperature, food type, frying time etc. on the efficacy of the soy protein hydrolysates. Varying these factors could provide insights into the optimal conditions for the hydrolysates to exert antioxidant effects. 5. Study the sensory qualities of fried foods with the soy protein hydrolysate additions. An analysis of taste, aroma, color acceptability by consumers would provide important information for potential commercial use of the hydrolysates as natural antioxidants.
Gemini-1.0	<ol style="list-style-type: none"> 1. Investigate the effects of different hydrolysis conditions on the antioxidant activity of soy protein hydrolysates. This could involve varying the enzyme concentration, temperature, and pH of the hydrolysis reaction. 2. Identify the specific peptides in the pepsin hydrolysate that are responsible for its antioxidant activity. This could be done using mass spectrometry and other analytical techniques. 3. Test the antioxidant activity of soy protein hydrolysates in other food systems. This could include using them to stabilize other types of oils or to protect food products from oxidation. 4. Investigate the potential health benefits of soy protein hydrolysates. This could include studying their effects on oxidative stress, inflammation, and other chronic diseases. 5. Develop new food products that incorporate soy protein hydrolysates as antioxidants. This could include developing new types of oil-based products, such as salad dressings and mayonnaise, as well as new types of food products, such as fortified cereals and snacks.
GPT-4	<ol style="list-style-type: none"> 1. Exploration of Peptide Sequences and Amino Acid Compositions for Enhanced Oxidative Stability: Investigate the specific peptide sequences and amino acid compositions derived from different proteases besides trypsin and pepsin to understand their contribution to the oxidative stability of oils. This could involve using a variety of proteolytic enzymes to hydrolyze soy proteins and other plant-based proteins, followed by an analysis of their peptide profiles and antioxidant activities in oil and food systems. 2. Application of Soy Protein Hydrolysates in Various Food Systems: Extend the application of soy protein hydrolysates to other food systems beyond frying oils, such as baked goods, dairy products, and meat alternatives, to assess their potential in improving oxidative stability, shelf-life, and nutritional profiles. This could involve comparative studies of hydrolysate effectiveness in different food matrices and processing conditions. 3. Mechanistic Studies on the Antioxidant Action of Hydrolysates: Conduct in-depth mechanistic studies to understand how soy protein hydrolysates interact with lipid molecules and radical species at the molecular level. This could involve computational modeling and in vitro experiments to explore the dynamics of peptide-lipid interactions and the role of specific amino acids in scavenging free radicals and metal ions. 4. Development of Environmentally Friendly and Health-focused Antioxidants: Given the interest in replacing synthetic antioxidants with natural alternatives, further research could focus on optimizing the production, purification, and application of soy protein hydrolysates as natural antioxidants. This could include exploring sustainable extraction methods, evaluating the safety and efficacy of hydrolysates in food systems, and assessing consumer acceptance. 5. Comparative Analysis of Hydrolysates from Different Oilseed Proteins: Since the study focused on soy proteins, future research could explore the antioxidative potential of hydrolysates derived from other oilseed proteins, such as sunflower, canola, or hemp. This would involve a comparative analysis of their antioxidative activities, peptide compositions, and effectiveness in enhancing the oxidative stability of different types of oils and fats used in food processing and storage.
GPT-3.5	<ol style="list-style-type: none"> 1. Investigate the impact of different proteases on the antioxidant properties of soy protein hydrolysates in stabilizing oils during frying cycles. 2. Study the influence of peptide size and amino acid composition on the oxidative stability of oils when treated with protein hydrolysates. 3. Explore the potential of specific amino acids, such as tryptophan, histidine, and methionine, in enhancing the antioxidant activity of hydrolyzed soy proteins in frying oils. 4. Examine the effects of pH adjustments during enzymatic hydrolysis on the antioxidant performance of soy protein hydrolysates. 5. Evaluate the long-term stability and effectiveness of pepsin and trypsin hydrolyzed soy protein in preventing oil oxidation in different frying conditions over extended periods.

Table 1: Example of generated response for chemistry domain. Paper: <https://www.ncbi.nlm.nih.gov/pmc/articles/PMC10528889/pdf/foods-12-03498.pdf>

Model	Response
Claude-2	<ol style="list-style-type: none"> 1. Investigate other machine learning models like recurrent neural networks for multi-round transfer learning in lung cancer detection. The paper focused on convolutional neural networks, but RNNs may capture temporal patterns in medical imaging data. 2. Explore different loss functions and regularization techniques to further minimize negative transfer. The paper proposed custom loss functions, but there is room to experiment with other formulations. 3. Evaluate the multi-round transfer learning approach on diverse medical imaging datasets beyond lung cancer, such as brain MRI scans. This could demonstrate the generalizability of the method. 4. Develop more advanced generative models like CycleGAN to synthesize intermediate domains between source and target. This could create higher quality bridging distributions. 5. Perform multi-round transfer learning in a low-data regime by leveraging data augmentation and semi-supervised learning techniques. This could show the approach is viable when target data is extremely scarce.
Gemini-1.0	<ol style="list-style-type: none"> 1. Investigate the impact of different prioritization algorithms on the performance of MTL-MGAN. The paper uses a hybrid approach that merges modified 2D dynamic warping (M2DW) and Silhouette coefficient to prioritize source domains. Future research could explore other prioritization algorithms, such as mutual information, transfer entropy, or graph-based methods, to determine if they can further improve the performance of MTL-MGAN. 2. Develop new loss functions to minimize negative transfer.** The paper proposes loss functions that are designed to minimize negative transfer in the aspects of domains, instances, and features. Future research could investigate other loss functions that can further reduce negative transfer, such as adversarial loss, maximum mean discrepancy, or knowledge distillation. 3. Explore different architectures for the MGAN.** The paper uses a modified GAN (MGAN) to create two intermediate domains as bridges between the source domain and the target domain. Future research could explore other GAN architectures, such as deep convolutional GAN (DCGAN), Wasserstein GAN (WGAN), or StyleGAN, to determine if they can further improve the performance of MTL-MGAN. 4. Apply MTL-MGAN to other medical diagnosis tasks.** The paper evaluates the performance of MTL-MGAN on 10 benchmark datasets related to lung cancer detection. Future research could apply MTL-MGAN to other medical diagnosis tasks, such as breast cancer detection, skin cancer detection, or diabetic retinopathy detection, to determine its generalizability. 5. Investigate the use of MTL-MGAN for other types of data.** The paper applies MTL-MGAN to medical images. Future research could investigate the use of MTL-MGAN for other types of data, such as text, audio, or time series data, to determine its applicability to a wider range of problems.
GPT-4	<ol style="list-style-type: none"> 1. Extension to Other Forms of Cancer and Diseases: Investigating the applicability and effectiveness of the MTL-MGAN approach for the detection and diagnosis of other types of cancer, such as breast, prostate, or skin cancer, and potentially other diseases that have distinct imaging characteristics. This would involve adapting the transfer learning and MGAN components to handle different imaging modalities and disease signatures. 2. Real-Time Diagnostic Systems Development: Developing real-time, AI-driven diagnostic systems using the MTL-MGAN framework that can be integrated into clinical workflows. This could significantly reduce diagnosis times and improve patient outcomes by providing immediate, accurate diagnostic information during patient examinations or surgeries. 3. Integration with Electronic Nose Technology for Early Detection: Combining the MTL-MGAN approach with emerging technologies like electronic nose devices, which can detect volatile organic compounds associated with lung cancer from breath samples. Research could focus on creating a hybrid detection system that leverages imaging data and breath analysis for earlier detection of lung cancer. 4. Exploration of Unsupervised and Semi-supervised Learning Techniques: Given the challenge of obtaining large, annotated medical imaging datasets, exploring unsupervised and semi-supervised learning methods within the MTL-MGAN framework could be valuable. This might involve developing algorithms that can learn from unlabelled data or very small labelled datasets, potentially increasing the model's applicability in low-resource settings. 5. Improvement of Transfer Learning Techniques for Heterogeneous Data Sources: Investigating advanced transfer learning techniques that can effectively handle more significant variations between source and target domains, particularly when dealing with heterogeneous data sources. This research could include the development of novel algorithms for better domain adaptation and intermediate domain creation to facilitate the transfer of knowledge across diverse medical datasets and imaging modalities.
GPT-3.5	<ol style="list-style-type: none"> 1. Exploring Multiround Transfer Learning in other Healthcare Applications: Investigate the applicability of multiround transfer learning in various healthcare domains beyond lung cancer detection, such as cardiovascular disease diagnosis, diabetic retinopathy detection, or infectious disease prediction. 2. Advanced Loss Function Design for Negative Transfer Avoidance: Develop novel loss functions to further minimize the impact of negative transfer in transfer learning models by incorporating more sophisticated domain, instance, and feature-based penalties. 3. Enhanced Generative Adversarial Networks for Bridging Domain Gaps: Investigate the development of advanced generative adversarial networks that can create more effective intermediate domains to bridge the gap between diverse source and target domains in transfer learning scenarios. 4. Automated Prioritization Algorithm for Source Domains: Develop an automated algorithm that can dynamically prioritize source domains based on their similarities to the target domain, thereby enhancing the efficiency and accuracy of the transfer learning process. 5. Evaluation of MTL-MGAN in Real-World Clinical Settings: Conduct a comprehensive evaluation of the proposed multiround transfer learning and modified generative adversarial network algorithm in real-world clinical settings to assess its performance, scalability, and generalizability in diverse healthcare environments.

Table 2: Example of generated response for computer domain. Paper: <https://www.hindawi.com/journals/ijis/2023/6376275/>

Model	Response
Claude-2	<ol style="list-style-type: none"> 1. Conduct qualitative research through interviews or focus groups to understand the specific barriers and facilitators to COVID-19 vaccination uptake in different socioeconomic groups within a country. This could provide insights to inform targeted interventions. 2. Examine the impact of COVID-19 vaccination policies and public health messaging on vaccination uptake across socioeconomic groups. For example, study how vaccination requirements or incentives affect different populations. 3. Investigate strategies to improve global collaboration and coordination in vaccine distribution and access. Research equitable pricing models, technology transfers, and policies to balance local needs with global supply. 4. Develop mathematical models to forecast COVID-19 vaccination coverage over time under different policy scenarios. Simulate the impact on infection rates, healthcare burden, and emergence of new variants. 5. Conduct intervention studies to test the effectiveness of community-based participatory approaches in increasing COVID-19 vaccine acceptance among disadvantaged populations. Evaluate culturally-tailored messaging and outreach.
Gemini-1.0	<ol style="list-style-type: none"> 1. Investigate the impact of socioeconomic factors on vaccine hesitancy and refusal. This could be done through qualitative studies to understand the underlying reasons for vaccine hesitancy and refusal, and quantitative studies to examine the association between socioeconomic factors and vaccine uptake. 2. Examine the role of social networks and community engagement in promoting vaccination. This could involve studying the influence of social networks on vaccination decisions, and exploring the effectiveness of community-based interventions in increasing vaccination rates. 3. Assess the effectiveness of different strategies for addressing vaccine inequality. This could include evaluating the impact of financial incentives, targeted outreach programs, and mobile vaccination clinics on vaccination rates among underserved populations. 4. Develop and evaluate interventions to improve the equitable distribution of vaccines. ** This could involve working with governments and international organizations to develop policies and programs that ensure that vaccines are distributed fairly and equitably to all populations. 5. Conduct longitudinal studies to track the long-term impact of socioeconomic factors on vaccination rates. This could help to identify trends and patterns in vaccination uptake over time, and inform the development of policies and interventions to address persistent disparities.
GPT-4	<ol style="list-style-type: none"> 1. Impact of Vaccine Acceptance and Hesitancy on Socioeconomic Disparities: Investigate how vaccine acceptance and hesitancy, influenced by cultural, historical, and information dissemination factors, contribute to the observed socioeconomic disparities in vaccination rates. This research could further dissect how misinformation and trust in healthcare systems intersect with socioeconomic status to affect vaccine uptake. 2. Longitudinal Studies on the Evolution of Vaccine Inequality: Conduct longitudinal studies to track changes in vaccine inequality over time, particularly as new variants emerge and booster vaccinations become more common. This research would provide insights into how socioeconomic disparities in vaccination rates evolve with the pandemic's progression and the introduction of new vaccine technologies or strategies. 3. Role of International and Public-Private Partnerships in Addressing Vaccine Inequity: Explore the effectiveness of international collaborations and public-private partnerships in improving vaccine distribution equity. This study could examine case studies of successful collaborations and identify best practices for leveraging these partnerships to reduce disparities in vaccine access. 4. Comparative Analysis of Vaccination Strategies and Socioeconomic Impact: Compare the vaccination strategies of different countries or regions with similar socioeconomic profiles to identify what strategies are most effective in mitigating inequalities in vaccination rates. This research could include the role of mobile vaccination units, community engagement initiatives, and targeted communication strategies in improving vaccine uptake among disadvantaged populations. 5. Impact of Socioeconomic Factors on Post-Vaccination Outcomes: Investigate how socioeconomic factors influence outcomes after vaccination, such as breakthrough infection rates, severity of breakthrough cases, and long-term immunity. This research could help identify whether socioeconomic disparities persist even after vaccination and how these disparities can be addressed through booster doses, tailored public health strategies, and improved healthcare access.
GPT-3.5	<ol style="list-style-type: none"> 1. Investigating the Impact of Socioeconomic Factors on Access and Uptake of COVID-19 Booster Vaccines: A study could focus on analyzing how socioeconomic indicators, such as GDP, human development index, and corruption perception index, influence access to and acceptance of booster doses of COVID-19 vaccines. This research could help identify disparities in vaccine distribution and uptake among different population groups. 2. Comparative Analysis of Inequality in COVID-19 Vaccination Across Continents: Future research could compare and contrast the levels of inequality in COVID-19 vaccination across different continents, especially focusing on the factors contributing to variations in vaccination rates and disparities in vaccine distribution. This comparative analysis could provide valuable insights for designing targeted interventions to address global vaccine inequality. 3. Longitudinal Study on the Impact of Socioeconomic Factors on COVID-19 Vaccination: A longitudinal study could be conducted to track changes in vaccination rates over time and assess how socioeconomic factors impact the progress of COVID-19 vaccination campaigns. By analyzing trends and patterns, researchers could gain a deeper understanding of the evolving dynamics of vaccine distribution and uptake. 4. Exploring Public Perception and Vaccine Hesitancy Among Different Socioeconomic Groups: Future research could delve into public perceptions and attitudes towards COVID-19 vaccination among diverse socioeconomic groups, investigating factors such as education level, income, and access to healthcare. This study could help identify barriers to vaccination and inform targeted communication strategies to address vaccine hesitancy. 5. Evaluation of Intervention Strategies to Reduce Inequality in COVID-19 Vaccination: Researchers could conduct a study to evaluate the effectiveness of various intervention strategies aimed at reducing inequality in COVID-19 vaccination. By implementing targeted initiatives and measuring their impact on vaccine distribution and uptake, this research could provide evidence-based recommendations for policy interventions to promote equitable access to vaccines.

Table 3: Example of generated response for economics domain. Paper: <https://www.mdpi.com/2076-393X/11/7/1147>

Model	Response
Claude-2	<ol style="list-style-type: none"> 1. Further optimize the minimal active H2 relaxin analog B9-31 through additional amino acid substitutions and modifications to improve binding affinity and activity. 2. Explore alternative methods to induce helicity and stabilize the minimal H2 relaxin analogs, such as cyclization or incorporation of other helix-inducing amino acids. 3. Develop longer-acting analogs by modifying B9-31 with polyethylene glycol, albumin binding moieties, or other half-life extending strategies. 4. Test the in vivo efficacy of optimized minimal analogs in animal models of fibrosis, heart failure, and other conditions to assess therapeutic potential. 5. Design biased analogs to selectively activate certain signaling pathways downstream of RXFP1 to optimize beneficial effects and reduce side effects.
Gemini-1.0	<ol style="list-style-type: none"> 1. Investigate the potential benefits of using ECMO in combination with other therapies for severe respiratory failure. For example, ECMO could be used in combination with lung transplantation, mechanical ventilation, or extracorporeal membrane oxygenation (ECMO). This could help to improve patient outcomes by providing more comprehensive support for the lungs and other organs. 2. Develop new strategies for managing complications associated with ECMO. Common complications of ECMO include bleeding, infection, and thrombosis. New strategies for managing these complications could help to improve patient safety and outcomes. 3. Study the long-term effects of ECMO on patients. There is limited data on the long-term effects of ECMO on patients. Studies are needed to investigate the potential risks and benefits of ECMO in the long term. 4. Develop new technologies to improve the performance of ECMO. New technologies could help to make ECMO more effective, safer, and easier to use. For example, new oxygenators could be developed that are more efficient and less likely to cause complications. 5. Conduct research to better understand the mechanisms of respiratory failure. This could help to identify new targets for therapy and improve the overall management of respiratory failure.
GPT-4	<ol style="list-style-type: none"> 1. Comparative Effectiveness of ECMO Configurations: Conduct randomized controlled trials comparing different ECMO cannulation strategies (e.g., dual-lumen cannula via the right internal jugular vein vs. traditional multi-cannula approaches) to assess their impact on patient outcomes, including survival rates, complication rates, and the ability to mobilize and rehabilitate during ECMO support. This research could also explore the use of image guidance for cannula placement and its impact on patient outcomes. 2. ECMO in the Management of COVID-19-Induced ARDS: Given the limited randomized controlled trial data on the efficacy of ECMO for COVID-19-associated respiratory failure, further research is needed to define the role of ECMO in this context. Future studies could focus on identifying which patients benefit most from ECMO, the timing of initiation, and how ECMO is best integrated with other supportive therapies (e.g., antivirals, anti-inflammatory agents). 3. Long-term Outcomes and Quality of Life Post-ECMO: Investigate the long-term outcomes of patients who have undergone ECMO support for severe respiratory failure, including physical, cognitive, and psychological recovery. This research could also assess the quality-adjusted life years (QALYs) gained through ECMO support and identify factors that predict better long-term outcomes. 4. Optimization of Anticoagulation Strategies: Develop and test new anticoagulation protocols or agents that minimize the risks of bleeding and thrombotic complications in ECMO patients. This could include comparative studies of direct thrombin inhibitors versus unfractionated heparin, as well as the exploration of novel anticoagulants and biocompatible circuit coatings that may reduce the need for systemic anticoagulation. 5. Integration of ECMO with Rehabilitation: Explore the feasibility, safety, and benefits of early rehabilitation protocols in ECMO-supported patients, including those on "awake ECMO." This research could assess the impact of rehabilitation on outcomes such as muscle strength, functional status at discharge, duration of hospital stay, and overall mortality. Studies could also investigate the best practices for physical therapy, nutritional support, and psychological support during ECMO.
GPT-3.5	<ol style="list-style-type: none"> 1. Investigating the long-term outcomes and quality of life of patients who have undergone VV-ECMO support for respiratory failure, including factors influencing long-term recovery and rehabilitation post-ECMO. 2. Exploring new technologies and techniques to improve the efficiency and safety of VV-ECMO, such as developing novel anticoagulation strategies or improving cannulation methods to reduce complications and enhance patient outcomes. 3. Conducting comparative studies to evaluate the effectiveness of different ventilation strategies in conjunction with VV-ECMO support, aiming to optimize patient management and potentially improve survival rates in severe respiratory failure cases. 4. Examining the impact of ECMO utilization during disease outbreaks, such as COVID-19, on healthcare resource allocation, patient outcomes, and healthcare system preparedness, to inform future pandemic response strategies. 5. Investigating the role of personalized medicine in VV-ECMO patient selection and management, including the potential use of biomarkers, genetic profiling, or other advanced techniques to tailor ECMO therapy to individual patient characteristics and optimize outcomes.

Table 4: Example of generated response for medical domain. Paper: <https://link.springer.com/article/10.1007/s41030-023-00214-2>

Model	Response
Claude-2	<ol style="list-style-type: none"> 1. Investigate the antioxidant and oil-stabilizing effects of specific peptide sequences identified in the pepsin and trypsin hydrolysates. The paper showed the pepsin hydrolysate had higher activity but did not identify the key active peptides. Bioinformatics could be used to predict promising peptides. 2. Test the soy protein hydrolysates in stabilizing other vegetable oils like canola, sunflower, etc. during deep frying. The effects may differ for oils with varying fatty acid compositions. 3. Evaluate the sensory qualities of foods fried in palm olein stabilized with the soy protein hydrolysates compared to unstabilized oil. This could include assessing odor, taste, and textural changes. 4. Study the effects of the hydrolysates on the nutritional quality of the palm olein during repeated deep frying cycles. Parameters could include vitamin E content, formation of trans fats, and retention of essential fatty acids. 5. Investigate combining the soy protein hydrolysates with other antioxidants like rosemary extract or green tea to evaluate synergistic effects on stabilizing frying oils. Mixtures may provide greater protection than individual additives.
Gemini-1.0	<ol style="list-style-type: none"> 1. Investigate the effect of different hydrolysis conditions on the antioxidant activity of soy protein hydrolysates. This could involve varying the enzyme concentration, temperature, pH, and hydrolysis time to determine the optimal conditions for producing hydrolysates with the highest antioxidant activity. 2. Evaluate the antioxidant activity of soy protein hydrolysates in different food systems. This could involve adding hydrolysates to edible oils, fried foods, or other food products and measuring the oxidative stability of the products over time. This would help to determine the potential applications of soy protein hydrolysates as natural antioxidants in food products. 3. Study the mechanism by which soy protein hydrolysates exert their antioxidant activity.** This could involve using in vitro and in vivo assays to investigate the ability of hydrolysates to scavenge free radicals, chelate metal ions, or inhibit lipid peroxidation. This information would help to elucidate the molecular mechanisms underlying the antioxidant activity of soy protein hydrolysates. 4. Explore the potential health benefits of soy protein hydrolysates. This could involve conducting animal or human studies to investigate the effects of hydrolysates on oxidative stress, inflammation, and other health markers. This would help to determine the potential role of soy protein hydrolysates in promoting human health. 5. Develop novel food products containing soy protein hydrolysates. This could involve incorporating hydrolysates into functional foods, such as beverages, snacks, or supplements, to improve their nutritional value and antioxidant content. This would help to increase the consumption of soy protein hydrolysates and promote their potential health benefits.
GPT-4	<ol style="list-style-type: none"> 1. DComparative Analysis of Different Plant-Based Proteins on Oil Stability: Extending the research to other plant-based proteins, such as pea, hemp, and rice proteins, to compare their effectiveness in improving oil oxidative stability during frying cycles. This could provide a broader understanding of the potential of plant-based proteins in enhancing the nutritional and safety profiles of fried foods. 2. Mechanism of Action at Molecular Level: Delving deeper into the molecular mechanisms behind the antioxidant activities of different hydrolysates. This could involve investigating the interaction between specific peptide sequences and oxidative compounds within the oil, using computational modeling and in vitro experiments to elucidate the pathways for their antioxidant actions. 3. Impact of Hydrolysate Concentration and Frying Duration: Exploring the effect of varying concentrations of the most effective hydrolysates (e.g., from pepsin digestion) over extended frying cycles beyond 12, to determine the optimal concentration for maximum oxidative stability without affecting the sensory qualities of the oil and the fried product. 4. Application in Industrial Frying Processes: Conducting pilot-scale studies in industrial settings to assess the feasibility and economic viability of incorporating hydrolysates into commercial frying oils. This research could include the development of guidelines for the use of hydrolysates in different types of frying operations and their impact on the quality and shelf-life of fried foods. 5. Development of Natural Antioxidant Blends: Formulating blends of hydrolysates with other natural antioxidants (e.g., extracts from spices, herbs, or other food by-products rich in phenolic compounds) to synergistically enhance the oxidative stability of frying oils. This research could also investigate the sensory impact of these blends on fried products and consumer acceptance.
GPT-3.5	<ol style="list-style-type: none"> 1. Investigating the impact of different proteases on the generation of antioxidant peptides from soy protein hydrolysates and their effectiveness in stabilizing oils during frying cycles. 2. Exploring the structural features of peptides derived from soy protein hydrolysates to determine the key amino acids responsible for their antioxidant properties. 3. Comparing the oxidative stability of different types of oils (e.g., sesame oil, canola oil, corn oil) when stabilized with soy protein hydrolysates under varied frying conditions. 4. Examining the influence of hydrolyzed protein residues on the formation of secondary oxidation products in oils during frying cycles and their impact on food quality and safety. 5. Utilizing bioinformatics tools to predict and select specific peptide sequences from soy protein hydrolysates that exhibit the highest antioxidant capacity and stability-enhancing properties in fried oils..

Table 5: Example of generated response for physics domain. Paper: <https://www.ncbi.nlm.nih.gov/pmc/articles/PMC10528889/pdf/foods-12-03498.pdf>

<ol style="list-style-type: none"> 1. Test-time Adaptation of Discriminative Models via Diffusion Generative Feedback Adapts pre-trained discriminative models to each unlabelled example in the test set using generative feedback from a diffusion model. 2. Adaptive Discriminative Generative Model for Object Tracking Formulates a novel discriminative generative framework that generalizes the conventional Fisher Linear Discriminant algorithm with a generative model and renders a proper probabilistic interpretation. 3. Classification with Hybrid Generative/Discriminative Models Describes a hybrid model in which a high-dimensional subset of the parameters are trained to maximize generative likelihood, and another, small, subset of parameters are discriminatively trained to maximize conditional likelihood. 4. Discriminative Level Set for Contour Tracking Integrates discriminative methods into a level set framework when constructing the level set energy function. 5. ManiFPT Defining and Analyzing Fingerprints of Generative Models Formalizes the definition of artifact and fingerprint in generative models, proposes an algorithm for computing them in practice, and finally study its effectiveness in distinguishing a large array of different generative models. 6. Generative Models for 3D Point Clouds Experiments with transformer encoders, latent-space flow models, and autoregressive decoders to improve the performance of point cloud latent-space generative models. 7. Models and Modeling 8. Do text-free diffusion models learn discriminative visual representations? Explores the possibility of a unified representation learner, a diffusion model, which addresses both generative and discriminative tasks simultaneously. 9. Fine-Tuning Generative Models as an Inference Method for Robotic Tasks Investigates how to quickly adapt the sample generation of neural network models to observations in robotic tasks. 10. Discriminative locally document embedding Learning a smooth affine map by approximation of the probabilistic generative structure of subspace 11. Working with Deep Generative Models and Tabular Data Imputation Provides a fair comparison of proposed methods for imputing missing values in tabular data using deep generative models. 12. Robust Discriminative Principal Component Analysis 13. Generative Second Language Acquisition 14. Nonlinear Models 15. Understanding how Differentially Private Generative Models Spend their Privacy Budget Analyzes how DP generative models distribute privacy budgets across rows and columns of tabular data. 16. Online multiple object tracking by hierarchical association of detection responses Presents a framework for multi-pedestrian tracking using a hierarchical association of detection responses, learning both discriminative and generative appearance models online. 17. Two-Stage Generative Learning Objects 18. Generative design games activity 19. First vs second quantization 20. Non-discrimination Criteria for Generative Language Models Studies how to uncover and quantify the presence of gender biases in generative language models, deriving generative AI analogues of three well-known non-discrimination criteria from classification.
--

Table 6: Example of background knowledge of <https://ieeexplore.ieee.org/document/10191295>