

Enhancing Agentic Textual Graph Retrieval with Synthetic Stepwise Supervision

Anonymous ACL submission

Abstract

Integrating textual graphs into Large Language Models (LLMs) is promising for complex graph-based QA. However, a key bottleneck is retrieving informative yet compact subgraphs that fit the LLM context. Existing retrievers often struggle, relying either on shallow embedding similarity or costly interactive policies that require excessive supervision. To address these challenges, we introduce Graph-S³, an agentic textual graph reasoning framework featuring an LLM-based retriever trained with synthetic stepwise supervision. Rather than relying on final answer rewards—which often yield sparse and unstable signals—we optimize the retriever by evaluating each step against offline-extracted golden subgraphs. Our approach distills golden subgraphs via a specialized data synthesis pipeline to formulate dense rewards, facilitating a two-stage training scheme that effectively learns the interactive graph exploration policy. Based on extensive experiments on three common datasets in comparison with seven strong baselines, our approach achieves an average improvement of 8.1% in accuracy and 9.7% in F₁ score. The advantage is even higher in more complicated multi-hop reasoning tasks. Our code will be open-sourced.

1 Introduction

Textual graphs are widely employed for structured knowledge representation in domains like question answering and scientific discovery (Peng et al., 2024; Procko and Ochoa, 2024; Zhang et al., 2025a). By explicitly modeling multi-hop relations, they enable interpretable, compositional reasoning that is difficult to achieve with unstructured text (Chen et al., 2020; Hogan et al., 2021; Zou, 2020). While early methods were constrained by inflexible symbolic inference and high annotation costs (Yih et al., 2016), the semantic capabilities of Large Language Models (LLMs) have alleviated these limitations (Chang et al.,

2024; Su et al., 2025). Consequently, integrating LLMs with textual graphs has become a prominent paradigm for general-purpose graph understanding and QA (Lewis et al., 2020; Peng et al., 2024; Procko and Ochoa, 2024; Zhang et al., 2025a; Jin et al., 2024; Chai et al., 2023).

LLM agents accessing graphs via tool calls surpass simple retrieval (Jiang et al., 2024; Yang et al., 2024; Ji et al., 2024), as illustrated in Figure 1 where an agent iteratively collects information. However, training such agents via supervised fine-tuning (SFT) often collapses the action space, favoring memorization over generalizable policies (Chu et al., 2025; Li et al., 2024). While outcome-supervised reinforcement learning (RL) offers a potential solution by exploring reasoning trajectories (Lightman et al., 2023; Paolo et al., 2024), it faces significant hurdles in this domain: the action space in real-world textual graphs is often too vast for efficient exploration, and outcome-based rewards are sparse and noisy. For instance, redundant or erroneous retrieval steps may coincidentally lead to the correct final answer, rendering outcome supervision unreliable for assessing reasoning quality (Liu et al., 2023; Rengarajan et al., 2022).

To overcome this limitation, we introduce a synthetic stepwise supervision scheme that provides explicit feedback at every decision step, ensuring that the model is guided not only by the correctness of the final answer but also by the quality of intermediate actions. The key idea is to **guide each graph retrieval step with golden subgraphs offline extracted from the target graph**. Specifically, we propose an automated pipeline to construct the golden subgraphs for reward computation. We first generate a large amount of subgraph candidates through random and LLM-guided exploration, and filter the candidates based on **information sufficiency**, i.e. whether they are able to produce correct answers with LLMs. These successful exploratory trajectories are used for SFT,




Figure 1: An illustration of agentic textual graph retrieval and question answering.

084 providing the retriever with basic navigation abil-
 085 ity as a warm-up stage. Then we further refine
 086 the subgraphs to enhance **information conciseness**
 087 by iteratively pruning redundant content while pre-
 088 serving answer consistency. With these refined sub-
 089 graphs, each online graph retrieval action can be
 090 associated with an explicit stepwise reward based
 091 on its contribution to the golden subgraphs. The
 092 combined two-step training pipeline guides the re-
 093 triever to improve reasoning decisions over long
 094 action chains.

095 Extensive experiments have demonstrated the
 096 effectiveness of our synthetic stepwise supervi-
 097 sion approach. For example, while retrieving only
 098 11.44% of the triples, Graph-S³ achieves an aver-
 099 age improvement of 8.1% in accuracy and 9.7% in
 100 F₁ score across the WebQSP, CWQ, and MetaQA
 101 benchmarks.

102 In summary, the main contributions of this work
 103 are as follows:

104 (1) We propose an automatic pipeline for synthe-
 105 sizing high-quality stepwise supervision data for
 106 interactive graph retrieval, addressing the scarcity
 107 of fine-grained training signals in this field.

108 (2) We design a two-stage training paradigm
 109 tailored for graph reasoning: SFT on raw synthetic
 110 trajectories to bootstrap basic navigation ability,
 111 followed by RL with synthetic stepwise rewards
 112 on refined trajectories to provide explicit feedback
 113 and strengthen reasoning strategies.

114 (3) Experimental results demonstrate that Graph-
 115 S³ achieves state-of-the-art performance on the We-
 116 bQSP, CWQ, and MetaQA datasets with accurate
 117 and compact graph retrieval.

2 Related Work 118

2.1 Graph Retrieval Methods 119

120 Graph retrieval approaches include similarity-
 121 based, GNN-based, and LLM-based meth-
 122 ods (Peng et al., 2024; Procko and Ochoa, 2024;
 123 Zhang et al., 2025a; Zhu et al., 2025; Han et al.,
 124 2024), but most perform one-shot retrieval and of-
 125 ten return redundant or incomplete subgraphs. Re-
 126 cent interactive frameworks (Jiang et al., 2024; Ji
 127 et al., 2024; Yang et al., 2024) allow iterative ex-
 128 ploration, yet their training predominantly relies on
 129 imitation of language patterns or outcome-based su-
 130 pervision, which provides only coarse feedback and
 131 limits stable multi-hop reasoning. In contrast, our
 132 work employs RL with synthetic stepwise rewards
 133 and a scalable data synthesis pipeline to provide
 134 supervision for interactive retrieval.

2.2 Stepwise RL for Graph Reasoning 135

136 Recent advances such as OpenAI o1 and DeepSeek-
 137 R1 (Jaech et al., 2024; Guo et al., 2025) demon-
 138 strate the effectiveness of RL in strengthening
 139 multi-step reasoning, enabling models to perform
 140 longer chains of thought with improved reliabil-
 141 ity in domains like mathematics and program-
 142 ming (Guo et al., 2024a; El-Kishky et al., 2025).
 143 In contrast, applying RL to textual graphs remains
 144 limited, partly due to the lack of fine-grained su-
 145 pervision data (Zhang et al., 2025a; Yao et al., 2025;
 146 Liu et al., 2025). RL-based graph agents (Das et al.,
 147 2017; Cui et al., 2025) relied on sparse outcome re-
 148 wards, making credit assignment across reasoning
 149 trajectories difficult. Although recent efforts have
 150 introduced reasoning-structured datasets (Pahila-
 151 jani et al., 2024), high-quality stepwise supervision




Figure 2: An Overview of our data synthesis pipeline and training scheme.

for graph-based RL remains scarce and difficult to construct at scale. These observations highlight the need for scalable approaches that can provide fine-grained supervision signals and support stable optimization for interactive graph retrieval.

3 Method

We present our agentic retrieval framework, designed to equip large language models with robust graph reasoning capabilities through stepwise supervision, a two-stage training paradigm, and an interactive retrieval strategy. As illustrated in Figure 2, the framework comprises three main components. First, we construct an automatic data synthesis pipeline that leverages GPT-4o (OpenAI, 2024) to generate diverse exploratory trajectories, which are subsequently refined into high-quality stepwise supervision data. This addresses the scarcity of fine-grained training signals for graph-based RL. Second, we adopt a two-stage training paradigm: SFT on raw synthetic trajectories provides a warm-up initialization for basic graph navigation, while RL with synthetic stepwise rewards on refined trajectories supplies explicit feedback at each decision step, stabilizing optimization and strengthening reasoning strategies. Finally, during inference, the retriever operates under an interactive retrieval mechanism that conducts stepwise, structure-aware exploration of the textual graph, thereby reducing redundancy and mitigating incomplete retrieval.

3.1 Data Synthesis

Existing LLMs are not pretrained on graph-structured data (Zhang et al., 2025b), which significantly limits their performance on graph reasoning tasks. As a result, effective training requires high-quality supervision to cultivate graph comprehension and reasoning capabilities. However, constructing such datasets is notoriously expensive, since it often relies on manual annotation by domain experts (Choubey et al., 2024), leading to a persistent scarcity of high-quality graph reasoning data. To address this issue, we design a pipeline that automatically synthesizes graph reasoning trajectories. Specifically, we first define a set of actions that enable structured interaction with the graph. Then, we leverage GPT-4o to perform these actions and collect valid action–response pairs, which form exploratory trajectories. The raw trajectories are directly used for SFT to provide the model with basic navigation ability, while a refinement step prunes redundant detours and preserves all answer-consistent trajectories, producing high-quality stepwise supervision data for RL.

3.1.1 Action Space for Graph Exploration

Given a textual graph $\mathcal{G} = \{t_i\}_{i=1}^m$, where each triple $t_i = (e_h^i, r^i, e_t^i) \in \mathcal{E} \times \mathcal{R} \times \mathcal{E}$ consists of a head entity $e_h^i \in \mathcal{E}$, a relation $r^i \in \mathcal{R}$, and a tail entity $e_t^i \in \mathcal{E}$. Here, \mathcal{E} and \mathcal{R} denote the sets of entities and relations, respectively. To enable stepwise exploration over \mathcal{G} , we define the retriever’s action

space as consisting of three types of operations. For clarity, we use (x, r, y) to denote a generic triple in \mathcal{G} , where $x, y \in \mathcal{E}$ and $r \in \mathcal{R}$.

Explore Entity: This operation expands the local neighborhood of a given entity by retrieving all directly connected triples in \mathcal{G} . Formally, for a target entity $x \in \mathcal{E}$, the operation is defined as

$$\text{Explore}(x) = \{(x, r, y) | (x, r, y) \in \mathcal{G}^p\} \cup \{(y, r, x) | (y, r, x) \in \mathcal{G}^p\} \quad (1)$$

where $r \in \mathcal{R}$ and $y \in \mathcal{E}$ denote relations and neighboring entities, respectively. The retrieved triples are added to the perception window \mathcal{G}^p for subsequent reasoning steps.

Choose Relation: The perception window \mathcal{G}^p obtained from the EXPLORE action may still contain many irrelevant triples. To avoid introducing redundant context into the LLM, this operation prunes \mathcal{G}^p into a query-relevant subgraph \mathcal{G}^{sub} :

$$\text{Choose}(q, \mathcal{G}^p) = \{(x, r, y) \in \mathcal{G}^p | F(q, (x, r, y)) = 1\}. \quad (2)$$

Here, q is the query, (x, r, y) denotes a triple in \mathcal{G}^p , and $F(q, (x, r, y))$ is the relevance function learned by the retriever to decide whether the triple should be preserved. F outputs 1 if the triple is judged relevant to the query and 0 otherwise.

Finish: This operation indicates that the retriever has gathered sufficient evidence in the current subgraph \mathcal{G}^{sub} to answer the query q . Once invoked, the exploration process terminates, and (q, \mathcal{G}^{sub}) is used to produce the final answer:

$$\text{Finish}(q, \mathcal{G}^{sub}) = \text{Answer}(q, \mathcal{G}^{sub}), \quad (3)$$

where $\text{Answer}(q, \mathcal{G}^{sub})$ denotes answering query q based on the retrieved subgraph.

3.1.2 Graph Reasoning Data Synthesis

Given the defined action space, we synthesize reasoning trajectories by letting a behavior model (GPT-4o) interact with the graph. We formalize the generation process as a Markov decision process (MDP) with deterministic transitions defined by the graph action space. Each trajectory consists of multiple decision steps, and is later decomposed into step-level training instances for SFT and RL.

State. We define each state as a tuple of four components: $s_t = (q, \mathcal{G}_t^p, \mathcal{G}_t^{sub}, h_t)$, where q is the query, \mathcal{G}_t^p the perception window aggregated by EXPLORE, and \mathcal{G}_t^{sub} the focused subgraph maintained by CHOOSE, and $h_t = (a_1, \dots, a_{t-1})$ the

action history up to step t . Including h_t allows the retriever to condition its decisions not only on the current graph view but also on the reasoning trajectory already taken.

Action. The parameterized action space is \mathcal{A} , defined in 3.1.1. During the synthesis phase, the behavior model selects $a_t \in \mathcal{A}$ given s_t , and additionally produces a natural language reasoning trace that explains the choice of action.

Transition. The execution of action a_t triggers a state transition $s_t \rightarrow s_{t+1}$ by updating the action history $h_{t+1} \leftarrow h_t \cup \{a_t\}$ and modifying the graph components based on the action type. Specifically, if $a_t = \text{EXPLORE}(x_t)$, the agent expands the partial graph \mathcal{G}_t^p by merging it with the newly explored neighbors. If $a_t = \text{CHOOSE}$, the agent updates the subgraph \mathcal{G}_t^{sub} by filtering relevant triples from \mathcal{G}_t^p via the selection function. The episode terminates when $a_t = \text{FINISH}$ or the time step t reaches the maximum limit T_{\max} .

Answer and retention. Upon termination at step T , we produce an answer $\hat{y} = \text{Answer}(q, \mathcal{G}_T^{sub})$ and keep the trajectory $\tau = \{(s_t, a_t)\}_{t=1}^T$ only if \hat{y} matches the set of ground-truth answers. After that, we use the raw action labels for SFT dataset: $\mathcal{D}_{\text{SFT}} = \{(s_t, a_t)\}_{\tau, t}$. In the next subsection, we further refine trajectories to obtain stepwise supervision signals for RL.

3.1.3 Trajectory Refinement for RL

While SFT directly benefits from raw trajectories, RL requires more concise training signals (Yue et al., 2025). Filtering trajectories only by final answer correctness often produces redundant exploration steps, introducing noise and inefficiency during policy optimization. To address this, we introduce a refinement procedure that removes unnecessary detours while preserving all answer-consistent trajectories, thereby yielding shorter and cleaner trajectories for RL.

Let the set of retained raw trajectories be $\mathcal{T} = \{\tau_i\}_{i=1}^N$, where each $\tau_i = \{(s_t, a_t)\}_{t=1}^{T_i}$ is a sequence of state-action pairs terminating at step T_i . We define a refinement operator \mathcal{R} that maps the raw set \mathcal{T} into a refined set \mathcal{T}^* :

$$\mathcal{T}^* = \mathcal{R}(\mathcal{T}). \quad (4)$$

For each τ_i , the refinement identifies the shortest feasible subsequence τ_i^* that still leads to the same correct final answer:

$$\tau_i^* = \arg \min_{\tau \in \mathcal{F}_i} |\tau|, \quad (5)$$

where \mathcal{F}_i is the set of all feasible answer-consistent trajectories equivalent to τ_i . Let $s_T(\tau)$ denotes the final state and $y(\tau)$ denotes the answer.

$$\mathcal{F}_i = \{\tau \mid s_T(\tau) = s_T(\tau_i) \wedge y(\tau) = y(\tau_i)\}. \quad (6)$$

Thus, the refined dataset \mathcal{T}^* retains trajectories that are semantically equivalent to the originals but stripped of redundant exploration steps. Each refined trajectory τ_i^* is then decomposed into step-level supervision signals by attaching a rule-based stepwise reward $\ell_t \in [0, 1]$ to each action a_t , indicating its correctness within the reasoning trajectory. Formally, the RL training dataset is constructed as $\mathcal{D}_{\text{RL}} = \{(s_t, a_t, \ell_t)\}_{\tau_i^*, t}$. This ensures that RL receives concise stepwise supervision signals, improving both stability and efficiency of training.

3.2 Training Stage

To enhance the model’s graph comprehension and reasoning capabilities, we adopt a two-stage fine-tuning approach. The first stage uses SFT with synthesized data to establish foundational abilities. The second stage employs GRPO with trajectory refinement, leveraging RL’s proven effectiveness in enhancing reasoning and exploration efficiency (Yue et al., 2025).

3.2.1 Stage I: Supervised fine-tuning

For each step t , let $s_t = (q, \mathcal{G}_t^p, \mathcal{G}_t^{sub}, h_t)$ be the serialized state, and let $y_t = (y_t^1, \dots, y_t^{L_t})$ be the target token sequence that concatenates the natural-language thought process and the action specification. Denote by $\mathcal{I}(s_t)$ the textual serialization of the state. The training loss of SFT is defined as

$$\mathcal{L}_{\text{SFT}}(\theta) = -\mathbb{E}_{\substack{(s_t, y_t) \\ \sim \mathcal{D}_{\text{SFT}}}} \left[\sum_{l=1}^{L_t} \log \pi_{\theta}(y_t^l \mid \mathcal{I}(s_t), y_t^{<l}) \right]. \quad (7)$$

where $\pi_{\theta}(y_t^l \mid \mathcal{I}(s_t), y_t^{<l})$ denotes the probability assigned by the model to the l -th token given the serialized state and the previously generated tokens.

3.2.2 Stage II: RL with stepwise rewards

For reward design, existing approaches predominantly rely on outcome-based reward signals, which have demonstrated remarkable effectiveness in domains such as mathematical reasoning and code generation. However, prior studies (Wang et al., 2025; Choudhury, 2025; Deng et al., 2024) have shown that in relatively complex scenarios such as graph retrieval, conventional outcome-based reward signals tend to be overly sparse. This

sparsity hampers effective credit assignment to early-stage actions, ultimately resulting in inefficient learning over long action chains. This observation motivates our adoption of process-level rewards in the training process, where the reward signal is determined by the contribution of each current action to the golden subgraphs.

Specifically, each step t is associated with a process-level rule-based reward ℓ_t that provides graded feedback according to the quality of the predicted action:

$$\ell_t = \begin{cases} 0, & \text{if Inv}(a_t), \\ c_1, & \text{if Fmt}(a_t) = 1 \wedge \text{Corr}(a_t) = 0, \\ c_2, & \text{if Part}(a_t) = 1, \\ 1.0, & \text{if } a_t = a_t^*. \end{cases} \quad (8)$$

Here, $\text{Inv}(\cdot)$, $\text{Fmt}(\cdot)$, $\text{Corr}(\cdot)$, and $\text{Part}(\cdot)$ denote the deterministic functions for checking validity, format correctness, action correctness, and partial correctness, respectively. c_1 and c_2 are dataset-specific hyperparameters. Consequently, we adopt the reward function shown in Eq. 8 to train our model using the GRPO method.

3.3 Interactive Retriever

At inference time, Graph- S^3 interacts with the textual graph through the defined action space. Unlike single-pass retrieval methods that return large subgraphs, our approach performs stepwise exploration by balancing EXPLORE and CHOOSE actions, terminating with FINISH when sufficient evidence is gathered. This interactive process enables precise control over retrieval depth while minimizing redundancy, producing concise subgraphs for reasoning. The detailed prompts designed for the interactive graph retriever are provided in Appendix B. An example of interactive reasoning process of Graph- S^3 can be found in Appendix D.

4 Experiments

4.1 Experimental Setup

Datasets. We evaluate Graph- S^3 on three widely used textual graph QA benchmarks. WebQSP (Yih et al., 2015) consists of real-world questions annotated with SPARQL queries against Freebase, primarily involving one- or two-hop reasoning. CWQ (Talmor and Berant, 2018) extends WebQSP with more complex multi-hop questions, posing a greater challenge for long reasoning chains. MetaQA (Zhang et al., 2018) is a movie-domain

Retriever + Generator	WebQSP		CWQ		MetaQA 1-hop		MetaQA 2-hop		MetaQA 3-hop	
	Acc	F ₁	Acc	F ₁	Acc	F ₁	Acc	F ₁	Acc	F ₁
No graph + Qwen3-8B	5.16	8.11	6.26	7.35	2.00	2.88	0.07	0.95	0.20	1.19
No retriever + Qwen3-8B	0.25	1.83	0.37	1.29	0.00	0.29	0.00	0.49	0.00	1.25
RAG/1hop + Qwen3-8B	27.89	<u>38.57</u>	12.55	16.18	<u>75.93</u>	<u>86.36</u>	0.77	1.74	<u>4.13</u>	<u>11.99</u>
RAG/2hop + Qwen3-8B	14.07	24.47	7.00	10.55	42.03	55.59	10.07	21.65	2.60	9.42
RAG/3hop + Qwen3-8B	1.54	7.94	0.99	3.12	0.37	3.03	0.13	2.21	0.13	3.45
ToG + Qwen3-8B	6.14	9.79	7.01	9.61	1.37	1.75	0.00	0.00	0.00	0.20
LightRAG + Qwen3-8B	18.39	31.67	<u>16.20</u>	<u>23.09</u>	1.13	1.76	0.00	0.19	0.07	0.40
G-retriever + Qwen3-8B	25.74	35.45	15.38	18.62	0.63	1.60	0.10	0.77	0.03	1.87
KG-Agent + Qwen3-8B	<u>29.66</u>	<u>38.02</u>	15.64	22.45	75.80	85.92	<u>28.41</u>	<u>33.66</u>	4.07	10.89
Graph-S ³ + Qwen3-8B	36.24	47.88	17.87	23.29	81.50	90.22	53.73	65.60	12.73	29.49
No graph + Llama3.1-8B	8.97	15.69	9.40	11.58	12.20	17.60	1.27	7.77	1.23	8.86
No retriever + Llama3.1-8B	0.18	1.97	0.14	1.29	0.00	0.58	0.00	1.11	0.00	2.94
RAG/1hop + Llama3.1-8B	24.82	35.28	13.85	17.26	60.17	70.84	2.40	5.98	<u>4.03</u>	<u>15.46</u>
RAG/2hop + Llama3.1-8B	11.06	22.94	6.29	10.68	29.07	42.47	4.50	15.06	1.80	11.30
RAG/3hop + Llama3.1-8B	1.04	6.67	0.65	3.43	0.33	3.67	0.17	3.37	0.07	5.76
ToG + Llama3.1-8B	8.85	14.28	8.42	12.33	12.40	15.88	0.00	0.63	1.43	6.10
LightRAG + Llama3.1-8B	15.85	36.66	8.33	15.01	13.13	21.47	0.93	4.33	1.00	6.38
G-retriever + Llama3.1-8B	22.67	32.26	<u>13.91</u>	<u>17.47</u>	0.67	1.56	0.10	0.83	0.10	1.77
KG-Agent + Llama3.1-8B	<u>32.04</u>	<u>41.99</u>	10.82	13.75	<u>65.55</u>	<u>75.03</u>	<u>32.51</u>	<u>44.52</u>	3.85	8.29
Graph-S ³ + Llama3.1-8B	32.31	43.26	17.11	21.17	67.50	76.56	40.17	55.49	10.73	29.55
No graph + Finetuned-8B	9.21	14.88	10.17	12.31	1.63	2.49	0.43	2.64	0.33	4.60
No retriever + Finetuned-8B	0.37	2.26	0.68	1.76	0.00	0.29	0.00	0.34	0.00	1.05
RAG/1hop + Finetuned-8B	28.87	41.48	19.85	26.01	59.50	69.54	1.83	7.44	<u>3.30</u>	<u>18.61</u>
RAG/2hop + Finetuned-8B	14.93	27.76	8.89	14.56	35.83	52.03	7.70	21.21	3.07	14.04
RAG/3hop + Finetuned-8B	1.54	7.81	0.93	4.36	0.57	2.99	0.43	2.31	0.13	4.23
ToG + Finetuned-8B	5.04	9.43	7.54	9.79	2.23	3.44	0.00	0.12	0.10	2.80
LightRAG + Finetuned-8B	17.38	32.59	13.85	19.96	13.77	20.60	0.97	3.71	0.53	4.28
G-retriever + Finetuned-8B	30.34	43.49	<u>22.68</u>	<u>28.38</u>	8.93	11.51	2.33	4.80	0.40	3.31
KG-Agent + Finetuned-8B	<u>42.60</u>	<u>55.38</u>	13.77	16.29	<u>75.99</u>	<u>86.02</u>	<u>30.19</u>	<u>43.95</u>	2.64	7.20
Graph-S ³ + Finetuned-8B	44.29	58.45	23.62	30.44	82.77	92.04	63.17	76.18	14.70	36.29

Table 1: Overall results on graph-based QA benchmarks. The best results are highlighted in bold and the second performance results are indicated by an underscore.

benchmark containing 135k triples and 43k entities, designed to evaluate multi-hop reasoning in a closed domain. Following prior work (Chen et al., 2024), we report accuracy (Acc) and F₁ score as evaluation metrics.

Baselines. To validate the effectiveness of our approach, we compare with several representative graph retrieval methods. We additionally evaluate the model’s inherent graph understanding capability through two configurations: (1) the *no graph* setting, where the model processes the query without any graph input, and (2) the *no retriever* setting, where the model receives the entire graph structure directly as input.

For traditional RAG, we implemented a multi-hop method where the model retrieves the most relevant graph nodes for the current query and then

performs a k-hop expansion to collect information for answer generation. We further compare with representative graph retrievers, including Think-on-Graph (ToG) (Sun et al., 2023), LightRAG (Guo et al., 2024b), G-Retriever (He et al., 2024) and agentic graph retrieval system KG-Agent (Jiang et al., 2024).

Implementation Details are provided in the Appendix A.

4.2 Main Results

The results of WebQSP, CWQ, and MetaQA are summarized in Table 1. In general, our framework achieves the best performance among all compared methods, demonstrating the effectiveness of combining two-stage training with interactive retrieval. We break down the analysis into several key obser-

429 vations.

430 **Superiority in Complex Multi-hop Reasoning.** Graph- S^3 exhibits a widening performance gap
431 over baselines as reasoning complexity increases. On the MetaQA benchmark, while competitive on
432 1-hop questions, our method dominates on multi-hop tasks. Specifically, on MetaQA 3-hop, Graph- S^3
433 significantly outperforming the next best agentic baseline and far surpassing traditional k -hop
434 RAG methods which struggle to maintain coherence over long chains.

440 **Effectiveness Against Training-Free Baselines.** Against sophisticated training-free baselines like
441 ToG and LightRAG, our model delivers substantial gains across all datasets. This highlights that while
442 LLM-based planning (ToG) or structural awareness (LightRAG) is beneficial, it is insufficient without
443 the dedicated fine-tuning and reinforcement learning provided by our pipeline to align the retriever
444 with graph-specific reasoning patterns.

449 **Advantage Over Trained Retrievers.** Compared to supervised retrievers like G-Retriever
450 and agentic frameworks like KG-Agent, Graph- S^3 consistently achieves higher F_1 scores, indicat-
451 ing better precision in answer generation. This improvement suggests that our interactive prun-
452 ing mechanism effectively balances recall and precision—retrieving enough context to answer cor-
453 rectly without overwhelming the generator with noise, a common pitfall for G-Retriever which re-
454 trieves larger, noisier subgraphs.

460 **Robustness Across Backbones.** The performance gains are consistent across different LLM
461 backbones and fine-tuning strategies. Notably, even when using a fine-tuned backbone, Graph- S^3 main-
462 tains its lead, achieving the highest scores on all benchmarks. This demonstrates that our method’s
463 benefits are orthogonal to the underlying model’s capability and can serve as a universal enhance-
464 ment for graph-based QA systems.

469 To gain deeper insights into the quantitative improvements, we analyzed specific reasoning exam-
470 ples to verify the effectiveness of our interactive pruning and stepwise supervision. A detailed pre-
471 sentation of these case studies and the corresponding reasoning processes of Graph- S^3 can be found
472 in Appendix C.

4.3 In-depth Analysis 476

4.3.1 Ablation Study 477

Our framework consists of four key components: supervised fine-tuning (SFT), reinforcement learn-
478 ing (RL) with stepwise rewards, interactive retrieval at inference time, and trajectory refinement
479 during data synthesis. To assess the contribution of each component, we remove one module at a time
480 and evaluate the resulting performance degradation. The results are reported in Table 2.

Ablation of SFT. Removing the SFT stage leads to a clear drop in Accuracy and F_1 across all bench-
481 marks. This confirms that SFT provides the retriever with essential navigation ability, compensat-
482 ing for the lack of graph-specific training during upstream pretraining and establishing a stable founda-
483 tion for subsequent RL optimization.

Ablation of RL. Eliminating the RL stage results in consistent performance degradation, with
484 particularly large declines on CWQ and MetaQA, which require longer reasoning chains. This demon-
485 strates that RL with stepwise rewards substantially strengthens the retriever’s reasoning capability, es-
486 pecially on complex multi-hop tasks.

Ablation of interactive inference. Disabling interactive retrieval causes significant performance
487 drops on 2-hop and 3-hop questions, where results approach those of conventional k -hop RAG. This
488 shows that interactive retrieval is crucial for adaptively controlling retrieval depth, effectively filter-
489 ing redundant neighbors while preserving critical relations.

Ablation of trajectory refinement. Removing trajectory refinement during data synthesis leads to
490 the largest degradation among all ablations. The results indicate that without refinement, synthetic tra-
491 jectories contain redundant detours, which produce noisy reward signals and undermine the stability of
492 RL optimization.

4.3.2 Effectiveness of Stepwise Supervision 515

To further validate the effectiveness of our proposed stepwise supervision, we conducted an ab-
493 lation study. Specifically, starting from the SFT-trained model, we ablated the stepwise reward
494 signals and modified the setup to rely solely on outcome-based rewards. The results of this ablation
495 study are shown in Table 3. Experimental results indicate that without stepwise rewards, model per-
496 formance experiences a significant decline across all benchmarks, particularly on CWQ and MetaQA

Methods of Ablation	Dataset									
	WebQSP		CWQ		MetaQA					
					1hop		2hop		3hop	
	Acc	F ₁	Acc	F ₁	Acc	F ₁	Acc	F ₁	Acc	F ₁
Graph-S³	44.29	58.45	23.62	30.44	82.77	92.04	63.17	76.18	14.70	36.29
w/o SFT	31.64	44.41	7.74	8.77	81.27	89.38	46.30	54.12	2.07	4.98
w/o RL	41.77	53.02	13.39	15.97	71.97	80.09	35.93	45.25	5.73	11.46
w/o interactive	28.87	41.48	19.85	26.01	59.50	69.54	1.83	7.44	3.30	18.61
w/o traj. refine	16.46	19.24	4.12	4.87	39.47	41.06	4.01	6.10	1.34	1.80

Table 2: Results of ablation studies.

Retriever Train Method	Dataset									
	WebQSP		CWQ		MetaQA					
					1hop		2hop		3hop	
	Acc	F ₁	Acc	F ₁	Acc	F ₁	Acc	F ₁	Acc	F ₁
w/o step supervision	41.83	53.87	13.47	16.40	72.63	81.12	34.97	45.14	6.43	11.34
Graph-S³	44.29	58.45	23.62	30.44	82.77	92.04	63.17	76.18	14.70	36.29

Table 3: Performance comparison of process-level rewards and outcome-based rewards training methods.




Figure 3: Number of retrieved graph triples in Graph-S³ and baselines on correct answers.

which involve longer reasoning chains. This confirms that fine-grained stepwise supervision enables more stable optimization and better generalization on complex multi-hop reasoning tasks.

4.3.3 Effective Information Quantification Analysis

To evaluate the efficiency of Graph-S³ in retrieving concise yet effective information, we compare it with baseline approaches by measuring the number of triples required to produce correct answers (see Figure 3). Unlike traditional methods that often retrieve large amounts of redundant information, our approach significantly reduces retrieval size while maintaining higher accuracy. In particular,

our experiments show that Graph-S³ requires only **11.44%** of the triples retrieved by G-Retriever on average, yet still achieves superior accuracy. These results highlight the framework’s ability to balance search depth with precision, thereby reducing redundancy.

5 Conclusion

We investigated the limitations of existing retrieval-augmented generation methods on textual graphs, highlighting their reliance on outcome-based supervision and their tendency to produce redundant or incomplete subgraphs. To overcome these challenges, we proposed a framework that integrates three key innovations:

- (1) A pipeline for high-quality, stepwise-supervised data synthesis;
 - (2) Two-stage training (SFT then RL) with process-level rewards;
 - (3) Fine-grained, interactive retrieval over textual graphs.
- Extensive experiments on WebQSP, CWQ, and MetaQA demonstrate that our approach consistently improves both accuracy and F_1 , validating the effectiveness of synthetic stepwise supervision and the proposed training strategy for enhancing interactive graph retrieval. These findings underscore the potential of fine-grained process supervision in bridging the gap between LLMs and structured knowledge, paving the way for more reliable and interpretable agentic reasoning systems.

6 Limitation

While this work has focused on validating GraphS³ on standard textual graph benchmarks, future research could explore extending the interactive retrieval framework to diverse problem scenarios. Additionally, with the rapid advancement of agent technology, the current framework can be further enhanced by designing a broader spectrum of actions and integrating external tools to tackle increasingly complex reasoning tasks.

References

- Ziwei Chai, Tianjie Zhang, Liang Wu, Kaiqiao Han, Xiaohai Hu, Xuanwen Huang, and Yang Yang. 2023. Graphllm: Boosting graph reasoning ability of large language model. *arXiv preprint arXiv:2310.05845*.
- Yupeng Chang, Xu Wang, Jindong Wang, Yuan Wu, Linyi Yang, Kaijie Zhu, Hao Chen, Xiaoyuan Yi, Cunxiang Wang, Yidong Wang, and 1 others. 2024. A survey on evaluation of large language models. *ACM transactions on intelligent systems and technology*, 15(3):1–45.
- Weijie Chen, Ting Bai, Jinbo Su, Jian Luan, Wei Liu, and Chuan Shi. 2024. Kg-retriever: Efficient knowledge indexing for retrieval-augmented large language models. *arXiv preprint arXiv:2412.05547*.
- Xiaojun Chen, Shengbin Jia, and Yang Xiang. 2020. A review: Knowledge reasoning over knowledge graph. *Expert systems with applications*, 141:112948.
- Prafulla Kumar Choubey, Xin Su, Man Luo, Xiangyu Peng, Caiming Xiong, Tiej Le, Shachar Rosenman, Vasudev Lal, Phil Mui, Ricky Ho, and 1 others. 2024. Distill-synthkg: Distilling knowledge graph synthesis workflow for improved coverage and efficiency. *arXiv preprint arXiv:2410.16597*.
- Sanjiban Choudhury. 2025. Process reward models for llm agents: Practical framework and directions. *arXiv preprint arXiv:2502.10325*.
- Tianzhe Chu, Yuexiang Zhai, Jihan Yang, Shengbang Tong, Saining Xie, Dale Schuurmans, Quoc V Le, Sergey Levine, and Yi Ma. 2025. Sft memorizes, rl generalizes: A comparative study of foundation model post-training. *arXiv preprint arXiv:2501.17161*.
- Ganqu Cui, Lifan Yuan, Zefan Wang, Hanbin Wang, Wendi Li, Bingxiang He, Yuchen Fan, Tianyu Yu, Qixin Xu, Weize Chen, and 1 others. 2025. Process reinforcement through implicit rewards. *arXiv preprint arXiv:2502.01456*.
- Rajarshi Das, Shehzaad Dhuliawala, Manzil Zaheer, Luke Vilnis, Ishan Durugkar, Akshay Krishnamurthy, Alex Smola, and Andrew McCallum. 2017. Go for a walk and arrive at the answer: Reasoning over

- paths in knowledge bases using reinforcement learning. *arXiv preprint arXiv:1711.05851*.
- Zhirui Deng, Zhicheng Dou, Yutao Zhu, Ji-Rong Wen, Ruibin Xiong, Mang Wang, and Weipeng Chen. 2024. From novice to expert: Llm agent policy optimization via step-wise reinforcement learning. *arXiv preprint arXiv:2411.03817*.
- Abhimanyu Dubey, Abhinav Jauhri, Abhinav Pandey, Abhishek Kadian, Ahmad Al-Dahle, Aiesha Letman, Akhil Mathur, Alan Schelten, Amy Yang, Angela Fan, and 1 others. 2024. The llama 3 herd of models. *arXiv e-prints*, pages arXiv–2407.
- Ahmed El-Kishky, Alexander Wei, Andre Saraiva, Borys Minaiev, Daniel Selsam, David Dohan, Francis Song, Hunter Lightman, Ignasi Clavera, Jakub Pachocki, and 1 others. 2025. Competitive programming with large reasoning models. *arXiv preprint arXiv:2502.06807*.
- Daya Guo, Dejian Yang, Haowei Zhang, Junxiao Song, Ruoyu Zhang, Runxin Xu, Qihao Zhu, Shirong Ma, Peiyi Wang, Xiao Bi, and 1 others. 2025. Deepseek-r1: Incentivizing reasoning capability in llms via reinforcement learning. *arXiv preprint arXiv:2501.12948*.
- Daya Guo, Qihao Zhu, Dejian Yang, Zhenda Xie, Kai Dong, Wentao Zhang, Guanting Chen, Xiao Bi, Yu Wu, YK Li, and 1 others. 2024a. Deepseek-coder: When the large language model meets programming—the rise of code intelligence. *arXiv preprint arXiv:2401.14196*.
- Zirui Guo, Lianghao Xia, Yanhua Yu, Tu Ao, and Chao Huang. 2024b. Lightrag: Simple and fast retrieval-augmented generation. *arXiv preprint arXiv:2410.05779*.
- Haoyu Han, Yu Wang, Harry Shomer, Kai Guo, Jiayuan Ding, Yongjia Lei, Mahantesh Halappanavar, Ryan A Rossi, Subhabrata Mukherjee, Xianfeng Tang, and 1 others. 2024. Retrieval-augmented generation with graphs (graphrag). *arXiv preprint arXiv:2501.00309*.
- Xiaoxin He, Yijun Tian, Yifei Sun, Nitesh Chawla, Thomas Laurent, Yann LeCun, Xavier Bresson, and Bryan Hooi. 2024. G-retriever: Retrieval-augmented generation for textual graph understanding and question answering. *Advances in Neural Information Processing Systems*, 37:132876–132907.
- Aidan Hogan, Eva Blomqvist, Michael Cochez, Claudia d’Amato, Gerard De Melo, Claudio Gutierrez, Sabrina Kirrane, José Emilio Labra Gayo, Roberto Navigli, Sebastian Neumaier, and 1 others. 2021. Knowledge graphs. *ACM Computing Surveys (Csur)*, 54(4):1–37.
- Aaron Jaech, Adam Kalai, Adam Lerer, Adam Richardson, Ahmed El-Kishky, Aiden Low, Alec Helyar, Aleksander Madry, Alex Beutel, Alex Carney, and 1 others. 2024. Openai o1 system card. *arXiv preprint arXiv:2412.16720*.

676	Yixin Ji, Kaixin Wu, Juntao Li, Wei Chen, Mingjie Zhong, Xu Jia, and Min Zhang. 2024. Retrieval and reasoning on kgs: Integrate knowledge graphs into large language models for complex question answering. In <i>Findings of the Association for Computational Linguistics: EMNLP 2024</i> , pages 7598–7610.	733
677		734
678		735
679		736
680		
681		
682	Jinhao Jiang, Kun Zhou, Wayne Xin Zhao, Yang Song, Chen Zhu, Hengshu Zhu, and Ji-Rong Wen. 2024. Kg-agent: An efficient autonomous agent framework for complex reasoning over knowledge graph. <i>arXiv preprint arXiv:2402.11163</i> .	737
683		738
684		739
685		740
686		741
687	Bowen Jin, Gang Liu, Chi Han, Meng Jiang, Heng Ji, and Jiawei Han. 2024. Large language models on graphs: A comprehensive survey. <i>IEEE Transactions on Knowledge and Data Engineering</i> .	742
688		743
689		744
690		745
691		746
692	Patrick Lewis, Ethan Perez, Aleksandra Piktus, Fabio Petroni, Vladimir Karpukhin, Naman Goyal, Heinrich Küttler, Mike Lewis, Wen-tau Yih, Tim Rocktäschel, and 1 others. 2020. Retrieval-augmented generation for knowledge-intensive nlp tasks. <i>Advances in neural information processing systems</i> , 33:9459–9474.	747
693		748
694		749
695		750
696		751
697		752
698	Ziniu Li, Congliang Chen, Tian Xu, Zeyu Qin, Jiancong Xiao, Ruoyu Sun, and Zhi-Quan Luo. 2024. Entropic distribution matching for supervised fine-tuning of llms: Less overfitting and better diversity. In <i>NeurIPS 2024 Workshop on Fine-Tuning in Modern Machine Learning: Principles and Scalability</i> .	753
699		754
700		755
701		756
702		757
703		758
704	Hunter Lightman, Vineet Kosaraju, Yuri Burda, Harrison Edwards, Bowen Baker, Teddy Lee, Jan Leike, John Schulman, Ilya Sutskever, and Karl Cobbe. 2023. Let’s verify step by step. In <i>The Twelfth International Conference on Learning Representations</i> .	759
705		760
706		761
707		
708		
709	Boyin Liu, Zhiqiang Pu, Yi Pan, Jianqiang Yi, Yanyan Liang, and Du Zhang. 2023. Lazy agents: A new perspective on solving sparse reward problem in multi-agent reinforcement learning. In <i>International Conference on Machine Learning</i> , pages 21937–21950. PMLR.	762
710		763
711		764
712		765
713		
714		
715	Han Liu, Shaojie Yang, Guokai Shi, and Zongcheng Miao. 2025. Knowledge graph reasoning: Mainstream methods, applications and prospects . <i>Engineering Applications of Artificial Intelligence</i> , 159:111625.	766
716		767
717		768
718		769
719		770
720	OpenAI. 2024. Gpt-4o system card. OpenAI Technical documentation. Available online: https://openai.com/index/gpt-4o-system-card/ .	771
721		772
722		773
723	Anish Pahilajani, Devasha Trivedi, Jincen Shuai, Khin S Yone, Samyak Rajesh Jain, Namyong Park, Ryan A Rossi, Nesreen K Ahmed, Franck Dernoncourt, and Yu Wang. 2024. Grs-qa-graph reasoning-structured question answering dataset. <i>arXiv preprint arXiv:2411.00369</i> .	774
724		775
725		776
726		777
727		778
728		779
729	Giuseppe Paolo, Miranda Coninx, Alban Lafflaquière, and Stephane Doncieux. 2024. Discovering and exploiting sparse rewards in a learned behavior space. <i>Evolutionary Computation</i> , 32(3):275–305.	780
730		781
731		782
732		783
		784
		785
		786
	Boci Peng, Yun Zhu, Yongchao Liu, Xiaohe Bo, Haizhou Shi, Chuntao Hong, Yan Zhang, and Siliang Tang. 2024. Graph retrieval-augmented generation: A survey. <i>arXiv preprint arXiv:2408.08921</i> .	
	Tyler Thomas Procko and Omar Ochoa. 2024. Graph retrieval-augmented generation for large language models: A survey. In <i>2024 Conference on AI, Science, Engineering, and Technology (AIXSET)</i> , pages 166–169. IEEE.	
	Desik Rengarajan, Gargi Vaidya, Akshay Sarvesh, Dileep Kalathil, and Srinivas Shakkottai. 2022. Reinforcement learning with sparse rewards using guidance from offline demonstration. <i>arXiv preprint arXiv:2202.04628</i> .	
	Jinbo Su, Lingzhe Gao, Wei Li, Shihao Liu, Haojie Lei, Xinyi Wang, Yuanzhao Guo, Ke Wang, Daiting Shi, and Dawei Yin. 2025. Racqc: Advanced retrieval-augmented generation for chinese query correction. In <i>Findings of the Association for Computational Linguistics: EMNLP 2025</i> , pages 675–689.	
	Jiashuo Sun, Chengjin Xu, Lumingyuan Tang, Saizhuo Wang, Chen Lin, Yeyun Gong, Lionel M Ni, Heung-Yeung Shum, and Jian Guo. 2023. Think-on-graph: Deep and responsible reasoning of large language model on knowledge graph. <i>arXiv preprint arXiv:2307.07697</i> .	
	Alon Talmor and Jonathan Berant. 2018. The web as a knowledge-base for answering complex questions. <i>arXiv preprint arXiv:1803.06643</i> .	
	Hanlin Wang, Chak Tou Leong, Jiashuo Wang, Jian Wang, and Wenjie Li. 2025. Spa-rl: Reinforcing llm agents via stepwise progress attribution. <i>arXiv preprint arXiv:2505.20732</i> .	
	An Yang, Anfeng Li, Baosong Yang, Beichen Zhang, Binyuan Hui, Bo Zheng, Bowen Yu, Chang Gao, Chengen Huang, Chenxu Lv, and 1 others. 2025. Qwen3 technical report. <i>arXiv preprint arXiv:2505.09388</i> .	
	Yuhao Yang, Jiabin Tang, Lianghao Xia, Xingchen Zou, Yuxuan Liang, and Chao Huang. 2024. Graphagent: Agentic graph language assistant. <i>arXiv preprint arXiv:2412.17029</i> .	
	Tianjun Yao, Haoxuan Li, Zhiqiang Shen, Pan Li, Tongliang Liu, and Kun Zhang. 2025. Learning efficient and generalizable graph retriever for knowledge-graph question answering. <i>arXiv preprint arXiv:2506.09645</i> .	
	Scott Wen-tau Yih, Ming-Wei Chang, Xiaodong He, and Jianfeng Gao. 2015. Semantic parsing via staged query graph generation: Question answering with knowledge base. In <i>Proceedings of the Joint Conference of the 53rd Annual Meeting of the ACL and the 7th International Joint Conference on Natural Language Processing of the AFNLP</i> .	

787 Wen-tau Yih, Matthew Richardson, Christopher Meek,
788 Ming-Wei Chang, and Jina Suh. 2016. The value of
789 semantic parse labeling for knowledge base question
790 answering. In *Proceedings of the 54th Annual Meet-*
791 *ing of the Association for Computational Linguistics*
792 *(Volume 2: Short Papers)*, pages 201–206.

793 Yang Yue, Zhiqi Chen, Rui Lu, Andrew Zhao, Zhaokai
794 Wang, Shiji Song, and Gao Huang. 2025. Does re-
795 inforcement learning really incentivize reasoning ca-
796 pacity in llms beyond the base model? *arXiv preprint*
797 *arXiv:2504.13837*.

798 Qinggang Zhang, Shengyuan Chen, Yuanchen Bei,
799 Zheng Yuan, Huachi Zhou, Zijin Hong, Junnan Dong,
800 Hao Chen, Yi Chang, and Xiao Huang. 2025a. A
801 survey of graph retrieval-augmented generation for
802 customized large language models. *arXiv preprint*
803 *arXiv:2501.13958*.

804 Yi-Fan Zhang, Xingyu Lu, Xiao Hu, Chaoyou Fu,
805 Bin Wen, Tianke Zhang, Changyi Liu, Kaiyu Jiang,
806 Kaibing Chen, Kaiyu Tang, and 1 others. 2025b.
807 R1-reward: Training multimodal reward model
808 through stable reinforcement learning. *arXiv preprint*
809 *arXiv:2505.02835*.

810 Yuyu Zhang, Hanjun Dai, Zornitsa Kozareva, Alexan-
811 der Smola, and Le Song. 2018. Variational reasoning
812 for question answering with knowledge graph. In
813 *Proceedings of the AAAI conference on artificial in-*
814 *telligence*, volume 32.

815 Zulun Zhu, Tiancheng Huang, Kai Wang, Junda Ye,
816 Xinghe Chen, and Siqiang Luo. 2025. Graph-based
817 approaches and functionalities in retrieval-augmented
818 generation: A comprehensive survey. *arXiv preprint*
819 *arXiv:2504.10499*.

820 Xiaohan Zou. 2020. A survey on application of knowl-
821 edge graph. In *Journal of Physics: Conference Se-*
822 *ries*, volume 1487, page 012016. IOP Publishing.

A Training Details

Implementation Details. In our experiments, we primarily employed the Llama3.1-8B (Dubey et al., 2024) and Qwen3-8B (Yang et al., 2025) models. Our data synthesis pipeline produced 9,035 SFT and 3,504 RL training instances; with this data, the Qwen3-8B model was trained for 3 SFT and 15 RL epochs on 8 A100 GPUs, requiring 32 hours in total.

For data generation, we apply our proposed data synthesis pipeline, producing a total of 9,035 training instances for SFT and 3,504 instances for RL. In the SFT stage, we fine-tune the Qwen3-8B with a learning rate of 1×10^{-4} for 3 epochs. In the RL stage, we adopt the GRPO algorithm with a batch size of 512, 15 training epochs, a learning rate of 1×10^{-5} , a value clipping range of 0.5, and a KL divergence coefficient of 0.001. The entire RL training phase takes approximately 32 hours on 8 NVIDIA A100 80GB GPUs.

Hyperparameter	Value
Learning rate	1×10^{-5}
Batch size	512
Epochs	15
Clip ratio	0.2
Gradient clipping	1.0
KL coefficient	0.001
PPO mini-batch size	16

Table 4: Key hyperparameters for RL training (GRPO).

B Prompt of Interactive Graph Retrieval

Prompts for Interactive Graph Retriever

You are an intelligent agent skilled in exploring Knowledge Graphs, with strong reasoning abilities. Your task is to perform question answering over a Knowledge Graph by gradually exploring it. You should start from the entities mentioned in the question and explore the graph step by step until you gather enough information to answer the question.

Your task follows these steps:

1. **Understand the Question**
2. **Analyze the Action History and Current Graph State**
3. **Choose the Next Action** from the following options:
 - **"Explore Entity"**: Explore all triples directly connected to a given entity in the Knowledge Graph.
 - **"Choose Relation"**: Select the triple(s) from the explored information that are most relevant to the question.

Attention: Only the triples included in the "Objects" field of the "Choose Relation" step will be retained in the future "Current Graph State". So You must filter and retain the information useful for answering the question or for further exploration.

- **"Finish"**: Choose this action when you believe you have gathered sufficient information to answer the question. Your final answers should be included in the "Objects" field.
4. **Select the Objects**: Depending on the action, provide the relevant entity or triple(s).
Attention: All objects must come from the "Entities in Question" or the current "Current Graph State". Do not create new entities or relations.
Examples:
 - If "Explore Entity": "Objects": ["EntityA", "EntityB"]
 - If "Choose Relation": "Objects": ["(Sub1, Rel1, Obj1)", ...]
 - If "Finish": "Objects": ["Answer1", "Answer2"]
 5. Output your response in JSON format, and include a **detailed thought process** explaining your reasoning at this step.

Question:
Entities in Question:
Current Graph State:
Action History:

Please respond using the following format:

Thought Process:

<Provide a step-by-step analysis>

Action Decision:

```
“‘json
{
  "Action": "<The type of action: 'Explore
Entity' | 'Choose Relation' | 'Finish'>",
  "Objects": [<The entities or triples>]
}”
```

C Case Study

Case 1

Question: When were the movies directed by [Sarah Polley] released?

True Answer: 2011, 2006, 2012

Action History: Step 1, Explore Entity, Objects: ['Sarah Polley']

Step 2, Choose Relation, Objects: ['(Away from Her, directed_by, Sarah Polley)', '(Stories We Tell, directed_by, Sarah Polley)', '(Take This Waltz, directed_by, Sarah Polley)']

Step 3, Explore Entity, Objects: ['Stories We Tell', 'Away from Her', 'Take This Waltz']

Step 4, Choose Relation, Objects: ['(Away from Her, release_year, 2006)', '(Stories We Tell, release_year, 2012)']

Step 5, Explore Entity, Objects: ['Take This Waltz']

Step 6, Choose Relation, Objects: ['(Take This Waltz, release_year, 2011)']

Step 7, Finish, Answer: ['2006', '2011', '2012']

Retrieved Triples: (Away from Her, release_year, 2006), (Away from Her, directed_by, Sarah Polley), (Take This

Waltz, release_year, 2011), (Stories We Tell, directed_by, Sarah Polley), (Stories We Tell, release_year, 2012), (Take This Waltz, directed_by, Sarah Polley)

To demonstrate the efficacy of our interactive pruning mechanism against high-degree entities, we analyze the query: "When were the movies directed by [Sarah Polley] released?" The entity "Sarah Polley" presents a significant challenge as a "hub node" with dual roles: she is a prolific actress with numerous connections but has directed comparatively fewer films.

Graph- S^3 Success via Structure-Aware Pruning: As shown in the trajectory, Graph- S^3 effectively overcomes the noise of Sarah Polley's acting career. In Step 2, the agent leverages the "Choose Relation" action to strictly select triples containing the "directed_by" relation, while deliberately pruning the dense subgraph of movies where she appears merely as an actress. This aligns with our framework's design to "avoid introducing redundant context into the LLM" and demonstrates the value of stepwise supervision in learning to distinguish task-relevant paths from high-degree noise. Consequently, the agent precisely navigates to the correct release years.

In contrast, baseline methods exhibited failures characteristic of shallow embedding similarity. The standard RAG suffered from severe lexical confusion. It retrieved unrelated entities such as "Pollyanna" and "Polly of the Circus", erroneously matching the token "Polly" with "Polley." This confirms that similarity-based matching often yields noisy results by ignoring precise relational constraints. G-Retriever failed to filter the entity's large neighborhood, retrieving generic attributes instead of the specific directorial path. This illustrates the limitation of one-shot retrievers that retrieve large neighborhoods discarding the graph's relational structure, whereas Graph- S^3 's interactive policy successfully identified the sparse signal within a noisy subgraph.

Case 2

Question: The screenwriter [Jane Anderson] co-wrote movies with whom?

True Answer: Anne Heche, Terry Ryan

Action History:

Step 1, Explore Entity, Objects: ['Jane Anderson']

Step 2, Choose Relation, Objects: ['(If These Walls Could Talk 2, written_by, Jane Anderson)', '(Normal, written_by, Jane Anderson)', '(The Prize Winner of Defiance, Ohio, written_by, Jane Anderson)']

Step 3, Explore Entity, Objects: ['If These Walls Could

Talk 2', 'Normal', 'The Prize Winner of Defiance, Ohio'] Step 4, Choose Relation, Objects: ['(If These Walls Could Talk 2, written_by, Jane Anderson)', '(Normal, written_by, Jane Anderson)', '(The Prize Winner of Defiance, Ohio, written_by, Jane Anderson)'] Step 5, Finish, Answer: ['If These Walls Could Talk 2', 'Normal', 'The Prize Winner of Defiance, Ohio']

Retrieved Triples: (The Prize Winner of Defiance, Ohio, written_by, Jane Anderson), (Normal, written_by, Jane Anderson), (If These Walls Could Talk 2, written_by, Jane Anderson)

To identify limitations in current reasoning policies, we analyze a failure case involving the collaborative query: "The screenwriter [Jane Anderson] co-wrote movies with whom?" The trajectory of the agent reveals a critical flaw in the processing of "sibling" relationships. In Steps 1 through 3, the agent correctly identified the intermediate nodes, successfully retrieving movies written by Jane Anderson.

The reasoning collapsed at Step 4. When expanding from the movie nodes to identify other writers, the agent exhibited a strong "self-verification bias." Instead of selecting edges pointing to new entities (the co-writers, such as Anne Heche), the agent selected the "written_by" relations pointing back to the query entity, Jane Anderson. Consequently, instead of discovering the target "sibling" nodes, the agent entered a redundant verification loop. It merely reconfirmed that Jane Anderson wrote the movies and prematurely terminated the search, outputting the movie titles instead of the co-writers' names. The model assigns disproportionate attention weight to entities explicitly named in the query, causing it to overlook unmentioned but structurally relevant entities.

D An Example of The Reasoning Process of Graph- S^3

```
{
  "step": 0,
  "question": "the films that share
    directors with the film [The
    Life of Oharu] were in which
    genres",
  "question_entities": [
    "The Life of Oharu"
  ],
  "now_state": [],
  "action_history": [],
  "extract_res": {
    "Action": "Explore Entity",
    "Objects": [
      "The Life of Oharu"
    ]
  },
  "step": 1,
```

```

938 "question": "the films that share
939 directors with the film [The
940 Life of Oharu] were in which
941 genres",
942 "question_entities": [
943 "The Life of Oharu"
944 ],
945 "now_state": [
946 "(The Life of Oharu,
947 starred_actors, Kinuyo
948 Tanaka)",
949 "(The Life of Oharu, directed_by
950 , Kenji Mizoguchi)",
951 "(The Life of Oharu,
952 release_year, 1952)",
953 "(The Life of Oharu, written_by,
954 Kenji Mizoguchi)",
955 "(The Life of Oharu, has_tags,
956 kenji mizoguchi)",
957 "(The Life of Oharu, in_language
958 , Japanese)"
959 ],
960 "action_history": [
961 "step 1, Explore Entity, Objects
962 : ['The Life of Oharu']"
963 ],
964 "extract_res": {
965 "Action": "Choose Relation",
966 "Objects": [
967 "(The Life of Oharu,
968 directed_by, Kenji
969 Mizoguchi)"
970 ]
971 }
972 },
973 {
974 "step": 2,
975 "question": "the films that share
976 directors with the film [The
977 Life of Oharu] were in which
978 genres",
979 "question_entities": [
980 "The Life of Oharu"
981 ],
982 "now_state": [
983 "(The Life of Oharu, directed_by
984 , Kenji Mizoguchi)"
985 ],
986 "action_history": [
987 "step 1, Explore Entity, Objects
988 : ['The Life of Oharu']",
989 "step 2, Choose Relation,
990 Objects: ['(The Life of
991 Oharu, directed_by, Kenji
992 Mizoguchi)']"
993 ],
994 "extract_res": {
995 "Action": "Explore Entity",
996 "Objects": [
997 "Kenji Mizoguchi"
998 ]
999 }
1000 },
1001 {
1002 "step": 3,
1003 "question": "the films that share
1004 directors with the film [The
1005 Life of Oharu] were in which
1006 genres",
1007 "question_entities": [
1008 "The Life of Oharu"
1009 ],
1010 "now_state": [
1011 "(Ugetsu, directed_by, Kenji
1012 Mizoguchi)",
1013 "(Sansho the Bailiff,
1014 directed_by, Kenji Mizoguchi
1015 )",
1016 "(The Crucified Lovers,
1017 directed_by, Kenji Mizoguchi
1018 )",
1019 "(The 47 Ronin, directed_by,
1020 Kenji Mizoguchi)",
1021 "(The Life of Oharu, directed_by
1022 , Kenji Mizoguchi)",
1023 "(Osaka Elegy, directed_by,
1024 Kenji Mizoguchi)",
1025 "(Sisters of the Gion,
1026 directed_by, Kenji Mizoguchi
1027 )",
1028 "(The Life of Oharu, has_tags,
1029 kenji mizoguchi)",
1030 "(Utamaro and His Five Women,
1031 directed_by, Kenji Mizoguchi
1032 )"
1033 ],
1034 "action_history": [
1035 "step 1, Explore Entity, Objects
1036 : ['The Life of Oharu']",
1037 "step 2, Choose Relation,
1038 Objects: ['(The Life of
1039 Oharu, directed_by, Kenji
1040 Mizoguchi)']",
1041 "step 3, Explore Entity, Objects
1042 : ['Kenji Mizoguchi']"
1043 ],
1044 "extract_res": {
1045 "Action": "Choose Relation",
1046 "Objects": [
1047 "(Ugetsu, directed_by, Kenji
1048 Mizoguchi)",
1049 "(Sansho the Bailiff,
1050 directed_by, Kenji
1051 Mizoguchi)",
1052 "(The Crucified Lovers,
1053 directed_by, Kenji
1054 Mizoguchi)",
1055 "(The 47 Ronin, directed_by,
1056 Kenji Mizoguchi)",
1057 "(Osaka Elegy, directed_by,
1058 Kenji Mizoguchi)",
1059 "(Sisters of the Gion,
1060 directed_by, Kenji
1061 Mizoguchi)",
1062 "(Utamaro and His Five Women,
1063 directed_by, Kenji
1064 Mizoguchi)"
1065 ]
1066 },
1067 {
1068 "step": 4,
1069 "question": "the films that share
1070 directors with the film [The
1071 Life of Oharu] were in which
1072 genres",
1073 "question_entities": [
1074 "The Life of Oharu"
1075 ],
1076 "now_state": [
1077 "(Ugetsu, directed_by, Kenji
1078 Mizoguchi)",
1079 "(Sansho the Bailiff,
1080 directed_by, Kenji Mizoguchi
1081 )",
1082 "(The Crucified Lovers,
1083 directed_by, Kenji Mizoguchi
1084 )",
1085 "(The 47 Ronin, directed_by,
1086 Kenji Mizoguchi)",
1087 "(The Life of Oharu, directed_by
1088 , Kenji Mizoguchi)",
1089 "(Osaka Elegy, directed_by,
1090 Kenji Mizoguchi)",
1091 "(Sisters of the Gion,
1092 directed_by, Kenji Mizoguchi
1093 )",
1094 "(Utamaro and His Five Women,
1095 directed_by, Kenji Mizoguchi
1096 )"
1097 ],
1098 "action_history": [
1099 "step 1, Explore Entity, Objects
1100 : ['The Life of Oharu']",
1101 "step 2, Choose Relation,
1102 Objects: ['(The Life of
1103 Oharu, directed_by, Kenji
1104 Mizoguchi)']",
1105 "step 3, Explore Entity, Objects
1106 : ['Kenji Mizoguchi']"
1107 ],
1108 "extract_res": {
1109 "Action": "Explore Entity",
1110 "Objects": [
1111 "Kenji Mizoguchi"
1112 ]
1113 }
1114 }
1115 }

```

```

1101 "action_history": [
1102   "step 1, Explore Entity, Objects
1103   : ['The Life of Oharu']",
1104   "step 2, Choose Relation,
1105   Objects: ['(The Life of
1106   Oharu, directed_by, Kenji
1107   Mizoguchi)']",
1108   "step 3, Explore Entity, Objects
1109   : ['Kenji Mizoguchi']",
1110   "step 4, Choose Relation,
1111   Objects: ['(Ugetsu,
1112   directed_by, Kenji Mizoguchi
1113   )', '(Sansho the Bailiff,
1114   directed_by, Kenji Mizoguchi
1115   )', '(The Crucified Lovers,
1116   directed_by, Kenji Mizoguchi
1117   )', '(The 47 Ronin,
1118   directed_by, Kenji Mizoguchi
1119   )', '(Osaka Elogy,
1120   directed_by, Kenji Mizoguchi
1121   )', '(Sisters of the Gion,
1122   directed_by, Kenji Mizoguchi
1123   )', '(Utamaro and His Five
1124   Women, directed_by, Kenji
1125   Mizoguchi)']"
1126 ],
1127 "extract_res": {
1128   "Action": "Explore Entity",
1129   "Objects": [
1130     "Ugetsu",
1131     "Sansho the Bailiff",
1132     "The Crucified Lovers",
1133     "The 47 Ronin",
1134     "Osaka Elogy",
1135     "Sisters of the Gion",
1136     "Utamaro and His Five Women"
1137   ]
1138 },
1139 },
1140 {
1141   "step": 5,
1142   "question": "the films that share
1143   directors with the film [The
1144   Life of Oharu] were in which
1145   genres",
1146   "question_entities": [
1147     "The Life of Oharu"
1148   ],
1149   "true_answer": [
1150     "Drama"
1151   ],
1152   "now_state": [
1153     "(Ugetsu, directed_by, Kenji
1154     Mizoguchi)",
1155     "(Sansho the Bailiff,
1156     directed_by, Kenji Mizoguchi
1157     )",
1158     "(The Crucified Lovers,
1159     directed_by, Kenji Mizoguchi
1160     )",
1161     "(The 47 Ronin, directed_by,
1162     Kenji Mizoguchi)",
1163     "(The Life of Oharu, directed_by
1164     , Kenji Mizoguchi)",
1165     "(Osaka Elogy, directed_by,
1166     Kenji Mizoguchi)",
1167     "(Sisters of the Gion,
1168     directed_by, Kenji Mizoguchi
1169     )",
1170     "(Sisters of the Gion, has_genre
1171     , Drama)",
1172     "(Ugetsu, has_genre, Drama)",
1173     "(Ugetsu, starred_actors,
1174     Masayuki Mori)",
1175     "(Utamaro and His Five Women,
1176     directed_by, Kenji Mizoguchi
1177     )"
1178   ],
1179   "action_history": [
1180     "step 1, Explore Entity, Objects
1181     : ['The Life of Oharu']",

```

```

"step 2, Choose Relation,
Objects: ['(The Life of
Oharu, directed_by, Kenji
Mizoguchi)']",
"step 3, Explore Entity, Objects
: ['Kenji Mizoguchi']",
"step 4, Choose Relation,
Objects: ['(Ugetsu,
directed_by, Kenji Mizoguchi
)', '(Sansho the Bailiff,
directed_by, Kenji Mizoguchi
)', '(The Crucified Lovers,
directed_by, Kenji Mizoguchi
)', '(The 47 Ronin,
directed_by, Kenji Mizoguchi
)', '(Osaka Elogy,
directed_by, Kenji Mizoguchi
)', '(Sisters of the Gion,
directed_by, Kenji Mizoguchi
)', '(Utamaro and His Five
Women, directed_by, Kenji
Mizoguchi)']",
"step 5, Explore Entity, Objects
: ['Ugetsu', 'Sansho the
Bailiff', 'The Crucified
Lovers', 'The 47 Ronin', '
Osaka Elogy', 'Sisters of
the Gion', 'Utamaro and His
Five Women']"
],
"extract_res": {
  "Action": "Choose Relation",
  "Objects": [
    "(Ugetsu, has_genre, Drama)"
    ,
    "(Sisters of the Gion,
has_genre, Drama)"
  ]
},
},
{
  "step": 13,
  "question": "the films that share
directors with the film [The
Life of Oharu] were in which
genres",
  "question_entities": [
    "The Life of Oharu"
  ],
  "true_answer": [
    "Drama"
  ],
  "now_state": [
    "(Ugetsu, directed_by, Kenji
Mizoguchi)",
    "(Sansho the Bailiff,
directed_by, Kenji Mizoguchi
)",
    "(The Crucified Lovers,
directed_by, Kenji Mizoguchi
)",
    "(The 47 Ronin, directed_by,
Kenji Mizoguchi)",
    "(The Life of Oharu, directed_by
, Kenji Mizoguchi)",
    "(Osaka Elogy, directed_by,
Kenji Mizoguchi)",
    "(Sisters of the Gion,
directed_by, Kenji Mizoguchi
)",
    "(Sisters of the Gion, has_genre
, Drama)",
    "(Ugetsu, has_genre, Drama)",
    "(Ugetsu, has_genre, Drama)",
    "(Utamaro and His Five Women,
directed_by, Kenji Mizoguchi
)"
  ],
  "action_history": [
    "step 1, Explore Entity, Objects
: ['The Life of Oharu']",
    "step 2, Choose Relation,
Objects: ['(The Life of

```

```

1264         Oharu, directed_by, Kenji
1265         Mizoguchi)']]",
1266     "step 3, Explore Entity, Objects
1267     : ['Kenji Mizoguchi']]",
1268     "step 4, Choose Relation,
1269     Objects: ['(Ugetsu,
1270     directed_by, Kenji Mizoguchi
1271     )', '(Sansho the Bailiff,
1272     directed_by, Kenji Mizoguchi
1273     )', '(The Crucified Lovers,
1274     directed_by, Kenji Mizoguchi
1275     )', '(The 47 Ronin,
1276     directed_by, Kenji Mizoguchi
1277     )', '(Osaka Elogy,
1278     directed_by, Kenji Mizoguchi
1279     )', '(Sisters of the Gion,
1280     directed_by, Kenji Mizoguchi
1281     )', '(Utamaro and His Five
1282     Women, directed_by, Kenji
1283     Mizoguchi)']]",
1284     "step 5, Explore Entity, Objects
1285     : ['Ugetsu', 'Sansho the
1286     Bailiff', 'The Crucified
1287     Lovers', 'The 47 Ronin', '
1288     Osaka Elogy', 'Sisters of
1289     the Gion', 'Utamaro and His
1290     Five Women']]",
1291     "step 6, Choose Relation,
1292     Objects: ['(Ugetsu,
1293     has_genre, Drama)', '(
1294     Sisters of the Gion,
1295     has_genre, Drama)']]"
1296 ],
1297 "extract_res": {
1298     "Action": "Finish",
1299     "Objects": [
1300         "Drama"
1301     ]
1302 }
1303 }

```