

GRAPHICS CAPSULE: LEARNING HIERARCHICAL 3D REPRESENTATIONS FROM 2D IMAGES AND ITS APPLICATION ON HUMAN FACES

Anonymous authors

Paper under double-blind review

ABSTRACT

The function of constructing the hierarchy of objects is important to the visual process of the human brain. Previous studies have successfully adopted capsule networks to decompose the digits and faces into parts in an unsupervised manner to investigate the similar perception mechanism of neural networks. However, their descriptions are restricted to the 2D space, limiting their capacities to imitate the intrinsic 3D perception ability of humans. In this paper, we propose an Inverse Graphics Capsule Network (IGC-Net) to learn the hierarchical 3D representations from large-scale unlabeled images. The core of IGC-Net is a new type of capsule, named graphics capsule, which represents 3D primitives with interpretable parameters in computer graphics (CG), including depth, albedo, and 3D pose. Specifically, IGC-Net first decomposes the objects into a set of semantic-consistent parts and then assembles them to the object-level descriptions to build the hierarchy. The learned graphics capsules reveal how the neural networks, oriented at visual perception, understand objects as a hierarchy of 3D models. Besides, the discovered parts can be deployed to the unsupervised face segmentation task to evaluate the semantic consistency of our method. Moreover, the part-level descriptions with explicit physical meanings give an insight into the face analysis that originally runs in a black box, such as the importance of shape and texture for face recognition. Experiments on CelebA, BP4D, and Multi-PIE validate the effectiveness of our method.

1 INTRODUCTION

A path toward autonomous machine intelligence (LeCun, 2022) is to enable machines to have human-like perception and learning abilities. As humans, by only observing the objects, we can easily decompose them into a set of part-level components and construct their hierarchy even though we have never seen these objects before. This phenomenon is supported by the psychological studies that the visual process of the human brain is related to the construction of the hierarchical structural descriptions (Marr, 2010; Hinton, 1979; Marr & Nishihara, 1978; Singh & Hoffman, 2001). To investigate the similar perception mechanism of neural networks, previous studies (Kosiorrek et al., 2019; Yu et al., 2022) incorporate the capsule networks, which are designed to present the hierarchy of objects and describe each entity with interpretable parameters. After observing a large-scale of unlabeled images, these methods successfully decompose the digits (Kosiorrek et al., 2019) or faces (Yu et al., 2022) into a set of parts, which gives an insight into how the neural networks understand the objects. However, their representations are limited in the 2D space. Specifically, these methods follow the analysis-by-synthesis strategy in model training and try to reconstruct the image by the decomposed parts. Since the parts are represented by 2D templates, the reconstruction becomes estimating the affine transformations to warp the templates and put them in the right places, which is just like painting with stickers. This strategy performs well when the objects are intrinsically 2D, like handwritten digits and frontal faces, but has difficulty in interpreting 3D objects in the real world, especially when we want a view-independent representation like humans (Biederman, 1987).

How to represent the perceived objects has been the core area of research in computer vision (Poggio & Edelman, 1990; Biederman & Gerhardstein, 1993). One of the most popular theories is the

Marr theory (Marr & Nishihara, 1978; Marr, 2010). He believed that the purpose of the vision is to build the descriptions of shapes and positions of things from the images and construct hierarchical 3D representations of objects for recognition. In this paper, we try to materialize Marr’s theory and propose an Inverse Graphics Capsule Network (IGC-Net), whose primitive is a new type of capsule (graphics capsule) that is defined by computer graphics (CG), to learn the hierarchical 3D representations from large-scale unlabeled images. Figure 1 shows an overview of the proposed method. Specifically, the hierarchy of the objects is described with the part capsules and the object capsules, where each capsule contains a set of interpretable parameters with explicit physical meanings, including depth, albedo, and pose. During training, the input image is first encoded to a global shape and albedo embeddings, which are sent to a decomposition module to get the spatially-decoupled part-level graphics capsules. Then, these capsules are decoded by a shared capsule decoder to get explicit 3D descriptions of parts. Afterward, the parts are assembled by their depth to generate the object capsules as the object-centered representations, naturally constructing the part-object hierarchy. Finally, the 3D objects embedded in the object capsules are illuminated, posed, and rendered to fit the input image, following the analysis-by-synthesis manner. When an IGC-Net is well trained, the learned graphics capsules naturally build hierarchical 3D representations.




Figure 1: Overview of the Inverse Graphics Capsule Network (IGC-Net). The input image is first encoded to global shape and albedo embeddings and then sent to a decomposition module to get the spatially-decoupled part-level graphics capsules. Afterward, these capsules are decoded to get the explicit 3D descriptions of parts, which are assembled by their depth to generate the object capsules as object-centered representations. Finally, the object capsules are illuminated, posed, and rendered to fit the input image. After training, the learned graphics capsules naturally build hierarchical 3D representations.

We apply IGC-Net to human faces, which have been widely used to investigate human vision system (Tanaka & Simonyi, 2016) due to the similar topology structures and complicated appearances. Thanks to the capacity of the 3D descriptions, IGC-Net successfully builds the hierarchy of in-the-wild faces that are captured under varied illuminations and poses, while the previous work equipped with 2D representations can only tackle frontal faces under controlled environment. We deploy IGC-Net to the unsupervised face segmentation task, where the silhouettes of the discovered parts are regarded as segment maps. Besides, since the graphics capsule provides each part with explicit graphics descriptions, we further apply it to interpretable face analysis to uncover the mechanism of neural networks when recognizing faces.

The main contributions of this paper are summarized as:

- This paper proposes an Inverse Graphics Capsule Network (IGC-Net) to learn the hierarchical 3D representations from large-scaled unlabeled images. The learned graphics capsules in the network provide an insight into how the neural networks, oriented at visual perception, understand objects as a hierarchy of 3D models.
- A Graphics Decomposition Module (GDM) is proposed for part-level decomposition, which incorporates shape and albedo information as cues to ensure that each part capsule represents a semantic consistent part of objects.

- We execute the interpretable face analysis based on the part-level 3D descriptions of graphics capsules. Besides, the silhouettes of 3D parts are deployed to the unsupervised face segmentation task. Experiments on CelebA, BP4D, and Multi-PIE show the effectiveness of our method.

2 RELATED WORK

Capsule Network. The connections of the human brain are thought to be sparse and hierarchical (Barrett, 2012; Bodegård et al., 2001; Jääskeläinen et al., 2022; Georgopoulos et al., 1986), which inspire the design of capsule networks to present the objects with dynamic parse trees. Given inputs, capsule networks (Hinton et al., 2011; Sabour et al., 2017; Hinton et al., 2018; Kosiorek et al., 2019; Sabour et al., 2021; Yu et al., 2022) will encode the images to a set of low-level capsules, which describe the local entities of the objects, and then assemble them into higher-level capsules to describe more complicated entities. The parameters of capsules are usually with explicit meanings, which enables the interpretability of neural networks. Recently, some capsule networks have been proposed to explore the hierarchy of objects. SCAE (Kosiorek et al., 2019) proposes to describe the objects with a set of visualizable templates through unsupervised learning. However, SCAE can only handle simple 2D objects like digits. HP-Capsule (Yu et al., 2022) extends SCAE to tackle human faces, which proposes subpart-level capsules and uses the compositions of subparts to present the variance of pose and appearance. Due to the limitation of 2D representations, HP-Capsule can only tackle faces with small poses. Sabour et al. (Sabour et al., 2021) propose to apply the capsule network for human bodies, but it needs optical flow as additional information to separate the parts. In this paper, we propose a new type of capsule (graphics capsule) to learn the hierarchical 3D representations from unlabeled images.

Unsupervised Part Segmentation. Our work is related to unsupervised face segmentation. Several methods have been proposed for this challenging task. DFF (Collins et al., 2018) proposes to use non-negative matrix factorization upon the CNN features to discover semantics, but it needs to optimize the whole dataset during inference. Choudhury et al. (Choudhury et al., 2021) follow a similar idea, which uses k-means to cluster the features obtained by a pre-trained network. SCOPS (Hung et al., 2019) and Liu et al. (Liu et al., 2021) propose to constrain the invariance of images between TPS transformation. However, their methods rely on the concentration loss to separate parts, leading to the similar silhouettes of different parts. HP-Capsule (Yu et al., 2022) proposes a bottom-up schedule to aggregate parts from subparts. The parts of the HP-Capsule rely on the learning of subpart-part relations, which is unstable when tackling faces with large poses. Compared with these methods, our IGC-Net can provide interpretable 3D representations of the parts, which are with salient semantics and keep semantic consistency across the in-the-wild faces with various poses.

Unsupervised 3D Face Reconstruction. Learning to recover the 3D face from 2D monocular images has been studied for years. Following the analysis-by-synthesis strategy, many methods (Tran & Liu, 2018; Zhou et al., 2019; Chen et al., 2020; Deng et al., 2019) propose to estimate the parameters of the 3D Morphable Model (Paysan et al., 2009), which describes the faces with a uniformed topology pre-defined by humans. Recently, several works (Wu et al., 2020; Zhang et al., 2021; 2022) have been proposed to only use the symmetric character of faces to learn the 3D face reconstruction. Under the graphics decomposition, these methods achieve promising results. Inspired by them, we propose the graphics capsule to learn the hierarchical 3D representations from images, which provides an insight into how the neural networks understand the objects as a hierarchy.

3 METHOD

Based on previous explorations in capsule networks (Kosiorek et al., 2019; Yu et al., 2022), our goal is to explore a system that can build hierarchical 3D representations of objects through browsing images and apply it on human faces to validate its effectiveness. Specifically, we aim to learn the part-object hierarchy of faces in an unsupervised manner, where each part is represented by a set of interpretable CG parameters, including shape, albedo, 3D poses, etc. In the following sections, we will introduce the graphics capsule and the overview of the network in Section 3.1, the graphics decomposition module that is used to build hierarchy in Section 3.2, and the loss functions that enable unsupervised learning in Section 3.3.

3.1 OVERVIEW

To learn a hierarchical 3D representation from unlabeled images, we propose an Inverse Graphics Capsule Network (IGC-Net), whose capsules are composed of interpretable CG descriptions, including a depth map D , an albedo map A and 3D pose parameters p . Our IGC-Net is applied to human faces, which have been widely used to investigate the human vision system due to their similar topology structures and complicated appearances. The overview of IGC-Net is shown in Figure 1. Following a bottom-up schedule, a CNN-based image encoder first encodes the input image I into the shape and the albedo embeddings f_s and f_a :

$$f_s, f_a = \text{ImageEncoder}(I). \quad (1)$$

Then a Graphics Decomposition Module (GDM) is employed to decompose the global embeddings into a set of part-level embeddings, which can be further decoded into interpretable graphics capsules:

$$\begin{aligned} \{\hat{e}_s^1, \dots, \hat{e}_s^M\}, \{\hat{e}_a^1, \dots, \hat{e}_a^M\} &= \text{GDM}(f_s, f_a), \\ \{D_p^m, A_p^m, p_p^m\} &= \text{GraphicsDecoder}(\hat{e}_s^m, \hat{e}_a^m), \end{aligned} \quad (2)$$

where \hat{e}_s^m is the shape embedding of the m th part, \hat{e}_a^m is the corresponding albedo embedding, M is the number of part capsules, and $\Theta_p^m : \{D_p^m, A_p^m, p_p^m\}$ is a graphics capsule that describes a part with depth, albedo, and 3D pose. Afterward, the part capsules are assembled according to their depth to generate the global object capsule:

$$\begin{aligned} V^m(i, j) &= \mathbf{1}_{m=\arg \max_n (D_p^n(i, j))}, \\ D_o &= \sum_m V^m \odot D_p^m, A_o = \sum_m V^m \odot A_p^m, p_o = \frac{1}{M} \sum_m p_p^m, \end{aligned} \quad (3)$$

where $V_{i,j}^m$ is the visibility map of the m th part capsule at the position (i, j) , \odot is the element-wise production, and $\Theta_o : \{D_o, A_o, p_o\}$ is the object capsule. During assembly, a capsule is visible at (i, j) only when its depth is higher than the others. The part-level depth and albedo maps are multiplied with their visibility maps and aggregated as one, respectively, and the object pose is the average of part poses. In the object capsule, both the depth D_o and albedo A_o are defined in the canonical space, and the pose p_o is used to project the 3D object to the image plane. Finally, by estimating the lighting l with another network, the recovered image \hat{I} is generated by the differentiable rendering Λ :

$$\hat{I} = \Lambda(D, A, p, l). \quad (4)$$

When training IGC-Net, we can minimize the distance between the input image I and the reconstructed image \hat{I} following the analysis-by-synthesis strategy, so that the network parameters can be learned in an unsupervised manner.

3.2 GRAPHICS DECOMPOSITION MODULE

Humans can decompose an object into a set of parts and construct a hierarchy by just observation. To realize this ability in neural networks, we propose the Graphics Decomposition Module (GDM) to decompose the global embedding of the image into a set of semantic-consistent parts. The illustration of GDM is shown in Figure 2.

Taking shape decomposition as an example, GDM maintains M shape basis $\{W_s^m\}$ as the implicit part templates. Given the global embeddings f_s extracted in Eqn. 1, GDM performs cross attention between the global embedding and the basis to get M disentangled D dimensional embeddings:

$$e_s^m = f_s W_s^m, \quad m = 1, \dots, M. \quad (5)$$

To further reduce the entanglement between $\{e_s^m\}$ and generate independent part-level embeddings, an M -way one-hot attention vector is generated for each of the D dimensions, by deploying that only one embedding can preserve its value and the others are set to 0 at each dimension. This dimension attention is formulated as:

$$\begin{aligned} \hat{e}_s^m &= e_s^m \odot M_{[m,:]}, \\ M_{[:,d]} &= \text{hard_softmax}([e_s^1(d), e_s^2(d), \dots, e_s^M(d)]), \\ \text{hard_softmax}(e) &= \frac{e}{\sum_i e(i)} \odot \text{onehot}(\frac{e}{\sum_i e(i)}), \end{aligned} \quad (6)$$




Figure 2: Illustration of the Graphics Decomposition Module (GDM). GDM is proposed to ensure that each part capsule presents a semantic consistent part of objects.

where $M_{M \times D}$ is the attention matrix, whose m th row is $M_{[m,:]}$ and d th column is $M_{[:,d]}$, $e_s^m(d)$ is the d th dimension of the embedding e_s^m , $\text{onehot}(\cdot)$ is the one-hot operation, and \hat{e}_s^m is the final part-level shape embedding. The same pipeline is applied to the albedo embeddings, where the only difference is that the attention M is copied from the shape embeddings, which ensures that the shape and the albedo information are decomposed synchronously.

By incorporating both shape and albedo information as cues, GDM successfully decomposes parts from objects under varied poses and appearances, ensuring that each part capsule represents a semantic-consistent part.

3.3 LOSSES AND REGULARIZATIONS

When training IGC-Net with unlabelled images, we employ the following constraints to learn the hierarchical 3D representations effectively:

Reconstruction. We adopt the negative log-likelihood loss (Wu et al., 2020) to measure the distance between the original image I and the reconstructed image \hat{I} :

$$\mathcal{L}_{rec} = -\frac{1}{|\Omega|} \sum \ln \frac{1}{\sqrt{2}\sigma} \exp -\frac{\sqrt{2}|\hat{I} - I|}{\sigma} - \frac{1}{|\Omega|} \sum \ln \frac{1}{\sqrt{2}\sigma} \exp -\frac{\sqrt{2}|\hat{I}_{flip} - I|}{\sigma}, \quad (7)$$

where Ω is for normalization and $\sigma \in \mathbb{R}^{H \times W}$ is the confidence map estimated by a network to present the symmetric probability of each position in I , \hat{I}_{flip} is the image reconstructed with the flipped albedo and shape.

Semantic consistency. In GDM, shape embedding is used as the cue for part decomposition. To improve the semantic consistency across samples, we employ a contrastive loss on the shape embedding \hat{e}_s^m of each capsule, which is formulated as:

$$\mathcal{L}_{contra} = -\sum_{b=1}^B \sum_{m=1}^M \log \frac{\sum_{i \neq b} \exp(e_s^{m,(b)} \cdot e_s^{m,(i)}/\tau)}{\sum_{i \neq b} \exp(e_s^{m,(b)} \cdot e_s^{m,(i)}/\tau) + \sum_{j \neq m} \sum_{i \neq b} \exp(e_s^{m,(b)} \cdot e_s^{j,(i)}/\tau)}, \quad (8)$$

where B is the batch size, M is the number of part capsules, $\hat{e}_s^{j,(i)}$ is the shape embedding of the j th part that belongs to the i th sample. \mathcal{L}_{contra} maximizes the shape similarity between the same capsule across the samples and minimizes the similarity across different capsules. τ is the hyperparameter utilized to control the discrimination across the negative pairs.

Sparsity. To prevent the network from collapsing to use one capsule to describe the whole objects, we employ the spatial sparsity constraint on the visible regions V^m of part capsules:

$$\mathcal{L}_{sparse} = \text{std}(\sum_{i,j} V_{i,j}^m), \quad (9)$$

where $\text{std}(\cdot)$ calculates the standard deviation, $V_{i,j}^m$ is the visibility map of the m th capsule at the position (i, j) .

Background seperation. The prerequisite for unsupervised part discovery is separating foreground and background so that the network can focus on the objects. To achieve that, previous works incorporate the salient maps or the ground-truth foreground masks during training. Instead, we use a specific part capsule to model the background. Note that the graphics capsule can recover the 3D information of the objects without any annotation, the foreground map can be easily estimated by setting a threshold to the depth:

$$\mathcal{L}_{bg} = \|V^{bg} - \tilde{V}\|, \quad \tilde{V} = \mathbf{1}_{D_o < \gamma}, \quad (10)$$

where V^{bg} is the visibility map of the part capsule that is used for background estimation, \tilde{V} is the external region of the object, D_o is the depth of the object, and γ is the threshold for locating the external region.

The final loss functions to train IGC-Net are combined as:

$$\mathcal{L}_{contra} = \mathcal{L}_{rec} + \lambda_{contra}\mathcal{L}_{contra} + \lambda_{sparse}\mathcal{L}_{sparse} + \lambda_{bg}\mathcal{L}_{bg}, \quad (11)$$

where λ_{contra} , λ_{sparse} and λ_{bg} are the hyper-parameters to balance different loss functions.

4 EXPERIMENTS

Implement Details. The image encoder, the capsule decoder, and the lighting module of IGC-Net are composed of convolutional neural networks. We set the number of the part-level graphics capsules $M = 6$, where one of them is used to model the background. Following unsup3d (Wu et al., 2020), we also incorporate the perceptual loss to improve the reconstruction results. Besides, the hyper-parameters for loss combination are set to be $\lambda_{contra} = 10^{-5}$, $\lambda_{sparse} = 10^{-1}$, $\lambda_{bg} = 10^{-1}$. For optimization, we use the Adam optimizer (Kingma & Ba, 2014) with 10^{-4} learning rate to train the networks on a GeForce RTX 3090 for 60 epochs.

Datasets. Following the recent study for the unsupervised face part discovery (Yu et al., 2022), we evaluate IGC-Net on BP4D (Zhang et al., 2014) and Multi-PIE (Gross et al., 2010). Both of these two datasets are captured in the controlled environment. To further validate the capability of tackling the images under real-world scenarios, we also adopt the CelebA (Liu et al., 2015) for experiments, which contains over 200K in-the-wild images of real human faces. In the experiments, BP4D and CelebA are used to evaluate the unsupervised face segmentation and Multi-PIE is used for the interpretable face analysis.

4.1 THE DISCOVERED FACE HIERARCHY

Thanks to the 3D representations embedded in the graphics capsules, IGC-Net successfully builds the hierarchy of in-the-wild faces that are captured under varied illuminations and poses, shown in Figure 3. By incorporating shape and albedo information as cues, the face images are naturally decomposed into six semantic-consistent parts: background, eyes, mouth, forehead, nose, and cheek, without any human supervision. Each part is described with a specific graphics capsule, which is composed of a set of interpretable parameters including pose, view-independent shape, and view-independent albedo. These parts are assembled by their depth to generate the object capsules as the object-centered representations, building a bottom-up face hierarchy.

4.2 INTERPRETABLE FACE ANALYSIS

The graphics capsules learned by IGC-Net provide the face hierarchy with explicit graphics descriptions, which is a feasible way to the interpretable face analysis. In this section, we apply it to the recognition task to uncover the mechanism of neural networks when recognizing faces. Besides, the graphics part-level descriptions can be used for face manipulation.

Face Recognition. To show the potential of IGC-Net for interpretable analysis, we design an experiment to explore which part-level graphics capsule is crucial for face recognition and which component of the capsule is more important, the shape or the albedo. Specifically, we assign the part-level




Figure 3: Illustration of the discovered face hierarchy with 3D descriptions. By incorporating shape and albedo information as cues, IGC-Net decomposes the images into six parts: background, eyes, mouth, forehead, nose, and cheek.

shape embeddings $\{\hat{e}_s^m\}$ and albedo embeddings $\{\hat{e}_a^m\}$ with trainable scalar $\{\omega_s^m\}$ and $\{\omega_a^m\}$ as the attention weights. The weight parameters $\{\omega^m \hat{e}^m\}$ are sent to a linear classifier for face recognition. After training with L1 penalization for sparsity, the attention weights of part capsules are shown in Figure 4. It can be seen that the eyes are the most important regions for recognition, followed by the nose, forehead, cheek, and mouth. The work of Williford et al. (Williford et al., 2020) also shows the similar phenomenon. Besides, by averaging the parts, we can see that the albedo is more important than the shape for face recognition.




Figure 4: The importance of part-level graphics capsules for face recognition. On average, the albedo is more crucial than the shape when recognizing faces. The albedo of the eyes is the most important component and the shape of the nose is more important than the shape of other parts.

Face Manipulation. Since IGC-Net provides view-independent part-level descriptions, we apply it for local face manipulation, which helps us to further understand the structure of faces. Figure 5 shows the shape-manipulated faces after replacing one part-level shape embedding with the corresponding target part. Figure 6 shows the albedo-manipulated faces. It can be seen that the edit of the albedo can be easily observed by humans, while the edit of the shape needs to be carefully identified.



Figure 5: The results of our IGC-Net for local shape-based face manipulation. The red boxes highlight the variations, which show that the appearance of the faces changes slightly with the shape.



Figure 6: The results of our IGC-Net for local albedo-based face manipulation. The edit of the albedo can be easily observed.



Figure 7: The qualitative comparison of unsupervised face segmentation on CelebA.




Figure 8: The qualitative comparison of unsupervised face segmentation on BP4D.

4.3 UNSUPERVISED FACE SEGMENTATION

To execute the quantitative and qualitative evaluation, we treat the silhouettes of parts as segment maps and apply them to the unsupervised face segmentation task. Note that there is no ground truth for the unsupervised part-level segmentation, the key of this task is to evaluate the semantic consistency of the parsing manners. The following experiments show the superiority of our method.

Baselines. Learning to segment the face parts from the unlabeled images is a challenging task as parts are difficult to be described by math. In this paper, we compare our method with the state-of-art methods for unsupervised face segmentation, including DFF (Collins et al., 2018), SCOPS (Hung et al., 2019) and HP-Capsule (Yu et al., 2022). To discover the semantic parts, DFF proposes to execute the non-negative matrix upon the CNN features, which need to optimize the whole dataset to get the segment results. SCOPS proposes a framework with the concentration loss to constrain the invariance of images between TPS transformation. However, due to the lack of effective constraints, their results tend to assign similar silhouettes to different parts. HP-Capsule proposes a bottom-up schedule to aggregate parts from subparts, whose parts are described with interpretable parameters. However, their descriptions are defined in the 2D space, limiting their capacity to tackle faces with large poses.

Quantitative Comparison. Following the previous work (Yu et al., 2022), we utilize the Normalized Mean Error (NME) of the landmarks predicted by segment maps to evaluate the quality of the parsing manners. Specifically, NME_L treats the centroid of the segment maps as landmarks and uses linear mapping to convert them to human-annotated landmarks. NME_{DL} incorporates a shallow network to directly predict the landmarks from the segment maps. Table 1 and Table 2 show the quantitative comparison results on CelebA and BP4D, which validate the effectiveness of our method.

Qualitative Comparison. The qualitative comparison results are shown in Figure 7 and Figure 8. It can be seen that our method performs better than other methods. The results of DFF can not successfully separate the foreground and the background. As for SCOPS, due to the lack of effective constraints, the segment maps of SCOPS are with some ambiguity, where the organs with salient se-

Table 1: The quantitative comparison of unsupervised face segmentation on CelebA. $NME_L(\%)$ and $NME_{DL}(\%)$ use the landmarks estimated from the segment maps to evaluate the semantic consistency of parts.

METHOD	NME_L	NME_{DL}
DFF	22.78	27.27
SCOPS	18.72	23.69
HP-Capsule	21.25	25.27
IGC-Net (ours)	11.84	18.88

Table 2: The quantitative comparison of unsupervised face segmentation on BP4D.

METHOD	NME_L	NME_{DL}
DFF	18.85	12.26
SCOPS	9.10	6.74
HP-Capsule	8.81	6.10
IGC-Net (ours)	6.35	4.32



Figure 9: The qualitative ablation study on CelebA. It can be seen that the semantic consistency will be damaged without the one-hot operation in GDM (see Eqn. 3.2) and the \mathcal{L}_{contra} (see Eqn. 8) is important for discovering parts with salient semantics.

Table 3: The quantitative ablation study on CelebA. The results show the importance of the one-hot operation in GDM and the semantic constraint \mathcal{L}_{contra} .

One-Hot	\mathcal{L}_{contra}	NME_L
	✓	19.10
✓		13.46
✓	✓	11.84

manics are assigned to different parts for different samples. For example, SCOPS sometimes takes the right eye as the green part while sometimes splitting it from the middle. The segment boundaries of HP-Capsule are clearer than DFF and SCOPS. However, limited by their 2D descriptions, HP-Capsule fails on the faces with large poses while our method performs well on these challenging samples.

4.4 ABLATION STUDIES

The basis of building the hierarchy of objects is to learn the parts with explicit semantics and keep the semantic consistency across different samples. In this section, we perform the ablation study to show the importance of the one-hot operation in the GDM (see Eqn. 3.2) and the semantic constraint \mathcal{L}_{contra} (see Eqn. 8) for discovering meaningful parts. Figure 9 shows the qualitative ablation study on CelebA. In the second row of Figure 9, it can be seen that, without the one-hot operation to prevent the information leakage of different parts, the semantic consistency across samples will be damaged. The third row of Figure 9 shows that the contrastive semantic constraint \mathcal{L}_{contra} is important for the discovery of parts with salient semantics. Without such constraint, the segmentation of the important organs such as the eyes will have ambiguity. These conclusions are also validated by the quantitative ablation study shown in Table 3.

5 CONCLUSION AND DISCUSSION

In this paper, we propose the IGC-Net to learn the hierarchical 3D representations from large-scale unlabeled in-the-wild images, whose primitive is the graphics capsule that contains the 3D representations with explicit meanings. By combining depth and albedo information as cues, IGC-Net successfully decomposes the objects into a set of part-level graphics capsules and constructs the hierarchy of objects by assembling the part-level capsules into object-level capsules. IGC-Net reveals how the neural networks, oriented at visual perception, understand objects as a hierarchy of 3D models. Besides, the part-level graphics descriptions can be used for unsupervised face segmentation and interpretable face analysis. Experiments on CelebA, BP4D, and Multi-PIE validate the effectiveness and the interpretability of our methods.

REFERENCES

- H Clark Barrett. A hierarchical model of the evolution of human brain specializations. *Proceedings of the national Academy of Sciences*, 109(supplement_1):10733–10740, 2012.
- Irving Biederman. Recognition-by-components: a theory of human image understanding. *Psychological review*, 94(2):115, 1987.
- Irving Biederman and Peter C Gerhardstein. Recognizing depth-rotated objects: evidence and conditions for three-dimensional viewpoint invariance. *Journal of Experimental Psychology: Human perception and performance*, 19(6):1162, 1993.
- Anna Bodegård, Stefan Geyer, Christian Grefkes, Karl Zilles, and Per E Roland. Hierarchical processing of tactile shape in the human brain. *Neuron*, 31(2):317–328, 2001.
- Yajing Chen, Fanzi Wu, Zeyu Wang, Yibing Song, Yonggen Ling, and Linchao Bao. Self-supervised learning of detailed 3d face reconstruction. *IEEE Transactions on Image Processing*, 29:8696–8705, 2020.
- Subhabrata Choudhury, Iro Laina, Christian Rupprecht, and Andrea Vedaldi. Unsupervised part discovery from contrastive reconstruction. *Advances in Neural Information Processing Systems*, 34:28104–28118, 2021.
- Edo Collins, Radhakrishna Achanta, and Sabine Susstrunk. Deep feature factorization for concept discovery. In *Proceedings of the European Conference on Computer Vision (ECCV)*, pp. 336–352, 2018.
- Yu Deng, Jiaolong Yang, Sicheng Xu, Dong Chen, Yunde Jia, and Xin Tong. Accurate 3d face reconstruction with weakly-supervised learning: From single image to image set. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition Workshops*, pp. 0–0, 2019.
- Apostolos P Georgopoulos, Andrew B Schwartz, and Ronald E Kettner. Neuronal population coding of movement direction. *Science*, 233(4771):1416–1419, 1986.
- Ralph Gross, Iain Matthews, Jeffrey Cohn, Takeo Kanade, and Simon Baker. Multi-pie. *Image and vision computing*, 28(5):807–813, 2010.
- Geoffrey Hinton. Some demonstrations of the effects of structural descriptions in mental imagery. *Cognitive Science*, 3(3):231–250, 1979.
- Geoffrey E Hinton, Alex Krizhevsky, and Sida D Wang. Transforming auto-encoders. In *International conference on artificial neural networks*, pp. 44–51. Springer, 2011.
- Geoffrey E Hinton, Sara Sabour, and Nicholas Frosst. Matrix capsules with em routing. In *International conference on learning representations*, 2018.
- Wei-Chih Hung, Varun Jampani, Sifei Liu, Pavlo Molchanov, Ming-Hsuan Yang, and Jan Kautz. Scops: Self-supervised co-part segmentation. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 869–878, 2019.
- Iiro P Jääskeläinen, Enrico Glerean, Vasily Klucharev, Anna Shestakova, and Jyrki Ahveninen. Do sparse brain activity patterns underlie human cognition? *NeuroImage*, pp. 119633, 2022.
- Diederik P Kingma and Jimmy Ba. Adam: A method for stochastic optimization. *arXiv preprint arXiv:1412.6980*, 2014.
- Adam Kosiorek, Sara Sabour, Yee Whye Teh, and Geoffrey E Hinton. Stacked capsule autoencoders. *Advances in neural information processing systems*, 32, 2019.
- Yann LeCun. A path towards autonomous machine intelligence version 0.9. 2, 2022-06-27. 2022.
- Shilong Liu, Lei Zhang, Xiao Yang, Hang Su, and Jun Zhu. Unsupervised part segmentation through disentangling appearance and shape. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 8355–8364, 2021.

- Ziwei Liu, Ping Luo, Xiaogang Wang, and Xiaoou Tang. Deep learning face attributes in the wild. In *Proceedings of the IEEE international conference on computer vision*, pp. 3730–3738, 2015.
- David Marr. *Vision: A computational investigation into the human representation and processing of visual information*. MIT press, 2010.
- David Marr and Herbert Keith Nishihara. Representation and recognition of the spatial organization of three-dimensional shapes. *Proceedings of the Royal Society of London. Series B. Biological Sciences*, 200(1140):269–294, 1978.
- Pascal Paysan, Reinhard Knothe, Brian Amberg, Sami Romdhani, and Thomas Vetter. A 3d face model for pose and illumination invariant face recognition. In *2009 sixth IEEE international conference on advanced video and signal based surveillance*, pp. 296–301. Ieee, 2009.
- Tomaso Poggio and Shimon Edelman. A network that learns to recognize three-dimensional objects. *Nature*, 343(6255):263–266, 1990.
- Sara Sabour, Nicholas Frosst, and Geoffrey E Hinton. Dynamic routing between capsules. *Advances in neural information processing systems*, 30, 2017.
- Sara Sabour, Andrea Tagliasacchi, Soroosh Yazdani, Geoffrey Hinton, and David J Fleet. Unsupervised part representation by flow capsules. In *International Conference on Machine Learning*, pp. 9213–9223. PMLR, 2021.
- Manish Singh and Donald D Hoffman. Part-based representations of visual shape and implications for visual cognition. In *Advances in psychology*, volume 130, pp. 401–459. Elsevier, 2001.
- James W Tanaka and Diana Simonyi. The “parts and wholes” of face recognition: A review of the literature. *Quarterly Journal of Experimental Psychology*, 69(10):1876–1889, 2016.
- Luan Tran and Xiaoming Liu. Nonlinear 3d face morphable model. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 7346–7355, 2018.
- Jonathan R Williford, Brandon B May, and Jeffrey Byrne. Explainable face recognition. In *European conference on computer vision*, pp. 248–263. Springer, 2020.
- Shangzhe Wu, Christian Rupprecht, and Andrea Vedaldi. Unsupervised learning of probably symmetric deformable 3d objects from images in the wild. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 1–10, 2020.
- Chang Yu, Xiangyu Zhu, Xiaomei Zhang, Zidu Wang, Zhaoxiang Zhang, and Zhen Lei. Hp-capsule: Unsupervised face part discovery by hierarchical parsing capsule network. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 4032–4041, 2022.
- Xing Zhang, Lijun Yin, Jeffrey F Cohn, Shaun Canavan, Michael Reale, Andy Horowitz, Peng Liu, and Jeffrey M Girard. Bp4d-spontaneous: a high-resolution spontaneous 3d dynamic facial expression database. *Image and Vision Computing*, 32(10):692–706, 2014.
- Zhenyu Zhang, Yanhao Ge, Renwang Chen, Ying Tai, Yan Yan, Jian Yang, Chengjie Wang, Jilin Li, and Feiyue Huang. Learning to aggregate and personalize 3d face from in-the-wild photo collection. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 14214–14224, 2021.
- Zhenyu Zhang, Yanhao Ge, Ying Tai, Weijian Cao, Renwang Chen, Kunlin Liu, Hao Tang, Xiaoming Huang, Chengjie Wang, Zhifeng Xie, et al. Physically-guided disentangled implicit rendering for 3d face modeling. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 20353–20363, 2022.
- Yuxiang Zhou, Jiankang Deng, Irene Kotsia, and Stefanos Zafeiriou. Dense 3d face decoding over 2500fps: Joint texture & shape convolutional mesh decoders. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 1097–1106, 2019.