

Revisiting Active Learning in the Era of Vision Foundation Models

Anonymous authors

Paper under double-blind review

Abstract

Foundation vision or vision-language models are trained on large unlabeled or noisy data and learn robust representations that can achieve impressive zero- or few-shot performance on diverse tasks. Given these properties, they are a natural fit for *active learning* (AL), which aims to maximize labeling efficiency, but the full potential of foundation models has not been explored in the context of AL, specifically in the low-budget regime. In this work, we evaluate how foundation models influence three critical components of effective AL, namely, 1) initial labeled pool selection, 2) ensuring diverse sampling, and 3) the trade-off between representative and uncertainty sampling. We systematically study how the robust representations of foundation models (DINOv2, OpenCLIP) challenge existing findings in active learning. Our observations inform the principled construction of a new simple and elegant AL strategy that balances uncertainty estimated via dropout with sample diversity. We extensively test our strategy on many challenging image classification benchmarks, including natural images as well as out-of-domain biomedical images that are relatively understudied in the AL literature. Source code will be made available.

1 Introduction

Foundation Models Oquab et al. (2023); Cherti et al. (2022); Bommasani et al. (2022) have become ubiquitous in computer vision. The advent of large vision and vision-language models, pretrained on web-scale data corpora, has facilitated a significant enhancement of visual representation spaces. Despite differences in pretraining (e.g. contrastive frameworks with language supervision Cherti et al. (2022) or vision-only instance discrimination Oquab et al. (2023)), the shared theme among vision Foundation Models are robust learned representations that can be effectively leveraged for state-of-the-art performance on multiple downstream tasks. These learned visual features have direct implications for machine learning paradigms designed to mitigate data paucity challenges, most notably deep active learning.

Active learning (AL) Sener & Savarese (2018); Ash et al. (2020); Gal et al. (2017); Kirsch et al. (2022); Akililu & Yeung (2022); Hacohen et al. (2022); Yehuda et al. (2022); Parvaneh et al. (2022); Mahmood et al. (2022) is a machine learning framework that addresses the scarcity of labeled data within a limited label budget. It achieves this by iteratively requesting labels from an external oracle, such as a clinical expert. Stated differently, the challenge is to determine the most beneficial labels to query when constrained by a limited labeling budget in order to maximize model performance. This approach is especially pertinent in practical computer vision applications that necessitate the creation of domain-specific datasets for custom tasks. In situations where labeled data is scarce and labor-intensive to produce — such as annotating high-resolution histopathology images for tumor classification — a well-designed AL strategy can optimize resource allocation and substantially lower acquisition costs.

Previous research has tested the benefit of using pretrained representations during AL by leveraging representations of unlabeled data to 1) address the cold-start problem by selecting a good initial pool of candidates for labeling Hacohen et al. (2022); Chen et al. (2023); Chandra et al. (2020), 2) improve query functions by selecting points that maximize the coverage of the representation space Yehuda et al. (2022); Sener & Savarese (2018) and, 3) incorporating unlabeled samples in the training process via semi-supervised learning

Gao et al. (2020); Simeoni et al. (2021). However, these studies limit their focus to supervised pretraining on ImageNet or self-supervised pretraining on available unlabeled data, which often proves impractical in many real-world scenarios. For instance, biomedical imaging datasets exhibit distribution shifts from natural images and may not have sufficient samples for effective self-supervised representation learning.

Foundation Models offer a compelling solution to these challenges. Image embeddings extracted from these models are semantically organized in the representation space, as evidenced by impressive zero- and few-shot performance with simple linear models, even on fine-grained classification datasets. There is also evidence to suggest that they are robust to domain shifts and generalize well to out-of-distribution data. Since these embeddings "just work" out of the box, building dataset-specific feature extractors is no longer necessary. For these reasons, we envision that future research in AL will build upon the ever-increasing capabilities Dehghani et al. (2023); Sun et al. (2023) of Vision and Vision-Language Foundation Models to formulate efficient and scalable acquisition strategies. However, there is limited research Tran et al. (2022) on the impact of Foundation Models on AL. Our work seeks to re-examine the pillars of effective AL strategies in this context, specifically, the low-budget regime in which only a handful of images per class can be annotated.

Our key contributions are the following: **1)** We introduce a simple, performant, and scalable AL strategy, **DropQuery**, which we construct based on a careful analysis of four key elements of successful AL methods. Our strategy outperforms the current state-of-the-art on a diverse collection of datasets including fine-grained image classification, out-of-distribution biomedical images, and image classification at scale, all of which are relatively understudied in AL. The preliminary experiments informing the construction of our strategy systematically explore the impact of initial pool selection, the trade-off between uncertainty and representative sampling, the importance of diversity in query selection, and the potential benefits of leveraging unlabeled data for model training. Our findings **2)** challenge established research on the cold-start problem and **3)** counter the notion that uncertainty-based queries are ineffective in the low-budget regime. Additionally, we demonstrate the difficulties of leveraging semi-supervised learning as a complementary approach for building accurate models. The compelling results and novel insights from our study will spur the use of Foundation Models as a "batteries included" launchpad for future AL research.

2 Background and Related Works

Traditional research in AL for image classification has largely focused on the development of acquisition functions to query samples for labeling by an oracle. These strategies have spanned uncertainty based sampling approaches Shannon (1948), Bayesian methods Gal et al. (2017); Kirsch et al. (2022), strategies to maximize sample diversity, query by committee strategies Melville & Mooney (2004) and techniques to estimate the largest update to the model parameters Ash et al. (2020).

Uncertainty-based methods supply a single measure of uncertainty (epistemic or aleatoric) for unlabeled samples so as to rank them for acquisition. **Entropy** selects instances with maximum predictive entropy, **Uncertainty** selects instances with the lowest confidence and **Margins** selects instances with the lowest margin between the highest and second highest predicted class probabilities. The Bayesian approaches to AL (Gal et al., 2017; Kirsch et al., 2019; Woo, 2023) leverage Bayesian neural networks to model uncertainty and the potential informativeness of unlabeled instances. Bayesian Active Learning by Disagreement (**BALD** (Gal et al., 2017)) aims to query instances that maximize the mutual information gain between model parameters and predictive outputs. Additionally, the **PowerBALD** Kirsch et al. (2022) query challenges the traditional top- B acquisition approach by noting the correlation of queried instances *between* each iteration of AL, which is alleviated by introducing stochasticity in the query.

The prior works that have placed an emphasis on diversity sampling argue that the classifier should learn good decision boundaries in the representation space early. In the lens of these diversity-based queries, the AL paradigm can be re-framed as "*what are the diverse instances that are representative of the data distribution?*". The **Coreset** algorithm Sener & Savarese (2018) can be approximated as solving the k -Center greedy problem Farahani & Hekmatfar (2009), where the distance between any instance and its nearest cluster center (the labeled instances from previous AL iterations) is minimized. Following the Coreset query, the recently developed **ProbCover** query aims to avoid selection of outlier instances and query more

representative points. This is done by recasting the AL problem as a max coverage problem Nemhauser et al. (1978).

A hybrid technique, **BADGE** Ash et al. (2020), uses an AL query that inspects the gradients of a neural network’s final layer relative to the current model’s prediction. This identifies unlabeled instances that could induce significant model updates. The underlying intuition is that samples prompting large gradient updates require substantial adjustments, signifying uncertainty in samples with new features. While this method yields diverse and highly uncertain samples, it is computationally intensive due to the storage of penultimate activations. **Alfa-Mix** Parvaneh et al. (2022) solicits unlabeled samples with the greatest classification prediction variability when their representations are linearly interpolated with labeled instances, suggesting that the model needs to learn new features from unlabeled data points. **Typiclust** Hacoen et al. (2022) during the early AL stages, queries typical instances leveraging the representation space. Clustering in a semantically meaningful feature space after self-supervised learning ensures maximum diversity sampling. Sampling dense regions within clusters aids in better classifier learning within feature space.

However, in most of the settings considered by these works, a model is trained from scratch at each iteration using a random initialization or an ImageNet pre-trained backbone. The resulting models are often poorly calibrated Guo et al. (2017) and provide fail to provide robust estimates of uncertainty. These settings also require a relatively large labeling budget as training deep non-linear models with limited labels can be challenging Yuan et al. (2020). Consequently, a number of such strategies have been shown to under perform random sampling in the low budget Simeoni et al. (2021); Hacoen et al. (2022), or do not perform significantly better than random when strong regularization is applied Munjal et al. (2022).

Recent methods designed for the low budget regime Hacoen et al. (2022); Yehuda et al. (2022) take a more holistic approach to developing an effective AL strategy by leveraging pre-trained model embeddings to cluster features and select representative points which has been shown to improve the selection of the initial labeled pool. Other approaches aim to exploit unlabeled points to using self-supervised or semi-supervised learning, or a combination of both (Chan et al. (2020); Bai et al. (2021)). Their findings demonstrate that leveraging rich representations leads to significant improvements in AL performance in the context of a small labelling budget.

Given these promising results, it is reasonable to conjecture that embeddings from large-scale vision transformers trained on billions of images would amplify the efficacy of these complementary components, constructing an effective strategy that surpasses a simpler baseline consisting of only a standalone acquisition function. To comprehensively investigate these facets of AL, we compare the impact of a simple pool initialization strategy which leverages the implicit structure of the representation space to sample diverse and representative points. Further, we investigate different classes of query functions in this context to compare uncertainty based approaches with typicality based methods as the latter have been shown to significantly outperform the former in the low-budget regime. Orthogonal to the query function, we investigate if semi-supervision via label propagation can be an effective aid in improving the performance of an Active Learner.

Although some recent work has explored the effects of pretraining on the AL query Hacoen et al. (2022); Tamkin et al. (2022), there has not been a rigorous evaluation of AL queries with respect to developments in Foundation Models and vision-language pretraining that have yielded highly expressive and rich visual representation spaces. In the following sections, we outline the critical components necessary for an effective AL query in the context of large Foundation Models.

3 Investigating the pillars of effective Active Learning strategies

Formally, we consider the batch AL setting: let $\mathcal{D} = \{\mathcal{D}_{\text{pool}} \cup \mathcal{D}_{\text{test}}\}$ be a dataset with a held-out test set and training pool $\mathcal{D}_{\text{pool}} = \{\mathcal{D}_U \cup \mathcal{D}_L\}$ consisting of unlabeled instances $\{\mathbf{x}_i\}$ for $i \in \{N_U\}$ and labeled instances $\{(\mathbf{x}_j, y_j)\}$ for $j \in \{N_L\}$. Let $f : \mathbb{R}^{H \times W \times 3} \rightarrow \mathbb{R}^d$ be a feature extractor such that $\mathbf{z}_i := f(\mathbf{x}_i) \in \mathbb{R}^d$ is a feature vector and d is the embedding dimension. Let $g(\mathbf{z}; \boldsymbol{\theta}) : \mathbb{R}^d \rightarrow \mathbb{R}^K$ be a classifier parameterized by $\boldsymbol{\theta}$. The typical AL procedure consists of a series of sequential iterations beginning at $t = 0$ where the labeled pool \mathcal{D}_L is the empty set. At each iteration, a querying function $a(\{\mathbf{z}_i : i \in \{N_U\}\}; \boldsymbol{\theta}_t)$, which given the current model parameters $\boldsymbol{\theta}_t$, receives as input all unlabeled instances, selects B instances to be labeled by

an external oracle (e.g. clinical expert). Once labels are acquired, these labeled instances are subsumed in \mathcal{D}_L and removed from the unlabeled pool, and the model is retrained on this slightly larger labeled pool. We simulate the AL procedure by hiding labels y_i until queried for a chosen instance \mathbf{x}_i .

In this work, we employ frozen vision-only or vision-language Foundation Models as the feature extractor $f(\cdot)$ and a linear head as the classifier $g(\cdot)$. We only require a single forward pass through the feature extractor to generate embeddings which are saved for use in our various experiments. This enables us to efficiently study a wide range of experimental settings for AL. Unless mentioned otherwise, we use a DINOv2 ViT-g14 Oquab et al. (2023) transformer as the feature extractor. Simple linear models trained on features extracted by this model achieve performance that is just shy of state-of-the-art, making them a compelling alternative to end-to-end fine-tuning of the backbone with scarce labels. Following the recommendations of Munjal et al. (2022), we apply strong regularization to our models in the form of weight decay (1e-2) and aggressive dropout (0.75). Note that the benchmarks used to evaluate the various AL methods in this work were not used in the pretraining of the foundation models we investigated (we refer the reader to the data curation processes outlined Oquab et al. (2023)).

In our experiments, we set a query budget B of 1 sample per class per iteration. We run our Active Learning loop for 20 iterations and average our results over 5 random seeds for each experiment. We analyze the following query functions: Random Sampling baseline, Entropy, Uncertainty, Margins, Core-Set (greedy k-centers), BALD, Power BALD, BADGE, ALFA-Mix, Typiclust, and ProbCover. The hyper-parameters for these query functions, if any, are taken from the original publication.

3.1 The impact of initial pool selection

We begin our study by measuring the impact of different initial pool selection strategies in AL, particularly in the *cold-start* scenario where no data has been used for training the classifier. It has been shown in the recent literature Hachohen et al. (2022); Yehuda et al. (2022); Chen et al. (2023) that the initial pool is crucial for establishing a good rudimentary classifier that enjoys performance gains throughout AL. Hachohen et al. (2022) and Yehuda et al. (2022) also argue that the AL acquisition function need not be decoupled from initial pool selection. Rather, an AL query should acquire representative samples so that the classifier can learn good decision boundaries from the very first query. Intuitively, in order for an AL query to be effective, it must rely on the current classifier’s estimates of uncertainty or informativeness.

To assess initialization strategies, we contrast AL query performance when the initial training pool for the active learner is randomly selected for labeling to a centroid-seeking approach following Pourahmadi et al. (2021), where the initial pool consists of samples from \mathcal{D}_U that are the closest to class centers after K -means clustering in the feature space, where B is the number of clusters. **Typiclust** Hachohen et al. (2022) and **ProbCover** utilize different initialization strategies based on sample density and maximizing coverage, respectively, so we hold these queries true to their initialization approach.

Table 1 compares the deltas (Δ) in test set performance of a linear classifier actively trained on Foundation Model features using a randomly initialized initial pool versus a centroid-based initial pool. Note that a random initial pool is suboptimal to methods that explicitly take advantage of semantically meaningful embedding spaces (i.e. **Typiclust** or **ProbCover**). The results dispel previous preliminary findings Chandra et al. (2020) that emphasize that there is no significant difference in initial pool selection strategies for AL. The tremendous performance gains in early AL iterations for uncertainty-based AL queries like **Entropy** sampling enable these methods to surpass queries like **Typiclust** Hachohen et al. (2022) and **ProbCover**.

Table 1 also demonstrates the impact of initial pool selection on AL queries acting on Foundation Model features. The results some queries like **Uncertainty**, **Entropy**, and **Coreset**, enjoy performance gains throughout AL given a centroid-based initialization, a major boost to random initialization. Interestingly, some queries like **Alfa-Mix** and **BADGE** have deltas that converge within 2-4 iterations, and in later iterations (8-16) we observe higher accuracy with a randomly selected initial pool. Since the **Alfa-Mix** query crucially relies on interpolation in the feature space, we hypothesize that the separability of Foundation Model representation space renders differences between initial pooling strategies negligible. After a few iterations, the robust visual representations from Foundation Models enable the selection of highly repre-

Table 1: Effect of initial pool selection on performance. Test set accuracy using our centroid-based initialization. In parentheses, we show the difference (Δ) in performance when utilizing our centroid initialization vs. random initialization where a positive (Δ) shown in green indicates improvement over random initialization. We show AL iterations t for datasets CIFAR100 Krizhevsky (2009), Food101 Bossard et al. (2014), ImageNet-100 Gansbeke et al. (2020), and DomainNet-Real Peng et al. (2019) (from top to bottom) with DINOv2 ViT-g14 as the feature extractor f . For both the Typiclust and ProbCover queries, we report the test accuracy using their own respective initialization strategies for the cold-start.

t	Random	Uncertainty	Entropy	Margins	BALD	pBALD	Coreset	BADGE	Alfa-mix	Typiclust	ProbCover
CIFAR100											
1	72.4 (+24.4)	72.4 (+24.4)	72.4 (+24.4)	72.4 (+24.4)	72.4 (+24.4)	72.4 (+24.4)	72.4 (+24.4)	72.4 (+24.4)	72.4 (+24.4)	64.6	62.3
2	78.1 (+13.6)	76.7 (+14.0)	76.5 (+18.4)	79.1 (+9.2)	78.6 (+11.3)	80.3 (+9.0)	77.7 (+13.2)	79.8 (+7.3)	80.7 (+2.7)	80.8	76.2
4	82.5 (+3.7)	80.6 (+5.9)	78.8 (+8.4)	84.0 (+1.4)	82.1 (+1.7)	85.2 (+1.3)	81.9 (+3.7)	84.6 (+0.5)	83.7 (-0.1)	86.8	81.9
8	86.4 (+0.4)	85.3 (+1.1)	84.0 (+2.6)	88.3 (+0.4)	86.3 (+1.1)	88.8 (+0.4)	84.5 (+0.2)	88.8 (-0.1)	87.3 (-0.5)	88.4	86.5
16	89.2 (-0.0)	89.2 (-0.0)	88.6 (+0.8)	90.9 (+0.2)	89.0 (+0.6)	90.9 (+0.1)	88.0 (-0.3)	90.7 (-0.2)	90.4 (-0.4)	89.3	89.1
Food101											
1	69.6 (+22.3)	69.6 (+22.3)	69.6 (+22.3)	69.6 (+22.3)	69.6 (+22.3)	69.6 (+22.3)	69.6 (+22.3)	69.6 (+22.3)	69.6 (+22.3)	68.3	66.1
2	74.5 (+10.1)	69.6 (+18.8)	69.4 (+19.5)	73.0 (+10.3)	69.7 (+18.9)	73.7 (+6.6)	69.9 (+18.5)	72.9 (+8.2)	77.1 (+3.0)	79.1	72.3
4	79.3 (+2.1)	73.2 (+9.7)	72.1 (+13.5)	78.1 (+2.7)	72.1 (+9.9)	79.0 (+0.8)	71.7 (+8.7)	78.7 (+1.2)	80.5 (+0.9)	83.1	78.1
8	83.9 (+0.1)	79.4 (+2.2)	77.9 (+4.9)	85.0 (+0.3)	78.0 (+3.7)	85.4 (-0.3)	76.8 (+3.5)	85.5 (+0.2)	85.1 (-0.5)	86.0	81.9
16	87.3 (-0.2)	85.6 (+0.4)	84.3 (+1.6)	89.4 (-0.1)	83.8 (+1.5)	89.4 (+0.0)	81.7 (+0.8)	89.5 (+0.1)	88.8 (-0.3)	87.3	85.1
ImageNet-100											
1	80.8 (+26.0)	80.8 (+26.0)	80.8 (+26.0)	80.8 (+26.0)	80.8 (+26.0)	80.8 (+26.0)	80.8 (+26.0)	80.8 (+26.0)	80.8 (+26.0)	76.7	76.6
2	85.4 (+8.9)	83.8 (+23.8)	82.5 (+24.7)	86.2 (+7.2)	86.6 (+7.9)	88.0 (+4.1)	84.8 (+8.3)	87.0 (+5.1)	87.3 (+2.4)	89.5	89.1
4	88.8 (+2.0)	86.2 (+11.8)	85.6 (+17.0)	88.9 (-0.1)	87.9 (-0.3)	90.6 (-0.1)	86.6 (+0.9)	89.6 (-0.2)	90.2 (-0.5)	92.3	91.7
8	91.6 (+0.6)	88.4 (+2.7)	87.8 (+6.0)	91.5 (-0.7)	89.2 (-0.6)	92.3 (-0.7)	88.6 (-0.5)	92.3 (-0.3)	93.2 (-0.2)	93.3	92.7
16	93.0 (-0.3)	91.0 (+0.5)	90.5 (+0.8)	93.5 (-0.8)	91.3 (-0.1)	94.1 (-0.3)	90.4 (-0.7)	93.8 (-0.4)	94.3 (-0.1)	93.4	93.3
DomainNet-Real											
1	68.5 (+23.6)	68.5 (+23.6)	68.5 (+23.6)	68.5 (+23.6)	68.5 (+23.6)	68.5 (+23.6)	68.5 (+23.6)	68.5 (+23.6)	68.5 (+23.6)	64.8	63.9
2	71.9 (+10.1)	70.6 (+16.5)	70.1 (+19.7)	72.0 (+10.1)	71.7 (+11.5)	73.1 (+7.8)	71.1 (+12.2)	72.6 (+7.4)	73.6 (+2.1)	73.0	73.8
4	76.0 (+2.9)	72.9 (8.4)	72.2 (+13.5)	75.7 (+3.3)	73.9 (4.6)	77.1 (1.4)	73.7 (+4.5)	76.6 (+1.2)	76.2 (-0.4)	74.8	77.8
8	79.6 (+0.4)	77.1 (+3.0)	76.5 (+6.2)	80.1 (+0.2)	77.5 (+1.2)	81.0 (+0.3)	77.0 (+1.1)	80.8 (+0.1)	78.4 (-0.3)	76.2	80.6
16	82.2 (+0.1)	81.3 (+0.9)	80.7 (+1.7)	84.0 (-0.0)	81.2 (+0.1)	84.0 (-0.0)	80.5 (+0.1)	84.3 (-0.1)	79.5 (-0.2)	78.0	82.3

sentative samples, which help the classifier establish good class boundaries in few-shot. We conclude that in the ultra-low budget, where few examples per class have been acquired, initialization is crucial for AL performance, but in later iterations, it is not as significant and a randomly selected initial pool works just as well.

3.2 On the importance of diversity in query selection

In line with initial pool selection, we evaluate how partitioning the representation space via clustering is crucial for AL performance in subsequent iterations even after the initial query. To conduct these experiments, we allow AL queries that use stand alone measures of uncertainty (i.e. **Uncertainty**, **Entropy**, **Margins**, and **BALD**) to deviate from the top- B acquisition pattern persistent in the AL literature. As noted by Kirsch et al. (2022), top- B acquisition can potentially lead to correlation between queried batches for some t_i and t_j , which can hurt performance.

We modify these queries to query the top- $(K \cdot B)$ samples based on their uncertainty metrics ($K = 50$), and then cluster these samples by k -means into B clusters and select points closest to the cluster centroids. We also experiment with enabling dropout at inference time to add an element of stochasticity that disrupts the classifier’s estimates of uncertainty, allowing for diverse sample selection. We report the results of our experiments in Table 2. To decouple the influence of the initial pool selection, all queries including **Typiclust** and **ProbCover** use an identical randomly selected pool of initial samples. By imposing simple diversity measures, uncertainty-based queries like **Uncertainty**, **Entropy**, **Margins**, and **BALD** surpass the performance of AL strategies that explicitly incorporate diversity in their queries.

3.3 Representative versus uncertainty sampling and the phase transition

Much prior art in AL has placed an emphasis on the distinction between sampling the most uncertain instances in \mathcal{D}_U for the active learner and sampling diverse, representative instances for establishing well-

Table 2: Marginal (Δ) in performance for stand-alone uncertainty measures (i.e. softmax uncertainty, predictive entropy, margins sampling, or BALD) when using clustering (Δ_k) or when using clustering with dropout during inference (Δ_{k+d}). For fairness, we hold all queries to use a randomly selected initial pool. Power BALD, Coreset, BADGE, Alfa-mix, Typiclust, and ProbCover inherently enforce diversity in their respective queries, so we do not show Δ s for these methods. The cells are color-coded according to the magnitude of Δ for better visualization.

t	Uncertainty			Entropy			Margins			BALD		pBALD	Coreset	BADGE	Alfa-mix	Typiclust	ProbCover
	Acc.	Δ_k	Δ_{k+d}	Acc.	Δ_k	Δ_{k+d}	Acc.	Δ_k	Δ_{k+d}	Acc.	Δ_k						
CIFAR100																	
2	79.6	+13.1	+17.0	79.4	+16.6	+21.4	80.4	+7.9	+10.5	76.9	+9.5	71.2	64.5	72.5	78.0	78.9	74.6
4	86.7	+12.0	+12.0	86.7	+15.9	+16.3	87.1	+4.1	+4.5	86.6	+6.2	83.9	78.2	84.1	83.9	86.4	82.2
8	89.9	+5.6	+5.7	89.8	+8.2	+8.4	89.8	+1.8	+1.9	89.3	+4.1	88.4	88.3	90.9	90.8	90.0	89.1
16	91.2	+2.2	+1.9	91.4	+3.5	+3.6	91.4	+0.9	+0.7	91.0	+2.7	90.8	88.3	90.9	90.8	90.0	89.1
Food101																	
2	70.3	+16.1	+19.4	68.8	+14.3	+18.9	72.3	+7.4	+9.6	64.0	+13.2	67.1	51.5	64.8	74.1	77.0	73.8
4	81.8	+17.0	+18.3	80.0	+17.6	+20.2	81.7	+5.7	+6.2	77.5	+15.3	78.2	63.0	77.5	79.6	82.5	78.6
8	86.4	+9.3	+9.1	85.7	+11.1	+12.7	86.1	+1.5	+1.5	84.3	+10.0	85.6	73.4	85.3	85.6	85.8	82.3
16	88.9	+4.5	+3.6	88.7	+5.9	+6.1	89.0	+0.1	-0.4	87.9	+5.6	89.4	80.8	89.4	89.2	87.4	85.3
ImageNet-100																	
2	88.5	+21.6	+28.5	88.4	+21.1	+30.5	88.5	+8.5	+9.5	86.7	+8.0	83.9	76.5	81.8	84.9	89.1	87.0
4	90.6	+15.6	+16.2	90.4	+20.9	+21.8	91.2	+2.3	+2.2	90.2	+2.0	90.6	85.7	89.8	90.7	92.4	91.8
8	93.3	+7.6	+7.6	92.0	+11.3	+10.3	93.3	+1.3	+1.1	91.4	+1.6	92.9	89.0	92.6	93.4	93.3	92.7
16	94.1	+4.1	+3.6	94.2	+4.7	+4.5	94.4	+0.3	+0.2	93.3	+1.9	94.4	91.1	94.1	94.4	93.8	93.8
DomainNet-Real																	
2	71.5	+12.6	+17.4	71.2	+15.4	+20.8	72.3	+7.1	+10.4	68.1	+7.8	65.3	58.8	65.2	71.4	72.4	71.3
4	79.4	+13.9	+14.9	78.8	+19.5	+20.1	79.1	+6.5	+6.6	78.0	+8.7	75.6	69.2	75.4	76.6	75.2	77.3
8	82.7	+8.3	+8.5	82.5	+12.2	+12.2	82.4	+2.6	+2.5	81.7	+5.4	80.7	76.0	80.7	78.7	77.0	80.4
16	84.6	+4.4	+4.2	84.5	+5.8	+5.5	84.4	+0.7	+0.4	84.5	+3.3	84.0	80.4	84.3	79.7	78.3	82.1

defined decision boundaries. It is a well-known fact that querying diverse, but relatively representative instances early on in the AL procedure allows for the classifier to learn the structure of the representation space early in order to make uncertainty estimates in later iterations more reliable Hacohen et al. (2022). This trade-off between diversity sampling in the low-data regime before uncertainty sampling is known as the *phase transition* Hacohen et al. (2022).

However, when leveraging large Foundation Models as feature extractors, we observe a phenomenon that is a striking deviation from the existing literature. As demonstrated in Table 2, when controlling for random initialization, uncertainty sampling is actually competitive to representative sampling methods like **Typiclust** as early as the 2nd AL iteration (CIFAR100, DomainNet-Real), and even beat these methods in later iterations. We see no evidence of the theorized phase transition, and directly disprove the current notion that uncertainty sampling is ineffective in low-budget AL. Further, we witness that **Typiclust** underperforms the uncertainty based queries in later iterations (8-16, Food101 & DomainNet-Real).

3.4 Leveraging unlabeled instances for training the active learner

Even with a good initial query, the classifier $g(\mathbf{z}_i; \boldsymbol{\theta})$ may perform poorly in the low-data regime since there are a limited number of training examples. In cases where the labeling budget is prohibitive, it may be difficult to acquire enough training instances for a classifier to establish good enough decision boundaries early on in AL. This motivates the use of unlabeled instances in a principled way to ensure that the classifier maximizes performance even in the low-data regime. However, in our experiments find that the efficacy of semi-supervised learning in this setting is questionable at best, with wide variation across query methods and datasets. While we do see an initial boost in performance, contrary to Gao et al. (2020); Simeoni et al. (2021), the gap quickly narrows and label propagation underperforms the reference query. Propagating labels from uncertain queried samples may cause points across the decision boundary to be assigned to incorrect classes, hampering performance in the long run. We point the reader to the supplements for an in depth analysis using a popular semi-supervised algorithm.

In summary, our experiments with initial pool selection (we study the importance of intelligently selecting the initial labeled pool by comparing centroid-based initialization with random initialization) motivates the use of a centroid-based initialization strategy to overcome the cold start problem. Additionally, our experiments modifying existing uncertainty-based approaches to enforce diversity in query selection motivates the use of clustering to select diverse samples during active learning. Our findings also indicate that a clustering approach similar to **Alfa-Mix** Parvaneh et al. (2022) selects diverse candidates which span the representation space. Furthermore, our investigation into the previously identified phase transition implicates the need for an uncertainty-based query function instead of representative sampling throughout active learning. We revisited the notion that uncertainty based queries are outperformed by representative sample selection methods such as **Typiclust** Hachohen et al. (2022) in the low-budget regime. We find that this is not the case, contradicting this existing notion. And finally, our inquiry into enhancing the active learner with unlabeled instances cautions against the use of semi-supervised learning as a complementary approach to active learning.

Based on our findings, an effective AL strategy would initialize the labeled set with representative samples, employ an uncertainty-based query function for shortlisting unlabeled candidates, and select a diverse subset of these candidates.

4 DropQuery , a simple, effective active learning strategy

Algorithm 1 DropQuery

Input: Given unlabeled instances $\mathbf{z}_i \in Z_U$, external oracle $\phi(\cdot)$, budget B .

Output: Queried labels $Y = \{y_i : i \in 1, \dots, B\}$

for $\mathbf{z}_i \in Z$ **do**

$\{\mathbf{z}_i^1, \dots, \mathbf{z}_i^M\} \leftarrow \text{Dropout}(\mathbf{z}_i; \rho)$

▷ Apply dropout to the input features

$n_i \leftarrow \sum_{m=1}^M \mathbb{1}[g(\mathbf{z}_i^m) = g(\mathbf{z}_i; \boldsymbol{\theta})]$

▷ Measure inconsistency among classifier predictions

end for

$Z_c = \{\mathbf{z}_i | n_i > 0.5M \forall \mathbf{z}_i \in Z_U\}$

▷ Use consistency as proxy for uncertainty

$C_k \leftarrow K\text{-means}(Z_c, B)$ where $k \in \{B\}$

▷ Cluster points to enforce diversity

$S_k \leftarrow \{\mathbf{z}_i : \arg \min_{\mathbf{z}_i \in Z_c} \|\mathbf{z}_i - \mathbf{c}_k\|_2^2 \text{ where } \mathbf{c}_k \in C_k\}$

$Y \leftarrow \phi(S_k)$

▷ Retrieve labels from samples closest to centroids

The observations from the previous sections inform the principled construction of a new AL strategy leveraging the robust visual features of Foundation Models, which we refer to as the **DropQuery**. We experiment using dropout perturbations to measure uncertainty and select candidates for annotation. Given features \mathbf{z}_i of an unlabeled instance, we produce M dropout samples of these inputs ($\rho = 0.75$) to get $\{\mathbf{z}_i^1, \dots, \mathbf{z}_i^M\}$. The current classifier at t then makes predictions on these M samples and the original instance \mathbf{z}_i , and we measure the consistency of classifier predictions $\hat{y}_i = g(\mathbf{z}_i; \boldsymbol{\theta})$. If more than half of the M predictions are inconsistent, we add \mathbf{z}_i to the candidate set Z_c . Then we cluster Z_c into B clusters and select the point closest to the center. In all of our experiments, we set $M = 3$.

We take inspiration from works like Ducoffe & Precioso (2017); Beluch et al. (2018), which leverage query-by-committee to distinguish informative samples. It is well-known that dropout on the weights of a classifier during inference simulates an ensemble of models Warde-Farley et al. (2014). However, our strategy is a nuanced but critical change from these works. **DropQuery** is more similar in spirit to ALFA-Mix, which interpolates unlabeled points with anchors to perturb them and tests the consistency of their class predictions. Applying dropout perturbs features and those lying close to the decision boundary will have inconsistent predictions, making them candidates for querying. Candidate clustering ensures the diversity of selected points as shown in Table 3. Since label propagation has a detrimental impact on our query, we do not consider it a core component.

Table 3: Test accuracy for our method (with random acquisition as a reference) utilizing dropout at inference time (DQ), with a centroid-based initial pool (DQ_c), and dropout with semi-supervised learning in the form of label propagation (DQ_{ssl}).

t	Random	DQ	DQ _c	DQ _{ssl}	Random	DQ	DQ _c	DQ _{ssl}	Random	DQ	DQ _c	DQ _{ssl}	Random	DQ	DQ _c	DQ _{ssl}
	CIFAR100				ImageNet-100				Food101				DomainNet-Real			
1	48.1	48.1	72.6	53.3	54.7	54.7	79.1	57.8	47.4	47.4	71.3	49.7	44.8	44.8	68.0	46.8
2	64.5	81.0	83.5	79.2	76.5	88.8	89.4	85.9	64.4	72.7	76.1	70.6	61.8	73.0	75.0	68.9
4	78.7	87.4	87.7	87.1	86.8	91.7	91.5	90.9	77.2	81.8	82.2	80.9	73.1	79.1	78.7	76.7
8	86.1	89.8	90.1	89.6	91.0	93.2	93.0	92.8	83.8	86.3	86.3	84.7	79.2	82.4	82.2	80.0
16	89.2	91.4	91.5	91.0	93.3	94.1	94.1	93.7	87.5	89.5	89.4	86.7	82.1	84.8	84.7	82.1

5 Experimental results

Our strategy’s effectiveness is demonstrated on several natural image, out-of-domain biomedical, and large-scale natural image datasets. Initially, we assess **DropQuery**’s performance, maintaining the dataset constant while altering the underlying representation space (see Figure 1). Our experiments confirm that larger models generate more resilient visual features, thereby enhancing linear classifier performance in low-budget scenarios. An intriguing phenomenon, observed during iterations 4-16 in Figure 1, reveals that *smaller* models produce embeddings that our AL strategy better accommodates in later iterations. The performance benefits of larger models in early iterations (limited data availability) diminish rapidly, likely due to their expressiveness compared to smaller models’ features. Hence, dropout-motivated uncertainty sampling is not as advantageous. We further note that, on average, Vision-Language Foundation Models outperform their Vision-only counterparts.




Figure 1: Results of our AL strategy on different representation spaces (i.e. DINOv2 Oquab et al. (2023) and OpenCLIP Cherti et al. (2022)). The y-axis is the delta in accuracy between iteration i and $i/2$. In early iterations, the improvements to AL query performance are more pronounced for larger models.

5.1 Natural Image Datasets

Our proposed AL strategy is evaluated through a comprehensive set of experiments on diverse natural image datasets sourced from the VTAB+ benchmark Schuhmann et al. (2022). The VTAB+ benchmark, an expanded version of the VTAB Zhai et al. (2020) benchmark, encompasses a range of challenging visual perception tasks, including fine-grained classification, and is typically used for assessing zero-shot performance. A notable drawback in many prior AL studies is the excessive reliance on datasets such as CIFAR100 or TinyImageNet with small image sizes that are not representative of real-world scenarios where AL would be necessary. Therefore, our experiments include several larger, more complex natural image datasets that closely mirror real-world scenarios. We leave extensive implementation and training details for the Appendix.

Among the fine-grained natural image classification datasets, in Stanford Cars Krause et al. (2013) and Oxford-IIIT Pets Parkhi et al. (2012), our **DropQuery** outperforms all other AL queries in each iteration, while also outperforming complex query approaches like **Alfa-Mix** and **Typiclust** in the low-budget regime




Figure 2: (Top row) Results on fine-grained natural image classification tasks Stanford Cars Krause et al. (2013), FVGC Aircraft Maji et al. (2013), Oxford-IIIT Pets Parkhi et al. (2012), and the Places365 datasets. (Bottom row) AL curves for biomedical datasets including images of peripheral blood smears Acevedo et al. (2020), retinal funduscopy Kaggle & EyePacs (2015), HeLa cell structures Murphy et al. (2000), and skin dermoscopy skinTschandl et al. (2018), covering pathology, ophthalmology, cell biology, and dermatology domains using various imaging modalities. Additional biomedical datasets are explored in the supplement.

in FVGC Aircraft Maji et al. (2013) (see Figure 2). Our approach, which is agnostic to dataset and model, outperforms the state-of-the-art AL queries, which often necessitate additional hyper parameter tuning given the underlying data distribution. We also test our method on a large-scale dataset with 365 classes, Places365 Zhou et al. (2017) (contains approximately 1.8 million images), and our strategy beats all other modern AL queries. These results exemplify the scalability of our method on large datasets where AL would be used to probe the unlabeled data space for important samples.

5.2 Out-of-domain datasets

In addition, we carry out experiments on a variety of biomedical datasets, which significantly deviate from the training distribution of the Foundation Models discussed in this study. The aim of these experiments is to underscore the effectiveness of AL queries when applied to datasets that are out-of-domain or underrepresented in pretraining. This kind of evaluation is especially pertinent in situations where a model, trained in one institution or setting, is deployed in another. An efficient AL query is helpful to obtain a minimum number of samples to label to fine-tune the model for the new task — a realistic scenario often neglected in previous studies. 2 illustrates our strategy’s performance on challenging out-of-domain data. In real-world contexts, **DropQuery** excels as a practical, efficient method for querying hard-to-classify samples for improving the model.

5.3 Statistical significance study

In order to verify the empirical strength of **DropQuery**, we furnish our results with statistical significance tests following the procedure in Parvaneh et al. (2022) and Ash et al. (2020). We conduct paired t -tests to




Figure 3: Win matrices for all AL strategies investigated in our study evaluated on natural image datasets and out-of-domain biomedical image datasets. **(a)** CIFAR100, Food101, Imagenet-100, and DomainNet-Real using DINOv2 VIT-g/14 features and Stanford Cars, FVGC Aircraft, Oxford-III Pets, and Places365 using OpenCLIP VIT-G/14 features (8 total settings). Due to computational costs, **ProbCover** was not evaluated on Places365, so the max value of cells in the **ProbCover** row/column is 7. **(b)** Blood Smear, Diabetic Retinopathy, IICBU Hela, and Skin cancer datasets using DINOv2 VIT-g/14 features (4 total settings). **DropQuery** outperforms all other methods on the natural image datasets and is a strong competitor to all other methods on the biomedical image datasets with statistical significance.

determine whether a particular AL strategy i outperforms another strategy j . We say that query strategy i beats or surpasses strategy j at iteration r if

$$c_{i,j}^r = \frac{\sqrt{5}\mu^r}{\sigma^r} > 2.776, \quad \mu^r = \frac{1}{5} \sum_{k=1}^5 (a_i^r - a_j^r), \quad \sigma^r = \sqrt{\frac{1}{5} \sum_{k=1}^5 (a_i^r - a_j^r - \mu^r)^2}$$

where a_i^r is the accuracy of strategy i at iteration r . This corresponds to the $p = 0.05$ threshold for significance. We compute these $c_{i,j}^r$ for all iterations and sum the number of times strategy i surpassed strategy j at each iteration r (divided by the total number of iterations) to indicate the score of i beating j in a specific dataset-model setting. Figure 3 illustrates two “win” matrices illustrating the proportion of times strategy i has a significantly higher ($p < 0.05$) mean accuracy compared to strategy j . For each pair, at each iteration, the mean accuracy for method i and j are compared using a t-test with $p < 0.05$ and the outcome is win, lose, or tie to yield a fraction of wins from (0, 1). This is repeated for all datasets considered and the values are summed to yield the proportion of wins. For example, in figure 3a, **DropQuery** beats random sampling 7.25/8 fractions of total AL iterations across the 8 dataset settings.

6 Conclusions

In this work, we systematically study four critical components of effective active learning in the context of Foundation Models. Given our observations, we propose a new AL strategy, named **DropQuery**, that combines the benefits of strong initial pool selection by class centroids and a dropout-motivated uncertainty measure for querying unlabeled instances. This method outperforms other AL queries in a variety of nat-

ural image, biomedical, and large-scale datasets and poses a paradigm shift to leveraging the properties of Foundation Model representations in AL.

Limitations and Societal Impact Our work is a principled investigation focused on the interplay of AL and Foundation Models, and we recognize certain limitations. Firstly, our approach presumes availability of public Foundation Models, which may not be universally accessible. Secondly, inherent biases and ethical dilemmas tied to these models could be reflected in our method, possibly leading to biased outcomes or propagation of harmful stereotypes. Despite these issues, the growth of Foundation Models encourages their use in AL, even with out-of-domain datasets. We urge future research to address these concerns while considering the broader ethical implications.

References

- Andrea Acevedo, Anna Merino, Santiago Alf  rez,   ngel Molina, Laura Bold  , and Jos   Rodellar. A dataset of microscopic peripheral blood cell images for development of automatic recognition systems. *Data Brief*, 30(105474):105474, June 2020.
- Josiah Aklilu and Serena Yeung. Alges: Active learning with gradient embeddings for semantic segmentation of laparoscopic surgical images. In Zachary Lipton, Rajesh Ranganath, Mark Sendak, Michael Sjoding, and Serena Yeung (eds.), *Proceedings of the 7th Machine Learning for Healthcare Conference*, volume 182 of *Proceedings of Machine Learning Research*, pp. 892–911. PMLR, 05–06 Aug 2022. URL <https://proceedings.mlr.press/v182/aklilu22a.html>.
- Jordan T. Ash, Chicheng Zhang, Akshay Krishnamurthy, John Langford, and Alekh Agarwal. Deep batch active learning by diverse, uncertain gradient lower bounds. In *International Conference on Learning Representations*, 2020. URL <https://openreview.net/forum?id=ryghZJBKPS>.
- Haoping Bai, Meng Cao, Ping Huang, and Jiulong Shan. Self-supervised semi-supervised learning for data labeling and quality evaluation, 2021.
- William Beluch, Tim Genewein, Andreas N  rnberger, and Jan Kohler. The power of ensembles for active learning in image classification. pp. 9368–9377, 06 2018. doi: 10.1109/CVPR.2018.00976.
- Rishi Bommasani, Drew A. Hudson, Ehsan Adeli, Russ Altman, Simran Arora, Sydney von Arx, Michael S. Bernstein, Jeannette Bohg, Antoine Bosselut, Emma Brunskill, Erik Brynjolfsson, Shyamal Buch, Dallas Card, Rodrigo Castellon, Niladri Chatterji, Annie Chen, Kathleen Creel, Jared Quincy Davis, Dora Demszky, Chris Donahue, Moussa Doumbouya, Esin Durmus, Stefano Ermon, John Etchemendy, Kavin Ethayarajh, Li Fei-Fei, et al. On the opportunities and risks of foundation models, 2022.
- Lukas Bossard, Matthieu Guillaumin, and Luc Van Gool. Food-101 – mining discriminative components with random forests. In *European Conference on Computer Vision*, 2014.
- Yao-Chun Chan, Mingchen Li, and Samet Oymak. On the marginal benefit of active learning: Does self-supervision eat its cake? *ICASSP 2021 - 2021 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*, pp. 3455–3459, 2020.
- Akshay L Chandra, Sai Vikas Desai, Chaitanya Devaguptapu, and Vineeth N. Balasubramanian. On initial pools for deep active learning. In *Preregister@NeurIPS*, 2020.
- Liangyu Chen, Yutong Bai, Siyu Huang, Yongyi Lu, Bihan Wen, Alan Yuille, and Zongwei Zhou. Making your first choice: To address cold start problem in medical active learning. In *Medical Imaging with Deep Learning*, 2023. URL <https://openreview.net/forum?id=5iSBMwm3ln>.
- Mehdi Cherti, Romain Beaumont, Ross Wightman, Mitchell Wortsman, Gabriel Ilharco, Cade Gordon, Christoph Schuhmann, Ludwig Schmidt, and Jenia Jitsev. Reproducible scaling laws for contrastive language-image learning, 2022.
- Mostafa Dehghani, Josip Djolonga, Basil Mustafa, Piotr Padlewski, Jonathan Heek, Justin Gilmer, Andreas Steiner, Mathilde Caron, Robert Geirhos, Ibrahim Alabdulmohsin, Rodolphe Jenatton, Lucas Beyer, Michael Tschannen, Anurag Arnab, Xiao Wang, Carlos Riquelme, Matthias Minderer, Joan Puigcerver, Utku Evci, Manoj Kumar, Sjoerd van Steenkiste, Gamaleldin F. Elsayed, Aravindh Mahendran, Fisher Yu, Avital Oliver, Fantine Huot, Jasmijn Bastings, Mark Patrick Collier, Alexey Gritsenko, Vighnesh Birodkar, Cristina Vasconcelos, Yi Tay, Thomas Mensink, Alexander Kolesnikov, Filip Paveti  , Dustin Tran, Thomas Kipf, Mario Lu    , Xiaohua Zhai, Daniel Keysers, Jeremiah Harmsen, and Neil Houlsby. Scaling vision transformers to 22 billion parameters, 2023.
- M  lanie Ducoffe and Fr  d  ric Precioso. Active learning strategy for cnn combining batchwise dropout and query-by-committee. In *The European Symposium on Artificial Neural Networks*, 2017.
- Reza Zanjirani Farahani and Masoud Hekmatfar. *Facility location: Concepts, Models, algorithms and case studies*. Springer - Verlag Berlin Heidelberg, 2009.

- Yarin Gal, Riashat Islam, and Zoubin Ghahramani. Deep Bayesian active learning with image data. In Doina Precup and Yee Whye Teh (eds.), *Proceedings of the 34th International Conference on Machine Learning*, volume 70 of *Proceedings of Machine Learning Research*, pp. 1183–1192. PMLR, 06–11 Aug 2017. URL <https://proceedings.mlr.press/v70/gal17a.html>.
- Wouter Van Gansbeke, Simon Vandenhende, Stamatios Georgoulis, Marc Proesmans, and Luc Van Gool. Scan: Learning to classify images without labels, 2020.
- Mingfei Gao, Zizhao Zhang, Guo Yu, Sercan Ö. Arik, Larry S. Davis, and Tomas Pfister. Consistency-based semi-supervised active learning: Towards minimizing labeling cost. In Andrea Vedaldi, Horst Bischof, Thomas Brox, and Jan-Michael Frahm (eds.), *Computer Vision – ECCV 2020*, pp. 510–526, Cham, 2020. Springer International Publishing. ISBN 978-3-030-58607-2.
- Chuan Guo, Geoff Pleiss, Yu Sun, and Kilian Q. Weinberger. On calibration of modern neural networks. In *International Conference on Machine Learning*, 2017.
- Guy Hacohen, Avihu Dekel, and Daphna Weinshall. Active learning on a budget: Opposite strategies suit high and low budgets. In Kamalika Chaudhuri, Stefanie Jegelka, Le Song, Csaba Szepesvari, Gang Niu, and Sivan Sabato (eds.), *Proceedings of the 39th International Conference on Machine Learning*, volume 162 of *Proceedings of Machine Learning Research*, pp. 8175–8195. PMLR, 17–23 Jul 2022. URL <https://proceedings.mlr.press/v162/hacohen22a.html>.
- Kaggle and EyePacs. Kaggle diabetic retinopathy detection, jul 2015. URL <https://www.kaggle.com/c/diabetic-retinopathy-detection/data>.
- Andreas Kirsch, Joost van Amersfoort, and Yarin Gal. Batchbald: Efficient and diverse batch acquisition for deep bayesian active learning. In H. Wallach, H. Larochelle, A. Beygelzimer, F. d'Alché-Buc, E. Fox, and R. Garnett (eds.), *Advances in Neural Information Processing Systems*, volume 32. Curran Associates, Inc., 2019. URL https://proceedings.neurips.cc/paper_files/paper/2019/file/95323660ed2124450caa2c46b5ed90-Paper.pdf.
- Andreas Kirsch, Sebastian Farquhar, Parmida Atighehchian, Andrew Jesson, Frederic Branchaud-Charron, and Yarin Gal. Stochastic batch acquisition for deep active learning, 2022.
- Jonathan Krause, Michael Stark, Jia Deng, and Li Fei-Fei. 3d object representations for fine-grained categorization. In *2013 IEEE International Conference on Computer Vision Workshops*, pp. 554–561, 2013. doi: 10.1109/ICCVW.2013.77.
- Alex Krizhevsky. Learning multiple layers of features from tiny images. 2009.
- Rafid Mahmood, Sanja Fidler, and Marc T Law. Low-budget active learning via wasserstein distance: An integer programming approach. In *International Conference on Learning Representations*, 2022. URL <https://openreview.net/forum?id=v80lxjGn23S>.
- S. Maji, J. Kannala, E. Rahtu, M. Blaschko, and A. Vedaldi. Fine-grained visual classification of aircraft. Technical report, 2013.
- Prem Melville and Raymond J. Mooney. Diverse ensembles for active learning. In *Proceedings of the Twenty-First International Conference on Machine Learning, ICML '04*, pp. 74, New York, NY, USA, 2004. Association for Computing Machinery. ISBN 1581138385. doi: 10.1145/1015330.1015385. URL <https://doi.org/10.1145/1015330.1015385>.
- Prateek Munjal, Nasir Hayat, Munawar Hayat, Jamshid Sourati, and Shadab Khan. Towards robust and reproducible active learning using neural networks, 2022.
- R F Murphy, M V Boland, and M Velliste. Towards a systematics for protein subcellular location: quantitative description of protein localization patterns and automated analysis of fluorescence microscope images. *Proc. Int. Conf. Intell. Syst. Mol. Biol.*, 8:251–259, 2000.

- George Nemhauser, Laurence Wolsey, and M. Fisher. An analysis of approximations for maximizing submodular set functions—i. *Mathematical Programming*, 14:265–294, 12 1978. doi: 10.1007/BF01588971.
- Maxime Oquab, Timothée Darcet, Théo Moutakanni, Huy Vo, Marc Szafraniec, Vasil Khalidov, Pierre Fernandez, Daniel Haziza, Francisco Massa, Alaaeldin El-Nouby, Mahmoud Assran, Nicolas Ballas, Wojciech Galuba, Russell Howes, Po-Yao Huang, Shang-Wen Li, Ishan Misra, Michael Rabbat, Vasu Sharma, Gabriel Synnaeve, Hu Xu, Hervé Jegou, Julien Mairal, Patrick Labatut, Armand Joulin, and Piotr Bojanowski. Dinov2: Learning robust visual features without supervision, 2023.
- Omkar M. Parkhi, Andrea Vedaldi, Andrew Zisserman, and C. V. Jawahar. Cats and dogs. In *IEEE Conference on Computer Vision and Pattern Recognition*, 2012.
- Amin Parvaneh, Ehsan Abbasnejad, Damien Teney, Gholamreza (Reza) Haffari, Anton van den Hengel, and Javen Qinfeng Shi. Active learning by feature mixing. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 12237–12246, June 2022.
- Xingchao Peng, Qinxun Bai, Xide Xia, Zijun Huang, Kate Saenko, and Bo Wang. Moment matching for multi-source domain adaptation. In *Proceedings of the IEEE International Conference on Computer Vision*, pp. 1406–1415, 2019.
- Kossar Pourahmadi, Parsa Nooralinejad, and Hamed Pirsiavash. A simple baseline for low-budget active learning. *arXiv preprint arXiv:2110.12033*, 2021.
- Christoph Schuhmann, Romain Beaumont, Richard Vencu, Cade Gordon, Ross Wightman, Mehdi Cherti, Theo Coombes, Aarush Katta, Clayton Mullis, Mitchell Wortsman, Patrick Schramowski, Srivatsa Kundurthy, Katherine Crowson, Ludwig Schmidt, Robert Kaczmarczyk, and Jenia Jitsev. Laion-5b: An open large-scale dataset for training next generation image-text models, 2022.
- Ozan Sener and Silvio Savarese. Active learning for convolutional neural networks: A core-set approach. In *International Conference on Learning Representations*, 2018. URL <https://openreview.net/forum?id=H1aIuk-RW>.
- C. E. Shannon. A mathematical theory of communication. *The Bell System Technical Journal*, 27(3): 379–423, 1948. doi: 10.1002/j.1538-7305.1948.tb01338.x.
- O. Simeoni, M. Budnik, Y. Avrithis, and G. Gravier. Rethinking deep active learning: Using unlabeled data at model training. In *2020 25th International Conference on Pattern Recognition (ICPR)*, pp. 1220–1227, Los Alamitos, CA, USA, jan 2021. IEEE Computer Society. doi: 10.1109/ICPR48806.2021.9412716. URL <https://doi.ieeecomputersociety.org/10.1109/ICPR48806.2021.9412716>.
- Quan Sun, Yuxin Fang, Ledell Wu, Xinlong Wang, and Yue Cao. Eva-clip: Improved training techniques for clip at scale, 2023.
- Alex Tamkin, Dat Pham Nguyen, Salil Deshpande, Jesse Mu, and Noah Goodman. Active learning helps pretrained models learn the intended task. In Alice H. Oh, Alekh Agarwal, Danielle Belgrave, and Kyunghyun Cho (eds.), *Advances in Neural Information Processing Systems*, 2022. URL <https://openreview.net/forum?id=0Ww7UVEoNue>.
- Dustin Tran, Jeremiah Liu, Michael W. Dusenberry, Du Phan, Mark Collier, Jie Ren, Kehang Han, Zi Wang, Zelda Mariet, Huiyi Hu, Neil Band, Tim G. J. Rudner, Karan Singhal, Zachary Nado, Joost van Amersfoort, Andreas Kirsch, Rodolphe Jenatton, Nithum Thain, Honglin Yuan, Kelly Buchanan, Kevin Murphy, D. Sculley, Yarin Gal, Zoubin Ghahramani, Jasper Snoek, and Balaji Lakshminarayanan. Plex: Towards reliability using pretrained large model extensions, 2022.
- Philipp Tschandl, Cliff Rosendahl, and Harald Kittler. The HAM10000 dataset, a large collection of multi-source dermatoscopic images of common pigmented skin lesions. *Sci. Data*, 5(1):180161, August 2018.
- David Warde-Farley, Ian J. Goodfellow, Aaron Courville, and Yoshua Bengio. An empirical analysis of dropout in piecewise linear networks, 2014.

- Jae Oh Woo. Active learning in bayesian neural networks with balanced entropy learning principle. In *The Eleventh International Conference on Learning Representations*, 2023. URL <https://openreview.net/forum?id=ZTMuZ68B1g>.
- Ofer Yehuda, Avihu Dekel, Guy Hacohen, and Daphna Weinshall. Active learning through a covering lens. In Alice H. Oh, Alekh Agarwal, Danielle Belgrave, and Kyunghyun Cho (eds.), *Advances in Neural Information Processing Systems*, 2022. URL <https://openreview.net/forum?id=u6MpfQP9ck>.
- Michelle Yuan, Hsuan-Tien Lin, and Jordan Boyd-Graber. Cold-start active learning through self-supervised language modeling. In *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pp. 7935–7948, Online, November 2020. Association for Computational Linguistics. doi: 10.18653/v1/2020.emnlp-main.637. URL <https://aclanthology.org/2020.emnlp-main.637>.
- Xiaohua Zhai, Joan Puigcerver, Alexander Kolesnikov, Pierre Ruyssen, Carlos Riquelme, Mario Lucic, Josip Djolonga, Andre Susano Pinto, Maxim Neumann, Alexey Dosovitskiy, Lucas Beyer, Olivier Bachem, Michael Tschannen, Marcin Michalski, Olivier Bousquet, Sylvain Gelly, and Neil Houlsby. A large-scale study of representation learning with the visual task adaptation benchmark, 2020.
- Bolei Zhou, Agata Lapedriza, Aditya Khosla, Aude Oliva, and Antonio Torralba. Places: A 10 million image database for scene recognition. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 2017.