

HopWeaver: Cross-Document Synthesis of High-Quality and Authentic Multi-Hop Questions

Anonymous ACL submission

Abstract

Multi-Hop Question Answering (MHQA) is crucial for evaluating the model’s capability to integrate information from diverse sources. However, creating extensive and high-quality MHQA datasets is challenging: (i) manual annotation is expensive, and (ii) current synthesis methods often produce simplistic questions or require extensive manual guidance. This paper introduces HopWeaver, the first cross-document framework synthesizing authentic multi-hop questions without human intervention. HopWeaver synthesizes bridge and comparison questions through an innovative pipeline that identifies complementary documents and constructs authentic reasoning paths to ensure true multi-hop reasoning. We further present a comprehensive system for evaluating the synthesized multi-hop questions. Empirical evaluations demonstrate that the synthesized questions achieve comparable or superior quality to human-annotated datasets at a lower cost. Our framework provides a valuable tool for the research community: it can automatically generate challenging benchmarks from any raw corpus, which opens new avenues for both evaluation and targeted training to improve the reasoning capabilities of advanced QA models, especially in domains with scarce resources.

1 Introduction

Integrating information from different sources shows the intelligence of Large Language Models (LLMs) and Retrieval-Augmented Generation (RAG) systems (Huang and Huang, 2024; Hu et al., 2024). Multi-Hop Question Answering (MHQA), as a critical benchmark for this ability, requires models to integrate information distributed across documents (Guo et al., 2024; Mavi et al., 2024). MHQA requires a model to connect intermediate entities or concepts across documents to infer answers. However, constructing extensive and high-quality MHQA datasets remains costly because




Figure 1: Examples of two multi-hop questions synthesized by HopWeaver: Bridge (top) and Comparison (bottom) question. These involve cross-document reasoning via a bridge entity or a shared attribute.

manual annotation (Yang et al., 2018; Ho et al., 2020; Trivedi et al., 2022) struggles to cover diverse reasoning paths at scale and often introduces annotation bias (Klie et al., 2024; Wich et al., 2021). Furthermore, existing benchmarks, while valuable, may not fully expose the limitations of sophisticated RAG systems, which can sometimes overfit to the prevalent reasoning patterns within these datasets (Tang and Yang, 2024; Liu et al., 2025).

Recent studies have established synthesized data generation as a new paradigm for model training and evaluation (Lu et al., 2023; Guo and Chen, 2024). However, automatically synthesizing authentic multi-hop questions remains particularly challenging (Mavi et al., 2022; Guo et al., 2024). Existing approaches either require substantial manual intervention or produce "pseudo multi-hop" questions answerable from single documents. They face two fundamental limitations: (i) inability to identify bridge entities across complementary con-

063 texts, and (ii) failure to retrieve documents that are
064 truly complementary rather than redundant.

065 We introduce **HopWeaver**, the first cross-
066 document framework that synthesizes multi-hop
067 questions without any manual intervention. Building
068 on established MHQA research (Yang et al.,
069 2018; Ho et al., 2020; Trivedi et al., 2022; Yang
070 et al., 2018; Ho et al., 2020), HopWeaver focuses
071 on synthesizing two predominant question types:
072 **bridge questions** (connecting facts across docu-
073 ments through intermediate entities) and **compari-
074 son questions** (contrasting attributes between en-
075 tities). It employs an innovative retrieval mecha-
076 nism that identifies authentic complementary docu-
077 ments and constructs reasoning paths that neces-
078 sitate cross-document information integration (as
079 shown in Figure 1).

080 We further develop a comprehensive evaluation
081 system using (i) LLM-as-judge, (ii) answerability
082 and difficulty, and (iii) evidence-accessibility. In
083 summary, HopWeaver enables the cost-effective
084 synthesis of high-quality MHQA data, making it
085 especially valuable in specialized domains where it
086 can generate multi-hop questions directly from raw
087 corpora without relying on human intervention or
088 structured knowledge bases. This work makes the
089 following key contributions:

090 (1) We propose HopWeaver, the first cross-
091 document framework that synthesizes multi-hop
092 questions without any manual intervention.

093 (2) Through a novel, multi-dimensional evalua-
094 tion system of our own design, we demonstrate that
095 questions synthesized by HopWeaver meet or ex-
096 ceed the quality of human-annotated benchmarks.

097 (3) We demonstrate that HopWeaver unlocks
098 new multi-hop reasoning patterns from raw corpora
099 to create diverse datasets. These datasets expose
100 limitations in advanced RAG systems, opening new
101 possibilities for robust model evaluation and tar-
102 geted training, especially in specialized domains
103 lacking annotated data.

104 2 Related Works

105 2.1 MHQA Datasets and Evaluation

106 The field of multi-hop question answering has
107 been driven by the development of challenging
108 datasets that require reasoning across multiple
109 sources. Yang et al. (2018) marked a significant
110 advancement by introducing HotpotQA with 113k
111 Wikipedia-based QA pairs requiring reasoning over
112 supporting documents, featuring both bridge and

113 comparison question types with sentence-level sup-
114 porting facts for explainability. Ho et al. (2020) en-
115 hanced this approach by constructing datasets using
116 both structured and unstructured data, introducing
117 evidence information as comprehensive reasoning
118 paths and utilizing logical rules to ensure multi-
119 hop requirements. Trivedi et al. (2022) took a sys-
120 tematic bottom-up approach by composing single-
121 hop questions into multi-hop ones with MuSiQue.
122 However, critical evaluation has revealed funda-
123 mental limitations in dataset construction. Min
124 et al. (2019) demonstrated that many supposedly
125 multi-hop questions in HotpotQA can be solved
126 through single-hop reasoning due to weak distrac-
127 tor paragraphs and entity type matching, underscor-
128 ing the difficulty of guaranteeing truly multi-hop
129 questions.

130 2.2 Multi-Hop Question Synthesis

131 From rule-based to neural question generation.

132 Early work transformed declarative sentences into
133 questions with hand-crafted rules or templates (e.g.,
134 Heilman and Smith, 2010; Wyse and Piwek, 2009).
135 Neural sequence-to-sequence models later enabled
136 data-driven question generation (Du et al., 2017;
137 Zhou et al., 2017; Sun et al., 2018). However, these
138 methods fundamentally rely on human-provided
139 source documents (Fei et al., 2022; Xia et al.,
140 2023)—they generate questions from given evi-
141 dence rather than discovering related evidence
142 pairs, making them unsuitable for automatic multi-
143 hop question synthesis. Recent PLM-based work
144 explores related ideas: Cheng et al. (2021) in-
145 troduced step-by-step rewriting within single pas-
146 sages, and Hwang et al. (2024) extended this to
147 2-hop questions on pre-paired paragraphs. Both
148 still require human-provided evidence, limiting au-
149 tomation.

150 **Structured knowledge supervision.** To address
151 the reliance on manually provided evidence docu-
152 ments, several studies leverage external structured
153 knowledge. Knowledge-graph-aware pipelines
154 (KGAST; Vuth et al., 2024, LLM+KG; Chen
155 et al., 2024a) and template-driven systems such
156 as MINTQA (He et al., 2024) assemble questions
157 from manually curated triples or predefined tem-
158 plates. Others compose multi-hop questions from
159 large pre-constructed pools of single-hop questions
160 (Chen et al., 2024b). However, they inherit the
161 limitations of structured resources: coverage gaps,
162 fixed schemas, and considerable human curation

163 effort, which severely constrain scalability.

164 **Recent LLM-based attempts.** Recent work
165 leverages LLMs to reduce manual effort but lacks
166 rigorous validation. Source2Synth (Lupidi et al.,
167 2024) generates synthetic data grounded in real
168 sources but requires pre-selected documents; Wu
169 et al. (2024) extend the methodology to multimodal
170 question generation, yet still rely on human-curated
171 image-text pairs; while Luo et al. (2024) propose
172 chain-of-exemplar approaches for educational dis-
173 tractor generation using carefully crafted prompts.
174 Despite their advances, these methods still cannot
175 automatically discover complementary document
176 pairs from raw corpora.

177 In short, existing methods either depend on struc-
178 tured resources or fall back to single-hop settings,
179 leaving the problem of fully automatic, corpus-only
180 multi-hop question synthesis largely unsolved.

181 2.3 Dataset Quality Evaluation

182 Traditional evaluation methods face fundamental
183 limitations in ensuring authentic multi-hop require-
184 ments. Min et al. (2019) demonstrated that many
185 "multi-hop" questions in HotpotQA are solvable
186 through single-hop reasoning, exposing critical
187 gaps in existing evaluation approaches. Moreover,
188 **human annotation exhibits significant reliability**
189 **issues**—Klie et al. (2024) and Wich et al. (2021) re-
190 vealed systematic annotation problems and biases,
191 with inter-rater agreement often unacceptably low
192 (Bavaresco et al., 2024).

193 Recent work explores LLM-based evaluation
194 as a scalable alternative. Liu et al. (2023) intro-
195 duced G-Eval for automated assessment, while Fu
196 et al. (2024b) proposed multi-dimensional frame-
197 works for question generation evaluation. However,
198 **LLM judges require careful validation**—Lee
199 et al. (2025) emphasized self-consistency over hu-
200 man alignment as a reliability criterion, and Zheng
201 et al. (2023) developed systematic benchmarks for
202 judge evaluation. These converging insights under-
203 score the need for comprehensive evaluation frame-
204 works that combine multiple assessment strate-
205 gies, particularly for synthesized MHQA datasets
206 where traditional human-only evaluation proves
207 both costly and unreliable.

208 3 Methodology

209 We introduce a framework for synthesizing two
210 types of multi-hop questions: bridge questions and

211 comparison questions (as shown in Figure 2). The
212 formal preliminaries are provided in Appendix A.

213 3.1 Bridge Question Synthesis

214 **Step 1: Bridge Entity Identification.** First, a
215 source document d_s is randomly sampled from the
216 corpus. An LLM then processes d_s . The primary
217 goal is to identify a reasonable *bridge entity* (e_b)
218 that links disparate information contexts. The LLM
219 achieves this goal by selecting a text segment (s_p)
220 from d_s that provides concentrated textual context
221 and then identifying e_b within s_p . Finally, based on
222 e_b and s_p , the LLM formulates an optimized query
223 (q), enabling the targeted retrieval of complemen-
224 tary documents in the next phase.

225 **Step 2: Two-Stage Coarse-to-Fine Retrieval.**
226 This step takes the query q and source document
227 d_s (from Step 1) as input. Its objective is to out-
228 put a ranked list of k complementary documents,
229 $D_t = \{d_t^1, \dots, d_t^k\}$, which are identified through a
230 two-stage retrieval strategy:

231 First, the **Coarse Retrieval** stage generates an
232 initial candidate list. An initial set of documents is
233 retrieved using q . Up to k candidates are greedily
234 selected from this set using a modified Maximum
235 Marginal Relevance (MMR) approach (Carbonell
236 and Goldstein, 1998). As defined in Equation 1,
237 this method balances query relevance ($\text{sim}(q, d_i)$)
238 with dissimilarity to the source document d_s (via
239 $-\text{sim}(d_i, d_s)$) and diversity among already selected
240 documents in set S (via $-\max_{d_j \in S} \text{sim}(d_i, d_j)$),
241 thereby promoting the selection of diverse and com-
242plementary contexts. The parameters $\lambda_1, \lambda_2, \lambda_3$
243 control this trade-off (as shown in Appendix H).

$$244 \begin{aligned} \text{Score}(d_i) = & \lambda_1 \text{sim}(q, d_i) - \lambda_2 \text{sim}(d_i, d_s) \\ & - \lambda_3 \max_{d_j \in S} \text{sim}(d_i, d_j) \end{aligned} \quad (1)$$

245 Next, the **Fine-grained Reranking** stage refines
246 this candidate list. Candidate documents d_i are
247 paired with q and re-scored by a fine-tuned reranker,
248 yielding the final set D_t composed of the top k
249 documents according to these new scores. The
250 details of the reranker model and its fine-tuning
251 methodology are provided in Section 3.3.

252 **Step 3: Multi-Hop Question Construction.**
253 This step constructs a verifiable multi-hop ques-
254 tion by integrating information from the source
255 document d_s and a selected complementary docu-
256 ment d_t (from D_t identified in Step 2), using the




Figure 2: HopWeaver: Question Synthesis Framework

bridge entity e_b as the pivot. The process consists of the following steps:

- (a) **Sub-Question Generation:** To construct the final multi-hop question that requires grounding in both documents, two sequential sub-questions are generated: (i) Sub-Question 1 formulated from d_s with the bridge entity e_b as its answer; (ii) Sub-Question 2 generated from d_t with e_b in its question text, targeting information unique to d_t .
- (b) **Multi-Hop Question Synthesis:** The two sub-questions are fused into a single, coherent multi-hop question. This final question is crafted to implicitly guide reasoning from d_s through e_b to d_t , without explicitly revealing e_b while necessitating multi-hop reasoning.
- (c) **Validation and Iteration:** The synthesized question undergoes a validation process. If a valid multi-hop question is not successfully formed (e.g., due to flawed fusion, an invalid bridge connection, or entity ambiguity), or if the resulting question violates the Fact Distribution or No-Shortcut constraints (defined in Section A.2), the current complementary document d_t is rejected. The question construction process then attempts to use the next ranked document from the list D_t .

The module generates a QA pair, a reasoning path ($d_s \rightarrow e_b \rightarrow d_t$), and sub-questions to ensure the interpretability and verifiability of each question. See Appendix E for an example of a synthesized bridge question and its generation details.

Step 4: Question Polishing and Validation. With the QA pair and its supporting segments gen-

erated in Step 3, we further enhance their quality by processing them through the Question Polishing and Validation module, detailed in Section 3.4.

3.2 Comparison Question Synthesis

Step 1: Entity and Attribute Identification. For each randomly sampled document d_a , the module:

- Identifies the primary subject entity e_a and its type (e.g., person, location, organization).
- Extracts 3-5 concise, factual attribute-value pairs (a, v_a) suitable for comparison (e.g., numeric, date, category).

Step 2: Filtering. To ensure concreteness and comparability, each entity and attribute is scored on a 1-5 scale (see Appendix G for detailed criteria), with only those meeting the threshold included in further steps.

Step 3: Query Generation and Retrieval. Based on its understanding of the source entity e_a and the filtered attributes from Step 2, the LLM generates queries and retrieves documents. The strategy selection is governed by a set of instructions provided to the LLM. The model defaults to Diversified Search unless it can confidently identify a comparable entity for Direct Recommendation.

- **Direct Recommendation:** The LLM selects a representative attribute of e_a , recommends a comparable entity e_c , and generates a verification query to retrieve documents containing e_c with the same attribute.
- **Diversified Search:** The LLM generates three diverse retrieval queries to find other entities of the same type as e_a . These queries are

used to retrieve documents from the corpus, and their top- k results are merged to discover documents containing comparable entities.

This step outputs a list of retrieved documents for the subsequent stage (Step 4).

Step 4: Question Construction. The system first identifies entity e_c within the retrieved document(s) and searches for a comparable attribute pair (a, v_a, v_b) where both entities have specific, factual values for the attribute a . The approach to finding this pair follows the strategy from Step 3:

- **Guided Comparison:** Following a Direct Recommendation, where a specific entity e_c and attribute a are specified, the system focuses on retrieving this exact pair.
- **Open Discovery:** Following a Diversified Search, the system iterates through the attributes of entity e_a to find the first valid comparable pair with any attribute of a discovered entity e_c .

When finding a comparable pair, the module generates a comparison QA pair (e.g., “Which has the higher a : e_a or e_c ?” “ e_a ”), along with the two document segments containing information of v_a and v_b , and a corresponding reasoning path. See Appendix E for an illustrative example of a comparison question.

Step 5: Question Polishing and Validation. The generated QA pair and its supporting segments are processed by the Question Polishing and Validation module (in Section 3.4) to ensure quality.

3.3 Fine-Tuning Reranker via Simulated Feedback




Figure 3: Fine-Tuning Reranker

To enhance the reranking stage (in Section 3.1, Step 2), we fine-tune the reranker using contrastive triples generated through simulating key steps of the bridge question synthesis process (Figure 3).

Generating Supervision Signals through Simulation. Our fine-tuning process begins with creating a labeled dataset directly from the bridge question synthesis process. We simulate this synthesis by retrieving a list of documents $\{d_i\}$ using our coarse retrieval methods. Each candidate d_i attempts to generate the connecting sub-questions required to link it with d_s through e_b . The success or failure of multi-hop question generation provides a supervision signal, with successful attempts yielding positive example (d^+) and failed attempts producing negative example (d^-).

Contrastive Learning Fine-Tuning of the Reranker. These positive and negative examples form the dataset for reranker fine-tuning. We construct contrastive training triples, typically (query = e_b, d^+, d^-), and train the reranker to distinguish complementary documents. This optimization is guided by a cross-entropy loss:

$$\mathcal{L} = -\frac{1}{N} \sum_{i=1}^N \log \left(\frac{\exp(f(e_b, d_i^+))}{\sum_{j=1}^k \exp(f(e_b, d_{ij}))} \right) \quad (2)$$

where $f(e_b, d)$ is the score produced by the reranker for a query-document pair, N is the batch size, d_i^+ is the positive document in the i -th group, and d_{ij} represents all documents (one positive and $k - 1$ negatives) in the j -th position within the i -th group for calculating the sum in the denominator.

This supervision signal, derived directly from the downstream task’s success, assists the reranker to learn what constitutes a truly complementary document. And an ablation study confirming the efficiency gains from our fine-tuned reranker is detailed in Appendix C.1.1.

3.4 Question Polishing and Validation

The polisher module assesses and refines each multi-hop question (both Bridge and Comparison types) via structured prompts, generating one of four outcomes:

- (i) **PASS:** accepts the question.
- (ii) **ADJUST:** applies minor wording or fluency improvements; outputs revised question and reasoning path.
- (iii) **REWORKED:** performs substantial restructuring; outputs new question, reasoning path, and answer.
- (iv) **REJECTED:** discards questions with irreparable flaws.

This step guarantees that each question (i) involves cross-document reasoning, (ii) hides the

bridge entity (for Bridge questions), and (iii) maintains fluency without exposing intermediate steps. We conducted an ablation study to validate the effectiveness of the Polisher module, the results of which are presented in Appendix C.1.2.

4 Data Quality Evaluation System

Evaluating the quality of multi-hop questions requires a comprehensive evaluation system that extends beyond traditional metrics. We introduce a three-dimensional evaluation system designed to capture the critical attributes of high-quality MHQA datasets.

4.1 LLM-as-Judge Evaluation

Our evaluation employs an LLM-as-judge approach with a Likert scale to evaluate each synthesized MHQA pair. Building on recent advances in question generation evaluation metrics and LLM-based assessment (Fu et al., 2024b; Liu et al., 2023), we establish a novel scoring framework tailored for multi-hop questions (detailed in Appendix F).

While LLM judges offer scalability, they require careful validation, as discussed in Section 2.3. We therefore prioritize self-consistency over human alignment as our primary reliability criterion, ensuring stable and reproducible evaluations (see Appendix F.2 for detailed rationale).

To identify suitable LLM judges, we evaluated multiple models based on output stability. Results show proprietary LLMs like GPT-4o demonstrate strong performance across metrics, while open-source models such as Gemma-3-27b offer stable, cost-effective evaluation with better reproducibility. See Appendix F.3 for complete metrics, model specifications, selection rationale, and results with visualizations. We adopted the average score across selected judges as our final evaluation standard. To validate this approach, a pairwise human study confirmed a 92% agreement with our judges’ rankings (detailed in Appendix C.2).

4.2 Answerability and Difficulty Evaluation

To evaluate the **answerability** and **difficulty** of our synthesized questions and their reliance on contextual evidence, we use multiple LLM solvers under two distinct conditions:

- **Q-Only:** The solver sees only the question. This setting primarily gauges the baseline answerability using the solver’s internal knowledge and reasoning capabilities.

- **Q+Docs:** The solver receives all supporting documents for the question, simulating a golden retrieval scenario. This setting evaluates the question’s answerability when all necessary evidence is available.

The performance improvement from the Q-Only to the Q+Docs indicates that: (i) the question is challenging and requires contextual evidence rather than just pre-existing knowledge or superficial cues; and (ii) the LLM-annotated golden evidence effectively supports a correct answer, confirming the question is answerable. These features are key signs of well-constructed multi-hop questions that test evidence integration.

4.3 Evidence-Accessibility Evaluation

We examine whether annotated evidence for our synthesized question evidence is **accessible** in the corpus and evaluate the difficulty of its complete retrieval. Distinct retrieval methods are employed to fetch the top- k documents for each question and record retrieval metrics: (i) MAP (mean average precision), (ii) RECALL@K (proportion of golden evidence retrieved in top- k), (iii) NDCG@K (normalized discounted cumulative gain at k), and (iv) SUPPORT F1 (overlap between retrieved and golden evidence).

This comprehensive evaluation approach uses the recorded metrics to achieve two primary objectives: (i) to gauge the accessibility of individual evidence documents (using RECALL@K, e.g., @20), which is crucial for verifying corpus grounding and evaluating retrieval ranking quality (via MAP and NDCG@K); and (ii) to identify specific difficulties in multi-source evidence assembly, indicated by SUPPORT F1 (complete-set retrieval accuracy) relative to individual document recall (RECALL@K). This detailed analysis provides a vital retrieval baseline for our dataset, enabling a clearer interpretation of MHQA performance by clearly distinguishing retrieval challenges from reasoning demands.

5 Experiments

HopWeaver is evaluated using the most popular English Wikipedia corpus and four LLM generators with different scales and performances for synthesis. We compare the synthesized question with three human-annotated MHQA datasets, providing a comprehensive statistical comparison in Appendix B. See Appendix H for the complete ex-

perimental setup and Appendix D for cost analysis, and Appendix C.6 for pipeline rejection statistics.

5.1 Main Quality Evaluation

Generation Source	Bridge Questions		Comparison Questions	
	Multi-Hop (%)	Avg. Score	Multi-Hop (%)	Avg. Score
HopWeaver (Ours)				
w/ Gemini-2.5-flash	96.4	4.27	98.6	4.45
w/ QwQ-32B	98.9	4.23	97.4	4.40
w/ Qwen3-14B	96.9	4.09	95.9	4.36
w/ GLM-4-9B-0414	89.8	3.87	93.9	4.26
Human Datasets (Baselines)				
HotpotQA	92.8	4.23	95.6	4.20
2WikiMultiHopQA	92.8	4.04	97.6	4.42
MuSiQue	91.2	3.78	N/A	N/A

Table 1: Quality evaluation of multi-hop questions (500 samples, 5 LLM judges). Multi-Hop (%) shows the proportion of questions authentically involving information from multiple documents. Avg. Score represents quality on a 1-5 scale (1=Very Poor, 5=Very Good) across multiple evaluation criteria (in Appendix F).

Our quality evaluation results in Table 1 contain the proportion of authentic multi-hop questions and their average scores. When employing the proprietary LLM Gemini-2.5-flash, HopWeaver achieves exceptional performance (98.6% multi-hop rate and 4.47 average score for Comparison questions; 96.4% and 4.27 for Bridge questions), surpassing all evaluated human-annotated datasets. This demonstrates HopWeaver’s capacity to produce data that advance MHQA research.

To evaluate HopWeaver’s performance with more accessible and reproducible setups, we also tested three leading open-source LLMs of varying scales (QwQ-32B, Qwen3-14B, GLM-4-9B-0414). These models also enable HopWeaver to synthesize high-quality questions that rival or exceed human datasets; the authenticity of this multi-hop nature is substantiated by a manual evaluation showing that the vast majority of the reasoning paths are correct (Appendix C.3). For instance, QwQ-32B achieves a 98.9% multi-hop rate and a 4.23 average score for Bridge questions. Even the smaller GLM-4-9B-0414 yields a high percentage of valid multi-hop questions (89.8% for Bridge, 93.9% for Comparison), offering a cost-effective solution for large-scale synthesis.

Notably, Comparison questions consistently outperform Bridge questions, which reflects inherent task complexity. This pattern aligns with our RAG evaluation (Table 4), where Comparison questions yield higher F1.

A multi-dimensional analysis is conducted to compare the average scores across key quality di-

mensions for HopWeaver-synthesized questions (using different LLMs) against human datasets. Figure 4 shows that the question synthesized by HopWeaver surpasses the benchmark of human datasets in most dimensions, especially in **logical sophistication** and **information integration**, although the top human dataset holds a marginal advantage in conciseness.




Figure 4: Multi-dimensional quality evaluation to compare HopWeaver-synthesized questions (by different LLMs) against baseline datasets across key criteria, with scale truncated to [3.0, 4.5] for visualization clarity (full scale: [1, 5]).

5.2 Answerability and Difficulty Evaluation

We evaluate various LLMs in both “Question-Only” (Q-Only) and “Question + Golden Documents” (Q+Docs) settings, as described in Section 4.2. The results, presented in Table 2, demonstrate a significant performance improvement across all models when the golden supporting documents are provided. For instance, GPT-4o’s Exact Match (EM) score rose from 29.0% to 51.0% on Bridge questions and jumped from 69.0% to 94.0% on Compare questions (Q-Only to Q+Docs).

This substantial gain confirms two critical aspects aligned with our evaluation goals: (i) the questions involve multi-hop reasoning and are difficult to answer based solely on the models’ internal knowledge; and (ii) the golden documents synthesized by HopWeaver are effective and contain the necessary information for models to deduce the correct answers, confirming the questions’ answerability given appropriate evidence. This performance gap between the Q+Docs setting and ground truth reflects the task’s inherent reasoning complexity, a

conclusion supported by our detailed error analysis (Appendix C.4), which shows that failures stem mostly from model reasoning limitations, not question quality flaws.

This pattern holds across model scales—even smaller models like Qwen3-8B show dramatic F1 improvements (22.3%→60.2%) with gold documents.

Model	Bridge				Compare			
	Q-Only (%)		Q+Docs (%)		Q-Only (%)		Q+Docs (%)	
	EM	F1	EM	F1	EM	F1	EM	F1
GPT-4o	29.0	40.5	51.0	65.0	69.0	70.5	94.0	94.2
Claude-3.7-Sonnet	23.0	33.0	50.0	62.0	47.0	50.2	91.0	93.4
Llama-3.3-70B	18.0	30.6	45.0	60.9	49.0	51.8	74.0	78.9
Qwen3-8B	10.0	22.3	47.0	60.2	50.0	55.4	62.0	66.0

Table 2: QA results of comparing model performance with Question Only (Q-Only) and Question + Golden Docs (Q+Docs) using 100 samples.

5.3 Evidence-Accessibility Evaluation

We evaluated the synthesized dataset (by Gemini-2.5-flash) using three retrievers. Our evaluation requires retrievers to identify the exact document sources used to synthesize each question.

The evidence-accessibility evaluation (Table 3) highlights several key findings regarding the dataset: (i) evidence documents are largely accessible by retriever within the corpus, as demonstrated by Recall@k (e.g., BM25 Recall@20 of 0.7050), affirming the questions’ strong corpus-grounding; and (ii) retrieving the complete set of necessary evidence documents simultaneously remains challenging (e.g., low Support F1: 0.17-0.22), despite individual document accessibility. This disparity underscores the genuine multi-hop nature of the questions, which necessitates integrating information from multiple, distinct sources; and (iii) the dataset effectively discriminates between retrieval strategies (e.g., BM25 > GTE > E5), demonstrating its utility as a benchmark for evaluating multi-hop retrieval systems.

Method	MAP	Recall@5	Recall@10	Recall@20	NDCG@5	NDCG@10	Support F1
BM25	0.5605	0.6150	0.6650	0.7050	0.6305	0.6510	0.2217
GTE	0.5092	0.5600	0.5900	0.6250	0.5828	0.5946	0.1967
E5	0.4107	0.4600	0.5150	0.5800	0.4720	0.4943	0.1717

Table 3: Evidence-Accessibility Evaluation Results. Evaluating different retrievers on the HopWeaver synthesized dataset.

5.4 End-to-End Evaluation on RAG Systems

To further validate the complexity of our synthesized dataset, we conduct an end-to-end perfor-

mance evaluation on several mainstream RAG systems. For a fair and direct comparison, we benchmark five representative RAG methods on our dataset using the standardized pipeline from the FlashRAG toolkit (Jin et al., 2025) and compare our results against its published scores on HotpotQA and 2WikiMultiHopQA.

The results, presented in Table 4, reveal several key findings. First, consistently low F1 scores, on par with established benchmarks, confirm our dataset presents a significant challenge to RAG systems. More importantly, advanced RAG methods often failed to outperform the standard RAG, sometimes showing significant performance drops on our dataset. This outcome suggests that while these sophisticated retrieval strategies are highly effective on established benchmarks, their performance may be contingent on the specific reasoning patterns prevalent in those datasets but not generalize. Herein lies the value of HopWeaver: its ability to synthesize benchmarks with a broader diversity of question structures and contexts. The failure of advanced RAG methods on our dataset is direct evidence that such diversity is crucial for identifying their limitations and guiding the development of more robust, generalizable systems.

Method	HopWeaver Bri.	HopWeaver Comp.	HotpotQA	2Wiki.
Standard RAG	0.318	0.417	0.353	0.210
REPLUG	0.226 (↓29%)	0.483 (↑16%)	0.312 (↓12%)	0.211 (↑1%)
SuRe	0.328 (↑3%)	0.265 (↓36%)	0.334 (↓5%)	0.206 (↓2%)
FLARE	0.136 (↓57%)	0.303 (↓27%)	0.280 (↓21%)	0.339 (↑61%)
IRCoT	0.158 (↓50%)	0.279 (↓33%)	0.415 (↑18%)	0.324 (↑54%)
Average	0.233	0.349	0.339	0.258

Table 4: Performance of RAG Systems on HopWeaver-Synthesized and Human-Annotated Datasets (F1-Score).

6 Conclusion

We presented HopWeaver, a fully automatic framework for synthesizing authentic multi-hop questions from raw corpora. Our experiments demonstrate that HopWeaver meets or exceeds human-level benchmarks across multiple evaluation dimensions, making it a practical solution for constructing complex MHQA datasets in domains where human annotation is limited. Our pipeline also extends to n-hop synthesis through recursive generation (Appendix C.5). Furthermore, our work provides a valuable tool for the research community; the synthesized questions serve as a challenging benchmark that reveals limitations in prevalent RAG systems, guiding future improvements.

645 Limitations

646 The performance of HopWeaver, like other genera-
647 tive frameworks, is inherently linked to the capabil-
648 ities of its underlying LLM and the quality of the
649 source corpus. While our approach demonstrates
650 robustness across several models, the nuance and
651 complexity of the synthesized questions are ulti-
652 mately bounded by the reasoning and language
653 generation abilities of the backbone LLM. Simi-
654 larly, the breadth of topics and the factual accuracy
655 of the generated questions are dependent on the
656 comprehensiveness and cleanliness of the text cor-
657 pora from which they are derived. Furthermore, as
658 the synthesis process is automated, it may inadver-
659 tently inherit and amplify subtle biases present in
660 the source data.

661 Regarding experimental scope, our evaluation
662 focuses on English Wikipedia to ensure fair compar-
663 ison with established benchmarks (HotpotQA,
664 2WikiMultiHopQA, MuSiQue). We emphasize
665 that this reflects resource constraints rather than
666 architectural limitations: HopWeaver’s retrieve-
667 then-synthesize pipeline is inherently domain- and
668 language-agnostic, requiring only substitution of
669 the source corpus and use of appropriate multilin-
670 gual embeddings. Cross-domain and multilingual
671 validation represents important future work.

672 References

673 Anna Bavaresco, Raffaella Bernardi, Leonardo Berto-
674 lazzi, Desmond Elliott, Raquel Fernández, Albert
675 Gatt, Esam Ghaleb, Mario Giulianelli, Michael
676 Hanna, Alexander Koller, André F. T. Martins,
677 Philipp Mondorf, Vera Neplenbroek, Sandro Pezzelle,
678 Barbara Plank, David Schlangen, Alessandro Sug-
679 lia, Aditya K. Surikuchi, Ece Takmaz, and Alberto
680 Testoni. 2024. [Llms instead of human judges? A large scale empirical study across 20 NLP evaluation tasks.](#) *CoRR*, abs/2406.18403.

683 Jaime G. Carbonell and Jade Goldstein. 1998. [The use of mmr, diversity-based reranking for reordering documents and producing summaries.](#) In *SIGIR '98: Proceedings of the 21st Annual International ACM SIGIR Conference on Research and Development in Information Retrieval, August 24-28 1998, Melbourne, Australia*, pages 335–336. ACM.

690 Ruirui Chen, Weifeng Jiang, Chengwei Qin,
691 Ishaan Singh Rawal, Cheston Tan, Dongkyu
692 Choi, Bo Xiong, and Bo Ai. 2024a. [LLM-based multi-hop question answering with knowledge graph integration in evolving environments.](#) In *Findings of the Association for Computational Linguistics: EMNLP 2024*, pages 14438–14451, Miami, Florida, USA. Association for Computational Linguistics.

Zhi Chen, Qiguang Chen, Libo Qin, Qipeng Guo, Hai-
jun Lv, Yicheng Zou, Wanxiang Che, Hang Yan, Kai
Chen, and Dahua Lin. 2024b. [What are the essential factors in crafting effective long context multi-hop instruction datasets? insights and best practices.](#) *CoRR*, abs/2409.01893.

Yi Cheng, Siyao Li, Bang Liu, Ruihui Zhao, Sujian Li,
Chenghua Lin, and Yefeng Zheng. 2021. [Guiding the growth: Difficulty-controllable question generation through step-by-step rewriting.](#) In *Proceedings of the 59th Annual Meeting of the Association for Computational Linguistics and the 11th International Joint Conference on Natural Language Processing (Volume 1: Long Papers)*, pages 5968–5978, Online. Association for Computational Linguistics.

David Cheng-Han Chiang and Hung-yi Lee. 2023. [Can large language models be an alternative to human evaluations?](#) In *Proceedings of the 61st Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers), ACL 2023, Toronto, Canada, July 9-14, 2023*, pages 15607–15631. Association for Computational Linguistics.

Xinya Du, Junru Shao, and Claire Cardie. 2017. [Learning to ask: Neural question generation for reading comprehension.](#) In *Proceedings of the 55th Annual Meeting of the Association for Computational Linguistics, ACL 2017, Vancouver, Canada, July 30 - August 4, Volume 1: Long Papers*, pages 1342–1352.

Zichu Fei, Qi Zhang, Tao Gui, Di Liang, Sirui Wang, Wei Wu, and Xuanjing Huang. 2022. [CQG: A simple and effective controlled generation framework for multi-hop question generation.](#) In *Proceedings of the 60th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers), ACL 2022, Dublin, Ireland, May 22-27, 2022*, pages 6896–6906. Association for Computational Linguistics.

Emilio Ferrara. 2023. [Should chatgpt be biased? challenges and risks of bias in large language models.](#) *First Monday*, 28(11).

Joseph L Fleiss. 1971. Measuring nominal scale agreement among many raters. *Psychological bulletin*, 76(5):378.

Jinlan Fu, See-Kiong Ng, Zhengbao Jiang, and Pengfei Liu. 2024a. [Gptscore: Evaluate as you desire.](#) In *Proceedings of the 2024 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies (Volume 1: Long Papers), NAACL 2024, Mexico City, Mexico, June 16-21, 2024*, pages 6556–6576. Association for Computational Linguistics.

Weiping Fu, Bifan Wei, Jianxiang Hu, Zhongmin Cai, and Jun Liu. 2024b. [QGEval: Benchmarking multi-dimensional evaluation for question generation.](#) In *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing*, pages 11783–11803, Miami, Florida, USA. Association for Computational Linguistics.

756	Shasha Guo, Lizi Liao, Cuiping Li, and Tat-Seng Chua. 2024. A survey on neural question generation: Methods, applications, and prospects . In <i>Proceedings of the Thirty-Third International Joint Conference on Artificial Intelligence, IJCAI 2024, Jeju, South Korea, August 3-9, 2024</i> , pages 8038–8047. ijcai.org.	813
757		814
758		
759		815
760		816
761		817
762	Xu Guo and Yiqiang Chen. 2024. Generative AI for synthetic data generation: Methods, challenges and the future . <i>CoRR</i> , abs/2403.04190.	818
763		819
764		
765	Jie He, Nan Hu, Wanqiu Long, Jiaoyan Chen, and Jeff Z. Pan. 2024. MINTQA: A multi-hop question answering benchmark for evaluating llms on new and tail knowledge . <i>CoRR</i> , abs/2412.17032.	820
766		821
767		822
768		823
769	Michael Heilman and Noah A. Smith. 2010. Good question! statistical ranking for question generation . In <i>Human Language Technologies: Conference of the North American Chapter of the Association of Computational Linguistics, Proceedings, June 2-4, 2010, Los Angeles, California, USA</i> , pages 609–617.	824
770		825
771		826
772		
773		827
774		828
775	Xanh Ho, Anh-Khoa Duong Nguyen, Saku Sugawara, and Akiko Aizawa. 2020. Constructing a multi-hop QA dataset for comprehensive evaluation of reasoning steps . In <i>Proceedings of the 28th International Conference on Computational Linguistics</i> , pages 6609–6625, Barcelona, Spain (Online). International Committee on Computational Linguistics.	829
776		830
777		831
778		832
779		833
780		834
781		
782	Linmei Hu, Zeyi Liu, Ziwang Zhao, Lei Hou, Liqiang Nie, and Juanzi Li. 2024. A survey of knowledge enhanced pre-trained language models . <i>IEEE Trans. Knowl. Data Eng.</i> , 36(4):1413–1430.	835
783		836
784		837
785		838
786	Yizheng Huang and Jimmy Huang. 2024. A survey on retrieval-augmented text generation for large language models . <i>CoRR</i> , abs/2404.10981.	839
787		840
788		841
789	Seonjeong Hwang, Yunsu Kim, and Gary Geunbae Lee. 2024. Explainable multi-hop question generation: An end-to-end approach without intermediate question labeling . In <i>Proceedings of the 2024 Joint International Conference on Computational Linguistics, Language Resources and Evaluation (LREC-COLING 2024)</i> , pages 6855–6866, Torino, Italia. ELRA and ICCL.	842
790		843
791		844
792		845
793		846
794		
795		847
796		848
797	Jiajie Jin, Yutao Zhu, Zhicheng Dou, Guanting Dong, Xinyu Yang, Chenghao Zhang, Tong Zhao, Zhao Yang, and Ji-Rong Wen. 2025. Flashrag: A modular toolkit for efficient retrieval-augmented generation research . In <i>Companion Proceedings of the ACM on Web Conference 2025, WWW 2025, Sydney, NSW, Australia, 28 April 2025 - 2 May 2025</i> , pages 737–740. ACM.	849
798		850
799		851
800		852
801		853
802		854
803		855
804		
805	Jiajie Jin, Yutao Zhu, Xinyu Yang, Chenghao Zhang, and Zhicheng Dou. 2024. Flashrag: A modular toolkit for efficient retrieval-augmented generation research . <i>CoRR</i> , abs/2405.13576.	856
806		857
807		858
808		859
809	Jan-Christoph Klie, Richard Eckart de Castilho, and Iryna Gurevych. 2024. Analyzing dataset annotation quality management in the wild . <i>Comput. Linguistics</i> , 50(3):817–866.	860
810		861
811		862
812		863
	Klaus Krippendorff. 2018. <i>Content analysis: An introduction to its methodology</i> . Sage publications.	864
	Noah Lee, Jiwoo Hong, and James Thorne. 2025. Evaluating the consistency of LLM evaluators . In <i>Proceedings of the 31st International Conference on Computational Linguistics</i> , pages 10650–10659, Abu Dhabi, UAE. Association for Computational Linguistics.	865
	Hao Liu, Zhengren Wang, Xi Chen, Zhiyu Li, Feiyu Xiong, Qinhan Yu, and Wentao Zhang. 2025. Hoprag: Multi-hop reasoning for logic-aware retrieval-augmented generation . In <i>Findings of the Association for Computational Linguistics, ACL 2025, Vienna, Austria, July 27 - August 1, 2025</i> , pages 1897–1913. Association for Computational Linguistics.	866
	Yang Liu, Dan Iter, Yichong Xu, Shuohang Wang, Ruochen Xu, and Chenguang Zhu. 2023. G-eval: NLG evaluation using gpt-4 with better human alignment . In <i>Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing, EMNLP 2023, Singapore, December 6-10, 2023</i> , pages 2511–2522. Association for Computational Linguistics.	867
	Adian Liusie, Potsawee Manakul, and Mark J. F. Gales. 2024. LLM comparative assessment: Zero-shot NLG evaluation through pairwise comparisons using large language models . In <i>Proceedings of the 18th Conference of the European Chapter of the Association for Computational Linguistics, EACL 2024 - Volume 1: Long Papers, St. Julian's, Malta, March 17-22, 2024</i> , pages 139–151. Association for Computational Linguistics.	868
	Yingzhou Lu, Huazheng Wang, and Wenqi Wei. 2023. Machine learning for synthetic data generation: a review . <i>CoRR</i> , abs/2302.04062.	869
	Haohao Luo, Yang Deng, Ying Shen, See-Kiong Ng, and Tat-Seng Chua. 2024. Chain-of-exemplar: Enhancing distractor generation for multimodal educational question generation . In <i>Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers), ACL 2024, Bangkok, Thailand, August 11-16, 2024</i> , pages 7978–7993. Association for Computational Linguistics.	870
	Alisia Lupidi, Carlos Gemmell, Nicola Cancedda, Jane Dwivedi-Yu, Jason Weston, Jakob Foerster, Roberta Raileanu, and Maria Lomeli. 2024. Source2synth: Synthetic data generation and curation grounded in real data sources . <i>CoRR</i> , abs/2409.08239.	871
	Vaibhav Mavi, Anubhav Jangra, and Adam Jatowt. 2022. A survey on multi-hop question answering and generation . <i>CoRR</i> , abs/2204.09140.	872
	Vaibhav Mavi, Anubhav Jangra, and Adam Jatowt. 2024. Multi-hop question answering . <i>Found. Trends Inf. Retr.</i> , 17(5):457–586.	873
	Sewon Min, Eric Wallace, Sameer Singh, Matt Gardner, Hannaneh Hajishirzi, and Luke Zettlemoyer. 2019.	874

869	Compositional questions do not necessitate multi-hop reasoning . In <i>Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics</i> , pages 4249–4257, Florence, Italy. Association for Computational Linguistics.	927
870		928
871		929
872		930
873		931
874	Xingwu Sun, Jing Liu, Yajuan Lyu, Wei He, Yanjun Ma, and Shi Wang. 2018. Answer-focused and position-aware neural question generation . In <i>Proceedings of the 2018 Conference on Empirical Methods in Natural Language Processing, Brussels, Belgium, October 31 - November 4, 2018</i> , pages 3930–3939.	932
875		933
876		934
877		935
878		936
879		937
880	Yixuan Tang and Yi Yang. 2024. Multihop-rag: Benchmarking retrieval-augmented generation for multi-hop queries . <i>CoRR</i> , abs/2401.15391.	938
881		939
882		940
883	Harsh Trivedi, Niranjan Balasubramanian, Tushar Khot, and Ashish Sabharwal. 2022. Musique: Multi-hop questions via single-hop question composition . <i>Trans. Assoc. Comput. Linguistics</i> , 10:539–554.	941
884		942
885		943
886		944
887	Nakanyseth Vuth, Gilles S�erasset, and Didier Schwab. 2024. KGAST: From knowledge graphs to annotated synthetic texts . In <i>Proceedings of the 1st Workshop on Knowledge Graphs and Large Language Models (KaLLM 2024)</i> , pages 43–55, Bangkok, Thailand. Association for Computational Linguistics.	945
888		946
889		947
890		
891		
892		
893	Maximilian Wich, Christian Widmer, Gerhard Hagerer, and Georg Groh. 2021. Investigating annotator bias in abusive language datasets . In <i>Proceedings of the International Conference on Recent Advances in Natural Language Processing (RANLP 2021), Held Online, 1-3 September, 2021</i> , pages 1515–1525. INCOMA Ltd.	
894		
895		
896		
897		
898		
899		
900	Ian Wu, Sravan Jayanthi, Vijay Viswanathan, Simon Rosenberg, Sina Pakazad, Tongshuang Wu, and Graham Neubig. 2024. Synthetic multimodal question generation . In <i>Findings of the Association for Computational Linguistics: EMNLP 2024, Miami, Florida, USA, November 12-16, 2024</i> , pages 12960–12993. Association for Computational Linguistics.	
901		
902		
903		
904		
905		
906		
907	Brendan Wyse and Paul Piwek. 2009. Generating questions from openlearn study units. In <i>Proceedings of the AIED 2009 Workshop on Question Generation</i> , pages 66–73, Brighton, UK.	
908		
909		
910		
911	Zehua Xia, Qi Gou, Bowen Yu, Haiyang Yu, Fei Huang, Yongbin Li, and Cam-Tu Nguyen. 2023. Improving question generation with multi-level content planning . In <i>Findings of the Association for Computational Linguistics: EMNLP 2023, Singapore, December 6-10, 2023</i> , pages 800–814. Association for Computational Linguistics.	
912		
913		
914		
915		
916		
917		
918	Zhilin Yang, Peng Qi, Saizheng Zhang, Yoshua Bengio, William W. Cohen, Ruslan Salakhutdinov, and Christopher D. Manning. 2018. Hotpotqa: A dataset for diverse, explainable multi-hop question answering . In <i>Proceedings of the 2018 Conference on Empirical Methods in Natural Language Processing, Brussels, Belgium, October 31 - November 4, 2018</i> , pages 2369–2380. Association for Computational Linguistics.	
919		
920		
921		
922		
923		
924		
925		
926		
	Jiayi Ye, Yanbo Wang, Yue Huang, Dongping Chen, Qihui Zhang, Nuno Moniz, Tian Gao, Werner Geyer, Chao Huang, Pin-Yu Chen, Nitesh V. Chawla, and Xi-angliang Zhang. 2024. Justice or prejudice? quantifying biases in llm-as-a-judge . <i>CoRR</i> , abs/2410.02736.	
	Lianmin Zheng, Wei-Lin Chiang, Ying Sheng, Siyuan Zhuang, Zhanghao Wu, Yonghao Zhuang, Zi Lin, Zhuohan Li, Dacheng Li, Eric P. Xing, Hao Zhang, Joseph E. Gonzalez, and Ion Stoica. 2023. Judging llm-as-a-judge with mt-bench and chatbot arena . In <i>Advances in Neural Information Processing Systems 36: Annual Conference on Neural Information Processing Systems 2023, NeurIPS 2023, New Orleans, LA, USA, December 10 - 16, 2023</i> .	
	Qingyu Zhou, Nan Yang, Furu Wei, Chuanqi Tan, Hangbo Bao, and Ming Zhou. 2017. Neural question generation from text: A preliminary study . In <i>Natural Language Processing and Chinese Computing - 6th CCF International Conference, NLPCC 2017, Dalian, China, November 8-12, 2017, Proceedings</i> , pages 662–671.	

A Preliminaries

While MHQA exhibits various patterns (e.g., bridge, comparison, intersection, commonsense), analysis of major benchmarks (Yang et al., 2018; Ho et al., 2020; Trivedi et al., 2022) indicates that two types are fundamental and challenging: **bridge questions** and **comparison questions**. Building on existing research in MHQA, we formalize the key concepts used throughout this paper as follows:

A.1 Core Notation

Let $E = \{e_1, e_2, \dots, e_n\}$ be the *entity set*, $R = \{r_1, r_2, \dots, r_m\}$ be the *relation set*, and $D = \{d_1, d_2, \dots, d_l\}$ be the *document set*. For each document $d_j \in D$, we define the function:

$$\text{Trips}(d_j) = \{t = (e_a, r_h, e_c) | t \text{ in } d_j\} \quad (3)$$

where each triplet $t = (e_a, r_h, e_c)$ represents a relational fact extracted from document d_j .

A.2 Bridge Question

Bridge questions link facts across documents through intermediate entities, necessitating cross-document reasoning. It aims to find a single sequential path P connecting a start entity e_s to a target entity e_t .

P is a sequence of k triplets (e_i, r_i, e_{i+1}) that form a path from e_1 to e_k :

$$P = \langle (e_1, r_1, e_2), \dots, (e_{k-1}, r_{k-1}, e_k) \rangle \quad (4)$$

This framework imposes two constraints:

Fact Distribution Constraint: Each triplet in the path must come from exactly one document.

$$\forall (e_i, r_i, e_{i+1}) \in P, \exists! d_j \in D : (e_i, r_i, e_{i+1}) \in \text{Trips}(d_j) \quad (5)$$

No-Shortcut Constraint: No single document can bridge non-adjacent entities in the path.

$$\forall i, j : |i - j| > 1, \forall d \in D, \forall r \in R : (e_i, r, e_j) \notin \text{Trips}(d) \quad (6)$$

A.3 Comparison Question

Comparison questions contrast two entities (similar entities of the same category) by identifying their values for a specific relation, shared attribute, denoted as $r_c \in R$. This involves establishing attribute triplets for each entity:

$$t_1 = (e_1, r_c, v_1) \quad \text{and} \quad t_2 = (e_2, r_c, v_2) \quad (7)$$

Each triplet can be represented by a logical reasoning path:

$$P = \langle (e_1, r_1, e_2), \dots, (e_{n-1}, r_{n-1}, e_n) \rangle \quad (8)$$

The paths may differ but must lead to attribute heads associated with r_c for effective comparison.

Distributed Source Constraint: A comparison requires multi-hop reasoning if no single document contains both facts t_1 and t_2 . Let $D(t)$ be the set of documents stating triplet t . This means the sets of supporting documents must be disjoint:

$$D(t_1) \cap D(t_2) = \emptyset \quad (9)$$

B Detailed Dataset Statistics

To provide a comprehensive context for our evaluation, this section presents a detailed statistical comparison between questions synthesized by HopWeaver and those from three widely-used human-annotated multi-hop QA benchmarks: HotpotQA, 2WikiMultiHopQA, and MuSiQue. The following table (Table 5) summarizes key characteristics, including dataset size, question type distribution, and linguistic properties. This comparison is intended to situate our work within the landscape of existing datasets and to clarify the rationale behind our experimental design for ensuring a fair comparison.

Dataset Interpretation and Evaluation Configuration. The statistics presented in Table 5 highlight several key aspects pertinent to the main evaluation in our paper. HopWeaver is a flexible framework capable of generating high-quality multi-hop questions at scale, offering a significant cost and time advantage over the manual annotation processes that produce static datasets.

For a fair and meaningful comparison in our main quality evaluation (Table 1), we did not compare datasets in their entirety but instead selected specific, comparable question types from each benchmark. This ensures that we evaluate genuinely similar reasoning patterns. The specific configuration was as follows:

- From **HotpotQA**, we used their designated *Bridge* and *Comparison* type questions, which directly align with the two question types synthesized by HopWeaver.
- From **2WikiMultiHopQA**, we selected their *Comparison* and *Compositional* questions.

Dataset	Total Size	Train/Dev/Test Split	Question Types	Avg. Question Length	Avg. Answer Length
HopWeaver	Scalable Synthesis ¹	N/A	Bridge, Comparison	20.16 words	2.80 words
HotpotQA	112,779	90,447 / 7,405 / 7,405	Bridge (42%), Comparison (27%) Intersection (15%), Other (16%)	14.68 words	2.27 words
2WikiMultiHopQA	192,606	167,454 / 12,576 / 12,576	Comparison (30.1%), Comp. (45.2%) Bridge-comp. (20.8%), Inf. (3.9%)	11.59 words	2.29 words
MuSiQue	24,814	19,938 / 2,417 / 2,459	2-hop (68%), 3-hop (24%), 4-hop (8%)	16.28 words	2.60 words

¹As a synthesis framework, HopWeaver can generate questions at any scale; for evaluation purposes, our analysis was conducted on a randomly sampled subset of the generated questions.

Table 5: A statistical comparison of the HopWeaver-synthesized dataset against major human-annotated MHQA benchmarks.

Their “Compositional” questions, which require chaining facts, serve as a strong analogue to our “Bridge” questions, particularly in their emphasis on avoiding reasoning shortcuts.

- From **MuSiQue**, which is structured by hop count rather than explicit reasoning type, we used their *2-hop questions* as a proxy for the “Bridge” type, as it is the most common form of bridge reasoning. MuSiQue does not offer a distinct set of comparison questions.

Hop Distribution. All questions evaluated in our study are 2-hop, with the exception of MuSiQue, which also includes a smaller number of 3-hop and 4-hop variants. Our focus on the prevalent 2-hop structure allows for a robust validation of our core synthesis methodology across established datasets.

C Additional Experimental Validation

This appendix provides supplementary experimental results that substantiate the claims made in the main paper. We first present an ablation study justifying our key architectural choices. We then provide a large-scale validation of our primary findings, a human-centric evaluation of our LLM-as-judge framework, a manual assessment of the synthesized reasoning paths, and a detailed error analysis of QA failures.

C.1 Ablation Study

C.1.1 Reranker Efficiency

To evaluate our fine-tuned reranker’s efficiency (in Section 3.3), we compare retrieval strategies for Bridge question synthesis using two metrics: *Success Rate* (percentage of documents yielding valid questions) and *Average Attempts for Success* (attempts needed to find successful pairs).

Table 6 reveals progressively stronger results from standard dense retrieval (‘standard’) and MMR diversity (‘diverse’) to zero-shot reranking

(‘diverse + rerank (ZS)’). The optimal performance comes from our fine-tuned reranker (‘diverse + rerank (FT)’), delivering both superior success rates and requiring fewer document retrieval attempts. This demonstrates that fine-tuning substantially improves question synthesis efficiency and reduces computational costs.

Retrieval Strategy	Success Rate (%) ↑	Avg. Attempts ↓
Standard Dense Retrieval	70.1	1.59
Diverse (MMR)	70.9	1.62
Diverse + Rerank (ZS)	74.0	1.32
Diverse + Rerank (FT - Ours)	75.3	1.17

Table 6: Ablation study on the effectiveness of the fine-tuned reranker for Bridge question synthesis.

C.1.2 Polisher Module Effectiveness

We investigate the contribution of the Polisher module (Section 3.4) to the final question quality. We use LLM-as-judge to compare the quality assessment of questions between directly synthesized by LLMs (‘Original’) and the questions after being processed by the Polishing module (‘Polished’).

Table 7 shows that the Polisher module improves both the multi-hop validity rate and the average quality score for both Bridge and Comparison questions. This demonstrates the importance of the refinement and validation step in ensuring high-quality synthesized data. Notably, our analysis reveals a differentiated impact based on the capabilities of the generator LLMs. For stronger models like Gemini-2.5-flash, the Polisher’s improvements are modest, while smaller models such as GLM-4-9B exhibit more substantial gains (e.g., bridge question score rising from 3.71 to 3.87)

This highlights the Polisher module’s value in a resource-optimized pipeline, enabling smaller generator models to achieve high-quality outputs through targeted refinement rather than scaling up model parameters.

Generator	Version	Bridge Questions		Comparison Questions	
		Multi-Hop (%)	Avg. Score	Multi-Hop (%)	Avg. Score
Gemini	Original	95.2	4.26	98.0	4.42
	Polished	96.4	4.27	98.6	4.45
QwQ-32B	Original	97.6	4.20	97.2	4.36
	Polished	98.9	4.23	97.4	4.40
Qwen3-14B	Original	96.8	4.03	94.0	4.34
	Polished	96.9	4.09	95.9	4.36
GLM-4-9B	Original	84.5	3.71	92.8	4.13
	Polished	89.8	3.87	93.9	4.25

Table 7: Ablation study on the effectiveness of the Polisher module across different generator LLMs.

C.2 Human Validation of LLM-as-Judge

To substantiate the reliability of our LLM-as-judge framework, we conducted a pairwise human validation study to measure its alignment with human expert judgment. We selected 100 questions from our evaluation set and created 50 pairwise comparisons, ensuring that the LLM score difference between the paired questions was greater than 0.3 to make the comparison non-trivial.

Three Master’s students in Computer Science, serving as human evaluators, were asked to choose the better multi-hop question in each pair based on our established evaluation criteria. The final agreement metrics from this study are detailed in Table 8.

Metric	Value
<i>Human-LLM Alignment</i>	
Majority Agreement (LLM vs. Human Majority)	94%
Complete Agreement (LLM vs. Human Unanimity)	62%
<i>Inter-Human Reliability</i>	
Fleiss’ Kappa (Among 3 Human Raters)	0.46

Table 8: Human validation metrics for the LLM-as-judge framework across 50 pairwise comparisons.

Using majority voting to determine the final human preference, we found a high level of agreement, with the LLM’s ranking aligning with the human consensus in 94% of cases. This robust alignment between our automated assessment and human expert judgment validates the reliability of our evaluation methodology for comparing multi-hop question quality.

C.3 Manual Evaluation of Reasoning Paths

To directly verify that our synthesized questions necessitate authentic multi-hop reasoning, we performed a manual evaluation of the reasoning path correctness. We randomly sampled 100 questions generated by QwQ-32B and manually inspected

their reasoning paths, which connect the source documents via the bridge entity.

The analysis, detailed in Table 9, reveals that 92% of the generated reasoning paths are correct and logically sound. The primary source of minor errors was "Information Gap," where the path was factually accurate but relied on information just outside the explicitly provided evidence segments. This manual verification confirms that Hop-Weaver’s synthesis process generates high-quality questions that are structurally sound and genuinely require multi-hop reasoning.

Error Type	Count	Percentage
Correct	92	92%
Information Gap Error	6	6%
Ambiguity Issue	1	1%
Factual Reasoning Error	1	1%

Table 9: Manual evaluation results of reasoning path correctness on 100 samples.

C.4 Error Analysis of QA Failures

To understand the nature of the task difficulty presented by our dataset, we conducted a detailed case-by-case analysis of QA failures. We examined all 49 cases where the GPT-4o model failed to produce an exact match (EM=0) for our generated bridge questions (from a set of 100, where the overall EM was 0.51 in table 2. Our comprehensive examination reveals three categories of failures:

- **Category 1: Correct Answers with Format Variations (18 cases, 36.7%).** In these instances, the model provided a factually correct answer that did not achieve a perfect string match due to minor variations in phrasing, punctuation, or completeness (e.g., providing the full name when only the last name was required).
- **Category 2: Logical Reasoning Errors (29 cases, 59.2%).** This was the largest category of failures, representing instances where the model’s logical reasoning was flawed. This highlights the complexity of the questions and the inherent challenges of multi-hop reasoning for current LLMs.
- **Category 3: Insufficient Evidence Segments (2 cases, 4.1%).** In these rare cases, the

provided evidence snippets were not comprehensive enough to fully answer the questions, although the questions themselves were factually correct and answerable with complete context.

This analysis demonstrates that the vast majority of failures are attributable to either minor format variations or inherent model reasoning limitations, rather than flaws in the synthesized questions. Therefore, the observed 50% EM performance reflects the genuine challenge of the multi-hop reasoning task rather than indicating issues with question answerability or dataset quality.

C.5 Extension to 3-Hop Question Synthesis

To demonstrate that HopWeaver is not fundamentally limited to 2-hop reasoning, we applied recursive iteration to our pipeline. The bridge question synthesis process can be naturally chained: the Target Document (d_t) retrieved in one iteration serves as the Source Document (d_s) for the subsequent iteration, enabling the construction of longer reasoning chains.

Example 3-Hop Question. We present a synthesized question requiring integration across three documents:

- **Question:** “Which Montmartre nightclub, associated with the jazz quintet led by the musician honored posthumously by Didier Lockwood in 2000, hosted that band in 1937?”
- **Answer:** La Grosse Pomme

Reasoning Chain

1. **Hop 1** (Doc A → Doc B): Didier Lockwood recorded a tribute album in 2000 for *Stéphane Grappelli*.
2. **Hop 2** (Doc B → Doc C): Stéphane Grappelli co-founded the *Quintette du Hot Club de France* in 1934.
3. **Hop 3** (Doc C → Answer): The Quintette du Hot Club de France was employed as a house band by *La Grosse Pomme* in 1937.

Verification. Each hop requires information from a distinct document:

- Sub-question 1: Who did Didier Lockwood honor with a tribute album in 2000? → Stéphane Grappelli

- Sub-question 2: Which quintet did Stéphane Grappelli co-found? → Quintette du Hot Club de France

- Sub-question 3: Which nightclub employed this quintet in 1937? → La Grosse Pomme

This example confirms that HopWeaver’s core modules—bridge entity identification and complementary document retrieval—can be recursively composed to generate n -hop questions, provided the corpus contains the necessary connecting paths. Our focus on 2-hop questions in the main experiments aligns with established benchmarks, which predominantly feature 2-hop reasoning.

C.6 Pipeline Filtering and Rejection Statistics

To provide transparency regarding synthesis efficiency, we conducted a systematic audit by generating 100 successful samples for each question type using Gemini-2.5-flash, tracking rejections at key pipeline stages. We define the failure types as follows:

Bridge Question Pipeline

- **Step 3a (Sub-Question Generation):** The model fails to formulate valid sub-questions from retrieved documents.
- **Step 3b (Synthesis):** Valid sub-questions cannot be merged into a coherent multi-hop question.

Comparison Question Pipeline

- **Step 2 (Attribute Filtering):** Intentional quality gate filtering entities/attributes with low concreteness scores.
- **Step 3 (Question Construction):** No valid comparable attribute pair found in retrieved documents.

Final Polishing. The Polisher module assesses generated question quality as a final filter.

Type	Stage	Count	Rate
Bridge	Step 3a: Sub-Question Gen.	29	22.3%
Bridge	Step 3b: Question Synthesis	4	3.1%
Bridge	Polisher Module	4	3.1%
Comparison	Step 2: Attribute Filtering	7	6.6%
Comparison	Step 3: Question Construction	2	1.9%
Comparison	Polisher Module	2	1.9%

Table 10: Rejection statistics at each pipeline stage.

Key Observations. Most rejections occur early—Step 3a accounts for 78% of Bridge failures—efficiently filtering unsuitable candidates

before expensive steps. The Polisher’s low rejection rate indicates upstream synthesis produces high-quality outputs. The 7.6 average API calls per question (Appendix D) already incorporates all retries.

D Cost Analysis

The tests were conducted on gemini-2.5-flash (the most expensive model we have tested). The following Table 11 summarizes the token consumption for question generation and LLM-as-Judge evaluation (on GPT-4o).

Process	Avg. Requests/Calls	Input Tokens (Per. Req.)	Output Tokens (Per. Req.)
Question Synthesis	7.6	1529.97	231.32
LLM-as-Judge Evaluation	5	1885.53	83.00

Table 11: Token consumption analysis.


For closed-source models, API calls can be made via their respective platforms. For example, based on the consumption data in this table, synthesizing 1000 multi-hop questions (7600 times requests) using Gemini 2.5 Flash (assuming API pricing of \$0.15 per million input tokens and \$3.50 per million output tokens) would cost approximately \$7.90. Similarly, using GPT-4o (assuming API pricing of \$2.5 per million input tokens and \$10 per million output tokens) as a single evaluation model to evaluate 1000 synthesized questions would cost approximately \$27.72. For open-source models, we utilized a setup with 4x A100 (40GB VRAM) GPUs for deployment and inference with bf16 precision. For some open-source models, due to considerations of complex deployment engineering efforts, we used APIs via OpenRouter while still ensuring high reproducibility.


The result implies that the cost of synthesizing a dataset with thousands of entries is significantly lower than manual annotation; if small-scale open-source models are used, these generation costs can be almost negligible. Furthermore, if multiple LLMs are required for large-scale evaluation of dataset quality, the corresponding computational power or financial costs must also be taken into consideration.


E Examples of Synthesized Questions


E.1 Bridge Question Example

Figure 5 shows an example of a synthesized bridge question detailing the involved reasoning path and source information.


 Source Document (**Anatomy Snippet**):
 "...medial tendinous margins of the crura... meet ... to form an arch ... known as the **median arcuate ligament**..."
 (Context: Defines the anatomical structure)

 Retrieved Document (**Pathology Snippet**):
 "**Median arcuate ligament syndrome (MALS)**... is a condition characterized by... compression ... by the **median arcuate ligament**."
 (Context: Links the structure to the medical condition)

 Bridge Entity: **median arcuate ligament**

 Reasoning Path :

1. Identify Structure (from Source): The anatomical structure formed is the **median arcuate ligament**.
2. Link to Condition (from Target): Compression by the **median arcuate ligament** leads to **Median arcuate ligament syndrome**.

 Question:
 What medical condition is attributed to the compression caused by the anatomical structure formed by the meeting of the medial tendinous margins of the diaphragm’s crura?


 Answer:
Median arcuate ligament syndrome (MALS)

Figure 5: An example of a bridge question synthesized by HopWeaver. The figure illustrates the source documents, the identified bridge entity, the reasoning steps, and the final generated question-answer pair.

E.2 Comparison Question Example


An example of a comparison question is presented in Figure 6, highlighting the entities and attributes under comparison.


F Evaluation Criteria for LLM-as-Judge


F.1 Pointwise Scoring Framework


To assign an absolute quality score to each synthesized question-answer pair and ensure a rigorous, multi-faceted evaluation, we employ a *pointwise* scoring approach. This method allows for the independent evaluation of each item against a predefined set of criteria by an LLM judge (Liu et al., 2023; Fu et al., 2024a). We opted for pointwise scoring over pairwise comparison (Liusie et al., 2024) because our synthesized questions are non-parallel and vary significantly in difficulty, making it challenging to establish fair comparative benchmarks necessary for pairwise approaches. The detailed criteria for our pointwise evaluation are organized into three main categories:

- **Multi-Hop QA Rule Dimension:** This is a binary (Yes/No) evaluation determining if the question authentically involves reasoning across multiple documents, where information from one document is necessary to un-

 Source Document (Composer Biography Snippet):
 "Mihály Mosonyi (4 September 1815 in Boldogasszony, Austria-Hungary – 31 October 1870 in Budapest) was a Hungarian composer."
 (Context: The biographical information of Hungarian composer Mihály Mosonyi)

 Retrieved Document (Composer Biography Snippet):
 "The future composer, only son of Adam Liszt and his wife Maria Anna, was born here on 22 October 1811."
 (Context: Details Liszt's birthplace and childhood)

 Compared Attribute: **Date of Birth**

 Reasoning Path:
 1. Identify Information (from Source): Mihály Mosonyi was born on September 4, 1815
 2. Identify Information (from Target): Franz Liszt was born on October 22, 1811
 3. Compare Dates: 1811 is earlier than 1815

 Question:
 Which composer has an earlier Date of Birth: **Mihály Mosonyi** or **Franz Liszt**?


 Answer:
Franz Liszt

Figure 6: An example of a comparison question synthesized by HopWeaver. This showcases the two entities being compared, the specific attribute, the source evidence snippets, and the resulting question.

1320 understand or utilize information in another, and
 1321 the answer cannot be derived from any single
 1322 document. This dimension is paramount; a
 1323 “No” indicates a fundamental failure.

- 1324 • **Linguistic Dimensions:** These evaluate the
 1325 quality of question presentation, ensuring un-
 1326 derstandability and precision. Criteria in-
 1327 clude:
 - 1328 – *Fluency:* Grammatical correctness and
 1329 coherence.
 - 1330 – *Clarity:* Unambiguous and precise ex-
 1331 pression.
 - 1332 – *Conciseness:* Absence of redundant in-
 1333 formation.
- 1334 • **Task-Oriented Dimensions:** These evalu-
 1335 ate the functional and logical aspects of the
 1336 question-answer pair within the provided doc-
 1337 ument context. Criteria include:
 - 1338 – *Relevance:* Appropriateness to the given
 1339 passages and focus on key information.
 - 1340 – *Consistency:* Strict adherence of the
 1341 question’s information to the source pas-
 1342 sages, free from contradictions or hallu-
 1343 cinations, however subtle.

- *Question Answerability:* Whether the 1344
 question can be clearly and unambigu- 1345
 ously answered solely from the provided 1346
 passages. 1347
- *Answer-Question Consistency:* Accuracy 1348
 and completeness of the answer in ad- 1349
 1350 dressing the question.
- *Information Integration Ability:* Coher- 1351
 ent and logical integration of informa- 1352
 1353 tion from multiple documents, without forc-
 1354 ing unnatural connections.
- *Reasoning Path Guidance:* Clear direc- 1355
 1356 tion for a multi-step reasoning process.
- *Logical Sophistication:* Non-trivial and 1357
 sound design requiring multi-step think- 1358
 1359 ing, free from logical gaps or fallacies,
 1360 presenting a genuinely challenging and
 1361 sound multi-hop problem.

Particularly, dimensions such as *Consistency*, 1362
Information Integration Ability, and *Logical* 1363
Sophistication are critical. Flaws in these ar- 1364
 1365 eas are heavily penalized, reflecting their sig-
 1366 nificance in ensuring the quality of authentic
 1367 multi-hop questions.

For scoring the Linguistic and Task-oriented di- 1368
 1369 mensions, a Likert-like scale (Very Poor, Poor, Fair,
 1370 Good, Very Good) is employed. However, the LLM
 1371 judge is instructed to adopt a **skeptical default**
 1372 **stance** and interpret these scale points with height-
 1373 ened strictness, as summarized below, to minimize
 1374 subjective bias and ensure only high-quality items
 1375 receive favorable scores (Liu et al., 2023):

- **Very Poor (Unacceptable):** Fundamentally 1376
 1377 flawed (e.g., not truly multi-hop, severe con-
 1378 tradictions, unanswerable).
- **Poor (Weak/Barely Usable):** Obvious, ma- 1379
 1380 jor flaws requiring significant revision (e.g.,
 1381 weak/forced logic, inconsistencies).
- **Fair (Acceptable/Passable):** Basic require- 1382
 1383 ments met but with notable flaws or room for
 1384 improvement; signifies minimum adequacy
 1385 only, not a positive endorsement.
- **Good:** Well-designed, logically clear, fluent, 1386
 1387 and meets multi-hop criteria without obvious
 1388 flaws.
- **Very Good (Excellent/Outstanding):** Exem- 1389
 1390 plary design with deep logic, precision, and
 1391 rigor.

This stringent evaluation mechanism, with a directive to assign lower ratings (‘Poor’ or ‘Very Poor’) when significant flaws are present (especially logical ones), effectively filters out low-quality or trivially multi-hop questions. A question with significant logical flaws cannot achieve a ‘Good’ or ‘Very Good’ rating overall, even if linguistically sound.

F.2 Beyond Human Alignment: The Case for LLM Self-Consistency

Human judgments, while valuable, exhibit limitations that challenge their role as the sole benchmark for aligning LLMs. First, inter-rater reliability in subjective tasks is often low; for example, human evaluations of dialogue quality show poor agreement (e.g., Krippendorff’s $\alpha = 0.33$ on PersonaChat, indicating fair agreement; $\alpha = 0.08$ on WMT 2020 Zh-En, indicating slight agreement; $\alpha = 0.49$ on QAGS, indicating moderate agreement, (Bavaresco et al., 2024)). Similarly, in MHQA tasks, which often span multiple domains and require complex reasoning, human judgments are likely to be inconsistent due to the subjective nature of criteria like question clarity, relevance, and logical sophistication. Second, human ratings are prone to systematic biases—such as fatigue, cultural preferences, or contextual misunderstandings—which introduce variability and undermine evaluation reliability. Indeed, research into human perceptions of LLM outputs reveals that factors unrelated to intrinsic quality, such as perceived LLM sentience or anthropomorphism, can influence human evaluations (Lee et al., 2025; Zheng et al., 2023; Chiang and Lee, 2023).

Furthermore, much of the current work on LLM-as-judge focuses on achieving high correlation with human preferences or ratings (Ye et al., 2024). While aligning with human intuition is a desirable goal, an overemphasis on mimicking human scores can inadvertently lead LLM judges to replicate the aforementioned human biases and inconsistencies. If human agreement itself is a noisy or unstable signal, then LLM judges optimized solely for human-LLM consistency may inherit these limitations rather than serving as a more objective or stable evaluation instrument. This is particularly problematic when the goal is to create a scalable and reliable evaluation framework (Lee et al., 2025; Zheng et al., 2023).

Given these constraints, we contend that while human feedback remains a crucial component in the broader LLM development lifecycle, pursuing

perfect alignment between LLM judge scores and raw human judgments as the *primary* evaluation metric for the judge itself is neither always feasible nor universally desirable for all evaluation tasks. Instead, we propose prioritizing the **self-consistency** of LLMs—defined as their ability to deliver stable, reproducible outputs for identical inputs under controlled conditions—as a foundational criterion for selecting qualified judge models. This shift towards emphasizing demonstrable reliability in the LLM judge’s own behavior ensures a more standardized and robust evaluation framework, mitigating the risk of amplifying the inherent shortcomings of human-based assessments when seeking fine-grained, repeatable quality scores.

F.3 LLM Reliability: Metrics and Evaluation Results

We posit that a trustworthy judge must produce stable outputs under identical conditions. Given each item, we sample $N = 5$ independent runs at temperature $T = 0$ to ensure output stability, as lower temperatures are suitable for evaluation tasks.

Metrics To provide a comprehensive evaluation of LLM judge reliability from multiple perspectives, we employ three complementary metrics: Avg. Intra-item SD measures the direct stability of scores, while Krippendorff’s Alpha and Fleiss’ Kappa evaluate the statistical significance of inter-run agreement corrected for chance.

(i) **Avg. Intra-item SD** measures score volatility for each item across N repeated runs:

$$SD_i = \text{std}(\{s_i^{(1)}, \dots, s_i^{(N)}\}) \quad (10)$$

$$\text{AvgSD} = \frac{1}{M} \sum_{i=1}^M SD_i \quad (11)$$

where $s_i^{(j)}$ is the score for item i in run j , and M is the total number of items.

(ii) **Krippendorff’s α** (Krippendorff, 2018) treats the N runs as raters and measures agreement beyond chance for various data types:

$$\alpha = 1 - \frac{D_o}{D_e} \quad (12)$$

where D_o is the observed disagreement and D_e is the expected disagreement by chance.

(iii) **Fleiss’ Kappa (κ)** (Fleiss, 1971) measures inter-rater agreement for categorical ratings, evaluating reliability among multiple raters (our N

1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501

runs):

$$\kappa = \frac{\bar{P} - \bar{P}_e}{1 - \bar{P}_e} \quad (13)$$

where \bar{P} is the mean proportion of observed agreement among raters, and \bar{P}_e is the mean proportion of agreement expected by chance.

Based on these reliability metrics, we evaluate several open-source and proprietary LLMs on a held-out subset ($M = 100$). The model with higher agreement metrics (α, κ) and lower AvgSD values is selected as the LLM judge. To avoid self-enhancement bias (Ferrara, 2023), the chosen judge never scores its own generations or those from close variants.



Figure 7: Heatmap visualizing AvgSD scores across different LLMs and evaluation dimensions.




Figure 8: Heatmap visualizing Krippendorff's Alpha scores across different LLMs and evaluation dimensions.

Final LLM Judge Ensemble Considering a balance of evaluation performance (as indicated by the reliability metrics defined earlier in this appendix and further detailed in Table 12 presented below)




Figure 9: Heatmap visualizing Fleiss' Kappa scores across different LLMs and evaluation dimensions.

and operational costs, we selected an ensemble of LLMs to serve as our final judges:

- claude-3-7-sonnet-20250219
- gpt-4o-2024-11-20
- gemini-2.0-flash
- google/gemma-3-27b-it
- meta-llama/llama-3.3-70b-instruct

The use of this diverse set of models, including both proprietary and open-source options, aims to provide a robust and comprehensive evaluation, while also considering the reproducibility and accessibility of the evaluation process. The average scores from this ensemble are used for the final quality evaluation of the synthesized multi-hop questions.

Model	AvgSD ↓	Krippendorff's Alpha ↑	Fleiss' Kappa ↑
Claude-3.7	0.280	0.634	0.446
Gemini-2.0-flash	0.147	0.669	0.654
Gemma-3-27b	0.191	0.732	0.562
GPT-4o	0.348	0.740	0.454
Llama-3.3-70b-instruct	0.276	0.669	0.541
DeepSeek-V3-0324	0.365	0.536	0.447
Llama-4-maverick	0.108	0.601	0.541
Mistral-small-3.1	0.411	0.376	0.148
Llama-3.3-nemotron-49b	0.543	0.182	0.085

Table 12: LLM reliability evaluation results. Performance of candidate LLMs on reliability metrics (AvgSD ↓, Krippendorff's Alpha ↑, Fleiss' Kappa ↑) used to inform judge selection.

G Entity and Attribute Filtering Mechanism

To ensure the quality and suitability of entities and attributes for synthesizing comparison multi-hop questions, we employ a filtering mechanism

1502
1503
1504
1505

based on evaluating the concreteness of subject entities and the comparability of their attribute values. This process assigns numerical scores on a 1-5 scale, facilitating downstream filtering of less ideal candidates. The detailed criteria, as defined in our COMPARE_ENTITY_FILTER_PROMPT, are summarized below:

G.1 Subject Entity Concreteness evaluation

The concreteness_score evaluates how specific, tangible, and suitable an entity is for direct attribute comparison. The scale is defined as:

- **5 (Highly Concrete):** Specific person, place, organization, tangible object, work, or clearly defined historical event (e.g., "Paris", "IBM"). Excellent candidate.
- **4 (Concrete):** Specific but less common entity types, like a specific named award or law (e.g., "Nobel Prize in Physics"). Good candidate.
- **3 (Borderline/Slightly Abstract):** Broader but well-defined categories or specific complex relationships (e.g., "Mammal", "World War II"). Use with caution.
- **2 (Abstract):** General relationships, abstract concepts, fields of study (e.g., "US-China relations", "Democracy"). Poor candidate.
- **1 (Highly Abstract):** Vague concepts, general feelings, ambiguous terms (e.g., "Happiness"). Unsuitable candidate.

G.2 Attribute Comparability Evaluation

The comparability_score evaluates each attribute value based on its suitability for direct and unambiguous comparison. The scale is defined as:

- **5 (Excellent):** Precise Dates (YYYY-MM-DD), specific Years, specific Numbers, exact Locations, specific Names, well-defined unambiguous Categories (e.g., Nationality).
- **4 (Good):** Specific but slightly less precise numbers (e.g., "1.2 million"), specific office/rank titles.
- **3 (Fair):** Broader categories, precise year ranges, specific event names. Potential candidate but less ideal.
- **2 (Poor):** Imprecise time (e.g., "Before 1960s"), descriptive reasons, lists. Unlikely suitable.

- **1 (Very Poor):** Vague statements, subjective opinions, long text. Unsuitable.

The filtering module processes each entity and its attributes based on these scoring criteria. Entities and attributes that do not meet a predefined threshold (default setting: a minimum score of 5 for subject entities and 4 for attributes) are filtered out before proceeding to the comparison query generation step (see Section 3.2 for their position in the pipeline). This specific 5/4 threshold was adopted based on the evaluation standards of a particular open-source model (Gemma-3-27B-it, as detailed in Appendix H), making it a reasonable choice for our study. Researchers can adjust it to fit different models or specific task requirements. This ensures that only entities with a sufficient level of concreteness and attributes with high comparability are used for synthesizing comparison questions, thereby enhancing the quality and relevance of the synthesized questions. The output format for these scores is a delimited string, with the first part being the entity's concreteness score and subsequent parts detailing each attribute's name, value, and comparability score.

H Experimental Settings

Corpus. We use the widely-adopted English Wikipedia dump from December 20, 2018. This date was chosen to align closely with the Wikipedia snapshots used in the baseline datasets (HotpotQA (Yang et al., 2018), 2WikiMultiHopQA (Holt et al., 2020), and MusiQue (Trivedi et al., 2022)), ensuring a fair comparison of synthesized question quality under consistent data conditions. We preprocess the corpus by removing articles with more than 4096 words and store the remaining articles in JSONL format.

Generator LLMs. We employ four LLMs with varying capabilities and parameter sizes for question synthesis pipeline: Gemini-2.5-flash-preview-04-17, QwQ-32B, Qwen3-14B, and GLM-4-9B-0414. Preliminary experiments showed that older or smaller models often lacked the capability to perform the complex generation steps. To prevent potential **self-enhancement bias** (Ferrara, 2023), these generator LLMs are deliberately kept distinct from those LLMs that constitute our LLM-as-judge evaluation system.

We also note that the outputs of closed-source

1619 models can fluctuate over time, potentially impact-
1620 ing reproducibility, an effect we observed with the
1621 Gemini model during our experimental period.

1622 **LLM-as-judge Models.** The details are shown
1623 in Appendix F.3.

1624 **Embedding and Reranker Models.** For initial
1625 retrieval (coarse retrieval and MMR calculation)
1626 during the synthesis pipeline, we uniformly use
1627 the gte-multilingual-base embedding model.
1628 For the reranking stage (Step 2 in Section 3.1), we
1629 use BAAI/bge-reranker-v2-m3. For the retrieval-
1630 based dataset Evaluation (Section 4.3), we evalu-
1631 ate using gte-multilingual-base, E5-base-4k,
1632 and BM25. Our retrieval implementation is based
1633 on the FlashRAG (Jin et al., 2024).

1634 **Parameters for Coarse Retrieval** In the coarse
1635 retrieval stage for bridge question synthesis (Sec-
1636 tion 3.1, Step 2), the MMR-like scoring function
1637 utilizes three trade-off parameters. We empirically
1638 set these parameters as follows: $\lambda_1 = 0.87$ (em-
1639 phasizing query relevance), $\lambda_2 = 0.03$ (penalizing
1640 similarity to the source document), and $\lambda_3 = 0.1$
1641 (promoting diversity among selected documents).
1642 These values are determined through preliminary
1643 experiments to balance the objectives of relevance,
1644 novelty, and diversity in the retrieved complemen-
1645 tary documents.

1646 **Comparison Datasets.** We compare the qual-
1647 ity of HopWeaver-synthesized questions against
1648 three established human-annotated multi-hop QA
1649 datasets: HotpotQA (Yang et al., 2018), 2WikiMul-
1650 tiHopQA (Ho et al., 2020), and MusiQue (Trivedi
1651 et al., 2022)

1652 **Evaluation LLM.** For the QA-based dataset
1653 Evaluation (Section 4.2), we use GPT-4o,
1654 Gemini-2.0-flash, Qwen3-9B, Llama-3.3-70B
1655 to obtain answers from LLMs with different per-
1656 formance levels.

1657 **Polisher LLM.** For the Polisher module exper-
1658 iments (Section 4.2), we use DeepSeek-R1 to get
1659 an effective supervision signal.

1660 **Filter LLM.** For the Filter module experiments
1661 (Step 2 in Section 3.2), we use Gemma-3-27B-it to
1662 get a stable rating threshold, which avoids fluctua-
1663 tions in question quality caused by different LLMs’
1664 standards when picking up entities and attributes.

Default Generation Parameters. For all LLMs
in our experiments, we use deterministic genera-
tion settings (temperature=0, do_sample=False)
with top_p=0.9 and max_tokens=8192 to ensure
reproducibility while accommodating complex rea-
soning chains required for multi-hop question syn-
thesis.

RAG System Settings. For the end-to-end RAG
system evaluation (Section 5.4), we adopt a uni-
fied configuration to ensure a fair comparison. The
generator component utilizes the LLAMA3-8B-
Instruct model with a maximum input length of
2048 tokens. The retriever employs the e5-base-v2
embedding model, configured to retrieve the top
5 documents for each query. To maintain consis-
tency, all experiments use a default prompt that
aligns with the standard practices of the FlashRAG
benchmark.

I Prompt Settings

Considering that this work involves a substantial
number of prompts, each with a relatively lengthy
original format, we have made appropriate simpli-
fications while retaining the essential information
from the original prompts. Readers interested in
the complete original prompts could refer to the
provided code file.

Bridge Entity Extraction Prompt (ENTITY_EXTRACTION_PROMPT)

Goal

Given a text document, select a single segment with high potential to contain a bridge entity for multi-hop question generation, identify one bridge entity from that segment, extract relevant text segments, and generate an expanded query statement for this bridge entity to retrieve related documents from a vector database.

Instructions

- 1. Select a Segment and Identify a Bridge Entity** - Select a text segment with high potential for containing a bridge entity, then identify one bridge entity. - **Principles:** - **High Connectivity:** The entity has multiple associations with other entities. - **Uniqueness and Clarity:** The entity is clearly defined within the segment. - **Attribute Richness:** The entity has multiple queryable attributes. - **Cross-Document Distribution:** Information likely spread across documents. - **Distinct from Title:** The bridge entity must not be identical to the document title. - Format: ("bridge_entity" <|> "entity_name" <|> "entity_type")
- 2. Extract Relevant Text Segments** - Extract a single part of the document that directly mentions or describes the entity. - Provide a brief introductory sentence followed by the extracted segment. - Format: ("relevant_segments" <|> "entity_name" <|> "entity_introduction + extracted_part")
- 3. Generate an Expanded Query Statement** - Generate a query to find COMPLEMENTARY information about the entity. - Use semantic direction shifting phrases like "instead of," "beyond," etc. - Format: ("query" <|> "entity_name" <|> "entity_query")
- 4. Return Output** - Return a single list with the bridge entity, relevant segments, and expanded query.
- 5. When Finished** - Output <|COMPLETE|>

Sub-Question Generation Prompt (SUB_QUESTION_GENERATION_PROMPT)

Goal

Analyze two documents connected by a bridge entity and generate two sequential sub-questions that form a multi-hop reasoning chain.

Instructions

Analyze how the bridge entity connects both documents by:

- Identifying key information about the bridge entity in Document A that is unique to Document A.
- Finding related information in Document B that connects via this bridge entity.
- Determining a clear reasoning path from Document A to Document B.
- If no valid bridge connection exists, return INVALID_BRIDGE_CONNECTION with explanation.

Generate two sequential sub-questions:

- **Sub-question 1:** A question about Document A where the answer is the bridge entity.
- **Sub-question 2:** A question that explicitly uses the bridge entity to find related information in Document B.

Each sub-question must:

- Be answerable from only one document.
- Have a definitive answer contained in its document.
- Be phrased as a standalone question without document references.
- Be specific with clear references to information in its document.
- Provide a clear, concise answer.
- Together form a logical reasoning chain.

Output Format

If no valid bridge connection exists:

INVALID_BRIDGE_CONNECTION
Reason: [Brief explanation]

If valid bridge connection exists:

ANALYSIS:

Bridge connection: [How the bridge entity connects the documents]

Document A segments: [Copy of the original Document A segments]

Document B segments: [Relevant excerpts from Document B]

Reasoning path: [Logical path from Document A to Document B]

SUB-QUESTIONS:

Sub-question 1: [Question about Document A]

Answer 1: [Answer from Document A - about the bridge entity]

Sub-question 2: [Question using bridge entity to find answer in Document B]

Answer 2: [Answer from Document B]

Multi-Hop Question Synthesis Prompt (MULTI_HOP_QUESTION_SYNTHESIS_PROMPT)

Goal

Synthesize a concise, natural multi-hop question that requires reasoning across two documents, connecting two sub-questions into a single logical inquiry.

Instructions

- FIRST, check if the bridge entity (Answer 1 from the first sub-question) is included in the text of the second sub-question. If not, return NONE.
- Review the analysis and sub-questions to trace the full reasoning chain.
- Create a single multi-hop question that:
 - Is ONE cohesive question, not multiple questions combined
 - Requires distinct information from both Document A and B
 - Reads naturally as a coherent, conversational question
 - Cannot be fully answered using only one document
 - Follows the reasoning path of the sub-questions, using the bridge entity (Answer 1) to link to information in Document B
 - Is clear, concise, and free of ambiguity
 - Doesn't explicitly mention the bridge entity or reasoning steps
 - If the sub-questions cannot be combined into a valid multi-hop question, return NONE with explanation.
- Ensure the final answer matches Answer 2 (the answer from Document B) from the sub-questions.

Output Format

If sub-questions cannot be combined:

NONE

Reason: [Brief explanation]

If a valid multi-hop question can be created:

MULTI-HOP QUESTION: [Your synthesized question]

ANSWER:

[The final answer, matching Answer 2 from Document B]

REASONING PATH:

[Step-by-step explanation showing:

1. How to find the bridge entity (Answer 1) in Document A
2. How this bridge entity leads to the final answer in Document B]

SOURCES:

[Document A and Document B, specifying their roles]

Bridge Polisher Prompt (POLISHER_PROMPT)

Goal

Validate and refine multi-hop questions to ensure they genuinely require cross-document reasoning and follow a proper reasoning chain where information from one document is essential to answer a question about content in another document.

Instructions

You are a Polisher module responsible for validating and refining multi-hop questions. Given a multi-hop question, its suggested answer, reasoning path, and source document segments, you will evaluate the question's quality and make one of four decisions:

1. **PASS:** The question is valid, well-formed, and genuinely requires both documents.
2. **ADJUST:** The question needs surface wording improvements only.
3. **REWORKED:** The question needs substantial structural changes.
4. **REJECTED:** The question has unfixable flaws.

Review and modify the question based on these key dimensions:

1. **True Multi-hop Necessity:** CRITICAL

- Information must flow from Document A to Document B in a logical sequence
- The answer must be impossible to determine using either document in isolation
- The reasoning path must demonstrate how Document A provides necessary context
- The question should require discovering connections not explicitly stated

2. **Hidden Bridge Structure:**

- The question should NOT directly mention the connecting entity or concept
- The bridge entity should remain implicit in the question wording
- The question should require identifying the relevant bridge entity
- Reframe questions that explicitly name the bridge entity

3. **Reasoning and Answer Quality:**

- Verify the reasoning follows a logical progression between documents
- Ensure the answer is factually accurate according to both documents
- Check that the answer requires synthesizing information across documents
- Improve question wording for clarity, fluency, and natural tone

Output Formats

1. *If the question passes all criteria without changes:*

[PASS]

2. *If the question needs minor adjustments:*

[ADJUST]

REFINED_REASONING_PATH: [Updated reasoning path]

REFINED_QUESTION: [Adjusted question]

REFINED_ANSWER: [Updated answer if needed]

3. *If the question needs significant refinement:*

[REWORKED]

REFINED_REASONING_PATH: [Revised reasoning path]

REFINED_QUESTION: [Substantially revised question]

REFINED_ANSWER: [Updated answer]

4. *If the question is fundamentally flawed:*

[REJECTED]

Goal

Conduct a **rigorous and critical** evaluation of multi-hop questions and their answers across multiple quality dimensions. Focus on ensuring questions require genuine cross-document reasoning **and are free from logical flaws**. A high-quality multi-hop question necessitates reasoning that flows between documents, where information from one document provides context for another, and the answer must be impossible to determine using any single document in isolation.

Instructions

You are a **strict and discerning** Multi-Hop Question Answering (MHQA) dataset quality assessment expert. Evaluate the given multi-hop question and its answer across key dimensions in three categories. **Apply rigorous scrutiny and do not hesitate to assign lower ratings if flaws are present, especially logical ones.**

1. **Multi-Hop QA Rule Dimension - Multi-Hop Reasoning Requirement:** Does the question genuinely require reasoning across multiple documents? (Yes/No)

2. **Linguistic Dimensions** (Rate as: Very Poor, Poor, Fair, Good, Very Good) - **Fluency:** Is the question grammatically correct, coherent, and easy to understand? - **Clarity:** Is the question clearly and precisely expressed without ambiguity? - **Conciseness:** Is the question concise without redundant information?

3. **Task-Oriented Dimensions** (Rate as: Very Poor, Poor, Fair, Good, Very Good) - **Relevance:** Is the question relevant to the given passages and asking for key information? - **Consistency:** Is the information in the question **completely and strictly** consistent with the provided passages? - **Question Answerability:** Can the question be **unambiguously** answered based **solely** on the given passages? - **Answer-Question Consistency:** Does the provided answer completely and accurately address the question? - **Information Integration Ability:** Does the question coherently integrate information from multiple documents **without forcing unnatural connections**? - **Reasoning Path Guidance:** Does the question guide the answerer through a multi-step reasoning process? - **Logical Sophistication:** Does the question demonstrate non-trivial and sound design that requires multi-step thinking and is **free from logical gaps or fallacies**?

Critical Scoring Guidance: - **Penalize Logical Flaws Heavily:** Pay close attention to Consistency, Logical Sophistication, and Information Integration Ability. - **Multi-Hop Requirement is Paramount:** If this requirement is "No," the question fundamentally fails. - **Clarification on 'Fair':** A 'Fair' rating signifies only basic adequacy and is not a positive endorsement.

Rating Scale Interpretation: - **Very Poor:** Unacceptable quality with serious functional/logical errors - **Poor:** Weak/Barely Usable quality with obvious, major flaws - **Fair:** Acceptable/Passable quality meeting basic requirements with clear flaws - **Good:** Standard good quality, well-designed without obvious flaws - **Very Good:** Excellent/Outstanding quality with clever, rigorous design

Output Format:

- Multi-Hop Reasoning Requirement: {yes/no}
 - Fluency: {rating}
 - Clarity: {rating}
 - Conciseness: {rating}
 - Relevance: {rating}
 - Consistency: {rating}
 - Question Answerability: {rating}
 - Answer-Question Consistency: {rating}
 - Information Integration Ability: {rating}
 - Reasoning Path Guidance: {rating}
 - Logical Sophistication: {rating}
- <|COMPLETE|>

Compare Entity Extraction Prompt (COMPARE_ENTITY_EXTRACTION_PROMPT)

Goal

Given a text document, identify its primary subject entity and extract multiple key attributes associated with this entity, along with their corresponding values. For each extracted attribute, generate an expanded query statement designed to retrieve documents about *other* similar entities that also possess this attribute, facilitating subsequent comparison.

Instructions

1. Identify the Primary Subject Entity

- Determine the main person, place, organization, event, concept, or work that the document is primarily about.
- Determine the **subject_entity_name** (capitalized) and its general **subject_entity_type**.

2. Extract Comparable Attributes, Values, and Generate Queries

- Identify **multiple (aim for 3-5 if possible)** distinct attributes associated with the primary subject entity.
- **Focus strictly on attributes whose VALUES are suitable for comparison.** Prioritize attributes that meet these criteria:
 - **Concise & Factual Value:** Short value (e.g., name, number, date, category, location).
 - **Common Data Types:** Prefer Numbers, Dates, Locations, Specific Names, Defined Categories.
 - **Likely Commonality:** Prefer attributes likely to exist for other similar entities.
- **For each identified comparable attribute:**
 - Determine the **attribute_name** (e.g., "Population", "Date of Birth").
 - Extract the **attribute_value** (e.g., "1.2 million", "1990-05-15").
 - Generate an **entity_b_query**: A concise query to find *other* entities with the same attribute.

3. Output Format Specification

- **Subject Entity Part:** ("subject_entity"<|>"subject_entity_name"<|>"subject_entity_type")
- **Attribute Parts:** ("attribute"<|>"attribute_name"<|>"attribute_value"<|>"entity_b_query")
- Use ## as delimiter between parts.
- Append <|COMPLETE|> at the end.

Compare Entity Filter Prompt (COMPARE_ENTITY_FILTER_PROMPT)

Goal

Assess the concreteness of a pre-identified subject entity and the comparability of its extracted attribute values. Assign numerical scores reflecting these assessments on a 1-5 scale to facilitate downstream filtering.

Instructions

- 1. Assess Subject Entity Concreteness:** - Evaluate the provided `subject_entity_name` and `subject_entity_type`. - Assign a **concreteness_score** on a scale of 1 to 5:
 - **5 (Highly Concrete):** Specific person, place, organization, tangible object, work, or defined event. (e.g., "Mihály Mosonyi", "Paris", "IBM")
 - **4 (Concrete):** Specific but less common entity types. (e.g., "Nobel Prize in Physics", "Treaty of Versailles")
 - **3 (Borderline/Slightly Abstract):** Broader well-defined categories. (e.g., "Mammal", "Impressionism")
 - **2 (Abstract):** General relationships, abstract concepts, fields of study. (e.g., "US-China relations", "Democracy")
 - **1 (Highly Abstract):** Very vague concepts, feelings, ambiguous terms. (e.g., "Happiness", "The problem with X")
- 2. Assess Attribute Comparability:** - Evaluate **each** provided `attribute_value`. - Assign a **comparability_score** (scale 1-5):
 - **5 (Excellent):** Precise Dates, Years, Numbers, exact Locations, specific Names, well-defined Categories.
 - **4 (Good):** Specific but slightly less precise numbers, specific titles.
 - **3 (Fair):** Broader categories, year ranges if precise, specific event names.
 - **2 (Poor):** Imprecise time, descriptive reasons, lists.
 - **1 (Very Poor):** Vague statements, subjective opinions, long text.
- 3. Format Output:** Generate the output string according to the specification.

Output Format Specification

Strictly adhere to the following output format:

- 1. Structure:** The entire output must be a single string containing multiple parts delimited by `##`.
- 2. First Part (Entity Score):** The *first* part MUST represent the entity's concreteness score. Format: (`"entity_score"<|>5`) (example shows score of 5).
- 3. Subsequent Parts (Attribute Scores):** For *each* attribute provided in the input, include a corresponding scoring part. Format: (`"attribute_score"<|>"Birth Date"<|>"4 September 1815"<|>5`) (example shows score of 5 for a date attribute).
- 4. Delimiter:** Use `##` strictly as the delimiter *between* parts. Do not use it at the beginning or end.
- 5. Completion Signal:** Append `<|COMPLETE|>` to the very end of the entire generated string.

Comparison Polisher Prompt (COMPARISON_POLISHER_PROMPT)

Goal

Validate and optimize **comparison-type** questions to ensure correct comparison logic, clear and natural phrasing, and sufficient background information to enhance question quality and comprehensibility.

Instructions

You are a Polisher module responsible for optimizing comparison questions. Based on the input of two entities (A and B), the attribute being compared, supporting facts, the original question-answer pair, and relevant document contexts, evaluate the quality of the question and make one of the following four decisions:

1. **PASS**: The question is valid, well-phrased, has correct comparison logic, and appropriate background information.
2. **ADJUST**: The question is basically valid but needs fine-tuning in wording, fluency, or background information.
3. **REWORKED**: The question has obvious flaws and needs structural rewriting.
4. **REJECTED**: The question has fundamental errors that cannot be fixed.

Review and modify the question based on the following key dimensions:

1. **Comparison Correctness (CRITICAL)**: - **Attribute Comparability**: Confirm that the attributes of entities A and B are indeed comparable. - **Logical Accuracy**: Verify that the comparison logic is consistent with the values provided. - **Answer Consistency**: Ensure the original answer accurately answers the question. - **Factual Support**: Check that the facts are key information extracted from the documents.
2. **Background Information Integration (IMPORTANT)**: - **Natural Integration**: Extract key background information and integrate it naturally. - **Provide Context Without Revealing Answers**: Background should provide context without revealing attribute values. - **Context Relevance**: Added background information should be relevant to the entities and attributes.
3. **Question Wording Optimization**: - **Clarity and Naturalness**: Improve wording to make it clear, fluid, and conversational. - **Direct Comparison Format**: Ensure the question explicitly asks for the result of the comparison. - **Hide Answer-Revealing Details**: Never include specific attribute values that would reveal the answer. - **Unified Question Format**: Create a single, unified question with smooth background incorporation.

Output Format

1. *If the question needs no modification:*

[PASS]

2. *If the question needs fine-tuning:*

[ADJUST]

REFINED_QUESTION: [Unified question with background]

REFINED_ANSWER: [Adjusted answer if needed]

3. *If the question needs substantial rewriting:*

[REWORKED]

REFINED_QUESTION: [Completely rewritten question]

REFINED_ANSWER: [New answer]

REFINED_FACT_A: [Corrected fact for entity A if needed]

REFINED_FACT_B: [Corrected fact for entity B if needed]

4. *If the question cannot be fixed:*

[REJECTED]

REASON: [Brief explanation of rejection reason]

Compare Question Builder Prompt (COMPARE_QUESTION_BUILDER_PROMPT)

Goal

Imagine you are comparing two documents, Document A (about Entity A) and Document B (a candidate potentially containing a related Entity B). Your task is to:

1. Identify the main subject entity within Document B (potential Entity B) and see if it's relevant to Entity A.
2. Find if there is **at least one specific, comparable attribute pair** between Entity A and the potential Entity B.
3. If a suitable comparison pair is found, **directly generate** a natural language **direct comparison question**, its **comparative answer**, and supporting **full sentence(s)**.
4. If no suitable entity or comparable attribute pair is found, indicate failure.

Instructions

1. **Analyze Inputs:** You are given:

- Primary Entity A: {**subject_entity_name**} (Type: {**subject_entity_type**})
- Document A Text: {**document_a_text**}
- Entity A's Attributes List: {**attributes_list_str_a**}
- Candidate Document B Text: {**document_b_text**}

2. **Identify Entity B and Find ONE Comparable Attribute Pair:**

- Identify the primary subject entity within Document B (Entity B).
- Check if Entity B's type is compatible for comparison with Entity A's type.
- Search for a comparable attribute pair between Entity A and Entity B.
- If found, proceed to step 3. Otherwise, proceed to step 4 (Failure).

3. **Generate DIRECT Comparison Question, COMPARATIVE Answer, and Facts:**

- Compare values to determine their precise relationship.
- Generate a **direct comparison question** that explicitly asks for the result of comparison.
- Provide a **concise comparative answer** (not just restating both values).
- Extract supporting sentences from both documents.
- Extract relevant paragraphs (50-150 words) from both documents.

4. **Indicate Failure** if no comparable pair or valid Entity B found.

Output Format Specification

1. *Success Output (If a comparable pair was found):*

PASS

entity_a: Name of Entity A (from input)

entity_b: Identified Entity B Name (from step 2)

attribute_compared: Matched Attribute Name

multi_hop_question: Generated DIRECT Comparison Question

answer: Concise COMPARATIVE Answer Text

fact_entity_a: Extracted Full Sentence(s) for Fact A

fact_entity_b: Extracted Full Sentence(s) for Fact B

relevant_paragraph_a: Complete substantive paragraph from Document A

relevant_paragraph_b: Complete substantive paragraph from Document B

2. *Failure Output:*

FAIL

Compare Query Generator Prompt (COMPARE_QUERY_GENERATOR_PROMPT)

Goal

Imagine you are an assistant helping to create interesting comparison questions that might require looking up information in different places (multi-hop). Your task is to analyze a primary entity (Entity A) and its known details. Based on this, decide the best *first step* to find another entity (Entity B) for comparison: either confidently suggest a specific Entity B and verify a *known attribute* of Entity A for it, OR generate 3 diverse search queries to explore potential candidates.

Instructions

1. **Analyze Input Context:** You are working with:

- Primary Entity A: {**subject_entity_name**} (Type: {**subject_entity_type**})
- Context about Entity A: {**document_a_text**}
- Known Attributes of Entity A: {**attributes_list_str_a**}

2. **Consider Two Paths (Choose ONE):**

Path 1: Direct Entity Recall & Focused Verification Query:

- **Think:** Based on Entity A's profile, can you confidently recall a *specific* entity (Entity B) that's relevant?
- Identify **one specific attribute** (Attribute X) *from the provided list* that would be an interesting point of comparison.
- **Condition:** Choose this path ONLY if you can confidently recall Entity B *and* select a suitable Attribute X.
- **Generate Verification Query:** Create a query to retrieve the value of that chosen attribute for Entity B.
- **Output:** Format as ("recall_focused_verify"<|>[Entity B Name]<|>[Attribute X Name]<|>[Verification Query]).

Path 2: Heuristic Search Query Generation:

- **Think:** If Path 1 isn't suitable, generate search queries to explore potential entities.
- **Generate Exactly 3 Queries:** Propose diverse search queries based on Entity A's overall profile.
- Ensure queries are concise, suitable for retrieval, and explore different angles.
- **Condition:** Choose this path if Path 1 is not suitable.
- **Output:** Format as ("search_queries"<|>Query 1<|>Query 2<|>Query 3).

3. **Output:** Return the chosen path's output string. You must choose exactly one path.

Output Format Specification

1. *Structure:* A single string containing the chosen path information.

2. *Output Parts (Choose ONE format):*

Path 1: ("recall_focused_verify"<|>Suggested Entity B Name<|>
Chosen Attribute X Name<|>Verification Query)

Path 2: ("search_queries"<|>Query 1<|>Query 2<|>Query 3)

3. *Completion Signal:* Append <|COMPLETE|> at the end.

Compare QA Quality Assessment Prompt (COMPARE_QA_QUALITY_ASSESSMENT_PROMPT)

Goal

Conduct a **rigorous and critical** evaluation of multi-hop comparison questions across multiple quality dimensions. Focus on ensuring questions require genuine cross-document reasoning **and are free from logical flaws**. A high-quality multi-hop question necessitates reasoning that flows between documents, where information from one document provides necessary context for another, making it impossible to answer using any single document in isolation.

Instructions

You are a **strict and discerning** Multi-Hop Question Answering (MHQA) expert evaluating the given question and answer across key dimensions in three categories:

1. Multi-Hop QA Rule Dimension

- **Multi-Hop Reasoning Requirement:** For comparison-type questions, determine if:

- 1) Answering requires factual information from at least two different documents
 - 2) No single document contains all necessary information about both entities being compared
- Rate "Yes" only if BOTH conditions are met, otherwise "No"

2. Linguistic Dimensions (Rate as: Very Poor, Poor, Fair, Good, Very Good)

- **Fluency:** Is the question grammatically correct, coherent, and easy to understand?

- **Clarity:** Is the question clearly and precisely expressed without ambiguity?

- **Conciseness:** Is the question concise without redundant information?

3. Task-Oriented Dimensions (Rate as: Very Poor, Poor, Fair, Good, Very Good)

- **Relevance:** Is the question relevant to the passages and asking for key information?

- **Consistency:** Is the question **completely and strictly** consistent with the passages?

- **Question Answerability:** Can the question be **unambiguously** answered based **solely** on the passages?

- **Answer-Question Consistency:** Does the answer completely and accurately address the question?

- **Information Integration:** Does the question logically integrate information from multiple documents?

- **Reasoning Path Guidance:** Does the question guide the answerer through a multi-step reasoning process?

- **Logical Sophistication:** Is the question free from logical gaps and requires multi-step thinking?

Critical Scoring Guidance:

- **Penalize Logical Flaws Heavily:** Pay close attention to Consistency, Logical Sophistication, and Information Integration.

- **Multi-Hop Requirement is Paramount:** If "No," the question fundamentally fails its purpose.

- Rating Scale Interpretation:

- **Very Poor:** Unacceptable quality with serious functional/logical errors

- **Poor:** Weak quality with obvious, major flaws requiring significant revision

- **Fair:** Acceptable quality meeting basic requirements with clear flaws (minimum adequacy only)

- **Good:** Standard good quality, well-designed without obvious flaws

- **Very Good:** Excellent quality with clever, rigorous design and deep logic

Output Format:

- Multi-Hop Reasoning Requirement: {yes/no}

- Fluency: {rating}

- Clarity: {rating}

. . .

- Reasoning Path Guidance: {rating}

- Logical Sophistication: {rating}

<|COMPLETE|>