

Reducing Predictive Feature Suppression in Resource-Constrained Contrastive Image-Caption Retrieval

Anonymous authors

Paper under double-blind review

Abstract

To train image-caption retrieval (ICR) methods, contrastive loss functions are a common choice for optimization functions. Unfortunately, contrastive ICR methods are vulnerable to predictive feature suppression. Predictive features are features that correctly indicate the similarity between a query and a candidate item. However, in the presence of multiple predictive features during training, encoder models tend to suppress redundant predictive features, since these features are not needed to learn to discriminate between positive and negative pairs. We introduce an approach to reduce predictive feature suppression for resource-constrained ICR methods: *latent target decoding* (LTD). We add an additional decoder to the contrastive ICR framework, to reconstruct the input caption in a latent space of a general-purpose sentence encoder, which prevents the image and caption encoder from suppressing predictive features. We implement the LTD objective as an optimization constraint, to ensure that the reconstruction loss is below a bound value while primarily optimizing for the contrastive loss. Importantly, LTD does not depend on additional training data or expensive (hard) negative mining strategies. Our experiments show that, unlike reconstructing the input caption in the input space, LTD reduces predictive feature suppression, measured by obtaining higher recall@k, r-precision, and nDCG scores than a contrastive ICR baseline. Moreover, we show that LTD should be implemented as an optimization constraint instead of a dual optimization objective. Finally, we show that LTD can be used with different contrastive learning losses and a wide variety of resource-constrained ICR methods.

1 Introduction

Image-caption retrieval (ICR) is the task of using an image or a caption as a query and ranking a set of candidate items in the other modality. Both the images and captions are mapped into a shared latent space by two encoders, which correspond to the two modalities. These encoders usually do not share parameters and are typically optimized with a contrastive loss function (Faghri et al., 2018; Lee et al., 2018; Li et al., 2019; Wang et al., 2019; Messina et al., 2020b; Chen et al., 2020a; Liu et al., 2020; Wang et al., 2020; Messina et al., 2020a; Jia et al., 2021; Diao et al., 2021; Yu et al., 2021). How well an ICR method generalizes beyond the specific training data depends on the features that the method has learned during training. The contrastive loss explicitly learns the similarity between positive (matching) candidates, while pushing away negative (non-matching) candidates during training. In the ideal situation, the contrastive objective optimizes the image and caption encoder such that both encoders extract all relevant information from the caption and image that is needed for matching the positive candidates during evaluation. However, it is not defined upfront what information is needed during evaluation for retrieving the correct item among a set of candidates.

Predictive feature suppression. Hermann & Lampinen (2020) show that, in the presence of two *predictive features* that redundantly predict the output label of the input data, a deep neural model preferentially represents one of the two predictive features while the other feature is suppressed. In this work, we define *predictive feature suppression* as the phenomenon of suppressing features that would be useful to correctly predict the match between a query and the positive candidate. For contrastive training tasks, the features

that are relevant for matching the query with the positive candidate (i.e, the predictive features) mainly depend on the negative candidates in the training batch. Only optimizing the contrastive InfoNCE loss does not guarantee avoidance of *shortcut features* that suppress certain (predictive) input features (Robinson et al., 2021). Especially in a resource-constrained training setup, it is likely that the majority of the input features in the caption and image are redundant for learning the similarity between matching images and captions, due to the limited number of negative samples available to contrast with. The contrastive optimization objective is easy to solve by only using a small subset of the predictive input features of the images and captions. Suppressing predictive features during training is an undesirable side-effect of contrastive representation learning in a resource-constrained training setup, since some of these features might be needed during evaluation to retrieve the matching candidate.

How to prevent predictive feature suppression. To increase the difficulty of a contrastive discrimination task, one can increase the batch size during training in order to increase the probability of having difficult in-batch negative samples (Chen et al., 2020c; Qu et al., 2021). It is, therefore, not surprising that most progress on the two widely used ICR benchmark evaluation sets, MS-COCO Captions (COCO) (Lin et al., 2014) and Flickr30k (F30k) (Young et al., 2014), recently has been made by using large-scale image-text matching training, mainly in combination with transformer network architectures (Jia et al., 2021; Yuan et al., 2021). Using more data and bigger model architectures improves performance but comes with a significant extra computational cost, both in terms of data needed for training and the number of parameters that need to be optimized.

The two benchmark datasets for ICR, the COCO and F30k datasets, are relatively small in terms of training samples compared to the training data of state-of-the-art pre-trained ICR or image-text matching methods (Jia et al., 2021; Yuan et al., 2021). When an ICR method is trained from scratch using these benchmark datasets only, for example, in a resource-constrained training setup, scaling up the size of a batch is not a feasible solution to increase performance, due to the limited data size of F30k and COCO or due to the lack of computational resources. Hence, it is important to develop algorithms that can improve the effectiveness of ICR methods in a *resource-constrained* training setup, without relying on more data and more compute to achieve this.

A method to increase the difficulty of the contrastive objective that does not rely on the size of the dataset to reduce predictive feature suppression is to directly mine *hard* negative examples for each query over the entire dataset, rather than relying on an increased batch size to include difficult negative examples. The disadvantage of hard-negative mining is that it can be computationally expensive as well (Chen et al., 2020b). Moreover, the COCO dataset contains many visually similar images (Parekh et al., 2020); when a similar image is mined as a hard-negative, it will be considered as a negative w.r.t. the query, which may create conflicting and incorrect supervision signals.

The autoencoding paradigm (Hinton & Salakhutdinov, 2006) provides an alternative solution to reduce predictive feature suppression by learning latent data representations that contain as much of the important input features as possible. Using the information bottle-neck principle, the encoder should compress the input information into a low-dimensional representation while preserving as much as possible of the input features. Combining autoencoding with contrastive learning should prevent the image and caption encoder from learning features that are only needed to solve the contrastive optimization objective. Therefore, a logical step is to add a decoder to the learning algorithm that decodes the original input from either the caption or image representation (or both). However, adding a decoder on top of the image representations, as in (Li et al., 2020a), is sub-optimal for the ICR task. The captions provided for each image are already a dense summary of the image; reconstructing every pixel in the image results in image representations that contain too much local information, which is irrelevant for the ICR task. A more natural choice would be to decode the input caption rather than the image, but adding a decoder on top of the caption representations might not result in a reduction of predictive feature suppression. Strong textual decoders can reduce a reconstruction loss by mainly relying on the learned language model (Lu et al., 2021). The input for this decoder (the latent caption representation) can mostly be ignored while correctly decoding the input sequence.

Our proposed solution. To address the disadvantages of current approaches to mitigating predictive feature suppression viz. (i) high costs (in terms of compute and data), and (ii) reconstruction of the input

caption and images in the input space, we introduce *latent target decoding* (LTD). For each caption in the training set, we generate a *latent target* representation by using a general-purpose sentence encoder. We train an image and caption encoder that can be trained in a resource-constrained setup, using a standard contrastive learning objective. Next to that, we add an extra decoder to the learning algorithm. We decode the information of the caption in a latent space of the sentence encoder. Thus, the decoder cannot rely on learning a dataset-specific language model to decode the input, and the caption representation learned by the caption encoder should contain all input features that are needed to decode the latent target. By reconstructing this latent target representation we aim to reduce predictive feature suppression by the caption encoder, which should result in representations that generalize better to the evaluation task. See Figure 1 in Section 3 for a high-level overview of our LTD method. LTD only requires an additional target representation for each caption and a simple feed-forward decoder network, and can be combined with any ICR method that uses a separate caption and image encoder to compute a global representation of the input data. LTD does *not* depend on (i) additional training data, (ii) extra manual data annotation or (hard) negative mining, or (iii) significantly more computational resources.

If we were to add LTD to the learning algorithm, the overall training objective would become a multi-task loss: a contrastive and reconstruction loss. However, multi-task losses are difficult to optimize (Malkiel & Wolf, 2021). The reconstruction loss should serve as an extra regularizer rather than the main learning objective. We also do not want the caption encoder to mainly focus on the reconstruction objective, since that can harm the contrastive utility of the representations. Therefore, we implement LTD as an optimization constraint. In this manner, we can target a specific value for that loss function. The main training objective is to minimize the contrastive loss, given the constraint that the reconstruction loss is below a certain bound value. Similar to (Rezende & Viola, 2018; van Rozendaal et al., 2020), we implement the reconstruction loss constraint using a Lagrange multiplier (Platt & Barr, 1987); the two losses are scaled automatically such that the reconstruction bound is met, while minimizing the contrastive loss.

Our main findings.

1. The proposed constrained-based LTD reduces predictive feature suppression and improves the generalizability of learned representations, as it outperforms ICR baselines that are only optimized by using a contrastive loss. We measure the reduction of predictive feature suppression by using the standard evaluation metrics for the ICR task.
2. Implementing LTD as dual loss, as opposed to an optimization constraint, does not reduce predictive feature suppression. Our analyses suggest that optimizing the reconstruction loss only until a specific bound value is met, results in better evaluation performance than minimizing the reconstruction loss as a dual loss.
3. LTD can be used in combination with different contrastive losses, for example, InfoNCE (Oord et al., 2018) and the triplet loss (Faghri et al., 2018), and it can be combined with a wide variety of ICR methods that can be optimized in a resource-constrained setup, such as VSRN (Li et al., 2019) and TERN (Messina et al., 2020b).

Below, we first cover related work, then introduce the proposed LTD method, before presenting our experimental setup and discussing the outcomes of our experiments, and concluding.

2 Related work

2.1 Image-caption retrieval

Neural architectures for ICR. We focus on ICR methods that compute a global representation for both image and caption. In general, an ICR method consists of two encoders: one to encode the image and one to encode the caption into a latent representation (Faghri et al., 2018; Li et al., 2019; Chun et al., 2021; Jia et al., 2021). Most work on ICR focuses on new network architectures to learn multi-modal feature representations. State-of-the-art results have been obtained using graph neural networks (Li et al., 2019; Wang et al., 2020; Liu et al., 2020; Diao et al., 2021) to represent visual relations in scenes as a graph, or attention mechanisms to align words in the caption with specific regions in the input image (Lee et al., 2018; Wang et al., 2019; Chen et al., 2020a; Yu et al., 2021). Li et al. (2019) combine a caption encoder-decoder with the image

encoder to add extra training signals to the learning algorithm. These methods are only trained and evaluated on the COCO and F30k datasets. Recently, there has been a shift to transformer-based (Vaswani et al., 2017) network architectures for both the image and caption encoder. Messina et al. (2020b;a) introduce a transformer-based network architecture solely trained for the ICR task. Since then, several transformer-based methods have been introduced (Lu et al., 2019; Chen et al., 2020d; Li et al., 2020b; 2021; Jia et al., 2021; Li et al., 2022); some combine the image and caption encoder into one unified architecture. These methods are all (pre-)trained on a large amount of additional training data and most are not trained for the ICR task specifically, but as general-purpose vision-text models.

Hard negative mining. Few publications have looked into the improvement of contrastive optimization for ICR methods. Faghri et al. (2018) introduce a new formulation of the triplet loss that only considers the hardest negative candidate in the training batch instead of all negative candidates, which significantly improved the evaluation scores on the ICR benchmarks. Since then, many ICR methods (Lee et al., 2018; Li et al., 2019; Wang et al., 2020; Liu et al., 2020; Messina et al., 2020b;a; Chen et al., 2020a; Diao et al., 2021; Yu et al., 2021) have used this loss function for optimization. Chen et al. (2020b) introduce an offline hard-negative mining approach for ICR in order to overcome the limitations of in-batch negative mining. Instead of mining an in-batch hard-negative, they mine additional negative candidates, for each query, over the entire training set to learn from so-called harder-to-distinguish negatives.

One-to-many problem. Chun et al. (2021) focus on the one-to-many problem in ICR. An image can be described by many captions. However, most methods in ICR learn one representation for the image, which should match with a number of different captions. They propose a probabilistic ICR method, where images and captions are represented as probability distributions in a shared latent space instead of a point representation. Although their method does not focus on contrastive optimization, it addresses predictive feature suppression by learning a distribution over features instead of a point prediction of features. Chun et al. (2021) also propose the plausible match metric, a heuristic for identifying missing positive examples by finding images that contain similar objects (i.e., plausible matches) and considering these in the evaluation.

Upshot

Unlike most previous work, we do not focus on the network architecture to improve the ICR performance. Similar to (Chun et al., 2021), we focus on small-scale learning set-ups to train an ICR method from scratch to show the strength of our method in a resource-constrained setting. Our proposed approach incorporates autoencoding into the learning algorithm in order to reconstruct the input caption to reduce predictive feature suppression.

2.2 Contrastive representation learning

Contrastive learning losses are used to learn discriminative representations of the input data that can be used to contrast positive and negative pairs of information in a latent space. These loss functions have made a big impact in representation learning, whether self-supervised (Oord et al., 2018; Hjelm et al., 2019; Chen et al., 2020c) or supervised (Radford et al., 2021; Karpukhin et al., 2020). Although ICR is a supervised contrastive learning task, some of the theoretical findings about self-supervised contrastive learning apply to supervised settings as well.

Self-supervised contrastive learning. A common approach to learn general-purpose representations in self-supervised manner, is to create two (matching) views of the same (or similar) data point(s) by applying different augmentations (Chen et al., 2020c) or by splitting the data into parts (Oord et al., 2018) (i.e., predicting the future). The two positive views are contrasted with other negative samples in the training batch. The goal is to learn encoders that are invariant under these augmentations and that can discriminate between positive and negative pairs. How well self-supervised representations generalize to different settings, after training, is often assessed using a down-stream evaluation task, such as object classification (Chen et al., 2020c) or speaker identification (Oord et al., 2018)

Some work examines data augmentation to learn strong feature representations. Good augmentations retain task-relevant information while removing task-irrelevant nuisances (Tian et al., 2020). The main purpose of

removing task-irrelevant nuisances is to prevent encoders from using this information as predictive features during training. Xiao et al. (2021) show that the features needed to learn good representations depend on the down-stream task. ICR does not depend on augmentations to generate positive and negative pairs. These pairs are given by the annotations of the benchmark datasets (Young et al., 2014; Lin et al., 2014). The difficulty of the discrimination task (and hence the learned features) mainly depends on which candidates are present in the training batch.

The generalizability of contrastive learning methods is also influenced by the number of (hard) negatives present in a training batch. In general, the larger the number of in-batch negatives, the higher the down-stream evaluation performance (Chen et al., 2020c). Some work has focused on methods to increase the number of negatives during training (He et al., 2020) or on applying hard-negative mining strategies to increase the number of hard negatives in the batch (Lindgren et al., 2021; Xiong et al., 2021). Since we are focusing on a resource-constrained setup in this work, scaling up the batch size to increase the number of (hard) negatives is not a feasible solution. Moreover, the COCO dataset contains many visually similar images (Parekh et al., 2020). Mining visually similar images as (hard) negatives will result in a suboptimal supervision signal, which makes hard-negative mining also not a feasible approach to reduce shortcut feature suppression.

Shortcut feature representations. Robinson et al. (2021) show that the contrastive InfoNCE loss (Oord et al., 2018) does not guarantee avoidance of shortcut feature representations. Shortcut feature representations are solutions that suppress predictive input features, i.e., a shortcut to discriminate between matching/non-matching candidates. The features learned by the InfoNCE loss depend on the difficulty of instance discrimination during training. If the instance discrimination task is easy to solve during training, the model will learn shortcut features. Especially in a resource-constrained ICR training setup, the contrastive objective is easy to solve, since the limited number of (hard) negative samples in the training batch, which will result in shortcuts/predictive feature suppression.

Feature suppression among competing features. Chen et al. (2021) introduce the notion of feature suppression among *competing features*. Chen et al. (2020c) show that, for example, the SimCLR method (Chen et al., 2020c) trained without the crop or color augmentation (which randomly crops or shifts the color distribution of an image), the performance on the down-stream evaluation task drops significantly. Apparently, the (color) pixel distribution of the image is a sufficient predictive feature to match two views of the same image during training. However, these features do not generalize well to a down-stream evaluation task, such as object classification. The desired predictive features of the input image (i.e., the object class and its properties) are suppressed by competing features (i.e., the color distribution of the image). Chen et al. (2021) refer to this phenomenon as *feature suppression among competing features*. Feature suppression among competing features is closely related to the work by Hermann & Lampinen (2020), who show that in the presence of multiple redundantly predictive features deep neural models prefer one of the features over the other, while the other feature is suppressed. Chen et al. (2021) add artificially generated features (i.e., MNIST digits) as an extra overlay to images. They show that the “easy” predictive features (the MNIST digits) are preferred by a deep neural encoder model over the real predictive features (i.e., the object class) when optimizing with a contrastive learning loss. Chen et al. (2021) conclude that contrastive losses rely on easy-to-detect features that solve the contrastive objective, while suppressing the remaining (partly irrelevant) information.

Predictive feature suppression is a prominent problem in resource-constrained contrastive ICR. Captions often describe multiple aspects of a scene. However, in a resource-constrained contrastive setup, only one (or a few) of the aspects that are described in the caption is likely to be sufficient to match with the positive candidate (i.e., the image) during training due to the limited number of negative candidate in the training batch. To mitigate this problem of predictive feature suppression for resource-constrained contrastive ICR, we need an extra optimization objective that is independent of the negative samples in the training batch.

Autoencoding. An approach to reduce predictive feature suppression is autoencoding (Hinton & Salakhutdinov, 2006). Autoencoding can be combined with a contrastive learning loss and reduces predictive feature suppression without depending on sampling (hard) negative candidates. To learn high-quality text sequence embeddings for the dense passage retrieval task, Lu et al. (2021) add a weak decoder on top of a document




Figure 1: Overview of LTD. The baseline (left) consists of a general image-caption retrieval framework with an image and caption encoder. The encoders are trained by using the contrastive InfoNCE loss. To reduce predictive feature suppression we add latent target decoding to the baseline ICR method (right). This extra decoder decodes the information of the input caption in a latent space of a general-purpose sentence encoder. The decoder is not used during inference, which we indicate by the dashed line around the model $h_\omega(\cdot)$.

encoder to reconstruct the original document. To make image encoders more robust against shortcut features, Li et al. (2020a) add a decoder on top of the image encoder to decode the input image.

Upshot

To reduce predictive feature suppression in a resource-constrained ICR task, we introduce *latent target decoding* (LTD). LTD reduces predictive feature suppression, without focusing on the difficulty of the contrastive discrimination task. LTD requires neither a large number of negative samples nor hard negative mining strategies. Unlike other methods that reconstruct the input data, we reconstruct the input information of the caption in a latent space instead of the input space.

3 Method

We start with preliminaries and then discuss the InfoNCE contrastive loss and why autoencoding captions in the input space is not a solution to reduce predictive feature suppression. Finally, we introduce latent target decoding (LTD) to reduce predictive feature suppression for resource-constrained ICR. In Figure 1 we provide an overview of LTD.

3.1 Preliminaries and notation

3.1.1 Notation

We follow the notation introduced in previous work (Chen et al., 2020c; Brown et al., 2020). For the ICR task we use a multi-modal dataset $\mathcal{D} = \{(\mathbf{x}_I^i, \mathbf{x}_{C1}^i, \dots, \mathbf{x}_{Ck}^i), \dots\}_{i=1}^N$. This dataset consists of N image-caption tuples. Each tuple contains one image \mathbf{x}_I^i and k captions \mathbf{x}_{Cj}^i , where $1 \leq j \leq k$, that describe the scene depicted in the image. At each training iteration, we randomly sample a batch \mathcal{B} of image-caption pairs from \mathcal{D} . Per image, one of the k captions is sampled per training iteration; together, this image and caption form a positive (or matching) image-caption pair. Each caption is used once during a training epoch.

The image and caption encoder are trained for two tasks: *image-to-text* (i2t) and *text-to-image* (t2i) retrieval. Thus, each image and caption in \mathcal{B} is used as a query \mathbf{q} . We denote the matching candidate in the other modality as \mathbf{v}^+ . All other candidates in \mathcal{B} , in the other modality, are considered as negative candidates \mathbf{v}^- . The set of all negative candidates for query \mathbf{q} in batch \mathcal{B} is \mathcal{S}_q^- , where $\mathbf{v}^- \in \mathcal{S}_q^-$.

3.1.2 Contrastive baseline model

The baseline (BL) ICR framework in this work consists of two encoders. The image encoder $f_\theta(\cdot)$ takes an image \mathbf{x}_I^i as input and encodes this image into a latent representation $\mathbf{z}_I^i := f_\theta(\mathbf{x}_I^i)$. The caption encoder $g_\phi(\cdot)$ takes a caption as input and encodes this caption into a latent representation $\mathbf{z}_{Cj}^i := g_\phi(\mathbf{x}_{Cj}^i)$. The vectors \mathbf{z}_{Cj}^i and \mathbf{z}_I^i have the same dimensionality and are normalized on the unit sphere. The encoders are only optimized by minimizing a contrastive learning loss \mathcal{L}_{con} . Our goal is not to obtain the highest possible evaluation performance, but to show the strength of LTD on resource-constrained training setups.

3.2 Contrastive loss

To train the image and caption encoder, we use the InfoNCE contrastive loss (Oord et al., 2018; Chen et al., 2020c). The InfoNCE loss is a popular loss function for self-supervised representation learning (Chen et al., 2020c; He et al., 2020) and multi-modal representation learning (Radford et al., 2021; Yuan et al., 2021; Jia et al., 2021). To keep the notation simple and intuitive, we use \mathbf{q} and \mathbf{v} for the latent representations computed by the caption and image encoder and not \mathbf{z}_{Cj} and \mathbf{z}_I . The InfoNCE loss is defined as follows:

$$\mathcal{L}_{con} = \frac{1}{|\mathcal{B}|} \sum_{(\mathbf{q}, \mathbf{v}^+) \in \mathcal{B}} -\log \frac{\exp(\mathbf{q}^T \mathbf{v}^+ / \tau)}{\exp(\mathbf{q}^T \mathbf{v}^+ / \tau) + \sum_{\mathbf{v}^- \in \mathcal{S}_q^-} \exp(\mathbf{q}^T \mathbf{v}^- / \tau)}. \quad (1)$$

\mathcal{L}_{con} in Eq. 1 is minimized when, given a query \mathbf{q} , the cosine similarity score with the positive candidate \mathbf{v}^+ is high (i.e., ≈ 1), while the similarity scores with the negative candidates $\mathbf{v}^- \in \mathcal{S}_q^-$ in the batch are as low as possible; τ serves as a temperature parameter. The main objective of a contrastive learning loss for the ICR task is to learn data representations that can be used to discriminate between similar and dissimilar image-caption pairs. However, there is no constraint that enforces the encoders to learn representations that contain all available input information to make this discrimination, which is what we add.

3.2.1 Gradient w.r.t. the input representations

To show some important properties of the InfoNCE loss, we provide the derivative of $-\mathcal{L}_{con}$ w.r.t. the input in Eq. 2 (Chen et al., 2020c):

$$Z(\mathbf{q}, \mathbf{v}) = \frac{\exp(\mathbf{q}^T \mathbf{v} / \tau)}{\exp(\mathbf{q}^T \mathbf{v} / \tau) + \sum_{\mathbf{v}^- \in \mathcal{S}_q^-} \exp(\mathbf{q}^T \mathbf{v}^- / \tau)} \quad (2a)$$

$$\frac{\partial \mathcal{L}_{con}}{\partial \mathbf{q}} \tau = (1 - Z(\mathbf{q}, \mathbf{v}^+)) \mathbf{v}^+ - \sum_{\mathbf{v}^- \in \mathcal{S}_q^-} Z(\mathbf{q}, \mathbf{v}^-) \mathbf{v}^- \quad (2b)$$

$$\frac{\partial \mathcal{L}_{con}}{\partial \mathbf{v}^+} \tau = (1 - Z(\mathbf{q}, \mathbf{v}^+)) \mathbf{q} \quad (2c)$$

$$\frac{\partial \mathcal{L}_{con}}{\partial \mathbf{v}^-} \tau = -Z(\mathbf{q}, \mathbf{v}^-) \mathbf{q}. \quad (2d)$$

$Z(\mathbf{q}, \mathbf{v})$ returns the similarity score of candidate \mathbf{v} w.r.t. the query \mathbf{q} , normalized by the sum of similarity scores of all candidates in the batch \mathcal{B} . Based on Eq. 2, we infer the following properties:

1. The update w.r.t. the query \mathbf{q} (Eq. 2b), is a weighted sum over the positive candidate \mathbf{v}^+ and all negatives $\mathbf{v}^- \in \mathcal{S}_q^-$. The query representation \mathbf{q} will be pulled closer to \mathbf{v}^+ , while being pushed away from all $\mathbf{v}^- \in \mathcal{S}_q^-$. The weight value of each candidate, $Z(\mathbf{q}, \mathbf{v})$ (Eq. 2a), depends on the similarity score with the query.
2. \mathbf{v}^+ (Eq. 2c) will be pulled closer to the query representation (and the other way around).
3. All negatives \mathbf{v}^- (Eq. 2d) will be pushed away from the query representation (and the other way around).

Without contrasting with negative candidates, the encoders will learn a trivial solution where latent representations collapse to a single point in the latent space (Jing et al., 2021). This means that the learned representation mainly depends on contrasting with negative candidates during training. If the representations

\mathbf{v} only contain a subset of the predictive input features (which still minimize the contrastive training objective), the query representation \mathbf{q} (in the other modality) will be updated to match/mismatch these representations. The contrastive InfoNCE objective itself does not guarantee that all the predictive features in the input data are learned (Robinson et al., 2021) and mainly relies on easy-to-detect features to contrast between positive and negative pairs (Chen et al., 2021).

Importantly, the query and candidate representations are in different modalities and therefore generated by different encoders. Hence, the update of the query and candidate representations is based on *fixed* representations in the other modality (e.g., the caption encoder can only try to match/not match with the representations of the image encoder and vice versa). By adding a constraint on the representations of one of the two modalities, the other modality encoder will follow automatically. Therefore, in order to prevent predictive feature suppression for the caption modality in a resource-constraint ICR setting, we add a constraint to the learning algorithm that forces the caption representation to be projected into the latent space of a general-purpose sentence encoder.

3.3 Autoencoding reconstruction objective

Autoencoding (Hinton & Salakhutdinov, 2006) is a natural choice for learning latent data representations that contain most of the important input features without relying on hard negative samples. To reconstruct the input caption from the encoded latent representation $\mathbf{z}_{\mathcal{C}_j}^i$, we introduce a decoder network $h_\omega(\cdot)$:

$$\tilde{\mathbf{x}}_{\mathcal{C}_j}^i := h_\omega(\mathbf{z}_{\mathcal{C}_j}^i). \quad (3)$$

The decoder network $h_\omega(\cdot)$ takes the latent caption representation as input and outputs a reconstruction of the input caption $\tilde{\mathbf{x}}_{\mathcal{C}_j}^i$. To decode the input sequence from the latent representation, this latent representation should be a dense representation of the entire input sequence. The reconstruction loss, \mathcal{L}_{rec} , of a sequence of tokens, x_i, \dots, x_n of length n , is the negative log-likelihood of the input data:

$$\mathcal{L}_{rec} = - \sum_{t=1}^n \log p(x_t | x_{t-1:1}, \mathbf{z}_{\mathcal{C}_j}^i). \quad (4)$$

Based on Eq. 4 it is clear that each predicted token x_t in the sequence is conditioned on: (i) the latent caption representation $\mathbf{z}_{\mathcal{C}_j}^i$, and (ii) the already predicted sequence $x_{t-1:1}$.

As discussed in Section 1, a strong decoder will mainly rely on the learned language model and language patterns to decode the input sequence (Lu et al., 2021). This implies that the input sequence can be decoded correctly while mainly ignoring $\mathbf{z}_{\mathcal{C}_j}^i$, especially when t is large. Therefore, decoding the caption sequence in the input space is not guaranteed to reduce predictive feature suppression.

3.4 Latent target decoding

In Section 3.2 we argued why the contrastive InfoNCE loss is prone to predictive feature suppression, and in Section 3.3 we discussed why decoding a caption in the input space will not prevent predictive feature suppression. In this section, we introduce *latent target decoding* (LTD). LTD decodes the semantics of the input caption in a latent space of a general-purpose sentence encoder to reduce predictive feature suppression, which can be used in combination with a contrastive loss. LTD addresses the issues of decoding the caption in the input space. See Figure 1 for a high-level overview of LTD for ICR.

For each caption $\mathbf{x}_{\mathcal{C}_j}^i$ in the training dataset we generate $\mathbf{y}_{\mathcal{C}_j}^i$, a *latent target representation*. The vector $\mathbf{y}_{\mathcal{C}_j}^i$ is a dense vector representation. We assume that this vector contains all the (semantic) information of the caption, captured by a general-purpose language encoder. We use our decoding network h_ω to decode $\mathbf{y}_{\mathcal{C}_j}^i$ instead of the input caption. By reconstructing a vector representation of the caption instead of the original input sequence, the reconstruction is not conditioned on the already predicted sequence of tokens. The latent target decoder assumes conditional independence of each feature in the latent target. Therefore, the decoder cannot rely on conditional (language model) patterns in the data to reconstruct the input semantics. This implies that we force the decoder to rely completely on $\mathbf{z}_{\mathcal{C}_j}^i$ to decode the latent target representation.

3.4.1 Target decoding network

To decode $\mathbf{y}_{\mathcal{C}_j}^i$ we use a three layer feed-forward decoder network:

$$h_\omega(\mathbf{z}_{\mathcal{C}_j}^i) = \mathbf{W}^{(3)} \sigma \left(\mathbf{W}^{(2)} \sigma \left(\mathbf{W}^{(1)} \mathbf{z}_{\mathcal{C}_j}^i \right) \right), \quad (5)$$

where σ is the ReLU non-linearity; h_ω takes the latent caption representation $\mathbf{z}_{\mathcal{C}_j}^i$ as input and maps it to a reconstruction of the latent target representation $\tilde{\mathbf{y}}_{\mathcal{C}_j}^i$.

3.4.2 Loss function

To train h_ω , we use the cosine distance between $\tilde{\mathbf{y}}_{\mathcal{C}_j}^i$ and $\mathbf{y}_{\mathcal{C}_j}^i$ as *reconstruction loss* \mathcal{L}_{rec} :

$$\mathcal{L}_{rec} = 1 - \frac{\tilde{\mathbf{y}}_{\mathcal{C}_j}^i \cdot \mathbf{y}_{\mathcal{C}_j}^i}{\|\tilde{\mathbf{y}}_{\mathcal{C}_j}^i\| \cdot \|\mathbf{y}_{\mathcal{C}_j}^i\|}. \quad (6)$$

Minimizing the cosine distance is equivalent to minimizing the mean squared error of two vectors normalized on the unit sphere (Chen & He, 2021; Grill et al., 2020). By introducing an extra loss criterion, the overall training objective becomes a dual optimization problem. The *dual loss* \mathcal{L}_{dual} is defined as follows:

$$\mathcal{L}_{dual} = \mathcal{L}_{con} + \beta \mathcal{L}_{rec}, \quad (7)$$

where β serves as a balancing parameter to scale the two losses.

3.4.3 Constraint-based optimization

By adding LTD to the learning framework, we introduce an extra loss component \mathcal{L}_{rec} . To effectively minimize \mathcal{L}_{dual} , we have to find the right value for the balancing parameter β in Eq. 7. This may require a considerable amount of manual tuning, and often one specific value for β does not generalize to different training settings. Besides that, \mathcal{L}_{rec} is not the main training objective for the ICR tasks. The main reason we add \mathcal{L}_{rec} to the learning algorithm is to reduce predictive feature suppression caused by solely optimizing the contrastive loss. We therefore argue that implementing LTD as an optimization *constraint* (Rezende & Viola, 2018; van Rozendaal et al., 2020), as opposed to an optimization *objective*, might be more effective. Our goal, then, is to minimize the contrastive loss \mathcal{L}_{con} given the constraint that the reconstruction loss is lower than or equal to a certain bound value η :

$$\min_{\theta, \psi, \omega} \mathcal{L}_{con} \text{ subject to } \mathcal{L}_{rec} \leq \eta. \quad (8)$$

We can implement this optimization constraint in combination with gradient descent by using the method of Lagrange multipliers:

$$\max_{\lambda} \min_{\theta, \psi, \omega} \mathcal{L}_{lag} = \mathcal{L}_{con} + \lambda \left(\frac{\mathcal{L}_{rec}}{\eta} - 1 \right). \quad (9)$$

The optimization objective is to minimize \mathcal{L}_{lag} w.r.t. the model parameters θ, ψ, ω , while maximizing \mathcal{L}_{rec} w.r.t. to the multiplier λ . The multiplier λ is tuned automatically by using stochastic gradient ascent with momentum. By optimizing λ with stochastic gradient ascent, the two losses will be balanced automatically during training such that the reconstruction constraint is met, while the contrastive loss is minimized by gradient descent.

3.4.4 Choice of latent target representation

To generate the latent target $\mathbf{y}_{\mathcal{C}_j}$, we use a Sentence-BERT transformer model (Reimers & Gurevych, 2019; Song et al., 2020).¹ Sentence-BERT is a general-purpose sentence encoder that is trained on a large amount of data to capture the semantic input information. Thus, we expect these embeddings to be more general than those we learn for the resource-constrained contrastive ICR task, which makes them a suitable choice for the latent target representations $\mathbf{y}_{\mathcal{C}_j}$.

¹<https://huggingface.co/sentence-transformers/all-mpnet-base-v2>

3.5 LTD vs. teacher-student framework

LTD is somewhat similar to a teacher-student framework used with knowledge distillation (Hinton et al., 2015). Indeed, the target generator can be seen as a teacher network and the caption encoder in combination with the target decoder as a student network. However, in contrast with knowledge distillation, the goal of LTD is *not* to closely mimic a teacher network. Instead, the goal is to learn caption representations that can be used for multi-modal contrastive-based retrieval while extracting as much of the textual semantic input information of the caption as possible.

4 Experimental setup

We design experiments aimed at showing: (i) a reduction of predictive feature suppression by using LTD, with a focus on the ICR task; (ii) the advantages of LTD over reconstructing the caption in the input space; (iii) the benefit of constraint-based optimization of LTD over dual loss optimization; and (iv) the generalizability of LTD to different contrastive losses and resource-constrained ICR methods that use different encoder network architectures. To facilitate reproducibility and further research of our work, we include the code with our submission.²

4.1 Datasets

For training and evaluating our ICR method, we use the two common ICR benchmark datasets: MS-COCO Captions (COCO) (Lin et al., 2014) and Flickr30k (F30k) (Young et al., 2014). The F30k dataset contains 31,000 image-caption tuples. We use the train, validate and test split from (Karpathy & Fei-Fei, 2015), with 29,000 images for training, 1,000 for validation, and 1,000 for testing. COCO consists of 123,287 image-caption tuples. We use the train, validate and test split from (Karpathy & Fei-Fei, 2015); we do not use the 1k test setup. Both F30k and COCO come with $k = 5$ captions per image.

We also use the CrissCrossed Captions (CxC) dataset, which extends the COCO validation and test set with additional annotations of similar captions and images (Parekh et al., 2020), so as to evaluate whether LTD improves the evaluation scores by retrieving semantically similar candidates.

4.2 Implementation details

Unless otherwise specified, we use the following architectures for the target decoder, image encoder, and caption encoder. We use similar network architectures for the image and caption encoder as the ones used in (Chun et al., 2021), which are simple network architectures that can be trained using a limited amount of training data.

Image encoder. For the image encoder, we use a pre-trained ResNet-50 (He et al., 2016) network. We apply average pooling on the last convolutional layer followed by a projection head to map the image feature vector into a shared multi-modal latent space; the projection head has two feed-forward layers and a ReLU non-linearity.

Caption encoder. For the caption encoder, we use a bi-directional, single-layer, GRU network (Cho et al., 2014). We use pre-trained GloVe embeddings (Pennington et al., 2014) as word embeddings. We use a similar projection head as for the image encoder (which does not share parameters) to map the caption embedding into the shared latent space.

Target decoding network. For the target decoding network, we use a three-layer feed-forward network as in Eq. 5. To generate the latent target representations, we use the HuggingFace *all-MiniLM-L6-v2* Sentence-BERT implementation. The target decoding network is trained together with the image and caption encoder. The target decoding network is *not* used during evaluation.

²<https://anonymous.4open.science/r/tmlr-predictive-feature-suppresion-icr/README.md>

Input decoding network. We compare *latent* target decoding (LTD) with *input* target decoding (ITD), which reconstructs the input caption in the input space (i.e., the input tokens). For ITD, we use a single-layer GRU (Cho et al., 2014) decoder that reconstructs the input tokens in the caption (as explained in Section 3.3). We train the word embeddings for ITD from scratch. ITD is optimized with the negative log-likelihood loss (Eq. 4).

Generalizability to different network architectures. LTD is a general method that can be combined with any global representation contrastive ICR method. To show that LTD works in combination with different network architectures, we apply LTD with multiple ICR methods that can be trained in a resource-constrained setup. To cover a wide spectrum of network architectures, we choose two methods that use different network architectures for the image and caption encoder.

VSRN. The Visual Semantic Reasoning Network (VSRN) (Li et al., 2019) consists of an image and caption encoder that both compute a global representation of each input modality. The caption encoder consists of a single directed GRU, similar to the caption encoder used in (Faghri et al., 2018). The image encoder takes a set of pre-computed regions of interest as input generated by a ResNet-101 (He et al., 2016) backbone, pre-trained on Visual Genome (Krishna et al., 2017). This set of pre-computed visual features is considered a fully connected graph of regions in the input image. To perform reasoning on the graph of visual features, a multi-layer Graph Convolutional Networks (Kipf & Welling, 2017) is used. Finally, to obtain one global representation of the entire image, a GRU is used to aggregate the regions of interest into one single representation. We use the same learning rate schedule as in (Li et al., 2019). We modify the original VSRN model on two points: (i) We use the same caption encoder as described in Section 4.2 instead of the *single* directed GRU used for the original VSRN model and use a hidden dimensional of 1024 instead of 2048 for the caption and image representations. The goal of this work is not to show which specific network architectures perform best for the ICR task, but to show the generalizability of LTD in combination with different encoder networks. (ii) The original VSRN model also comes with an additional caption decoder that decodes the input caption from the visual features. In this work, we investigate the reduction of predictive feature suppression for the general ICR framework, consisting of two encoders optimized by using a contrastive loss. If we would add LTD to the original VSRN method, we would have two reconstruction objectives and a contrastive loss. The main reason we use VSRN is for the use of Graph Convolution Networks in the image encoder to show the generalizability of LTD in combination with different encoder networks. Therefore, we remove this caption decoder from the learning algorithm.

TERN. Transformer Reasoning Network (TERN) (Messina et al., 2020b) is a transformer-based ICR method that is solely trained and evaluated on the COCO dataset. TERN consists of a pre-trained BERT (Devlin et al., 2018) caption encoder. The image encoder takes a set of pre-computed regions of interest as input (similar to VSRN) and consists of a stack of four transformer layers. The pre-computed features are only available for the COCO dataset. Next, both the image and caption features are pushed through a stack of shared transformer layers. Although the weights of the last part of the caption and image encoder are shared, there is no (cross) attention between the two modalities; the representations of the images and captions are still computed independently. The image and caption CLS token is used as a global representation of both the image and the caption. We use the same learning rate schedule, dropout rate, and data augmentations as in (Messina et al., 2020b).

In this work, we use ICR methods that are trained from scratch on the F30k and COCO dataset. That does not imply that some of the weights of our encoders are not initialized with pre-trained parameters. However, we only use pre-trained weights that are trained on a uni-modal task(s), and not for image-text matching specifically.

Training. We use the same number of epochs, batch size, and learning rate schedule as in (Chun et al., 2021). The Lagrange multiplier is initialized with a value of 1, bounded between 0 and 100, and is optimized by stochastic gradient ascent with a fixed learning rate of $5e^{-3}$ and a momentum (to prevent λ from fluctuating too much) and dampening value of $\alpha = 0.9$. When we use \mathcal{L}_{dual} , we set β to 1. For the InfoNCE loss, we use a temperature value τ of 0.05. Evaluation scores of ICR methods tend to differ depending on the random seed used during training (Rao et al., 2022); to improve robustness, we apply stochastic weight averaging (SWA) (Izmailov et al., 2018); we take the average of 5 checkpoints, stored during the last 10% of the training

iterations each epoch. For the reconstruction constraint bound η , we try for all experiments several values, $\eta \in \{0.05, 0.1, 0.15, 0.2, 0.25, 0.3\}$. When we apply ITD we use $\eta \in \{0.5, 1, 2, 3, 4, 5, 6\}$. All results are based on the best-performing value of η .

4.3 Evaluation metrics

To measure the reduction of predictive feature suppression, we evaluate how well the learned encoders generalize to the ICR evaluation task. The more predictive features the encoders learn to capture, the better these encoders are able to retrieve the correct candidate given a query. The standard evaluation metric for ICR is recall@ k metric, with $k = \{1, 5, 10\}$. During training, we evaluate the model after each training epoch on the validation set. Similar to (Faghri et al., 2018; Lee et al., 2018; Li et al., 2019; Chen et al., 2020a; Chun et al., 2021), we select the model with the highest score on the validation set (using the sum of all recall@ k scores as a metric) for evaluation on the test set.

Recall@ k . For ICR, recall@ k is implemented as the fraction of how many times a matching candidate is present in the top- k ranking (Karpathy & Fei-Fei, 2015; Parekh et al., 2020). For the t2i task, there is only one matching image per query caption. For the i2t task, there are 5 matching captions per image. Only the highest-ranked caption per query is used for calculating the recall scores. When using the CxC annotations, for both i2t and t2i, we take the highest-ranked candidate.

R-precision. When extending the COCO dataset with the CxC annotations, we have one or more matching candidates per query for both i2t and t2i. Like (Chun et al., 2021), we also use the r-precision metric (R-P) for evaluation; it measures the precision for a top- r ranking, where r is the number of matching candidates given a query.

nDCG. The standard evaluation metric for the ICR task, recall@ k , mainly measures if the positive candidate is present in the top k of the ranking. However, this does not provide much insight into the overall quality of the ranking. To address the limitations of only using recall@ k , Messina et al. (2020b) start using nDCG as an additional evaluation metric for t2i retrieval. However, for t2i retrieval there is only one positive image per query caption. To generate more positive images per caption query, images that have captions with a high overlap with the query caption, are also considered positive. As similarity measurements between the captions, ROUGE-L (Lin, 2004) and SPICE (Anderson et al., 2016) are used. There are multiple re-annotations of COCO available that provide multiple matching images per caption query; see, for example, (Parekh et al., 2020). However, these re-annotations are not used by (Messina et al., 2020b) to compute the nDCG scores. To keep the evaluation consistent, we use the same relevance labels as used in (Messina et al., 2020b). The nDCG relevance labels are only available for COCO and not for F30k.

5 Results

In Section 5.1, we compare a contrastive ICR baseline with the same baseline combined with LTD. Next, in Section 5.2 we ask if similar results can be achieved with ITD as with LTD. In Section 5.3, we then investigate the role of the optimization constraint and compare constrained-based LTD with LTD optimized as a dual loss. Finally, in Section 5.4, we ask whether LTD can be used in combination with a different contrastive loss function, and in Section 5.5 we show that LTD can be combined with a wide variety of resource-constrained ICR methods.

5.1 Contrastive ICR baseline vs. baseline + LTD

In Table 1 we compare the contrastive ICR baseline, which is optimized by using the contrastive loss \mathcal{L}_{con} defined in Eq. 1, with the baseline combined with LTD. Based on Table 1, row 1.1, 1.4, 2.1.1, 2.4.1, and 2.4.2, 2.4.2, we observe that LTD optimized as a dual loss (\mathcal{L}_{dual}) with $\beta = 1$ does not convincingly (or only with a small margin) outperform the baseline ICR method, which is optimized solely in a contrastive manner, in terms of recall@ k , nDCG, and r-precision for both datasets and both i2t and t2i.

#	Method	Loss	i2t				t2i					
			R@k			R-P	R@k			R-P	nDCG	
			1	5	10		1	5	10		ROUGE-L	SPICE
F30k												
1.1	BL	\mathcal{L}_{con}	47.4	75.9	84.8	0.34	33.9	65.2	76.6	-	-	-
1.2	BL + ITD	$\mathcal{L}_{dual}, \beta=1$	45.7	74.0	84.4	0.33	33.7	65.1	75.8	-	-	-
1.3	BL + ITD	$\mathcal{L}_{lag}, \eta=6$	36.6	66.8	76.5	0.28	27.8	59.1	71.0	-	-	-
1.4	BL + LTD	$\mathcal{L}_{dual}, \beta=1$	46.1	75.3	84.1	0.34	34.0	65.9	77.4	-	-	-
1.5	BL + LTD	$\mathcal{L}_{lag}, \eta=0.2$	49.6	78.7	86.4	0.37	36.7	68.4	79.3	-	-	-
COCO												
2.1.1	BL	\mathcal{L}_{con}	33.7	64.4	76.6	0.24	24.2	53.5	67.0	-	0.6487	0.5729
2.2.1	BL + ITD	$\mathcal{L}_{dual}, \beta=1$	32.7	64.4	76.3	0.24	24.2	53.8	67.6	-	0.6496	0.5733
2.3.1	BL + ITD	$\mathcal{L}_{lag}, \eta=4$	28.4	59.2	72.2	0.22	22.0	50.4	64.5	-	0.6424	0.5638
2.4.1	BL + LTD	$\mathcal{L}_{dual}, \beta=1$	34.2	64.7	76.6	0.25	25.0	54.3	67.9	-	0.6510	0.5756
2.5.1	BL + LTD	$\mathcal{L}_{lag}, \eta=0.15$	36.0	66.5	78.1	0.26	26.2	56.2	69.4	-	0.6531	0.5786
CxC												
2.1.2	BL	\mathcal{L}_{con}	36.1	68.1	80.2	0.22	26.7	57.6	71.0	0.23	-	-
2.2.2	BL + ITD	$\mathcal{L}_{dual}, \beta=1$	35.0	68.0	79.7	0.22	26.6	58.0	71.6	0.23	-	-
2.3.2	BL + ITD	$\mathcal{L}_{lag}, \eta=4$	31.0	62.9	75.8	0.20	24.6	54.8	68.9	0.21	-	-
2.4.2	BL + LTD	$\mathcal{L}_{dual}, \beta=1$	36.6	68.1	79.9	0.23	27.6	58.8	72.0	0.24	-	-
2.5.2	BL + LTD	$\mathcal{L}_{lag}, \eta=0.15$	38.4	70.4	81.5	0.24	28.9	60.4	73.3	0.25	-	-

Table 1: Recall@k, nDCG, and r-precision (R-P) evaluation scores for the F30k and COCO datasets (including the CxC annotations). We evaluate three loss functions \mathcal{L}_{con} , \mathcal{L}_{dual} and \mathcal{L}_{lag} . We use three methods, the contrastive ICR baseline (BL), BL + input target decoding (ITD), and BL + latent target decoding (LTD). Boldface indicates the highest value for each evaluation metric per dataset. ‘-’ indicates that it is not possible to compute the evaluation score for that dataset/experiment since the annotations are not available.

In contrast, when we implement LTD as an optimization constraint, by using \mathcal{L}_{lag} , row 1.5, 2.1.5, and 2.2.5, we observe that LTD consistently outperforms the baseline ICR methods on both F30k and COCO for both tasks (i2t and t2i) with a large margin. An increase in recall also comes with an increase in the r-precision scores and nDCG scores. Hence, features learned by constrained-based LTD perform better on the evaluation task, which is an indication of the reduction of predictive feature suppression.

5.2 Latent Target Decoding vs. Input Target Decoding

As argued in Section 3.3, decoding the caption in the input space will probably not result in a reduction of predictive feature suppression due to overfitting of the learned language model. To empirically show this, we also implemented a decoder that decodes tokens of the input caption (ITD) to reduce predictive feature suppression (see Section 4.2 for details). Based on row 1.2, 2.1.2, and 2.2.2 in Table 1, we conclude that implementing ITD as a dual loss does not result in improved recall@k scores, for most values of k, compared to the contrastive baseline. Surprisingly, when we implement ITD as an optimization constraint (with $\eta = 4$ for F30k and $\eta = 6$ for COCO, other values of η do not yield improvements) the evaluation scores are even lower (row 1.3, 2.1.3 and 2.2.3) than when implemented as a dual loss. We conclude that: (i) ITD does not reduce predictive feature suppression for ICR, and (ii) implementing ITD as an optimization constraint even hurts performance.




Figure 2: Overview of constrained based optimization on the evaluation metric and the optimization objectives. We train \mathcal{L}_{lag} with four different values of $\eta \in \{0.05, 0.10, 0.15, 0.20, 0.25\}$. All training steps are to the power of $1e5$.

5.3 The role of the optimization constraint

What is the role of the optimization constraint when minimizing \mathcal{L}_{rec} and what is the effect on the evaluation scores compared to using \mathcal{L}_{dual} ? In Figure 2b we plot the trajectory of λ for different values of $\eta \in \{0.05, 0.1, 0.15, 0.2, 0.25\}$ during training on the COCO dataset. We also provide (i) the trajectory of the evaluation score (recall sum) over the validation set during training (Figure 2a), (ii) the trajectory of the reconstruction loss for different values of η and when optimized without using a constraint (\mathcal{L}_{dual}) (Figure 2c), and (iii) the trajectory of the contrastive loss for different values of η (Figure 2d). Based on Figure 2 we observe:

1. λ increases until the optimization constraint is met (i.e., the bound η). The closer the reconstruction loss is to η , the slower the increase of λ . When the reconstruction constraint is met, λ decreases to 0 (Figure 2b).
2. λ is positive again when the reconstruction loss becomes higher than the bound η (Figure 2b, purple line).
3. The reconstruction loss converges to the value of η (Figure 2c). However, it is not possible to meet every value of η . E.g., $\eta = 0.05$ is too low to achieve for the model.
4. A lower reconstruction loss does not necessarily result in higher evaluation scores (Figure 2a). E.g., the recall sum is higher for $\eta = 0.15$ than for $\eta = 0.1$ or $\eta = 0.05$.

#	Method	Loss	i2t			t2i		
			R@1	R@5	R@10	R@1	R@5	R@10
F30k								
3.1.1	BL	\mathcal{L}_{con}	12.8	33.2	45.4	11.1	32.6	46.6
3.1.2	BL + LTD	$\mathcal{L}_{dual}, \beta = 1$	17.1	42.7	56.4	13.1	40.5	55.7
3.1.3	BL + LTD	$\mathcal{L}_{lag}, \eta = 0.2$	54.7	81.5	88.3	40.8	71.3	80.6
COCO								
3.2.1	BL	\mathcal{L}_{con}	37.1	67.1	78.2	27.8	56.6	69.3
3.2.2	BL + LTD	$\mathcal{L}_{dual}, \beta = 1$	37.4	67.8	79.1	28.2	57.2	70.5
3.2.3	BL + LTD	$\mathcal{L}_{lag}, \eta = 0.2$	39.1	69.3	80.6	29.6	59.4	72.2

Table 2: Recall@ k evaluation scores for the F30k and COCO datasets. For experiments 3.*, we use the triplet loss with in-batch hard-negative mining, as defined in (Faghri et al., 2018) instead of the InfoNCE loss (Oord et al., 2018) for \mathcal{L}_{con} . Boldface indicates the highest value for each evaluation metric per dataset.

5. The value and the development of the contrastive loss do not depend much on the value of the reconstruction loss (Figure 2d). E.g., a model optimized with \mathcal{L}_{con} has the same contrastive loss trajectory as a model that is optimized with \mathcal{L}_{lag} and \mathcal{L}_{dual} . Hence, the contrastive loss on its own does not provide a good indication of the performance on the evaluation task. Similar trajectories of the contrastive loss result in different evaluation scores (hence different learned representations).

When we implement LTD as a dual loss, there is always a gradient from the reconstruction loss w.r.t. the parameters of the caption encoder, until the reconstruction loss is 0. This is not the case when we implement LTD as a reconstruction constraint. When the constraint is met λ drops to zero and there is no gradient anymore from the reconstruction loss. We can conclude that a constant gradient from the reconstruction loss does not improve the learned representations of the caption encoder in terms of evaluation scores. The evaluation scores are higher when there is only a gradient until a certain reconstruction bound η is met.

5.4 Generalizability w.r.t. contrastive loss

In Section 3.2 we argue that the InfoNCE loss is prone to predictive feature suppression. A popular choice of contrastive loss function for ICR methods is the triplet loss with in-batch hard-negative mining (Faghri et al., 2018). The triplet loss with in-batch hard-negative mining is a special case of the InfoNCE loss, where the number of positives and negatives are each one (Khosla et al., 2020). Therefore, our line of reasoning in Section 3.2 holds for the triplet loss too.

To show the strength and generalizability of LTD to other contrastive losses, we run the same experiments as in Section 5.1 (only for LTD not for ITD), with the triplet loss instead of the InfoNCE loss as \mathcal{L}_{con} . To prevent the triplet loss from collapsing to the trivial solution, we added a batch normalization layer after the projection head, for both the image and caption encoder; we use a margin value of $\alpha = 0.2$ (Faghri et al., 2018; Li et al., 2019; Messina et al., 2020b). Based on Table 1, we can observe that the highest recall@ k scores also come with the highest r-precision and nDCG scores. Since the main goal of this experiment is to show that LTD can be used in combination with different contrastive losses we, therefore, only evaluate for recall@ k .

Table 2 provides the recall@ k scores for the F30k and COCO datasets. For both F30k and COCO the triplet loss with constraint-based LTD (see rows 3.1.3 and 3.2.3) results in higher evaluation scores than the InfoNCE loss with constraint-based LTD (see Table 1, rows 1.5 and 2.5). Our goal here is not to identify the best contrastive loss for ICR or LTD, but to show the generalizability of LTD to different contrastive losses. Moreover, using the triplet loss as \mathcal{L}_{con} (see row 3.2.1), results in expected evaluation scores on the COCO dataset (given the reproducibility work in (Bleeker & de Rijke, 2022)). Surprisingly, however, the evaluation scores for the F30k dataset while using the triplet loss as \mathcal{L}_{con} (see row 3.1.1) are lower than expected (when

#	Method	Loss	i2t			t2i				
			R@k			R@k			nDCG	
			1	5	10	1	5	10	ROUGE-L	SPICE
VSRN										
F30k										
5.1.1	BL	\mathcal{L}_{con}	60.3	85.6	90.8	44.9	74.0	83.3	-	-
5.1.2	BL + LTD	$\mathcal{L}_{dual}, \beta = 1$	59.6	86.6	91.6	44.3	74.7	83.5	-	-
5.1.3	BL + LTD	$\mathcal{L}_{lag}, \eta = 0.25$	61.9	86.8	92.1	45.3	76.4	84.4	-	-
COCO										
5.2.1	BL	\mathcal{L}_{con}	47.0	76.9	87.0	34.5	65.7	78.1	0.6779	0.6080
5.2.2	BL + LTD	$\mathcal{L}_{dual}, \beta = 1$	45.9	77.8	87.6	34.6	66.2	78.3	0.6791	0.6088
5.2.3	BL + LTD	$\mathcal{L}_{lag}, \eta = 0.15$	47.6	79.0	87.8	35.0	66.7	78.9	0.6797	0.6112
TERN										
COCO										
5.3.1	BL	\mathcal{L}_{con}	41.2	72.6	83.6	31.0	61.9	74.7	0.6648	0.5926
5.3.2	BL + LTD	$\mathcal{L}_{dual}, \beta = 1$	42.3	74.3	84.4	31.4	62.7	75.4	0.6684	0.5993
5.3.3	BL + LTD	$\mathcal{L}_{lag}, \eta = 0.2$	44.1	74.8	85.7	33.6	64.6	76.9	0.6727	0.6059

Table 3: Recall@k and nDCG evaluation scores for the F30k and COCO datasets using the VSRN and TERN network architectures. Boldface indicates the highest value for each evaluation metric per dataset. ‘-’ indicates that it is not possible to compute the evaluation score for that dataset/experiment since the annotations are not available.

compared to Table 1, row 1.1). It is unclear why we observe these low evaluation scores for the F30k dataset when only using the triplet loss as \mathcal{L}_{con} . In contrast, we observe that constraint-based LTD in combination with the triplet loss drastically improves the evaluation scores for the F30k dataset, which shows the strength of constraint-based LTD for improving ICR evaluation scores and also making the triplet loss more robust to predictive feature suppression and feature collapsing.

5.5 Generalizability w.r.t. network architectures

In this section, we consider whether LTD can be used in combination with different resource-constrained ICR methods that use different network architectures. To answer this question we use LTD in combination with the VSRN and TERN methods.

In line with the observations in Table 1, we observe in Table 3 that for both VSRN and TERN: (i) constrained-based LTD outperforms the contrastive baseline, and (ii) constrained-based LTD results in a stronger performance improvement than implementing LTD as a dual loss.

In line with the results in (Messina et al., 2020b), the VSRN baseline outperforms the TERN baseline in terms of Recall@k. However, the difference in nDCG scores between the two models is relatively small. Although constrained-based LTD outperforms both the baseline and LTD implemented as a dual loss, improvements gained by using LTD in combination with VSRN are less convincing than for TERN.

The most consistent improvement in evaluation scores is obtained by combining LTD with TERN, which is a fully transformer-based ICR method. This is a substantially different architecture from that in Table 1 and VSRN, and such transformer network architectures are the most prominent network architectures these days for multi-modal tasks (Radford et al., 2021; Chen et al., 2020d; Lu et al., 2019; Yuan et al., 2021). When only a limited amount of training data is available and one wants to make use of (partly) pre-trained transformer

networks for multi-modal contrastive learning, constrained-based LTD can help to significantly improve the evaluation scores for ICR.

Furthermore, TERN makes use of a pre-trained BERT (Devlin et al., 2018) model as a caption encoder. BERT is a general-purpose text encoder pre-trained on text only. An open question is still why to train a caption encoder, while we use a (frozen) general-purpose sentence encoder to generate the latent targets for LTD; why not use the target decoder directly as a caption encoder? The results in Table 3 show that fine-tuning a general-purpose language encoder (i.e., BERT) with a contrastive loss as caption encoder results in lower evaluation scores than fine-tuning the caption encoder in combination with constrained-based LTD. This shows that LTD helps to extract features (i.e., not suppressing these features) from the input data that are relevant for the ICR task, that are not captured by either the pre-trained BERT model or by only using the contrastive optimization objective.

6 Conclusion

We have presented latent target decoding, a novel approach to reduce predictive feature suppression for contrastive resource-constrained ICR methods. Instead of reconstructing the captions in the input space, LTD reduces predictive feature suppression by reconstructing the input caption in the latent space of a general-purpose sentence encoder. By reconstructing the input caption, it is more difficult for the image and caption encoder to suppress predictive features that are not needed to solve the contrastive optimization objective.

Main findings. Our results show that constraint-based LTD obtains higher evaluation scores than both a contrastive ICR baseline and LTD implemented as a dual loss. This implies that we are able to reduce predictive feature suppression (and hence improve evaluation performance) by using constraint-based LTD, which does not require additional image-text training data or hard-negative mining strategies. Furthermore, we show that constraint-based LTD consistently results in a bigger improvement in evaluation scores than implementing LTD as a dual loss. These results suggest that, instead of simply minimizing both the contrastive and reconstruction loss, better evaluation scores can be obtained by only optimizing the reconstruction loss until a certain bound value η is met. Finally, we show that constraint-based LTD can be combined with different contrastive learning losses and a wide variety of resource-constrained ICR methods.

Implications. The result of our work shows that in a resource-constrained setup the evaluation performances of contrastive ICR methods can be substantially improved by using constrained-based LTD, without relying on more training data or hard-negative mining strategies. We, therefore, argue that, in a resource-constrained setup, LTD should be part of the standard ICR framework to mitigate the problem of predictive feature suppression. Furthermore, we argue that when one uses an additional reconstruction objective to reduce predictive feature suppression, this objective should be considered to be implemented as an optimization constraint instead of a dual loss.

Limitations. In this work, we use a general-purpose sentence encoder to generate our latent target representation \mathbf{y}_{ck} . However, we need to assume that this latent target representation contains the relevant information of the input caption. Furthermore, the availability of a general-purpose sentence encoder is not always guaranteed (e.g., when working with low-resource languages).

For the ICR task, the predictive features are the features needed to retrieve the positive item from a set of candidates. We, therefore, measure the reduction of predictive feature suppression by using the standard ranking evaluation metrics, such as recall@ k , r-precision, and nDCG. However, we do not explicitly know which features are causing the observed improvement in the evaluation scores by using LTD.

Future work. We have several directions for future work. First, we plan to examine if the choice of different target generators will result in different ICR evaluation scores. Moreover, we also want to look into generating latent target representations without relying on a pre-trained sentence encoder.

A second promising direction for future work is analyses on the exact role of the optimization constraint. In Section 5.3 we examine the role of the optimization constraint when training the image and caption encoder.

When the optimization constraint η is met, λ (i.e., the balancing parameter of the two losses) drops to zero and the reconstruction loss no longer provides a gradient (Figure 2b). Although λ is (close to) zero for the majority of the training after the constraint is met, the evaluation scores on the validation set remain higher than when optimizing with \mathcal{L}_{dual} , with $\beta = 1$ (Figure 2a). This suggests that a constant gradient from the reconstruction loss does not benefit the training process, which is the case if LTD is implemented as a dual loss. We plan future research into the role of the optimization constraint, by trying constrained-based optimization for other multi-task optimization problems.

Finally, we suggest working on methods to measure which features are responsible for the gained improvement in evaluation performance. A logical choice would be to use feature attribution methods. However, different feature attribution methods tend to disagree with each other, for both RNN and transformer-based models (Neely et al., 2021). Therefore, the choice of feature attribution method will influence the analyses on which predictive features are better captured by using LTD. To gain more insight into which features are captured by the learned encoders, we would recommend developing task-specific feature attribution methods that can measure the reduction of predictive feature suppression directly.

References

- Peter Anderson, Basura Fernando, Mark Johnson, and Stephen Gould. SPICE: semantic propositional image caption evaluation. In *Computer Vision - ECCV 2016 - 14th European Conference, Amsterdam, The Netherlands, October 11-14, 2016, Proceedings, Part V*, 2016.
- Maurits Bleeker and Maarten de Rijke. Do lessons from metric learning generalize to image-caption retrieval? In *Advances in Information Retrieval - 44th European Conference on IR Research, ECIR 2022, Stavanger, Norway, April 10-14, 2022, Proceedings, Part I*, 2022.
- Andrew Brown, Weidi Xie, Vicky Kalogeiton, and Andrew Zisserman. Smooth-AP: Smoothing the path towards large-scale image retrieval. In *Computer Vision - ECCV 2020 - 16th European Conference, Glasgow, UK, August 23-28, 2020, Proceedings, Part IX*, 2020.
- Hui Chen, Guiguang Ding, Xudong Liu, Zijia Lin, Ji Liu, and Jungong Han. IMRAM: iterative matching with recurrent attention memory for cross-modal image-text retrieval. In *2020 IEEE/CVF Conference on Computer Vision and Pattern Recognition, CVPR 2020, Seattle, WA, USA, June 13-19, 2020*, 2020a.
- Tianlang Chen, Jiajun Deng, and Jiebo Luo. Adaptive offline quintuplet loss for image-text matching. In *Computer Vision - ECCV 2020 - 16th European Conference, Glasgow, UK, August 23-28, 2020, Proceedings, Part XIII*, 2020b.
- Ting Chen, Simon Kornblith, Mohammad Norouzi, and Geoffrey E. Hinton. A simple framework for contrastive learning of visual representations. In *Proceedings of the 37th International Conference on Machine Learning, ICML 2020, 13-18 July 2020, Virtual Event*, 2020c.
- Ting Chen, Calvin Luo, and Lala Li. Intriguing properties of contrastive losses. In *Advances in Neural Information Processing Systems 34: Annual Conference on Neural Information Processing Systems 2021, NeurIPS 2021, December 6-14, 2021, virtual*, 2021.
- Xinlei Chen and Kaiming He. Exploring simple siamese representation learning. In *IEEE Conference on Computer Vision and Pattern Recognition, CVPR 2021, virtual, June 19-25, 2021*, 2021.
- Yen-Chun Chen, Linjie Li, Licheng Yu, Ahmed El Kholy, Faisal Ahmed, Zhe Gan, Yu Cheng, and Jingjing Liu. UNITER: universal image-text representation learning. In *Computer Vision - ECCV 2020 - 16th European Conference, Glasgow, UK, August 23-28, 2020, Proceedings, Part XXX*, 2020d.
- Kyunghyun Cho, Bart van Merriënboer, Dzmitry Bahdanau, and Yoshua Bengio. On the properties of neural machine translation: Encoder-decoder approaches. In *Proceedings of SSST@EMNLP 2014, Eighth Workshop on Syntax, Semantics and Structure in Statistical Translation, Doha, Qatar, 25 October 2014*, 2014.

- Sanghyuk Chun, Seong Joon Oh, Rafael Sampaio de Rezende, Yannis Kalantidis, and Diane Larlus. Probabilistic embeddings for cross-modal retrieval. In *IEEE Conference on Computer Vision and Pattern Recognition, CVPR 2021, virtual, June 19-25, 2021*, 2021.
- Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. BERT: pre-training of deep bidirectional transformers for language understanding. In *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, NAACL-HLT 2019, Minneapolis, MN, USA, June 2-7, 2019, Volume 1 (Long and Short Papers)*, 2018.
- Haiwen Diao, Ying Zhang, Lin Ma, and Huchuan Lu. Similarity reasoning and filtration for image-text matching. In *Thirty-Fifth AAAI Conference on Artificial Intelligence, AAAI 2021, Thirty-Third Conference on Innovative Applications of Artificial Intelligence, IAAI 2021, The Eleventh Symposium on Educational Advances in Artificial Intelligence, EAAI 2021, Virtual Event, February 2-9, 2021*, 2021.
- Fartash Faghri, David J. Fleet, Jamie Ryan Kiros, and Sanja Fidler. VSE++: improving visual-semantic embeddings with hard negatives. In *British Machine Vision Conference 2018, BMVC 2018, Newcastle, UK, September 3-6, 2018*, 2018.
- Jean-Bastien Grill, Florian Strub, Florent Alché, Corentin Tallec, Pierre H. Richemond, Elena Buchatskaya, Carl Doersch, Bernardo Ávila Pires, Zhaohan Guo, Mohammad Gheshlaghi Azar, Bilal Piot, Koray Kavukcuoglu, Rémi Munos, and Michal Valko. Bootstrap your own latent - A new approach to self-supervised learning. In *Advances in Neural Information Processing Systems 33: Annual Conference on Neural Information Processing Systems 2020, NeurIPS 2020, December 6-12, 2020, virtual*, 2020.
- Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *2016 IEEE Conference on Computer Vision and Pattern Recognition, CVPR 2016, Las Vegas, NV, USA, June 27-30, 2016*, 2016.
- Kaiming He, Haoqi Fan, Yuxin Wu, Saining Xie, and Ross B. Girshick. Momentum contrast for unsupervised visual representation learning. In *2020 IEEE/CVF Conference on Computer Vision and Pattern Recognition, CVPR 2020, Seattle, WA, USA, June 13-19, 2020*, 2020.
- Katherine L. Hermann and Andrew K. Lampinen. What shapes feature representations? exploring datasets, architectures, and training. In *Advances in Neural Information Processing Systems 33: Annual Conference on Neural Information Processing Systems 2020, NeurIPS 2020, December 6-12, 2020, virtual*, 2020.
- Geoffrey E Hinton and Ruslan R Salakhutdinov. Reducing the dimensionality of data with neural networks. *Science*, 2006.
- Geoffrey E. Hinton, Oriol Vinyals, and Jeffrey Dean. Distilling the knowledge in a neural network. *arXiv preprint arXiv:1503.02531*, 2015.
- R. Devon Hjelm, Alex Fedorov, Samuel Lavoie-Marchildon, Karan Grewal, Philip Bachman, Adam Trischler, and Yoshua Bengio. Learning deep representations by mutual information estimation and maximization. In *7th International Conference on Learning Representations, ICLR 2019, New Orleans, LA, USA, May 6-9, 2019*, 2019.
- Pavel Izmailov, Dmitrii Podoprikin, Timur Garipov, Dmitry P. Vetrov, and Andrew Gordon Wilson. Averaging weights leads to wider optima and better generalization. In *Proceedings of the Thirty-Fourth Conference on Uncertainty in Artificial Intelligence, UAI 2018, Monterey, California, USA, August 6-10, 2018*, 2018.
- Chao Jia, Yinfei Yang, Ye Xia, Yi-Ting Chen, Zarana Parekh, Hieu Pham, Quoc V. Le, Yun-Hsuan Sung, Zhen Li, and Tom Duerig. Scaling up visual and vision-language representation learning with noisy text supervision. In *Proceedings of the 38th International Conference on Machine Learning, ICML 2021, 18-24 July 2021, Virtual Event*, 2021.

- Li Jing, Pascal Vincent, Yann LeCun, and Yuandong Tian. Understanding dimensional collapse in contrastive self-supervised learning. In *The Tenth International Conference on Learning Representations, ICLR 2022, Virtual Event, April 25-29, 2022*, 2021.
- Andrej Karpathy and Li Fei-Fei. Deep visual-semantic alignments for generating image descriptions. In *IEEE Conference on Computer Vision and Pattern Recognition, CVPR 2015, Boston, MA, USA, June 7-12, 2015*, 2015.
- Vladimir Karpukhin, Barlas Oguz, Sewon Min, Patrick S. H. Lewis, Ledell Wu, Sergey Edunov, Danqi Chen, and Wen-tau Yih. Dense passage retrieval for open-domain question answering. In *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing, EMNLP 2020, Online, November 16-20, 2020*, 2020.
- Prannay Khosla, Piotr Teterwak, Chen Wang, Aaron Sarna, Yonglong Tian, Phillip Isola, Aaron Maschinot, Ce Liu, and Dilip Krishnan. Supervised contrastive learning. In *Advances in Neural Information Processing Systems 33: Annual Conference on Neural Information Processing Systems 2020, NeurIPS 2020, December 6-12, 2020, virtual*, 2020.
- Thomas N. Kipf and Max Welling. Semi-supervised classification with graph convolutional networks. In *5th International Conference on Learning Representations, ICLR 2017, Toulon, France, April 24-26, 2017, Conference Track Proceedings*, 2017.
- Ranjay Krishna, Yuke Zhu, Oliver Groth, Justin Johnson, Kenji Hata, Joshua Kravitz, Stephanie Chen, Yannis Kalantidis, Li-Jia Li, David A. Shamma, Michael S. Bernstein, and Li Fei-Fei. Visual genome: Connecting language and vision using crowdsourced dense image annotations. *International Journal of Computer Vision*, 2017.
- Kuang-Huei Lee, Xi Chen, Gang Hua, Houdong Hu, and Xiaodong He. Stacked cross attention for image-text matching. In *Computer Vision - ECCV 2018 - 15th European Conference, Munich, Germany, September 8-14, 2018, Proceedings, Part IV*, 2018.
- Junnan Li, Ramprasaath R. Selvaraju, Akhilesh Deepak Gotmare, Shafiq R. Joty, Caiming Xiong, and Steven C. H. Hoi. Align before fuse: Vision and language representation learning with momentum distillation. In *Advances in Neural Information Processing Systems 34: Annual Conference on Neural Information Processing Systems 2021, NeurIPS 2021, December 6-14, 2021, virtual*, 2021.
- Junnan Li, Dongxu Li, Caiming Xiong, and Steven C. H. Hoi. BLIP: bootstrapping language-image pre-training for unified vision-language understanding and generation. In *International Conference on Machine Learning, ICML 2022, 17-23 July 2022, Baltimore, Maryland, USA, 2022*.
- Kunpeng Li, Yulun Zhang, Kai Li, Yuanyuan Li, and Yun Fu. Visual semantic reasoning for image-text matching. In *2019 IEEE/CVF International Conference on Computer Vision, ICCV 2019, Seoul, Korea (South), October 27 - November 2, 2019*, 2019.
- Tianhong Li, Lijie Fan, Yuan Yuan, Hao He, Yonglong Tian, Rogerio Feris, Piotr Indyk, and Dina Katabi. Making contrastive learning robust to shortcuts. *arXiv preprint arXiv:2012.09962*, 2020a.
- Xiujun Li, Xi Yin, Chunyuan Li, Pengchuan Zhang, Xiaowei Hu, Lei Zhang, Lijuan Wang, Houdong Hu, Li Dong, Furu Wei, Yejin Choi, and Jianfeng Gao. Oscar: Object-semantics aligned pre-training for vision-language tasks. In *Computer Vision - ECCV 2020 - 16th European Conference, Glasgow, UK, August 23-28, 2020, Proceedings, Part XXX*, 2020b.
- Chin-Yew Lin. Rouge: A package for automatic evaluation of summaries. In *Text summarization branches out*, 2004.
- Tsung-Yi Lin, Michael Maire, Serge Belongie, James Hays, Pietro Perona, Deva Ramanan, Piotr Dollár, and C Lawrence Zitnick. Microsoft COCO: Common objects in context. In *Computer Vision - ECCV 2014 - 13th European Conference, Zurich, Switzerland, September 6-12, 2014, Proceedings, Part V*, 2014.

- Erik Lindgren, Sashank J. Reddi, Ruiqi Guo, and Sanjiv Kumar. Efficient training of retrieval models using negative cache. In *Advances in Neural Information Processing Systems 34: Annual Conference on Neural Information Processing Systems 2021, NeurIPS 2021, December 6-14, 2021, virtual*, 2021.
- Chunxiao Liu, Zhendong Mao, Tianzhu Zhang, Hongtao Xie, Bin Wang, and Yongdong Zhang. Graph structured network for image-text matching. In *2020 IEEE/CVF Conference on Computer Vision and Pattern Recognition, CVPR 2020, Seattle, WA, USA, June 13-19, 2020*, 2020.
- Jiasen Lu, Dhruv Batra, Devi Parikh, and Stefan Lee. Vilbert: Pretraining task-agnostic visiolinguistic representations for vision-and-language tasks. In *Advances in Neural Information Processing Systems 32: Annual Conference on Neural Information Processing Systems 2019, NeurIPS 2019, December 8-14, 2019, Vancouver, BC, Canada*, 2019.
- Shuqi Lu, Di He, Chenyan Xiong, Guolin Ke, Waleed Malik, Zhicheng Dou, Paul Bennett, Tie-Ya Liu, and Arnold Overwijk. Less is more: Pre-training a strong siamese encoder using a weak decoder. In *Proceedings of the 2021 Conference on Empirical Methods in Natural Language Processing*, 2021.
- Itzik Malkiel and Lior Wolf. Mtadam: Automatic balancing of multiple training loss terms. In *Proceedings of the 2021 Conference on Empirical Methods in Natural Language Processing, EMNLP 2021, Virtual Event / Punta Cana, Dominican Republic, 7-11 November, 2021*, 2021.
- Nicola Messina, Giuseppe Amato, Andrea Esuli, Fabrizio Falchi, Claudio Gennaro, and Stéphane Marchand-Maillet. Fine-grained visual textual alignment for cross-modal retrieval using transformer encoders. *ACM Trans. Multim. Comput. Commun. Appl.*, 2020a.
- Nicola Messina, Fabrizio Falchi, Andrea Esuli, and Giuseppe Amato. Transformer reasoning network for image-text matching and retrieval. In *25th International Conference on Pattern Recognition, ICPR 2020, Virtual Event / Milan, Italy, January 10-15, 2021*, 2020b.
- Michael Neely, Stefan F. Schouten, Maurits Bleeker, and Ana Lucic. Order in the court: Explainable AI methods prone to disagreement. *arXiv preprint arXiv:2105.03287*, 2021.
- Aaron van den Oord, Yazhe Li, and Oriol Vinyals. Representation learning with contrastive predictive coding. *arXiv preprint arXiv:1807.03748*, 2018.
- Zarana Parekh, Jason Baldridge, Daniel Cer, Austin Waters, and Yinfei Yang. Crisscrossed captions: Extended intramodal and intermodal semantic similarity judgments for ms-coco. In *Proceedings of the 16th Conference of the European Chapter of the Association for Computational Linguistics: Main Volume, EACL 2021, Online, April 19 - 23, 2021*, 2020.
- Jeffrey Pennington, Richard Socher, and Christopher D. Manning. Glove: Global vectors for word representation. In *Proceedings of the 2014 Conference on Empirical Methods in Natural Language Processing, EMNLP 2014, October 25-29, 2014, Doha, Qatar, A meeting of SIGDAT, a Special Interest Group of the ACL*, 2014.
- John C. Platt and Alan H. Barr. Constrained differential optimization. In *Neural Information Processing Systems, Denver, Colorado, USA, 1987*, 1987.
- Yingqi Qu, Yuchen Ding, Jing Liu, Kai Liu, Ruiyang Ren, Wayne Xin Zhao, Daxiang Dong, Hua Wu, and Haifeng Wang. Rocketqa: An optimized training approach to dense passage retrieval for open-domain question answering. In *Proceedings of the 2021 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, NAACL-HLT 2021, Online, June 6-11, 2021*, 2021.
- Alec Radford, Jong Wook Kim, Chris Hallacy, Aditya Ramesh, Gabriel Goh, Sandhini Agarwal, Girish Sastry, Amanda Askell, Pamela Mishkin, Jack Clark, Gretchen Krueger, and Ilya Sutskever. Learning transferable visual models from natural language supervision. In *Proceedings of the 38th International Conference on Machine Learning, ICML 2021, 18-24 July 2021, Virtual Event*, 2021.

- Jun Rao, Fei Wang, Liang Ding, Shuhan Qi, Yibing Zhan, Weifeng Liu, and Dacheng Tao. Where does the performance improvement come from?-a reproducibility concern about image-text retrieval. In *SIGIR '22: The 45th International ACM SIGIR Conference on Research and Development in Information Retrieval, Madrid, Spain, July 11 - 15, 2022*, 2022.
- Nils Reimers and Iryna Gurevych. Sentence-BERT: Sentence embeddings using siamese bert-networks. In *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing, EMNLP-IJCNLP 2019, Hong Kong, China, November 3-7, 2019*, 2019.
- Danilo J. Rezende and Fabio Viola. Generalized ELBO with constrained optimization, GECO. In *Workshop on Bayesian Deep Learning, NeurIPS*, 2018.
- Joshua Robinson, Li Sun, Ke Yu, Kayhan Batmanghelich, Stefanie Jegelka, and Suvrit Sra. Can contrastive learning avoid shortcut solutions? In *Advances in Neural Information Processing Systems 34: Annual Conference on Neural Information Processing Systems 2021, NeurIPS 2021, December 6-14, 2021, virtual*, 2021.
- Kaitao Song, Xu Tan, Tao Qin, Jianfeng Lu, and Tie-Yan Liu. Mpnet: Masked and permuted pre-training for language understanding. In *Advances in Neural Information Processing Systems 33: Annual Conference on Neural Information Processing Systems 2020, NeurIPS 2020, December 6-12, 2020, virtual*, 2020.
- Yonglong Tian, Chen Sun, Ben Poole, Dilip Krishnan, Cordelia Schmid, and Phillip Isola. What makes for good views for contrastive learning? In *Advances in Neural Information Processing Systems 33: Annual Conference on Neural Information Processing Systems 2020, NeurIPS 2020, December 6-12, 2020, virtual*, 2020.
- Ties van Rozendaal, Guillaume Sautière, and Taco S. Cohen. Lossy compression with distortion constrained optimization. In *2020 IEEE/CVF Conference on Computer Vision and Pattern Recognition, CVPR Workshops 2020, Seattle, WA, USA, June 14-19, 2020*, 2020.
- Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N. Gomez, Lukasz Kaiser, and Illia Polosukhin. Attention is all you need. In *Advances in Neural Information Processing Systems 30: Annual Conference on Neural Information Processing Systems 2017, December 4-9, 2017, Long Beach, CA, USA*, 2017.
- Sijin Wang, Ruiping Wang, Ziwei Yao, Shiguang Shan, and Xilin Chen. Cross-modal scene graph matching for relationship-aware image-text retrieval. In *IEEE Winter Conference on Applications of Computer Vision, WACV 2020, Snowmass Village, CO, USA, March 1-5, 2020*, 2020.
- Zihao Wang, Xihui Liu, Hongsheng Li, Lu Sheng, Junjie Yan, Xiaogang Wang, and Jing Shao. CAMP: cross-modal adaptive message passing for text-image retrieval. In *2019 IEEE/CVF International Conference on Computer Vision, ICCV 2019, Seoul, Korea (South), October 27 - November 2, 2019*, 2019.
- Tete Xiao, Xiaolong Wang, Alexei A. Efros, and Trevor Darrell. What should not be contrastive in contrastive learning. In *9th International Conference on Learning Representations, ICLR 2021, Virtual Event, Austria, May 3-7, 2021*, 2021.
- Lee Xiong, Chenyan Xiong, Ye Li, Kwok-Fung Tang, Jialin Liu, Paul N. Bennett, Junaid Ahmed, and Arnold Overwijk. Approximate nearest neighbor negative contrastive learning for dense text retrieval. In *9th International Conference on Learning Representations, ICLR 2021, Virtual Event, Austria, May 3-7, 2021*, 2021.
- Peter Young, Alice Lai, Micah Hodosh, and Julia Hockenmaier. From image descriptions to visual denotations: New similarity metrics for semantic inference over event descriptions. *Transactions of the Association for Computational Linguistics*, 2014.

- Tan Yu, Yi Yang, Yi Li, Lin Liu, Hongliang Fei, and Ping Li. Heterogeneous attention network for effective and efficient cross-modal retrieval. In *SIGIR '21: The 44th International ACM SIGIR Conference on Research and Development in Information Retrieval, Virtual Event, Canada, July 11-15, 2021*, 2021.
- Lu Yuan, Dongdong Chen, Yi-Ling Chen, Noel Codella, Xiyang Dai, Jianfeng Gao, Houdong Hu, Xuedong Huang, Boxin Li, Chunyuan Li, Ce Liu, Mengchen Liu, Zicheng Liu, Yumao Lu, Yu Shi, Lijuan Wang, Jianfeng Wang, Bin Xiao, Zhen Xiao, Jianwei Yang, Michael Zeng, Luwei Zhou, and Pengchuan Zhang. Florence: A new foundation model for computer vision. *arXiv preprint arXiv:2111.11432*, 2021.