

FEA-Bench: A Benchmark for Evaluating Repository-Level Code Generation for Feature Implementation

Anonymous ACL submission

Abstract

Implementing new features in repository-level codebases is a crucial application of code generation models. However, current benchmarks lack a dedicated evaluation framework for this capability. To fill this gap, we introduce FEA-Bench, a benchmark designed to assess the ability of large language models (LLMs) to perform incremental development within code repositories. We collect pull requests from 83 GitHub repositories and use rule-based and intent-based filtering to construct task instances focused on new feature development. Each task instance containing code changes is paired with relevant unit test files to ensure that the solution can be verified. The feature implementation requires LLMs to simultaneously possess code completion capabilities for new components and code editing abilities for other relevant parts in the code repository, providing a more comprehensive evaluation method of LLMs' automated software engineering capabilities. Experimental results show that LLMs perform significantly worse in the FEA-Bench, highlighting considerable challenges in such repository-level incremental code development.

1 Introduction

The remarkable text generation capabilities of large language models (LLMs) (Achiam et al., 2023) have extended their impact into the domain of code generation (Xu et al., 2022), which has led to the emergence of developer assistants such as Copilot, Cursor, Devin, etc. An important research topic to evaluate the effectiveness of LLMs in generating code across diverse scenarios. Many of the existing benchmarks focus on evaluating standalone programming problems, such as HumanEval, MBPP, and LiveCodeBench (Chen et al., 2021; Austin et al., 2021; Jain et al., 2024). These benchmarks offer little insight into the challenges developers face in real-world projects, where codebases are composed of multiple interconnected files. In such




Figure 1: The proposed FEA-Bench aims to evaluate incremental repository development, while SWE-bench (Jimenez et al., 2024) focuses on repairing issues.

projects, modifications in one part of the code often necessitate corresponding edits elsewhere. This type of collaborative, large-scale development is referred to as repository-level code development.

In the realm of repository-level code generation, much of the current evaluation effort is centered around code completion (Li et al., 2024b; Yang et al., 2024a). Code completion refers to generating correct code snippets at specified locations within a given code context. However, this task is inherently limited—it typically targets localized generation and does not account for broader implications beyond the scope of completion.

Recent advancements in the capabilities of LLMs have expanded their potential role from merely suggesting code snippets to managing the full lifecycle of repository development. A prominent benchmark in this domain is SWE-bench (Jimenez et al., 2024), which evaluates LLMs on resolving issues, primarily focusing on bug fixes within repositories. In practice, as shown in Figure 1, a more critical aspect of software engineering is the launch of new features, which often entails introducing new functions or even entire files into the repository. The continuous implementation of new features drives software growth and is a key focus of automated software engineering. We define such tasks as repository-level incremental code development. In this work, to bridge the

gap in benchmarks for this domain, we construct a dataset derived from pull requests in GitHub repositories that specifically focus on adding new components, with the overarching goal of implementing new features. Each task instance in our dataset is paired with its corresponding unit test files, culminating in the creation of the **Feature Implementation Benchmark (FEA-Bench)**, which comprises 1,401 task instances sourced from 83 diverse GitHub repositories.

Statistically, our dataset exhibits characteristics that significantly differ from the bug-fix-oriented SWE-bench. Task instances in FEA-Bench require the implementation of new functions and classes in Python and involve substantially longer code generation compared to SWE-Bench. Experimental results demonstrate that current LLMs perform poorly on the proposed benchmark. According to our execution-based metrics, the best-performing LLM, DeepSeek-R1, successfully resolves only about 10% of the task instances. The key contributions of this paper are as follows:

- We introduce the task of repository-level incremental code development, addressing a critical challenge in real-world software engineering where the continuous implementation of new features is essential for sustaining software growth.
- We construct the first benchmark to evaluate repository-level incremental code development. By employing parsing and other filtering methods, we constructed a dataset composed of feature implementation tasks, offering execution-based evaluation.
- Using an automated pipeline, we scale the test data to include 83 diverse code repositories, ensuring high diversity. We will publicly release our data collection and evaluation codebase, allowing FEA-Bench to be continuously updated and expanded.

2 Related Work

2.1 Code Large Language Models

Large language models (LLMs) have revolutionized software engineering by enabling code generation, debugging, and translation capabilities (Pan et al., 2024; Li et al., 2023a; Joshi et al., 2023; Shi et al., 2024). Large-scale pre-trained LLMs such as GPT-4 (Achiam et al., 2023), CodeLlama

(Roziere et al., 2023), DeepSeek-Coder (Guo et al., 2024; Zhu et al., 2024), and Qwen2.5-Coder (Hui et al., 2024) have demonstrated proficiency in generating functional code across multiple programming languages. Recent advancements also include instruction-tuned models like Starcoder (Li et al., 2023b), WizardCoder (Luo et al., 2023), WaveCoder (Yu et al., 2024b), Magicoder (Wei et al., 2024) and EpiCoder (Wang et al., 2025). With these advancements, code LLMs are poised to further revolutionize how developers interact with code, promising increased efficiency in software creation. Additionally, the integration of agents has further enhanced the performance of LLMs in software engineering tasks (Yang et al., 2024b; Xia et al., 2024; Zhang et al., 2024). In this paper, we further evaluate the performance of current LLMs in the incremental code development scenarios at the repository level. This investigation aims to drive the research on code LLMs toward addressing more intricate software engineering challenges, thereby advancing the capabilities of these models in handling sophisticated development tasks.

2.2 Code Generation Benchmarks

Recent code generation benchmarks, such as HumanEval (Chen et al., 2021) and MBPP (Austin et al., 2021), have primarily focused on synthesizing standalone functions or scripts from natural language, while subsequent efforts like APPS (Hendrycks et al., 2021), EvalPlus (Liu et al., 2023a), CoderEval (Yu et al., 2024a), ClassEval (Du et al., 2023), BigCodeBench (Zhuo et al., 2024), and FullStackBench (Liu et al., 2024b) have expanded evaluation to more complex scenarios. However, these benchmarks largely overlook the repository-level challenges of real-world software development, a gap addressed by recent works (Bairi et al., 2024; Zhang et al., 2023). Because of the wild applications of auto code completion tools like Github Copilot (Dakhel et al., 2023), most repository-level code generation benchmarks aim to evaluate the code completion capabilities of LLMs (Liu et al., 2023b). Repository-level code completion aims to generate code for incomplete code snippets within a repository (Wang et al., 2024). Benchmarks such as DevEval (Li et al., 2024b), EvoCodeBench (Li et al., 2024a), CodevBench (Pan et al., 2024), and ExecRepoBench (Yang et al., 2024a) evaluate this capability. However, code completion data constructed by removing a single line or function body can suffer from

future context leakage issues (Zheng et al., 2024).

In practice, autonomous development of a code repository should include all edits to the code, rather than simply completing the specified code under perfect context. SWE-bench (Jimenez et al., 2024) focuses on repairing repositories’ issues by revising existing programs. This highlights the need for models to effectively modify and integrate changes within the repository. Our work fills another gap of incremental repository-level development by introducing a benchmark that evaluates LLMs on the implementation of new features, further bridging the divide between code completion and real-world software engineering.

3 Benchmark Construction

3.1 Overview

The task instances in FEA-Bench are constructed based on existing pull request (PR) data from GitHub. As illustrated in Figure 2, each task instance contains the following elements:

① **Feature Request** Content of the pull request and corresponding issues (if any) provide essential information regarding the new feature or functionality to be developed.

② **Definition of New Components** This includes the signatures and documentation of newly added functions and classes. The name of the new component must be consistent with that in PR, which is the prerequisite for completing the task, because unit tests are written based on the specified name.

③ **Environment Setup** This includes the relevant information for the repository and specifies the base commit of the code repository for each task instance. Besides, the configurations of the building execution environment are also included.

④ **Patch** It describes the changes made to the code in the repository and can be processed by the `unidiff` standard library¹. Additionally, the changes can be applied to the repository using the `git apply` tool. A patch can be divided into a test patch and a gold patch; the former pertains to changes in test codes, while the latter involves the other changes affecting the software itself.

⑤ **Unit Test** The correctness of the code changes is verified based on the result of running these tests. We get the ground truth status by actually running `pytest` before and after applying the gold patch.

¹<https://github.com/matiasb/python-unidiff>




Figure 2: An example of the task instances from the FEA-Bench. During the inference of LLMs, the first two items: feature request and new components are considered as known information. The environment setup serves as a prerequisite for creating the testbed and environment. Python file patches and unit tests are used as labels and evaluation metrics and should not be leaked during the inference of LLMs.

Our data collection pipeline is developed based on SWE-bench. As shown in Figure 3, the proposed collection pipeline ensures data diversity and comprehensiveness, enabling a robust evaluation of LLMs’ capabilities in implementing new features at the repository level. By making our data collection and evaluation codes publicly available, we aim to facilitate continuous updates and the creation of new versions of FEA-Bench. In the rest of this section, we will discuss the construction and the characteristics of FEA-Bench.

3.2 Repository Collection

To determine the scope of GitHub repositories for data collection, we initially focus on the GitHub repositories corresponding to Python packages listed on the Top PyPI website². Packages appearing on this list are generally influential Python software with high data quality, and most repositories use a unified `pytest` format for testing, which facilitates later execution. This leaderboard contains 8,000 Python packages. We filter out repositories

²<https://hugovk.github.io/top-pypi-packages/>




Figure 3: The data collection pipeline for the FEA-Bench. First, determine the scope of GitHub repositories from which task instances will be collected. Next, gather pull requests as task instances and apply filtering criteria to select instances that meet the purpose of adding new features. Finally, use the included test files to execute unit tests, ensuring that only task instances with reproducible test results are included in FEA-Bench. For a more detailed construction process, please refer to Appendix A.2.

240 that have a license and more than 1,000 pull requests, resulting in approximately 600 repositories meeting these criteria.

243 **Fast Validation** Except for repositories already included in SWE-bench, the remaining repositories do not have customized installation procedures or testing methods. While environment configurations vary among different Python packages, pip offers a unified installation approach³. And we adopt pytest as the default method for unit testing. Based on these settings, for each repository, we extract the first 20 pull requests that include changes to test files and observe the unit test status. Repositories that have at least one task instance where the unit tests passed with the default configuration are retained, as they possess the potential to generate task instances that meet our criteria.

257 After this fast validation process, in addition to the 18 Python packages included in the SWE-bench dataset, another 101 Python packages are identified as sources for extracting repository-level data for our benchmark.

262 3.3 Task Collection and Filtering

263 Based on existing repository data, we crawl all pull requests and filter out those that include changes to test files as valid task instances. Given our focus on the incremental feature development task, we introduce the following steps to filter out final task instances for FEA-Bench:

269 **Extraction of new components** For each task instance candidate, we perform parsing on all Python scripts involved in the gold patch. We compare the state before and after applying the patch to identify newly added namespaces, including classes and functions, and extract their signatures and docstrings as metadata.

276 **Filtering based on new components** We retain only those task instances that contain at least one new component. To ensure that implementing

³pip install -e .

279 new features is the primary purpose of the pull request, we further restrict the new components to occupy more than 25% of all edited lines in gold patch. This threshold is set relatively low because code changes often need to include modifications to other related code in addition to the new components themselves.

286 **Intent-based filtering** The pull requests filtered using the above rule-based approach still include some that are not primarily aimed at feature implementation. Therefore, we use GPT-4o to classify the intent based on the pull request description. Only pull requests classified as "new feature" are retained.

293 **Verification by running unit tests** For each instance, we first set up the environment and testbed. We then apply the test patch and run the unit test files involved in the test patch. Theoretically, some unit tests should fail at this stage. After applying the gold patch, we rerun the same unit tests. If the configuration is correct, all unit tests should pass. Unlike SWE-bench, we do not impose restrictions on whether ImportError or AttributeError occurs before applying the gold patch, as these errors are almost inevitable before new components are implemented. Instead, to ensure data quality, we exclude samples where tests remain in the failed status after applying the gold patch. The status of each test function before and after applying the gold patch is recorded.

309 After task collection and filtering, 83 out of 119 repositories collected by the method in Section 3.2 produce 1,401 task instances for new feature implementation.

313 3.4 Benchmark Characteristics

314 **Semi-guided software engineering task** Although the signatures for new components are provided, the primary objective of the FEA-Bench is to evaluate the whole solution of new feature implementation. This is a comprehensive real-world software

	FEA-Bench		SWE-bench	
	Full	Lite	Full	Verified
[Repositories]	83	48	12	12
[Tasks]	1401	200	2294	500
# Lines of oracle files	2115.5	1366.8	1961.3	1488.2
# Files edited	2.62	1.54	1.66	1.24
# Lines edited	128.5	68.1	37.71	14.32
# Lines of added components	87.1	47.2	10.9	2.1
% Added components	67.8	69.3	28.9	14.7
# Functions added	4.49	2.02	0.73	0.25
# Classes added	0.78	0	0.064	0.006

Table 1: Statistics for FEA-Bench and its lite subset, as well as for SWE-bench and its verified subset. The metrics include: 1) the number of task instances and involved repositories; 2) the average total number of lines in all Python files involved in code changes (i.e., the *Oracle* setting described in Section 4.2), and the average number of edited files and lines; 3) the average number of lines of new components, the average percentage of new component lines relative to all edited lines, and the average number of added functions and classes.

engineering task, distinct from code completion. As shown in Table 1, each instance in FEA-Bench involves an average of 128.5 modified lines, with 87.1 lines attributed to the new components themselves. This indicates that approximately 41.4 lines of changes are made elsewhere in the repository. Implementing new features not only requires the ability to generate code for specified new components but also necessitates making complementary changes within the existing repository.

Lite version We have also curated a subset to serve as a lite version of our dataset. This subset was filtered based on criteria including higher quality and lower difficulty. This lite version is particularly useful for evaluating systems that are computationally intensive and time-consuming. Detailed information can be found in Section A.3.

New components driven generation task From Table 1, we can observe that, on average, the number of lines for new components in each FEA-Bench task instance is more than $8\times$ that of SWE-bench. Furthermore, the new components account for approximately 67.8% of all edited lines in FEA-Bench, compared to just 28.9% in SWE-bench. The difference in this metric between FEA-Bench lite and SWE-bench verified is even more pronounced. These statistics indicate that the task instances in FEA-Bench are primarily aimed at implementing new features. In SWE-bench, the average number of new functions is 0.73, indicating that its task instances mainly involve editing existing code rather than incremental development.

Complex solutions While SWE-bench focuses on fixing issues, which generally involve simpler problems, the task instances in FEA-Bench exhibit greater complexity. From Table 1, whether measured by the number of edited lines or edited files, the solutions of task instances in FEA-Bench are notably more complex than those in SWE-bench.

4 Experimental Design

4.1 Models

Due to its repository-level code generation characteristics, FEA-Bench requires models to have a long context window. We evaluate representative code LLMs and general-purpose LLMs with strong foundational capabilities on the FEA-Bench. The code LLMs used in our evaluation include CodeLlama, Codestral⁴, Qwen2.5-Coder, and DeepSeek-Coder-V2 (Roziere et al., 2023; Hui et al., 2024; Zhu et al., 2024). For general-purpose LLMs, we evaluate the performance of GPT-4, GPT-4o (Achiam et al., 2023; Hurst et al., 2024) and DeepSeek-V3 (Liu et al., 2024a), as well as models with long chain-of-thought (CoT) capabilities such as o1 and DeepSeek-R1 (Jaech et al., 2024; Guo et al., 2025).

4.2 Context

To explore the capabilities and potential limits of LLMs in implementing new features within code repositories, we construct different prompts from several perspectives based on our collected data. Each task instance is evaluated using various context settings to provide a comprehensive understanding of model performance.

New component hints In FEA-Bench, information about new components can be derived from two sources: 1) signatures and documentation of newly extracted functions and classes, and 2) changes in non-Python files within the patch, which often contain relevant information about the new components. Based on this, we have two settings: **Brief**. Only provides the signatures of new components. **Detailed**. Includes all the aforementioned information.

Retrieval method Given the extensive amount of code across multiple files in a repository, selective inclusion of file contents as context is necessary. Firstly, the README file and files containing new components are always included in the context. For other files, similar to SWE-bench, we divide

⁴<https://mistral.ai/en/news/codestral>

Model	Size	Window	FEA-Bench				FEA-Bench lite			
			Oracle		BM25 (27K)		Oracle		BM25 (27K)	
			Detailed	Brief	Detailed	Brief	Detailed	Brief	Detailed	Brief
CodeLlama	13B	16K	0.14	0.43	×	×	0.0	0.0	×	×
	34B	16K	0.57	0.57	×	×	0.0	0.0	×	×
Qwen2.5-Coder	14B	32K	3.57	3.57	3.71	2.93	3.5	4.5	3.5	2.5
	32B	32K	4.43	3.64	3.85	2.78	6.0	5.5	2.0	2.5
Codestral-22B	22B	32K	0.86	0.93	1.43	1.36	0.5	1.0	0.0	0.0
DeepSeek-Coder-V2	16B	128K	0.21	0.29	0.57	0.36	0.0	0.5	0.0	0.5
DeepSeek-R1-Distill	32B	128K	3.78	4.07	4.78	4.21	5.5	7.5	7.0	5.5
DeepSeek-V3	671B	64K	8.14	-	8.21	-	14.5	-	13.0	-
DeepSeek-R1	671B	64K	9.92	-	10.49	-	14.5	-	12.0	-
GPT-4		128K	4.71	4.21	3.14	2.86	6.0	6.5	2.0	1.0
GPT-4o		128K	6.14	5.57	5.28	4.50	5.0	5.0	4.0	3.5
o1-mini		128K	1.93	1.86	2.28	2.57	2.0	3.5	1.0	2.0
o1		200K	7.28	6.57	6.78	6.64	10.0	12.5	5.0	7.0

Table 2: The resolved ratios on FEA-Bench (lite) task instances. The evaluation is conducted on single-round generation outputs by each model and a task instance is considered resolved only if all unit tests are passed. The prompt using BM25 retrieved files is limited to length of 27K tokens. This ensures that, with a maximum generation of 4K tokens, the total length will not exceed 32K tokens, which is the context window limits of most tested models. "Detailed" and "Brief" refer to the levels of hints regarding new components in prompt, as mentioned in Section 4.2.

retrieval methods into: **Oracle**. Includes all files involved in the patch in the context. **BM25**. Retrieves relevant files across the entire repository by BM25 algorithm (Robertson et al., 2009) based on the content of the pull request, and ranks them by relevance and filling the context until reaching a specified length.

Output format Generating an entire file can lead to interruptions due to generation limits and is costly. Therefore, our experiments offer two edit-based generation settings: **Natural**. Generates code edits in a natural format as pairs of before-and-after snippets, which can be converted into patches applicable to the code repository through post-processing. **Patch**. Directly generates edits in patch format. Since patches use line numbers for fragment location, this setting includes line numbers in the context’s code content.

The details of prompt and experimental settings are shown in Appendix B.

5 Evaluation Results

The performance of LLMs The evaluation results of FEA-Bench are presented in Table 2. It is observed that in *Oracle* and *Detailed* prompt settings, the best resolved ratio of task instances is 9.92%, indicating the poor performance of LLMs in the incremental development task at the repository level. Generally, the models with larger parameter sizes

demonstrate better results. Among code LLMs, Qwen2.5-Coder exhibited performance comparable to that of GPT-4, highlighting its superiority in the domain of code generation. Despite this, general-purpose LLMs with stronger foundational capabilities can approach the performance of specialized code LLMs. For example, R1-Distill, which shares the same underlying architecture as Qwen2.5-Coder, showed competitive performance. Among the models evaluated, the latest DeepSeek-V3 and R1 models achieve the best performance, significantly outperforming OpenAI’s GPT-4 and o1 series. This underscores the importance of foundational capabilities in LLMs for repository-level development tasks. Additionally, the performance on the lite version is slightly higher, but the relative trends remain largely consistent. When computational resources are limited, the metrics from FEA-Bench lite can be used to reflect the performance on the full benchmark.

The performance under different contexts As shown in Table 2, we evaluate the performance of LLMs under different settings of new component hints and retrieval methods. Overall, detailed new component hints lead to better model performance. However, in the results from FEA-Bench lite, brief hints that only provide signatures performed better. This discrepancy could be attributed to the lack of structured presentation of new components and

	BM25 (27K)	BM25 (40K)
	Retrieval Metrics (%)	
Precision Avg.	40.26	31.85
Recall Avg.	76.04	77.14
Recall All	51.61	53.03

	Resolved Ratio (%)			
	Detailed	Brief	Detailed	Brief
GPT-4	3.14	2.86	3.14	2.78
GPT-4o	5.28	4.50	4.78	4.64

Table 3: The retrieval metrics and the instance resolved ratios under 27K and 40K token length limits of the prompt in *BM25* retrieval mode.

their documentation within the prompt, as illustrated in Figure 6. Regarding retrieval methods, the *Oracle* setting generally outperforms the *BM25* setting, although the difference is not substantial. This may be because code files containing new components, which are regarded as known conditions in the FEA-Bench, ensure a certain baseline performance. Considering the simplest instances in the dataset: those involving modifications to only one code file. Since instances in FEA-Bench always include new components, the unique code file is known information. In this case, *BM25* retrieved files supplement additional information, which can lead to better model performance compared to the *Oracle* setting.

6 Discussion

6.1 Retrieved Files in Context

We aim to investigate whether providing more code context helps LLMs improve new feature development. Therefore, we conducted experiments by increasing the prompt limit from 27K to 40K tokens, which surpasses the original context window limit of Qwen2.5-Coder but can contain more retrieved files. The results are presented in Table 3. The evaluated models include GPT-4 and GPT-4o, and we also report the average precision and recall of Python files in the context relative to those in the gold patch, as well as the proportion of instances where all involved files are recalled.

Although the recalls slightly improve at the limit of 40K tokens, model performance decreases. This indicates that current LLMs still struggle to extract useful information from long contexts in repository-level code development tasks. To improve performance on FEA-Bench, enhancing the precision of retrieval may be an effective approach than simply

Model	%Apply		%Resolved	
	Natural	Patch	Natural	Patch
Qwen2.5-Coder(32B)	44.82	12.92	4.43	1.71
R1-Distill(32B)	55.75	19.06	3.78	1.71
GPT-4	59.10	33.26	4.71	3.07
GPT-4o	66.38	19.49	6.14	1.86
o1	57.03	-	7.28	-
DeepSeek-V3	69.09	-	8.14	-
DeepSeek-R1	73.16	-	9.92	-

Table 4: The impact of output formats *Natural* and *Patch*. We show the success rates of applying code edits to the code repository and the final resolved ratios. The experiments on directly generating patches are conducted only on the models shown in the first four columns.

increasing the context length.

6.2 Output Format of Edits

Direct repository-level code development outputs edits rather than new code itself. How LLMs can better generate edits remains an open question. Therefore, we analyze the impact of output formats using the two configurations described in Section 4.2. The two rightmost columns of Table 4 illustrate a comparison between the *Natural* and the *Patch* generation method, with the former demonstrating significantly higher performance. The possible reason is that generating patches imposes stricter formatting requirements, which current LLMs find challenging to adhere to accurately. Therefore, the main results presented in Table 2 adopt the performance by *Natural* generation method.

Whether using patches converted by converting before-and-after code snippets in *Natural* mode or directly generating patches in *Patch* mode, during evaluation, these patches must be applied to the repository. The success rates of the `git apply` are shown in the middle two columns of Table 4. It can be observed that the success rate in the *Natural* prompt mode is significantly higher, contributing to the superior performance of LLMs in *Natural* mode. Further observation reveals a significant positive correlation between the success rate of applying patches and the resolved ratio, regardless of whether *Natural* or *Patch* mode is used. DeepSeek-R1, which performs the best on FEA-Bench, has the highest values for both metrics. This indicates that the format of code edits is a critical factor limiting the performance of LLMs on such tasks.

6.3 Performances across Repositories

To further analyze LLMs' performance at a finer granularity, we examine resolved ratios across dif-




Figure 4: The resolved ratios grouped by the categories of the repositories.




Figure 5: Histogram of the number of added functions both in all task instances and resolved task instances by DeepSeek-R1 (under *Natural* and *Detailed* prompt settings).

ferent categories of repositories. We classify repositories into several categories, as shown in Appendix A.1. The performance of DeepSeek-R1, o1, and GPT-4o across different categories is illustrated in Figure 4. The resolved ratios of different models vary across categories; task instances in the *Testing* category (from the repo: *joke2k/faker*) have the highest resolved ratio, followed by the *Internet* category. For the remaining categories, the pass ratio of the three models are at a similar level.

Among the three LLMs, GPT-4o shows slightly weaker performance compared to the other models, but its trend is largely consistent with o1. Notably, DeepSeek-R1 exhibits weaker performance in the *Testing* category but significantly outperforms both GPT-4o and o1 in all other categories. This suggests that integrating different models might further enhance overall performance on FEA-Bench.

6.4 Performances under Different Complexity of New Components

To further investigate whether the implementation of new components adds pressure on LLMs in completing feature implementation tasks, we examine the relationship between the number of new func-

tions and the number of resolved instances. The number of added functions is more indicative of the complexity of new components, as functions are more atomic compared to classes. Figure 5 illustrates the distribution of task instances and those solved by R1 with respect to the number of added functions. Excluding instances where the number of added functions is zero (i.e., adding only classes for storing variables), it is evident that the resolved ratio decreases as the number of added functions increases. The resolved ratio is 18.96% when the number of added functions is 1, 8.24% when it is 2, and 5.47% when it is greater than or equal to 3. This indicates that implementing new features is a more challenging task than fixing bugs, which constitute the majority of instances in SWE-bench. Moreover, the more complex the new components, the higher the difficulty of successful implementation.

7 Conclusion

In this paper, we introduce FEA-Bench, a novel benchmark for evaluating the repository-level incremental code development capabilities of large language models (LLMs). Our benchmark focuses on the critical task of implementing new features by adding new components to existing code repositories. Through our comprehensive dataset and rigorous evaluation, we demonstrate that current LLMs face significant challenges in this domain. We also analyzed that the retrieval method of files, the output format, the repository itself, and the complexity of new components all impact the implementation of new features. Our work highlights the need for further advancements in LLMs' reasoning and generation capabilities to better address real-world software engineering tasks. We hope that FEA-Bench will serve as a valuable resource for the research community, driving progress in this important area.

591 Limitations

592 Our constructed data and experiments have certain
593 limitations. Firstly, the quantity of high-quality
594 data suitable for repository-level incremental de-
595 velopment is limited. High-quality and usable pull
596 requests for new feature development are relatively
597 scarce. Many repository-level code developments
598 for implementing new functionalities were commit-
599 ted during the early stages of repositories, without
600 going through the rigorous code review process
601 typical of the open-source community, resulting
602 in lower data quality that cannot be utilized. Fur-
603 thermore, the software’s early-stage developments
604 might not even have been conducted using the
605 GitHub platform, posing a challenge for data col-
606 lection and utilization. Consequently, FEA-Bench,
607 which is built on publicly available data and sub-
608 jected to stringent filtering, may exhibit certain
609 scenario limitations.

610 Secondly, due to the long context involved in
611 repository-level code development, the cost of con-
612 ducting experiments using LLMs is relatively high.
613 Therefore, the experimental results are based on
614 a single round generation, akin to Pass@1, which
615 may introduce a certain level of bias into the results.
616 Additionally, given the scarcity of API resources
617 for models like DeepSeek-V3 and R1, some results
618 in the main experiments presented in Table 2 are
619 missing. We hope that more affordable models
620 similar to DeepSeek can be further developed to
621 facilitate research and applications in the field of
622 repository-level code development.

623 Ethics Statement

624 We collected the data from publicly available
625 Github repositories only for research purposes. All
626 the repositories have licenses that allow free soft-
627 ware use. LLMs are used only for classification
628 during the construction of the FEA-Bench dataset,
629 so no harmful information can be created in the
630 dataset. The dataset and code for our proposed
631 method will be made publicly available for aca-
632 demic research. However, we should note that
633 the inference results of the task instances from the
634 benchmark may contain code that is harmful to
635 computer systems. Evaluation by docker is recom-
636 mended, just like SWE-bench.

637 Additionally, the ChatGPT platform was used as
638 an AI assistant for refining the paper writing.

References

- 640 Josh Achiam, Steven Adler, Sandhini Agarwal, Lama 640
641 Ahmad, Ilge Akkaya, Florencia Leoni Aleman, 641
642 Diogo Almeida, Janko Altschmidt, Sam Altman, 642
643 Shyamal Anadkat, et al. 2023. [Gpt-4 technical report](#). 643
644 *ArXiv preprint*, abs/2303.08774. 644
- Jacob Austin, Augustus Odena, Maxwell Nye, Maarten 645
646 Bosma, Henryk Michalewski, David Dohan, Ellen 646
647 Jiang, Carrie Cai, Michael Terry, Quoc Le, et al. 647
648 2021. [Program synthesis with large language models](#). 648
649 *ArXiv preprint*, abs/2108.07732. 649
- Ramakrishna Bairi, Atharv Sonwane, Aditya Kanade, 650
651 Arun Iyer, Suresh Parthasarathy, Sriram Rajamani, 651
652 B Ashok, and Shashank Shet. 2024. [Codeplan: 652
653 Repository-level coding using llms and planning](#). 653
654 *Proceedings of the ACM on Software Engineering*, 654
655 1(FSE):675–698. 655
- Mark Chen, Jerry Tworek, Heewoo Jun, Qiming Yuan, 656
657 Henrique Ponde De Oliveira Pinto, Jared Kaplan, 657
658 Harri Edwards, Yuri Burda, Nicholas Joseph, Greg 658
659 Brockman, et al. 2021. [Evaluating large lan- 659
660 guage models trained on code](#). *ArXiv preprint*, 660
661 abs/2107.03374. 661
- Arghavan Moradi Dakhel, Vahid Majdinasab, Amin 662
663 Nikanjam, Foutse Khomh, Michel C Desmarais, and 663
664 Zhen Ming Jack Jiang. 2023. [Github copilot ai pair 664
665 programmer: Asset or liability?](#) *Journal of Systems 665
666 and Software*, 203:111734. 666
- Xueying Du, Mingwei Liu, Kaixin Wang, Hanlin Wang, 667
668 Junwei Liu, Yixuan Chen, Jiayi Feng, Chaofeng 668
669 Sha, Xin Peng, and Yiling Lou. 2023. [Classe- 669
670 val: A manually-crafted benchmark for evaluating 670
671 llms on class-level code generation](#). *ArXiv preprint*, 671
672 abs/2308.01861. 672
- Daya Guo, Dejian Yang, Haowei Zhang, Junxiao Song, 673
674 Ruoyu Zhang, Runxin Xu, Qihao Zhu, Shirong Ma, 674
675 Peiyi Wang, Xiao Bi, et al. 2025. [Deepseek-r1: In- 675
676 centivizing reasoning capability in llms via reinforce- 676
677 ment learning](#). *ArXiv preprint*, abs/2501.12948. 677
- Daya Guo, Qihao Zhu, Dejian Yang, Zhenda Xie, 678
679 Kai Dong, Wentao Zhang, Guanting Chen, Xiao 679
680 Bi, Yu Wu, YK Li, et al. 2024. [Deepseek-coder: 680
681 When the large language model meets programming– 681
682 the rise of code intelligence](#). *ArXiv preprint*, 682
683 abs/2401.14196. 683
- Dan Hendrycks, Steven Basart, Saurav Kadavath, Man- 684
685 tas Mazeika, Akul Arora, Ethan Guo, Collin Burns, 684
686 Samir Puranik, Horace He, Dawn Song, et al. 2021. 686
687 [Measuring coding challenge competence with apps](#). 687
688 *ArXiv preprint*, abs/2105.09938. 688
- Binyuan Hui, Jian Yang, Zeyu Cui, Jiayi Yang, Day- 689
690 iheng Liu, Lei Zhang, Tianyu Liu, Jiajun Zhang, 689
691 Bowen Yu, Keming Lu, et al. 2024. [Qwen2. 5-coder 691
692 technical report](#). *ArXiv preprint*, abs/2409.12186. 692

693	Aaron Hurst, Adam Lerer, Adam P Goucher, Adam	Jiawei Liu, Chunqiu Steven Xia, Yuyao Wang, and Ling-	750
694	Perelman, Aditya Ramesh, Aidan Clark, AJ Os-	ming Zhang. 2023a. Is your code generated by chat-	751
695	trow, Akila Welihinda, Alan Hayes, Alec Radford,	gpt really correct? rigorous evaluation of large lan-	752
696	et al. 2024. Gpt-4o system card . <i>ArXiv preprint</i> ,	guage models for code generation . In <i>Advances in</i>	753
697	abs/2410.21276 .	<i>Neural Information Processing Systems 36: Annual</i>	754
698	Aaron Jaech, Adam Kalai, Adam Lerer, Adam Richard-	<i>Conference on Neural Information Processing Sys-</i>	755
699	son, Ahmed El-Kishky, Aiden Low, Alec Helyar,	<i>tems 2023, NeurIPS 2023, New Orleans, LA, USA,</i>	756
700	Aleksander Madry, Alex Beutel, Alex Carney, et al.	<i>December 10 - 16, 2023</i> .	757
701	2024. Openai ol system card . <i>ArXiv preprint</i> ,	Siyao Liu, He Zhu, Jerry Liu, Shulin Xin, Aoyan Li, Rui	758
702	abs/2412.16720 .	Long, Li Chen, Jack Yang, Jinxiang Xia, ZY Peng,	759
703	Naman Jain, King Han, Alex Gu, Wen-Ding Li, Fanjia	et al. 2024b. Fullstack bench: Evaluating llms as full	760
704	Yan, Tianjun Zhang, Sida Wang, Armando Solar-	stack coder . <i>ArXiv preprint</i> , abs/2412.00535 .	761
705	Lezama, Koushik Sen, and Ion Stoica. 2024. Live-	Tianyang Liu, Canwen Xu, and Julian McAuley.	762
706	codebench: Holistic and contamination free eval-	2023b. Repobench: Benchmarking repository-level	763
707	uation of large language models for code . <i>ArXiv</i>	code auto-completion systems . <i>ArXiv preprint</i> ,	764
708	<i>preprint</i> , abs/2403.07974 .	abs/2306.03091 .	765
709	Carlos E Jimenez, John Yang, Alexander Wettig,	Ziyang Luo, Can Xu, Pu Zhao, Qingfeng Sun, Xi-	766
710	Shunyu Yao, Kexin Pei, Ofir Press, and Karthik R	ubo Geng, Wenxiang Hu, Chongyang Tao, Jing Ma,	767
711	Narasimhan. 2024. SWE-bench: Can language mod-	Qingwei Lin, and Daxin Jiang. 2023. Wizardcoder:	768
712	els resolve real-world github issues? In <i>The Twelfth</i>	Empowering code large language models with evol-	769
713	<i>International Conference on Learning Representa-</i>	instruct . <i>ArXiv preprint</i> , abs/2306.08568 .	770
714	<i>tions</i> .	Zhenyu Pan, Rongyu Cao, Yongchang Cao, Yingwei	771
715	Harshit Joshi, José Pablo Cambronero Sánchez, Sumit	Ma, Binhua Li, Fei Huang, Han Liu, and Yongbin	772
716	Gulwani, Vu Le, Gust Verbruggen, and Ivan Radicek.	Li. 2024. Codev-bench: How do llms understand	773
717	2023. Repair is nearly generation: Multilingual pro-	developer-centric code completion? <i>ArXiv preprint</i> ,	774
718	gram repair with llms . In <i>Thirty-Seventh AAAI Con-</i>	abs/2410.01353 .	775
719	<i>ference on Artificial Intelligence, AAAI 2023, Thirty-</i>	Stephen Robertson, Hugo Zaragoza, et al. 2009. The	776
720	<i>Fifth Conference on Innovative Applications of Arti-</i>	probabilistic relevance framework: Bm25 and be-	777
721	<i>ficial Intelligence, IAAI 2023, Thirteenth Symposium</i>	<i>eyond</i> . <i>Foundations and Trends® in Information Re-</i>	778
722	<i>on Educational Advances in Artificial Intelligence,</i>	<i>trieval</i> , 3(4):333–389.	779
723	<i>EAAI 2023, Washington, DC, USA, February 7-14,</i>	Baptiste Roziere, Jonas Gehring, Fabian Gloeckle, Sten	780
724	<i>2023</i> , pages 5131–5140. AAAI Press.	Sootla, Itai Gat, Xiaoqing Ellen Tan, Yossi Adi,	781
725	Jia Li, Ge Li, Zhuo Li, Zhi Jin, Xing Hu, Kechi Zhang,	Jingyu Liu, Tal Remez, Jérémy Rapin, et al. 2023.	782
726	and Zhiyi Fu. 2023a. Codeeditor: Learning to edit	Code llama: Open foundation models for code .	783
727	source code with pre-trained models . <i>ACM Trans-</i>	<i>ArXiv preprint</i> , abs/2308.12950 .	784
728	<i>actions on Software Engineering and Methodology,</i>	Yuling Shi, Songsong Wang, Chengcheng Wan, and	785
729	<i>32(6):1–22</i> .	Xiaodong Gu. 2024. From code to correctness: Clos-	786
730	Jia Li, Ge Li, Xuanming Zhang, Yihong Dong, and	ing the last mile of code generation with hierarchical	787
731	Zhi Jin. 2024a. Evocodebench: An evolving code	debugging . <i>ArXiv preprint</i> , abs/2410.01215 .	788
732	generation benchmark aligned with real-world code	Yanlin Wang, Yanli Wang, Daya Guo, Jiachi Chen,	789
733	repositories . <i>ArXiv preprint</i> , abs/2404.00599 .	Ruikai Zhang, Yuchi Ma, and Zibin Zheng. 2024.	790
734	Jia Li, Ge Li, Yunfei Zhao, Yongmin Li, Huanyu	RlCoder: Reinforcement learning for repository-level	791
735	Liu, Hao Zhu, Lecheng Wang, Kaibo Liu, Zheng	code completion . <i>ArXiv preprint</i> , abs/2407.19487 .	792
736	Fang, Lanshen Wang, et al. 2024b. Deveval:	Yaoliang Wang, Haoling Li, Xin Zhang, Jie Wu, Xiao	793
737	A manually-annotated code generation benchmark	Liu, Wenxiang Hu, Zhongxin Guo, Yangyu Huang,	794
738	aligned with real-world code repositories . <i>ArXiv</i>	Ying Xin, Yujiu Yang, et al. 2025. Epicoder: Encom-	795
739	<i>preprint</i> , abs/2405.19856 .	passing diversity and complexity in code generation .	796
740	Raymond Li, Loubna Ben Allal, Yangtian Zi, Niklas	<i>arXiv preprint arXiv:2501.04694</i> .	797
741	Muennighoff, Denis Kocetkov, Chenghao Mou, Marc	Yuxiang Wei, Zhe Wang, Jiawei Liu, Yifeng Ding, and	798
742	Marone, Christopher Akiki, Jia Li, Jenny Chim, et al.	Lingming Zhang. 2024. Magicoder: Empowering	799
743	2023b. Starcoder: may the source be with you!	code generation with oss-instruct . In <i>Forty-first Inter-</i>	800
744	<i>ArXiv preprint</i> , abs/2305.06161 .	<i>national Conference on Machine Learning</i> .	801
745	Aixin Liu, Bei Feng, Bing Xue, Bingxuan Wang,	Chunqiu Steven Xia, Yinlin Deng, Soren Dunn, and	802
746	Bochao Wu, Chengda Lu, Chenggang Zhao, Chengqi	Lingming Zhang. 2024. Agentless: Demystify-	803
747	Deng, Chenyu Zhang, Chong Ruan, et al. 2024a.	ing llm-based software engineering agents . <i>ArXiv</i>	804
748	Deepseek-v3 technical report . <i>ArXiv preprint</i> ,	<i>preprint</i> , abs/2407.01489 .	805
749	abs/2412.19437 .		

806	Frank F. Xu, Uri Alon, Graham Neubig, and Vincent Josua Hellendoorn. 2022. A systematic evaluation of large language models of code . In <i>Proceedings of the 6th ACM SIGPLAN International Symposium on Machine Programming</i> , MAPS 2022, page 1–10, New York, NY, USA. Association for Computing Machinery.	864
807		865
808		866
809		867
810		868
811		869
812		
813	Jian Yang, Jiajun Zhang, Jiayi Yang, Ke Jin, Lei Zhang, Qiyao Peng, Ken Deng, Yibo Miao, Tianyu Liu, Zeyu Cui, et al. 2024a. Execrepobench: Multi-level executable code completion evaluation . <i>ArXiv preprint</i> , abs/2412.11990.	
814		
815		
816		
817		
818	John Yang, Carlos E Jimenez, Alexander Wettig, Kilian Lieret, Shunyu Yao, Karthik Narasimhan, and Ofir Press. 2024b. Swe-agent: Agent-computer interfaces enable automated software engineering . <i>ArXiv preprint</i> , abs/2405.15793.	
819		
820		
821		
822		
823	Hao Yu, Bo Shen, Dezhi Ran, Jiaxin Zhang, Qi Zhang, Yuchi Ma, Guangtai Liang, Ying Li, Qianxiang Wang, and Tao Xie. 2024a. Codereval: A benchmark of pragmatic code generation with generative pre-trained models . In <i>Proceedings of the 46th IEEE/ACM International Conference on Software Engineering</i> , pages 1–12.	
824		
825		
826		
827		
828		
829		
830	Zhaojian Yu, Xin Zhang, Ning Shang, Yangyu Huang, Can Xu, Yishujie Zhao, Wenxiang Hu, and Qiufeng Yin. 2024b. WaveCoder: Widespread and versatile enhancement for code large language models by instruction tuning . In <i>Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)</i> , pages 5140–5153, Bangkok, Thailand. Association for Computational Linguistics.	
831		
832		
833		
834		
835		
836		
837		
838		
839	Fengji Zhang, Bei Chen, Yue Zhang, Jacky Keung, Jin Liu, Daoguang Zan, Yi Mao, Jian-Guang Lou, and Weizhu Chen. 2023. RepoCoder: Repository-level code completion through iterative retrieval and generation . In <i>Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing</i> , pages 2471–2484, Singapore. Association for Computational Linguistics.	
840		
841		
842		
843		
844		
845		
846		
847	Yuntong Zhang, Haifeng Ruan, Zhiyu Fan, and Abhik Roychoudhury. 2024. Autocoderever: Autonomous program improvement . In <i>Proceedings of the 33rd ACM SIGSOFT International Symposium on Software Testing and Analysis</i> , ISSTA 2024, page 1592–1604, New York, NY, USA. Association for Computing Machinery.	
848		
849		
850		
851		
852		
853		
854	Dewu Zheng, Yanlin Wang, Ensheng Shi, Ruikai Zhang, Yuchi Ma, Hongyu Zhang, and Zibin Zheng. 2024. Towards more realistic evaluation of llm-based code generation: an experimental study and beyond . <i>ArXiv preprint</i> , abs/2406.06918.	
855		
856		
857		
858		
859	Qihao Zhu, Daya Guo, Zhihong Shao, Dejian Yang, Peiyi Wang, Runxin Xu, Y Wu, Yukun Li, Huazuo Gao, Shirong Ma, et al. 2024. Deepseek-coder-v2: Breaking the barrier of closed-source models in code intelligence . <i>ArXiv preprint</i> , abs/2406.11931.	
860		
861		
862		
863		
	Terry Yue Zhuo, Minh Chien Vu, Jenny Chim, Han Hu, Wenhao Yu, Ratnadira Widayarsi, Imam Nur Bani Yusuf, Haolan Zhan, Junda He, Indraneil Paul, et al. 2024. Bigcodebench: Benchmarking code generation with diverse function calls and complex instructions . <i>ArXiv preprint</i> , abs/2406.15877.	864
		865
		866
		867
		868
		869
	A Dataset Details	870
	A.1 Repositories	871
	The task instances in FEA-Bench are derived from 83 Python packages corresponding to GitHub repositories. For each package, we obtained its license information and topic classification from the PyPI website. For packages missing the topic attribute, we utilized their README files and employed GPT-4o to classify them into topics available on the PyPI website ⁵ . Finally, considering the distribution of the topics of task instances in FEA-Bench, we further simplify the topics to several categories to facilitate data visualization and analysis, as presented in Section 6.3.	872
		873
		874
		875
		876
		877
		878
		879
		880
		881
		882
		883
	The relevant information regarding the involved code repositories is summarized in Table 5.	884
		885
	A.2 Construction Details	886
	Table 6 shows the number of remaining task instances for each stage during the data collection process. In Section 3.2, we mentioned that after the fast validation step, including the 18 repositories from SWE-bench, a total of 119 repositories (18 + 101) are available for further data collection. On this basis, we crawl the pull requests from GitHub to obtain code changes. Files with names containing words like <i>test</i> are identified as unit test files executable by <i>pytest</i> .	887
		888
		889
		890
		891
		892
		893
		894
		895
		896
		897
		898
		899
		900
		901
		902
		903
		904
		905
		906
		907
		908
		909
		910
		911
		912

⁵<https://pypi.org/classifiers/>




Figure 6: The prompt for the inference of the task instances.

not exist in SWE-bench, leading to a smaller number of candidate task instances in our benchmark dataset.

Finally, for each instance, we apply the test patch to the repository in the base commit state to verify that unit tests could accurately evaluate the corresponding code edits. Similar to SWE-bench, our pipeline annotates each instance with the corresponding repository version and provides environment and installation configurations based on versions. For repositories included in SWE-bench, we directly utilize their environment setup and test configurations grouped by versions. For other repositories, minimal installation instructions

(`pip install -e .`) and basic `pytest` testing configurations are used. Initially, we run the unit tests directly and observe the pass status. Subsequently, we apply the gold patch from the PR and execute the unit tests again. We allowed errors such as `AttributeError` and `ImportError` in the first test, which are common when new components are not yet implemented, but these errors are not permitted in SWE-bench data collection pipeline. For the second test after applying the gold patch, any `FAILED` status is unacceptable to ensure data quality. After this execution-based filtering process, the final task instances constitute the FEA-Bench task instances, as shown in the "# in Full" column of

941	Table 6.		984
942	We only present information for repositories that	feature request includes both pull request content	985
943	have at least one instance in FEA-Bench. Specifi-	and issue content. Information about new com-	986
944	cally, out of the 119 repositories identified during	ponents and related code files is listed straightfor-	987
945	the repository collection phase, only 83 repositories	wardly within the prompt.	988
946	contain at least one task instance.	In Figure 6, the italicized text indicates place-	989
947	A.3 FEA-Bench lite	holders that need to be filled with specific data	990
948	The feature implementation task proposed in this	of each task instance, while the other text repre-	991
949	study, as one primary type of repository-level in-	sents standard prompt content. Red text highlights	992
950	cremental code development tasks, require LLMs	additional information for detailed hints of new	993
951	with long context capabilities to perform reasoning	components, and blue text indicates parts that need	994
952	over extensive file contents. Such inference is com-	to be modified when directly generating patches as	995
953	putationally expensive. Considering the possible	results.	996
954	evaluation of multi-round code generation systems,	In this study, we provide two formats for generat-	997
955	it is necessary to select a high-quality subset for	ing code edits: <i>Natural</i> and <i>Patch</i> . The correspond-	998
956	more efficient evaluation. Therefore, we establish	ing output instructions are illustrated in Figure 7.	999
957	stricter criteria to curate a higher-quality, lower-	To ensure that the models produce outputs in the	1000
958	difficulty FEA-Bench lite subset.	correct format, both modes are accompanied by	1001
959	Instances meeting any of the following low-	detailed instructions and examples.	1002
960	quality criteria are excluded:	We include several different prompts mentioned	1003
961		above for each task instance in the dataset files.	
962	• The feature request descriptions contain fewer	B.2 Generation Configurations	1004
963	than 40 words.	For models with fewer than 32 billion parameters,	1005
964	• The instance involves cascading issues or com-	we utilized the vLLM framework ⁶ on an 8-GPU	1006
965	mit SHA-256 references.	NVIDIA A100 workstation, employing tensor par-	1007
966	• The descriptions contain images.	allelism for inference. The maximum number of	1008
967	Additionally, to limit task difficulty, instances	generated tokens is limited to 4096, matching the	1009
968	meeting any of the following criteria are also ex-	generation length limits of used OpenAI GPT-4	1010
969	cluded:	and GPT-4o in our experiments.	1011
970		For larger open-source and all closed-source	1012
971	• Involve deleting code files.	models, specifically DeepSeek-V3, R1, and Ope-	1013
972	• Involve more than three code files.	nAI series models, we invoke their APIs for infer-	1014
973	• The gold patch contains More than 10 code	ence. The versions of the OpenAI models used are	1015
974	change hunks.	as follows:	1016
975	• Natural-formatted code change content ex-	• GPT-4: <i>gpt-4-turbo-2024-04-09</i>	1017
976	ceeding 4K(4096) tokens.	• GPT-4o: <i>gpt-4o-2024-05-13</i>	1018
977	• Contain new class(es).	• o1: <i>o1-2024-12-17</i>	1019
978	• Contain more than ten added functions.	• o1-mini: <i>o1-mini-2024-09-12</i>	1020
979	B Inference	When possible, the temperature and top-p set-	1021
980	B.1 Prompt	tings are fixed at 0.2 and 0.95, respectively. For	1022
981	In Section 4.2, we present different prompt set-	DeepSeek-V3 and R1, the max output tokens are	1023
982	tings for the context of inference. A more detailed	8K (8192). For o1 and o1-mini, the max output	1024
983	prompt structure is illustrated in Figure 6. The	tokens is 100,000 and 65,536 (64K), respectively.	1025
	prompt is constructed using the first two items	During the inference process, LLMs perform a	1026
	shown in Figure 2 as known input information. The	single generation for each task instance in FEA-	1027
		Bench, and the output is converted into a patch	1028
		for evaluation. The evaluation tools are adapted	1029
		⁶ https://github.com/vllm-project/vllm	

1030 from the SWE-bench evaluation scripts which are
1031 based on docker, ensuring safety and easy use for
1032 the evaluation process.

"Natural" Format Output Instructions

Please solve the feature request with adding the functions or classes between the <definitions> and </definitions>. You do not need to output any changes or edits for description files like .md or .rst files.
I need you to make multiple edits across one or more files in a repository to implement a specific feature or improvement mentioned above.
For each edit, output the changes in the following format:

```

...
<edit>
[start of the snippet before editing in <file_path>]
<code_before_edit>
[end of the snippet before editing in <file_path>]

[start of the snippet after editing in <file_path>]
<code_after_edit>
[end of the snippet after editing in <file_path>]
</edit>
...

```

Notes:

- The <file_path> is the relative path of the file being edited.
- The <code_before_edit> snippet should include several lines before and after the modified region, unless the file was originally empty.
- If a file was originally empty, leave <code_before_edit> blank but ensure <code_after_edit> includes the new content.
- Ensure the edits are sequential and address all necessary changes to achieve the requested feature.

Here is an example of the output format:

```

<edit>
[start of the snippet before editing in src/code.py]
def factorial(a):
    res = 1
    while a >= 0:
        res *= a
    return res
[end of the snippet before editing in src/code.py]

[start of the snippet after editing in src/code.py]
def factorial(a):
    assert type(a) == int and a >= 0
    res = 1
    while a >= 2:
        res *= a
        a -= 1
    return res
[end of the snippet after editing in src/code.py]
</edit>

<edit>
[start of the snippet before editing in src/code.py]
def exact_division(x, y):
    return x % y == 0
[end of the snippet before editing in src/code.py]

[start of the snippet after editing in src/code.py]
def exact_division(x, y):
    assert type(x) == type(y) == int and x > 0 and y > 0
    return x % y == 0
[end of the snippet after editing in src/code.py]
</edit>

<edit>
[start of the snippet before editing in src/demo.py]
[end of the snippet before editing in src/demo.py]

[start of the snippet after editing in src/demo.py]
from code import factorial
print(factorial(5))
[end of the snippet after editing in src/demo.py]
</edit>

```

I need you to solve the feature request with a series of edits in the format shown above. Respond below:

"Patch" Format Instructions

Please solve the feature request with adding the functions or classes between the <definitions> and </definitions>. You do not need to output any changes or edits for description files like .md or .rst files.
I need you to make multiple edits across one or more files in a repository to implement a specific feature or improvement mentioned above.
The edits should be output in patch format.

Here is an example of a patch file. It consists of changes to the code base. It specifies the file names, the line numbers of each change, and the removed and added lines.
A single patch file can contain changes to multiple files.

```

<patch>
diff --git a/src/code.py b/src/code.py
--- a/src/code.py
+++ b/src/code.py
@@ -1,11 +1,14 @@
def factorial(a):
+ assert type(a) == int and a >= 0
    res = 1
- while a >= 0:
+ while a >= 2:
+     res *= a
+     a -= 1
    return res
#
#
#
def exact_division(x, y):
+ assert type(x) == type(y) == int and x > 0 and y > 0
    return x % y == 0
diff --git a/src/demo.py b/src/demo.py
new file mode 100644
--- /dev/null
+++ b/src/demo.py
@@ -0,0 +1,2 @@
+from code import factorial
+print(factorial(5))
</patch>

```

I need you to solve the provided feature request by generating a single patch file that I can apply directly to this repository using git apply. Please respond with a single patch file in the format shown above.
Respond below:

Figure 7: The output instructions at the rear of the inference prompt.

Repo Name	License	Topic	Category	Source
astropy/astropy	BSD-3-Clause	Scientific/Engineering::Astronomy	Physics	SWE-Bench
django/django	BSD-3-Clause	Internet::WWW/HTTP	Internet	SWE-Bench
matplotlib/matplotlib	Other	Scientific/Engineering::Visualization	Other	SWE-Bench
mwaskom/seaborn	BSD-3-Clause	Scientific/Engineering::Visualization	Other	SWE-Bench
pallets/flask	BSD-3-Clause	Internet::WWW/HTTP	Internet	SWE-Bench
pvlib/pvlib-python	BSD-3-Clause	Scientific/Engineering::Physics	Physics	SWE-Bench
pydata/xarray	Apache-2.0	Scientific/Engineering::Information Analysis	Other	SWE-Bench
pydicom/pydicom	Others	Scientific/Engineering::Medical Science Apps.	Medical	SWE-Bench
pylint-dev/astroid	LGPL-2.1	Software Development::Libraries	Libraries	SWE-Bench
pylint-dev/pylint	GPL-2.0	Software Development::Quality Assurance	Other	SWE-Bench
pyvista/pyvista	MIT	Scientific/Engineering::Information Analysis	Other	SWE-Bench
scikit-learn/scikit-learn	BSD-3-Clause	Scientific/Engineering::Artificial Intelligence	AI	SWE-Bench
sphinx-doc/sphinx	BSD-2-Clause	Text Processing::Markup	Other	SWE-Bench
sqlfluff/sqlfluff	MIT	Software Development::Quality Assurance	Other	SWE-Bench
sympy/sympy	Others	Scientific/Engineering::Mathematics	Mathematics	SWE-Bench
Aider-AI/aider	Apache-2.0	Software Development::Code Generators	Other	Fast-Validation
Cog-Creators/Red-DiscordBot	GPL-3.0	Communications::Chat	Other	Fast-Validation
DLR-RM/stable-baselines3	MIT	Scientific/Engineering::Artificial Intelligence	AI	Fast-Validation
EleutherAI/lm-evaluation-harness	MIT	Scientific/Engineering::Artificial Intelligence	AI	Fast-Validation
Project-MONAI/MONAI	Apache-2.0	Scientific/Engineering::Medical Science Apps.	Medical	Fast-Validation
PyThaiNLP/pythainlp	Apache-2.0	Text Processing::Linguistic	Other	Fast-Validation
RDFLib/rdfib	BSD-3-Clause	Software Development::Libraries	Libraries	Fast-Validation
Textualize/rich	MIT	Software Development::Libraries	Libraries	Fast-Validation
Textualize/textual	MIT	Software Development::User Interfaces	Other	Fast-Validation
TileDB-Inc/TileDB-Py	MIT	Software Development::Libraries	Libraries	Fast-Validation
astronomer/astronomer-cosmos	Apache-2.0	Software Development::Build Tools	Build Tools	Fast-Validation
atlassian-api/atlassian-python-api	Apache-2.0	Internet::WWW/HTTP	Internet	Fast-Validation
aws-cloudformation/cfn-lint	MIT-0	Software Development::Quality Assurance	Other	Fast-Validation
aws-powertools/powertools-lambda-python	MIT-0	Software Development::Libraries	Libraries	Fast-Validation
aws/sagemaker-python-sdk	Apache-2.0	Scientific/Engineering::Artificial Intelligence	AI	Fast-Validation
biopragnatics/bioregistry	MIT	Scientific/Engineering::Bio-Informatics	Other	Fast-Validation
boto/boto3	Apache-2.0	Software Development::Libraries	Libraries	Fast-Validation
boto/botocore	Apache-2.0	Software Development::Libraries	Libraries	Fast-Validation
cocotb/cocotb	BSD-3-Clause	Scientific/Engineering::Electronic Design Automation (EDA)	Other	Fast-Validation
conan-io/conan	MIT	Software Development::Build Tools	Build Tools	Fast-Validation
deepset-ai/haystack	Apache-2.0	Scientific/Engineering::Artificial Intelligence	AI	Fast-Validation
docker/docker-py	Apache-2.0	Software Development::Libraries	Libraries	Fast-Validation
dpkp/kafka-python	Apache-2.0	Software Development::Libraries	Libraries	Fast-Validation
embeddings-benchmark/mteb	Apache-2.0	Scientific/Engineering::Artificial Intelligence	AI	Fast-Validation
facebookresearch/hydra	MIT	Software Development::Libraries	Libraries	Fast-Validation
fairlearn/fairlearn	MIT	Scientific/Engineering::Artificial Intelligence	AI	Fast-Validation
falconry/falcon	Apache-2.0	Internet::WWW/HTTP	Internet	Fast-Validation
google-deeppmind/optax	Apache-2.0	Scientific/Engineering::Artificial Intelligence	AI	Fast-Validation
googleapis/python-aiplatform	Apache-2.0	Scientific/Engineering::Artificial Intelligence	AI	Fast-Validation
googleapis/python-bigquery	Apache-2.0	Internet::WWW/HTTP	Internet	Fast-Validation
gradio-app/gradio	Apache-2.0	Scientific/Engineering::Human Machine Interfaces	Other	Fast-Validation
graphql-python/graphene	MIT	Software Development::Libraries	Libraries	Fast-Validation
huggingface/accelerate	Apache-2.0	Scientific/Engineering::Artificial Intelligence	AI	Fast-Validation
huggingface/datasets	Apache-2.0	Scientific/Engineering::Artificial Intelligence	AI	Fast-Validation
huggingface/huggingface_hub	Apache-2.0	Scientific/Engineering::Artificial Intelligence	AI	Fast-Validation
huggingface/pytorch-image-models	Apache-2.0	Software Development::Libraries	Libraries	Fast-Validation
huggingface/trl	Apache-2.0	Scientific/Engineering::Artificial Intelligence	AI	Fast-Validation
joblib/joblib	BSD-3-Clause	Software Development::Libraries	Libraries	Fast-Validation
joke2k/faker	MIT	Software Development::Testing	Testing	Fast-Validation
lark-parser/lark	MIT	Text Processing::Linguistic	Other	Fast-Validation
minio/minio-py	Apache-2.0	Software Development::Libraries	Libraries	Fast-Validation
open-mmlab/mengine	Apache-2.0	Utilities	Other	Fast-Validation
openvino-toolkit/datamaro	MIT	Scientific/Engineering::Image Processing	Other	Fast-Validation
pgmpy/pgmpy	MIT	Scientific/Engineering::Artificial Intelligence	AI	Fast-Validation
pre-commit/pre-commit	MIT	Software Development::Quality Assurance	Other	Fast-Validation
prometheus/client_python	Apache-2.0	System::Monitoring	Other	Fast-Validation
prompt-toolkit/python-prompt-toolkit	BSD-3-Clause	Software Development::User Interfaces	Other	Fast-Validation
pygments/pygments	BSD-2-Clause	Software Development::Documentation	Other	Fast-Validation
pyocd/pyOCD	Apache-2.0	Software Development::Debuggers	Other	Fast-Validation
pypa/hatch	MIT	Software Development::Build Tools	Build Tools	Fast-Validation
pyro-ppl/pyro	Apache-2.0	Scientific/Engineering::Artificial Intelligence	AI	Fast-Validation
python-hyper/h2	MIT	Internet::WWW/HTTP	Internet	Fast-Validation
roboflow/supervision	MIT	Scientific/Engineering::Image Processing	Other	Fast-Validation
rytilahti/python-miio	GPL-3.0	Home Automation	Other	Fast-Validation
saleweaver/python-amazon-sp-api	MIT	Internet::WWW/HTTP	Internet	Fast-Validation
scrapy/scrapy	BSD-3-Clause	Software Development::Libraries	Libraries	Fast-Validation
scverse/scanpy	BSD-3-Clause	Scientific/Engineering::Bio-Informatics	Other	Fast-Validation
slackapi/bolt-python	MIT	Communications::Chat	Other	Fast-Validation
slackapi/python-slack-sdk	MIT	Communications::Chat	Other	Fast-Validation
snowflake/snowflake-connector-python	Apache-2.0	Software Development::Libraries	Libraries	Fast-Validation
softlayer/softlayer-python	MIT	Software Development::Libraries	Libraries	Fast-Validation
spec-first/connexion	Apache-2.0	Internet::WWW/HTTP	Internet	Fast-Validation
statsmodels/statsmodels	BSD-3-Clause	Scientific/Engineering::Information Analysis	Other	Fast-Validation
tfranzel/df-spectacular	BSD-3-Clause	Software Development::Documentation	Other	Fast-Validation
tobymao/sqlglot	MIT	Database::Database Engines/Servers	Database	Fast-Validation
tornadoweb/tornado	Apache-2.0	Internet::WWW/HTTP	Internet	Fast-Validation
tortoise/tortoise-orm	Apache-2.0	Database::Front-Ends	Database	Fast-Validation
wagtail/wagtail	BSD-3-Clause	Internet::WWW/HTTP	Internet	Fast-Validation

Table 5: The information of the repositories involved in FEABench.

Repository Name	Class (Short)	Max PR No.	# PR	# All tasks	# Candidates	# in Full	# in Lite
sympy/sympy	Mathematics	27454	12857	6034	819	239	46
joke2k/faker	Testing	2144	1386	518	186	126	8
conan-io/conan	Build Tools	17534	6185	3715	473	124	23
tobymao/sqlglot	Database	4597	2463	1996	185	116	14
scikit-learn/scikit-learn	AI	30289	17489	4174	186	83	9
pvlib/pvlib-python	Physics	2336	1072	444	102	52	10
deepset-ai/haystack	AI	8669	4132	1438	317	49	8
Project-MONAI/MONAI	Medical	8275	3468	1809	463	37	1
matplotlib/matplotlib	Other	29140	18163	4057	164	34	7
sphinx-doc/sphinx	Other	13196	5798	1597	126	30	4
googleapis/python-aiplatform	AI	4830	2927	826	241	29	1
astropy/astropy	Physics	17525	11205	4292	405	27	8
Textualize/textual	Other	5444	2205	819	139	27	1
falconry/falcon	Internet	2425	1279	499	67	27	3
softlayer/softlayer-python	Libraries	2207	1277	661	105	26	2
Textualize/rich	Libraries	3548	1142	283	41	24	4
rytilahti/python-miio	Other	1993	979	249	46	23	1
sqlfluff/sqlfluff	Other	6534	3448	2079	296	19	2
google-deeppmind/optax	AI	1164	805	174	54	19	3
pydata/xarray	Other	9879	4310	1838	234	17	2
boto/boto3	Libraries	4371	757	130	38	17	2
roboflow/supervision	Other	1773	1021	94	30	14	7
RDFLib/rdflib	Libraries	3025	1562	370	21	13	2
huggingface/datasets	AI	7342	4118	792	99	12	2
aws-cloudformation/cfn-lint	Other	3898	2583	790	92	11	0
boto/botocore	Libraries	3331	2145	777	83	11	0
pgmpy/pgmpy	AI	1887	902	368	76	11	2
huggingface/huggingface_hub	AI	2683	1559	586	130	10	1
prometheus/client_python	Other	1080	429	134	14	10	1
pypa/hatch	Build Tools	1860	721	313	34	9	1
scrapy/scrapy	Libraries	6598	3253	846	53	9	2
slackapi/python-slack-sdk	Other	1627	764	266	29	9	0
django/django	Internet	18807	18482	725	32	7	1
pydicom/pydicom	Medical	2195	979	494	42	7	1
pylint-dev/pylint	Other	10168	4431	1859	79	7	1
embeddings-benchmark/mteb	AI	1730	1050	137	15	7	1
python-hyper/h2	Internet	1291	1072	144	11	6	0
mwaskom/seaborn	Other	3798	1093	469	40	5	0
pyvista/pyvista	Other	7045	3837	1149	292	5	2
dcpk/kafka-python	Libraries	2442	937	212	17	5	0
lark-parser/lark	Other	1503	467	135	10	5	2
astronomer/astronomer-cosmos	Build Tools	1439	754	270	39	4	1
fairlearn/fairlearn	AI	1472	937	229	29	4	1
huggingface/accelerate	AI	3293	1607	352	67	4	2
docket/docker-py	Libraries	3297	1554	538	24	3	1
huggingface/trl	AI	2550	1181	248	29	3	0
joblib/joblib	Libraries	1641	701	250	11	3	0
open-mmlab/mxnet	Other	1620	1013	350	59	3	1
openvinotoolkit/datumaro	Other	1689	1388	521	98	3	0
pygments/pygments	Other	2837	886	346	79	3	1
pyocd/pyOCD	Other	1734	954	175	11	3	0
pyro-ppl/pyro	AI	3413	2302	1038	369	3	0
tortoise/tortoise-orm	Database	1840	607	283	46	3	0
DLR-RM/stable-baselines3	AI	2069	534	199	23	2	0
EleutherAI/lm-evaluation-harness	AI	2609	961	52	9	2	1
PyThaiNLP/pythainlp	Other	1056	667	269	39	2	1
TileDB-Inc/TileDB-Py	Libraries	2128	1184	488	34	2	0
atlassian-api/atlassian-python-api	Internet	1476	849	49	14	2	0
aws/sagemaker-python-sdk	AI	4987	3219	715	116	2	2
googleapis/python-bigquery	Internet	2102	1372	358	65	2	0
gradio-app/gradio	Other	10271	4707	1210	81	2	0
graphql-python/graphql	Libraries	1583	68	19	2	2	1
prompt-toolkit/python-prompt-toolkit	Other	1949	713	49	3	2	0
snowflakedb/snowflake-connector-python	Libraries	2127	1311	466	22	2	0
spec-first/connexion	Internet	2011	879	327	31	2	0
statsmodels/statsmodels	Other	9462	3793	1444	121	2	0
tornadoweb/tornado	Internet	3452	1573	341	16	2	0
pallets/flask	Internet	5640	2604	404	17	1	0
pylint-dev/astroid	Libraries	2669	1810	301	8	1	0
Aider-AI/aider	Other	2767	346	31	1	1	0
Cog-Creators/Red-DiscordBot	Other	6499	4060	157	18	1	0
aws-powertools/powertools-lambda-python	Libraries	5814	4398	517	115	1	1
biopragmatics/bioregistry	Other	1346	784	156	28	1	0
cocotb/cocotb	Other	4345	2137	493	34	1	0
facebookresearch/hydra	Libraries	3005	1301	442	35	1	0
huggingface/pytorch-image-models	Libraries	2398	551	85	17	1	1
minio/minio-py	Libraries	1472	890	242	14	1	0
pre-commit/pre-commit	Other	3382	1222	527	23	1	0
saleweaver/python-amazon-sp-api	Internet	1638	1027	21	9	1	0
scverse/scanpy	Other	3427	1535	516	35	1	0
slackapi/bolt-python	Other	1234	446	159	9	1	0
tfranzel/drf-spectacular	Other	1362	345	135	12	1	1
wagtail/wagtail	Internet	12732	7070	1531	213	1	0

Table 6: Statistics of how many PRs (task instances) are left during the data collection procedures.