Compositional Flows for 3D Molecule and Synthesis Pathway Co-design

Tony Shen¹*, Seonghwan Seo²*, Ross Irwin^{3,4}, Kieran Didi^{5,6} Simon Olsson⁴, Woo Youn Kim², Martin Ester¹

¹ Simon Fraser University, ² KAIST, ³ AstraZeneca, ⁴ Chalmers University,

⁵ University of Oxford, ⁶ NVIDIA

Abstract

Many generative applications, such as synthesis-based 3D molecular design, involve constructing compositional objects with continuous features. Here, we introduce Compositional Generative Flows (CGFlow), a novel framework that extends flow matching to generate objects in compositional steps while modeling continuous states. Our key insight is that modeling compositional state transitions can be formulated as a straightforward extension of the flow matching interpolation process. We further build upon the theoretical foundations of generative flow networks (GFlowNets), enabling reward-guided sampling of compositional structures. We apply CGFlow to synthesizable drug design by jointly designing the molecule's synthetic pathway with its 3D binding pose. Our approach achieves state-of-the-art binding affinity on all 15 targets from the LIT-PCBA benchmark, and $5.8 \times$ improvement in sampling efficiency compared to 2D synthesis-based baseline. To our best knowledge, our method is also the first to achieve state of-art-performance in both Vina Dock (-9.38 kcal/mol) and AiZynthFinder success rate (62.2%) on the CrossDocked benchmark.

1 INTRODUCTION

Sampling objects through *compositional* steps while modeling *continuous* state is essential for a wide range of scientific applications Jain et al. (2023a); Wang et al. (2023). One such important application is synthesizable target-based drug design, which aims to jointly generate molecules through a sequence of compositional reaction steps and predict their continuous 3D conformations relative to a protein target Li et al. (2022). To this end, we propose a flow-based generative framework that jointly models the compositional structure and continuous state of objects.

Diffusion models Sohl-Dickstein et al. (2015); Ho et al. (2020); Song et al. (2021) and flow matching models Lipman et al. (2023) have achieved state-of-the-art performance in high-dimensional modeling tasks such as 3D molecule generation and protein structure design Hoogeboom et al. (2022); Campbell et al. (2024); Schneuing et al. (2024a). However, standard diffusion and flow matching are restricted to modeling all the dimensions of the object at once (Chen et al., 2024). This results in an inability to model the compositional structure of objects through sequential construction steps. As a consequence, two main limitation arise: (1) the validity of compositional objects cannot be ensured, as invalid generative actions cannot be masked, and (2) the potential for efficient reward credit assignment in the compositional space is restricted Bengio et al. (2021); Hansen et al. (2022); Yao et al. (2023). In drug design, where synthesizability is crucial for wet-lab validation, molecules can be naturally viewed as compositional objects constructed through sequential synthesis steps. Unfortunately, existing diffusion and flow matching models lack the ability to effectively model and respect the compositional nature of synthesis construints when generating molecules.

Sequential models are a natural fit for generating composite objects. For instance, autoregressive models have been applied for 3D molecular design Peng et al. (2023); Gebauer et al. (2020). However, current autoregressive models lack mechanisms to correct errors from earlier steps, causing slight errors in early position predictions to cascade Jin et al. (2022). Generative flow networks

^{*}Equal contribution. Correspondence to tsa87@sfu.ca



Figure 1: Overview of 3DSynthFlow generation. 3D Molecule x = (C, S) consisting of its synthesis pathway C and 3D conformation S (visualized using x). CGFlow generation interleaves 1). the continuous process for modeling position S, and 2). the sequential sampling of synthesis steps at discrete intervals (t={0, 0.25, 0.5, 0.75}). The modeling of synthesis pathways and position are both dependent on the object $x_t = \{S_t, C_t\}$, ensuring the interplay between the two processes.

(GFlowNets; Bengio et al., 2021) have recently shown success in sampling compositional structure for synthesis-based molecule design Koziarski et al. (2024); Cretu et al. (2024); Seo et al. (2024), but remain limited to 2D molecules.

In this paper, we identify the key gap in standard *flow matching* and *sequential models* when generating compositional objects with continuous properties. To address this limitation, we introduce **Compositional Generative Flows (CGFlow)**, a novel generative framework that enables flowbased compositional generative modeling. Our key insight is that compositional generation in flow matching can be realized through a straightforward extension of the interpolation process to accommodate compositional state transitions. CGFlow represents a new generative modeling paradigm that combines the strengths of flow matching models for high-dimensional data while respecting the innate compositional nature of objects.

CGFlow consists of two interleaved flow processes: (1) *Compositional Flow* for modeling the probability path of compositional structure from data distribution to empty structures, and (2) *State Flow* for transporting the state variables associated with the compositional structure from data distribution to noise distribution.

To generate the interpolation path from data to noise, *Compositional Flow* progressively dismantles the compositional structure until it reaches an empty state. *State Flow* follows the standard optimal transport interpolation of flow matching, with the distinction that it assigns higher noise levels to the states of components removed earlier in the process, as described in Ruhe et al. (2024).

To generate compositional structures from the empty state, CGFlow samples constructive compositional steps with the generative policy, which can be modeled using distribution learning approaches, reinforcement learning, or GFlowNets. In particular, GFlowNets is used to prompt efficient exploration of compositional state spaces by reward-guided sampling (Bengio et al., 2021). The conditional flow matching (CFM) objective Lipman et al. (2023) is used to estimate the vector field for generating state variables. Both compositional structure and state variables serve as inputs, ensuring interdependence throughout the generative process.

As an application of the CGFlow framework, we present 3DSynthFlow, the method for target-based drug design ensuring synthesizability. We combine flow matching-based 3D structure generation with the GFlowNet-based synthesis-aware molecular generative model developed by Seo et al. (2024). Fig. 1 illustrates how 3DSynthFlow jointly generates the synthesis pathway (compositional structure) and 3D conformation (continuous state) of molecules. Previous flow-based generative models focused on generating either the 3D molecular structure or the synthesis pathway, but not both (see Sec. 5). 3DSynthFlow can jointly generate synthesis pathways and 3D molecular structures. This enables effective modeling of protein-ligand interactions and ensures synthesizability, both of which are essential for target-based drug discovery.

In our experiments, we evaluate 3DSynthFlow on the task of designing synthesizable drugs directly within protein pockets. 3DSynthFlow achieves 5.8x sampling efficiency improvement, and state-of-the-art performance across all 15 targets in the LIT-PCBA benchmark (Tran-Nguyen et al., 2020) for binding affinity. 3DSynthFlow can be extended to pocket-conditional setting and achieve state of-art-performance in both Vina Dock (-9.38) and AiZynth success rate (62.2%) on the CrossDocked benchmark.

Our contributions are summarized as follows:

- We propose Compositional Generative Flows (CGFlow), a flow-based framework that enables a generation of compositional objects while modeling continuous states.
- We incorporate GFlowNets in CGFlow to enable efficient exploration of compositional statespace for high-rewarded samples.
- We use our compositional framework to develop 3DSynthFlow for 3D molecule and synthesis pathway co-design. 3DSynthFlow achieves 5.8x improvement in sampling efficiency and demonstrate significant improvements in binding affinity and ligand efficiency on the LIT-PCBA benchmark.
- To the best of our knowledge, 3DSynthFlow is the first model to achieve state-of-the-art performance in both binding affinity and synthesis success rate on CrossDocked2020.

2 **GFLOWNETS PRELIMINARY**

Generative Flow Networks (GFlowNets; Bengio et al., 2021) are a family of probabilistic models that learn a stochastic policy to construct compositional objects $x \in \mathcal{X}$ proportional to the reward of terminate state R(x), i.e., $p(x) \propto R(x)$. Each object x is constructed through a trajectory $\tau = (s_0 \rightarrow ... \rightarrow s_n = x) \in \mathcal{T}$ from the initial state s_0 and a series of state transitions $s \rightarrow s'$, where the terminate state is the object $s_n = x \in \mathcal{X}$.

A GFlowNet models a flow F as an unnormalized density function along a directed acyclic graph (DAG) $\mathcal{G} = (\mathcal{S}, \mathcal{A})$, where \mathcal{S} denotes the state space and \mathcal{A} represents transitions. We define the *trajectory flow* $F(\tau)$ as a flow through the trajectory τ . The *node flow* F(s) is defined as the sum of trajectory flows through the node s, i.e., $F(s) = \sum_{s \in \tau} F(\tau)$, and the *edge flow* $F(s \to s')$ is defined as the total flow along the edge $s \to s'$, i.e., $F(s \to s') = \sum_{(s \to s') \in \tau} F(\tau)$.

From the flow network, we define two policy distributions. The forward policy $P_F(s'|s)$ executes the state transition $s \to s'$ from the flow distribution, i.e., $P_F(s'|s) = F(s \to s')/F(s)$. Similarly, the backward policy $P_B(s|s')$ distributes the node flow F(s) to reverse transitions $s \dashrightarrow s'$, i.e., $P_B(s|s') = F(s' \to s)/F(s)$.

To match the likelihood of generating $x \in \mathcal{X}$ with the reward function R, two boundary conditions must be achieved. First, the node flow of each terminal state x, which represents the unnormalized probability of sampling the object x, must equal its reward, i.e., F(x) = R(x). Second, the initial node flow s_0 , which represents the *partition function* Z, must equal the sum of all rewards. i.e., $Z = \sum_{x \in \mathcal{X}} R(x)$. One such objective to satisfy these conditions is *trajectory balance* (TB; Malkin et al., 2023), defined as follows:

$$\mathcal{L}_{\text{TB}}(\tau) = \left(\log \frac{Z_{\theta} \prod_{t=1}^{n} P_F(s_t | s_{t-1}; \theta)}{R(x) \prod_{t=1}^{n} P_B(s_{t-1} | s_t; \theta)}\right)^2,\tag{1}$$

where the P_F , P_B , and Z are directly parameterized to minimize the TB objective.

3 Compositional Generative Flows

CGFlow is a generative framework for modeling compositional objects with continuous states. The framework consists of two interleaved flows: the *Compositional Flow* for modeling compositional structures and the *State Flow* for modeling continuous states.

Data representation. Many applications naturally require compositional structure modeling, such as composing molecules via synthesis pathways Gao et al. (2022) or constructing a causal graph Nishikawa-Toomey et al. (2024).



Figure 2: (A.) Overview of sampling and training using the pre-trained state flow model $p_{1|t}^{\theta}$. At $t = i\lambda$, compositional flow model π^{ϕ} samples a component $C^{(i)}$ based on the state x_t and its previous prediction \hat{x}_1^t . Then, the transition function T incorporates the component $C^{(i)}$ into the object. At t = 1, the compositional flow model is trained based on the reward of the generated object x_1 . (B.) Local time for each component over time, with n = 4, $\lambda = 0.2$, and $t_{window} = 0.4$. $t_{local}^{(i)} = 0$ indicates the $S^{(i)}$ has not yet been initialized. (C.) Illustration of synthesis-based composition rules: (a.) reactant unit-based and (b.) synthon unit-based (ours).

Here, we represent an object x as a tuple $(\mathcal{C}, \mathcal{S})$, where \mathcal{C} denotes the compositional structure and \mathcal{S} represents the associated continuous states. For a given object, the compositional structure is defined as an ordered sequence $\mathcal{C} = (\mathbf{C}^{(i)})_{i=1}^n$, where n denotes the number of its compositional components (e.g., molecular building blocks). The *i*-th component $\mathbf{C}^{(i)}$ is added at the *i*-th generative step of the trajectory τ (e.g., synthesis pathway).

Each compositional component $\mathbf{C}^{(i)}$ contains m_i points (e.g., atoms) and m_i may vary across components. Each point has an associated continuous state of dimension d (e.g., atom position). $\mathbf{S}^{(i)}$ represents the states associated with component i and is of size (m_i, d) . The continuous state \mathbf{S} is defined as an ordered tuple of all states from each component $\mathcal{S} = (\mathbf{S}^{(i)})_{i=1}^n$.

This representation differs from standard flow matching, which models only state variables while ignoring the compositional structure and generation order of the object. In CGFlow, the compositional structure and state variables of an object are modeled jointly, ensuring the validity of the composition in generated objects.

3.1 JOINT CONDITIONAL FLOW PROCESS

We first define a joint conditional flow Lipman et al. (2023) consisting of two components, the *compositional flow* and *state flow*. The joint conditional flow $\mathcal{P}_{t|1}(\cdot|\mathbf{x}_1)$ interpolates the object \mathbf{x} from an initial state \mathbf{x}_0 to the final object \mathbf{x}_1 . At the initial state, $\mathbf{x}_0 = (\mathcal{C}_0, \mathcal{S}_0)$, the compositional structure is represented as an empty graph, $\mathcal{C}_0 = \emptyset$, and the continuous state $\mathcal{S}_0 = []$ has no dimension. The final object $\mathbf{x}_1 = (\mathcal{C}_1, \mathcal{S}_1)$ consists of its complete structure \mathcal{C}_1 and its continuous states \mathcal{S}_1 . Our proposed flow must satisfy the following boundary conditions:

$$\mathcal{P}_{t|1}(\boldsymbol{x}_t | \boldsymbol{x}_1) = \begin{cases} \delta(\boldsymbol{x}_t = \boldsymbol{x}_0), & t = 0, \\ \delta(\boldsymbol{x}_t = \boldsymbol{x}_1), & t = 1. \end{cases}$$
(2)

which ensures that at t = 0, the flow starts at the initial state x_0 , and at t = 1, it reaches the final state x_1 .

3.1.1 COMPOSITIONAL FLOW

Compositional Flow defines a conditional probability flow over the compositional structure C, progressively transitioning it from an empty graph C_0 to a complete structure C_1 . Components are added sequentially in a predefined valid order, where $\mathbf{C}^{(1)}$ is the first component added. The function k(t)

determines how many components have been added at time t, defined as:

$$k(t) = \begin{cases} 0, & t = 0, \\ \min(\lfloor t/\lambda \rfloor + 1, n), & t > 0, \end{cases}$$
(3)

where λ defines time interval between adding each compositional components. At time t, the compositional structure C_t includes the first k(t) components from this order. k(t) increases in discrete steps as t progresses, starting from k(0) = 0 and ensuring k(1) = n, such that all n components are added by t = 1. Each component $\mathbf{C}^{(i)}$ is generated at time $t_{\text{gen}}^{(i)} = \lambda \cdot (i-1)$. To ensure that all components are generated within the valid time range, we require $\lambda \leq 1/n$ for all datapoints, satisfying $t_{\text{gen}} \leq 1 - \lambda$. The compositional structure at time t is then given by:

$$\mathcal{C}_t = (\mathbf{C}^{(i)})_{i=1}^{k(t)},\tag{4}$$

This formulation guarantees a gradual and sequential construction of C_t , transitioning from the empty state C_0 to the fully constructed structure C_1 at fixed intervals.

Previous work models transitions across dimensions in diffusion processes using a rate function (Campbell et al., 2023). In contrast, we formulate transitions at fixed discrete intervals. Our approach retains key advantages of autoregressive generation, including simplified likelihood evaluation and learning objectives.

3.1.2 STATE FLOW

State flow defines a conditional probability path over the continuous states $S = (S^{(i)})_{i=1}^n$. Each continuous state $S^{(i)}$ is initialized only when its corresponding compositional component $C^{(i)}$ is generated, and components are generated at different times. Intuitively, we have greater uncertainty in the continuous states of recently added components than those generated earlier. Therefore, we introduce a temporal bias similar to that used in diffusion-based video generation Ruhe et al. (2024): the global time t is reparameterized into a component-wise local time $t_{local}^{(i)}$, defined as:

$$t_{\text{local}}^{(i)} = \text{clip}\left(\frac{t - t_{\text{gen}}^{(i)}}{t_{\text{window}}}\right),\tag{5}$$

where $t_{\text{gen}}^{(i)}$ is the generation time of component $C^{(i)}$, t_{window} is the interpolation time window, and $\operatorname{clip}(x)$ ensures $t_{\text{local}}^{(i)} \in [0, 1]$. Intuitively, $t_{\text{local}}^{(i)} = 0$ when the current time is $t = t_{\text{gen}}^{(i)}$, and $t_{\text{local}}^{(i)} = 1$ when the current time surpasses $t_{\text{gen}}^{(i)} + t_{\text{window}}$.

State flow is modeled as a linear interpolation based on $t_{local}^{(i)}$, combined with Gaussian noise applied throughout:

$$\mathbf{S}_{t}^{(i)} = \begin{cases} \mathcal{N}(t_{\text{local}}^{(i)} \mathbf{S}_{1}^{(i)} + (1 - t_{\text{local}}^{(i)}) \mathbf{S}_{0}^{(i)}, \sigma^{2}), & \text{if } t > t_{\text{gen}}^{(i)}, \\ [], & \text{else.} \end{cases}$$
(6)

where $\mathbf{S}_{0}^{(i)}$ represents the fully noisy initial state, and $\mathbf{S}_{1}^{(i)}$ is the final refined state. The continuous state $\mathbf{S}_{t}^{(i)}$ exists only if the corresponding component $\mathbf{C}_{t}^{(i)}$ has been generated, i.e., $t > t_{\text{gen}}^{(i)}$. To summarize, *state flow* enables the interpolation of continuous states when their associated compositional components are generated sequentially.

3.2 SAMPLING

During the sampling process, objects are generated by interleaving the integration of the *state flow* model $p_{1|t}^{\theta}$ and sampling actions using the *compositional flow* policy π^{θ} . The process alternates between refining continuous states S_t and sequentially constructing the compositional structure C_t at fixed time points.

For state flow, the vector field governing the continuous states for the *i*-th component $S^{(i)}$ is defined as $\hat{S}_1^{(i)} - S_t^{(i)}$, where $\hat{S}_1^{(i)}$ is the predicted clean state by $p_{1|t}^{\theta}$, as formulated in previous works Le et al. (2023). The rate at which we step in this vector field $\kappa^{(i)}$ is determined by the time remaining in the interpolation process for the state $S^{(i)}$:

$$\kappa^{(i)} = \frac{\min(t_{\text{end}}^{(i)} - t, \Delta t)}{t_{\text{window}}},\tag{7}$$

where $t_{\text{end}}^{(i)} = t_{\text{gen}}^{(i)} + t_{\text{window}}$ is the time at which the interpolation for component *i* is completed, and t_{window} is the interpolation window. The state values $S^{(i)}$ are updated using Euler's method:

$$\mathbf{S}_{t+\Delta t}^{(i)} = \mathbf{S}_{t}^{(i)} + (\hat{\mathbf{S}}_{1}^{(i)} - \mathbf{S}_{t}^{(i)}) \cdot \kappa^{(i)} \Delta t,$$
(8)

Intuitively, if $t \ge t_{\text{end}}^{(i)}$, the state $S_t^{(i)}$ is directly set to the predicted clean value $\hat{S}_1^{(i)}$, ensuring the coherence of the continuous state.

For compositional structure generation, new components $\mathbf{C}^{(i)}$ are sampled from the compositional flow policy π^{θ} at discrete time intervals separated by λ . Transition function $T(\boldsymbol{x}_t, \mathbf{C}^{(i)})$ incorporates newly sampled component $\mathbf{C}^{(i)}$ into the object. T also incorporates the new component's associated state $S_0^{(i)}$ by sampling its value from a noise distribution (typically Gaussian).

3.3 TRAINING OBJECTIVES

We train CGFlow to jointly approximate the distribution of continuous states S and the sequential generation of the compositional structure C with two models: (1) a state flow model $p_{1|t}^{\theta}$ for updating continuous states, and (2) a compositional flow policy π^{θ} for sampling compositional components. Both models are conditioned on the entire object $\mathbf{x}_t = (C_t, S_t)$ with self-conditioning $\hat{\mathbf{x}}_1^t = (C_t, \hat{S}_1^t)$ at time t, where $\hat{S}_1^t = (\hat{S}_1^{(i)})_{i=1}^{k(t)}$ from the previous prediction (Chen et al., 2022). This formulation ensures their dependence on both the compositional structure and the continuous state of the object.

3.3.1 STATE FLOW LOSS.

The state flow model can be trained *simulation-free*, and independently of the compositional flow model. For each object x, we first assign a generation trajectory τ over its compositional components C. Then we can sample x_t according to the joint interpolation process (see Sec. 3.1).

The state flow model $p_{1|t}^{\theta}$ takes the entire object $\boldsymbol{x}_t = (\mathcal{C}_t, \mathcal{S}_t)$ as input and outputs $\hat{\mathcal{S}}_1^{t+\Delta t}$, the predicted clean continuous states. The objective sums over the continuous states $\boldsymbol{S}_t^{(i)}$ corresponding to components $\mathbf{C}^{(i)}$ that have already been generated at the sampled time t:

$$\mathcal{L}_{\text{state}} = \mathbb{E}_{p_{\text{data}}(\boldsymbol{x}_1)\mathcal{U}(t)} \sum_{i=1}^{k(t)} \left\| p_{1|t}^{\theta}(\boldsymbol{x}_t)^{(i)} - \boldsymbol{S}_1^{(i)} \right\|_2^2,$$
(9)

where k(t) represents the number of components generated at time t. The refinement model $p_{1|t}^{\theta}(\boldsymbol{x}_t)^{(i)}$ predicts $\hat{\boldsymbol{S}}_1^{(i)}$, the clean continuous states for component i, and we compute the MSE loss compared to the ground truth $\boldsymbol{S}_1^{(i)}$.

3.3.2 COMPOSITIONAL FLOW LOSS.

Given a pre-trained state flow model $p_{1|t}^{\theta}$, the compositional flow model π_{ϕ} samples a trajectory τ by sequentially adding a component $C^{(i)}$ at $t = i\lambda$, conditioned on the current state x_t and self-conditioning \hat{x}_1^t . This strategy allows the compositional flow model to make decisions using a less noisy estimate \hat{x}_1^t , which is particularly advantageous in protein-ligand interaction modeling (Harris et al., 2023).

Inspired by GFlowNets (Bengio et al., 2021), we optimize the compositional flow model such that the probability of sampling a compositional structure for x_1 is proportional to its reward $R(x_1)$, using the trajectory balance (TB; Eq. (1)) objective. However, the object $x_1 = (C_1, S_1)$ from a trajectory τ is stochastic due to the transition function T, which samples the initial state $S_0^{(i)}$ from a noise distribution. To ensure a deterministic transition $T(x_t, C^{(i)})$, we fix the random seed when sampling the initial state $S_0^{(i)}$.

Given a deterministic transition function and a fixed state flow model ODE, $\boldsymbol{x}_t = (\mathcal{C}_t, \mathcal{S}_t)$ is uniquely determined by a given trajectory τ sampled from the compositional flow model π^{ϕ} . This formulation views the interpolation with the state flow model $p_{1|t}^{\theta}$ as the transition of the state resulting from the sampled action by the compositional flow policy $\pi^{\phi 1}$ Then, TB loss is computed as:

$$\mathcal{L}_{\text{TB}}(\tau) = \left(\log \frac{Z_{\phi} \prod_{i=0}^{n-1} P_F(\boldsymbol{C}_{(i)} | \boldsymbol{x}_{i\lambda}, \hat{\boldsymbol{x}}_1^{i\lambda}; \phi)}{R(\boldsymbol{x}_1)}\right)^2.$$
(10)

We provide the theoretical background for this derivation in Sec. B.

By enabling *on-policy* training, this approach generalizes beyond trajectories observed in the empirical data, as it can sample new data under the current policy. Alternatively, the compositional flow model can be trained using a maximum likelihood objective based on the data distribution (see Sec. A.3).

We refer readers to Sec. A.1 for a summary of the key steps in applying CGFlow to a new data domain. In the next section, we demostrate CGFlow's application to 3D molecular generation and synthesis pathway design.

4 3D MOLECULE AND SYNTHESIS PATHWAY CO-DESIGN WITHIN PROTEIN POCKETS

Synthesizability is a critical factor for ensuring molecules can be readily made for wet lab validation. Recent works have incorporated combinatorial chemistry principles into generative models to respond to this challenge Koziarski et al. (2024); Cretu et al. (2024); Seo et al. (2024). Despite these advancements, these synthesis-based generative models are restricted to 2D molecular graphs, limiting their ability to capture the 3D protein-ligand interactions that are essential for biological efficacy.

To address this limitation, we introduce 3DSynthFlow, a generative method based on CGFlow, enabling the co-design of synthesis pathways and 3D molecular conformations. This approach facilitates effective modeling of protein-ligand interactions and synthesizability, which are both essential for target-based drug discovery.

State flow model predicts the docking pose of a molecule within a target protein pocket. Unlike typical docking, where the full 2D molecule is provided at t = 0, the state flow model must predict the pose for the ligand that is sequentially constructed at discrete time intervals. Molecules for training the state flow model x are first decomposed into their compositional structure C, which represents the sequentially composed synthesis pathway using Enamine reaction rules, and their continuous state S, which represents the 3D coordinates refined over time. We discuss the motivation behind this formulation in App. E.1.2.

The state flow model is then trained using the objective described in Sec. 3.3.1 on the protein-ligand complex dataset, independent of the compositional flow model. The *Semla* architecture Irwin et al. (2024), originally designed for 3D molecular generation, is used to parameterize the State flow model. We introduce new protein-encoding and protein and ligand message passing layers to enable protein-ligand modeling (See Sec. D.2.1).

Compositional flow model generates a synthesis pathway to construct a molecular structure. The action space for the composition flow model consists of all valid synthetic steps for a given compositional structure C_t (details in App. D.1). We modify the architecture from RxnFlow Seo et al. (2024) to model the sampling policy for synthesis steps using 3D protein-ligand complexes as input (see Sec. D.2.2). The compositional flow model is trained online as described in Sec. 3.3.2.

¹Conceptually, it resembles an internal model of the world: used to predict the next state of the world as a function of the current state and action Bryson & Ho (1969). The state flow model weights are fixed to remain faithful to the data distribution.

		Average Vina Docking Score (kcal/mol, \downarrow)						
Category	Method	ADRB2	ALDH1	ESR_ago	ESR_antago	FEN1	Avg.	Med.
Fragment	FragGFN FragGFN+SA	$\begin{array}{c} -10.19 \ (\pm \ 0.33) \\ -9.70 \ (\pm \ 0.61) \end{array}$	$\begin{array}{c} -10.43 \ (\pm \ 0.29) \\ -9.83 \ (\pm \ 0.65) \end{array}$	$\begin{array}{c} -9.81 \ (\pm \ 0.09) \\ -9.27 \ (\pm \ 0.95) \end{array}$	$\begin{array}{c} -9.85 \ (\pm \ 0.13) \\ -10.06 \ (\pm \ 0.30) \end{array}$	$\begin{array}{c} -7.67 \ (\pm \ 0.71) \\ -7.26 \ (\pm \ 0.10) \end{array}$	-9.58 -9.22	-9.85 -9.58
Reaction	SynNet BBAR SynFlowNet ^a SynFlowNet ^b RGFN RxnFlow	$\begin{array}{c} -8.03 \ (\pm \ 0.26) \\ -9.95 \ (\pm \ 0.04) \\ -10.85 \ (\pm \ 0.10) \\ -9.17 \ (\pm \ 0.68) \\ -9.84 \ (\pm \ 0.21) \\ -11.45 \ (\pm \ 0.05) \end{array}$	$\begin{array}{c} -8.81 \ (\pm \ 0.21) \\ -10.06 \ (\pm \ 0.14) \\ -10.69 \ (\pm \ 0.09) \\ -9.37 \ (\pm \ 0.29) \\ -9.93 \ (\pm \ 0.11) \\ -11.26 \ (\pm \ 0.07) \end{array}$	$\begin{array}{c} -8.88 \ (\pm \ 0.13) \\ -9.97 \ (\pm \ 0.03) \\ -10.44 \ (\pm \ 0.05) \\ -9.17 \ (\pm \ 0.12) \\ -9.99 \ (\pm \ 0.11) \\ -11.15 \ (\pm \ 0.02) \end{array}$	$\begin{array}{c} -8.52 \ (\pm \ 0.16) \\ -9.92 \ (\pm \ 0.05) \\ -10.27 \ (\pm \ 0.04) \\ -9.05 \ (\pm \ 0.14) \\ -9.72 \ (\pm \ 0.14) \\ -10.77 \ (\pm \ 0.04) \end{array}$	$\begin{array}{c} -6.36 \ (\pm \ 0.09) \\ -6.84 \ (\pm \ 0.07) \\ -7.47 \ (\pm \ 0.02) \\ -6.45 \ (\pm \ 0.13) \\ -6.92 \ (\pm \ 0.06) \\ -7.66 \ (\pm \ 0.02) \end{array}$	-8.12 -9.35 -9.95 -8.78 -9.08 -10.46	-8.52 -9.84 -10.34 -9.17 -9.91 -10.84
3D Reaction	3DSynthFlow	-11.97 (± 0.43)	-12.25 (± 0.07)	-11.31 (± 0.12)	-11.25 (± 0.07)	-7.92 (± 0.22)	-10.97	-11.25

Table 1: Average Vina docking score of Top-100 diverse modes. We report two versions of SynFlowNet ($v2024.05^a$ and $v2024.10^b$). Avg. and Med. are the average and median values over the average docking scores for all 15 LIT-PCBA protein targets. The results for the remaining 10 target proteins are reported in Appendix. 16 The best results are in bold.

5 RELATED WORK

Synthesis-based generative models. Generative models have emerged as the key paradigm for discovering candidates by bypassing the expensive virtual screening. However, most generative models often render molecules outside the bounds of synthesizable chemical space, limiting their practical use in real-world applications (Gao & Coley, 2020). To address this limitation, several studies (Shen et al., 2024; Guo & Schwaller, 2024) have employed various synthetic complexity estimation methods (Ertl & Schuffenhauer, 2009; Coley et al., 2018; Kim et al., 2023; Neeser et al., 2024; Genheden et al., 2020) as the reward function.

Another promising direction is to design molecules by assembling purchasable building blocks under predefined synthesis protocols. (Gao et al., 2022; Li et al., 2022; Seo et al., 2023; Swanson et al., 2024; Gao et al., 2024). This strategy explicitly constrains the sample space to synthesizable chemical space. More recently, Koziarski et al. (2024); Cretu et al. (2024); Seo et al. (2024) have extended this strategy using GFlowNets, formulating synthesis pathway generation as trajectories of GFlowNets. This effectively explores the chemical space to discover diverse candidate molecules while balancing exploration and exploitation.

Diffusion for sequential data. Diffusion models have recently gained traction for generative modeling of sequential structures in diverse domains, spanning biological sequences Campbell et al. (2024); Stark et al. (2024), videos Ruhe et al. (2024), and language modeling Lou et al. (2024). Campbell et al. (2023) propose a jump process for transitioning between different dimensional spaces to address the variable-dimension nature of data. To exploit the temporal causal dependency in sequences, Ruhe et al. (2024); Zhang et al. (2023) explore frame-level noise schedules for diffusion-based video generation for arbitrary-length frame rollout. Wu et al. (2023); Chen et al. (2024) apply similar ideas of training next-token prediction models while diffusing past ones for applications in planning and language modeling. Most similar to our work for molecule generation using diffusion models are methods that use a separate diffusion process for each sequentially added fragment Peng et al. (2023); Ghorbani et al. (2023); Li et al. (2024).

We provide an extended related works for sequential diffusion for molecular generation and structure-based drug design in App. C.

6 EXPERIMENTS

Overview We evaluate 3DSynthFlow for synthesizable target-based drug design in two common settings: pocket-specific optimization (Sec. 6.1) and pocket-conditional generation (Sec. 6.2). Our experiments aims to address three main key questions: (1) Does 3DSynthFlow generate molecules with improved binding affinity and ligand efficiency compared to existing synthesis-based baselines? (2) Does co-designing 3D structures improve the sampling efficiency in discovering diverse high-reward modes? (3) How does 3DSynthFlow generalize to the pocket-conditional setting, and how does it compare to existing SBDD baselines?



Figure 3: Number of discovered modes (satisfying Vina <-10 kcal/mol, QED >0.5, Sim <0.5) as a function of sampling budget for the first four LIT-PCBA targets for 3DSynthFlow (3D) vs RxnFlow (2D) across 2 seeds. Lower is better.

To answer these questions, We first apply 3DSynthFlow to optimize for targets in the LIT-PCBA benchmark (Tran-Nguyen et al., 2020). We evaluate the affinity, ligand efficiency, synthesis success rate and protein-ligand interactions of generated molecules. Then, we compare the sampling efficiency of 3DSynthFlow against 2D-based baseline. Lastly, we comapre 3DSynthFlow against SBDD methods in the pocket-conditional setting on the CrossDocked dataset (Francoeur et al., 2020).

Setup. We utilize 1.2M molecular fragments from the Enamine Catalog and 38 bimolecular Enamine synthesis protocols from Gao et al. (2024). To ensure tractability, molecular generation is limited to two synthesis steps, consistent with Enamine REAL Space guidelines (Grygorenko et al., 2020). To estimate synthesizability, we employ the retrosynthetic analysis tool AiZynthFinder (Genheden et al., 2020).

We pre-train the state flow model for 3D pose prediction on the CrossDocked dataset Francoeur et al. (2020) with LIT-PCBA targets removed (see App. E.2.2). We sample a synthesis pathway for each ligand using reaction rules to fragment the ligand (see Fig. 2). This exposes the state flow model to intermediate states - allowing it to predict their poses for partial structures during compositional flow model training (see App. E.1.2 for motivation).

6.1 POCKET-SPECIFIC OPTIMIZATION

Setup. We follow Seo et al. (2024) in both the reward function and evaluation protocol. To estimate the binding affinity, we use the GPU-accelerated docking tool UniDock (Yu et al., 2023). Each method generates up to 64,000 molecules for each protein target. To prevent *reward hacking* by increasing molecular size to improve the docking score, QED (Bickerton et al., 2012) is jointly optimized, and we set a generation of 40 heavy atoms. This ensure that the generated molecules have drug-like properties. Specifically, we optimize $R(x) = w_1 \text{QED}(x) + w_2 \overline{\text{Vina}}(x)$, where $\overline{\text{Vina}}(x)$ is a normalized docking score. The parameters w_1 and w_2 serve as conditions of multi-objective GFlowNets (Jain et al., 2023b), and are set to 0.5 for non-GFlowNet baselines.

Generated molecules are filtered based on property constraints (QED > 0.5), and the top 100 diverse modes are selected according to docking scores, ensuring structural diversity with a Tanimoto distance threshold of 0.5^2 . Finally, we evaluated the average **Vina Docking Score** and **AiZynthFinder Success Rate** of the selected molecules. **Ligand Effiency** as computed by (Vina / number of heavy atoms) is also reported to confirm the docking score improvement do not arise from simply increase in molecular size.

Baselines. We compare our approach against several synthesis-based methods, including a genetic algorithm **SynNet** (Gao et al., 2022), a conditional generative model **BBAR** (Seo et al., 2023), and multiple GFlowNets. We consider two settings of fragment-based GFlowNets, with and without synthetic accessibility score (SA; Ertl & Schuffenhauer, 2009) objective (**FragGFN, FragGFN+SA**), and three different synthesis-based GFlowNets (**RGFN, SynFlowNet, RxnFlow**) (Koziarski et al., 2024; Cretu et al., 2024; Seo et al., 2024).

²Since we select top 100 modes filtering for similarity, diversity is not reported in this section.

		Validity (†)	Vina	a (↓)	QE	D (†)	AiZynth	. Succ. (†)	Div (†)	Time (\downarrow)
Category	Method	Validity	Avg.	Med.	Avg.	Med.	Avg.	Med.	Avg.	Avg.
	Reference	-	-7.71	-7.80	0.48	0.47	36.1%	-	-	-
Atom	Pocket2Mol TargetDiff DecompDiff DiffSBDD MolCRAFT MolCRAFT-large	98.3% 91.5% 66.0% 76.0% 96.7% 70.8%	-7.60 -7.37 -8.35 -6.95 -8.05 <u>-9.25</u>	-7.16 -7.56 -8.25 -7.10 -8.05 -9.24	$\begin{array}{c} 0.57 \\ 0.49 \\ 0.37 \\ 0.47 \\ 0.50 \\ 0.45 \end{array}$	0.58 0.49 0.35 0.48 0.50 0.44	29.1% 9.9% 0.9% 2.9% 16.5% 3.9%	22.0% 3.2% 0.0% 2.0% 9.1% 0.0%	0.83 <u>0.87</u> 0.84 0.88 0.84 0.82	2504 3428 6189 135 141 >141
Fragment	TacoGFN	100.0%	-8.24	-8.44	0.67	0.67	1.3%	1.0%	0.67	4
2D Reaction	RxnFlow	100.0%	-8.85	-9.03	0.67	0.67	34.8%	34.5%	0.81	4
3D Reaction	3DSynthFlow (low β) 3DSynthFlow (med β) 3DSynthFlow (high β)	100.0% 100.0% 100.0%	-9.00 -9.16 -9.38	-9.27 <u>-9.41</u> -9.62	0.72 <u>0.73</u> 0.74	0.72 0.74 0.74	55.0% 56.6% 62.2%	54.5% <u>56.0%</u> 63.0%	0.79 0.76 0.66	24 24 24

Table 2: **Benchmark Results for Generative Methods.** We report the average (Avg.) and median (Med.) values for each metric when available. Reference denotes known actives. For methods where only one value is available, the median is indicated as "–".

Results. Table. 1 presents the Vina results for the first five targets, while the full property results for all targets are in Sec. F.8. 3DSynthFlow consistently outperforms all baselines across LIT-PCBA targets in affinity and ligand efficiency, demonstrating that co-designing 3D molecular structures alongside synthesis pathways enhances the discovery of high-affinity molecules. Furthermore, 3DSynthFlow achieves 5.8x sampling efficiency to 2D baselines, as detailed in Sec. 6.1.1. Molecules generated by 3DSynthFlow also exhibit a higher number of protein-ligand interactions, as quantified by PoseCheck, highlighting the benefits of 3D-aware modeling for target-based drug design (see App. F.5).

Finally, we conduct extensive ablation studies on the various technical decisions regarding: flow matching steps (App. F.2), time scheduling (App. F.3), and use of pose-based rewards (App. F.1). Analysis on training efficiency can be found in App. E.1.3.

6.1.1 3DSYNTHFLOW IMPROVES SAMPLING EFFICIENCY

We evaluate sample efficiency on the first 5 LIT-PCBA targets and report results in Fig. 3 and Table. 15. Diverse high-scoring modes were defined by QED > 0.5, Vina < -10 kcal/mol³, and Tanimoto similarity < 0.5 to any other mode. After sampling 10,000 molecules, 3DSynthFlow identified 5.8x number of diverse high-scoring modes compared to RxnFlow (316 vs 54.6). This enhanced sampling efficiency validates the effectiveness of 3DSynthFlow framework, and suggests a higher probability of experimental success in downstream drug discovery applications.

6.2 POCKET-CONDITIONAL GENERATION.

Setup. Our method generalizes to pocket-conditional generation problem setting (Peng et al., 2022; Guan et al., 2023; Schneuing et al., 2024a), enabling the design of binders for unseen pockets with a single model and no additional oracle calls. We follow the same pocket-conditional experimental setup used in TacoGFN (Shen et al., 2024) and RxnFlow (Seo et al., 2024). 3DSynthFlow adopt the pre-trained proxy from TacoGFN trained on CrossDock2020 train set, which leverages pharmacophore representation (Seo & Kim, 2024), to compute rewards for training a pocket-conditional policy.

Each method generates 100 molecules for each of the 100 test pockets in the CrossDocked2020 benchmark (Francoeur et al., 2020) and are evaluated on these additional metrics compared to the pocket-specific setting: **Diversity** represents the average pairwise Tanimoto distance computed from ECFP4 fingerprints (Morgan, 1965). We also report **Validity** (%), the proportion of unique molecules that can be parsed by RDKit, and **Time** (sec.), the average duration required to sample 100 molecules.

³Except for FEN1, where we use Vina threshold below -7 kcal/mol to maintain similar number of modes compared to the other four targets.

Baselines. We compare 3DSynthFlow with state-of-the-art distribution learning-based models trained on a synthesizable drug set, including the autoregressive model **Pocket2Mol** (Peng et al., 2022), and diffusion-based methods: **TargetDiff** (Guan et al., 2023), **DiffSBDD** (Schneuing et al., 2024b), **DecompDiff** (Guan et al., 2024), and **MolCRAFT** (Qu et al., 2024). We further include comparisons with optimization-based approaches: the fragment-based method **TacoGFN** (Shen et al., 2024) and the reaction-based method **RxnFlow** (Seo et al., 2024). To ensure a fair evaluation of distribution learning-based methods, we use the docking proxy trained on CrossDocked training set. To balance exploration and exploitation during sampling, we vary the reward exponentiation parameter β of **3DSynthFlow**: **low** β (sampled from Uniform(1, 64)), **medium** β (Uniform(32, 64)), and **high** β (Uniform(48, 64)).

Results. As shown in Table. 2, 3DSynthFlow achieves significant improvements in pocketconditional generation, particularly in synthesizability and docking scores. In particular, 3DSynthFlow- high β attains an average docking score of -9.38 kcal/mol, outperforming RxnFlow (-8.85) and state-of-the-art diffusion-based methods like MolCRAFT-large (-9.25) and DecompDiff (-8.35). We attribute this improvement largely to our explicit consideration of 3D co-design in the reaction-based generation framework.

6.2.1 3DSYNTHFLOW ACHIEVES COMPETITIVE SYNTHESIZABILITY

3DSynthFlow also ensures high AiZynth success rate via synthesis-based generation, achieving success rates of 55.0%-62.2% across different β values in the pocket-conditioned setting. This surpasses synthesis-based RxnFlow (34.8%), and TacoGFN (1.3%), which optimize for SA score.

The reported average AiZynth success rates of RxnFlow on LIT-PCBA is 65.4% and is significantly higher to their performance on CrossDocked, and consistently outperforms 3DSynthFlow (avg. 53.12%) (See Table. 14). It's unclear where the inter-dataset variability arises from for RxnFlow. However, we note the synthesis success rate of our model is consistently strong for both CrossDock (55.0% - 62.2%) and LIT-PCBA benchmarks (53.12%).

SBDD methods such as MolCRAFT-large can attain strong binding affinity (-9.25) similar to 3DSynthFlow (-9.38), however their synthesis success rate is much lower (3.9% vs 62.2%). The main contribution of 3DSynthFlow is representing both the compositional nature for synthesis constraints and modeling 3D poses for binding. Both synthesizability and binding are both necessary requirement for experimental validation.

7 DISCUSSION

Limitations. Our synthesis-based action space based on brick and linker synthons does not yet explore certain synthetic pathways including nonlinear synthesis pathway such as ring-forming reactions. This synthon-based generation is chosen to prevent the atoms from intermediate states being lost from reactions or forming new rings - which would degrade the accuracy of pose prediction for intermediate states. However, this constraint can be substantially mitigated by expanding the chemical search space through incorporating a larger building block library. For example, Sadybekov et al. (2021) successfully achieved a notable hit rate of 33% with brick-and-linker design.

Conclusion. In this work, we introduce Compositional Generative Flows (CGFlow), a flexible generative framework for jointly modeling compositional structures and continuous states. We introduce a simple extension to the flow matching interpolation process for handling compositional state transition. CGFlow enables the integration of GFlowNets for efficient exploration of compositional state spaces with flow matching for continuous state modeling. We apply CGFlow to 3D molecule and synthesis pathway co-design and develop 3DSynthFlow, which achieves state-of-the-art performance on both LIT-PCBA and CrossDocked benchmark. Future work includes using a more expressive model for pose prediction in 3DSynthFlow and developing more application-specific methods using CGFlow.

REFERENCES

- Emmanuel Bengio, Moksh Jain, Maksym Korablyov, Doina Precup, and Yoshua Bengio. Flow network based generative models for non-iterative diverse candidate generation. In M. Ranzato, A. Beygelzimer, Y. Dauphin, P.S. Liang, and J. Wortman Vaughan (eds.), Advances in Neural Information Processing Systems, volume 34, pp. 27381–27394. Curran Associates, Inc., 2021. URL https://proceedings.neurips.cc/paper_files/paper/2021/ file/e614f646836aaed9f89ce58e837e2310-Paper.pdf.
- G Richard Bickerton, Gaia V Paolini, Jérémy Besnard, Sorel Muresan, and Andrew L Hopkins. Quantifying the chemical beauty of drugs. *Nature chemistry*, 4(2):90–98, 2012.
- Caterina Bissantz, Bernd Kuhn, and Martin Stahl. A medicinal chemist's guide to molecular interactions. *Journal of Medicinal Chemistry*, 53(14):5061–5084, 2010. doi: 10.1021/jm100112j. URL https://doi.org/10.1021/jm100112j. PMID: 20345171.
- I. D. Brown. On the geometry of $O-H \cdots O$ hydrogen bonds. Acta Crystallographica Section A, 32 (1):24–31, Jan 1976. doi: 10.1107/S0567739476000041.
- A. E. Bryson and Y. C. Ho. Applied Optimal Control. Blaisdell, New York, 1969.
- Andrew Campbell, William Harvey, Christian Weilbach, Valentin De Bortoli, Tom Rainforth, and Arnaud Doucet. Trans-dimensional generative modeling via jump diffusion models, 2023. URL https://arxiv.org/abs/2305.16261.
- Andrew Campbell, Jason Yim, Regina Barzilay, Tom Rainforth, and Tommi Jaakkola. Generative flows on discrete state-spaces: Enabling multimodal flows with applications to protein co-design, 2024. URL https://arxiv.org/abs/2402.04997.
- Boyuan Chen, Diego Marti Monso, Yilun Du, Max Simchowitz, Russ Tedrake, and Vincent Sitzmann. Diffusion forcing: Next-token prediction meets full-sequence diffusion, 2024. URL https://arxiv.org/abs/2407.01392.
- Ting Chen, Ruixiang Zhang, and Geoffrey Hinton. Analog bits: Generating discrete data using diffusion models with self-conditioning. *arXiv preprint arXiv:2208.04202*, 2022.
- Connor W Coley, Luke Rogers, William H Green, and Klavs F Jensen. Scscore: synthetic complexity learned from a reaction corpus. *Journal of chemical information and modeling*, 58(2): 252–261, 2018.
- Miruna Cretu, Charles Harris, Julien Roy, Emmanuel Bengio, and Pietro Lio. Synflownet: Towards molecule design with guaranteed synthesis pathways. In *ICLR 2024 Workshop on Generative and Experimental Perspectives for Biomolecular Design*, 2024. URL https://openreview.net/forum?id=kjcBA2I2My.
- Peter Ertl and Ansgar Schuffenhauer. Estimation of synthetic accessibility score of drug-like molecules based on molecular complexity and fragment contributions. *Journal of cheminformatics*, 1:1–11, 2009.
- Paul G. Francoeur, Tomohide Masuda, Jocelyn Sunseri, Andrew Jia, Richard B. Iovanisci, Ian Snyder, and David R. Koes. Three-dimensional convolutional neural networks and a cross-docked data set for structure-based drug design. *Journal of Chemical Information and Modeling*, 60(9): 4200–4215, 2020. doi: 10.1021/acs.jcim.0c00411. PMID: 32865404.
- Richard A. Friesner, Jay L. Banks, Robert B. Murphy, Thomas A. Halgren, Jasna J. Klicic, Daniel T. Mainz, Matthew P. Repasky, Eric H. Knoll, Mee Shelley, Jason K. Perry, David E. Shaw, Perry Francis, and Peter S. Shenkin. Glide: A new approach for rapid, accurate docking and scoring. 1. method and assessment of docking accuracy. *Journal of Medicinal Chemistry*, 47(7):1739–1749, 2004. doi: 10.1021/jm0306430. URL https://doi.org/10.1021/jm0306430. PMID: 15027865.
- Wenhao Gao and Connor W. Coley. The synthesizability of molecules proposed by generative models, 2020. URL https://arxiv.org/abs/2002.07007.

- Wenhao Gao, Rocío Mercado, and Connor W. Coley. Amortized tree generation for bottom-up synthesis planning and synthesizable molecular design. In *International Conference on Learning Representations*, 2022. URL https://openreview.net/forum?id=FRxhHdnxt1.
- Wenhao Gao, Shitong Luo, and Connor W Coley. Generative artificial intelligence for navigating synthesizable chemical space. arXiv preprint arXiv:2410.03494, 2024.
- Niklas W. A. Gebauer, Michael Gastegger, and Kristof T. Schütt. Symmetry-adapted generation of 3d point sets for the targeted discovery of molecules, 2020. URL https://arxiv.org/ abs/1906.00957.
- Samuel Genheden, Amol Thakkar, Veronika Chadimová, Jean-Louis Reymond, Ola Engkvist, and Esben Bjerrum. Aizynthfinder: a fast, robust and flexible open-source software for retrosynthetic planning. *Journal of cheminformatics*, 12(1):70, 2020.
- Mahdi Ghorbani, Leo Gendelev, Paul Beroza, and Michael J. Keiser. Autoregressive fragment-based diffusion for pocket-aware ligand design, 2023. URL https://arxiv.org/abs/2401.05370.
- Oleksandr O Grygorenko, Dmytro S Radchenko, Igor Dziuba, Alexander Chuprina, Kateryna E Gubina, and Yurii S Moroz. Generating multibillion chemical space of readily accessible screening compounds. *Iscience*, 23(11), 2020.
- Jiaqi Guan, Wesley Wei Qian, Xingang Peng, Yufeng Su, Jian Peng, and Jianzhu Ma. 3d equivariant diffusion for target-aware molecule generation and affinity prediction, 2023. URL https:// arxiv.org/abs/2303.03543.
- Jiaqi Guan, Xiangxin Zhou, Yuwei Yang, Yu Bao, Jian Peng, Jianzhu Ma, Qiang Liu, Liang Wang, and Quanquan Gu. Decompdiff: Diffusion models with decomposed priors for structure-based drug design, 2024. URL https://arxiv.org/abs/2403.07902.
- Jeff Guo and Philippe Schwaller. It takes two to tango: Directly optimizing for constrained synthesizability in generative molecular design. *arXiv preprint arXiv:2410.11527*, 2024.
- Nicklas Hansen, Xiaolong Wang, and Hao Su. Temporal difference learning for model predictive control, 2022. URL https://arxiv.org/abs/2203.04955.
- Charles Harris, Kieran Didi, Arian R. Jamasb, Chaitanya K. Joshi, Simon V. Mathis, Pietro Lio, and Tom Blundell. Benchmarking generated poses: How rational is structure-based drug design with generative models?, 2023. URL https://arxiv.org/abs/2308.07413.
- Jonathan Ho, Ajay Jain, and Pieter Abbeel. Denoising diffusion probabilistic models, 2020. URL https://arxiv.org/abs/2006.11239.
- Emiel Hoogeboom, Victor Garcia Satorras, Clément Vignac, and Max Welling. Equivariant diffusion for molecule generation in 3d, 2022. URL https://arxiv.org/abs/2203.17003.
- Ross Irwin, Alessandro Tibo, Jon Paul Janet, and Simon Olsson. Efficient 3d molecular generation with flow matching and scale optimal transport, 2024. URL https://arxiv.org/abs/2406.07266.
- Moksh Jain, Tristan Deleu, Jason Hartford, Cheng-Hao Liu, Alex Hernandez-Garcia, and Yoshua Bengio. Gflownets for ai-driven scientific discovery. *Digital Discovery*, 2:557–577, 2023a. doi: 10.1039/D3DD00002H. URL http://dx.doi.org/10.1039/D3DD00002H.
- Moksh Jain, Sharath Chandra Raparthy, Alex Hernández-Garcia, Jarrid Rector-Brooks, Yoshua Bengio, Santiago Miret, and Emmanuel Bengio. Multi-objective gflownets. In *International conference on machine learning*, pp. 14631–14653. PMLR, 2023b.
- Wengong Jin, Jeremy Wohlwend, Regina Barzilay, and Tommi Jaakkola. Iterative refinement graph neural network for antibody sequence-structure co-design, 2022. URL https://arxiv.org/abs/2110.04624.

- Bowen Jing, Stephan Eismann, Patricia Suriana, Raphael J. L. Townshend, and Ron Dror. Learning from protein structure with geometric vector perceptrons, 2021. URL https://arxiv.org/abs/2009.01411.
- Bowen Jing, Ezra Erives, Peter Pao-Huang, Gabriele Corso, Bonnie Berger, and Tommi Jaakkola. Eigenfold: Generative protein structure prediction with diffusion models, 2023. URL https: //arxiv.org/abs/2304.02198.
- Hyeongwoo Kim, Kyunghoon Lee, Chansu Kim, Jaechang Lim, and Woo Youn Kim. Dfrscore: deep learning-based scoring of synthetic complexity with drug-focused retrosynthetic analysis for high-throughput virtual screening. *Journal of Chemical Information and Modeling*, 64(7): 2432–2444, 2023.
- Leon Klein, Andreas Krämer, and Frank Noé. Equivariant flow matching, 2023. URL https: //arxiv.org/abs/2306.15030.
- Michał Koziarski, Andrei Rekesh, Dmytro Shevchuk, Almer van der Sloot, Piotr Gaiński, Yoshua Bengio, Cheng-Hao Liu, Mike Tyers, and Robert A Batey. Rgfn: Synthesizable molecular generation using gflownets. arXiv preprint arXiv:2406.08506, 2024.
- Tuan Le, Julian Cremer, Frank Noé, Djork-Arné Clevert, and Kristof Schütt. Navigating the design space of equivariant diffusion-based generative models for de novo 3d molecule generation, 2023. URL https://arxiv.org/abs/2309.17296.
- Xinze Li, Penglei Wang, Tianfan Fu, Wenhao Gao, Chengtao Li, Leilei Shi, and Junhong Liu. Autodiff: Autoregressive diffusion modeling for structure-based drug design, 2024. URL https://arxiv.org/abs/2404.02003.
- Yibo Li, Jianfeng Pei, and Luhua Lai. Synthesis-driven design of 3d molecules for structure-based drug discovery using geometric transformers. *arXiv preprint arXiv:2301.00167*, 2022.
- Yaron Lipman, Ricky T. Q. Chen, Heli Ben-Hamu, Maximilian Nickel, and Matt Le. Flow matching for generative modeling, 2023. URL https://arxiv.org/abs/2210.02747.
- Tairan Liu, Misagh Naderi, Chris Alvin, Supratik Mukhopadhyay, and Michal Brylinski. Break down in order to build up: decomposing small molecules for fragment-based drug design with e molfrag. *Journal of chemical information and modeling*, 57(4):627–631, 2017.
- Aaron Lou, Chenlin Meng, and Stefano Ermon. Discrete diffusion modeling by estimating the ratios of the data distribution, 2024. URL https://arxiv.org/abs/2310.16834.
- Shitong Luo, Jiaqi Guan, Jianzhu Ma, and Jian Peng. A 3D generative model for structure-based drug design. In *NeurIPS*, 2021.
- Nikolay Malkin, Moksh Jain, Emmanuel Bengio, Chen Sun, and Yoshua Bengio. Trajectory balance: Improved credit assignment in gflownets, 2023. URL https://arxiv.org/abs/2201. 13259.
- Harry L Morgan. The generation of a unique machine description for chemical structures-a technique developed at chemical abstracts service. *Journal of chemical documentation*, 5(2):107–113, 1965.
- Rebecca M Neeser, Bruno Correia, and Philippe Schwaller. Fsscore: A personalized machine learning-based synthetic feasibility score. *Chemistry-Methods*, 4(11):e202400024, 2024.
- Mizu Nishikawa-Toomey, Tristan Deleu, Jithendaraa Subramanian, Yoshua Bengio, and Laurent Charlin. Bayesian learning of causal structure and mechanisms with gflownets and variational bayes, 2024. URL https://arxiv.org/abs/2211.02763.
- Mohit Pandey, Gopeshh Subbaraj, Artem Cherkasov, Martin Ester, and Emmanuel Bengio. Pretraining generative flow networks with inexpensive rewards for molecular graph generation, 2025. URL https://arxiv.org/abs/2503.06337.

- Xingang Peng, Shitong Luo, Jiaqi Guan, Qi Xie, Jian Peng, and Jianzhu Ma. Pocket2mol: Efficient molecular sampling based on 3d protein pockets. In *ICML*, pp. 17644–17655. PMLR, 2022.
- Xingang Peng, Jiaqi Guan, Jian Peng, and Jianzhu Ma. Pocket-specific 3d molecule generation by fragment-based autoregressive diffusion models, 2023. URL https://openreview.net/forum?id=HGsoelwmRW5.
- Yanru Qu, Keyue Qiu, Yuxuan Song, Jingjing Gong, Jiawei Han, Mingyue Zheng, Hao Zhou, and Wei-Ying Ma. Molcraft: Structure-based drug design in continuous parameter space, 2024. URL https://arxiv.org/abs/2404.12141.
- Matthew Ragoza, Tomohide Masuda, and David Ryan Koes. Generating 3d molecules conditional on receptor binding sites with deep generative models. *Chemical science*, 13(9):2701–2713, 2022.
- Danny Reidenbach. EvoSBDD: Latent evolution for accurate and efficient structure-based drug design. In *ICLR 2024 Workshop on Machine Learning for Genomics Explorations*, 2024. URL https://openreview.net/forum?id=sLhUNz0uTz.
- David Ruhe, Jonathan Heek, Tim Salimans, and Emiel Hoogeboom. Rolling diffusion models, 2024. URL https://arxiv.org/abs/2402.09470.
- Arman A. Sadybekov, Anastasiia V. Sadybekov, Yongfeng Liu, Christos Iliopoulos-Tsoutsouvas, Xi-Ping Huang, Julie Pickett, Blake Houser, Nilkanth Patel, Ngan K. Tran, Fei Tong, Nikolai Zvonok, Manish K. Jain, Olena Savych, Dmytro S. Radchenko, Spyros P. Nikas, Nicos A. Petasis, Yurii S. Moroz, Bryan L. Roth, Alexandros Makriyannis, and Vsevolod Katritch. Synthon-based ligand discovery in virtual libraries of over 11 billion compounds. *Nature*, 601(7893):452–459, December 2021. ISSN 1476-4687. doi: 10.1038/s41586-021-04220-9. URL http://dx. doi.org/10.1038/s41586-021-04220-9.
- Arne Schneuing, Charles Harris, Yuanqi Du, Kieran Didi, Arian Jamasb, Ilia Igashov, Weitao Du, Carla Gomes, Tom Blundell, Pietro Lio, Max Welling, Michael Bronstein, and Bruno Correia. Structure-based drug design with equivariant diffusion models, 2024a. URL https://arxiv.org/abs/2210.13695.
- Arne Schneuing, Charles Harris, Yuanqi Du, Kieran Didi, Arian Jamasb, Ilia Igashov, Weitao Du, Carla Gomes, Tom Blundell, Pietro Lio, Max Welling, Michael Bronstein, and Bruno Correia. Structure-based drug design with equivariant diffusion models, 2024b. URL https://arxiv. org/abs/2210.13695.
- Seonghwan Seo and Woo Youn Kim. Pharmaconet: deep learning-guided pharmacophore modeling for ultra-large-scale virtual screening. *Chem. Sci.*, 15:19473–19487, 2024. doi: 10.1039/ D4SC04854G. URL http://dx.doi.org/10.1039/D4SC04854G.
- Seonghwan Seo, Jaechang Lim, and Woo Youn Kim. Molecular generative model via retrosynthetically prepared chemical building block assembly. *Advanced Science*, 10(8):2206674, 2023.
- Seonghwan Seo, Minsu Kim, Tony Shen, Martin Ester, Jinkyoo Park, Sungsoo Ahn, and Woo Youn Kim. Generative flows on synthetic pathway for drug design, 2024. URL https://arxiv.org/abs/2410.04542.
- Tony Shen, Seonghwan Seo, Grayson Lee, Mohit Pandey, Jason R Smith, Artem Cherkasov, Woo Youn Kim, and Martin Ester. Tacogfn: Target-conditioned gflownet for structure-based drug design, 2024. URL https://arxiv.org/abs/2310.03223.
- Jascha Sohl-Dickstein, Eric A. Weiss, Niru Maheswaranathan, and Surya Ganguli. Deep unsupervised learning using nonequilibrium thermodynamics, 2015. URL https://arxiv.org/ abs/1503.03585.
- Yang Song, Jascha Sohl-Dickstein, Diederik P. Kingma, Abhishek Kumar, Stefano Ermon, and Ben Poole. Score-based generative modeling through stochastic differential equations, 2021. URL https://arxiv.org/abs/2011.13456.

- Yuxuan Song, Jingjing Gong, Minkai Xu, Ziyao Cao, Yanyan Lan, Stefano Ermon, Hao Zhou, and Wei-Ying Ma. Equivariant flow matching with hybrid probability transport, 2023. URL https://arxiv.org/abs/2312.07168.
- Hannes Stark, Bowen Jing, Chenyu Wang, Gabriele Corso, Bonnie Berger, Regina Barzilay, and Tommi Jaakkola. Dirichlet flow matching with applications to dna sequence design, 2024. URL https://arxiv.org/abs/2402.05841.
- Hannes Stärk, Bowen Jing, Regina Barzilay, and Tommi Jaakkola. Harmonic self-conditioned flow matching for multi-ligand docking and binding site design, 2024. URL https://arxiv.org/abs/2310.05764.
- Kyle Swanson, Gary Liu, Denise B Catacutan, Autumn Arnold, James Zou, and Jonathan M Stokes. Generative ai for designing and validating easily synthesizable and structurally novel antibiotics. *Nature Machine Intelligence*, 6(3):338–353, 2024.
- Viet-Khoa Tran-Nguyen, Célien Jacquemard, and Didier Rognan. Lit-pcba: an unbiased data set for machine learning and virtual screening. *Journal of chemical information and modeling*, 60(9): 4263–4273, 2020.
- Hanchen Wang, Tianfan Fu, Yuanqi Du, Wenhao Gao, Kexin Huang, Ziming Liu, Payal Chandak, Shengchao Liu, Peter Van Katwyk, Andreea Deac, Anima Anandkumar, Karianne Bergen, Carla P Gomes, Shirley Ho, Pushmeet Kohli, Joan Lasenby, Jure Leskovec, Tie-Yan Liu, Arjun Manrai, Debora Marks, Bharath Ramsundar, Le Song, Jimeng Sun, Jian Tang, Petar Veličković, Max Welling, Linfeng Zhang, Connor W Coley, Yoshua Bengio, and Marinka Zitnik. Scientific discovery in the age of artificial intelligence. *Nature*, 620(7972):47–60, August 2023.
- Tong Wu, Zhihao Fan, Xiao Liu, Yeyun Gong, Yelong Shen, Jian Jiao, Hai-Tao Zheng, Juntao Li, Zhongyu Wei, Jian Guo, Nan Duan, and Weizhu Chen. Ar-diffusion: Auto-regressive diffusion model for text generation, 2023. URL https://arxiv.org/abs/2305.09515.
- Shunyu Yao, Dian Yu, Jeffrey Zhao, Izhak Shafran, Thomas L. Griffiths, Yuan Cao, and Karthik Narasimhan. Tree of thoughts: Deliberate problem solving with large language models, 2023. URL https://arxiv.org/abs/2305.10601.
- Yuejiang Yu, Chun Cai, Jiayue Wang, Zonghua Bo, Zhengdan Zhu, and Hang Zheng. Uni-dock: Gpu-accelerated docking enables ultralarge virtual screening. *Journal of chemical theory and computation*, 19(11):3336–3345, 2023.
- Seongjun Yun, Minbyul Jeong, Sungdong Yoo, Seunghun Lee, S Yi Sean, Raehyun Kim, Jaewoo Kang, and Hyunwoo J Kim. Graph transformer networks: Learning meta-path graphs to improve gnns. *Neural Networks*, 153:104–119, 2022.
- Zihan Zhang, Richard Liu, Kfir Aberman, and Rana Hanocka. Tedi: Temporally-entangled diffusion for long-term motion synthesis, 2023. URL https://arxiv.org/abs/2307.15042.
- Alex Zhavoronkov, Yan A Ivanenkov, Alex Aliper, Mark S Veselov, Vladimir A Aladinskiy, Anastasiya V Aladinskaya, Victor A Terentiev, Daniil A Polykovskiy, Maksim D Kuznetsov, Arip Asadulaev, et al. Deep learning enables rapid identification of potent ddr1 kinase inhibitors. *Nature biotechnology*, 37(9):1038–1040, 2019.

A CGFLOW DETAILS

All code is provided in supplementary material.

A.1 CGFLOW RECIPE

We now summarize the key steps for implementing CGFlow for generative tasks which constructs compositional structures with continuous states.

- 1. Decompose the object into its compositional and continuous part (e.g., 2D structure and 3D coordinates) (See Sec. 3).
- 2. Define action space for additive composition steps.
- 3. Define a function for sampling action sequence for constructing the compositional structure (e.g. synthesis order).
- 4. Train State Flow model on existing datasets (e.g. 3D protein-ligand complexes) (Sec. 3.3.1).
- 5. Train the compositional flow model using GFlowNets-based Compositional Flow loss, if reward function R(x) (docking score) is available, else use cross-entropy loss (Sec. 3.3.2).
- 6. Run sampling using trained state flow and compositional flow model (Algorithm 1).

A.2 SAMPLING ALGORITHM

Algorithm 1 Compositional Flow Sampling with CGFlow

Require: step size Δt , interval λ , time window t_{window} 1: init $t = 0, i = 0, C_t = C_0, S_0 = S_0, \hat{S}_1^t = S_0$ 2: while t < 1 do $\boldsymbol{x}_t \leftarrow (\mathcal{C}_t, \mathcal{S}_t, \hat{\mathcal{S}}_1^t)$ 3: \triangleright Use self-conditioning. 4: if $t \mod \lambda = 0$ then 5: $i \leftarrow i + 1$ $\mathbf{C}^{(i)} \sim \pi_{\theta}(\boldsymbol{x}_t) \mathrel{\triangleright} \mathbf{Compositional flow model:} Sample the next compositional component$ 6: $m{S}_t^{(i)} \sim \mathcal{N}(0,1)$ \triangleright Initialize new state values for component *i* under the fixed seed 7: $\boldsymbol{x}_t \leftarrow T(\boldsymbol{x}_t, \mathbf{C}^{(i)}, \boldsymbol{S}_t^{(i)})$ > Transition with sampled composition and state value. 8: $t_{\text{gen}}^{(i)} \gets t$ 9: 10: end if $t_{\text{local}}^{(j)} \leftarrow \text{clip}\left(\frac{t - t_{\text{gen}}^{(j)}}{t_{\text{window}}}\right), \, \forall j \leq i$ 11: $\hat{\boldsymbol{S}}_{1}^{(j)} \leftarrow p_{1|t}^{\theta}(\boldsymbol{x}_{t}, t_{\text{local}}^{(j)}), \forall j \leq i \qquad \triangleright \text{ State flow model: } Predict final state values. \\ \boldsymbol{S}_{t+\Delta t}^{(j)} \leftarrow \boldsymbol{S}_{t}^{(j)} + (\hat{\boldsymbol{S}}_{1}^{(j)} - \boldsymbol{S}_{t}^{(j)}) \cdot \kappa^{(j)} \Delta t, \forall j \leq i \qquad \triangleright \text{ Step according to the predicted vector }$ 12: 13: field. $t \leftarrow t + \Delta t$ 14: 15: end while 16: return x_1

A.3 ALTERNATIVE TRAINING OBJECTIVES

There may be cases where reward function R(x) is not available, or the goal is to model the data distribution instead. In these settings, the compositional flow model can adopt cross-entropy loss to maximize the log-likelihood of sampling $C^{(\sigma_i)}$ at each step *i*, aligned with the valid generation order σ . The loss is:

$$\mathcal{L}_{\text{comp}} = -\mathbb{E}_{p_t(\boldsymbol{x}_t)} \sum_{i=1}^n \log \pi^{\theta}(\mathbf{C}^{(\sigma_i)} | \boldsymbol{x}_{t=t_{gen}^{(\sigma_i)}}),$$
(11)

where $\pi^{\theta}(\mathbf{C}^{(\sigma_i)}|\mathbf{x}_t)$ represents the policy model for generating the next compositional component $\mathbf{C}^{(\sigma_i)}$, conditioned on the entire object \mathbf{x}_t .

B THEORETICAL BACKGROUND

The object $x = (\mathcal{C}, \mathcal{S})$ is sequence data where $\mathcal{C} = (\mathbf{C}^{(i)})_{i=1}^n$ and $\mathcal{S} = (\mathbf{S}^{(i)})_{i=1}^n$. Therefore, we formulate the generative process as an auto-regressive process, i.e., $P_B(-|-) = 1.0$.

To train the compositional flow model with the trajectory balance (TB) objective, we must estimate forward transition probabilities along the trajectory $\tau = (\mathbf{x}_0 \to \mathbf{x}_{i\lambda} \to \cdots \to \mathbf{x}_{n\lambda} \to \mathbf{x}_1)$, where λ is the time interval between successive components $\mathbf{C}^{(\cdot)}$, and $n < 1/\lambda$ is the total number of components.

Since the state flow model $p_{1|t}^{\theta}$ introduces randomness in the initial state $S_0^{(i)} \sim \mathcal{N}(0, \sigma^2)$, estimating the forward transition probability involves integrating over this noise distribution as follows:

$$P_{F}\left(\boldsymbol{x}_{(i+1)\lambda} \middle| \boldsymbol{x}_{i\lambda}, \hat{\boldsymbol{x}}_{1}^{t}; \phi, p_{1|t}^{\theta}\right)$$
(12)
$$= P_{F}\left(\boldsymbol{C}^{(i)} \middle| \boldsymbol{x}_{i\lambda}, \hat{\boldsymbol{x}}_{1}^{t}; \phi\right) \int P\left(\boldsymbol{x}_{(i+1)\lambda} \middle| T(\boldsymbol{x}_{i\lambda}, \boldsymbol{C}^{(i)}, \boldsymbol{S}_{0}^{(i)}); p_{1|t}^{\theta}\right) p(\boldsymbol{S}_{0}^{(i)}) d\boldsymbol{S}_{0}^{(i)}$$
$$= P_{F}\left(\boldsymbol{C}^{(i)} \middle| \boldsymbol{x}_{i\lambda}, \hat{\boldsymbol{x}}_{1}^{t}; \phi\right) \int \delta\left(\Phi^{\theta}\left(T(\boldsymbol{x}_{i\lambda}, \boldsymbol{C}^{(i)}, \boldsymbol{S}_{0}^{(i)}), \lambda, \Delta t\right) = \boldsymbol{x}_{(i+1)\lambda}\right) p(\boldsymbol{S}_{0}^{(i)}) d\boldsymbol{S}_{0}^{(i)},$$
(13)

where Φ^{θ} is the ODE solver of the state flow model $p_{1|t}^{\theta}$. This integration induces a Dirac delta term, making direct probability estimation challenging.

Proposition B.1. Let the initial state $S_0^{(i)}$ be fixed⁴. Then, the object $x_t = (C_t, S_t)$ is uniquely determined by a given trajectory τ sampled from the compositional flow model π^{ϕ} .

Proof. When $S_0^{(i)}$ is fixed, the ODE solver fully specifies $S_{(i+1)\lambda}$ based on $S_{i\lambda}$, the self-conditioning \hat{x}_1^t , and the sampled component $C^{(i)}$. Consequently, the sequence $(C^{(1)}, \ldots, C^{(k(t))})$ directly determines S_t . Given that the generative progress is auto-regressive, there is a one-to-one correspondence between x_t and $(C^{(1)}, \ldots, C^{(k(t))})$ for every t.

Building on this determinism, we simplify the forward transition probability $P_F(\mathbf{x}_{(i+1)\lambda}|\mathbf{x}_{i\lambda;\phi;p_{1|t}^{\theta}})$ as:

$$P_F\left(\boldsymbol{x}_{(i+1)\lambda} \middle| \boldsymbol{x}_{i\lambda}, \hat{\boldsymbol{x}}_1^t; \phi, p_{1|t}^\theta\right) = P_F\left(\boldsymbol{C}^{(i)} \middle| \boldsymbol{x}_{i\lambda}, \hat{\boldsymbol{x}}_1^t; \phi\right)$$
(14)

This allows us to write the TB objective in a more tractable form:

$$\mathcal{L}_{\text{TB}}(\tau) = \left(\log \frac{Z_{\phi} \prod_{i=0}^{n-1} P_F(\boldsymbol{x}_{(i+1)\lambda} | \boldsymbol{x}_{i\lambda}; \phi, p_{1|t}^{\theta})}{R(\boldsymbol{x}_1) \prod_{i=0}^{n-1} P_B(\boldsymbol{x}_{i\lambda} | \boldsymbol{x}_{(i+1)\lambda}; \phi, p_{1|t}^{\theta})} \times \underbrace{P(\boldsymbol{x}_1 | \boldsymbol{x}_{n\lambda}; p_{1|t}^{\theta})}{P(\boldsymbol{x}_{n\lambda} | \boldsymbol{x}_1; p_{1|t}^{\theta})} \right)^2 = \left(\log \frac{Z_{\phi} \prod_{i=0}^{n-1} P_F(\boldsymbol{C}^{(i)} | \boldsymbol{x}_{i\lambda}; \phi)}{R(\boldsymbol{x}_1)} \right)^2.$$
(15)

By enforcing trajectory balance under these conditions, we ensure that the likelihood of sampling a final object x_1 is proportional to its reward $R(x_1)$, while sidestepping the complexities introduced by the continuous noise integration.

C EXTENDED RELATED WORKS

Sequential diffusion for molecular generation Peng et al. (2023); Ghorbani et al. (2023); Li et al. (2024) sequentially generate molecules fragment by fragment using diffusion models. These methods use a separate diffusion process to generate each 3D fragment graph, with atomic positions

⁴To minimize the influence of the fixed initial state value, we sample the initial state from the noise distribution using the manual random seed which is equal to the size of the current object, such as the number of atoms.

fixed post-generation. They also lack the ability to enforce compositional synthesis constraints during the generation process. Instead, 3DSynthFlow formulates a joint flow process: state flow refines all atomic positions throughout, mitigating the issue with cascading error in position prediction; composition flow sequentially constructs the synthesis pathway, effectively enforcing the synthesis constraint.

Structure-based drug design We categorize structure-based drug design (SBDD) in two main categories: pocket-specific and pocket-conditional following Seo et al. (2024).

The first approach optimizes docking scores for a target. Methods include evolutionary algorithms (Reidenbach, 2024), reinforcement learning (RL) (Zhavoronkov et al., 2019), and GFlowNets (Bengio et al., 2021; Pandey et al., 2025; Koziarski et al., 2024). The drawback of this approach is that each pocket must be optimized individually, which can restrict scalability.

In contrast, the pocket-conditional generation approach produces molecules tailored to any given pocket without the need for extra training. This strategy leverages distribution-based generative models (Ragoza et al., 2022; Peng et al., 2022; Guan et al., 2024; Schneuing et al., 2024b; Qu et al., 2024) that are trained on protein-ligand complex datasets to learn the distribution of ligands suitable for different pockets. Recently, Shen et al. (2024); Seo et al. (2024) adopted pocket-conditioned policy for GFlowNets that generates samples from reward-biased distributions in a zero-shot setting.

D 3DSYNTHFLOW DETAILS

D.1 ACTION SPACE

Following Cretu et al. (2024); Koziarski et al. (2024); Seo et al. (2024), we treat chemical reactions as forward transitions and synthetic pathways as trajectories for molecular generation.

Compared to previous methods, we represent a building block as *synthon*, which is not a complete molecule. The synthons can be connected at the *attachment point* according to the pre-defined connection rules, i.e., reactions \mathcal{R} (See Fig. 2). To prevent a generation trajectory terminating at an incomplete structure, we define two types of synthon according to Liu et al. (2017): *brick* is the synthon including one attachment point, and *linker* is the synthon including two attachment points.



Figure 4: Examples of brick and linker synthons.

We define \mathcal{B} as the entire synthon set, $\mathcal{B}' \subseteq \mathcal{B}$ as the brick synthon set, and $\mathcal{B}_r \subseteq \mathcal{B}$ as the allowable synthon set for reaction $r \in \mathcal{R}$.

At the initial state C_0 , the model always selects FirstSynthon, which samples a brick synthon b from the entire brick synthon set \mathcal{B}' to serve as the starting molecule. For subsequent states C_t , the model chooses AddSynthon, which firstly identifies the available reaction set $\mathcal{R}(C_t) \subseteq \mathcal{R}$ and then samples the synthon from the available synthon set $\cup_{r \in \mathcal{R}(C_t)} \mathcal{B}_r$. If the brick synthon is selected, the trajectory is terminated. When the trajectory reaches the maximum length, the model always selects a brick synthon.

In summary, the allowable action space $\mathcal{A}(\mathcal{C})$ for a given compositional state \mathcal{C} is:

$$\mathcal{A}(\mathcal{C}) = \begin{cases} \mathcal{B}' & \text{if } t = 1, \\ \bigcup_{r \in \mathcal{R}(\mathcal{C})} \mathcal{B}_r & \text{otherwise,} \end{cases}$$
(16)

D.2 3DSYNTHFLOW MODEL ARCHITECTURE

D.2.1 STATE FLOW MODEL

To model state flow for predicting ligand docking poses in 3DSynthFlow, we extend the *Semla* architecture introduced by Irwin et al. (2024). *Semla* is a scalable, E(3)-equivariant model originally

designed for 3D molecular generation; We refer reader to the original paper for full details. To adapt it for modeling 3D protein-ligand complexes, we incorporate protein encoding layers and protein-ligand message passing to capture interactions critical for binding, making the following modifications:

Let $P = \{1, ..., M\}$ index protein residues. Specifically, we use GVP Jing et al. (2021) to encode the protein pocket, producing an invariant feature vector for each residue $\mathbf{h}_i^{(\text{pro})} \in \mathbb{R}^d$, $\forall i \in P$. The protein residue embeddings, along with their original positions $\mathbf{x}_i^{(\text{pro})}$, are combined with the ligand atom embeddings $(\mathbf{h}_j^{(\text{lig})}, \mathbf{x}_j^{(\text{lig})})$ for pairwise message passing at each modified *Semla* layer $(i, j) \in V \times P$, defined as:

$$\left(\boldsymbol{m}_{i,j}^{\text{inv}}, \ \boldsymbol{m}_{i,j}^{\text{equi}}\right) = \Omega_{\theta}^{(pro-lig)} \left(\tilde{\boldsymbol{h}}_{i}, \ \tilde{\boldsymbol{h}}_{j}, \ \tilde{\boldsymbol{x}}_{i} \cdot \tilde{\boldsymbol{x}}_{j}\right), \tag{17}$$

where \tilde{h}_i and \tilde{x}_i are normalized linearly projected features. The protein-ligand messages are aggregated with the original ligand-ligand messages and used for attention-based updates. This formulation enables message exchange between residue nodes and atom nodes, ensuring that the model effectively learns protein-ligand interactions critical to binding.

Since the atom type and bond connections are generated by the compositional flow model instead of the state flow model, therefore they remain fixed throughout the process. This means we cannot use techniques such as equivariant-OT to reduce the transport cost Klein et al. (2023); Song et al. (2023), since they assume interchangeability between newly initialized nodes. We have also tried using harmonic prior from Jing et al. (2023); Stärk et al. (2024) to initialize position with bonding information as prior. We observed improved pose prediction with Gaussian noise during initial training, but no advantage of the harmonic prior over the Gaussian prior at convergence.

D.2.2 COMPOSITIONAL FLOW MODEL

We adopt a model architecture inspired by Bengio et al. (2021); Cretu et al. (2024); Seo et al. (2024), using a graph transformer (Yun et al., 2022) as the backbone f_{θ} , and a multi-layer perceptron (MLP) g_{θ} for action embedding. The graph embedding dimension is d_1 and the synthon embedding dimension is d_2 . The GFlowNet condition such as temperature β or multi-objective weights are encoded in condition vector c.

To capture spatial relationships between the protein and ligand, the model uses a 3D protein-ligand complex graph for each state. The protein is represented as a residual graph, where each node corresponds to a C_{α} atom and connects to its K-nearest neighbors. Each ligand atom also connects to its K-nearest protein nodes. All pairwise distances between nodes are encoded in the graph edges, enabling the model to reason about the 3D structure. We represent each state *s* as a molecular graph *s* and include a GFlowNet condition vector *c*.

Initial synthon selection. For the initial state $s = s_0$, the model always selects FirstSynthon to sample brick synthon $b \in \mathcal{B}'$ for the starting molecule with MLP_{AddSynthon} : $\mathbb{R}^{d^1} \to \mathbb{R}^{d^2}$.

$$F_{\theta}(s_0, b, c) = \mathrm{MLP}_{\mathrm{FirstSynthon}}(f_{\theta}(s_0, c)) \odot g_{\theta}(b)$$
(18)

Adding synthon selection. For the later states $s \neq s_0$, the model selects AddSynthon to sample allowable brick or linker synthon $b \in \bigcup_{r \in \mathcal{R}(s)} \mathcal{B}_r$ with MLP_{AddSynthon} : $\mathbb{R}^{d^1} \to \mathbb{R}^{d^2}$. We note that the reaction type information is included in synthon embedding:

$$F_{\theta}(s, (r, b), c) = \mathsf{MLP}_{\mathsf{AddSynthon}}(f_{\theta}(s, c)) \odot g_{\theta}(r, b)).$$
(19)

Synthon masking. The state flow model is trained on the data distribution of active ligands. This may sometimes not work well for out-of-distribution molecules that are much larger than the training data. Therefore, we restrict the actions which make the state to have more than 40 atoms. This process can be performed simply in a synthon-based action space.

E EXPERIMENTAL DETAILS

E.1 TRAINING DETAILS

E.1.1 3DSYNTHFLOW HYPERPARAMETERS

Table 3: **Default hyperparameters** used for compositional structure.

Hyperparameters	Values
Time per action λ	0.3
Interpolation window t_{window}	0.4
Maximum decomposed part	3
Minimum decomposed fragment size	5
Minimum trajectory length	2 (minimum reaction steps: 1)
Maximum trajectory length	3 (maximum reaction steps: 2)

Here we define the hyperparameters used for 3DSynthFlow:

- 1. Time per action (λ): Defines the time interval between adding each additional synthon.
- 2. Interpolation window (t_{window}) : Specifies the fixed time window that affects the noise scheduling of the continuous states of each component.
- 3. Maximum decomposed part: Determines the maximum number of synthons a molecule can be decomposed into, preventing molecules from being associated with excessive synthesis steps.
- 4. Minimum decomposed fragment size: Specifies the minimum number of atoms that each synthon product must contain when a molecule is decomposed according to reaction rules. This ensures that synthons are of realistic size when decomposing CrossDocked ligands for training a pose prediction model.
- 5. **Minimum trajectory length**: Defines the minimum trajectory length for sampling composition steps in 3DSynthFlow.
- 6. Maximum trajectory length: Specifies the maximum trajectory length that can be reached.

We further exam the effect of performance for different setting of time scheduling, varying λ and t_{window} in Appendix F.3.

Hyperparameters	Values
Number of protein layers	6
Noise prior	Gaussian
Time alpha α	1.0
Time beta β	1.0
Time step Δt	0.0125

Table 4: **Default hyperparameters** used for State flow model.

For parameterizing the state flow model for pose prediction, we use the same hyperparameter from the official repository ⁵. We show the additional hyperparameters in Table. 4 and provide an explanation for each below:

- 1. **Number of protein layers**: the number of layers with protein-ligand message passing. This must be less or equal to the total number of layers.
- 2. Noise prior: Defines the noise distribution which initial state values are drawn from.
- 3. **Time alpha**: Defines the alpha parameter of the Beta distribution which time is sampled from.
- 4. Time beta: Defines the beta parameter of the Beta distribution which time is sampled from.
- 5. **Time step**: Defines the time step for inference.

⁵Follow SemlaFlow's hyperparameter settings in train.py at https://github.com/rssrwn/ semla-flow/blob/main/semlaflow/train.py

_

Composition flow model In this work, we set most parameters to the default values⁶ for all GFlowNet baselines (Some of the parameters are in Table. 5). However, since 3DSynthFlow is built from RxnFlow, it follows some important parameters of RxnFlow except for maximum trajectory length and state embedding size. We note that our state embedding dimension is smaller than other GFlowNet baselines.

Table 5: Default hyperparameters used in all GFlowNets. The settings are from seh_frag.py (Bengio et al., 2021)

Hyperparameters	Values
GFN temperature β	Uniform(0, 64)
Sampling tau (EMA factor)	0.9
Learning rate (Z)	10^{-3}
Learning rate (P_F, P_B)	10^{-4}
State embedding dimension	128

Table 6: Specific hyperparameters used in 3DSynthFlow training. The parameters are from Rxn-Flow (Seo et al., 2024), except for the maximum trajectory length (4 for RxnFlow) and state embedding size (128 for RxnFlow and other GFlowNets).

Hyperparameters	Values
Minimum trajectory length Maximum trajectory length State embedding dimension Action embedding dimension Action space subsampling ratio	2 (minimum reaction steps: 1) 3 (maximum reaction steps: 2) 64 64 1%
Train random action probability	5%

For action space subsampling, we randomly subsample 1% actions for AddFirstReactant and each bi-molecular reaction template $r \in \mathcal{R}_2$. However, for bi-molecular reactions with small possible reactant block sets $\mathcal{B}_r \in \mathcal{B}$, the memory benefit from the action space subsampling is small while a variance penalty is large. Therefore, we set the minimum subsampling size to 100 for each bi-molecular reaction, and the action space subsampling is not performed when the number of actions is smaller than 100.

⁶Follow default hyperparameter settings in seh_frag.py and seh_frag_moo.py at https://github.com/recursionpharma/gflownet/blob/trunk/src/gflownet/tasks

The number of actions for each action type is imbalanced, and the number of reactant blocks (\mathcal{B}_r) for each bi-molecular reaction template r is also imbalanced. This can make some rare action categories not being sampled during training. We empirically found that ReactBi action were only sampled during 20,000 iterations (1.28M samples) in a toy experiment that uses one bi-molecular reaction template and 10,000 building blocks in some random seeds. Therefore, we set the random action probability as the default of 5%, and the model uniformly samples each action category in the random action sampling. This prevents incorrect predictions by ensuring that the model experiences trajectories including rare actions. We note that this random selection is only performed during model training.

E.1.2 DETAILS OF STATE FLOW MODEL TRAINING

To expose the state flow model to realistic partial ligand structures, we decompose each Cross-Docked ligand into up to three fragments using 38 bimolecular Enamine synthesis protocols, defined by reaction SMARTS patterns. For each molecule, we randomly select a fragment ordering and sample a time step t, so the model observes the molecule at varying stages of assembly (e.g., only fragment A at t = 1, fragments A and B at t = 2, etc.). This mimics the compositional assembly process used during generation and teaches the model to predict physically plausible docking conformations for incomplete ligands.

Importantly, the decomposition is not intended to yield commercially purchasable Enamine synthons. Instead, the use of Enamine protocols ensures the resulting fragments are chemically meaningful and synthetically relevant, even if they do not match existing catalog synthons. This allows us to use any CrossDocked molecule for training while staying aligned with the synthetic priors used at generation time.

Across the CrossDocked dataset, we find that over 93% of molecules can be decomposed into at least two fragments using this protocol, and over 87% can be decomposed into three. This high decomposition rate enables robust learning from partially constructed molecules and ensures strong coverage of fragment combinations encountered during inference.

E.1.3 TRAINING TIME AND COMPUTATIONAL EFFICIENCY

The state flow model (i.e., the pocket-conditional pose predictor) was trained for 100 epochs with a batch size of 32 on 4 L40 GPUs (48GB), requiring a total of 18.4 hours. Since the state flow model is trained on the CrossDocked dataset and is reused across different test pockets, it incurs only a one-time computational cost. We plan to release the pretrained weights, so that users will need to train only the composition flow model tailored to their custom reward function and target.

In contrast, the composition flow model is trained individually for each pocket for 1,000 steps with a batch size of 64 and 80 flow matching steps. Training with GPU-accelerated docking takes between 12 and 20 hours (depending on the target) on a single A4000 GPU (16GB), making the computational requirement accessible for most practical drug discovery campaigns. Moreover, the composition flow model can be trained in a pocket-conditioned manner to enable zero-shot molecule sampling for any target pocket, thereby converting the training into a one-time cost in this setting.

Table 7: Summary of Training Time for 3DSynthFlow Components.

Model Component	Hardware	Batch Size	Number of Iterations	Training Time
State Flow Model	$\begin{array}{c} 4 \times \text{L40} \ (\text{48GB}) \\ 1 \times \text{A4000} \ (\text{16GB}) \end{array}$	32	100 epochs	18.4 hours
Composition Flow Model		64	1,000 steps	12–20 hours

E.2 DATASETS

E.2.1 LIT-PCBA POCKETS

Table. 8 describes the protein information used in pocket-specific optimization with UniDock, which is performed on Sec. 6. We follow the same procedure used in pocket extraction for the CrossDock dataset: taking all residue of the protein within 10 Å radius to the reference ligand as the binding pocket.

2		•
Target	PDB Id	Target name
ADRB2	4ldo	Beta2 adrenoceptor
ALDH1	512m	Aldehyde dehydrogenase 1
ESR_ago	2p15	Estrogen receptor α with agonist
ESR_antago	2iok	Estrogen receptor α with antagonist
FEN1	5fv7	FLAP Endonuclease 1
GBA	2v3d	Acid Beta-Glucocerebrosidase
IDH1	4umx	Isocitrate dehydrogenase 1
KAT2A	5h86	Histone acetyltransferase KAT2A
MAPK1	4zzn	Mitogen-activated protein kinase 1
MTORC1	4dri	PPIase domain of FKBP51, Rapamycin
OPRK1	6b73	Kappa opioid receptor
PKM2	4jpg	Pyruvate kinase muscle isoform M1/M2
PPARG	5y2t	Peroxisome proliferator-activated receptor γ
TP53	3zme	Cellular tumor antigen p53
VDR	3a2i	Vitamin D receptor

Table 8: The basic target information of the LIT-PCBA dataset and PDB entry used in this work.

E.2.2 CROSSDOCKED2020

We train the State flow model of 3DSynthFlow on the commonly used **CrossDocked** dataset (Francoeur et al., 2020). We apply the splitting and processing protocol on the CrossDocked dataset to obtain the same training split of protein-ligand pairs as previous methods (Luo et al., 2021; Peng et al., 2022). To ensure fairness against baseline methods on the LIT-PCBA benchmark, we remove all PDB ids associated with LIT-PCBA proteins from the training set. Since we co-design 3D binding pose and synthesis pathway, unlike the pervious 2D-based methods, we can leverage this dataset for training the auxiliary State flow pose prediction model.

E.3 BASELINES

SynNet, BBAR We reused the values reported in Seo et al. (2024).

FragGFN, RGFN, RxnFlow. All GFlowNet baselines share the same training parameters under the multi-objective GFlowNet (Jain et al., 2023b) setting. We also reused the values reported in Seo et al. (2024).

SynFlowNet. There are two versions for SynFlowNet (Cretu et al., 2024): 2024.3 and 2024.8. For version 2024.3, we reused the values in Seo et al. (2024). For version 2024.8, we followed the processes and settings according to the original paper and official code repository ⁷. To construct the action space, we randomly selected 10,000 building blocks from Enamine Global Stock (v2025.01.11) with 105 reaction templates. We trained SynFlowNet using backward policy learning maximum likelihood, maximum trajectory length to 3, and action embedding with Morgan finger-print (Morgan, 1965). Finally, we set the training parameters used in other GFlowNet baselines (See Table. 5). The training code and data used in the benchmark study are included in the supplementary materials.

F ADDITIONAL RESULTS

F.1 REWARD COMPUTATION WITHOUT FULL DOCKING

The most computational and time-intensive process in the training process is often docking the generated candidates with molecular docking for evaluation. Glide, a standard docking software in the industry, takes around 6 minutes per compound in its most accurate setting Friesner et al. (2004). This constraint necessitates either reducing the number of Oracle queries or trading speed for less accurate docking settings. Docking scores are typically computed via **Full docking**, which

⁷Follow SynFlowNet's hyperparameter settings in reactions_task.py at https://github.com/ mirunacrt/synflownet/tree/46a4acabd2255eb964c317ffbb86b743a13a4685

Method	Reward setting	Docking score (\downarrow)
RxnFlow	Full docking	$-11.26 (\pm 0.07)$
3DSynthFlow	Full docking	$-11.97 (\pm 0.07)$
3DSynthFlow	Local opt.	$-11.44 \ (\pm 0.06)$
3DSynthFlow _{finetuned}	Local opt.	$-11.62 (\pm 0.02)$

Table 9: Ablation study on reward setting for Vina docking scores. Evaluated on the ADH1 pocket. Results are averaged over 3 runs.

performs a full search for the optimal binding pose at a high computational cost. However, it can also be computed via **Local optimization** for significantly faster computation, if an existing binding pose is available. ⁸

In this setting, we investigate directly using the final predicted pose from 3DSynthFlow to compute reward using local optimization compared to using the full docking score. In the 3DSynthFlow finetuned setting for local opt., we first finetune the pose predictor on re-docked poses from the first 9,600 sampled molecules to improve binding pose prediction, thereby enabling accurate local optimization docking scores.

From Table. 9, we see that regardless of the scoring function used or whether we perform fine tuning, 3DSynthFlow outperformed the best 2D baseline RxnFlow, confirming the benefit of 3D structure co-design. Interestingly, 3DSynthFlow using local opt. do not perform as well as 3DSynthFlow trained with signals from full docking in both settings. While fine tuning the pose prediction module helps, the gap between full docking and local opt. is not fully closed. Empirically, we find the poses predicted from 3DSynthFlow sometimes contain steric clashes, leading to inaccurate estimation of the reward signal. Accordingly, improving the pose prediction module emerges as a key next step to reduce steric clashes and enhance the accuracy of local optimization docking scores, as disccussed in Sec. 7.

By co-designing binding pose and molecule, 3DSynthFlow using local opt. can bypass the computational burden of full docking which 2D generative methods are subjected to, while surpassing their performance. This is a key advantage for 3DSynthFlow in cases where accurate full docking is prohibitively expensive for a large number of ligands.

F.2 EFFECT OF FLOW MATCHING STEPS

n seconds per iteration, and sampling time is reported in seconds per molecule.						
Flow Matching Steps	Avg Vina (\downarrow)	Top 100 Vina (\downarrow)	Training Time (sec/iter)	Sampling Time (sec/mol)		
10	-10.28 ± 0.32	-14.27 ± 0.59	33	0.053		
20	-10.24 ± 0.18	-14.38 ± 0.22	34	0.080		
40	-10.40 ± 0.13	-14.51 ± 0.27	39	0.123		
60	-10.50 ± 0.14	-14.57 ± 0.24	44	0.160		
80	-10.44 ± 0.18	-14.53 ± 0.16	49	0 199		

Table 10: Effect of flow matching steps on performance for the ALDH1 target with the Vina reward. We report both the average docking score (Avg Vina) over all generated molecules and the top 100 docking scores (Top 100 Vina), with lower values indicating better binding. Training time is reported in seconds per iteration, and sampling time is reported in seconds per molecule.

We further analyzed how the number of flow matching steps impacts performance using the ALDH1 target with the Vina reward. As shown in Table 10, performance slightly improves with increasing flow matching steps and appears to saturate around 40–60 steps. This marginal improvement may stem from the fact that the pose prediction module's primary role is to provide a spatial context between intermediate molecules and the pocket; hence, extremely precise pose predictions have limited additional impact on model decisions.

⁸Scoring a predicted pose using the local-optimization setting in AutoDock Vina is 7× faster than performing full docking. This speedup is even greater for more accurate docking programs, since the vast majority of time is spent on pose searching rather than scoring.

F.3 ABLATION STUDY ON TIME SCHEDULING OF 3DSYNTHFLOW

We conducted an ablation study to assess the effect of time scheduling in state flow training. Specifically, we compared three scheduling strategies:

- No overlap: strictly autoregressive denoising each synthon denoised after the previous one is completed. ($\lambda = 0.33, t_{window} = 0.33$).
- **Overlapping**: partial overlap of synthon denoising ($\lambda = 0.3, t_{window} = 0.4$).

To highlight the impact of noise scheduling on the final pose, we report the average local-optimized Vina docking scores across different training iterations for the ALDH1 target over 3 seeds:

# of mol explored	10,000	20,000	30,000
No overlap Overlapping	$\begin{array}{c} -5.68 \pm 0.29 \\ -6.28 \pm 0.22 \end{array}$	$-6.33 \pm 0.26 \\ -7.28 \pm 0.21$	$-7.02 \pm 0.34 \\ -7.22 \pm 0.12$

Table 11: Ablation study on time scheduling for state flow training on the ALDH1 target.

3DSynthFlow 's **overlapping** strategy, where positions are refined as synthons are added, clearly outperforms conventional autoregressive approaches - **No overlap**, adopted in previous works (See Appendix C).

F.4 STATE SPACE SIZE ESTIMATION

We estimate the sample space size based on the number of synthetic steps: 10^{11} molecules with a single reaction step, 10^{17} molecules with two reaction steps, and 10^{23} molecules with three reaction steps. In our experiments, we employed up to two reaction steps according to Enamine REAL. The resulting state space size is comparable to RGFN (up to 4 steps with 8,350 blocks) and SynFlowNet (up to 3 steps with 200k blocks).

To assess the breadth of building block (BB) exploration, we analyzed the number of unique BBs encountered during training across the first five LIT-PCBA targets. Our model explored an average of approximately 55,000 unique BBs within 1,000 training iterations using a batch size of 64. This indicates significantly broader exploration compared to SynFlowNet, which reported around 15,000 unique BBs over 8,000 iterations with a batch size of 8.

Table 12: Number of unique building blocks explored during training across 5 LIT-PCBA targets.

Target	ADRB2	ALDH1	ESR_ago	ESR_antago	FEN1
Number of Unique BBs	45520 ± 7876	48644 ± 1983	55211 ± 5611	58097 ± 8529	69400 ± 5259

F.5 POSECHECK PROTEIN-LIGAND INTERACTIONS

Table 13:	PoseCheck p	rotein-ligand	interactions.	We r	report	two	versions	of S	SynFlowNe	et
(v2024.05 ^a	and $v2024.10^{b}$)	. Averages and	d standard dev	viations	over	3 run	s, for the	top	100 divers	se
modes per l	LIT-PCBA pocke	et. The best res	sults in each c	olumn	are in	bold				

	PoseCheck Metrics ([†])							
Method	H-Bond Acceptors	H-Bond Donors	Van der Waals	Hydrophobic	Sum			
SynFlowNet ^a	$0.22~(\pm 0.01)$	0.11 (± 0.01)	9.31 (± 0.05)	10.41 (± 0.05)	20.05			
SynFlowNet ^b	$0.22 \ (\pm 0.03)$	$0.10 \ (\pm \ 0.01)$	8.38 (± 0.05)	$9.44 (\pm 0.06)$	18.14			
RGFN	$0.19~(\pm 0.01)$	$0.11 \ (\pm \ 0.01)$	$9.19 (\pm 0.28)$	$10.25~(\pm 0.12)$	19.73			
RxnFlow	$0.22~(\pm 0.00)$	$0.10 \ (\pm \ 0.01)$	9.63 (± 0.09)	$10.67 (\pm 0.10)$	20.62			
3DSynthFlow	0.27 (± 0.03)	$0.12 (\pm 0.01)$	$10.33 (\pm 0.13)$	$11.15 (\pm 0.05)$	21.87			

Lastly, we evaluate the protein-ligand interactions of the top 100 generated molecules using PoseCheck Harris et al. (2023). Since baselines do not generate 3D poses, we assess all methods using their redocked structures for consistency. PoseCheck evaluates four key protein-ligand interactions: H-bond acceptors, H-bond donors, van der Waals contacts, and hydrophobic effects.

Hydrogen bonds (H-bonds) are the most important specific interactions in protein-ligand recognition Bissantz et al. (2010) and require precise geometric alignment to form Brown (1976). Unlike hydrophobic and van der Waals interactions, which are non-directional and broadly applicable, Hbonds require strict atomic alignment, reinforcing the need for accurate 3D molecular modeling.

Notably, 3DSynthFlow achieves the highest H-bond acceptor and donor counts, outperforming all baselines. This improvement suggests that co-designing 3D structure and synthesis pathways enhances the geometric alignment of polar functional groups, leading to more stable and specific protein-ligand interactions. In addition, 3DSynthFlow-generated molecules also result in more hydrophobic and van der Waals interactions to baselines, as shown in Table. 13, further enhancing binding stability.

F.6 SYNTHESIS SUCCESS RATE RESULT ON LIT-PCBA

Table 14:	The average	success ra	te and	synthetic	steps	estimated	from	AiZynthF	inder	for	all	15
LIT-PCBA	protein target	ts.										

Method	Success Rate (%, \uparrow)	Synthesis Steps (\downarrow)
FragGFN+SA	3.52	3.74
SynNet	47.50	3.45
BBAR	17.92	3.68
SynFlowNet ^a	54.60	2.55
SynFlowNet ^b	58.38	2.47
RGFN	47.43	2.46
RxnFlow	65.35	2.17
3DSynthFlow	48.04	3.15

Table. 14 shows that 3DSynthFlow attains comparable synthesizability to 2D baselines, demonstrating its generated molecules remain likely to be synthesizable. While the main contribution of our work is 3D co-design rather than improving synthesizability, these results confirm that our synthonbased 3D generation remains effective, with minimal trade-offs in synthetic feasibility.

F.7 FULL SAMPLING EFFICIENCY RESULTS

			Number of Molecules Explored					
Target	Method	1,000	5,000	10,000	30,000	64,000		
ADRB2	RxnFlow 3DSynthFlow	3.0 (±1.4) 16.0 (±5.7)	21.5 (± 4.9) 124.0 (± 2.8)	52.0 (± 24.0) 318.5 (± 60.1)	500.0 (± 137.2) 1609.5 (± 939.7)	1282.5 (± 234.1) 5378.0 (±1492.0)		
ALDH1	RxnFlow 3DSynthFlow	$\begin{array}{c} 4.5 \ (\pm 2.1) \\ 10.0 \ (\pm 5.7) \end{array}$	$\begin{array}{c} 26.5 \ (\pm \ 7.8) \\ \textbf{198.0} \ (\pm 83.4) \end{array}$	73.5 (± 33.2) 623.0 (±291.3)	472.5 (± 99.7) 3069.5 (±1885.9)	$\begin{array}{r} 1240.0 (\pm \ 75.0) \\ \textbf{8838.0} \ (\pm 5152.0) \end{array}$		
ESR_ago	RxnFlow 3DSynthFlow	5.0 (±4.2) 8.0 (±4.2)	17.0 (± 4.2) 51.0 (± 2.8)	44.0 (± 8.5) 234.5 (±174.7)	$\begin{array}{rrr} 440.5 (\pm & 60.1) \\ 1498.0 (\pm 1306.7) \end{array}$	1174.0 (± 100.4) 3738.0 (±1861.1)		
ESR_antago	RxnFlow 3DSynthFlow	3.0 (±2.8) 6.5 (±7.8)	$\begin{array}{l} 14.5 \ (\pm \ 0.7) \\ \textbf{53.5} \ (\pm \ 9.2) \end{array}$	$\begin{array}{rrr} 28.0 (\pm & 0.0) \\ 184.5 (\pm & 40.3) \end{array}$	218.0 (± 21.2) 1083.5 (± 113.8)	559.0 (± 50.9) 3010.0 (± 264.5)		
FEN1	RxnFlow 3DSynthFlow	3.5 (±0.7) 10.0 (±4.2)	29.0 (±18.4) 92.0 (±97.6)	75.5 (± 57.3) 219.5 (±195.9)	372.0 (± 46.7) 774.5 (± 323.1)	1057.5 (± 38.9) 3276.5 (± 451.8)		
Average	RxnFlow 3DSynthFlow	3.8 10.1	21.7 103.7	54.6 316.0	400.6 1607.0	1062.6 4848.1		

Table 15: Average number of diverse modes discovered versus the number of molecules explored. The best results are in bold.

F.8 FULL RESULTS FOR LIT-PCBA TARGET

		Average Vina Docking Score (kcal/mol, \downarrow)					
Category	Method	ADRB2	ALDH1	ESR_ago	ESR_antago	FEN1	
	FragGFN	$-10.19 (\pm 0.33)$	-10.43 (± 0.29)	-9.81 (± 0.09)	-9.85 (± 0.13)	$-7.67 (\pm 0.71)$	
Fragment	FragGFN+SA	$-9.70 (\pm 0.61)$	$-9.83 (\pm 0.65)$	$-9.27~(\pm 0.95)$	$-10.06 \ (\pm \ 0.30)$	$-7.26 (\pm 0.10)$	
	SynNet	$-8.03 (\pm 0.26)$	$-8.81 (\pm 0.21)$	$-8.88 (\pm 0.13)$	$-8.52 (\pm 0.16)$	$-6.36 (\pm 0.09)$	
	BBAR	$-9.95 (\pm 0.04)$	$-10.06 (\pm 0.14)$	$-9.97 (\pm 0.03)$	$-9.92 (\pm 0.05)$	$-6.84 (\pm 0.07)$	
Reaction	SynFlowNet ^a	$-10.85 (\pm 0.10)$	$-10.69 (\pm 0.09)$	$-10.44 (\pm 0.05)$	$-10.27 (\pm 0.04)$	$-7.47 (\pm 0.02)$	
Reaction	SynFlowNet ^b	-9.17 (± 0.68)	-9.37 (± 0.29)	-9.17 (± 0.12)	-9.05 (± 0.14)	$-6.45 (\pm 0.13)$	
	RGFN	$-9.84 (\pm 0.21)$	$-9.93 (\pm 0.11)$	-9.99 (± 0.11)	-9.72 (± 0.14)	$-6.92 (\pm 0.06)$	
	RxnFlow	$-11.45 (\pm 0.05)$	$-11.26 (\pm 0.07)$	$-11.15 (\pm 0.02)$	$-10.77 (\pm 0.04)$	$-7.66 (\pm 0.02)$	
3D Reaction	3DSynthFlow	-11.97 (± 0.17)	-12.25 (± 0.43)	-11.31 (± 0.07)	-11.25 (± 0.12)	-7.92 (± 0.07)	
		GBA	IDH1	KAT2A	MAPK1	MTORC1	
	FragGFN	$-8.76 (\pm 0.46)$	$-9.91 (\pm 0.32)$	$-9.27 (\pm 0.20)$	$-8.93 (\pm 0.18)$	$-10.51 (\pm 0.31)$	
Fragment	FragGFN+SA	$-8.92 (\pm 0.27)$	$-9.76 (\pm 0.64)$	$-9.14 (\pm 0.43)$	$-8.28 (\pm 0.40)$	$-10.14 (\pm 0.30)$	
	SynNet	-7.60 (± 0.09)	$-8.74 (\pm 0.08)$	$-7.64 (\pm 0.38)$	$-7.33 (\pm 0.14)$	$-9.30 (\pm 0.45)$	
	BBAR	$-8.70 (\pm 0.05)$	$-9.84 (\pm 0.09)$	$-8.54 (\pm 0.06)$	$-8.49 (\pm 0.07)$	$-10.07 (\pm 0.16)$	
Reaction	SynFlowNet ^a	$-9.27 (\pm 0.06)$	$-10.40 (\pm 0.08)$	$-9.41 (\pm 0.04)$	$-8.92 (\pm 0.05)$	$-10.84 (\pm 0.03)$	
Reaction	SynFlowNet ^b	-8.28 (± 0.15)	-9.18 (± 0.35)	$-8.06 (\pm 0.15)$	$-7.89 (\pm 0.13)$	$-9.60 (\pm 0.16)$	
	RGFN	$-8.48 (\pm 0.06)$	$-9.49 (\pm 0.13)$	$-8.53 (\pm 0.11)$	$-8.22 (\pm 0.15)$	$-9.89 (\pm 0.06)$	
	RxnFlow	$-9.62 (\pm 0.04)$	$-10.95~(\pm 0.05)$	$-9.73 (\pm 0.03)$	$-9.30 (\pm 0.01)$	$-11.39 (\pm 0.09)$	
3D Reaction	3DSynthFlow	-9.89 (± 0.22)	-11.42 (± 0.26)	-10.19 (± 0.19)	-9.69 (± 0.15)	-12.03 (± 0.27)	
		OPRK1	PKM2	PPARG	TP53	VDR	
Engenerat	FragGFN	-10.28 (± 0.15)	-11.24 (± 0.27)	$-9.54 (\pm 0.12)$	$-7.90 (\pm 0.02)$	-10.96 (± 0.06)	
Fragment	FragGFN+SA	$-9.58 (\pm 0.44)$	$-10.83 (\pm 0.34)$	$-9.19 \ (\pm \ 0.29)$	$-7.61 (\pm 0.27)$	$-10.66 \ (\pm \ 0.61)$	
	SynNet	$-8.70 (\pm 0.36)$	-9.55 (± 0.14)	-7.47 (± 0.34)	$-5.34 (\pm 0.23)$	$-10.98 (\pm 0.57)$	
	BBAR	$-9.84 (\pm 0.10)$	$-11.39 (\pm 0.08)$	$-8.69 (\pm 0.10)$	$-7.05~(\pm 0.09)$	$-11.07 (\pm 0.04)$	
Reaction	SynFlowNet ^a	$-10.34 (\pm 0.07)$	-11.98 (± 0.12)	$-9.40 (\pm 0.05)$	$-7.90 (\pm 0.10)$	$-11.62 (\pm 0.13)$	
Reaction	SynFlowNet ^b	$-9.36 (\pm 0.25)$	$-10.64 (\pm 0.19)$	$-8.25 (\pm 0.10)$	$-6.84 (\pm 0.06)$	$-10.32 (\pm 0.07)$	
	RGFN	$-9.61 (\pm 0.11)$	$-10.96 (\pm 0.18)$	$-8.53 (\pm 0.07)$	$-7.07 (\pm 0.06)$	$-10.86 (\pm 0.11)$	
	RxnFlow	$-10.84 \ (\pm 0.03)$	$-12.53 (\pm 0.02)$	$-9.73 (\pm 0.02)$	$-8.09 (\pm 0.06)$	$-12.30 (\pm 0.07)$	
3D Reaction	3DSynthFlow	-11.22 (± 0.12)	-13.73 (± 0.25)	-10.26 (± 0.14)	-8.49 (± 0.27)	-12.97 (± 0.20)	

 Table 16:
 Average Vina docking score for top-100 diverse modes generated against 15 LIT-PCBA targets. The best results are in bold.

		Average Ligand Efficiency (\downarrow)						
Category	Method	ADRB2	ALDH1	ESR_ago	ESR_antago	FEN1		
	FragGFN	$0.410 (\pm 0.006)$	$0.368 (\pm 0.007)$	$0.347 (\pm 0.003)$	$0.358 (\pm 0.002)$	$0.246 (\pm 0.004)$		
Fragment	FragGFN+SA	$0.406 (\pm 0.007)$	$0.374 (\pm 0.023)$	$0.369 \ (\pm \ 0.003)$	$0.345 (\pm 0.024)$	$0.210 (\pm 0.004)$		
	SynNet	$0.274~(\pm 0.041)$	$0.272 (\pm 0.006)$	$0.317 (\pm 0.005)$	$0.289 \ (\pm 0.020)$	$0.196 \ (\pm \ 0.003)$		
	BBAR	$0.412 \ (\pm 0.006)$	$0.401 \ (\pm 0.008)$	$0.380 \ (\pm \ 0.001)$	$0.387~(\pm 0.003)$	$0.257 (\pm 0.003)$		
Reaction	SynFlowNet ^a	$0.401 \ (\pm 0.006)$	$0.380 (\pm 0.007)$	$0.361 (\pm 0.003)$	$0.361 (\pm 0.004)$	$0.247 (\pm 0.004)$		
recuellon	Synflownet ^b	$0.380 (\pm 0.021)$	$0.362 (\pm 0.016)$	$0.351 \ (\pm \ 0.008)$	$0.349 \ (\pm 0.005)$	$0.234 (\pm 0.007)$		
	RGFN	$0.393 (\pm 0.005)$	$0.357 (\pm 0.004)$	$0.346 (\pm 0.002)$	$0.344 (\pm 0.002)$	$0.241 (\pm 0.001)$		
	RxnFlow	$0.412 (\pm 0.005)$	$0.396 (\pm 0.005)$	$0.375 (\pm 0.002)$	$0.380 (\pm 0.004)$	$0.246~(\pm 0.001)$		
3D Reaction	3DSynthFlow	$0.438~(\pm~0.015)$	$0.409 (\pm 0.020)$	$0.385 (\pm 0.006)$	$0.396 (\pm 0.010)$	$0.247 (\pm 0.000)$		
		GBA	IDH1	KAT2A	MAPK1	MTORC1		
F (FragGFN	0.333 (± 0.018)	0.367 (± 0.009)	0.322 (± 0.008)	0.302 (± 0.002)	0.354 (± 0.005)		
Fragment	FragGFN+SA	$0.318 \ (\pm \ 0.005)$	$0.369 \ (\pm \ 0.020)$	$0.298 (\pm 0.020)$	$0.294 \ (\pm \ 0.015)$	$0.355 (\pm 0.027)$		
	SynNet	$0.244~(\pm 0.013)$	$0.281 \ (\pm \ 0.016)$	$0.294 \ (\pm \ 0.042)$	$0.226~(\pm 0.004)$	$0.316\ (\pm\ 0.035)$		
	BBAR	$0.336 (\pm 0.002)$	$0.382 (\pm 0.005)$	$0.332 (\pm 0.003)$	$0.320 \ (\pm \ 0.002)$	$0.385~(\pm 0.004)$		
Reaction	SynFlowNet ^a	$0.330 (\pm 0.004)$	$0.368 (\pm 0.002)$	$0.327~(\pm 0.003)$	$0.305~(\pm 0.002)$	$0.368 (\pm 0.002)$		
reaction	SynFlowNet ^b	$0.324 (\pm 0.007)$	$0.360 (\pm 0.013)$	$0.309 (\pm 0.004)$	$0.297~(\pm 0.011)$	$0.361 (\pm 0.009)$		
	RGFN	$0.310 (\pm 0.002)$	$0.351 (\pm 0.003)$	$0.310 (\pm 0.003)$	$0.298~(\pm 0.002)$	$0.346 (\pm 0.004)$		
	RxnFlow	$0.327 (\pm 0.004)$	$0.378 (\pm 0.001)$	$0.330 (\pm 0.001)$	$0.313 (\pm 0.001)$	$0.370 (\pm 0.001)$		
3D Reaction	3DSynthFlow	$0.344~(\pm~0.021)$	$0.394 (\pm 0.012)$	$0.322 \ (\pm \ 0.010)$	$0.314\;(\pm\;0.012)$	$0.376 (\pm 0.009)$		
		OPRK1	PKM2	PPARG	TP53	VDR		
F (FragGFN	0.352 (± 0.004)	$0.442 (\pm 0.008)$	0.319 (± 0.007)	$0.307 (\pm 0.005)$	0.394 (± 0.006)		
Fragment	FragGFN+SA	$0.327~(\pm 0.014)$	$0.440 \ (\pm 0.009)$	$0.303 \ (\pm \ 0.013)$	$0.248~(\pm 0.025)$	$0.390 \ (\pm \ 0.020)$		
	SynNet	$0.298 (\pm 0.039)$	$0.296 (\pm 0.005)$	$0.253 (\pm 0.031)$	$0.211 \ (\pm \ 0.031)$	$0.359 (\pm 0.015)$		
	BBAR	$0.370 (\pm 0.006)$	$0.442 (\pm 0.004)$	$0.326~(\pm 0.007)$	$0.288~(\pm 0.005)$	$0.409 \ (\pm 0.002)$		
Reaction	SynFlowNet ^a	$0.359 (\pm 0.004)$	$0.427~(\pm 0.003)$	$0.317 (\pm 0.002)$	$0.287~(\pm 0.008)$	$0.393 \ (\pm 0.003)$		
Reaction	SynFlowNet ^b	$0.355~(\pm 0.008)$	$0.410 \ (\pm \ 0.018)$	$0.296 \ (\pm \ 0.010)$	$0.282~(\pm 0.005)$	$0.380 \ (\pm \ 0.005)$		
	RGFN	$0.349 \ (\pm \ 0.001)$	$0.405~(\pm 0.002)$	$0.307~(\pm 0.002)$	$0.271~(\pm 0.001)$	$0.381~(\pm 0.002)$		
	RxnFlow	$0.369 \ (\pm 0.007)$	$0.436~(\pm 0.005)$	$0.319 \ (\pm \ 0.002)$	$0.289~(\pm 0.003)$	$0.405~(\pm 0.002)$		
3D Reaction	3DSynthFlow	$0.373 (\pm 0.015)$	0.460 (± 0.019)	$0.328 (\pm 0.007)$	0.293 (± 0.013)	$0.408 (\pm 0.012)$		

Table 17: Average ligand efficiency for top-100 diverse modes generated against 15 LIT-PCBAtargets. The best results are in bold.

		AiZynthFinder Success Rate (%, ↑)						
Category	Method	ADRB2	ALDH1	ESR_ago	ESR_antago	FEN1		
Fragment	FragGFN FragGFN+SA	$4.00 (\pm 3.54)$ 5.75 (± 1.48)	$3.75 (\pm 1.92)$ $6.00 (\pm 2.55)$	$1.00 (\pm 1.00)$ $4.00 (\pm 2.24)$	$3.75 (\pm 1.92)$ $1.00 (\pm 0.00)$	$\begin{array}{rrrr} 0.25 (\pm & 0.43) \\ 0.00 (\pm & 0.00) \end{array}$		
	SynNet	54.17 (+ 7.22)	50.00 (+ 0.00)	50.00 (+ 0.00)	25.00 (+ 25.00)	50.00 (+ 0.00)		
	BBAR	$21.25 (\pm 5.36)$	$19.50 (\pm 3.00)$	$17.50 (\pm 1.50)$	$19.50 (\pm 3.64)$	$20.00(\pm 2.12)$		
	SvnFlowNet ^a	$52.75 (\pm 1.09)$	$57.00 (\pm 6.04)$	$53.75 (\pm 9.52)$	$56.50 (\pm 2.29)$	$53.00 (\pm 8.92)$		
Reaction	SynFlowNet ^b	$56.50 (\pm 6.58)$	$56.00 (\pm 3.08)$	$61.00 (\pm 2.74)$	$64.50 (\pm 9.86)$	$60.75 (\pm 3.77)$		
	RGFN	$46.75 (\pm 6.86)$	$47.50 (\pm 4.06)$	$50.25 (\pm 2.17)$	$49.25 (\pm 4.38)$	$48.50 (\pm 6.58)$		
	RxnFlow	60.25 (± 3.77)	63.25 (± 3.11)	71.25 (± 4.15)	66.50 (± 4.03)	65.50 (± 4.09)		
3D Reaction	3DSynthFlow	$47.67 \ (\pm \ 19.15)$	$49.33\ (\pm\ 3.40)$	$50.33 (\pm 5.73)$	$61.33\ (\pm\ 5.56)$	52.67 (± 5.79)		
		GBA	IDH1	KAT2A	MAPK1	MTORC1		
F (FragGFN	5.00 (± 4.24)	$4.50 (\pm 1.66)$	$1.25 (\pm 0.83)$	$0.75 (\pm 0.83)$	$2.75 (\pm 1.30)$		
Fragment	FragGFN+SA	3.00 (± 1.00)	4.50 (± 4.97)	1.50 (± 0.50)	3.25 (± 1.48)	3.50 (± 2.50)		
	SynNet	50.00 (± 0.00)	50.00 (± 0.00)	45.83 (± 27.32)	50.00 (± 0.00)	54.17 (± 7.22)		
	BBAR	17.75 (± 2.28)	$19.50 (\pm 1.50)$	18.75 (± 1.92)	$16.25 (\pm 3.49)$	18.75 (± 3.90)		
Peaction	SynFlowNet ^a	$58.00 (\pm 4.64)$	$59.00 (\pm 4.06)$	55.50 (± 10.23)	$47.25 (\pm 6.61)$	57.00 (± 7.58)		
Reaction	SynFlowNet ^b	$61.50 (\pm 3.84)$	$60.50 (\pm 3.91)$	57.25 (± 4.97)	44.50 (± 9.29)	62.00 (± 1.22)		
	RGFN	48.00 (± 1.22)	43.00 (± 2.74)	49.00 (± 1.22)	$42.00 (\pm 3.00)$	44.50 (± 4.03)		
	RxnFlow	66.00 (± 1.58)	64.00 (± 5.05)	66.50 (± 2.06)	63.00 (± 4.64)	70.50 (± 2.87)		
3D Reaction	3DSynthFlow	$51.50\;(\pm\;12.08)$	$50.50 (\pm 7.79)$	$38.67 (\pm 9.10)$	$48.00 (\pm 18.24)$	$34.00 \ (\pm \ 7.87$		
		OPRK1	PKM2	PPARG	TP53	VDR		
F (FragGFN	2.50 (± 2.29)	8.75 (± 3.11)	$0.75 (\pm 0.43)$	4.25 (± 1.64)	3.50 (± 2.18)		
Fragment	FragGFN+SA	3.25 (± 1.79)	$9.75 (\pm 2.28)$	$1.25 (\pm 1.09)$	$2.25~(\pm 1.92)$	3.75 (± 2.77)		
	SynNet	54.17 (± 7.22)	50.00 (± 0.00)	54.17 (± 7.22)	29.17 (± 18.16)	45.83 (± 7.22)		
	BBAR	$13.75 (\pm 3.11)$	$20.00 (\pm 0.71)$	15.50 (± 2.29)	$18.50 (\pm 3.28)$	12.25 (± 3.34)		
Reaction	SynFlowNet ^a	$56.50 (\pm 7.63)$	50.75 (± 1.09)	$53.50 (\pm 5.68)$	55.50 (± 9.94)	53.50 (± 1.80)		
Reaction	SynFlowNet ^b	56.25 (± 2.49)	58.00 (± 7.00)	57.00 (± 5.74)	$66.50 (\pm 6.80)$	53.50 (± 3.84)		
	RGFN	48.00 (± 2.55)	$48.50 (\pm 3.20)$	$47.00 (\pm 5.83)$	53.25 (± 3.63)	$46.50 (\pm 2.69)$		
	RxnFlow	72.25 (± 2.05)	62.00 (± 3.24)	$65.50 (\pm 4.03)$	67.50 (± 2.96)	$66.75 (\pm 2.28)$		
3D Reaction	3DSvnthFlow	43.67 (± 2.36)	54.67 (± 13.42)	$41.00 (\pm 2.94)$	$49.33 (\pm 13.42)$	$49.00 (\pm 19.87)$		

Table 18: Average success rate of AiZynthFinder for top-100 diverse modes generated against 15LIT-PCBA targets. The best results are in bold.

		Average Number of Synthesis Steps (\downarrow)						
Category	Method	ADRB2	ALDH1	ESR_ago	ESR_antago	FEN1		
Fragmant	FragGFN	3.60 (± 0.10)	3.83 (± 0.08)	3.76 (± 0.20)	3.76 (± 0.16)	$3.34 (\pm 0.18)$		
Tuginent	FragGFN+SA	$3.73 (\pm 0.09)$	$3.66 (\pm 0.04)$	$3.66 (\pm 0.07)$	$3.67 (\pm 0.21)$	$3.79 (\pm 0.19)$		
	SynNet	$3.29 (\pm 0.36)$	$3.50 \ (\pm 0.00)$	$3.00 (\pm 0.00)$	$4.13 (\pm 0.89)$	$3.50 (\pm 0.00)$		
	BBAR	$3.60 (\pm 0.17)$	$3.62 (\pm 0.19)$	$3.76 (\pm 0.04)$	$3.72 (\pm 0.11)$	$3.59 (\pm 0.14)$		
Reaction	SynFlowNet ^a	$2.64 (\pm 0.07)$	$2.48 (\pm 0.07)$	$2.60 (\pm 0.25)$	$2.45 (\pm 0.09)$	$2.56 (\pm 0.29)$		
Redetion	SynFlowNet ^b	$2.42 (\pm 0.10)$	$2.48 (\pm 0.10)$	$2.38 (\pm 0.10)$	$2.34 (\pm 0.30)$	$2.41 (\pm 0.14)$		
	RGFN	$2.88 (\pm 0.21)$	$2.65 (\pm 0.09)$	$2.78 (\pm 0.19)$	$2.91 (\pm 0.23)$	$2.76 (\pm 0.17)$		
	RxnFlow	$2.42 (\pm 0.23)$	2.19 (± 0.12)	$1.95 (\pm 0.20)$	$2.15 (\pm 0.18)$	$2.23 (\pm 0.18)$		
3D Reaction	3DSynthFlow	$2.95 \ (\pm 0.42)$	$3.17 (\pm 0.21)$	$3.09~(\pm~0.23)$	$2.72 (\pm 0.24)$	3.11 (± 0.24)		
		GBA	IDH1	KAT2A	MAPK1	MTORC1		
Eroamont	FragGFN	3.94 (± 0.11)	3.74 (± 0.10)	3.78 (± 0.09)	3.72 (± 0.18)	3.84 (± 0.18)		
Flagment	FragGFN+SA	$3.94~(\pm 0.15)$	$3.84 (\pm 0.23)$	$3.66 (\pm 0.18)$	$3.69 \ (\pm \ 0.21)$	$3.94 \ (\pm \ 0.08)$		
	SynNet	3.38 (± 0.22)	3.38 (± 0.22)	3.46 (± 0.95)	3.50 (± 0.00)	3.29 (± 0.36)		
	BBAR	$3.71 (\pm 0.12)$	$3.68 (\pm 0.02)$	$3.63 (\pm 0.05)$	3.73 (± 0.05)	$3.77 (\pm 0.09)$		
Peaction	SynFlowNet ^a	$2.48 \ (\pm 0.18)$	$2.61 (\pm 0.13)$	$2.45 (\pm 0.37)$	$2.81 (\pm 0.24)$	$2.44 (\pm 0.27)$		
Reaction	SynFlowNet ^b	$2.45 (\pm 0.08)$	$2.46 (\pm 0.12)$	$2.45 (\pm 0.12)$	$2.83 (\pm 0.27)$	$2.39 (\pm 0.17)$		
	RGFN	$2.77 (\pm 0.20)$	$2.97 (\pm 0.15)$	$2.78 (\pm 0.10)$	$2.86 (\pm 0.19)$	$2.92 (\pm 0.06)$		
	RxnFlow	$2.10 (\pm 0.08)$	$2.16 (\pm 0.11)$	$2.29 (\pm 0.05)$	$2.29 (\pm 0.11)$	$2.05 (\pm 0.09)$		
3D Reaction	3DSynthFlow	3.05 (± 0.38)	$3.05 \ (\pm \ 0.31)$	$3.43 (\pm 0.23)$	$3.20 \ (\pm 0.39)$	$3.45 (\pm 0.22)$		
		OPRK1	PKM2	PPARG	TP53	VDR		
England and	FragGFN	3.82 (± 0.13)	3.71 (± 0.12)	3.73 (± 0.24)	3.73 (± 0.23)	3.75 (± 0.06)		
Fragment	FragGFN+SA	$3.62 (\pm 0.12)$	$3.84 (\pm 0.21)$	$3.71 (\pm 0.04)$	$3.66 \ (\pm \ 0.05)$	$3.67 (\pm 0.25)$		
	SynNet	3.29 (± 0.36)	3.50 (± 0.00)	3.29 (± 0.36)	3.67 (± 0.91)	3.63 (± 0.22)		
	BBAR	$3.70 (\pm 0.17)$	$3.61 (\pm 0.05)$	$3.72 (\pm 0.13)$	$3.65 (\pm 0.05)$	$3.77 (\pm 0.16)$		
Reaction	SynFlowNet ^a	$2.49 \ (\pm 0.33)$	$2.62 (\pm 0.10)$	$2.56 (\pm 0.12)$	$2.51 (\pm 0.27)$	$2.55 (\pm 0.09)$		
Reaction	SynFlowNet ^b	$2.50 (\pm 0.11)$	$2.52 (\pm 0.20)$	$2.53 (\pm 0.06)$	$2.34 (\pm 0.10)$	$2.51 (\pm 0.17)$		
	RGFN	$2.81 (\pm 0.12)$	$2.82 (\pm 0.10)$	$2.82 (\pm 0.18)$	$2.64 (\pm 0.10)$	$2.84 (\pm 0.18)$		
	RxnFlow	$2.00 (\pm 0.09)$	$2.34 (\pm 0.19)$	$2.21 (\pm 0.06)$	$2.12 (\pm 0.12)$	$2.12 (\pm 0.12)$		
3D Reaction	3DSvnthFlow	3.34 (+0.07)	3.10 (+ 0.49)	$3.45 (\pm 0.12)$	$3.08 (\pm 0.39)$	3.06 (+ 0.62)		

Table 19: Average synthesis steps estimated from AiZynthFinder for top-100 diverse modes gener-ated against 15 LIT-PCBA targets. The best results are in bold.



F.9 EXAMPLE GENERATION TRAJECTORIES

Figure 5: The example generation trajectory against ALDH1 target. The top row shows the 3D molecule x_t (green). The mid row shows the predicted final pose at each time step (cyan). The bottom row shows the synthesis pathway.