TIMEOMNI-1: INCENTIVIZING COMPLEX REASONING WITH TIME SERIES IN LARGE LANGUAGE MODELS

Anonymous authors
Paper under double-blind review

000

001

003 004 005

006

008 009

010 011

012

013

014

016

018

019

021

023

024

025

026

028

029

031

034

037 038

039

040

041

042

043

044

046

047

048

051

052

ABSTRACT

Recent advances in multimodal time series learning underscore a paradigm shift from analytics centered on basic patterns toward advanced time series understanding and reasoning. However, existing multimodal time series datasets mostly remain at the level of surface alignment and question answering, without reaching the depth of genuine reasoning. The absence of well-defined tasks that genuinely require time series reasoning, along with the scarcity of high-quality data, has limited progress in building practical time series reasoning models (TSRMs). To this end, we introduce Time Series Reasoning Suite (TSR-SUITE), which formalizes four atomic tasks that span three fundamental capabilities for reasoning with time series: (1) perception, acquired through scenario understanding and causality discovery; (2) extrapolation, realized via event-aware forecasting; and (3) decision-making, developed through deliberation over perception and extrapolation. TSR-SUITE is the first comprehensive time series reasoning suite that supports not only thorough evaluation but also the data pipeline and training of TSRMs. It contains more than 23K samples, of which 2.3K are carefully curated through a human-guided hierarchical annotation process. Building on this foundation, we introduce TIMEOMNI-1, the first unified reasoning model designed to address diverse real-world problems demanding time series reasoning. The model is trained in multiple stages, integrating a mixture of task scenarios, novel reward functions, and tailored optimizations. Experiments show that TIMEOMNI-1 delivers strong out-of-distribution generalization across all tasks and achieves a high rate of valid responses. It significantly improves causality discovery accuracy (64.0% vs. 35.9% with GPT-4.1) and raises the valid response rate by over 6% compared to GPT-4.1 on the event-aware forecasting task. Our code is available at https://anonymous.4open.science/r/TimeOmni-1.

1 Introduction

Time series data underpin a wide range of real-world systems, including energy, transportation, finance, and healthcare (Lu & Xu, 2024; Liu et al., 2023b; Guan et al., 2023; Lan et al., 2025). Comprehending real-world time series extends beyond mere pattern recognition, it necessitates multistep reasoning to identify external factors driving temporal changes and to support downstream tasks that inherently build upon upstream pattern understanding and extrapolation (Kong et al., 2025b). For instance, effectively scheduling energy demand requires integrating external knowledge such as extreme weather events, inferring causal mechanisms, anticipating event-driven variations, and ultimately supporting downstream decisions (MacKinlay, 1997; Liang et al., 2025). However, most existing time series approaches remain centered on basic pattern analytics and fall short in addressing such complex reasoning requirements, restricting their effectiveness in scenarios that demand a deeper understanding of context and robust decision-making support.

Large language models (LLMs) have recently demonstrated impressive multi-step reasoning abilities across text, code, and mathematics (Wei et al., 2023; Shao et al., 2024). This potential for time series reasoning, however, remains largely untapped. The primary obstacle is the scarcity of large-scale multimodal time series alignment, instruction, and labeled chain-of-thoughts data during pretraining, which hinders the development of corresponding time series reasoning abilities. This capability gap is further evidenced on even leading LLMs (e.g., GPT-4.1) by recent benchmark (Merrill et al.,

2024; Chow et al., 2024). Furthermore, time series specific architectures such as Time-MoE (Shi et al., 2024) and Moirai (Woo et al., 2024) remain largely confined to forecasting tasks and lack the generalized reasoning capabilities required for broader applications. These gaps underscore the urgent need for dedicated time series reasoning models (TSRMs) that advance time series understanding, strengthen reasoning, and facilitate temporal analytics and knowledge generation, paving the way toward general-purpose time series intelligence.

However, two key limitations hinder the development of TSRMs: (1) The scarcity of high-quality data to support general-purpose reasoning over time series. Early efforts, such as constructing TSQA datasets (Kong et al., 2025a), remain largely at the level of surface time series question answering and suffer from insufficient input context. Moreover, the formulation of time series reasoning tasks in existing multimodal datasets has not been systematically studied, leaving them unable to capture genuine reasoning depth with time series data. (2) The lack of a validated and feasible pathway for effective time series reasoning across tasks. It remains unclear which tasks genuinely demand reasoning capabilities over time series, as this question has not been systematically studied. This gap, combined with data scarcity, has confined existing research to narrow, task-specific settings. Many current approaches are trained independently for each task or even each dataset; for example, TimeMaster (Zhang et al., 2025b) employs six distinct models for six datasets. Such fragmentation hinders the transfer of reasoning capabilities across tasks and leaves the development of general-purpose time series reasoning an open challenge. These challenges naturally raise a pivotal question: How can we take a solid step toward fully incentivizing reasoning capabilities in LLMs over time series, so they can tackle complex real-world problems that inherently demand such reasoning?

Answering this question first drives us to tackle the challenge of data scarcity. Based on the limitations of existing time series QA datasets, we argue that time series reasoning tasks should adhere to two key principles. First, they should reward genuine reasoning rather than superficial pattern matching by systematically incorporating multi-step reasoning tasks and complete reasoning chains. Second, they should ensure context sufficiency to enable unambiguous answering or response generation, thereby strengthening the model's reasoning capacity and generalization across diverse scenarios. Guided by these principles, we formalize four atomic tasks that genuinely require reasoning with time series and introduce TSR-SUITE, which covers three fundamental time series reasoning capabilities: (1) perception, acquired through scenario understanding and causal discovery, reveals key temporal patterns; (2) extrapolation, realized via event-aware forecasting, predicts future trends and anomalies; and (3) decision-making, developed through perception and extrapolation, supports informed, adaptive actions. Building on this foundation, we present TIMEOMNI-1, the first generalized reasoning model for time series. The central premise is that effective time series reasoning requires internalizing fundamental temporal priors. To this end, TIMEOMNI-1 first injects the above three capabilities identified by TSR-SUITE into LLMs through supervised fine-tuning (SFT) as priors. We then design novel time series task-grounded rewards to cultivate genuine reasoning from these priors via policy optimization. Finally, to validate that these capabilities represent complementary facets of general time series reasoning, we unify all task capabilities within a single model with joint training.

Our contributions lie in three aspects:

- 1. **New Datasets and Testbed.** We introduce **TSR-SUITE**, the first comprehensive time series reasoning suite that formalizes four core tasks spanning three capabilities: perception, extrapolation, and decision-making. It contains more than 23K samples, of which 2.3K are carefully curated through a human-guided hierarchical annotation process. The suite serves not only as a testbed for thorough evaluation but also as a foundational data pipeline for training TSRMs.
- 2. New Models. We present TIMEOMNI-1, the first generalized reasoning model on time series data. It unifies diverse reasoning tasks within a two-stage curriculum: Stage 1 employs supervised fine-tuning with human-guided reasoning traces to inject temporal priors across the three key capabilities: perception, extrapolation, and decision-making; Stage 2 leverages reinforcement learning with novel task-grounded rewards to go beyond mimicking priors to robust reasoning.
- 3. Comprehensive Evaluation and Key Insights. TIMEOMNI-1 achieves Top-2 performance under both in-distribution (ID) and out-of-distribution (OOD) testbeds. Notably, it surpasses GPT-4.1 by 40.6% (ID) and 28.1% (OOD) in causal discovery accuracy while maintaining high valid-response rates across all tasks. Further experiments provide the first evidence that joint training across diverse time series reasoning tasks yields mutual gains across capabilities.

2 RELATED WORK

Large Time Series Models. Early efforts primarily aimed to endow time series models with zeroshot capability, mitigating domain-specific limitations when large-scale time series data were scarce. Time-LLM (Jin et al., 2024) sought to transfer the generalization ability of LLMs into the time series domain. Prior developments of time series models are discussed in Appendix B. With the increasing availability of large-scale time series datasets, training time series foundation models (TSFMs) from scratch emerged as the mainstream approach (Woo et al., 2024; Ansari et al., 2024; Shi et al., 2024). These models demonstrated promising zero-shot performance but still fell short of supporting multi-task and multimodal capability. With the advent of multimodal models (Alayrac et al., 2022; OpenAI et al., 2024a) and reasoning-centric models (OpenAI et al., 2024b; Guo et al., 2025), the intersection of time series and LLMs has re-emerged at the forefront. Broadly, existing approaches can be categorized into two main groups. The first are time series language models (TSLMs), which primarily adapt the language modeling paradigm to temporal data, emphasizing representation learning and simple time series QA without reasoning (Xie et al., 2025; Kong et al., 2025a; Zhang et al., 2025a; Yang et al., 2025). The second are time series reasoning models (TSRMs), distinguished by their attempt to employ RL to cultivate genuine reasoning ability rather than pattern matching, and by their use of explicit reasoning to improve accuracy while providing interpretable, step-by-step explanations that enhance trustworthiness (Wang et al., 2025; Tan et al., 2025b; Luo et al., 2025). However, this line of research is still in its infancy: the definition and necessity of reasoning remain vague, existing QA datasets are of limited quality, and most current works restrict themselves to single-task experiments under the R1-paradigm (Guo et al., 2025), without yet establishing a general-purpose reasoning framework for time series analogous to LLMs.

Reasoning with Large Language Models. Generative LLMs offer greater flexibility and generalization than traditional deep learning models, making them effective in complex tasks that require multi-step reasoning (Wei et al., 2023; Kojima et al., 2022). However, reasoning errors can propagate and degrade performance in some cases. To address this, Lightman et al. (2023) introduces a step-level reward mechanism into both data construction and model fine-tuning to enhance reasoning. DeepSeek-R1-Zero (Guo et al., 2025) shows that RL using only format and final answers can also improve reasoning. And it has expanded to math, code, translation, and multimodal tasks (Zhang et al., 2025d;c; Feng et al., 2025; Huang et al., 2025; Zhan et al., 2025; Liu et al., 2025). However, LLM-based reasoning for time series remains underexplored due to data scarcity.

3 METHODOLOGY

Problem Definition. We define time series reasoning as the process in which reasoning model (RM) p_{θ} first generate a sequence of intermediate rationales $R = (r_1, \ldots, r_K)$ and then produce a final answer y, conditioned on (1) observed time series inputs $X = \{x_{1:T}^{(m)}\}_{m=1}^{M}$ and (2) auxiliary context C (e.g., task instructions or external knowledge). Formally:

$$(R, y) \sim p_{\theta}(R, y \mid X, C) = p_{\theta}(R \mid X, C) p_{\theta}(y \mid R, X, C).$$
 (1)

This formulation covers both discrete-output tasks, where y is a categorical option, and sequence-output tasks, where y is a numerical sequence, under a unified reasoning framework. To standardize outputs, RMs must generate rationales R within <think></think> tags, followed by the final answer y enclosed in an <answer></answer> block. In contrast, non-reasoning models directly predict $y \sim p_{\theta}(y \mid X, C)$ without rationales, producing only the <answer></answer>.

3.1 FORMULATING REASONING-CRITICAL TIME SERIES TASKS

Limitations of Existing QA Tasks. We use Time-MQA (Kong et al., 2025a), the largest existing time series question answering (TSQA) dataset, to highlight two limitations. (1) *Many questions are overly simple and straightforward, where invoking reasoning leads to over-thinking.* At the aggregate level, as shown in Figure 1(a), the accuracy gap between stronger models (GPT-4.1) and smaller baselines (Qwen2.5-14B) is marginal, and in some cases reversed, indicating that additional reasoning capacity brings no benefit. Furthermore, all models achieve accuracy above 75%, highlighting that the tasks are not sufficiently challenging. At the instance level, as illustrated by the True/False QA from Time-MQA in Figure 1(b), the question can be directly answered by non-reasoning models, while reasoning




Figure 1: Limitations of existing TSQA dataset (Kong et al., 2025a). (a) The marginal performance gap between RMs and NRMs. (b) Reasoning on simple TSQA leads to over-thinking. (c) Insufficient context leads to a performance plateau. (d) Ambiguous options forcing models to guess.

complicates the process. (2) Questions often lack sufficient input information, either in the time series X or the context C, which prevents well-grounded answers and introduces ambiguity. As shown in Figure 1(c), even advanced models plateau below 65% accuracy and show no gains after SFT. To investigate this, we conducted a human evaluation, which revealed numerous ambiguous cases caused by missing context. As exemplified in Figure 1(d), the options are not clearly distinguished (e.g., no explicit thresholds for high, moderate, and low volatility), forcing the model to guess rather than reason. Consequently, errors reflect chance rather than insufficient time series reasoning ability (see Appendix C for detailed analysis of existing TSQA datasets). To address these issues, we propose two design principles for formulating time series QA tasks that require genuine reasoning.

Principle 1 — **QA-pairs must reward reasoning.** A reasoning model $M_{\rm RM}$ explicitly generates rationales R before producing the answer y, whereas a non-reasoning baseline $M_{\rm NRM}$ directly outputs y. To determine whether a task requires reasoning, RMs should (significantly) outperform non-reasoning models (NRMs): $\bar{S}(M_{\rm RM})\gg \bar{S}(M_{\rm NRM})$, where $\bar{S}(\cdot)$ denotes the mean score across tasks (e.g., accuracy for categorical prediction tasks or regression metrics for regression tasks).

Principle 2 — QA-pairs must ensure context sufficiency. Both the time series input X and auxiliary context C constitute the basis for reasoning. Unlike coding and mathematical problem solving, where a well-posed problem typically admits a unique solution (Imani et al., 2023), time series problem solving is especially sensitive to the sufficiency of X and C. Let K denote the number of ambiguous options. Even an ideal reasoner with infinite reasoning capacity ($RC \to \infty$) will be forced to guess if X or C is underspecified (e.g., missing thresholds for distinguishing high vs. low variance), while it should substantially exceed random guessing once X and C are sufficient:

$$\lim_{RC \to \infty} P(\text{correct} \mid X, C) \begin{cases} \approx \frac{1}{K}, & \text{if } X \text{ or } C \text{ is underspecified,} \\ \gg \frac{1}{K}, & \text{if } X \text{ and } C \text{ are sufficient.} \end{cases}$$
 (2)

Therefore, ensuring context sufficiency is a critical design principle for formulating reasoning-critical time series tasks, as it prevents ambiguity and enables reasoning to be applied meaningfully.

Reasoning-Critical Tasks. The two principles motivate us to directly address the unique challenges of time series reasoning (ensuring QA requires reasoning and context sufficiency). To this end, we design a suite of tasks that form a progressive pathway covering three fundamental time series reasoning capabilities: (1) perception, (2) extrapolation, and (3) decision-making.

As shown in Figure 2, the foundation of time series reasoning capabilities is perception, where the model first recognizes temporal patterns and then uncovers their underlying causes. This includes **Task 1: Scenario Understanding**, which focuses on single-series attribution by linking fluctuations to generative scenarios or external events (e.g., higher temperatures leading to increased ice-cream sales). It also encompasses **Task 2: Causality Discovery**, which extends attribution to the multiseries setting, requiring the model to compare trends across sequences and identify causal relations (e.g., upstream discharge influencing downstream flow). Together, these tasks ensure the model not only observes time series but also interprets them in a context-aware and causal manner. **Task 3: Event-aware Forecasting** requires the model to build on its perception ability to extrapolate future trajectories under explicit event perturbations. Accurate extrapolation depends on leveraging intrinsic temporal knowledge to analyze external events and infer their impact on temporal dynamics. Finally,




Figure 2: Illustrative examples of the four reasoning-critical time series tasks in TSR-SUITE.

Task 4: Decision Making represents the culmination of this chain. Building on the perception of temporal patterns (Task 1), causal relations (Task 2), and extrapolation (Task 3), the model must integrate these to select actions (Task 4) that maximize downstream utility (e.g., maximizing profits). By following the progressive capabilities of perception, extrapolation, and decision-making in formulating reasoning-critical tasks, we ensure that reasoning is an intrinsic requirement. Solving these tasks demands explicit reasoning from the outset, unlike conventional analytical tasks such as interpolation, where models often succeed through implicit fitting without reasoning.

3.2 TSR-SUITE

To mitigate the scarcity of data in the field, we construct Time Series Reasoning Suite (TSR-SUITE), the first unified dataset suite tailored for time series reasoning. Unlike prior benchmarks designed purely for evaluation, TSR-SUITE is built as a training-and-evaluation suite that supports TSRMs development. The dataset spans 10 diverse domains and contains 23,605 curated QA pairs. Among them, 2,339 samples are annotated through a human-guided hierarchical annotation process. Detailed statistics for each task are provided in Appendix D.2. As shown in Figure 3(a), the data organization comprises three components as follows.

Raw Data Collection. Guided by the "perception–extrapolation–decision-making" pathway underlying our four tasks, we systematically collect publicly available time series data across 10 domains. Figure 3(a) provides an overview of the domain distribution, see Appendix D.1 for data source details.

Task Formulation. To align with our task design and support RL, we standardize the QA format across tasks. Specifically, Tasks 1, 2, and 4 are framed as discrete-output selection problems, while Task 3 is formulated as a sequence-output forecasting task, as shown in Figure 2. Each task adopts a customized data construction pipeline and is extensible to support further scaling with new input series. A key improvement over prior datasets is that our dataset, with over 23K QA pairs, is sufficiently large to support both training and evaluation (e.g., CiK with 355 samples (Williams et al.), TSAIA with 1,054 samples (Ye et al., 2025)), rather than serving solely as a testbed.

Hierarchical Chain-of-Thoughts. Existing time series QA datasets typically provide only labels (Kong et al., 2025a), overlooking the fact that LLMs lack temporal priors for time series reasoning. To fill the gap, we design a hierarchical annotation pipeline involving an LLM Analyzer, Human Reviewers, and an LLM Rewriter (Figure 3(b)). (1) Human-guided solvable annotation. Instead of asking the LLM analyzer to directly solve the problems, we guide it with structured templates to elicit consistent reasoning, and we retain correctly solved samples as Step-1 CoT data. (2) **Context sufficiency verification.** For questions answered incorrectly in the first step, human experts use a customized evaluation interface (see Appendix D.4) to examine whether the provided context is sufficient to disambiguate the answer. If a question is solvable by human reviewers, expert-written reasoning chains are subsequently polished by the rewriter to follow our structured templates, and the resulting samples are collected as Step-2 CoT data. Task 3 (Event-aware Forecasting) is treated as a special case: unlike tasks with unique answers, forecasting outputs cannot perfectly match the ground truth due to inherent noise in real-world time series data. Human reviewers examine the cases and select 400 samples with relatively low mean absolute error (MAE). As a result, annotated predictions in Task 3 may not coincide exactly with the ground truth, but they capture plausible and well-justified reasoning. Additional analysis of Task 3 is provided in Appendix D.3.

Figure 3: Overview of data and training pipeline. (a) Construction of TSR-SUITE, including *domain distribution* and *sample statistics*. (b) Hierarchical CoT annotation pipeline with outputs from each step for all tasks. (c) Two-stage training of TIMEOMNI-1: Stage 1 injects temporal priors via SFT; Stage 2 refines reasoning with task-grounded reward signals under RL.


3.3 TIMEOMNI-1

Developing time series reasoning poses unique challenges compared to other domains. Pretrained LLMs lack temporal priors, as they are not largely exposed to time series data during pretraining. To bridge this gap, we propose a two-stage training paradigm: (1) injecting temporal priors to anchor the model in a temporal knowledge space, and (2) refining these priors for robust reasoning through task-grounded rewards (Figure 3(c)). All experiments in this section use in-distribution (ID) testbeds.

Stage 1: Injecting Time Series Reasoning Priors. Human-guided reasoning priors instruct LLMs on how to decompose time series tasks into meaningful components. These traces narrow the exploration space to focus on three key capabilities (i.e., perception, extrapolation, and decision-making) instead of drifting toward commonsense heuristics or generic algebraic QA. We inject this knowledge through supervised fine-tuning (SFT). Implementation details of SFT are provided in Appendix F.1.

Finding 1: Time series reasoning ability need not be innate; it can be effectively cultivated via supervised fine-tuning on a small set of high-quality, curated reasoning traces.

Base models without temporal priors collapse to chance-level accuracy when questions require fundamental temporal understanding (e.g., Task 2: 21.6% vs. 33.3% random guess in Figure 4). Injecting reasoning traces, even with <1K seeds, boosts Task 2 accuracy by 46.1% after Stage 1, with comparable gains across other tasks. This prove that time series reasoning is not inherent to LLMs but can be systematically established through temporal priors.






Figure 4: Stage 1 boosts accuracy; Base model at chance.

Figure 5: Human-guided templates are critical for priors.

Finding 2: Human-guided traces establish decomposition priors critical for time series reasoning.

Without guidance, LLMs tend to produce unstable, generic math-style reasoning traces that inconsistent across samples and fail to capture temporal dependencies. In contrast, when prompted with human-guided templates, the pretrained LLMs generates structured traces that explicitly follow decomposition strategies and achieve substantially higher accuracy. As shown in Figure 5, on GPT-4.1, human-guided templates improve zero-shot consistency accuracy from 28.7% to 71.1% on Task 2, with improvements also observed across all four tasks. These further confirm that pretrained LLMs lack temporal priors and must be enhanced through Stage 1 training.

Stage 2: Refining Reasoning with Task-grounded Rewards. While Stage 1 provides priors, they remain insufficient for robust reasoning. Stage 2 employs reinforcement learning (RL) through group relative policy optimization (Shao et al., 2024) to turn mimicking priors into stable and generalizable reasoning behaviors (Figure 3(c)). Implementation details of RL stage are provided in Appendix F.2.

Here we focus on designing task-grounded, outcome-based rewards for time series reasoning, with full definitions provided in Appendix G. Each sample receives a reward composed of format verification and task correctness. \mathcal{R}_{format} enforces the <think></think><answer></answer> schema. For correctness, we distinguish task types: for Tasks 1, 2, and 4, $\mathcal{R}_{discrete} \in \{0,1\}$ denotes exact-match accuracy (1 if correct, 0 otherwise). For Task 3, we add a counting bonus $\mathcal{R}_{count}=0.1$ if the predicted sequence length matches the required horizon. This structural reward is essential since LLMs still struggle with counting. For example, our Stage I checkpoint achieves only 55.7% success on sequence length. In addition, we use an exponential decay to map the unbounded MAE into a normalized range, which compresses arbitrarily large MAE toward zero to ensure higher rewards for smaller MAE.




Figure 6: Stage 2 RL alone fails without Stage 1 priors.

Finding 3: Reinforcement learning works reliably only once the base model is anchored with fundamental temporal priors, which prevent collapse into spurious exploration.

Applying Stage 2 directly to a base model yields only marginal or even negative improvements (as shown in Figure 6, with a 5.3% drop on Task 4), since the rewards cannot distinguish genuine temporal knowledge from exploration within the pretraining corpus space. In contrast, when preceded by Stage 1, the same rewards refine temporal priors and progressively develop into robust reasoning.

Joint Training for Time Series Reasoning. Unlike prior single-task (or single-dataset) pipelines (Tan et al., 2025a; Zhang et al., 2025b), we investigate whether unifying perception, extrapolation, and decision-making objectives through joint training yields mutual benefits. We design the following two complementary experimental settings to systematically study the synergistic gains among the three reasoning capabilities.

Finding 4: Joint training turns perception, extrapolation, and decision-making from silos into complementary capabilities, supporting a train-once, use-across-tasks paradigm for TSRMs.

Progressive Capability Trans-This evaluates whether precursor reasoning capabilities transfer to downstream decision-making in a zeroshot manner. We evaluate three conditions on the ID decision-making testbed: (1) base model without precursor training, (2) model trained only on perception tasks, and (3) model trained on both perception and extrapolation tasks. As shown in Figure 7(a), accuracy on decision-making tasks increases from 25.5% to 26.2% and further to 31.3%, indicating that precursor capabilities




Figure 7: Joint training results: (a) Zero-shot capability transfer from precursor tasks (C1: Perception, tasks 1, task 2; C2: Extrapolation, task 3) to decision-making; (b) Supervised capability supplement by progressively incorporating tasks (C3: Decision-Making); (c) Joint training outperforms single-task training.

enhance downstream reasoning even without direct supervision.

Progressive Capability Supplement. This assesses supervised joint training by gradually incorporating precursor tasks. We compare: (1) training solely on decision-making, (2) joint training on extrapolation and decision-making, and (3) full joint training across four tasks covers all three capabilities.

Decision-making accuracy rises from 40.9% to 45.7% and peaks at 47.9%, as shown in Figure 7(b), confirming that progressively supplementing related tasks creates complementary learning benefits.

Scaling to All Tasks. Building on the above complementary settings, we compare single-task training against joint training across all four tasks. As shown in Figure 7(c), joint training consistently outperforms single-task training on the ID testbed. These results support a "train-once, use-across-task" paradigm for time series reasoning, where joint training effectively captures intrinsic connections within the temporal reasoning capabilities without task interference.

4 EXPERIMENTS

 Evaluation Metrics. We observe that different models vary significantly in instruction-following ability, sometimes generating repetitive or malformed outputs. To ensure fair comparison, we adopt the standardized system prompt shown in Appendix E.2 and apply regular expressions to extract answers. We report the Success Rate (SR), which is the proportion of model outputs that yield a valid and extractable answer. All subsequent evaluation metrics are computed only on these valid cases, ensuring that performance reflects time series reasoning ability rather than instruction-following compliance. For discrete-output tasks (Scenario Understanding, Causality Discovery, Decision Making), we use Accuracy (ACC) via exact match. For the sequence-output task (Event-aware Forecasting), we use Mean Absolute Error (MAE) to assess forecasting precision. Higher ACC and lower MAE indicate better performance. The hyperparameters used are provided in Appendix H.

Baselines. We compare TIMEOMNI-1 against up-to-date models in two categories: (1) **Time series language models:** Time-MQA (Kong et al., 2025a) (fine-tuned 7B-8B models tailored for TSQA), ChatTS (Xie et al., 2025) (fine-tuned 14B model for time series understanding), and Time-R1 (Luo et al., 2025) (TSRMs for classical forecasting). (2) **General-purpose LLMs:** two GPT-4.1 variants as proprietary representatives, and five open-source LLMs (7B to 70B) for comprehensive evaluation.

4.1 MAIN RESULTS

As shown in Table 1, TIMEOMNI-1 consistently ranks among the top-2 models across all time series reasoning tasks. Notably, it exceeds GPT-4.1 by 40.6% (ID) and 28.1% (OOD) on causal discovery. While achieving comparable accuracy on scenario understanding, TIMEOMNI-1 surpasses GPT-4.1 by a wide margin on tasks requiring deeper temporal priors (e.g., decision-making). Existing time series specialized models, however, exhibit weaker instruction-following ability than general LLMs (consistently lower SR). For example, ChatTS achieves 0% SR on the event-aware forecasting task; upon inspection, we found it fails to produce the required numeric sequences, generating

Table 1: Model comparison on four tasks, reporting ACC for Tasks 1, 2, and 4, MAE for Task 3, together with SR under ID and OOD testbeds. All metrics are computed only on valid responses. "—" denotes SR below 10%, where results are omitted for lack of statistical significance and therefore we choose not to report them. **Red**: the best, Blue: the 2nd best.

		Scenario Understanding			Causality Discovery			Event-aware Forecasting			Decision Making							
Method	Base LLMs	ID		O	OOD		ID		OOD		ID		OOD		ID		OOD	
		ACC	SR%	ACC	SR%	ACC	SR%	ACC	SR%	MAE	SR%	MAE	SR%	ACC	SR%	ACC	SR%	
Proprietary Models																		
GPT-4.1-2025-04-14		85.5	100.0	87.8	100.0	28.7	99.9	35.9	100.0	13.79	97.4	170.78	76.1	25.5	100.0	27.8	100.0	
GPT-4.1-Nano		66.2	97.5	62.6	98.7	29.8	98.6	28.0	98.4	18.98	92.8	170.78	76.1	28.9	99.5	34.1	97.8	
Open-Source Models																		
Llama-3.1-70B-Instruct		56.4	100.0	59.6	100.0	23.4	100.0	28.9	99.9	24.67	92.8	238.98	97.0	20.3	96.8	17.7	97.4	
Mistral-Small-3.1-24B-Ins		64.8	100.0	69.2	100.0	24.6	100.0	25.8	100.0	17.28	72.0	120.97	43.4	44.7	100.0	42.9	100.0	
Llama-3.1-8B-Instruct		36.6	46.5	32.1	46.8	-	3.7	-	1.9	27.68	52.91	186.80	29.8	7.4	28.7	16.2	42.9	
Mistral-7B-v0.3		40.5	92.2	34.7	87.6	29.0	86.0	26.9	82.6	-	5.3	-	0.0	24.3	94.2	16.7	96.7	
Qwen2.5-Instruct-7B		48.5	100.0	42.8	100.0	21.6	99.8	26.3	100.0	23.28	53.1	146.12	55.46	25.5	100.0	24.9	100.0	
Time Series Language Models																		
Time-MQA	Llama3-8B	32.2	29.5	25.1	32.6	30.1	44.3	31.2	37.2	-	1.4	-	0.4	12.0	13.3	11.6	15.8	
Time-MQA	Mistral-7B-v0.3	15.1	21.5	27.8	22.1	8.4	50.2	4.0	52.2	-	0.2	-	0.0	5.4	36.1	10.0	47.3	
Time-MQA	Qwen2.5-7B	25.0	14.0	37.5	22.7	29.5	33.0	30.5	32.0	19.76	12.2	-	6.5	23.8	58.0	26.4	44.3	
ChatTS		-	6.0	-	6.9	18.2	30.1	18.6	26.7	-	0.0	-	0.0	5.8	27.1	11.1	27.1	
Time Series Reasoning Models																		
Time-R1	Qwen2.5-Instruct-7B	30.9	94.0	34.0	92.5	30.2	53.8	31.4	48.9	17.61	38.7	-	6.3	27.8	95.7	32.2	93.1	
Ours																		
TIMEOMNI-1	Qwen2.5-Instruct-7B	90.7	97.5	87.7	98.3	69.3	99.8	64.0	99.8	14.30	93.8	145.53	82.3	47.9	100	58.9	100	

only free-form text. This highlights a critical limitation of existing time series task-specific models: over-specialization compromises generalization ability.

4.2 MORE ANALYSIS

General Reasoning Capability. We evaluate whether our time series specialization diminishes general reasoning ability. We compare the base model, Stage 1 SFT model, and TIMEOMNI-1 on three general reasoning benchmarks: DROP (Dua et al., 2019), GPQA (Rein et al., 2024), and ReClor (Yu et al., 2020), which focus respectively on numerical reasoning, graduate-level knowledge reasoning, and logical reasoning. As shown in Figure 8, TIMEOMNI-1 improves average accuracy by 16.5% over the base model and 1.3% over the Stage 1 model. This indicates our approach not only maintains but also enhances general reasoning capabilities while specializing in time series tasks, avoiding the instruction-following degradation observed in other specialized models.




Figure 8: Performance on general reasoning benchmarks.

Ablation on Training Stage. We evaluate two configurations: (1) **Stage 1 models**, including NRMs via answer-only fine-tuning (ANS-

SFT) and RMs via CoT fine-tuning (CoT-SFT); (2) **Stage 1+ Stage 2 models** (CoT-SFT+RL), which first activates reasoning via CoT-SFT and then applies RL. We analyze performance under multitask joint training. As shown in Table 2, complete two-stage training (CoT-SFT+RL) delivers the most balanced performance, ranking Top-2. In causal discovery, CoT-SFT reaches 67.7% accuracy compared to only 30.5% for ANS-SFT, showing that answer-only supervision merely fits answer distributions without fostering reasoning. On decision-making, the CoT-SFT vs. ANS-SFT gap narrows from 10.1% (ID) to 5.5% (OOD), further confirming that ANS-SFT fails to foster reasoning, whereas CoT-SFT establishes transferable reasoning skills that are consolidated by RL in Stage II.

Ablation on Training Strategy. We compare single-task fine-tuning against multi-task joint training under identical training budgets. As shown in Table 2, multi-task joint training often enhances performance across all tasks and training stages. On the ID testbed, the jointly trained CoT-SFT+RL model (TIMEOMNI-1) achieves accuracy gains of 8.2%, 1.8%, 2.46 (MAE), and 7.0% across the four tasks compared to single-task training. Together with Figure 7, which demonstrates progressive capability *transfer* and *supplement*, these results validate that joint training effectively integrates temporal reasoning capabilities, reinforcing the "train-once, use-across-tasks" paradigm.

Table 2: Comparison across training stages and training strategies. Red: the best, Blue: the 2nd best.

TD	The state of the state of	Scenario Understanding			Causality Discovery			Event-aware Forecasting				Decision Making					
Training Stage	Training Strategy	ID		OOD		ID		OOD		ID		OOD		ID		OOD	
		ACC	SR%	ACC	SR%	ACC	SR%	ACC	SR%	MAE	SR%	MAE	SR%	ACC	SR%	ACC	SR%
Base Model	Qwen2.5-Instruct-7B	48.5	100.0	42.8	100.0	21.6	99.8	26.3	100.0	23.28	53.1	146.12	55.5	25.5	100.0	24.9	100.0
ANS-SFT	Single-task	77.5	100.0	73.9	100.0	35.7	100.0	33.8	100.0	23.87	39.7	150.42	0.6	20.2	100.0	24.2	100.0
	Multi-task Joint	80.5	100.0	76.6	100.0	30.5	100.0	34.6	100.0	13.23	48.3	156.78	38.9	51.0	100.0	58.2	100.0
CoT-SFT	Single-task	73.9	100.0	85.6	83.9	66.3	96.0	61.8	92.4	15.10	64.6	157.21	34.5	39.4	98.40	47.3	94.87
	Multi-task Joint	89.8	88.0	85.8	88.2	67.7	98.8	61.1	97.0	15.53	71.8	151.41	55.7	40.9	100.0	52.7	100.0
CoT-SFT+RL	Single-task	82.5	100.0	87.0	98.7	67.5	99.6	61.7	99.0	16.76	79.2	169.88	66.0	40.9	100.0	63.6	99.6
	Multi-task Joint	90.7	97.5	87.7	98.3	69.3	99.8	64.0	99.8	14.30	93.8	145.53	82.3	47.9	100.0	58.9	100.0

5 Conclusion

In this paper, we introduce **TSR-SUITE**, which addresses the scarcity of reasoning-critical time series data. It formalizes four tasks across three fundamental capabilities for time series reasoning: perception, extrapolation, and decision-making. On this basis, we present **TIMEOMNI-1**, the first generalized, unified model for time series reasoning. It first injects temporal priors through supervised fine-tuning. Then, reinforcement learning with task-grounded rewards guides the model beyond mimicking priors toward robust reasoning. Experiments show that TIMEOMNI-1 achieves top-tier performance while preserving the general reasoning ability of the base model. Finally, we demonstrate that joint training across diverse reasoning tasks yields mutual gains, supporting a "train-once, use-across-tasks" paradigm for future time series reasoning models.

ETHICS STATEMENT

Our work focuses solely on scientific challenges and does not involve human subjects, animals, or environmentally sensitive materials. We foresee no ethical risks or conflicts of interest. We are committed to upholding the highest standards of scientific integrity and ethical conduct to ensure the validity and reliability of our findings.

7 REPRODUCIBILITY STATEMENT

To ensure reproducibility, we provide: Detailed hyperparameters for multiple training stages (Appendix H); All system prompts used in annotation, training, and evaluation (Appendix E). Our source code for TSR-SUITE construction and TIMEOMNI-1 training is available at: https://anonymous.4open.science/r/TimeOmni-1.

REFERENCES

- Jean-Baptiste Alayrac, Jeff Donahue, Pauline Luc, Antoine Miech, Iain Barr, Yana Hasson, Karel Lenc, Arthur Mensch, Katherine Millican, Malcolm Reynolds, Roman Ring, Eliza Rutherford, Serkan Cabi, Tengda Han, Zhitao Gong, Sina Samangooei, Marianne Monteiro, Jacob L. Menick, Sebastian Borgeaud, Andy Brock, Aida Nematzadeh, Sahand Sharifzadeh, Mikołaj Bińkowski, Ricardo Barreira, Oriol Vinyals, Andrew Zisserman, and Karén Simonyan. Flamingo: A Visual Language Model for Few-Shot Learning. *Advances in Neural Information Processing Systems*, 35: 23716–23736, 2022.
- Abdul Fatir Ansari, Lorenzo Stella, Caner Turkmen, Xiyuan Zhang, Pedro Mercado, Huibin Shen, Oleksandr Shchur, Syama Sundar Rangapuram, Sebastian Pineda Arango, Shubham Kapoor, Jasper Zschiegner, Danielle C. Maddix, Hao Wang, Michael W. Mahoney, Kari Torkkola, Andrew Gordon Wilson, Michael Bohlke-Schneider, and Yuyang Wang. Chronos: Learning the Language of Time Series, 2024.
- Wanlin Cai, Kun Wang, Hao Wu, Xiaoxu Chen, and Yuankai Wu. Forecastgrapher: Redefining multivariate time series forecasting with graph neural networks. *arXiv preprint arXiv:2405.18036*, 2024.
- Winnie Chow, Lauren Gardiner, Haraldur T. Hallgrímsson, Maxwell A. Xu, and Shirley You Ren. Towards Time Series Reasoning with LLMs, 2024.
- Dheeru Dua, Yizhong Wang, Pradeep Dasigi, Gabriel Stanovsky, Sameer Singh, and Matt Gardner. DROP: A reading comprehension benchmark requiring discrete reasoning over paragraphs. In *Proc. of NAACL*, 2019.
- Zhaopeng Feng, Shaosheng Cao, Jiahan Ren, Jiayuan Su, Ruizhe Chen, Yan Zhang, Zhe Xu, Yao Hu, Jian Wu, and Zuozhu Liu. Mt-r1-zero: Advancing llm-based machine translation via r1-zero-like reinforcement learning. *arXiv preprint arXiv:2504.10160*, 2025.
- Chengqian Gao, Haonan Li, Liu Liu, Zeke Xie, Peilin Zhao, and Zhiqiang Xu. Principled data selection for alignment: The hidden risks of difficult examples, 2025. URL https://arxiv.org/abs/2502.09650.
- Shanghua Gao, Teddy Koker, Owen Queen, Thomas Hartvigsen, Theodoros Tsiligkaridis, and Marinka Zitnik. UNITS: A Unified Multi-Task Time Series Model.
- Yunfeng Ge, Ming Jin, Yiji Zhao, Hongyan Li, Bo Du, Chang Xu, and Shirui Pan. EventTSF: Event-Aware Non-Stationary Time Series Forecasting, 2025.
- Tong Guan, Jiaheng Peng, Yinxiao Zhan, and Jun Liang. ST-DCAN: Spatio-Temporal Dual Compression Attention Network for Traffic Prediction. In 2024 China Automation Congress (CAC), pp. 5048–5053.
- Tong Guan, Jiaheng Peng, and Jun Liang. Spatial-temporal graph multi-gate mixture-of-expert model for traffic prediction. In 2023 IEEE 26th International Conference on Intelligent Transportation Systems (ITSC), pp. 36–41. IEEE, 2023.

- Daya Guo, Dejian Yang, Haowei Zhang, Junxiao Song, Ruoyu Zhang, Runxin Xu, Qihao Zhu, Shirong Ma, Peiyi Wang, Xiao Bi, et al. Deepseek-r1: Incentivizing reasoning capability in llms via reinforcement learning. *arXiv preprint arXiv:2501.12948*, 2025.
 - Wenxuan Huang, Bohan Jia, Zijie Zhai, Shaosheng Cao, Zheyu Ye, Fei Zhao, Zhe Xu, Yao Hu, and Shaohui Lin. Vision-r1: Incentivizing reasoning capability in multimodal large language models. *arXiv preprint arXiv:2503.06749*, 2025.
 - Shima Imani, Liang Du, and Harsh Shrivastava. MathPrompter: Mathematical Reasoning using Large Language Models, 2023.
 - Hassan Ismail Fawaz, Germain Forestier, Jonathan Weber, Lhassane Idoumghar, and Pierre-Alain Muller. Transfer learning for time series classification. In 2018 IEEE International Conference on Big Data (Big Data), pp. 1367–1376.
 - Peng Jiaheng, Guan Tong, and Liang Jun. A Bipartite Graph Based Method for Traffic Continuous Data Imputation. In 2023 China Automation Congress (CAC), pp. 4220–4225.
 - Ming Jin, Shiyu Wang, Lintao Ma, Zhixuan Chu, James Y. Zhang, Xiaoming Shi, Pin-Yu Chen, Yuxuan Liang, Yuan-Fang Li, Shirui Pan, and Qingsong Wen. Time-Ilm: Time series forecasting by reprogramming large language models, 2024. URL https://arxiv.org/abs/2310.01728.
 - Takeshi Kojima, Shixiang Shane Gu, Machel Reid, Yutaka Matsuo, and Yusuke Iwasawa. Large language models are zero-shot reasoners. *Advances in neural information processing systems*, 35: 22199–22213, 2022.
 - Yaxuan Kong, Yiyuan Yang, Yoontae Hwang, Wenjie Du, Stefan Zohren, Zhangyang Wang, Ming Jin, and Qingsong Wen. Time-MQA: Time Series Multi-Task Question Answering with Context Enhancement, 2025a.
 - Yaxuan Kong, Yiyuan Yang, Shiyu Wang, Chenghao Liu, Yuxuan Liang, Ming Jin, Stefan Zohren, Dan Pei, Yan Liu, and Qingsong Wen. Position: Empowering Time Series Reasoning with Multimodal LLMs, 2025b.
 - Xiang Lan, Feng Wu, Kai He, Qinghao Zhao, Shenda Hong, and Mengling Feng. Gem: Empowering mllm for grounded ecg understanding with time series and images. *arXiv* preprint arXiv:2503.06073, 2025.
 - Mengdi Li, Jiaye Lin, Xufeng Zhao, Wenhao Lu, Peilin Zhao, Stefan Wermter, and Di Wang. Curriculum-rlaif: Curriculum alignment with reinforcement learning from ai feedback, 2025. URL https://arxiv.org/abs/2505.20075.
 - Zhonghang Li, Lianghao Xia, Yong Xu, and Chao Huang. GPT-ST: Generative Pre-Training of Spatio-Temporal Graph Neural Networks. *Advances in Neural Information Processing Systems*, 36:70229–70246, 2023.
 - Yuebing Liang, Yichao Liu, Xiaohan Wang, and Zhan Zhao. Exploring large language models for human mobility prediction under public events. *Computers, Environment and Urban Systems*, 112: 102153, 2024. ISSN 0198-9715.
 - Yuxuan Liang, Haomin Wen, Yutong Xia, Ming Jin, Bin Yang, Flora Salim, Qingsong Wen, Shirui Pan, and Gao Cong. Foundation Models for Spatio-Temporal Data Science: A Tutorial and Survey. In *Proceedings of the 31st ACM SIGKDD Conference on Knowledge Discovery and Data Mining V.2*, pp. 6063–6073. ACM, 2025.
 - Hunter Lightman, Vineet Kosaraju, Yuri Burda, Harrison Edwards, Bowen Baker, Teddy Lee, Jan Leike, John Schulman, Ilya Sutskever, and Karl Cobbe. Let's verify step by step. In *The Twelfth International Conference on Learning Representations*, 2023.
 - Guolong Liu, Jinjie Liu, Yan Bai, Chengwei Wang, Haosheng Wang, Huan Zhao, Gaoqi Liang, Junhua Zhao, and Jing Qiu. EWELD: A Large-Scale Industrial and Commercial Load Dataset in Extreme Weather Events. *Scientific Data*, 10(1):615, 2023a. ISSN 2052-4463.

- Hengbo Liu, Ziqing Ma, Linxiao Yang, Tian Zhou, Rui Xia, Yi Wang, Qingsong Wen, and Liang Sun. Sadi: A self-adaptive decomposed interpretable framework for electric load forecasting under extreme events, 2023b. URL https://arxiv.org/abs/2306.08299.
 - Yong Liu, Tengge Hu, Haoran Zhang, Haixu Wu, Shiyu Wang, Lintao Ma, and Mingsheng Long. itransformer: Inverted transformers are effective for time series forecasting. In *The Twelfth International Conference on Learning Representations*, 2024.
 - Ziyu Liu, Zeyi Sun, Yuhang Zang, Xiaoyi Dong, Yuhang Cao, Haodong Duan, Dahua Lin, and Jiaqi Wang. Visual-rft: Visual reinforcement fine-tuning. *arXiv preprint arXiv:2503.01785*, 2025.
 - Minrong Lu and Xuerong Xu. Trnn: An efficient time-series recurrent neural network for stock price prediction. *Information Sciences*, 657:119951, 2024.
 - Yucong Luo, Yitong Zhou, Mingyue Cheng, Jiahao Wang, Daoyu Wang, Tingyue Pan, and Jintao Zhang. Time Series Forecasting as Reasoning: A Slow-Thinking Approach with Reinforced LLMs, 2025.
 - A. Craig MacKinlay. Event Studies in Economics and Finance. *Journal of Economic Literature*, 35 (1):13–39, 1997. ISSN 0022-0515.
 - Mike A. Merrill, Mingtian Tan, Vinayak Gupta, Tom Hartvigsen, and Tim Althoff. Language Models Still Struggle to Zero-shot Reason about Time Series, 2024.
 - Kingsley Nweye, Zoltan Nagy, Sharada Mohanty, Dipam Chakraborty, Siva Sankaranarayanan, Tianzhen Hong, Sourav Dey, Gregor Henze, Jan Drgona, Fangquan Lin, et al. The citylearn challenge 2022: Overview, results, and lessons learned. *NeurIPS 2022 Competition Track*, pp. 85–103, 2023.
 - OpenAI, Josh Achiam, Steven Adler, Sandhini Agarwal, Lama Ahmad, Ilge Akkaya, Florencia Leoni Aleman, Diogo Almeida, et al. GPT-4 Technical Report, 2024a.
 - OpenAI, Aaron Jaech, Adam Kalai, Adam Lerer, Adam Richardson, Ahmed El-Kishky, et al. OpenAI o1 System Card, 2024b.
 - Jeff Rasley, Samyam Rajbhandari, Olatunji Ruwase, and Yuxiong He. Deepspeed: System optimizations enable training deep learning models with over 100 billion parameters. In *Proceedings of the 26th ACM SIGKDD international conference on knowledge discovery & data mining*, pp. 3505–3506, 2020.
 - David Rein, Betty Li Hou, Asa Cooper Stickland, Jackson Petty, Richard Yuanzhe Pang, Julien Dirani, Julian Michael, and Samuel R. Bowman. GPQA: A graduate-level google-proof q&a benchmark. In *First Conference on Language Modeling*, 2024. URL https://openreview.net/forum?id=Ti67584b98.
 - Zhihong Shao, Peiyi Wang, Qihao Zhu, Runxin Xu, Junxiao Song, Xiao Bi, Haowei Zhang, Mingchuan Zhang, YK Li, Y Wu, et al. Deepseekmath: Pushing the limits of mathematical reasoning in open language models. *arXiv preprint arXiv:2402.03300*, 2024.
 - Guangming Sheng, Chi Zhang, Zilingfeng Ye, Xibin Wu, Wang Zhang, Ru Zhang, Yanghua Peng, Haibin Lin, and Chuan Wu. Hybridflow: A flexible and efficient rlhf framework. *arXiv preprint arXiv:* 2409.19256, 2024.
 - Xiaoming Shi, Shiyu Wang, Yuqi Nie, Dianqi Li, Zhou Ye, Qingsong Wen, and Ming Jin. Timemoe: Billion-scale time series foundation models with mixture of experts. *arXiv preprint arXiv:2409.16040*, 2024.
 - Gideon Stein, Maha Shadaydeh, Jan Blunk, Niklas Penzel, and Joachim Denzler. CausalRivers Scaling up benchmarking of causal discovery for real-world time-series, 2025.
 - Huajie Tan, Yuheng Ji, Xiaoshuai Hao, Minglan Lin, Pengwei Wang, Zhongyuan Wang, and Shanghang Zhang. Reason-rft: Reinforcement fine-tuning for visual reasoning, 2025a. URL https://arxiv.org/abs/2503.20752.

- Mingtian Tan, Mike A. Merrill, Zack Gottesman, Tim Althoff, David Evans, and Tom Hartvigsen.
 Inferring Events from Time Series using Language Models, 2025b.
- Qwen Team. Qwen2.5: A party of foundation models, September 2024. URL https://qwenlm.github.io/blog/qwen2.5/.
 - Binwu Wang, Jiaming Ma, Pengkun Wang, Xu Wang, Yudong Zhang, Zhengyang Zhou, and Yang Wang. STONE: A Spatio-temporal OOD Learning Framework Kills Both Spatial and Temporal Shifts. In *Proceedings of the 30th ACM SIGKDD Conference on Knowledge Discovery and Data Mining*, KDD '24, pp. 2948–2959. Association for Computing Machinery. ISBN 979-8-4007-0490-1.
 - Jiahao Wang, Mingyue Cheng, and Qi Liu. Can Slow-thinking LLMs Reason Over Time? Empirical Studies in Time Series Forecasting, 2025.
 - Kun Wang, Hao Wu, Yifan Duan, Guibin Zhang, Kai Wang, Xiaojiang Peng, Yu Zheng, Yuxuan Liang, and Yang Wang. Nuwadynamics: Discovering and updating in causal spatio-temporal modeling. In *The Twelfth International Conference on Learning Representations*, 2024a.
 - Shiyu Wang, Jiawei Li, Xiaoming Shi, Zhou Ye, Baichuan Mo, Wenze Lin, Shengtong Ju, Zhixuan Chu, and Ming Jin. Timemixer++: A general time series pattern machine for universal predictive analysis. *arXiv* preprint arXiv:2410.16032, 2024b.
 - Jason Wei, Xuezhi Wang, Dale Schuurmans, Maarten Bosma, Brian Ichter, Fei Xia, Ed Chi, Quoc Le, and Denny Zhou. Chain-of-thought prompting elicits reasoning in large language models, 2023. URL https://arxiv.org/abs/2201.11903.
 - Andrew Robert Williams, Arjun Ashok, Étienne Marcotte, Valentina Zantedeschi, Jithendaraa Subramanian, Roland Riachi, James Requeima, Alexandre Lacoste, Irina Rish, Nicolas Chapados, and Alexandre Drouin. Context is Key: A Benchmark for Forecasting with Essential Textual Information.
 - Gerald Woo, Chenghao Liu, Akshat Kumar, Caiming Xiong, Silvio Savarese, and Doyen Sahoo. Unified Training of Universal Time Series Forecasting Transformers, 2024.
 - Haixu Wu, Tengge Hu, Yong Liu, Hang Zhou, Jianmin Wang, and Mingsheng Long. Timesnet: Temporal 2d-variation modeling for general time series analysis. *ICLR*, 2023.
 - Zhe Xie, Zeyan Li, Xiao He, Longlong Xu, Xidao Wen, Tieying Zhang, Jianjun Chen, Rui Shi, and Dan Pei. ChatTS: Aligning Time Series with LLMs via Synthetic Data for Enhanced Understanding and Reasoning, 2025.
 - Yiyuan Yang, Zichuan Liu, Lei Song, Kai Ying, Zhiguang Wang, Tom Bamford, Svitlana Vyetrenko, Jiang Bian, and Qingsong Wen. Time-RA: Towards Time Series Reasoning for Anomaly with LLM Feedback, 2025.
 - Wen Ye, Jinbo Liu, Defu Cao, Wei Yang, and Yan Liu. When LLM Meets Time Series: Can LLMs Perform Multi-Step Time Series Reasoning and Inference, 2025.
 - Kun Yi, Qi Zhang, Wei Fan, Hui He, Liang Hu, Pengyang Wang, Ning An, Longbing Cao, and Zhendong Niu. Fouriergnn: Rethinking multivariate time series forecasting from a pure graph perspective. *Advances in Neural Information Processing Systems*, 36, 2024.
 - Weihao Yu, Zihang Jiang, Yanfei Dong, and Jiashi Feng. Reclor: A reading comprehension dataset requiring logical reasoning. *arXiv preprint arXiv:2002.04326*, 2020.
 - Yufei Zhan, Yousong Zhu, Shurong Zheng, Hongyin Zhao, Fan Yang, Ming Tang, and Jinqiao Wang. Vision-r1: Evolving human-free alignment in large vision-language models via vision-guided reinforcement learning. *arXiv preprint arXiv:2503.18013*, 2025.
 - Haochuan Zhang, Chunhua Yang, Jie Han, Liyang Qin, and Xiaoli Wang. TempoGPT: Enhancing Time Series Reasoning via Quantizing Embedding, 2025a.

- Junru Zhang, Lang Feng, Xu Guo, Yuhan Wu, Yabo Dong, and Duanqing Xu. TimeMaster: Training Time-Series Multimodal LLMs to Reason via Reinforcement Learning, 2025b.
 - Qingyang Zhang, Haitao Wu, Changqing Zhang, Peilin Zhao, and Yatao Bian. Right question is already half the answer: Fully unsupervised llm reasoning incentivization. *arXiv preprint arXiv:2504.05812*, 2025c.
 - Xiaojiang Zhang, Jinghui Wang, Zifei Cheng, Wenhao Zhuang, Zheng Lin, Minglei Zhang, Shaojie Wang, Yinghan Cui, Chao Wang, Junyi Peng, et al. Srpo: A cross-domain implementation of large-scale reinforcement learning on llm. *arXiv preprint arXiv:2504.14286*, 2025d.
 - Bendong Zhao, Huanzhang Lu, Shangfeng Chen, Junliang Liu, and Dongya Wu. Convolutional neural networks for time series classification. 28(1):162–169. ISSN 1004-4132.
 - Yanli Zhao, Andrew Gu, Rohan Varma, Liang Luo, Chien-Chin Huang, Min Xu, Less Wright, Hamid Shojanazeri, Myle Ott, Sam Shleifer, et al. Pytorch fsdp: experiences on scaling fully sharded data parallel. *arXiv preprint arXiv:2304.11277*, 2023.
 - Zirui Zhao, Hanze Dong, Amrita Saha, Caiming Xiong, and Doyen Sahoo. Automatic curriculum expert iteration for reliable LLM reasoning. In *The Thirteenth International Conference on Learning Representations*, 2025. URL https://openreview.net/forum?id=3ogIALgghF.
 - Yaowei Zheng, Richong Zhang, Junhao Zhang, Yanhan Ye, Zheyan Luo, Zhangchi Feng, and Yongqiang Ma. Llamafactory: Unified efficient fine-tuning of 100+ language models. *arXiv* preprint arXiv:2403.13372, 2024.
 - Yu Zheng, Huan Yee Koh, Ming Jin, Lianhua Chi, Haishuai Wang, Khoa T. Phan, Yi-Ping Phoebe Chen, Shirui Pan, and Wei Xiang. Graph spatiotemporal process for multivariate time series anomaly detection with missing values. 106:102255. ISSN 1566-2535.

A THE USE OF LARGE LANGUAGE MODELS

During the preparation of this manuscript, we only employed large language models as auxiliary tools for non-substantive tasks. Their applications were limited to assisting in code debugging, checking grammar and formatting consistency, and improving the fluency of written text. The research design, experimental analysis, and conceptual contribution were independent of the LLMs output. All scientific insights and conclusions presented in this work are solely attributable to the authors.

B FURTHER RELATED WORK

756

757 758

759

760

761

762

763 764 765

766 767 768

769

770

771

772

773

774

775

776

777

778

779

781

782

783

784

785

786

787

788

789

790

791 792 793

794

796

797

798

799

800

801

802

803

804

805

806

807

808

Time series analysis has underpinned applications in finance, energy, transportation, healthcare, among others, over the past decade (Lu & Xu, 2024; Liu et al., 2023b; Guan et al., 2023; Lan et al., 2025). Most existing studies still concentrate on a single specific task, such as forecasting, classification, anomaly detection, and imputation (Guan et al.; Zhao et al.; Zheng et al.; Jiaheng et al.). These systems are typically task-specific and lack generality across tasks. Attempts such as TimesNet (Wu et al., 2023) and UNITS (Gao et al.) replace the output layer and loss to reuse a common backbone across tasks, but the resulting models still exhibit limited out-of-distribution (OOD) robustness. Transfer-learning approaches (Ismail Fawaz et al.; Wang et al.) and pre-trained models (Li et al., 2023) seek to mitigate OOD shifts; however, empirical evaluations typically remain domain-specific (e.g., different districts of one city) rather than achieving genuine transfer from domain A to domain B. A growing line of work further argues that a core bottleneck in time series analytics lies in the lack of integration with supplementary textual knowledge (Williams et al.; Ge et al., 2025), yet current models remain **modality-locked**, being unable to ingest such event information in textual form. In addition, most existing models adopt fixed output formats and depend on black-box computation, providing limited interpretability, even though some efforts rely on attention map (Liu et al., 2024), causal inference (Wang et al., 2024a), or visualization of hidden representations (Wang et al., 2024b; Cai et al., 2024; Yi et al., 2024) to offer implicit explanations. Such latent interpretability, however, is often difficult for non-experts to understand or trust.

In contrast to these models, TSR-SUITE mitigates domain-specific brittleness by curating cross-domain, reasoning-critical time series data and expanding the task space beyond surface QA. And TIMEOMNI-1 improves reasoning accuracy and OOD generalization at scale across diverse domains through multi-task joint training. Finally, TIMEOMNI-1 yields step-by-step rationales that decompose temporal priors, event effects, and decision criteria, turning black-box predictions into transparent, reproducible reasoning.

C LIMITATIONS OF EXISTING TIME SERIES REASONING DATASETS

As a supplement to the Section 3.1, we also conducted additional experiments on existing datasets to assess how these limitations affect reasoning performance (shown in Figure 9): (1) Reasoning necessity. Across most tasks, Time-MQA, pre-trained LLMs, and fine-tuned TS-LLMs do not exhibit clear performance separation, indicating that the difficulty distribution lacks sufficient granularity to discriminate model capabilities. Moreover, CoT-based SFT does not outperform ANS-based SFT, suggesting that explicit reasoning is not required to solve these tasks. In fact, when tasks can be addressed through surface-level pattern matching, extra reasoning capacity yields only marginal gains. Therefore, we should construct dataset with calibrated difficulty gradients that genuinely require reasoning to solve. (2) Context sufficiency. For anomaly detection, current datasets lack relevant contextual information, forcing models to decide solely from the input sequences. As a result, both Time-MQA and pre-trained LLMs achieve only 50-60% accuracy, barely above random selection. After training, performance of ANS-based SFT improves by more than 20% on the ID subset, whereas CoT-based gains are less than half of that, indicating that improvements primarily come from directly mapping encoded sequence features to anomalous outcomes, rather than reasoning about the causes of anomalies. Consequently, for TSR with LLMs, we should prioritize providing sufficient context to support reasoning, rather than pushing models to overfit of time-series signals.




Figure 9: Evidence for the necessity of reasoning and the sufficiency of context on Time-MQA dataset: multiple-choice and true/false tasks saturate in in-distribution settings, while the anomaly-detection task exhibits apparent guessing under out-of-distribution shift.

D DATASET DETAILS

D.1 RAW DATA SOURCE

Task 1: Scenario Understanding. We collect diverse time series data across different scenarios from the work of Merrill et al. (2024). The out-of-distribution (OOD) test set is constructed based on the original domains of the time series data: specifically, samples from the *Agricultural*, *Education* and *Healthcare* domains are used as OOD test data.

Task 2: Causality Discovery. We perform causal discovery on river discharge time series from the CausalRivers dataset (Stein et al., 2025), aiming to uncover causal relationships from observational data. Ground-truth causal directions are determined according to river flow: the amount of water measured at an upstream station directly influences the amount measured downstream at a later time, and we thus consider such relations causal; if two rivers are not connected, we consider them non-causal. For the OOD test set, we split by geographical regions: training and in-distribution (ID) test data are taken from Eastern Germany, while the OOD test set is sourced from Bavaria.

Task 3: Event-aware Forecasting. We use a human mobility dataset as the primary training scenario, specifically taxi drop-off data near the Barclays Center in New York City. We collect the raw time series together with aligned events from Liang et al. (2024); Ge et al. (2025). For the OOD test set,

we adopt electricity load time series paired with weather events from the EWELD dataset (Liu et al., 2023a).

Task 4: Decision Making. To evaluate decision-making with counterfactual reasoning ability (i.e., reasoning about the outcomes of unobserved actions), we adopt a sandbox environment based on real building load data. Specifically, we use the CityLearn dataset (Nweye et al., 2023), which provides building load profiles and battery charge/discharge operations under a dynamic pricing scheme. Given 48 hours of historical building load and peak-valley pricing information, models are required to determine charge/discharge strategies for the next 24 hours. For the OOD test set, we select two buildings whose load patterns differ significantly from those in the training and ID test sets.

For all four tasks, we construct clear data pipelines, as detailed in Section 3.2, thereby facilitating future dataset expansions and task extensions.

D.2 DATA STATISTICS

This section provides the detailed quantitative breakdown of TSR-SUITE, complementing the high-level overview in Section 3.2. Table 3 lists the number of samples available for each reasoning task, stratified by their use in the two-stage training (Stage 1 SFT and Stage 2 RL) as well as in-distribution (ID) and out-of-distribution (OOD) testbed. The data confirms a substantial scale for SFT (Stage 1) and an even larger set for RL (Stage 2), ensuring robust learning and generalization evaluation for each task.

Task	#Stage 1 Train	#Stage 2 Train	#ID Test	#OOD Test
Scenario Understanding	609	5104	200	899
Causality Discovery	778	6044	800	800
Event-aware Forecasting	400	2780	418	476
Decision Making	552	3284	188	273

Table 3: Detailed sample count statistics for the four time series reasoning tasks in TSR-SUITE across training stages and testbed.

D.3 TASK 3 (EVENT-AWARE FORECASTING) SPECIAL NOTES

Table 4: MAE(\downarrow) of CoT-SFT with different chain construction on Task 3.

	ID	OOD
LLM Analyzer Generated Ground Truth Guided		157.2 395.56

Unlike multiple-choice tasks, where correct answers are explicitly listed among options, Task 3 requires forecasting future sequence within a fixed output window. This open-ended formulation significantly increases the difficulty of constructing coherent reasoning chains and prevents the LLM Analyzer from perfectly predicting results that are fully aligned with the ground truth. However, instead of guiding the generation of reasoning chains using the ground truth, we allowed the LLM Analyzer to generate predictions based on its own understanding. In our experiments, reasoning chains generated with ground-truth hints consistently resulted in worse CoT based SFT performance compared to those produced directly by the LLM Analyzer as shown in Table 4. This result also aligns with recent findings (Zhao et al., 2025; Gao et al., 2025; Li et al., 2025), which suggests that the most effective training data are instances slightly beyond a model's current ability but not prohibitively difficult. Furthermore, ground-truth—guided chains tend to obscure the task's inherent difficulty and deviate from the base model's natural data distribution. Therefore, we examine the cases and select 400 samples with relatively low MAE chains generated by the LLM Analyzer without relying on ground-truth hints as supervision for Stage 1 training to balance difficulty and quality.

D.4 HUMAN EVALUATION INTERFACE

As described in Figure 3, when the LLM Analyzer (GPT-4.1 in our case) fails to solve a sample in Step 1, the instance proceeds to Step 2. In this step, human reviewers use the interface shown in Figure 10 to examine whether the provided context is sufficient to disambiguate the answer. If the question is solvable by human reviewers, their reasoning chains are further polished by the LLM Rewriter to follow our structured templates, and the resulting samples are collected as Step 2 CoT data.




Figure 10: Screenshot of the human evaluation interface used in Step 2 of Hierarchical CoT Annotation.

E PROMPT USED IN THIS PAPER

E.1 HUMAN-GUIDED REASONING TEMPLATE FOR HIERARCHICAL COT ANNOTATION.

As detailed in Section 3.2, our hierarchical annotation pipeline relies on structured reasoning templates to ensure consistency and quality in the Chain-of-Thought (CoT) generation process. These templates serve as explicit guidelines for the LLM Analyzer in the initial solving phase, as well as for human experts during verification and the LLM Rewriter in the refinement phase. The templates defined in this section are specifically designed for CoT annotation only. They provide a systematic framework for breaking down each reasoning task into logical steps, ensuring that all annotated traces follow a consistent structure while capturing the essential temporal reasoning processes. This approach guarantees that the resulting CoT data maintains high quality and facilitates effective model learning.

Human-guided Reasoning Template for Task1: Scenario Understanding

Step 1. Series length check Observed length={L}. Expected per option: A{exp_len_A}; B{exp_len_B}; C{exp_len_C}; D{exp_len_D}. Retain option(s) whose expected length \approx L.

Step 2. Magnitude & unit sanity

 Value range= $\{\min\}-\{\max\}$. Typical ranges: A $\{\text{range_A}\}$; B $\{\text{range_B}\}$; C $\{\text{range_C}\}$; D $\{\text{range_D}\}$. Eliminate options whose units/ranges mismatch.

Step 3. Shape & temporal pattern

Note trends/seasonality/spikes: {key_patterns}. Compare to option narratives: A{match_or_not}; B{match_or_not}; C{match_or_not}. Keep best-matching narratives.

Step 4. External-event alignment

Identify clear events (e.g., single-day surge, mid-series drop): {events}. Which option explicitly explains this?

Step 5. Final elimination & plausibility

Remaining candidates: {remaining}. Choose the scenario that satisfies all of length, magnitude, pattern, and event consistency.

Step 6. Double-check length consistency

Confirm {tentative_choice} expected length =={L}? \rightarrow {yes/no}. If "no", revert to next best candidate; else accept. Final choice: {chosen_option}.

Human-guided Reasoning Template for Task2: Causality Discovery

Step 1. Trend Consistency

Check whether the two series demonstrate structurally consistent trends, such as shared "stable \rightarrow rise \rightarrow fall" shapes, both rise/fall at similar points (within $\pm 1-2$ time steps), and flat/stable periods aligned in time. It's OK for their absolute values to differ — match shape, not magnitude. Red Flag: If one rises while the other stays flat or falls \rightarrow Stop in the option: are not causal. Be perceptually flexible. Flatness doesn't require perfect constancy — as long as fluctuations are very small relative to the scale of the full time series, they can still be considered flat.

Step 2. Key Fluctuation Alignment

Check whether the two time series have notable peaks, dips, or inflection points at the same or nearly the same time.

You must ensure: Spikes/dips occur within ± 1 –2 steps (which means ≤ 24 hours lag if sampling is 12h). For time series with low overall discharge (maybe near 0), even modest changes can be meaningful if they represent a clear pattern change relative to baseline. If peaks differ by ≥ 3 steps, it's too much lag to infer causality \rightarrow the two time series are not causal. Do not confuse visually similar shapes with causality if key changes happen at clearly different times.

Step 3. Direction of Causality

Only perform this step if both Step 1 and 2 pass. Use the domain principle: "Small rivers flow into big rivers" — not the reverse.

 $Rule: If \text{`mean}(A) < mean(B)\text{`, then `}A \rightarrow B\text{`. If `mean}(B) < mean(A)\text{`, then `}B \rightarrow A\text{`.}$

Notes: If Step 1 or 2 fails, skip Step 3. Timing matters: 3 steps of lag (36h) is already too much. Matching is about structure and timing, not numbers.

Human-guided Reasoning Template for Task3: Event-aware Forecasting

Step 1. Identify the baseline patterns

You should first identify the baseline patterns and trend from the historical series.

Step 2. Estimate the impact of any events

Next, estimate the incremental impact of any special events (pre-event buildup, during-event lift, post-event dispersal) as an overlay on the baseline.

Step 3. Combine the baseline and event effects

Finally, given the current context, combine the baseline and event effects to generate the forecast sequence.

Human-guided Reasoning Template for Task4: Decision Making

Step 1. Forecast the next 24-hour load

Use the historical 48-hour load pattern to generate a forecast for tomorrow's 24-hour load. Pay special attention to the peak-price hours and estimate the likely loads during those hours.

Step 2. Principles for evaluating strategies

Charging should take place during off-peak hours when electricity price is low. Discharging should take place during peak hours when electricity price is high and forecasted load is significant. Avoid charging during peak hours or discharging during off-peak hours, as these operations increase cost instead of saving it.

Step 3. Cost calculation and strategy comparison

For each strategy, compute the expected saving using:

Saving =
$$\sum_{h \in \text{peak}} \min(\hat{L}(h), P_{\text{max}}^{\text{dis}}) \cdot (p_{\text{peak}} - p_{\text{valley}})$$

where $\hat{L}(h)$ is the forecasted load at hour h, P_{\max}^{dis} is the maximum discharging power, and p_{peak} , p_{valley} are the peak and valley electricity prices. Select the strategy with the highest saving.

E.2 System Prompt for Training and Evaluation

This section presents the system prompts used in the ablation study on training stages (Section 4.2). The prompts are categorized into two types: **Chain-of-Thought(CoT)** prompts that require models to generate reasoning traces before answers, and **Answer-only(ANS)** prompts that directly output final answers without explicit reasoning.

For Tasks 1, 2, and 4, the CoT prompts enforce a structured output format where models must provide step-by-step reasoning within <think> tags before the final answer in <answer> tags. The ANS prompts for these tasks skip the reasoning step and output only the final answer. For Task 3, the prompts are adapted to accommodate sequence predictions while maintaining the same CoT/ANS distinction. These prompts ensure consistent evaluation across different training configurations: ANS-SFT uses ANS prompts, CoT-SFT uses CoT prompts, and CoT-SFT+RL uses CoT prompts during both training stages.

System Prompt of CoT for Task1, 2 and 4

Output Format:

<think>Your step-by-step reasoning process that justifies your answer</think>
<answer>Your final answer(Note: Only output a single uppercase letter of the correct option)</answer>

System Prompt of CoT for Task3

You should think the impact of the event first, then output the predicted sequence.

Output Format:

 <think>Your step-by-step reasoning process</think>

<answer>[Your predicted sequence]</answer>

System Prompt of ANS for Task1, 2 and 4

Output Format:

<answer>Your final answer(Note: Only output a single uppercase letter of the correct option)</answer>

System Prompt of ANS for Task3

You should output the predicted sequence directly.

Output Format:

<answer>[Your predicted sequence]</answer>

F IMPLEMENTATION DETAILS OF THE TRAINING STAGES

F.1 STAGE 1: SUPERVISED FINE-TUNING (SFT)

SFT is a process where a pre-trained model is further trained on a labeled dataset to adapt it for a specific task. This is achieved by minimizing the negative log-likelihood of the output given the input data. In the context of time series reasoning, the model learns to generate intermediate rationales and final answers based on observed time series data and auxiliary context. Specifically, based on a carefully curated dataset $\mathcal{D} = \{(X_i, C_i, R_i, y_i)\}_{i=1}^N$, the model's parameters θ are updated by minimizing the loss function:

$$\mathcal{L}(\theta; \mathcal{D}) = -\frac{1}{N} \sum_{i=1}^{N} \log \pi_{\theta}((R_i', y_i') | (X_i, C_i))$$
(3)

where R'_i and y'_i are the predicted rationale and final answer, respectively. And for the *i*-th example, X_i and C_i represent the observed time series and auxiliary context.

F.2 STAGE 2: REINFORCEMENT LEARNING (RL)

In reinforcement learning, we employ the group relative policy optimization (GRPO) algorithm (Shao et al., 2024) to refine our post-SFT model using carefully designed reward functions. Given an input pair (X,C), GRPO samples N rationale-answer trajectories $\{(R_i,y_i)\}_{i=1}^N$ from the policy model π_θ , and organizes them into groups $\{\mathcal{G}_b\}_{b=1}^B$. The reward for trajectory $i \in \mathcal{G}_b$ is computed as

$$\hat{A}_i = \mathcal{R}(R_i, y_i) - \frac{1}{|\mathcal{G}_b|} \sum_{j \in \mathcal{G}_b} \mathcal{R}(R_j, y_j), \tag{4}$$

where \mathcal{R} combines both the correctness of the answer and the quality of the response format. The policy is then updated using the following objective:

$$\mathcal{L}^{\text{GRPO}}(\theta) = \frac{1}{N} \sum_{i=1}^{N} \left[\min \left(\frac{\pi_{\theta}(R_i, y_i \mid X, C)}{\pi_{\theta_{\text{refer}}}(R_i, y_i \mid X, C)} \hat{A}_i, \right. \right.$$

$$\left. \text{clip}\left(\frac{\pi_{\theta}}{\pi_{\theta_{\text{refer}}}}, 1 - \epsilon, 1 + \epsilon \right) \hat{A}_i \right) - \beta D_{\text{KL}}(\pi_{\theta} \parallel \pi_{\theta_{\text{refer}}}) \right]$$
(5)

Here, $\pi_{\theta_{\text{refer}}}$ indicates the post-SFT model. ϵ and β are hyperparameters that control the clipping threshold of the PPO update and the weight of the Kullback-Leibler (KL) divergence penalty, respectively.

G TIME SERIES TASK-GROUNDED REWARD DESIGN

All samples are required to follow a *basic format reward* \mathcal{R}_{format} , which checks whether outputs comply with the schema <think>...</think><answer>...</answer>. For discrete-output tasks (scenario understanding, causality discovery, decision-making), correctness is directly measurable by

$$\mathcal{R}_{\text{discrete}} = \begin{cases} 1, & \hat{y} = y, \\ 0, & \text{otherwise.} \end{cases}$$
 (6)

For sequence-output task (event-aware forecasting), we define a continuous reward based on the exponential decay of mean absolute error (MAE):

$$MAE = \frac{1}{T} \sum_{t=1}^{T} |\hat{y}_t - y_t|,$$
 (7)

$$\mathcal{R}_{\text{sequence}} = \begin{cases} 0, & \text{if } \operatorname{len}(\hat{y}) \neq \operatorname{len}(y), \\ \exp(-\alpha \cdot \operatorname{MAE}) + \mathcal{R}_{\text{count}}, & \text{if } \operatorname{len}(\hat{y}) = \operatorname{len}(y), \end{cases}$$
(8)

together with a horizon-matching bonus $\mathcal{R}_{count} = 0.1$. And the final per-sample reward integrates all components as:

$$\mathcal{R}_i = \lambda \mathcal{R}_{\text{format}} + (1 - \lambda) \mathcal{R}_{\text{task}}, \tag{9}$$

where $\mathcal{R}_{\text{task}}$ refers to $\mathcal{R}_{\text{discrete}}$ for discrete-output tasks and $\mathcal{R}_{\text{sequence}}$ for sequence-output task. We set $\lambda = 0.1$ in all experiments.

H TRAINING CONFIGURATION

Our training process follows a two-stage procedure, consisting of supervised fine-tuning (SFT) followed by reinforcement learning (RL). For the SFT stage, we begin by fine-tuning the Qwen2.5-7B-Instruct (Team, 2024) with full-parameter updates for a total of 1 epoch, utilizing DeepSpeed ZeRO-3 (Rasley et al., 2020) for efficient training. The fine-tuning is performed in BF16 precision with FlashAttention-2 enabled to accelerate attention operations. The maximum sequence length is set to 8192, and the per-device batch size is 1, with gradient accumulation of 32. The optimization procedure uses a peak learning rate of 1.0×10^{-5} with a cosine learning rate scheduler and the warm-up ratio as 0.1. All training is carried out using the LLaMA-Factory repository (Zheng et al., 2024) on a system equipped with a single NVIDIA H200-140G GPU. In the RL stage, we continue training from the Stage 1 checkpoint using the verl repository (Sheng et al., 2024) and FSDP (Zhao et al., 2023) under BF16 precision. The maximum sequence length is reduced to 2048, and training is performed across 8 NVIDIA A100-80G GPUs. The training batch size is 128, with RL minibatches of size 32 and per-GPU micro-batches of 8. Gradient clipping is applied with a maximum global norm of 3.0, and a KL-penalty coefficient of 0.04 is used to regulate the model. For rollouts, 8 trajectories are collected per update, with a sampling temperature of 0.7. The learning rate is set to 1.0×10^{-6} , and training continues for 3 epochs.


I CASE STUDY

Table 5: Task1 (Scenario Understanding) example with options and reasoning process.

1195 Task1: Scenario Understanding

User

You are given a time series. Please identify the scenario that most likely created it. [39, 58, 51, 45, 40, 39, 57, 45, 45, 34, 40, 32.64, 62, 92, 37, 31, 29.52, 46, 69, 79, 43, 51, 50, 50, 56, 45, 57, 32, 35, 55, 38, 41, 38, 54, 33, 48, 54, 40.45, 30.31, 56, 49, 37.41, 45, 39, 49, 31.52, 47, 51, 33, 53, 38.49, 33, 30, 35.52, 41, 32.61, 52, 44, 29.68, 41, 32.44, 46.5, 49, 48, 38, 46, 38, 49, 45, 52, 47, 45, 39, 47, 44.47, 28, 36, 39, 27.67, 43, 37, 41, 52, 50, 37, 30, 30, 27.4, 33, 40, 35.51, 38, 35.43, 38, 37, 42, 28.49, 27, 47, 32.45, 30, 42, 36.39, 29.62, 27, 29.55, 32, 46, 44, 29.42, 26.72, 32, 44, 34.61, 37, 45, 45, 38.44, 42, 50, 34, 47.5, 51, 30, 31.56, 34, 42, 45, 39, 30, 42, 34, 50, 27.33, 38, 41.55, 32.43, 40, 40, 50, 39, 33.53, 26, 25.73, ..., 27, 30, 22.59, 38, 33, 26.58, 23.48, 32.62, 40, 20.33, 27.4, 33.44, 35.42, 33.34, 31, 38, 34, 21, 21, 38, 36].



Options:

- A. ATM daily cash withdrawals over a year with an annual festival (365 daily samples).
- **B.** Weekend music festival causing a surge in noise levels (96 hourly samples).
- C. Hourly restaurant food orders during a 2-week local food festival (336 hourly samples).
- **D.** NYC daily taxi pick-ups over a year with a subway strike (365 daily samples).

TIMEOMNI-1

<think>

1) Length check.

Observed length is 336. Options expect: A= 365, B= 96, C= 336, D= 365. Only C matches exactly.

2) Magnitude sanity.

Values span ≈ 15 –92, reasonable for *hourly* food orders in a busy restaurant (C). NYC daily taxi rides (D) are typically in the thousands; A and B already fail length.

3) Shape/pattern.

Fluctuating baseline with intermittent surges (e.g., 92) and no single prolonged spike—consistent with repeated demand bursts during a local festival (C).

4) Event alignment.

A 2-week festival plausibly produces multiple hourly peaks across days (C), rather than one annual or weekend-only spike (A/B), and not daily-year scale (D).

5) Double-check.

2 weeks \times 24 hours = 336 \Rightarrow consistent with (C).

</think>

<answer>C</answer>

1246 1247

1248 1249

1250

1251

1252

1255

1256

1257

1259

1261 1262

1263 1264

1265 1266 1267

1268 1269

1270

1271

1272

1273

1278

1279

1280

1281

1282

1283

1284

1285

1286

1290

1291

1293

1242


Table 6: Task2 (Causal discovery) example with options and reasoning process.

Task2: Causal Discovery



User

You are given two time series related to river discharge measurements, expressed in m^3/s . Through causal discovery methods, we aim to identify potential causal relationships between different measuring stations from time-series data alone. The time series of A463 is: [4.12, 3.8, 3.44, 3.11, 2.97, 2.85, 2.79, 2.76, 2.63, 2.74, 2.69, 2.77, 2.75, 2.79, 2.97, 3, 3.09, 3.18, 3.24, 3.16, 3.16, 3.37, 3.37, 3.54, 3.56, 3.51, 3.43, 3.37, 3.37, 3.21, 3.12, 3.07, 3.16, 3.12, 3.16, 3.15, 2.95, 3, 2.95, 2.84, 2.75, 2.74, 2.74, 2.74, 2.74, 2.74, 2.6, 2.56, 2.56, 2.53, 2.54, 2.52, 2.33, 2.33, 2.33, 2.4, 2.61, 2.9, 3.22, 3.45, 3.58, 3.95], the time series of 4PRY is [7.55, 7.31, 7, 6.78, 6.5, 6.2, 6.08, 6, 6, 5.91, 5.82, 5.78, 5.84, 5.92, 5.88, 5.89, 5.82, 6, 6.25, 6, 5.94, 5.9, 5.9, 5.89, 5.89, 6, 6, 5.9, 5.74, 5.81, 5.67, 5.55, 5.35, 5.29, 5.14, 5.11, 5.18, 5.12, 5.11, 5.07, 4.89, 4.81, 4.82, 4.7, 4.69, 4.61, 4.67, 4.58, 4.45, 4.55, 4.42, 4.44, 4.32, 4.28, 4.37, 4.53, 4.5, 4.62, 4.84, 5, 5.43, 5.74]. Please identify the causal relationships between the two measurement stations? The data is collected every 12 hours from 2020-01-01 to 2020-01-31 totally 62 points each series.



Options:

- A. A463 is the cause and 4PRY is the effect
- B. A463 and 4PRY are not causal.
- C. 4PRY is the cause and A463 is the effect

🎢 TIMEOMNI-1

<t.hink>

1) Trend consistency (perceptual matching).

- Both A463 and 4PRY start with a gradual decrease over the first 10–12 points.
- Both show a rise around point 15–20, peaking at similar positions (A463 rises from 2.7 to 3.5, 4PRY from 5.8 to 6).
- Both then decline after their peaks, with a secondary smaller rise around point 45–50 (A463: 2.5 to 3.9; 4PRY: 4.3 to 5.7).
- The overall shapes match: both series are "decline \rightarrow flat \rightarrow rise \rightarrow fall \rightarrow rise" with similar timing.
- No major segment where one rises while the other falls or stays flat.

2) Key fluctuation alignment (peak synchrony).

- Major peaks occur nearly simultaneously (points \sim 19–20: A463 \approx 3.37; 4PRY \approx 5.9).
- Secondary peaks/dips are aligned within 1–2 steps.
- No meaningful lag (> 2 steps) between corresponding changes.

3) Direction of causality (hydrologic magnitude heuristic).

- Mean level: mean(A463) < mean(4PRY) (A463 mostly 2.5–3.5; 4PRY mostly 4.5–
- Hydrology rule-of-thumb: smaller tributaries feed larger channels ⇒ upstream (smaller) \rightarrow downstream (larger).

</think>

<answer>A</answer>

1301 1302 1303

1304

1305 1306

1307

1309

1310

1311

1313 1314

1315

1316

1317

1318

1319 1320

1321 1322

1323

1324

1325

1326

1328

1331

1332

1333

1334

1335

1336

1337

1338

1339

1340

1341

1342 1343 1344

1296 1297

Table 7: Task3 (Event-aware forecasting) example with reasoning process.

Task3: Event-aware forecasting



User

Over the past 48 hours (from 2015-05-29 00:00:00 to 2015-05-30 23:00:00), hourly taxi pickups were:

[26, 22, 9, 6, 1, 6, 3, 8, 11, 18, 11, 28, 22, 22, 26, 33, 44, 49, 76, 91, 85, 53, 69, 133, 116, 64, 28, 7, 8, 7, 1, 3, 12, 10, 22, 22, 35, 51, 37, 59, 57, 61, 50, 87, 54, 72, 56, 49]. Significant event in this window:

2015-05-29 17:00 BROOKLYN BOXING: Amir Khan vs. Chris Algieri & Fortuna vs. Vasquez.

In the next 24 hours: 2015-05-31 19:30 Ed Sheeran.



🎢 TIMEOMNI-1

<think>

1) Identify Baseline Patterns and Trends.

The data covers two days (48 hourly values). There is a clear daily pattern: low pickups overnight (midnight-6am), rising through morning, peaking late afternoon/evening. On both days, there is a pronounced spike around 17:00-20:00, likely due to the boxing event. After the spike, pickups drop sharply, then gradually decrease into the night.

2) Estimate Event Impact.

The 2015-05-29 17:00 boxing event caused a large surge: 17:44, 18:49, 19:76, 20: 91, 21: 85, 22: 53, 23: 69, then post-event dispersal 0-3h: 133, 116, 64, 28; well above baseline (\sim 20–30/h).

3) Context for Next Day.

Next event: 2015-05-31 19:30 Ed Sheeran concert. Expect similar pre-event buildup, a sharp spike during/after, then decline. No other events.

4) Forecast Sequence.

Use the prior non-event pattern as baseline and overlay an event-shaped spike at the concert time: Overnight (0–6) low (1–8); Morning (7–11) rising (8–18); Early afternoon (12–16) moderate (18–33); Pre-event (17–18) increase (33–44); Event spike (19–21) large (76–91); Post-event (22–23) decline (53–69).

5) Finalize Sequence.

For each hour, use baseline + event effect if applicable.

</think>

<answer>

[7, 5, 3, 2, 1, 2, 4, 7, 10, 13, 15, 18, 20, 22, 25, 30, 35, 44, 49, 76, 91, 85, 53, 69]


1347

Table 8: Task4 (Decision-making) example with reasoning process.

Task4: Decision-making



You manage a home energy storage system with battery capacity 18 kWh, current state-of-charge (SoC) 5 kWh, max charging power 5 kW, max discharging power 10 kW. Historical 48-hour hourly load (kWh) from 2023-07-10 00:00 to 2023-07-11 23:00 is given. Tomorrow's 24-hour pricing: off-peak \$0.22/kWh (hours 0–14, 20–23), peak \$0.54/kWh (hours 15–19). Based on historical usage, predict tomorrow's load and select the optimal 24-hour battery strategy from Options A–D (hour indices 0–23).



Options:

A. Charge: { 5,11 }; Discharge: { 2,18 }
B. Charge: { 1,2 }; Discharge: { 15,17 }
C. Charge: { 2,10 }; Discharge: { 18,19 }
D. Charge: { 11,14 }; Discharge: { 16,18 }

RIMEOMNI-1

<think>

1) Load forecast.

Mirror the most recent day (hours 24–47) as tomorrow's profile: [1.42, 3.16, 2.06, 1.03, 1.81, 1.02, 0.71, 0.34, 0.62, 0.75, 0.87, 2.44, 3.71, 1.98, 4.86, 1.37, 1.00, 0.65, 2.40, 0.40, 2.32, 2.51, 1.59, 0.76].

2) Prices & principle.

Off-peak: hours 0–14, 20–23 (\$0.22/kWh). Peak: hours 15–19 (\$0.54/kWh). Charge in off-peak, discharge in peak to maximize spread $\Delta p=0.54-0.22=0.32$ \$/kWh.

3) Feasibility & SoC constraints.

Capacity 18 kWh; initial SoC 5 kWh; max charge 5 kWh/h; max discharge 10 kWh/h.

- A: Discharge at hour 2 (off-peak) \Rightarrow violates principle \Rightarrow exclude.
- B: Charge $\{1,2\}$ (off-peak) \Rightarrow SoC: $5 \rightarrow 10 \rightarrow 15$; Discharge $\{15,17\}$ (peak).
- C: Charge $\{2,10\}$ \Rightarrow SoC: $5 \rightarrow 10 \rightarrow 15$; Discharge $\{18,19\}$ (peak).
- D: Charge $\{11,14\} \Rightarrow SoC: 5 \rightarrow 10 \rightarrow 15$; Discharge $\{16,18\}$ (peak).

4) Discharge amounts & savings (bounded by load and 10 kWh/h).

Peak-hour loads (forecast):

h15 = 4.86, h16 = 1.37, h17 = 1.00, h18 = 0.65, h19 = 2.40.

- B: discharge at $\{15,17\} \Rightarrow 4.86 + 1.00 = 5.86$ kWh; saving $= 5.86 \times 0.32 = \$1.8752$. (If discharging also at h16 is allowed as listed, then 4.86 + 1.37 + 1.00 = 7.23 kWh $\Rightarrow \$2.3136$.)
- $C: \{18,19\} \Rightarrow 0.65 + 2.40 = 3.05 \text{ kWh} \Rightarrow \$0.976.$
- $D: \{16,18\} \Rightarrow 1.37 + 0.65 = 2.02 \,\text{kWh} \Rightarrow \$0.6464.$

All satisfy SoC bounds (start 5 kWh, charge to 15 kWh, discharge \leq available). </think>

<answer>B</answer>