
Improving Language Model Negotiation with Self-Play and In-Context Learning from AI Feedback

Anonymous Author(s)

Affiliation

Address

email

Abstract

1 We study whether multiple large language models (LLMs) can autonomously
2 improve each other in a negotiation game by playing, reflecting, and criticizing.
3 We are interested in this question because if LLMs were able to improve each other,
4 it would imply the possibility of creating strong AI agents with minimal human
5 intervention. We ask two LLMs to bargain with each other, playing the roles of a
6 buyer and a seller, respectively. They aim to reach a deal with the buyer targeting
7 a lower price and the seller a higher one. A third language model, playing the
8 critic, provides feedback to a player to improve the player’s negotiation strategies.
9 We let the two agents play multiple rounds, using previous negotiation history
10 and AI feedback as in-context demonstrations to improve the model’s negotiation
11 strategy iteratively. We use different LLMs (GPT and Claude) for different roles
12 and use the deal price as the evaluation metric. Our experiments reveal multiple
13 intriguing findings: (1) Only a subset of the language models we consider can
14 self-play and improve the deal price from AI feedback, weaker models either do
15 not understand the game’s rules or cannot incorporate AI feedback for further
16 improvement. (2) Models’ abilities to learn from the feedback differ when playing
17 different roles. For example, it is harder for Claude-instant to improve as the
18 buyer than as the seller. (3) When unrolling the game to multiple rounds, stronger
19 agents can consistently improve their performance by meaningfully using previous
20 experiences and iterative AI feedback, yet have a higher risk of breaking the
21 deal. We hope our work provides insightful initial explorations of having models
22 autonomously improve each other with game playing and AI feedback.

23 1 Introduction

24 We study whether multiple Large Language Models (LLMs) can improve each other in a negotiation
25 game with minimal human intervention, in the fashion of AlphaGo Zero [31] where AI agents improve
26 themselves by continuously playing competitive games under well-defined rules. The answers to this
27 research question have profound implications. On the positive side, if the agents *were* able to improve
28 autonomously, strong agents might be created with very few human annotations, which greatly saves
29 the cost compared to today’s data-hungry LLM training [8, 17]. On the risky side, it also implies
30 strong agents with limited human oversight [4]. In this work, we ask two language models (a seller
31 and a buyer) to bargain about a product. The seller is asked to sell the product at a higher price, while
32 the buyer aims to purchase it at a lower price (Fig. 1A). After reaching a deal, we ask a third language
33 model to play as the critic and give feedback to a player. Then we play the game again, asking the
34 player to improve their strategy using AI feedback provided by the critic LLM.

35 We choose the bargaining game because it comes with well-defined rules described in text, and a
36 clear and measurable objective (a lower/ higher deal price) for strategic negotiation. Although the




Figure 1: Settings of our negotiation game. **A.** We ask two LLM agents to play a bargaining game as the seller and the buyer. Their goals are to sell/ buy the product at a higher/ lower price. After a round, we ask an AI critic, a third LLM, to provide feedback to the player we want to improve. Then we ask the player to improve their negotiation strategies based on the feedback. We repeat this process for multiple rounds and study if models can continuously improve. See Fig. 2 for an example run. **B.** Bargaining techniques that we observed from the AI Critic and how the player incorporates these techniques into the negotiation strategy. **C.** Abilities that are required in our game (C2 - negotiation, C3 - AI feedback, and C4 - continuous improvements) classify models into different tiers. We find out that only strong and well-aligned models (like gpt-4 and claude-v1.3) can continuously improve from iterative AI feedback (see Fig. 3 for example models that do not exhibit these abilities).

game seems easy at first glance, it requires non-trivial capabilities of the language models, as the model needs to: (1) clearly understand and strictly follow the textual rules of the negotiation game (2) correspond to the textual feedback provided by the critic LM and improve based on it iteratively (see example feedback in Fig 1B); (3) reflect upon the strategy and feedback over the long term and improve over multiple rounds. We will see that not all models we considered show all these abilities (Fig. 1C), and only models that can (1) *understand negotiation rules and strategies* (capable) and (2) *respond to AI instructions* (well-aligned) can continuously improve from AI feedback over multiple rounds (in our experiments, only gpt-3.5-turbo, gpt-4, and claude-v1.3) meet these requirements). We have also tried more complicated textual games including board games and textual RPG games in the preliminary experiments, but they are more challenging for current agents to understand and follow the rules.

We call our approach *In-Context Learning from AI Feedback* (ICL-AIF). Specifically, we use the feedback from the AI critic as well as the previous rounds of dialog history as in-context demonstrations [5]. By doing this, the critic’s suggestions for improvements and the player’s actual improvement in the previous rounds effectively become the few-shot prompts for the next round of negotiation. We use in-context learning for two reasons: (1) tuning large language models with reinforcement learning is prohibitively expensive [25, 15] and the base model [24] may not be accessible to a wide range of the community; (2) in-context learning is recently shown to be closely related to gradient descent [11, 1, 32], such that the conclusions we draw is fairly likely to generalize when one actually finetunes the model (if resources permit). One notable difference between our ICL-AIF and the mainstream Reinforcement Learning from Human Feedback (RLHF) is that in RL the reward is a

Claude-instant-v1.0 v.s. GPT-3.5-Turbo 2023-05-10 Round 1, before AI Feedback		AI Feedback to seller	Round 2, After AI Feedback	
Claude-ins-1.0 Seller	Hi, this is a good balloon and its price is \$20	Claude-ins-1.0 Seller Critic	Claude-ins-1.0 Seller	Hi, this is a good balloon and its price is \$20
GPT-3.5-T Buyer	Would you consider selling it for \$10?	1. Focus on the qualities and benefits of the balloon, not just the price. Highlight how rare and special it is.	GPT-3.5-T Buyer	Would you consider selling it for \$10?
Claude-ins-1.0 Seller	No, that price is too low.	2. Build rappor t and connection with the buyer to make them feel like they are getting a good deal from a trusted seller .	Claude-ins-1.0 Seller	No, \$10 is much too low. This balloon is made of high quality latex and handcrafted by expert artisans . It's unique one-of-a-kind piece.
GPT-3.5-T Buyer	What about \$15?	3. Be willing to walk away if needed. Let the buyer know you have other interested buyers, so they realize the value in meeting your price.	GPT-3.5-T Buyer	What would be the lowest price you could offer me for this balloon?
Claude-ins-1.0 Seller	\$15 is better, but still not enough.	Claude-ins-1.0 Seller	Claude-ins-1.0 Seller	Well, because I trust you and value your business , I will offer you this special balloon at \$17. This price is only available to valued customers like yourself today.
GPT-3.5-T Buyer	What is the lowest price you can offer?		GPT-3.5-T Buyer	Can you give me a better deal, like \$15?
Claude-ins-1.0 Seller	My lowest price is \$18.		Claude-ins-1.0 Seller	I apologize, but \$15 does not even cover my costs. I have to charge at least \$17 for this unique, high-quality balloon.
GPT-3.5-T Buyer	I understand. Could you do \$16? That's the highest I can go.		GPT-3.5-T Buyer	Alright, you've got a deal. I will take the special balloon for \$17.
Claude-ins-1.0 Seller	\$16 will work for today. Congratulations, you got a good deal!			
A. Round 1, before AI feedback to seller, the bargaining process is relatively simple, final price \$16.		B. AI critic give feedbacks to the seller based on the previous round, then seller acknowledge.	C. Round 2, seller improves the reasoning strategy based on the feedback, final price \$17.	

Figure 2: An example of playing the negotiation game and then improving from AI feedback. **A:** claude-instant-v1.0 plays the seller and gpt-3.5-turbo the buyer, bargaining about a balloon. **B:** then we use a claude-instant-v1.0 critic to provide feedback. **C:** upon receiving the feedback, the seller improves its strategy based on the suggestions. Note that colored phrases like “high quality latex and handcrafted by expert artisans” correspond to previous AI feedback “how rare and special it is”. We measure the final price as the proxy of the effectiveness of the strategy because the overall goal is to get a better price. In this case, it improves from \$16 to \$17.

58 *scalar* [25, 15] while in ICL the feedback is in *natural language*. We study AI feedback (rather than
59 rely on human intervention after each round) because it is more scalable and can allow models to
60 self-improve automatically.

61 Our experiments lead to several intriguing findings: (1) The requirements of our bargaining game
62 effectively serve as a testbed for assessing the abilities of LLMs (Fig. 1C): although most models can
63 do chitchat in a casual scenario, as of our experiment date (May 2023), cohere-command [10] model
64 does not understand the rule of bargaining (Fig. 3A), ai21-jurassic [18] model does not respond
65 to AI feedback (Fig. 3B), claude-instant-v1.0 can at most improve one round (Fig. 5), and only
66 gpt-3.5-turbo, gpt-4, and claude-v1.3 can continuously improve over multiple rounds. (2)
67 Models behave differently upon receiving feedback when playing different roles. Models playing the
68 buyer role may be harder to improve than when in the seller role (Fig. 4). (3) It is indeed possible
69 for strong agents like gpt-4 to continuously improve meaningfully using previous experiences and
70 online iterative AI feedback, yet the attempt to sell at a higher price (or buy at a lower price) comes
71 with the risk of failing to reach a deal at all (Fig. 6). We further show evidence of the model being
72 able to negotiate in a less verbose but more strategic (thus more effective) way (Fig. 7). Overall,
73 we hope our work serves as a meaningful initiative for improving language models’ negotiation in a
74 game setting using AI feedback.

75 2 Problem Setting

76 Our goal is to study whether LLMs can improve each other by playing a negotiation game and
77 incorporating AI feedback, as shown in Fig. 1A. We set the product being bargained as a balloon (and
78 our results hold when changing the balloon to other items). We use different combinations of backend
79 LLM engines: cohere-command [10], AI21’s jurassic-2 [18], OpenAI’s gpt-3.5-turbo and
80 gpt-4 [24], Anthropic’s claude-instant-v1.0 (which supposedly matches gpt-3.5-turbo [14])
81 and claude-v1.3 (which is supposed to be slightly worse but close to gpt-4 [14]). throughout our
82 experiments, we *provide feedback to improve only one* of the two players, while its rival receives no
83 feedback, clears the negotiation history of previous rounds, and restarts. We vary the engines for the
84 model being improved while fixing its rival’s engine to be gpt-3.5-turbo. Essentially, our game
85 is gpt-3.5-turbo vs. all other engines. We keep the LM engine behind the critic is always the
86 same as the player it provides feedback to. One example setting is a gpt-4 seller playing against a
87 gpt-3.5-turbo buyer, with a gpt-4 critic. After one round, the gpt-4 critic provides feedback to
88 the gpt-4 seller such that the seller can improve in the next round while its rival gpt-3.5-turbo
89 buyer clears its dialog history and restarts.

Process of the Game Before the game begins, the rules of the negotiation game are explained to the models through textual instructions with the objective of selling/ buying at a higher/ lower price. We set the deal price to [\$10, \$20] for easier evaluation, since other the deal price may vary in a wide range according to the observations from our preliminary experiments. To achieve this, we hard code the seller to kick off the negotiation with “This is a good balloon and its price is \$20.” Similarly, the buyer always opens with “Would you consider selling it for \$10?” When both players strictly follow the game rules, the deal price would be between \$10 and \$20. We let the models play multiple runs and measure the average deal price before and after AI feedback. During the game, the seller’s output is used to prompt the buyer and vice versa, conditioning on the entire conversation history. This process is repeated till a terminal state is reached. Fig. 2A shows an example round. We define three game states: (1) ON-GOING: the negotiation between the two players is still ongoing; (2) DEAL: the negotiation has concluded and the two players have reached a deal; (3) NO DEAL: the players cannot agree on a price and have failed to reach a deal. To track the game states, we set an additional moderator (powered by a fourth LLM, in our case, gpt-3.5-turbo) to read the current dialog and classify the states (we will discuss more details about the moderator later). We measure the performance of the players based on the final deal price.

Critic A round is finished when the negotiation reaches a terminating state, either a DEAL or NO DEAL. After each round, the critic LM is asked to provide constructive feedback to the player we aim to improve. This player’s dialog history from all past rounds and all feedback it has received are used to prompt the critic LM (Fig. 2B). The critic model is instructed to provide three suggestions to the player, in order to improve its negotiation strategies to achieve a more favorable price in the next game. Before the next round, the player being improved receives the critic’s feedback as a textual prompt, while its rival clears its negotiation history and restarts.

The Moderator The game state is classified by prompting a gpt-3.5-turbo moderator using few-shot demonstrations. The moderator reads the most recent four rounds (as well as in-context examples of different dialog states) and determines the state of the negotiation. Empirically, we found that four rounds of conversations are sufficient for the moderator to determine the negotiation state. One key challenge here is detecting no-deals as the model seems to be better at recognizing DEAL than NO DEAL. We mitigate this issue by playing multiple runs, inspect failure cases manually, and add them to the prompt with corrected labels. We find this method an effective side product recommend it as a technique for prompt optimization for generic classification tasks.

Playing for Multiple Rounds Finally, we would like to explore whether the players can continuously improve from AI feedback in a game over multiple rounds. Intuitively, the more rounds the players play, the more challenging to keep improving because the (already improved) price from the previous round becomes the baseline for the next round. In the experiments, we will show that only gpt-4 can improve over 5 rounds while other models’ improvements may saturate at about 3 rounds.

3 Related Work

Game Playing and AlphaGo Zero Our setting is strongly inspired by AlphaGo Zero [31] where two agents play the game of Go and improve each other with minimal human intervention. Here we would like to explore its counterpart in natural language. Our work is similar to AlphaGo Zero in the sense that we also have AI agents (large language models) playing *competitive* games (bargaining) and try to improve with little human supervision. Yet there is an important difference between our work and AlphaGo Zero: we have a third agent, *the critic*, to give feedback helping its player to improve. This is a *cooperative* relationship that does not exist in AlphaGo Zero. On the NLP side, the closest related work is Lewis et al. [19] where they have (small) RNN [9] language models to bargain, and our work can be viewed as a more developed version of them since we change the engine to be large language models. In general, our work is broadly under the area of AI negotiation [6, 6], strategic reasoning [12], and general game playing [30].

Large Language Models as Generative Agents Large language models have demonstrated incredible multi-dimensional capabilities [33, 24], especially in complex reasoning [34, 28, 13] and multi-round dialog [15, 2, 3], which serve as the foundation of this work. Our work is related to concurrent works like Generative Agents [26] and CAMEL [20] as they also study the behavior of LLMs in a multi-agent game setting. The core difference between our work and theirs is that we

Cohere command-xlarge-nightly 2023-04-22 v.s. human		AI21 j2-jumbo-instruct 2023-05-09 v.s. GPT-3.5-Turbo	
Cohere Buyer	Would you consider selling it for \$15?	Round 1 AI21 Seller	I can't sell it for \$10, but I can consider selling it for \$12
User Seller	Yes, I can sell the balloon for \$15.	GPT-3.5-Turbo Buyer	How about \$11?
Cohere Buyer	Would you consider selling it for \$17?	AI21 Seller	I can consider selling it for \$11
	# Asking \$17 after seller agreed on \$15	GPT-3.5-Turbo Buyer	Thank you, I'll take it for \$11.
Cohere command-nightly 2023-05-11 v.s. human		AI Feedback AI21 Seller Critic	Feedback: 1. Emphasizing its unique characteristics or qualities 2. Create a sense of urgency 3. Encourage the buyer to elaborate on their needs
User Buyer	Would you consider selling it for \$10?	Round 2 AI21 Seller	I can't sell it for \$10, but I can consider selling it for \$12
Cohere Seller	No. This is a good balloon and its price is \$20.		# Repeat previous strategy, does not listen to critic
User Buyer	Understood. What is the lowest price you would accept for the balloon?	GPT-3.5-Turbo Buyer	How about \$11? That's the most I can offer.
Cohere Seller	I would accept \$8 for the balloon.	AI21 Seller	I can consider selling it for \$11.
	# Accept \$8 while reject \$10	GPT-3.5-Turbo Buyer	# Does not defend its position Great, it's a deal then. Thank you!
A. Examples where model does not understand bargaining		B. Examples where model does not incorporate feedback	

Figure 3: Not all models can play bargaining. **A.** As of May 2023, the cohere model does not understand the rule of bargaining and agrees on irrational prices. **B.** The AI21 Jurassic-2 model, although understanding the rule of bargaining, does not incorporate the feedback from the critic. Since these models are consistently being updated, we include the timestamp and note future versions may have improved performance.

143 have a clear objective (the deal price) for the model to improve through competition and cooperation,
144 while their work studies the generic social behavior of LLMs.

145 **Learning from AI Feedback** Our method is also strongly inspired by constitutional AI [3] as
146 we both use AI feedback, while the difference is that our feedback is directly in natural language
147 (not a scalar from a reward model). There are also related/ concurrent works demonstrating the
148 effectiveness of natural language feedback [29, 27, 22] and self-refinement [7, 23]. Our work further
149 confirms the effectiveness of AI feedback in the strategic negotiation game setting.

150 4 Experiments

151 In our experiments, we consider three stages that gradually deepen our exploration of learning from
152 AI feedback: (1) We first set up the basics of the game (Sec. 4.2), showing that only a few models can
153 improve from AI critics, in which case AI feedback can be comparable (but more scalable) as human
154 feedback. Other models either do not understand/ follow the rule of bargaining, or cannot incorporate
155 AI feedback for improvements. (2) Then we study the models' behaviors when playing different roles
156 (Sec. 4.3). We discover the intriguing result that buyers are in general harder to improve than sellers.
157 (3) Finally, we study whether models can continuously improve over multiple rounds (Sec. 4.4), and
158 show a tradeoff of deal price versus success rate: although some models can continuously improve
159 the deal price, it comes with a higher risk of breaking a deal. We further show evidence of negotiation
160 in a more strategic way: both gpt-4 and claude-v1.3's responses become longer after multiple
161 rounds of AI feedback (note that verbosity is a straightforward negotiation strategy), yet gpt-4 is less
162 verbose than claude-v1.3 but achieves higher deal price and deal rate, meaning that its responses,
163 although using fewer words, are more strategic and effective.

164 4.1 Experiment Setup

165 **Model Engines** The minimum requirement for models to enter our game is that they should be a
166 chatbot. All models we consider (cohere-command, AI21's jurassic-2, OpenAI's gpt and Anthropic's claude) can be accessed by API calls. Among them, gpt-4 is the most expensive one and
167 running 500 rounds of negotiation costs about \$120 and gpt-3.5-turbo costs about \$10. Other mod-
168 els are beta testing (as of May 2023) and do not charge money. For reference, the approximate rank
169 of these models, from benchmarks like chain-of-thought hub [14] and HeLM [21], is that gpt-4 and
170 claude-v1.3 are approximately similar, better than gpt-3.5-turbo and claude-instant-v1.0,
171 and better than cohere-command and j2-jumbo-instruct. We will consider more models in the
172 future, such as Google's PaLM-2 [16].

174 We let all models compete with gpt-3.5-turbo, effectively making it a baseline for all other models.
175 We will show that, aligning with other concurrent model rankings [14, 21], gpt-3.5-turbo is a
176 middle-level powerful engine (worse than gpt-4, better than claude-instant-v1.0). For a given
177 model engine (say claude-v1.3), we run it as the seller (with gpt-3.5-turbo as the buyer) and

Table 1: **Seller performance** using AI feedback vs. randomly selected human feedback from a pre-defined pool. Recall that the buyer is fixed to be gpt-3.5-turbo and has no access to previous rounds. AI’s feedback is comparable to human’s, but is more scalable, as the two both induce similar price increases.

	GPT-3.5-Turbo	Claude-instant-v1.0	Claude-v1.3
Before feedback	16.26	14.74	15.40
Random sampled human feedback	16.83 (+0.57)	16.33 (+1.59)	16.89 (+1.49)
AI feedback	17.03 (+0.77)	15.98 (+1.24)	16.98 (+1.58)

as a buyer (with gpt-3.5-turbo now as the seller) We first let the models to play one round and manually inspect if they understand the rules of bargaining. If they do, we let them play two rounds to see if they could respond to AI feedback. For the critic model, we set its engine the same as its player. We repeat the game 500 times to compute the average deal price before and after AI feedback. If they do improve one round, we let them play multiple rounds and see if they could continuously improve their strategy. We repeat the game 200 times with 5 max rounds to compute the average deal price for each round. When decoding from the model engines, we use sampling with default temperature (1.0 for gpt and claude, 0.75 for cohere and 0.7 for j2).

Prompt Engineering In this work, we only had to manually optimize the prompts for the moderator because the player may reach/ break a deal with very diverse expressions, and we would like to make sure the moderator correctly recognizes all of them. As mentioned above, we identify the errors made by the moderator in identifying deals and keep adding them as in-context demonstrations until the model reaches a sufficiently high accuracy (about 90+ by manual inspection). For the players and the critic, we do not do prompt engineering and keep the instructions the same for all engines (but the format may be different, e.g., claude requires two linebreaks before “HUMAN:” and j2 requires two “##” after each dialog round). Code and Prompts will be released publicly on publication.

4.2 Basic Experiments

In this section, we first study the minimal requirements for models to participate in our game, namely (1) understanding the rule of bargaining and (2) responding to AI feedback. Then we consider basic comparison between AI and human feedback, showing that AI feedback can be comparable to human feedback, but more scalable.

Conversational ability does not guarantee ability to negotiate or learning from feedback We study whether conversational models can understand the rule of bargaining by manually checking traces of the dialog, and found that cohere-command fails to understand the rules, as is shown in Fig 3A. We observe that it does not realize what price is a better deal. For example, when playing seller, it rejects a proposal of \$10 but accepts \$8. We also observe that AI21’s j2-jumbo-instruct model, although understanding the rule of bargaining, cannot incorporate AI feedback, as is shown in Fig. 3B. Generally, when instructed with AI feedback, the model keeps the same strategy as before, without any improvements.

After ruling out the cohere-command and j2-jumbo-instruct models, we consider the three remaining models: gpt-3.5-turbo, claude-instant-v1.0 and claude-v1.3. For these three engines, we do not observe the problems in Fig. 3. This means that these models can be used for our multi-round games.

AI Feedback can be comparable to human feedback Now we consider some initial comparison between AI and human feedback. We emphasize that our goal is not to show which one is better – a similar level of effectiveness would suffice our study (to see if LLMs can continuously improve through self-play and AI feedback). For the human feedback, we manually write down a pool of 10 suggestions. Then we play 500 runs of the game, computing the deal price before and after feedback. After 500 runs, we compare the improvements after: (1) randomly sampling 3 suggestions from the predefined pool and (2) asking the AI critic to write down 3 suggestions. We note that this may underestimate the performance of human feedback, yet it would be impractical to ask human to write down 3 suggestions for all 1500 runs (while AI feedback does not have this problem). The results are shown in Table 1 where we see that all three models (gpt-3.5-turbo, claude-instant-v1.0 and claude-v1.3) exhibit comparable improvements over human and AI feedback.




Figure 4: Binned deal price frequencies of 500 games, before v.s. after feedback. Effective feedback should move the distribution towards a lower/ higher price range. X-axis: intervals of deals from \$10 (buyers’ initial price) to \$20 (sellers’ asking price). Y-axis: the frequency of the price. **A** and **B**: for weaker agents like `claude-instant-v1.0` and `gpt-3.5-turbo`, improving from AI feedback as the seller is easier than as buyer. For sellers, AI feedback moves the deal distribution to a higher range (rightward), but does not move buyers’ deal distribution much. Consequently, the change in average deal price when playing as buyers (-0.2 and -0.5) is clearly smaller than those as sellers (+1.0 and +1.7). **C**. Stronger agents (`claude-v1.3` and `gpt-4`), when playing buyers, can still improve from AI feedback even as buyers, with larger changes in average deal price (-1.2 and -3.0).

4.3 Behaviors of Different LLM Backend

So far we have established that our game setting is valid for stronger LLM engines. Now we consider the detailed behavior comparisons using different engines for different roles. Specifically, we use `claude-instant-v1.0`, `claude-v1.3`, `gpt-3.5-turbo`, and `gpt-4` to play the seller/ buyer (against a `gpt-3.5-turbo` buyer/ seller respectively), then study the deal price distribution before/ after AI feedback (also recall that the AI critic is powered by the same engine as its player). The results are visualized in Fig. 4. When `claude-instant-v1.0` and `gpt-3.5-turbo` play the seller, they are able to improve their average deal price after AI feedback (Fig. 4A). But when they play the buyer role, their average deal price does not improve, which indicates that buyers tend to be a harder role than sellers (Fig. 4B). Yet this observation does not hold for engines like `gpt-4` and `claude-v1.3`, as they can still improve from AI feedback even playing buyers. Overall, this set of experiments reveal the nuanced capability differences between the four engines we consider.

4.4 Towards Continuous Improvements from Iterative AI Feedback

Now we unroll the game to multiple rounds and see if models can continuously improve from previous dialog history and iterative AI feedback. Specifically, we let `gpt-3.5-turbo`, `gpt-4`, `claude-instant-v1.0`, and `claude-v1.3` play as the seller/ buyer respectively against a rival powered by `gpt-3.5-turbo`. As mentioned before, the critic shares the same engine as the player it




Figure 5: In the multi-round setting, different engines have different behavior when playing seller/buyer. Line plots are the average price over 200 runs and bar plots represent the price distribution. **A1** v.s. **B1**. When playing sellers, gpt-3.5-turbo can improve from AI feedback in multiple rounds, while claude-instant-v1.0 only improves the first round. **A2** v.s. **B2**. When playing buyers, gpt-3.5-turbo can improve in multiple rounds, while claude-instant-v1.0 cannot.

helps with. We play 200 runs of the game, and unroll each game to be 5 rounds. We compute the final deal price and the deal success rate and see if the price can be continuously improved.

Fig. 5 shows gpt-3.5-turbo and claude-instant-v1.0 playing different roles. For a given engine, improvements over one round may not necessarily extrapolate to multiple rounds, as we observe that gpt-3.5-turbo can improve over multiple rounds, but claude-instant-v1.0 only improves at most one round.

Now we consider the tradeoff between the tendency of achieving a higher deal price versus the risk of breaking a deal, as is shown in Fig 6. We see that when playing sellers, all four model engines can improve over at least one round, but this comes at the cost of decreasing deal success ratio. When playing buyers, there are models that cannot improve (claude-instant-v1.0), or saturate over 3 rounds (claude-v1.3), while gpt-4 and gpt-3.5-turbo can continuously improve, and gpt-4 achieves better (lower) deal price and higher deal rate than gpt-3.5-turbo.

Finally, we study how iterative AI feedback influences the language complexity used by the agents by plotting the average response length (measured in number of characters) after each round, as is shown in Fig. 7. We see that both claude-v1.3 and gpt-4 become more verbose after iterative AI feedback with a continuously increasing response length. This is intuitive because being verbosity is a straightforward strategy in negotiation. Yet for claude-v1.3, the verbosity does not translate to better negotiation strategy, as its improvement saturates after three rounds (Fig. 6B1). In comparison, gpt-4's increase verbosity is more strategic, as it use less words than claude-v1.3, but achieves better deal price and deal success rate (Fig. 6B). This observation serve as strong evidence that AI feedback improves players' response towards a word-tuned, strategic direction.

5 Conclusions

In this work, we study whether multiple large language models can autonomously improve each other in a negotiation game by role-playing and learning from AI feedback. Our experiments show that certain models can indeed improve by continuously playing competition games with iterative AI feedback, under well-defined rules in an AlphaGo Zero fashion. We also show the tradeoff between next-round price improvement and success rate, as a better deal price also comes with a higher risk




Figure 6: Performance of GPT and Claude models in multi-round games and their success rate of getting a deal. **A1** and **A2**: when playing the seller, most models can improve over multiple rounds. Yet higher prices also mean that it is more likely the seller may break the deal, as shown in the continuously decreasing curve of A2. **B1** and **B2**: when playing buyer, cLaude-instant-v1.0 cannot improve over multiple rounds while others can. Again, a better buying price also comes with a higher chance of running away from a deal. We see that GPT-4 achieves the best trade-off here: it gets the best price over multiple rounds with a higher success rate of reaching a deal.




Figure 7: The average response length increases as the model learns from multiple rounds. Here we show examples of the seller’s response when being asked the buyer’s initial query “Would you consider selling it for \$10?” After multiple rounds of negotiation, the seller’s responses become more verbose and word-tuned. Yet verbosity does not mean better strategy: cLaude-v1.3 is more verbose (higher curve) than gpt-4, but it has a worse success rate and deal price (recall Fig. 6). This indicates that gpt-4’s verbosity is more strategic.

of deal breaking. This suggests future research may consider global optimization for improving the overall gain over multiple rounds. We further show evidence of improved language from iterative AI feedback: in a multi-round game, one model may be less verbose than another, but be better word-tuned, thus more effective in getting a better deal.

We believe our results have profound implications for AI research: on the positive side, it indicates the possibility of continuously improving language models with minimal human intervention. On the risky side, it might be more challenging to oversight the model behavior in our framework because models are acting autonomously, which calls for future alignment and safety research in the multi-agent game setting. Overall, we believe our work provides a meaningful initial exploration for large language models’ learning from game-playing and iterative AI feedback.

References

- [1] Ekin Akyürek, Dale Schuurmans, Jacob Andreas, Tengyu Ma, and Denny Zhou. What learning algorithm is in-context learning? investigations with linear models. *arXiv preprint arXiv:2211.15661*, 2022.
- [2] Amanda Askell, Yuntao Bai, Anna Chen, Dawn Drain, Deep Ganguli, Tom Henighan, Andy Jones, Nicholas Joseph, Ben Mann, Nova DasSarma, et al. A general language assistant as a laboratory for alignment. *arXiv preprint arXiv:2112.00861*, 2021.
- [3] Yuntao Bai, Saurav Kadavath, Sandipan Kundu, Amanda Askell, Jackson Kernion, Andy Jones, Anna Chen, Anna Goldie, Azalia Mirhoseini, Cameron McKinnon, et al. Constitutional ai: Harmlessness from ai feedback. *arXiv preprint arXiv:2212.08073*, 2022.
- [4] Samuel R Bowman, Jeeyoon Hyun, Ethan Perez, Edwin Chen, Craig Pettit, Scott Heiner, Kamile Lukosuite, Amanda Askell, Andy Jones, Anna Chen, et al. Measuring progress on scalable oversight for large language models. *arXiv preprint arXiv:2211.03540*, 2022.
- [5] Tom Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared D Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, et al. Language models are few-shot learners. *Advances in neural information processing systems*, 33:1877–1901, 2020.
- [6] Kushal Chawla, Jaysa Ramirez, Rene Clever, Gale Lucas, Jonathan May, and Jonathan Gratch. Casino: A corpus of campsite negotiation dialogues for automatic negotiation systems. *arXiv preprint arXiv:2103.15721*, 2021.
- [7] Xinyun Chen, Maxwell Lin, Nathanael Schärli, and Denny Zhou. Teaching large language models to self-debug. *arXiv preprint arXiv:2304.05128*, 2023.
- [8] Aakanksha Chowdhery, Sharan Narang, Jacob Devlin, Maarten Bosma, Gaurav Mishra, Adam Roberts, Paul Barham, Hyung Won Chung, Charles Sutton, Sebastian Gehrmann, et al. Palm: Scaling language modeling with pathways. *arXiv preprint arXiv:2204.02311*, 2022.
- [9] Junyoung Chung, Caglar Gulcehre, KyungHyun Cho, and Yoshua Bengio. Empirical evaluation of gated recurrent neural networks on sequence modeling. *arXiv preprint arXiv:1412.3555*, 2014.
- [10] Cohere. Cohere command models. *Cohere website*, 2023. URL <https://docs.cohere.com/docs/models>.
- [11] Damai Dai, Yutao Sun, Li Dong, Yaru Hao, Zhifang Sui, and Furu Wei. Why can gpt learn in-context? language models secretly perform gradient descent as meta optimizers. *arXiv preprint arXiv:2212.10559*, 2022.
- [12] Meta Fundamental AI Research Diplomacy Team (FAIR)[†], Anton Bakhtin, Noam Brown, Emily Dinan, Gabriele Farina, Colin Flaherty, Daniel Fried, Andrew Goff, Jonathan Gray, Hengyuan Hu, et al. Human-level play in the game of diplomacy by combining language models with strategic reasoning. *Science*, 378(6624):1067–1074, 2022.
- [13] Yao Fu, Hao Peng, Ashish Sabharwal, Peter Clark, and Tushar Khot. Complexity-based prompting for multi-step reasoning. *arXiv preprint arXiv:2210.00720*, 2022.
- [14] Yao Fu, Litu Ou, Mingyu Chen, and Yuhao Wan. Measuring llms’ reasoning performance. *Github*, 2023. URL <https://github.com/FranxYao/chain-of-thought-hub>.
- [15] Amelia Glaese, Nat McAleese, Maja Trębacz, John Aslanides, Vlad Firoiu, Timo Ewalds, Maribeth Rauh, Laura Weidinger, Martin Chadwick, Phoebe Thacker, et al. Improving alignment of dialogue agents via targeted human judgements. *arXiv preprint arXiv:2209.14375*, 2022.
- [16] Google. Palm 2 technical report. *ArXiv*, 2023.
- [17] Jordan Hoffmann, Sebastian Borgeaud, Arthur Mensch, Elena Buchatskaya, Trevor Cai, Eliza Rutherford, Diego de Las Casas, Lisa Anne Hendricks, Johannes Welbl, Aidan Clark, et al. Training compute-optimal large language models. *arXiv preprint arXiv:2203.15556*, 2022.

- [18] AI21 Labs. Announcing jurassic-2 and task-specific apis. *AI21 Blog*, 2023. URL <https://www.ai21.com/blog/introducing-j2>.
- [19] Mike Lewis, Denis Yarats, Yann N Dauphin, Devi Parikh, and Dhruv Batra. Deal or no deal? end-to-end learning for negotiation dialogues. *arXiv preprint arXiv:1706.05125*, 2017.
- [20] Guohao Li, Hasan Abed Al Kader Hammoud, Hani Itani, Dmitrii Khizbullin, and Bernard Ghanem. Camel: Communicative agents for" mind" exploration of large scale language model society. *arXiv preprint arXiv:2303.17760*, 2023.
- [21] Percy Liang, Rishi Bommasani, Tony Lee, Dimitris Tsipras, Dilara Soylu, Michihiro Yasunaga, Yian Zhang, Deepak Narayanan, Yuhuai Wu, Ananya Kumar, et al. Holistic evaluation of language models. *arXiv preprint arXiv:2211.09110*, 2022.
- [22] Hao Liu, Carmelo Sferrazza, and Pieter Abbeel. Languages are rewards: Hindsight finetuning using human feedback. *arXiv preprint arXiv:2302.02676*, 2023.
- [23] Aman Madaan, Niket Tandon, Prakhar Gupta, Skyler Hallinan, Luyu Gao, Sarah Wiegrefe, Uri Alon, Nouha Dziri, Shrimai Prabhumoye, Yiming Yang, et al. Self-refine: Iterative refinement with self-feedback. *arXiv preprint arXiv:2303.17651*, 2023.
- [24] OpenAI. Gpt-4 technical report. *ArXiv*, abs/2303.08774, 2023.
- [25] Long Ouyang, Jeffrey Wu, Xu Jiang, Diogo Almeida, Carroll Wainwright, Pamela Mishkin, Chong Zhang, Sandhini Agarwal, Katarina Slama, Alex Ray, et al. Training language models to follow instructions with human feedback. *Advances in Neural Information Processing Systems*, 35:27730–27744, 2022.
- [26] Joon Sung Park, Joseph C O’Brien, Carrie J Cai, Meredith Ringel Morris, Percy Liang, and Michael S Bernstein. Generative agents: Interactive simulacra of human behavior. *arXiv preprint arXiv:2304.03442*, 2023.
- [27] Ethan Perez, Sam Ringer, Kamilė Lukošiušė, Karina Nguyen, Edwin Chen, Scott Heiner, Craig Pettit, Catherine Olsson, Sandipan Kundu, Saurav Kadavath, et al. Discovering language model behaviors with model-written evaluations. *arXiv preprint arXiv:2212.09251*, 2022.
- [28] Shuofei Qiao, Yixin Ou, Ningyu Zhang, Xiang Chen, Yunzhi Yao, Shumin Deng, Chuanqi Tan, Fei Huang, and Huajun Chen. Reasoning with language model prompting: A survey. *arXiv preprint arXiv:2212.09597*, 2022.
- [29] Jérémy Scheurer, Jon Ander Campos, Jun Shern Chan, Angelica Chen, Kyunghyun Cho, and Ethan Perez. Training language models with natural language feedback. *arXiv preprint arXiv:2204.14146*, 2022.
- [30] David Silver, Aja Huang, Chris J Maddison, Arthur Guez, Laurent Sifre, George Van Den Driessche, Julian Schrittwieser, Ioannis Antonoglou, Veda Panneershelvam, Marc Lanctot, et al. Mastering the game of go with deep neural networks and tree search. *nature*, 529(7587):484–489, 2016.
- [31] David Silver, Julian Schrittwieser, Karen Simonyan, Ioannis Antonoglou, Aja Huang, Arthur Guez, Thomas Hubert, Lucas Baker, Matthew Lai, Adrian Bolton, et al. Mastering the game of go without human knowledge. *nature*, 550(7676):354–359, 2017.
- [32] Johannes von Oswald, Eyvind Niklasson, Ettore Randazzo, João Sacramento, Alexander Mordvintsev, Andrey Zhmoginov, and Max Vladymyrov. Transformers learn in-context by gradient descent. *arXiv preprint arXiv:2212.07677*, 2022.
- [33] Jason Wei, Yi Tay, Rishi Bommasani, Colin Raffel, Barret Zoph, Sebastian Borgeaud, Dani Yogatama, Maarten Bosma, Denny Zhou, Donald Metzler, et al. Emergent abilities of large language models. *arXiv preprint arXiv:2206.07682*, 2022.
- [34] Jason Wei, Xuezhi Wang, Dale Schuurmans, Maarten Bosma, Ed Chi, Quoc Le, and Denny Zhou. Chain of thought prompting elicits reasoning in large language models. *arXiv preprint arXiv:2201.11903*, 2022.