ROBUST CONSENSUS ANCHOR LEARNING FOR EFFI CIENT MULTI-VIEW SUBSPACE CLUSTERING

Anonymous authors

004

010

Paper under double-blind review

ABSTRACT

011 As a leading unsupervised classification algorithm in artificial intelligence, multiview subspace clustering segments unlabeled data from different subspaces. Re-012 cent works based on the anchor have been proposed to decrease the computation 013 complexity for the datasets with large scales in multi-view clustering. The major 014 differences among these methods lie on the objective functions they define. De-015 spite considerable success, these works pay few attention to guaranting the robust-016 ness of learned consensus anchors via effective manner for efficient multi-view 017 clustering and investigating the specific local distribution of cluster in the affine 018 subspace. Besides, the robust consensus anchors as well as the common clus-019 ter structure shared by different views are not able to be simultaneously learned. In this paper, we propose Robust Consensus anchors learning for efficient multi-021 view Subspace Clustering (RCSC). We first show that if the data are sufficiently sampled from independent subspaces, and the objective function meets some conditions, the achieved anchor graph has the block-diagonal structure. As a special 023 case, we provide a model based on Frobenius norm, non-negative and affine con-024 straints in consensus anchors learning, which guarantees the robustness of learned 025 consensus anchors for efficient multi-view clustering and investigates the specific 026 local distribution of cluster in the affine subspace. While it is simple, we theoretically give the geometric analysis regarding the formulated RCSC. The union 028 of these three constraints is able to restrict how each data point is described in 029 the affine subspace with specific local distribution of cluster for guaranting the robustness of learned consensus anchors. RCSC takes full advantages of correla-031 tion among consensus anchors, which encourages the grouping effect and groups 032 highly correlated consensus anchors together with the guidance of view-specific projection. The anchor graph construction, partition and robust anchor learning are jointly integrated into a unified framework. It ensures the mutual enhancement 034 for these procedures and helps lead to more discriminative consensus anchors as well as the cluster indicator. We then adopt an alternative optimization strategy for solving the formulated problem. Experiments performed on eight multi-view datasets confirm the superiority of RCSC based on the effectiveness and efficiency.

039 040

041

1 INTRODUCTION

042 Clustering is an important field in artificial intelligence and machine learning Jain (2008). As the 043 information technology develops, large amounts of data from multiple views or channels can be 044 collected in real-world scenarios. This type of data is termed as multi-view data and it widely exists in the world. For instance, we can depict an image by multiple representations, such as local binary pattern (LBP), histogram of oriented gradient (HOG) and Gabor feature representation. For dealing 046 with the multi-view data in clustering tasks, various multi-view clustering approaches have been 047 presented in the literature. As opposed to clustering for the data with single view Bai et al. (2023); 048 Bandyapadhyay et al. (2023), multi-view clustering can achieve more reasonable performance in practice. It is able to integrate diverse feature representations of an object obtained by different views and provide more comprehensive object information. Among the existing multi-view clustering 051 works, methods based on the graph have gained significant attention in recent years. 052

The graph-based methods for multi-view clustering Nie et al. (2017b); Zhan et al. (2019); Wang et al. (2020) can reflect the relationships among samples in multi-view data by constructing graph

054 structures. Then the final results can be achieved based on the partition of the obtained graph. These 055 methods usually adopt an $n \times n$ adjacent graph to formulate the relationships among data points. Cao 056 et al. Cao et al. (2015) presented a multi-view clustering method based on diversity and smoothness, 057 which investigates the complementarity among different representations. Wang et al. Wang et al. 058 (2020) learned the unified global graph and view-specific graphs by adopting the mutual reinforcement technique. Chen et al. (2020) simultaneously learned the global self-representation, latent embedding space and cluster structure for subspace learning on multi-view data. Liang et 060 al. Liang et al. (2020) utilized the multi-view graph learning to learn a unified graph and lever-061 aged the incosistency and consistency among multiple view-specific graphs. Nie et al. Nie et al. 062 (2017a) presented to simultaneously perform local structure learning and semi-supervised classifi-063 cation/clustering. Wang et al. Wang et al. (2020) coupled unified graph, graph induced by similarity 064 across views and indicator into a unified framework. Despite significant progress, most of these 065 multi-view clustering approaches tend to suffer from high computation complexity. It takes $O(n^2)$ 066 to construct an $n \times n$ adjacent graph and needs $O(n^3)$ in partitioning this graph, which limits their 067 scalability for multi-view datasets with large scales. 068

For dealing with the computation complexity issue, multi-view clustering methods based on the an-069 chor have been given Nie et al. (2017c); Guo & Ye (2019), which show promising capability in real 070 applications. Different from constructing an $n \times n$ graph, the methods based on the anchor typically 071 produce small number of anchors from the dataset and represent the structure of data by building an 072 $n \times l$ anchor graph, where l denotes the total number of anchors. In general, l is lower than n, which 073 enables the scale of data to be greatly decreased for reaching the goal of increasing the clustering 074 efficiency. Specifically, Yang et al. (2021) increased the efficiency and all views are 075 required to yield the same anchors. Kang et al. Kang et al. (2020) employed the subspace learning based on the anchor to learn a anchor graph for each view and then heuristically combined different 076 anchor graphs into a unified one. Li et al. (2022) presented a scalable multi-view clustering 077 method by fusing anchor graphs. It is able to employ the discrete cluster structure to adaptively learn a unified graph by anchor graph fusion. Wang et al. (2022) employed multiple 079 projection matrices and a set of latent consensus anchors to learn a unified anchor graph. Yang et 080 al. Yang et al. (2022) seeked for l anchors on the original data with the guidance of K-means. The 081 produced centroids are regarded as anchors and a sparse anchor graph is constructed between the obtained anchors and the original dataset. Despite great success, these methods pay few attention to 083 ensuring the robustness of learned consensus anchors for efficient multi-view clustering and inves-084 tigating the specific local distribution of cluster in the affine subspace. The correlation among the 085 learned consensus anchors, which encourages the grouping effect and tends to group highly corre-086 lated anchors together, is not able to be fully explored. Besides, the robust consensus anchors and the common cluster structure shared by different views are not able to be simultaneously learned in 087 a unified framework. Then the mutual enhancement for these procedures is not guaranteed in this 880 manner and more discriminative consensus anchors as well as cluster indicator are not obtained. 089

To cope with the above issues, we propose a novel Robust Consensus anchor learning for efficient 091 multi-view Subspace Clustering (RCSC). We first theoretically show that a block-diagonal anchor 092 graph can be obtained if the objective function meets certain conditions based on the independent subspace assumption. As a special case, we provide a model based on Frobenius norm, non-negative 093 and affine constraints in consensus anchors learning, which guarantees the robustness of learned 094 consensus anchors for efficient multi-view clustering and investigates the specific local distribution 095 of cluster in the affine subspace. While it is simple, we theoretically give the geometric analysis 096 regarding the formulated RCSC. The union of these three constraints is able to restrict how each data point is described in the affine subspace with specific local distribution of cluster for guarant-098 ing the robustness of learned consensus anchors. We can fully explore the correlation among the learned consensus anchors with the view-specific projection, which encourages the grouping effect 100 and groups highly correlated anchors together. The robust anchor learning, partition and anchor 101 graph construction are jointly modeled in a unified framework. Then the robust consensus anchors 102 and the common cluster structure shared by different views are able to be simultaneously learned. 103 We can guarantee the mutual enhancement for these procedures in this manner and achieve more 104 discriminative consensus anchors as well as the cluster indicator. By imposing the orthogonal constraints on the actual bases, we constrain a factor matrix to be the cluster indicator matrix based 105 on the rigorous clustering interpretation. We then develop an alternate minimizing algorithm for 106 solving the formulated problem. The major contributions in this paper are: 107

- 108
 1. We propose a novel Robust Consensus anchor learning for efficient multi-view Subspace Clustering (RCSC). We first theoretically demonstrate that an anchor graph with blockdiagonal structure can be achieved if the objective function satifies certain conditions. As a special case, we give a model based on Frobenius norm, non-negative and affine constraints in consensus anchors learning, which guarantees the robustness of learned consensus anchors for efficient multi-view clustering and investigates the specific local distribution of cluster in the affine subspace.
 - 2. We are able to fully explore the correlation among the learned consensus anchors with the guidance of view-specific projection, which encourages the grouping effect and tends to group highly correlated anchors together. We jointly perform the robust anchor learning, partition and anchor graph construction in a unified framework. Then, the robust consensus anchors and the common cluster structure shared by different views are simultaneously learned, which ensures the mutual enhancement for these procedures and helps lead to more discriminative consensus anchors as well as the cluster indicator.
 - 3. We impose the orthogonal constraints on the actual bases and constrain a factor matrix to be the cluster indicator matrix built on the rigorous clustering interpretation. Extentive experiments on different multi-view datasets validate the effectiveness and efficiency of RCSC, especially on the datasets with large scales.

2 Methodology

115

116

117

118

119

121

122

123

125 126

127 128

129

130 131

132

143

144

149

150 151 In this section, we present the motivation and formulation of RCSC, followed by the optimization process and the related analysis of computation complexity for RCSC.

2.1 MOTIVATION

133 The anchor strategy is usually employed to find the underlying structure by choosing a small number 134 of data points as anchor bases. Some existing mutli-view clustering methods based on the anchor 135 conduct K-means to achieve clustering centroids with the anchor bases being fixed. Despite great 136 success, these methods pay few attention to guaranting the robustness of learned consensus anchors 137 for efficient multi-view clustering and investigating the specific local distribution of cluster in the 138 affine subspace. The correlation among the learned consensus anchors, which encourages the group-139 ing effect and groups highly correlated anchors together, is ignored to be fully explored. Moreover, 140 the robust consensus anchors and the common cluster structure shared by multiple views are not simultaneously learned. Therefore, the mutual enhancement for these procedures is not effectively 141 ensured and more discriminative consensus anchors as well as cluster indicator are not acquired. 142

2.2 FORMULATION

We generate view-specific data points via certain generation model based on a latent space. Given multi-view dataset $\{X^p \in R^{d_p \times n}\}_{p=1}^v$ with d_p and n being the dimension and size of dataset, we first assume that the data are noise free and formulate the corresponding objective function as:

$$\min_{U^p,A,S} \sum_{p=1}^{v} ||X^p - U^p AS||_F^2, \ s.t. \ (U^p)^T U^p = I, \ A^T A = I,$$
(1)

where $S \in \mathbb{R}^{l \times n}$ is the shared affinity matrix, $\{U^p\}_{p=1}^v \in \mathbb{R}^{d_p \times d}$ indicates a projection matrix as the consensus anchor guidance, $A \in \mathbb{R}^{d \times l}$ represents the unified anchors, l and d are the number of anchors and shared dimension across views, respectively. $U^p A \in \mathbb{R}^{d_p \times l}$ represents the basis matrix. We then theoretically demonstrate that a block-diagonal anchor graph can be achieved if the corresponding objective function satisifies certain conditions based on the independent subspace assumption, which is shown as Theorem 1 in the following.

Theorem 1. Assume the subspaces $\{\Omega_i\}_{i=1}^k$ are independent, X_i^p is a matrix with columns consisting of some vectors from Ω_i and $U_i^p A_i$ is a matrix with columns consisting of a basis of Ω_i , where $(U^p)^T U^p = I$ and $A^T A = I$. The solution S to the following form

$$X^p = (U^p A)S \tag{2}$$

is block-diagonal and unique. 163

168

169 170

177 178

179

181

182

183

185 186

187

188

199 200 201

203

204 205

207

208 209 210

214 215

Proof. For data point $x^p \neq 0$ and $x^p \in \Omega_i$, we just need to prove that there exists a unique s, $x^p = (U^p A)s$, where $s = [s_1^T, \dots, s_k^T]$, with $s_i \neq 0$ and $s_j = 0$ for all $j \neq i$. Since $(U^p)^T U^p = I$ and $A^T A = I$, we can obtain $(U^p A)^T (U^p A) = A^T (U^p)^T U^p A = I$. Thus, $U^p A$ is orthogonal. Due to the orthogonality among subspaces, there exists a unique decomposition for x^p as follows:

$$x^{p} = 0 + \dots + x^{p} + \dots + 0$$

= $(U_{1}^{p}A_{1})s_{1} + \dots + (U_{i}^{p}A_{i})s_{i} + \dots + (U_{k}^{p}A_{k})s_{k},$ (3)

where $(U_i^p A_i)s_i \in \Omega_i$ and $i = 1, \dots, k$. Therefore, $(U_i^p A_i)s_i = x^p$ and $(U_j^p A_j)s_j = 0$ for all $j \neq i$. Since $U_i^p A_i$ is a basis of Ω_i , we have $s_i \neq 0$, s_i is unique, and $s_j = 0$ for all $j \neq i$.

Accoring to Theorem 1, a basis of X^p can be learned and we use it as the dictionary. It is easy to obtain a true solution by solving the problem in Eq. (1) if subspaces are independent. To deal with more general multi-view clustering issue in the affine subspace, we introduce the affine constraint $S^T \mathbf{1} = 1$ to the original objective function and obtain the optimization problem as:

$$\min_{U^{p},A,S} \sum_{p=1}^{v} ||X^{p} - U^{p}AS||_{F}^{2}, \quad s.t. \ S^{T}\mathbf{1} = 1, \ (U^{p})^{T}U^{p} = I, \ A^{T}A = I,$$
(4)

where 1 denotes the vector with all entries being one. To locally depict the distribution of contaminated data points from different subspaces, we add a non-negative constraint for S and achieve the problem as:

$$\min_{U^{p},A,S} \sum_{p=1}^{\circ} ||X^{p} - U^{p}AS||_{F}^{2}, \quad s.t. \ S \ge 0, \ S^{T}\mathbf{1} = 1, \ (U^{p})^{T}U^{p} = I, \ A^{T}A = I.$$
(5)

Thus, the non-negative constraint endows the learned S with the probabilistic meaning. In real applications, the data are usually contaminated with the possible noise. We then adopt the Frobenius norm for penalizing the noise based on affine and non-negative constraint in Eq. (5), formulated as:

$$\min_{U^{p},A,S} \sum_{p=1}^{v} ||X^{p} - U^{p}AS||_{F}^{2} + \lambda ||S||_{F}^{2}, \ s.t. \ S \ge 0, \ S^{T}\mathbf{1} = 1, \ (U^{p})^{T}U^{p} = I, \ A^{T}A = I,$$
(6)

where $\lambda > 0$ is a parameter to balance different parts. We then guarantee the robustness for efficient multi-view clustering and investigate the specific local distribution of cluster in the affine subspace. The grouping effect is stated in the theorem as follows.

Theorem 2. Given data point $x^p \in R^{d_p}$, matrix $U^p A \in R^{d_p \times n}$ and parameter λ . Assume each column of $U^p A$ is normalized. Let s^* be the optimal solution to the following problem:

$$\min_{U^{p},A,s} \sum_{p=1}^{v} ||x^{p} - U^{p}As||_{2}^{2} + \lambda ||s||_{2}^{2}, \quad s.t. \ S \ge 0, \ S^{T}\mathbf{1} = 1, \ (U^{p})^{T}U^{p} = I, \ A^{T}A = I.$$
(7)

202 We have

$$\frac{\|s_i^* - s_j^*\|_2}{\|x^p\|_2} \le \frac{1}{\lambda}\sqrt{2(1-r)},\tag{8}$$

where $r = (u_i^p a_i)^T (u_j^p a_j)$ denotes the basis correlation.

Proof. Let $L(s) = ||x^p - U^p As||_2^2 + \lambda ||s||_2^2$. Since s^* is the optimal solution to Eq. (7), it meets

$$\left. \frac{\partial L(s)}{\partial s_k} \right|_{s=s^*} = 0. \tag{9}$$

Since $(U^p)^T U^p = I$ and $A^T A = I$, we can obtain $(U^p A)^T (U^p A) = A^T (U^p)^T U^p A = I$. Thus, $U^p A$ is orthogonal. Then we have

$$-2(u_i^p a_i)^T (x^p - U^p A s^*) + 2\lambda s_i^* = 0, (10)$$

$$-2(u_j^p a_j)^T (x^p - U^p A s^*) + 2\lambda s_j^* = 0,$$
(11)

Thus

217 218

$$s_i^* - s_j^* = \frac{1}{\lambda} ((u_i^p a_i)^T - (u_j^p a_j)^T) (x^p - U^p A s^*),$$
(12)

$$\|u_i^p a_i\|^2 = \|u_j^p a_j\|^2 = 1,$$
(13)

and

$$(u_i^p a_i)^T u_j^p a_j = 0. (14)$$

Then we have $||u_i^p a_i - u_j^p a_j||_2 = \sqrt{2}$. Note that s^* is the optimal solution to Eq. (7), we can obtain

$$\|x^{p} - U^{p}As^{*}\|_{2}^{2} + \lambda \|s^{*}\|_{2}^{2} = L(s^{*}) \le L(0) = \|x^{p}\|_{2}^{2}.$$
(15)

Therefore, $||x^p - U^p As^*||_2 \le ||x^p||_2$. Thus, Eq. (15) implies

$$\frac{\|s_i^* - s_j^*\|_2}{\|x^p\|_2} \le \frac{\sqrt{2}}{\lambda}.$$
(16)

The grouping effect in the above theorem demonstrates that the obtained solution is correlation dependent. Theorem 2 shows that the difference between s_i^* and s_j^* is nearly zero if $u_i^p a_i$ and $u_j^p a_j$ are highly correlated. We then fully explore the correlation among the learned consensus anchors A with the guidance of view-specific projection U^p , which encourages the grouping effect and groups highly correlated anchors together.

As abovementioned, we introduce the Frobenius norm, non-negative and affine constraints into the shared affinity matrix learning. While it is simple, the union of these three constraints can restrict how each data point is described in the affine subspace with specific local distribution of cluster for guaranting the robustness of learned consensus anchors. We then denote the basis matrix $U^P A$ as

$$U^{p}A = [(U^{p}A)^{1}, \cdots, (U^{p}A)^{t}, \cdots, (U^{p}A)^{k}],$$
(17)

where $(U^p A)^t$ is the basis matrix lying in the *t*-th affine subspace. We adopt $(U^p A)_{-i}^t$ to denote basis matrices in the *t*-th affine subspace except the basis $(U^p A)_i$. $(U^p A)^{-t}$ is employed to indicate basis matrices in all affine subspaces except the *t*-th affine subspace. The sets of basis in $(U^p A)^t$, $(U^p A)^{-t}$ and $(U^p A)_{-i}^t$ can be denoted by $\Gamma((U^p A)^t)$, $\Gamma((U^p A)^{-t})$ and $\Gamma((U^p A)_{-i}^t)$, respectively. A basis tends to locate in three possible positions regarding $(U^p A)^t$, i.e., edge, inside and vertex. We adopt $edge((U^p A)^t)$, *inside* $((U^p A)^t)$ and $vertex((U^p A)^t)$ to indicate these three positions. For non-vertex (edge and inside) basis, we first give the lemma and then have the theorem as follows:

Lemma 1. Assume that A and D are square matrices, we can obtain

 $\left\| \begin{pmatrix} A & B \\ C & D \end{pmatrix} \right\|_{*} \geq \left\| \begin{pmatrix} A & \mathbf{0} \\ \mathbf{0} & D \end{pmatrix} \right\|_{*} = \|A\|_{*} + \|D\|_{*} \text{ for matrices } B \text{ and } C \text{ with compatible dimension}$

Theorem 3. For any non-vertex basis $(U^pA)_i \in edge((U^pA)^t)$ and $(U^pA)_i \in inside((U^pA)^t)$ with $t = 1, 2, \dots, k$, the optimal solution to Eq. (6) is block diagonal if $\Gamma((U^pA)^t)$ does not intersect with $\Gamma((U^pA)^{-t})$.

Proof. We prove the above theorem by the contrapositive and assume that there is an optimal solution S to Eq. (6) and S does not have the block diagonal property. We set the block diagonal matrix W as

$$W_{ij} = \begin{cases} S_{ij}, & \text{if } (U^p A)_i \text{ and } (U^p A)_j \text{ in the same subspace,} \\ 0, & \text{otherwise.} \end{cases}$$
(18)

Then Q = S - W is adopted to denote the difference between S and W. We employ $l = \{j : (U^p A)_j \in \Gamma((U^p A)^t)\}$ and $k = \{j : (U^p A)_j \notin \Gamma((U^p A)^t)\}$ to indicate indices of basis for the *t*-th affine subspace and other affine subspaces, respectively. Each edge and inside basis $(U^p A)_i$ lying in $\Gamma((U^p A)^t)$ which causes S against the block diagonal structure can be written as

269
$$\sum_{j \in \mathbb{k}} Q_{ij} (U^p A)_j = (U^p A)_i - \sum_{j \in \mathbb{C}} W_{ij} (U^p A)_j.$$
(19)

218 219

220 221

222 223 224

225 226 227

241 242

250

251

252 253 254

259

260

261 262 263

216

Since $\sum_{j \in \mathcal{C}} W_{ij} + \sum_{j \in \mathbb{k}} Q_{ij} = 1$, we divide two sides of Eq. (19) by $\sum_{j \in \mathbb{k}} Q_{ij}$ and obtain:

274

284

287 288 289

290 291

292

293

295

296 297

298

299

305 306 307

308

309

315 316 317

321 322 323

$$\frac{\sum_{j \in \Bbbk} Q_{ij} (U^p A)_j}{\sum_{j \in \Bbbk} Q_{ij}} = \frac{(U^p A)_i - \sum_{j \in \complement} W_{ij} (U^p A)_j}{\sum_{j \in \Bbbk} Q_{ij}} = \frac{(U^p A)_i - \sum_{j \in \complement} W_{ij} (U^p A)_j}{1 - \sum_{j \in \complement} W_{ij}}.$$
 (20)

We observe that the left and right sides of Eq. (20) are basis in $\Gamma((U^pA)^{-t})$ and $\Gamma((U^pA)^t)$, respectively. It can be concluded that $\Gamma((U^pA)^{-t})$ does intersect with $\Gamma((U^pA)^t)$. Therefore, according to Lemma 1, we have $||S||_* \ge ||W||_*$. Then, W is the optimal and owns the block diagonal structure. Though it is hard to give sufficient conditons of the similar structure for vertices as Theorem 3, we find that the proportions of vertices are far more less than edge and inside basis in practice.

To integrate the partition into the unified framework, we adopt the orthogonal and nonnegative factorization to directly assign clusters to the data. Then extra post-processing steps are not needed in recovering cluster structures based on the factor matrix. Specifically, we impose the orthogonal constraint on the actual bases. The above process is formulated as:

$$\min_{\alpha, U^{p}, A, S, G, F} \sum_{p=1}^{v} \alpha_{p}^{2} ||X^{p} - U^{p}AS||_{F}^{2} + \lambda ||S||_{F}^{2} + \beta ||S - GF||_{F}^{2}, \ s.t. \ S \ge 0, \ S^{T}\mathbf{1} = 1,$$

$$\alpha^{T}\mathbf{1} = 1, \ (U^{p})^{T}U^{p} = I, \ A^{T}A = I, \ G^{T}G = I, \ F_{ij} \in \{0, 1\}, \ \sum_{i=1}^{k} F_{ij} = 1, \ \forall j = 1, 2, \cdots, n,$$
(21)

where α_p^2 denotes the learned coefficients, $\beta > 0$ is a parameter for balancing different terms, $G \in \mathbb{R}^{l \times k}$ stands for the centroid matrix and $F \in \mathbb{R}^{k \times n}$ represents the cluster assignment with $F_{ij} = 0$ if j-th data point is not belonged to the i-th cluster and 1 otherwise.

2.3 Optimization

For solving the problem in Eq. (21), we design an alternate optimization algorithm to seek for the solution to each variable while fixing the other variables.

 U^{p} -subproblem: With the other variables being fixed, the objective function regarding U^{p} is

$$\min_{U^p} \sum_{p=1}^{v} \alpha_p^2 ||X^p - U^p AS||_F^2, \quad s.t. \quad (U^p)^T U^p = I.$$
(22)

We then transform the above optimization problem by trace as follows:

$$\max_{U^p} Tr((U^p)^T C^p), \quad s.t. \quad (U^p)^T U^p = I,$$
(23)

where $C^v = X^p S^T A^T$. Assuming the singular value decomposition (SVD) of C^v is $U'_C \Sigma_C V^T_C$, we can easily obtain the optimal U^p by calculating $U'_C V^T_C$.

S-subproblem: With the other variables being fixed, the objective function regarding S is

$$\min_{S} \sum_{p=1}^{v} \alpha_{p}^{2} ||X^{p} - U^{p}AS||_{F}^{2} + \lambda ||S||_{F}^{2} + \beta ||S - GF||_{F}^{2}, \quad s.t. \ S \ge 0, \ S^{T}\mathbf{1} = 1.$$
(24)

We then rewrite it by the quadratic programming (QP) problem as follows:

$$\min h^T S_{:,j} + \frac{1}{2} S_{:,j}^T W S_{:,j}, \quad s.t. \ S \ge 0, \ S_{:,j}^T \mathbf{1} = 1,$$
(25)

where $h^T = -2\sum_{p=1}^{v} (X_{;,j}^p)^T U^p A - 2\beta F_{;,j}^T G^T$ and $W = 2(\sum_{p=1}^{v} \alpha_p^2 + \lambda + \beta)I$. Thus, we tackle the QP problem to achieve the optimization for each column in S.

A-subproblem: With the other variables being fixed, the objective function regarding A is

$$\min_{A} \sum_{p=1}^{v} \alpha_{p}^{2} ||X^{p} - U^{p}AS||_{F}^{2}, \quad s.t. \; A^{T}A = I.$$
(26)

Likewise, Eq. (26) is equal to the problem as follows:

$$\max_{A} Tr(A^T B), \quad s.t. \; A^T A = I, \tag{27}$$

where $B = \sum_{p=1}^{v} \alpha_p^2 (U^p)^T X^p S^T$. Then the optimal A is $U'_B V^T_B$, where $B = U'_B \Sigma_B V^T_B$.

F-subproblem: With the other variables being fixed, the objective function regarding F is

$$\min_{F} \beta \|S - GF\|_{F}^{2}, \quad s.t. \; F_{ij} \in \{0, 1\}, \; \sum_{i=1}^{\kappa} F_{ij} = 1, \; \forall j = 1, 2, \cdots, n.$$
(28)

We then independently solve each object for the optimization problem and obtain

$$\min_{F_{:,j}} \beta \|S_{:,j} - GF_{:,j}\|^2, \quad s.t. \; F_{:,j} \in \{0,1\}^k, \; \|F_{:,j}\|_1 = 1.$$
(29)

We can find the optimal row by

$$i^* = \arg\min_i \|S_{:,j} - G_{:,i}\|^2.$$
 (30)

G-subproblem: With the other variables being fixed, the objective function regarding G is

$$\min_{C} \beta \|S - GF\|_{F}^{2}, \quad s.t. \ G^{T}G = I.$$
(31)

Then the optimization problem regarding G is rewritten as

$$\max_{G} Tr(G^{T}J), \quad s.t. \ G^{T}G = I,$$
(32)

where $J = SF^T$. Then, the optimal G is equal to $U'_J V^T_J$, where $J = U'_J \Sigma_J V^T_J$.

 α_p -subproblem: With the other variables being fixed, the objective function regarding α_p is

$$\min_{\alpha} \sum_{p=1}^{v} \alpha_p^2 ||X^p - U^p AS||_F^2, \quad s.t. \; \alpha^T \mathbf{1} = 1.$$
(33)

Based on Cauchy-Buniakowsky-Schwarz inequality, the optimal α_p can be obtained by

$$\alpha_p = \frac{\frac{||X^p - U^p AS||_F}{\sum_{p=1}^v \frac{1}{||X^p - U^p AS||_F}}.$$
(34)

The objective function monotonically decreases in each iteration until convergence since the convex property for each sub-problem. We list the procedure of RCSC in Algorithm 1.

Algorithm 1: Algorithm of RCSC

Input: Multi-view dataset $\{X^p\}_{p=1}^v$, parameter λ, β , number of clusters k. Output: Cluster assignment F. **Initialize:** Initialize $A, U^p, \{\alpha_p\}_{p=1}^v, S, F \text{ and } G.$ repeat Update S by solving Eq. (24); Update $\{U_p\}_{p=1}^v$ by solving Eq. (22); Update A by solving Eq. (26); Update G by solving Eq. (31); Update F by solving Eq. (28); Update α by solving Eq. (33); until convergence;

2.4 COMPLEXITY ANALYSIS

The computation cost of our method includes the costs brought by optimizing all variables. Specificly, it costs $O(l^3n)$ to update S. In optimizing U^p , conducting matrix multiplication needs $O(d_p dk^2)$ and SVD consumes $O(d_p d^2)$ for each view. It needs $O(dlk^2)$ in matrix multiplication and $O(dl^2)$ in SVD for optimizing A. The complexity of O(lnk) is needed to optimize F. It takes $O(lk^2 + lk^3)$ to update G, which consists of the time cost in SVD and matrix multiplication. It needs O(1) to update α_p . The total time cost of our method is $O((pd^2 + pdk^2 + dlk^2 + nl^3 + lk^2 + lk^3 + dl^2 + lnk)o)$ with o being the total number of iterations, where $p = \sum_{p=1}^{v} d_p$. Since $n \gg k$ and $n \gg l$, the computation cost of our method is nearly linear to O(n).



In this part, we evaluate the proposed method against the representive methods on eight multi-view datasets under different metrics in terms of effectiveness and efficiency.



Figure 4: Robustness study of our method on different datasets in terms of ACC.

3.1 DATASETS AND EXPERIMENTAL SETTINGS

405

411 412

413

414 415

416 417 418

419

For the experimental evaluation, we use eight real-world multi-view datasets, namely, ORL, Mfeat,
Caltech101-20, Caltech101-all, SUNRGBD Song et al. (2015), NUSWIDEOBJ Chua et al. (2009),
AWA and YoutubeFace. In the experiment, eight representive multi-view clustering methods are
employed for comparison, including AMGL Nie et al. (2016), SFMC Li et al. (2022), BMVC Zhang
et al. (2019), LMVSC Kang et al. (2020), MSGL Kang et al. (2022), FRMVS Wang et al. (2022),
EOMSC-CA Liu et al. (2022) and OMSC Chen et al. (2022).

We need to determine the anchor number in evaluating the clustering performance of all methods. For ensuring the fairness, the best parameters are used for compared methods. The anchor number of our method is tuned in the range of $[2k, 3k, \dots, 7k]$, where k denotes the total number of clusters in dataset. To reduce the randomness, we repeat each experiment for 20 times and report their mean values and variances in the experiment. We evaluate the clustering results by three widely adopted metrics, which consists of accuracy (ACC), normalized mutual information (NMI) and F1-score. A high value for each of these metrics indicates better clustering performance on the dataset.

4	3	2
4	3	3
4	3	4

Table 1: Clustering results based on ACC (%) on all datasets. "N/A" denotes out of memory.

Dataset	AMGL	SFMC	BMVC	LMVSC	MSGL	FPMVS	EOMSC-CA	OMSC	Ours
ORL	64.50 ± 0.01	$61.40 {\pm} 0.05$	48.70±0.05	58.60 ± 0.02	21.00 ± 0.05	52.00 ± 0.50	62.20 ± 0.05	63.80±0.00	65.20±0.00
Mfeat	82.60 ± 0.02	75.50 ± 0.20	69.30 ± 0.05	81.75 ± 0.05	75.40 ± 0.02	82.20 ± 0.05	82.25 ± 0.03	84.00 ± 0.05	$85.60 {\pm} 0.00$
Caltech101-20	28.70 ± 0.20	59.40 ± 0.05	16.80 ± 0.05	29.00 ± 0.30	48.00 ± 0.02	66.15 ± 0.10	64.10 ± 0.50	65.00 ± 0.10	$67.40 {\pm} 0.00$
Caltech101-all	14.80 ± 0.01	17.70 ± 0.05	21.20 ± 0.03	15.50 ± 0.01	14.10 ± 0.02	27.50 ± 0.05	22.30 ± 0.03	24.00 ± 0.00	$28.00 {\pm} 0.50$
SUNRGBD	9.80 ± 0.01	11.30 ± 0.05	16.70 ± 0.01	18.00 ± 0.05	13.00 ± 0.01	23.40 ± 0.05	23.70 ± 0.05	25.20 ± 0.00	27.00 ± 0.00
NUSWIDEOBJ	N/A	12.20 ± 0.05	12.90 ± 0.05	14.70 ± 0.05	12.00 ± 0.05	19.20 ± 0.05	19.60 ± 0.05	21.00 ± 0.05	$23.50 {\pm} 0.00$
AWA	N/A	3.92 ± 0.03	8.60 ± 0.05	7.20 ± 0.03	8.00 ± 0.02	8.90 ± 0.01	8.65 ± 0.05	9.00 ± 0.10	$10.50 {\pm} 0.10$
YoutubeFace	N/A	N/A	$8.90 {\pm} 0.05$	14.00 ± 0.02	16.70 ± 0.01	23.00 ± 0.03	26.45 ± 0.05	26.50 ± 0.00	$27.80 {\pm} 0.00$

Table 2: Clustering results based on NMI (%) on all datasets. "N/A" denotes out of memory.

Dataset	AMGL	SFMC	BMVC	LMVSC	MSGL	FPMVS	EOMSC-CA	OMSC	Ours
ORL	87.10±0.07	82.70±0.01	67.70±0.03	78.50 ± 0.03	43.70 ± 0.02	74.40 ± 0.05	88.10±0.02	88.50±0.10	90.00±0.00
Mfeat	84.70 ± 0.05	84.80 ± 0.10	66.05 ± 0.15	76.00 ± 0.20	76.54 ± 0.05	79.40 ± 0.01	83.20 ± 0.15	84.20 ± 0.10	$85.32 {\pm} 0.15$
Caltech101-20	47.50 ± 0.20	42.80 ± 0.00	16.20 ± 0.03	41.20 ± 0.10	$31.50 {\pm} 0.05$	$63.30 {\pm} 0.05$	51.10 ± 0.05	51.80 ± 0.30	52.40 ± 0.00
Caltech101-all	35.30 ± 0.01	26.10 ± 0.03	42.50 ± 0.04	33.30 ± 0.02	26.10 ± 0.02	34.10 ± 0.05	24.65 ± 0.05	30.00 ± 0.00	31.30 ± 0.00
SUNRGBD	18.50 ± 0.10	2.30 ± 0.05	19.50 ± 0.05	24.50 ± 0.05	9.30 ± 0.05	24.10 ± 0.05	22.50 ± 0.01	24.30 ± 0.00	$25.00 {\pm} 0.10$
USWIDEOBJ	N/A	0.96 ± 0.01	12.90 ± 0.02	12.80 ± 0.05	5.70 ± 0.03	13.20 ± 0.05	13.20 ± 0.15	14.00 ± 0.00	$15.20 {\pm} 0.00$
AWA	N/A	0.30 ± 0.05	9.70 ± 0.02	8.50 ± 0.05	7.90 ± 0.03	8.50 ± 0.03	9.70 ± 0.03	10.00 ± 0.02	$10.22 {\pm} 0.00$
YoutubeFace	N/A	N/A	5.90 ± 0.05	11.80 ± 0.01	0.07 ± 0.01	2.40 ± 0.01	0.32 ± 0.01	0.37 ± 0.00	0.50 ± 0.00



Figure 5: Logarithm of running time on different datasets.

We first study how parameters β and λ influence the final clustering performance. These two pa-rameters are adopted to negotiate the importances of partition term and Frobenious norm term. We illustrate the clustering performance of the proposed method with varying parameters λ and β in Figs. 1-2. It is observed that appropriate values for these two parameters are generally beneficial to the clustering results on different datasets. According to Figs. 1-2, we observe that relatively desired clustering results are achieved when $\beta = 0.1$ and $\lambda = 0.1$ on various datasets. Moreover, the results of the proposed method are generally stable over varying values within the range of parameters β and λ on different datasets, which shows that RCSC is generally robust to these two parameters.

3.2 EXPERIMENTAL RESULTS AND ANALYIS

In this section, the proposed method is compared with the eight representive methods on several multi-view datasets. To be specific, we report the clustering results with respect to ACC, NMI and F1-score of all multi-view clustering methods in Tables 1-3, respectively. We adopt N/A to indicate that the method is not able to be computationally feasible on the dataset caused by out of memory.
Based on the obtained clustering results in Tables 1-3, we can draw some conclusions as follows:

 • For most datasets, the proposed method achieves more desired performance under different metrics and still behaves well on multi-view datasets with relatively large scale. For example, the clustering performance gain of the proposed method is about 2.32% higher than MSGL in terms of NMI on AWA.

483
484
484
485
485
486
486
487
487
488
488
488
488
489
489
480
480
480
481
481
481
482
483
485
485
485
485
485
486
486
486
487
487
488
488
488
488
488
488
488
489
489
480
480
480
481
481
482
483
484
485
485
485
486
486
486
487
487
488
488
488
488
488
488
488
488
488
488
488
488
488
488
488
488
488
488
488
488
488
488
488
488
488
488
488
488
488
488
488
488
488
488
488
488
488
488
488
488
488
488
488
488
488
488
488
488
488
488
488
488
488
488
488
488
488
488
488
488
488
488
488
488
488
488
488
488
488
488
488
488
488
488
488
488
488
488
488
488
488
488
488
488
488
488
488
488
488
488
488
488
488
488
488
488
488
488
488

Dataset	AMGL	SFMC	BMVC	LMVSC	MSGL	FPMVS	EOMSC-CA	OMSC	Ours
ORL	51.20 ± 0.03	30.60 ± 0.05	30.50 ± 0.04	45.90 ± 0.09	51.50 ± 0.20	38.40±0.15	62.10±0.00	63.20 ± 0.10	65.00±0.00
Mfeat	79.80 ± 0.05	71.10 ± 0.15	$58.80 {\pm} 0.01$	72.50 ± 0.02	70.10 ± 0.02	76.00 ± 0.40	77.00 ± 0.01	78.20 ± 0.00	79.90±0.00
Caltech101-20	21.80 ± 0.05	31.60 ± 0.02	11.40 ± 0.20	25.60 ± 0.50	41.80 ± 0.05	66.00 ± 0.05	64.70 ± 0.20	65.00 ± 0.10	66.79±0.20
Caltech101-all	4.05 ± 0.10	4.65 ± 0.10	18.00 ± 0.05	10.50 ± 0.05	8.60 ± 0.04	17.90 ± 0.03	10.80 ± 0.03	15.00 ± 0.00	18.20 ± 0.15
SUNRGBD	6.40 ± 0.40	12.10 ± 0.00	10.20 ± 0.01	11.60 ± 0.20	9.50 ± 0.15	16.00 ± 0.05	15.30 ± 0.05	17.00 ± 0.00	19.20 ± 0.00
NUSWIDEOBJ	N/A	11.50 ± 0.01	8.80 ± 0.02	9.30 ± 0.05	8.50 ± 0.05	13.50 ± 0.07	13.60 ± 0.05	14.50 ± 0.00	15.60 ± 0.10
AWA	N/A	4.60 ± 0.03	5.59 ± 0.02	3.60 ± 0.05	4.20 ± 0.01	6.20 ± 0.05	5.90 ± 0.05	6.20 ± 0.00	$7.00 {\pm} 0.20$
YoutubeFace	N/A	N/A	5.80 ± 0.02	8.30 ± 0.01	15.00 ± 0.10	14.00 ± 0.05	16.40 ± 0.01	17.10 ± 0.00	18.50 ± 0.00

Table 3: Clustering results based on F1-score (%) on all datasets. "N/A" denotes out of memory.

• The proposed method produces consitently better results than other methods based on the anchor for most of the multi-view datasets, which validates the necessarity of ensuring the robustness of learned consensus anchors for efficient multi-view subspace clustering and exploring the correlation among the learned consensus anchors with the guidance of view-specific projection in the manner of encouraging the grouping effect and grouping highly correlated anchors together.

3.3 SENSITIVITY INVESTIGATION AND ROBUSTNESS STUDY

We investigate how the total number of anchors impacts the clustering results in this part. For simplicity, we fix the shared dimension and conduct the sensity analysis for the number of anchors on several datasets in terms of different metrics. According to Fig. 3, we find that the proposed method is not significantly influenced by the number of anchors and the clustering results with different number of anchors are relatively stable.

We also study the robustness of the proposed method on different datasets. To be specific, we 510 randomly select half of the multi-view dataset to be corrupted with white Gaussian noise. This type 511 of noise is added to the selected data point x_i^p via $x_i^p = x_i^p + pj$, where $x_i^p \in [0, 255]$, p denotes 512 the corrupted ratio and i is the noise satisfying the standard Gaussian distribution. According to 513 Fig. 4, we can observe that the proposed method is robust on different datasets compared with other 514 methods and performs better on these datasets, which can be explained by the fact that the ensuring 515 the robustness of learned consensus anchors in the affine subspace for efficient multi-view subspace 516 clustering is helpful in achieving satisfied performance. 517

518 519

486

497

498

499

500

501 502

3.4 RUNNING TIME

520 We report the execution times of the compared methods and ours on different datasets. Note that 521 Caltech101-20 and Caltech101-all are two versions of Caltech101 dataset and we just list the running 522 time of Caltech101-all for simplicity. As shown in Fig. 5, it is observed that the proposed method 523 has shown comparable logarithm of running time cost to the existing efficient methods on most of 524 the multi-view datasets, i.e., MSGL. Thus, our method can obtain advantageous clustering results on various datasets while maintaining relatively competitive efficiency. It can be explained by the 525 fact that jointly modeling the robust consensus anchors and the common cluster structure in a unified 526 framework is crucial to guide the efficiency for multi-view clustering. The extra clustering algorithm 527 is not needed to obtain the final results, i.e., spectral clustering. 528

529

530 4 CONCLUSION

531

We propose a novel RCSC in this work. We theoretically demonstrate that a block-diagonal anchor graph is obtained if the objective function satisfies certain conditions. As a special case, we give a model based on Frobenius norm, non-negative and affine constraints in consensus anchors learning, which guarantees the robustness of learned consensus anchors for efficient multi-view clustering and investigates the specific local distribution of cluster in the affine subspace. We jointly perform the robust anchor learning, partition and anchor graph construction in a unified framework. We then give an alternate minimizing algorithm for solving the formulated problem and analyze the time complexity of the proposed method. Extensive experiments verify the effectiveness and efficiency of the proposed method on different multi-view datasets under three metrics.

540 REFERENCES

581

582

583

584

- Liang Bai, Minxue Qi, and Jiye Liang. Spectral clustering with robust self-learning constraints.
 Artif. Intell., 320:103924, 2023.
- Sayan Bandyapadhyay, Fedor V. Fomin, Petr A. Golovach, William Lochet, Nidhi Purohit, and Kirill
 Simonov. How to find a good explanation for clustering? *Artif. Intell.*, 322:103948, 2023.
- Xiaochun Cao, Changqing Zhang, Huazhu Fu, Si Liu, and Hua Zhang. Diversity-induced multi view subspace clustering. In *IEEE Conference on Computer Vision and Pattern Recognition*, pp. 586–594, 2015.
- Mansheng Chen, Ling Huang, Chang-Dong Wang, and Dong Huang. Multi-view clustering in latent embedding space. In *The AAAI Conference on Artificial Intelligence*, pp. 3513–3520, 2020.
- Mansheng Chen, Chang-Dong Wang, Dong Huang, Jian-Huang Lai, and Philip S. Yu. Efficient
 orthogonal multi-view subspace clustering. In *The ACM SIGKDD Conference on Knowledge Discovery and Data Mining*, pp. 127–135, 2022.
- Tat-Seng Chua, Jinhui Tang, Richang Hong, Haojie Li, Zhiping Luo, and Yantao Zheng. NUS WIDE: a real-world web image database from national university of singapore. In *Proceedings* of the 8th ACM International Conference on Image and Video Retrieval, 2009.
- Jun Guo and Jiahui Ye. Anchors bring ease: An embarrassingly simple approach to partial multi view clustering. In *The AAAI Conference on Artificial Intelligence*, pp. 118–125, 2019.
- Anil K. Jain. Data clustering: 50 years beyond k-means. In *Machine Learning and Knowledge Discovery in Databases*, volume 5211, pp. 3–4, 2008.
- Zhao Kang, Wangtao Zhou, Zhitong Zhao, Junming Shao, Meng Han, and Zenglin Xu. Large-scale
 multi-view subspace clustering in linear time. In *The AAAI Conference on Artificial Intelligence*,
 pp. 4412–4419, 2020.
- Zhao Kang, Zhiping Lin, Xiaofeng Zhu, and Wenbo Xu. Structured graph learning for scalable subspace clustering: From single view to multiview. *IEEE Trans. Cybern.*, 52(9):8976–8986, 2022.
- Xuelong Li, Han Zhang, Rong Wang, and Feiping Nie. Multiview clustering: A scalable and
 parameter-free bipartite graph fusion method. *IEEE Trans. Pattern Anal. Mach. Intell.*, 44(1):
 330–344, 2022.
- Youwei Liang, Dong Huang, Chang-Dong Wang, and Philip S. Yu. Multi-view graph learning by joint modeling of consistency and inconsistency. *CoRR*, abs/2008.10208, 2020.
- Suyuan Liu, Siwei Wang, Pei Zhang, Kai Xu, Xinwang Liu, Changwang Zhang, and Feng Gao.
 Efficient one-pass multi-view subspace clustering with consensus anchors. In *AAAI Conference* on Artificial Intelligence, pp. 7576–7584, 2022.
 - Feiping Nie, Jing Li, and Xuelong Li. Parameter-free auto-weighted multiple graph learning: A framework for multiview clustering and semi-supervised classification. In *Proceedings of the International Joint Conference on Artificial Intelligence*, pp. 1881–1887, 2016.
- Feiping Nie, Guohao Cai, and Xuelong Li. Multi-view clustering and semi-supervised classification
 with adaptive neighbours. In *Proceedings of the AAAI Conference on Artificial Intelligence*, pp. 2408–2414, 2017a.
- Feiping Nie, Jing Li, and Xuelong Li. Self-weighted multiview clustering with multiple graphs. In *Proceedings of the International Joint Conference on Artificial Intelligence*, pp. 2564–2570, 2017b.
- Feiping Nie, Xiaoqian Wang, Cheng Deng, and Heng Huang. Learning A structured optimal bipartite graph for co-clustering. In *Advances in Neural Information Processing Systems*, pp. 4129–4138, 2017c.

594 595 596	Shuran Song, Samuel P. Lichtenberg, and Jianxiong Xiao. SUN RGB-D: A RGB-D scene under- standing benchmark suite. In <i>IEEE Conference on Computer Vision and Pattern Recognition</i> , pp. 567–576, 2015.
597 598 599	Hao Wang, Yan Yang, and Bing Liu. GMC: graph-based multi-view clustering. <i>IEEE Trans. Knowl. Data Eng.</i> , 32(6):1116–1129, 2020.
600 601 602	Siwei Wang, Xinwang Liu, Xinzhong Zhu, Pei Zhang, Yi Zhang, Feng Gao, and En Zhu. Fast parameter-free multi-view subspace clustering with consensus anchor guidance. <i>IEEE Trans. Image Process.</i> , 31:556–568, 2022.
603 604 605 606	Ben Yang, Xuetao Zhang, Feiping Nie, Fei Wang, Weizhong Yu, and Rong Wang. Fast multi-view clustering via nonnegative and orthogonal factorization. <i>IEEE Trans. Image Process.</i> , 30:2575–2586, 2021.
607 608 609	Ben Yang, Xuetao Zhang, Feiping Nie, Badong Chen, Fei Wang, Zhixiong Nan, and Nanning Zheng. Ecca: Efficient correntropy-based clustering algorithm with orthogonal concept factor- ization. <i>IEEE Transactions on Neural Networks and Learning Systems</i> , pp. 1–14, 2022.
610 611 612	Kun Zhan, Feiping Nie, Jing Wang, and Yi Yang. Multiview consensus graph clustering. <i>IEEE Trans. Image Process.</i> , 28(3):1261–1270, 2019.
613 614	Zheng Zhang, Li Liu, Fumin Shen, Heng Tao Shen, and Ling Shao. Binary multi-view clustering. <i>IEEE Transactions on Pattern Analysis and Machine Intelligence</i> , 41(7):1774–1782, 2019.
616	
617	
618	
619	
620	
621	
622	
623	
624	
625	
626	
627	
628	
629	
630	
620	
632	
634	
635	
636	
637	
638	
639	
640	
641	
642	
643	
644	
645	
646	
647	