

SELF-PREFERENCE BIAS IN LLM-AS-A-JUDGE

Anonymous authors

Paper under double-blind review

ABSTRACT

Automated evaluation leveraging large language models (LLMs), commonly referred to as LLM evaluators or LLM-as-a-judge, has been widely used in measuring the performance of dialogue systems. However, the self-preference bias in LLMs has posed significant risks, including promoting specific styles or policies intrinsic to the LLMs. Despite the importance of this issue, there is a lack of established methods to measure the self-preference bias quantitatively, and its underlying causes are poorly understood. In this paper, we introduce a novel quantitative metric to measure the self-preference bias. Our experimental results demonstrate that GPT-4 exhibits a significant degree of self-preference bias. To explore the causes, we hypothesize that LLMs may favor outputs that are more familiar to them, as indicated by lower perplexity. We analyze the relationship between LLM evaluations and the perplexities of outputs. Our findings reveal that LLMs assign significantly higher evaluations to outputs with lower perplexity than human evaluators, regardless of whether the outputs were self-generated. This suggests that the essence of the bias lies in perplexity and that the self-preference bias exists because LLMs prefer texts more familiar to them.

1 INTRODUCTION

Measuring the quality of responses in dialogue systems presents unique challenges due to the diverse range of response strategies. Nowadays, thanks to the strong text understanding of large language models (LLMs), various automatic evaluations can be easily implemented by employing LLMs as evaluators (often referred to as LLM evaluators or LLM-as-a-judge). MT-Bench (Zheng et al., 2024) is an example of a benchmark utilizing this approach to score dialogue systems.

However, as Deutsch et al. (2022) reported, LLM evaluators are inherently biased. The inherent bias might cause inappropriate testing and inject biased preferences into the target dialogue systems (Zheng et al., 2024). One of the most significant biases is self-preference bias, which refers to the tendency of LLMs to overestimate the quality of their own outputs, as demonstrated in Figure 1a. The self-preference bias poses potential risks, including the promotion of specific ideologies or response styles intrinsic to the LLM evaluator.

In this paper, we measure the self-preference biases of LLMs in the pairwise evaluation. To accomplish this, we propose a new metric to quantify self-preference bias on the basis of algorithmic fairness concepts, thereby enabling discussions within the existing frameworks of fairness. In our experiment, we measured self-preference bias in eight LLMs. The results indicated that GPT-4 exhibited a significant self-preference bias (Figure 1b). This finding suggests a potential concern: using GPT-4 as a judge may lead to excessive influence from GPT-4’s unique styles and policies.

Furthermore, we investigated the underlying causes of self-preference bias. Although LLM evaluators are not explicitly informed whether a given text is their own, they still exhibit self-preference bias. We hypothesized that LLM evaluators might be affected by the perplexity of the text, which tends to be lower perplexity when it is generated by themselves. To test this hypothesis, we analyzed the relationship between the perplexities of the texts to be evaluated and their corresponding evaluations. Our analysis revealed that LLMs assign significantly higher evaluations to texts with lower perplexity than human evaluators, regardless of whether the texts were self-generated. This suggests that the fundamental cause of self-preference bias may be the familiarity of the texts to the LLM evaluators, specifically how likely they are to generate the same response.

054
055
056
057
058
059
060
061
062
063
064
065
066
067
068
069
070
071
072
073
074
075
076
077
078
079
080
081
082
083
084
085
086
087
088
089
090
091
092
093
094
095
096
097
098
099
100
101
102
103
104
105
106
107

User:
Describe your current outlook of the financial markets and the us economy.


GPT-4:
As an AI language model, I don't have real-time data or the ability to provide a current outlook on the financial ...

Vicuna-13B:
Currently, the US economy is in a period of expansion and the financial markets have been performing well ...

GPT-4 Preferred

Human Preferred

(a)



(b)

Figure 1: **How much do LLMs prefer their own responses over human evaluations?** (a) illustrates an example where GPT-4 favors its own response, even when human evaluations prefer to a response generated by Vicuna-13B. (b) compares the self-preference bias scores using our proposed metric (Definition 3.1). These figures demonstrate that GPT-4 exhibits a stronger self-preference bias than other models, suggesting that it tends to rate its own outputs more favorably than human evaluations. For detailed experimental settings, refer to Section 3.

1.1 RELATED WORK

Several studies have addressed the issue of self-preference bias; however, there is a lack of reliable metrics to quantify the extent of self-preference bias, and the fundamental causes of this phenomenon remain unclear. Panickssery et al. (2024) reported on the relationship between self-preference bias and self-recognition ability, but their work lacked a comparison with human evaluators. Xu et al. (2024) and Stureborg et al. (2024) addressed quantifying self-preference bias within an evaluation approach where LLMs assign an absolute score to a single generated text. In this approach, gold-standard evaluators are required to assign scores based on abstract criteria while ensuring consistency with prior evaluations, making it challenging to obtain accurate assessments. As a result, these studies often restricted their scope to specific tasks, such as text summarization or machine translation, and relied on reference-based metrics like BLEURT (Sellam et al., 2020), which does not reflect the diversity of real-world use cases.

By contrast, a pairwise evaluation approach that involves direct comparison between two texts enables evaluators to recognize specific differences more readily, resulting in more consistent human judgments. Consequently, such pairwise evaluation methods are particularly suitable for analyzing biases related to discrepancies with human evaluations.

1.2 CONTRIBUTIONS

The contributions of this paper are threefold: (1) We propose a new metric to quantify self-preference bias in LLMs; (2) Using this metric, we evaluate the extent of self-preference bias across eight different LLMs; and (3) We identify a tendency for LLMs to assign higher ratings to texts with lower perplexity while exploring potential causes for this self-preference bias.

2 PRELIMINARIES: FAIRNESS AND BIAS

The measurement of bias in classifiers has been widely discussed within the framework of fairness (Calders et al., 2009; Hardt et al., 2016). In this section, we focus on a representative definition of fairness, Equal Opportunity, as the preparation for quantifying the self-preference bias in LLM evaluators.

Equal Opportunity (Hardt et al., 2016) is a fairness definition that requires the classifier to achieve equal recall across groups with different sensitive attributes (e.g. gender or race). Specifically, let the sensitive attribute be $S \in \{0, 1\}$, the prediction of the classifier be $Y' \in \{0, 1\}$, and the ground truth label be $Y \in \{0, 1\}$. The classifier satisfies Equal Opportunity if the following condition holds:

$$P(Y' = 1|S = 1, Y = 1) = P(Y' = 1|S = 0, Y = 1) \quad (1)$$

When quantifying bias in the classifier, the difference or ratio between both sides of the equation are often used. The amount of bias derived from this definition is the difference in how well the classifier matches the ground truth between groups with different sensitive attributes. Therefore, if there is already bias towards sensitive attributes during the creation of the ground truth, Equation 1 cannot be considered an ideal definition of fairness.

To address this drawback, the fairness definition known as Demographic Parity (Calders et al., 2009), which does not rely on ground truth, is also widely used. Demographic Parity requires that the predictive distribution of the classifier be consistent across groups with different sensitive attributes. It is based on the assumption that there is no inherent causal relationship between the sensitive attributes and the predicted labels.

LLM-as-a-judge is a technique aimed at replacing human evaluators with LLMs, and more specifically, it assumes that dialogue system are aligned based on human preferences. Therefore, in this study, we employ the concept of Equal Opportunity to quantify self-preference bias by treating LLM evaluators as classifiers.

3 QUANTIFYING SELF-PREFERENCE BIAS

In this section, we propose a new metric to quantify self-preference bias. In particular, we focus on a setting where evaluators compare two texts and select the one higher quality, allowing comparison with reliable human evaluations.

3.1 SELF-PREFERENCE BIAS METRIC

To measure the extent to which an LLM’s evaluation deviates from human evaluations across its own responses and those generated by others, we employ the concept of Equal Opportunity (Hardt et al., 2016). The bias is quantified by calculating the difference between both sides of Equation 1. A rigorous definition is provided below.

Definition 3.1. (*self-preference bias of the evaluator f .*) Let f be the evaluator assessing the quality of dialogue responses, capable of generating its own responses. For a pair of responses y_0 and y_1 in a dialogue, define: $Y \in \{0, 1\}$ as the index of the human-preferred response, $Y' \in \{0, 1\}$ as the index of the f -preferred response, and $S \in \{0, 1\}$ as the index of the f -generated response. We define the self-preference bias of the evaluator f in dialogue comparison evaluation as follows:

$$Bias = P(Y' = 1|S = 1, Y = 1) - P(Y' = 1|S = 0, Y = 1). \quad (2)$$

In this definition, the amount of bias is represented by the difference between the conditional probability of the evaluator f rating itself favorably given that the human evaluator has rated it favorably, and the conditional probability of the evaluator f rating itself unfavorably given that the human evaluator has rated it unfavorably. A value of 0 indicates the absence of bias, while a value close to 1 suggests a high degree of bias. Conversely, a value of -1 would indicate the presence of a reverse bias, where the evaluator f tends to undervalue its own responses. In this definition, the case where y_1 is preferred is explicitly considered, but this does not result in a loss of generality by treating the preferred response as y_1 .

3.2 EXPERIMENTAL SETTING

The aim of our experiment is to quantify the self-preference bias in various LLMs. To address a wide range of tasks and topics, we have LLMs evaluate responses in open-ended dialogues and measure the bias using the Definition 3.1.

162 First, we provide the LLM evaluator with a user query written by a human and two responses
 163 generated by different LLMs. We then ask the LLM evaluator to determine which of the two
 164 responses demonstrates higher quality. For clarity and ease of reference during evaluation, we
 165 designate the two responses as “response A” and “response B”. Finally, using the probabilities that
 166 the LLM evaluator outputs for “A” and “B”, denoted as $p(A|\text{context})$ and $p(B|\text{context})$, we calculate
 167 the score for response A using the following equation.

$$\text{score}_A = \frac{p(A|\text{context})}{\sum_{w \in \{A, B\}} p(w|\text{context})} \quad (3)$$

173 The score for response B is calculated in the same manner. This post-processing, as shown in
 174 Equation 3 is designed to enhance the interpretability of analyses across LLMs with different
 175 probability distributions, following the approach of Schick et al. (2021). Additionally, according to
 176 Zheng et al. (2024), LLMs may exhibit position bias, which refers to the tendency to prefer responses
 177 located in specific positions within the prompt. To mitigate this bias, we swap the positions of
 178 responses A and B, and the evaluation scores are averaged over two iterations. Using the scores
 179 obtained through the above process, we examine the extent to which there is a difference in evaluation
 180 scores between the LLM’s own generated response and responses generated by other LLMs.

181 Empirical evaluation uses Chatbot Arena dataset (Zheng et al., 2024), which contains 33,000 dialogues
 182 and each consisting of a user query and a pair of responses generated by two different LLMs. We
 183 calculate evaluation scores for the pre-existing response pairs stored in the dataset. In this dataset,
 184 every response pair is labeled with either “model.a”, “model.b”, or “tie” as a result of a human
 185 evaluation comparing the quality of the responses.

186 As the LLM evaluators, we employed the following eight LLMs, which also used in Chatbot Arena
 187 dataset: the closed-source GPT-3.5-Turbo and GPT-4 (Josh et al., 2024), and the open-source Vicuna-
 188 7b, Vicuna-13b (Chiang et al., 2023), oasst-pythia-12b (Biderman et al., 2023), dolly-v2-12b (Conover
 189 et al., 2023), Koala-13b (Geng et al., 2023), and stablelm-tuned-alpha-7b (Jonathan Tow). We used
 190 the same prompt as Zheng et al. (2024) to calculate the evaluation scores of responses A and B
 191 for all LLM evaluators. This prompt was created based on the work of Zheng et al. (2024), and it
 192 instructs the LLM to output either “[A]”, “[B]”, or “[C]” after providing an explanation. In the
 193 implementation, we used the output probability distribution following the token corresponding to
 194 “[A]” in the generated text to compute the score using Equation 3. Additionally, if the LLM evaluators
 195 failed to comply with the prompt instructions and did not provide a response in the format of “[A]”
 196 or a similar structure, these cases were excluded from the analysis.

198 3.3 RESULT

200 The results of the bias measurement using Definition 3.1 are presented in Figure 1b. It was confirmed
 201 that GPT-4 exhibits the highest self-preference bias. Definition 3.1 focuses on the recall of the LLM
 202 evaluator concerning both high and low ratings by the human evaluator. Thus, it can be concluded
 203 that GPT-4 showed lower recall in cases where humans evaluated unfavorably compared to when
 204 higher evaluating. When examining the recall values in the confusion matrix shown in Figure 2, they
 205 are calculated as $0.945 \approx \frac{1852}{108+1852}$ and $0.425 \approx \frac{118}{160+118}$. The difference between these values is
 206 0.520, which corresponds to the value reported in Figure 1b. Following GPT-4, Vicuna-13b and
 207 Koala-13b also exhibited significant bias. In contrast, other LLMs displayed values relatively close to
 208 zero. Notably, oasst-pythia-12, dolly-v2-12b, and stablelm-tuned-alpha-7b showed negative values,
 209 indicating a reverse bias where the LLMs tend to underestimate their own outputs.

210 Table 1 presents a randomly selected example of self-preference bias in GPT-4, where humans favored
 211 the alternative response. In this example, the user query is a straightforward request to list blue
 212 items. While GPT-4 states that it lacks physical recognition before listing, GPT-3.5-Turbo directly
 213 lists the blue items without any such explanation. Both responses are of high quality, and the final
 214 evaluation reflects the evaluator’s policy and stylistic preferences. Although humans and GPT-3.5-
 215 Turbo preferred the response from GPT-3.5-Turbo, GPT-4 favored its own response, illustrating a
 typical case of self-preference bias.

216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269




Figure 2: Confusion matrix for each LLM evaluator’s assessment of pairs including its own output. It suggests that **some LLMs, including GPT-4, have relatively high true positive rates than true negative rate, which means that they have self-preference bias.**

Table 1: **An example of self-preference bias in GPT-4.** The user query involves a simple request to list blue items. GPT-4 responds by first acknowledging its lack of physical cognition, and then proceeds to list blue items. In contrast, GPT-3.5-Turbo directly lists blue items without any preliminary explanation which human evaluation prefers.

User: Please list the blue items	
<p>GPT-4: As a language model AI, I can’t see the physical objects around you. However, here are some common blue items that people might have:</p> <ol style="list-style-type: none"> 1. Blue shirt 2. Blue jeans 3. Blue pen 4. Blue coffee mug 5. Blue pillow 6. Blue blanket 7. Blue towel 8. Blue notebook 9. Blue umbrella 10. Blue vase <p>Please specify the context or the category of items you are interested in if you need a more precise list.</p>	<p>GPT-3.5-Turbo: Sure, here are some blue items:</p> <ol style="list-style-type: none"> 1. Blue jeans 2. Blueberries 3. Blue shirt 4. Blue pen 5. Blue car 6. Blue backpack 7. Blue notebook 8. Blue umbrella 9. Blue sneakers 10. Blue curtains
GPT-4 preferred	Human and GPT-3.5-Turbo preferred

4 HOW DO LLMs OVERESTIMATE THEIR OWN OUTPUTS?

We have shown that certain LLM evaluators tend to assign disproportionately high scores based on whether the output being generated from themselves, even though LLM evaluators are not explicitly provided with labels indicating whether a given output is their own. We hypothesized that LLM evaluators might be affected by the similarity of the response to their own output. To investigate this further, we focus on how LLM evaluators change their evaluation depending on the perplexities of responses.

As in previous experiments, we employed the pairwise evaluation framework where evaluators compare two responses, response A and B. First, we computed the perplexities of responses conditioned on the prompt, and took the difference between response A and B for all samples. Next, we divided the perplexity differences into bins and calculated the probabilities that each LLM evaluator judged response A as the winner in each subset. Additionally, we computed the winning judgment rate of the




Figure 3: **LLMs vs human conditioned on perplexity.** Winning judgment rates by LLMs conditioned on perplexity with human winning judgment rates are plotted. All models except dolly-v2-12b and stablelm-tuned-alpha-7b demonstrated a clear tendency to assign higher evaluations to responses with lower perplexity.

human for response A within each bin. In this experiment, we excluded GPT-4 and GPT-3.5-Turbo, as perplexity values could not be obtained for these models.

Figure 3 shows the comparison of winning judgment rates within each perplexity bin for six models. All models except stablelm-tuned-alpha-7b demonstrated a clear tendency to assign higher evaluations to responses with lower perplexity. Furthermore, it was confirmed that this tendency was stronger in vicuna-13b, vicuna-7b, koala-13b, and oasst-pythia-12b than in humans. This result indicates that LLM evaluators overly change their evaluation depending on perplexities of responses.

To further investigate the effect of differences in whether the output is self-generated or not, we segmented the evaluation results by the LLM evaluators into two distinct groups: one where the LLM evaluators' own output is included in the pair and another where it is not. We present the results with the output of the LLM evaluator as response A, without loss of generality. As shown in Figure 4, the winning judgment rates between two groups were similar for all models except dolly-v2-12b and stable-tuned-alpha-7b. This suggests that the factor influencing the LLM evaluators' judgments is not whether the response is their own but rather the perplexity of the responses. As confirmed by Figure 5, LLMs tend to exhibit lower perplexity for their own outputs. In other words, these findings imply that self-preference bias may be a phenomenon where the model's own output inherently exhibits lower perplexity.

In these experiments, we were unable to obtain perplexity values from GPT-4 and GPT-3.5-Turbo, resulting in a lack of analysis on the competitive LLMs. To address this gap, we conducted additional experiments using Llama2 (Touvron et al., 2023) and Llama3 (Dubey et al., 2024). However, the Chatbot Arena dataset does not contain human annotations for these LLMs' responses. Therefore, we obtained evaluations for existing responses from these Llama models and only compared them with human evaluations.

The results are presented in Figure 6. We found that all models changed their evaluations more than humans, depending on the difference in perplexity. This indicates that even in the competitive models, including Llama 3.1, perplexity may be causing unfair bias in the evaluation.

324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377




Figure 4: **LLM vs other LLMs conditioned on perplexity.** Winning judgment rates by LLMs on their own texts and texts generated by other models conditioned on perplexity are plotted. Across all models, except for dolly-v2-12b and stablelm-tuned-alpha-7b, no significant difference was observed between the judgment rates for their own texts and those generated by other models. This suggests that LLM evaluators assign higher ratings to texts with lower perplexity, regardless of whether the text was self-generated or produced by other models.




Figure 5: **Average of log-perplexity of responses for each LLM evaluator.** The red bars represent the perplexity for responses generated by the LLM evaluator itself, while the blue bars represent the perplexity for responses generated by other LLMs. Across all models, the average perplexity is lower for responses generated by the evaluators themselves.

5 DISCUSSION

To reduce self-preference bias, one possible approach is ensemble evaluation using multiple models. This method is expected to provide a more equitable evaluation by avoiding reliance on a single model. Specifically, when a model exhibits low perplexity on a sample, decreasing the weight assigned to that model’s evaluation for that sample may contribute to bias mitigation. To evaluate the effectiveness of bias reduction strategies, our proposed new metric can be utilized. Therefore, we believe that our




Figure 6: **Llama family vs human conditioned on perplexity.** Winning judgment rates with condition on perplexity are plotted. Llama-2 and later models models exhibited significantly higher winning judgment rate with lower perplexity compared to human evaluators.

research makes a significant contribution to the understanding of self-preference bias and will greatly facilitate the development of future research in this area.

Our experimental results reveal that LLM evaluators tend to assign higher scores to texts with lower perplexity. We further discuss the reasons behind this phenomenon. First, LLMs are trained during the pretraining phase to reduce perplexity on large-scale text corpora. Moreover, when aligning with human preferences, the models are also trained to minimize perplexity on the given dialogue data. Therefore, high-perplexity texts are likely those that the LLM has not frequently encountered during training, suggesting that such texts may be related to domains that the LLM evaluators do not fully comprehend.

This observation may seem contradicted by the fact that GPT-4, which is well-versed across various domains due to a wide range of benchmarks, exhibits a high degree of self-preference bias. However, by investigating specific cases of self-preference bias, as shown in Figure 1a and Table 1, we found that the bias was often not related to clear factual errors but rather to differences in response styles, such as the handling of specialized domains or the description of premises before answering. This suggests that, advanced models like GPT-4, which thoroughly understand and adhere to their predefined policies, may use the degree of alignment with these policies as a deciding factor when evaluating responses of comparable quality.

6 CONCLUSION

In this study, we propose a metric to quantify the self-preference bias in LLM-as-a-judge and measured the self-preference bias of eight LLMs. Experimental results confirmed that GPT-4, in particular, exhibits a high self-preference bias. This finding suggests a risk that GPT-4 as a judge may inadvertently reinforce its own style and policies.

Furthermore, we hypothesized that the self-preference bias is related to the perplexity of the texts, and showed that, compared to human evaluators, LLM evaluators assigned higher evaluations to texts with lower perplexity, and this tendency was observed regardless of whether the text was generated by themselves or not. This suggests that the essence of the bias lies in perplexity and that the self-preference bias exists because LLMs prefer texts more familiar to them.

REFERENCES

- Stella Biderman, Hailey Schoelkopf, Quentin Gregory Anthony, Herbie Bradley, Kyle O’Brien, Eric Hallahan, Mohammad Aflah Khan, Shivanshu Purohit, USVSN Sai Prashanth, Edward Raff, et al. Pythia: A suite for analyzing large language models across training and scaling. In *International Conference on Machine Learning*, pp. 2397–2430. PMLR, 2023.
- Toon Calders, Faisal Kamiran, and Mykola Pechenizkiy. Building classifiers with independency constraints. In *2009 IEEE International Conference on Data Mining Workshops*, pp. 13–18, 2009. doi: 10.1109/ICDMW.2009.83.
- Wei-Lin Chiang, Zhuohan Li, Zi Lin, Ying Sheng, Zhanghao Wu, Hao Zhang, Lianmin Zheng, Siyuan Zhuang, Yonghao Zhuang, Joseph E. Gonzalez, Ion Stoica, and Eric P. Xing. Vicuna: An open-source chatbot impressing gpt-4 with 90%* chatgpt quality, March 2023. URL <https://lmsys.org/blog/2023-03-30-vicuna/>.
- Mike Conover, Matt Hayes, Ankit Mathur, Jianwei Xie, Jun Wan, Sam Shah, Ali Ghodsi, Patrick Wendell, Matei Zaharia, and Reynold Xin. Free dolly: Introducing the world’s first truly open instruction-tuned llm, 2023. URL <https://www.databricks.com/blog/2023/04/12/dolly-first-open-commercially-viable-instruction-tuned-llm>.
- Daniel Deutsch, Rotem Dror, and Dan Roth. On the limitations of reference-free evaluations of generated text. In Yoav Goldberg, Zornitsa Kozareva, and Yue Zhang (eds.), *Proceedings of the 2022 Conference on Empirical Methods in Natural Language Processing*, pp. 10960–10977, Abu Dhabi, United Arab Emirates, December 2022. Association for Computational Linguistics. doi: 10.18653/v1/2022.emnlp-main.753. URL <https://aclanthology.org/2022.emnlp-main.753>.
- Abhimanyu Dubey, Abhinav Jauhri, Abhinav Pandey, Abhishek Kadian, Ahmad Al-Dahle, Aiesha Letman, Akhil Mathur, Alan Schelten, and Amy Yang et al. The llama 3 herd of models, 2024. URL <https://arxiv.org/abs/2407.21783>.
- Xinyang Geng, Arnav Gudibande, Hao Liu, Eric Wallace, Pieter Abbeel, Sergey Levine, and Dawn Song. Koala: A dialogue model for academic research. Blog post, April 2023. URL <https://bair.berkeley.edu/blog/2023/04/03/koala/>.
- Moritz Hardt, Eric Price, and Nathan Srebro. Equality of opportunity in supervised learning. In *Proceedings of the 30th International Conference on Neural Information Processing Systems, NIPS’16*, pp. 3323–3331, Red Hook, NY, USA, 2016. Curran Associates Inc. ISBN 9781510838819.
- et al. Jonathan Tow. Stablelm alpha v2 models. URL <https://huggingface.co/stabilityai/stablelm-tuned-alpha-7b>.
- Achiam Josh, Adler Steven, Agarwal Sandhini, Ahmad Lama, Akkaya Ilge, Leoni Aleman Florencia, Almeida Diogo, Altmenschmidt Janko, Altman Sam, and et al. Shyamal, Anadkat. Gpt-4 technical report, 2024. URL <https://arxiv.org/abs/2303.08774>.
- Arjun Panickssery, Samuel R. Bowman, and Shi Feng. Llm evaluators recognize and favor their own generations, 2024. URL <https://arxiv.org/abs/2404.13076>.
- Timo Schick, Sahana Udupa, and Hinrich Schütze. Self-diagnosis and self-debiasing: A proposal for reducing corpus-based bias in NLP. *Transactions of the Association for Computational Linguistics*, 9:1408–1424, 2021. doi: 10.1162/tacl.a.00434. URL <https://aclanthology.org/2021.tacl-1.84>.
- Thibault Sellam, Dipanjan Das, and Ankur Parikh. BLEURT: Learning robust metrics for text generation. In Dan Jurafsky, Joyce Chai, Natalie Schluter, and Joel Tetreault (eds.), *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, pp. 7881–7892, Online, July 2020. Association for Computational Linguistics. doi: 10.18653/v1/2020.acl-main.704. URL <https://aclanthology.org/2020.acl-main.704>.
- Rickard Stureborg, Dimitris Alkaniotis, and Yoshi Suhara. Large language models are inconsistent and biased evaluators, 2024. URL <https://arxiv.org/abs/2405.01724>.

486 Hugo Touvron, Louis Martin, Kevin Stone, Peter Albert, Amjad Almahairi, and Yasmine Babaei et al.
487 Llama 2: Open foundation and fine-tuned chat models, 2023. URL [https://arxiv.org/abs/](https://arxiv.org/abs/2307.09288)
488 [2307.09288](https://arxiv.org/abs/2307.09288).
489
490 Wenda Xu, Guanglei Zhu, Xuandong Zhao, Liangming Pan, Lei Li, and William Yang Wang. Pride
491 and prejudice: Llm amplifies self-bias in self-refinement, 2024. URL [https://arxiv.org/abs/](https://arxiv.org/abs/2402.11436)
492 [2402.11436](https://arxiv.org/abs/2402.11436).
493 Lianmin Zheng, Wei-Lin Chiang, Ying Sheng, Siyuan Zhuang, Zhanghao Wu, Yonghao Zhuang,
494 Zi Lin, Zhuohan Li, Dacheng Li, Eric P. Xing, Hao Zhang, Joseph E. Gonzalez, and Ion Stoica.
495 Judging llm-as-a-judge with mt-bench and chatbot arena. In *Proceedings of the 37th International*
496 *Conference on Neural Information Processing Systems, NIPS '23*, Red Hook, NY, USA, 2024.
497 Curran Associates Inc.
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539