

ENTER: Event Based Interpretable Reasoning for VideoQA

Anonymous ACL submission

Abstract

In this paper, we present ENTER, an interpretable Video Question Answering (VideoQA) system based on event graphs. Event graphs convert videos into graphical representations, where video events form the nodes and event-event relationships (temporal/causal/hierarchical) form the edges. This structured representation offers many benefits: 1) Interpretable VideoQA via generated code that parses event-graph; 2) Incorporation of contextual visual information in the reasoning process (code generation) via event graphs; 3) Robust VideoQA via Hierarchical Iterative Update of the event graphs. Existing interpretable VideoQA systems are often top-down, disregarding low-level visual information in the reasoning plan generation, and are brittle. While bottom-up approaches produce responses from visual data, they lack interpretability. Experimental results on NExT-QA, IntentQA, NExT-GQA, and STAR demonstrate that not only does our method outperform existing top-down approaches while obtaining competitive performance against bottom-up approaches, but more importantly, it offers superior interpretability and explainability in the reasoning process.

1 Introduction

Video Question Answering (VideoQA) (Xiao et al., 2021a; Yu et al., 2019) is a challenging task that requires recognizing objects, people, actions, and events, and understanding their relationships’ evolution across time. Traditional VideoQA models (Wang et al., 2022; Song et al., 2024) were trained end-to-end, and while these systems perform strongly, they suffer from a lack of interpretability in their decision process. This lack of transparency undermines trust and reliability and limits their utility when understanding the model’s decision-making process is crucial.

To address this, modular reasoning approaches (Surís et al., 2023; Min et al., 2024) break down




Figure 1: Comparison of our proposed method with existing approaches for VideoQA. Bottom-up approaches directly process visual data but their reasoning is not transparent. In contrast, Top-down methods are interpretable but fail to use visual information in the plan or code generation piece. In contrast, our intermediate multimodal graph-based method combines the strengths of both: interpretability + use of visual information for event graph generation, making our predictions more transparent and context-aware.

the reasoning process into interpretable steps, making the decision-making process more transparent, reliable, and trustworthy. Such properties are vital for applications in high-stakes environments, real-world deployments where human oversight is essential, and improving individual reasoning or perception modules through explicit feedback. Despite their promise, current interpretable approaches for VideoQA (Surís et al., 2023; Min et al., 2024) follow a top-down approach by generating reasoning plans solely from the input question. While the modular structure improves interpretability, it fails to fully utilize the visual modality. Ignoring this visual context during plan generation limits the reasoning system’s ability to incorporate contextual clues that are critical for answering complex ques-

tions or navigating complex media assets such as long-range videos. Further, these systems are brittle: if the key visual clues are missing from the initial plan, the system is not able to correct the incomplete plan. In contrast, bottom-up approaches (Zhang et al., 2024a; Fan et al., 2024) directly use the frames to produce the answer. While some methods (Wang et al., 2024c) select frames based on the questions, allowing these systems to be contextual and robust, but the reasoning process is still opaque since they directly produce the answer from captions using Large Language Models (LLMs).

To bridge this gap, we propose ENTER, **E**vent **B**ased **I**nterpretable **R**easoning. ENTER combines the interpretability of modular reasoning with the contextual awareness and robustness of bottom-up systems by integrating visual information into the plan generation process. ENTER uses a structured and intermediate representation of videos known as event graphs, as shown in fig. 1. In these graphs, nodes represent events and edges capture relationships between events, forming a rich structured representation of the events in the video. The event graph, along with the question, is passed to a large language model (LLM) to generate modular, Python-based code that parses the graph. This process allows the system to explicitly model relationships between events and incorporate them into the reasoning process. The generated code is then executed to arrive at the final answer.

ENTER uses a hierarchical approach to enhance graph completeness for answering questions to maximize efficiency. Initially, ENTER generates a dense graph from available captions, as this is the least costly operation. If the initial graph lacks necessary detail, ENTER enhances the captions and regenerates a denser graph. Only if these steps are insufficient does ENTER introduce multimodal edges, which is a more resource-intensive operation. By doing so, ENTER makes efficient use of computational resources but also enhances the robustness of the graph to mitigate failure cases caused by incomplete graphs.

ENTER’s syntactic, interpretable code and event graph provide full transparency into its decision-making process. Event graphs provide ENTER with a powerful representation that captures explicit relationships between events throughout an entire video, enabling it to address questions requiring long-range dependencies. The structured design of these graphs naturally embeds complex semantic relationships, such as causality and temporal

order, enabling robust, interpretable reasoning. ENTER combines the clarity and modularity of interpretable models with the contextual awareness of end-to-end systems, offering users a balanced, transparent, and effective reasoning framework.

We demonstrate the effectiveness of ENTER through comparable or even better performance than state-of-the-art on the NExT-QA (Xiao et al., 2021a), IntentQA (Li et al., 2023a), NExT-GQA, (Xiao et al., 2024), and STAR (Wu et al., 2024) VideoQA datasets and highlight the benefits of structured event graphs for video reasoning. Our qualitative results highlight the advantages of this representation and illustrate how event-based graphs contribute to more accurate and interpretable reasoning. Finally, our approach allows more focused debugging and easily allows isolation of the root cause of the error from the representation, the executable reasoning, or the reasoner’s use of the knowledge.

2 Related Works

2.1 Top-Down vs. Bottom-Up in Video QA

Existing interpretable VideoQA methods (Yang et al., 2023b; Wang et al., 2024a; Zheng et al., 2024; Surís et al., 2023; Min et al., 2024) often take a top-down approach generating reasoning steps in response to a specific question. Typically, these steps are structured as programs that use APIs to interact with the video (Surís et al., 2023; Min et al., 2024; Subramanian et al., 2023; Gupta and Kembhavi, 2022) or as chains of thought grounded in visual cues (Fei et al., 2024). However, because reasoning steps are generated independently of the visual data, their ability to fully understand video content is constrained. In contrast, bottom-up approaches (Lin et al., 2021; Wang et al., 2022; Ashutosh et al., 2023; Islam et al., 2024; Zhang et al., 2023; Fan et al., 2024; Zhang et al., 2024a; Li et al., 2024a; Maaz et al., 2024; Wang et al., 2024c) jointly process both the question and video, allowing for reasoning that integrates richer visual information. For example, methods like LLoVi (Zhang et al., 2024a) employ extensive captioning, while VideoAgent (Fan et al., 2024) iteratively selects keyframes. While these models can incorporate more detailed visual data, they often lack interpretability. To bridge this gap, recent work (Lin et al., 2023; Liu et al., 2021; Yang et al., 2023a; Chen et al., 2024; Fan et al., 2024; Lin et al., 2024) explored end-to-end methods that aim to integrate

visual data while maintaining interpretability. However, these still struggle to fully address complex queries, often providing limited reasoning steps or relying on simple visual or commonsense cues.

2.2 Contextual Plan Generation

Our work is inspired by Neural Module Networks (Andreas et al., 2017), which suggests that complex vision tasks are inherently compositional and should be divided into atomic perceptual units. CodeVQA (Subramanian et al., 2023), ViperGPT (Surís et al., 2023), and VisProg (Gupta and Kembhavi, 2022) achieve accuracy comparable to end-to-end systems by leveraging GPT-3’s (Brown et al., 2020) and GPT-4’s (OpenAI et al., 2024) ability to generate code that acts as a plan for answering visual questions through reasoning steps. MoReVQA (Min et al., 2024) introduces multi-stage plan generation but does not integrate visual context throughout its reasoning process. In contrast, our method can generate and adaptively refine the reasoning plan in response to evolving visual details from complex dynamic scenes in videos.

2.3 Iterative Robustness in VideoQA

Many existing VideoQA methods (Ko et al., 2023; Min et al., 2024; Choudhury et al., 2023; Mogrovejo and Solorio, 2024; Pan et al., 2023; Shen et al., 2024; Han et al., 2024; Wu, 2024; Xu et al., 2024; Zhang et al., 2024b; Wang et al., 2024b) focus on question-answering without incorporating a comprehensive error analysis mechanism. This leads to models that are less robust when given complex or ambiguous queries. To solve this, TravelER (Shang et al., 2024) iteratively refines its understanding through locating, evaluating, and replanning agents. VidF4 (Liang et al., 2024) introduces frame-scoring mechanisms for question relevance and inter-frame similarity. VideoInsta (Liao et al., 2024) applies a self-reflective reasoning approach to enhance information sufficiency in VideoQA. VideoTree (Wang et al., 2024c) iteratively refines keyframe selection based tree-based structure. ENTER’s self-correction strategy helps ensure a more thorough understanding of the video content when needed, allowing robust performance of the VideoQA system.

3 Method

We propose a modular approach for VideoQA that represents videos with event graphs and generates code to parse the graph interpretably. Starting with

a detailed video description, we construct the event graph (Section 3.1), which, along with the input question, directs the generation of a Python-based reasoning plan (Section 3.2). This code is then executed to answer the question or, if details are missing, performs self-correction by iteratively retrieving necessary information (Section 3.3) for improved robustness.

3.1 Event Graph Generation

To generate event graphs from videos, we first convert the video to captions using Vision Language Model (VLM) and then extract event graphs from captions using LLMs. The two stages leverage the strength of VLM and LLM for each of their respective tasks in the process. In comparison, a single-stage process to convert videos to event graphs suffers from noisy predictions since VLMs were not inherently trained on graph generation tasks.

3.1.1 Caption Generation from Video

To build our event graph, we generate structured descriptions of video events. Standard captioning methods, like frame-based captioning (Zhang et al., 2024b), often lose entity coherence and miss subtle event relationships, limiting their effectiveness for detailed graph construction. Although recent work (Raajesh et al., 2024) enhances coreference for people, it lacks depth in capturing complex relationships for generic objects.

Our approach (shown as ① in Figure 2) emphasizes preserving event relationships, providing detailed descriptions, and maintaining consistent entity coreference. We prompt the model to use relational keywords like “after,” “due to,” or “meanwhile” to capture temporal, causal, and hierarchical links. Entities are described specifically (e.g., “white Honda Civic”) and consistently referenced (e.g., “black car with broken window”) throughout. This structured captioning supports event graph generation that links entities and relationships across the video needed for robust reasoning.

3.1.2 Graph Generation

To build the event graph (shown as ② in Figure 2), we extract events and their relationships from the caption, where each node represents an event, and directed edges capture intra-event semantic relationships: temporal, causal, and hierarchical. Temporal edges link events occurring sequentially, causal edges connect events with cause-effect relationships, and hierarchical edges denote




Figure 2: Overall pipeline of our method. Video is first converted to event-graph via captioning. Next, python code is generated to parse the graph. Further, any missing information in graph is added via iterative hierarchical update. Bottom-left flow chart depicts the flow of our method, along with the relative cost of each operation.

Prec. Nodes	Prec. Edges	Sufficiency
96.5	87.7	92.0

Table 1: Precision of nodes and edges measure the percentage of nodes/edges present in the graph that are indeed in the video, i.e. the described events/relations are not hallucinated, fabricated, or incorrect. Sufficiency measures the percentage of questions that are sufficiently answerable given the graph.

event containment.

Each node includes arguments that represent participants or objects involved in the event (e.g., in “A man driving a car,” the event “Drive” includes “actor” as “man” and “vehicle” as “car”). To preserve coreference, we prompt the model for consistent naming of arguments and events across the graph, as discussed in Section 3.1.1. Additionally, the model is prompted to identify all relevant event relationships to produce a comprehensive, cohesive graph that captures the video’s full semantics.

To ensure the information recorded in the graphs are correct and sufficient to answer the question, we sampled 341 event nodes and 853 edges. We manually verified their correctness, i.e. the event/relation described is indeed in the video. We also sample 50 graphs to verify if the graph itself is sufficient to answer the question. As shown in Table 1, the graph nodes have a precision of 96.5% and edges are 87.7%, meaning the event graphs are precise descriptions of the videos. The sufficiency of the event graphs is 92.0%, meaning most questions are sufficiently answerable given the event graphs.

3.2 Code Generation and Execution

To answer questions, we generate Python code that utilizes both the event graph and the textual question. Inspired by ViperGPT’s API (Surís et al., 2023), we designed an API with Event and EventGraph classes to navigate and query the graph. For example, EventGraph includes a get_child method to retrieve hierarchically related nodes for a given event. The code generator receives an abstract API definition with function signatures and examples. This API and prompt guide the model to produce Python code focused on task-specific logic, executed via Python’s interpreter using basic control structures, statements, and loops. This abstraction improves efficiency by focusing the model on high-level reasoning.

To derive the final answer, we extract the relevant event and arguments from the question, locate the corresponding node in the graph, and traverse its subgraph to collect the necessary details. Unlike other VideoQA methods that may overlook visual features or process video data inefficiently, our approach uses the event graph’s compact, text-based representation to integrate visual context efficiently in the code generation process. Code generation and execution correspond to steps ③ and ⑤ in Figure 2. In case of multiple choice question, a reasoner (LLM) call is made via select_answer(question, possible_answers, info).

3.3 Iterative Hierarchical Graph Update

In cases where the initial event graph lacks the details necessary to answer the question, we perform

Method	NExT-QA				IntentQA				STAR				
	All	Cau.	Tem.	Des.	All	CW	CH	TP&TN	Mean	Int	Seq	Pre	Fea
<i>End-to-End</i>													
VideoChat2 HD (Li et al., 2024b)	61.7	61.9	57.4	69.9	-	-	-	-	-	-	-	-	-
SeViLA (Yu et al., 2023)	63.6	61.5	61.3	75.6	60.9	-	-	-	44.6	-	-	-	-
Gemini 1.5 Flash	70.4	71.9	64.1	78.1	68.8	70.8	76.2	59.2	-	-	-	-	-
<i>Bottom-up</i>													
LLoVi (Zhang et al., 2024b)	67.7	69.5	61.0	75.6	67.1	-	-	-	-	-	-	-	-
VideoTree (Wang et al., 2024c)	75.6	76.5	70.6	83.9	66.9	-	-	-	-	-	-	-	-
LVNet (Park et al., 2024)	72.9	75.0	65.5	81.5	71.7	75.0	74.4	62.1	-	-	-	-	-
Q-ViD (Zhang et al., 2024b)	66.3	67.6	61.6	72.2	-	-	-	-	45.7	48.2	47.2	43.9	43.4
VideoINSTA(Liao et al., 2024)	72.3	-	-	-	72.8	-	-	-	-	-	-	-	-
<i>Top-Down/Modular</i>													
ProViQ (Choudhury et al., 2023)	63.8	-	-	-	-	-	-	-	-	-	-	-	-
MoReVQA (Min et al., 2024)	69.2	61.3	61.5	75.6	-	-	-	-	-	-	-	-	-
TraveLER (Shang et al., 2024)	68.2	70.0	60.5	78.2	65.2	69.9	64.7	54.4	44.9	-	-	-	-
ViperGPT (Suris et al., 2023)	60.0	-	-	-	54.7	-	-	-	41.6	-	-	-	-
Ours	75.1	77.9	68.2	79.2	71.5	73.2	79.1	61.4	67.1	63.9	69.1	67.2	69.1

Table 2: Our method on NExT-QA, IntentQA, and STAR compared with other zero-shot methods. Our method outperforms most of them while maintaining interpretability.

an Iterative Hierarchical Graph Update process to address information gaps. Missing information can result from limitations in the captioning, graph generation or modality gap between video and text information. Unlike existing modular methods that risk undetected gaps or hallucinated results, our graph-based approach identifies and addresses these gaps through a structured, self-correcting process. The update mechanism applies a three-stage approach. Starting with low-cost graph consolidation, it progressively adds detail by refining captions and, if needed, incorporating multimodal data. The hierarchical refinement, described below, iteratively refines the event graph with additional layers of information only as needed which improves the system’s ability to accurately answer questions, while remaining efficient.

Denser Graph Generation. If the missing information exists in the captions but is not captured in the graph, we generate a denser graph by reprocessing the captions with a focus on the missing details. We implement `generate_denser_graph(graph, caption, request)`, which reinvokes the graph generator using the current graph, captions, and a request to include the missing nodes or relations. This stage corresponds to the ③ to ② Figure 2.

Denser Caption Generation. When necessary events or relations are absent from the captions themselves, we generate denser captions by prompting the captioner to include the missing information. The function `generate_denser_caption(caption, video, request)` reprocesses the video to extract these details. The new information is then integrated into the graph using `generate_denser_graph`. This stage is represented by the ③ to ① loop in Figure 2. We repeat this procedure a fixed number of times or until the relevant events and relations are

included before proceeding to the next step.

Multimodal Information Incorporation. If the denser captions and graphs remain insufficient to answer the question, we enhance the graph using multimodal information. Uncertainty in the model’s answers can be detected using confidence assessments (You et al., 2023). Upon detecting uncertainty, we invoke `get_new_info(question, request, video)`, prompting the captioner to revisit the video and retrieve the required information. If gaps remain and are detected by `has_sufficient_info`, as the last fail-safe, we enhance the graph nodes with relevant video clips to create a multimodal representation. Specifically, `generate_multi_modal_edges(subgraph)` iterates through the nodes of the subgraph (Section 3.2) and retrieves node-relevant video clips using Gemini 1.5 Flash as the retrieval model. The enhanced multimodal subgraph is then passed to a vision-language model to answer the question. This stage corresponds to the ④ to ③ loop in Figure 2.

We list all the prompts in Section G, and we will release our code on acceptance.

4 Experiments

To validate the effectiveness of our approach, we conduct a series of experiments on the NExT-QA (Xiao et al., 2021b), IntentQA (Li et al., 2023b), NExT-GQA, (Xiao et al., 2024), and STAR (Wu et al., 2024) datasets. These experiments are designed to provide our system’s performance on multiple-choice question-answering tasks and comparisons against existing methods. In addition to performance metrics, we also focus on the interpretability of our approach. The following sections show our experimental setup and results.

Model	Raw QA	ACC@GQA	mIoP	IoP@0.5	mIoU	TIoU@0.5
LLoVi	66.8	24.3	37.3	36.9	20.0	15.3
DeVi(Qin et al., 2024)	71.6	28.0	39.3	37.9	22.3	17.4
MoReVQA	-	31.0	44.1	43.0	20.7	18.3
Ours	75.49	38.2	49.1	49.0	32.1	28.8

Table 3: Grounded VideoQA results on NExT-GQA. Our method outperforms other methods on all metrics.

4.1 Experimental Setup

Our system employs Gemini 1.5 Flash for captioning, graph generation, and code generation, with GPT-4 serving as the reasoner. Accuracy is used as the primary evaluation metric across all the multiple-choice VideoQA datasets.

NExT-QA(Xiao et al., 2021b): This dataset contains 4996 multiple choice questions, corresponding to 570 videos. The average length of the video clips is 43 seconds. The questions are categorized into three types: Causal (Cau), Temporal (Tem), and Descriptive (Des).

IntentQA(Li et al., 2023b): This dataset specifically focuses on inference-based QA types, including Causal and Temporal questions. It includes two subtypes under Causal—Causal Why (CW) and Causal How (CH), and two under Temporal—Temporal Previous (TP) and Temporal Next (TN). The dataset contains 2,134 questions corresponding to 567 videos.

NExT-GQA(Xiao et al., 2024): Built upon the existing videos of NExT-QA. It not only tests the model’s raw accuracy, but also requires the model to ground its answer in the video by providing the evidence in the form of time stamps. The correctness of grounding are measured in intersection over union (IoU) and intersection over prediction (IoP). Only correctly grounded answers (i.e. $\text{IoP} \geq 0.5$) are credited when calculating the GQA accuracy.

STAR(Wu et al., 2024): This dataset focuses on the ability to perform logical reasoning in the form of multiple-choice question-answering on real-world videos. It offers two evaluation splits: an evaluation set of 7,098 video-question pairs with publicly available answers, and a test set of 7,377 video-question pairs with hidden answers. We report our results on the evaluation set following the work of papers such as TraveLER (Shang et al., 2024) and SeViLA (Yu et al., 2023). NExT-QA, IntentQA, and STAR are particularly suited for evaluation of our approach as they are event-centric and require strong causal and temporal reasoning.

Baselines. We evaluate our approach against three categories of baselines: *End-to-End*, *Bottom-Up*, and *Top-Down/Modular*. *End-to-End* models, such

as large vision-language models like Gemini, are typically not interpretable and may be pre-trained on VideoQA datasets. Similarly, *Bottom-Up* approaches such as VideoTree (Wang et al., 2024c) also lack interpretability. As such, these models are not directly comparable to our method. Our primary comparisons are with *Top-Down/Modular* methods, which emphasize interpretability. The most direct comparison for our work is against prior modular approaches like MoReVQA (Min et al., 2024), which provide transparent reasoning processes similar to ours.

4.2 Experiments Results

Table 2 summarizes our results. We make the following observations.

Our approach achieves outperforms top-down approaches on NExT-QA. Compared to the best modular approach, MoReVQA (Min et al., 2024), we achieve a 16.6% improvement on causal questions and a 6.7% improvement on temporal questions and achieve comparable accuracy to the SOTA approach. For descriptive questions, we outperform all modular methods and achieve comparable accuracy to the best bottom-up approach, VideoTree (Wang et al., 2024c).

Our performance on IntentQA is very close to the existing state-of-the-art method. We achieve comparable performance against the best-performing Bottom-Up method. The accuracy of our method slightly lags behind VideoINSTA(Liao et al., 2024) by 1.3% and LVNet(Park et al., 2024) by 0.5%. However, our method offers interpretability, with a small compromise in accuracy. No modular approaches report benchmark scores on the IntentQA dataset, so a direct comparison against those methods was not possible.

We outperform all zero-shot and top-down approaches on STAR. Our method surpasses all top-down and zero-shot approaches on the STAR dataset, with more than 20% improvement over modular approaches like ViperGPT (Surís et al., 2023) and TraveLER (Shang et al., 2024). This considerable improvement highlights that our approach in handling complex, real-world event-based reasoning tasks require a deeper understanding of the event relations in video content. Additional ablation experiment on STAR is presented in Section A. **We achieve SOTA result on NExT-GQA.** As shown in table Table 3, our model outperforms current SOTA method by 7.2% on GQA accuracy. For video grounding metrics, we achieved 5% and

Model	Acc.	Model	System	NExT-QA	IntentQA
Llama 3	72.5	Llama 3	LLOVi (Zhang et al., 2024a)	46.6 ↓ 21.1	48.9 ↓ 18.2
Llama 3.1	72.6		VideoINSTA (Liao et al., 2024)	58.3 ↓ 14.0	53.0 ↓ 19.8
GPT4	75.1		Ours	72.5 ↓ 2.6	69.0 ↓ 2.5

(a) Reasoner (b) Comparison with other methods using open-source LLM reasoner. Gray values ablation on indicate performance difference from the GPT4 NExT-QA. reasoner.

Table 4: (a) Performance comparison of our methodology using different LLMs as the reasoner. (b) We compare our method with others using an open-source language model as the reasoner. Here, the performance difference from using a proprietary language model as the reasoner is shown in gray.

6% increase on mIoP and IoP@0.5 than SOTA score, and 9.8% and 11.4% increase on mIoU and IoU@0.5. This indicates that our method not only has transparent and interruptible reasoning process, but can also achieve grounded question-answering.

In sum, our method surpasses all prior modular approaches on the NExT-QA, IntentQA, and STAR datasets and achieves comparable or superior performance to bottom-up methods on event-centric datasets like NExT-QA and IntentQA. While bottom-up models perform better on tasks requiring detailed video understanding, our model offers a clear advantage in transparency in its decision-making process—something unachievable with non-interpretable models. We provide experiments on additional datasets in Section C.

4.3 Ablation

All of ENTER’s design components make an important contribution. Table 5 demonstrates the effectiveness of each of our model components on NExT-QA. Denser graph and Denser captions update mechanism boost performance from 63.8% to 66.3% and 67.2% respectively (row 2 and 3). Further, updating the graph iteratively until 4 loops pushes the performance to 71.5% (row 6). Finally, we see that adding multimodal edges to compensate for lost visual information further improves the performance to 75.1% (last row). We provide further quantitative and qualitative ablations on the hierarchical update mechanism in Section D. In addition, we constructed a simple baseline with the LLMs we used – Gemini and GPT-4o – to isolate the gains from ENTER’s event graph/code-based parsing. Gemini captioned the video while GPT-4o acted as the reasoner. The baseline’s performance – 70.5% – lagged significantly behind ENTER’s (75.1%), demonstrating our method’s contributions.

Reliable performance across both open-source

Den. Gph	Den. Cap.	Gph Type	# Iter	Acc.
✗	✗	Text	1	63.8
✓	✗	Text	1	66.3
✓	✓	Text	1	67.2
✓	✓	Text	2	70.8
✓	✓	Text	3	71.1
✓	✓	Text	4	71.5
✓	✓	Text	5	71.5
✓	✓	Video	4	75.0
✓	✓	MM (parent node)	4	74.3
✓	✓	MM (subgraph)	4	75.1

Table 5: Ablation of the denser graph generator, denser caption generator, multimodal graph generator, and iterative answer retrying mechanisms. Here MM denotes multimodal. Activating the denser graph (Den. Gph) and caption (Den. Cap.), with four #Iter of retrying, along with multimodal subgraph gives the best result.

and proprietary reasoners. To evaluate the robustness of our approach to reasoning models, in Table 4a we show ablations on using open-source to proprietary LLMs as the reasoner, . There is a 2.5% difference in performance between the Llama 3.1 (Dubey et al., 2024) and the GPT4. The low fluctuation shows our method remains robust across different sized LLMs.

ENTER stays consistent, while other models fluctuate across reasoner types. We further ablate against other approaches while keeping an open-source LLM (Llama 3) as the reasoner model across all systems to ensure a fair comparison. As shown in Table 4b, when using the same open-source reasoner, our method overwhelmingly outperforms LloVi (Zhang et al., 2024a) and VideoINSTA (Liao et al., 2024) by 25.9% and 14.2% in NExT-QA, and 20.1% and 16% in IntentQA respectively. Our model comfortably outperforms other models when open-source LLMs are considered. Interestingly, our performance difference between open-source Llama 3 and closed-source GPT4 is only around 2.6% and 2.5% in NExT-QA and IntentQA respectively. Comparing to LLOVi (Zhang et al., 2024a) and VideoINSTA (Liao et al., 2024), the score difference is more than 21% and 18% for NExT-QA, and 14% and 19% for IntentQA. Existing methods show huge degradation in performance when using open-source reasoners, while our method excels. This emphasizes our method is less dependent on the choice of reasoner.

Comparison to scene graphs. In a human sufficiency study, we found event graphs were sufficient to answer the question in 92% of cases, versus 21% for scene graphs. Details are in Appendix B.

Accuracy and Interpretability of Intermediate Steps We conducted a human study on 30 randomly




Figure 3: Qualitative examples of ENTER on NExT-QA showing interpretability while maintaining correctness.

selected videos from the NExT-QA validation set. Annotators were asked to evaluate (1) whether the reasoning steps correctly led to the final answer, and (2) whether the reasoning steps were interpretable. Results show that in 66.67% of cases, the reasoning steps aligned with the correct answer, and in 86.67% of cases, they were judged interpretable. Considering ENTER achieves 75.1% accuracy on NExT-QA, this implies that when ENTER answers correctly, its reasoning is valid in 88.89% of those cases. These findings suggest that our method not only produces accurate answers but also supports interpretable reasoning in most cases.

5 Qualitative Analysis

We present two qualitative examples in Figure 3. In the first example (left figure), the task is to count the total number of people in the video. The model iterates through event nodes, identifying human-related arguments, which are then counted by the final LLM reasoner using the `simple_query` function. The second example (right figure) involves a more complex scenario. The question asks about the dog’s action before being petted, which is missed by the captioner. The graph generator linked the man sitting on the chair as the event before petting. As this information dealt with the action of the man rather than the dog, it was insufficient. Consequently, `generate_multimodal_edges` retrieved the relevant clips. The dog’s action, "Chasing its tail," occurring simultaneously with "Sitting," was retrieved, providing the correct answer. The examples depict the reasoning employed by our approach, showing its interpretability. Additional

examples in Section E.

5.1 Error Analysis

The interpretability offered by our approach enables the diagnosis of different types of errors that our model makes and traces the source of the error. We categorized the errors into three types primarily.

Error Type: Insufficient Knowledge occurs when the model lacks the necessary knowledge to properly interpret the scene.

Error Type: Inconsistent Referencing occurs when the model references the same entity as two distinct ones due to inconsistent labeling. When the reasoning requires references to specific entities (i.e. counting, multiple actions of the same entity etc.), the information retrieval might be confused when inconsistent referencing happens.

Error Type: Missed Information occurs when the model misses key details needed.

Please refer to Section F for detailed analysis and qualitative examples.

6 Conclusion

This paper introduced **ENTER**, a novel interpretable VideoQA system that uses event graphs for contextually-aware and transparent video reasoning. ENTER transforms videos into event graphs allows it to bridge the gap between the interpretability of modular reasoning and the rich contextual awareness of bottom-up methods. Experiments show ENTER not only achieves state-of-the-art performance, but also offers a significantly more transparent and explainable reasoning process.

7 Limitations

ENTER demonstrates strong performance while maintaining interpretability, though its limitations should be noted, too. While ENTER is generalizable to non-event tasks, its design is specialized for event-related tasks and may be less suited to, e.g., visually intensive applications. Additionally, although the multi-pass graph update reduces the risk of omitting information, it can incur higher computational costs, especially with longer videos, and may be susceptible to prompt-based attacks. Future work can explore alternative video representations to enhance the capability of non-event-centric tasks while maintaining interpretability.

References

- Jacob Andreas, Marcus Rohrbach, Trevor Darrell, and Dan Klein. 2017. [Neural module networks](#). *Preprint*, arXiv:1511.02799.
- Kumar Ashutosh, Rohit Girdhar, Lorenzo Torresani, and Kristen Grauman. 2023. [Hiervl: Learning hierarchical video-language embeddings](#). *Preprint*, arXiv:2301.02311.
- Tom B. Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, Sandhini Agarwal, Ariel Herbert-Voss, Gretchen Krueger, Tom Henighan, Rewon Child, Aditya Ramesh, Daniel M. Ziegler, Jeffrey Wu, Clemens Winter, and 12 others. 2020. [Language models are few-shot learners](#). *Preprint*, arXiv:2005.14165.
- Qirui Chen, Shangzhe Di, and Weidi Xie. 2024. [Grounded multi-hop videoqa in long-form egocentric videos](#). *Preprint*, arXiv:2408.14469.
- Rohan Choudhury, Koichiro Niinuma, Kris M. Kitani, and László A. Jeni. 2023. [Zero-shot video question answering with procedural programs](#). *Preprint*, arXiv:2312.00937.
- Abhimanyu Dubey, Abhinav Jauhri, Abhinav Pandey, Abhishek Kadian, Ahmad Al-Dahle, Aiesha Letman, Akhil Mathur, Alan Schelten, Amy Yang, Angela Fan, Anirudh Goyal, Anthony Hartshorn, Aobo Yang, Archi Mitra, Archie Sravankumar, Artem Korenev, Arthur Hinsvark, Arun Rao, Aston Zhang, and 6 others. 2024. [The llama 3 herd of models](#). *Preprint*, arXiv:2407.21783.
- Yue Fan, Xiaojian Ma, Rujie Wu, Yuntao Du, Jiaqi Li, Zhi Gao, and Qing Li. 2024. [Videoagent: A memory-augmented multimodal agent for video understanding](#). *Preprint*, arXiv:2403.11481.
- Hao Fei, Shengqiong Wu, Wei Ji, Hanwang Zhang, Meishan Zhang, Mong-Li Lee, and Wynne Hsu. 2024.

- [Video-of-thought: Step-by-step video reasoning from perception to cognition](#). In *Forty-first International Conference on Machine Learning*.
- Tanmay Gupta and Aniruddha Kembhavi. 2022. [Visual programming: Compositional visual reasoning without training](#). *Preprint*, arXiv:2211.11559.
- Kai Han, Jianyuan Guo, Yehui Tang, Wei He, Enhua Wu, and Yunhe Wang. 2024. [Free video-llm: Prompt-guided visual perception for efficient training-free video llms](#). *Preprint*, arXiv:2410.10441.
- Md Mohaiminul Islam, Ngan Ho, Xitong Yang, Tushar Nagarajan, Lorenzo Torresani, and Gedas Bertasius. 2024. [Video recap: Recursive captioning of hour-long videos](#). *Preprint*, arXiv:2402.13250.
- Dohwan Ko, Ji Soo Lee, Wooyoung Kang, Byungseok Roh, and Hyunwoo J. Kim. 2023. [Large language models are temporal and causal reasoners for video question answering](#). *Preprint*, arXiv:2310.15747.
- Jiapeng Li, Ping Wei, Wenjuan Han, and Lifeng Fan. 2023a. [Intentqa: Context-aware video intent reasoning](#). In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pages 11963–11974.
- Jiapeng Li, Ping Wei, Wenjuan Han, and Lifeng Fan. 2023b. [Intentqa: Context-aware video intent reasoning](#). In *Proceedings of the IEEE/CVF International Conference on Computer Vision (ICCV)*, pages 11963–11974.
- KunChang Li, Yinan He, Yi Wang, Yizhuo Li, Wenhai Wang, Ping Luo, Yali Wang, Limin Wang, and Yu Qiao. 2024a. [Videochat: Chat-centric video understanding](#). *Preprint*, arXiv:2305.06355.
- Kunchang Li, Yali Wang, Yinan He, Yizhuo Li, Yi Wang, Yi Liu, Zun Wang, Jilan Xu, Guo Chen, Ping Luo, Limin Wang, and Yu Qiao. 2024b. [Mvbench: A comprehensive multimodal video understanding benchmark](#). *Preprint*, arXiv:2311.17005.
- Jianxin Liang, Xiaojun Meng, Yueqian Wang, Chang Liu, Qun Liu, and Dongyan Zhao. 2024. [End-to-end video question answering with frame scoring mechanisms and adaptive sampling](#). *Preprint*, arXiv:2407.15047.
- Ruotong Liao, Max Erler, Huiyu Wang, Guangyao Zhai, Gengyuan Zhang, Yunpu Ma, and Volker Tresp. 2024. [VideoINSTA: Zero-shot long video understanding via informative spatial-temporal reasoning with LLMs](#). In *Findings of the Association for Computational Linguistics: EMNLP 2024*, pages 6577–6602, Miami, Florida, USA. Association for Computational Linguistics.
- Xudong Lin, Gedas Bertasius, Jue Wang, Shih-Fu Chang, Devi Parikh, and Lorenzo Torresani. 2021. [Vx2text: End-to-end learning of video-based text generation from multimodal inputs](#). In *Proceedings*

732	of the <i>IEEE/CVF Conference on Computer Vision and Pattern Recognition</i> , pages 7005–7015.	788
733		789
734	Xudong Lin, Manling Li, Richard Zemel, Heng Ji, and	790
735	Shih-Fu Chang. 2024. Training-free deep concept	791
736	injection enables language models for video question	792
737	answering. In <i>Proceedings of the 2024 Conference</i>	793
738	<i>on Empirical Methods in Natural Language Process-</i>	794
739	<i>ing</i> , pages 22399–22416.	
740	Xudong Lin, Simran Tiwari, Shiyuan Huang, Manling	795
741	Li, Mike Zheng Shou, Heng Ji, and Shih-Fu Chang.	796
742	2023. Towards fast adaptation of pretrained con-	797
743	trastive models for multi-channel video-language re-	798
744	trieval. In <i>Proceedings of the IEEE/CVF Conference</i>	
745	<i>on Computer Vision and Pattern Recognition</i> , pages	799
746	14846–14855.	800
747	Fei Liu, Jing Liu, Weining Wang, and Hanqing Lu.	801
748	2021. Hair: Hierarchical visual-semantic relational	802
749	reasoning for video question answering . In <i>2021</i>	803
750	<i>IEEE/CVF International Conference on Computer</i>	804
751	<i>Vision (ICCV)</i> , pages 1678–1687.	805
752	Muhammad Maaz, Hanoona Rasheed, Salman Khan,	806
753	and Fahad Shahbaz Khan. 2024. Video-chatgpt: To-	807
754	wards detailed video understanding via large vision	808
755	and language models . <i>Preprint</i> , arXiv:2306.05424.	809
756	Karttikeya Mangalam, Raiymbek Akshulakov, and Ji-	810
757	tendra Malik. 2023. Egoschema: A diagnostic bench-	811
758	mark for very long-form video language understand-	812
759	ing . <i>Preprint</i> , arXiv:2308.09126.	
760	Juhong Min, Shyamal Buch, Arsha Nagrani, Minsu	813
761	Cho, and Cordelia Schmid. 2024. Morevqa: Explor-	814
762	ing modular reasoning models for video question	815
763	answering . <i>arxiv</i> .	816
764	David Mogrovejo and Tamar Solorio. 2024. Question-	817
765	instructed visual descriptions for zero-shot video an-	
766	swering . In <i>Findings of the Association for Computa-</i>	818
767	<i>tional Linguistics: ACL 2024</i> , pages 9329–9339,	819
768	Bangkok, Thailand. Association for Computational	820
769	Linguistics.	821
770	OpenAI, Josh Achiam, Steven Adler, Sandhini Agarwal,	822
771	Lama Ahmad, Ilge Akkaya, Florencia Leoni Ale-	823
772	man, Diogo Almeida, Janko Altschmidt, Sam Alt-	824
773	man, Shyamal Anadkat, Red Avila, Igor Babuschkin,	825
774	Suchir Balaji, Valerie Balcom, Paul Baltescu, Haim-	
775	ing Bao, Mohammad Bavarian, Jeff Belgum, and	826
776	9 others. 2024. Gpt-4 technical report . <i>Preprint</i> ,	827
777	arXiv:2303.08774.	828
778	Junting Pan, Ziyi Lin, Yuying Ge, Xiatian Zhu, Renrui	829
779	Zhang, Yi Wang, Yu Qiao, and Hongsheng Li. 2023.	830
780	Retrieving-to-answer: Zero-shot video question	831
781	answering with frozen large language models . <i>Preprint</i> ,	832
782	arXiv:2306.11732.	
783	Jongwoo Park, Kanchana Ranasinghe, Kumara Ka-	833
784	hatapitiya, Wonjeong Ryoo, Donghyun Kim, and	834
785	Michael S. Ryoo. 2024. Too many frames, not	835
786	all useful:efficient strategies for long-form video qa .	836
787	<i>Preprint</i> , arXiv:2406.09396.	
	Hangyu Qin, Junbin Xiao, and Angela Yao. 2024.	837
	Question-answering dense video events . <i>Preprint</i> ,	838
	arXiv:2409.04388.	839
	Haran Raajesh, Naveen Reddy Desanur, Zeeshan Khan,	840
	and Makarand Tapaswi. 2024. Micap: A uni-	841
	fied model for identity-aware movie descriptions .	
	<i>Preprint</i> , arXiv:2405.11483.	
	Chuyi Shang, Amos You, Sanjay Subramanian, Trevor	
	Darrell, and Roei Herzig. 2024. Traveler: A modu-	
	lar multi-lmm agent framework for video question-	
	answering . <i>Preprint</i> , arXiv:2404.01476.	
	Xiaoqian Shen, Yunyang Xiong, Changsheng Zhao,	
	Lemeng Wu, Jun Chen, Chenchen Zhu, Zechun Liu,	
	Fanyi Xiao, Balakrishnan Varadarajan, Florian Bor-	
	des, Zhuang Liu, Hu Xu, Hyunwoo J. Kim, Bilge	
	Soran, Raghuraman Krishnamoorthi, Mohamed Elho-	
	seiny, and Vikas Chandra. 2024. Longvu: Spatiotem-	
	poral adaptive compression for long video-language	
	understanding . <i>Preprint</i> , arXiv:2410.17434.	
	Enxin Song, Wenhao Chai, Guanhong Wang, Yucheng	
	Zhang, Haoyang Zhou, Feiyang Wu, Haozhe Chi,	
	Xun Guo, Tian Ye, Yanting Zhang, Yan Lu, Jenq-	
	Neng Hwang, and Gaoang Wang. 2024. Moviechat:	
	From dense token to sparse memory for long video	
	understanding . <i>Preprint</i> , arXiv:2307.16449.	
	Sanjay Subramanian, Medhini Narasimhan, Kushal	
	Khangonkar, Kevin Yang, Arsha Nagrani, Cordelia	
	Schmid, Andy Zeng, Trevor Darrell, and Dan Klein.	
	2023. Modular visual question answering via code	
	generation . <i>Preprint</i> , arXiv:2306.05392.	
	Dídac Surís, Sachit Menon, and Carl Vondrick. 2023.	
	ViperGPT: Visual inference via python execution for	
	reasoning . <i>Proceedings of IEEE International Con-</i>	
	<i>ference on Computer Vision (ICCV)</i> .	
	Xiaohan Wang, Yuhui Zhang, Orr Zohar, and Serena	
	Yeung-Levy. 2024a. Videoagent: Long-form video	
	understanding with large language model as agent .	
	<i>Preprint</i> , arXiv:2403.10517.	
	Yi Wang, Kunchang Li, Yizhuo Li, Yinan He, Bingkun	
	Huang, Zhiyu Zhao, Hongjie Zhang, Jilan Xu, Yi Liu,	
	Zun Wang, Sen Xing, Guo Chen, Junting Pan, Ji-	
	ashuo Yu, Yali Wang, Limin Wang, and Yu Qiao.	
	2022. Internvideo: General video foundation models	
	via generative and discriminative learning . <i>Preprint</i> ,	
	arXiv:2212.03191.	
	Yueqian Wang, Yuxuan Wang, Kai Chen, and Dongyan	
	Zhao. 2024b. Stair: Spatial-temporal reasoning with	
	auditable intermediate results for video question an-	
	swering . <i>Preprint</i> , arXiv:2401.03901.	
	Ziyang Wang, Shoubin Yu, Elias Stengel-Eskin, Jae-	
	hong Yoon, Feng Cheng, Gedas Bertasius, and Mo-	
	hit Bansal. 2024c. Videotree: Adaptive tree-based	
	video representation for llm reasoning on long videos .	
	<i>Preprint</i> , arXiv:2405.19209.	

842	Bo Wu, Shoubin Yu, Zhenfang Chen, Joshua B Tenenbaum, and Chuang Gan. 2024. Star: A benchmark for situated reasoning in real-world videos . <i>Preprint</i> , arXiv:2405.09711.	896
843		897
844		
845		
846	Wenhao Wu. 2024. Freeva: Offline mllm as training-free video assistant . <i>Preprint</i> , arXiv:2405.07798.	
847		
848	Junbin Xiao, Xindi Shang, Angela Yao, and Tat-Seng Chua. 2021a. Next-qa:next phase of question-answering to explaining temporal actions . <i>Preprint</i> , arXiv:2105.08276.	898
849		899
850		900
851		901
852	Junbin Xiao, Xindi Shang, Angela Yao, and Tat-Seng Chua. 2021b. Next-qa:next phase of question-answering to explaining temporal actions . <i>Preprint</i> , arXiv:2105.08276.	
853		
854		
855		
856	Junbin Xiao, Angela Yao, Yicong Li, and Tat Seng Chua. 2024. Can i trust your answer? visually grounded video question answering . <i>Preprint</i> , arXiv:2309.01327.	
857		
858		
859		
860	Mingze Xu, Mingfei Gao, Zhe Gan, Hong-You Chen, Zhengfeng Lai, Haiming Gang, Kai Kang, and Afshin Dehghan. 2024. Slowfast-llava: A strong training-free baseline for video large language models . <i>Preprint</i> , arXiv:2407.15841.	
861		
862		
863		
864		
865	Jingkang Yang, Wenxuan Peng, Xiangtai Li, Zujin Guo, Liangyu Chen, Bo Li, Zheng Ma, Kaiyang Zhou, Wayne Zhang, Chen Change Loy, and Ziwei Liu. 2023a. Panoptic video scene graph generation . <i>Preprint</i> , arXiv:2311.17058.	
866		
867		
868		
869		
870	Zhengyuan Yang, Linjie Li, Jianfeng Wang, Kevin Lin, Ehsan Azarnasab, Faisal Ahmed, Zicheng Liu, Ce Liu, Michael Zeng, and Lijuan Wang. 2023b. Mm-react: Prompting chatgpt for multimodal reasoning and action . <i>Preprint</i> , arXiv:2303.11381.	
871		
872		
873		
874		
875	Haoxuan You, Rui Sun, Zhecan Wang, Long Chen, Gengyu Wang, Hammad A. Ayyubi, Kai-Wei Chang, and Shih-Fu Chang. 2023. Idealgpt: Iteratively decomposing vision and language reasoning via large language models . <i>Preprint</i> , arXiv:2305.14985.	
876		
877		
878		
879		
880	Shoubin Yu, Jaemin Cho, Prateek Yadav, and Mohit Bansal. 2023. Self-chained image-language model for video localization and question answering . <i>Preprint</i> , arXiv:2305.06988.	
881		
882		
883		
884	Zhou Yu, Dejing Xu, Jun Yu, Ting Yu, Zhou Zhao, Yuet-ing Zhuang, and Dacheng Tao. 2019. Activitynet-qa: A dataset for understanding complex web videos via question answering . <i>Preprint</i> , arXiv:1906.02467.	
885		
886		
887		
888	Ce Zhang, Taixi Lu, Md Mohaiminul Islam, Ziyang Wang, Shoubin Yu, Mohit Bansal, and Gedas Bertasius. 2024a. A simple llm framework for long-range video question-answering . <i>Preprint</i> , arXiv:2312.17235.	
889		
890		
891		
892		
893	Ce Zhang, Taixi Lu, Md Mohaiminul Islam, Ziyang Wang, Shoubin Yu, Mohit Bansal, and Gedas Bertasius. 2024b. A simple llm framework for	
894		
895		

We provide additional details in this section which further elucidate the claims and contributions of the paper. It’s divided into the following sections:

- Additional Baseline on STAR. (Appendix A)
- Comparison Against Scene Graphs (Appendix B)
- Ablation on EgoSchema (Appendix C)
- Ablation on Hierarchical Update Mechanism (Appendix D)
- More Qualitative Samples (Appendix E)
- More Error Analysis (Appendix F)
- Prompts (Appendix G)

A Additional Baseline on STAR

Given that our method, ENTER, uses Gemini and GPT-4o as intermediate components, we also tested another modular method, TravelER, by substituting its LLMs with Gemini and GPT-4o, for fair comparison. This *upgraded* TravelER baseline scores 65% overall accuracy on STAR as compared to ENTER’s 67.1%. This further demonstrates that gains from ENTER are not merely a result of using superior LLMs, but rather originate from a superior methodology.

B Comparison Against Scene Graphs

Graph Type	Sufficiency
Event Graph	92.0
Scene Graph	21.0

Table 6: Comparison between the sufficiency of event graphs to scene graphs. Event graphs’ high-level information allows them to be more expressive than scene graphs, thus more suitable for event-based tasks.

are captured in events and their entity arguments (*actor, object, item, place, etc*). In addition, event graphs contain explicit high-level temporal, hierarchical, and causal event-event relationships, making them far more expressive. To prove this hypothesis, we generated scene graphs for 38

The graphical nature of scene graphs draw natural comparisons against event-graphs. Scene graphs capture fine-grained object-level details – *subject, object, and predicates*. A closer look at event graphs shows that they are a super set of scene graphs. The *subject, object, and predicates* relationships

videos from the NExT-QA dataset and asked human annotators to judge whether the information contained in the given graph was sufficient to answer the associated question. Annotators reported that the scene graphs were sufficient in only 21% of the cases. In contrast, our event graph representations achieved a sufficiency rate of 92%, as shown in Table 6. This difference highlights the superior expressiveness of event graphs for complex reasoning tasks.

C Experiment on EgoSchema

We perform an additional experiment on EgoSchema (Mangalam et al., 2023) to demonstrate our model ENTER’s robustness across diverse scenarios. This dataset has long (180 seconds) egocentric videos with multiple-choice question-answering. It offers two evaluation splits: a hidden test set (Full set) of 5,000 videos evaluated via an external server, and a publicly available validation set (Subset) of 500 videos. We only consider the Full set in our evaluation. Although EgoSchema focuses on long video understanding rather than event analysis, we include it to show ENTER can be generalized to non-event-centric tasks.

Table 8 compares our method to other modular methods on EgoSchema. Our method surpasses all approaches on the EgoSchema dataset, with a 1.1% improvement over ProViQ (Choudhury et al., 2023) and TravelER (Shang et al., 2024). Although primarily designed for event-centric reasoning, our approach demonstrates stable performance on descriptive questions as well.

D Ablation on Hierarchical Update Mechanism

To evaluate the contribution of each component described in Section 3 to our method’s performance, we conducted a detailed analysis of the percentage of data points activating each functionality and their corresponding accuracy. Table 7 presents an ablation study of the three hierarchical update mechanisms, detailing how frequently each component from Section 3 is activated. The "Base" component refers to cases where the generated code operates without triggering additional modules like the "Denser Graph." Our results indicate that 63.6% of data points achieve high accuracy without requiring additional visits to the video, demonstrating the baseline capability of our method to address a




Figure 4: Qualitative examples of ENTER on NExT-QA, demonstrating interpretable reasoning alongside correct predictions.

substantial portion of the dataset effectively. However, when critical information is overlooked during the initial video pass or cannot be adequately represented by unimodal graphs (as revealed in the qualitative error analysis), our method effectively identifies these scenarios and leverages the "Denser Graph," "Denser Caption," or "Multimodal Graph" functionalities. It is important to note that the subset activating "Multimodal Graph" overlaps with those activating "Denser Graph" and "Denser Caption," so the percentages do not sum to 100.

We also ran a qualitative experiment to judge the helpfulness of iterative graph update mechanism. We sample 30 graphs and ask human annotators to rate whether the information supplied in the update contains critical information to answer the question. The study reveals that when hierarchical update is called, 66.67% time the update is helpful. Given that the answer accuracy of the samples where hierarchical update is called is 71% (Table 7), being helpful 66.67% time aligns well with the performance. These results prove and highlight the effectiveness of our hierarchical update mechanism

E Qualitative Analysis

We further present two more positive examples in Figure 4 to demonstrate how the multimodal feature from our model and event graph can provide interpretability

The first example (left figure) addresses a question about what caused a girl in a pink dress to move backward. Initially, the captioner and

Activated Component	Percent	Subset Accuracy
Base	63.6	78.6
Denser Graph	15.3	71.9
Denser Caption	4.8	81.9
Multimodal Graph	20.9	62.5

Table 7: Subset sizes of samples in NextQA that activate different hierarchical update mechanisms. The majority of the answers are sufficiently answerable by the base method without activating any additional mechanisms.

Method	EgoSchema Fullset
ProViQ (Choudhury et al., 2023)	53.3
MoReVQA (Min et al., 2024)	51.7
TravelER (Shang et al., 2024)	53.3
ViperGPT (Surís et al., 2023)	-
Ours	54.4

Table 8: Our method EgoSchema compared with other zero-shot methods and modular methods.

the model was able to construct an event graph and retrieved the event correctly, as shown in the light-orange highlighting. However, while the system identified the "Moving_0" event, it missed the crucial causal information explaining why the girl moved backward, as indicated by the green-highlighted code. To address this gap, the model employed the `generate_multimodal_edges` function to analyze relevant clips and construct multimodal edges connected to the "Moving_0" event. This analysis revealed the missing causal action: "the girl dodging the ball," which led to the correct answer "dodge the ball."

The second example (right figure) demonstrates




Figure 5: The figure demonstrates an example of case where *generate_denser_caption* and *generate_denser_graph* helps take care of failure case where text event graph is incomplete. The question asks about an event that occurred *after* lady in yellow turned to the man. However, the initial graph didn't contain any after event. As such, *generate_denser_caption* and *generate_denser_graph* are called to include this missing information to finally arrive at the correct answer.

a different scenario. The question references why the ladies were watching the guy in black; however, neither the event graph nor the generated code contains causal edges or code for retrieving the causal relationship for the event "Watch", making it insufficient to determine the answer. To resolve this, the model invokes the *generate_multimodal_edges* function to analyze relevant video clips for additional context. Through this analysis, it successfully identified the missing causal relationships and confirmed the final answer. These examples demonstrate ENTER's ability to incorporate visual information explicitly to recover from failure cases where information in the text-only event graph proves insufficient.

Figure 5 illustrates how *generate_denser_caption* and *generate_denser_graph*

work to mitigate incomplete graph failure cases. The question in the figure asks about an event that occurred *after* 'speaking' event. However, the initial event graph didn't contain any event with after edge from 'speaking' event. This triggered the *generate_denser_caption* and *generate_denser_graph* functions to try to incorporate this missing information. In this example, these two function successfully combined to include the missing information in the graph – the fact that the lady started walking after 'speaking'. This led to the successful prediction of the correct answer.

F Error Analysis

To demonstrate our model's interpretability capabilities, we analyze examples of incorrect predictions to trace the source of different types of errors,

including **Insufficient Knowledge, Missed Information** and **Inconsistent Referencing**.

- **Insufficient Knowledge Leads to Incorrect Predictions Despite Correct Reasoning Steps** The insufficient knowledge error types occurs when the input lacks crucial information needed for accurate scene interpretation.

Figure 9 top example highlights an error caused by the limited knowledge of the captioner. The question, “*How do the two men play the instrument?*” should be answered with “*Roll the handle.*” However, the captioner misidentifies the instrument as “*look like a guitar.*”. The code fails to detect missing information in this case since it successfully retrieves the child node, even though with misinformation, resulting in the incorrect inference “*strum the strings.*” The error shows how the captioner’s misunderstanding of the instrument misleads the model’s reasoning.

Figure 6 illustrates two examples where the model attempts to identify video locations but fails due to insufficient knowledge. In the top example, although the model successfully generates the correct code to search for location information by traversing nodes in the event graph, it still fails to produce the correct answer due to missing critical information in the graph itself. While the ground truth location is “*hallway*”, this information is absent from the captioner’s output, resulting in an event graph that lacks any node containing the “*hallway*” information. Instead, the event graph erroneously includes “*church*” as a location node. Thus, despite the model’s successful retrieval of location-related nodes and correct code execution, it cannot arrive at the correct answer due to this fundamental gap in the input knowledge. Similarly, in the second example, the model retrieves location-related nodes including “*outdoors*”, “*backyard*” and “*ground*”. However, none of these nodes correspond to the ground truth location. This again demonstrates how insufficient knowledge provided to the model can lead to prediction errors, even when the model’s code functions properly.

- **Missed Information Leads to Incorrect Event Reasoning**

Figure 7 presents two examples where the event graph captures basic events but fails to establish crucial causal relationships, leading to incorrect answers. In the top example, a child plays with

toys and turns back at the end of the video to get a cube. While the sequence of events is captured in the graph with a temporal edge from “*Turn Around*” to “*Look back*” and a causal edge from “*Look back*” to “*Get*”, the event graph misses causal edges connecting the event “*Turn Around*” to events related to the ground truth answer “*Get*”. This missing causal relationship makes the model unable to infer the why the baby turned around, resulting in an incorrect prediction. Similarly, in the bottom example, a lion on the left raises its front legs in response to the lion on the right starting to fight. While these basic events are captured in the graph, the model cannot establish causal edges from the event “*Raise*” to the event “*Fight*”, as the event graph lacks information linking to the true cause, making the model unable to infer the actual reason why the lion raised her front legs.

- **Inconsistent Referencing of Entities Result in Incorrect Answers**

Figure 9 shows the model missing the event “*Trying to film*” which explains why the man is near the fighting field. Instead, the model guesses the wrong answer, “*Wants to join the fight*” due to this oversight. The missed event leads the model to an incorrect inference about the man’s intention.

Figure 8 shows two examples where errors occur due to inconsistent entity referencing in the event graph. In the top example, the same baby is incorrectly referenced with two different labels: “*Baby*” and “*Baby girl*”. This inconsistency leads to the code double counting the number of babies in the video, resulting in an incorrect answer of two instead of one. Similarly, in the bottom example, the event graph generation shows the same referencing error. The video depicts a woman giving a haircut to a boy while another woman holds a camera, but the same child is referenced twice with different labels: “*boy*” and “*Young boy*”. Both examples illustrate how inconsistent entity referencing leads to counting errors in the final analysis.




Figure 6: ENTER’s interpretability analysis demonstrates two examples of insufficient knowledge errors (where information is not enough). The top example fails because the captioner failed to generate an event graph with the necessary location detail "hallway" needed for the ground truth answer. Similarly, the bottom example fails because the event graph has no node containing information corresponding to the ground truth answer "park."




Figure 7: ENTER’s interpretability analysis demonstrates two examples of missed information errors (where required information is missing). The top example fails because while the sequence of events "Turn Around" to "Look back" and "Look back" to "Get" are captured, the event graph misses the crucial causal edge from "Turn Around" to events related to "Get", making the model unable to infer why the baby turned around. The bottom example shows a similar case where, although the basic events are captured, the event graph lacks the causal edge connecting "Raise" to "Fight", preventing the model from understanding why the lion raised its front legs, leading to incorrect results.




Figure 8: ENTER’s interpretability analysis demonstrates two examples of inconsistent referencing errors (where the model misreferences objects or entities as the same or different). The top example shows the model incorrectly referencing the same baby from different frames as different objects, resulting in an incorrect result. Similarly, the bottom example shows incorrect referencing of the same group of people across different frames as a different group, leading to inaccurate counting of the number of people.




Figure 9: ENTER’s interpretability allows the diagnosis and classification of errors into three major types: insufficient knowledge, inconsistent referencing, and missed information. Here, we depict insufficient knowledge and missing information error type.

G Prompts

Captioner Prompt

You will be given a video. You need to describe the events in the video. Start your description with the first event happening in the video, describe all the events in chronological, causal, or hierarchical order, and end your description with the last event in the video. In your description, indicate temporal relations of events using keywords such as "after" "then" "meanwhile" etc.; indicate causal relations of events using key words such as "causing" etc.; indicate hierarchical relations of events using keywords such as "by" "with" etc.

When referring to entities, always use descriptive keywords representing their characteristics, such as "white Honda Civic", "man in black suit", "chair on the left", etc. Make sure the references to the entities are consistent, for example, if you mentioned a "black car with broken window", refer to it with the same name ("black car with broken window") everywhere else you mention it. For entities mentioned in the question, reference them using the same name everywhere else, for example, if the question mentions "man in black pants", use "man in black pants" to reference that entity.

Your description will be used to answer the following question: {question}? Choices: A. {a0} B. {a1} C. {a2} D. {a3} E. {a4}. When describing the video, do not answer the question, only describe the video in detail.

Example description: Two boxers, one in gold-white shorts, and the other one in orange-white shorts, facing each other in a boxing ring; meanwhile, the referee is observing the fight inside the ring; at the same time, a large number of audiences are watching. During the fight, the boxer in gold-white shorts throws a left jab, knocking down the opponent in orange-white shorts. After that, the referee counts to ten while the boxer in gold-white shorts raises his hand in victory; at the same time, the crowd cheers and applauds after the knockout. The referee announced the victory the boxer in gold-white victorious after he counted to ten; after that the boxer in gold-white shorts goes to a big screen and celebrates. Meanwhile, the referee and the boxer's cornermen check the well-being of the boxer in orange-white shorts.

Graph Generator prompt - Part 1

Given a paragraph, please extract all events and its argument roles in the following format:

```
<event_1>: {<argument_role_type_1>: [argument_role_1_1, argument_role_1_2, ...], <argument_role_type_2>: [argument_role_2_1, argument_role_2_2, ... ], ...},
<event_2>: {<argument_role_type_1>: [argument_role_1_1, argument_role_1_2, ...], <argument_role_type_2>: [argument_role_2_1, argument_role_2_2, ...], ...},
...
```

Coreference of argument roles with different names should follow the name of the first occurrence of the argument. For example, "blue car driving left" and "blue car turning left" both should be named "driving".

Coreference of events with different names should follow the name of the first occurrence of the argument. For example, "blue car" and "blue vehicle" both should be named "blue car".

Collective arguments that are should maintain its finest grained form in the text. For example, if "three cars" containing "red car", "blue car", and "green car", then reference the three cars as ["red car", "blue car", "green car"] in the graph.

Differentiate events with the same name with indices. For example: "man in blue shirt is eating pasta" and "woman is eating broccoli and rice" should be {"eating_0": {"agent": "man in white"}, "item": ["pasta"]}, {"eating_1": {"agent": "woman"}, "item": ["rice", "broccoli"]}}, this should also be reflected in the event graph.

In addition, extract all possible event-event relationships. The relationships should be from among causal, temporal and hierarchical relationships and the relationship should be directed.

The format should be:

```
<event_1>: {causal: [<event_4>, <event_5>], temporal: [<event_2>], hierarchical: [<event_7>, <event_8>}},
<event_2>: {causal: [<event_1>}},
<event_3>: {},
....}
```

Causal Definition: An event A is causally related to event B if A was the cause of event B. For example: Black car hits the man in white. The man in white falls. Event relation: {"Hit": {"causal": ["Fall"]}}.

Temporal Definition: An event A is temporally related to event B if A started before B did.

Graph Generator prompt - Part 2

Hierarchical Definition: An event A is hierarchically related to event B if B occurred spatiotemporally within A. Example: The man in white is fighting the person in monster costume. The man in white throws a punch. Event relation: {"Fight": {"hierarchical": ["Throw"]}}. Example: The waiter is serving the food by passing a tray. Event relation: {"Serve": {"hierarchical": ["Pass"]}}. Example: The soldier is holding his gun while patrolling. Event relation: {"Patrol": {"hierarchical": ["Hold"]}}.

In addition, you will also be given a question related to the text. You should focus on the events related to the question when generating the graph.

Example Text:

People are marching on a street during a protest. Police fired tear gas to disperse the crowd.

Example Question: Why did the police fired the tear gas?

Example Response:

Events:

```
{
  "Protest": {"agent": ["people"], "place": "street", "description": "People are protesting on the street."},
  "Marching": {"agent": ["people"], "place": "street", "description": "People are marching on the street."},
  "Fired": {"agent": ["police"], "item": "tear gas", "description": "Police fired tear gas."},
  "Disperse": {"item": "crowd", "description": "Crowd dispersed."}
}
```

Events-Events Relationships:

```
{
  "Protest": {"hierarchical": ["marching", "fired", "disperse"]},
  "Marching": {"temporal": ["Fired"]},
  "Fired": {"causal": ["disperse"], "temporal": ["disperse"]},
  "Disperse": {}
}
```

Example Question: Who came after the black car in the middle turned right?

Example Text:

Three cars are waiting at a traffic light. When it turned green, the red one went left, the black one on the right went right, and the middle black one went straight. After the black car turned right, a red tow truck drove through the road.

Example Response:

Events:

```
{
  "Waiting": {"agent": ["red car", "black car on the right", "middle black car"], "place": "traffic light", "description": "The red car, the black car on the right, and the black car in the middle are waiting for traffic light."},
  "Turned": {"agent": ["traffic light"], "color": "green", "description": "The traffic light turned green."},
  "Went_0": {"agent": ["red car"], "direction": "left", "description": "The red car turned left."},
  "Went_1": {"agent": ["black car on the right"], "direction": "right", "description": "The black car on the right turned right."},
  "Went_2": {"agent": ["middle black car"], "direction": "straight", "description": "The middle black car turned straight."},
  "Drive": {"agent": ["red tow truck"], "place": "road", "description": "The red tow truck drove through the road."}
}
```

Graph Generator prompt - Part 3

Events-Events Relationships:

```
{
  \"Waiting\": {\"temporal\": [\"Turned\"]},
  \"Turned\": {\"causal\": [\"Went_0\", \"Went_1\", \"Went_2\", \"Drive\"], \"temporal\": [\"Went_0\",
    \"Went_1\", \"Went_2\"]},
  \"Went_0\": {\"temporal\": [\"Drive\"]},
  \"Went_1\": {\"temporal\": [\"Drive\"]},
  \"Went_2\": {\"temporal\": [\"Drive\"]},
  \"Drive\": {}
}
```

Question: What made the crowd applaud?

Example Text:

Two boxers, one in gold-white shorts, and the other one in orange-white shorts, facing each other in a boxing ring. The boxer in gold-white shorts throws a left jab, knocking down the opponent in orange-white shorts. The referee counts to ten as the boxer in gold-white shorts raises his hand in victory. The crowd cheers and applauds. The boxer in gold-white shorts goes to a big screen and celebrates while the referee and the boxer's cornermen check the well-being of the boxer in orange-white shorts.

Example Response:

Events:

```
{
  \"Facing\": {\"agent\": [\"boxer in gold-white shorts\", \"boxer in orange-white shorts\"], \"direction\": [\"each other\"], \"location\": [\"ring\"], \"description\": \"Boxer in gold-white shorts and boxer in orange-white shorts are facing each other in the ring.\"},
  \"Throw\": {\"agent\": [\"boxer in gold-white shorts\"], \"action\": [\"left jab\"], \"description\": \"The boxer in gold-white shorts throws a left jab\"},
  \"Knock down\": {\"agent\": [\"boxer in gold-white shorts\"], \"target\": [\"boxer in orange-white shorts\"], \"description\": \"The boxer in gold-white shorts knocks down the boxer in orange-white shorts\"},
  \"Count to ten\": {\"agent\": [\"refree\"], \"description\": \"The refree counts to ten\"},
  \"Raise\": {\"agent\": [\"boxer in gold-white shorts\"], \"item\": [\"hands\"], \"description\": \"Boxer in gold-white shorts raises his hands in victory.\"},
  \"Applaud\": {\"agent\": [\"the crowd\"], \"description\": \"The crowd applauds.\"},
  \"Go\": {\"agent\": [\"boxer in gold-white shorts\"], \"destination\": [\"big screen\"], \"description\": \"Boxer in gold-white shorts goes to the big screen\"},
  \"Celebrate\": {\"agent\": [\"boxer in gold-white shorts\"], \"description\": \"Boxer in gold-white shorts celebrates.\"},
  \"Check\": {\"agent\": [\"referee\", \"boxer's cornermen\"], \"target\": [\"boxer in orange-white shorts\"], \"description\": \"the referee and the boxer's cornermen check the well-being of the boxer in orange-white shorts.\"}
}
```

Events-Events Relationships:

```
{
  \"Facing\": {\"temporal\": [\"Throw\"]},
  \"Throw\": {\"causal\": [\"Knock down\"]},

  \"Knock down\": {\"causal\": [\"Count to ten\", \"Raise\", \"Check\", \"Applaud\"], \"temporal\": [\"Count to ten\", \"Raise\", \"Applaud\"]},
  \"Count to ten\": {\"temporal\": [\"Go\", \"Check\"]},
  \"Raise\": {\"temporal\": [\"Go\", \"Check\"]},
  \"Applaud\": {\"temporal\": [\"Go\", \"Check\"]},
  \"Go\": {\"temporal\": [\"Celebrate\"]},
  \"Celebrate\": [],
  \"Check\": []
}
```

Given Text:

Code Generator Prompt - Part 1

Given the list of available python apis, please generate python code to answer the given question.

```
class Event:
    def __init__(self, name:str, args:dict):
        \"\"\"Initializes the event class with an event name and argument roles
        Parameters
        -----
        name: str
            name of the event
        args: dict
            event argument in this format: {arg_role: [arg_values]}
        \"\"\"

    def __str__(self,):
        return self.description

    def find_node(self, name, arguments):
        \"\"\"Returns an event node from the event graph given the event name and the associated
        arguments
        -----
        >>> # Find the event "riding" with agent "man in hat"
        >>> def execute_command(graph, caption, question, possible_answers, video_file_name):
        >>>     event_graph = EventGraph(graph, question, possible_answers)
        >>>     event_name = \"riding\"
        >>>     agent = \"man in hat\"
        >>>     event_node = event_graph.find_node(event_name, args={\"agent\": agent})
        \"\"\"

    def simple_query(self, query):
        \"\"\"Returns the answer to a basic question yes-or-no asked about arguments of the event,
        returns either True or False. The questions are about basic information about the event,
        and are not meant to be used for complex reasoning for the event, reasoning between
        among events, or external knowledge.
        Examples
        -----
        >>> # Find if the event "running" has a dog in it
        >>> def execute_command(graph, caption, question, possible_answers, video_file_name):
        >>>     event_graph = EventGraph(graph, question, possible_answers)
        >>>     event_name = \"running\"
        >>>     event_node = event_graph.find_node(event_name)
        >>>     has_dog = event_node.simple_query(\"Is there a dog in this event?.\") # Ask an simple
        yes-or-no question to determine if the event contains a dog
        >>>     if has_dog:
        >>>         return 'yes'
        >>>     else:
        >>>         return 'no'
        \"\"\"

class EventGraph:
    def __init__(self, event_graph, question, possible_answers):
        \"\"\"Initializes an event graph. Also creates an Event item for each event.
        Each event is stored internally as a string but interfaces with outside class with Event
        items.
        Parameters
        -----
        event_graph: Tuple[dict,dict]
            event_graph in the following format: ({ <event_1>: {<argument_role_type_1>:
            argument_role_1, <argument_role_type_2>: argument_role_2, ...},
            <event_2>: {<argument_role_type_1>: argument_role_1, <
            argument_role_type_2>: argument_role_2, ...},
            ...}, # Containing events and their arguments,
            {<event_1>: {causal: [<event_4>, <event_5>], temporal: [<event_2>], hierarchical: [<
            event_7>, <event_8>]},
            <event_2>: {causal:[<event_1>]},
            <event_3>:{},
            ...} # Containing relationships between events)
        \"\"\"
        self.event_graph, self.events = self.parse_events(event_graph)
        self.event_graph = event_graph
        self.events_dict = {}
        for event, args in events_json.items():
            self.events_dict[event] = Event(event, args)
```

Code Generator Prompt - Part 2

```
def iterate_nodes(self):
    \"\"\" Iterates through all nodes in the graph, to be used in a for loop
    >>> # How many people are there in this video?
    >>> def execute_command(graph, caption, question, possible_answers, video_file_name):
    >>>     event_graph = EventGraph(graph, question, possible_answers)
    >>>     all_people = set()
    >>>     for event in event_graph.iterate_nodes():
    >>>         for arg_name, arg_values in event.args.items():
    >>>             for arg_value in arg_values: # arg_values: List[str] contains all the
    >>>                 arguments under arg_name
    >>>                 is_person = event.simple_query(f\"Is {arg_value} a person?\") # Ask an
    >>>                 simple yes-or-no question to determine if the argument is a person or not
    >>>                 if is_person:
    >>>                     all_people.add(arg_value)
    >>>     info = {\"all the people in the video\": all_people}
    >>>     answer = select_answer(question, possible_answers, info, event_graph)
    >>>     return answer, info, event_graph\"\"\"
    return find_node(event_graph, node)

def find_node(self, event_name, args=None):
    \"\"\" Returns an event node from the event graph given the event name and the associated
    arguments
    >>> # Find the event \"knight riding horse\"
    >>> def execute_command(graph, caption, question, possible_answers, video_file_name):
    >>>     event_graph = EventGraph(graph, question, possible_answers)
    >>>     event_name = \"riding\"
    >>>     agent = \"knight\"
    >>>     item = \"horse\"
    >>>     event_node = event_graph.find_node(event_name, args={\"agent\": agent, \"item\":
    >>>         item})
    >>>     info = {\"event\": event_node}
    >>>     answer = select_answer(question, possible_answers, info, event_graph)
    >>>     return answer, info, event_graph\"\"\"
    return find_node(event_graph, node)

def get_children(self, node):
    \"\"\" Returns all the children nodes of the specified event node
    >>> # Find the child events of \"how are the protesters getting more attention\"
    >>> def execute_command(graph, caption, question, possible_answers, video_file_name):
    >>>     event_graph = EventGraph(graph, question, possible_answers)
    >>>     event_name = \"getting attention\"
    >>>     agent = \"protesters\"
    >>>     event_node = event_graph.find_node(event_name, args={\"agent\": agent})
    >>>     children = event_graph.get_children(event_node)
    >>>     info = {\"event\": event_node, \"events contained by the protesters getting
    >>>         attention\": children}
    >>>     answer = select_answer(question, possible_answers, info, event_graph)
    >>>     return answer, info, event_graph
    \"\"\"
    return get_children(event_graph, node)

def get_parent(self, node):
    \"\"\" Returns the parent node of the specified event node
    >>> # Find the parent events of \"why is the man cutting vegetables\"
    >>> def execute_command(graph, caption, question, possible_answers, video_file_name):
    >>>     event_graph = EventGraph(graph, question, possible_answers)
    >>>     event_name = \"Cut\"
    >>>     agent = \"man\"
    >>>     item = \"vegetables\"
    >>>     event_node = event_graph.find_node(event_name, args={\"agent\": agent, \"item\":
    >>>         item})
    >>>     parent = event_graph.get_parent(event_node)
    >>>     caused_by = event_graph.get_caused_by(event_node)
    >>>     info = {\"event\": event_node, \"events containing man cutting vegetables\": parent,
    >>>         \"events caused man cutting vegetables\": caused_by}
    >>>     answer = select_answer(question, possible_answers, info, event_graph)
    >>>     return answer, info, event_graph
    \"\"\"

    return get_parent(event_graph, node)
```

```

def get_temporal_after(self, node):
    """Returns all the events that happened after the specified event node
    >>> # Find the events happened after "man in blue driving black car"
    >>> def execute_command(graph, caption, question, possible_answers, video_file_name):
    >>>     event_graph = EventGraph(graph, question, possible_answers)
    >>>     event_name = "driving"
    >>>     agent = "man in blue"
    >>>     item = "black car"
    >>>     event_node = event_graph.find_node(event_name, args={"agent": agent, "item":
    item})
    >>>     after = event_graph.get_temporal_after(event_node)
    >>>     info = {"event": event_node, "events after man in blue driving black car": after
    }
    >>>     answer = select_answer(question, possible_answers, info, event_graph)
    >>>     return answer, info, event_graph
    """
    return temporal_after(node)

def get_temporal_before(self, node):
    """Returns all the events that happened before the specified event node

    >>> # Find the events happened before "the white horse with number 3 passed the finish line"
    >>> def execute_command(graph, caption, question, possible_answers, video_file_name):
    >>>     event_graph = EventGraph(graph, question, possible_answers)
    >>>     event_name = "pass"
    >>>     agent = "white horse with number 3"
    >>>     location = "finish line"
    >>>     event_node = event_graph.find_node(event_name, args={"agent": agent, "location":
    location})
    >>>     before = event_graph.get_temporal_before(event_node)
    >>>     info = {"event": event_node, "the white horse with number 3 passed the finish
    line": before}
    >>>     answer = select_answer(question, possible_answers, info, event_graph)
    >>>     return answer, info, event_graph
    """
    return temporal_before(node)

def get_resulted_in(self, node):
    """Returns the event that resulted in specified event node
    >>> # Find the events causing "the soldier camouflage fell to the ground"
    >>> def execute_command(graph, caption, question, possible_answers, video_file_name):
    >>>     event_graph = EventGraph(graph, question, possible_answers)
    >>>     event_name = "fall"
    >>>     agent = "soldier in camouflage"
    >>>     event_node = event_graph.find_node(event_name, args={"agent": agent})
    >>>     resulted_in = event_graph.get_resulted_in(event_node)
    >>>     before_event = event_graph.get_temporal_before(event_node)
    >>>     info = {"event": event_node, "The soldier camouflage fell to the ground because
    of these events": resulted_in, "These events happened before the soldier in camouflage
    fell to the ground": before_event}
    >>>     answer = select_answer(question, possible_answers, info, event_graph)
    >>>     return answer, info, event_graph
    """
    return caused_by(node)

def get_caused_by(self, node):
    """Returns all the events that happened due to the specified event node
    >>> # Find the events happened due to "the samurai in Japanese armor wielding his katana"
    >>> def execute_command(graph, caption, question, possible_answers, video_file_name):
    >>>     event_graph = EventGraph(graph, question, possible_answers)
    >>>     event_name = "wield"
    >>>     agent = "samurai in Japanese armor"
    >>>     item = "katana"
    >>>     event_node = event_graph.find_node(event_name, args={"agent": agent, "item":
    item})
    >>>     happened_after = event_graph.get_temporal_after(event_node)
    >>>     caused_by = event_graph.get_caused_by(event_node)
    >>>     info = {"event": event_node, "The samurai in Japanese armor wielding his sword
    caused these events to happen": caused_by, "These events happened after the samurai in
    Japanese armor wielding his sword": happened_after}
    >>>     answer = select_answer(question, possible_answers, info, event_graph)
    >>>     return answer, info, event_graph
    """
    return resulted_in(node)

```

Code Generator Prompt - Part 4

```
def select_answer(question, possible_answers, info, event_graph):
    \"\"\"Selects an Answer from the possible answers given the question and the info in a
    dictionary format.\"\"\"
    return select_answer(question, possible_answers, info, event_graph)

Question: How many cats are there in the video? A. one B. two C. three D. four E. five

def execute_command(graph, caption, question, possible_answers, video_file_name):
    event_graph = EventGraph(graph, question, possible_answers)
    events_mentioning_location = []

    all_cats = set()
    for event in event_graph.iterate_nodes():
        for arg_name, arg_values in event.args.items():
            for arg_value in arg_values: # arg_value: List[str] contains the arguments under
                arg_name
                is_cat = event.simple_query(f\"Is {arg_value} a cat?\")
                if is_cat:
                    all_cats.add(arg_value)
    info = {\"all the cats in the video\": all_cats}
    answer = select_answer(question, possible_answers, info, event_graph)
    return answer

Example Question: Where is the video taking place? A. Road B. House C. Dog D. Dining room E. street

def execute_command(graph, caption, question, possible_answers, video_file_name):
    event_graph = EventGraph(graph, question, possible_answers)
    events_mentioning_location = []
    for event in event_graph.iterate_nodes():
        query_result = event.simple_query(\"Does this event mention any location, or does it hint
        the location where the event is happening?\")
        if query_result:
            events_mentioning_location.append(event)
    info = {\"the events mentioning location\": events_mentioning_location}
    retry_answering = 3
    answer = select_answer(question, possible_answers, info, event_graph)
    return answer

Example Question: how is the man in blue feeling after standing up from the chair? A. Happy B. Sad C
. Angry D. Neutral E. Surprised

def execute_command(graph, caption, question, possible_answers, video_file_name):
    event_graph = EventGraph(graph, question, possible_answers)
    event_name = \"stand up\"
    agent = \"man in blue\"
    item = \"chair\"
    event_node = event_graph.find_node(event_name, args={\"agent\": agent, \"item\": item})

    after = event_graph.get_temporal_after(event_node)
    children = event_graph.get_children(event_node)
    caused_by = event_graph.get_caused_by(event_node)
```

```

retry_getting_events = 3
denser_graph_prompt = "\"\"\"Read the question and the paragraph, and find relations and/or
events in the paragraph that are related to the event the man in blue standing up. Use these
events to generate a new graph, such that the new graph has at least one of the following
for question answering: the event after \"stand up\", what happens after the man in blue
standing up, if you find these events, create these new events and draw the event relation
\"stand up\": {\"temporal\": [\"<event>\", ...]} for these events; the event contained by \"
stand up\", what is the man doing while he is standing up, if you find these events, create
these new events and draw the event relation \"stand up\": {\"hierarchical\": [\"<event>, ...]}
for these events; the event caused by \"stand up\", what happened due to the man standing
up, if you find these events, create these new events and draw the event relation \"stand up
\": {\"causal\": [\"<event>, ...]} for these events.\"\"\"
denser_caption_prompt = "\"\"\"Watch the video, describe what happens after the man in blue
standing up; is he doing while standing up; what event happened due to the man standing up;
and everything else that is helpful in answering the question.\"\"\"
if len(after)+len(children)+len(caused_by) == 0:
    graph = generate_denser_graph(event_node, graph, caption, question, possible_answers,
    denser_graph_prompt, 0)
    event_graph = EventGraph(graph, question, possible_answers)
    event_node = event_graph.find_node(event_name, args={\"agent\": agent, \"item\": item})
    after = event_graph.get_temporal_after(event_node)
    children = event_graph.get_children(event_node)
    caused_by = event_graph.get_caused_by(event_node)
for i in range(retry_getting_events):
    if len(after)+len(children)+len(caused_by) == 0:
        caption = generate_denser_caption(event_node, graph, caption, question, possible_answers
        , denser_caption_prompt, video_file_name, i)
        graph = generate_denser_graph(event_node, graph, caption, question, possible_answers,
        denser_graph_prompt, i+1)
        event_graph = EventGraph(graph, question, possible_answers)
        event_node = event_graph.find_node(event_name, args={\"agent\": agent, \"item\": item})
        after = event_graph.get_temporal_after(event_node)
        children = event_graph.get_children(event_node)
        caused_by = event_graph.get_caused_by(event_node)
    else:
        break
info = {\"event\": event_node,
    \"events after the man in blue standing up\": after,
    \"events containing the man in blue standing up\": children,
    \"events caused by the man in blue standing up\": caused_by
}
retry_answering = 3
for i in range(retry_answering):
    answer = select_answer(question, possible_answers, info, event_graph)
    if \"not sure\" in answer and i < retry_answering - 1:
        info = get_new_info(answer, info, graph, caption)
    else:
        break
return answer

```

Example Question: whom was the police firing the tear gas to? A. Robbers B. Terrorists C. Protesters
D. Attackers E. Prisoners

Code Generator Prompt - Part 6

```

Python Code:
def execute_command(graph, caption, question, possible_answers, video_file_name):
    event_graph = EventGraph(graph, question, possible_answers)
    event_name = \"fire\"
    agent = \"police\"
    item = \"tear gas\"
    event_node = event_graph.find_node(event_name, args={\"agent\": agent, \"item\": item})

    resulted_in = event_graph.get_resulted_in(event_node)
    parents = event_graph.get_parent(event_node)
    caused_by = event_graph.get_caused_by(event_node)

    retry_getting_events = 3
    denser_graph_prompt = \"\\\"\\\"Read the question and the paragraph, and find relations and/or
    events in the paragraph that are related to the event the police firing tear gas. Use these
    events to generate a new graph, such that the new graph has at least one of the following
    for answering the question: the event causing \"fire\", what events directly caused the
    police to fire tear gas, if you find these events, create these new events and draw the
    event relation <event>: {\"causal\": [\"fire\", ...]} for these events; the event contains \"
    fire\", what do they achieve by firing the tear gas, if you find these events, create these
    new events and draw the event relation <event>: {\"hierarchical\": [\"fire\", ...]} for these
    events; the event caused by \"fire\", what happened due to the firing of tear gas, if you
    find these events, create these new events and draw the event relation \"fire\": {\"causal
    \": [\"event\", ...]} for these events.\\\"\\\"\"
    denser_caption_prompt = \"\\\"\\\"Watch the video, describe what causes the police to fire the tear
    gas; what do they need to achieve to fire the tear gas; what event happened due to the
    police firing tear gas; and everything else that is helpful in answering the question.\\\"\\\"\"
    if len(caused_by)+len(parents)+len(resulted_in) == 0:
        graph = generate_denser_graph(event_node, graph, caption, question, possible_answers,
        denser_graph_prompt, 0)
        event_graph = EventGraph(graph, question, possible_answers)
        event_node = event_graph.find_node(event_name, args={\"agent\": agent, \"item\": item})
        resulted_in = event_graph.get_resulted_in(event_node)
        parents = event_graph.get_parent(event_node)
        caused_by = event_graph.get_caused_by(event_node)
    for i in range(retry_getting_events):
        if len(caused_by)+len(parents)+len(resulted_in) == 0:
            caption = generate_denser_caption(event_node, graph, caption, question, possible_answers
            , denser_caption_prompt, video_file_name, i)
            graph = generate_denser_graph(event_node, graph, caption, question, possible_answers,
            denser_graph_prompt, i+1)
            event_graph = EventGraph(graph, question, possible_answers)
            event_node = event_graph.find_node(event_name, args={\"agent\": agent, \"item\": item})
            resulted_in = event_graph.get_resulted_in(event_node)
            parents = event_graph.get_parent(event_node)
            caused_by = event_graph.get_caused_by(event_node)
        else:
            break

    info = {\"event\": event_node,
    \"events resulted in police firing tear gas\": resulted_in,
    \"events containing the police firing tear gas\": parents,
    \"events caused by police firing tear gas\": caused_by
    }

    retry_answering = 3
    for i in range(retry_answering):
        answer = select_answer(question, possible_answers, info, event_graph)
        if \"not sure\" in answer and i < retry_answering - 1:
            info = get_new_info(answer, info, graph, caption)
        else:
            break
    return answer, info, event_graph

```

Code Generator Prompt - Part 7

Example Question: how did the man in blue shirt cook the steak? A. Hold with hands B. Put on a grill
C. Fry in pan D. Boil in water E. Putting it in the oven

Python Code:

```
def execute_command(graph, caption, question, possible_answers, video_file_name):
    event_graph = EventGraph(graph, caption, video_file_name)
    event_name = \"cook\"
    agent = \"man in blue shirt\"
    item = \"steak\"
    # Get the event node related to the question
    event_node = event_graph.find_node(event_name, args={\"agent\": agent, \"item\": item})

    children = event_graph.get_children(event_node)
    before = event_graph.get_temporal_before(event_node)

    retry_getting_events = 3
    denser_graph_prompt = \"\\\"\\\"Read the question and paragraph, and find relations and/or events
    that are related to the man is cooking steak in the paragraph. Use these events to generate
    a new graph, such that the new graph has one of the following for question answering: the
    events contained by \"cook\", focus on what tools techniques and methods is he using, if you
    find these events, create new event nodes for them and add the event relation \"cook\":{\\\"
    hierarchical\\\":[<event>, ...]} for these events; the events before the man cooking the steak
    , focus on the possible preparation he did for the cooking, if you find these events, create
    new events for them and add the event relation <event>:{\\\"temporal\\\":[\\\"cook\\\", ...]}.
    \\\"\\\"\"
    denser_caption_prompt = \"\\\"\\\"Watch the video, describe: what happens before the man in blue
    shirt cooking the steak; what is the environment is it like; what is he doing while cooking
    the steak; what method, technique or tool he is using to cook the steak; and everything else
    that is helpful in answering the question.\\\"\\\"\"
    if len(children)+len(before) == 0:
        graph = generate_denser_graph(event_node, graph, caption, question, possible_answers,
        denser_graph_prompt, 0)
        event_graph = EventGraph(graph, question, possible_answers)
        event_node = event_graph.find_node(event_name, args={\"agent\": agent, \"item\": item})
        children = event_graph.get_children(event_node)
        before = event_graph.get_temporal_before(event_node)
    for i in range(retry_getting_events):
        if len(children)+len(before) == 0:
            caption = generate_denser_caption(event_node, graph, caption, question, possible_answers
            , denser_caption_prompt, video_file_name, i)
            graph = generate_denser_graph(event_node, graph, caption, question, possible_answers,
            denser_graph_prompt, i+1)
            event_graph = EventGraph(graph, question, possible_answers)
            event_node = event_graph.find_node(event_name, args={\"agent\": agent, \"item\": item})
            children = event_graph.get_children(event_node)
            before = event_graph.get_temporal_before(event_node)
        else:
            break

    info = {\"event\": event_node, \"events contained by the man cooking steak\": children, \"events
    before the man cooking steak\": before}

    retry_answering = 3
    for i in range(retry_answering):
        answer = select_answer(question, possible_answers, info, event_graph)
        if \"not sure\" in answer and i < retry_answering - 1:
            info = get_new_info(answer, info, graph, caption)
        else:
            break
    return answer, info, event_graph
```

Code Generator Prompt - Part 8

```
Example Question: how does the kid get the ball at the beginning? A. With his hand B. Kicks it C.
Run to fetch it D. Looks at the baby E. Happy
def execute_command(graph, caption, question, possible_answers, video_file_name):
    event_graph = EventGraph(graph, question, possible_answers)
    event_name = \"get\"
    agent = \"kid\"
    item = \"ball\"
    # Get the event node related to the question
    event_node = event_graph.find_node(event_name, args={\"agent\": agent, \"item\": item})

    children = event_graph.get_children(event_node)
    before = event_graph.get_temporal_before(event_node)

    retry_getting_events = 3
    denser_graph_prompt = \"\\\"\\\"Read the question and paragraph, and find relations and/or events
    that are related to the kid getting the ball in the paragraph. Use these events to generate
    a new graph, such that the new graph has one of the following for question answering: the
    events contained by \"get\", focus on what actions he is performing in order to get the ball
    , if you find these events, create new event nodes for them and add the event relation \"get
    \":{\\\"hierarchical\\\":[<event>, ...]} for these events; the events before the kid getting the
    ball, focus where is the ball located, what action the kid is doing before getting the ball
    , if you find these events, create new events for them and add the event relation <event
    >:{\\\"temporal\\\":[\\\"get\\\", ...]}. \\\"\\\"\\\"
    denser_caption_prompt = \"\\\"\\\"Watch the video, describe: what happens before the kid getting the
    the ball; where is the ball located; what is the kid doing while getting the ball; what
    action is the kid doing to get the ball; and everything else that is helpful in answering
    the question.\\\"\\\"\\\"
    if len(children) + len(before) == 0:
        graph = generate_denser_graph(event_node, graph, caption, question, possible_answers,
        denser_graph_prompt, 0)
        event_graph = EventGraph(graph, question, possible_answers)
        event_node = event_graph.find_node(event_name, args={\"agent\": agent})
        children = event_graph.get_children(event_node)
        before = event_graph.get_temporal_before(event_node)
    for i in range(retry_getting_events):
        if len(children) + len(before) == 0:
            caption = generate_denser_caption(event_node, graph, caption, question, possible_answers
            , denser_caption_prompt, video_file_name, i)
            graph = generate_denser_graph(event_node, graph, caption, question, possible_answers,
            denser_graph_prompt, i+1)
            event_graph = EventGraph(graph, question, possible_answers)
            event_node = event_graph.find_node(event_name, args={\"agent\": agent})
            children = event_graph.get_children(event_node)
            before = event_graph.get_temporal_before(event_node)
        else:
            break

    info = {\"event\": event_node,
    \"child events of the kid getting the ball\": children,
    \"before the kid getting the ball\": before}

    retry_answering = 3
    for i in range(retry_answering):
        answer = select_answer(question, possible_answers, info, event_graph)
        if \"not sure\" in answer and i < retry_answering - 1:
            info = get_new_info(answer, info, graph, caption)
        else:
            break
    return answer, info, event_graph

Example Question: what did the hen do after the chicks wandered off? A. Moves the food in her hand B
. Eat the corn C. Lay down on the straw D. Flip onto back E. look around
```

Code Generator Prompt - Part 9

Python Code:

```
def execute_command(graph, caption, question, possible_answers, video_file_name):
    event_graph = EventGraph(graph, question, possible_answers)
    event_name = \"wander\"
    agent = \"chicks\"
    # Get the event node related to the question
    event_node = event_graph.find_node(event_name, args={\"agent\": agent})

    after = event_graph.get_temporal_after(event_node)
    caused_by = event_graph.get_caused_by(event_node)

    retry_getting_events = 3
    denser_graph_prompt = \"\"\"Read the question and paragraph, and find relations and/or events
    that are related to the chicks wandered off that describe what did the hen do in the
    paragraph. Use these events to generate a new graph such that the new graph has one of the
    following for question answering: the events after \"wander\", focus on what was the
    behavior of the hen, or what did it interact with, if you find these events, create new
    event nodes for them and add the event relation \"wander\":{\"temporal\":[<event>, ...]} for
    these events; the events caused by \"wander\", focus on what caused the hen did due to the
    chicks wandered off, what was its reaction to the chicks, if you find these events, create
    new events for them and add the event relation \"wander\":{\"causal\":[<event>, ...]}.
    \"\"\"
    denser_caption_prompt = \"\"\"Watch the video, describe: what happened to the hen after the
    chicks wandered off; what was the hen's behavior after the chicks wandered off; the chicks
    wandered off caused the hen to do what; and everything else that is helpful in answering the
    question.\"\"\"
    if len(after)+len(caused_by) == 0:
        graph = generate_denser_graph(event_node, graph, caption, question, possible_answers,
            denser_graph_prompt, 0)
        event_graph = EventGraph(graph, question, possible_answers)
        event_node = event_graph.find_node(event_name, args={\"agent\": agent})
        after = event_graph.get_temporal_after(event_node)
        caused_by = event_graph.get_caused_by(event_node)
    for i in range(retry_getting_events):
        if len(after)+len(caused_by) == 0:
            caption = generate_denser_caption(event_node, graph, caption, question, possible_answers,
                denser_caption_prompt, video_file_name, i)
            graph = generate_denser_graph(event_node, graph, caption, question, possible_answers,
                denser_graph_prompt, i+1)
            event_graph = EventGraph(graph, question, possible_answers)
            event_node = event_graph.find_node(event_name, args={\"agent\": agent})
            after = event_graph.get_temporal_after(event_node)
            caused_by = event_graph.get_caused_by(event_node)
        else:
            break

    info = {\"event\": event_node, \"events after the chicks wandered off\": after, \"events caused
        by the chicks wandered off\": caused_by}

    retry_answering = 3
    for i in range(retry_answering):
        answer = select_answer(question, possible_answers, info, event_graph)
        if \"not sure\" in answer and i < retry_answering - 1:
            info = get_new_info(answer, info, graph, caption)
        else:
            break
    return answer, info, event_graph

For the provided question and graph below, please generate python code to solve it. When you are
looking for events by name, make sure to specify the exact name, include the indices if they
are present in the graph (i.e.Run_0, Eat_1). Only generate the execute_command method, do not
generate anything else.
```

1186

Denser Graph Prompt

```
input_text = f\"{graph_prompt}\\n Paragraph: {caption} \\n Graph: {original_graph} \\n You need to
generate a new graph based on the original graph that has additional events and/or
relations that addresses the following concern: {request}. The new graph will be used to
answer the following question Question: {question}? {choices} \\n Response: \\n Events: \\n\"
where graph prompt is the prompt for graph generator
```

1187

Denser Caption Prompt

You will be given a video and a request. The request is made to ask for specific details the provided description is missing. You need to generate a new description that addresses the requested details. \n In your description, indicate temporal, causal, or hierarchical relations of events clearly using keywords such as \"at the same time\", \"mean while\", \"after\", \"causing\", \"due to\", etc.\n When referring to entities, always use descriptive keywords representing their characteristics, such as \"white Honda Civic\", \"woman in purple dress\", \"man in black suit\", \"chair on the left and chair on the right\", etc. Make sure the references to the entities are consistent, for example, if you mentioned a \"black car with broken window\", refer to it with the same name (\"black car with broken window\") everywhere else you mention it. When making the description, do not answer the question.\n Now, generate a new text addressing the concerns stated in the request: {request}:

Event Simple Query Prompt

```
[
  {
    "role": "system",
    "content": "You will be given a description to an event and a simple question. Answer the question with \"yes\" or \"no\" based on the information provided. Do not generate anything else besides \"yes\" or \"no\"."
  },
  {
    "role": "user",
    "content": f"Event: {self.description}.\n Question: {query}. Answer the question with \"yes\" or \"no\" only.\n Your answer:\n"
  }
]
```

Reasoner Prompt

```
[{"role": "system",
  "content": "You will be given a set of information describing events in a video and a multiple choice question. You need to answer the question with the information from the paragraph. Chose one and only one of the answer from the five choices by returning the corresponding letter from A-E. You must choose one as your final answer, or make an educated guess. If the information provided is insufficient to answer the question, you must: First, guess an answer by choosing one of the choices from A, B, C, D, or E. Then, indicate you are not sure by saying \"I am not sure\". Finally, explain what additional information you need, and explain what details or events you will focus on to obtain the information if you are watching the video. Only say you are not sure when the events do not mention what is being asked."},
{"role": "user",
  "content": [
    {
      "type": "text",
      "text": user_input
    }
  ]
}]
```

Get Additional Info Prompt

You will be given a video, a question, and a textual request generated by a language model asking for additional information to answer the question. You should watch the video, read the question and the request, then generate a textual description of the video focusing on what is being asked in the request. You should not try to determine if it answered correctly, nor answer the question directly. You should generate information addressing what the request is asking for, additionally you can also generate information helpful for answering the question. \n Question: {question} \n Choices: {choices} \n Request: {concern}. \n Your response: '

Reasoning with multimodal graph prompt

You will be given a set of multimodal information as a multimodal graph, a question, and a set of choices. You need to answer the question with the multimodal graph by selecting from one of the choices, represented by one letter. Your answer must contain a single letter only without any additional text. \n Question: {question} Choices: {choices}