FINDINGDORY: A Benchmark to Evaluate Memory in Embodied Agents

Karmesh Yadav* Georgia Tech Yusuf Ali* Georgia Tech **Gunshi Gupta** University of Oxford

Yarin GalUniversity of Oxford

Zsolt KiraGeorgia Tech

Abstract

Large vision-language models have recently demonstrated impressive performance in planning and control tasks, driving interest in their application to real-world robotics. However, deploying these models for reasoning in embodied contexts is limited by their ability to incorporate long-term experience collected across multiple days and represented by vast collections of images. Current VLMs typically struggle to process more than a few hundred images concurrently, highlighting the need for more efficient mechanisms to handle long-term memory in embodied settings. To effectively evaluate these models for long-horizon control, a benchmark must specifically target scenarios where memory is crucial for success. Existing long-video QA benchmarks overlook embodied challenges like object manipulation and navigation, which demand low-level skills and fine-grained reasoning over past interactions. Moreover, effective memory integration in embodied agents involves both recalling relevant historical information and executing actions based on that information, making it essential to study these aspects together rather than in isolation. In this work, we introduce a new benchmark for long-range embodied tasks in the Habitat simulator. This scalable, procedurally-generated benchmark evaluates memory-based capabilities across 60 tasks requiring sustained engagement and contextual awareness in an environment. We also present baselines that integrate state-of-the-art VLMs with low level navigation policies, assessing their performance on these memory-intensive tasks and highlight areas for improvement. Our dataset and code can be found here.

1 Introduction

Memory is a core capability for intelligent agents, enabling them to recall past experiences, adapt to dynamic environments, and make informed decisions over extended timescales. In humans and animals, memory supports navigation, reasoning, and goal-directed behavior. As we develop more capable embodied systems, robust memory mechanisms become essential—especially in settings involving high-dimensional, multimodal inputs. Recent advances in Vision-Language Models (VLMs) have enhanced high-level reasoning for embodied tasks by leveraging large-scale multimodal training. However, most VLM applications focus on short-term or static tasks such as image captioning or VQA, which require minimal memory. Extending these models to long-horizon control introduces new challenges: unlike VQA, embodied agents must integrate fine-grained changes in observations over time and act based on past experiences. Efforts on long-context understanding—through long video or document comprehension (Song et al., 2023; Xiong et al., 2025; Ma et al., 2024) fall short in modeling long-term memory for physical decision-making. Many benchmarks rely on multiple-

39th Conference on Neural Information Processing Systems (NeurIPS 2025) Workshop: SPACE in Vision, Language, and Embodied AI (SpaVLE).

choice questions and are susceptible to guessing, or require heavy annotation efforts. In contrast, we propose embodied memory tasks that demand fine-grained recall and multi-hop reasoning.

Table 1: Example task categories in FINDINGDORY with their text prompts and memory requirements. Refer Table 3 for complete task suite. See Appendix G for specific task instances.

Task Category	Example Instructions	Memory Requirement
le Interaction Spatial	Navigate to any object that you did not interact with yesterday.	Differentiate b/w interacted & uninteracted objects.
Spatial Relationship	Navigate to the object which you interacted with which is the farthest from your current location.	Spatial relationships to objects.
Interaction Order Time-Based	Navigate to the object you interacted with immediately after {object_category}.	Sequence of objects interactions.
Time-Based	Navigate to the object that you interacted with at <i>{HH:MM}</i> yesterday.	Time of interaction & final position of objects.
ਦ Unordered ਉ Revisitation	Revisit all the receptacles you picked objects from yesterday.	Past object locations and best visitation order.
Ordered Revisitation	Revisit all the objects you interacted with yesterday in specific order.	Past object locations and their interaction order.

We introduce FINDINGDORY, a benchmark for evaluating long-horizon memory in photorealistic simulated environments. It includes **60 diverse tasks** categorized by memory requirements, demanding both spatial and temporal reasoning while discouraging heuristics or guessing. Tasks are designed such that success depends on memory, and involve dynamic scenes that evolve through agent interaction. FINDINGDORY is procedurally extensible, enabling it to scale with model capabilities. Unlike traditional QA datasets reliant on manual annotations, our benchmark uses simulation for automatic, quantifiable evaluation. Tasks such as navigation to a previously placed object require not only explicit memory retrieval but also effective spatio-temporal reasoning to select the entity that is closest to the agent. We propose metrics that assess not just recall, but also efficiency in task completion. Finally, we comprehensively evaluate high-level VLM policies equipped with low-level navigation, highlighting strengths and limitations in memory-demanding tasks.

2 FINDINGDORY

2.1 Benchmark Overview

The goal of FINDINGDORY is to evaluate an agent's ability to retain and utilize past experiences to efficiently complete future tasks. Unlike standard navigation or perception-based evaluations, our benchmark explicitly tests memory by structuring tasks around past interactions To achieve this, we design a two-phase setup consisting of an *experience collection phase*, where scripted oracle agents autonomously gather experiences in the environment, followed by an *interaction phase*, where they are evaluated on their ability to recall and act upon that history.

This decomposition allows for a controlled and standardized evaluation of memory, ensuring that the agent's ability to remember past interactions is isolated from its ability to explore effectively. The experience collection phase introduces dynamism into the environment by having the agent interact with and rearrange different objects. This ensures that the history contains meaningful state changes, allowing us to construct tasks that require spatio-temporal reasoning. Using oracle information from the simulator, the agent moves objects between designated receptacles. Episodes vary in length from 400 to 3500 frames, containing 2-11 object rearrangements. Further details in Appendix C.3.

Once the experience collection phase ends, the interaction phase begins. Here, a new task is sampled from a predefined set of templated instructions, requiring the agent to recall and act upon the state of the environment from the previous phase. The agent is given access to its full history, including recorded images, pose, and past actions. This setup explicitly tests its ability to integrate long-term memory into decision-making. In the next section, we outline the task instructions, with implementation details provided in Appendix C.1.

2.2 Tasks

Our benchmark is designed to evaluate a broad spectrum of memory challenges faced by embodied agents, beyond narrow tasks that could be solved with simple heuristics or non-generalizable strategies.




Figure 1: FINDINGDORY Task Performance

We construct tasks that require reasoning over the **temporal** sequence or durations of events, the **spatial** relationships between visited locations, the nature of **interactions** performed within the environment, and remembering miscellaneous **attributes** (e.g., color, shape, material) of different entities in the environment. We include tasks that refer indirectly to objects that were interacted with during experience collection. This enables the benchmark to distinguish baselines that can do flexible visual and semantic reasoning over memory, from methods that create static representations of scenes such as semantic maps (Chang et al., 2023) or textual memory (Kahatapitiya et al., 2024).

Single versus Multiple Goals: The majority of tasks in our benchmark involve single-goal navigation, where agents must reason over their experience to identify a destination and trace the shortest path to it. A smaller subset includes multi-goal tasks, requiring navigation to multiple destinations, sometimes in a specific order. Notably, single-goal tasks often demand reasoning over extended history, such as identifying unmanipulated objects by recalling all past interactions. Object interactions add further complexity by requiring agents to track movement across pre- and post-rearrangement states, requiring them to track object movement and ignore distractors (see Figure 4b) - in contrast to single-frame information retrieval.

Extensibility through Procedural Generation Our task set is procedurally extensible, allowing difficulty to be increased by modifying experience collection conditions. For instance, a greater number of object interactions expands the temporal reasoning space. Some tasks require recalling specific objects or receptacles, tracking "when" (temporal sequencing) and "how" (interaction type: picked vs. placed). Other tasks demand reasoning over global spatial context (e.g., rooms visited, farthest location), semantic attributes (e.g., material or functionality), and tracking temporal progression (e.g., the object that took the longest to rearrange).

3 Results

We present our experimental setup including the baselines and evaluation metrics in Appendix D. In this section, we empirically analyze the performance of the outlined baselines on FINDINGDORY, presenting results grouped according to the categories described in Section 2.2.

VLMs struggle on the FINDINGDORY benchmark. From Figure 1, we observe consistently low success rates on all task subsets across baselines, with GPT-40 achieving the highest performance at 27.3%, Gemini-2.0-Flash reaching 25.7%, while Qwen2.5-VL and Gemma-3 score in the 13–16% range. Notably, the supervised fine-tuned (SFT) variant outperforms all frozen VLMs, achieving an average improvement of 25% across tasks. Spatial relationship tasks have generally lower performance as they require VLMs to reason about distances between different entities relative to the agent. In contrast, tasks involving room identification yield high performance, likely due to the limited number of distinct rooms within environments and relatively simpler condition of navigating to any location within the goal room. Comparable performance between conditional interaction and object attribute tasks suggests that current VLMs can locate objects based on categories or attributes with similar accuracy. Temporal tasks highlight additional challenges, as models consistently struggle with accurately identifying the interaction order among entities, which requires multi-hop reasoning. Duration tracking poses similar challenges requiring models to infer time spent for each interaction.

Poor performance on multi-goal tasks. From Figure 1, we observe that performance of each VLM baseline that we consider is close to zero on most multi-goal tasks. This suggests that VLMs find it hard to track and remember multiple object-receptacle interactions. For the multi-goal evaluations, we use a single-shot prompt and require the high level VLM agent to predict all target frame indices in one single response - primarily to avoid multiple inferences with long sequence lengths. Qualitatively,

we observe that the VLMs generally fail to even predict the correct number of targets required to solve the multi-goal task. Our trained Qwen model performs slightly better, achieving close to 20% accuracy, but still significantly lags behind Oracle performance.




Figure 2: (a, b) Relaxed metrics for objects and receptacles tasks (respectively). (c) Success Rate vs SPL performance. (d) Hierarchical policy results on FINDINGDORY.

VLMs can identify target receptacles but not precisely locate them spatially. We conduct an experiment to analyze the performance difference between tasks involving objects and receptacle entities. From Figure 2b, we observe that both the relaxed SC-SR and DTG-SR metrics (see Appendix C.4 for details) are higher for receptacle-based tasks. This suggests that VLMs are able to identify frames from which large entities (receptacles) are easily viewed but cannot accurately identify frames which are spatially closest to the target entity. In contrast, object-focused tasks do not exhibit the same improvement (see Figure 2a), as only few frames clearly show the objects.

VLMs struggle with identifying the closest entity that solves the task. In Fig. 2c we report the HL-SPL metric (Appendix D.2) which captures the efficiency with which the high level VLM-based modules select goal frames nearest to the current robot position. We observe that for tasks involving multiple valid solution objects (consequently, multiple solution frames), there is a wide gap between HL-SR and HL-SPL (upto 50% in case of interaction-based tasks). This implies that although VLMs can correctly recognize valid entities, they fail to perform a fine-grained spatial analysis of the multiple valid entities being rearranged dynamically.

Policy decomposition causes performance degradation. To benchmark the hierarchical agent proposed in Appendix D.1, we employ Qwen2.5-VL-7B as high-level VLM with image-goal navigation policy and mapping policy as the low-level agents. The low-level policy activates only when the high-level VLM select correct subgoal. As depicted in Figure 2d, the (LL-SR) metric drops across all FINDINGDORY tasks for both low-level navigation policies. The mapping agent suffers only a 25% relative drop in LL-SR but the image-goal navigation suffers significantly. We attribute the drop in performance for the latter to a substantial difference between the VLM-selected image-goal frames (typically concentrated near receptacle surfaces) and the randomly sampled image-goals seen during policy training. Additionally, the LL-SPL of both baselines remains in single digits, highlighting the need for more efficient low-level navigation policies.

Frame Subsampling. We analyze how the number of input frames affects high-level performance by evaluating agents on subsampled interaction videos of varying lengths (Figure 3). The results suggest that frozen VLMs—despite being capable of accepting long contexts—do not improve with more frames. In fact, their performance often degrades at higher frame counts (minimal subsampling), indicating that they struggle to reason over larger




Figure 3: Model performance at different number of subsampled video frames.

number of frames. In contrast, the fine-tuned model (Qwen-SFT) demonstrates clear gains when trained with longer videos, leveraging additional context to improve reasoning. This indicates that with appropriate supervision, models can move beyond shallow matching and utilize richer temporal signals from the interaction history.

4 Conclusion

We introduced FINDINGDORY, a benchmark for evaluating long-horizon memory in embodied agents grounded in a photorealistic indoor simulator. Our findings reveal limitations in VLM context scaling, particularly in handling long observation sequences required for memory-intensive tasks. FINDINGDORY provides informative metrics that disentangle different aspects of memory and allows procedural task generation to support research on context scaling and memory efficiency in VLMs.

References

- Explore vision capabilities with the gemini api. https://ai.google.dev/gemini-api/docs/vision?lang=python.
- Constructions Aeronautiques, Adele Howe, Craig Knoblock, ISI Drew McDermott, Ashwin Ram, Manuela Veloso, Daniel Weld, David Wilkins Sri, Anthony Barrett, Dave Christianson, et al. Pddll the planning domain definition language. *Technical Report, Tech. Rep.*, 1998.
- Abrar Anwar, John Welsh, Joydeep Biswas, Soha Pouya, and Yan Chang. ReMEmbR: Building and Reasoning Over Long-Horizon Spatio-Temporal Memory for Robot Navigation. *arXiv e-prints*, art. arXiv:2409.13682, 2024.
- Abrar Anwar, John Welsh, Joydeep Biswas, Soha Pouya, and Yan Chang. Remembr: Building and reasoning over long-horizon spatio-temporal memory for robot navigation. In 8th Annual Conference on Robot Learning, 2024
- Shuai Bai, Keqin Chen, Xuejing Liu, Jialin Wang, Wenbin Ge, Sibo Song, Kai Dang, Peng Wang, Shijie Wang, Jun Tang, Humen Zhong, Yuanzhi Zhu, Mingkun Yang, Zhaohai Li, Jianqiang Wan, Pengfei Wang, Wei Ding, Zheren Fu, Yiheng Xu, Jiabo Ye, Xi Zhang, Tianbao Xie, Zesen Cheng, Hang Zhang, Zhibo Yang, Haiyang Xu, and Junyang Lin. Qwen2.5-vl technical report, 2025.
- Dhruv Batra, Aaron Gokaslan, Aniruddha Kembhavi, Oleksandr Maksymets, Roozbeh Mottaghi, Manolis Savva, Alexander Toshev, and Erik Wijmans. Objectnav revisited: On evaluation of embodied agents navigating to objects. arXiv preprint arXiv:2006.13171, 2020.
- Shyamal Buch, Cristóbal Eyzaguirre, Adrien Gaidon, Jiajun Wu, Li Fei-Fei, and Juan Carlos Niebles. Revisiting the "Video" in Video-Language Understanding. *arXiv e-prints*, art. arXiv:2206.01720, 2022.
- Matthew Chang, Theophile Gervet, Mukul Khanna, Sriram Yenamandra, Dhruv Shah, So Yeon Min, Kavit Shah, Chris Paxton, Saurabh Gupta, Dhruv Batra, Roozbeh Mottaghi, Jitendra Malik, and Devendra Singh Chaplot. GOAT: GO to Any Thing. arXiv e-prints, art. arXiv:2311.06430, 2023.
- Jasmine Collins, Shubham Goel, Achleshwar Luthra, Leon Xu, Kenan Deng, Xi Zhang, Tomas F Yago Vicente, Himanshu Arora, Thomas Dideriksen, Matthieu Guillaumin, et al. Abo: Dataset and benchmarks for real-world 3d object understanding. In CVPR, 2022.
- Laura Downs, Anthony Francis, Nate Koenig, Brandon Kinman, Ryan Hickman, Krista Reymann, Thomas B McHugh, and Vincent Vanhoucke. Google scanned objects: A high-quality dataset of 3d scanned household items. In *ICRA*, 2022.
- Chaoyou Fu, Yuhan Dai, Yondong Luo, Lei Li, Shuhuai Ren, Renrui Zhang, Zihan Wang, Chenyu Zhou, Yunhang Shen, Mengdan Zhang, et al. Video-mme: The first-ever comprehensive evaluation benchmark of multi-modal llms in video analysis. *arXiv* preprint arXiv:2405.21075, 2024.
- Aaron Hurst, Adam Lerer, Adam P Goucher, Adam Perelman, Aditya Ramesh, Aidan Clark, AJ Ostrow, Akila Welihinda, Alan Hayes, Alec Radford, et al. Gpt-4o system card. arXiv preprint arXiv:2410.21276, 2024.
- Kumara Kahatapitiya, Kanchana Ranasinghe, Jongwoo Park, and Michael S. Ryoo. Language Repository for Long Video Understanding. arXiv e-prints, art. arXiv:2403.14622, 2024.
- Charles C Kemp, Aaron Edsinger, Henry M Clever, and Blaine Matulevich. The design of stretch: A compact, lightweight mobile manipulator for indoor human environments. In 2022 International Conference on Robotics and Automation (ICRA), pages 3150–3157. IEEE, 2022.
- Mukul Khanna*, Yongsen Mao*, Hanxiao Jiang, Sanjay Haresh, Brennan Shacklett, Dhruv Batra, Alexander Clegg, Eric Undersander, Angel X. Chang, and Manolis Savva. Habitat Synthetic Scenes Dataset (HSSD-200): An Analysis of 3D Scene Scale and Realism Tradeoffs for ObjectGoal Navigation. arXiv preprint, 2023.
- Mukul Khanna*, Ram Ramrakhya*, Gunjan Chhablani, Sriram Yenamandra, Theophile Gervet, Matthew Chang, Zsolt Kira, Devendra Singh Chaplot, Dhruv Batra, and Roozbeh Mottaghi. Goat-bench: A benchmark for multi-modal lifelong navigation, 2024.
- Eric Kolve, Roozbeh Mottaghi, Winson Han, Eli VanderBilt, Luca Weihs, Alvaro Herrasti, Daniel Gordon, Yuke Zhu, Abhinav Gupta, and Ali Farhadi. Al2-THOR: an interactive 3d environment for visual Al. arXiv, 2017.
- Bohao Li, Rui Wang, Guangzhi Wang, Yuying Ge, Yixiao Ge, and Ying Shan. Seed-bench: Benchmarking multimodal llms with generative comprehension. *arXiv* preprint arXiv:2307.16125, 2023.

- Kunchang Li, Yali Wang, Yinan He, Yizhuo Li, Yi Wang, Yi Liu, Zun Wang, Jilan Xu, Guo Chen, Ping Luo, Limin Wang, and Yu Qiao. MVBench: A Comprehensive Multi-modal Video Understanding Benchmark. arXiv e-prints, art. arXiv:2311.17005, 2023.
- Xiaojian Ma, Silong Yong, Zilong Zheng, Qing Li, Yitao Liang, Song-Chun Zhu, and Siyuan Huang. Sqa3d: Situated question answering in 3d scenes. In *International Conference on Learning Representations*, 2023.
- Yubo Ma, Yuhang Zang, Liangyu Chen, Meiqi Chen, Yizhu Jiao, Xinze Li, Xinyuan Lu, Ziyu Liu, Yan Ma, Xiaoyi Dong, Pan Zhang, Liangming Pan, Yu-Gang Jiang, Jiaqi Wang, Yixin Cao, and Aixin Sun. Mmlongbench-doc: Benchmarking long-context document understanding with visualizations, 2024.
- Arjun Majumdar, Karmesh Yadav, Sergio Arnaud, Jason Ma, Claire Chen, Sneha Silwal, Aryan Jain, Vincent-Pierre Berges, Tingfan Wu, Jay Vakil, et al. Where are we in the search for an artificial visual cortex for embodied intelligence? Advances in Neural Information Processing Systems, 36:655–677, 2023.
- Arjun Majumdar, Anurag Ajay, Xiaohan Zhang, Pranav Putta, Sriram Yenamandra, Mikael Henaff, Sneha Silwal, Paul Mcvay, Oleksandr Maksymets, Sergio Arnaud, Karmesh Yadav, Qiyang Li, Ben Newman, Mohit Sharma, Vincent Berges, Shiqi Zhang, Pulkit Agrawal, Yonatan Bisk, Dhruv Batra, Mrinal Kalakrishnan, Franziska Meier, Chris Paxton, Sasha Sax, and Aravind Rajeswaran. Openeqa: Embodied question answering in the era of foundation models. In *Conference on Computer Vision and Pattern Recognition (CVPR)*, 2024.
- Karttikeya Mangalam, Raiymbek Akshulakov, and Jitendra Malik. EgoSchema: A Diagnostic Benchmark for Very Long-form Video Language Understanding. *arXiv e-prints*, art. arXiv:2308.09126, 2023.
- So Yeon Min, Xavi Puig, Devendra Singh Chaplot, Tsung-Yen Yang, Akshara Rai, Priyam Parashar, Ruslan Salakhutdinov, Yonatan Bisk, and Roozbeh Mottaghi. Situated Instruction Following. *arXiv e-prints*, art. arXiv:2407.12061, 2024.
- Tianwei Ni, Michel Ma, Benjamin Eysenbach, and Pierre-Luc Bacon. When do transformers shine in RL? decoupling memory from credit assignment. In *Thirty-seventh Conference on Neural Information Processing Systems*, 2023.
- Jurgis Pašukonis, Timothy P Lillicrap, and Danijar Hafner. Evaluating long-term memory in 3d mazes. In *The Eleventh International Conference on Learning Representations*, 2023.
- Marco Pleines, Matthias Pallasch, Frank Zimmer, and Mike Preuss. Memory gym: Partially observable challenges to memory-based agents. In *International Conference on Learning Representations*, 2023.
- Santhosh Kumar Ramakrishnan, Erik Wijmans, Philipp Kraehenbuehl, and Vladlen Koltun. Does spatial cognition emerge in frontier models? *arXiv preprint arXiv:2410.06468*, 2024.
- Ruchit Rawal, Khalid Saifullah, Ronen Basri, David Jacobs, Gowthami Somepalli, and Tom Goldstein. Cinepile: A long video question answering dataset and benchmark. *arXiv preprint arXiv:2405.08813*, 2024.
- Allen Z. Ren, Jaden Clark, Anushri Dixit, Masha Itkina, Anirudha Majumdar, and Dorsa Sadigh. Explore until confident: Efficient exploration for embodied question answering. In arXiv preprint arXiv:2403.15941, 2024.
- Vishnu Sashank Dorbala, Prasoon Goyal, Robinson Piramuthu, Michael Johnston, Reza Ghanadhan, and Dinesh Manocha. S-EQA: Tackling Situational Queries in Embodied Question Answering. *arXiv e-prints*, art. arXiv:2405.04732, 2024.
- Manolis Savva, Abhishek Kadian, Oleksandr Maksymets, Yili Zhao, Erik Wijmans, Bhavana Jain, Julian Straub, Jia Liu, Vladlen Koltun, Jitendra Malik, Devi Parikh, and Dhruv Batra. Habitat: A Platform for Embodied AI Research. ICCV, 2019.
- James A Sethian. A fast marching level set method for monotonically advancing fronts. *proceedings of the National Academy of Sciences*, 93(4):1591–1595, 1996.
- Dingjie Song, Shunian Chen, Guiming Hardy Chen, Fei Yu, Xiang Wan, and Benyou Wang. Milebench: Benchmarking mllms in long context. *arXiv preprint arXiv:2404.18532*, 2024.
- Enxin Song, Wenhao Chai, Guanhong Wang, Yucheng Zhang, Haoyang Zhou, Feiyang Wu, Xun Guo, Tian Ye, Yan Lu, Jenq-Neng Hwang, et al. Moviechat: From dense token to sparse memory for long video understanding. *arXiv* preprint arXiv:2307.16449, 2023.
- Andrew Szot, Alexander Clegg, Eric Undersander, Erik Wijmans, Yili Zhao, John Turner, Noah Maestre, Mustafa Mukadam, Devendra Singh Chaplot, Oleksandr Maksymets, et al. Habitat 2.0: Training home assistants to rearrange their habitat. In *NeurIPS*, 2021.

- Andrew Szot, Max Schwarzer, Harsh Agrawal, Bogdan Mazoure, Rin Metcalf, Walter Talbott, Natalie Mackraz, R Devon Hjelm, and Alexander T Toshev. Large language models as generalizable policies for embodied tasks. In *The Twelfth International Conference on Learning Representations*, 2024.
- Gemini Team, Petko Georgiev, Ving Ian Lei, Ryan Burnell, Libin Bai, Anmol Gulati, Garrett Tanzer, Damien Vincent, Zhufeng Pan, Shibo Wang, et al. Gemini 1.5: Unlocking multimodal understanding across millions of tokens of context. *arXiv preprint arXiv:2403.05530*, 2024.
- Gemma Team, Aishwarya Kamath, Johan Ferret, Shreya Pathak, Nino Vieillard, Ramona Merhej, Sarah Perrin, Tatiana Matejovicova, Alexandre Ramé, Morgane Rivière, et al. Gemma 3 technical report. arXiv preprint arXiv:2503.19786, 2025.
- Cunxiang Wang, Ruoxi Ning, Boqi Pan, Tonghui Wu, Qipeng Guo, Cheng Deng, Guangsheng Bao, Qian Wang, and Yue Zhang. Novelqa: A benchmark for long-range novel question answering, 2024.
- Saim Wani, Shivansh Patel, Unnat Jain, Angel Chang, and Manolis Savva. Multion: Benchmarking semantic map memory using multi-object navigation. *NeurIPS*, 2020.
- Quanting Xie, So Yeon Min, Tianyi Zhang, Kedi Xu, Aarav Bajaj, Ruslan Salakhutdinov, Matthew Johnson-Roberson, and Yonatan Bisk. Embodied-RAG: General Non-parametric Embodied Memory for Retrieval and Generation. *arXiv e-prints*, art. arXiv:2409.18313, 2024.
- Haomiao Xiong, Zongxin Yang, Jiazuo Yu, Yunzhi Zhuge, Lu Zhang, Jiawen Zhu, and Huchuan Lu. Streaming video understanding and multi-round interaction with memory-enhanced knowledge, 2025.
- Zhuo Xu, Hao-Tien Lewis Chiang, Zipeng Fu, Mithun George Jacob, Tingnan Zhang, Tsang-Wei Edward Lee, Wenhao Yu, Connor Schenck, David Rendleman, Dhruv Shah, Fei Xia, Jasmine Hsu, Jonathan Hoech, Pete Florence, Sean Kirmani, Sumeet Singh, Vikas Sindhwani, Carolina Parada, Chelsea Finn, Peng Xu, Sergey Levine, and Jie Tan. Mobility VLA: Multimodal instruction navigation with long-context VLMs and topological graphs. In 8th Annual Conference on Robot Learning, 2024.
- Karmesh Yadav, Arjun Majumdar, Ram Ramrakhya, Naoki Yokoyama, Alexei Baevski, Zsolt Kira, Oleksandr Maksymets, and Dhruv Batra. Ovrl-v2: A simple state-of-art baseline for imagenav and objectnav. https://arxiv.org/abs/2303.07798, 2023.
- Jihan Yang, Shusheng Yang, Anjali W Gupta, Rilyn Han, Li Fei-Fei, and Saining Xie. Thinking in space: How multimodal large language models see, remember, and recall spaces. arXiv preprint arXiv:2412.14171, 2024.
- Sriram Yenamandra, Arun Ramachandran, Karmesh Yadav, Austin Wang, Mukul Khanna, Theophile Gervet, Tsung-Yen Yang, Vidhi Jain, Alexander William Clegg, John Turner, et al. Homerobot: Open-vocabulary mobile manipulation. arXiv preprint arXiv:2306.11565, 2023.
- Ce Zhang, Taixi Lu, Md Mohaiminul Islam, Ziyang Wang, Shoubin Yu, Mohit Bansal, and Gedas Bertasius. A simple llm framework for long-range video question-answering, 2023.
- Peiyuan Zhang, Kaichen Zhang, Bo Li, Guangtao Zeng, Jingkang Yang, Yuanhan Zhang, Ziyue Wang, Haoran Tan, Chunyuan Li, and Ziwei Liu. Long context transfer from language to vision. *arXiv* preprint *arXiv*:2406.16852, 2024.
- Junjie Zhou, Yan Shu, Bo Zhao, Boya Wu, Shitao Xiao, Xi Yang, Yongping Xiong, Bo Zhang, Tiejun Huang, and Zheng Liu. Mlvu: A comprehensive benchmark for multi-task long video understanding. arXiv preprint arXiv:2406.04264, 2024.
- Hao Zhu, Raghav Kapoor, So Yeon Min, Winson Han, Jiatai Li, Kaiwen Geng, Graham Neubig, Yonatan Bisk, Aniruddha Kembhavi, and Luca Weihs. Excalibur: Encouraging and evaluating embodied exploration. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 14931–14942, 2023.

Supplementary Material

A Related Work

Table 2: Comparison of FINDINGDORY with popular memory-focused embodied AI benchmarks.

Benchmark	Photorealism	Semantic Reasoning	Task Specification	Template Categories	# Resulting Tasks	Memory Length (π^*)	Isolates Memory
MemoryMaze (Pašukonis et al., 2023)	Х	Х	One-hot	Х	1	500-1000 steps	×
MemoryGym (Pleines et al., 2023)	X	Х	One-hot	×	3	128-512 steps (Extensible)	×
MultiON (Wani et al., 2020)	/	X	One-hot	X	1	500 steps	×
SIF (Min et al., 2024)	/	✓	Language	3	240 (val/test)	✗ (Uses semantic map)	×
OpenEQA (Active) (Majumdar et al., 2024)	/	/	Language	×	1600	75 steps	×
GoatBench (Khanna* et al., 2024)	/	✓	Language + Image	X	1800 - 3600 (val)	500 steps (Static Env)	×
Excalibur (Zhu et al., 2023)	/	✓	Language	11	21	Requires exploration	×
Ours	/	✓	Language	11	$\approx 6000 (\text{val})$	500-3500 steps (Extensible)	

In this section, we review related work on long-video question answering and embodied AI benchmarks that incorporate historical experience in their problem formulation. We defer the discussion of different approaches for augmenting policies with memory-like mechanisms to Appendix A.3.

A.1 Video QA benchmarks

Recent analyses of video QA benchmarks (Mangalam et al., 2023; Buch et al., 2022) show that many tasks can be solved by attending to key frames, not full video sequences, suggesting that current benchmarks may favor keyframe selection over evaluating long-term memory. Long-context evaluations for foundation models also focus on "needle-in-a-haystack" tasks, evaluating retrieval of specific details rather than integrating information across many segments (Zhang et al., 2024). While recent video benchmarks feature more challenging questions (Mangalam et al., 2023; Li et al., 2023; Wang et al., 2024; Fu et al., 2024; Song et al., 2023, 2024; Li et al., 2023; Rawal et al., 2024; Yang et al., 2024; Zhou et al., 2024; Majumdar et al., 2024), they adopt multiple-choice QA formats which are not suitable for evaluating fine-grained decision-making over long histories. They may also allow models to succeed through guessing and are not extensible since they require substantial human annotation effort.

A.2 Embodied AI benchmarks

Various benchmarks have been proposed to evaluate multi-modal language models in embodied settings where agents must leverage their experience in environments to improve future decision-making (Wani et al., 2020). Many focus on embodied question answering (EQA), such as HM-EQA (Ren et al., 2024), which requires active exploration, and Open-EQA (Majumdar et al., 2024), which tests VLMs in a passive setting with pre-collected episode histories. Notably, Open-EQA found that a *blind* LLM baseline—one that ignores visual input—still performed well, suggesting that multiple-choice evaluation can introduce biases and reduce the need for genuine memory recall. Other benchmarks study the situated instruction following setting where agents must gather information to interpret ambiguous instructions (Sashank Dorbala et al., 2024; Ma et al., 2023; Min et al., 2024). However, many allow agents to sidestep memory challenges by precomputing relevant objects and locations based on recent history, effectively turning potentially memory-intensive tasks into structured instruction-following problems. Memory-Maze and Memory-Gym (Pašukonis et al., 2023; Pleines et al., 2023) focus on partially observable decision-making with history-based state modeling, but their simplistic visuals and small state spaces limit their relevance to complex real-world memory settings.

In Table 2, we compare our proposed benchmark to the most related benchmarks within embodied AI and RL research with respect to the following desired properties:

- 1. **Photorealism**: Measures the visual complexity of environments, affecting the meaningful evaluation of foundation models trained on real-world data.
- 2. **Scope of semantic reasoning needed over memory**: Distinguishes between benchmarks that require agents to recall diverse semantic information versus a narrow set of attributes such as object locations.
- 3. **Task Specification**: Evaluates whether tasks are defined using flexible language-based descriptions, enabling richer memory challenges.
- 4. **Memory horizon length**: Adapting the definition from Ni et al. (2023), this measures the temporal scope over which memory must be maintained for optimal task performance.

Unlike static benchmarks requiring localized frame recall, dynamic environments demand reasoning over events distributed across extended observation sequences. This metric becomes difficult to quantify when tasks require substantial exploration phases.

 Memory isolation: Whether benchmark performance isolates memory evaluation from confounding factors, particularly exploration requirements, which represent orthogonal challenges to memory recall and reasoning.

Our benchmark isolates memory evaluation by avoiding confounding related to exploration and focuses on careful and extensible task curation with automated metrics, requiring agents to recall and reason over long-horizon environmental observations.

A.3 An overview of approaches tackling memory in Long VQA and embodied tasks

Many recent works equip large language models with memory-like capabilities through task-specific knowledge bases or semantic maps for navigation planning (Min et al., 2024; Chang et al., 2023). MobilityVLA (Xu et al., 2024) leverages long-context VLMs to process past frames, enabling goal-frame selection via Gemini, while topological mapping guides navigation without explicit pathfinding. ReMEmbR (Anwar et al., 2024) and Embodied RAG (Xie et al., 2024) introduce nonparametric memory trees to store and retrieve past experiences for planning. For video question answering, Zhang et al. (2023); Kahatapitiya et al. (2024) propose a streaming-based approach that accumulates frame-wise captions for later querying. However, this method constrains memory to the expressivity of vision-language or captioning models, potentially omitting critical details. We include the hierarchical approach involving long-context VLMs and the approach utilizing textual memory traces as baselines in our evaluations on the benchmark tasks.

B Limitations

While FINDINGDORY provides a rigorous evaluation framework for long-horizon memory in embodied AI, it has certain limitations that highlight areas for future improvement.

First, our most competitive baseline, which integrates a VLM with a navigation policy, is constrained by its low-level controller. Current memory-guided navigation policies struggle to take the shortest paths in large environments after reasoning over long interaction histories. As a result, models perform poorly on spatial awareness metrics, making it difficult to assess their true memory capabilities beyond basic path efficiency. Future work should explore improved memory-driven navigation policies to better leverage long-term spatial reasoning.

Second, in the experience collection phase, our scripted oracle policy for object interactions (Magic Grasp) executes pick-and-place actions in an unnatural way—objects are abruptly transferred from the receptacle surface to the agent's gripper without smooth motion. This may confuse VLMs, as the sudden change is visually subtle and may be overlooked if the model does not attend to the specific frames where it occurs. Developing more naturalistic interaction models could improve the realism and interpretability of memory traces.

Third, while we introduce distractor objects to discourage guessing, we do not explicitly control how prominently these objects appear in the experience collection phase. Currently, objects the agent interacts with are often viewed more frequently and closely compared to distractors, which tend to be featured less prominently in the agent's field of view. Although some tasks mitigate this by explicitly referencing non-interacted objects, future iterations of the benchmark may need stronger distractions by ensuring more balanced exposure between distractors and interacted objects.

Finally, while the experience collection phase involves both navigation and manipulation, the current interaction phase tasks are all navigation-based, as memory reasoning is primarily required for locating objects rather than executing pick-and-place actions, which are Markovian once the goal is known. However, our benchmark is easily extensible to include manipulation-based memory tasks, which would further enrich the evaluation of long-term reasoning in embodied AI.

Despite these limitations, FINDINGDORY establishes a strong foundation for studying long-horizon memory, offering extensible challenges that will evolve alongside advances in vision-language models and embodied learning.

C Benchmark Details

C.1 Implementation details

Simulation Setup and Dataset Composition. We build FINDINGDORY using the Habitat simulator (Savva et al., 2019; Szot et al., 2021) and scenes from the Habitat Synthetic Scenes Dataset (HSSD)(Khanna* et al., 2023). Our benchmark uses 107 scenes from the training split and 30 from the validation split, resulting in 1,478 training and 100 validation episodes. We populate these scenes with the same object sets used in OVMM(Yenamandra et al., 2023), combining assets from AI2Thor (Kolve et al., 2017), Amazon-Berkeley Objects (Collins et al., 2022), Google Scanned Objects (Downs et al., 2022), and HSSD (Khanna* et al., 2023).

Across these episodes, we include 839/247 object instances spanning 84/72 distinct categories in the train/val splits, respectively. Objects are rearranged during the experience collection phase to induce temporally grounded memory challenges. Additionally, agents interact with 17/16 distinct receptacle categories in the train/val splits (e.g., tables, chairs, beds). To support attribute-based tasks (see Table 1), we generate semantic descriptions of object instances using GPT-40. We prompt the model with multi-view images of each object to extract attributes such as shape, color, material, and functionality. These descriptions are used to populate the object attribute task templates (5 total), which are limited to the validation set and undergo manual quality review.

In total, our benchmark includes 82, 174 training and 5,876 validation task instances. Details on the procedural generation pipeline for episodes and instructions are provided in Appendix C.2.

Agent Setup. We adopt the Hello Robot Stretch embodiment (Kemp et al., 2022) in our simulation. The agent is equipped with RGB and depth sensors (resolution 640×480) and a GPS+Compass sensor. The agent can execute one of four discrete navigation actions: MOVE_FORWARD (0.25m), TURN_LEFT / TURN_RIGHT (by 10°) and a STOP action. During the experience collection phase, the agent can also manipulate its arm joints (extension, lift, yaw, pitch, roll) and activate a manipulation_mode for pick-and-place actions, which rotates the base (90°) and directs the head camera toward the gripper.

PDDL-based Task Verification. Since we operate with a large and diverse set of instruction templates (see Table 1), we leverage the PDDL (Aeronautiques et al., 1998) specification system as instantiated in Szot et al. (2024). For each instruction template, we create a template goal condition that uses various predicate expressions such as <code>is_robot_at_object(x, "OBJECT"</code> or <code>is_robot_at_receptacle(x, "RECEPTACLE"</code> where x is some placeholder variable. These placeholder variables are sampled based on various constraints such as <code>target_color</code> or <code>interaction_order</code> that are defined through the template. Together, the placeholder constraints and goal conditions enable us to create scalable, automated verification routines for each task in FINDINGDORY.

C.2 FINDINGDORY Episode Creation

In this section, we give details about our episode creation pipeline that allows us to procedurally generate data for our benchmark.

Object-Receptacle Pairing. The first step in the episode creation involves generating valid spawning positions for various object-receptacle pairs by sampling entities from the respective split in consideration (train/val). The objective is to identify *candidate objects* that can be picked up from a *start receptacle* and placed stably on a *goal receptacle*. We use the pipeline proposed in Yenamandra et al. (2023) to procedurally generate various object placements on receptacle surfaces by running physics checks for stable placements. To make the generation procedure easier, we assume that each object is picked and placed only once during an episode. Additionally, we constrain the *start receptacle* category to be distinct from the *goal receptacle* category. We also ensure that for each *candidate object* category, a corresponding *non-interacted object* of the same category is spawned to serve as distractor entities during the interaction phase. Figures 4b and 4c provide a distribution of distractor objects and receptacles in the val episodes. The number of sampled object-receptacle pairings is equal to the number of rearrangements in the particular episode and can be configured through an argument. In essence, this controls the distribution of video frame lengths in the FINDINGDORY tasks(see Figure 4a).

Object Placement Sequences. Once we have identified the set of candidate objects and the corresponding goal receptacles, we require an oracle policy through which we can "naturally" drop objects on the receptacle surfaces. In practice, one can achieve this by training a "place" skill through end-to-end reinforcement learning or use a heuristic agent that can place objects on receptacles but both frameworks do not guarantee perfect 100% success which is crucial for solvability in FINDINGDORY tasks. To address this, we construct an offline pipeline that produces the set of low-level "oracle" joint actions that lead to stably placing the object on the goal receptacle. We spawn the agent (with the object snapped in its end-effector) at the associated viewpoints of goal receptacles on the navigation mesh. From each viewpoint, we try to execute a heuristic, state-machine based placing policy which performs a set of predefined joint effector actions after identifying a "clutter-free" region in the receptacle pointcloud (using an onboard depth sensor). The output of this routine produces a set of low level joint actions and the corresponding receptacle viewpoint for each goal receptacle that was identified in the previous object-receptacle pairing stage. We reject episodes where the heuristic-based place policy cannot stably place the object from any of the associated goal receptacle viewpoints.

Task Creation. Once we have the final filtered set of episodes, we populate task instructions for each episode using yaml-based instruction templates as used in Szot et al. (2024). We employ the instruction templates to *procedurally* populate various placeholders such as object names, attributes and appearance orders that create specific task instructions grounded in the entities (objects and receptacles) present in the episode in an automated manner. We present the diverse instructions templates we use for each task category in Table 3. In total, we create 82174/5876 unique task instructions within the train/val split respectively.




Figure 4: Summary statistics of episode data.

C.3 Experience Collection Phase

We now outline the details of the experience collection phase grounded in the episodes created by the pipeline outlined in the previous section. The experience collection phase is designed to collect a "clean" and "natural" video sequence of an agent interacting in an home environment while interacting with various entities. We focus on *object rearrangements* as the core interaction routine followed by the embodied agent. We construct an OracleAgent agent that uses privileged information from the simulator instance to efficiently generate such interaction routines. We now detail the OracleAgent policy to generate such video sequences for a particular episode.

Nav-to-Pick. The agent begins by being spawned at a random location in the scene associated with a particular episode. We then query a ShortestPath function that leverages privileged simulator information to navigate to the object that has to be picked up. The OracleAgent follows the shortest path to the object and collects images as it navigates in the environment.

Pick. Once the OracleAgent reaches the object location, it executes a hardcoded pick policy sequence which results in the object being magically grasped by the OracleAgent. The pick policy uses the onboard depth sensor to orient itself with the object instance placed on the receptacle infront of the agent. Once the object is in clear view (using the ground truth instance mask from the simulator), the and effector extends outwards to perform a magic_grasp action. In cases when the object is not visible, we re-query the ShortestPath function to navigate to an alternate viewpoint associated with the receptacle that would lead to the object being clearly visible.

Nav-to-Place. After grasping the object, the OracleAgent navigates to the corresponding *goal receptacle* that was sampled during the episode creation phase. Specifically, the agent navigates to the specific viewpoint associated with the *goal receptacle* from which the pre-recorded placement action sequence is to be executed.

Place. Once the agent reaches the specific viewpoint, we re-play the end-effector action sequence that was found to lead to a stable object placement during episode creation. This marks the end of a single rearrangement interaction routine and the agent transitions to rearrange the next *candidate object* in the episode until no more objects are left.

Final Navigation. At the end of all interaction routines within an episode, the agent navigates to a predefined location to ensure that it does not remain in close proximity to the final interacted object or the final *goal_receptacle*. This ensures that tasks are not solvable by selecting only the last few frames in the video sequence. We ensure that the agent navigates to a distance of 3 m away from the final interaction location.

The above OracleAgent routine enables us to procedurally create videos of the agent rearranging objects in the environment. Additionally, as the agent navigates the environment between the pick and place substeps, it collects additional frames detailing the scene environment which can be useful (or serve as distractor frames) when attempting to solve FINDINGDORY tasks. We present an example experience collection trajectory and associated "magic" pick-place sequence in Figures 11 and 12.

C.4 Evaluations

In this section, we define the primary evaluation metrics employed to benchmark the performance of various baselines on the FINDINGDORY tasks. Following Batra et al. (2020), we focus on metrics that systematically quantify both the success and efficiency of the agent in solving specified instructions. Success focuses on accurately selecting frames from the interaction video that lead to task completion, while efficiency evaluates if the agent selects and navigates to the optimal frame that solves the task using the fewest low-level control actions. Notably, optimizing efficiency poses a significant challenge for current methods (Ramakrishnan et al., 2024; Yang et al., 2024).

High-Level Policy Success Rate (HL-SR). This metric measures the percentage of episodes in which the high-level agent correctly predicts frame indices required to solve the specified task. We define an episode as successful if the frame(s) predicted by the VLM satisfy the following criteria:

- *Distance-to-Goal*: The agent is within a specified distance of the target entity upon reaching the predicted frame. We use thresholds of 2.0 m for objects and 0.1 m for receptacles. The larger threshold for objects accounts for the possibility of objects being positioned on elongated receptacles (e.g., couches), potentially affecting reachability.
- Angle-to-Goal: The agent is oriented within a specified angular distance toward the target entity's center. We set angle thresholds of 45° for objects and 90° for receptacles due to their typically larger dimensions.

- Semantic Coverage: The semantic mask of the target entity covers at least 0.1% of the pixels in the frame.
- Room Region Check: For room visitation tasks, we verify if the agent is located within the designated target region.

These thresholds and criteria were qualitatively validated through manual inspection to ensure their appropriateness; During evaluation, these criteria are verified by teleporting the robot to the pose associated with the frame(s) selected by the high-level agent.

Low-Level Policy Success Rate (LL-SR). This metric measures the percentage of episodes where the low-level navigation agent successfully navigates to the target entity. The low-level agent is activated only if the high-level agent correctly predicts the frame indices, meaning LL-SR is evaluated conditionally upon HL-SR being true for each episode. The success criteria match those outlined for HL-SR.

Success-weighted-by-Path-Length. This metric evaluates task completion efficiency, computed per task episode as follows (Batra et al., 2020):

$$SPL_i = S_i \cdot \frac{l_i}{\max(p_i, l_i)}$$

where S_i denotes HL-SR/LL-SR for computing the HL-SPL/LL-SPL respectively, l_i is the length of the shortest possible path to the closest successful goal frame (or shortest path to revisit all subgoals), and p_i is the actual path length traveled by the agent.

Additionally, we introduce two relaxed success metrics to analyze baseline failure modes:

- **Distance-to-Goal-Only Success Rate** (DTG-SR). Computed identically to HL-SR but without the semantic coverage requirement. This metric helps quantify instances where the agent selects frames close to the goal without necessarily capturing it visually.
- Semantic Coverage Success Rate (SC-SR). Computed identically to HL-SR but without the distance-to-goal requirement. This metric evaluates instances where the agent correctly selects frames showing the target entity but fails to meet proximity criteria.

D Experimental Setup

In this section, we describe the primary baselines evaluated on FINDINGDORY.

D.1 Evaluated Approaches

To establish strong baselines, we adopt a hierarchical architecture (Figure 10) comprising two modules:

- (1) a high-level goal selection module, which processes the interaction history to select goal frames, and
- (2) a low-level navigation policy, which executes actions to reach the selected frame.

This architecture enables reasoning over long-horizon multimodal experience while delegating fine-grained control to a learned policy. Inspired by prior work (Xu et al., 2024), we avoid directly predicting actions using VLMs due to their poor performance in continuous control, and instead restrict them to high-level goal prediction.

D.1.1 High-Level Goal Selection

Video LM Agent. This agent receives the full interaction video along with a task instruction. Each frame in the video is annotated with its index and the time of day at which it was captured. The agent is tasked with predicting the index of a frame from the video that corresponds to a viable goal state. Specifically, the predicted frame should represent a viewpoint from which, if the agent were to navigate back to the same camera position, it could successfully complete the task. Although

the model outputs a single frame index, selecting the correct one often requires reasoning over multiple temporally scattered observations, including frames where the agent may not be actively interacting. Since different VLMs are capable of handling different numbers of frames in context, we subsample the frames passed to each model based on what empirically performs best. We evaluate both proprietary (Gemini-2.0-Flash (Team et al., 2024), GPT-40) and open-source (Qwen2.5-VL (Bai et al., 2025), Gemma-3 (Team et al., 2025)) vision-language models capable of processing long video contexts. See Appendices E.1 to E.3 for more details.

Textual Memory Agent. Similar to Min et al. (2024); Anwar et al. (2024), we also consider an explicit, memory-building baseline which breaks down the video frames into chunks and uses a VLM to generate textual summaries for each video chunk. After "captioning" the entire video sequence, the VLM selects frame indices by reasoning over the generated textual descriptions. See Appendix E.4 for more details.

Supervised Fine-Tuning (SFT). We additionally explore a supervised fine-tuning approach where the high-level VLM is trained to predict goal frame indices, given the task prompt and interaction history. Since multiple frames may validly represent the goal (e.g., several consecutive frames showing an object being placed), we supervise the model on the full list of acceptable target frames. At test time, a single frame is sampled from the list of predictions and is considered correct if it matches any of these valid frames. This setup enables the model to learn task-specific cues from examples and serves as a stronger baseline than zero-shot prompting, particularly for tasks requiring subtle temporal grounding. We provide additional details in Appendix E.5.

D.1.2 Low-Level Navigation

To execute the high-level plan, we use a low-level policy that takes the selected goal frame and outputs discrete actions: MOVE-FORWARD, TURN-RIGHT, TURN-LEFT, and STOP. Our primary policy is the LSTM-based controller from OVRLv2 (Yadav et al., 2023), trained to reach image goals from egocentric RGB-D observations (see Appendix F.1).

We also evaluate a mapping-based policy that deterministically navigates to the location corresponding to the goal frame using a global map, without relying on learned visual features (Appendix F.2).

Solvability. Since the action space of our high-level baseline is constrained to frames observed during the experience collection phase, there are tasks for which this is insufficient. For example, in the task "Navigate to a room that you did not visit yesterday," all available waypoints correspond to previously visited locations, making it impossible to satisfy the instruction regardless of the selected frame. To establish an upper bound on task difficulty, we quantify the percentage of episodes that could theoretically be solved through optimal goal selection from interaction history, assuming perfect navigation (teleportation) to the selected waypoint. This upper bound is the dashed line (Oracle) in Figure 1.

D.2 Evaluation Metrics

We benchmark agent performance on the FINDINGDORY tasks using **Low Level Success Rate** (LL-SR), assessing whether the agent finds the right target entities, and **Low Level Success-weighted-by-Path-Length** (LL-SPL), evaluating if the agent selects and navigates to the optimal entity using the shortest possible path. Since we use a hierarchical baseline, we additionally introduce a **High-Level Policy Success Rate** (HL-SR), and **High-Level Policy SPL** (HL-SPL) which measures the accuracy and efficiency of the high-level policy in selecting the correct and closest goal frames for navigation. To further analyze failure modes, we also report two relaxed variants: **Distance-to-Goal-Only SR** (DTG-SR), which relaxes the requirement that the target object must be visible in the selected frame, and **Semantic Coverage SR** (SC-SR), which ignores spatial proximity. Additional metrics, success criteria, and threshold specifics are provided in Appendix C.4.

E Baseline Details

E.1 Gemini Agent

We experiment with the gemini-2.0-flash model which can process upto 1 million tokens in the context window. We strictly follow the outlined Google Gemini API developer guidelines (gem)

gemini-2.0-flash Task Prompt

You are an intelligent question answering agent. In the prompt video preceeding the text, you will be shown a long stream of images that have been collected by a robot while navigating around a home and asked to answer a question about the space to assist a user in completing tasks in this home. In the video stream, the robot is picking up objects and rearranging them to different arbitrary locations throughout the house.

The questions asked by user will require being able to look at the full set of images collected by robot to be able to provide the answer. Your task is to identify the exact point in the video (by timestamp) where the user should move to best accomplish their goal. You can do this by outputting the exact timestep in the video where you are most confident that the object or place that they should move to, was viewed closely.

The images in the video also have the time of day information in top left. You need to use the time of day information for tasks that require to revisit objects or receptacles at a specific time of day.

For some tasks that require revisiting multiple receptacles or objects, you should output multiple frame indices corresponding to the correct order of revisitation (only if specified). For all user goals, identify the minimum number of objects or receptacles (targets) that you need to revisit to complete the user's goal. For each revisitation, you should select one corresponding timestep in the video that you will move to. You need to ensure that you are not revisiting targets that are not relevant to the user's goal.

Generate timestamps in the MM:SS format where the first two digits represent minutes and the last two digits represent seconds. To solve the tasks effectively, you should try to summarize the video by listing out the objects that were picked and placed, the receptacles from which each object was picked up and the receptacle where it was dropped.

The user's goal is to: {goal}. Now look at the full video containing all the images. Give your final response with NUM_TARGETS_TO_REVISIT: ||<num_target>||. TIMESTAMP_INDEX: ||<timestamp_1>,...,<timestamp_num_target>||. You can include multiple timestamps if the task requires visiting more than one target (one timestamp for each target). Do not add any other text.

Figure 5: System Prompt for gemini-2.0-flash model

to structure the prompt and perform API calls over the long videos in the FINDINGDORY tasks. We do not use a "structured output" format such as json in the output responses as we empirically observed it failed to produce coherent outputs when supplied with long videos in the context. Since the gemini-2.0-flash model expects the input frames to be sampled at 1 FPS, we prompt the model to directly generate specific timestamps in the recommended MM:SS format to localize the frame corresponding to the target entity. We provide the detailed prompt that we use for evaluations in Fig. 5.

E.2 Qwen and Gemma Agent

We run the Qwen2.5-VL-7B (Bai et al., 2025) and Gemma3-12B (Team et al., 2025) locally for evaluations on the FINDINGDORY tasks. The Qwen model uses a maximum of 768 frames sampled uniformly across the input sequence while Gemma does not impose a maximum frame limit. For evaluation on 768 frames, we use two A40 GPUs with 48GB of memory. For experiments with shorter context lengths and higher subsampling (24–384 frames), a single A40 GPU suffices. We provide the full task prompt we use for inference with Qwen and Gemma in Fig. 6 and utilize structured JSON outputs.

E.3 GPT Agent

We use the official OpenAI GPT-4o (Hurst et al., 2024) API to run evaluations on the FINDINGDORY tasks with video frames subsampled at 96 frames to optimize API costs. For running complete evaluation on the entire validation task suite, we incurred a total cost of ≈ 400 USD. We provide the full system prompt used for GPT-4o evaluations in Fig. 7.

Qwen/Qwen2.5-VL-7B-Instruct and google/gemma-3-12b-it Task Prompt

You are an expert and intelligent question answering agent. You will be shown a video that was collected by a robot yesterday while navigating around a house and picking and placing objects. Your job is to help the robot complete a task today by looking at the video and finding the frame indices that the robot should move to. Make sure your response is all within the JSON.

Note:

- The robot uses a magic grasp action to pick up an object, where a gripper goes close to the object and the object gets magically picked up.

Output Format (should be in JSON format):

```
'''json
{
    "chain_of_thought": str.
    "frame_indices": list[int].
}
'''
```

Where:

- Chain of Thought: A detailed explanation of the robot's thought process in determining the frame indices.
- Frame Indices: The frame indices in the video stream showing the object or place that the robot should move to.
- When deciding which frame indices to choose, make sure you choose the frame indices that are closest to the object/place.
- If task requires the agent to go to multiple places, output one frame index per object/place. (Do not use ellipsis)

The robot's goal is: {goal}

Figure 6: System Prompt for Qwen2.5-VL and Gemma3 model

E.4 Text Agent

We implement the the text-based VLM agent using the Qwen2.5-VL (Bai et al., 2025) model. For every chunk_size number of frames in the video, we generate a description using the VLM. We then attach the frame indices and *time of day* information to the generated summary for the frame window in consideration. We use the prompt shown in Fig. 8 to generate the structured JSON outputs for each chunk in the video. We then concatenate all the generated JSON outputs and pass it to the Qwen model to perform text-only reasoning over the entire text-based history of the video. The text-based reasoning prompt is provided in Fig. 9. We note that using the same Qwen model for generating the individual text summaries and performing the final text-based reasoning helps in optimizing inference load as we maintain only a single instance of the VLM through the entire evaluation.

E.5 Supervised Finetuning Baseline

We leverage the FINDINGDORY training split which consists of 82174 unique task instantiations across the categories mentioned in Table 1. Each video-instruction pair is coupled with a list of ground-truth frame indices that solve the task. For multi-goal tasks, each subgoal has a corresponding ground-truth frame indices sublist. Since the FINDINGDORY video sequences can be extremely long, we uniformly subsample all videos to 96 frames. The ground truth frame indices are also subsampled to match the shorter video lengths to ensure the model chooses from within the subsampled frames.

Training Details. We conduct full-finetuning of the Qwen/Qwen2.5-VL-3B model using the open-source huggingface/trl library. For hyperparameter optimization, we utilized a smaller representative split of the training dataset with 36274 samples and conducted a grid search over the learning rate, num_epochs and weight_decay parameters. The best checkpoints from all runs were selected by evaluating performance on all video-instruction pairs in the full validation split. This "offline" evalua-

gpt-4o-2024-07-18 Task Prompt

** OBJECTIVE **

You are an expert and intelligent question answering agent. You will be shown a video that was collected by a robot yesterday while navigating around a house and picking and placing objects. Your job is to help the robot complete a task today by looking at the video and finding the frame indices that the robot should move to, to complete the task.

```
** OUTPUT FORMAT **

'''json
    "chain_of_thought": str.
    "frame_indices": list[int].
'''
```

Where:

- Chain of Thought: A detailed explanation of the robot's thought process in determining the frame indices.
- Frame Indices: The frame indices in the video stream showing the object or place that the robot should move to.
- When deciding which frame indices to choose, make sure you choose the frame indices that are closest to the object/place.
- If task requires the agent to go to multiple places, output one frame index per object/place.

```
** NOTES **
```

- The robot uses a magic grasp action to pick up an object, where a gripper goes close to the object and the object gets magically picked up.

```
** TASK **
The robot's goal is: {goal}
```

Figure 7: System Prompt for gpt-4o model

tion is conducted without instantiating the simulator by directly comparing the model's predicted keyframe indices with the ground-truth keyframe indices using exact string matching (thus, we dont compute metrics proposed in Appendix D.2). We use the cosine learning rate decay scheduler for all experiments. For the final training on the larger dataset, we found that a learning rate of 5×10^{-6} over 5 epochs with 0 weight decay worked best. For all experiments, we train in bfloat16 format using 8 A40 GPUs on a single node with a batch size of 1 and gradient_accumulation of 4 - providing an effective batch_size of 32 samples. To further optimize training, we use gradient_checkpointing and highly optimized flash_attention implementation. In this setup, the full training run takes ≈ 120 hrs to complete.

Goal Sampling for Online Simulator Eval. The best trained checkpoint is used in online simulator evaluations on the FINDINGDORY task suite. Since the model is trained to predict the complete list of ground-truth frame indices, we select a single representative index from each generated subgoal solution list to serve as the predicted frame index. Empirically, we found that choosing either the first or a random index (of a sublist corresponding to a subgoal) yields comparable performance, while using the last index results in slightly worse performance. Therefore, we use the first index of each list as a simple and effective heuristic.

F Low-level Policy Details

F.1 Image-Goal Navigation Agent

Policy Training. We train the image-goal navigation policy using the architecture and training recipe described in Yadav et al. (2023). Specifically, we employ an end-to-end reinforcement learning policy trained using DDPPO, which predicts discrete navigation actions conditioned on visual RGB inputs and a goal image. The agent utilizes a ViT based visual encoder along with a 2-layer LSTM backbone. Similar to OVRL-v2 (Yadav et al., 2023), the output patch representations from the ViT

Text Agent(VLM) Task Prompt

You are an expert and intelligent question answering agent. You will be shown a stream of {chunk_size} images taken by a robot while navigating around a simulated house and picking and placing objects. Your job is to describe the image based on the output format. Make sure your response is all within the JSON format.

Output Format (should be in JSON format):

```
""ijson
{
    "room_name": str.
    "picking_placing_or_navigating": str("picking", "placing" or "navigating").
    "object_being_manipulated": str.
    "receptacle_being_manipulated": str.
    "other_objects_in_scene": list[str].
}
```

Where:

- Room name: The name of the room the robot is in.
- Picking, placing, or navigating: Whether the robot is picking or placing an object, or navigating around the house.
- Object being manipulated: The object that the robot is picking or placing (if relevant).
- Receptacle being manipulated: The receptacle that the robot is picking up from or placing an object into (if relevant).
- Other objects in scene: Objects present in the scene besides the main object and the receptacle.

Note

- The robot uses a magic grasp action to pick up an object, where a gripper goes close to the object and the object gets magically picked up.

Figure 8: System Prompt for Qwen2.5-VL model to generate text summaries based on chunk_size frames

are reshaped into a 3D grid and downsampled to a lower dimension using a convolutional layer called the compression layer. However, we slightly deviate from OVRL-v2 by first concatenating the patch representations from the current and goal images before passing them through the compression layer.

The policy training occurs in the training scene split of the HSSD dataset (Khanna* et al., 2023), consisting of 1166 episodes distributed across 111 scenes (a subset of the original 125 training scenes). In the Habitat simulator, the agent is modeled as a Hello Robot Stretch (Kemp et al., 2022) with a height of 1.41 m and a cylindrical base radius of 0.25 m. The agent's RGB sensor is positioned at a height of 1.31 m, with a resolution of 160×120 pixels and a horizontal field of view of 43° . During training, each episode has a maximum step budget of 1000 steps, with success defined by invoking the STOP action within 1.0 m of the goal image position.

As our visual encoder, we use the VC-1-Base (Majumdar et al., 2023) model which was previously finetuned with ImageNav on a smaller training scene split from the HSSD dataset. Empirically, we found that freezing the visual encoder after this targeted finetuning significantly accelerates the overall training performance. During the VC-1 finetuning, we use a smaller learning rate of 1.5×10^{-6} for the encoder.

We train the agents for a total of 500M timesteps on 32 A40 GPUs running 32 parallel environments each (1024 envs in total). Following the approach from Majumdar et al. (2023), we collect 64 steps of experience and subsequently perform 2 PPO epochs with a mini-batch size of 2. The reward function employed is the improved formulation proposed by Yadav et al. (2023), using parameters: success weighting $c_s = 5.0$, angle success weighting $c_a = 5.0$, goal radius $r_g = 1.0$, angle threshold $\theta_g = 25^\circ$, and slack penalty $\gamma = -0.002$. We optimize using AdamW with a learning rate of 2.5×10^{-4} and weight decay 10^{-6} .

Text Agent(LLM) Task Prompt

You are an expert and intelligent question answering agent. You will be provided a list of textual descriptions of the environment created by an agent while navigating around a house and picking and placing objects. The descriptions correspond to logs made after collecting and viewing a small chunk of frames, and contain information about which frame numbers they correspond to. You will also be provided a goal that now needs to be accomplished, for which you will need to use the history to decide where to go. Your job is to identify the desired frame index to navigate to, based on the provided task. Make sure your response is all within the JSON.

Agent's History information:

- Room name: The name of the room the agent was in.
- Picking, placing, or navigating: Whether the robot was picking or placing an object, or navigating around the house.
- Object being manipulated: The object that the robot was picking or placing (if relevant).
- Receptacle being manipulated: The receptacle that the robot was picking up from or placing an object into (if relevant).
- Other objects in scene: Objects present in the scene besides the main object and the receptacle.

Output Format (should be in JSON format):

```
'''json
{
    "chain_of_thought": str.
    "frame_indices": list[int].
}
'''
```

Where:

- Chain of Thought: A detailed explanation of your thought process in determining the frame indices.
- Frame Indices: A list of one or more frame indices relevant to accomplishing the goal.
- If its a single object/place task, output only one frame index.
- If task requires the agent to go to multiple places, output one frame index per object/place. (Do not use ellipsis)

Agent's history: history

The goal is {goal}

Figure 9: System Prompt for Qwen2.5-VL model to perform textual reasoning over the concatenated textual summaries

We select the best-performing policy checkpoint based on a validation success rate obtained by evaluating on 1000 image-goal navigation episodes from the FINDINGDORY validation set, achieving a success rate of 78% and SPL of 48.21%.

F.2 Explicit Mapping Agent

We augment the OracleAgent (see Appendix C.3) with a top-down occupancy map as it navigates the environment to generate the video sequence. In addition, we also store the 2D poses corresponding to each frame that is collected in the video sequence. The constructed map is employed by a path planning module to generate a deterministic navigation sequence to the 2D map coordinates that correspond to the image-goal location selected by the high-level goal selection agent (see Appendix D.1).

Map Construction. We leverage the onboard depth sensor and project the depth image at each timestep into an egocentric pointcloud using camera intrinsics. The pointcloud is then binned along the z-axis to compute occupancy values on a local 2D grid map centered around the current position of the agent. The pose sensor provides the instantaneous pose of the agent which is employed to register the computed local map in the global map of the environment. In this way, we continuously update the global map as the OracleAgent navigates the environment and visits multiple pick-place




Figure 10: Hierarchical agent architecture when using a VLM for goal frame selection and low level policies for action generation.

targets. We freeze the map updates during the pick-place subroutines as no additional occupancy information is encountered during their execution.

Planner. When the high-level goal agent selects a particular goal frame, we lookup the corresponding target 2D pose in the global map. Simlar to the local navigation policy employed in Chang et al. (2023), we use the Fast Marching Method (Sethian, 1996) to generate the shortest path to the goal pose. We use one of four discrete navigation actions (see Appendix C.1) to reach each waypoint on the generated shortest path.

G Qualitative Examples

In this section, we include representative qualitative examples from the FINDINGDORY task suite. In Figure 11, we provide a birds-eye view depiction of the trajectory executed during experience collection (see Appendix C.3) in a validation episode involving 5 pick-place interaction routines. For this episode, the collected video consists of 1308 frames in total. We provide detailed responses (and meta-analysis) from various baselines across the various task categories in Figures 13 to 18. In the following, we briefly discuss the different failure modes encountered in the generated responses across the 3 high-level task categories defined in Table 1.

Single-Goal Spatial Tasks. We observe that for the *Object Recall* task (Figure 13), the models are able to identify a frame with the target *chest of drawers* but do not select the closest frames to ensure success. In the *Interaction* based tasks (Figures 13 and 14), we observe models fail to accurately list the sequence of interaction events which can be partially attributed to supplying only 96 subsampled frames from the original video. In one case, GPT-40 instead focuses on a "distractor" target object (Figure 14). All models perform poorly on the *Spatial Relationship* tasks (Figure 14) as they are unable to coherently reason about the spatial layout of the house in the provided video.

Single-Goal Temporal Tasks. For the *Interaction Order* task, we observe that the closed-source models are able to accurately identify the target object but the open-source variants fail to do so (Figure 16). Models are generally able to select the correct frame in the *Time-Based* task as the model only needs to retrieve a single frame corresponding to the correct overlaid timestamp. For the *Duration Tracking* task, only GPT-40 generates the correct reasoning and frame prediction. Intersetingly, Gemma-3 tries to track the duration spent in each room by matching the floor color observed in the images but eventually fails at the task (Figure 17).

Multi-Goal Tasks. All models fail to perform successfully on tasks under this category. Only GPT-40 gets a correct response for all subgoals. Surprisingly, the reasoning trace has a hallucination but this mistake is omitted in the final frame sequence prediction (Figure 18). The models struggle to coherently list the event sequence and also hallucinate interactions. Furthermore, Gemini-2.0-flash also struggles to adapt the sequence of events it lists into the query revisitation sequence specified in the task (Figure 18).




Figure 11: An example experience collection trajectory executed by OracleAgent.




Figure 12: Example "magic" pick-place sequences executed by the OracleAgent for sample episode in Fig. 11.

Single-Goal Spatial Tasks

Object Recall Task: Navigate to a chest of drawers. ▲ GPT-4o: To accomplish the task of navigating to a chest of drawers, I need to identify the frames where the

A GPT-4o: To accomplish the task of navigating to a chest of drawers, I need to identify the frames where the

A GPT-4o: To accomplish the task of navigating to a chest of drawers, I need to identify the frames where the

A GPT-4o: To accomplish the task of navigating to a chest of drawers, I need to identify the frames where the

A GPT-4o: To accomplish the task of navigating to a chest of drawers, I need to identify the frames where the

A GPT-4o: To accomplish the task of navigating to a chest of drawers, I need to identify the frames where the

A GPT-4o: To accomplish the task of navigating to a chest of drawers, I need to identify the frames where the

A GPT-4o: To accomplish the frame that the frame chest of drawers is visible. The focus will be on frames showing the chest of drawers most prominently and closely. Starting from frame 0, I will scan through the images focusing on furniture that matches a typical chest of drawers. I observed a chest of drawers in frames 53 and 54 located in the kitchen area, which confirms the presence in those frames. frame_indices: [53] Meta Analysis: Misidentifies kitchen counter as target object √ Gemini-2.0-flash: The robot performs the following actions: - Picks up a green spray bottle and blue √ <u>Gemini-2.8-flash:</u> The robot performs the following actions: - Picks up a green spray bottle and blue lunchbox from a chair and places it on a table. - Picks up an apple from a table and places it on another chair. - Picks up the lunchbox from the table and puts it in the bathroom sink. - Picks up a shoe from a shelf and places it next to a lamp on a bedside table. - Picks up a green alarm clock from a dresser and places it near the washing machine. - Picks up a panda figurine from a shelf and places it next to the lamp. - Picks up the spray bottle from the bedside table. - Picks up the panda figurine from bedside table and places it near a chair. The user wants to navigate to a chest of drawers. The video shows chest of drawers at [00:37], [00:47], [00:53], [00:71], [00:78]. NUM_TARGETS_TO_REVISIT: ||1||. TIMESTAMP_INDEX: ||00:37|| frame_indices: [37] various rooms and eventually reaches a room with a chest of drawers visible on the right side of the screen. frame_indices: [49]
Meta Analysis: Selects a frame too distant from the target despite a closer one being available 🗡 <u>Gemma-3:</u> The robot needs to navigate to a chest of drawers. I will examine the video frames to identify the chest of drawers and select the frame index that shows the chest of drawers clearly. The chest of drawers appears in frames 71, 72, and 78. Frame 71 shows the chest of drawers clearly, so I will select that frame index. frame_indices: [71] Meta Ānalysis: Šelects a frame too distant from the target despite a closer one being available X <u>Text Agent:</u> The goal is to navigate to a chest of drawers. From the history, we see that the agent navigated through various rooms including the bedroom and living room. The dresser mentioned in the placing action at frame index 672 could be a chest of drawers. Therefore, the most relevant frame index to achieve the goal is 672.
frame_indices: [672] Meta Analysis: Selects a frame where target objects is not visible but was visible in nearby frames Interaction Task: Navigate to any receptacle you placed an object on. $\sqrt{\text{GPT-4o:}}$ To find a frame where the robot placed an object on a receptacle, I analyzed the video frames. In Frame 15, the robot places a lunchbox on a table. This frame clearly shows the object being placed, which matches the goal of navigating to a receptacle where an object was placed. Thus, Frame 15 is the most relevant frame for the task. frame_indices: [15] Gemini-2.0-flash: Here's a breakdown of the objects picked and placed in the video, to help answer the user's question: ***Spray bottle:** Picked from a chair (00:03), placed on a nightstand (01:16). *

Lunchbox: Picked from a chair (00:03), placed on a bathroom sink (00:25). * **Apple:** Picked from a table (00:07), kept on the ottoman (01:34). * **Shoe:** Picked from shelf (00:33), placed under lamp (00:41). *

Alarm clock: Picked from a side table (00:55), kept on bathroom sink (01:05). * **Toy:** Picked from a table (01:27), placed on a chair (01:33). The user wants to navigate to any receptacle where an object was placed. So, we can choose any of the destination receptacles. Let's pick the ottoman (where the apple was placed). NUM_TARGETS_TO_REVISIT: ||1||. TIMESTAMP_INDEX: ||01:34||

frame indices: [94] frame_indices: [94] Meta Analysis: Misidentifies the location of placing the apple which is the table Qwen-2.5-VL: The robot needs to navigate to a receptacle where it previously placed an object. From the video, we can see that the robot has placed various objects on different surfaces such as tables, chairs, and dressers. To achieve the goal, the robot should identify the last object it placed and then move to the receptacle where it was placed.

frame_indices: [12, 25, 47, 63, 78, 93]

Meta Analysis: Provides incorrect reasoning and identifies multiple frames (some incorrect) instead of single frame Gemma-3: The robot needs to navigate to the receptacles where it placed objects. Let's analyze the video to identify those frames. 1. **Frame 11:** The robot places a suitcase on a table. 2. **Frame 26:** The robot places a suitcase on a sink. 3. **Frame 65:** The robot places a clock on a sink. 4. **Frame 93:** The robot places a suitcase on a chair. Therefore, the frame indices to navigate to are 11, 26, 65, and 93. frame_indices: [11, 26, 65, 93] Meta Analysis: Incorrect event tracking and reasoning leads to misidentified frames $\sqrt{\text{Text Agent:}}$ The goal is to navigate to any receptacle where an object has been placed. From the history, the last action was placing an alarm clock on the dresser in the bedroom. Therefore, I should navigate to the bedroom. frame_indices: [576]

Figure 13: FINDINGDORY Spatial Tasks for the sample episode in Figure 11. Each VLM model uses 96 subsampled frames. *Text Agent* processes full video as defined in Appendix E.4.

Meta Analysis: Incorrect event tracking but still selects a valid frame

Single-Goal Spatial Tasks

Conditional Interaction

Task: Navigate to the receptacle that you picked the backpack from.

X GPT-40: The task requires the robot to return to the receptacle where it previously picked up the backpack. By reviewing the sequence of frames in the video, frames 3 through 17 show the robot's interaction with the backpack. The backpack is first clearly seen on a chair in frame 3, and the robot interacts with it until frame 17. After frame 17, the robot seems to have moved away from the chair with the backpack. Thus, the frame closest to the object (the chair with the backpack) before it was picked is frame 3.

frame_indices: [3]
Meta Analysis: Ignores backpack that was picked from the table and focuses on "distractor" backpack that agent never
interacted with

Gemini-2.0-flash: Here's a breakdown of the video and the solution: * **Video Summary:** * The robot picks up a green spray bottle and a dinosaur lunchbox from a chair (00:03). * The robot picks up a red apple from a table (00:07). * The robot picks up the dinosaur lunchbox from a table (00:15). * The robot places the dinosaur lunchbox on a bathroom sink (00:26). * The robot picks up a black-and-blue sneakers from a shelf (00:33). * The robot places a black-and-blue sneakers on the cabinet next to a table lamp (00:41). * The robot picks up the green alarm clock (00:56). * The robot placed the alarm clock next to the lunch box on the bathroom counter (01:05). * The robot picks up the green spray bottle and panda toy from the cabinet next to the lamp (01:16). * The robot places the green spray bottle and the lunchbox back on the chair (01:33). * **Tlask:**Navigate to the receptacle that you picked the backpack from. * **Solution:** The robot picked the backpack from the chair at 00:03. Therefore, the response is: NUM_TARGETS_TO_REVISIT: ||1||. TIMESTAMP_INDEX: ||00:03|| frame_indices: [3]

Meta Analysis: Correctly tracks events but makes error in reasoning over the events

Meta Analysis: Correctly tracks events but makes error in reasoning over the events

√ <u>Qwen-2.5-VL</u>: The robot needs to navigate back to the location where it picked up the backpack. From the video, the backpack was picked up on frame 16 when the robot was in the bathroom. Therefore, the robot should move to the frame where the backpack was last seen.

frame_indices: [16]

Meta Analysis: Backpack was dropped in the bathroom

√ <u>Gemma-3:</u> The robot picked up the backpack from a receptacle. I need to find the frame index where the receptacle is visible. The backpack was picked up in frames 15-16. The receptacle is the small table with a dinosaur-themed bag on it. The frame index where the receptacle is visible is frame 15. frame indices: [15]

Text Agent: The goal is to navigate to the receptacle where the backpack was picked. From the history, we see that the backpack was picked in the bedroom at frame index 384. Therefore, we should navigate to the bedroom. frame_indices: [384]

Spatial Relationship

Task: Navigate to the receptacle that you picked an object from which is the farthest from your current location.

**GPT-4o: The robot picked up objects from various receptacles during the navigation. To determine the farthest receptacle from the current location, it's important to identify the locations where the robot previously picked up items and then calculate which of these locations is the farthest from the end point of the video. Key frames to consider include: - Frame 4: Picked up an item from the chair near the glass door. - Frame 17: Picked up an item from a table in what seems to be the living area. - Frame 41: Picked up a shoe from a different location. The current location (final frame) seems to indicate the cabet is in a bedrace Polative to this the farthest nicking location would likely be Frame 4, where the robot picked the robot is in a bedroom. Relative to this, the farthest picking location would likely be Frame 4, where the robot picked an item up from a chair near the glass door. This probable distance is because the living room and shoe area seem to be closer to the bedroom than the chair near the glass door. Thus, the robot should navigate to the receptacle at Frame 4.

Meta Analysis: Incorrect description of final agent location as bedroom. In addition, chair from which item was picked is visible clearly visible in final frame

X Gemini-2.0-flash: Here's how we can solve this problem: 1. **Summarize the Robot's Actions:** * **Chair:** * Picked up a **Cemini-2.0-flash: Here's how we can solve this problem: 1. **Summarize the Robot's Actions:** * **Chair:** * Picked up a spray bottle and a lunchbox from the chair near the sliding doors (00:30). * Placed the spray bottle on the nightstand next to the lamp in the bedroom (01:16). * Picked up an apple from the table in the balcony (00:07). * Dropped the lunchbox on the bathroom sink (00:26). * **Table** * Picked up a shoe from the shelf behind the sofa (00:33). * Dropped the shoe to the nightstand (00:41). * **Washing Machine** * Picked up an alarm clock from the top of washing machine (00:56). * Dropped the alarm clock near the lunchbox in the bathroom sink (01:08). * **Chair near sofa** * Picked up a toy from the chair near the sofa(01:27). * Dropped the lunchbox near the chair in the balcony (01:35). 2. **Determine Distances:** * The chair near the sliding doors and washing machine appears to be the farthest receptacles from current position (frame 00:08). 3. **Identify the First Receptacle:** The first receptacle is the chair near the sliding doors. 4. **Final Answer:** Based on the the final answer is: NUM_TARGETS_TO_REVISIT: ||1||. TIMESTAMP_INDEX: ||00:03||

frame_indices: [3]
Meta Analysis: Incorrect event tracking and no clear spatial reasoning exhibited

X Owen-2.5-VL: The robot needs to navigate to the farthest receptacle from its current location. It has previously picked up a red object from a table and a lunchbox from a sink. The red object is on a table, and the lunchbox is on a sink. The table is located in the dining area, and the sink is in the bathroom. The dining area is further away from the current location than the bathroom. Therefore, the robot should move towards the dining area. frame_indices: [12]

Meta Analysis: Agent final location is close to the chair from which the red object was picked

X Gemma-3: The robot's goal is to navigate to the receptacle that it picked an object from which is the farthest from its current location. The robot picked up a blue object from a table in the first few frames. The receptacle is the table table is located in the outdoor area of the house. The robot is currently in the bathroom. Therefore, the robot should navigate to frame 84, which shows the table in the outdoor area.

frame_indices: [84]
Meta Analysis: Incorrect event tracking and spatial reasoning

X Text Agent: To determine the farthest receptacle from the current location, we need to calculate the distance between the agent and each receptacle it has interacted with. However, since we don't have explicit distance data, we'll assume the order of rooms visited reflects the order of interaction. The farthest room from the starting point would likely be the last one visited. In this case, the last room visited is the 'living room' at frame index 1308. frame_indices: [1308]

Meta Analysis: No spatial reasoning and reliance on unfounded assumptions

Figure 14: FINDINGDORY Spatial Tasks for the sample episode in Figure 11. Each VLM model uses 96 subsampled frames. Text Agent processes full video as defined in Appendix E.4.

Single-Goal Spatial Tasks

Object Attributes

Task: Navigate to a red colored object again that you interacted with yesterday.

√ <u>GPT-4o:</u> The video shows consecutive frames captured by a robot inside a house. The task is to identify the frame where the robot had an interaction with a red-colored object. Upon reviewing the frames, the robot interacted closely with a red apple. This interaction can be observed between frames 6 and 11, with the robot's gripper appearing close to the apple. Therefore, the frame where the robot seems closest to the apple is frame 7. frame_indices: [7]

Gemini-2.0-flash: The robot picks up the following objects and places them at different locations: - A green spray bottle and a lunch box from a chair and places them on a table in the bathroom (frame 26). - A red apple from a table and does not drop it, implies it is still holding it (frame 11). - A shoe from a shelf and drops it next to a lamp in a bedroom (frame 41). - An alarm clock from a counter and drops it near the lunch box in the bathroom (frame 65). - A panda toy from a shelf in a bedroom and drops it near the spray bottle (frame 77). The user wants to revisit the red colored object (red apple). Since the robot never dropped it, we should revisit the table where it picked up the apple to see if it placed it back there. NUM_TARGETS_TO_REVISIT: ||1||. TIMESTAMP_INDEX: ||00:07|| frame_indices: |7|
Meta Analysis: Does not identify the dropping of apple on table but calcute versus from

Meta Analysis: Does not identify the dropping of apple on table but selects correct frame based on where the apple was viewed

√ Qwen-2.5-VL: The robot needs to navigate back to the red object it interacted with yesterday. From the video frames, the red object appears on a table in the living room at frame 10. frame_indices: [10]

Gemma-3: The robot's goal is to navigate to a red colored object that it interacted with yesterday. Looking through the video, I can see the robot interacting with a red suitcase multiple times. The first time the robot interacts with the red suitcase is around frame 15. The robot then interacts with the suitcase again around frame 25, 66, 68, 86, 92, and 95. I will choose frame 15 as the frame index to navigate to the red suitcase. frame_indices: [15]

Meta Analysis: Fails to identify the red apple object that was dropped on the table

Text Agent: To accomplish the goal of navigating to a red colored object, I need to identify the red object from the history. From the given history, there is no explicit mention of a red object. However, if we assume the red object was picked or placed at some point, we should look for the most recent navigation action involving a red object. Since the history does not specify the color, we'll choose the last navigation action as it might be the most recent interaction.

frame_indices: [1308]
Meta Analysis: Fails to identify the red apple object that was dropped on the table

Room Visitation

Task: Navigate to the room where you placed the backpack in.

GPT-4o: The robot needs to find the room where it placed the backpack. While reviewing the frames, the backpack appears prominently in frames 3, 25, and 93, among others. The most recent placement seems to be in frame 93, which occurs at time 11:06, showing the backpack is located on a chair initially visible in the earlier part of the video. This suggests that the robot placed the backpack there later in the sequence since it was previously interacting with it near the bathroom sink (frame 25). Thus, the correct location the robot should navigate to is found in frame 93.

frame_indices: [93]

Meta Analysis: Focuses on "distractor" backpack that agent never interacted with

√ <u>Gemini-2.0-flash:</u> Here's a breakdown of the objects picked and placed, to help answer the question: * **Spray Bottle:** Picked from the chair at 00:03, placed on the nightstand at 01:16 * **Red Apple:** Picked from the table at 00:07, placed on the chair at 00:03 * **Shoe:** Picked from shelf at 00:33, placed near the lamp at 00:41 * **Lunchbox:** Picked from table at 00:15, placed on bathroom counter at 00:26 * **Clock:** Picked from the drawer at 00:56, placed on the lunchbox on bathroom counter at 01:05 * **Panda Toy:** Placed on the nightstand at 01:16, picked from the nightstand lamp table at 01:16, placed on table at 00:15 The lunchbox (referred to as "backpack" in the prompt) was placed on the bathroom counter. So, to navigate to where the backpack was placed, we should go to the bathroom. NUM_TARGETS_TO_REVISIT: ||1||. TIMESTAMP_INDEX: ||00:26|| frame_indices: [26]

√ <u>Owen-2.5-VL</u>: The robot needs to navigate to the room where it placed the backpack. From the video, we can see the backpack being placed on a sink in a bathroom. The robot should move to this location to find the backpack. frame_indices: [25]

Gemma-3: The robot needs to navigate to the room where the backpack was placed. From the video, the backpack was placed on a chair in a room with a table and a plant. The frames showing the backpack on the chair are frames 93 and 95. I will choose frame 93 as it is a clearer view of the backpack and the surrounding environment. frame_indices: [93]

Meta Analysis: Focuses on "distractor" backpack that agent never interacted with

Text Agent: To determine the room where the backpack was placed, I need to find the frame where the agent was placing an object. From the history, the last frame where the agent was placing an object was at frame 672, where the alarm clock was placed on the dresser in the bedroom. Since the goal is to navigate to the room where the backpack was placed, we should look for a frame where the agent was navigating to a specific room. The next navigation frame is at 768, which is in the bathroom. However, there is no indication that the backpack was placed in the bathroom. The next navigation frame is at 960, which is in the bathroom as well. The next navigation frame is at 960, which is in the bedroom. Therefore, the backpack was likely placed in the bedroom.

frame_indices: [960]
Meta Analysis: Misses tracking frames where backpack is picked from table in living room and placed in bathroom sink

Figure 15: FINDINGDORY Spatial Tasks for the sample episode in Figure 11. Each VLM model uses 96 subsampled frames. *Text Agent* processes full video as defined in Appendix E.4.

Single-Goal Temporal Tasks

Interaction Order

Task: Navigate to the object you that you interacted with between the interactions with apple and shoe.

 $\sqrt{\text{GPT-4o:}}$ First, identify the interactions involving the apple and shoe. The apple interaction occurs at frames 7 to 11. The shoe interaction occurs at frames 33 to 43. Between these interactions, the robot interacted with a lunchbox. The relevant frames for this interaction are from 25 to 28 and 64 to 68. The robot should navigate to the lunchbox in this task. frame_indices: [26]

Gemini-2.0-flash: Here's a breakdown of the robot's actions in the video: 1. **00:03**: Robot picks up a spray bottle and lunchbox from a chair. 2. **00:07**: Robot picks up an apple from a table. 3. **00:15**: Robot places the lunchbox on another table. 4. **00:25**: Robot places the lunchbox on the bathroom sink. 5. **00:33**: Robot picks up a shoe from a shelf. 6. **00:41**: Robot places the shoe under a lamp on a nightstand. 7. **00:55**: Robot picks up an alarm clock from a table. 8. **01:05**: Robot places the alarm clock near the lunchbox on the bathroom sink. 9. **01:16**: Robot places the spray bottle on a nightstand. The object interacted with between the apple and shoe is the lunchbox. It was picked up at 00:03 and placed on the cipk of 00:25 AUMI TAPCET TO DEVICE THE TABLET TABLET TO DEVICE THE TABLET TABLET.

sink at 00:25. NUM_TARGETS_TO_REVISIT: ||1||. TIMESTAMP_INDEX: ||00:03||
frame_indices: [3]

Meta Analysis: Correct event tracking and target identification but incorrectly navigates to the object picking location instead of final placement location

X Qwen-2.5-VL: The robot needs to navigate from the apple interaction to the shoe interaction. The apple interaction occurred at frame 10, and the shoe interaction occurred at frame 35. Therefore, the robot should move to the frame right after the apple interaction.

frame_indices: [11]

Meta Analysis: Fails to identify the backpack target object for navigation

Gemma-3: The robot interacted with an apple in frame 7 and a shoe in frame 43. The object between these interactions is the green alarm clock. The robot interacted with the alarm clock in frame 55. Therefore, the frame index to move to is 55.

frame_indices: [55]

Meta Analysis: Incorrect target object identification due to temporal reasoning error

X <u>Text Agent:</u> The goal is to navigate to the object you interacted with between the interactions with apple and shoe. From the history, the interaction with the apple occurred at frame 672 and the interaction with the shoe occurred at frame 384. Therefore, we need to find the frame index between these two events.

frame_indices: [576]
Meta Analysis: Incorrect event tracking and ignores the initial interaction with the apple

Time-Based

Task: Navigate to the object that you interacted with at 8:26 yesterday. **For this task, the query timestamp can be slightly different but target solution object remains constant

✓ <u>GPT-4o:</u> To find the frame index where the robot should move, we need to first identify the object that was The robot's interacted with at 8:06. Reviewing the timestamps on the images, we can see that the robot interacted with an object around that time. At 8:08 (frame 39), the robot is near the nightstand with a lamp and small weights. The robot's interaction here suggests it is the object of interest. Moving a bit further into frames, the shoe is being interacted with from frame 39 to frame 41. Therefore, the frame closest to this moment, and thus relevant for the task, is frame 39. frame_indices: [39]

 $\sqrt{\text{Gemini-2.0-flash:}}$ The robot performs the following actions: - Picks up a spray bottle from the chair (00:03), - Picks up an apple from the table (00:07), - Picks up a lunchbox from the table (00:16), - Places lunchbox on bathroom sink (00:26), - Picks up a shoe from the shelf (00:33), - Places shoe on the nightstand (00:41), - Picks up an alarm clock from the table next to the washing machine (00:56), - Places alarm clock on the bathroom sink next to lunchbox (01:05), - Picks up a panda figurine next to the lamp (01:16), - Places spray bottle next to the lamp (01:17). The user is asking to revisit the object that was interacted with at 08:21, which is the shoe. NUM_TARGETS_TO_REVISIT: ||1||. TIMESTAMP_INDEX: ||00:41|| frame_indices: [41]

✓ Qwen-2.5-VL: The robot needs to navigate back to the object it interacted with at 8:26 yesterday. From the video frames, the object it interacted with appears to be a shoe on the floor near the bed at frame 43. frame_indices: [43]

 ∧ Gemma-3: The robot interacted with a suitcase at 08:27. I need to find the frame index where the robot is closest to the suitcase. Looking at the images, the suitcase is visible in frames 64, 65, 66, 67, 68, 69, 88, 90, 92, 93, 94, 95. Frame 93 seems to be the closest to the suitcase.

frame_indices: [93]

Meta Analysis: Identifies the incorrect target object. In addition, focuses on the "distractor" backpack which

was not interacted with

X Text Agent: To determine the frame index corresponding to the interaction at 8:27 yesterday, I need to find the timestamp closest to 8:27. The timestamps provided are in a 24-hour format, so 8:27 would be 20:27 in military time. The closest timestamp in the history is 09:27, which corresponds to the frame indices 864 and 960. Since the goal is to navigate to the object interacted with at 8:27, we should choose the frame index that aligns with this timestamp.

frame_indices: [864]

Meta Analysis: Erroneous conversion of query timestamp to a new value (09:27). But retrieves the correct

object corresponding to interaction at 09:27

Figure 16: FINDINGDORY Temporal Tasks for the sample episode in Figure 11. Each VLM model uses 96 subsampled frames. Text Agent processes full video as defined in Appendix E.4.

Task: Navigate to to the room that you spent most time in. √ GPT-40: I need to identify which room the robot spent the most time in during the navigation. Analyzing the frames, the setting shifts around a few distinct locations, primarily different rooms in the house. The living room appears frequently, with repetitive views of chairs, tables, and decorative setups. The frames in the living room spans from the start, go through frames with consistent furniture and decor like in frames 1-12, and reappear frequently towards the latter part, such as around frames 98-60ish. Other parts like the bathroom or kitchen have fewer frames indicating less time spent. Thus, identifying the living room as the room where the robot spent the most time, the earliest close frame in that setting is a good reference for moving to the dominant room setting. ★ Semini-2.9-flash: The robot spends most of its time in the living room and the bedroom. Since both rooms are spent similar mount of time, I will default to choosing the living room. NUM_TARGETS_TO_REVISIT: ||1||. ★ TIMESTAMP_INDEX: ||01:34|| ★ Trame_indices: ||40|| Meta Analysis: Decides to choose the living room but selects a frame where agent is in the smaller patio area ★ Qwen-2.5-VL: The robot needs to navigate to the room it spent the most time in. Based on the frames, the robot spends more time in the bedroom, as indicated by the higher frame numbers and the bedroom. ★ Gemma-3: The robot spent most of its time in the room with the blue floor. The video starts in a room with a blue wall, then moves to a room with a white floor, moving around and interacting with various objects. The robot spends more time in the room with the blue floor. The video starts in a room with a blue floor. The robot apend and interacting with to a bathroom, and then back to the room with the blue floor, moving around and interacting with to a bathroom, and then back to the room with a white floor, then to a room with a blue wall, then to a bathroom, and then back to the room with the blu

Figure 17: FINDINGDORY Temporal Tasks for the sample episode in Figure 11. Each VLM model uses 96 subsampled frames. *Text Agent* processes full video as defined in Appendix E.4.

Multi-Goal Tasks

Unordered Revisitation

```
Task: Revisit all the receptacles you picked objects from yesterday.
 GPT-40: The video shows the robot navigating through a house while picking up objects from various receptacles. To complete the task, the robot needs to revisit the same receptacles where objects were picked up. 1. Frame 3 shows the robot picking an object from the chair. Revisit this chair. 2. Frame 7 shows the robot picking an object (an apple) from the dining table. Revisit this table. 3. Frame 15 shows the robot picking an object from a round table beside a chair. Revisit this table. 4. Frame 33 shows the robot picking a shoe from a low shelf. Revisit this shelf. 5. Frame 55 shows the robot picking a clock from a countertop. Revisit this countertop. 6. Frame 76 shows the robot picking a spray bottle from a side
   picking a clock from a countertop.
table near a lamp. Revisit this tal
   table near a lamp. Revisit this table. These are the main locations the robot picked objects from, so these frames need to be revisited.
  frame_indices: [3, 15, 33, 55, 76]
Meta Analysis: Incorrectly identifies apple being picked from table whereas the apple was dropped on table. But omits index 7 in final solution without any clear reason
     Gemini-2.8-flash: Here's a breakdown of the objects picked and placed, to determine the receptacles that need
 **Nomental-2.0-14881. Here's a breakdown of the Objects picked and placed, to determine the receptations in head revisiting: ***Spray bottle & Lunchbox:** * Picked from: Chair in the living room (00:04), then plant table (00:15), then sink (00:26). * **Apple:** * Picked from: Plant table (00:07) * Placed on: Plant table (00:11). * **Shoe:** * Picked from: Shelf in living room (00:33) * Placed on: Nightstand in bedroom (00:41). * **Lunchbox:** * Picked from: Sink in bathroom (00:27) * Placed on: Ottoman (01:24) * **Clock:** * Picked from: Washing Machine (00:56) * Placed on: Sink in bathroom (01:08) * **Panda Toy:** * Picked from: Nightstand in bedroom (01:16) * Placed
 Machine (00:56) * Placed on: Sink in bathroom (01:08) * **Panda Toy:** * Picked from: Nightstand in bedroom (01:16) * Place on: Chair in living room (01:27) Now, let's identify the timestamps for revisiting the original receptacles: 1. **Chair in living room:** Where the spray bottle and lunchbox were initially placed. (00:03) 2. **Plant table:** Where the apple was initially placed. (00:07) 3. **Shelf in living room:** Where the shoe was initially placed. (00:33) 4. **Washing machine:** Where the clock was initially placed. (00:56) 5. **Nightstand in bedroom:** Where the panda toy was initially placed. (01:05) 6. **Sink in bathroom** Where the lunchbox was initially placed. (00:27) NUM_TARGETS_TO_REVISIT: ||6||.

TIMESTAMP_INDEX: ||00:03, 00:07, 00:03, 00:56, 01:16, 00:27||
frame_indices: [3, 7, 33, 56, 76, 27]|
Meta_Analysis: Incorrect event tracking and misidentifies backpack placement frames as pick frames
     X <u>Qwen-2.5-VL:</u> The robot needs to revisit all the receptacles it picked objects from yesterday. From the video, we can see
   that the robot picked up objects from various receptacles such as a table, a suitcase, a nightstand, and a dresser. To achieve the goal, the robot should revisit these locations in the order they were visited.

frame_indices: [12, 16, 34, 50]
    Meta Analysis: Inadequate reasoning and hallucinates suitcase as a receptacle
      Kemma-3: Error parsing output
   frame_indices: [-1]
Meta Analysis: Model fails to produce any coherent output
 Text Agent: To revisit all the receptacles from which objects were picked yesterday, I need to identify the rooms where objects were picked and then navigate back to those rooms. From the history, we see that objects were picked from the living room, kitchen, bedroom, and bathroom. Therefore, I should navigate to these rooms. frame indices: [8, 96, 192, 288, 384, 480, 576, 672, 768, 864, 966, 1856, 1152, 1248]
Meta Analysis: Incorrectly focuses only on room revisitation instead of revisiting specific receptacles
                                                                                                                                                                                            Ordered Revisitation
   Task: Revisit all the receptacles you placed objects on yesterday in specific order. The order to revisit them is: fifth,
    second, first, third.
 GPT-40: The robot needs to revisit specific receptacles in order. To do this, it needs to identify the frames where objects were placed: 1. **First Receptacle (Fifth in order of placement):** - Frame 64: Lunchbox on the sink in the bathroom. 2. **Second Receptacle (Second in order of placement):** - Frame 7: Apple on the table in the dining area. 3. **Third Receptacle (First in order of placement):** - Frame 16: Lunchbox on the small table in the living room. 4. **Fourth Receptacle (Third in order of placement):** - Frame 33: Shoe on the shelf in the entryway. The robot should start with the lunchbox on the sink (fifth placement), then the apple on the table (second placement), revisit the lunchbox in the living room (first placement), and finally go to the shoe on the shelf (third placement).

Meta Analysic: Unable to list out the original object placement events and then adapt to the query revisitation sequence
   frame_indices: [64, 7, 16, 33]
Meta Analysis: Unable to list out the original object placement events and then adapt to the query revisitation sequence
Meta Analysis: Unable to list out the original object placement events and then adapt to the query revisitation sequence

**Gemini-2.0-flash:** Here's a summary of the objects picked and placed, and their locations: * **Apple:** Picked from the table near the plant (00:07), placed on the table on the balcony (00:03). * **Spray bottle:** Picked from the chair on the balcony (00:083), placed under the lamp on the nightstand (01:41). * **Lunchbox:** Picked from the table (00:15), placed on the bathroom counter (00:25). * **Clock:** Picked from the table next to the washing machine (00:55), placed on the bathroom counter next to lunchbox (01:05). * **Panda:** Picked from under the lamp on the nightstand, placed on the side table in living room (01:27). Given the objects and placements, let's identify the receptacles for revisitation in the required order: 1. The fifth item that was placed was the **clock** on the bathroom counter. 2. The second item that was placed was the **spray bottle* under the lamp on the nightstand. 3. The first item that was placed was the **spray bottle* under the lamp on the nightstand. 4. The first item that was placed was the **spray bottle and shoe on the nightstand: **Apple on the chair on the balcony. 4. The third item that was placed was the **spray bottle and shoe on the nightstand: ***Orice the samp on the chair on the balcony. **

**Orice To New York of the Province of the placement sequence although hallucinates interaction with spray bottle. Confuses picking and placement timestamps while generating final solution

**Care To New York of the samp of the placement sequence although shallucinates interaction with spray bottle. Confuses picking and placement timestamps while generating final solution
 Qwen-2.5-VL: The robot needs to revisit the receptacles it placed objects on yesterday in the specified order: fifth, second, first, third. To achieve this, we need to identify the frames where these receptacles were visited. The frames provided show the robot interacting with various objects and moving through different rooms. We need to find the frames corresponding to the receptacles in the given order.

frame_indices: [59, 13, 26, 48]

Meta Analysis: No clear reasoning on how the original placement sequence was adapted to the query revisitation sequence
   Gemma-3: Error parsing output frame_indices: [-1]
Meta Analysis: Model fails to produce any coherent output
 Text Agent: To accomplish the goal of revisiting the receptacles in the specified order, I need to identify the receptacles that were placed with objects. From the history, the receptacles mentioned are 'dresser' and 'sink'. The order to revisit them is fifth, second, first, third. Based on the timestamps and room names, the 'dresser' was visited at frame indices 672 and 768, and the 'sink' was visited at frame indices 288 and 384. The order given is fifth, second, first, third, so we should start with the 'dresser' (frame indices 672 and 768), then the 'sink' (frame indices 288 and 384). frame_indices: [672, 768, 288, 384]
Meta Analysis: Only lists out two receptacles on which objects were placed but task requires revisiting all of them
```

Figure 18: FINDINGDORY Multi-Goal Tasks for the sample episode in Figure 11. Each VLM model uses 96 subsampled frames. *Text Agent* processes full video as defined in Appendix E.4.

Table 3: Task Categories with all associated prompts

Memory Type	Example Instructions
Object Recall	Navigate to a {target_object_name}.
Object Recuir	Navigate to a {target_receptacle_name}.
	Navigate to any receptacle you interacted with.
	Navigate to any receptacle you did not interact with.
Interaction	Navigate to any object that you interacted with yesterday.
interaction	Navigate to any object that you did not interact with yesterday.
	Navigate to any receptacle you picked an object from.
	Navigate to any receptacle you placed an object from.
	Navigate to the {target_object_name} that you interacted with yesterday.
	Navigate to a {target_object_name} that you did not interact with yesterday.
Conditional	Navigate to a {target_receptacle_name} you did not interact with yesterday.
Interaction	Navigate to a {target_receptacle_name} you picked an object from.
111101111011	Navigate to a {target_receptacle_name} you placed an object on.
	Navigate to the receptacle that you picked the {target_object_name} from.
	Navigate to the object that you picked from the {target_receptacle_name}.
	Navigate back to a {target_shape} shaped object that you interacted with yesterday.
	Navigate back to a {target_color} colored object that you interacted with yesterday.
Object Attributes	Navigate to an interacted object with {target_print_or_design} on it.
	Find an already interacted object that is made of {target_material}.
	Go back to an interacted object that is used for {target_functionality}.
	Navigate to the receptacle that you interacted with which is the farthest from your curren location.
	Navigate to the receptacle that you did not interact with which is the farthest from you current location.
	Navigate to the receptacle that you picked an object from which is the farthest from you current location.
Spatial Relationship	Navigate to the receptacle that you placed an object on which is the farthest from you current location.
	Navigate to the object which you interacted with which is the farthest from your currer location.
	Navigate to the room where you picked the {target_appearance_order} object from.
	Navigate to the room where you placed the {target_appearance_order} object in.
Room Visitation	Navigate to the room where you picked the {target_object_name} from.
	Navigate to the room where you placed the {target_object_name} in.
	Navigate to a room that you did not visit yesterday.
	Navigate to the {target_appearance_order} object that you interacted with yesterday.
	Navigate to the {target_appearance_order} receptacle that you picked an object from.
	Navigate to the {target_appearance_order} receptacle that you placed an object on.
	Navigate to the receptacle that you picked the {target_appearance_order} object from.
	Navigate to the object that you picked from the {target_appearance_order} receptacle.
	Navigate to the object you interacted with immediately after ending the interaction wit {target_object_name}.
	Navigate to the object you interacted with immediately before interacting with {taget_object_name}.
	Navigate to the object you interacted with {target_num_counts} interactions after {taget_object_name}.
	Navigate to the object you interacted with {target_num_counts} interactions before {taget_object_name}.
	Navigate to the object that you interacted with between the interactions with {ta get_object_name_1} and {target_object_name_2}.
	Navigate to the receptacle that you placed an object on right before you started interactin with {target_object_name}.
	Navigate to the receptacle that you picked an object from right after you finished interactin with {target_object_name}.
	Continued on the next nage

Continued on the next page...

Interaction Order

Memory Type	Example Instructions
	Navigate to the receptacle that you placed an object on {target_num_counts} interactions before you started interacting with {target_object_name}.
	Navigate to the receptacle that you picked an object from {target_num_counts} interactions after you finished interacting with {target_object_name}.
	Navigate to the receptacle that you placed an object on between the interactions with {target_object_name_1} and {target_object_name_2}.
	Navigate to the receptacle that you picked an object from between the interactions with {target_object_name_1} and {target_object_name_2}.
Time-Based	Navigate to the receptacle that you interacted with at {XX:XX} yesterday.
	Navigate to the object that you interacted with at {XX:XX} yesterday.
	Navigate to the object which took the longest time to rearrange.
Duration Tracking	Navigate to the room that you spent the most time in.
	Navigate to the object which took the shortest time to rearrange.
Unordered Revisitation	Revisit all the receptacles you picked objects from yesterday.
	Revisit all the receptacles you placed objects on yesterday.
	Revisit all the {target_receptacle_name} you placed objects on yesterday.
	Revisit all the {target_receptacle_name} you picked objects from yesterday.
	Revisit all the objects you interacted with yesterday.
	Revisit all the receptacles you interacted with yesterday.
Ordered Revisitation	Revisit all the receptacles you picked objects from yesterday in specific order.
	Revisit all the receptacles you placed objects on yesterday in specific order.
	Revisit all the objects you interacted with yesterday in specific order.