

# What Does Softmax Probability Tell Us about Classifiers Ranking Across Diverse Test Conditions?

**Weijie Tu**

*Australian National University*

*weijie.tu@anu.edu.au*

**Weijian Deng**

*Australian National University*

*weijian.deng@anu.edu.au*

**Liang Zheng**

*Australian National University*

*liang.zheng@anu.edu.au*

**Tom Gedeon**

*Australian National University*

*Curtin University*

*University of Óbuda*

*tom.gedeon@curtin.edu.au*

**Reviewed on OpenReview:** <https://openreview.net/forum?id=vtiDUgGjyx>

## Abstract

This work aims to develop a measure that can accurately rank the performance of various classifiers when they are tested on unlabeled data from out-of-distribution (OOD) distributions. We commence by demonstrating that conventional uncertainty metrics, notably the maximum Softmax prediction probability, possess inherent utility in forecasting model generalization across certain OOD contexts. Building on this insight, we introduce a new measure called Softmax Correlation (SoftmaxCorr). It calculates the cosine similarity between a class-class correlation matrix, constructed from Softmax output vectors across an unlabeled test dataset, and a predefined reference matrix that embodies ideal class correlations. A high resemblance of predictions to the reference matrix signals that the model delivers confident and uniform predictions across all categories, reflecting minimal uncertainty and confusion. Through rigorous evaluation across a suite of datasets, including ImageNet, CIFAR-10, and WILDS, we affirm the predictive validity of SoftmaxCorr in accurately forecasting model performance within both in-distribution (ID) and OOD settings. Furthermore, we discuss the limitations of our proposed measure and suggest avenues for future research.

## 1 Introduction

Machine learning (ML) models typically excel on test sets coming from the same distribution as the training set. However, this assumption seldom holds in real-world deployments, where the test environments often experience distribution shifts caused by factors such as sample bias and non-stationarity. Recognizing this challenge, there is a pressing need to assess ML model performance in unlabeled testing environments where traditional evaluation metrics which require data annotations, such as accuracy and  $F1$  score, may become infeasible. Hence, our focus shifts towards the vital yet under-explored task of ranking models under these conditions. Specifically, given a pool of trained models and an unlabeled test set, the objective is to efficiently select the most suitable model for utilization.

Various complexity measures have been proposed to predict the in-distribution (ID) accuracy of models (Jiang et al., 2020a; Neyshabur et al., 2015; Bartlett et al., 2017; Keskar et al., 2017; Nagarajan & Kolter, 2019; Neyshabur et al., 2017; Chuang et al., 2021; Jiang et al., 2020b; Smith & Le, 2018; Arora et al., 2018; Dziugaite & Roy, 2017; Dinh et al., 2017). For the OOD test sets, classical domain adaptation theory provides

a partial answer by quantifying the distance between the ID and OOD distributions (Ben-David et al., 2006). Moreover, the “accuracy-on-the-line” phenomenon Miller et al. (2021) shows the linear correlation in the probit scale between ID and OOD performance. However, such phenomenon does not always hold on some distributions (Teney et al., 2022). Building on previous research, our objective is to develop a robust measure capable of ranking models on both ID and OOD datasets *without* testing labels.

Softmax prediction probability has been shown to be useful in analyzing test data in several tasks, such as open-set data detection (Hendrycks & Gimpel, 2016), accuracy estimation (Guillory et al., 2021; Garg et al., 2022), and misclassified input detection (Deng et al., 2022). For example, Hendrycks & Gimpel (2016) and Liang et al. (2018) utilize maximum Softmax prediction probability to identify samples from open-set classes. Driven by these insights, we develop OOD measures based on Softmax probability. Concretely, given various deep models, we aim to develop probability-based measures that monotonically relate to OOD generalization. To validate the feasibility, we conduct extensive and large-scale correlation studies using various models and different types of dataset shifts. We construct a catalog of empirical prediction probability-based measures and create a wide range of experimental setups. We collect 573 different classification models ranging from standard convolutional neural networks to Vision Transformers. We cover 11 ID and OOD datasets with various types of distribution shift, such as ImageNet-V2 (Recht et al., 2019) with dataset reproduction shift and ImageNet-R (Hendrycks et al., 2021a) with style shift.

Based on experimental results, we first show the demand for measures to rank model performance beyond in-distribution accuracy (Miller et al., 2021). Then, we observe that empirical uncertainty measures based on prediction probabilities (*e.g.*, maximum softmax probability) are useful in characterizing OOD generalization to some extent. However, we note that these measures solely account for prediction certainty. In response, we introduce SoftmaxCorr, a method designed to harness both prediction certainty and diversity. Confidence pertains to the certainty of individual predictions, whereas dispersity indicates the spread of predictions across all categories. Specifically, for each classifier, we compute a class-class correlation matrix from all prediction vectors in a test set. Then, we calculate its cosine similarity with a predefined reference matrix, designed to represent desirable prediction patterns, to evaluate whether this classifier makes diverse and certain predictions. The broad correlation study shows the efficacy of SoftmaxCorr in ranking models.

## 2 Related Work

**Predicting generalization in deep learning** studies the ID generalization gap (*i.e.*, the difference between training and test accuracy) of deep neural networks. Representative methods develop complexity measures based on model parameters and training set (Jiang et al., 2020a;b; Neyshabur et al., 2015; Keskar et al., 2017; Bartlett et al., 2017; Neyshabur et al., 2018; Liang et al., 2019; Chuang et al., 2021; Smith & Le, 2018; Arora et al., 2018; Dziugaite & Roy, 2017; Dinh et al., 2017; Dziugaite et al., 2020), such as distance of training weights from initialization (Nagarajan & Kolter, 2019), the product of norms of weights across layers (Neyshabur et al., 2017) and the change of model accuracy with respect to different perturbation levels in training data (Schiff et al., 2021). The above methods assume that training and test data come from the same distribution and do not incorporate characteristics of test data, so we can unlikely make reasonable predictions on a different distribution. To mitigate this limitation, we investigate the model generalization under distribution shift by developing measures that reflect the models’ generalization ability on OOD datasets.

**OOD generalization.** Machine learning models should generalize from training distribution to OOD datasets (Djulonga et al., 2021; Koh et al., 2021; Kirsch & Gal, 2022). To study this problem, several benchmarks are proposed (Hendrycks & Dietterich, 2019; Koh et al., 2021; Gulrajani & Lopez-Paz, 2021), such as corruption benchmark (Hendrycks & Dietterich, 2019) and domain generalization testbed (Gulrajani & Lopez-Paz, 2021). Moreover, several methods are proposed to improve model OOD generalization (Volpi et al., 2018; Zhao et al., 2020; Sagawa et al., 2020; Liu et al., 2021; Mansilla et al., 2021; Shi et al., 2021; Krishnamachari et al., 2023; Zhang et al., 2021; Huang et al., 2023; Foret et al., 2020; Huang et al., 2022), such as adversarial domain augmentation (Volpi et al., 2018; Qiao & Peng, 2021; Alhamoud et al., 2022) and inter-domain gradient matching (Shi et al., 2021).

Prior research has established theoretical frameworks for assessing classifier performance amid distribution shifts. Ben-David et al. (2006) introduced the first VC-dimension-based generalization bound, quantifying the difference in classifier error between source and target distributions using a divergence measure. Mansour et al. (2009) extended this analysis to more general loss functions, providing refined generalization bounds via Rademacher complexity. Other studies (Blitzer et al., 2007; Hoffman et al., 2018; Mansour et al., 2008) expanded upon these findings to include multiple source domains. Some works further bound the OOD generalization error based on the divergence between the two distributions (Acuna et al., 2021; Zhang et al., 2019; Tachet des Combes et al., 2020). However, as suggested by Miller et al. (2021), when the distribution shift becomes larger, the above bounds on OOD performance become looser. In addition, Vedantam et al. (2021) report that the adapting theory from domain adaptation is limited in predicting OOD generalization.

**Unsupervised accuracy estimation (UAE)** aims to predict the performance of a given model on various unlabelled out-of-distribution datasets. One line of research utilizes the model outputs on the test sets (Guillory et al., 2021; Garg et al., 2022; Deng et al., 2023; Tu et al., 2023b). For instance, Guillory et al. (2021) uses the maximum value of prediction probability to estimate model accuracy. A parallel line of works predicts model performance by gauging distribution discrepancy between training and test sets using image features (Deng & Zheng, 2021; Tu et al., 2023a; Xie et al., 2024; Lu et al., 2024). For example, Deng & Zheng (2021) uses the first- and second-order statistics of image features and Fréchet Distance to jointly measure the model performance. In contrast, other studies investigate this task through model weights (Yu et al., 2022).

While UAE predicts OOD accuracy of a single model across various test sets, our work focuses on ranking multiple models’ OOD performance on an unlabeled test dataset. UAE methods may be deployed in this task by predicting the performance of each single model. However, to derive the estimated performance, most UAE methods (*e.g.*, BoP (Tu et al., 2023a) or Dispersion score (Xie et al., 2024)) require training an accuracy predictor on a number of datasets. These operations make the deployment of methods computational expensive in our tasks. We have included efficient Softmax-based UAE methods in our study

### 3 Task Formulation

**Task definition.** We consider a  $K$ -way classification task, and let  $\mathcal{Y} = \{1, \dots, K\}$  denote the label space and  $\mathcal{X} \in \mathbb{R}^d$  denote the input space. We are given a labeled training set  $\mathcal{D}^S$  that contains data i.i.d drawn from a source distribution  $P_S$ , and an OOD test set  $\mathcal{D}^T := \{(x_i, y_i)\}_{i=1}^N$  that contains  $N$  data i.i.d drawn from another distribution  $P_T$  ( $P_S \neq P_T$ ). We train  $M$  neural network classifiers  $\{\phi_m\}_{m=1}^M$  on  $\mathcal{D}^S$ . Given a sample  $(\mathbf{x}, y)$  from  $\mathcal{D}^T$ , the classifier  $\phi_m : \mathcal{X} \rightarrow \Delta^K$  gives Softmax probabilities for  $\mathbf{x}$  on  $K$  classes, where  $\Delta^K$  denote  $K - 1$  dimensional unit simplex. By testing on  $\mathcal{D}^T$ ,  $\phi_m$  yields a prediction matrix  $\mathbf{P} \in \mathbb{R}^{N \times K}$ , whose each row represents prediction probabilities of a test data. Specifically, the prediction matrix satisfies  $\sum_{j=1}^K P_{i,j} = 1 \forall i \in 1 \dots N$  and  $P_{i,j} \geq 0 \forall i \in 1 \dots N, j \in 1 \dots K$ , where  $P_{i,j}$  indicates the probability that  $i$ -th sample is predicted to the  $j$ -th class.

The dataset has an evaluation metric (*e.g.*, accuracy) to obtain ground-truth generalization  $G_m$  of classifier  $\phi_m$ . The goal is to design a measure to calculate a score  $S_m$  for each classifier  $\phi_m$  without access to data annotations. The calculated scores  $\{S_m\}_{m=1}^M$  ideally should correlate well with  $\{G_m\}_{m=1}^M$ , so that we can rank the OOD generalization of models based on the scores.

**Evaluation metrics.** We use Spearman’s Rank Correlation coefficient  $\rho$  (Kendall, 1948) to measure monotonicity between calculated scores and model generalization. In addition, we also compute the weighted variant of Kendall’s rank correlation  $\tau_w$ , which is shown to be a useful measure when selecting the best-ranked item of interest (You et al., 2021). Both coefficients range from  $[-1, 1]$ . A value closer to  $-1$  or  $1$  indicates a strong negative or positive correlation, respectively, and  $0$  means no correlation. Similar to Miller et al. (2021) and Baek et al. (2022), we apply the same probit scale to both accuracy and SoftmaxCorr in our experiment for a better linear fit.




Figure 1: **Correlation study between MaxPred and accuracy (%) on ImageNet-S and ImageNet-R.** Every point denotes a classifier. We use 173 ImageNet models and 89 vision–language models introduced in Section 5. The straight line is fit with robust linear regression (Huber, 2011) and the shadow means the 95% Clopper-Pearson confidence intervals. We show that MaxPred exhibits a moderate correlation with accuracy, while accuracy on ImageNet-validation shows a relatively low correlation with performance on ImageNet-R. Moreover, Vision-Language Models (VLMs) exhibit varying linear trends in terms of their ID and OOD accuracy compared to standard supervised models.

## 4 Softmax Probability-based OOD Measures

### 4.1 What Makes OOD Measures Interesting?

**Beyond Accuracy-on-the-Line (AoL).** Miller et al. (2021) report an AoL phenomenon where there exists a strong linear correlation between probit-scaled ID and OOD generalization. This implies that ID accuracy is a good predictor of OOD generalization. However, delving deeper into OOD measures is warranted for three compelling reasons. **First**, Miller et al. (2021) discuss that AoL is not universal. That is, on some datasets, ID, and OOD accuracy do not show a clear positive correlation. This point is further discussed by Wenzel et al. (2022). Specifically, Wenzel et al. (2022) suggest two patterns preventing this phenomenon: (1) underspecification (*e.g.*, Camelyon17) where the same ID performance leads to different OOD behavior; (2) models do not transfer information from ID to OOD domains (*e.g.*, DomainNet). That is, despite various ID performance, all models perform poorly on OOD datasets. Paradoxically, identifying the failure patterns itself requires labeled OOD data (Teney et al., 2024). **Second**, it is demanding and sophisticated to design ID test sets (Engstrom et al., 2020), which are expected to be unbiased and representative of distribution to effectively measure model ID accuracy. Further, it is a trade-off to split a full dataset into training, validation and test sets in terms of training and evaluation quality. **Third**, recent advancements in vision-language models, such as CLIP (Radford et al., 2021) and BLIP (Li et al., 2022), have achieved remarkable zero-shot classification performance. This means that collecting a dataset for a specific task to train such models is not required. Due to their diverse and large-scale training data, it might not be suitable to use a proxy dataset (*e.g.*, ImageNet validation set) to reflect their performance. As shown in Figure 1, Vision-Language models (VLM) exhibit varying linear trends in terms of their ID and OOD accuracy compared to standard supervised models. Furthermore, even among VLMs themselves, consistency in these linear trends is not always guaranteed. These findings suggest that AoL alone does not suffice to accurately rank CLIP models.

**Why Use Softmax Prediction Probability?** Deep neural networks often exhibit a tendency to provide overly confident predictions, as evidenced by various studies (Ovadia et al., 2019; Minderer et al., 2021; Guo et al., 2017; Hein et al., 2019). Initially, this characteristic might raise doubts about the reliability of using Softmax Prediction as a measure of uncertainty on test data. However, existing research has shed light on its informative nature when analyzing test environments. For instance, Hendrycks & Gimpel (2016) demonstrated that the maximum Softmax prediction probability (MaxPred) for correctly classified samples tends to be higher than that of incorrectly classified or out-of-distribution (OOD) samples. This observation has paved the way for utilizing MaxPred in error/success prediction and ID/OOD detection. Building upon this insight, Guillory et al. (2021) and Garg et al. (2022) have proposed leveraging MaxPred to estimate the accuracy of trained classifiers on test samples.

Moreover, Softmax probabilities can be efficiently computed without requiring any changes to the network architecture or additional data preprocessing. Additionally, they can be derived solely from unlabeled data. These characteristics endow prediction probability-based measures with substantial practical value as reliable

indicators of OOD generalization. Inspired by the above discussion, this work aims to validate the feasibility of using model output-based methods (such as softmax probability) for assessing and ranking models.

**Proof of concept.** The above works imply the prediction probability is likely to be effective in measuring the OOD performance of a pool of models. Given an OOD test set (ImageNet-R) and various ImageNet models, we conduct a correlation study between MaxPred and classification accuracy. In Figure 1, we show that there is a relatively strong correlation between MaxPred and model accuracy ( $\rho = 0.829$  and  $\tau_w = 0.884$ ) on ImageNet-R. This indicates that MaxPred is feasible in ranking OOD performance. Based on this observation, we further explore more empirical prediction probability-based measures and develop a more effective measure that exploits more semantics reflected in the prediction probability.

## 4.2 Exploring More Empirical Measures

In addition to accuracy-on-the-line (AoL) and maximum prediction probability (MaxPred), we investigate other empirical measures as follows:

**Average Thresholded Confidence with Maximum Confidence (ATC-MC)** (Garg et al., 2022). This method is used to predict the performance of a specific trained model under distributional shift. Here, we deploy it to rank various models’ performance on one particular OOD test set. It firstly identifies a threshold  $t$  on  $\mathcal{D}^S$  such that the number of samples with confidence score lower than  $t$  is equal to the model’s error. Then, the ATC on  $\mathcal{D}^T$  is given by the number of points whose confidence is less than  $t$ . The formula is:  $ATC = \mathbb{E}_{x \sim \mathcal{D}^T} [\mathbb{I}[\arg \max_{j \in \mathcal{Y}} \mathbf{P}_{:,j} < t]]$ , where  $\mathbb{I}[E]$  is the binary indicator of event  $E$ .

**Softmax Gap (SoftGap).** MaxPred only uses the maximal value of Softmax vectors while disregarding values on other entries. Inspired by Baldock et al. (2021), we introduce SoftGap based on MaxPred which further considers the second-largest entry in a prediction vector. Specifically, it calculates the average difference between the largest and second-largest Softmax prediction probabilities over all samples. A high SoftGap indicates a confident prediction, while a low SoftGap suggests confusion between the two classes corresponding to the highest and second-highest probabilities.

## 4.3 Ours: Softmax Correlation (SoftmaxCorr)

**Class-class correlation matrix** Given the prediction matrix  $\mathbf{P} \in \mathbb{R}^{N \times K}$  predicted by  $\phi_m$ , a class correlation matrix  $\mathbf{C} \in \mathbb{R}^{K \times K}$  is computed by  $\mathbf{C} = \frac{\mathbf{P}^T \mathbf{P}}{N}$ . An entry  $C_{i,j}$  indicates a correlation between prediction probabilities of class  $i$  and class  $j$  over all samples. We define the sum of diagonals of the correlation matrix as intra-class correlation ( $I_a$ ) and the sum of off-diagonals as inter-class correlation ( $I_e$ ). The sum of  $\mathbf{C}$  is 1, which means  $I_a = 1 - I_e$ . Moreover,  $\text{trace}(\mathbf{P}^T \mathbf{P}) = \sum_{i=1}^N \sum_{j=1}^K P_{i,j}^2 = \|\mathbf{P}\|^2$ , where  $\|\cdot\|$  is the Frobenius norm of a matrix. Thus, we can derive  $I_a = \frac{\|\mathbf{P}\|^2}{N}$ . According to Cui et al. (2020),  $\|\mathbf{P}\|$  has strict opposite monotonicity, and the minimum of the entropy  $H(\mathbf{P})$  and the maximum of  $\|\mathbf{P}\|$  could be achieved at the same value. Therefore,  $I_a$  reflects the certainty of predictions.

**Motivation:** In domain generalization, it has been observed that class-class correlation encodes class confusion, thereby offering the potential for regularization to enhance model generalization ability (Chen et al., 2022; Jin et al., 2020; Li et al., 2021; Cui et al., 2020). Additionally, existing literature underscores the significance of both high prediction certainty and prediction diversity in identifying discriminative features (Yang et al., 2021; Wang & Isola, 2020; Asano et al., 2019).

Inspired by these insights, we can propose an OOD metric, which leverages a class-class correlation matrix to take into account the two characteristics:

- Prediction certainty: the model’s ability to produce confident predictions. Given the strict opposite monotonicity between  $I_a$  and entropy  $H(\mathbf{P})$ , prediction certainty can be reflected by a high  $I_a$  and consequently a low  $I_e = 1 - I_a$  within the class correlation matrix  $\mathbf{C}$ .
- Prediction diversity: relying solely on prediction confidence may be inadequate. For instance, a model may exhibit high certainty yet be biased towards a single class, making the diagonal entries of  $\mathbf{C}$  skewed.

In such cases, while prediction confidence is high, it does not necessarily indicate high model performance. Driven by this, we further evaluate prediction diversity: each class should be predicted and involved in predictions. To measure this, we expect the diagonals of  $\mathbf{C}$  to be well-distributed across all classes instead of biased towards few classes.

Combining two characteristics, a desirable class correlation matrix has zeros on the off-diagonal entries, and values on diagonal elements match the distribution of classes. The similarity between the class correlation matrix of an evaluated model and the desirable class correlation matrix reflects the model performance.

**Implementation:** To achieve this, we propose **SoftmaxCorr** and define it as the cosine similarity between the class-class correlation matrix  $\mathbf{C}$  and a reference matrix  $\mathbf{R}$ :  $\text{cos}(\mathbf{C}, \mathbf{R}) = \frac{\sum_{i,j} (\mathbf{C} \odot \mathbf{R})_{i,j}}{\|\mathbf{C}\| \cdot \|\mathbf{R}\|}$ , where  $\odot$  is the element-wise product between matrices. The reference matrix captures the essence of the desirable class correlations: it is a diagonal matrix whose off-diagonal elements are 0 while its diagonal entries mirror the class marginal distribution. To approximate this class distribution, we use the average prediction probability across test data generated by a zero-shot vision-language model (ViT-bigG/14-CLIPA). The range of the SoftmaxCorr is  $[0, 1]$ . For a fixed reference matrix, the maximum is obtained 1) when a model confidently assigns probability 1 to the predicted class and 2) the proportion of predictions for each class matches the class distribution. The minimal value is achieved when a model is extremely biased towards one specific class with the prediction probability of one, while the estimated distribution for such a class is zero.

## 5 Experiments

In this section, we first describe three setups including ImageNet, CIFAR-10, and WILDS. Then, we analyze the experiment results of prediction probability-based measures on three setups. After that, we study the impacts of class distribution estimator on predictive ability of SoftmaxCorr. Furthermore, we study whether SoftmaxCorr can rank the performance of model checkpoints along the training trajectory. Also, we validate the effectiveness of SoftmaxCorr under the domain adaption setting. Lastly, we study the correlation between SoftmaxCorr and the accuracy of a single model on various OOD test sets.

### 5.1 Experimental Setup

**ImageNet setup.** We collect 173 models publicly accessible from TIMM (Wightman, 2019). They are trained or fine-tuned on ImageNet (Deng et al., 2009) and have various architectures, training strategies and training paradigms. We use five OOD datasets for the correlation study. Specifically, OOD datasets are: (1) ImageNet-V2 (Recht et al., 2019); (2) ObjectNet (Barbu et al., 2019); (3) ImageNet-S(ketch) (Wang et al., 2019); (4) ImageNet-Blur severity 5 (Hendrycks & Dietterich, 2019); (5) ImageNet-R(ention) (Hendrycks et al., 2021a); ImageNet-R and ObjectNet contain 200 and 113 ImageNet classes respectively.

**CIFAR-10 setup.** We collect 65 networks trained with the scheme provided by Wightman (2017) on CIFAR-10 training set (Krizhevsky et al., 2009). These models have different model architectures. CIFAR-10-Val(idation) is the ID test set. For OOD datasets, we use (1) CIFAR-10.2 (Recht et al., 2018b) (2) CINIC (Darlow et al., 2018) (3) CIFAR-10-Noise with severity 5 (Hendrycks & Dietterich, 2019). We use accuracy as the metric of model generalization.

**WILDS setup.** We consider a classification tasks of this setup: Camelyon17 (Bandi et al., 2018). It is a binary classification dataset where the objective is to classify whether a slide contains a tumor issue. We use 45 models varying in architectures and random seeds. ID and OOD datasets are the default ID validation set and OOD test set respectively. For each task, we follow the same training scheme provided by Koh et al. (2021) to train or fine-tune models.

**Zero-shot vision language models.** In addition to models which are trained on the ID training dataset, we also consider 89 zero-shot vision-language models, including CLIP (Radford et al., 2021), SigLIT (Zhai et al., 2023), BLIP (Li et al., 2022), BLIP-2 (Li et al., 2023) and Flava (Singh et al., 2022). We use default

| Setup                     | Dataset        | Validation Required |              |              |              | Validation Free |          |         |          |              |              |
|---------------------------|----------------|---------------------|--------------|--------------|--------------|-----------------|----------|---------|----------|--------------|--------------|
|                           |                | AoL                 |              | ATC-MC       |              | MaxPred         |          | SoftGap |          | SoftmaxCorr  |              |
|                           |                | $\rho$              | $\tau_w$     | $\rho$       | $\tau_w$     | $\rho$          | $\tau_w$ | $\rho$  | $\tau_w$ | $\rho$       | $\tau_w$     |
| ImageNet                  | ImageNet-V2    | 0.954               | 0.911        | 0.994        | 0.961        | 0.711           | 0.597    | 0.796   | 0.644    | 0.921        | 0.758        |
|                           | ImageNet-A     | 0.593               | 0.636        | 0.830        | 0.895        | 0.756           | 0.813    | 0.805   | 0.846    | 0.964        | 0.915        |
|                           | ImageNet-R     | 0.452               | 0.431        | 0.950        | 0.954        | 0.829           | 0.884    | 0.902   | 0.911    | 0.951        | 0.928        |
|                           | ImageNet-S     | 0.505               | 0.467        | 0.981        | 0.959        | 0.862           | 0.864    | 0.887   | 0.871    | 0.935        | 0.909        |
|                           | ObjectNet      | 0.619               | 0.545        | 0.961        | 0.821        | 0.883           | 0.849    | 0.908   | 0.865    | 0.963        | 0.895        |
|                           | ImageNet-Blur  | 0.637               | 0.576        | 0.937        | 0.905        | 0.816           | 0.821    | 0.844   | 0.845    | 0.961        | 0.907        |
|                           | Average        | 0.627               | 0.594        | <b>0.942</b> | <b>0.916</b> | 0.810           | 0.805    | 0.857   | 0.830    | <b>0.949</b> | <b>0.885</b> |
| CIFAR-10                  | CIFAR-10.2     | 0.983               | 0.949        | 0.992        | 0.966        | 0.837           | 0.809    | 0.854   | 0.818    | 0.894        | 0.836        |
|                           | CINIC          | 0.866               | 0.890        | 0.952        | 0.902        | 0.665           | 0.663    | 0.690   | 0.681    | 0.821        | 0.763        |
|                           | CIFAR-10-Noise | 0.641               | 0.765        | 0.219        | 0.461        | 0.051           | 0.131    | 0.139   | 0.213    | 0.931        | 0.917        |
|                           | Average        | <b>0.830</b>        | <b>0.868</b> | 0.721        | 0.776        | 0.518           | 0.534    | 0.561   | 0.571    | <b>0.892</b> | <b>0.846</b> |
| WILDS                     | Camelyon17-OOD | -0.021              | -0.072       | -0.111       | -0.075       | 0.192           | 0.320    | 0.192   | 0.320    | 0.420        | 0.560        |
|                           | DomainNet-OOD  | 0.350               | 0.219        | 0.513        | 0.254        | 0.403           | 0.274    | 0.407   | 0.258    | 0.740        | 0.680        |
|                           | Average        | <b>0.165</b>        | <b>0.074</b> | 0.201        | 0.217        | 0.298           | 0.597    | 0.300   | 0.289    | <b>0.580</b> | <b>0.620</b> |
| Average over three setups |                | 0.598               | 0.575        | <b>0.747</b> | <b>0.751</b> | 0.637           | 0.693    | 0.675   | 0.609    | <b>0.864</b> | <b>0.824</b> |

Table 1: **Method comparison on ImageNet, CIFAR-10, WILDS and DomainNet.** We compare SoftmaxCorr with four measures: accuracy-on-the-line (AoL) (Miller et al., 2021), average thresholded confidence with maximum confidence (ATC-MC) (Garg et al., 2022), MaxPred (Hendrycks & Gimpel, 2016) and SoftGap (Baldock et al., 2021). Spearman’s rank correlation ( $\rho$ ) and weighted Kendall’s correlation ( $\tau_w$ ) are metrics. The highest correlation in each row is highlighted in **bold** and the second highest is in **blue**. We show that our method is stable and yields the highest average correlations over three setups.

prompt set for corresponding models. If the default prompt sets are not provided, “A picture of {class}.” is deployed. Unless specified, we use ViT-bigG/14-CLIPA to estimate class distribution for all setups.

## 5.2 Main Observations

**Albeit requiring no access to validation/proxy set, SoftmaxCorr exhibits a strong correlation with model generalization.** In Figure 2 and Table 1, we observe that SoftmaxCorr is indicative of model performance under the three setups. Particularly on the ImageNet setup, SoftmaxCorr has consistently strong correlations with models’ OOD performance. For example, the average Spearman’s Rank Correlation coefficient  $\rho$  is 0.949, 0.627, 0.942, 0.810, and 0.857 for our method, AoL, ATC-MC, MaxPred and SoftGap, respectively. We also notice that AoL exhibits very strong correlation with model accuracy on ImageNet-V2 ( $\rho = 0.954$ ), but such a correlation drops noticeably on other OOD datasets. This implies that it is insufficient to rank both supervised models and vision–language models based solely on this phenomenon. On CIFAR-10 and WILDS, while on some test sets it does not present the strongest correlation, we still think that SoftmaxCorr is a preferred measure because it has very competitive average correlation scores. For Camelyon17, we see that all methods are less useful. We speculate this is caused by the under-specification phenomenon (Wenzel et al., 2022) where the model relies on spurious features.

**SoftmaxCorr gives stable correlation, while the other four measures have mixed performance on different test sets.** On CIFAR-10-Noise, we find that SoftmaxCorr correlates well with model performance ( $\rho = 0.931$  and  $\tau_w = 0.917$ ). In contrast, AoL, ATC-MC, MaxPred, SoftGap show a weaker correlation. Although ATC-MC has a higher average weighted Kendall’s correlation than SoftmaxCorr ( $\rho = 0.916$  vs. 0.885) on ImageNet setup, it exhibits a weaker correlation on CIFAR-10 and WILDS setups. While in some cases SoftmaxCorr does not present the highest correlation, we emphasize that it overall gives more stable and stronger correlations. Thus, we think SoftmaxCorr is generally indicative of model generalization.




Figure 2: **SoftmaxCorr vs. model generalization under ImageNet, CIFAR-10 and WILDS setups.** In each subfigure, each point denotes a model trained for the corresponding task. For ImageNet setup, OOD test sets are ObjectNet and ImageNet-S and ImageNet-Blur. For CIFAR-10 setup, OOD test sets are CIFAR-10.2, CINIC and CIFAR-10-Noise. For WILDS, OOD test sets are Camelyon17-OOD and DomainNet-OOD. The  $y$ -axis is top-1 accuracy, top-1 accuracy and macro-F1 for the three setups, respectively. Straight lines are fit with robust linear regression (Huber, 2011). Axes are probit scaled as described in Section 3. We observe that SoftmaxCorr is a reliable and effective metric. Particularly on ImageNet, SoftmaxCorr is predictive of model generalization with strong performance ( $\rho > 0.92$ ).

**Compared to MaxPred and SoftGap, SoftmaxCorr better utilizes Softmax prediction probabilities.** We use SoftGap on top of MaxPred as a simple approach to explicitly consider more entries (the second largest probability) in Softmax predictions. As shown in Table 1, SoftmaxCorr and SoftGap both achieve higher correlation results than MaxPred ( $\rho = 0.864, 0.675$  and  $0.637$ , respectively). This indicates that it is helpful to analyze the distribution of softmax outputs. Compared with MaxPred and SoftGap, the class-wise correlation considered in our SoftmaxCorr better reveals the knowledge encoded by Softmax predictions. This is supported by the higher average correlation and more stable performance of SoftmaxCorr.

### 5.3 Sensitivity Analysis on Test Set Size

We study the sensitivity of SoftmaxCorr to test set size. Specifically, we reduce the dataset size by randomly sampling 1%, 5%, 10% and 30% of the original data. We report the averaged Spearman’s correlation of three random runs on six datasets (*e.g.*, ImageNet-V2, ImageNet-R, ObjectNet, CINIC, CIFAR-10-Noise and DomainNet-OOD). As shown in Table 3, we observe that when the number of test data is very small (1%), the correlation of SoftmaxCorr drops. When the dataset size increases ( $\geq 10\%$ ), SoftmaxCorr exhibits a stable and high correlation with model performance. This suggests that SoftmaxCorr requires a reasonable number of samples to capture model generalization.



| Dataset       | Certainty | Diversity | SoftmaxCorr  |
|---------------|-----------|-----------|--------------|
| ImageNet-V2-A | 0.619     | 0.551     | <b>0.921</b> |
| ImageNet-R    | 0.851     | 0.743     | <b>0.951</b> |
| ObjectNet     | 0.881     | 0.812     | <b>0.963</b> |
| CIFAR-10.2    | 0.881     | 0.766     | <b>0.894</b> |
| CINIC         | 0.643     | 0.543     | <b>0.821</b> |
| DomainNet-OOD | 0.412     | 0.139     | <b>0.740</b> |

Table 2: Comparison between SoftmaxCorr and two variants (Certainty and Diversity). Rank correlation ( $\rho$ ) is used as the metric.

| Dataset        | 1%    | 5%    | 10%   | 30%   | 100%  |
|----------------|-------|-------|-------|-------|-------|
| ImageNet-V2    | 0.851 | 0.791 | 0.817 | 0.862 | 0.921 |
| ImageNet-R     | 0.913 | 0.949 | 0.945 | 0.951 | 0.951 |
| ObjectNet      | 0.906 | 0.950 | 0.955 | 0.963 | 0.963 |
| CIFAR-10-Noise | 0.910 | 0.933 | 0.930 | 0.930 | 0.931 |
| CINIC          | 0.596 | 0.838 | 0.837 | 0.832 | 0.821 |
| DomainNet-OOD  | 0.758 | 0.784 | 0.789 | 0.789 | 0.740 |

Table 3: **Sensitivity analysis of SoftmaxCorr on test set sizes.** We test four sampling ratios and report  $\rho$  on six datasets. SoftmaxCorr is stable given a reasonable number of samples.

| Method       | ImageNet-V2-A | ImageNet-R | ObjectNet | CIFAR-10.2 | CINIC | DomainNet-OOD |
|--------------|---------------|------------|-----------|------------|-------|---------------|
| Disagreement | -0.379        | 0.746      | 0.021     | 0.264      | 0.314 | -0.083        |
| SoftmaxCorr  | 0.921         | 0.951      | 0.963     | 0.894      | 0.821 | 0.740         |

Table 4: Comparison between SoftmaxCorr and Disagreement. Rank correlation ( $\rho$ ) is used as the metric.

## 5.4 Impacts of Class Distribution Estimator

In previous experiments, we solely use a vision-language model as the reference model to estimate class distribution. Another baseline usage of such a reference model is to measure the disagreements between the predictions of evaluated models and the reference model (Disagreement). In Table 4, we compare Spearman’s rank correlation of Disagreement and SoftmaxCorr. We observe that SoftmaxCorr consistently gives a stronger correlation than Disagreement. Disagreement explicitly measures the similarity between the evaluated models and the reference model, so the performance of the reference model significantly influences the predictive ability of Disagreement. In contrast, SoftmaxCorr only uses it for estimating the empirical class distribution, which constitutes the diagonal elements of the reference matrix  $\mathbf{R}$ , with all off-diagonal elements set to zero.

To study the influence caused by the estimator, we further use a less accurate zero-shot vision-language model (ViT-H-14) and an ideal estimator for calculating the marginal class distribution. We evaluate them on ObjectNet, because it has imbalanced class distribution. In Figure 3, we observe that with a moderately accurate ViT-H-14, SoftmaxCorr remains predictive, and the reference estimator further enhances SoftmaxCorr. Note that, we only use the average of softmax prediction probability to estimate class weights. Some better-designed algorithms (Lipton et al., 2018; Garg et al., 2020; Sun et al., 2022) may improve SoftmaxCorr’s stability, and we leave it as future work.

## 5.5 Different Characterizations of Correlation Matrix

To investigate the importance of prediction diversity and certainty for predicting OOD generalization, we compare SoftmaxCorr with two variants: (1) the sum of diagonal entries in the class correlation matrix (Certainty). It measures whether the values in diagonal entries are large, indicating prediction certainty; (2) the Euclidean distance between diagonal elements in the class correlation matrix and estimated class distribution (Diversity). It measures whether models make diverse predictions whose distribution matches the estimated distribution of each class. In Table 2, we present Spearman’s rank correlation of three methods on six datasets from three setups. Both variants give weaker correlation strength than SoftmaxCorr. Specifically, SoftmaxCorr is more predictive of OOD generalization than Certainty and Diversity ( $\rho = 0.821$  vs.  $0.643$  vs.  $0.543$ ) on CINIC. This indicates that it is important to measure both prediction diversity and certainty for OOD generalization assessment.

## 5.6 Effectiveness of SoftmaxCorr for Domain Adaptation

On ImageNet, CIFAR and WILDS setups, all models are trained by standard empirical risk minimization and do not use the unlabeled OOD samples from training. In some scenarios, domain adaptation (DA) algorithms




Figure 3: **(a) Impacts of class distribution estimator**, we use three estimators: ViT-H-14, ViT-bigG-14-CLIPA and the ground truth. We find SoftmaxCorr is fairly stable. **(b) SoftmaxCorr v.s. accuracy on ImageNet-C benchmark**. In every subfigure, each dot indicates a dataset of ImageNet-C.. We see strong correlations between SoftmaxCorr and OOD accuracy on various test set.

are employed for learning target-adaptive models with additional unlabeled OOD samples (Kouw & Loog, 2019; Zhou et al., 2022). To explore whether SoftmaxCorr is still effective in assessing the generalization of these models, we conduct a correlation study under DomainNet setup (Peng et al., 2019; Sagawa et al., 2021). The models are trained by 9 different DA algorithms (*e.g.*, DeepCORAL (Sun & Saenko, 2016), DANN (Ganin et al., 2016)). In Table 1, we observe that SoftmaxCorr performs reasonably on DomainNet-OOD. We also notice that ID accuracy-based methods (AoL and ATC-MC) become less useful. DA algorithms likely focus on improving OOD performance, while ID accuracy may not be enhanced accordingly.

## 5.7 SoftmaxCorr Reflects a Model’s Generalization on Various OOD Test Sets

We investigate how a given trained model generalizes to various OOD datasets. In detail, we evaluate a single model on all test sets of ImageNet-C benchmark (Hendrycks & Dietterich, 2019) and conduct a correlation study between accuracy and SoftmaxCorr. We additionally use Pearson’s correlation ( $r$ ) to measure the overall linear trend. This coefficient varies in  $[-1, 1]$ . A value closer to  $-1/1$  indicates better negative/positive linearity and 0 means no correlation. We use ImageNet networks: EfficientNet-B2 (Tan & Le, 2019), ViT-Base (Dosovitskiy et al., 2020) and CLIP-RN/50 (Radford et al., 2021). Figure 3 shows a strong linear relationship and high-rank correlation ( $r > 0.95$  and  $\rho > 0.97$ ). It indicates that with linear regression, SoftmaxCorr can also help estimate the accuracy of a given model on various test sets.

## 5.8 Evaluation Along Training Trajectory

In previous sections, SoftmaxCorr is used to measure the performance of models varying in different architectures and training strategies. In practice, we are sometimes interested in evaluating the models at different training checkpoints. Hence, we analyze whether SoftmaxCorr is helpful in this case. We collect prediction probabilities on CINIC every 10 epochs along the training process of ResNet-20, DenseNet-121 (Huang et al., 2017), VGG11 (Simonyan & Zisserman, 2014) and MobileNet (Howard et al., 2017) trained on CIFAR-10. In Fig. 4, we observe SoftmaxCorr has a high-rank correlation ( $\rho > 0.93$ ) with model performance. This means we can potentially apply SoftmaxCorr to assay model generalization along the training process.




Figure 4: **Correlation analysis: SoftmaxCorr and accuracy on CINIC.** Each point represents a checkpoint. We consider CIFAR-10 models: ResNet-20, DenseNet-121, VGG-11 and MobileNet. Axes are probit scaled as in Section 3. In each subfigure, every point means a checkpoint of the model along the training process. For four models, we see strong correlations ( $\rho > 0.93$ ). This suggests that SoftmaxCorr is helpful in assessing checkpoints along the training process.

## 6 Discussion and Potential Directions

**Discussion on imbalanced test sets.** SoftmaxCorr is defined as cosine similarity between correlation matrix  $C$  and a reference matrix  $R_K$ . The reference matrix is a diagonal matrix and each entry represents the corresponding class distribution. To derive class distribution, a zero-shot vision-language model is used for efficient deployment without training and shows strong robustness towards distribution shifts. Consequently, the predictive ability of SoftmaxCorr correlates to the deployed vision-language model and the method used to estimate the distribution. Hence, it would be beneficial to use advanced label shift estimation techniques (Lipton et al., 2018; Garg et al., 2020; Sun et al., 2022) and employ more performant vision-language models, and we leave it as future work.

**Potential OOD measures.** This work proposes SoftmaxCorr to use class-wise relationships encoded by Softmax prediction probabilities. Here, we discuss other potential ways. **First**, SoftGap computes the difference between the largest and second-largest prediction probabilities. We show that SoftGap exhibits a stronger correlation with performance compared to MaxPred. It would be interesting to improve SoftGap by utilizing more probabilities (e.g., top five probabilities). **Second**, for a perfectly calibrated model, its MaxPred over a test set corresponds to its accuracy. Yet, calibration methods seldom exhibit desired performance under distribution shift (Ovadia et al., 2019). That said, it would be promising to study post-hoc calibration methods for OOD datasets, which benefits MaxPred for assessing model generalization. **Last**, this work focuses on Softmax prediction probability. We tested our method based on logits but no obvious correlation is exhibited. This may be because the logits of different models vary in significantly different ranges. We also think that studying other model statistics (e.g., weights and feature representations) would be interesting.

## 7 Conclusion

This paper studies an important problem of assaying and ranking model generalization under distribution shifts. To this end, we explore the use of Softmax prediction probability for developing OOD measures. We start by identifying the demand for OOD measures beyond accuracy-on-the-line and finding that maximum Softmax prediction probability is to some extent useful to measure the OOD performance. We then propose Softmax Correlation (SoftmaxCorr) which leverages class confusion encoded by the class-class correlation matrix and thus better reflects the overall quality of the classifier predictions. To validate the usefulness of SoftmaxCorr, we compare it with four other empirical measures across 11 datasets under ImageNet, CIFAR-10 and WILDS setups. We observe SoftmaxCorr generally presents a stable and high correlation with model performance on different OOD datasets. This paper establishes some baseline usage of Softmax prediction probability and a specific improvement, and more investigation will be made in the future.

## Acknowledgements

We sincerely thank all the anonymous reviewers and area chairs for their constructive comments and valuable suggestions, which have greatly helped in enhancing this paper.

## References

- David Acuna, Guojun Zhang, Marc T Law, and Sanja Fidler. f-domain adversarial learning: Theory and algorithms. In *International Conference on Machine Learning*, pp. 66–75, 2021.
- Kumail Alhamoud, Hasan Abed Al Kader Hammoud, Motasem Alfarra, and Bernard Ghanem. Generalizability of adversarial robustness under distribution shifts. *Transaction on Machine Learning Research*, 2022.
- Sanjeev Arora, Rong Ge, Behnam Neyshabur, and Yi Zhang. Stronger generalization bounds for deep nets via a compression approach. In *International Conference on Machine Learning*, pp. 254–263, 2018.
- Yuki Markus Asano, Christian Rupprecht, and Andrea Vedaldi. Self-labelling via simultaneous clustering and representation learning. In *International Conference on Learning Representations*, 2019.
- Christina Baek, Yiding Jiang, Aditi Raghunathan, and Zico Kolter. Agreement-on-the-line: Predicting the performance of neural networks under distribution shift. In *Advances in Neural Information Processing Systems*, 2022.
- Robert Baldock, Hartmut Maennel, and Behnam Neyshabur. Deep learning through the lens of example difficulty. In *Advances in Neural Information Processing Systems*, volume 34, pp. 10876–10889, 2021.
- Peter Bandi, Oscar Geessink, Quirine Manson, Marcory Van Dijk, Maschenka Balkenhol, Meyke Hermesen, Babak Ehteshami Bejnordi, Byungjae Lee, Kyunghyun Paeng, Aoxiao Zhong, et al. From detection of individual metastases to classification of lymph node status at the patient level: the camelyon17 challenge. *IEEE Transactions on Medical Imaging*, 2018.
- Andrei Barbu, David Mayo, Julian Alverio, William Luo, Christopher Wang, Dan Gutfreund, Josh Tenenbaum, and Boris Katz. Objectnet: A large-scale bias-controlled dataset for pushing the limits of object recognition models. In *Advances in Neural Information Processing Systems*, 2019.
- Peter L Bartlett, Dylan J Foster, and Matus J Telgarsky. Spectrally-normalized margin bounds for neural networks. In *Advances in Neural Information Processing Systems*, 2017.
- Shai Ben-David, John Blitzer, Koby Crammer, and Fernando Pereira. Analysis of representations for domain adaptation. In *Advances in Neural Information Processing Systems*, 2006.
- John Blitzer, Koby Crammer, Alex Kulesza, Fernando Pereira, and Jennifer Wortman. Learning bounds for domain adaptation. In *Advances in neural information processing systems*, 2007.
- Lin Chen, Huaian Chen, Zhixiang Wei, Xin Jin, Xiao Tan, Yi Jin, and Enhong Chen. Reusing the task-specific classifier as a discriminator: Discriminator-free adversarial domain adaptation. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, 2022.
- Ching-Yao Chuang, Youssef Mroueh, Kristjan Greenewald, Antonio Torralba, and Stefanie Jegelka. Measuring generalization with optimal transport. In *Advances in Neural Information Processing Systems*, pp. 8294–8306, 2021.
- Shuhao Cui, Shuhui Wang, Junbao Zhuo, Liang Li, Qingming Huang, and Qi Tian. Towards discriminability and diversity: Batch nuclear-norm maximization under label insufficient situations. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 3941–3950, 2020.
- Luke N Darlow, Elliot J Crowley, Antreas Antoniou, and Amos J Storkey. Cinic-10 is not imagenet or cifar-10. *arXiv preprint arXiv:1810.03505*, 2018.
- Ailin Deng, Shen Li, Miao Xiong, Zhirui Chen, and Bryan Hooi. Trust, but verify: Using self-supervised probing to improve trustworthiness. In *European Conference on Computer Vision*, 2022.
- Jia Deng, Wei Dong, Richard Socher, Li-Jia Li, Kai Li, and Li Fei-Fei. Imagenet: A large-scale hierarchical image database. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 248–255, 2009.

- Weijian Deng and Liang Zheng. Are labels always necessary for classifier accuracy evaluation? In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 15069–15078, 2021.
- Weijian Deng, Yumin Suh, Stephen Gould, and Liang Zheng. Confidence and dispersity speak: Characterising prediction matrix for unsupervised accuracy estimation. In *International Conference on Machine Learning*, 2023.
- Laurent Dinh, Razvan Pascanu, Samy Bengio, and Yoshua Bengio. Sharp minima can generalize for deep nets. In *International Conference on Machine Learning*, pp. 1019–1028, 2017.
- Josip Djolonga, Jessica Yung, Michael Tschannen, Rob Romijnders, Lucas Beyer, Alexander Kolesnikov, Joan Puigcerver, Matthias Minderer, Alexander D’Amour, Dan Moldovan, et al. On robustness and transferability of convolutional neural networks. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 16458–16468, 2021.
- Alexey Dosovitskiy, Lucas Beyer, Alexander Kolesnikov, Dirk Weissenborn, Xiaohua Zhai, Thomas Unterthiner, Mostafa Dehghani, Matthias Minderer, Georg Heigold, Sylvain Gelly, et al. An image is worth 16x16 words: Transformers for image recognition at scale. In *International Conference on Learning Representations*, 2020.
- Gintare Karolina Dziugaite and Daniel M Roy. Computing nonvacuous generalization bounds for deep (stochastic) neural networks with many more parameters than training data. In *Proceedings of the Thirty-Third Conference on Uncertainty in Artificial Intelligence*, 2017.
- Gintare Karolina Dziugaite, Alexandre Drouin, Brady Neal, Nitarshan Rajkumar, Ethan Caballero, Linbo Wang, Ioannis Mitliagkas, and Daniel M Roy. In search of robust measures of generalization. In *Advances in Neural Information Processing Systems*, pp. 11723–11733, 2020.
- Logan Engstrom, Andrew Ilyas, Shibani Santurkar, Dimitris Tsipras, Jacob Steinhardt, and Aleksander Madry. Identifying statistical bias in dataset replication. In *International Conference on Machine Learning*, pp. 2922–2932. PMLR, 2020.
- Pierre Foret, Ariel Kleiner, Hossein Mobahi, and Behnam Neyshabur. Sharpness-aware minimization for efficiently improving generalization. In *International Conference on Learning Representations*, 2020.
- Ustinova Ganin, Germain Ajakan, Laviolette Larochelle, Marchand, and Lempitsky. Domain-adversarial training of neural networks. In *Journal of Machine Learning Research*, 2016.
- Saurabh Garg, Yifan Wu, Sivaraman Balakrishnan, and Zachary Lipton. A unified view of label shift estimation. In *Advances in Neural Information Processing Systems*, pp. 3290–3300, 2020.
- Saurabh Garg, Sivaraman Balakrishnan, Zachary C Lipton, Behnam Neyshabur, and Hanie Sedghi. Leveraging unlabeled data to predict out-of-distribution performance. In *International Conference on Learning Representations*, 2022.
- Robert Geirhos, Kantharaju Narayanappa, Benjamin Mitzkus, Tizian Thieringer, Matthias Bethge, Felix A Wichmann, and Wieland Brendel. Partial success in closing the gap between human and machine vision. In *Advances in Neural Information Processing Systems*, 2021.
- Devin Guillory, Vaishaal Shankar, Sayna Ebrahimi, Trevor Darrell, and Ludwig Schmidt. Predicting with confidence on unseen distributions. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pp. 1134–1144, 2021.
- Ishaan Gulrajani and David Lopez-Paz. In search of lost domain generalization. In *International Conference on Learning Representations*, 2021.
- Chuan Guo, Geoff Pleiss, Yu Sun, and Kilian Q Weinberger. On calibration of modern neural networks. In *International Conference on Machine Learning*, pp. 1321–1330, 2017.

- Kaiming He, Xinlei Chen, Saining Xie, Yanghao Li, Piotr Dollár, and Ross Girshick. Masked autoencoders are scalable vision learners. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, 2022.
- Matthias Hein, Maksym Andriushchenko, and Julian Bitterwolf. Why relu networks yield high-confidence predictions far away from the training data and how to mitigate the problem. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 41–50, 2019.
- Dan Hendrycks and Thomas Dietterich. Benchmarking neural network robustness to common corruptions and perturbations. *International Conference on Learning Representations*, 2019.
- Dan Hendrycks and Kevin Gimpel. A baseline for detecting misclassified and out-of-distribution examples in neural networks. In *International Conference on Learning Representations*, 2016.
- Dan Hendrycks, Steven Basart, Norman Mu, Saurav Kadavath, Frank Wang, Evan Dorundo, Rahul Desai, Tyler Zhu, Samyak Parajuli, Mike Guo, et al. The many faces of robustness: A critical analysis of out-of-distribution generalization. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pp. 8340–8349, 2021a.
- Dan Hendrycks, Kevin Zhao, Steven Basart, Jacob Steinhardt, and Dawn Song. Natural adversarial examples. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 15262–15271, 2021b.
- Judy Hoffman, Mehryar Mohri, and Ningshan Zhang. Algorithms and theory for multiple-source adaptation. In *Advances in neural information processing systems*, 2018.
- Andrew G Howard, Menglong Zhu, Bo Chen, Dmitry Kalenichenko, Weijun Wang, Tobias Weyand, Marco Andreetto, and Hartwig Adam. Mobilenets: Efficient convolutional neural networks for mobile vision applications. *arXiv preprint arXiv:1704.04861*, 2017.
- Gao Huang, Zhuang Liu, Laurens Van Der Maaten, and Kilian Q Weinberger. Densely connected convolutional networks. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 4700–4708, 2017.
- Zhuo Huang, Xiaobo Xia, Li Shen, Bo Han, Mingming Gong, Chen Gong, and Tongliang Liu. Harnessing out-of-distribution examples via augmenting content and style. In *International Conference on Learning Representations*, 2022.
- Zhuo Huang, Muyang Li, Li Shen, Jun Yu, Chen Gong, Bo Han, and Tongliang Liu. Winning prize comes from losing tickets: Improve invariant learning by exploring variant parameters for out-of-distribution generalization. *arXiv preprint arXiv:2310.16391*, 2023.
- Peter J Huber. Robust statistics. In *International Encyclopedia of Statistical Science*, pp. 1248–1251. Springer, 2011.
- Gabriel Ilharco, Mitchell Wortsman, Ross Wightman, Cade Gordon, Nicholas Carlini, Rohan Taori, Achal Dave, Vaishaal Shankar, Hongseok Namkoong, John Miller, Hannaneh Hajishirzi, Ali Farhadi, and Ludwig Schmidt. Openclip, July 2021. URL <https://doi.org/10.5281/zenodo.5143773>. If you use this software, please cite it as below.
- Yiding Jiang, Pierre Foret, Scott Yak, Daniel M Roy, Hossein Mobahi, Gintare Karolina Dziugaite, Samy Bengio, Suriya Gunasekar, Isabelle Guyon, and Behnam Neyshabur. Neurips 2020 competition: Predicting generalization in deep learning. *arXiv preprint arXiv:2012.07976*, 2020a.
- Yiding Jiang, Behnam Neyshabur, Hossein Mobahi, Dilip Krishnan, and Samy Bengio. Fantastic generalization measures and where to find them. In *International Conference on Learning Representations*, 2020b.
- Ying Jin, Ximei Wang, Mingsheng Long, and Jianmin Wang. Minimum class confusion for versatile domain adaptation. In *European Conference on Computer Vision*, pp. 464–480, 2020.

- Maurice George Kendall. *Rank correlation methods*. Griffin, 1948.
- Nitish Shirish Keskar, Dheevatsa Mudigere, Jorge Nocedal, Mikhail Smelyanskiy, and Ping Tak Peter Tang. On large-batch training for deep learning: Generalization gap and sharp minima. In *International Conference on Learning Representations*, 2017.
- Andreas Kirsch and Yarin Gal. A note on " assessing generalization of sgd via disagreement". *Transaction on Machine Learning Research*, 2022.
- Pang Wei Koh, Shiori Sagawa, Henrik Marklund, Sang Michael Xie, Marvin Zhang, Akshay Balsubramani, Weihua Hu, Michihiro Yasunaga, Richard Lanus Phillips, Irena Gao, et al. Wilds: A benchmark of in-the-wild distribution shifts. In *International Conference on Machine Learning*, pp. 5637–5664, 2021.
- Wouter M Kouw and Marco Loog. A review of domain adaptation without target labels. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 43(3):766–785, 2019.
- Kiran Krishnamachari, See-Kiong Ng, and Chuan-Sheng Foo. Mitigating real-world distribution shifts in the fourier domain. *Transactions on Machine Learning Research*, 2023.
- Alex Krizhevsky, Geoffrey Hinton, et al. *Learning multiple layers of features from tiny images*. Citeseer, 2009.
- Junnan Li, Dongxu Li, Caiming Xiong, and Steven Hoi. Blip: Bootstrapping language-image pre-training for unified vision-language understanding and generation. In *International Conference on Machine Learning*, 2022.
- Junnan Li, Dongxu Li, Silvio Savarese, and Steven Hoi. BLIP-2: bootstrapping language-image pre-training with frozen image encoders and large language models. In *International Conference on Machine Learning*, 2023.
- Shuang Li, Fangrui Lv, Binhui Xie, Chi Harold Liu, Jian Liang, and Chen Qin. Bi-classifier determinacy maximization for unsupervised domain adaptation. In *Proceedings of the AAAI conference on artificial intelligence*, pp. 8455–8464, 2021.
- Shiyu Liang, Yixuan Li, and Rayadurgam Srikant. Enhancing the reliability of out-of-distribution image detection in neural networks. In *International Conference on Learning Representations*, 2018.
- Tengyuan Liang, Tomaso Poggio, Alexander Rakhlin, and James Stokes. Fisher-rao metric, geometry, and complexity of neural networks. In *The 22nd International Conference on Artificial Intelligence and Statistics*, pp. 888–896, 2019.
- Zachary Lipton, Yu-Xiang Wang, and Alexander Smola. Detecting and correcting for label shift with black box predictors. In *International Conference on Machine Learning*, pp. 3122–3130, 2018.
- Evan Z Liu, Behzad Haghgoo, Annie S Chen, Aditi Raghunathan, Pang Wei Koh, Shiori Sagawa, Percy Liang, and Chelsea Finn. Just train twice: Improving group robustness without training group information. In *International Conference on Machine Learning*, pp. 6781–6792, 2021.
- Yuzhe Lu, Yilong Qin, Runtian Zhai, Andrew Shen, Ketong Chen, Zhenlin Wang, Soheil Kolouri, Simon Stepputtis, Joseph Campbell, and Katia Sycara. Characterizing out-of-distribution error via optimal transport. In *Advances in Neural Information Processing Systems*, 2024.
- Lucas Mansilla, Rodrigo Echeveste, Diego H Milone, and Enzo Ferrante. Domain generalization via gradient surgery. In *Proceedings of the IEEE International Conference on Computer Vision*, 2021.
- Yishay Mansour, Mehryar Mohri, and Afshin Rostamizadeh. Domain adaptation with multiple sources. In *Advances in neural information processing systems*, 2008.
- Yishay Mansour, Mehryar Mohri, and Afshin Rostamizadeh. Domain adaptation: Learning bounds and algorithms. *arXiv preprint arXiv:0902.3430*, 2009.

- John P Miller, Rohan Taori, Aditi Raghunathan, Shiori Sagawa, Pang Wei Koh, Vaishaal Shankar, Percy Liang, Yair Carmon, and Ludwig Schmidt. Accuracy on the line: on the strong correlation between out-of-distribution and in-distribution generalization. In *International Conference on Machine Learning*, pp. 7721–7735, 2021.
- Matthias Minderer, Josip Djolonga, Rob Romijnders, Frances Hubis, Xiaohua Zhai, Neil Houlsby, Dustin Tran, and Mario Lucic. Revisiting the calibration of modern neural networks. In *Advances in Neural Information Processing Systems*, pp. 15682–15694, 2021.
- Vaishnavh Nagarajan and J Zico Kolter. Generalization in deep networks: The role of distance from initialization. *arXiv preprint arXiv:1901.01672*, 2019.
- Behnam Neyshabur, Ryota Tomioka, and Nathan Srebro. Norm-based capacity control in neural networks. In *Conference on Learning Theory*, pp. 1376–1401, 2015.
- Behnam Neyshabur, Srinadh Bhojanapalli, David McAllester, and Nati Srebro. Exploring generalization in deep learning. In *Advances in Neural Information Processing systems*, 2017.
- Behnam Neyshabur, Srinadh Bhojanapalli, and Nathan Srebro. A pac-bayesian approach to spectrally-normalized margin bounds for neural networks. In *International Conference on Learning Representations*, 2018.
- Yaniv Ovadia, Emily Fertig, Jie Ren, Zachary Nado, David Sculley, Sebastian Nowozin, Joshua Dillon, Balaji Lakshminarayanan, and Jasper Snoek. Can you trust your model’s uncertainty? evaluating predictive uncertainty under dataset shift. In *Advances in Neural Information Processing Systems*, 2019.
- Xingchao Peng, Qinxun Bai, Xide Xia, Zijun Huang, Kate Saenko, and Bo Wang. Moment matching for multi-source domain adaptation. In *Proceedings of the IEEE International Conference on Computer Vision*, pp. 1406–1415, 2019.
- Fengchun Qiao and Xi Peng. Uncertainty-guided model generalization to unseen domains. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 6790–6800, 2021.
- Alec Radford, Jong Wook Kim, Chris Hallacy, Aditya Ramesh, Gabriel Goh, Sandhini Agarwal, Girish Sastry, Amanda Askell, Pamela Mishkin, Jack Clark, et al. Learning transferable visual models from natural language supervision. In *International Conference on Machine Learning*, 2021.
- Benjamin Recht, Rebecca Roelofs, Ludwig Schmidt, and Vaishaal Shankar. Do cifar-10 classifiers generalize to cifar-10? *arXiv preprint arXiv:1806.00451*, 2018a.
- Benjamin Recht, Rebecca Roelofs, Ludwig Schmidt, and Vaishaal Shankar. Do cifar-10 classifiers generalize to cifar-10? *arXiv preprint arXiv:1806.00451*, 2018b.
- Benjamin Recht, Rebecca Roelofs, Ludwig Schmidt, and Vaishaal Shankar. Do imagenet classifiers generalize to imagenet? In *International Conference on Machine Learning*, pp. 5389–5400, 2019.
- Shiori Sagawa, Pang Wei Koh, Tatsunori B Hashimoto, and Percy Liang. Distributionally robust neural networks for group shifts: On the importance of regularization for worst-case generalization. In *International Conference on Learning Representations*, 2020.
- Shiori Sagawa, Pang Wei Koh, Tony Lee, Irena Gao, Sang Michael Xie, Kendrick Shen, Ananya Kumar, Weihua Hu, Michihiro Yasunaga, Henrik Marklund, et al. Extending the wilds benchmark for unsupervised adaptation. *arXiv preprint arXiv:2112.05090*, 2021.
- Yair Schiff, Brian Quanz, Payel Das, and Pin-Yu Chen. Predicting deep neural network generalization with perturbation response curves. In *Advances in Neural Information Processing Systems*, pp. 21176–21188, 2021.
- Yuge Shi, Jeffrey Seely, Philip HS Torr, N Siddharth, Awni Hannun, Nicolas Usunier, and Gabriel Synnaeve. Gradient matching for domain generalization. *arXiv preprint arXiv:2104.09937*, 2021.



- Karen Simonyan and Andrew Zisserman. Very deep convolutional networks for large-scale image recognition. *arXiv preprint arXiv:1409.1556*, 2014.
- Amanpreet Singh, Ronghang Hu, Vedanuj Goswami, Guillaume Couairon, Wojciech Galuba, Marcus Rohrbach, and Douwe Kiela. Flava: A foundational language and vision alignment model. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, 2022.
- Samuel L Smith and Quoc V Le. A bayesian perspective on generalization and stochastic gradient descent. In *International Conference on Learning Representations*, 2018.
- Baochen Sun and Kate Saenko. Deep coral: Correlation alignment for deep domain adaptation. In *European Conference on Computer Vision*, pp. 443–450, 2016.
- Tao Sun, Cheng Lu, and Haibin Ling. Prior knowledge guided unsupervised domain adaptation. In *European Conference on Computer Vision*, 2022.
- Remi Tachet des Combes, Han Zhao, Yu-Xiang Wang, and Geoffrey J Gordon. Domain adaptation with conditional distribution matching and generalized label shift. In *Advances in Neural Information Processing Systems*, pp. 19276–19289, 2020.
- Mingxing Tan and Quoc Le. Efficientnet: Rethinking model scaling for convolutional neural networks. In *International Conference on Machine Learning*, pp. 6105–6114, 2019.
- Damien Teney, Seong Joon Oh, and Ehsan Abbasnejad. Id and ood performance are sometimes inversely correlated on real-world datasets. *arXiv preprint arXiv:2209.00613*, 2022.
- Damien Teney, Yong Lin, Seong Joon Oh, and Ehsan Abbasnejad. Id and ood performance are sometimes inversely correlated on real-world datasets. In *Advances in Neural Information Processing Systems*, 2024.
- Weijie Tu, Weijian Deng, Tom Gedeon, and Liang Zheng. A bag-of-prototypes representation for dataset-level applications. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, 2023a.
- Weijie Tu, Weijian Deng, Tom Gedeon, and Liang Zheng. A bag-of-prototypes representation for dataset-level applications. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 2881–2892, 2023b.
- Ramakrishna Vedantam, David Lopez-Paz, and David J Schwab. An empirical investigation of domain generalization with empirical risk minimizers. In *Advances in Neural Information Processing Systems*, pp. 28131–28143, 2021.
- Riccardo Volpi, Hongseok Namkoong, Ozan Sener, John Duchi, Vittorio Murino, and Silvio Savarese. Generalizing to unseen domains via adversarial data augmentation. In *Advances in Neural Information Processing Systems*, 2018.
- Haohan Wang, Songwei Ge, Zachary Lipton, and Eric P Xing. Learning robust global representations by penalizing local predictive power. In *Advances in Neural Information Processing Systems*, 2019.
- Tongzhou Wang and Phillip Isola. Understanding contrastive representation learning through alignment and uniformity on the hypersphere. In *International Conference on Machine Learning*, pp. 9929–9939, 2020.
- Florian Wenzel, Andrea Dittadi, Peter Vincent Gehler, Carl-Johann Simon-Gabriel, Max Horn, Dominik Zietlow, David Kernert, Chris Russell, Thomas Brox, Bernt Schiele, et al. Assaying out-of-distribution generalization in transfer learning. In *Advances in Neural Information Processing Systems*, 2022.
- Ross Wightman. Train cifar10 with pytorch. <https://github.com/kuangliu/pytorch-cifar>, 2017.
- Ross Wightman. Pytorch image models. <https://github.com/rwightman/pytorch-image-models>, 2019.
- Renchunzi Xie, Hongxin Wei, Lei Feng, Yuzhou Cao, and Bo An. On the importance of feature separability in predicting out-of-distribution error. In *Advances in Neural Information Processing Systems*, 2024.

- Shiqi Yang, Joost van de Weijer, Luis Herranz, Shangling Jui, et al. Exploiting the intrinsic neighborhood structure for source-free domain adaptation. In *Advances in Neural Information Processing Systems*, pp. 29393–29405, 2021.
- Kaichao You, Yong Liu, Jianmin Wang, and Mingsheng Long. Logme: Practical assessment of pre-trained models for transfer learning. In *International Conference on Machine Learning*, pp. 12133–12143, 2021.
- Yaodong Yu, Zitong Yang, Alexander Wei, Yi Ma, and Jacob Steinhardt. Predicting out-of-distribution error with the projection norm. In *International Conference on Machine Learning*, 2022.
- Xiaohua Zhai, Basil Mustafa, Alexander Kolesnikov, and Lucas Beyer. Sigmoid loss for language image pre-training. In *International Conference on Computer Vision*, 2023.
- Dinghuai Zhang, Kartik Ahuja, Yilun Xu, Yisen Wang, and Aaron Courville. Can subnetwork structure be the key to out-of-distribution generalization? In *International Conference on Machine Learning*, pp. 12356–12367, 2021.
- Yuchen Zhang, Tianle Liu, Mingsheng Long, and Michael Jordan. Bridging theory and algorithm for domain adaptation. In *International Conference on Machine Learning*, pp. 7404–7413, 2019.
- Long Zhao, Ting Liu, Xi Peng, and Dimitris Metaxas. Maximum-entropy adversarial data augmentation for improved generalization and robustness. In *Advances in Neural Information Processing Systems*, 2020.
- Kaiyang Zhou, Ziwei Liu, Yu Qiao, Tao Xiang, and Chen Change Loy. Domain generalization: A survey. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 2022.

## A Appendix

In the appendix, we first introduce the experimental details including access to models, datasets, and computation resources.

### A.1 Experimental Setup

#### A.1.1 Datasets

We carefully check the licenses of all datasets used in the experiment and list the open sources to them.

ImageNet (Deng et al., 2009):  
<https://www.image-net.org>;  
 ImageNet-C (Hendrycks & Dietterich, 2019):  
<https://github.com/hendrycks/robustness>;  
 ImageNet-V2 (Recht et al., 2019):  
<https://github.com/modestyachts/ImageNetV2>;  
 ImageNet-Adversarial (Hendrycks et al., 2021b):  
<https://github.com/hendrycks/natural-adv-examples>;  
 ImageNet-Rendition (Hendrycks et al., 2021a):  
<https://github.com/hendrycks/robustness>;  
 ImageNet-Sketch (Wang et al., 2019):  
<https://github.com/HaohanWang/ImageNet-Sketch>;  
 ObjectNet (Barbu et al., 2019):  
<https://objectnet.dev/download.html>;  
 CIFAR-10 (Krizhevsky et al., 2009):  
<https://www.cs.toronto.edu/~kriz/cifar.html>;  
 CIFAR-10-C (Hendrycks & Dietterich, 2019):  
<https://github.com/hendrycks/robustness>;  
 CIFAR-10.2 (Recht et al., 2018a):  
<https://github.com/modestyachts/CIFAR-10.1>;  
 CINIC (Darlow et al., 2018):  
<https://www.v7labs.com/open-datasets/cinic-10>;  
 Camelyon17 (Bandi et al., 2018):  
<https://camelyon17.grand-challenge.org/>;  
 DomainNet (Peng et al., 2019):  
<http://ai.bu.edu/M3SDA/>;

#### A.1.2 Model Pool

**ImageNet models** are publicly available via TIMM (Wightman, 2019). Models pre-trained by contrastive learning can be used from model-vs-human project (Geirhos et al., 2021). Some MAE models (He et al., 2022) are accessible from (<https://github.com/facebookresearch/mae>).

PIRL  
 InsDis  
 MoCo  
 MoCoV2  
 InfoMin  
 simclr\_resnet50x4  
 simclr\_resnet50x1  
 simclr\_resnet50x2  
 resnet50\_l2\_eps1  
 resnet50\_l2\_eps0\_5  
 resnet50\_l2\_eps0\_25

resnet50\_l2\_eps0\_03  
resnet50\_l2\_eps0\_01  
ens\_adv\_inception\_resnet\_v2  
adv\_inception\_v3  
tf\_efficientnet\_b0\_ap  
resnet50\_trained\_on\_SIN\_and\_IN  
resnet50\_trained\_on\_SIN\_and\_IN\_then\_finetuned\_on\_IN  
resnet50\_trained\_on\_SIN  
resnet50\_augmix  
resnet50\_cutmix  
resnet50\_deeppaugment  
resnet50\_deeppaugment\_and\_augmix  
resnet50\_feature\_cutmix  
resnet50\_pixmap  
convnext\_xlarge\_384\_in22ft1k  
convnext\_xlarge\_in22ft1k  
resnetv2\_152x2\_bitm  
resnetv2\_50x1\_bitm  
convnext\_base\_384\_in22ft1k  
convnext\_base\_in22ft1k  
resmlp\_big\_24\_224\_in22ft1k  
resmlp\_big\_24\_distilled\_224  
tf\_efficientnetv2\_s\_in21ft1k  
tf\_efficientnetv2\_m\_in21ft1k  
tf\_efficientnetv2\_l\_in21ft1k  
tf\_efficientnetv2\_xl\_in21ft1k  
vit\_large\_patch16\_384  
swin\_large\_patch4\_window12\_384  
beit\_large\_patch16\_512  
beit\_large\_patch16\_384  
beit\_large\_patch16\_224  
beit\_base\_patch16\_384  
vit\_base\_patch16\_384  
vit\_small\_r26\_s32\_384  
vit\_tiny\_patch16\_384  
vit\_large\_r50\_s32\_384  
mixer\_b16\_224\_miil  
resmlp\_big\_24\_224  
resnetv2\_50x1\_bit\_distilled  
ig\_resnext101\_32x16d  
ig\_resnext101\_32x32d  
ig\_resnext101\_32x8d  
ig\_resnext101\_32x48d  
resnext101\_32x16d\_wsl  
tf\_efficientnet\_l2\_ns\_475  
tf\_efficientnet\_b7\_ns  
tf\_efficientnet\_b6\_ns  
tf\_efficientnet\_b5\_ns  
ssl\_resnext101\_32x8d  
ssl\_resnext101\_32x16d  
swsl\_resnext101\_32x8d  
swsl\_resnext101\_32x16d  
ssl\_resnext101\_32x4d  
ssl\_resnext50\_32x4d

ssl\_resnet50  
swsl\_resnext101\_32x4d  
swsl\_resnext50\_32x4d  
swsl\_resnet50  
swin\_small\_patch4\_window7\_224  
swin\_base\_patch4\_window12\_384  
deit\_base\_patch16\_224  
deit\_small\_distilled\_patch16\_224  
resmlp\_36\_224  
cait\_s36\_384  
cait\_s24\_224  
convit\_base  
convit\_tiny  
twins\_pcpvt\_base  
eca\_nfnet\_l1  
xcit\_tiny\_24\_p8\_384\_dist  
efficientnet\_b1  
efficientnet\_b3  
efficientnet\_b4  
tf\_efficientnet\_b2  
tf\_efficientnet\_lite1  
convnext\_base  
convnext\_small  
resnetrs350  
pit\_xs\_distilled\_224  
crossvit\_small\_240  
botnet26t\_256  
tinynet\_e  
tinynet\_d  
repvgg\_b2g4  
mnasnet\_small  
dla46x\_c  
lcnet\_050  
tv\_resnet34  
tv\_resnet50  
tv\_resnet101  
tv\_resnet152  
densenet121  
inception\_v4  
resnet26d  
mobilenetv2\_140  
hrnet\_w40  
xception  
xception41  
resnet18  
resnet34  
seresnet50  
mobilenetv2\_050  
seresnet33ts  
wide\_resnet50\_2  
wide\_resnet101\_2  
resnet18d  
hrnet\_w18\_small  
gluon\_resnet152\_v1d

hrnet\_w48  
hrnet\_w44  
repvgg\_b2  
densenet201  
hrnet\_w18\_small  
resnet101d  
gluon\_resnet101\_v1d  
gluon\_resnet101\_v1s  
gluon\_xception65  
gluon\_seresnext50\_32x4d  
gluon\_senet154  
gluon\_inception\_v3  
gluon\_resnet101\_v1c  
tf\_inception\_v3  
tv\_densenet121  
tv\_resnext50\_32x4d  
repvgg\_b1g4  
resnext26ts  
ghostnet\_100  
crossvit\_9\_240  
deit\_base\_patch16\_384  
rexnet\_150  
rexnet\_130  
resnetrs50  
resnet50d  
resnet50  
resnetv2\_50  
resnetrs152  
resnetrs101  
resnet50\_aa  
resnet50\_fastaa  
resnet50\_randaa  
vgg19\_bn  
vgg16\_bn  
vgg13\_bn  
vgg11\_bn  
vgg11  
vgg11\_bn  
vgg16  
vgg19  
resnet10t  
resnet14t  
darknet53  
cs3darknet\_m  
cs3darknet\_focus\_m  
cs3darknet\_l  
cs3darknet\_focus\_l  
regnety\_040  
regnety\_064  
regnety\_080  
regnetv\_040  
regnetv\_064  
regnetz\_040

regnetz\_040h

**CIFAR-10 models** can be downloaded through (<https://github.com/cheneafo/pytorch-cifar-models>). The training script for training trajectory experiment borrows from (<https://github.com/kuangliu/pytorch-cifar>).

VGG16

VGG13

ResNet34

ResNet50

ResNet101

ResNet152

ShuffleNetG2

ShuffleNetG3

PreActResNet18

PreActResNet34

PreActResNet50

PreActResNet101

densenet\_cifar

DenseNet121

DenseNet169

DenseNet201

DenseNet161

ResNeXt29\_8x64d

ResNeXt29\_32x4d

MobileNetV2

RegNetX\_200MF

DLA

DPN

PNASNetB

RegNetX\_400MF

RegNetY\_400MF

MobileNet

ResNet18

VGG11

SimpleDLA

ResNeXt29\_4x64d

ResNeXt29\_2x64d

EfficientNetB0

SENet18

ShuffleNetV2

GoogLeNet

DPN92

ResNet34-160

ResNet34-170

ShuffleNetG2-170

ShuffleNetG2-180

ShuffleNetG2-190

SimpleDLA-90

SimpleDLA-105

SimpleDLA-120

SimpleDLA-135

SimpleDLA-150

SENet18-60

SENet18-75

SENet18-90  
 SENet18-120  
 SENet18-135  
 SENet18-150  
 SENet18-165  
 ShuffleNetG2-170  
 ShuffleNetG2-180  
 ShuffleNetG2-190  
 densenet\_cifar-135  
 densenet\_cifar-150  
 densenet\_cifar-165  
 MobileNetV2-135  
 MobileNetV2-150  
 MobileNetV2-165  
 LeNet  
 PreActResNet152

**WILDS models** (Camelyon17 and DomainNet) are trained by github (<https://github.com/p-lambda/wilds>).

**Zero-shot vision-language models** are provided in OpenCLIP (Ilharco et al., 2021). They are listed as follows in the pattern (architecture, source):.

(RN50, openai)  
 (RN50, yfcc15m)  
 (RN50, cc12m)  
 (RN50-quickgelu, yfcc15m)  
 (RN50-quickgelu, cc12m)  
 (RN101, openai)  
 (RN101, yfcc15m)  
 (RN101-quickgelu, yfcc15m)  
 (RN50×4, openai)  
 (RN50×16, openai)  
 (RN50×64, openai)  
 (ViT-B-32, openai)  
 (ViT-B-32, laion400m\_e32)  
 (ViT-B-16, openai)  
 (ViT-B-16, laion400m\_e32)  
 (ViT-L-14, openai)  
 (ViT-L-14, laion2b\_s32b\_b82k)  
 (ViT-L-14-336, openai)  
 (ViT-H-14, laion2b\_s32b\_b79k)  
 (ViT-g-14, laion2b\_s34b\_b88k)  
 (ViT-bigG-14, laion2b\_s39b\_b160k)  
 (convnext\_base, laion400m\_s13b\_b51k)  
 (convnext\_base\_w, laion\_aesthetic\_s13b\_b82k)  
 (convnext\_base\_w\_320, laion\_aesthetic\_s13b\_b82k\_augreg)  
 (convnext\_large\_d, laion2b\_s26b\_b102k\_augreg)  
 (convnext\_large\_d\_320, laion2b\_s29b\_b131k\_ft\_soup)  
 (convnext\_xlarge, laion2b\_s34b\_b82k\_augreg)  
 (ViT-B-32, Model-B-32\_Data-80M\_Samples-34B\_lr-1e-3\_bs-88k.pt)  
 (ViT-B-16, Model-B-16\_Data-80M\_Samples-34B\_lr-1e-3\_bs-88k.pt)  
 (ViT-L-14, Model-L-14\_Data-80M\_Samples-34B\_lr-1e-3\_bs-88k.pt)  
 (ViT-B-32, datacomp\_m\_s128m\_b4k)  
 (ViT-B-32, commonpool\_m\_clip\_s128m\_b4k)



(ViT-B-32, commonpool\_m\_laion\_s128m\_b4k)  
(ViT-B-32, commonpool\_m\_image\_s128m\_b4k)  
(ViT-B-32, commonpool\_m\_text\_s128m\_b4k)  
(ViT-B-32, commonpool\_m\_basic\_s128m\_b4k)  
(ViT-B-32, commonpool\_m\_s128m\_b4k)  
(ViT-B-32, datacomp\_s\_s13m\_b4k)  
(ViT-B-32, commonpool\_s\_clip\_s13m\_b4k)  
(ViT-B-32, commonpool\_s\_laion\_s13m\_b4k)  
(ViT-B-32, commonpool\_s\_image\_s13m\_b4k)  
(ViT-B-32, commonpool\_s\_text\_s13m\_b4k)  
(ViT-B-32, commonpool\_s\_basic\_s13m\_b4k)  
(ViT-B-32, commonpool\_s\_s13m\_b4k)  
(ViT-B-16, datacomp\_l\_s1b\_b8k)  
(ViT-L-14, datacomp\_xl\_s13b\_b90k)  
(EVA01-g-14, laion400m\_s11b\_b41k)  
(EVA01-g-14-plus, merged2b\_s11b\_b114k)  
(EVA02-B-16, merged2b\_s8b\_b131k)  
(EVA02-L-14, merged2b\_s4b\_b131k)  
(EVA02-L-14-336, merged2b\_s6b\_b61k)  
(EVA02-E-14, laion2b\_s4b\_b115k)  
(EVA02-E-14-plus, laion2b\_s9b\_b144k)  
(ViT-B-32-quickgelu, metaclip\_fullcc)  
(ViT-B-16-quickgelu, metaclip\_fullcc)  
(ViT-L-14-quickgelu, metaclip\_fullcc)  
(ViT-L-14-CLIPA-336, datacomp1b)  
(ViT-H-14-CLIPA, datacomp1b)  
(ViT-H-14-CLIPA-336, datacomp1b)  
(ViT-bigG-14-CLIPA, datacomp1b)  
(ViT-bigG-14-CLIPA-336, datacomp1b)  
(ViT-B-16-SigLIP, webli)  
(ViT-B-16-SigLIP-256, webli)  
(ViT-L-16-SigLIP-384, webli)  
(ViT-S0400M-14-SigLIP, webli)  
(ViT-S0400M-14-SigLIP-384, webli)  
(ViT-B-32-quickgelu, metaclip\_fullcc)  
(ViT-B-16-quickgelu, metaclip\_fullcc)  
(ViT-L-14-quickgelu, metaclip\_fullcc)

BLIP (Li et al., 2022) and BLIP-2 (Li et al., 2023) models are from LAVIS library (<https://github.com/salesforce/LAVIS/tree/main>);

### A.1.3 Computation Resources

PyTorch version is 1.10.2+cu102. All experiments run on one 2080Ti and the CPU AMD Ryzen Threadripper 2950X 16-Core Processor.

| Models | ImageNet-V2-A | ImageNet-R | ObjectNet |
|--------|---------------|------------|-----------|
| 20%    | 0.705         | 0.940      | 0.856     |
| 50%    | 0.746         | 0.934      | 0.894     |
| 70%    | 0.778         | 0.928      | 0.906     |
| 100%   | 0.758         | 0.928      | 0.895     |

Table 5: Correlation strength of SoftmaxCorr with different number models. Weighted Kendall correlation ( $\tau_w$ ) is used as the metric.

| Models | ImageNet-V2-A | ImageNet-R | ObjectNet |
|--------|---------------|------------|-----------|
| 20%    | 0.540         | 0.841      | 0.786     |
| 50%    | 0.542         | 0.877      | 0.846     |
| 70%    | 0.579         | 0.867      | 0.846     |
| 100%   | 0.597         | 0.884      | 0.849     |

Table 6: Correlation strength of MaxPred with different number models. Weighted Kendall correlation ( $\tau_w$ ) is used as the metric.

## A.2 Sensitivity analysis on $\tau_w$

We use Scipy implementation of weighted Kendall’s rank correlation ( $\tau_w$ )<sup>1</sup>, which does not provide a p-value to indicate the statistical significance. It is because the null distribution of the statistic is unknown even in the additive hyperbolic case. Thus, to examine whether the evaluation metric is stable, we conduct a sensitivity analysis on  $\tau_w$  by randomly dropping some models from the model pool. The results are summarized in Table 5 and Table 6. We find that  $\tau_w$  has a consistent assessment on two methods with different numbers of models, suggesting the stability of  $\tau_w$ .

<sup>1</sup><https://docs.scipy.org/doc/scipy/reference/generated/scipy.stats.weightedtau.html>