

MASS: Deep Research for Social Sciences with Memory-Augmented Social Simulation

Anonymous ACL submission

Abstract

Deep Research agents powered by Large Language Models (LLMs) have exhibited extraordinary potential in automated paper writing tasks. However, existing systems rely heavily on literature retrieval and synthesis through internet and local knowledge bases, often resulting research lacking insight and creativity in social science. To address this issue, we propose “Memory-Augmented Social Simulation (MASS)”, an innovative paradigm that leverages highly realistic and research-oriented social simulations to the creativity and empirical founding of LLMs-generated research. Specifically, MASS integrates three core components—dynamic goal-path planning with multi-level social norm restraint to guide the simulation, a multi-disciplinary behavior dataset for agent memory cold-start, and a structured forgetting mechanism inspired by the Ebbinghaus curve. Together, these ensure simulation authenticity and provide a robust empirical foundation for generating innovative scholarly papers. Experimental results demonstrate the effectiveness of our method, showing a 6.81% improvement in generation overall quality over foundation LLMs and 17.19% gain in Insight over strong baselines. Dataset and codes will be released.¹

1 Introduction

Large Language Model agents have achieved breakthrough progress, demonstrating exceptional capabilities in knowledge discovery, information integration, and multi-agent collaboration. This potential is gradually permeating academic research, spurring exploration into automated scientific research and data analysis (Xu and Peng, 2025; Zhang et al., 2025).

Among them, Deep Research agents have been widely applied in social science, which is an autonomous research agent that executes workflows

and generates papers by planning and iterative retrieval, a process critically dependent on retrieving and synthesizing vast literature. They, however, prove particularly limiting in social science, a field characterized by complexity, practicality and subjectivity, where true insight arises from the interplay between theory and practice (Ashworth et al., 2021; Gërkhani et al., 2022). Merely reprocessing existing texts generates theoretical insight and academic creativity that are insufficient to social science research.

To address this challenge, we propose an innovative paradigm for automated social scientific writing, Memory-Augmented Social Simulation (MASS). Departing from the conventional “retrieve-and-generate” mechanism of Deep Research Agent, MASS constructs a realistic and research-oriented virtual social simulation environment. Under such setting, LLMs are guided to conduct exploratory and creative social simulation, thereby generating original, empirical “first-hand” data that provides a substantive foundation for subsequent paper writing.

Specifically, the MASS framework consist of four tightly integrated core modules: 1) The **Task Planning and Deep Reasoning Module**, which employs a divergence Chain-of-Thought (COT) structure to generate diverse research hypotheses and conducts multi-dimensional evaluations to determine the optimal research pathway (Zhu et al., 2025); 2) The **COT Execution and Tool Dispatching Module**, which translates the chosen pathway into executable steps, including retrieving knowledge via internet access and conducting social simulation experiments to generate original empirical data; 3) The **Social Simulation Experiment Module**, which represents the core innovation of MASS to standardize experimental design using the ODD protocol (Grimm et al., 2020) and establishes a virtual social environment with dynamic goal planning and social norm constraints. Agents are en-

¹<https://anonymous.4open.science/r/MASS-Deep-Research-Agent-8D30>




Figure 1: Diagram of the MASS Deep Research framework. Involve four steps: (1) Using divergence COT to plan the process; (2) Calling tools; (3) Agents interact with the memory module; (4) Analyzing retrieved and simulated data, writing with formal style.

dowed with a memory system grounded in multidisciplinary knowledge and an Ebbinghaus-inspired forgetting mechanism, ensuring authentic and reliable simulations. 4) The **Structured Writing Module**, which adheres to academic templates and genre conventions, formatting and composing the final output to meet scholarly standards (Becker, 2008).

We present a paradigm shift in Deep Research, enhancing the research pipeline with a generative social simulation that produces novel empirical evidence, as illustrated in Figure 1. The main contributions are summarized as follows:

- **The MASS Paradigm:** We propose Memory-Augmented Social Simulation paradigm, a novel framework that advances automated social science research beyond conventional approaches.
- **Dataset & Memory Mechanism:** We develop a multi-disciplinary social behavior dataset and an Ebbinghaus-inspired memory mechanism, significantly enhancing the authenticity and cognitive continuity of agent behavior.
- **Goal-Planning with Norm Constraints:** We design a dynamic goal-planning scheme under multi-layered social norm restraint, which imbues the core simulation process with a clear research orientation.

2 Related Work

Deep Research Agent. The development of Deep Research agent systems generally progress through several key phases. Early primarily adopt a single-agent architecture (Nakano et al., 2021; Yao et al., 2022). Subsequently, multi-agent architectures emerge to enable specialized division of labor (Tang et al., 2025; Zheng et al., 2025). Furthermore, hybrid architectures subsequently arise, aiming to balance the flexibility and efficiency (Saied, 2025). Recent end-to-end paradigms incorporate Reinforcement Learning to enhance reasoning capabilities (Team et al., 2025; Wan et al., 2025). Our work inspires creativity by a specialized simulation paradigm in social science.

Agent Behavior and Decision-Making. Research on agent behavior and decision-making is primarily categorized into three paradigms. The static planning paradigm predefines a complete action sequence. (Lei et al., 2025; Zhang et al., 2023). The dynamic planning operates through a “perception-decision-action” cycle for real-time interaction (Wu, 2025; Yao et al., 2022). The dual-system synergistic paradigm integrates both approaches to balance rapid response with long-term objectives (Chen et al., 2025). Through multi-level restraint and dynamic goal planning, MASS framework enhances the autonomy of agents.

Social Simulation. First, data injection and fine-tuning techniques improve behavioral authenticity in micro-level simulations (Merrill and Srivastava,

2025; Vu et al., 2020). Next, to lower the technical barrier, large-scale asynchronous parallel social experiment simulation platforms also emerge (Gao et al., 2023a; Wang et al., 2025; Piao et al., 2025). Meanwhile, mean-field theory is introduced to reduce computational costs in agent-group interactions (Mi et al., 2025). Our framework enhances the authenticity of social simulation by introducing memory augmentation module.

3 MASS Deep Research

The Deep Research framework is grounded in Memory-Augmented Social Simulation (MASS). The framework shifts from the passive integration of information to the active generation of experiential insights, directly facilitating the production of social science research papers.

3.1 Task Planning and Deep Thought

In complex reasoning tasks, traditional chain-of-thought approaches, such as COT and its Best-of-N extensions, can enhance single-step logic but often struggle with limited exploration in multi-step, highly divergent tasks (Wei et al., 2022; Yao et al., 2023). To improve the decision-making exploration capability of Deep Research in task planning, enable stronger divergent thinking in tackling complex tasks, effectively address the “error accumulation” problem in multi-step reasoning tasks, and enhance both the coherence and outcome diversity, we propose a Stepwise Best-of-N (SW-BoN) strategy.

Distinguished from the traditional COT and its extended form COT Best-of-N, the core of our strategy lies in expanding the search space of deep research through stepwise multi-path exploration and real-time optimal selection within each stage. Specifically, we define the SW-BoN as follows. At step i of the task, agents first generate n candidate reasoning nodes, denoted as $\mathbf{C}_i = [c_{i1}, c_{i2}, \dots, c_{in}]$. Subsequently, each node is evaluated by a scoring function $S(c_{ij}) \in [0, 10]$ against a predefined threshold θ . Candidates failing to meet the threshold are regenerated and replaced. The resulting filtered set is denoted as $\mathbf{C}_i^*$.

Next, the optimal node is selected from $\mathbf{C}_i^*$ through a multi-agent voting mechanism. We define a consensus evaluation function $V(c_{ij}^*)$ to quantify the consensus level for a candidate c_{i1}^* :

$$\nu(c_{ij}^*) = \sum_{m=1}^n \psi(c_{im}^*, c_{ij}^*)$$

where the function $\psi(\cdot, \cdot)$ assesses the alignment between two candidate nodes (i.e., voting consensus), implemented in our work via semantic similarity measurement. The final output a_i for step i is then obtained by maximizing the objective function:

$$a_i = \arg \max_{c_{ij}^* \in \mathbf{C}_i^*} V(c_{ij}^*) \quad (\forall i = 1, \dots, k)$$

Guided by the objective function, the task undergoes continuous refinement through an iterative process. The system determines the globally optimal task planning path at step k via filtering and consensus-based selection mechanisms. Following this path, three categories of external tools are invoked in a structured manner: search APIs for retrieving real-time information, academic database interfaces for sourcing relevant literature, and notably, social simulation experiments for generating critical behavioral data. All outputs are integrated and fed back into the system, forming a closed-loop planning-execution-learning cycle that persists until the Deep Research task is fully completed.

3.2 Automated Experimental Design

Upon completion of SW-BoN planning, MASS will invoke the key tool of social simulation experiment during the tool using. The initial phase of simulation is the automated experimental design. This phase employs the ODD protocol as its normative framework, integrating dynamic path planning and multi-layered social constraints to construct a simulation environment that effectively balances focus and realism.

At the beginning of automated experimental design, we adopt the ODD protocol as the top-level specification for the experiment (Grimm et al., 2006, 2020), ensuring both the reproducibility of the experimental process and consistency between the social simulation and the experimental design. Specifically, the three components of the ODD protocol function as follows: The Overview section clearly defines the research questions, key agents, and scenario boundaries; the Design Concepts section articulate the behavioral foundations and attribute hierarchy of agents, linking Overview to Details; the Details section specifies the simulation implementation, including agent attributes, interaction mechanisms, and environmental restraints.

To strengthen the research orientation of the simulation process, this study further parses and instantiates two key social experiment control meth-




Figure 2: Experimental design in Stage 3. The framework automatically designs agent behavioral trajectory based on the ODD protocol, with agent acting along it under multi-layered restraints.

ods from the “Details” section of the ODD protocol. The first is dynamic goal-oriented path planning, which outlines a macro-level execution path closely aligned with the research theme for agent exploration and enables dynamic adjustments during simulation, as well as ensures focused behavior on the core topic while preserving autonomy in exploration. The second is multi-layered social norm restraints. This method emulates real-world social structures through three progressively restrictive layers: institutional enforcement, social morality, and cultural conventions. By applying rules with varying constraints, it regulates the decision-making space of agents during the simulation, thereby constructing a highly structured and realistic social environment.

In summary, this module establishes an automated pipeline from standardized protocol specifications to an executable experimental system. The final code generation component, building upon the concrete details outlined in the “Details” section and powered by an executable code generation agent, automatically implements both agent class definitions and parameterized environment configurations, thereby providing a reliable and extensible foundation for subsequent simulation.

3.3 Memory Augmentation Framework

Memory Augmentation Framework serves as an important component that drives Deep Research in social science toward exploratory and creative research. To achieve this goal, this section focuses

on constructing a knowledge foundation rooted in real human society that can support the simulation of intelligent agent behavior.

3.3.1 Behavioral Dataset Construction

To enable agents in social simulation experiment with realistic behavioral cognition, while provide traceable, multidimensional behavioral knowledge support for their decision-making logic and interaction patterns, we first systematically constructed a multidimensional and extensible social behavior knowledge dataset grounded in six primary disciplines: economics, political science, jurisprudence, sociology, psychology, and history.

During the construction process, each primary discipline is further refined into representative sub-disciplinary fields (e.g., economics is subdivided into behavioral economics, macroeconomics, etc.) to guide the dataset generation work. By consolidating and cleaning authoritative resources in fields, public social media platform user behavior data, and high-quality case repositories from these domains, we ultimately establish a structured dataset comprising nearly 300,000 entries. This dataset provides an authentic and rich behavioral foundation for subsequent agent simulations.

3.3.2 Memory Initialization

Based on the constructed social behavior knowledge base described above, to prevent agents from starting in a memory-less initial state, this study introduces an agent cold-start mechanism that leverages Retrieval-Augmented Generation (RAG) to equip each agent with personalized initial memories (Gao et al., 2023b). The specific procedure can be decomposed into three stages: 1) **Semantic Vector Representation of Role Profiles**. The role profile of the i -th agent, A_i , in the experiment is defined by k core dimensional features generated during the experimental design, denoted as $P_i = \{p_{i1}, p_{i2}, \dots, p_{ik}\}$. A semantic embedding model is employed to map this feature set into a semantic query vector: $q_j = f_{\text{emb}}(P_i)$. This process produces a vectorized representation of role features for retrieval queries. 2) **Similarity Retrieval from the Behavior Database**. Let the domain behavior dataset be $D_i = \{d_1, d_2, \dots, d_m\}$. First, all behavior data are converted into feature vectors using a unified embedding model: $d_j = f_{\text{emb}}(D_i)$. Subsequently, using q_j as the query, we retrieve data from dataset D_i via cosine similarity and select the top- n entries in descending order to form




Figure 3: Detailed memory augmentation mechanism in Stage 3. It comprises three core parts: (1) A 300K-entry social behavior dataset. (2) Agent memory cold-start via RAG. (3) Dynamic memory activation and forgetting.

the candidate D_{can}^i . 3) **Topic-Oriented Initial Memory Generation.** To ensure precise alignment between the generated memory and the research theme, this stage randomly selects one behavior d_i from candidate set D_{can}^i . A topic-alignment function then generates the research-theme-aligned initial memory: $m_i^{\text{init}} = f_{\text{LLM}}(d_i)$. This completes the effective cold-start of the agent’s memory system.

3.3.3 Dynamic Memory Modeling

Following memory initialization, during the experimental phase, this study constructs a dynamic quantification model of memory strength based on the Ebbinghaus forgetting curve (Murre and Dros, 2015; Wixted, 2022), which simulates memory strength evolution, associative activation, and probabilistic forgetting. The core logic is as follows. First, for the basic quantification of memory strength, let the memory sequence of agent A_i at time t be $M_i(t) = \{m_i^{\text{init}}, m_2, \dots, m_t\}$. The relative time interval between any historical memory m_s ($s < t$) and the latest memory m_t is defined as x ($x = \frac{t-s}{t} \times 100\%$). Through nonlinear fitting of the Ebbinghaus curve, the function for quantifying basic memory strength is constructed: $y = 90 \times e^{(-4.8x)} + 10$. Whenever a new memory m_t is generated, this function is applied to calculate the basic strength for all historical memories in $M_i(t)$.

Second, an associative enhancement mechanism is introduced. The semantic similarity between the new memory m_t and a historical memory m_s is

calculated by $s = \text{sim}(f_{\text{emb}}(m_t), f_{\text{emb}}(m_s)) \times 100\%$, based on which a random increment Δy is applied to the strength of m_s :

$$\Delta y = \begin{cases} \text{rand}(8, 15), & s \geq 70\% \\ \text{rand}(3, 7), & 40\% \leq s < 70\% \\ 0, & s < 40\% \end{cases}$$

The updated memory strength after activation becomes $y' = y + \Delta y$. Finally, probabilistic forgetting is implemented based on memory strength. Each memory is assigned a forgetting probability P_{forget} according to its activated strength y' via a mapping relationship, shown in Appendix Table 3. Remaining memory subset $M'_i(t)$ after this filtering process then serves as the effective basis for agent’s decision-making in the next moment, thereby closing the loop of memory evolution.

3.4 Agent Interaction Execution

In this section, we delineate how agents, within a structured and standardized virtual environment, achieve highly realistic and controllable simulations of social behavior through perception, decision-making, action, and concurrent execution.

In perceiving to external environment, agents don’t rely on a global omniscient perspective but rather achieve this through social interactions with other agents, which constitutes their fundamental approach to perceiving the outside world. Specifically, agents primarily acquire information by perceiving the states of their social neighborhoods and engaging in direct interactions (Koley, 2025; Xue et al., 2025). They are capable of detecting state changes within their neighborhoods and forming a dispositional understanding of the attitudes within local groups. When an agent detects that other agents in its domain exhibit an intention to interact, it initiates information exchange and interaction within the bounds of simulation protocols, thereby generating immediate interactive outcomes.

The cognitive and decision-making module undertakes the core reasoning functions of agent. The decision-making process is neither random nor entirely free; rather, it operates under the dual constraints of “dynamic goal-driven” mechanisms and “multi-level social norms.” An agent possesses both guiding long-term goals and situational short-term intentions. Agent evaluates potential action options, optimizes the selection of the action with the highest comprehensive value, and conducts rationality

judgments within the framework of multi-level social norms. The decision results are translated by the execution layer into specific action commands, which produce direct or indirect outcomes in the simulation experiments. Upon completion of the actions, both the process and the results are stored as memories within the agent’s memory system, thereby forming a complete logical closed loop for the social simulation experiment.

3.5 Structured Writing Module

The Structured Writing Module serves as the final output component of the MASS Deep Research Agent, with its core function being to integrate research outcomes from all preceding modules and produce a social science research paper that adheres to academic standards.

Building upon the reasoning chain nodes generated via the Stepwise Best-of-N strategy, this module conducts a comprehensive analysis of the tool invocation results associated with each node and subsequently composes the corresponding sections of the paper. For instance, it systematically synthesizes results obtained from web searches and literature reviews, summarizing relevant theoretical and empirical evidence. Concurrently, it performs an in-depth analysis of both qualitative and quantitative data derived from social simulation experiments, extracting emergent behavioral patterns, procedural mechanisms, and key research findings (Maning et al., 2024). Based on these analyses, the module incrementally generates coherent textual segments corresponding to each reasoning chain node, thereby producing a preliminary draft.

This framework predefines four stylistic templates—academic paper, research paper, policy brief, and review article—along with their corresponding writing procedures and format specifications. Based on the research topic and content characteristics, the system automatically selects the most appropriate writing genre. Then following the corresponding steps, it integrates the interim draft sections generated earlier into a structurally complete, formally standardized final research paper.

4 Experiment

We present a series of experiments designed to conduct a quantitative and qualitative evaluation of the proposed MASS Deep Research framework. It systematically evaluates the framework’s output in generating papers, verifies the efficacy of Memory-

Model & Framework	Comp.	Insight	Inst. Fol.	Read.	Overall
<i>Model</i>					
Qwen3-235B	46.16	44.90	47.68	47.87	46.12
DeepSeek-V3.1	44.83	44.33	48.13	46.49	45.68
GLM-4.6	44.32	42.09	46.83	44.68	44.05
Claude-Sonnet-4.5	43.57	42.60	46.99	44.28	44.76
ERNIE-4.5	40.50	38.39	44.85	43.32	42.82
<i>Framework</i>					
Gemini Deep Research	49.82	46.79	51.69	49.14	50.04
Tongyi Deep Research	46.70	46.71	48.97	49.35	47.89
MASS Deep Research	46.73	52.23	45.42	46.38	48.23

Table 1: This study uses social science dataset from DeepResearch Bench to evaluate report quality. The table’s top section shows results for large-scale LLMs; the bottom compares existing agent frameworks with ours.

Augmented Social Simulation module in modeling social movements, and analyzes the quality of the constructed multidisciplinary dataset on social behaviors.

4.1 Main Experimental Findings

We evaluate the performance of proposed framework on Deep Research tasks. **Baseline Setting:** The experiment uses Qwen3-30B as the base model and compares it against mainstream large-scale LLMs (e.g., DeepSeek-V3.1) and Deep Research frameworks (e.g., Tongyi Deep Research). **Experimental Setup:** The base model of MASS Deep Research was deployed on two A6000 GPUs, while other baseline models were accessed via provided API. **Evaluation Metrics:** We employ the widely recognized Deep Research benchmark—DeepResearch Bench—for systematic assessment (Du et al., 2025), assessing the quality of generated papers on its social science subset across comprehensiveness, insight, instruction following, and readability. Results are presented in Table 1.

Based on the evaluation results, the proposed MASS Deep Research framework demonstrates the following characteristics. In terms of overall score, it significantly outperforms the large-scale LLMs, exceeding their average by 6.81%, which reflects its strong capability in generating high-quality social science papers. Moreover, it demonstrates comparable overall performance to peer frameworks using the same base model (Tongyi Deep Research), while achieving a notably higher score in the “Insight” dimension—exceeding the comparison average by 17.19%. These results highlight the distinct capability of the MASS framework to drive




Figure 4: The relationship between leader proportion and conflict technology elasticity (m). Solid and dashed lines depict simulated and theoretical trends respectively. The blue, green, and orange curves track the proportions of leaders, followers, and the value of m respectively.




Figure 5: Heatmap of contract dispute resolution toughness. Each cell is assigned an average score based on SMEs' selected resolution methods: 0 for shelving, 1 for mediation, 2 for arbitration, and 3 for litigation.

research toward greater depth and produce more insightful findings.

4.2 Social Simulation: Case Studies

In this section, we aim to systematically validate the effectiveness of the proposed framework by designing two multi-dimensional social science experiments and analyzing in depth the experimental processes and outcomes of intelligent agents under the constraints of memory enhancement, goal planning, and social norms.

4.2.1 Conflict-Driven State Formation

This study conducts a simulation-based examination of the central political and sociological science theoretical proposition that “conflict is a necessary condition for state formation”. It simulates in a stateless environment, where agents reallocate resources through conflict and cooperation. Key findings indicate that as the conflict elasticity parameter m increases, leaders begin to emerge at $m = 0.86$ and stabilize after $m > 0.97$. This trend aligns closely with theoretical predictions. The formation of leaders emerges at $m = 0.76$ and stabilizes near $m > 1.0$, signaling the gradual emergence of a state (Han, 2024) (Figure 4).

Simulations further reveal a systematic shift in resource allocation: under anarchy, the proportion of social resources invested in conflict fluctuates around 23%; with the emergence of governance, the system stabilizes and such investment falls below 10% (Appendix Figure 8). This aligns with theoretical predictions of 30 – 45% conflict investment in stateless settings, declining to under 10% under hierarchy (Han, 2024). The two findings provide empirical support for conflict-driven state formation theories.

4.2.2 SME Dispute Strategies Compared

This experiment, situated within the intersecting fields of economics and law, examines how variations in enterprises' objective and subjective attributes influence small and medium-sized enterprises (SMEs') choice of dispute resolution strategies for contractual conflicts. Results indicate that with stronger legal awareness, external support, and risk-taking capacity, SMEs show a greater tendency to resolve contract disputes through legal channels. Among them, the non-specialized show a strong reliance on external support in litigation decisions, whereas specialized and innovative SMEs tend to adopt a more assertive approach to contractual disputes (Figure 5).

Further, industry attributes and dispute amounts significantly moderate firms' strategic choices: the financial sector relies on formal judicial pathways due to high risk aversion; manufacturing and technology industries adjust strategies stepwise with amount; while the service sector prefers low-confrontation approaches like deferral or arbitration in labor disputes (Appendix Figure 9).

Consistent with empirical evidence (Center, 2024), specialized SMEs exhibit stable operations and low dispute-related disruption, in contrast to non-specialized SMEs, which adopt conservative approaches due to limited risk tolerance. The financial sector relies on formal mechanisms for high-value disputes, while manufacturing and technology industries pursue amount-sensitive strategies under cost constraints. In labor disputes within the service sector, the generally low dispute amounts typically make deferral or arbitration more cost-effective than litigation.

Base Model	Ablation1		Ablation2		Ablation3	
	Insight	Overall	Insight	Overall	Insight	Overall
Qwen3-30B	42.33	43.97	49.47	47.19	52.23	48.23
DeepSeek-V3.1	44.33	45.68	47.28	48.53	51.29	49.76
GLM-4.6	42.09	44.05	48.60	48.04	49.83	48.94
ERNIE-4.5	38.39	42.82	46.51	45.10	49.02	46.83
Hunyuan-A13B	35.46	38.25	42.03	40.60	46.02	41.96

Table 2: This table performs comparison of different base models’ insight and overall scores. From Ablation1 to Ablation3, it represents high to low ablation settings.




Figure 6: Example of complete ablation results on Qwen3-30B. Groups from left to right represent high-to-low ablation settings, with scores shown across evaluation dimensions on DeepResearch Bench.

4.3 Ablation Study

To thoroughly analyze the contribution of each core module, this study systematically designs an ablation experiment. Using a controlled variable approach, it compares performance differences after removing key modules, specifically to verify the critical role of the Memory-Augmented Social Simulation module.

The experiment employs various base models and is also evaluated on the DeepResearch Bench. It’s conducted through the following comparison groups: 1) the complete MASS Deep Research framework; 2) a framework that removes the MASS module and its associated tool-use functionality; 3) a pure base LLM. All were evaluated on DeepResearch-Bench, with results shown in Table 2 and Figure 6. Results show a stepwise increase in overall score, confirming the framework’s effectiveness. A trade-off emerges between insight and instruction following after integrating the social simulation module: the output shifts from surface-level compliance to an in-depth analysis of underlying social mechanisms and dynamic processes, leading to a significant gain in insight while slightly reducing instruction following. This demonstrates the framework’s strength in driving research beyond superficial task execution and en-




Figure 7: Dataset evaluation results. (a) Radar chart: text integrity, hallucination-free rate, information density and textual richness (all scaled 0–1, higher is better). (b) Bar chart: behavioral rationality comparison (cold-start vs. no cold-start).

hancing scholarly innovation.

4.4 Dataset Evaluation

We conduct a systematic evaluation focusing on the quality of constructed social behavior dataset and the effectiveness of agent cold-start. The evaluation is performed with a 10% sampling interval. In terms of experimental configuration and evaluation design, the DeepEval framework(Ip et al., 2024) is employed to detect hallucinations (threshold >0.3) and contextual integrity (threshold <0.7). Semantic diversity and distribution uniformity are assessed through text information density and entropy normalization, respectively. The rationality of agent behaviors with and without dataset cold-start is compared using the LangChain evaluation framework. Results are shown in Figure 7.

Experimental results show that the dataset achieves high reliability, with 94.21% of data passing hallucination detection and 97.51% passing integrity evaluation. Its text information density (0.89) and textual richness (0.75) both approach the theoretical optimum of 1, demonstrating strong adaptability across diverse simulation scenarios. Furthermore, cold-start using this dataset yields a 5.84% improvement in the agent’s action rationality score, confirming its effectiveness in enhancing behavioral authenticity and decision quality.

5 Conclusion

In this paper, the Memory-Augmented Social Simulation (MASS) paradigm integrates automated experimental design and the Ebbinghaus-inspired memory mechanism, providing an empirical foundation for social science research. Combined with exploratory reasoning and structured writing, the framework provides an innovative approach for Deep Research in social sciences.

Limitations

Computational Cost and Runtime. High-fidelity, large-scale social simulation is computationally expensive. Although this study simplifies the workflow and incorporates optimization designs such as parallelization, the associated resource consumption and runtime remain significant. Future work should further explore lightweight architectures and elastic computing solutions to enhance the framework’s time efficiency and resource efficiency.

Hallucination. It manifests at two levels. In text generation, models may fabricate non-existent academic concepts or data, thereby undermining the credibility of the output. In simulation systems, hallucinations can infiltrate the decision-making and interactions of agents, leading to issues of cognitive distortion. It is anticipated that as LLMs technology continues to advance, the extent of hallucination is expected to gradually diminish.

Ethics Statement

Given that social simulation experiments directly model and analyze human interactions, examining their ethical implications is crucial. The core methodology of our work does not presuppose or enforce specific social outcomes or behavioral patterns, but rather focuses on constructing simulation environments that reflect complex social dynamics. We particularly emphasize constraining the behavior of agents within an ethical framework during the development and interpretation of such simulations. For constructed cold-start behavioral dataset, we have removed all direct personal identifiers and generalized indirect identity information to prevent re-identification, rigorously safeguarding individual privacy. This framework and experimental design ensure that the social science research process and outputs neither contain nor reinforce biased content, while adhering to relevant data protection laws and social norms.

References

- Scott Ashworth, Christopher R Berry, and Ethan Bueno De Mesquita. 2021. *Theory and credibility: Integrating theoretical and empirical social science*. Princeton University Press.
- Howard S Becker. 2008. *Writing for social scientists: How to start and finish your thesis, book, or article*. University of Chicago Press.
- China SME Development Promotion Center. 2024. *2024 annual assessment report on the development*

- environment of small and medium-sized enterprises*. Technical report, China SME Development Promotion Center.
- Guoxin Chen, Zile Qiao, Wenqing Wang, Donglei Yu, Xuanzhong Chen, Hao Sun, Minpeng Liao, Kai Fan, Yong Jiang, Pengjun Xie, Wayne Xin Zhao, Ruihua Song, and Fei Huang. 2025. *Mars: Optimizing dual-system deep research via multi-agent reinforcement learning*. arXiv preprint arXiv:2510.04935.
- Mingxuan Du, Benfeng Xu, Chiwei Zhu, Xiaorui Wang, and Zhendong Mao. 2025. *Deeprerearch bench: A comprehensive benchmark for deep research agents*. Preprint, arXiv:2506.11763.
- Chen Gao, Xiaochong Lan, Zhihong Lu, Jinzhu Mao, Jinghua Piao, Huandong Wang, Depeng Jin, and Yong Li. 2023a. *S3: Social-network simulation system with large language model-empowered agents*. arXiv preprint arXiv:2307.14984.
- Yunfan Gao, Yun Xiong, Xinyu Gao, Kangxiang Jia, Jinliu Pan, Yuxi Bi, Yixin Dai, Jiawei Sun, Haofen Wang, and Haofen Wang. 2023b. *Retrieval-augmented generation for large language models: A survey*. arXiv preprint arXiv:2312.10997, 2(1).
- Klarita Gërzhani, Nan Dirk De Graaf, and Werner Raub. 2022. *Handbook of sociological science*. Cheltenham: Edward Elgar.
- Volker Grimm, Uta Berger, Finn Bastiansen, Sigrunn Eliassen, Vincent Ginot, Jarl Giske, John Goss-Custard, Tamara Grand, Simone K Heinz, Geir Huse, and 1 others. 2006. *A standard protocol for describing individual-based and agent-based models*. *Ecological modelling*, 198(1-2):115–126.
- Volker Grimm, Steven F Railsback, Christian E Vincenot, Uta Berger, Cara Gallagher, Donald L DeAngelis, Bruce Edmonds, Jiaqi Ge, Jarl Giske, Juergen Groeneveld, and 1 others. 2020. *The odd protocol for describing agent-based and other simulation models: A second update to improve clarity, replication, and structural realism*. *Journal of Artificial Societies and Social Simulation*, 23(2).
- Zhongyuan Han. 2024. *The technology of conflict and endogenous authority: On the possibility of state origin*. *Journal of [Fill in the Specific Journal Name]*, [Fill in the Volume Number if Applicable](10):841–964.
- Jeffrey Ip, Cale, and contributors. 2024. *Deepeval: The llm evaluation framework*.
- Gaurav Koley. 2025. *Salm: A multi-agent framework for language model-driven social network simulation*. arXiv preprint arXiv:2505.09081.
- Yu Lei, Shuzheng Si, Wei Wang, Yifei Wu, Gang Chen, Fanchao Qi, and Maosong Sun. 2025. *Rhinoinsight: Improving deep research through control mechanisms for model behavior and context*. arXiv preprint arXiv:2511.18743.

717	Benjamin S Manning, Kehang Zhu, and John J Horton.	Jason Wei, Xuezhi Wang, Dale Schuurmans, Maarten	773
718	2024. Automated social science: Language models	Bosma, Fei Xia, Ed Chi, Quoc V Le, Denny Zhou,	774
719	as scientist and subjects . Technical report, National	and 1 others. 2022. Chain-of-thought prompting elic-	775
720	Bureau of Economic Research.	its reasoning in large language models . volume 35,	776
		pages 24824–24837.	777
721	Scott Merrill and Shashank Srivastava. 2025. Point	John T Wixted. 2022. The enigma of forgetting .	778
722	of order: Action-aware llm persona modeling	<i>Proceedings of the National Academy of Sciences</i> ,	779
723	for realistic civic simulation . <i>arXiv preprint</i>	119(12):e2201332119.	780
724	<i>arXiv:2511.17813</i> .		
725	Qirui Mi, Mengyue Yang, Xiangning Yu, Zhiyu Zhao,	Zihao Wu. 2025. Autono: A react-based highly ro-	781
726	Cheng Deng, Bo An, Haifeng Zhang, Xu Chen, and	bust autonomous agent framework . <i>arXiv preprint</i>	782
727	Jun Wang. 2025. Mf-llm: Simulating population	<i>arXiv:2504.04650</i> .	783
728	decision dynamics via a mean-field large language		
729	model framework . <i>arXiv preprint arXiv:2504.21582</i> .	Renjun Xu and Jingwen Peng. 2025. A comprehensive	784
		survey of deep research: Systems, methodologies,	785
730	Jaap MJ Murre and Joeri Dros. 2015. Replication and	and applications . <i>arXiv preprint arXiv:2506.12594</i> .	786
731	analysis of ebbinghaus' forgetting curve . <i>PloS one</i> ,		
732	10(7):e0120644.	Xiao Xue, Deyu Zhou, Ming Zhang, and Fei-Yue Wang.	787
		2025. From agent simulation to social simulator:	788
733	Reiichiro Nakano, Jacob Hilton, Suchir Balaji, Jeff Wu,	A comprehensive review (part 1) . <i>arXiv preprint</i>	789
734	Long Ouyang, Christina Kim, Christopher Hesse,	<i>arXiv:2510.18271</i> .	790
735	Shantanu Jain, Vineet Kosaraju, William Saunders,		
736	and 1 others. 2021. Webgpt: Browser-assisted	Shunyu Yao, Dian Yu, Jeffrey Zhao, Izhak Shafran, Tom	791
737	question-answering with human feedback . <i>arXiv</i>	Griffiths, Yuan Cao, and Karthik Narasimhan. 2023.	792
738	<i>preprint arXiv:2112.09332</i> .	Tree of thoughts: Deliberate problem solving with	793
		large language models . volume 36, pages 11809–	794
739	Jinghua Piao, Yuwei Yan, Jun Zhang, Nian Li, Junbo	11822.	795
740	Yan, Xiaochong Lan, Zhihong Lu, Zhiheng Zheng,		
741	Jing Yi Wang, Di Zhou, and 1 others. 2025. Agentso-	Shunyu Yao, Jeffrey Zhao, Dian Yu, Nan Du, Izhak	796
742	ciety: Large-scale simulation of llm-driven genera-	Shafran, Karthik R Narasimhan, and Yuan Cao. 2022.	797
743	tive agents advances understanding of human behav-	React: Synergizing reasoning and acting in language	798
744	iors and society . <i>arXiv preprint arXiv:2502.08691</i> .	models . In <i>The eleventh international conference on</i>	799
		<i>learning representations</i> .	800
745	Riwa Saied. 2025. How to use perplexity ai (2025):	Shiwei Zhang, Lansong Diao, Siyu Wang, Zongyan Cao,	801
746	Screenshots, citations & setup . Online Technical	Yiliang Gu, Chang Si, Ziji Shi, Zhen Zheng, Chuan	802
747	Guide.	Wu, and Wei Lin. 2023. Auto-parallelizing large	803
748	Jiabin Tang, Tianyu Fan, and Chao Huang. 2025. Au-	models with rhino: A systematic approach on produc-	804
749	toagent: A fully-automated and zero-code framework	tion ai platform . <i>arXiv preprint arXiv:2302.08141</i> .	805
750	for llm agents . <i>arXiv preprint arXiv:2502.05957</i> .		
751	Tongyi DeepResearch Team, Baixuan Li, Bo Zhang,	Wenlin Zhang, Xiaopeng Li, Yingyi Zhang, Pengyue Jia,	806
752	Dingchu Zhang, Fei Huang, Guangyu Li, Guoxin	Yichao Wang, Huifeng Guo, Yong Liu, and Xiangyu	807
753	Chen, Huifeng Yin, Jialong Wu, Jingren Zhou, and 1	Zhao. 2025. Deep research: A survey of autonomous	808
754	others. 2025. Tongyi deepresearch technical report .	research agents . <i>arXiv preprint arXiv:2508.12752</i> .	809
755	<i>arXiv preprint arXiv:2510.24701</i> .		
756	Tuong Manh Vu, Charlotte Probst, Alexandra Nielsen,	Yuxiang Zheng, Dayuan Fu, Xiangkun Hu, Xiaojie Cai,	810
757	Hao Bai, Charlotte Buckley, Petra S Meier, Mark	Lyumanshan Ye, Pengrui Lu, and Pengfei Liu. 2025.	811
758	Strong, Alan Brennan, and Robin C Purshouse. 2020.	Deepresearcher: Scaling deep research via reinforce-	812
759	A software architecture for mechanism-based social	ment learning in real-world environments . <i>arXiv</i>	813
760	systems modelling in agent-based simulation models .	<i>preprint arXiv:2504.03160</i> .	814
761	<i>Journal of artificial societies and social simulation:</i>		
762	JASSS, 23(3):1.	King Zhu, Hanhao Li, Siwei Wu, Tianshun Xing, Dehua	815
763	Yi Wan, Jiuqi Wang, Liam Li, Jinsong Liu, Ruihao	Ma, Xiangru Tang, Minghao Liu, Jian Yang, Jiaheng	816
764	Zhu, and Zheqing Zhu. 2025. Pokeereseach: Effec-	Liu, Yuchen Eleanor Jiang, and 1 others. 2025. Scal-	817
765	tive deep research via reinforcement learning from	ing test-time compute for llm agents . <i>arXiv preprint</i>	818
766	ai feedback and robust reasoning scaffold . <i>arXiv</i>	<i>arXiv:2506.12928</i> .	819
767	<i>preprint arXiv:2510.15862</i> .		
768	Lei Wang, Heyang Gao, Xiaohe Bo, Xu Chen, and Ji-		
769	Rong Wen. 2025. Yulan-onesim: Towards the next		
770	generation of social simulator with large language		
771	models . In <i>Workshop on Scaling Environments for</i>		
772	<i>Agents</i> .		

A Supplementary Materials Appendix

A.1 Forgetting Probability Mapping Table

Memory strength	Forgetting probability
$60 \leq y' \leq 70$	[0%, 8%]
$50 \leq y' < 60$	[8%, 20%]
$35 \leq y' < 50$	[20%, 40%]
$30 \leq y' < 35$	[40%, 55%]
$10 \leq y' < 30$	[55%, 80%]

Table 3: This table defines the mapping between the activated memory strength y' and the corresponding forgetting probability P_{forget} interval in the framework.

A.2 Case Experiment Graphs




Figure 8: Conflict Investment and Resource Distribution. The blue curve shows total resources, the red curve shows conflict investment, and the bar chart shows their proportion.




Figure 9: Contract Dispute Resolution Box Plot. The box plot shows SMEs' contract dispute preferences and compares behavioral differences across dispute amounts.

B Example Appendix

B.1 Example of SW-BoN

Taking the research topic “How can classroom participation of students with autism be enhanced? What effective strategies are available?” As a case study, this appendix section presents the outputs from each reasoning node in the first round of divergent reasoning under the SW-BoN strategy (Appendix Table 4), and illustrates the complete reasoning process of the strategy applied to this case (Appendix Table 5).

Node	Reasoning Content
1	In writing the research report, summarize autism education strategies, supported by psychological (ABA, positive reinforcement) and sociological (classroom environment) frameworks. Detail social simulation experiments, questionnaire/interview data in research methods to form a reliable strategy evaluation system.
2	Need to specify implementation paths of literature retrieval and social simulation experiments, cover recent 5-year core journals on strategy effectiveness, design virtual classrooms, adopt group comparison, control variables, and ensure ethical review and guardian consent.
3*	We need to focus the report on strategies for autistic students' classroom participation, clarify title elements, concisely present findings in the abstract, contextualize with policies, data and multi-disciplinary insights, and design literature review plus social simulation experiments to test strategy feasibility.
4	We need to build a strategy effectiveness matrix with literature and simulation data, test core strategies' effect on autistic students' participation, analyze their scenario applicability, and lay empirical groundwork for subsequent suggestions based on relevant theories.
5	In findings, we'll compare literature and simulation data to build an analysis framework, verify strategy transferability, explore how classroom settings reduce anxiety sociologically, then focus on analyzing root causes of low participation from individual, social and policy dimensions.

Table 4: This table presents the divergent reasoning results from Step 1 of the SW-BoN strategy applied to this example. Asterisked nodes are the selected reasoning.

Step	Reasoning Content
1	We need to focus the report on strategies for autistic students' classroom participation, clarify title elements, concisely present findings in the abstract, contextualize with policies, data and multi-disciplinary insights, and design literature review plus social simulation experiments to test strategy feasibility.
2	Need to refine each report module, ground the background in policies and the 30% – 40% participation gap data, build a strategy effectiveness matrix, and analyze causes via sociological adaptation and psychological sensory processing theories.
3	Putting forward evidence-based, actionable strategies by tiered interventions for different severity levels, emphasize psychological positive reinforcement, propose sociological systemic suggestions, and ensure all strategies comply with ethical standards.
4	Build a three-dimensional analysis framework for findings with literature and simulation data, cover psychological and sociological quantitative indicators, add dynamic strategy comparisons, supplement case statistics via literature, and verify sociological adaptability of environment sensitivity schemes.
5	Verify cross-data of literature and simulations, supplement dynamic data on classroom environmental variables' impact, combine relevant theories, introduce long-term case data, analyze family support-participation correlation, and ensure statistical significance and interdisciplinary explanatory power of all data.
6	Deepen strategy effectiveness verification with literature and simulation data, adopt dual theories for cause analysis, clarify multi-stakeholder responsibilities in suggestions, and supplement uncovered variables like TCM adjuvant effects and long-term intervention data in simulations.
7	We should construct an interdisciplinary analysis framework for findings: integrate psychological attention and emotional indicators and sociological classroom and home-school data, supplement unaddressed simulation variables like TCM adjuvant effects, and ensure logical closure with literature statistics.
8	We shall analyze causes from psychological and sociological perspectives, interpret sensory abnormalities and environmental adaptation imbalance with relevant theories, supplement observed simulation variables, and verify applicability of non-mainstream interventions to ensure theoretical depth and empirical support.

Table 5: This table presents the complete reasoning process of SW-BoN

B.2 Experimental Design Demonstration

This appendix section will use the topic “conflict is a necessary condition for state formation” as an example to demonstrate “Details” in ODD protocol and goal-oriented path of automated experimental design.

Category	Detail Content
Partial Attributes	Cognitive level (e); Resource allocation preference (Pd); Contest input (F); Resource possession (R); technological elasticity of conflict (m); External environmental threat index (T).
Partial Restraints	(1) Closed Neolithic-early dynastic area; 50×50 grid; 200 max population. (2) Forced governance other than violent means is prohibited. (3) Three stages – Stone Soldier (Low m), Bronze Soldier (Medium m), Iron Soldier (High m)
Partial Interaction Principal	(1) Each action of social entities generates a dual feedback loop. (2) Failed interaction increases historical conflict experience H by 1 and cuts the next-round contention willingness. (3) Environmental pressure elevates the nonlinear growth coefficient of F during interaction.
Time Interval	One natural cycle equals the minimum human social cooperation cycle, i.e., three months. The Stone Soldier stage lasts 5 cycles, and the Bronze Soldier stage lasts 3 cycles.

Table 6: This table presents Details for different categories in ODD protocol.




Figure 10: The flowchart illustrates the goal-oriented path under this topic.

Conflict is Necessity for State Formation
Agent Actions: Cold-Start: Post-conflict field visits to farming tribes reveal a 25% shrinkage of valley pastures has fueled rising inter-tribal conflicts: some mark water boundaries with stones, which sparked distinct tribal antagonism. →I partnered with entity12 for cross-tribal tech cooperation, used technical gap complementarity for three initiatives, enabled tech transfer, built an agricultural alliance prototype, raised shared resources and metrics, supported the Bronze Soldier Stage and consolidated entity2’s early control. →I and neighboring Entity21 had their first conflict over 25% reduced valley grassland resources and the latter’s irrigation shortage. Failed negotiations led us to deploy 74 units for counterattack, repelling the opponent but suffering western ditch damage and lower irrigation efficiency, with subsequent plans to establish a defense mechanism with [7,43]. → I deploy half our workforce to boost grassland water supply and reinforce agriculture. Partner with entity41 on a joint lab, sharing soil plans for smelting R&D support. Use 252 granaries against 5% depletion, raise C>0.47, cap conflict spending at 74 units (8.8%). This builds peace cycles, advances hierarchy, and improves regional resource use and stability. Attributes Changing: Resource Possession: 5.0 , 6.9 , 6.2 , 6.8 , 7.0 External Threat Index: 5.0 , 4.1 , 6.3, 7.1 , 5.1 Conflict Investment: 0 , 0.2 , 1.3 , 2.1 , 1.8

Table 7: This table displays the behavior of a representative agent in the simulation theme “Conflict is necessary for state formation”.

SMEs’ Contract Dispute Resolution Choices
Agent Actions: Cold-Start: I interpreted the relevant clause; the startup and university signed an industrialization agreement based on the professor’s research; we verified its IP ownership in the agreement during review, and the startup obtained tax incentives successfully. →On 15 Mar, an IP dispute of RMB 160K arose with specialized & innovative tech firm entity8 over a patent license agreement due to technical standard disputes. Based on its 24 annual disputes, legal awareness (9) and risk tolerance (Level 3), we conducted a multi-assessment, analyzed trade-offs and preliminarily prioritized dispute resolution paths. →After comprehensive assessment, the enterprise prioritized arbitration for its better timeliness (28 days and 60 days for litigation) and backed by legal awareness score 9 for a more formal resolution. Dispute status updated to “Arbitration Pending”, with RMB158,000 frozen for the process to underpin subsequent decisions compliantly. →Based on regional legal environment parameters (42-day arbitration time, 65% litigation publicity rate) and enterprise attributes (RMB158k dispute amount, legal awareness score 9), arbitration was initiated. We filed the application with arbitral institution entity12, to cover potential enforcement risks, updated dispute status to “Arbitration in Progress”. Attributes Changing: External Support: 2.5 , 7.2 , 9.5 , 9.3 , 4.5 Resolution Intensity: 6.5 , 8.2 , 7.9 , 8.5 , 8.0 Court Efficiency: 4.1 , 4.2 , 4.7 , 4.3 , 5.1

Table 8: This table displays the change of an agent in the theme “SMEs’ Contract Dispute Resolution Choices”.

B.4 Presentation of Behavioral Dataset

To illustrate its multidimensional characteristics, a representative sample of data from each core discipline is presented in Appendix Table 9 and Table 10.

Economical: As an independent director of Shenzhen Unilumin, I reviewed the second-phase employee stock ownership plan. I supported its aim to align core staff with company growth and address retention issues but highlighted the need to prevent free-riding, proposing a tiered dividend mechanism. During bad debt write-off discussions, I required aging details and credit ratings for each receivable to ensure compliance with accounting standards. History: I am Wang Bo, deeply devoted to poetry and prose, specializing in parallel prose. I find inspiration in nature, traveling to enrich my work. My learning is broad and eclectic. Once, inspired by a scene of sunset clouds, a lone bird, and autumn waters, I wrote Preface to the Pavilion of Prince Teng spontaneously. I believe writing must be sincere and elegantly natural—powerful yet profound, flowing effortlessly. This experience solidified my literary path and brought widespread recognition. Jurisprudence: While serving as project manager in an industrial zone in Lyon, I discovered our company had failed to declare a new chemical storage facility as required by Article L.512-8 of the Environmental Code. Pressed by deadlines, we had skipped filing the necessary documents. An unannounced inspection led to a potential €50,000 fine under Article L.512-5 and mandatory retroactive submission. This incident underscored the critical importance of strict compliance with administrative procedures, even under time pressure.
--

Table 9: Listing 1, examples of Economical, History and Jurisprudence.

Politics: In March 2023, while moving with a rebel reconnaissance unit through Nganja Forest in Fizi, DRC, I witnessed intense clashes between the Yakutumba armed group and government forces. After hearing gunfire, we hid in dense foliage and saw armored vehicles surrounding a rebel outpost. The group’s leader, Amuli Yakutumba, was struck in the leg by stray bullets. The fighting resulted in at least 12 civilian casualties. During our retreat, the sky was darkened by burning trees, and the air smelled of smoke and burnt wood. Psychology: After participating in a Rational Emotive Behavior Therapy (REBT) session at university, I noticed significant social improvements. The counselor encouraged me to apply rational thinking and behaviors in daily life, so I began trying to express myself more confidently with my roommates. For instance, I would actively share my views when they discussed their interests. Although initially nervous, consistent practice helped me gradually feel more comfortable. This experience made me realize that through REBT, I can progressively overcome social barriers and build more positive social connections. Society: I joined a deep analysis group discussing anime adaptations. We explored whether narrative differences between animations and manga affect audience reception. Using Neon Genesis Evangelion as an example, I noted that the anime enhanced characters’ psychological changes through visual expression, while the manga focused more on plot logic. This highlighted how different media shape audiences’ cognitive frameworks and influence their interpretation of the same story.

Table 10: Listing 2, examples of Politics, Psychology and Society.

B.5 Example of Structured Writing

As an example prompt of the research genre “Academic Paper”, this appendix will systematically elaborate on how structured writing, as an output component, assists in completing the task of writing a social science research paper in a step-by-step manner. The standardized writing steps are as follows:

- Part 1. **Title:** Succinctly summarize the study’s core. Include subject, key variables, and method. (10 – 30 words)
- Part 2. **Abstract & Keywords:** Write an abstract covering purpose, method, results, and conclusion. For social sciences, highlight the research question and significance. List 3-5 keywords. (300 – 400 words)
- Part 3. **Introduction:** Present the background, state the research question, and explain the study’s significance and innovation. For social sciences, emphasize the theoretical gap. (1200 – 1500 words)
- Part 4. **Literature Review:** Systematically review existing work to position the study. Provide a critical synthesis, classify relevant theories, and identify consensus and gaps. (2500 - 3500 words)
- Part 5. **Methods:** Detail the research design for replicability. Use subheadings for sections covering subjects, sampling, procedures, etc. (1500 - 2000 words)
- Part 6. **Results & Analysis:** Objectively present data and interpret findings theoretically. Use quotes and thematic analysis for qualitative work. (2500 - 3500 words)
- Part 7. **Discussion:** Interpret the results’ meaning, compare with existing literature, and note study limitations. Address whether hypotheses were supported and the theoretical contribution. (2000 - 2500 words)
- Part 8. **Conclusion:** Summarize core findings and suggest practical implications or future research directions. (500 - 800 words)

B.6 Example of Cold-Start Evaluation

Store Operations Strategy Designing

Background: As a convenience store owner in a monopolistically competitive market , a new competitor has recently opened nearby(many firms, free entry/exit). Now design strategy with justification. Core economic principles:

- (1) In monopolistic competition, non-price competition is more sustainable than price wars (avoiding race-to-the-bottom).
- (2) Strategies must align with community needs.
- (3) Approaches should Focus on serving the local community of convenience stores.

No Cold-Start: Strategy: Enhance community services and customized product offerings. Reason: In a monopolistic competition market, this approach boosts customer loyalty and brand differentiation by meeting personalized and local needs, avoiding price wars while building on community trust.

Result Score:0.778

Cold-Start: Strategy: Launch a “Community Regulars Program” with points redeemable for neighborhood services (parcel pickup, shared chargers, health checks). Reason: Anchors the store in community needs, making it a service hub, not just a store. This avoids price wars, builds loyalty through value-added services, and transforms customers into lasting community assets—leveraging non-price competition in a monopolistic market.

Result Score:0.968

Table 11: The table compares agent’s behavior before and after the cold-start under the “store operations strategy designing” scenario.

C Algorithm Pseudocode

This appendix section presents the algorithmic pseudocode for agents interaction processes in social simulation experiment.

Algorithm LLM Agent Social Simulation

```
1: Initialize: Set social Agents  $A = \{a_1, a_2, \dots, a_N\}$ 
2: for all  $a_i \in A$  parallel do // Multi-threaded
3:    $\text{memory}_i \leftarrow \text{Cold-Start}(\text{dataset}, \text{topic})$ 
4:    $\text{attributes}_i \leftarrow \text{InitAttributes}()$ 
5: end for
6: for  $t = 1 \rightarrow T$  do // Simulation steps
7:    $\text{BarrierSync}(A)$ 
8:   for all  $a_i \in A$  parallel do
9:     if  $\text{ShouldInteract}(a_i)$  then // Interaction decision
10:       $\text{partners} \leftarrow \text{FindNeighbors}(a_i, \text{radius})$ 
11:       $\text{available} \leftarrow \emptyset$ 
12:      for  $a_j \in \text{partners}$  do
13:        if  $\text{RequestConsent}(a_i, a_j)$  then
14:           $\text{available} \leftarrow \text{available} \cup \{a_j\}$ 
15:        end if
16:      end for
17:      if  $\text{available} \neq \emptyset$  then
18:         $\text{ExecuteInteraction}(a_i, \text{available})$ 
19:      end if
20:    end if
21:     $\text{action} \leftarrow \text{GetAction}(a_i)$ 
22:    while  $\neg \text{CheckConstraints}(\text{action})$  do
23:       $\text{RemoveAction}(a_i, \text{action})$ 
24:       $\text{action} \leftarrow \text{GetNewAction}(a_i)$ 
25:    end while
26:     $\text{ExecuteAction}(a_i, \text{action})$ 
27:     $\text{attributes}_i \leftarrow \text{AdjustAttributes}(\text{attributes}_i, \text{action})$ 
28:  end for
29: end for
```
